




US 20120090873A1

(19) **United States**(12) **Patent Application Publication**
Gundel(10) **Pub. No.: US 2012/0090873 A1**(43) **Pub. Date: Apr. 19, 2012**(54) **SHIELDED ELECTRICAL CABLE**(76) Inventor: **Douglas B. Gundel**, Cedar Park,
TX (US)of application No. 61/348,800, filed on May 27, 2010,
which is a division of application No. 61/352,473, filed
on Jun. 8, 2010.**Publication Classification**(21) Appl. No.: **13/377,873**(51) **Int. Cl.**
H01B 11/10 (2006.01)(22) PCT Filed: **Jun. 17, 2010**(52) **U.S. Cl.** **174/113 R**(86) PCT No.: **PCT/US10/38943**§ 371 (c)(1),
(2), (4) Date: **Dec. 13, 2011**(57) **ABSTRACT****Related U.S. Application Data**(62) Division of application No. 61/218,739, filed on Jun.
19, 2009, which is a division of application No.
61/260,881, filed on Nov. 13, 2009, which is a division

A shielded electrical cable (4302) includes a conductor set (4304) and a shielding film (4308). The conductor set (4304) includes one or more substantially parallel longitudinal insulated conductors (4306). The shielding film (4308) includes a cover portion (4308'') partially covering the conductor set (4304), and parallel portions (4308'') extending from both sides of the conductor set (4304).






FIG. 1




FIG. 2a




FIG. 2b




FIG. 2c




FIG. 2d




FIG. 2e




FIG. 3




FIG. 5






FIG. 6






FIG. 4c




FIG. 4d




FIG. 7a




FIG. 7b




FIG. 7c




FIG. 7d




FIG. 8A




FIG. 8b




FIG. 8c




FIG. 9a




FIG. 9B




FIG. 10a




FIG. 10b




FIG. 10c




FIG. 10d




FIG. 10e




FIG. 10f




FIG. 10g




FIG. 11a




FIG. 11b




FIG. 11c

FIG. 126




FIG. 13a




FIG. 13b




FIG. 14a




FIG. 14b




FIG. 15a




FIG. 15b











FIG. 15C










FIG. 17a




FIG. 17b




FIG. 18




FIG. 19




FIG. 20a




FIG. 20b




FIG. 20c




FIG. 20d




FIG. 20e




FIG. 20f




FIG. 21a




FIG. 21b




FIG. 21c




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26a




FIG. 26b




FIG. 26c




FIG. 26d




FIG. 27




FIG. 28a




FIG. 28b




FIG. 28c




FIG. 28d




FIG. 29a




FIG. 29b




FIG. 29c




FIG. 29d

SHIELDED ELECTRICAL CABLE

TECHNICAL FIELD

[0001] The present disclosure relates generally to shielded electrical cables for the transmission of electrical signals. In particular, the present invention relates to shielded electrical cables that can be mass-terminated and provide high speed electrical properties.

BACKGROUND

[0002] Electrical cables for transmission of electrical signals are well known. One common type of electrical cable is a coaxial cable. Coaxial cables generally include an electrically conductive wire surrounded by an insulator. The wire and insulator are surrounded by a shield, and the wire, insulator, and shield are surrounded by a jacket. Another common type of electrical cable is a shielded electrical cable comprising one or more insulated signal conductors surrounded by a shielding layer formed, for example, by a metal foil. To facilitate electrical connection of the shielding layer, a further un-insulated conductor is sometimes provided between the shielding layer and the insulation of the signal conductor or conductors. Both these common types of electrical cable normally require the use of specifically designed connectors for termination and are often not suitable for the use of mass-termination techniques, i.e., the simultaneous connection of a plurality of conductors to individual contact elements, such as, e.g., electrical contacts of an electrical connector or contact elements on a printed circuit board. Although electrical cables have been developed to facilitate these mass-termination techniques, these cables often have limitations in the ability to mass-produce them, in the ability to prepare their termination ends, in their flexibility, and in their electrical performance. In view of the advancements in high speed electrical and electronic components, a continuing need exists for electrical cables that are capable of transmitting high speed signals, facilitate mass-termination techniques, are cost-effective, and can be used in a large number of applications.

SUMMARY

[0003] In one aspect, the present invention provides a shielded electrical cable including a conductor set and a shielding film. The conductor set includes one or more substantially parallel longitudinal insulated conductors. The shielding film includes a cover portion partially covering the conductor set, and parallel portions extending from both sides of the conductor set.

[0004] In another aspect, the present invention provides a shielded electrical cable including a plurality of spaced apart conductor sets arranged generally in a single plane and a shielding film. Each conductor set includes one or more substantially parallel longitudinal insulated conductors. The shielding film includes a plurality of cover portions partially covering the conductor sets, and a parallel portion disposed between adjacent conductor sets and configured to electrically isolate the adjacent conductor sets from each other.

[0005] The above summary of the present invention is not intended to describe each disclosed embodiment or every implementation of the present invention. The Figures and

detailed description that follow below more particularly exemplify illustrative embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 is a perspective view of an exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0007] FIGS. 2a-2e are front cross-sectional views of five other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0008] FIG. 3 is a perspective view of two shielded electrical cables of FIG. 1 terminated to a printed circuit board.

[0009] FIGS. 4a-4d are top views of an exemplary termination process of a shielded electrical cable according to an aspect of the present invention.

[0010] FIG. 5 is a top view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0011] FIG. 6 is a top view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0012] FIGS. 7a-7d are front cross-sectional views of four other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0013] FIGS. 8a-8c are front cross-sectional views of three other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0014] FIGS. 9a-9b are top and partially cross-sectional front views, respectively, of an exemplary embodiment of an electrical assembly according to an aspect of the present invention terminated to a printed circuit board.

[0015] FIGS. 10a-10e and 10f-10g are perspective and front cross-sectional views, respectively, illustrating an exemplary method of making a shielded electrical cable according to an aspect of the present invention.

[0016] FIGS. 11a-11c are front cross-sectional views illustrating a detail of an exemplary method of making a shielded electrical cable according to an aspect of the present invention.

[0017] FIGS. 12a-12b are a front cross-sectional view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention and a corresponding detail view, respectively.

[0018] FIGS. 13a-13b are front cross-sectional views of two other exemplary embodiments of a shielded electrical cable according to an aspect of the present invention.

[0019] FIGS. 14a-14b are front cross-sectional views of two other exemplary embodiments of a shielded electrical cable according to an aspect of the present invention.

[0020] FIGS. 15a-15c are front cross-sectional views of three other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0021] FIGS. 16a-16g are front cross-sectional detail views illustrating seven exemplary embodiments of a parallel portion of a shielded electrical cable according to aspects of the present invention.

[0022] FIGS. 17a-17b are front cross-sectional detail views of another exemplary embodiment of a parallel portion of a shielded electrical cable according to an aspect of the present invention.

[0023] FIG. 18 is a front cross-sectional detail view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention in a bent configuration.

[0024] FIG. 19 is a front cross-sectional detail view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0025] FIGS. 20a-20f are front cross-sectional detail views illustrating six other exemplary embodiments of a parallel portion of a shielded electrical cable according to aspects of the present invention.

[0026] FIG. 21a-21b are front cross-sectional views of two other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0027] FIG. 22 is a graph comparing the electrical isolation performance of an exemplary embodiment of a shielded electrical cable according to an aspect of the present invention to the electrical isolation performance of a conventional electrical cable.

[0028] FIG. 23 is a front cross-sectional view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0029] FIG. 24 is a front cross-sectional view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0030] FIG. 25 is a front cross-sectional view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0031] FIG. 26a-26d are front cross-sectional views of four other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0032] FIG. 27 is a front cross-sectional view of another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention.

[0033] FIG. 28a-28d are front cross-sectional views of four other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0034] FIG. 29a-29d are front cross-sectional views of four other exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

DETAILED DESCRIPTION

[0035] In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings that form a part hereof. The accompanying drawings show, by way of illustration, specific embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized, and structural or logical changes may be made without departing from the scope of the present invention. The following detailed description, therefore, is not to be taken in a limiting sense, and the scope of the invention is defined by the appended claims.

[0036] Referring now to the Figures, FIG. 1 illustrates an exemplary embodiment of a shielded electrical cable according to an aspect of the present invention. Shielded electrical cable 2 includes a plurality of spaced apart conductor sets 4 arranged generally in a single plane. Each conductor set includes two substantially parallel longitudinal insulated conductors 6. Insulated conductors 6 may include insulated signal wires, insulated power wires, or insulated ground wires. Two generally parallel shielding films 8 are disposed around conductor sets 4. A conformable adhesive layer 10 is disposed between shielding films 8 and bonds shielding films 8 to each other on both sides of each conductor set 4. In one embodiment, conductor sets 4 have a substantially curvilinear cross-sectional shape, and shielding films 8 are disposed around conductor sets 4 such as to substantially conform to and maintain the cross-sectional shape. Maintaining the cross-

sectional shape maintains the electrical characteristics of conductor sets 4 as intended in the design of conductor sets 4. This is an advantage over some conventional shielded electrical cables where disposing a conductive shield around a conductor set changes the cross-sectional shape of the conductor set.

[0037] Although in the embodiment illustrated in FIG. 1, each conductor set 4 includes two insulated conductors 6, in other embodiments, each conductor set 4 may include one or more insulated conductors 6. For example, instead of shielded electrical cable 2 including four conductor sets 4 each including two insulated conductors 6 as shown in FIG. 1, shielded electrical cable 2 may include one conductor set 4 including eight insulated conductors 6, or eight conductor sets 4 each including one insulated conductor 6. This flexibility in arrangements of conductor sets 4 and insulated conductors 6 allows shielded electrical cable 2 to be configured suitable for the intended application. For example, conductor sets 4 and insulated conductors 6 may be configured to form a multiple twinaxial cable, i.e., multiple conductor sets 4 each including two insulated conductors 6, a multiple coaxial cable, i.e., multiple conductor sets each including one insulated conductor 6, or a combination thereof. In other embodiments, a conductor set 4 may further include a conductive shield (not shown) disposed around the one or more insulated conductors 6, and an insulative jacket (not shown) disposed around the conductive shield.

[0038] In the embodiment illustrated in FIG. 1, shielded electrical cable 2 further includes optional longitudinal ground conductors 12. Ground conductors 12 may include ground wires or drain wires. Ground conductors 12 are spaced apart from and extend in substantially the same direction as insulated conductors 6. Conductor sets 4 and ground conductors 12 are arranged generally in a single plane. Shielding films 8 are disposed around ground conductors 12 and conformable adhesive layer 10 bonds shielding films 8 to each other on both sides of ground conductors 12. Ground conductors 12 may electrically contact at least one of shielding films 8.

[0039] FIGS. 2a-2e illustrate various exemplary embodiments of a shielded electrical cable according to aspects of the present invention. FIGS. 2a-2e are specifically intended to illustrate various examples of arrangements of conductors disposed between two shielding films.

[0040] Referring to FIG. 2a, shielded electrical cable 102 includes a single conductor set 104. Conductor set 104 includes a single longitudinal insulated conductor 106. Two generally parallel shielding films 108 are disposed around conductor set 104. A conformable adhesive layer 110 is disposed between shielding films 108 and bonds shielding films 108 to each other on both sides of conductor set 104. Shielded electrical cable 102 further includes optional longitudinal ground conductors 112. Ground conductors 112 are spaced apart from and extend in substantially the same direction as insulated conductor 106. Conductor set 104 and ground conductors 112 are arranged generally in a single plane. Shielding films 108 are disposed around ground conductors 112 and conformable adhesive layer 110 bonds shielding films 108 to each other on both sides of ground conductors 112. Ground conductors 112 may electrically contact at least one of shielding films 108. Insulated conductor 106 is effectively arranged in a coaxial or single ended cable arrangement.

[0041] Referring to FIG. 2b, shielded electrical cable 202 is similar to shielded electrical cable 102 illustrated in FIG. 2a.

Where shielded electrical cable **102** includes a single conductor set **104** including a single longitudinal insulated conductor **106**, shielded electrical cable **202** includes a single conductor set **204** including two substantially parallel longitudinal insulated conductors **206**. Insulated conductors **206** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement.

[0042] Referring to FIG. 2c, shielded electrical cable **302** is similar to shielded electrical cable **102** illustrated in FIG. 2a. Where shielded electrical cable **102** includes a single conductor set **104** including a single longitudinal insulated conductor **106**, shielded electrical cable **302** includes a single conductor set **304** including two longitudinal insulated conductors **306**. Insulated conductors **306** are arranged effectively in a twisted pair cable arrangement, whereby insulated conductors **306** twist around each other in longitudinal direction.

[0043] Referring to FIG. 2d, shielded electrical cable **402** is similar to shielded electrical cable **102** illustrated in FIG. 2a. Where shielded electrical cable **102** includes a single conductor set **104** including a single longitudinal insulated conductor **106**, shielded electrical cable **402** includes a single conductor set **404** including four longitudinal insulated conductors **406**. Insulated conductors **406** are arranged effectively in a quad cable arrangement, whereby insulated conductors **406** may twist around each other in longitudinal direction, or may be substantially parallel.

[0044] Referring back to FIGS. 2a-2d, further embodiments of shielded electrical cables according to aspects of the present invention may include a plurality of spaced apart conductor sets **104**, **204**, **304** or **404**, or combinations thereof, arranged generally in a single plane. Optionally, the shielded electrical cables may include a plurality of ground conductors **112** spaced apart from and extending generally in the same direction as the insulated conductors of the conductor sets, wherein the conductor sets and ground conductors are arranged generally in a single plane. FIG. 2e illustrates an exemplary embodiment of such a shielded electrical cable.

[0045] Referring to FIG. 2e, shielded electrical cable **502** includes a plurality of spaced apart conductor sets **104**, **204** arranged generally in a single plane. Shielded electrical cable **502** further includes optional ground conductors **112** disposed between conductor sets **104**, **204** and at both ends of shielded electrical cable **502**. Two generally parallel shielding films **508** are disposed around conductor sets **104**, **204** and ground conductors **112**. A conformable adhesive layer **510** is disposed between shielding films **508** and bonds shielding films **508** to each other on both sides of each conductor set **104**, **204** and each ground conductor. Shielded electrical cable **502** includes a combination of coaxial cable arrangements (conductor sets **104**) and a twinaxial cable arrangement (conductor set **204**) and may therefore be referred to as a hybrid cable arrangement.

[0046] FIG. 3 illustrates two shielded electrical cables **2** terminated to a printed circuit board **14**. Because insulated conductors **6** and ground conductors **12** are arranged generally in a single plane, shielded electrical cables **2** are well suited for mass-stripping, i.e., the simultaneous stripping of shielding films **8** and insulated conductors **6**, and mass-termination, i.e., the simultaneous terminating of the stripped ends of insulated conductors **6** and ground conductors **12**, which allows a more automated cable assembly process. This is an advantage of the shielded electrical cables according to aspects of the present invention. In FIG. 3, the stripped ends of insulated conductors **6** and ground conductors **12** are ter-

minated to contact elements **16** on printed circuit board **14**. In other embodiments, the stripped ends of insulated conductors **6** and ground conductors **12** may be terminated to any suitable individual contact elements of any suitable termination point, such as, e.g., electrical contacts of an electrical connector.

[0047] FIGS. 4a-4d illustrate an exemplary termination process of shielded electrical cable **2** to printed circuit board **14**. This termination process can be a mass-termination process and includes the steps of stripping (illustrated in FIGS. 4a-4b), aligning (illustrated in FIG. 4c), and terminating (illustrated in FIG. 4d). When forming shielded electrical cable **2**, the arrangement of conductor sets **4**, insulated conductors **6**, and ground conductors **12** of shielded electrical cable **2** may be matched to the arrangement of contact elements **16** on printed circuit board **14**, which would eliminate any significant manipulation of the end portions of shielded electrical cable **2** during alignment or termination.

[0048] In the step illustrated in FIG. 4a, an end portion **8a** of shielding films **8** is removed. Any suitable method may be used, such as, e.g., mechanical stripping or laser stripping. This step exposes an end portion of insulated conductors **6** and ground conductors **12**. In one aspect, mass-stripping of end portion **8a** of shielding films **8** is possible because they form an integrally connected layer that is separate from the insulation of insulated conductors **6**. Removing shielding films **8** from insulated conductors **6** allows protection against electrical shorting at these locations and also provides independent movement of the exposed end portions of insulated conductors **6** and ground conductors **12**. In the step illustrated in FIG. 4b, an end portion **6a** of the insulation of insulated conductors **6** is removed. Any suitable method may be used, such as, e.g., mechanical stripping or laser stripping. This step exposes an end portion of the conductor of insulated conductors **6**. In the step illustrated in FIG. 4c, shielded electrical cable **2** is aligned with printed circuit board **14** such that the end portions of the conductors of insulated conductors **6** and the end portions of ground conductors **12** of shielded electrical cable **2** are aligned with contact elements **16** on printed circuit board **14**. In the step illustrated in FIG. 4d, the end portions of the conductors of insulated conductors **6** and the end portions of ground conductors **12** of shielded electrical cable **2** are terminated to contact elements **16** on printed circuit board **14**. Examples of suitable termination methods that may be used include soldering, welding, crimping, mechanical clamping, and adhesively bonding, to name a few.

[0049] FIG. 5 illustrates another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention. Shielded electrical cable **602** is similar to shielded electrical cable **2** illustrated in FIG. 1. In addition, shielded electrical cable **602** includes a plurality of longitudinal splits **18** disposed between conductor sets **4**. Splits **18** separate individual conductor sets **4** at least along a portion of the length of shielded electrical cable **602**, thereby increasing at least the lateral flexibility of shielded electrical cable **602**. This allows shielded electrical cable **602** to be placed more easily into a curvilinear outer jacket, e.g. In other embodiments, splits **18** may be placed such as to separate individual or multiple conductor sets **4** and ground conductors **12**. To maintain the spacing of conductor sets **4** and ground conductors **12**, splits **18** may be discontinuous along the length of shielded electrical cable **602**. To maintain the spacing of conductor sets **4** and ground conductors **12** in at least one end portion A of shielded electrical cable **602** and thereby maintaining mass-termination capability, splits **18** may not extend

into one or both end portions A. Splits **18** may be formed in shielded electrical cable **602** using any suitable method, such as, e.g., laser cutting or punching. Instead of or in combination with longitudinal splits, other suitable shapes of openings may be formed in shielded electrical cable **602**, such as, e.g., holes, e.g., to increase at least the lateral flexibility of shielded electrical cable **602**.

[0050] FIG. 6 illustrates another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention. Shielded electrical cable **702** is similar to shielded electrical cable **602** illustrated in FIG. 5. Effectively, in shielded electrical cable **702**, one of conductor sets **4** is replaced by two ground conductors **12**. Shielded electrical cable **702** includes longitudinal splits **18** and **18'**. Split **18** separates individual conductor sets **4** along a portion of the length of shielded electrical cable **702** and does not extend into end portions A of shielded electrical cable **702**. Split **18'** separates individual conductor sets **4** along the length of shielded electrical cable **702** and extends into end portions A of shielded electrical cable **702**, which effectively splits shielded electrical cable **702** into two individual shielded electrical cables **702'**, **702''**. Shielding films **8** and ground conductors **12** provide an uninterrupted ground plane in each of the individual shielded electrical cables **702'**, **702''**. This exemplary embodiment illustrates the advantage of the parallel processing capability of the shielded electrical cables according to aspects of the present invention, whereby multiple shielded electrical cables may be formed simultaneously.

[0051] FIGS. 7a-7d illustrate four other exemplary embodiments of a shielded electrical cable according to aspects of the present invention. FIGS. 7a-7e are specifically intended to illustrate various examples of constructions of the shielding films of the shielded electrical cables. In one aspect, at least one of the shielding films may include a conductive layer and a non-conductive polymeric layer. The conductive layer may include any suitable conductive material, including but not limited to copper, silver, aluminum, gold, and alloys thereof. The non-conductive polymeric layer may include any suitable polymeric material, including but not limited to polyester, polyimide, polyamide-imide, polytetrafluoroethylene, polypropylene, polyethylene, polyphenylene sulfide, polyethylene naphthalate, polycarbonate, silicone rubber, ethylene propylene diene rubber, polyurethane, acrylates, silicones, natural rubber, epoxies, and synthetic rubber adhesive. The non-conductive polymeric layer may include one or more additives and/or fillers to provide properties suitable for the intended application. In another aspect, at least one of the shielding films may include a laminating adhesive layer disposed between the conductive layer and the non-conductive polymeric layer. In another aspect, at least one of the shielding films may include a stand-alone conductive film. The construction of the shielding films may be selected based on a number of design parameters suitable for the intended application, such as, e.g., flexibility, electrical performance, and configuration of the shielded electrical cable (such as, e.g., presence and location of ground conductors). In one embodiment, the shielding films include an integrally formed shielding film. In one embodiment, the shielding films have a thickness in the range of 0.01 mm to 0.05 mm. The shielding films provide isolation, shielding, and precise spacing between the conductor sets, and enable a more automated and lower cost cable manufacturing process. In addition, the shielding films prevent a phenomenon known as "signal suck-out" or reso-

nance, whereby high signal attenuation occurs at a particular frequency range. This phenomenon typically occurs in conventional shielded electrical cables where a conductive shield is wrapped around a conductor set.

[0052] Referring to FIG. 7a, shielded electrical cable **802** includes a single conductor set **804**. Conductor set **804** includes two substantially parallel longitudinal insulated conductors **806**. Two generally parallel shielding films **808** are disposed around conductor set **804**. Shielding films **808** include a conformable adhesive layer **810** that bonds shielding films **808** to each other on both sides of conductor set **804**. Insulated conductors **806** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielding films **808** include a conductive layer **808a** and a non-conductive polymeric layer **808b**. Non-conductive polymeric layer **808b** faces insulated conductors **806**. Conductive layer **808a** may be deposited onto non-conductive polymeric layer **808b** using any suitable method.

[0053] Referring to FIG. 7b, shielded electrical cable **902** includes a single conductor set **904**. Conductor set **904** includes two substantially parallel longitudinal insulated conductors **906**. Two generally parallel shielding films **908** are disposed around conductor set **904**. Shielding films **908** include a conformable adhesive layer **910** that bonds shielding films **908** to each other on both sides of conductor set **904**. Insulated conductors **906** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielding films **908** include a conductive layer **908a** and a non-conductive polymeric layer **908b**. Conductive layer **908a** faces insulated conductors **906**. Conductive layer **908a** may be deposited onto non-conductive polymeric layer **908b** using any suitable method.

[0054] Referring to FIG. 7c, shielded electrical cable **1002** includes a single conductor set **1004**. Conductor set **1004** includes two substantially parallel longitudinal insulated conductors **1006**. Two generally parallel shielding films **1008** are disposed around conductor set **1004**. Shielding films **1008** include a conformable adhesive layer **1010** that bonds shielding films **1008** to each other on both sides of conductor set **1004**. Insulated conductors **1006** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielding films **1008** include a stand-alone conductive film.

[0055] Referring to FIG. 7d, shielded electrical cable **1102** includes a single conductor set **1104**. Conductor set **1104** includes two substantially parallel longitudinal insulated conductors **1106**. Two generally parallel shielding films **1108** are disposed around conductor set **1104**. Shielding films **1108** include a conformable adhesive layer **1110** that bonds shielding films **1108** to each other on both sides of conductor set **1104**. Insulated conductors **1106** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielding films **1108** include a conductive layer **1108a**, a non-conductive polymeric layer **1108b**, and a laminating adhesive layer **1108c** disposed between conductive layer **1108a** and non-conductive polymeric layer **1108b**, thereby laminating conductive layer **1108a** to non-conductive polymeric layer **1108b**. Conductive layer **1108a** faces insulated conductors **1106**.

[0056] Referring back to FIG. 1, conformable adhesive layer **10** of shielded electrical cable **2** is disposed between shielding films **8** and bonds shielding films **8** to each other on both sides of each conductor set **4**. In one embodiment, conformable adhesive layer **10** may be disposed on one of shield-

ing films 8. In another embodiment, conformable adhesive layer 10 may be disposed on both shielding films 8. Conformable adhesive layer 10 may include an insulative adhesive and provide an insulative bond between shielding films 8. Optionally, conformable adhesive layer 10 may provide an insulative bond between at least one of shielding films 8 and insulated conductors 6, and between at least one of shielding films 8 and ground conductors 12. Conformable adhesive layer 10 may include a conductive adhesive and provide a conductive bond between shielding films 8. Optionally, conformable adhesive layer 10 may provide a conductive bond between at least one of shielding films 8 and ground conductors 12. Suitable conductive adhesives include conductive particles to provide the flow of electrical current. The conductive particles can be any of the types of particles currently used, such as spheres, flakes, rods, cubes, amorphous, or other particle shapes. They may be solid or substantially solid particles such as carbon black, carbon fibers, nickel spheres, nickel coated copper spheres, metal-coated oxides, metal-coated polymer fibers, or other similar conductive particles. These conductive particles can be made from electrically insulating materials that are plated or coated with a conductive material such as silver, aluminum, nickel, or indium tin-oxide. The metal-coated insulating material can be substantially hollow particles such as hollow glass spheres, or may comprise solid materials such as glass beads or metal oxides. The conductive particles may be on the order of several tens of microns to nanometer sized materials such as carbon nanotubes. Suitable conductive adhesives may also include a conductive polymeric matrix. In one aspect, conformable adhesive layer 10 may include a continuous adhesive layer extending along the entire length and width of shielding films 8. In another aspect, conformable adhesive layer 10 may include a discontinuous adhesive layer. For example, conformable adhesive layer 10 may be present only in some portions along the length or width of shielding films 8. In one embodiment, discontinuous adhesive layer 10 includes a plurality of longitudinal adhesive stripes that are disposed, e.g., on both sides of each conductor set 4 and ground conductors 12. In one embodiment, conformable adhesive layer 10 includes at least one of a pressure sensitive adhesive, a hot melt adhesive, a thermoset adhesive, and a curable adhesive. In one embodiment, conformable adhesive layer 10 is configured to provide a bond between shielding films 8 that is substantially stronger than a bond between one or more insulated conductor 6 and shielding films 8. This may be achieved, e.g., by selecting the adhesive formulation accordingly. An advantage of this adhesive configuration is that shielding films 8 are readily strippable from the insulation of insulated conductors 6. In another embodiment, conformable adhesive layer 10 is configured to provide a bond between shielding films 8 and a bond between one or more insulated conductor 6 and shielding films 8 that are substantially equally strong. An advantage of this adhesive configuration is that insulated conductors 6 are anchored between shielding films 8. On bending shielded electrical cable 2, this allows for little relative movement and therefore reduces the likelihood of buckling of shielding films 8. Suitable bond strengths may be chosen based on the intended application. In one embodiment, conformable adhesive layer 10 has a thickness of less than about 0.13 mm. In a preferred embodiment, conformable adhesive layer 10 has a thickness of less than about 0.05 mm.

[0057] Conformable adhesive layer 10 may conform to achieve desired mechanical and electrical performance char-

acteristics of shielded electrical cable 2. In one aspect, conformable adhesive layer 10 may conform to be thinner between shielding films 8 in areas between conductor sets 4, which increases at least the lateral flexibility of shielded electrical cable 2. This allows shielded electrical cable 2 to be placed more easily into a curvilinear outer jacket, e.g. In another aspect, conformable adhesive layer 10 may conform to be thicker in areas immediately adjacent conductor sets 4 and substantially conform to conductor sets 4. This increases the mechanical strength and enables forming a curvilinear shape of shielding films 8 in these areas, which increases the durability of shielded electrical cable 2, e.g., during flexing of the cable. In addition, this helps to maintain the position and spacing of insulated conductors 6 relative to shielding films 8 along the length of shielded electrical cable 2, which results in uniform impedance and superior signal integrity of shielded electrical cable 2. In another aspect, conformable adhesive layer 10 may conform to effectively be partially or completely removed between shielding films 8 in areas between conductor sets 4. As a result, shielding films 8 electrically contact each other in these areas, which increases the electrical performance of shielded electrical cable 2. In another aspect, conformable adhesive layer 10 may conform to effectively be partially or completely removed between at least one of shielding films 8 and ground conductors 12. As a result, ground conductors 12 electrically contact at least one of shielding films 8 in these areas, which increases the electrical performance of shielded electrical cable 2. Even if a thin conformable adhesive layer 10 exists between at least one of shielding films 8 and ground conductors 12, asperities on ground conductors 12 may break through conformable adhesive layer 10 to establish electrical contact as intended.

[0058] FIGS. 8a-8c illustrate three other exemplary embodiments of a shielded electrical cable according to aspects of the present invention. FIGS. 8a-8c are specifically intended to illustrate examples of the placement of ground conductors in the shielded electrical cables. An aspect of a shielded electrical cable is proper grounding of the shield. Shielded electrical cables according to aspects of the present invention can be grounded in a number of ways. In one aspect, the ground conductors electrically contact at least one of the shielding films such that grounding the ground conductors also grounds the shielding films. In this arrangement, the ground conductors may also be referred to as "drain wires". In another aspect, the ground conductors do not electrically contact the shielding films, but are individual elements in the cable construction that may be independently terminated to any suitable individual contact element of any suitable termination point, such as, e.g., a contact element on a printed circuit board. In this arrangement, the ground conductors may also be referred to as "ground wires". FIG. 8a illustrates an exemplary embodiment of a shielded electrical cable according to an aspect of the present invention wherein the ground conductors are positioned external to the shielding films. FIGS. 8b-8c illustrate two exemplary embodiments of a shielded electrical cable according to aspects of the present invention wherein the ground conductors are positioned between the shielding films, and may be included in the conductor set. One or more ground conductors may be placed in any suitable position external to the shielding films, between the shielding films, or a combination of both.

[0059] Referring to FIG. 8a, shielded electrical cable 1202 includes a single conductor set 1204. Conductor set 1204 includes two substantially parallel longitudinal insulated con-

ductors **1206**. Two generally parallel shielding films **1208** are disposed around conductor set **1204**. A conformable adhesive layer **1210** is disposed between shielding films **1208** and bonds shielding films **1208** to each other on both sides of conductor set **1204**. Insulated conductors **1206** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielded electrical cable **1202** further includes a plurality of ground conductors **1212** positioned external to shielding films **1208**. Ground conductors **1212** are placed over, under, and on both sides of conductor set **1204**. Optionally, shielded electrical cable **1202** includes protective films **1220** surrounding shielding films **1208** and ground conductors **1212**. Protective films **1220** include a protective layer **1220a** and an adhesive layer **1220b** bonding protective layer **1220a** to shielding films **1208** and ground conductors **1212**. Alternatively, shielding films **1208** and ground conductors **1212** may be surrounded by an outer conductive shield, such as, e.g., a conductive braid, and an outer insulative jacket (not shown).

[0060] Referring to FIG. **8b**, shielded electrical cable **1302** includes a single conductor set **1304**. Conductor set **1304** includes two substantially parallel longitudinal insulated conductors **1306**. Two generally parallel shielding films **1308** are disposed around conductor set **1304**. A conformable adhesive layer **1310** is disposed between shielding films **1308** and bonds shielding films **1308** to each other on both sides of conductor set **1304**. Insulated conductors **1306** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielded electrical cable **1302** further includes a plurality of ground conductors **1312** positioned between shielding films **1308**. Two of the ground conductors **1312** are included in conductor set **1304**, and two of the ground conductors **1312** are spaced apart from conductor set **1304**.

[0061] Referring to FIG. **8c**, shielded electrical cable **1402** includes a single conductor set **1404**. Conductor set **1404** includes two substantially parallel longitudinal insulated conductors **1406**. Two generally parallel shielding films **1408** are disposed around conductor set **1404**. A conformable adhesive layer **1410** is disposed between shielding films **1408** and bonds shielding films **1408** to each other on both sides of conductor set **1404**. Insulated conductors **1406** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielded electrical cable **1402** further includes a plurality of ground conductors **1412** positioned between shielding films **1408**. All of the ground conductors **1412** are included in conductor set **1404**. Two of the ground conductors **1412** and insulated conductors **1406** are arranged generally in a single plane.

[0062] FIGS. **9a-9b** illustrate an exemplary embodiment of an electrical assembly according to an aspect of the present invention terminated to a printed circuit board. Electrical assembly **1500** includes a shielded electrical cable **1502** and an electrically conductive cable clip **1522**. Shielded electrical cable **1502** includes a plurality of spaced apart conductor sets **1504** arranged generally in a single plane. Each conductor set includes two substantially parallel longitudinal insulated conductors **1506**. Two generally parallel shielding films **1508** are disposed around conductor sets **1504**. A conformable adhesive layer **1510** is disposed between shielding films **1508** and bonds shielding films **1508** to each other on both sides of each conductor set **1504**. Cable clip **1522** is clamped or otherwise attached to an end portion of shielded electrical cable **1502** such that at least one of shielding films **1508** electrically

contacts cable clip **1522**. Cable clip **1522** is configured for termination to a ground reference, such as, e.g., contact element **1516** on printed circuit board **1514**, to establish a ground connection between shielded electrical cable **1502** and the ground reference. Cable clip may be terminated to the ground reference using any suitable method, including soldering, welding, crimping, mechanical clamping, and adhesively bonding, to name a few. When terminated, cable clip **1522** may facilitate termination of the end portions of the conductors of insulated conductors **1506** of shielded electrical cable **1502** to contact elements of a termination point, such as, e.g., contact elements **16** on printed circuit board **14**. Shielded electrical cable **1502** may include one or more ground conductors as described herein that may electrically contact cable clip **1522** in addition to or instead of at least one of shielding films **1508**.

[0063] FIGS. **10a-10g** illustrate an exemplary method of making a shielded electrical cable according to an aspect of the present invention. Specifically, FIGS. **10a-10g** illustrate an exemplary method of making shielded electrical cable **2** illustrated in FIG. **1**.

[0064] In the step illustrated in FIG. **10a**, insulated conductors **6** are formed using any suitable method, such as, e.g., extrusion. Insulated conductors **6** may be formed of any suitable length. Insulated conductors **6** may then be provided as such or cut to a desired length. Ground conductors **12** may be formed and provided in a similar fashion (not shown). In the step illustrated in FIG. **10b**, shielding films **8** are formed. A single layer or multilayer web may be formed using any suitable method, such as, e.g., continuous wide web processing. Shielding films **8** may be formed of any suitable length. Shielding films **8** may then be provided as such or cut to a desired length and/or width. Shielding films **8** may be preformed to have transverse partial folds to increase flexibility in the longitudinal direction. As illustrated in FIG. **10b**, shielding films **8** include conformable adhesive layer **10**, which may be formed on shielding films **8** using any suitable method, such as, e.g., laminating or sputtering. In the step illustrated in FIG. **10c**, a plurality of insulated conductors **6**, ground conductors **12**, and shielding films **8** are provided. A forming tool **24** is provided. Forming tool **24** includes a pair of forming rolls **26a**, **26b** having a shape corresponding to a cross-sectional shape of shielded electrical cable **2** and include a bite **28**. Insulated conductors **6**, ground conductors **12**, and shielding films **8** are arranged according to the configuration of shielded electrical cable **2**, and positioned in proximity to forming rolls **26a**, **26b**, after which they are concurrently fed into bite **28** of forming rolls **26a**, **26b** and disposed between forming rolls **26a**, **26b**. Forming tool **24** forms shielding films **8** around conductor sets **4** and ground conductor **12** and bonds shielding films **8** to each other on both sides of each conductor set **4** and ground conductors **12**. Heat may be applied to facilitate bonding. Although in this embodiment, forming shielding films **8** around conductor sets **4** and ground conductor **12** and bonding shielding films **8** to each other on both sides of each conductor set **4** and ground conductors **12** occur in a single operation, in other embodiments, these steps may occur in separate operations. FIG. **10d** illustrates shielded electrical cable **2** as it is formed by forming tool **24**. In the step illustrated in FIG. **10e**, longitudinal splits **18** are formed between conductor sets **4**. Splits **18** may be formed in shielded electrical cable **2** using any suitable method, such as, e.g., laser cutting or punching. In the step illustrated in FIG. **10f**, shielding films **8** of shielded electrical

cable 2 are folded and an outer conductive shield 30 is provided around the folded shielding films 8 using any suitable method. In the step illustrated in FIG. 10g, an outer jacket 32 is provided around outer conductive shield 30 using any suitable method, such as, e.g., extrusion. In other embodiments, outer conductive shield 30 may be omitted and outer jacket 32 may be provided around the folded shielding films 8.

[0065] FIGS. 11a-11c illustrate a detail of an exemplary method of making a shielded electrical cable according to an aspect of the present invention. FIGS. 11a-11c are specifically intended to illustrate an example of the conforming of conformable adhesive layers during the forming and bonding of shielding films.

[0066] In the step illustrated in FIG. 11a, an insulated conductor 1606, a ground conductor 1612 spaced apart from insulated conductor 1606, and two shielding films 1608 are provided. Shielding films 1608 each include a conformable adhesive layer 1610. In the steps illustrated in FIGS. 11b-11c, shielding films 1608 are formed around insulated conductor 1606 and ground conductor 1612 and bonded to each other. Initially, as illustrated in FIG. 11b, conformable adhesive layers 1610 still have their original thickness. As the forming and bonding of shielding films 1608 proceeds, conformable adhesive layers 1610 conform to achieve desired mechanical and electrical performance characteristics of shielded electrical cable 1602. Specifically, as illustrated in FIG. 11c, conformable adhesive layers 1610 conform to be thinner between shielding films 1608 on both sides of insulated conductor 1606 and ground conductor 1612; a portion of conformable adhesive layers 1610 displaces away from these areas. Further, conformable adhesive layers 1610 conform to be thicker in areas immediately adjacent insulated conductor 1606 and ground conductor 1612, and substantially conform to insulated conductor 1606 and ground conductor 1612; a portion of conformable adhesive layers 1610 displaces into these areas. Further, conformable adhesive layers 1610 conform to effectively be removed between shielding films 1608 and ground conductor 1612; conformable adhesive layers 1610 displace away from these areas such that ground conductor 1612 electrically contacts shielding films 1608.

[0067] In certain exemplary embodiments, the shielded electrical cable according to an aspect of the present invention includes a transition portion positioned on one or both sides of the conductor set. This transition portion is configured to provide high manufacturability and strain and stress relief of the shielded electrical cable. Maintaining this transition portion at a substantially constant configuration (including aspects such as, e.g., size, shape, and content) along the length of the shielded electrical cable facilitates the shielded electrical cable to have substantially uniform electrical properties, such as, e.g., impedance, skew, insertion loss, reflection, mode conversion, eye opening, and jitter. Additionally, in certain embodiments, such as, e.g., embodiments wherein the conductor set includes two substantially parallel longitudinal insulated conductors arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement, maintaining this transition portion at a substantially constant configuration along the length of the shielded electrical cable beneficially provides substantially the same electromagnetic field deviation from an ideal concentric case for both conductors in the conductor set. Thus, careful control of the configuration of this transition portion along the length of the shielded electrical cable contributes to the electrical performance of the cable. FIGS. 12a-14b illustrate various

exemplary embodiments of a shielded electrical cable according to aspects of the present invention that include a transition portion disposed on one or both sides of the conductor set.

[0068] Referring now to FIGS. 12a-12b, shielded electrical cable 1702 includes a single conductor set 1704. Conductor set 1704 includes a single longitudinal insulated conductor 1706. Two generally parallel shielding films 1708 are disposed around conductor set 1704. An optional conformable adhesive layer 1710 is disposed between shielding films 1708 and bonds shielding films 1708 to each other on both sides of conductor set 1704. Insulated conductor 1706 is effectively arranged in a coaxial or single ended cable arrangement. Shielding films 1708 include a conductive layer 1708a and a non-conductive polymeric layer 1708b. Conductive layer 1708a faces insulated conductors 1706. This configuration of shielding films 1708 is similar to the configuration of shielding films 908 shown in FIG. 7b. Alternatively, the configuration of shielding films 1708 may be similar to the configuration of shielding films 808 shown in FIG. 7a, shielding films 1008 shown in FIG. 7c, or shielding films 1108 shown in FIG. 7d, for example. Shielding films 1708 include a concentric portion 1708' substantially concentric with conductor 1706 and parallel portions 1708" wherein shielding films 1708 are substantially parallel. In other embodiments, shielding films 1708 may include a single parallel portion 1708". Shielded electrical cable 1702 further includes transition portions 1734 positioned on both sides of conductor set 1704. In other embodiments, shielded electrical cable 1702 may include a transition portion 1734 positioned on only one side of conductor set 1704. Transition portions 1734 are defined by shielding films 1708 and conductor set 1704 and provide a gradual transition between concentric portion 1708' and parallel portion 1708" of shielding films 1708. As opposed to a sharp transition, such as, e.g., a right-angle transition or a transition point (as opposed to a transition portion), a gradual transition, such as, e.g., a substantially sigmoidal transition, provides strain and stress relief for shielding films 1708 in transition portions 1734 and prevents damage to shielding films 1708 when shielded electrical cable 1702 is in use, e.g., when laterally or axially bending shielded electrical cable 1702. This damage may include, e.g., fractures in conductive layer 1708a and/or debonding between conductive layer 1708a and non-conductive polymeric layer 1708b. In addition, a gradual transition prevents damage to shielding films 1708 in manufacturing of shielded electrical cable 1702, which may include, e.g., cracking or shearing of conductive layer 1708a and/or non-conductive polymeric layer 1708b.

[0069] The configuration of shielded electrical cables according to aspects of the present invention including a transition portion on one or both sides of the conductor set represents a departure from conventional cable configurations, such as, e.g., an ideal coaxial cable, wherein a shield is generally continuously disposed around a single insulated conductor, or an ideal twinaxial cable, wherein a shield is generally continuously disposed around a pair of insulated conductors. Although these ideal cable configurations provide ideal electromagnetic profiles, these profiles are not necessary to achieve acceptable electrical properties. In the shielded electrical cables according to aspects of the present invention, acceptable electrical properties can be achieved by minimizing the electrical impact of the transition portion, e.g., by minimizing the size of the transition portion and carefully controlling the configuration of the transition portion

tion along the length of the shielded electrical cable. Minimizing the size of the transition portion minimizes the capacitance deviation and minimizes the required space between multiple conductor sets, thereby reducing the conductor set pitch and/or increasing the electrical isolation between conductor sets. Careful control of the configuration of the transition portion along the length of the shielded electrical cable contributes to obtaining predictable electrical behavior and consistency, which is important for high speed transmission lines so that electrical data can be reliably transmitted, and becomes more important when the size of the transition portion cannot be minimized. An electrical characteristic that is often considered is the characteristic impedance of the transmission line. Any impedance changes along the length of a transmission line may cause power to be reflected back to the source instead of being transmitted to the target. Ideally, the transmission line will have no impedance variation along its length, but, depending on the intended application, variations up to 5-10% may be acceptable. Another electrical characteristic that is often considered in twinaxial cables (differentially driven) is skew or unequal transmission speeds of two transmission lines of a pair along at least a portion of their length. Skew produces conversion of the differential signal to a common mode signal that can be reflected back to the source, reduces the transmitted signal strength, creates electromagnetic radiation, and dramatically increases the bit error rate, in particular jitter. Ideally, a pair of transmission lines will have no skew, but, depending on the intended application, a differential S-parameter SCD21 or SCD12 value (representing the differential-to-common mode conversion from one end of the transmission line to the other) of less than -25 to -30 dB up to a frequency of interest, such as, e.g., 6 GHz, may be acceptable. Alternatively, skew can be measured in the time domain and compared to a required specification. Depending on the intended application, values of less than about 20 picoseconds/meter (ps/m) and preferably less than about 10 ps/m may be acceptable.

[0070] Referring back to FIGS. 12a-12b, in part to help achieve acceptable electrical properties, transition portions 1734 of shielded electrical cable 1702 may each include a cross-sectional area 1734a that is smaller than a cross-sectional area 1706a of conductor 1706. As best shown in FIG. 12b, cross-sectional area 1734a of transition portion 1734 is defined by transition points 1734', where shielding films 1708 deviate from being substantially concentric with insulated conductor 1706, and transition points 1734", where shielding films 1708 deviate from being substantially parallel. In addition, each cross-sectional area 1734a may include a void portion 1734b. Void portions 1734b may be substantially the same. Further, conformable adhesive layer 1710 may have a thickness T_{ac} in concentric portion 1708', and a thickness in transition portion 1734 that is greater than thickness T_{ac} in concentric portion 1708'. Similarly, conformable adhesive layer 1710 may have a thickness T_{ap} in parallel portion 1708", and a thickness in transition portion 1734 that is greater than thickness T_{ap} in parallel portion 1708". Conformable adhesive layer 1710 may represent at least 25% of cross-sectional area 1734a. The presence of conformable adhesive layer 1710 in cross-sectional area 1734a, in particular at a thickness that is greater than thickness T_{ac} or thickness T_{ap} , contributes to the strength of transition portion 1734. Careful control of the manufacturing process and the material characteristics of the various elements of shielded electrical cable 1702 may reduce variations in void portion 1734b and the thickness of

conformable adhesive layer 1710 in transition portion 1734, which may in turn reduce variations in the capacitance of cross-sectional area 1734a. Shielded electrical cable 1702 may include a transition portion 1734 positioned on one or both sides of conductor set 1704 that includes a cross-sectional area 1734a that is substantially equal to or smaller than a cross-sectional area 1706a of conductor 1706. Shielded electrical cable 1702 may include a transition portion 1734 positioned on one or both sides of conductor set 1704 that includes a cross-sectional area 1734a that is substantially the same along the length of conductor 1706. For example, cross-sectional area 1734a may vary less than 50% over a length of 1 m. Shielded electrical cable 1702 may include transition portions 1734 positioned on both sides of conductor set 1704 that each include a cross-sectional area 1734a, wherein the sum of cross-sectional areas 1734a is substantially the same along the length of conductor 1706. For example, the sum of cross-sectional areas 1734a may vary less than 50% over a length of 1 m. Shielded electrical cable 1702 may include transition portions 1734 positioned on both sides of conductor set 1704 that each include a cross-sectional area 1734a, wherein the cross-sectional areas 1734a are substantially the same. Shielded electrical cable 1702 may include transition portions 1734 positioned on both sides of conductor set 1704, wherein the transition portions 1734 are substantially identical. Insulated conductor 1706 has an insulation thickness T_i and transition portion 1734 may have a lateral length L_t that is less than insulation thickness T_i . Insulated conductor 1706 has a diameter D_c , and transition portion 1734 may have a lateral length L_t that is less than diameter D_c . The various configurations described above may provide a characteristic impedance that remains within a desired range, such as, e.g., within 5-10% of a target impedance value, such as, e.g., 50 Ohms, over a given length, such as, e.g., 1 m.

[0071] Factors that control the configuration of transition portion 1734 along the length of shielded electrical cable 1702 include the manufacturing process, the thickness of conductive layers 1708a and non-conductive polymeric layers 1708b, conformable adhesive layer 1710, and the bond strength between insulated conductor 1706 and shielding films 1708, to name a few.

[0072] In one aspect, conductor set 1704, shielding films 1708, and transition portion 1734 are cooperatively configured in an impedance controlling relationship. An impedance controlling relationship means that conductor set 1704, shielding films 1708, and transition portion 1734 are cooperatively configured to control the characteristic impedance of the shielded electrical cable.

[0073] FIGS. 13a-13b illustrate two other exemplary embodiments of a shielded electrical cable according to aspects of the present invention including two insulated conductors. Referring to FIG. 13a, shielded electrical cable 1802 includes a single conductor set 1804 including two substantially parallel longitudinal individually insulated conductors 1806. Two generally parallel shielding films 1808 are disposed around conductor set 1804. An optional conformable adhesive layer 1810 is disposed between shielding films 1808 and bonds shielding films 1808 to each other on both sides of conductor set 1804. Insulated conductors 1806 are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement. Shielding films 1808 include a conductive layer 1808a and a non-conductive polymeric layer 1808b. Conductive layer 1808a faces insulated conductors 1806. Shielding films 1808 include concentric

portions **1808'** substantially concentric with corresponding conductors **1806** and parallel portions **1808"** wherein shielding films **1808** are substantially parallel. Shielded electrical cable **1802** includes transition portions **1834** positioned on both sides of conductor set **1804** that each include a cross-sectional area **1834a**, wherein the sum of cross-sectional areas **1834a** is substantially the same along the length of conductors **1806**. For example, the sum of cross-sectional areas **1834a** may vary less than 50% over a length of 1 m. In addition, cross-sectional areas **1834a** are substantially the same and transition portions **1834** are substantially identical. This configuration of transition portions **1834** may provide a characteristic impedance for each conductor **1806** (single-ended) and a differential impedance that both remain within a desired range, such as, e.g., within 5-10% of a target impedance value over a given length, such as, e.g., 1 m. In addition, this configuration of transition portions **1834** may minimize skew of the two conductors **1806** along at least a portion of their length. Referring to FIG. **13b**, shielded electrical cable **1902** is similar to shielded electrical cable **1802**. Whereas shielded electrical cable **1802** has individually insulated conductors **1806**, shielded electrical cable **1902** has jointly insulated conductors **1906**. Nonetheless, transition portions **1934** are identical to transition portions **1834** and provide the same benefits to shielded electrical cable **1902**.

[0074] FIGS. **14a-14b** illustrate two other exemplary embodiments of a shielded electrical cable according to aspects of the present invention including two insulated conductors. These exemplary embodiments are intended to illustrate variations in position and configuration of the transition portions. Shielded electrical cables **2002** (FIGS. **14a**) and **2102** (FIG. **14b**) are similar to shielded electrical cable **1802**. Whereas in shielded electrical cable **1802**, parallel portions **1808"** of shielding films **1808** and insulated conductors **1806** are arranged generally in a single plane, in shielded electrical cables **2002** and **2102**, parallel portions **2008"** and **2108"** of shielding films **2008** and **2108** and insulated conductors **2006** and **2106** are arranged in different planes. As a result, transition portions **2034** and **2134** have a different position and configuration. For reasons including that transition portions **2034** and **2134** are positioned substantially symmetrically with respect to corresponding insulated conductors **2006** and **2106** and that the configuration of transition portions **2034** and **2134** is carefully controlled along the length of shielded electrical cables **2002** and **2102**, shielded electrical cables **2002** and **2102** are configured to still provide acceptable electrical properties.

[0075] In further exemplary embodiments, shielded electrical cables according to aspects of the present invention include a plurality of spaced apart conductor sets arranged generally in a single plane. Each conductor set includes one or more substantially parallel longitudinal insulated conductors. Two generally parallel shielding films are disposed around the conductor sets and include a plurality of concentric portions substantially concentric with at least one of the conductors and a plurality of parallel portions wherein the shielding films are substantially parallel. A plurality of transition portions defined by the shielding films and the conductor sets provide a gradual transition between the concentric portions and the parallel portions of the shielding films. The transition portions may be positioned on both sides of each conductor set. For example, the shielded electrical cable may include a combination of one or more conductor sets **1704**, wherein insulated conductor **1706** is effectively arranged in a coaxial

or single ended cable arrangement, and one or more conductor sets **1804**, wherein insulated conductors **1806** are effectively arranged in a twinaxial or differential pair cable arrangement. The conductor sets, shielding films and transition portions may be cooperatively configured in an impedance controlling relationship.

[0076] FIGS. **15a-15c**, **18** and **19** illustrate several other exemplary embodiments of a shielded electrical cable according to aspects of the present invention. FIGS. **16a-16g**, **17a-17b** and **20a-20f** illustrate several exemplary embodiments of a parallel portion of a shielded electrical cable according to aspects of the present invention. FIGS. **15a-20f** are specifically intended to illustrate examples of a parallel portion that is configured to electrically isolate a conductor set of the shielded electrical cable. The conductor set may be electrically isolated from an adjacent conductor set (e.g., to minimize crosstalk between adjacent conductor sets, FIGS. **15a-15c** and **16a-16g**) or from the external environment of the shielded electrical cable (e.g., to minimize electromagnetic radiation escape from the shielded electrical cable and minimize electromagnetic interference from external sources, FIGS. **19** and **20a-20f**). In both cases, the parallel portion may include various mechanical structures to realize the electrical isolation. Examples include close proximity of the shielding films, high dielectric constant material between the shielding films, ground conductors that make direct or indirect electrical contact with at least one of the shielding films, extended distance between adjacent conductor sets, physical breaks between adjacent conductor sets, intermittent contact of the shielding films to each other directly either longitudinally, transversely, or both, and conductive adhesive, to name a few. In one aspect, a parallel portion of the shielding films is defined as a portion of the shielding films that is not covering a conductor set.

[0077] In FIGS. **15a**, shielded electrical cable **2202** includes two conductor sets **2204**, each including two substantially parallel longitudinal insulated conductors **2206**, and two generally parallel shielding films **2208** disposed around conductor sets **2204**. Shielding films **2208** include parallel portions **2208"** wherein shielding films **2208** are substantially parallel. Parallel portions **2208"** positioned in between conductor sets **2204** are configured to electrically isolate conductor sets **2204** from each other. In shielded electrical cable **2202**, parallel portions **2208"** of shielding films **2208** and insulated conductors **2206** are arranged generally in a single plane.

[0078] In FIGS. **15b**, shielded electrical cable **2302** includes two conductor sets **2304**, each including one longitudinal insulated conductor **2306**, and two generally parallel shielding films **2308** disposed around conductor sets **2304**. Shielding films **2308** include parallel portions **2308"** wherein shielding films **2308** are substantially parallel. Parallel portions **2308"** positioned in between conductor sets **2304** are configured to electrically isolate conductor sets **2304** from each other. In shielded electrical cable **2302**, parallel portions **2308"** of shielding films **2308** and insulated conductors **2306** are arranged generally in a single plane.

[0079] In FIGS. **15c**, shielded electrical cable **2402** includes two conductor sets **2404**, each including two substantially parallel longitudinal insulated conductors **2406**, and two generally parallel shielding films **2408** disposed around conductor sets **2404**. Shielding films **2408** include parallel portions **2408"** wherein shielding films **2408** are substantially parallel. Parallel portions **2408"** positioned in

between conductor sets **2404** are configured to electrically isolate conductor sets **2404** from each other. In shielded electrical cable **2402**, parallel portions **2408** of shielding films **2408** and insulated conductors **2406** are arranged in different planes.

[0080] In FIG. **16a**, shielded electrical cable **2502** includes a parallel portion **2508** wherein shielding films **2508** are spaced apart. Spacing apart shielding films **2508**, i.e., not having shielding films **2508** make direct electrical contact continuously along their seam, increases the strength of parallel portion **2508**. This is an advantage over shielded electrical cables wherein relatively thin and fragile shielding films may fracture or crack during manufacturing if forced to make direct electrical contact continuously along their seam. Spacing apart shielding films **2508** may permit crosstalk between adjacent conductor sets if effective means are not used to reduce the crosstalk potential. Generally, the electrical and magnetic fields must be contained to the general area of the conductor sets and not permitted to impinge on an adjacent conductor set. In the embodiment illustrated in FIG. **16a**, this is achieved by providing a low characteristic impedance between shielding films **2508**. This may be accomplished by spacing apart shielding films **2508** at close proximity. In one embodiment, shielding films **2508** are spaced apart by less than about 0.13 mm in at least one location of parallel portion **2508**. The resulting characteristic impedance between shielding films **2508** may be less than about 15 Ohms, and the resulting crosstalk between adjacent conductor sets may be less than about -25 dB. In one embodiment, parallel portion **2508** has a minimum thickness of less than about 0.13 mm. In one embodiment, shielding films **2508** are spaced apart by a separation medium. The separation medium may include conformable adhesive layer **2510**. In one embodiment, the separation medium has a dielectric constant of at least 1.5. A high dielectric constant decreases the characteristic impedance between shielding films **2508**, thereby decreasing the crosstalk (increasing the electrical isolation) between adjacent conductor sets. Shielding films **2508** may make direct electrical contact with each other in at least one location of parallel portion **2508**. Shielding films **2508** may be forced together in selective locations as suitable for the intended application such that conformable adhesive layer **2510** conforms around these locations. This can be done, e.g., with a patterned tool making intermittent pinch contact between shielding films **2508** in these locations. These locations may be patterned longitudinally or transversely. In one embodiment, the separation medium may be electrically conductive to enable direct electrical contact between shielding films **2508**.

[0081] In FIG. **16b**, shielded electrical cable **2602** includes a parallel portion **2608** including a longitudinal ground conductor **2612** disposed between shielding films **2608**. Ground conductor **2612** makes indirect electrical contact with both shielding films **2608**. Ground conductor **2612** has a low but non-zero impedance with respect to shielding films **2608**. In other embodiments, ground conductor **2612** may make direct or indirect electrical contact with at least one of the shielding films **2608** in at least one location of parallel portion **2608**. In one embodiment, shielded electrical cable **2602** includes a conformable adhesive layer **2610** disposed between shielding films **2608** and configured to provide controlled separation of at least one of shielding films **2608** and ground conductor **2612**. In one aspect, this means that conformable adhesive layer **2610** has a non-uniform thickness that allows ground

conductor **2612** to make direct or indirect electrical contact with at least one of shielding films **2608** in selective locations as suitable for the intended application. In one embodiment, ground conductor **2612** may include surface asperities or a deformable wire, such as, e.g., a stranded wire, to provide this controlled electrical contact between ground conductor **2612** and at least one of shielding films **2608**.

[0082] In FIG. **16c**, shielded electrical cable **2702** includes a parallel portion **2708** including a longitudinal ground conductor **2712** disposed between shielding films **2708**. Ground conductor **2712** makes direct electrical contact with both shielding films **2708**.

[0083] In FIG. **16d**, shielded electrical cable **2802** includes a parallel portion **2808** wherein shielding films **2808** make direct electrical contact with each other by any suitable means, such as, e.g., conductive element **2844**. Conductive element **2844** may include a conductive plated via or channel, a conductive filled via or channel, or a conductive adhesive, to name a few.

[0084] In FIG. **16e**, shielded electrical cable **2902** includes a parallel portion **2908** including an opening **2936** in at least one location of parallel portion **2908**. In other words, parallel portion **2908** is discontinuous. Opening **2936** may include a hole, a perforation, a slit, and any other suitable element. Opening **2936** provides at least some level of physical separation, which contributes to the electrical isolation performance of parallel portion **2908** and increases at least the lateral flexibility of shielded electrical cable **2902**. This separation may be discontinuous along the length of parallel portion **2908**, and may be discontinuous across the width of parallel portion **2908**.

[0085] In FIG. **16f**, shielded electrical cable **3002** includes a parallel portion **3008** wherein at least one of shielding films **3008** includes a break **3038** in at least one location of parallel portion **3008**. In other words, at least one of shielding films **3008** is discontinuous. Break **3038** may include a hole, a perforation, a slit, and any other suitable element. Break **3038** provides at least some level of physical separation, which contributes to the electrical isolation performance of parallel portion **3008** and increases at least the lateral flexibility of shielded electrical cable **3002**. This separation may be discontinuous or continuous along the length of parallel portion **3008**, and may be discontinuous across the width of parallel portion **3008**.

[0086] In FIG. **16g**, shielded electrical cable **3102** includes a parallel portion **3108** that is piecewise planar in a folded configuration. All other things being equal, a piecewise planar parallel portion has a greater actual width than a planar parallel portion having the same projected width. If the actual width of a parallel portion is much greater than the spacing between the shielding films, a low characteristic impedance results, which contributes to the electrical isolation performance of the parallel portion. In one embodiment, a characteristic impedance of less than 5 to 10 Ohms results in good electrical isolation. In one embodiment, parallel portion **3108** of shielded electrical cable **3102** has an actual width to minimum spacing ratio of at least 5. In one embodiment, parallel portion **3108** is pre-bent and thereby increases at least the lateral flexibility of shielded electrical cable **3102**. Parallel portion **3108** may be piecewise planar in any other suitable configuration.

[0087] Referring now to FIGS. **17a-17b**, another exemplary embodiment of a parallel portion of a shielded electrical cable according to an aspect of the present invention is illus-

trated. Shielded electrical cable **3202** includes two generally parallel shielding films **3208** include a parallel portion **3208"** wherein shielding films **3208** are substantially parallel. Shielding films **3208** include a non-conductive polymeric layer **3208b**, a conductive layer **3208a** disposed on non-conductive polymeric layer **3208b**, and a stop layer **3208d** disposed on conductive layer **3208a**. A conformable adhesive layer **3210** is disposed on stop layer **3208d**. Parallel portion **3208"** includes a longitudinal ground conductor **3212** disposed between shielding films **3208**. Ground conductor **3212** makes indirect electrical contact with conductive layers **3208a** of shielding films **3208**. This indirect electrical contact is enabled by a controlled separation of conductive layer **3208a** and ground conductor **3212** provided by stop layer **3208d**. In one embodiment, stop layer **3208d** is a non-conductive polymeric layer. As shown in FIGS. **17a-17b**, an external pressure (FIG. **17a**) is used to press conductive layers **3208a** together and force conformable adhesive layers **3210** to conform around ground conductor **3212** (FIG. **17b**). Because stop layer **3208d** does not conform at least under the same conditions, it prevents direct electrical contact between ground conductor **3212** and conductive layer **3208a** of shielding films **3208**. The thickness and dielectric properties of stop layer **3208d** may be selected to achieve a target characteristic impedance. In one embodiment, a characteristic impedance of less than 5 to 10 Ohms results in good electrical isolation.

[0088] FIG. **18** illustrates another exemplary embodiment of a shielded electrical cable according to an aspect of the present invention. Shielded electrical cable **3302** includes two generally parallel shielding films **3308** disposed around spaced apart conductor sets **3304**. Shielding films **3308** include parallel portions **3308"** wherein shielding films **3308** are substantially parallel. Parallel portions **3308"** are configured to be laterally bent at an angle α of at least 30° . This lateral flexibility of parallel portions **3308"** enables shielded electrical cable **3302** to be folded in any suitable configuration, such as, e.g., a configuration that can be used in a round cable (see, e.g., FIG. **10g**). In one embodiment, the lateral flexibility of parallel portions **3308"** is enabled by shielding films **3308** including two or more relatively thin individual layers. To warrant the integrity of these individual layers in particular under bending conditions, it is preferred that the bonds between them remain intact. In one embodiment, parallel portions **3308"** have a minimum thickness of less than about 0.13 mm, and the bond strength between individual layers is at least 17.86 g/mm (1 lbs/inch) after thermal exposures during processing or use.

[0089] In one aspect, it is beneficial to the electrical performance of a shielded electrical cable according to aspect of the present invention for the parallel portions to have approximately the same size and shape on both sides of a conductor set. Any dimensional changes or imbalances may produce imbalances in capacitance and inductance along the length of the parallel portion. This in turn may cause impedance differences along the length of the parallel portion and impedance imbalances between adjacent conductor sets. At least for these reasons, control of the spacing between the shielding films may be desired. In one embodiment, the shielding films on both sides of a conductor set are spaced apart within about 0.05 mm of each other.

[0090] In FIG. **19**, shielded electrical cable **3402** includes two conductor sets **3404**, each including two substantially parallel longitudinal insulated conductors **3406**, and two generally parallel shielding films **3408** disposed around conduc-

tor sets **3404**. Shielding films **3408** include parallel portions **3408"** wherein shielding films **3408** are substantially parallel. Parallel portions **3408"** positioned at or near an edge of shielded electrical cable **3402** are configured to electrically isolate conductor sets **3404** from the external environment. In shielded electrical cable **3402**, parallel portions **3408"** of shielding films **3408** and insulated conductors **3406** are arranged generally in a single plane.

[0091] In FIG. **20a**, shielded electrical cable **3502** includes a parallel portion **3508"** wherein shielding films **3508** are spaced apart. Parallel portion **3508"** is similar to parallel portion **2508"** described above and illustrated in FIG. **16a**. Whereas parallel portion **2508"** is positioned in between conductor sets, parallel portion **3508"** is positioned at or near an edge of shielded electrical cable **3502**.

[0092] In FIG. **20b**, shielded electrical cable **3602** includes a parallel portion **3608"** including a longitudinal ground conductor **3612** disposed between shielding films **3608**. Parallel portion **3608"** is similar to parallel portion **2608"** described above and illustrated in FIG. **16b**. Whereas parallel portion **2608"** is positioned in between conductor sets, parallel portion **3608"** is positioned at or near an edge of shielded electrical cable **3602**.

[0093] In FIG. **20c**, shielded electrical cable **3702** includes a parallel portion **3708"** including a longitudinal ground conductor **3712** disposed between shielding films **3708**. Parallel portion **3708"** is similar to parallel portion **2708"** described above and illustrated in FIG. **16c**. Whereas parallel portion **2708"** is positioned in between conductor sets, parallel portion **3708"** is positioned at or near an edge of shielded electrical cable **3702**.

[0094] In FIG. **20d**, shielded electrical cable **3802** includes a parallel portion **3808"** wherein shielding films **3808** make direct electrical contact with each other by any suitable means, such as, e.g., conductive element **3844**. Conductive element **3844** may include a conductive plated via or channel, a conductive filled via or channel, or a conductive adhesive, to name a few. Parallel portion **3808"** is similar to parallel portion **2808"** described above and illustrated in FIG. **16d**. Whereas parallel portion **2808"** is positioned in between conductor sets, parallel portion **3808"** is positioned at or near an edge of shielded electrical cable **3802**.

[0095] In FIG. **20e**, shielded electrical cable **3902** includes a parallel portion **3908"** that is piecewise planar in a folded configuration. Parallel portion **3908"** is similar to parallel portion **3108"** described above and illustrated in FIG. **16g**. Whereas parallel portion **3108"** is positioned in between conductor sets, parallel portion **3908"** is positioned at or near an edge of shielded electrical cable **3902**.

[0096] In FIG. **20f**, shielded electrical cable **4002** includes a parallel portion **4008"** that is piecewise planar in a curved configuration and positioned at or near an edge of shielded electrical cable **4002**.

[0097] A shielded electrical cable according to an aspect of the present invention may include at least one longitudinal ground conductor, an electrical article extending in substantially the same direction as the ground conductor, and two generally parallel shielding films disposed around the ground conductor and the electrical article. In this configuration, the shielding films and ground conductor are configured to electrically isolate the electrical article. The ground conductor may extend beyond at least one of the ends of the shielding films, e.g., for termination of the shielding films to any suitable individual contact element of any suitable termination

point, such as, e.g., a contact element on a printed circuit board or an electrical contact of an electrical connector. Beneficially, only a limited number of ground conductors is needed for a cable construction, and can, along with the shielding films, complete an electromagnetic enclosure of the electrical article. The electrical article may include at least one longitudinal conductor, at least one conductor set including one or more substantially parallel longitudinal insulated conductors, a flexible printed circuit, or any other suitable electrical article of which electrical isolation is desired. FIGS. 21a-21b illustrate two exemplary embodiments of such shielded electrical cable configuration.

[0098] In FIG. 21a, shielded electrical cable 4102 includes two spaced apart substantially parallel longitudinal ground conductors 4112, an electrical article 4140 positioned between and extending in substantially the same direction as ground conductors 4112, and two generally parallel shielding films 4108 disposed around ground conductors 4112 and electrical article 4140. Electrical article 4140 includes three conductor sets 4104. Each conductor set 4104 includes two substantially parallel longitudinal insulated conductors 4106. Ground conductors 4112 make indirect electrical contact with both shielding films 4108. Ground conductors 4112 have a low but non-zero impedance with respect to shielding films 4108. In other embodiments, ground conductors 4112 may make direct or indirect electrical contact with at least one of the shielding films 4108 in at least one location of shielding films 4108. In one embodiment, shielded electrical cable 4102 includes a conformable adhesive layer 4110 disposed between shielding films 4108 and bonding shielding films 4108 to each other on both sides of ground conductors 4112 and electrical article 4140. Conformable adhesive layer 4110 is configured to provide controlled separation of at least one of shielding films 4108 and ground conductors 4112. In one aspect, this means that conformable adhesive layer 4110 has a non-uniform thickness that allows ground conductors 4112 to make direct or indirect electrical contact with at least one of shielding films 4108 in selective locations as suitable for the intended application. In one embodiment, ground conductors 4112 may include surface asperities or a deformable wire, such as, e.g., a stranded wire, to provide this controlled electrical contact between ground conductors 4112 and at least one of shielding films 4108. In one embodiment, shielding films 4108 are spaced apart by a minimum spacing in at least one location of shielding films 4108, and ground conductors 4112 have a thickness that is greater than the minimum spacing. In one embodiment, shielding films 4108 have a thickness of less than about 0.025 mm.

[0099] In FIG. 21b, shielded electrical cable 4202 includes two spaced apart substantially parallel longitudinal ground conductors 4212, an electrical article 4240 positioned between and extending in substantially the same direction as ground conductors 4212, and two generally parallel shielding films 4208 disposed around ground conductors 4212 and electrical article 4240. Shielded electrical cable 4202 is similar to shielded electrical cable 4102 described above and illustrated in FIG. 21a. Whereas in shielded electrical cable 4102, electrical article 4140 includes three conductor sets 4104 each including two substantially parallel longitudinal insulated conductors 4106, in shielded electrical cable 4202, electrical article 4240 includes a flexible printed circuit including three conductor sets 4242.

[0100] FIG. 22 illustrates the far end crosstalk (FEXT) isolation between two adjacent conductor sets of a conven-

tional electrical cable wherein the conductor sets are completely isolated, i.e., have no common ground (Sample 1), and between two adjacent conductor sets of shielded electrical cable 2202 illustrated in FIG. 15a wherein shielding films 2208 are spaced apart by about 0.025 mm (Sample 2), both having a cable length of about 3 m. The test method for creating this data is well known in the art. The data was generated using an Agilent 8720ES 50 MHz-20 GHz S-Parameter Network Analyzer. It can be seen by comparing the far end crosstalk plots that the conventional electrical cable and shielded electrical cable 2202 provide a similar far end crosstalk performance. Specifically, it is generally accepted that a far end crosstalk of less than about -35 dB is suitable for most applications. It can be easily seen from FIG. 22 that for the configuration tested, both the conventional electrical cable and shielded electrical cable 2202 provide satisfactory electrical isolation performance. The satisfactory electrical isolation performance in combination with the increased strength of the parallel portion due to the ability to space apart the shielding films is an advantage of a shielded electrical cable according to an aspect of the present invention over conventional electrical cables.

[0101] In exemplary embodiments described above, the shielded electrical cable includes two generally parallel shielding films disposed around a conductor set or around a plurality of spaced apart conductor sets. In further embodiments, the shielded electrical cable may include a single shielding film. Advantages of a shielded electrical cable including a single shielding film, compared to a shielded electrical cable including two shielding films, include a decrease in its material cost and an increase in its mechanical flexibility, manufacturability, and ease of stripping and termination. A single shielding film may provide an acceptable level of electromagnetic interference (EMI) isolation and may reduce the proximity effect thereby decreasing signal attenuation. FIGS. 23-29d illustrate various exemplary embodiments of a shielded electrical cable according to aspects of the present invention including a single shielding film.

[0102] Referring now to FIG. 23, shielded electrical cable 4302 includes two spaced apart conductor sets 4304 and a single shielding film 4308. Each conductor set 4304 includes a single longitudinal insulated conductor 4306. Insulated conductors 4306 are arranged generally in a single plane and effectively in a coaxial or single ended cable arrangement. Shielding film 4308 includes parallel portions 4308" extending from both sides of each conductor set 4304. Parallel portions 4308" cooperatively define a generally planar shielding film. Shielding film 4308 further includes two cover portions 4308'" each partially covering a conductor set 4304. Each cover portion 4308'" includes a concentric portion 4308' substantially concentric with corresponding conductor 4306. Shielding film 4308 includes a conductive layer 4308a and a non-conductive polymeric layer 4308b. Conductive layer 4308a faces insulated conductors 4306. Shielded electrical cable 4302 further includes an optional non-conductive carrier film 4346. Carrier film 4346 includes parallel portions 4346" extending from both sides of each conductor set 4304 and disposed opposite parallel portions 4308" of shielding film 4308. Carrier film 4346 further includes two cover portions 4346'" each partially covering a conductor set 4304 opposite cover portion 4308' of shielding film 4308. Each cover portion 4346'" includes a concentric portion 4346' substantially concentric with corresponding conductor 4306.

Carrier film **4346** may include any suitable polymeric material, including but not limited to polyester, polyimide, polyamide-imide, polytetrafluoroethylene, polypropylene, polyethylene, polyphenylene sulfide, polyethylene naphthalate, polycarbonate, silicone rubber, ethylene propylene diene rubber, polyurethane, acrylates, silicones, natural rubber, epoxies, and synthetic rubber adhesive. Carrier film **4346** may include one or more additives and/or fillers to provide properties suitable for the intended application. Carrier film **4346** may be used to complete physical coverage of conductor sets **4304** and add to the mechanical stability of shielded electrical cable **4302**.

[0103] Referring to FIG. 24, shielded electrical cable **4402** is similar to shielded electrical cable **4302** described above and illustrated in FIG. 23. Whereas shielded electrical cable **4302** includes conductor sets **4304** each including a single longitudinal insulated conductor **4306**, shielded electrical cable **4402** includes conductor sets **4404** including two substantially parallel longitudinal insulated conductors **4406**. Insulated conductors **4406** are arranged generally in a single plane and effectively in a twinaxial or differential pair cable arrangement.

[0104] Referring to FIG. 25, shielded electrical cable **4502** is similar to shielded electrical cable **4402** described above and illustrated in FIG. 24. Whereas shielded electrical cable **4402** has individually insulated conductors **4406**, shielded electrical cable **4502** has jointly insulated conductors **4506**.

[0105] In one aspect, as can be seen in FIGS. 23-25, the shielding film is re-entrant between adjacent conductor sets. In other words, the shielding film includes a parallel portion that is disposed between adjacent conductor sets. This parallel portion is configured to electrically isolate the adjacent conductor sets from each other. In one aspect, the parallel portion eliminates the need for a ground conductor to be positioned between adjacent conductor sets, which simplifies the cable construction and increases the cable flexibility, among other benefits. In one embodiment, the parallel portion is positioned at a depth d (FIG. 23) that is greater than about one third of the diameter of the insulated conductors. In another embodiment, the parallel portion is positioned at a depth d that is greater than about one half of the diameter of the insulated conductors. In one aspect, depending on the spacing between adjacent conductor sets, the transmission distance, and the signaling scheme (differential versus single-ended), this re-entrant configuration of the shielding film more than adequately electrically isolates the conductor sets from each other.

[0106] The conductor sets and shielding film may be cooperatively configured in an impedance controlling relationship. In one aspect, this means that the partial coverage of the conductor sets by the shielding film is accomplished with a desired consistency in geometry along the length of the shielded electrical cable such as to provide an acceptable impedance variation as suitable for the intended application. In one embodiment, this impedance variation is less than 5 Ohms and preferably less than 3 Ohms along a representative cable length, such as, e.g., 1 m. In another aspect, if the insulated conductors are arranged effectively in a twinaxial or differential pair cable arrangement, this means that the partial coverage of the conductor sets by the shielding film is accomplished with a desired consistency in geometry between the insulated conductors of a pair such as to provide an acceptable impedance variation as suitable for the intended application. In one embodiment, this impedance variation is less than 2

Ohms and preferably less than 0.5 Ohms along a representative cable length, such as, e.g., 1 m.

[0107] FIGS. 26a-26d illustrate various exemplary embodiments of a shielded electrical cable according to aspects of the present invention. FIGS. 26a-26d are specifically intended to illustrate various examples of partial coverage of the conductor set by the shielding film. The amount of coverage by the shielding film varies between the embodiments. In the embodiment illustrated in FIG. 26a, the conductor set has the most coverage. In the embodiment illustrated in FIG. 26d, the conductor set has the least coverage. In the embodiments illustrated in FIGS. 26a and 26b, more than half of the periphery of the conductor set is covered by the shielding film. In the embodiments illustrated in FIGS. 26c and 26d, less than half of the periphery of the conductor set is covered by the shielding film. A greater amount of coverage provides better electromagnetic interference (EMI) isolation and reduced signal attenuation (resulting from a reduction in the proximity effect).

[0108] Referring to FIG. 26a, shielded electrical cable **4602** includes a conductor set **4604** and a shielding film **4608**. Conductor set **4604** includes two longitudinal insulated conductors **4606**. Shielding film **4608** includes parallel portions **4608''** extending from both sides of conductor set **4604**. Parallel portions **4608''** cooperatively define a generally planar shielding film. Shielding film **4608** further includes a cover portion **4608'''** partially covering conductor set **4604**. Cover portion **4608'** includes concentric portions **4608'** substantially concentric with corresponding conductor **4306**. Shielded electrical cable **4602** further includes an optional non-conductive carrier film **4646**. Carrier film **4646** includes parallel portions **4646''** extending from both sides of conductor set **4604** and disposed opposite parallel portions **4608''** of shielding film **4608**. Carrier film **4646** further includes a cover portion **4646'''** partially covering conductor set **4604** opposite cover portion **4608'** of shielding film **4608**. Cover portion **4608'''** of shielding film **4608** covers the top side and the entire left and right sides of conductor set **4604**. Cover portion **4646'''** of carrier film **4646** covers the bottom side of conductor set **4604**, completing the enclosure of conductor set **4604**. In this embodiment, parallel portions **4646''** and cover portion **4646'''** of carrier film **4646** are substantially coplanar.

[0109] Referring to FIG. 26b, shielded electrical cable **4702** is similar to shielded electrical cable **4602** described above and illustrated in FIG. 26a. However, in shielded electrical cable **4702**, cover portion **4708'** of shielding film **4708** covers the top side and more than half of the left and right sides of conductor set **4704**. Cover portion **4746'''** of carrier film **4746** covers the bottom side and the remainder (less than half) of the left and right sides of conductor set **4704**, completing the enclosure of conductor set **4704**. Cover portion **4746'''** of carrier film **4746** includes concentric portions **4746'** substantially concentric with corresponding conductor **4706**.

[0110] Referring to FIG. 26c, shielded electrical cable **4802** is similar to shielded electrical cable **4602** described above and illustrated in FIG. 26a. However, in shielded electrical cable **4802**, cover portion **4808'** of shielding film **4808** covers the bottom side and less than half of the left and right sides of conductor set **4804**. Cover portion **4846'''** of carrier film **4846** covers the top side and the remainder (more than half) of the left and right sides of conductor set **4804**, completing the enclosure of conductor set **4804**.

[0111] Referring to FIG. 26d, shielded electrical cable **4902** is similar to shielded electrical cable **4602** described

above and illustrated in FIG. 26a. However, in shielded electrical cable 4902, cover portion 4908''' of shielding film 4908 covers the bottom side of conductor set 4904. Cover portion 4946''' of carrier film 4946 covers the top side and the entire left and right sides of conductor set 4904, completing the enclosure of conductor set 4904. In this embodiment, parallel portions 4908'' and cover portion 4908''' of shielding film 4908 are substantially coplanar.

[0112] Similar to embodiments of the shielded electrical cable including two generally parallel shielding films disposed around a conductor set or around a plurality of spaced apart conductor sets, embodiments of the shielded electrical cable including a single shielding film may include at least one longitudinal ground conductor. In one aspect, this ground conductor facilitates electrical contact of the shielding film to any suitable individual contact element of any suitable termination point, such as, e.g., a contact element on a printed circuit board or an electrical contact of an electrical connector. The ground conductor may extend beyond at least one of the ends of the shielding film to facilitate this electrical contact. The ground conductor may make direct or indirect electrical contact with the shielding film in at least one location along its length, and may be placed in suitable locations of the shielded electrical cable.

[0113] FIG. 27 is specifically intended to illustrate exemplary locations of a ground conductor in a shielded electrical cable according to an aspect of the present invention. Shielded electrical cable 5002 is similar to shielded electrical cable 4402 described above and illustrated in FIG. 24, but includes ground conductors 5012 in various exemplary locations. Ground conductors 5012 extend in substantially the same direction as insulated conductors 5006 of conductor sets 5004 and are positioned between shielding film 5008 and carrier film 5046. One ground conductor 5012 is included in a parallel portion 5008'' of shielding film 5008 and three ground conductors 5012 are included in a conductor set 5004. One of these three ground conductors 5012 is positioned between insulated conductors 5006 and shielding film 5008 and two of these three ground conductors 5012 and insulated conductors 5006 are arranged generally in a single plane.

[0114] FIGS. 28a-28d illustrate various exemplary embodiments of a shielded electrical cable according to aspects of the present invention. FIGS. 28a-28d are specifically intended to illustrate various examples of partial coverage of the conductor set by the shielding film without the presence of a carrier film. The amount of coverage by the shielding film varies between the embodiments. In the embodiment illustrated in FIG. 28a, the conductor set has the most coverage. In the embodiment illustrated in FIG. 28d, the conductor set has the least coverage. In the embodiments illustrated in FIGS. 28a and 28b, more than half of the periphery of the conductor set is covered by the shielding film. In the embodiment illustrated in FIG. 28c, about half of the periphery of the conductor set is covered by the shielding film. In the embodiment illustrated in FIG. 28d, less than half of the periphery of the conductor set is covered by the shielding film. A greater amount of coverage provides better electromagnetic interference (EMI) isolation and reduced signal attenuation (resulting from a reduction in the proximity effect). Although in these embodiments, a conductor set includes two substantially parallel longitudinal insulated conductors, in other embodiments, a conductor set may include one or more than two substantially parallel longitudinal insulated conductors.

[0115] Referring to FIG. 28a, shielded electrical cable 5102 includes a conductor set 5104 and a shielding film 5108. Conductor set 5104 includes two longitudinal insulated conductors 5106. Shielding film 5108 includes parallel portions 5108'' extending from both sides of conductor set 5104. Parallel portions 5108'' cooperatively define a generally planar shielding film. Shielding film 5108 further includes a cover portion 5108''' partially covering conductor set 5104. Cover portion 5108' includes concentric portions 5108' substantially concentric with corresponding conductor 5106. Cover portion 5108''' of shielding film 5108 covers the bottom side and the entire left and right sides of conductor set 5104.

[0116] Referring to FIG. 28b, shielded electrical cable 5202 is similar to shielded electrical cable 5102 described above and illustrated in FIG. 28a. However, in shielded electrical cable 5202, cover portion 5208''' of shielding film 5208 covers the bottom side and more than half of the left and right sides of conductor set 5204.

[0117] Referring to FIG. 28c, shielded electrical cable 5302 is similar to shielded electrical cable 5102 described above and illustrated in FIG. 28a. However, in shielded electrical cable 5302, cover portion 5308''' of shielding film 5308 covers the bottom side and about half of the left and right sides of conductor set 5304.

[0118] Referring to FIG. 28d, shielded electrical cable 5402 is similar to shielded electrical cable 5102 described above and illustrated in FIG. 28a. However, in shielded electrical cable 5402, cover portion 5408''' of shielding film 5408 covers the bottom side and less than half of the left and right sides of conductor set 5404.

[0119] As an alternative to a carrier film, for example, shielded electrical cables according to aspects of the present invention may include an optional non-conductive support. This support may be used to complete physical coverage of a conductor set and add to the mechanical stability of the shielded electrical cable. FIGS. 29a-29d illustrate various exemplary embodiments of a shielded electrical cable according to aspects of the present invention including a non-conductive support. Although in these embodiments, a non-conductive support is used with a conductor set that includes two substantially parallel longitudinal insulated conductors, in other embodiments, a non-conductive support may be used with a conductor set that includes one or more than two substantially parallel longitudinal insulated conductors, or with a ground conductor. The support may include any suitable polymeric material, including but not limited to polyester, polyimide, polyamide-imide, polytetrafluoroethylene, polypropylene, polyethylene, polyphenylene sulfide, polyethylene naphthalate, polycarbonate, silicone rubber, ethylene propylene diene rubber, polyurethane, acrylates, silicones, natural rubber, epoxies, and synthetic rubber adhesive. The support may include one or more additives and/or fillers to provide properties suitable for the intended application.

[0120] Referring to FIG. 29a, shielded electrical cable 5502 is similar to shielded electrical cable 5102 described above and illustrated in FIG. 28a, but further includes a non-conductive support 5548 partially covering conductor set 5504 opposite cover portion 5508''' of shielding film 5508. Support 5548 covers essentially the entire top side of conductor set 5504, essentially fully enclosing insulated conductors 5506. Support 5548 includes a generally planar top surface 5548a. Top surface 5548a and parallel portions 5508'' are substantially coplanar.

[0121] Referring to FIG. 29*b*, shielded electrical cable 5602 is similar to shielded electrical cable 5202 described above and illustrated in FIG. 28*b*, but further includes a non-conductive support 5648 partially covering conductor set 5604 opposite cover portion 5608''' of shielding film 5608. Support 5648 only partially covers the top side of conductor set 5604, leaving insulated conductors 5606 partially exposed.

[0122] Referring to FIG. 29*c*, shielded electrical cable 5702 is similar to shielded electrical cable 5302 described above and illustrated in FIG. 28*c*, but further includes a non-conductive support 5748 partially covering conductor set 5704 opposite cover portion 5708''' of shielding film 5708. Support 5748 covers essentially the entire top side of conductor set 5704, essentially fully enclosing insulated conductors 5706. At least a portion of support 5748 is substantially concentric with insulated conductors 5706. A portion of support 5748 is disposed between insulated conductors 5706 and shielding film 5708.

[0123] Referring to FIG. 29*d*, shielded electrical cable 5802 is similar to shielded electrical cable 5402 described above and illustrated in FIG. 28*d*, but further includes a non-conductive support 5848 partially covering conductor set 5804 opposite cover portion 5808''' of shielding film 5808. Support 5848 only partially covers the top side of conductor set 5804, leaving insulated conductors 5806 partially exposed. A portion of support 5848 is disposed between insulated conductors 5806 and shielding film 5808.

[0124] The following items are exemplary embodiments of a shielded electrical cable according to aspects of the present invention.

[0125] Item 1 is a shielded electrical cable comprising a conductor set including one or more substantially parallel longitudinal insulated conductors; and a shielding film including a cover portion partially covering the conductor set, and parallel portions extending from both sides of the conductor set.

[0126] Item 2 is the shielded electrical cable of item 1, wherein the parallel portions cooperatively define a generally planar shielding film.

[0127] Item 3 is the shielded electrical cable of item 1, wherein the cover portion includes a concentric portion substantially concentric with at least one of the conductors.

[0128] Item 4 is the shielded electrical cable of item 1 further comprising a non-conductive carrier film including a cover portion partially covering the conductor set opposite the cover portion of the shielding film, and parallel portions extending from both sides of the conductor set and disposed opposite the parallel portions of the shielding film.

[0129] Item 5 is the shielded electrical cable of item 4, wherein the cover portion of the carrier film includes a concentric portion substantially concentric with at least one of the conductors.

[0130] Item 6 is the shielded electrical cable of item 1 further comprising at least one longitudinal ground conductor extending in substantially the same direction as the one or more insulated conductors.

[0131] Item 7 is the shielded electrical cable of item 6, wherein the ground conductor makes direct electrical contact with the shielding film in at least one location along its length.

[0132] Item 8 is the shielded electrical cable of item 6, wherein the ground conductor makes indirect electrical contact with the shielding film in at least one location along its length.

[0133] Item 9 is the shielded electrical cable of item 6, wherein the ground conductor extends beyond at least one of the ends of the shielding film.

[0134] Item 10 is the shielded electrical cable of item 6, wherein the ground conductor is included in the conductor set.

[0135] Item 11 is the shielded electrical cable of item 6, wherein the ground conductor is included in the parallel portion.

[0136] Item 12 is the shielded electrical cable of item 1, wherein the conductor set and shielding film are cooperatively configured in an impedance controlling relationship.

[0137] Item 13 is the shielded electrical cable of item 1 further comprising a non-conductive support partially covering the conductor set opposite the cover portion of the shielding film.

[0138] Item 14 is the shielded electrical cable of item 13, wherein the support includes a concentric portion substantially concentric with at least one of the conductors.

[0139] Item 15 is a shielded electrical cable comprising a plurality of spaced apart conductor sets arranged generally in a single plane, each conductor set including one or more substantially parallel longitudinal insulated conductors; and a shielding film including a plurality of cover portions partially covering the conductor sets, and a parallel portion disposed between adjacent conductor sets and configured to electrically isolate the adjacent conductor sets from each other.

[0140] Item 16 is the shielded electrical cable of item 15, wherein the parallel portion is positioned at a depth that is greater than about one third of the diameter of the insulated conductors.

[0141] Item 17 is the shielded electrical cable of item 15, wherein the parallel portion is positioned at a depth that is greater than about one half of the diameter of the insulated conductors.

[0142] Although specific embodiments have been illustrated and described herein for purposes of description of the preferred embodiment, it will be appreciated by those of ordinary skill in the art that a wide variety of alternate and/or equivalent implementations calculated to achieve the same purposes may be substituted for the specific embodiments shown and described without departing from the scope of the present invention. Those with skill in the mechanical, electro-mechanical, and electrical arts will readily appreciate that the present invention may be implemented in a very wide variety of embodiments. This application is intended to cover any adaptations or variations of the preferred embodiments discussed herein. Therefore, it is manifestly intended that this invention be limited only by the claims and the equivalents thereof.

1. A shielded electrical cable comprising:

- a conductor set including one or more substantially parallel longitudinal insulated conductors;
- a shielding film including a cover portion partially covering the conductor set, and parallel portions extending from both sides of the conductor set; and
- a non-conductive support partially covering the conductor set opposite the cover portion of the shielding film, leaving the conductor set partially exposed.

2. The shielded electrical cable of claim 1, wherein the parallel portions cooperatively define a generally planar shielding film.

3. The shielded electrical cable of claim 1, wherein the cover portion includes a concentric portion substantially concentric with at least one of the conductors.

4. The shielded electrical cable of claim 1, wherein a portion of the non-conductive support is disposed between the one or more substantially parallel longitudinal insulated conductors and the shielding film.

5. The shielded electrical cable of claim 1 further comprising at least one longitudinal ground conductor extending in substantially the same direction as the one or more insulated conductors.

6. The shielded electrical cable of claim 5, wherein the ground conductor extends beyond at least one of the ends of the shielding film.

7. The shielded electrical cable of claim 1, wherein the conductor set and shielding film are cooperatively configured in an impedance controlling relationship.

8. The shielded electrical cable of claim 1 having an impedance variation along a length of about 1 meter that is less than about 5.

9. A shielded electrical cable comprising:

a plurality of spaced apart conductor sets arranged generally in a single plane, each conductor set including one or more substantially parallel longitudinal insulated conductors; and

a shielding film including a plurality of cover portions partially covering the conductor sets, and a parallel portion disposed between adjacent conductor sets and configured to electrically isolate the adjacent conductor sets from each other, wherein the parallel portion is positioned at a depth that is greater than about one third of the diameter of the insulated conductors.

10. The shielded electrical cable of claim 9, wherein the parallel portion is positioned at a depth that is greater than about one half of the diameter of the insulated conductors.

* * * * *