

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
22 March 2007 (22.03.2007)

PCT

(10) International Publication Number
WO 2007/032827 A1

(51) International Patent Classification:

B05B 12/08 (2006.01) **B05B 12/14** (2006.01)
B05B 9/04 (2006.01)

(21) International Application Number:

PCT/US2006/030176

(22) International Filing Date:

3 August 2006 (03.08.2006)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

11/225,723 13 September 2005 (13.09.2005) US

(71) Applicant (for all designated States except US): **ILLINOIS TOOL WORKS INC.** [US/US]; 3600 West Lake Avenue, Glenview, IL 60026 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SMITH, Alan, A.** [GB/GB]; 13 The Crescent, Burntwood, Staffordshire WS7 2PA (GB). **WOOD, Nigel, C.** [GB/GB]; 55 Hunslett Road, Burntwood, Staffordshire WS7 9LA (GB). **THOMAS, Michael, A.** [US/US]; 3600 West Lake Avenue, Chicago, IL 60026 (US).(74) Agent: **HAUPTMAN, Benjamin, J.**; LOWE HAUPTMAN & BERNER, LLP, 1700 DIAGONAL RD., Suite 300, Alexandria, VA 22314 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PAINT CIRCULATING SYSTEM AND METHOD



WO 2007/032827 A1

(57) Abstract: A paint circulating system is suitable for providing paint to applicators in a product finishing facility. The system includes a pump (22) for pumping paint around the system and a back-pressure regulator (BPR) (25), which substantially eliminates pressure fluctuations of paint in the system upstream of the BPR (25). Control means (26) are provided for controlling the pump (22) and the BPR (25) to operate in one of a flow mode, wherein a required flow rate of paint around the system is maintained, and a pressure mode, wherein a pressure of paint between the pump (22) and the BPR (25) is maintained. The paint circulating method includes switching operation of the pump and the BPR between the flow mode and the pressure mode.

PAINT CIRCULATING SYSTEM AND METHOD

The present invention relates to a paint circulating system and method, of a type suitable for use with automated spray finishing processes.

5

BACKGROUND OF THE INVENTION

Traditional paint spray systems, of the type employed in car manufacturing for example, usually consist of several separate paint lines, each providing a different coloured paint to a spray booth for distribution to a number of user points (e.g. spray applicators). In general, only one colour is sprayed or in use at any one time, so only one line is actively employed whilst the rest remain ready for use.

When a system is not in use because the paint is not being sprayed, it is usual to maintain the spraying pressure and paint velocity in the paint line, by pumping paint from a paint tank around a circuit and back to the tank. This is done for two reasons: firstly, because the liquid paint must be kept moving, otherwise pigmentation may start to settle out in the paint lines; secondly, because the lines must be primed to the required pressure before spraying commences. However, maintaining the lines at pressure is wasteful of energy.

20 To ensure that the paint is at the required pressure for spraying, a Back Pressure Regulator (BPR) is used in combination with the paint pump to regulate and maintain the required fluid pressure and flow at the spray booth. In conventional systems, the BPR is adjusted manually and uses a coil spring acting on a diaphragm to vary the width of a flow passage. This helps to maintain the paint pressure upstream of the BPR by controlling the 25 fluid flow rate returning to the paint tank. Also, in many systems (such as those employing certain types of turbine or lobe pumps) the pump will be set to operate at a fixed pressure and flow rate and the BPR used to maintain the required system pressure. In this type of system, the BPR controls system pressure by adjusting flow rate to

compensate for variations in the amount of fluid used at the spray booth. Thus, each line is usually operated in the condition required for spraying, whether the paint is being used or merely circulated. This is extremely inefficient and results a large waste of energy.

For example, a system operating 24 hours a day may only be required to spray each

5 individual colour, for, say, 1 hour a day. Each pump would be operated at the pressure and flow rate required to meet the system requirement for 24 hours a day even though the paint is not required to operate at the full system pressure and flow rate for 23 hours of the day.

10 In addition, a pump that is required to provide a higher flow rate and pressure for a longer period of time will suffer a higher rate of wear, requiring maintenance in a much shorter period of time than one that is used more sparingly.

15 It is an object of the present invention to provide a paint circulation system, which alleviates the aforementioned problems.

SUMMARY OF THE INVENTION

The paint circulating system according to the invention comprises a pump for pumping paint around the system, and a back-pressure regulator (BPR) to substantially eliminate

20 pressure fluctuations of paint upstream of the BPR. Control means control the pump and the BPR to operate in one of a flow mode, wherein a required flow rate of paint around the system is maintained, and a pressure mode, wherein a pressure of paint between the pump and the BPR is maintained.

25 In embodiments of the invention, in the flow mode, the BPR is configured to be deactivated so as to allow paint to flow without varying the flow rate in response to pressure fluctuations. The BPR is preferably an automated type, whereby activation means such as

compressed air or a hydraulic fluid is provided to activate and/or de-activate the BPR. The BPR may comprise a diaphragm that is acted upon by a spring or by fluid pressure on one side, and by the paint pressure on the other side. In the flow mode, the control means may be configured to control the pump so as to pump paint at a fixed flow rate. The fixed flow 5 rate is preferably a low flow rate, at or just above a minimum flow rate required for the paint.

It is an advantage that the system is able to place the BPR and pump into the flow mode when pressurised paint is not required at the spray booth. In this flow mode there is no need 10 to maintain a high paint pressure in the lines, and the pump can be operated at a steady, low flow rate to reduce energy consumption and wear.

In embodiments of the invention, when in the pressure mode, the BPR is configured to be activated so as to respond to variations in the paint pressure to maintain a substantially 15 constant pressure upstream of the BPR. In the pressure mode, the pump is preferably configured to deliver paint at a predetermined pressure. The pump may be a variable speed, or variable capacity pump responsive to a control signal to maintain the predetermined pressure. A pressure sensor may be provided at the pump outlet, or other suitable position in the system, to provide a pressure signal as a basis for the control signal. The control 20 means may be arranged to receive the pressure signal and to provide the control signal to the pump for maintaining the predetermined pressure.

It is an advantage that, when paint is required at the spray booth, the system can be placed into the pressure mode by activating (i.e. turning on) the BPR and operating the pump to 25 deliver paint at a high pressure, thereby ensuring that the paint is delivered to the spray booth at the required flow rate and pressure.

In embodiments of the invention, the controller may be operable to switch the system between the flow mode and the pressure mode in response to a demand signal. The demand signal may be provided from a plant scheduling or 'job queue' data processing apparatus.

5 In one embodiment of the invention, the controller comprises a control card for mounting in a programmable controller or computer device. The control card is preferably provided with a plurality of input and output terminals for receiving signals from sensors in the system and for providing control signals to the BPR and the pump. The control card may be provided with a data link to a graphics system for set-up and monitoring purposes.

10

The control card may include a plurality of channels for controlling a plurality of paint circulating systems, each providing paint to a spray booth. Each of the plurality of paint circulating systems may provide a different colour of paint to the spray booth.

15 It is an advantage that the system can operate in a manner that will allow the "job queue" data to control circulating system operating parameters. "Job queue" data is defined as the data collected by software that monitors the position of parts throughout an automotive OEM, Tier 1 or industrial plant once the parts have been loaded on a conveyor system. The job queue data may be used to provide demand signals to the colour valves to turn on
20 and turn off the supply of paint to the applicators in the spray booth. In the same manner, with the system of the present invention, the job queue data can now be used to provide demand signals that automatically pressurize or de-pressurize the circulating system, depending on the needs at the applicator. This ability provides great savings with regard to paint wear (shear) energy usage and general pump component wear.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Particular embodiments of the invention are illustrated in the accompanying drawings wherein:-

Figure 1 is a schematic representation of a known paint circulation system;
5 Figure 2 is schematic representation of a paint circulation system according to the present invention; and

Figure 3 is schematic representation of a controller for use in the paint circulation system of Figure 2.

10 DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Figure 1, a paint circulation system 10 includes a paint tank 11 containing a reservoir of liquid paint. A pump 12 is operable to supply paint from the paint tank 11, optionally through a paint filter 13, to a spray booth 14. The spray booth 14 typically includes one or more applicators 16. For example these may be spray nozzles manipulated 15 by robot arms. Any unused paint flows past the spray booth and is returned to the paint tank 11 via a BPR 15.

In this set-up, the BPR 15 is employed to control the upstream pressure in the system at the desired level, typically 5 to 10 bar when the paint is in use. The BPR 15 typically includes 20 a diaphragm, one side of which is acted upon by a coiled spring. The pressure of paint entering the BPR 15 urges the diaphragm against the spring force to open up a passage for paint. Any reduction in paint pressure results in the diaphragm moving under the spring force, tending to close the passage. This acts as a restriction to the flow of paint, which means that a greater pressure drop occurs across the BPR 15 so that the upstream pressure is 25 maintained. The spring force acting on the diaphragm is pre-set so that the BPR 15 acts to maintain a set upstream pressure.

The known circulating system of Figure 1 is based on pump flow rates being set to provide the maximum flow demand from the paint take-offs (i.e. applicators 16), assuming all are in use at the same time. As paint line pressure drops due to paint usage, the BPR 15 closes to reduce the fluid flow returning to the paint tank 11 thus maintaining the desired line 5 pressure.

Referring to Figure 2, there is shown a system 20 according to the present invention, wherein equivalent components to those shown in Figure 1 have the same reference numeral. In this case an electric variable speed pump 22, referred to hereafter as a smart 10 pump, pumps the paint from the paint tank 11 to the spray booth 14. Although the smart pump described herein is an electric pump, it will be appreciated by those of skill in the art that alternative pumps may be used, for example air driven or hydraulically driven pumps. The smart pump 22 includes a pressure sensor 24. Paint not used in the spray booth 14 is circulated back to the paint tank 11 via an automatically controlled BPR 25, referred to 15 hereafter as a smart BPR. The smart BPR is of a type that can be activated and de-activated by way of a suitable control mechanism, for example compressed air or hydraulic fluid. An example of such a regulator is described in the applicants' concurrently filed United Kingdom patent application entitled "Back Pressure Regulator", the contents of which are hereby incorporated by reference. The smart pump 22 and the smart BPR 25 are controlled 20 from a controller 26. A signal from the pressure sensor 24 is provided as an input to the controller 26. The controller 26 may be a PLC or other suitable programmable device. In an exemplary embodiment, the controller comprises a smart card, as will be described in more detail below.

25 The controller 26 is configured to control the smart pump 22 and the smart BPR 25 so that these will operate in either a flow mode or a pressure mode. The mode may be determined from job queue data.

When paint is needed at the applicators 16 (as per job queue data), the system 20 will be operated in the pressure mode. The controller 26 will issue a command signal that will cause the smart BPR to be activated so that it will operate to maintain the upstream pressure

5 according to a predetermined set pressure. The user will also have pre-set the desired system pressure into a memory of the controller 26, for example via a laptop or PC input during initial start up. The controller 26 is programmed to control the pump speed so that the pressure will be maintained, by means of a suitable control loop. The pressure sensor 24 transmits the actual pressure in the paint line to the controller 26, which reacts by using the

10 control loop to output a signal that controls the speed of the smart pump 22. For example if the paint pressure drops in the line below the set pressure due to usage at the applicators 16, the pump 22 will speed up in order to maintain pressure. Note: The smart BPR 25 will initially dynamically reduce the amount of fluid returning to the paint tank 11 in order to maintain the set pressure. The smart pump 22 only speeds up once the BPR 25 can no

15 longer maintain the system pressure.

When material is not in demand (as per job queue data) the system 20 will be operated in flow mode. The user will have input the minimum flow rate required to meet the desired minimum paint velocity as recommended by material supplier and the controller will

20 control the smart pump 22 to operate at the speed required to provide this minimum flow rate. In addition the controller 26 will issue a command to de-activate the smart BPR 25. The smart BPR 25 will no longer operate to maintain the upstream pressure, so that the only system back pressure will be due to the pipework frictional resistance. Energy usage will now be at a minimum.

25

Referring to Figure 3, more detail is shown of an exemplary controller 26 for controlling the smart pump 22 and smart BPR 25 of the system 20 of Figure 2. This controller 26 includes

a smart card 30. The smart card 30 typically comprises one or more printed circuit boards (PCBs) housed in a plastic carrier and mountable to a DIN rail in a purpose built or an existing control panel. The smart card 30 contains circuitry that includes a programmable memory and a processor. Alternatively, the smart card may include an interface for
5 communicating with an external processor, for example a PLC or a computer. The smart card 30 may include a plurality (e.g. 8) channels, each channel on the card being used to control one of a number of paint lines, each of which may provide a different colour, feeding the spray booth. Each channel on the smart card 30 includes a number of input/output terminals. These include:

10

- A digital input 41 for receiving a system mode signal
- An input 42 for receiving a signal (e.g. 4-20mA) from the pressure sensor 24
- An output 43 for providing a signal (e.g. 4-20mA) corresponding to a frequency to an AC frequency inverter 32 for controlling the speed of the
15 smart pump 22
- An output 44 (e.g. capable of driving 24v at 50mA) for controlling the switching of a valve 34 for connecting/disconnecting a supply of compressed air 36 to the smart BPR 25.

20

In addition, the smart card 30 is provided with a serial communications link 45. This is used as a data link to a computer 38 (e.g. a PC or a lap-top) that includes a graphics system for use in setting up the smart card, and for monitoring, data-logging and display of system parameters. The computer 38 may also receive data via one or more inputs 47 relating to other operating parameters of the system, for example differential pressures across the paint
25 filter 13, or level indicators on the paint tank 11. The smart card 30 may also be provided with a further data link 46 to another, similar smart card, so that a plurality of smart cards may be cascaded in a single control system.

In use, set point values are inputted to the smart card 30 at initial start up via the communications link 45 from the laptop or PC 38. Job queue data from the software that monitors the position of parts being conveyed through the plant reports which paint system

5 (i.e. which colour) needs to be in readiness for production, this data will be received by the smart card 30 to control the smart pump 22 and smart BPR 25 accordingly. The job queue data is transmitted to the smart card 30 by CCR LAN to the monitoring PC 38 or by digital input 41.

10 The memory on the smart card 30 includes a programmed control algorithm that defines the control loop for the operation of the smart pump 22 in response to the sensed pressure from the pressure sensor 24, when the system is operating in pressure mode.

Sequence of Operation:

15 **Material is not in use (Job Queue load data shows no immediate need for paint)**

- Smart pump 22 operates in flow mode. A preset frequency setting is equal to the low flow rate required to maintain the specified minimum paint velocity.

20

- The smart BPR 25 is fully unloaded (de-activated).

25

- The system operates at the lowest recommended flow rate with the only pressure being that required to overcome the paint line pressure loss. Therefore paint shear, energy usage and pump wear are at a minimum.

Material will be needed shortly (before color will be required at the applicators).

Information is automatically provided by the job queue load data.

- The smart BPR 25 is activated to provide the pre-set system pressure.

5

- The smart pump 22 is switched to pressure mode. The pressure setting is preset and the controller 26 will operate the smart pump 22 in accordance with the control loop according to the pressure senses at the pressure sensor 24.

10

- If the system pressure drops due to demand at the applicators 16 the BPR 25 will dynamically close in order to maintain pressure. If the BPR 25 can no longer maintain system pressure the smart pump 22 will automatically speed up, thus maintaining the pressure at the set point.

15

- The system will continue to operate in this mode until the job queue data shows that the paint material is no longer needed.

Material is no longer needed (after color is no longer needed at the spraybooth)

20

- The smart pump 22 is switched to flow mode. The preset frequency setting is equal to flow rate required to maintain minimum paint velocity in the line.
- The smart BPR is fully unloaded (de-activated).

25

It will be recognised that the in the pressure mode, the control of the paint pressure at the spray booth results from a combination of the operation of the smart pump 22 and the smart BPR 25. Table 1 shows an example of how the paint flow rates provided by the smart

pump 22 and through the smart BPR 25 might change as different amounts of paint are taken out through the applicators 16. In this example there are five applicators, designated A1, A2, A3, A4 and A5. Four different rates of paint usage are shown.

- 5 In condition 1, the system has been switched into the pressure mode, but there is not yet any paint being taken out through the applicators. The smart pump provides a flow rate of 9 L/min to ensure the required paint pressure at the applicators, and all of this flow circulates around the system through the smart BPR.
- 10 In condition 2, two applicators are spraying at a rate of 2 L/min, while one is spraying at 1 L/min and the other two are not spraying. The total amount being taken out is 5 L/min. In this condition, instead of the flow through the BPR dropping to 4 L/min and the smart pump continuing to provide a flow of 9 L/min, the amount of paint circulating through the smart BPR has only dropped to 6L/min, while the smart pump has increased its speed to provide a 15 flow of 11L/min.

Similarly in condition 3, all the applicators are taking out 2 L/min each (a total of 10 L/min), while the smart pump has increased its speed to deliver 13 L/min, and the amount circulating back through the BPR has dropped to 3L/min. This means that the smart BPR is 20 still controlling the upstream pressure, even though the amount of paint being taken out is more than was originally being provided. The pressure of paint at the spray booth will therefore continue to be maintained by the smart BPR when there is a subsequent increase in the amount being sprayed.

- 25 In condition 4, the applicators are spraying at their maximum capacity of 3L/min each (a total of 15 L/min). In this case there is no need to provide any flow through the smart BPR as there can be no further increase in the amount of paint being taken out of the system.

The smart BPR therefore closes the line back to the paint tank and all the flow is provided from the smart pump (15L/min).

5

Table 1

Condition	A1 L/min	A2 L/min	A3 L/min	A4 L/min	A5 L/min	Pump flow L/min	BPR flow L/min
1	0	0	0	0	0	9	9
2	0	2	2	1	0	11	6
3	2	2	2	2	2	13	3
4	3	3	3	3	3	15	0

We claim:

1. A paint circulating system suitable for providing paint to applicators in a product finishing facility, the system comprising:

5 a pump for pumping paint around the system;

a back-pressure regulator (BPR) to substantially eliminate pressure fluctuations of paint upstream of the BPR;

10 control means for controlling the pump and the BPR to operate in one of a flow mode, wherein a required flow rate of paint around the system is maintained, and a pressure mode, wherein a pressure of paint between the pump and the BPR is maintained.

2. The paint circulating system of claim 1 wherein, in the flow mode, the BPR is configured to be de-activated so as to allow paint to flow without being responsive to pressure fluctuations.

15

3. The paint circulating system of claim 2 wherein the BPR is an automated type, whereby activation means is provided to activate and/or de-activate the BPR.

20 4. The paint circulating system of claim 3 wherein the activation means comprises compressed air.

5. The paint circulating system of claim 3, wherein the activation means comprises an hydraulic fluid.

25 6. The paint circulating system of claim 3 wherein the BPR comprises a diaphragm that is acted upon by a spring on one side, and by the paint pressure on the other side.

7. The paint circulating system of claim 3 wherein the BPR comprises a diaphragm that is acted upon by fluid pressure on one side, and by the paint pressure on the other side.

8. The paint circulating system of claim 1 wherein, in the flow mode, the control
5 means is configured to control the pump so as to pump paint at a fixed flow rate.

9. The paint circulating system of claim 8 wherein the fixed flow rate is a low flow rate, at or just above a minimum flow rate required for the paint.

10 10. The paint circulating system of claim 1 wherein, when in the pressure mode, the BPR is configured to be activated so as to respond to variations in the paint pressure to maintain a substantially constant pressure upstream of the BPR.

11. The paint circulating system of claim 1 wherein, in the pressure mode, the pump is
15 configured to deliver paint at a predetermined pressure.

12. The paint circulating system of claim 11 wherein the pump is a variable speed pump responsive to a control signal to maintain the predetermined pressure.

20 13. The paint circulating system of claim 11 wherein the pump is a variable capacity pump responsive to a control signal to maintain the predetermined pressure.

14. The paint circulating system of claim 1 wherein a pressure sensor is provided to provide a pressure signal as a basis for a control signal.

15. The paint circulating system of claim 14 wherein the control means is arranged to receive the pressure signal and to provide the control signal to the pump for maintaining the pressure.

5 16. The paint circulating system of claim 1 wherein the controller is operable to switch the system between the flow mode and the pressure mode in response to a demand signal.

17. The paint circulating system of claim 16 wherein the demand signal is provided from a plant scheduling apparatus.

10

18. The paint circulating system of claim 16 wherein the demand signal is provided from a 'job queue' data processing apparatus.

15

19. The paint circulating system of claim 1 wherein the control means comprises a control card for mounting in a programmable computing device.

20. The paint circulating system of claim 19 wherein the control card is provided with a plurality of input and output terminals for receiving signals from sensors in the system and for providing control signals to the BPR and the pump.

20

21. The paint circulating system of claim 19 wherein the control card is provided with a data link to a graphics system for set-up and monitoring purposes.

25

22. The paint circulating system of claim 19 wherein the control card includes a plurality of channels for controlling a plurality of paint circulating systems, each providing paint to a spray booth.

23. The paint circulating system of claim 22 wherein each of the plurality of paint circulating systems provides a different colour of paint to the spray booth.

24. A paint circulating system for use in association with a paint spray-booth, the system
5 comprising:

a variable speed pump for pumping paint around the system;
a back-pressure regulator operable in an active condition for varying a flow rate of paint in response to pressure fluctuations of paint flowing into the back-pressure regulator so as to maintain upstream paint pressure, and in an inactive condition wherein paint is free
10 to flow through the regulator; and

a controller for controlling the system to operate in one of a flow mode and a pressure mode,

wherein:

in the flow mode the controller is configured to place the back-pressure regulator in
15 the inactive condition and to operate the pump at a fixed speed so as to provide a required flow rate of paint around the system at a minimum pressure, and


in the pressure mode, the controller is configured to place the back-pressure regulator in the active condition and to control the pump speed so as to maintain a pressure of paint at the spray booth,

20 the controller being further operable to switch the system between the flow mode and the pressure mode in response to a demand signal.

25. A method of operating a paint circulating system to provide paint to applicators in a product finishing facility, the system comprising:

a pump for pumping paint around the system;
a back-pressure regulator (BPR) to substantially eliminate pressure fluctuations of paint upstream of the BPR; and

control means for controlling the pump and the BPR, the method comprising: switching operation of the pump and the BPR between a flow mode, wherein a required flow rate of paint around the system is maintained, and a pressure mode, wherein a pressure of paint between the pump and the BPR is maintained.







FIGURE 2

3/3

FIGURE 3



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2006/030176

A. CLASSIFICATION OF SUBJECT MATTER
INV. B05B12/08 B05B9/04
ADD. B05B12/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 816 025 A (O NEILL W) 11 June 1974 (1974-06-11)	1-11, 14-16,25
A	column 2, line 24 - column 4, line 16; figures	24
X	US 2003/101931 A1 (ESTELLE PETER W [US] ET AL) 5 June 2003 (2003-06-05)	1-23,25
A	paragraphs [0025] - [0033]; figure 1	25
X	GB 1 155 328 A (CLIFFORD COVERING COMPANY LTD) 18 June 1969 (1969-06-18)	1-5,8,9, 11,16,25
A	page 1, line 70 - page 2, line 24; figure	24
	-----	-/-

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search:	Date of mailing of the international search report
16 November 2006	24/11/2006
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Brévier, François

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2006/030176

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 917 296 A (KONIECZNSKI RONALD D [US]) 17 April 1990 (1990-04-17) column 4, lines 16-51 column 5, lines 1-17; figure 1 -----	1-3,5,8, 9,25
A	US 5 096 120 A (LUCKARZ MIROSLAV [DE]) 17 March 1992 (1992-03-17) column 3, line 28 - column 4, line 20 column 5, lines 17-20; figure 1 -----	1,17-21, 24,25
A	FR 2 656 348 A3 (BREINING MASCHINEN FAFRZEUGBAU [DE]) 28 June 1991 (1991-06-28) page 6, line 25 - page 7, line 22 page 8, lines 7-32; figure 1 -----	1,24,25
A	US 5 195 680 A (HOLT EARL R [US]) 23 March 1993 (1993-03-23) abstract; figure 1 -----	1,24,25

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2006/030176

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 3816025	A	11-06-1974		NONE		
US 2003101931	A1	05-06-2003	DE	10150230 A1	25-07-2002	
			JP	2002200445 A	16-07-2002	
			SE	523754 C2	11-05-2004	
			SE	0103429 A	01-05-2002	
			US	6517891 B1	11-02-2003	
GB 1155328	A	18-06-1969		NONE		
US 4917296	A	17-04-1990		NONE		
US 5096120	A	17-03-1992	DE	3821440 A1	28-12-1989	
			EP	0347607 A2	27-12-1989	
			ES	2061788 T3	16-12-1994	
FR 2656348	A3	28-06-1991	DE	3942496 A1	27-06-1991	
			DE	8915850 U1	19-09-1991	
US 5195680	A	23-03-1993		NONE		