



US010948215B2

(12) **United States Patent**
Zelczer et al.

(10) **Patent No.:** **US 10,948,215 B2**
(45) **Date of Patent:** **Mar. 16, 2021**

(54) **SYSTEM AND METHOD FOR WIRELESS ENVIRONMENTAL ZONE CONTROL**

(58) **Field of Classification Search**
CPC F24F 13/10; F24F 3/044; F24F 2110/30; F24F 2140/40

(71) Applicant: **ARZEL ZONING TECHNOLOGY, INC.**, Cleveland, OH (US)

See application file for complete search history.

(72) Inventors: **Al Zelczer**, University Heights, OH (US); **Leonard Roth**, University Heights, OH (US); **Richard Wilson**, Cleveland, OH (US); **Kenneth Barton**, Willoughby, OH (US); **Adam Bush**, Mayfield Heights, OH (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,945,565 A 3/1976 Lynch et al.
4,253,483 A * 3/1981 Cornelius F16K 3/3165
137/240

(Continued)

FOREIGN PATENT DOCUMENTS

JP 04136656 A * 5/1992
JP 04184035 A 7/1992

(Continued)

OTHER PUBLICATIONS

Wireless Damper HVAC Zoning System. Bush. Jul. 1, 2015. <https://contest.techbriefs.com/2015/entries/consumer-products/6162>.

(Continued)

Primary Examiner — Nelson J Nieves
(74) *Attorney, Agent, or Firm* — Vorys, Sater, Seymour and Pease LLP; Scott M. Guttman

(73) Assignee: **ARZEL ZONING TECHNOLOGY, INC.**, Cleveland, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 31 days.

(21) Appl. No.: **16/249,252**

(22) Filed: **Jan. 16, 2019**

(65) **Prior Publication Data**

US 2019/0154298 A1 May 23, 2019

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/881,920, filed on Oct. 13, 2015, now Pat. No. 10,190,794.
(Continued)


(51) **Int. Cl.**
F24F 13/10 (2006.01)
F24F 3/044 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **F24F 13/10** (2013.01); **F24F 3/044** (2013.01); **H02J 9/06** (2013.01); **F24F 2110/30** (2018.01); **F24F 2140/40** (2018.01); **G01D 5/142** (2013.01)

(57) **ABSTRACT**

A system and method to control environmental parameters of predefined zones within a structure. An embodiment of the system uses damper assemblies that are entirely wireless as a result of energy capturing devices which convert air flow within the HVAC system ductwork into electrical current and a wireless control module that remove the need for hard-wiring for power or control. Still further, an embodiment of the system uses wireless components to monitor the environmental parameters of a structure's zones, process and communicate necessary zone adjustments, and actuate system components.

15 Claims, 12 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 62/107,789, filed on Jan. 26, 2015, provisional application No. 62/063,207, filed on Oct. 13, 2014.
- (51) **Int. Cl.**
F24F 140/40 (2018.01)
F24F 110/30 (2018.01)
H02J 9/06 (2006.01)
G01D 5/14 (2006.01)

References Cited

U.S. PATENT DOCUMENTS

4,545,524 A 10/1985 Zelczer
 4,702,412 A 10/1987 Zelczer et al.
 4,783,048 A * 11/1988 St. Clair F16K 3/0281
 251/129.11
 4,838,310 A * 6/1989 Scott A01G 25/16
 137/624.14
 5,251,815 A * 10/1993 Foye G05D 7/0635
 236/49.3
 5,458,148 A 10/1995 Zelczer et al.
 5,544,853 A * 8/1996 Choi F16T 1/00
 251/129.01
 5,806,830 A 9/1998 Alvarez
 5,857,617 A 1/1999 Weng
 5,944,098 A * 8/1999 Jackson F24F 11/006
 165/207
 5,979,872 A 11/1999 Stearns et al.
 6,198,243 B1 * 3/2001 Ritmanich F24F 13/1426
 318/466
 6,698,445 B2 3/2004 Zelczer
 6,786,473 B1 9/2004 Alles
 6,997,390 B2 2/2006 Alles
 7,062,830 B2 6/2006 Alles
 7,945,973 B2 * 5/2011 Khorshid E03C 1/055
 251/129.04
 8,086,352 B1 12/2011 Elliott
 8,478,447 B2 7/2013 Fadell et al.
 8,550,370 B2 10/2013 Barrett et al.
 8,552,597 B2 10/2013 Song et al.
 8,600,556 B2 12/2013 Neisler et al.
 8,660,708 B2 2/2014 Narayanamurthy et al.
 8,802,981 B2 8/2014 Wallaert et al.
 9,273,879 B2 3/2016 Kates
 9,303,890 B2 4/2016 Haines et al.
 9,477,239 B2 10/2016 Bergman et al.
 9,477,241 B2 10/2016 Schultz et al.
 2002/0030172 A1 * 3/2002 Twito F24F 13/14
 251/305
 2003/0140637 A1 * 7/2003 Masui F24F 11/30
 62/127
 2005/0136829 A1 * 6/2005 Beaver A62C 2/14
 454/292
 2006/0063522 A1 3/2006 McFarland
 2006/0071089 A1 * 4/2006 Kates G05D 23/1934
 236/94

2006/0097063 A1 * 5/2006 Zeevi F24F 11/30
 236/49.3
 2007/0119958 A1 * 5/2007 Kates F24F 3/044
 236/1 B
 2007/0228183 A1 * 10/2007 Kennedy F24F 11/30
 236/1 C
 2008/0033599 A1 2/2008 Aminpour et al.
 2008/0121729 A1 * 5/2008 Gray G05D 23/1934
 236/51
 2008/0277486 A1 11/2008 Seem et al.
 2010/0307733 A1 12/2010 Karamanos et al.
 2011/0034120 A1 * 2/2011 Jaiyeola G05D 23/1934
 454/335
 2011/0059685 A1 * 3/2011 Ido B60H 1/00692
 454/69
 2012/0248206 A1 * 10/2012 Kaiser F04D 27/003
 236/49.3
 2013/0024799 A1 * 1/2013 Fadell G06F 3/048
 715/771
 2013/0068846 A1 3/2013 Bluestone
 2014/0081465 A1 * 3/2014 Wang G05B 15/02
 700/276
 2014/0144530 A1 5/2014 Miller
 2014/0222216 A1 8/2014 Chen
 2014/0349566 A1 * 11/2014 Lamb G05D 23/1932
 454/255
 2015/0058779 A1 2/2015 Bruck et al.
 2015/0192938 A1 * 7/2015 Lee F24F 11/00
 700/276
 2015/0308704 A1 * 10/2015 Jung F24F 11/62
 700/276
 2015/0345816 A1 * 12/2015 Donovan F24F 3/044
 165/209
 2015/0369504 A1 12/2015 Flaherty et al.
 2015/0369505 A1 * 12/2015 Malve F24F 11/64
 700/276
 2016/0258639 A1 9/2016 Wiley et al.
 2016/0305677 A1 * 10/2016 Hirsch F24F 11/0001
 2017/0059193 A1 * 3/2017 Mignot F24F 11/62
 2017/0328413 A1 * 11/2017 Bamberger F16D 1/076

FOREIGN PATENT DOCUMENTS

JP 04281105 A 10/1992
 JP 2005180747 A 7/2005
 WO 2016182891 A1 11/2016

OTHER PUBLICATIONS

Feasibility of Retrofitting Centralized HVAC Systems for Room-Level Zoning. Sookoor, et al. 2012. <http://www.cs.virginia.edu/~whitehouse/research/buildingEnergy/sookoor12feasibility.pdf>.
 Predictive Control for Energy Efficient Buildings with Thermal Storage. Ma, et al. Feb. 2012. <http://sdb.cs.berkeley.edu/wiki/images/1/15/Ma12mpc.pdf>.

* cited by examiner




FIG. 1

202




FIG. 2A

204




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



SYSTEM AND METHOD FOR WIRELESS ENVIRONMENTAL ZONE CONTROL

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 14/881,920 filed Oct. 13, 2015, assigned U.S. Pat. No. 10,190,794, which claims priority to and the benefit of U.S. Provisional Patent Application No. 62/063,207 filed on Oct. 13, 2014, and U.S. Provisional Patent Application No. 62/107,789 filed on Jan. 26, 2015, all of which are incorporated herein in their entirety.

TECHNICAL FIELD

Certain embodiments of the present invention relate to HVAC zoning. More particularly, certain embodiments of the present invention relate to a system and method to control environmental parameters of predefined zones within an environment.

BACKGROUND

The cooling and heating of commercial buildings and residential homes is typically accomplished via forced air and forced hot or cooled water distribution systems. A furnace, heat pump, other fossil fuel furnace, and/or air conditioner are typically used to supply heated air or cooled air to areas of the building or home via ducts. Such distribution systems are often controlled by a single thermostat which is centrally located within the building or home. A person sets the thermostat to a particular temperature setting. When the temperature measured by the thermostat deviates a predefined amount from the set temperature, a furnace, heat pump, other fossil fuel furnace, or air conditioner is turned on to provide heated or cooled air or water to the various regions of the building or home via the duct work or water lines.

Even though the desired temperature may be achieved at the location of the thermostat, the resultant temperatures in the various other regions of the building or home may still deviate quite a bit from this desired temperature. Therefore, a single centrally located thermostat may not provide adequate temperature control for individual rooms and areas. In an attempt to address this problem, duct work and pipes throughout the building or home are fitted with manually adjustable registers, dampers, or valves which help to control the flow of air or water to the various regions.

A damper, which may generally be a valve or plate that stops or regulates the flow of air inside a duct, chimney, variable air volume box, air handler, or other air handling equipment, can utilize manual or automatic functions to shut off or restrict the flow of air into various rooms in order to regulate its temperature and climate. Manual dampers and valves are typically each adjusted to a single position and left in that state. Such an adjustment may be sufficient for a particular time of year, outside temperature level, and humidity level, but is likely not optimal for most other times of the year and other temperature and humidity levels. Furthermore, such an adjustment may only be suitable for a particular time of day due to the internal and external daily load variances that occur depending on, for example, the position of the sun, whether or not lights are on, and how many people are in a particular area. Moreover, it may be time consuming and difficult to manually re-adjust the dampers and valves for optimal comfort level. Dampers

actuated by electric motors or pneumatic components are a recent industry development which relieve homeowners of manual damper adjustments, but they may also require the installation of expensive and complex wiring, and/or pressurized air lines, to power sources and thermostats.

The complexity of damper flow control systems continues to increase as the industry has developed multi-zone control systems in an attempt to better control the environmental parameters in each room or region of a home or building, for example, by placing thermostats and/or sensors in each room or groups of rooms. A zone may be equipped with a temperature, humidity, motion, or other sensor in communication with a central thermostat or thermostat located in the zone. When the temperature falls outside of the defined acceptable range, the thermostat or sensor triggers actuation of the heating or cooling source, and/or movement of the dampers, until the zone once again achieves the desired temperature.

However, such systems are not entirely successful since a structure with multiple rooms and zones requires the installation of highly complex wiring systems, and/or pneumatic air lines, in order to provide power and control signals to the thermostats, sensors, and/or dampers. Specifically, the expense of the required wiring or air lines, its installation, and the utility bills associated with powering associated dampers, sensors, and thermostats can be cost prohibitive. Retrofit installation of wiring systems can be particularly difficult and expensive.

Moreover, known climate control systems are typically controlled by a centralized thermostat which is hardwired to a single location. This centralized thermostat, in turn, is hardwired to a power source and all dampers associated with the climate control system. Thus, a person desiring a change in temperature must physically move to the centralized thermostat in order to enter temperature control instructions.

In view of the foregoing discussion, it is apparent that there is a need for a more efficient way of controlling the distribution of air or water and environmental parameters for several zones in a building or home.

Further limitations and disadvantages of conventional, traditional, and proposed approaches will become apparent to one of skill in the art, through comparison of such systems and methods with the system and method as set forth in the remainder of the present application with reference to the drawings.

SUMMARY

In one example embodiment, a system to wirelessly control environmental parameters of a predefined zone is disclosed. The system includes a damper associated with the zone and configured to regulate the flow of air inside an air duct of the zone. The damper includes an optional wireless energy harvesting device adapted to capture energy in an HVAC conduit. The damper further includes an energy storage device adapted to store energy captured by the energy harvesting device. The damper assembly is configured to operate using energy generated by the energy harvesting device. The system further includes a temperature controller associated with the damper, configured to monitor the temperature in the zone, to receive as input a desired temperature for the zone, and to communicate data representative of the zone temperature and the desired temperature and to request service at the zone. The system further includes a control box in wireless communication with the damper assembly and the temperature controller, the control box configured to adjust the position of the damper to

3

regulate the flow of air inside the air duct of the zone based on the data representative of the zone temperature and the desired temperature received from the temperature controller.

In one example embodiment, a damper for an HVAC system is disclosed. The damper includes a rail assembly for providing support to the damper and for securing and sealing the damper on an air duct. The damper further includes a damper blade assembly configured to regulate the amount of air passing through an air duct. The damper further includes a damper module configured to control the orientation of the damper blade assembly. The damper further includes an optional scavenger assembly configured to harvest energy from air passing by the damper inside the air duct. The damper further includes a scavenger module configured to store energy harvested by the scavenger module.

In one example embodiment, a method for wirelessly controlling environmental parameters of a predefined zone is disclosed. The method includes the step of providing a control box, a wireless temperature controller associated with the zone, and a damper assembly associated with the zone, the damper including a wireless energy harvesting device, an energy storage device, and a module for actuating damper assembly operation. The method further includes the step of collecting data representative of the environmental parameters of the zone and data representative of desired temperature for the zone via the wireless temperature controller. The method further includes the step of wirelessly transmitting the collected data from the wireless temperature controller to the control box. The method further includes the step of processing the collected data to determine a corresponding control signal. The method further includes the step of wirelessly transmitting the control signal from the control box to the damper assembly. The method further includes the step of actuating damper assembly operation, in response to the control signal, using energy generated by the energy harvesting device.

The systems and methods described herein permit wireless control of HVAC systems via various wireless communications devices. The disclosure also provides for an HVAC system that utilizes "green energy" damper assemblies which convert air flow generated within routine operation into electrical power that powers various system components.

These and other advantages and novel features of the present disclosure, as well as details of illustrated embodiments thereof, will be more fully understood from the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a schematic block diagram of an example embodiment of a system to wirelessly control environmental parameters of predefined zones within an environment.

FIG. 2A illustrates an example damper of FIG. 1.

FIG. 2B illustrates an example damper of FIG. 1.

FIG. 3 illustrates the example system of FIG. 1 configured in a star topology.

FIG. 4 illustrates an example damper of FIG. 1.

FIG. 5 illustrates a portion of an example damper of FIG. 1.

FIG. 6 illustrates a portion of an example damper of FIG. 1.

FIG. 7 illustrates a block diagram of an example damper of FIG. 1.

4

FIG. 8 illustrates a block diagram of an example temperature controller of FIG. 1.

FIG. 9 illustrates a block diagram of a control box of FIG. 1.

FIG. 10 illustrates a block diagram of an example homeowner computing device of FIG. 1.

FIG. 11 illustrates a block diagram of an example administrator computing device of FIG. 1.

FIG. 12 illustrates a schematic diagram of an example computer for implementing the example homeowner computing device and the administrator computing device of FIG. 1.

DETAILED DESCRIPTION

Described herein is a customizable system for wirelessly controlling environmental parameters of predefined zones. The system combines temperature data with predefined zone parameters to determine how much air to deliver to a zone and when to deliver air to a zone. It should be appreciated that, although the system is described herein with respect to forced air systems, the system may also be applied to water distribution systems for heating and cooling. It should be appreciated that, although temperature measurements are referenced through the description, other suitable parameters such as humidity may also be measured, monitored, and/or controlled.

FIG. 1 illustrates a schematic block diagram of an example embodiment of a system **100** to wirelessly control environmental parameters of predefined zones **102A** and **102B** (hereinafter referred to as "zone" or "zones" **102**) within a first environment, in accordance with various aspects of the present disclosure. A zone **102** may comprise a portion of a large room, a separate room, or other connected areas in a house or other building, for example. A zone **102** may also be defined by a time of day. For example, a bedroom zone **102** may only be dynamically controlled at night when the bedroom is in use, and left closed off during the day when the bedroom is not in use. Similarly, an office building or restaurant not used at night may be closed off at certain hours of the night and dynamically controlled during the day. It should be appreciated that although the example system **100** is illustrated to wirelessly control environmental parameters of a first predefined zone **102A** and a second predefined zone **102B**, the example system **100** can be configured to wirelessly control any suitable number of zones **102**.

It should be appreciated that controlling temperatures in a configurable zone may be additionally advantageous in that static pressure buildup may be preventable. In particular, to prevent static buildup in a room, a zone may be configured in such a way as to prevent a certain group or groups of dampers from all being closed at the same time, which may otherwise result in static pressure buildup if they were all closed at the same time.

The system **100** further includes at least one wireless air damper **104A** and **104B** associated with each of the zones **102A** and **102B** respectively (hereinafter referred to as "damper" or "dampers" **104**). The damper **104** is configured to regulate the flow of air inside an air duct of an associated zone **102**.

In accordance with various embodiments of the present disclosure, the damper **104** may be a wireless damper that is powered by an energy capture device in combination with an associated rechargeable energy storage device (not shown). The damper **104** may be electromechanical, pneumatic, or

any other type of suitable damper. In some examples, damper **104** may articulate via a shape memory alloy.

The system **100** further includes temperature controllers **106A** and **106B** associated with each of the zones **102A** and **102B** respectively (hereinafter referred to as “temperature controller” or “temperature controllers” **106**). The temperature controllers **106** serve as user interfaces capable of setting a temperature in a corresponding zone **102**. Thus, a first temperature controller **106A** may be configured to provide an interface for adjusting the temperature in a first zone **102A** while a second temperature controller **106B** may be configured to provide an interface for adjusting the temperature in a second zone **102B**. In one example, temperature controllers **106** are portable and wireless and therefore may be moved according to user needs. For example, a user may move the temperature controller **106** to a couch while watching TV to enable the user to adjust the temperature in the zone **102** while watching TV. Thus, the temperature controller **106** may monitor, and in turn control, the temperature near the user in particular instead of a fixed location in a room or zone. In another example, a user may move the temperature controller **106** to a fixed location within the zone **102** while away from the zone **102** to prevent unauthorized access. In one example, the temperature controller **106** may be configured to be mountable on a wall or otherwise secured to a fixed location within the zone **102**.

The temperature controller **106** is configured to monitor the temperature in a zone and to display the temperature via an interface and also to receive input from a user about desired temperature. Desired input may be input, for example, via an interface at the temperature controller **106**. It should be appreciated that the user may also input a desired temperature via an alternative interface such as a remote computing device. As mentioned below, the temperature controller **106** may also be configured to monitor humidity in a zone and display information indicative of the same, and also receive input from a user about a desired humidity (i.e., whether to run a humidification cycle or a dehumidification cycle). In even other embodiments, the temperature controller **106** may include other types of sensors to measure air quality in a zone and/or the presence of certain gases. For example, the temperature controller **106** may include a sensor configured to detect carbon monoxide, or a gas leak, or smoke, etc. In this manner, the system **100** may alert (e.g., an audible and/or visual alarm) the user to the dangerous condition (i.e., carbon monoxide and/or a gas leak) such that the user may take preventative action, such as exiting the zone/home, addressing the leak, opening windows, etc. In addition, the system **100** may monitor the building or one or more zones thereof for other parameters such as allergens, light, sound, etc. Moreover, the system **100** may be configured to take preventative action in such situations, for example, by alerting authorities and/or opening a vent to the outside environment to bring in outside air and/or clean, fresh air.

The temperature controller **106** is operatively connected to a control box **108** and configured to wirelessly communicate the zone temperature and desired temperature to the control box **108** and to request service at the zone **102**. For example, zone service may include any of a heating call, a cooling call, a humidification call, a dehumidification call, and a fan-only call, in accordance with an embodiment of the present disclosure. The control box **108** is further operatively coupled to the damper **104** and configured to adjust the position of the damper **104** based on the received information from the temperature controller **106**. For

example, the damper **104** may be adjusted a fully closed position **202**, as illustrated in FIG. 2A, in order to block all or a majority of air from passing through inside a duct, or the damper **104** may be adjusted to a fully open position **204**, as illustrated in FIG. 2B, in order to allow the maximum amount of air to pass through inside the duct.

Once a desired temperature in a zone associated with the temperature controller **106** is reached, the temperature controller **106** may communicate such information to the control box **108** so that the control box **108** may in turn adjust the damper **104** position accordingly if necessary. In one example, the control box **108** may determine that the system **100** may be experiencing a problem if a measured temperature at a temperature controller is not reaching a desired temperature and inform a homeowner or a contractor of the potential problem. For example, if a temperature controller **106** is broken or removed from an associated zone, it will not be able to accurately measure the temperature in its assigned zone. In such a scenario, the control box **108** may notify a homeowner of the problem and also either automatically close and open the damper **104** associated with the assigned zone where a problem is detected or rely on a wired backup temperature sensor to determine when to close the damper **104**. In some examples, the system **100** may be configured to selectively condition one or more zones as needed while minimizing conditioning in other zones that don't need it, thereby providing energy savings and reducing hot and cold spots and temperature fluctuations between zones. For example, each of the zones may include a temperature sensors (e.g., in the temperature controller **106**) and, based on temperature readings from the various zone, the control box **108** may identify which zones do and do not need heating, cooling, and/or air circulation. The control box **108** may then send instructions to the dampers **104** associated with the identified zones causing them to open or close (partially or fully) as needed to achieve the needed heating, cooling, and/or air flow. Thus, the control box **108** may control the dampers **104** to direct air flow to certain zones while minimizing (or even ceasing) air flow to other zones.

The control box **108**, at the heart of the system **100**, may be hardwired into a centralized location, or be of a portable wireless variety as described herein. In one example, the control box **108** may be configured as a micro access point or a Wi-Fi station, which may result in cost savings since a separate wireless access point **112** may not be required. In one example, the outer shell of the control box **108** is comprised of a suitable combination metal or other durable material to prevent damage to the inner components of the control box **108** as well as injection molded plastic to limit wireless signal attenuation. In one example, the control box **108** may be configured to be opened up in order to allow access to the inside of the control box **108** for maintenance and repair purposes.

Referring back to FIG. 1, the control box **108** is further communicatively coupled to one or more components associated with heating and cooling (“HVAC”) equipment **110** such a heat pump, a furnace, a refrigeration evaporator, an electric resistance heater, or other suitable auxiliary components and equipment. The control box **108** is operationally connected to the HVAC equipment **110** via a relay connector or other suitable wired or wireless connector such that the control box **108** is configured to control the HVAC equipment **110**. In some examples, the HVAC equipment **110** may be utilized to dehumidify. For example, if humidity falls below a user desired value, the heat from the HVAC equipment **110** may be turned on to dehumidify; whereas, if humidity rises above such user desired level, the cooling

from the HVAC equipment **110** may be utilized to extract moisture and thereby dehumidify. In other examples, a heating or cooling call is not needed to humidify or dehumidify. In these other examples, the HVAC equipment **110** may include a humidifier and/or dehumidifier and the user may simply initiate a dehumidifying and/or humidifying cycle on-demand. In these latter examples, the user may assess whether to initiate such on-demand humidity cycle based on humidity measurements. The humidity measurements may be taken from one or more locations in the home and then averaged to provide the user an average humidity level for the home such that they may control the humidity in the entire home; however, in some examples, zone specific humidity measurements may be provided to the user such that the user may control the humidity in one or more specific zones rather than the entire home. To measure humidity, one or more humidity sensors may be located throughout the home, for example, in one or more separate zones. In some examples, the temperature controllers **106** may be configured to measure humidity.

System **100** further may include a wireless outdoor temperature sensor (hereinafter referred to as "OA Sensor") **114** and a wireless leaving air temperature sensor (hereinafter referred to as "LAT") **116** in communication with the control box **108**. The OA sensor **114** and LAT **116** provide temperature data to control box **108** for optimizing the closed loop transfer functions of the complete HVAC installation, as well for protecting the system **100** from overheating or freezing. The system **100** may further include a wired failsafe temperature sensor **118** in communication with the control box **108** and configured to provide the control box **108** with ambient indoor temperature data in the event of a wireless connectivity problem which would protect the system **100** from freezing. In another example, a return air temperature may be used as an approximation of the ambient indoor temperature. In one example, the OA sensor **114** and LAT **116** help provide protection against equipment back-up lockout. In one example, the OA sensor **114** and LAT **116** assist in fuel balancing and equipment staging. In some examples, the system **100** includes an economy mode or setting where outside air is brought into the building to cool (or heat) instead of utilizing the HVAC equipment **110** to drive temperature. For example, the building may have an outside vent configured to bring outside air into the building (or one or more zones thereof) when opened. The outside vent may include a damper such as damper **104** and, when running the system **100** in the economy mode, the OA sensor **114** may measure outside air temperature and the control box **108** may direct the damper **104** of the outside vent to open when the outdoor temperature is sufficient to cool or heat the building (or zones thereof) to the user desired temperature. Not only will this economy mode save energy, but it will also input fresh air in the building or one or more zones thereof. Thus, outdoor air measured by the OA sensor **114** may be utilized to control the indoor temperature of the building.

The system **100** further includes a homeowner computing device **120** configured to enable a user or homeowner to wirelessly access the control box **108** and to control the system **100**, either directly while at home and within range of the control box **108**, or remotely while away from home by connecting to the home wireless access point **112**, via the Internet **126**. The system **100** further includes an administrator computing device **122** configured to enable a contractor or other suitable systems administrator to wirelessly access the control box **108** and to perform initial setup and future troubleshooting and maintenance of system **100**. In

one example, administrator computing device **122**, is restricted to only accessing the control box **108** while at the home and connected to the system's **100** wireless network, which is distinct from a home's wireless network. This restricts the administrator's access and does not require granting of access to a home's wireless network to the administrator. In another example, the administrator computing device **122** may be granted access to the control box **108** remotely as well, either directly via a cellular network of control box **108** or via a secure connection through a home's router. In some examples, the system **100** is configured to integrate with and/or connect to various smart home systems and/or devices. For example, the system **100** may connect to hubs such as Google Home, Amazon Alexa, Amazon Echo, etc. In these examples, the user may control the system **100** with voice commands (and/or motion command such as sign language) received by the smart home systems or devices. Here, the user may tell the smart home system/device to raise or lower the temperature (or address another parameter in the building and/or zone), which in turn transmits the command to the control box **108** such that the action or adjustment is performed. However, in some embodiments, the system **100** may be configured to receive and respond to a user's voice commands without a smart home system and/or device. In some examples, the system **100** is configured to integrate with and/or connect to various home or building automation systems or devices, such as those of Crestron Electronics, Inc., Control4 Corporation, Savant Systems LLC, etc. For example, the system **100** may be connected to a voice activated remote control, such as the Savant "Pro Remote" or Amazon Alexa, for adjusting the indoor environment via voice command, and such devices may be used to send a signal to the system **100** to adjust temp in any zone upon receiving voice command from the user.

It should be appreciated that the homeowner computing device **120** and the administrator computing device **122** may be any suitable computing device such as a hard-wired desktop or laptop personal computer or a portable wireless electronic device—such as a mobile phone, laptop computer, and/or tablet computer—utilizing a software application (cloud, website, and/or device based) configured to monitor and respond to environmental factors received from the system **100**. The homeowner computing device **120** and the administrator computing device **122** may consist of dedicated software and can operate on computers utilizing Windows™, Mac™, Linux™, or any other operating system and may use a private intranet or public website to access the network. The administrator computing device in particular **122** may be used by an installation worker during configuration and HVAC system setup, for example, while the homeowner computing device may provide users with information about zone environmental conditions and HVAC system status and permit users to request changes to environmental conditions in one or more zones in the structure through an interface system. As described below, the administrator computing device **122** may also be used by an energy supplier to control heating and cooling in one or more zones.

In some embodiments, other home or building automation devices—such as security, lighting, curtains, blinds, door bells, or other functions—may be controlled via the homeowner computing device **120** and the administrator computing device **122**. In some examples where the building is outfitted with remote controlled valves and energy harvesting technologies, the system **100** may control other building parameters automatically and/or via user input. For example, hot water pipes and/or radiant heating in one or more zones may include Zigbee radio-controlled valves that the may be

controlled via the homeowner computing device **120** and the administrator computing device **122**. In such embodiments, the Zigbee radio-controlled valves may be hard wired to the building's power source or may instead include energy harvesting or renewable energy technology, or combinations thereof. Also, the system **100** may be integrated into a building's geo-thermal (if any) such that a user may monitor and/or control the geo-thermal system, for example, via the homeowner computing device **120** and the administrator computing device **122**.

System **100** further includes a remote computer data server **124** in the cloud, accessible via the Internet **126**. The computer data server **124** is configured to receive and store data from the control box **108**. For example, the computer data server **124** may store data relating to the HVAC usage of a homeowner. Such data may be beneficial for analyzing trends and making recommendations to the homeowner. In one example, the computer data server **124** may further be configured to perform such calculations and analysis based on received data and to provide recommendations or other suitable reports to the homeowner or to other authorized parties. In one example, only the homeowner computing device **120** may be configured to access the data stored by the computer data server **124** while in other examples, other suitable computing devices may be granted access to the stored data. In one example, the computer data server **124** may further be configured to be capable of communicating alerts or messages to the homeowner computing device **120**, if for example the system **100** is malfunctioning or with other suitable information. In some examples, the homeowner's energy supplier may be granted access to the computer data server **124** for inputting historical data, analyzing usage data, etc. In these example, the system **100** may be configured to provide energy conservation tips to the homeowner.

It should be appreciated that network communication between the components of system **100** can occur via analog or digital signals, with or without the use of a master or coordinator, and can create relationships that can include master/slave, peer-to-peer, or a combination of both. In addition, although specific components of system **100** have been described herein, it is to be understood that the number and arrangement of such system **100** components can be capped or scalable, that interoperability between components may or may not require bridging hardware, and that the network may be publicly or privately shared within a variable geometric spatial scope but may or may not communicate with other networks.

It should be further appreciated that the network topology for the system **100** communication control system may consist of various combinations of wired and/or wireless mediums. For wired connections, the control box **108** may transfer communications over, by way of non-limiting examples, twisted pair, coaxial, fiber optic, or ITU-T G.hn components, and may be interoperable with other networks via a gateway using BACnet or LonTalk protocols. For wireless connections, communications may occur, again by way of non-limiting example, via open or proprietary satellite, cellular, radio, infrared and/or other wireless personal area network protocols such as ZigBee™ Bluetooth™, Wi-Fi, Z-Wave™ or EnOcean™. The topological layout may be open (i.e., Mesh™ or Star™) as with the geographical scale (i.e., LAN, PAN, WAN). FIG. 3 illustrates one example in which the control box **108** is configured to control multiple zones **302A-H** by communicating with respective dampers and temperature controllers in each of the zones **302A-H** in a star topology. Such a start topology

may be beneficial in that the control box **108** may communicate directly with each of the zones **302A-H**. Thus, the control box **108** is having difficulty communicating with a first zone, such a malfunction will not interfere with the control box's **108** ability to communicate with the remaining zones. It should be understood that numerous combinations of wired and wireless system arrangements are contemplated to fall within the scope of this disclosure.

In one example, the control box **108** is configured to control a subset of dampers **104** based damper **104** associations with the multiple zones **302A-H**. As described herein, the control box **108** may also be configured to control other devices or systems (or a subset of the same) associated with the multiple zones **302A-H**, for example, security systems (and components thereof), fire alarm systems, home automation systems, lighting systems, curtain and/or blinds systems, door lock systems, door opening or closing actuator systems, garage door systems, hot water and/or radiant heating valve systems, geothermal systems, indoor and/or outdoor sprinkler systems, etc.

In various embodiments of the present disclosure, portions, or all of, the system **100** equipment are controlled via wireless communications. In one embodiment particularly suited for retrofitting an existing HVAC system with an at least partially wireless control configuration, the control box **108** is hard-wired into a centralized location but also operationally connected to home router and access point **112**. In another embodiment, the control box **108** may have integrated wireless communications components adapted to communicate wirelessly with other components of system **100** without requiring connection to or interference with a home wireless network.

FIG. 4 illustrates an example damper **104** in more detail. Damper **104** includes a rail assembly **402** for providing support to the damper **104** and for securing and sealing the damper on an air duct. The damper **104** further includes a damper blade assembly **404** configured to regulate the amount of air passing through an air duct. In particular, the damper blade assembly **404** prevents substantially all or a portion of air flowing inside an air duct to pass through, depending on the damper blade assembly **404** orientation. The damper **104** further includes a damper module **406** configured to control the orientation of the damper blade assembly **404**. In particular, the damper module **406** is configured to communicate with the control box **108** and to open and close the damper blade assembly **404** based on received instructions from the control box **108**.

In one example, the damper module **406** is able to determine the position of the damper blade assembly **404** based on the amount of power being drawn by a motor to open and close the damper blade assembly **404**. For example, a motor may require more energy to move the damper blade assembly **404** from a completely open state to a partially open state as compared to the amount of energy that may be required to move the damper blade assembly **404** from a partially open state to a closed state. Thus, the damper module **406** may translate the required energy into an approximation of the current state of the damper blade assembly **404**. In another example, the damper module **406** is able to determine the position of the damper blade assembly **404** based on data received from a Hall Effect sensor. For example, a Hall Effect sensor may be used to measure the magnetic field produced by a magnet in a drive shaft and, with this information, the position of the damper blade assembly **404** may be determined and adjustments to the position of the damper blade assembly **404** may be made,

for example, to open (fully or proportionally) or close (fully or proportionally) it to control the volume of air flow.

The damper **104** is further configured to generate and store its own power but also rely on a battery power source or an external hard wired source when needed. Thus, the damper **104** further includes an optional scavenger assembly **408** for harvesting energy from the air that passes by the damper **104** inside the air duct. In particular, the scavenger assembly **408** includes an impeller that rotates as air passes by. The rotation of the impeller in the scavenger assembly **408** is translated into energy and stored by the scavenger module **410**. It should be appreciated that other suitable energy harvesting techniques may be used in place of a rotating impeller. It should further be appreciated that an energy harvesting may supplement energy requirements rather than providing all of required energy. In one example, the scavenger assembly **408** or the scavenger module **410** may be optional and removable.

In one example, the scavenger assembly **408** may consist of a wind-turbine type device that comprises one or more of a blade, rotor, shaft, pitch system, gear box, and generator to turn wind forces into wind-generated electrical power. In one example, the scavenger assembly **408** may have blades that are spoon shaped or airfoil propeller shaped. In one example, the scavenger assembly **408** may arrange turbine components on a vertical or horizontal axis in the form of upwind, downwind, shrouded, Savonius, flapping panel, or Darrieus or Giromill type devices. In one example, the scavenger assembly **408** may utilize gearless or reduction-gear assemblies. In one example, the scavenger assembly **408** may use electromagnetic induction. In other embodiments, the scavenger assembly **408** may use movement or pressure within system ductwork to capture energy for storage by the scavenger module **410**. In still other embodiments, the scavenger module **410** may be recharged via the scavenger assembly **408** using thermally driven (thermoelectric), solar-powered (photovoltaic solar cells; concentrated solar power in the form of a Fresnel reflector, stirring dish, power tower, or other solar powering arrangements known in the art), radio scavenging, or rectenna/nantenna type harvesting technologies.

In the event that the scavenger module **410** does not have enough stored energy generated from the scavenger assembly **408**, the scavenger module includes a battery backup which can be used to power the damper **104**. The battery may be of various combinations of chemicals such as alkaline, lead-acid, nickel cadmium, nickel metal hydride, nickel iron, nickel hydrogen, nickel zinc, lithium ion, lithium ion polymers, lithium-air, lithium cobalt oxide, lithium iron phosphate, lithium sulfur, lithium titanate, sodium ion, thin film lithium, zinc bromide, vanadium redox, sodium-sulfur, molten salt, silver-oxide, or oxide semiconductors. In one example, the battery may be rechargeable.

In one example, the scavenger module **410** may be configured to operate the damper **104** in one of three modes depending on how much energy has been generated by the scavenger assembly **408** and stored and how much energy is currently being generated. For example, in a first mode, the scavenger module **410** may operate the damper **104** in a full energy scavenging mode, meaning the damper **104** is only being powered by energy being harvested by the scavenger assembly **408** or energy stored by the scavenger module **410** that was previously generated by the scavenger assembly **408**. In this mode, the airspeed must meet a minimum predefined rate. For example, the airspeed may need to be at least 600 feet/minute for the scavenger module **410** to

operate in the first mode. Air speed may be determined, by example, with a velocity sensor or a hand-held anemometer. In a second mode, the scavenger module **410** may operate the damper **104** in battery mode, meaning the damper **104** is powered entirely using the battery backup. This mode may be required if the air speed drops below a predefined threshold. For example, the scavenger module **410** may operate in battery mode when airspeed drops below 200 feet/minute. In a third mode, when the airspeed in the air duct is above the battery power mode threshold but below the full energy scavenging mode, the scavenger module **410** may operate the damper **104** in a hybrid mode using a combination of power from the battery backup and power generated by the scavenger assembly **408**. In one example, the functionality of a damper **104** may be limited or restricted while operating in battery power mode or in hybrid mode. For example, while a damper **104** may function as a wireless router to facilitate wireless communication within system **100**, the damper **104** may be restricted to an end device only when operating in battery power mode. It should be appreciated that the scavenger module **410** may be configured to operate in other suitable modes using various combinations of energy sources. For example, a fourth mode may include operating using an external hardwired energy source. In some examples, the damper **104** may function as a router or an end node regardless of how it is being powered, and in these examples the damper **104** may be configured to automatically detect whether it should operate as a router or an end node. For example, the damper **104** may be configured to automatically operate as a router when it is plugged into a power source (e.g., a 24 Volt power source). Once configured as a router, the damper **104** may operate in concert with the other damper devices allowing them to use the router feature to send and receive signals from the control box **108**, and in some examples, the Zigbee chip in the dampers **104** does this automatically by “finding the easiest path” to send data to and from each other.

In one example, the impeller of the scavenger assembly **408** may function as an anemometer for determining actual speed of air passing through the air duct. The scavenger module **410** may be configured to store this information and communicate the information to the control box **108**. In one example, the determined air speed may be used to select an operating power mode.

In one example, the energy generated by the scavenger assembly **408** may also provide power to the system control box **108**, or other components of system **100**. It should be appreciated that energy generated by the scavenger assembly **408** may also be used to power suitable components outside of the system **100**. For example, the generated energy may be used to power a UV light for bacteria cleansing.

It should be appreciated that the damper **104** may be of different types such as, for example, an electric damper driven by an electric motor that can be wirelessly activated or a pump that may be activated by wireless control signals to provide pneumatic pressure that opens and closes the damper **104**.

It should be appreciated that the disclosure should not be limited to any particular damper assembly arrangement. Rather, any damper **104** that is capable of sealing or otherwise restricting air flow through an HVAC ductwork or air flow enclosure is intended to fall within the scope of the following arrangements. By way of non-limiting examples, mechanical power and transmission for damper operations may use solenoids and an air piston, bladder, diaphragm, or electrical motor with a gear box, for example. Linkage for

mechanical transmissions may also consist of belts and pulleys, an axle, or a linear actuator. It should be further appreciated that the impeller of the scavenger assembly 408 may be of any shape chosen by a person of sound engineering judgment, including but not limited to round, oval, triangular, rectangular, pentagonal, or hexagonal. The shape of the blade may be accomplished by foldable or expandable movement.

In a preferred embodiment, the damper 104 is of a wireless configuration, in that it does not require conventional wiring to the structure's central electrical system and does not need to be hardwired into control box 108 in order to receive control communications.

In other embodiments of the invention, the damper module 406 may also be adapted to receive and/or process wireless control signals forwarded from the temperature controller 102 or the control box 108. Control signals received by the damper module 406 may prompt a request for transmission of power contained in the scavenger module 410 that is sufficient to actuate the damper blade assembly 404 to open or close, to varying degrees, depending on the amount of air flow required to bring a zone within desired environmental temperature or humidity ranges. The damper module 406 may optionally terminate actuation of the damper blade assembly 404 when control signals received indicate desired environmental conditions have been achieved.

It should be appreciated that an existing HVAC system may be retrofitted for wireless control of zone heating and cooling using the system 100 described herein. In particular, the damper 104 may be adapted to be retrofitted into existing ductwork. It should be further appreciated that in some instances, installation of the damper 104 may require portions of the ductwork to be removed while in other embodiments, the damper 104 may be inserted through an unmodified ductwork and/or register boot. In some examples, the damper 104 may be inserted below or behind the register and, in these examples, the scavenger assembly 408 thereof (if any) may be similarly positioned relative to the register such that it is able to harvest energy from air passing through the duct work even when the register is closed. In some examples, the damper 104 may be integrated into the register unit, such that the register includes the damper and (optionally) the scavenger assembly 408. In this manner, installation of the damper 104 is facilitated as it is installed with the register and without needing a separate installation step. The system 100 may also be suitable for new construction homes and buildings where the HVAC system may be designed to work with the system 100.

FIG. 5 illustrates an expanded view of a damper module 406. The damper module 406 includes a housing 502 inside which is disposed a damper printed circuit board 506 coupled to an LED indicator light pipe 504. An adjustment knob 508 for assisting with installation and removal is coupled to an actuator nut 512. The adjustment knob 508 may further be used for manual actuation in the event of a malfunction. Gearbox bearings 516 are disposed on either side of the actuator nut 512. The drive motor 514, coupled to the drive gear 518 which is operationally coupled with the actuator nut 512, drives movement in the damper blade assembly 404. An actuator mount 510, actuator retainer 522, and motor retention spring 520 provides support for the actuator motor 514 inside the housing 502 which is sealed by the damper module cap 524. The motor retention spring 520 also acts as a spring-back when adjustment knob 508 is used during manual actuation.

FIG. 6 illustrates an expanded view of a scavenger module 410. The scavenger module 410 includes a housing 608 to support a battery cell cradle 606. A battery cover 602 secures one or more batteries 604 in the battery cradle 606. The scavenger module 410 further includes a power connector 610. The scavenger module 410 further includes a printed circuit board 612 for facilitating operation of the scavenger module 410. For example, the printed circuit board 612 is configured to receive and store energy harvested from the impeller. The printed circuit board 612 is also configured to manage distribution of power. The printed circuit board 612 is secured to the housing 608 by a cap 614. It should be appreciated that, although the scavenger module 404 is illustrated to include a single printed circuit board 612, the functionality of the printed circuit board 612 may also be separated into two or more printed circuit boards.

FIG. 7 is a block diagram of the example damper 104 of FIG. 1. The damper 104 includes a microcontroller 702 for facilitating communication and control of the damper 104 with control box 108. In one example, the microcontroller 702 is an 88MZ1000 manufactured by Marvel. However, it should be appreciated that any suitable microcontroller can be used. A damper actuator 712 receives control signals from the microcontroller 702 instructing the damper actuator 712 when to open and close the damper in order to allow air to pass by or to block air. In one example, the microcontroller 702 also may receive suitable data from the damper actuator 712. For example, a sensor coupled to the damper actuator 712 may measure torque generated by passing air and communicate the measured data to the microcontroller 702.

In one example, the microcontroller 702 may be configured to detect current spikes while the damper is opening or closing to prevent the damper from actuating when current spikes are detected.

The damper 104 may be configured to determine the position of the damper blade of damper actuator 712 and/or to control operation of the damper actuator 712 via a Hall Effect sensor. For example, one or more Hall Effect sensors may be coupled to the damper actuator 712 that moves the damper blade and be configured to communicate with the microcontroller 702. Here, the microcontroller 702 receives feedback signals from the Hall Effect sensors, where such feedback is indicative or representative of the position of the damper blade that is coupled to the damper actuator 712. Using this feedback, the microcontroller 702 may determine a position or orientation of the damper blade (of the damper actuator 712), for example, by correlating the feedback information to an actual damper position via a look up table or mathematical relationship or the like. The microcontroller 702 may also be configured to control operation of the damper actuator 712 via the sensed position of the damper blade. For example, the microcontroller 702 may determine the speed, distance, and/or direction at which the damper actuator 712 drives the damper blade via data received from the Hall Effect sensors.

A power management module 704 manages the collection and distribution of power. For example, the power management module 704 is configured to receive power from an energy harvesting device 708 as well as from a rechargeable battery 710. The power management module 704 also distributes power based on either the harvested energy or energy produced by the rechargeable battery to the controller and to the damper actuator 712. In one example, the power management module 704 may further be coupled to and receive power from an AC power supply 710.

The damper 104 includes a pushbutton 722 to enable a contractor or administrator to initiate a communication with

15

the control box **108** that will help identify the damper **104** for configuration purposes. The damper **104** also includes an LED indicator **714** that is configured to blink a corresponding zone color which can further assist a contractor or administrator in configuring the system **100** and setting up zones. In one example, the LED indicator **714** may keep blinking for a predefined time period such as 5 minutes to give the contractor sufficient time to identify the damper **104**. In another example, the LED indicator **714** may keep blinking until the pushbutton **712** is again pushed. In one example, a buzzer **716** may provide a contractor with an audible notification which may further assist with identifying the damper **104** during configuration. It should be appreciated that either an audible or a visual notification may be used as needed, or a combination of both. In addition to assisting with configuration, the push button **722**, the LED indicator **714**, and the buzzer **716** may further assist the contractor when troubleshooting the system **100**.

In one example, the damper **104** may further include one or more connectors for coupling to the microcontroller **702** for maintenance, debugging, configuration, and so on. In one example, the damper **104** includes a Joint Test Action Group (“JTAG”) connector **718** and a Universal Asynchronous Receiver/Transmitter (“UART”) connector **720**. In one example, the damper **104** may further include an encoder for converting signals into digital form.

FIG. **8** is a block diagram of an example temperature controller **106** of FIG. **1**. The temperature controller **106** includes a microcontroller **802** for facilitating communication and control of the temperature controller **106** with control box **108**. In one example, the microcontroller **802** is an 88MZ1000 manufactured by Marvel. However, it should be appreciated that any suitable microcontroller can be used. The microcontroller **802** includes a wireless onboard antenna to communicate temperature and humidity data to the control box **108**. The microcontroller **802** is further configured to communicate the temperature and humidity information to display **806**.

The display **806** is configured to communicate data to a user. For example, the display **806** communicates or displays, in addition to temperature and humidity information, battery level, a temperature set point as desired by a user, a “heating” icon to indicate a heating mode, a “cooling” icon to indicate a cooling mode, and a “fan” icon to indicate a fan mode. In one example, the display **806** is further configured to display an icon or text indicating that a user action is required via the homeowner computing device **120**. In one example, the display **806** is further configured to display an energy saving icon, indicating that due to an energy saving plan, a requested set point is not available.

In one example, the temperature controller **106** further includes one or more push buttons for enabling a user to provide input and set a temperature. It should be appreciated that such push buttons may also be provided via the display **806** using a touch screen interface. In one example, the display **806** may be further configured to display a current zone name.

The temperature controller **106** further includes a battery power supply **810** for powering the microcontroller **802**. The temperature controller **106** further includes a sensor **808** configured to detect the presence of a person nearby and communicate the information to the microcontroller **802**. In one example, the microcontroller **802** is configured to maintain the temperature controller **106** in a sleep mode to conserve the battery power supply **810** until a person is detected nearby, indicating that the person may wish to interact with the temperature controller **106**. At that point,

16

the microcontroller **802** “wakes up” the temperature controller **106** and turns on the display **806** in preparation for interaction with the person. In another example, the microcontroller **802** is configured to maintain the display **806** in an active or on state while no person is detected nearby, displaying current room temperature. The microcontroller **802** may be further configured to change the display **806** to communicate a “set temperature screen” when a person is detected as being nearby.

The temperature controller **106** further includes a pushbutton **812** to enable a contractor or administrator to initiate a communication from the temperature controller **106** that will help identify the temperature controller **106** for configuration purposes. In one example, a buzzer **816** may provide a contractor with an audible notification which may further assist with identifying the temperature controller **106** during configuration. In addition to assisting with configuration, the push button **812** and the buzzer **816** may further assist the contractor when troubleshooting the system **100**.

The temperature controller **106** further includes one or more connectors for coupling to the microcontroller **802** for maintenance, debugging, configuration, and so on. In one example, the temperature controller **106** includes a Joint Test Action Group (“JTAG”) connector **818** and a Universal Asynchronous Receiver/Transmitter (“UART”) connector **820**.

The temperature controller **106** further includes a “WiFi join” pushbutton **814** that enables the administrator computing device **122** to connect to the control box **108** and enter a router password.

In another example, the temperature controller **106** is configured as a sensor without any user input or user output/readout capabilities. For example, the temperature controller **106** may be configured to measure one or more parameters, such as temperature, humidity, presence of a gases such as carbon monoxide, light, allergens such as pollen, smoke, etc. to maintain the building or zones thereof at acceptable levels, which may be pre-set according to relevant safety standards and/or user defined levels. Here, the temperature controller **106** may be hard wired to the buildings power, or may instead be battery powered such as with a coin cell or similar device, and/or it may even be configured to be powered via solar power.

FIG. **9** is a block diagram of and control box **108** of FIG. **1**. The control box **108** includes a microcontroller **902**, including a wireless communication coordinator such as ZigBee, for coordinating wireless communications and managing functionality of the system **100**. In particular, the microcontroller **902** is configured to receive information from multiple temperature controllers **102** and to provide instructions to associated dampers **104** based on received information. The microcontroller **902** is also configured to provide operating signals to HVAC equipment. Interface connections **906** provide an interface for microcontroller **902** to send and receive data and various suitable inputs and outputs.

The control box **108** further includes an I/O expander **908** to provide additional HVAC output lines if needed. In one example, the I/O expander **908** is a serial to parallel converter. The control box **108** further includes a power source **910**. In one example, the power source **910** may be an AC power source. In another example, the power source **910** may include a rechargeable backup battery.

The control box **108** further includes one or more LEDs **912** for assisting a contractor with troubleshooting and configuration. For example, a combination of LEDs **912**, using a combination of colors, may provide indications with

respect to whether the wireless network is active, whether the control box **108** is connected to the server **124**, whether the various sensors are functioning properly, the status of the dampers **104**, the status of the temperature controllers **102**, and the status of the HVAC equipment **110**.

The control box **108** further includes a “WiFi join” pushbutton **914** that enables the administrator computing device **122** to connect to the control box **108** and enter a router password. The control box **108** further includes a “Reset” pushbutton **916** that enables users to restart the control box **108** if necessary. The control box **108** further includes a power source button **918** that enables a contractor to select, upon system setup, between an onboard supplied power source **910** and an external alternate power source.

The control box **108** further includes a settings data store **920** for storing various system **100** settings. For example, microcontroller **902** may receive and store in data store **920** settings received from the administrator computing device **122** in connection with the initial setup of the system **100**. The microcontroller **902** may also receive and store in settings data store **920** settings received from the homeowner computing device **120** in connection with user defined preferences. Table 1 lists an example set of parameters that may be received and stored in settings data store **920** as well as a description of the parameter, options for setting the parameter, and example factory default values for the parameters. It should be appreciated that additional suitable parameters may be included as necessary.

TABLE 1

Example System Parameters			
Parameter	Description	Options	Factory Default
System Name	Accepts a string of characters to be used for identifying the control box and its associated control system. Possible string terminators and illegal characters to be defined.	16 characters	Test_System
Server Update Period	Time period between Wi-Fi based server updates, in seconds	10-60 Sec	20
ZigBee Period	Time period of ZigBee communications for all ZigBee devices except ZigBee OA sensor. Impacts battery life and system response time. Time units are seconds.	1-300 Sec	5
ZigBee OAT Period	Time period of ZigBee communications for the outside air temperature sensor (OA sensor). Demo mode sets a period of 5 seconds. Standard operating times are 1, 2, or 3 hours. For app temperature updates, it is suggested to use local weather data rather than the actual OA sensor value, to avoid the perception of a slow sensor.	Demo or 1-3 Hours by integer values	Demo
ZigBee Missed Beacon Retries	Number of additional attempts at contacting a ZigBee mesh node. Impacts power consumption of system.	3-10	3
TC Screen Refresh Period	Time period between temperature controller screen refresh events of the temperature controller, not counting switch interrupt events, in seconds.	10-60 Sec	30
Temperature Display	Determines the temperature display units.	Fahrenheit Celsius	Fahrenheit
TC Data Display Style	Determines the amount and detail of data to be displayed on temperature controller screen. Simple = Temperature, Battery, and HVAC Equipment status only. Detail = Temperature, Battery, HVAC Equipment status, monthly utility bill associated with HVAC setting.	Simple or Detail	Detail (supports R&D data gathering and troubleshooting)
Damper ZigBee Mode Lock	Forces all dampers into ZigBee Router configuration. This will burn the most battery across the board, but will be useful for the R&D pilot, or to support troubleshooting. ZR Lock = ZigBee Router Functionality Locked ON, Automatic = ZigBee router or ZigBee End Device functionality, depending on scavenging strength and power budget.	ZR Lock or Automatic	ZR Lock (for R&D uses)
Priority Mode	Allows specific mode to interrupt active cycle. Priority options include: Automatic, Heating, Cooling, or Zone Weight Priority. Details to found in definitions section to follow.	Automatic Zone Weight Heating Cooling	Automatic
Zone 1 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 2 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 3 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 4 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 5 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 6 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 7 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 8 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 9 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 10 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 11Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone 12 Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Zone X _{1-i} (i = 99) Weight	Follow the Zone Weight Calculation (below).	10-90%, Δ5%	50%
Minimum On Stage Threshold	Minimum Zone Weight Required to initiate a Heating/Cooling or Fan call to the HVAC Equipment	0-90%, 5% increments	25%

TABLE 1-continued

Example System Parameters			
Parameter	Description	Options	Factory Default
A.H. Stage-Up Threshold	CFM Stage-up threshold, Y2 output to Air Handler or W2 to FF Furnace engaged when threshold % is reached. Set the percentage of ductwork you would want to be open before the control board will send a Y2 signal to the air handler to increase CFM or W2 signal to furnace to increase output capacity and CFM.	30-100%, 5% increments	50%
Heat Stage Threshold	Min leaving air temperature required for comfort at 30 degrees outside air temperature. This set point resets by ½ degree for every 1 degree change in outside air temperature. Sets the minimum supply air temperature in the heating mode. At the factory default the control board will maintain a 100 degrees F supply air temperature at 30 degrees F. outdoor temperature. The supply air temperature will raise or lower ½ degree F. for every 1 degree F. change in outdoor air temperature.	80-130 degrees F., 1 degree increments	100 degrees F.
Cool Stage Threshold	Max cooling supply air temp, Y2 is energized if this leaving air temperature is not reached with Y1 output. Sets the maximum supply air temperature allowable before bringing on second stage cooling. Does not reset with the outside air temperature sensor.	20-60 degrees F., 1 degree increments	55 degrees F.
Balance Point - outside air temperature sensor	Heat pump operates above BP set point and FF furnace operates below set-point. Set the outdoor temperature at which you want to lock the heat pump out and have the fossil fuel back up to take over on a call for heat. This setting is overridden by the "Heat Stage Threshold" function.	0-50 degrees F., 1 degree increments or "Lock in Backup Heat" for non-heat pump applications	30 degrees F.
Resistance Lockout - outside air temperature sensor	Aux Heat (Electric Resistance Heat) will be locked out when the outside air temperature exceeds this setting. Set the outdoor temperature at which you want to lock out the electric resistance heat.	0-40 degrees F., or "Lock in Aux" to allow electric aux heat staging regardless of outside air temperature	30 degrees F.
H.P. leaving air temperature Htg. Limit	High limit of heat pump leaving air temperature. Set the maximum allowable supply air temperature in heat pump mode.	100-125 degrees F., 1 degree F. steps	120 degree F.
Cooling leaving air temperature Low Temp	Cooling leaving air temperature low limit. Set the minimum supply air temperature in the cooling cycle to prevent the coil from freezing.	34-46 degrees F., 1 degree F. steps	42 degrees F.
Type of Backup Heat	Specify type of Aux "Backup" heat. Select the type of heat that will be initiated when the heat pump can no longer maintain the setting of the heat stage threshold.	Electric or Fossil Fuel	Electric
Humidification	Required Averaged Humidify throughout conditioned area	0-75%	35%
Backup Controls Fan	G output for fossil fuel heat operation True = "W", False = "W", "G". Select true if the backup heat source controls the fan internally or false if the control box needs to initiate the fan.	True or False	True
Dehumidifier Call Voltage	Required voltage to energize a dehumidification call. (Note: Leave setting at 24 V when not used.) Set to the dehumidification control voltage output on the dehumidistat control, Y.	0 Volt or 24 Volt	24 Volt
Secondary Purge Time	End-of-cycle purge time to diffuse residual heating or cooling. Set the amount of time in seconds to run the pump after a cycle to open all dampers. Typically 5 seconds per damper.	0-180 seconds, 10 second increments	60 Seconds
Dehumidification Cycle Time	Dehumidification "On Cycle" time limit to proven over-cooling of space once cooling set-points are reached (off cycle is fixed at 10 minutes). Set the maximum "ON" time for dehumidification cycle to prevent overcooling of the space. The "OFF" cycle is set at a fixed time of 10 minutes.	5-15 minutes, 5 minute increments	10 minutes
Cooling Low Ambient Lock-Out	Minimum outside air temperature that mechanical cooling is allowed to operate (locks out Y output). Set the outdoor temperature at which the cooling will no longer come on.	20-60, 1 degree F. increments	35
Rev Valve Energized	Heat pump rev valve energize in heating or cooling (Zone 1 HP stat always calls "O" for clg call). Set the mode in which the reversing valve is energized. Note: If the heat pump thermostat has a setting for	Cooling or Heating	Cooling

TABLE 1-continued

Example System Parameters			
Parameter	Description	Options	Factory Default
	reversing valve in the configuration mode, set the thermostat to energize the reversing valve in cooling.		
Use Balance Point for Electric	Allow Balance Point to be used on all electric system. True heat pump will shut down when ODT is below Balance Point setting.	True or False	False
Demo Mode Enable	Demo mode speeds up all HVAC timing sequences by a factor of 12. Used for demonstrations and for initial system commissioning. ZigBee and Wi-Fi time bases are unaffected and remain set by the parameter values.	True or False	False
Language Selection	Permits user to select language.	English, Spanish, French, Chinese, Japanese, Korean, German, etc.	English

It should be appreciated that the control box 108 may include additional components as well, such as solenoids, relays, and a power supply for providing power and/or control air to the various system HVAC elements. For example, relays may be active in the control box 108 to switch electrical power to the HVAC elements. As another example, to provide air from an air handling unit or pump to one of the air dampers 104, the microcontroller 902 activates (via an activation signal) a solenoid to switch air to an air damper 104.

In accordance with one embodiment of the present disclosure, the control box 108 may be accessed by an operator to aid the operator in manually selecting setting options. Such manual selecting includes the steps of powering up the control box 108, displaying a first set of options, selecting at least one of the options from the first set of options, displaying a second set of options, and selecting at least one of the options from the second set of options. The process of displaying a next set of options and selecting from the next set of options may continue until all available selections are made. Also, the homeowner computing device 120 and the administrator computing device 122 may function as an input/output indicator by displaying each thermostat call and the service currently being provided in accordance with an embodiment of the present invention. In one example, the administrator computing device 122 and the homeowner computing device 120 may be used to access the control box 108 and select such settings options.

In one example, control box 108 may further include a USB (universal serial bus) port. The USB port allows a wireless communications device, for example, a tablet computer, to interface to the control box 108. In accordance with an embodiment of the present invention, the control box 108 stores a history of operational data (a data log) which may be read out by a computing device via the USB port. Also, in accordance with an embodiment of the present invention, the USB port may be used to allow the control box 108 to interface with suitable home automation equipment (e.g., a home automation device). The control box 108 is designed with suitable “hooks” or APIs for integration with home automation packages. Data that may be output via the USB port to a home automation package include the last five events, the current damper states, the current service being provided, the current LAT, the current OA sensor, and any current thermostat or sensor requests. The home automation equipment may include a separate device with software that takes the data provided by the control box 108 and reports

the data to a remote user, email, or a web-based interface, for example. The user may have the capability to respond to the report in a similar manner in order to, for example, change the temperature in the home or turn off part of the HVAC system. The interface between the control box 108 and the home automation equipment may be wireless in accordance with various embodiments of the present invention.

Configuration and operation of system 100 may be further appreciated in view of the homeowner computing device 120 and the administrator computing device 122. FIG. 10 illustrates a block diagram of an example homeowner computing device 120 for enabling a homeowner or other user to interface with system 100. Homeowner computing device 120 includes a sign-in module 1002 for enabling a homeowner to sign in to an account. The sign-in module 1002 also enables a homeowner to sign up for a new account if it's the homeowner's first time using the homeowner computing device 120. As part of the sign-up process, the sign-in module 1002 requires the homeowner to select a wireless home network for accessing the control box 108. It should be appreciated that, although references are made herein with respect to a homeowner, any suitable user with proper access credentials may interface with homeowner computing device 120.

The homeowner computing device 120 further includes a dashboard module 1004. The dashboard module 1004 provides the homeowner with a centralized view of, and access to, the HVAC system for a home. For example, the dashboard module 1004 communicates to the homeowner the current temperature of the home. In one example, the dashboard module 1004 accesses weather through a third party service such as Google or Yahoo. The dashboard module 1004 further communicates to the homeowner a summary of different defined zones of the home. For example, the dashboard module 1004 displays, for each zone, the temperature in that particular zone, whether the zone is currently being heated, cooled, or neither, and whether the zone is locked or unlocked indicating whether the temperature of the zone can be adjusted. The dashboard module 1004 further enables a homeowner to select a specific zone and access more detailed information about the selected zone. The dashboard module 1004 further enables a homeowner to review the currently set heating and cooling schedule and to select a different defined schedule. The dashboard module 1004 further enables the homeowner to select a defined schedule in order to view more details or to

make edits. The dashboard module **1004** also provides a homeowner with an option of creating a new schedule.

The homeowner computing device **120** further includes a zone module **1006**. In response to a homeowner selecting a zone via the dashboard module **1004**, the zone module **1006** communicates an overview of the selected zone to the homeowner. For example, the zone module **1006** displays the temperature of the zone as well as heat and cool set points. In one example, both the heat and cool set points are displayed while the zone mode is set to auto, only the heating set point is displayed when the zone mode is set to heat, and the only the cool set point is displayed when the zone mode is set to cool. In one example, the zone module **1006** is further configured to display a humidity level for a selected zone. In one example, the zone module **1006** is further configured to display a status of the zone. In one example, the zone module **1006** is further configured to display the assigned schedule for the zone. For example, the zone module **1006** may be configured to display “30 minutes until cooling down to 65 F” if the zone is schedule to be cooled down to a temperature of 65 F in 30 minutes. The zone module **1006** also enables a homeowner to return to an overview of all of the zones provided by dashboard module **1004**.

In one example, the zone module **1006** enables a homeowner to quickly switch to viewing information about another zone without accessing the dashboard module **1004**. For example, the zone module **1006** may enable the homeowner to swipe to the left or right on a touch screen of the homeowner computing device **120** in order to change zone views.

It should be appreciated that “communicating” as used herein may include transmitting data to a display of the homeowner computing device **120** for a homeowner to view. In addition, “communicating” may also include other suitable forms or conveying information, such as audibly, by storing and communicating data electronically, and so on.

In one example, the zone module **1006** enables the homeowner to initiate a “zone hold” which occurs when a homeowner changes the set point to anything other than a set point in the schedule. When a hold occurs, the zone module **1006** changes the status of a zone to default hold. In one example, the default hold is a hold that lasts until the next scheduled profile is assigned. In one example, the zone module **1006** enables a homeowner to change the hold option. For example, the zone module **1006** may enable the homeowner to select one of several hold options including: “hold until next schedule,” “hold for an amount of time,” where the time is configurable, or “hold indefinitely.” In addition, the zone module **1006** may enable the homeowner to cancel the hold and revert back to the selected schedule.

The homeowner computing device **120** further includes a scheduling module **1008** configured to enable a homeowner to select a schedule to run for a zone. The scheduling module **1008** may provide one or more predefined schedules for a homeowner to choose from. For example, the scheduling module **1008** may provide a predefined “primary” schedule which may be a seven-day schedule and may be the most commonly selected schedule. The scheduling module **1008** may further provide a predefined “away” schedule for vacations and business trips, for example. The scheduling module **1008** may also provide a predefined “energy savings schedule” which may include parameters designed to maintain a certain comfort level in a zone while saving energy costs.

The scheduling module **1008** further enables a homeowner to view details about schedules, to edit existing

schedules, and to add new schedules. For example, the scheduling module **1008** may enable a homeowner to define specific days associated with a schedule, specific temperatures for certain defined times of the day such as “morning,” “away,” “arrive home,” and “sleep.” The scheduling module **1008** enables the homeowner to set different schedules for individual zones or to set a single schedule and apply it to all zones.

The homeowner computing device **120** further includes a messaging module **1010**. The messaging module **1010** is configured to communicate various types of messages to a homeowner that may be generated by the system **100**. For example, messaging module **1010** may be configured to receive “information” messages which are for information purposes only and require no action. In some examples, the messaging module **1010** may be configured to alert the end user about up-coming scheduled maintenance and/or appointments regarding the same. Messaging module **1010** may further be configured to receive “warning” messages which may require troubleshooting by the homeowner. The messaging module **1010** may further be configured to receive “error” messages which may require attention by a contractor. The messaging module **1010** may further be configured to receive “energy tip” messages which may inform the homeowner about potential ways to conserve energy. In one example, such “energy tip” messages may be generated by the computer data server **124** based on historical temperature data or other historical data and/or may suggest to the end user an adjustment based on such data (e.g., increase or decrease heating or cooling). The messaging module **1010** may further be configured to receive “success” messages indicating a contractor’s successful visit or system upgrade. It should be appreciated that the messaging module **1010** may be configured to receive other suitable types of messages that may or may not require specific actions by the homeowner or the contractor. For example, messaging module **1010** may be configured to provide current weather information and/or weather forecast information to the end user. In such examples where the messaging module **1010** provides current weather information and/or weather forecast information to the end user, “energy tips” may be provided to the messaging module **1010** to inform the end user if the weather is changing and/or suggest turning up or down the HVAC equipment **110** based on that information.

In one example, if a message does not require action including contractor assistance, the messaging module **1010** may be configured to provide the homeowner with an option to delete the message after it is read. In one example, if a message does require action including contractor assistance, the messaging module **1010** may be configured to provide the homeowner with an option to contact the contractor. For example, the messaging module **1010** may provide a homeowner with an option of either calling or emailing the contractor. If the homeowner selects the “call” option, the messaging module **1010** may automatically initiate a telephone call to the contractor. If the homeowner selects the “email” option, the messaging module **1010** may open an email template from the homeowner’s default email application and prepopulate the template with information presented in the received message including, for example, a diagnostics report, a description of any detected failures or issues, and/or a parts list of any parts needed to address or fix the issue. In one example, the messaging module **1010** may prepopulate the email address with the appropriate email address of a contractor associated with the homeowner’s account. In one example, the messaging module **1010**

may be configured to automatically contact the contractor, either by email or a telephone call, when a message that requires action including contractor assistance is generated. Thus, a self-diagnostic feature may be provided that alerts the contractor that something is wrong with the system **100**, and lets the contractor know the parts needed to fix the problem and may also provide the contractor with instructions for solving the problem as well. In some examples, the homeowner may order replacement parts or other products or services via the homeowner computing device **120**, for example, the messaging module **1010**. In some examples, the system **100** may be configured to alert the contractor of a predicted failure and order the necessary parts without the user's input.

The homeowner computing device **120** further includes a settings module **1012** for enabling a homeowner to access and adjust various suitable settings. For example, the settings module **1012** may enable a homeowner to add or delete other users and to grant them access to one or more zones within a location or to all zones within a specific location. In one example the settings module **1012** may enable a homeowner to view and edit contractor information. It should be appreciated that the settings module **1012** may further be configured to enable a homeowner to modify other suitable settings, including, for example, zone names, WiFi configuration, display preferences, access credentials and levels of users, and so on.

The system **100** may also include energy conservation functions whereby the end user is rewarded for conserving energy. The "energy tips" may advise the end user to adjust operation of the HVAC equipment **110** based on historical data. In some examples, these "energy tips" may be tied to energy supplier promotions and/or rebates. For example, an end-user's energy supplier may be notified that the end-user is conserving energy by following the "energy tips" such that the end user is eligible for promotions, rebates, reduced rates, etc. The "energy tips" may also provide the end user the option of whether to let the energy supplier remotely control the system **100** and/or the HVAC equipment **110**, for which the energy supplier may reward the end-user with energy discounts or rebates. For example, energy suppliers may offer rebates or discounts to end-users permit the energy supplier to control heating and cooling in the building (or one or more zones thereof) during peak power usage times.

FIG. 11 illustrates a block diagram of an example administrator computing device **122** for enabling a contractor, an energy supplier, or other systems administrator to interface with system **100**. Administrator computing device **122** includes a sign-in module **1102** configured to receive login credentials from a contractor and to grant access to the system **100** upon successfully validating the received credentials. If the contractor is accessing a system **100** for the first time, the sign-in module **1102** requires provisioning of the system **100**. For example, the sign-in module **1102** requires the contractor to select from a list of detected control boxes **108** and to provide an identifier such as serial number, or other suitable information, to ensure that the contractor is accessing the correct control box **108**. In one example, the sign-in module **1102** may require the contractor to perform some interaction with the control box **108**, such as to push a button or observe a flashing light in order to further ensure that the contractor is accessing the correct control box **1108**.

The administrator computing device **122** further includes a dashboard module **1104** for providing information about the system **100** that the contractor can use for maintenance, monitoring, and troubleshooting purposes. The dashboard

module **1104** may also be configured to permit the contractor or energy supplier to control the system **100** and/or the HVAC equipment **110** for example, for energy conservation purposes.

If a contractor is accessing a control box **108** for the first time, a setup module **1106** enables a contractor to set up a system by defining hardware of the system **100** and associating the hardware with different zones. For example, the setup module **1106** may enable a contractor to drag and drop hardware, such as dampers and temperature controllers, from a list of available unassigned hardware and to associate the hardware with specific zones. Thus, zones can be defined in a variety of ways including a single room of a home, multiple rooms, a portion of a room, and so on. In one example, the setup module **1106** enables a contractor to initiate an LED indicator of a selected hardware to flash in order to ensure that the correct hardware is being assigned to a specific zone. In one example, the setup module **1106** enables a contractor to define new zones, edit zones, or delete zones.

The administrator computing device **122** further includes messaging module **1108** configured to enable a contractor to draft and communicate messages to a homeowner about the status of the system **100**. In one example, the messaging module **1108** may include one or more predefined messages that the contractor can select from and send to the homeowner. In some examples, the messaging module **1108** may be configured to alert the contractor and/or energy supplier about up-coming scheduled maintenance and/or appointments regarding the same.

In some examples, the system **100** is configured to predict and address failures before they occur. For example, the system **100** may be configured to sense changes in operation of various components of the system **100** and/or the HVAC equipment **110** or count cycles to determine the likelihood of something failing. Upon determination that failure is likely, the system **100** may be configured to order a replacement part and/or schedule preventative maintenance appointment. For example, if it is known that a certain component of the damper **104** is susceptible to failure after a certain number of cycles or after being in operation a certain amount of time (e.g., that the damper motor or any other part begins to weaken after a certain number of cycles (i.e., X cycles)), then the system **100** may be configured to make a recommendation to the installer that this certain component should be addressed (e.g., recommend to the installer that the motor or other part should be replaced) to prevent a future failure before the components actually breaks and causes an issue.

FIG. 12 is a schematic diagram of an example computer **1200** for implementing the example homeowner computing device **120** and the administrator computing device **122** of FIG. 1. The example computer **1200** is intended to represent various forms of digital computers, including laptops, desktops, handheld computers, tablet computers, smartphones, servers, and other similar types of computing devices. Computer **1200** includes a processor **1202**, memory **1204**, a storage device **1206**, and a communication port **1208**, operably connected by an interface **1222** via a bus **1210**.

Processor **1202** processes instructions, via memory **1204**, for execution within computer **1200**. In an example embodiment, multiple processors along with multiple memories may be used.

Memory **1204** may be volatile memory or non-volatile memory. Memory **1204** may be a computer-readable medium, such as a magnetic disk or optical disk. Storage device **1206** may be a computer-readable medium, such as floppy disk devices, a hard disk device, optical disk device,

a tape device, a flash memory, phase change memory, or other similar solid state memory device, or an array of devices, including devices in a storage area network of other configurations. A computer program product can be tangibly embodied in a computer readable medium such as memory 1204 or storage device 1206.

Computer 1200 can be coupled to one or more input and output devices such as a display 1214, a printer 1216, a scanner 1218, and a mouse 1220.

To the extent that the term “includes” or “including” is used in the specification or the claims, it is intended to be inclusive in a manner similar to the term “comprising” as that term is interpreted when employed as a transitional word in a claim. Furthermore, to the extent that the term “or” is employed (e.g., A or B) it is intended to mean “A or B or both.” When the applicants intend to indicate “only A or B but not both” then the term “only A or B but not both” will be employed. Thus, use of the term “or” herein is the inclusive, and not the exclusive use. See, Bryan A. Garner, A Dictionary of Modern Legal Usage 624 (2d. Ed. 1995). Also, to the extent that the terms “in” or “into” are used in the specification or the claims, it is intended to additionally mean “on” or “onto.” Furthermore, to the extent the term “connect” is used in the specification or claims, it is intended to mean not only “directly connected to,” but also “indirectly connected to” such as connected through another component or components.

While the claimed subject matter of the present application has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the claimed subject matter. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the claimed subject matter without departing from its scope. For example, any system 100 component described herein could be of either wired or wireless connection, according to various embodiment. Therefore, it is intended that the claimed subject matter not be limited to the particular embodiment disclosed, but that the claimed subject matter will include all embodiments falling within the scope of the appended claims.

What is claimed is:

1. A damper for an HVAC system configured to distribute airflow through at least one air duct, the damper comprising:
 - a rail assembly for providing support to the damper and securing and sealing the damper on the air duct;
 - a damper blade assembly for regulating the amount of airflow passing through the air duct, the damper blade assembly having blade that is movable between an open position and a closed position;
 - a damper module configured to control an orientation of the blade between the open position and the closed position;
 - a scavenger assembly removably attached to the rail assembly and configured to harvest energy from airflow passing by the damper inside the air duct, wherein the

scavenger assembly, when detached from the rail assembly, may be positioned at a first location within the air duct that is spaced apart from a second location where the rail assembly is installed on the air duct; and a scavenger module configured to store power generated from energy harvested by the scavenger assembly and to supply power to the damper module for positioning the blade.

2. The damper of claim 1, wherein the damper operates in a scavenger mode using only power generated by the scavenger assembly where airflow is greater than or equal to a predefined maximum rate.

3. The damper of claim 2, further comprising a supplemental power source configured to supply power to the damper where airflow is less than the predefined maximum rate.

4. The damper of claim 3, wherein the damper operates in a supplemental power mode using power supplied only by the supplemental power source where air flow is less than or equal to a predefined minimum rate, wherein the predefined minimum rate is less than the predefined maximum rate.

5. The damper of claim 4, wherein the damper operates in a hybrid power mode using power supplied by both the scavenger assembly and the supplemental power source where airflow is less than the predefined maximum rate and greater than the predefined minimum rate.

6. The damper of claim 3, wherein the supplemental power source is selected from the group consisting of a rechargeable battery and an external power source hard-wired to the damper, and combinations of the same.

7. The damper of claim 1, wherein the scavenger assembly includes an impeller that rotates as airflow passes by, and wherein the scavenger module is configured to translate the rotation of the impeller into power.

8. The damper of claim 7, wherein the impeller is configured as an anemometer for measuring velocity of airflow.

9. The damper of claim 8, wherein the damper determines whether to operate using a supplemental source of power based on feedback indicative of velocity of airflow.

10. The damper of claim 8, wherein the damper module adjusts orientation of the blade based on feedback indicative of velocity of airflow.

11. The damper of claim 7, wherein the impeller does not boost airflow through the air duct.

12. The damper of claim 1, wherein the rail assembly is secured over a removed portion of the air duct.

13. The damper of claim 1, wherein the damper module includes a sensor configured to measure the rate at which the damper module actuates the blade.

14. The damper of claim 13, wherein the damper module includes a controller that is in communication with the sensor and is configured to determine position of the blade from feedback received from the sensor.

15. The damper of claim 13, wherein the sensor is at least one Hall Effect sensor.

* * * * *