



(86) Date de dépôt PCT/PCT Filing Date: 2008/09/05  
(87) Date publication PCT/PCT Publication Date: 2009/03/12  
(85) Entrée phase nationale/National Entry: 2010/02/25  
(86) N° demande PCT/PCT Application No.: EP 2008/007414  
(87) N° publication PCT/PCT Publication No.: 2009/030508  
(30) Priorité/Priority: 2007/09/07 (EP07075776.0)

(51) Cl.Int./Int.Cl. *C07D 307/46* (2006.01),  
*C10L 1/00* (2006.01)  
(71) Demandeur/Applicant:  
FURANIX TECHNOLOGIES B.V., NL  
(72) Inventeurs/Inventors:  
GRUTER, GERARDUS JOHANNES MARIA, NL;  
MANZER, LEO ERNEST, US  
(74) Agent: GOWLING LAFLEUR HENDERSON LLP

(54) Titre : ETHERS D'HYDROXYMETHYLFURFURAL OBTENUS A PARTIR DE SUCRES OU DE HMF ET D'ALCOOLS MIXTES

(54) Title: HYDROXYMETHYLFURFURAL ETHERS FROM SUGARS OR HMF AND MIXED ALCOHOLS

(57) **Abrégé/Abstract:**

Accordingly, the current invention provides a method for the manufacture of a mixture of 5-hydroxymethylfurfural ethers by reacting a hexose-containing starting material or HMF with mixed alcohols in the presence of an acid catalyst.



## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
12 March 2009 (12.03.2009)

PCT

(10) International Publication Number  
**WO 2009/030508 A2**

(51) International Patent Classification:  
C07D 307/46 (2006.01) C10L 1/00 (2006.01)

(74) Agent: KORTEKAAS, M.C.J.A.; Exter Polak & Char-  
louis B.V., P.O. Box 3241, 2280 GE Rijswijk (NL).

(21) International Application Number:  
PCT/EP2008/007414

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:  
5 September 2008 (05.09.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
07075776.0 7 September 2007 (07.09.2007) EP

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): FU-  
RANIX TECHNOLOGIES B.V. [NL/NL]; Zeker-  
ingstraat 29, NL-1014 BV Amsterdam (NL).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): GRUTER, Gerar-  
dus, Johannes, Maria [NL/NL]; 14 Asterkade, NL-2106  
BA Heemstede (NL). MANZER, Leo, Ernest [US/US];  
714 Burnley Road, Wilmington, DE 19803 (US).

Published:

— *without international search report and to be republished upon receipt of that report*



WO 2009/030508 A2

(54) Title: HYDROXYMETHYLFURFURAL ETHERS FROM SUGARS OR HMF AND MIXED ALCOHOLS

(57) Abstract: Accordingly, the current invention provides a method for the manufacture of a mixture of 5-hydroxymethylfurfural ethers by reacting a hexose-containing starting material or HMF with mixed alcohols in the presence of an acid catalyst.

Title: Hydroxymethylfurfural ethers from sugars or HMF and mixed alcohols

5

### Technical Field

The present invention concerns a method for the manufacture of a mixture of 5-hydroxymethylfurfural (5-(hydroxymethyl)-2-furaldehyde, or HMF) ethers from biomass.

10

### Background Art

Fuel, fuel additives and various chemicals used in the petrochemical industry are derived from oil, gas and coal, all finite sources. Biomass, on the other hand, is considered a renewable source. Biomass is biological material (including biodegradable wastes) which can be used for the production of fuels or for industrial production of e.g. fibres, chemicals or heat. It excludes organic material which has been transformed by geological processes into substances such as coal or petroleum.

15

Production of biomass derived products for non-food applications is a growing industry. Bio-based fuels are an example of an application with strong growing interest..

20

Biomass contains sugars (hexoses and pentoses) that may be converted into value added products. Current biofuel activities from sugars are mainly directed towards the fermentation of sucrose or glucose into ethanol or via complete breakdown via Syngas to synthetic liquid fuels. EP 0641 854 describes the use of fuel compositions comprising of hydrocarbons and/or vegetable oil derivatives containing at least one glycerol ether to reduce particulate matter emissions.

25

More recently, the acid catalysed reaction of fructose has been re-visited, creating HMF as an intermediate of great interest. Most processes investigated have the disadvantage that HMF is not very stable at the reaction conditions required for its formation. Fast removal from the water-phase containing the sugar starting material and the acid catalyst has been viewed as a solution for this problem. Researchers at the University of Wisconsin-Madison have developed a process to make HMF from fructose. HMF can be converted into monomers for plastics, petroleum or fuel extenders, or even into fuel itself. The process by prof. James Dumesic and co-workers first dehydrates the fructose in an aqueous phase with the use of an acid catalyst (hydrochloric acid or an acidic ion-exchange resin). Salt is added to salt-out

30

35

the HMF into the extracting phase. The extracting phase uses an inert organic solvent that favors extraction of HMF from the aqueous phase. The two-phase process operates at high fructose concentrations (10 to 50 wt %), achieves high yields (80% HMF selectivity at 90% fructose conversion), and delivers HMF in a separation-friendly solvent ( DUMESIC, James  
5 A, et al. "Phase modifiers promote efficient production of Hydroxymethylfurfural from fructose" . Science. 30 juni 2006, vol.312, no.5782, p.1933-1937). Although the HMF yields from this process are interesting, the multi-solvent process has cost-disadvantages due to the relatively complex plant design and because of the less than ideal yields when cheaper and less reactive hexoses than fructose, such as glucose or sucrose, are used as a starting  
10 material. HMF is a solid at room temperature which has to be converted in subsequent steps to useful products. Dumesic has reported an integrated hydrogenolysis process step to convert HMF into dimethylfuran (DMF), which is assumed to be an interesting gasoline additive.

15 In WO 2006/063220 a method is provided for converting fructose into 5- ethoxymethylfurfural (EMF) at 60 °C, using an acid catalyst either in batch during 24 hours or continuously via column elution during 17 hours. Applications of EMF were not discussed.

Also in copending patent application PCT/EP2007/002145 the manufacture of HMF ethers  
20 are described, including the use of such ethers as fuel or fuel additive. Indeed, both the methyl ether and the ethyl ether (methoxymethylfurfural, or MMF; ethoxyethylfurfural or EMF) were prepared and tested. The invention of the copending patent application, however, was limited to the use of primary aliphatic alcohols, and preferably primary C1-C5 alcohols. No examples were provided with mixed alcohols e.g., a mixture of one alcohol containing at least  
25 5 vol.% of another alcohol. Although MMF and EMF are useful as fuel or fuel additive, the inventors found that the ethers leave room for improvement, in particular when used in higher concentration blends with fuels such as gasoline, kerosene, diesel, biodiesel or green diesel. The inventors have therefore set out to overcome this shortfall.

30 Surprisingly, the inventors have found that ethers of HMF obtained from mixtures of alcohols have superior blending properties compared to ethers obtained from single alcohol ether analogs.

The ethers of HMF with these alcohols may be produced in a reasonable yield from hexose  
35 containing feedstock or from HMF, with reduced levels of by-product formation and in a manner that does not require cumbersome process measures (such as 2-phase systems) or lengthy process times.

Disclosure of Invention

Accordingly, the current invention provides a method for the manufacture of a mixture of 5-hydroxymethylfurfural ethers by reacting a hexose-containing starting material or HMF with mixed alcohols in the presence of an acid catalyst.

When the reaction product of the above method is used as such or when it is used as an intermediate for a subsequent conversion, the selectivity of the reaction is preferably high as the product is preferably pure. However, when the reaction product of the above method is used as a fuel, a fuel additive or as a fuel or a fuel additive intermediate, the reaction product does not necessarily need to be pure. Indeed, in the preparation of fuel and fuel additives from biomass, which in itself is a mixture of various monosaccharides, disaccharides and polysaccharides, the reaction product may contain non-interfering components such as levulinic acid derivatives and/or derivatives of pentoses and the like. For ease of reference, however, the method and the reaction product are described in terms of the reaction of a hexose-containing starting material, resulting in an ether of HMF. Also within the scope of the invention is the reaction of HMF with the branched alcohol, since HMF is believed to be produced as intermediate from the hexose-containing starting material.

The current invention also provides for the use of the reaction product made according to the present invention as fuel or as fuel additive. Fuels for blending with the product of the present invention include but are not limited to gasoline and gasoline-ethanol blends, kerosene, diesel, biodiesel (refers to a non-petroleum-based diesel fuel consisting of short chain alkyl (methyl or ethyl) esters, made by transesterification of vegetable oil, which can be used (alone, or blended with conventional petrodiesel), Fischer-Tropsch liquids (for example obtained from GTL, CTL or BTL gas-to-liquids/coal-to-liquids/biomass to liquids processes), diesel-biodiesel blends and green diesel and blends of diesel and/or biodiesel with green diesel (green diesel is a hydrocarbon obtained by hydrotreating biomass derived oils, fats, greases or pyrolysis oil; see for example the UOP report OPPORTUNITIES FOR BIORENEWABLES IN OIL REFINERIES FINAL TECHNICAL REPORT, SUBMITTED TO: U.S. DEPARTMENT OF ENERGY (DOE Award Number: DE-FG36-05GO15085). The product is a premium diesel fuel containing no sulfur and having a cetane number of 90 to 100). Fuels for blending with the product of the present invention may also include one or more other furanics, wherein the expression furanics is used to include all derivatives of furan and tetrahydrofuran. The invention also provides a fuel composition comprising a fuel element as described above and the reaction product made according to the present invention.

### Mode(s) for Carrying Out the Invention

Biomass resources are well known. The components of interest in biomass are the mono-, di- or polysaccharides (hereinafter referred to as hexose-containing starting material). Suitable  
5 6-carbon monosaccharides include but are not limited to fructose, glucose, galactose, mannose and their oxidized, reduced, etherified, esterified and amidated derivatives, e.g. aldonic acid or alditol, with glucose being the most abundant, the most economic and therefore the most preferred monosaccharide, albeit less reactive than fructose. On the other hand, the current inventors have also succeeded to convert sucrose, which is also available  
10 in great abundance. Other disaccharides that may be used include maltose, cellobiose and lactose. The polysaccharides that may be used include cellulose, inulin (a polyfructan), starch (a polyglucan) and hemi-cellulose. The polysaccharides and disaccharides are converted into their monosaccharide component(s) and dehydrated during the manufacture of the 5-HMF ether.

15

The mixture of alcohols used in the method of the current invention is typically a mixture of two or more monoalcohols, having a primary, secondary or tertiary hydroxyl group. Suitable alcohols have 1 to 20 carbon atoms, preferably 1 to 8 carbon atoms, and may be selected from the group comprising methanol, ethanol, and any of the isomers of propanol up to  
20 octanol. Of particular importance is the presence of a second alcohol, again having 1 to 20 carbon atoms, but being different from the first alcohol. This second alcohol needs to be present in an amount of at least 5 vol.%, preferably 10 vol.%, more preferably at least 15 vol.% in order to disturb the crystallization of the reaction product. Suitable mixtures therefore include methanol and ethanol, in a volume ratio of 5:95 to 95:5, preferably of 10:90 to 90:10,  
25 more preferably of 15:85 to 85:15. This means that "contaminated" ethanol may be used, to produce a product that even outperforms EMF in usefulness. Synthetic alcohols may be used as well, e.g., alcohols made via the Guerbet reaction (e.g., 2-ethylhexanol, prepared from butanol; "Selective synthesis of 2-ethyl-1-hexanol from n-butanol through the Guerbet reaction by using bifunctional catalysts based on copper or palladium precursors and sodium  
30 butoxide", by Carlo Carlini, Journal of Molecular Catalysis A: Chemical 212 (2004) 65–70), which therefore typically comprise a higher alcohol in combination with the lower (starting) alcohol.

Obviously, also a mixture of three or more alcohols may be used, as long as the total amount  
35 of the second and further alcohol is at least 5 vol.% in the alcohol mixture.

The amount of alcohol mixture used during the manufacture of the HMF ether is preferably at least equimolar on the hexose content of the feedstock, but typically is used in much greater excess. Indeed, the alcohol mixture (such as 50/50 butanol/ethanol) may be used as solvent or co-solvent. In such a case, a sufficient amount of alcohol is present to form the HMF ether.

5 As the alcohols have different reactivities in the etherification reaction, the ether product ratio is not necessarily equal to the mixed alcohol feed ratio.

The acid catalyst in the method of the present invention can be selected from amongst (halogenated) organic acids, inorganic acids, Lewis acids, ion exchange resins and zeolites  
10 or combinations and/or mixtures thereof. It may be a homogeneous catalyst, but heterogeneous catalysts (meaning solid) are preferred for purification reasons. The HMF ethers can be produced with a protonic, Brønsted or, alternatively, a Lewis acid or with catalysts that have more than one of these acidic functionalities.

15 The protonic acid may be organic or inorganic. For instance, the organic acid can be selected from amongst oxalic acid, levulinic acid, maleic acid, trifluoro acetic acid (triflic acid), methansulphonic acid or para-toluenesulphonic acid. Alternatively, the inorganic acid can be selected from amongst (poly)phosphoric acid, sulphuric acid, hydrochloric acid, hydrobromic acid, nitric acid, hydroiodic acid, optionally generated in situ.

20

Certain salts may be used as catalyst, wherein the salt can be any one or more of  $(\text{NH}_4)_2\text{SO}_4/\text{SO}_3$ , ammonium phosphate, pyridinium chloride, triethylamine phosphate, pyridinium salts, pyridinium phosphate, pyridinium hydrochloride/hydrobromide/perbromate, DMAP, aluminium salts, Th and Zr ions, zirconium phosphate, Sc and lanthanide ions such  
25 as Sm and Y as their acetate or trifluoroacetate (triflate) salt, Cr-, Al-, Ti-, Ca-, In-ions,  $\text{ZrOCl}_2$ ,  $\text{VO}(\text{SO}_4)_2$ ,  $\text{TiO}_2$ , V-porphyrine, Zr-, Cr-, Ti-porphyrine.

Lewis acids selected as dehydration catalyst can be any one of  $\text{ZnCl}_2$ ,  $\text{AlCl}_3$ ,  $\text{BF}_3$ .

30 Ion exchange resins can be suitable dehydration catalysts. Examples include Amberlite™ and Amberlyst™, Diaion™ and Levatit™. Other solid catalyst that may be used include natural clay minerals, zeolites, supported acids such as silica impregnated with mineral acids, heat treated charcoal, metal oxides, metal sulfides, metal salts and mixed oxides and mixtures thereof. If elevated reactions temperatures are used, as defined hereafter, then the  
35 catalyst should be stable at these temperatures.

An overview of catalysts that may be used in the method of the current invention may be found in Table 1 of the review article prepared by Mr. Lewkowski: "Synthesis, chemistry and applications of 5-hydroxymethylfurfural and its derivatives" Arkivoc. 2001, p.17-54.

5 The amount of catalyst may vary, depending on the selection of catalyst or catalyst mixture. For instance, the catalyst can be added to the reaction mixture in an amount varying from 0.01 to 40 mole % drawn on the hexose content of the biomass resource, preferably from 0.1 to 30 mole %, more preferably from 1 to 20 mole %.

10 In the preferred embodiment, the catalyst is a heterogeneous catalyst.

The temperature at which the reaction is performed may vary, but in general it is preferred that the reaction is carried out at a temperature from 50 to 300 degrees Celsius, preferably from 125 to 250 degrees Celsius, more preferably from 150 to 225 degrees Celsius. In  
15 general, temperatures higher than 300 are less preferred as the selectivity of the reaction reduces and as many by-products occur, inter alia caramelisation of the sugar. Performing the reaction below the lowest temperature is also less preferable because of the low reaction rate. If the reactions are carried out above the boiling temperature of water, then the reactions are preferably carried out under pressure, e.g., 10 bar nitrogen or higher.

20

The hexose-containing starting material is typically dissolved or suspended in a solvent which can be the mixed alcohol reactant, in order to facilitate the reaction. The solvent system may be one or more selected from the group consisting of water, sulfoxides, preferably DMSO, ketones, preferably methyl ethylketone, methylisobutylketone and acetone, ethylene glycol  
25 ethers, preferably diethyleneglycol dimethyl ether (diglyme). Also so-called ionic liquids may be used. The latter refers to a class of inert ionic compounds with a low melting point, which may therefore be used as solvent. Examples thereof include e.g., 1-H-3-methyl imidazolium chloride, discussed in "Dehydration of fructose and sucrose into 5-hydroxymethylfurfural in the presence of 1-H-3-methyl imidazolium chloride acting both as solvent and catalyst", by  
30 Claude Moreau et al, Journal of Molecular Catalysis A: Chemical 253 (2006) 165-169.

A sufficient amount of solvent is preferably present to dissolve or suspend the starting material and to limit undesired side-reactions.

35 The method of the current invention may be carried out in a batch process or in a continuous process, with or without recycle of (part of) the product stream to control the reaction temperature (recycle via a heat exchanger). For instance, the method of the invention can be



performed in a continuous flow process. In such method, homogenous catalysts may be used and the residence time of the reactants in the flow process is between 0.1 second and 10 hours, preferably from 1 second to 1 hours, more preferably from 5 seconds to 20 minutes.

- 5 Alternatively, the continuous flow process may be a fixed bed continuous flow process or a reactive (catalytic) distillation process with a heterogeneous acid catalyst. To initiate or regenerate the heterogeneous acid catalyst or to improve performance, an inorganic or organic acid may be added to the feed of the fixed bed or reactive distillation continuous flow process. In a fixed bed process, the liquid hourly space velocity (LHSV) can be from 1 to 10 1000, preferably from 5 to 500, more preferably from 10 to 250 and most preferably from 25 to 100 min<sup>-1</sup>.

The above process results in a stable HMF ether, which can then be used as such or be converted into a further derivative before being used as fuel and/or as fuel additive. The 15 inventors are of the opinion that some of the products prepared by the method of the current invention are actually new. Thus, the mixed ethers made with mixed alcohols, are new and are excellent fuel components or fuel additives. Since these alcohols may be made from biomass, this might open a class of products that are fully biomass-derived. Accordingly, these new ethers are claimed as well.

20

The mixed HMF ethers of the invention can also be used as or can be converted to compounds that can be used as solvent, as monomer in a polymerization (such as 2,5-furan dicarboxylic acid or FDCA), as fine chemical or pharmaceutical intermediate, or in other applications. Oxidation of the mixed HMF ethers using an appropriate catalyst under 25 appropriate conditions such as for example described for p-xylene with a NHPI/Co(OAc)<sub>2</sub>/MnOAc)<sub>2</sub> catalyst system in Adv. Synth. Catal. 2001, 343, 220-225 or such as described for HMF with a Pt/C catalyst system at pH < 8 in EP 0 356 703 or or such as described for HMF with a Pt/C catalyst system at pH > 7 in FR 2 669 634, all with air as an oxidant, resulted in the formation of 2,5- Furan dicarboxylic acid (FDCA).

30

The invention further concerns the use of the mixed HMF ethers prepared by the method of the current invention as fuel and/or as fuel additive. Of particular interest is the use of the mixed ethers in diesel, biodiesel or "green diesel", given its (much) greater solubility therein than ethanol. Conventional additives and blending agents for diesel fuel may be present in 35 the fuel compositions of this invention in addition to the above mentioned fuel components. For example, the fuels of this invention may contain conventional quantities of conventional additives such as cetane improvers, friction modifiers, detergents, antioxidants and heat

stabilizers, for example. Especially preferred diesel fuel formulations of the invention comprise diesel fuel hydrocarbons and HMF ether as above described together with peroxidic or nitrate cetane improvers such as ditertiary butyl peroxide, amyl nitrate and ethyl hexyl nitrate for example.

5

Examples are enclosed to illustrate the method of the current invention and the suitability of the products prepared therefrom as fuel. The examples are not meant to limit the scope of the invention.

### 10 Example 1. Mixed ether formation – batch experiment

In a 7.5 ml batch reactor, 0.053 mmol fructose in methanol/ethanol/n-butanol/water 23/45/23/9 v/v/v/v, was reacted for 1 hour at a temperature of 150 degrees Celsius with 9 mg acid catalyst. Four furan peaks were observed in the UV spectrum. Mass spectrometry  
15 identified these products as HMF, methoxymethyl furfural (MMF), ethoxymethyl furfural (EMF) and n-butoxymethylfurfural (nBMF). Also levulinic acid (LA) was found. Selectivities and conversions for catalysts used in this example can be found in table below.

Conversion of substrate, selectivity and yield of furan derivatives were calculated according  
20 to the following formulae:

$$X = 100 * m_r \text{ substrate} / m_0 \text{ substrate}$$

X conversion (%)

$m_r \text{ substrate}$  amount of reacted substrate (mg)

$m_0 \text{ substrate}$  amount of substrate in feed (mg)

25

$$S_{\text{compound}} = 100 * n_r \text{ substrate} / n_0 \text{ substrate}$$

$S_{\text{compound}}$  selectivity to compound (%)

$n_r \text{ substrate}$  moles of substrate reacted

$n_0 \text{ substrate}$  moles of substrate in feed

30

$$\text{Yield} = 100 * n_{\text{product}} / n_0 \text{ substrate}$$

Yield yield (%)

$n_{\text{product}}$  moles of product formed

35 Table 1. Conversion and selectivities for the dehydration of fructose in the presence of mixed alcohols in batch.

Cat	Conversion [%]	s HMF [%]	s EMF [%]	s MMF [%]	s nBuMF [%]	s LA [%]
CrCl <sub>2</sub>	91.6	9.7	10.5	10.0	2.8	4.8
Ce(IV) triflate hydrate	97.5	2.4	13.5	10.2	4.4	2.7
Amberlyst36Dry	99.7	4.2	17.6	14.5	4.2	6.6
Amberlyst36Wet	99.8	10.2	18.5	16.5	4.1	14.9

### Example 2. Mixed ethers formation from fructose (or glucose) and mixed alcohols-continuous flow experiment

5 A 1.25 wt% solution of sugar (Frc or Glc) in methanol/ethanol/n-butanol/water 23/45/23/9 v/v/v/v, was flowed through a fixed bed (200  $\mu$ l) of a catalyst at 190 °C. Flow rates were selected such to achieve a space velocity of 0.25 or 0.5 min<sup>-1</sup>, i.e. a contact time of 2 or 4 min.

In all cases tBMF was detected by HPLC and identified by LC-MS (CI) in the effluent stream.

10 Conversion of substrate, selectivity and yield of furan derivatives were calculated using the same method as for the batch reactions.

Table 2. Conversion and selectivities for the dehydration of fructose in the presence of mixed alcohols in flow.

15

Substrate	Cat	Contact time [min]	Space velocity [min <sup>-1</sup> ]	TOS [min]	Conversion [%]	sEthers [%]	S EMF [%]	S MMF [%]	S nBuMF [%]	S HMF [%]
Frc	Bentonite	0.7	1.5	80	84.6	33.7	13.4	18.1	2.2	54.4
Frc	Bentonite	4.0	0.3	80	98.8	26.6	1.4	19.9	5.3	4.4
Frc	H <sub>2</sub> SO <sub>4</sub>	11.3	0.1	105	87.6	40.3	15.1	21.5	3.7	3.0
Frc	H <sub>2</sub> SO <sub>4</sub>	13.2	0.1	105	78.9	79.1	29.3	42.7	7.2	7.3
Glc	Bentonite	3.1	0.3	70	97.7	30.6	11.1	16.5	2.9	3.3
Glc	Bentonite	0.4	2.5	70	87.7	21.4	8.4	11.5	1.5	18.1
Glc	Bentonite	3.1	0.3	80	97.6	33.5	12.2	18.1	3.2	3.6
Glc	Bentonite	0.4	2.5	80	87.7	20.4	8.0	11.0	1.4	18.6

### Example 3

In a batch experiment, 0.36 mmol of substrate (glucose, fructose or HMF) and 6.5 mg of a solid acid catalyst were mixed in a reactor coated inside with Teflon. 0.8 ml of alcohols mixture (Methanol, Ethanol and n-Butanol with 1/2/1 volume ratio) was added and pressurized at 12.5 bar with nitrogen. The reaction was performed at different temperatures and different reaction time. Four main peaks were observed in the UV spectrum and identified as HMF, 5-(ethoxymethyl)furfural (EMF), 5-(methoxymethyl)furfural (MMF) and 5-(butoxymethyl)furfural nBuMF. In this experiment and in the experiment of Example 4, the selectivity was calculated slightly different, based on the formula:

20

25

$$\text{Selectivity} = 100 * n_t(\text{product}) / [n_0(\text{substrate}) - n_t(\text{substrate})]$$

Where:

$n_0$ - the initial number of moles

$n_t$ - the number the moles of a compound at time "t".

5

The results are listed in Table 3.

Table 3. Conversion (Conv.) of glucose or fructose and selectivities (S) to furan compounds, in the presence of different solid acid catalysts at 1 h and 150 °C.

10

Subst.	Catalyst	Conv. (%)	s HMF (%)	s EMF (%)	s MMF (%)	s nBuMF (%)
Fructose	Zeolite $\beta$	81.8	2.9	14.9	14.9	5.2
	Zeolite HY 15	74.2	7	14.2	14.2	4.4
	HY 5	81.8	16	10.5	12.6	2.1
	Montmorillonite K 5	84.4	9.5	14.5	15.5	3.9
	CrCl <sub>2</sub>	99.4	12.6	15.7	14.8	5
	Amberlyst 36 dry	98.2	11.4	17.4	19.1	4.9
	Amberlyst 36 wet	93.1	17.5	14.4	16.9	3.6
	Amberlyst 70	85.8	22.2	12.5	14	3.3
Glucose	CrCl <sub>2</sub>	100	7.8	11.8	10.2	2.7
	Zeolite HY 5	100	4.3	4.8	5.4	0.8

#### Example 4

In a batch experiment, 0.36 mmol of substrate (glucose, fructose or HMF) and 6.5 mg of a  
 15 solid acid catalyst were mixed in a reactor coated inside with Teflon. 0.8 ml of alcohols  
 mixture (Ethanol, Isobutanol and n-Hexanol, with 4/2/1 volume ratio) was added and  
 pressurized at 12.5 bar with nitrogen (12.5 bar). The etherification was carried out at different  
 temperatures and different reaction time. Four main peaks were observed in the UV  
 spectrum and identified as HMF, 5-(ethoxymethyl)furfural (EMF), 5-(isobutoxymethyl)furfural  
 20 (iBuMF) and 5-(hexoxymethyl)furfural (nHexMF). The results are listed in Table 4.

Table 4. Conversion (Conv.) of HMF and selectivities (S) to 5-(alkoxymethyl)furfural, in the presence of different solid acid catalysts at 3 h reaction time and 100 °C

Catalyst	Conv. (%)	S EMF (%)	S iBuMF (%)	S nHexMF (%)
Amberlyst 70	81.2	48.8	24.4	2.8
Dowex Dr-2030	94.9	57.9	21.2	1.9
Lewatit K-2629, H <sup>+</sup> Form	90.7	61.0	21.8	2.1
Montmorillonite K 5	88.5	55.9	31.3	3.3
Nafion	98.7	49.7	32.3	4.6
Amberlyst36Wet	82.3	54.4	22.0	2.3
Zeolite H-USY SAR15	79.6	51.8	29.2	4.6

### Analytical Method

5 The reaction products were quantified with the aid of HPLC-analysis with an internal standard (saccharine, Sigma Aldrich). An Agilent 1100 series chromatograph, equipped with UV and ELSD detectors, was used. Stationary phase was reverse phase C18 (Sunfire 3.5  $\mu$ m, 4.6x100mm, Waters) column. A gradient elution at a constant flow 0.6 ml/min and temperature 40 °C was used according to the following scheme.

10

Time	H <sub>2</sub> O(vol%)	MeOH (vol%)	MeCN (vol%)	Flow (ml/min)	T ( C )
Initial	95	0	5	1	40
1	89	3	8	1	40
8	25	3	72	1	40

15

### Example 5. diesel fuel applications

#### Fuel solubility

20 Fuel solubility is a primary concern for diesel fuel applications. Not all highly polar oxygenates have good solubility in the current commercial diesel fuels. Results show that in the 5 vol%, in the 25 vol% and in the 40 vol% blends of total HMF ether content, obtained from a mixed alcohol etherification method according to the present invention, with commercial diesel, both liquid blend components are completely miscible. In a comparative set of experiments it was

25 shown that ethoxymethylfurfural (EMF) is completely miscible in a 5 vol% blend with commercial diesel, but that phase separation occurs with the 25 vol% and with the 40 vol% blends of EMF and diesel.

References

- DUMESIC, James A, et al. "Phase modifiers promote efficient production of Hydroxymethylfurfural from fructose" . Science. 30 June 2006, vol.312, no.5782, p.1933-1937.
- 5 • WO 2006/063220
- Chapter 15 of Advanced Organic Chemistry, by Jerry March, and in particular under reaction 5-4. (3<sup>rd</sup> ed., © 1985 by John Wiley & Sons, pp. 684-685).
- LEWKOWSKI, Jaroslaw. Synthesis, chemistry and applications of 5-hydroxymethylfurfural and its derivatives. Arkivoc. 2001, p.17-54. `
- 10 • MOREAU, Claude, et al. "Dehydration of fructose and sucrose into 5-hydroxymethylfurfural in the presence of 1-H-3-methyl imidazolium chloride acting both as solvent and catalyst", Journal of Molecular Catalysis A: Chemical 253 (2006) p. 165-169.
- EP 0641 854
- 15 • UOP report OPPORTUNITIES FOR BIORENEWABLES IN OIL REFINERIES FINAL TECHNICAL REPORT, SUBMITTED TO: U.S. DEPARTMENT OF ENERGY (DOE Award Number: DE-FG36-05GO15085))
- Adv. Synth. Catal. 2001, 343, 220-225
- EP 0 356 703
- 20 • FR 2 669 634

## Claims

1. Method for the manufacture of a mixture of 5-hydroxymethylfurfural ethers by reacting a hexose-containing starting material or HMF with a mixture of at least two dissimilar alcohols, with the second alcohol present in an amount of at least 5 vol.% on the alcohol mixture, in the presence of an acid catalyst.  
5
2. Method according to claim 1, wherein the alcohols making up the mixture are C1-C20 alcohols.
3. Method according to claim 1, wherein the alcohols are mixtures obtained from a  
10 Fischer-Tropsch alcohol synthesis process
4. Method according to claim 1, wherein the alcohols are mixtures obtained from a Guerbet alcohol synthesis process
- 15 5. Method according to claim 1 to 4, wherein the acid catalyst is selected from the group consisting of homogeneous or heterogeneous catalysts selected from solid organic acids, inorganic acids, salts, Lewis acids, ion exchange resins, zeolites or mixtures and/or combinations thereof.
- 20 6. Method according to claim 1 to 4, wherein the acid is a solid Brønsted acid.
7. Method according to claim 1 to 4, wherein the acid is a solid Lewis acid.
8. Method according to any one of the claims 1 to 7, wherein the reaction is performed at  
25 a temperature from 50 to 300 degrees Celsius, preferably from 125 to 250 degrees Celsius, more preferably from 150 to 225 degrees Celsius.
9. Method according to any one of the claims 1 to 8, wherein the hexose-containing starting material is used and wherein the hexose starting material is selected from the group  
30 of
  - starch, amylose, galactose, cellulose, hemi-cellulose,
  - glucose-containing disaccharides such as sucrose, maltose, cellobiose, lactose, preferably glucose-containing disaccharides, more preferably sucrose,
  - glucose or fructose.

10. Method according to any one of the claims 1 to 9, wherein the starting material is 5-(hydroxymethyl)furfural.

11. Method according to any one of the claims 1 to 9, wherein the starting material 5 comprises glucose, fructose, galactose and mannose and their oxidized (aldonic acid) or reduced (alditol) derivatives or mixtures thereof.

12. Method according to any one of the claims 1 to 9 wherein the starting material is an esterified, etherified monosaccharide or an amido sugar.

10

13. Method according to any one of the claims 1 to 12, performed in the presence of a solvent, wherein the solvent or solvents are selected from the group consisting of water, sulfoxides, preferably DMSO, ketones, preferably methyl ethylketone, ionic liquids, methylisobutylketone and/or acetone esters, ethers, preferably ethylene glycol ethers, more 15 preferably diethyleneglycol dimethyl ether (diglyme) or the reactant olefin and mixtures thereof.

14. Method according to any one of the claims 1 to 13, wherein the method is performed in a continuous flow process.

20

15. Method according to claim 14, wherein the residence time in the flow process is between 0.1 second and 10 hours, preferably from 1 second to 1 hours, more preferably from 5 seconds to 20 minutes.

25 16. Method according to claim 15, wherein the continuous flow process is a fixed bed continuous flow process.

17. Method according to claim 16, wherein the fixed bed comprises a heterogeneous acid catalyst.

30

18. Method according to claim 17, wherein the continuous flow process is a reactive distillation or a catalytic distillation process.

35 19. Method according to claims 17 - 18, wherein in addition to a heterogeneous acid catalyst, an inorganic or organic acid catalyst is added to the feed of the fixed bed or catalytic distillation continuous flow process.



## AMENDED CLAIMS

received by the International Bureau on 23 April 2009 (23.04.2009)

20. Method according to claim 16-19, wherein the liquid hourly space velocity ("LHSV") is from 1 to 1000, preferably from 5 to 500, more preferably from 10 to 250 and most preferably from 25 to 100.
21. Use of the ether mixture produced by the method of any one of claims 1-20 as fuel or fuel additive.
22. A fuel or fuel composition comprising the ether mixture produced by the method of any one of claims 1-20 as fuel component, optionally blended with one or more of gasoline and gasoline-ethanol blends, kerosene, diesel, biodiesel (a non-petroleum-based diesel fuel consisting of short chain alkyl (methyl or ethyl) esters, made by transesterification of vegetable oil), Fischer-Tropsch liquids, diesel-biodiesel blends and green diesel (a hydrocarbon obtained by hydrotreating biomass derived oils, fats, greases or pyrolysis oil) and blends of diesel and/or biodiesel with green diesel and other derivatives of furan and tetrahydrofuran.