

(12) **United States Patent**  
**Tsukamoto et al.**

(10) **Patent No.:** **US 10,800,292 B2**  
(45) **Date of Patent:** **Oct. 13, 2020**

(54) **VEHICLE SEAT**

(71) Applicants: **TS TECH CO., LTD.**, Asaka-shi, Saitama (JP); **HONDA MOTOR CO., LTD.**, Minato-ku, Tokyo (JP)

(72) Inventors: **Masaru Tsukamoto**, Reynoldsburg, OH (US); **Muneyuki Nogami**, Reynoldsburg, OH (US); **Takuro Yamada**, Tochigi (JP); **Daisuke Ogino**, Tochigi (JP); **Ronald C. Cozzo**, Delaware, OH (US); **David A. Juarez**, Marysville, OH (US); **Masakazu Okada**, Dublin, OH (US)

(73) Assignees: **TS TECH CO., LTD.**, Saitama (JP); **HONDA MOTOR CO., LTD.**, Tokyo (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/245,915**

(22) Filed: **Jan. 11, 2019**

(65) **Prior Publication Data**

US 2019/0217745 A1 Jul. 18, 2019

**Related U.S. Application Data**

(60) Provisional application No. 62/616,569, filed on Jan. 12, 2018.

(51) **Int. Cl.**  
**B60N 2/02** (2006.01)  
**B60N 2/58** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **B60N 2/0284** (2013.01); **B60N 2/5825** (2013.01); **B60N 2/68** (2013.01)

(58) **Field of Classification Search**

CPC ..... B60N 2/0284; B60N 2/62; B60N 2/72  
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,588,708 A \* 12/1996 Rykken ..... A47C 7/506  
297/423.2  
5,820,213 A \* 10/1998 Severinski ..... A47C 31/023  
297/218.5

(Continued)

FOREIGN PATENT DOCUMENTS

DE 102008043196 A1 \* 4/2010 ..... B60N 2/0284  
FR 2862579 A1 \* 5/2005 ..... B60N 2/0284

(Continued)


*Primary Examiner* — Rodney B White

(74) *Attorney, Agent, or Firm* — Hamre, Schumann, Mueller & Larson, P.C.

(57) **ABSTRACT**

In a vehicle seat, a movable frame provided at a front end portion of a stationary frame is configured to be slidable frontward and rearward between a first position and a second position frontward of the first position. An outer covering provided to extend frontward from an upper side of the stationary frame is configured to wrap around a front end portion of the movable frame. First and second straps are provided to extend rearward from a front end of the outer covering and configured to pull the front end of the outer covering rearward. The front end of the outer covering from which the first and second straps extend is arranged under the stationary frame. The first strap and the second strap are in positions spaced out laterally from each other. The first strap and the second strap are being pulled laterally inward.

**12 Claims, 14 Drawing Sheets**



(51)	<b>Int. Cl.</b>			8,573,696 B2 *	11/2013	Kuno .....	A47C 7/506
	<b>B60N 2/62</b>	(2006.01)					297/284.11
	<b>B60N 2/68</b>	(2006.01)		9,016,785 B2 *	4/2015	Freisleben .....	B60N 2/0232
(58)	<b>Field of Classification Search</b>						297/284.11
	USPC .....	297/284.11, 218.1, 218.2, 218.3, 218.4,		9,073,469 B2 *	7/2015	Fujikawa .....	B60N 2/72
		297/218.5		9,365,142 B1 *	6/2016	Line .....	B60N 2/62
	See application file for complete search history.			9,399,418 B2 *	7/2016	Line .....	B60N 2/929
				9,616,776 B1 *	4/2017	Kondrad .....	B60N 2/0284
				9,809,132 B2 *	11/2017	Bortolon .....	B60N 2/62
				9,981,582 B2 *	5/2018	Line .....	B29C 43/18
(56)	<b>References Cited</b>			10,045,623 B2 *	8/2018	Bortolon .....	B60N 2/914
	<b>U.S. PATENT DOCUMENTS</b>			10,046,681 B2 *	8/2018	Line .....	B60N 2/0284
				10,081,279 B2 *	9/2018	Line .....	B60N 2/68
				10,266,073 B2 *	4/2019	Line .....	B60N 2/0232
				10,286,818 B2 *	5/2019	Line .....	B60N 2/62
	5,826,939 A *	10/1998	Beyer .....	2007/0090673 A1 *	4/2007	Ito .....	B60N 2/0284
			B60N 2/6009				297/330
			297/218.3				
	5,988,748 A *	11/1999	Morrison .....	2007/0108817 A1 *	5/2007	Lee .....	B60N 2/62
			B60N 2/0232				297/284.11
			297/284.11 X				
	6,386,633 B1 *	5/2002	Newton .....	2009/0174242 A1 *	7/2009	Kohl .....	B60N 2/0284
			B60N 2/62				297/284.11
			297/284.11 X				
	7,192,087 B2 *	3/2007	Adragna .....	2011/0254335 A1 *	10/2011	Pradier .....	B60N 2/0232
			B60N 2/62				297/284.11
			297/284.11 X				
	7,556,312 B2 *	7/2009	Yoshikawa .....	2015/0352980 A1 *	12/2015	Reh fuss .....	B60N 2/0284
			B60N 2/42763				297/284.11
			297/284.11 X				
	7,669,929 B2 *	3/2010	Simon .....	2016/0137104 A1 *	5/2016	Bortolon .....	B60N 2/62
			B60N 2/0224				297/284.11
			297/284.11				
	7,874,621 B2 *	1/2011	Gumbrich .....	2016/0227932 A1 *	8/2016	Bortolon .....	B60N 2/62
			B60N 2/0284				
			297/284.11				
	7,997,648 B2 *	8/2011	Becker .....	2016/0339806 A1 *	11/2016	Popescu .....	B60N 2/0284
			B60N 2/0284				2018/0099595 A1 *
			297/284.11				4/2018
			B60N 2/0284				Kondrad .....
			297/284.11				B60N 2/0232
	8,011,728 B2 *	9/2011	Kohl .....	2019/0135139 A1 *	5/2019	Ioppolo .....	B60N 2/0284
			B60N 2/0284				2019/0160990 A1 *
			297/284.11				5/2019
			B60N 2/62				Morrow .....
			297/284.11				B60N 2/72
	8,128,167 B2 *	3/2012	Zhong .....	2019/0184858 A1 *	6/2019	Anzenberger .....	B60N 2/0284
			B60N 2/62				
			297/284.11				
	8,272,687 B2 *	9/2012	Gross .....				
			B60N 2/4221				
			297/284.11 X				
	8,297,697 B2 *	10/2012	Gross .....				
			B60N 2/4221				
			297/284.11 X				
	8,393,681 B2 *	3/2013	Gross .....				
			B60N 2/42763				
			297/284.11				

FOREIGN PATENT DOCUMENTS

FR	2958593 A1 *	10/2011	.....	B60N 2/0232
FR	3051738 B1 *	6/2018	.....	B60N 2/72
JP	2011189783 A	9/2011		

\* cited by examiner

FIG. 1






FIG. 3




FIG.4A




FIG.4B




FIG.5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG.9A




FIG.9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12A





FIG. 12B




FIG. 13A





FIG. 13B




FIG. 14A





FIG. 14B




FIG.15A





FIG.15B



1

**VEHICLE SEAT****CROSS-REFERENCE TO RELATED APPLICATION(S)**

This application claims the benefit of U.S. Provisional Application No. 62/616,569, filed on Jan. 12, 2018, the disclosure of which is incorporated herein by reference in its entirety.

**BACKGROUND**

## 1. Field

Apparatuses disclosed herein relate to a vehicle seat with a length-adjustable seating surface.

## 2. Description of the Related Art

A vehicle seat of which a seating surface is adjustable for length in a front-rear direction according to a physique of an occupant to be seated is known in the art. For example, a vehicle seat disclosed in JP 2011-189783 A comprises a main pad body fixed to a stationary frame for a seat cushion, a movable pad provided at the front of the main pad body in a manner that permits a front end position of the movable pad to be shifted in the front-rear direction, and a mechanism for causing the movable pad to be changed in its position. The main pad body and the movable pad are covered with an outer covering. A strap is provided at a front end portion of the outer covering. This strap extends rearward under the stationary frame, and has a distal end portion fixed to an undersurface of the stationary frame. This causes the front end portion of the outer covering to be pulled rearward by the strap.

With a structure as mentioned above in which the position of the movable pad is changeable frontward and rearward, the position of the front end portion of the outer covering moves according as the position of the movable pad changes; thus, the strap should be long enough to accommodate the stroke of such motion. However, the strap which extends straight in the front-rear direction requires an empty space that is long enough to accommodate the long strap in the front-rear direction.

It would thus be desirable to provide a vehicle seat in which a sufficiently long strap for pulling an outer covering is provided while a space for accommodating the strap can be made smaller and located in a position closer to the front end.

It would also be desirable to provide a vehicle seat in which the motion/action of the strap for pulling the outer covering is rendered stable.

It would further be desirable to provide a vehicle seat which ensures that the outer covering can be pulled firmly by a strap.

**SUMMARY**

In one aspect, a vehicle seat comprising a stationary frame, a movable frame, an outer covering, a first strap, and a second strap is disclosed. The movable frame is provided at a front end portion of the stationary frame and configured to be slidable frontward and rearward between a first position and a second position that is frontward of the first position. The outer covering is provided to extend frontward from an upper side of the stationary frame and configured to wrap around a front end portion of the movable frame. The

2

outer covering has a front end arranged under the stationary frame. The first strap is provided to extend rearward from the front end of the outer covering and configured to pull the front end of the outer covering rearward. The second strap is provided to extend rearward from the front end of the outer covering and configured to pull the front end of the outer covering rearward. The first strap and the second strap are in positions spaced out laterally from each other. The first strap and the second strap are being pulled laterally inward.

With this configuration, the straps can be provided with a sufficient length for pulling the outer covering, while the straps provided under the stationary frame can be arranged in positions closer to the front end of the stationary frame.

The vehicle seat configured as described above may further comprise a first engageable portion and a second engageable portion. The first engageable portion is a portion provided under the stationary frame and configured to allow the first strap to be hitched around the first engageable portion whereby a direction of extension of the first strap is changed. The second engageable portion is a portion provided under the stationary frame and configured to allow the second strap to be hitched around the second engageable portion whereby a direction of extension of the second strap is changed.

With this additional feature, the first engageable portion and the second engageable portion may be used to hold the first strap and the second strap, and thus the motion of the first strap and the second strap can be controlled with improved stability.

In the vehicle seat configured as described above with the aforementioned additional feature, the first engageable portion and the second engageable portion may be configured to each include a metal rod that extends obliquely at an angle of 45 degrees with respect to a front-rear direction.

With this additional feature, the directions of extension of the first strap and the second strap can be changed from the front-rear direction to laterally inward directions by 90 degrees.

In the vehicle seat configured as described above with one or more of the aforementioned additional features, the first engageable portion and the second engageable portion may be arranged to intersect one and same plane perpendicular to a front-rear direction.

With this further additional feature, portions of the first strap and the second strap extending in the front-rear direction have the same lengths, so that the outer covering can be pulled with evenly balanced forces.

In the vehicle seat configured as described above with one or more of the aforementioned additional features, the stationary frame may further be configured to include a pair of left and right side frames and a plate-shaped pan frame connecting front end portions of the left and right side frames. In this configuration, the first engageable portion and the second engageable portion may be provided on an underside of the pan frame.

With this further additional feature, the first engageable portion and the second engageable portion may be attached with increased ease, because the first engageable portion and the second engageable portion are attached to the plate-shaped member (i.e., pan frame).

In the aforementioned vehicle seat with or without any of the additional features mentioned above, the first strap and the second strap may be configured to each include a belt-shaped member.

With this further additional feature, the outer covering can be pulled more firmly by the belt-shaped first strap and the belt-shaped second strap in comparison with an alternative

3

configuration in which the first strap and the second strap each include a thin-string member in place of a belt-shaped member.

In the above-described vehicle seat with one or more of the additional features mentioned above, the first strap may be configured to include two first belts laid over each other with the first engageable portion disposed between the first belts, the first belts having far end portions farther away from the front end of the outer covering, the far end portions of the first belts being joined together; and the second strap may be configured to include two second belts laid over each other with the second engageable portion disposed between the second belts, the second belts having far end portions farther away from the front end of the outer covering, the far end portions of the second belts being joined together.

With this further additional feature, the ranges of movement of the first strap and the second strap can be restricted.

The above-described vehicle seat with or without any of the additional features mentioned above may further comprise a drive source provided under the stationary frame to drive the movable frame. The first strap may be arranged to extend rearward from the front end of the outer covering at a first side of the drive source and further extend laterally inwardly at a rear side of the drive source; and the second strap may be arranged to extend rearward from the front end of the outer covering at a second side of the drive source and further extend laterally inwardly at the rear side of the drive source, the first and second sides being opposite sides of the drive source.

With this further additional feature, interference of the first strap and the second strap with the drive source can be suppressed.

In the above-described vehicle seat with or without any of the additional features mentioned above, distal ends of the first strap and the second strap may be connected to each other.

With this further additional feature, an improved space-saving design and reduction of constitutional parts can be achieved, in comparison with an alternative configuration in which the distal end of the first strap and the distal end of the second strap are connected, respectively, to other portions.

In the above-described vehicle seat with or without any of the additional features mentioned above, distal ends of the first strap and the second strap may be connected to each other via a connecting member.

With this further additional feature, the first strap and the second strap can be installed in the vehicle seat with increased ease in comparison with an alternative configuration in which the first strap and the second strap are directly connected to each other, e.g., the first strap and the second strap are configured as a single long strap.

In the above-described vehicle seat with or without any of the additional features mentioned above, particularly where the connecting member is provided to connect the first strap and the second strap to each other, the connecting member may include a spring.

With this additional feature, decrease in tension of the connecting member can be retarded appreciably in comparison with an alternative configuration in which a rubber member is used in place of a spring to pull the first strap and the second strap.

In the above-described vehicle seat with or without any of the additional features mentioned above, particularly where the connecting member is provided to connect the first strap and the second strap to each other, the connecting member may include a metal part that is covered with a plastic cover member.

4

With this additional feature, the metal part of the connecting member is kept from direct contact with other members, so that unpleasant noise can be significantly reduced.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, other advantages and further features of the proposed apparatuses will become more apparent by describing in detail illustrative, non-limiting embodiments thereof with reference to the accompanying drawings, in which:

FIG. 1 is a perspective view showing an outer appearance of a car seat according to one illustrative, non-limiting embodiment;

FIG. 2 is an exploded perspective view showing an overview of a seat frame;

FIG. 3 is an exploded perspective view showing a cushion pad and an outer covering;

FIG. 4A is a perspective view showing a right bolster cover as viewed from the left side;

FIG. 4B is a perspective view showing the right bolster cover as viewed from the right side;

FIG. 5 is a section view showing a side frame and the right bolster cover taken along a plane containing a section of an engageable portion;

FIG. 6A is a bottom view showing a movable frame;

FIG. 6B is a section view showing the movable frame taken along the line I-I of FIG. 6A;

FIG. 7 is a perspective view showing an engageable member;

FIG. 8 is a section view showing a side cover and the engageable member;

FIG. 9A is a section view showing the outer covering, the cushion pad and the bolster cover taken along a plane containing a movement restriction plate and a front protrusion;

FIG. 9B is a section view showing a connecting frame, the outer covering, the cushion pad and the bolster cover taken along a plane containing a J hook and an inner fixing portion;

FIG. 10A is a bottom view showing a front end portion of a seat cushion in which the movable frame is in a first position;

FIG. 10B is a perspective view showing a first strap, a first engageable portion and a spring provided in the front end portion of the seat cushion;

FIG. 11 is a bottom view showing the front end portion of the seat cushion in which the movable frame is in a second position;

FIG. 12A is a section view showing the front end portion of the seat cushion in which the movable frame is in the first position;

FIG. 12B is a section view showing the front end portion of the seat cushion in which the movable frame is in the second position;

FIG. 13A is a schematic diagram showing a first modified configuration of the first strap and the second strap;

FIG. 13B is a schematic diagram showing a second modified configuration of the first strap and the second strap;

FIG. 14A is a schematic diagram showing a third modified configuration of the first strap and the second strap, in which the movable frame is in the first position;

FIG. 14B is a schematic diagram showing the third modified configuration of the first strap and the second strap, in which the movable frame is in the second position;

5

FIG. 15A is a schematic diagram showing an alternative configuration of a spring arrangement with a spring cover, in which the movable frame is in the first position; and

FIG. 15B is a schematic diagram showing the alternative configuration, in which the movable frame is in the second position.

#### DESCRIPTION OF THE EMBODIMENTS

A description will now be given of one embodiment of a vehicle seat with reference to the drawings. In the following description, the terms front and rear, left and right (lateral), upper (upward) and lower (downward) are used to designate the relevant directions or relative positions with respect to the viewpoint of an occupant seated on the vehicle seat. The terms “laterally inward” and “laterally outward” are used to designate the relevant directions or relative positions with respect to the vehicle seat (i.e., “laterally inward” means a direction toward or a position closer to a plane passing through a center of the vehicle seat and extending in a direction perpendicular to a lateral direction of the vehicle seat, whereas “laterally outward” means a direction away from or a position farther than the plane passing through the center of the vehicle seat and extending in the direction perpendicular to the lateral direction of the vehicle seat).

As shown in FIG. 1, a car seat S, as an example of a vehicle seat, mainly includes a seat cushion S1, a seat back S2, and a headrest S3. The car seat S is configured such that a front end portion of the seat cushion S1 can be moved in a front-rear direction so that the length in the front-rear direction of the seating surface is rendered adjustable according to the physique of an occupant.

The seat cushion S1 and the seat back S2 incorporate a seat frame F as shown in FIG. 2. The seat frame F mainly includes a cushion frame F1 and a seat back frame F2. The cushion frame F1 constitutes a frame of the seat cushion S1, and the seat back frame F2 constitutes a frame of the seat back S2.

The seat cushion S1 includes a cushion pad 1 and an outer covering 2 as shown in FIG. 3. The seat cushion S1 is formed by upholstering the seat cushion frame F1 with the cushion pad 1 and the outer covering 2 with which the cushion pad 1 is covered.

As shown in FIG. 2, the cushion frame F1 is installed on a floor of an automobile (as an example of a car) via slide rails SL. In this way, the car seat S is rendered adjustable in the position in the front-rear direction.

The cushion frame F1 includes a stationary frame 3, a movable frame 4, and a plastic plate 9. The movable frame 4 is provided at a front end portion of the stationary frame 3.

The stationary frame 3 includes a pair of left and right side frames 3A, a plate-shaped pan frame 3B connecting front end portions of the left and right side frames 3A, a connecting pipe 7 connecting rear end portions of the left and right side frames 3A, and a pair of left and right bolster covers 100.

The pair of left and right side frames 3A and the pan frame 3B are comprised of a pair of left and right support frames 5 and a plate-shaped connecting frame 6 connecting the pair of support frames 5.

Each of the support frames 5 is a metal frame extending in the front-rear direction. The pair of support frames 5 are in positions spaced out laterally from each other.

The connecting frame 6 includes left and right side frame portions 61 and a pan frame portion 62. The side frame portions 61 are laid on the support frames 5. The pan frame

6

portion 62 is a plate-shaped portion extending between the left and right side frame portions 61. The side frame portions 61 of the connecting frame 6 are fixed respectively to the support frames 5 by welding or the like.

In this embodiment, the pair of support frames 5 and the left and right side frame portions 61 of the connecting frame 6 constitute the pair of left and right side frames 3A, whereas the pan frame portion 62 of the connecting frame 6 constitutes the pan frame 3B connecting the pair of side frames 3A.

Each of the side frame portions 61 is so shaped substantially like a letter U in cross section as to cover the corresponding support frame 5, and extends from a rear end portion of the support frame 5 frontward up to a position beyond a front end of the support frame 5. To be more specific, the side frame portion 61 includes an upper side frame portion 61A disposed above the support frame 5, an inner side frame portion 61B extending from a laterally inner end of the upper side frame portion 61A downward and disposed at a laterally inner side of the support frame 5, and an outer side frame portion 61C extending from a laterally outer end of the upper side frame portion 61A downward and disposed at a laterally outer side of the support frame 5. The side frame portion 61 has a first fixing hole 63 formed in a front end portion of the upper side frame portion 61A.

The pan frame portion 62 connects lower ends of the left and right inner side frame portions 61B. The pan frame portion 62 includes, at a front end thereof, a movable frame support portion 64.

The movable frame support portion 64 has a recessed shape contoured to fit the movable frame 4, and opens to the front. The movable frame support portion 64 includes four guide protrusions 65 protruding upward.

The pan frame portion 62 has four second fixing holes 66, of which two are aligned in front and behind and disposed at a left end portion of the pan frame portion 62, and the other two are aligned in front and behind and disposed at a right end portion of the pan frame portion 62. Although the pair of second fixing holes 66 at the left end portion are not shown in FIG. 2, they are provided in positions symmetric to those of the pair of second fixing holes 66 at the right end portion.

The bolster covers 100 are members configured to form bank portions having a desired height at the left and at the right of the cushion frame F1. Each of the bolster covers 100 is disposed on the corresponding side frame 3A, specifically, on the corresponding side frame portion 61 of the connecting frame 6.

The movable frame 4 is provided movably in the front-rear direction relative to the stationary frame 3. To be more specific, the movable frame 4 is configured to be slidable frontward and rearward between a first position that is a rearmost position of the movable frame 4 as shown in FIG. 12A, and a second position that is frontward of the first position as shown in FIG. 12B. Referring back to FIG. 2, the movable frame 4 includes a body frame 8, a carrier cover 200 and a pair of left and right side covers 300. The carrier cover 200 and the side covers 300 are attached to the body frame 8.

The body frame 8 consists, for example, of a metal plate. It is to be understood that the body frame 8 may be of plastic. The body frame 8 includes a flat plate portion 81 disposed on the movable frame support portion 64 of the connecting frame 6, and a bent portion 82 extending from a front end of the flat plate portion 81 downward at a front side of the connecting frame 6, and then bent to extend rearward.

The bent portion **82** includes a plurality of projections **88** elongated in an upward-downward direction. The plurality of projections **88** are arranged laterally at the outer surface of the bent portion **82** so that slip between the cushion pad **1** and the bent portion **82** is improved. The bent portion **82** also has four fourth engageable holes **87**. One pair of the fourth engageable holes **87** are arranged one above the other and disposed at a left end portion of the bent portion **82**. The other pair of the fourth engageable holes **87** are arranged one above the other and disposed at a right end portion of the bent portion **82**.

The carrier cover **200** is a plastic member fixed on the flat plate portion **81** of the body frame **8**. The side covers **300** are plastic members disposed at the left and right sides of the carrier cover **200**.

The plastic plate **9** is a plate-shaped member made of plastic with flexibility. The plastic plate **9** extends continuously from a position over the pan frame **3B** to a position over the movable frame **4**. The plastic plate **9** laterally spans continuously from the left end portion to the right end portion of the pan frame **3B**. Provision of the plastic plate **9** in this manner serves to smoothly connect regions different in level with a sharp drop or rise like a step provided on the surface between the pan frame **3B** and the movable frame **4**, thereby improving the comfort of an occupant seated on the car seat **S**.

Since the plastic plate **9** is made of plastic that may be soft, pliable and flexible, the upper surface of the pan frame **3B** and the upper surface of the movable frame **4** can be connected smoothly.

The plastic plate **9** is, as shown in FIG. **12A**, disposed under the cushion pad **1**, and has a rear end portion thereof fixed to the pan frame **3B** by screws **B**.

A description will now be given of a detailed construction of the bolster covers **100**.

As shown in FIG. **2**, the bolster covers **100** are made of plastic, and each formed in an elongate shape that is longer in the front-rear direction. Each of the bolster covers **100** includes an upper wall portion **110** disposed over the side frame portion **61**, an inner wall portion **120** disposed at a laterally inner side of the side frame portion **61**, an outer wall portion **130** disposed at a laterally outer side of the side frame portion **61**, and a front wall portion **140** disposed at a front side of the side frame portion **61**. The left and right bolster covers **100** have shapes substantially symmetric to each other; therefore, in FIGS. **4** and **5**, the right bolster cover **100** only is illustrated.

As shown in FIG. **4A**, the upper wall portion **110** has, at a front end portion thereof, a front fixing portion **111**. The front fixing portion **111** is a circular recessed portion with a bottom having a front fixing hole **112** piercing in the upward-downward direction.

The inner wall portion **120** extends from a laterally inner end of the upper wall portion **110** downward. The inner wall portion **120** includes an inner ledge **121**. The inner ledge **121** extends laterally inward from a lower end of the inner wall portion **120**.

The inner wall portion **120** includes two inner fixing portions **150**. One of the inner fixing portions **150** is disposed at a rear end portion of the inner wall portion **120**. The other of the inner fixing portions **150** is disposed at a middle portion, in the front-rear direction, of the inner wall portion **120**. Each inner fixing portion **150** is configured as a plate-shaped portion extending laterally inward from the inner ledge **121** and having top and bottom faces (facing

upward and downward, respectively). The inner fixing portion **150** has an inner fixing hole **151** piercing in the upward-downward direction.

As shown in FIG. **4B**, the outer wall portion **130** extends from the laterally outer end of the upper wall portion **110** downward. The outer wall portion **130** includes two openings **131**, two engageable portions **132** each provided at an edge of the corresponding opening **131**, a first reinforcing portion **133** provided in a position between the two openings **131**, a second reinforcing portion **134**, and J-hook engageable portions **135**. The second reinforcing portion **134** is provided in a rear end portion of the outer wall portion **130**. The J-hook engageable portions **135** are provided in a lower end portion of the outer wall portion **130**.

The openings **131** are formed in the outer wall portion **130**. One of the openings **131** is disposed at a front end portion of the outer wall portion **130**, and the other is disposed at a middle portion, in the front-rear direction, of the outer wall portion **130**. Each opening **131** includes a through hole **131A** piercing through the outer wall portion **130** in the lateral direction, and a recessed portion **131B** formed at an upper edge of the through hole **131A**. The recessed portion **131B** is recessed laterally inwardly and opens upward. In other words, the upper edge of the opening **131** is positioned at the upper wall portion **110**.

The engageable portions **132** extend from a lower edge of each opening **131** laterally inwardly, i.e., toward the side frame portion **61**. Each engageable portion **132** includes an engageable tab **132A**. The engageable tab **132A** extends upward from an inner end of the laterally inwardly extending portion of the engageable portion **132**.

Each of the first reinforcing portion **133** and the second reinforcing portion **134** is configured as a bead bent to bulge outwardly in the outer wall portion **130**, and extends in the upward-downward direction. The first reinforcing portion **133** is provided below a phantom line **L1** joining the upper edges (provided at the upper wall portion **110**) of the two adjacent openings **131**.

Provision of this first reinforcing portion **133** between the two openings **131** serves to enhance the rigidity of the outer wall portion **130** having the plurality of openings **131** provided therein. Furthermore, the bead-shaped configurations of the first reinforcing portion **133** and the second reinforcing portion **134** make it possible to provide reinforcing portions with a simple construction.

The J-hook engageable portions **135** are portions each bent to bulge laterally outwardly in the outer wall portion **130**. One of the J-hook engageable portions **135** is provided in a front end portion of the outer wall portion **130** and the other is provided in a rear end portion of the outer wall portion **130**. The front J-hook engageable portion **135** is disposed frontward of the first reinforcing portion **133**, and the rear J-hook engageable portion **135** is disposed rearward of the first reinforcing portion **133**. In other words, the first reinforcing portion **133** is provided in a position between these two J-hook engageable portions **135**. The rear opening **131** (the opening **131** disposed in the middle portion of the outer wall portion **130**) is provided in a position between the two J-hook engageable portions **135**.

The front wall portion **140** is configured to extend from the front end of the upper wall portion **110** downward. The front wall portion **140** has a laterally outer end joined to the front end of the outer wall portion **130**. The front surface of the front wall portion **140** inclines rearward with respect to the upward-downward direction such that it is disposed farther rearward with increasing distance from a lower end toward upward. The front wall portion **140** includes a front

protrusion **160** protruding toward frontward. In other words, the bolster cover **100** includes the front protrusion **160**, which is provided at a front end portion of the bolster cover **100**.

The front protrusion **160** is formed as a plate thinner than a lateral width of the bolster cover **100**, and extends from a laterally inner end of the front wall portion **140** toward frontward. The upper end of the front protrusion **160** is provided in a position lower than the upper wall portion **110**. With this configuration, the bolster cover **100** only protrudes at the laterally inner front protrusion **160** toward frontward, and thus the laterally outer portion of the front end portion of the seat cushion **S1** is configured to be soft, so that when an occupant getting on and off the car seat **S**, his/her leg and any other part is unlikely to get snagged on the laterally outer portion of the front end portion of the seat cushion **S1**.

The bolster cover **100** configured as described above is, as shown in FIG. **5**, attached to the side frame **3A**. To be more specific, the engageable portion **132** extends from the outer wall portion **130**, lying under the outer side frame portion **61C** of the side frame portion **61**, to a laterally inner side of the outer side frame portion **61C**. The engageable tab **132A** of the engageable portion **132** engages with the lower edge of the outer side frame portion **61C**.

Since the first reinforcing portion **133** is provided below the phantom line **L1** joining the upper edges of the two adjacent openings **131**, the outer wall portion **130** can be bent for engagement of the engageable portion **132** with the outer side frame portion **61C** with increased ease in comparison with an alternative configuration in which the first reinforcing portion **133** is provided across the phantom line **L1**.

Since the engageable portion **132** extends from the edge of the opening **131**, the state of engagement of the outer side frame portion **61C** with the engageable portion **132** can be visually inspected through the opening **131**.

As shown in FIG. **9B**, the inner fixing portions **150** lie on the pan frame **3B** (i.e., on the pan frame portion **62** of the connecting frame **6**). The upper surface of each inner fixing portion **150** is parallel to the upper surface of the pan frame portion **62**. This makes it possible to obviate the potential discomfort an occupant would feel, in comparison with an alternative configuration in which the inner fixing portion **150** has a bulging portion.

The inner fixing portions **150** are fixed on the pan frame portion **62** by screws **B** inserted through the inner fixing holes **151** of the inner fixing portions **150** and the second fixing holes **66** of the pan frame **62**. With this configuration, the bolster cover **100** can be fixed with a part on which the weight of an occupant is put from above; therefore, the bolster cover **100** can be fixed securely. Because the inner fixing portions **150** lie on the pan frame **3B**, the weight of an occupant is likely to be received by the inner fixing portions **150**, and thus the bolster cover **100** can be securely fixed to the pan frame portion **62**.

As shown in FIG. **2**, the front fixing portion **111** is fixed on an upper surface of the side frame **61** of the connecting frame **6**, i.e., on an upper surface of the side frame **3A**, by a screw inserted through the front fixing hole **112** and the first fixing hole **63** of the side frame portion **61**. Since the buttocks of occupants vary in size with the individual, it may be preferable that the bolster cover **100** be allowed to deform so that the upper wall portion **110** thereof shift slightly in the laterally outward directions to accommodate large buttocks. This is achieved, in this embodiment, by fixing the bolster cover **100** to the side frame **3A** only at the front end portion of the bolster cover **100**, but not at the rear end portion of the

bolster cover **100** which may contact the buttocks of the occupant. Such laterally outward deformation of the bolster covers **100** which slightly widen the space between the left and right upper wall portions **110** at the rear end portion would help suppress a tight, cramped feel the occupant may have in his/her buttocks.

As described above, the bolster cover **100** is fixed to the side frame **3A** or the pan frame **3B** of the stationary frame **3** only at the front fixing portion **111** and two inner fixing portions **150**, while the rear end portion of the upper wall portion **110** and the outer wall portion **130** are not fixed to the side frame **3A** or the pan frame **3B** by screws or the like. Since the laterally outer side portion of the bolster cover **100** is not fixed at all, a force received from an occupant by the bolster cover **100** can be relieved to the laterally outward direction.

Next, a detailed description will be given of structural features of the body frame **8**, the carrier cover **200**, and side covers **300** which constitute the movable frame **4**.

The flat plate portion **81** of the body frame **8** has an upper surface formed substantially parallel to the upper surface of the pan frame portion **62** of the connecting frame **6**. As shown in FIG. **6A**, the flat plate portion **81** includes a plurality of guide slots **83** extending in the front-rear direction. In the guide slots **83**, guide projections **65** of the connecting frame **6** are disposed. With these features, the body frame **8** is configured to move in the front-rear direction along the direction of extension of the guide slots **83** as the guide projections **65** inside the guide slots **83** can move relative to the guide slots **83**.

The flat plate portion **81** has, at an upper surface thereof, two first engageable holes **84**, two second engageable holes **85**, and two third engageable holes **86**. The first engageable holes **84** are provided in the front end portion of the flat plate portion **81**. The second engageable portions **85** are provided in positions rearwardly of the corresponding first engageable holes **84**, respectively. The third engageable holes **86** are provided in left and right end portions of the flat plate portion **81**.

As shown in FIG. **6B**, the carrier cover **200** is a member having a bulge to be provided on the flat plate portion **81**, and has a curved surface **201** protruding upwardly. To be more specific, the carrier cover **200** rises with increasing distance from a rear end thereof frontward, and lowers with increasing distance from an uppermost portion thereof toward a front end thereof. The carrier cover **200** protrudes upward beyond an extended plane **P** of the upper surface of the pan frame portion **62** (see FIG. **12A**). The uppermost portion of the carrier cover **200** is provided frontwardly of a center of the carrier cover **200** in the front-rear direction. By virtue of this carrier cover **200** provided on the flat plate portion **81**, thighs of an occupant can be properly supported.

As shown in FIG. **2**, the curved surface **201** of the carrier cover **200** has a laterally elongate shape extending along the length from the left end to the right end of the flat plate portion **81**. With this configuration, the thighs of an occupant can be supported more comfortably in comparison with an alternative configuration in which the curved surface **201** is provided partly in the lateral direction.

Since the curved surface **201** is provided on the carrier cover **200**, the curved surface can be provided on the movable frame **4** with increased ease in comparison with an alternative configuration in which such a curved surface is provided on the upper surface of the body frame **8**.

Particularly, in this embodiment, the carrier cover **200** is made of plastic and the body frame **8** is made of metal; therefore, the curved surface **201** can be provided on the

## 11

carrier cover **200** more easily than on the body frame **8**. Moreover, provision of the plastic carrier cover **200** on the metal body frame **8** serves to reduce noise which would be produced when the cushion pad **1** and the movable frame **4** rub against each other.

As shown in FIG. 6A, the carrier cover **200** has an undersurface, and includes two first hooks **210**, two second hooks **220**, and two engageable bosses **230**, all of which are provided at the undersurface of the carrier cover **200**. The first hooks **210** are provided at a front end portion of the carrier cover **200** and arranged side by side in the lateral direction. Each first hook **210** protrudes downward and includes a first claw **211** extending frontward. The first claw **211** is provided at a distal end portion of the first hook **210**. The second hooks **220** are provided rearwardly of the first hooks **210**, respectively. Each second hook **220** protrudes downward and includes a second claw **221** extending rearward, i.e., in a direction opposite to the direction in which the first claw **211** of the first hook **210** extends. The second claw **221** is provided at a distal end portion of the second hook **220**. The engageable bosses **230** are provided at left and right end portions of the carrier cover **200**, and protrude downward.

As shown in FIG. 6B, the first hook **210** engages with the first engageable hole **84** of the body frame **8**. The first claw **211** of the first hook **210** hooks on the edge of the first engageable hole **84**. The second hook **220** engages with the second engageable hole **85**. The second claw **221** of the second hook **220** hooks on the edge of the second engageable hole **85**. The engageable boss **230** engages in the third engageable hole **86**.

In this manner, the carrier cover **200** is fixed to the body frame **8** in a simple construction only by engaging the first hooks **210**, second hooks **220** and engageable bosses **230** provided on the carrier cover **200** with the holes **84**, **85**, **86** of the body frame **8**.

Moreover, since the claws **211**, **221** at the distal end portions of the first hooks **210** and the second hooks **220** are hooked on the edges of the holes **84**, **85** of the body frame **8**, the engagement of the first hooks **210** with the body frame **8** and engagement of the second hooks **220** with the body frame **8** are rendered unlikely to disengage.

As shown in FIGS. 6A, 6B, the side covers **300** each include a side cover body **310** and a flange portion **320** both of which are provided along the outer surface of the body frame **8**. The side cover body **300** extends from an upper side of the body frame **8**, along a front side of the body frame **8**, up to an underside of the body frame **8**. The flange portion **320** extends from the side cover body **310** laterally inward.

The side cover body **310** has a groove **330**. The groove **330** extends from an upper surface of the side cover body **310**, through a front surface of the side cover body **310**, and to an undersurface of the side cover body **310**. The configuration of the groove **330** will be described later in detail.

As shown in FIG. 6B, the flange portion **320** is formed along the surface of the body frame **8**. The flange portion **320** includes a third hook **321** and a fourth hook **322** which are arranged in a direction perpendicular to the lateral direction (in the present embodiment, the third and fourth hooks **321**, **322** are arranged in the upward-downward direction). The third hook **321** and the fourth hook **322** protrude from the flange portion **320** on the body frame **8** side. The third hook **321** includes a third claw **321A** protruding upward. The third claw **321A** is provided at the distal end portion of the third hook **321**. The fourth hook **322** is provided under the third hook **321**, and includes a fourth claw **322A** protruding downward, i.e., in a direction opposite

## 12

to the direction in which the third claw **321A** protrudes. The fourth claw **322A** is provided at the distal end portion of the fourth hook **322**.

The third hook **321** engages with the upper fourth engageable hole **87** of the body frame **8**. The third claw **321A** of the third hook **321** is hooked on the edge of the fourth engageable hole **87**. The fourth hook **322** engages with the lower fourth engageable hole **87** of the body frame **8**. The fourth claw **322A** of the fourth hook **322** is hooked on the edge of the fourth engageable hole **87**.

Provision of the third hook **321** and the fourth hook **322** in the flange portion **320** provides a simple construction by which the side cover **300** can be fixed to the body frame **8**. Since the third hook **321** and the fourth hook **322** are arranged in the upward-downward direction, the side cover **300** can be fixed securely to the body frame **8** without enlarging the flange portion **320** in the lateral direction.

Next, a description will be given of a detailed configuration of the cushion pad **1** and the outer covering **2**.

As shown in FIG. 3, the cushion pad **1** is made of a cushiony material such as urethane foam. The cushion pad **1** includes a center portion **11** for an occupant to be seated thereon, and left and right side portions **12** provided, respectively, at the left and right sides of the center portion **11**.

The center portion **11** is a portion laid over the pan frame portion **62** of the connecting frame **6** and the movable frame **4**. The side portions **12** are portions configured to cover the side frames **3A** and the bolster covers **100**. The cushion pad **1** has a first slit **1A** provided between the center portion **11** and each of the side portions **12**, i.e., in a position laterally inward of the side frame **3A**. The first slit **1A** extends from a front end of the cushion pad **1** rearward. The center portion **11** is longer than the side portions **12** and extends farther frontward beyond the front ends of the side portions **12**.

The center portion **11** is provided, as shown in FIG. 12, to extend frontward from an upper side of the pan frame **3B** and configured to wrap around the front end portion of the movable frame **4**.

As shown in FIG. 3, the cushion pad **1** has a tuck-in groove **1B** provided between the center portion **11** and each of the side portions **12**. The tuck-in groove **1B** is a groove recessed down from the upper surface of the cushion pad **1**. The tuck-in groove **1B** is disposed rearward of the first slit **1A** and extends in the front-rear direction. An outer covering attachment member (not shown) for tucking in the outer covering **2** is provided at a bottom of the tuck-in groove **1B**.

As shown in FIG. 9B, the side portion **12** is configured to bulge upward beyond an upper side of the center portion **11**. The tuck-in groove **1B** is provided inwardly in the lateral direction relative to the lateral position of the inner fixing portion **150** of the bolster cover **100**. In other words, the inner fixing portion **150** is provided on a laterally outer side relative to a position directly under the tuck-in groove **1B**. Similarly, a screw **B** by which the inner fixing portion **150** is fixed to the pan frame **3B** is in a position directly under the tuck-in groove **1B** or on a laterally outer side relative to the position directly under the tuck-in groove **1B**. This position of the screw **B** serves to suppress the potential discomfort an occupant would feel.

Returning to FIG. 3, the outer covering **2** is made of a synthetic leather, fabrics or the like. The outer covering **2** includes a center cover **21** disposed to cover the center portion **11** of the cushion pad **1**, and left and right side covers **22** disposed, respectively, at left and right sides of the center portion **11** to cover the left and right side portions **12** of the cushion pad **1**. The outer covering **2** has a second slit **2A** provided between the center cover **21** and each of the left

13

and right side covers **22**, i.e., in a position laterally inward of the side frame **3A**. The second slit **2A** extends from the front end of the outer covering **2** rearward.

The center cover **21** extends farther frontward beyond the front ends of the side covers **22**. This center cover **21** is configured to extend frontward from an upper side of the pan frame **3B** and configured to wrap around a front end portion of the movable frame **4**, as shown in FIG. **12**.

Referring back to FIG. **3**, left and right engageable members **25** are provided, respectively, on front portions of the left and right end portions of the center cover **21** (i.e., portions extending beyond the front ends of the side covers **22**). The left and right engageable members **25** are members like a trim cord that has an elongate shape extending along the left and right end portions of the center cover **21**. At the front end of the center cover **21**, a first strap **26** and a second strap **27** are provided. The first strap **26** and the second strap **27** are connected to each other via a spring **28** as an example of a connecting member.

Left and right movement restriction plates **24** are provided at laterally inner end portions of the front end portions of the left and right side covers **22**, respectively. Each side cover **22** includes a J hook **23**. The J hook **23** is provided at a laterally outer end portion of the side cover **22**.

The movement restriction plate **24** is shaped like a letter U and disposed such that the letter U opens rearward. The movement restriction plate **24** is fixed to the inner end portion (i.e., the side on which the second slit **2A** is provided) of the front end portion of the side cover **22**.

As shown in FIG. **9A**, the front protrusion **160** of the bolster cover **100** is disposed in the first slit **1A** of the cushion pad **1**. The front protrusion **160** is disposed adjacent to the movement restriction plate **24** in a position laterally outward of the movement restriction plate **24**.

As shown in FIG. **9B**, the J hook **23** is fixed to the laterally outer end portion of the side cover **22**. The J hook **23** is shaped substantially like a letter J that extends downward from the side cover **22** and is bent laterally inwardly. The J hook **23** is engaged with the lower edge of the J hook engageable portion **135** of the bolster cover **100**. Thus, the outer covering **2** is pulled down at both of the left and right end portions (see arrow in FIGS. **9A** and **9B**).

As the left and right end portions of the outer covering **2** are pulled down, the cushion pad **1** under the outer covering **2** is also pulled in the lateral direction; however, in the present embodiment, the movement restriction plate **24** is brought into contact with the front protrusion **160** of the bolster cover **100** that is disposed at the laterally outer side of the movement restriction plate **24**, and the movement of the outer covering **2** in the lateral direction is restricted. Accordingly, the side portion **12** is restrained from being pulled in the lateral direction, so that the front end portion of the cushion pad **1** can be kept in shape.

By providing the front protrusion **160** as an engageable portion (with which the movement restriction plate **24** is engageable) in the bolster cover **100**, such an engageable portion can be provided in the cushion frame **F1** with a simple construction.

The engageable members **25** provided at the center cover **21** include a body portion **25A** and a hook tab **25B**, as shown in FIG. **7**. The body portion **25A** is an elongate plate-shaped portion extending along each of the left and right end portions of the center cover **21**. The hook tab **25B** is a portion extending from the distal end (the protruding end protruding from the center cover **21**) of the body portion **25A** in a direction different from the protruding direction of the body portion **25A**. Each engageable member **25** has a

14

substantially L-shaped cross section with the body portion **25A** and the hook tab **25B**. The portion of the body portion **25A** at an end (proximal end) opposite to the distal end from which the hook tab **25B** extends (i.e., the proximal end portion of the body portion **25A** of the engageable member **25**) is fixed to the center cover **21** by sewing.

The body portion **25A** has slits **25C** provided in the proximal end portion of the body portion **25A** (the proximal end portion is the portion fixed to the center cover **21**). The slits **25C** of the body portion **25A** are arranged along the length of the engageable member **25**. Provision of such slits **25C** renders the engageable member **25** flexible, i.e., easy to bend in accordance with the center cover **21**.

The engageable member **25** is, as shown in FIG. **8**, inserted in the groove **330** provided in the side cover **300** of the movable frame **4**.

Hereinafter, a detailed description will be given of the specific construction of the groove **330**.

The groove **330** includes a first groove section **331** extending deep in a direction away from the outer covering **2**, and a second groove section **332** extending from the first groove section **331** in a direction different from a direction in which the first groove section **331** extends.

In the present embodiment, the direction in which the second groove section **332** extends from the first groove section **331** is the laterally inward direction. The second groove section **332** has a first wall **332A** and a second wall **332B** opposite the first wall **332A**, where the position of the first wall **332A** is closer to the outer covering **2** than the position of the second wall. The first wall **332A** has a first end portion and a second end portion, where the position of the first end portion being closer to the first groove section **331** than the position of the second end portion. The second groove section **332** includes a barb protrusion **333** protruding from the first end portion of the first wall **332A** of the second groove section **332** toward the hook tab **25B**.

The engageable member **25** is disposed such that the body portion **25A** is disposed in the first groove section **331**, and the hook tab **25B** is disposed in the second groove section **332**. In this arrangement, even if the center cover **21** is pulled and a force tending to cause the engageable member **25** to be pulled out of the groove **330** (e.g., upward in FIG. **8**) is generated, the hook tab **25B** is caught on the edge of the second groove section **332** so that the engageable member **25** can be kept from coming off from the groove **330**.

Moreover, as the barb protrusion **333** protrudes toward the hook tab **25B**, the hook tab **25B** is likely to catch on the barb protrusion **333**, and the engageable member **25** can be more effectively kept from coming off from the groove **330**.

The hook tab **25B** extends laterally inward from the body portion **25A**. With this configuration, when an occupant is seated on the car seat **S**, the center cover **21** is pulled laterally inward but the hook tab **25B** moves in such a direction that the hook tab **25B** catches on the second groove section **332**; resultantly, the engageable member **25** can be still more effectively kept from coming off from the groove **330**.

As shown in FIG. **10A**, the first strap **26** and the second strap **27** are members configured to pull the front end of the center cover **21** arranged under the stationary frame **3**. In the present embodiment, the first strap **26** and the second strap **27** are each configured as a wide belt-shaped member so that the center cover **21** can be pulled firmly.

The first strap **26** is fixed to the left end portion of the front end of the center cover **21**. The second strap **27** is in a

position spaced out laterally from the position of the first strap 26, and is fixed to the right end portion of the front end of the center cover 21.

The first strap 26 extends from the front end of the center cover 21 rearward, and is hitched around the first engageable portion 67 provided under the connecting frame 6 whereby a direction of extension of the first strap 26 is changed to the laterally inward direction.

The first engageable portion 67 includes a metal rod having a circular cross section, which is provided on an underside of the pan frame portion 62 so that the first engageable portion 67 can be fixed to the connecting frame 6 with ease. The first engageable portion 67 includes an engageable body 67A, a front end portion 67B, and a rear end portion 67C. The engageable body 67A extends substantially in parallel to the pan frame portion 62 under the pan frame portion 62. The front end portion 67B extends from the front end of the engageable body 67A toward the pan frame portion 62. The rear end portion 67C extends from the rear end of the engageable body 67A toward the pan frame portion 62.

The engageable body 67A extends obliquely at an angle of 45 degrees with respect to the front-rear direction such that the engageable body 67A is disposed farther inwardly, i.e., rightward, with increasing distance from the front end toward rearward. As shown in FIG. 10B, the front end portion 67B is welded or otherwise fixed to the pan frame portion 62. The rear end portion 67C is spaced apart from the pan frame portion 62. With this configuration, the first strap 26 can be hitched around the first engageable portion 67 easily through a space between the rear end portion 67C and the pan frame portion 62.

The first strap 26 is bent to hold the engageable body 67A of the first engageable portion 67 from above and from below. To be more specific, the first strap 26 extends under the first engageable body 67A of the first engageable portion 67 from the front to the rear, then turning around the rear side of the engageable body 67A, and further extends above the engageable body 67A from the left to the right.

With this simple configuration, the direction of extension of the first strap 26 can be changed from the front-rear direction to the laterally inward direction by 90 degrees merely by hitching the first strap 26 around the first engageable portion 67, and the first strap 26 can be held firmly by the first engageable portion 67.

As shown in FIG. 10A, the second strap 27 extends from the front end of the center cover 21 rearward, and is hitched around the second engageable portion 68 provided under the connecting frame 6 whereby a direction of extension of the second strap 27 is changed to the laterally inward direction.

The second engageable portion 68 includes a metal rod having a circular cross section, which is provided on the underside of the pan frame portion 62 so that the second engageable portion 68 can be fixed to the connecting frame 6 with ease. The second engageable portion 68 has a shape symmetric to the first engageable portion 67. This second engageable portion 68 includes an engageable body 68A, a front end portion 68B, and a rear end portion 68C. The engageable body 68A extends substantially in parallel to the pan frame portion 62 under the pan frame portion 62. The front end portion 68B extends from the front end of the engageable body 68A toward the pan frame portion 62. The rear end portion 68C extends from the rear end of the engageable body 68A toward the pan frame portion 62.

The engageable body 68A extends, under the pan frame portion 62, obliquely at an angle of 45 degrees with respect to the front-rear direction such that the engageable body 68A

is disposed farther inwardly, i.e., leftward, with increasing distance from the front end toward rearward. The front end portion 68B is welded or otherwise fixed to the pan frame portion 62. The rear end portion 68C is spaced apart from the pan frame portion 62. With this configuration, the second strap 27 can be hitched around the second engageable portion 68 easily through a space between the rear end portion 68C and the pan frame portion 62.

The second strap 27 is bent to hold the engageable body 68A of the second engageable portion 68 from above and from below. To be more specific, the second strap 27 extends under the second engageable body 68A of the second engageable portion 68 from the front to the rear, then turning around the rear side of the engageable body 68A, and further extends above the engageable body 68A from the right to the left.

With this simple configuration, the direction of extension of the second strap 27 can be changed from the front-rear direction to the laterally inward direction by 90 degrees merely by hitching the second strap 27 around the second engageable portion 68, and the second strap 27 can be held firmly by the second engageable portion 68.

The first engageable portion 67 and the second engageable portion 68 are arranged in the same position in the front-rear direction, i.e., to intersect one and same plane perpendicular to the front-rear direction. With this feature, portions of the first strap 26 and the second strap 27 extending in the front-rear direction have the same lengths, and the portions of the first strap 26 and the second strap 27 extending in the lateral direction are in the same position in the front-rear direction. Therefore, the center cover 21 can be pulled easily with evenly balanced forces by the first strap 26 and the second strap 27.

The spring 28 is a tension spring made of metal, which expands and contracts in the lateral direction. The spring 28 has a left end fixed to the distal end of the first strap 26 and a right end fixed to the distal end of the second strap 27 to connect the distal end of the first strap 26 and the distal end of the second strap 27. With this configuration, the first strap 26 and the second strap 27 are being pulled laterally inward. Use of the spring 28 to pull the first strap 26 and the second strap 27 serves to suppress reduction of the pulling force effectively in comparison with an alternative configuration in which a member made of rubber is used to pull the first strap 26 and the second strap 27.

With this configuration in which one and the same spring 28 is used to pull the first strap 26 and the second strap 27, space saving and reduction in number of parts can be achieved in comparison with an alternative configuration in which dedicated members (such as springs) are used to pull the first strap 26 and the second strap 27.

With this configuration in which discrete straps (first strap 26 and second strap 27) are provided and connected via the spring 28, installation of the straps to a car seat S can be performed with increased ease in comparison with an alternative configuration in which the first strap and the second strap are directly connected, for example, a single longer strap is provided.

In this embodiment, the first strap 26 and the second strap 27 are disposed near the front end of the space under the stationary frame 3, while keeping a distance sufficient to pull the center cover 21. Under the stationary frame 3, to be more specific, under the pan frame portion 62, a drive source M is provided to drive the movable frame 4. The drive source M is fixed to the front end portion of the underside of the pan frame portion 62. To be more specific, the drive source M is provided in a position shifted frontward from the positions

17

of the first engageable portion 67 and the second engageable portion 68 in the front-rear direction and between the first engageable portion 67 and the second engageable portion 68 in the lateral direction. Accordingly, the first strap 26 is arranged to extend from the front end of the center cover 21 rearward at a first side (left side) of the drive source M and further extend laterally inwardly at the rear side of the drive source M. The second strap 27 is arranged to extend from the front end of the center cover 21 rearward at a second side (the side opposite to the first side of the drive source M at which the first strap 26 extend; right side) of the drive source M and further extend laterally inwardly at the rear side of the drive source M. With this arrangement, interference of the first strap 26 and the second strap 27 with the drive source M can be prevented.

A description will now be given of an operation of the car seat S configured as described above.

When the movable frame 4 is in the first position, as shown in FIG. 12A, the first strap 26 and the second strap 27 are pulling the front end portion of the center cover 21 of the outer covering 2 rearward, and the front end portion of the center portion 11 of the cushion pad 1 and the front end portion of the center cover 21 are thus pressed against the bent portion 82 of the body frame 8.

When the movable frame 4 moves from the first position to the second position, as shown in FIG. 12B, the movable frame 4 pushes out the center portion 11 of the cushion pad 1 frontward. Accordingly, the center cover 21 is pulled frontward, and the front end thereof moves frontward. In this way, the movement of the movable frame 4 to the second position makes the seating surface longer frontward than when the movable frame 4 is in the first position.

When the movable frame 4 moves to the second position, the engageable members 25 provided at the left and right end portions of the center cover 21 move along the grooves 330 of the side covers 300.

In the present embodiment, the carrier cover 200 is provided on the body frame 8, and the movable frame 4 thereby has an upwardly-bulging shape. Thus, the shape of the front end upper portion of the movable frame 4 (i.e., the shape of the portion of the movable frame 4 which pushes the cushion pad 1) is made gentle in comparison with an alternative configuration in which no bulge is provided on the flat upper surface of the movable frame 4. Therefore, the frontward movement of the movable frame 4 relative to the cushion pad 1 can be made smooth. Since the plastic plate 9 is placed on the pan frame 3B (of the stationary frame 3) and the carrier cover 200 (of the movable frame 4), the shape of the members provided under the cushion pad 1 is made smooth, so that when the carrier cover 200 moves frontward under the thighs of an occupant, the occupant would be less likely to feel discomfort which would be caused by such movement. Moreover, since the plastic plate 9 is fixed to the pan frame 3B (not movable, stationary frame) and does not move when the movable frame 4 moves, the occupant would be less likely to feel discomfort which would be caused by such movement.

As shown in FIG. 11, when the first strap 26 and the second strap 27 are pulled frontward by the frontward movement of the front end of the center cover 21, the spring 28 is extended and becomes longer than it is when the movable frame is in the first position.

As shown in FIG. 12A, when the movable frame 4 is moved to the first position again, the first strap 26 and the second strap 27 pull the front end portion of the center cover 21 rearward by elasticity of the spring 28. Accordingly, the

18

center portion 11 of the cushion pad 1 and the center cover 21 are pulled rearward as if they stick to the movable frame 4.

At this time, the engageable members 25 provided at the left and right end portions of the center cover 21 move along the grooves 330 of the side covers 300.

In the present embodiment, as the rear end portion of the plastic plate 9 is fixed to the pan frame 3B that constitutes the stationary frame 3, the plastic plate 9 does not move when the movable frame 4 moves relative to the cushion pad 1. Therefore, when the movable frame 4 moves to the first position, undesirable rubbing or hitching of the rear end edge of the plastic plate 9 against the cushion pad 1 can be prevented.

Although an illustrative embodiment has been described above, specific configurations may be changed or modified, where appropriate, without departing from the spirits of the present invention.

In the above-described embodiment, the distal end portions of the first strap 26 and the second strap 27 are connected via the spring 28, but feasible configurations of the first strap and the second strap are not limited to this specific example. As an alternative, as shown in FIG. 13A, the distal ends of a first strap 26A and a second strap 27A may not be connected to each other.

Specifically, the first strap 26A extends straight from the front end of the center cover 21 obliquely in the rearward-and-rightward direction. The distal end of the first strap 26A is fixed to one end of a spring 28A of which the other end is connected to the stationary frame 3. With this configuration, the first strap 26A is being pulled by the spring 28A in the rearward-and-laterally-inward direction.

The second strap 27A extends straight from the front end of the center cover 21 above or below the first strap 26A obliquely in the rearward-and-leftward direction. As seen in the upward-downward direction, the first strap 26A and the second strap 27A intersect each other. The distal end of the second strap 27A is fixed to one end of a spring 28B of which the other end is connected to the stationary frame 3. With this configuration, the second strap 26B is being pulled by the spring 28B in the rearward-and-laterally-inward direction.

Alternatively, as shown in FIG. 13B, the first strap 26B and the second strap 27B may not be connected via any connecting member, but may be configured as a single long strap 29.

Specifically, the strap 29 is made of an elastic (expandable and contractible) material, such as rubber band or the like. One end of the strap 29 is fixed to the right end portion of the front end of the center cover 21, and the other end of the strap 29 is fixed to the left end portion of the front end of the center cover 21. The pan frame 3B includes an engageable portion 69. The engageable portion 69 is disposed substantially in a laterally central position on an undersurface of the pan frame 3B, and protrudes downward. The middle portion of the strap 29 is hooked on the engageable portion 69. In this alternative configuration, the left-side half of the strap 29 (portion from the left end to the center that is in contact with the engageable portion 69) serves as the first strap 26B, which pulls the front end of the center cover 21 rearward and laterally inward (in the rearward-and-laterally-inward direction), and the right-side half of the strap 29 serves as the second strap 27B, which pulls the front end of the center cover 21 rearward and laterally inward (in the rearward-and-laterally-inward direction).

In the above-described embodiment, the first strap 26 and the second strap 27 are each configured as a single belt-

19

shaped member; however feasible configurations of the first strap and the second strap may not be limited to this specific example. As an alternative, as shown in FIG. 14A, a first strap 26C may be configured to include two first belts 261 which are laid over each other with a first engageable portion 67 disposed between the first belts 261, and of which far end portions (end portions of the first belts 261 farther away from the outer covering 2) are joined together, and a second strap 27C may be configured to include two second belts 271 which are laid over each other with a second engageable portion 68 disposed between the second belts 271, and of which far end portions (end portions of the second belts 271 farther away from the outer covering 2) are joined together.

Specifically, the two first belts 261 are sewn together at two positions separate from each other in the longitudinal direction of the first strap 26C, with the first engageable portion 67 being disposed between the two sewn positions. Similarly, the two second belts 271 are sewn together at two positions separate from each other in the longitudinal direction of the second strap 27C, with the second engageable portion 68 being disposed between the two sewn positions.

When the center cover 21 is pulled frontward to a large extent as shown in FIG. 14B, the sewn portion 262 of the first strap 26C is brought into contact with the first engageable portion 67, and the sewn portion 272 of the second strap 27C is brought into contact with the second engageable portion 68. Accordingly, the movable ranges of the first strap 26C and the second strap 27C are restricted. Therefore, the spring 28 can be prevented from getting stretched to its full length (to such an extent as could disadvantageously make the spring 28 unrestorable) even when the center cover 21 is pulled frontward to a large extent.

In an alternative configuration by which the spring 28 is prevented from getting stretched to its full length, the spring 28 may be provided with a cover member 400, as shown in FIG. 15A.

The cover member 400 is configured to have a generally tubular shape enveloping the spring 28. The cover member 400 is made of plastic, fabrics, or other nonmetal materials, and pleated like an accordion or bellows so as to be expandable and contractible. The left end of the cover member 400 is fixed to the distal end of the first strap 26, and the right end of the cover member 400 is fixed to the distal end of the second strap 27.

This alternative configuration provided with the cover member 400, even when the center cover 21 is pulled frontward with full strength to such an extent that the first strap 26 and the second strap 27 would move to excess, the movement of the first strap 26 and the second strap 27 is restricted by the length of the fully extended cover member 400. Accordingly, the spring 28 can be prevented from getting stretched to its full length to such an extent as would disadvantageously make the spring 28 unrestorable at worst.

Since the metal spring 28 is covered with the cover member 400 made of plastic or the like, the spring 28 is kept from direct contact with other members. So, unpleasant noise can be significantly reduced.

In the above-described embodiment, the first strap 26 and the second strap 27 are belt-shaped members, but feasible configurations of the first strap and the second strap may not be limited to this specific example. As an alternative, the first strap and the second strap may each include a thin string.

In the above-described embodiment, the first engageable portion 67 and the second engageable portion 68 each include a metal rod that extends obliquely at an angle of 45 degrees with respect to the front-rear direction; however, feasible configuration of the first engageable portion and the

20

second engageable portion may not be limited to this specific example. As an alternative, the first engageable portion and the second engageable portion may be configured to each include an annular member, through which the first strap 26 and the second strap 27 may be hitched and the directions of extension of the first strap 26 and the second strap 27 are changed.

In the above-described embodiment, the first engageable portion 67 and the second engageable portion 68 are each made of a metal rod having a circular cross section, but feasible configurations of the first engageable portion and the second engageable portion may not be limited to this specific example. As an alternative, the first engageable portion and the second engageable portion may each have a shape of plate.

Any of the elements of the embodiments and alternative configurations described above may be selectively combined as desired for particular applications.

What is claimed is:

1. A vehicle seat comprising:

a stationary frame;

a movable frame provided at a front end portion of the stationary frame and configured to be slidable frontward and rearward between a first position and a second position that is frontward of the first position; an outer covering provided to extend frontward from an upper side of the stationary frame and configured to wrap around a front end portion of the movable frame, the outer covering having a front end arranged under the stationary frame;

a first strap provided to extend rearward from the front end of the outer covering and configured to pull the front end of the outer covering rearward; and

a second strap provided to extend rearward from the front end of the outer covering and configured to pull the front end of the outer covering rearward, wherein the first strap and the second strap are in positions spaced out laterally from each other,

wherein the first strap and the second strap are being pulled laterally inward.

2. The vehicle seat according to claim 1, further comprising:

a first engageable portion provided under the stationary frame and configured to allow the first strap to be hitched around the first engageable portion whereby a direction of extension of the first strap is changed; and a second engageable portion provided under the stationary frame and configured to allow the second strap to be hitched around the second engageable portion whereby a direction of extension of the second strap is changed.

3. The vehicle seat according to claim 2, wherein the first strap includes two first belts laid over each other with the first engageable portion disposed between the first belts, the first belts having far end portions farther away from the front end of the outer covering, the far end portions of the first belts being joined together, and

wherein the second strap includes two second belts laid over each other with the second engageable portion disposed between the second belts, the second belts having far end portions farther away from the front end of the outer covering, the far end portions of the second belts being joined together.

4. The vehicle seat according to claim 2, wherein the first engageable portion and the second engageable portion each include a metal rod that extends obliquely at an angle of 45 degrees with respect to a front-rear direction.

21

5. The vehicle seat according to claim 2, wherein the first engageable portion and the second engageable portion are arranged to intersect one and same plane perpendicular to a front-rear direction.

6. The vehicle seat according to claim 2, wherein the stationary frame includes a pair of left and right side frames and a plate-shaped pan frame connecting front end portions of the left and right side frames, and

wherein the first engageable portion and the second engageable portion are provided on an underside of the pan frame.

7. The vehicle seat according to claim 1, wherein the first strap and the second strap each include a belt-shaped member.

8. The vehicle seat according to claim 1, further comprising a drive source provided under the stationary frame to drive the movable frame,

wherein the first strap is arranged to extend rearward from the front end of the outer covering at a first side of the

22

drive source and further extend laterally inwardly at a rear side of the drive source, and

wherein the second strap is arranged to extend rearward from the front end of the outer covering at a second side of the drive source and further extend laterally inwardly at the rear side of the drive source, the first and second sides being opposite sides of the drive source.

9. The vehicle seat according to claim 1, wherein distal ends of the first strap and the second strap are connected to each other.

10. The vehicle seat according to claim 1, wherein distal ends of the first strap and the second strap are connected to each other via a connecting member.

11. The vehicle seat according to claim 10, wherein the connecting member includes a spring.

12. The vehicle seat according to claim 10, further comprising a plastic cover member,

wherein the connecting member includes a metal part that is covered with the plastic cover member.

\* \* \* \* \*