




US 20080222793A1

(19) **United States**(12) **Patent Application Publication**
Cook(10) **Pub. No.: US 2008/0222793 A1**(43) **Pub. Date: Sep. 18, 2008**(54) **RIBBED PREFABRICATED POLYURETHANE
SHOWER MODULE****Publication Classification**(51) **Int. Cl.**
A47K 3/00 (2006.01)(52) **U.S. Cl.** **4/612**(57) **ABSTRACT**(75) **Inventor: Joseph R. Cook, Parkland, FL (US)**

Correspondence Address:

**BRINKLE Y, MORGAN, SOLOMON, TATUM,
STANLEY, LUNNY,
& CROSBY, LLP
200 E. LAS OLAS BLVD, SUITE 1900
FORT LAUDERDALE, FL 33301 (US)**(73) **Assignee: Tile Redi, LLC**(21) **Appl. No.: 11/724,873**(22) **Filed: Mar. 17, 2007**

A prefabricated, polyurethane reaction injection molded, leak-proof shower module suitable for use in constructing a tiled shower includes a plurality of sidewalls (101, 102, 103, 104), a floor (110) and a plurality of ribs (120) connected to the floor. The floor has an upper surface, a lower surface, and a plurality of peripheral edges and is bounded along at least one peripheral edge by at least one sidewall that extends substantially vertically from the at least one peripheral edge. Each rib extends parallel to, perpendicular to, or at an acute angle to at least one peripheral edge and runs toward at least one drain wall and terminates in an outer edge lying in a common plane. In one embodiment, the upper surface slopes downward toward the drain wall at a pitch of $\frac{1}{8}$ inch per foot or greater and each rib extends downward from the lower surface, resulting in a horizontal common plane.






FIG. 1






FIG. 2






FIG. 4A




FIG. 4B




FIG. 5
PRIOR ART




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16








FIG. 17

**FIG. 18**






FIG. 22




FIG. 23








FIG. 24



**FIG. 25**






FIG. 28




FIG. 29





FIG. 30

**FIG. 31**




FIG. 32

RIBBED PREFABRICATED POLYURETHANE SHOWER MODULE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present patent application is related to co-pending and commonly owned U.S. patent application Ser. No. _____, Attorney Docket No. 8540-07003, entitled "Method for Manufacturing a Prefabricated Modular Shower Curb and Associated Modular Shower Curb," U.S. patent application Ser. No. _____, Attorney Docket No. 8540-07004, entitled "Prefabricated Shower Pan Having Varying Sidewall Heights and Method of Attaching a Modular Curb Thereto," U.S. patent application Ser. No. _____, Attorney Docket No. 8540-07005, entitled "Improved Drain Wall for a Prefabricated Shower Module," U.S. patent application Ser. No. _____, Attorney Docket No. 8540-07006, entitled "Improved Method for Manufacturing a Prefabricated Shower Module," and U.S. patent application Ser. No. _____, Attorney Docket No. 8540-07007, entitled "Method of Manufacturing and Installation of Prefabricated Shower Bench and Associated Shower Bench," filed on even date with the present patent application, the entire teachings of which being hereby incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates generally to prefabricated shower modules and, more particularly, to a ribbed, prefabricated, leak-proof polyurethane shower module for use in constructing a tiled shower enclosure and having surfaces suitable for receiving shower tile, marble or stone thereon.

[0004] 2. Description of the Prior Art

[0005] Most tile-covered shower enclosures are created using complicated construction methods. For example, using conventional techniques, a skilled installer frames out the area to be enclosed using two-by-four wooden or aluminum studs to create a frame and curb. Felt or tar paper is then laid over a subfloor area enclosed within the newly formed frame. A flexible, leak-proof liner is installed on top of the felt or tar paper and attached to the frame. Next, the installer attaches dry wall boards to the framing studs, creating shower sidewalls. A hole is cut in the liner to allow for a drain, and a layer of mortar is applied to the shower sidewalls and curb and allowed to cure. Additional mortar is applied on top of the leak-proof liner and hand-shaped to form a shower floor which slopes toward the drain such that water from the shower flows toward the drain. After the mortar has cured, shower tile is applied to the sidewalls and floor to create the finished enclosure.

[0006] The process of creating the enclosed shower is time-consuming and requires a certain degree of skill in order to maintain the proper pitch and uniformity in shaping the floor. Irregularities in the pitch of the floor can cause water from the shower not to drain properly or make tiling the shower enclosure difficult. The liners are also susceptible to punctures or leaks and may be difficult for the installer to properly form square corners at the intersection of the shower sidewalls and floor. Additionally, the mortar layer used to create the floor is necessarily thick in order to form a sloped surface, therefore the time required for the floor to cure before applying tile may be quite long (e.g., greater than 24 hours).

[0007] In recent years, the process of shower installation has been vastly improved by the introduction of prefabricated shower base modules used for forming the floor. Use of the prefabricated modules significantly decreases the amount of time and skill required to construct a tile-covered shower enclosure, as well as providing more of a consistent and reliable flooring surface upon which to tile. These modules are pre-constructed molded units having a sloping floor, an integrated drain, curb, sidewalls, and a horizontal surface on the top of each sidewall for mounting drywall such that the drywall is substantially flush to the module sidewalls. Installation of the module involves securing a section of drain pipe to the drain, applying adhesive and sealing material to the subfloor where the module will rest, and seating the module on the subfloor. Tile can then be applied directly to the shower walls and module without the need for first applying mortar.

[0008] However, these prefabricated shower modules contain weaknesses in the design which add cost to the final product. For instance, certain modules are manufactured using plastics-forming processes that inject molten polymeric resins into molds. After filling the mold with the resin, the module must cool (e.g., solidify) before being removed. If the module is removed before it is completely solid, bowing may occur as the module hardens. However, the mold or "tool" for creating each unit can be quite expensive, thus a manufacturer generally limits the number of tools for producing each module. Therefore, the number of modules manufactured in a given amount of time depends on the amount of time required for one module to sufficiently cool enough to be removed from the mold.

[0009] Because the mold is needed to create other modules, the manufacturer is pressed to find ways to decrease the required cooling time. This problem is exacerbated by non-uniform thicknesses of the plastic material throughout the module. Cooling rates for thick areas of the module are slower than for thinner areas. Thus, if the module is removed from the mold before it is completely cooled, areas of the modules having different thicknesses cool at different rates, resulting in bowing across the surface of the floor. As a result, severely bowed modules must be discarded, increasing the unit cost for other modules. Additionally, slightly bowed modules present potential field problems (i) by impacting uniform tile adhesion on the upper surface of the floor of the shower module, (ii) by preventing the lower surface of the floor of the shower module from sitting flush on the subfloor, and (iii) by changing the pitch of the upper floor of the shower module, which causes puddling or ponding of water on the upper floor of the shower module rather than properly pitched draining. Further, uneven cooling along the drain aperture may result in a misshapen aperture, thereby (i) preventing the installer from acquiring (or hampering his/her ability to acquire) a water-tight seal around the drain fixture, and (ii) interfering with the insertion of the drain fixture into the drain aperture. Uneven cooling along the drain assembly (i) may prevent a proper connection (e.g., a water-tight connection) between the drain assembly and the shower module, (ii) may warp the drain aperture at the top of the drain assembly, thereby interfering with the insertion of the drain top into the top of drain assembly, and (iii) may warp the drain aperture in the bottom of the drain assembly, thereby interfering with the connection of the drain assembly to the plumbing line.

[0010] Further, each size module requires a specific mold, thus the manufacturer is forced to limit the selection of available modules to a few standard sizes. Because the curb may be

integrated into the shower module, both the positioning of the curb, as well as the overall dimensions of the module are set by a single tool. The design options for a customer (e.g., an architect, a designer, a contractor, an installer, or homeowner) desiring to implement a prefabricated shower module are therefore limited to a few set arrangements.

[0011] Additionally, features such as shower benches or ledges must still be constructed by hand, or added in a piecemeal fashion, thereby compromising the leak-proof integrity of the prefabricated shower module.

[0012] Therefore, a need exists for, among other things, a ribbed, prefabricated, leak-proof polyurethane shower module for use in constructing a tiled shower enclosure and having surfaces suitable for receiving shower tile, marble or stone thereon to overcome the shortcomings of the prior art.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 is a top plan view of a prefabricated shower module in accordance with one embodiment of the present invention.

[0014] FIG. 2 is a side cross-sectional elevational view of the prefabricated shower module of FIG. 1 along the line 2-2.

[0015] FIG. 3 is a bottom plan view of the prefabricated shower module of FIG. 1, illustrating a horizontal support rib arrangement.

[0016] FIG. 4 is a front/top perspective view of the shower module of FIG. 1.

[0017] FIG. 4A is a front/top perspective view of a shower module in accordance with an alternative embodiment of the present invention.

[0018] FIG. 4B is a front/top perspective view of a shower module in accordance with another alternative embodiment of the present invention.

[0019] FIG. 5 is a cross-sectional view of a prior art shower module drain assembly.

[0020] FIG. 6 is a cross-sectional view of an exemplary drain assembly, in accordance with an embodiment of the present invention.

[0021] FIG. 7 is a bottom plan view of a prefabricated shower module, illustrating an exemplary sunburst support rib arrangement, in accordance with an alternative embodiment of the present invention.

[0022] FIG. 8 is a bottom plan view of a prefabricated shower module, illustrating an exemplary diamond support rib arrangement, in accordance with an alternative embodiment of the present invention.

[0023] FIG. 9 is a bottom plan view of a prefabricated shower module, illustrating an exemplary honeycomb support rib arrangement, in accordance with another alternative embodiment of the present invention.

[0024] FIG. 10 is a front/top perspective view of a prefabricated shower module having pre-scored indentations for attaching a modular curb along any sidewall, in accordance with another alternative embodiment of the present invention.

[0025] FIG. 11 is a front/top perspective view of a handicapped-accessible prefabricated shower module in accordance with an alternative embodiment of the present invention.

[0026] FIG. 12 is a front/top perspective view of a handicapped-accessible prefabricated shower module in accordance with another alternative embodiment of the present invention.

[0027] FIG. 13 is a front elevational view of the prefabricated shower module of FIG. 11.

[0028] FIG. 14 is a front/top perspective view of a prefabricated shower module having an integrated curb, in accordance with another alternative embodiment of the present invention.

[0029] FIG. 15 is a front/top perspective view of a prefabricated shower module having an integrated curb, in accordance with another alternative embodiment of the present invention.

[0030] FIG. 16 is a cross-sectional view of the prefabricated shower module of FIG. 15 along the line 16-16.

[0031] FIGS. 17-18 are logic flow diagrams of various steps executed to implement a method for manufacturing an improved, prefabricated leak-proof shower module, in accordance with exemplary embodiments of the present invention.

[0032] FIG. 19 is a front/top perspective view of a prior art modular curb.

[0033] FIG. 20 is a front/top perspective view of a prefabricated modular curb in accordance with one embodiment of the present invention.

[0034] FIG. 21 is a front/bottom perspective view of a prefabricated modular curb in accordance with one embodiment of the present invention.

[0035] FIG. 22 is a side/top perspective view illustrating an exemplary installation of the modular curb of FIG. 21 with the shower module of FIG. 1.

[0036] FIG. 23 is a side/top perspective view illustrating an exemplary installation of an alternative embodiment of a modular curb in accordance with an exemplary embodiment of the present invention.

[0037] FIG. 24 is a front/bottom perspective view of a prefabricated modular curb in accordance with an alternative embodiment of the present invention.

[0038] FIG. 24A is a side cross-sectional view illustrating an exemplary installation of an alternative embodiment of a modular curb in accordance with an exemplary embodiment of the present invention.

[0039] FIGS. 25-27 are logic flow diagrams of various steps executed to implement a method for creating a tiled shower stall using a prefabricated leak-proof shower module and a prefabricated modular curb, in accordance with exemplary embodiments of the present invention.

[0040] FIG. 28 is a front/top perspective view of a prefabricated shower seat in accordance with an embodiment of the present invention.

[0041] FIG. 29 is a front/top perspective view of a prefabricated shower seat in accordance with an alternative embodiment of the present invention.

[0042] FIG. 30 is a side elevational view illustrating an exemplary installation of the prefabricated shower seat of FIG. 28 installed with a prefabricated shower module of FIG. 1, in accordance with an embodiment of the present invention.

[0043] FIG. 31 is a logic flow diagram of various steps executed to implement a method for creating a tiled shower stall using a prefabricated leak-proof shower module and a prefabricated shower seat, in accordance with exemplary embodiments of the present invention.

[0044] FIG. 32 is a front/top perspective view of a complete shower enclosure system constructed using a prefabricated shower module, a prefabricated modular curb, and a prefab-

ricated shower bench, in accordance with exemplary embodiments of the present invention.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENT(S)

[0045] Before describing in detail exemplary embodiments that are in accordance with the present invention, it should be observed that the embodiments reside primarily in combinations of apparatus components and processing steps related to implementing a method for improving manufacturability of a pre-molded leak-proof shower module having surfaces for receiving shower tile or stone thereon and the associated shower module. Accordingly, the apparatus and method components have been represented where appropriate by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the present invention so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein.

[0046] In this document, relational terms, such as “first” and “second,” “top” and “bottom,” and the like, may be used solely to distinguish one entity or element from another entity or element without necessarily requiring or implying any physical or logical relationship or order between such entities or elements. The terms “comprises,” “comprising,” or any other variation thereof are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements, but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. The term “plurality of” as used in connection with any object or action means two or more of such object or action. A claim element preceded by the article “a” or “an” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that includes the element. The term “tile” also encompasses “stone” and/or “marble.” The term “tiled” means any surface having tile, stone, and/or marble applied thereon. The term “sidewall,” in relation to a shower module, means any vertical surface rising above the floor of the shower module along one or more peripheral edges and may be any height or any width, including, without limitation, an integrated curb.

[0047] Generally, the present invention encompasses a prefabricated modular system for constructing a tiled shower enclosure; an improved prefabricated shower module, modular curb, and shower seat for use within the system, and methods for manufacturing and installing the above components.

[0048] In a preferred embodiment, a prefabricated leak-proof shower module suitable for use in constructing a tiled shower includes a plurality of sidewalls, and a floor that is bounded along at least one peripheral edge by at least one sidewall that extends vertically from the peripheral edge. The floor has an upper surface sloping downward from each peripheral edge toward a drain aperture and a lower surface with a plurality of support ribs, where each support rib extends downward from the lower surface to terminate in a common horizontal plane. Additionally, the upper surface may contain a plurality of pitching ribs which provide a uniform pitch from each peripheral edge to the drain aperture. Each support rib runs and each pitching rib runs either parallel to, perpendicular to, or at an acute angle to, at least one peripheral edge of the floor. The shower module may be created using polyurethane reaction injection molding pro-

cessing. Alternative embodiments may include a horizontal bottom plane and/or an integrated molded curb.

[0049] In another embodiment, a prefabricated modular curb suitable for use in constructing a tiled shower enclosure includes a mounting wall with an outer surface for engaging a sidewall of a shower module, an exterior wall, and a top wall that extends from an upper edge of the exterior wall to the upper edge of the mounting wall in a plane either substantially perpendicular to the mounting wall and to the exterior wall or pitching downward from the exterior wall to the mounting wall. The curb further includes at least one reinforcing curb rib that is attached to at least one of the top curb wall, the inner surface of the mounting wall, the inner surface of the exterior wall, and the bottom wall if any, and which rib runs either parallel to, perpendicular to, or at an acute angle to the mounting wall or the exterior wall.

[0050] In another embodiment, a prefabricated shower bench for installation in a tiled shower includes a seating surface having a plurality of peripheral edges, and at least three sidewalls, wherein each sidewall is connected to a corresponding peripheral edge of the seating along an upper edge. One of the sidewalls includes a setback area along its entire lower edge that has a height greater than the height of one of the sidewalls of a prefabricated shower module. The lower edge of each sidewall terminates in a common plane.

[0051] 1. Prefabricated Shower Module

[0052] The present invention can be more readily understood with reference to FIGS. 1-32, in which like reference numerals designate like items. FIGS. 1-4 depict an exemplary prefabricated leak-proof shower module **100** suitable for use in constructing a tiled shower in accordance with one embodiment of the present invention. As depicted in FIGS. 1-4, the exemplary shower module **100** includes a floor **110**, and vertical sidewalls **101**, **102**, **103**, **104** (4 shown). The upper surface **112** of the floor **110** and the vertical sidewalls **101**, **102**, **103**, **104** are suitable for retaining tile, stone, or marble installed thereon. Each sidewall **101**, **102**, **103**, **104** extends vertically from a peripheral edge of the floor **110**. The floor **110** has an upper surface **112** that slopes downward from each peripheral edge toward a drain aperture **130**, and a lower surface **114** that connects to a plurality of support ribs **120**. The upper surface **112** slopes downward from each peripheral edge to the drain aperture **130** at a pitch of $\frac{1}{8}$ "/foot or greater.

[0053] Each support rib **120** extends downward from the lower surface **114** such that the bottom edge **122** of each support rib **120** terminates in a common horizontal plane. Additionally, each support rib **120** runs either parallel to, perpendicular to, or at an acute angle to, at least one peripheral edge of the floor **110**. When the shower module **100** is installed to construct a shower enclosure, the shower module **100** is positioned on a subfloor of the shower enclosure in such a manner that the plurality of support ribs **120** provide support for the shower module **110** by resting on the subfloor, and a drain wall **132** surrounding the drain aperture **130** is positioned inside or above an opening in the subfloor that contains a plumbing connection.

[0054] In an alternative embodiment, as shown in FIG. 4A, the shower module **700** includes a bottom panel **160** that extends from each sidewall **101**, **102**, **103**, **104** and/or each peripheral edge to the drain wall **132** in a horizontal plane. Thus, the bottom panel **160** rests on the subfloor of the shower enclosure when the shower module **100** has been installed. Additionally, the bottom edge **122** of each support rib **120** is connected to the bottom panel **160**.

[0055] In another alternative embodiment, as shown in FIG. 4B, the shower module 800 includes a floor 110 that extends in a horizontal plane from each sidewall 101, 102, 103, 104 and/or peripheral edge to a drain wall 132 surrounding the drain aperture 130. Pitching ribs 121 extend upwards from the upper surface 112 and terminate in an upper edge sloping downwards from the peripheral edge to the drain aperture 130.

[0056] In one embodiment, at least one sidewall 104 has a height that is lower than the height of the remaining sidewalls 101, 102, 103. The height of the lower sidewall 104 is preferably at least one inch lower than the height of the remaining sidewalls 101, 102, 103. The lowered height insures that in the event that the plumbing connection becomes clogged, any standing water in the shower module 100 will spill over onto the floor of the bathroom in which the shower enclosure is constructed instead of seeping into the walls; preventing water damage or mold accumulation. Additionally, the top surface of any sidewall 101, 102, 103, 104 should either be flat or pitched towards the shower module 100 so that any water accumulating on the top surface flows back into the shower module 100.

[0057] The height of the lower sidewall 104 is preferably sufficient to permit installation of a modular curb 300 (see FIG. 21) adjacent to the sidewall 104. The lower sidewall 104 may be initially molded to the required height, molded to the same height as the other sidewall 101, 102, 103 and trimmed as a part of post-production process, or may contain a horizontal fatigue line 108 (see FIG. 10) located at a height suitable for a portion of the sidewall 104 to be removed, thereby allowing installation of a modular curb adjacent to the sidewall. The horizontal fatigue line 108 denotes a thinner section of the sidewall 104 and can be easily broken, or cut, and removed. The fatigue line 108 may be molded into the sidewall during an injection molding process, or pre-scored by the manufacturer. The fatigue line 108 may be included on any or all of the sidewalls 101, 102, 103, 104 so that an installer may have the option of choosing a sidewall 101, 102, 103, 104 for attaching the prefabricated modular curb 300. After installation of tile on the surface of the shower module 100, any inherent weakness in a sidewall 101, 102, 103, 104 still containing a horizontal fatigue line 108 does not affect the integrity of the shower enclosure and is obscured by the tile.

[0058] In an alternative embodiment, the outer surface of the lower sidewall 104 may include an attachment mechanism 106 (see FIG. 23) for engaging a corresponding attachment mechanism 316 of a modular curb 300. Exemplary methods for attaching the modular curb 300 to the shower module 100 are discussed in greater detail in Section 2. The attachment mechanism 106 may be a tab, a notch, a slot, a tongue, a groove, a ridge, a peg, an aperture, an interlocking clip, an adhesive material, or any other mechanism suitable for connecting the modular curb 300 to the shower module 100.

[0059] In one embodiment of the present invention, the shower module 100 is constructed using polyurethane reaction injection molded processes. When using injection-molding techniques, the shower module 100 may be molded from a polymeric material such as polyurethane foam having a density equal to or greater than 12 pounds per cubic foot. A lower density polyurethane material would be, most likely, unable to support a connection to the drain.

[0060] The overall thickness of the material, as well as variances in the thickness of material used, has a substantial impact on the quality of the shower module 100, 700, 800. During manufacturing, the shower module 100, 700, 800 is formed by injecting a liquid polymeric material into a tool having a core and a cavity, which define the shape of the finished shower module 100, 700, 800. The core and cavity of the tool, when fastened together, form a hollowed area that corresponds to the final shower module 100, 700, 800. As the polymeric material cools, it conforms to the shape defined by the tool and solidifies into the final shower module 100, 700, 800. The thickness of the material affects the cooling rate of the finished product. Thicker sections cool at a slower rate than thinner sections. If a shower module 100, 700, 800 contains sections having an uneven thickness, the thinner sections will cool much more quickly than the thick sections, which may cause the upper surface and the lower surface of the shower module 100, 700, 800 to bow or warp.

[0061] The area surrounding the drain aperture 130 is of particular importance in the cooling process. In the drain area in previous prefabricated shower modules, such as the drain area shown in FIG. 5, the drain wall was maintained at a constant diameter below the bottom floor of the shower module, but smaller than the plumbing opening in the shower enclosure subfloor. The rationale for shaping the drain wall in this fashion was that the constant diameter would provide a more secure fit, and would support the drain. However, by maintaining a constant outer diameter of the drain wall, the thickness of the drain wall surrounding the drain aperture or the drain assembly varies as the depth of the drain wall increases from the top of the drain aperture or drain assembly to the bottom of the drain aperture or drain assembly, because the diameter of the drain aperture or drain assembly at the top of the drain aperture or drain assembly is larger than the diameter at the bottom. Because of the difference in material thickness in the drain wall, the thinner areas cooled faster than the thicker areas.

[0062] This cooling differential resulted in bowing and warping in one or more of the upper surface in the vicinity of the drain wall, the lower surface in the vicinity of the drain wall, the drain aperture, the drain assembly, and the drain aperture inside the drain assembly, thereby (i) causing problems with the pitch of the upper surface, (ii) impacting tile adhesion to the upper surface, (iii) impacting the water tightness of the seal between the drain fixture (not shown) and the drain aperture at or around the upper surface, the drain fixture and the drain aperture at or around the lower surface, and the drain fixture and the inside of the drain aperture, (iv) impacting whether the lower surface of the shower module is level around the drain wall, (v) impacting the top and bottom shape of the drain aperture thereby interfering with the insertion of a drain fixture into the drain aperture, and (vi) impacting the shape of the drain aperture inside the drain assembly thereby interfering with the connection of the drain assembly to the plumbing line and the insertion of the drain top into the drain assembly.

[0063] As shown in FIG. 2, a drain may be attached to the shower module 100, 700, 800 at the drain aperture 130 in one of two methods. The shower module 100, 700, 800 may be molded with a prefabricated drain assembly 134 integrated into the shower module floor 110 and encased inside the drain wall 132, or with a drain fixture 135 affixed to the shower module 100 after fabrication of the shower module 100 by inserting the drain fixture 135 into the drain aperture 130.

molded into the shower module floor **10** and drain wall **132**. When the drain fixture **135** is attached to the shower module **100** subsequent to fabrication, a water-tight seal must be established between the drain fixture **135** and the shower module **100** at one or more of the drain aperture **130**, the upper surface **112**, and the lower surface **114**, to prevent leaking.

[0064] In an embodiment of the present invention, as shown in FIG. 6, the drain wall **132** surrounding the drain assembly **134** or the drain aperture **130** has a thickness that is contoured to approximate variances in the diameter of the drain assembly **134** or the drain fixture **135**. The top of the drain aperture **130** and the drain assembly **134** may have a greater diameter than the bottom of the drain aperture **130** and the drain assembly **134**, because the top portion of most drain fixtures and drain assemblies is wider where the water drains from the floor **110** of the shower module **100** into the drain assembly **134** or the drain fixture **135**, than at the bottom portion of the drain fixture **135** and/or the drain assembly **134** where they connect to the plumbing line. Accordingly, the upper portion of the drain wall **132** may have a greater diameter than the lower portion of the drain wall **132**, as the drain wall **132** is contoured to more closely and uniformly follow the diameter of the respective portions of the either drain assembly **134** or the drain aperture **130** used to connect a drain fixture **135**.

[0065] The largest diameter of the drain wall **132** at the thickest part of the drain wall **132** is equal to or less than 4 times the diameter of the drain aperture **130** at the bottom of the drain wall **130**. The thickness of the bottom of the drain wall **132** measured from the outside wall of the bottom of the drain wall **132** to the drain aperture **130** at the bottom of the drain wall **132** is equal to or less than 1½ times the diameter of the drain aperture at the bottom of the drain wall **130**. The actual thickness of the drain wall **132**, the thickness of the shower module floor **110** at the drain wall **132**, the diameter of the drain wall **132**, and the contour of the drain wall **132**, will vary depending upon the size of the drain, the weight of the drain, the size of the drain aperture, and whether the drain is made of one or more of PVC, ABS, brass, copper, iron, or other metal. By adhering to the above guidelines, most instances of bowing or warping of the shower module floor **110**, the drain wall **132**, the drain assembly **134**, and the drain aperture **130** may be significantly reduced.

[0066] If a prefabricated drain assembly **134** is integrated into the shower module floor **110**, the prefabricated drain assembly **134** is inserted into the tool prior to injecting the polymeric material. A drain reinforcing structure **136**, which has an opening in the center with a diameter that is slightly smaller than the outer diameter of the drain assembly **134**, is placed over the drain assembly **134** in such a manner that edges of an interior diameter of the drain reinforcing structure **136** interfere with the outer diameter of the prefabricated drain assembly **134**. The drain assembly **134** with the attached drain reinforcing structure **136** is then placed inside the tool such that it lies in a horizontal plane in an intermediary position between the cavity and the core of the tool. The polymeric material surrounds the drain assembly **134** and the drain reinforcing structure **136** when injected into the tool, thereby permanently embedding the drain assembly **134** with the attached drain reinforcing structure **136** within the floor **110** of the shower module **100** and integrating the prefabricated drain assembly **134** within the shower module **100**. The prefabricated drain assembly **134** may be any PVC, ABS, brass, copper, iron, or metal drain assembly designed to be coupled with any standard sized drain pipe. The drain rein-

forcing structure **136** may be mesh, solid, or porous, and made from wire, metal, fiberglass, plastic, polymers, or any combination of the foregoing. The density, thickness, size and shape of the drain reinforcing structure **136** will vary depending on the size, weight, drain aperture, and material of the drain assembly **134**.

[0067] Both the prefabricated drain assembly **134** and the drain fixture **135** subsequently attached to the drain aperture **130** may contain a male drain top which is inserted into a female drain either by pushing down or screwing down the male drain top into the female drain top. The male drain top may also be connected to a detachable drain screen **138** covering an aperture in the center of the male drain top. The detachable drain screen **138** may have the form of any geometric shape (e.g., circular, oval, square, rectangular, diamond, etc.). When the shower module **100**, **700**, **800** has been covered by tile, the male drain top with the drain screen **138** attached may either rest slightly below the surface of the tile or be substantially flush with the tile. Upon installation, the tile is cut to conform to the shape of the detachable drain screen **138**. The male drain top is lowered to the height of the tile or just below the tile height, and then the detachable drain screen **138** is attached to the top of the drain in a manner to conform to the drain screen shape formed by the installed tile. The height of the male drain top may be adjusted for use with tile of any thickness.

[0068] Any bowing or warping of the shower module **100**, **700**, **800**, the drain aperture **130**, or the drain assembly **134** creates problems in (i) attempting to properly seal the connection between the drain fixture **135** or the drain assembly **134** and the drain wall **132**, (ii) attempting to adhere the tiles to the upper surface **112** of the shower module **100**, **700**, **800**, (iii) attempting to connect the drain fixture **135** or the drain assembly **134** to a plumbing line, (iv) attempting to lower a male drain top into the female drain top of the drain assembly **134**, (v) attempting to insert the drain fixture **135** into the drain aperture **130**, (vi) attempting to have the lower surface **114** of the shower module floor **110** sit level on the subfloor once the drain wall **132** or drain fixture **135** is inserted into the opening in the subfloor, and (vii) maintaining a constant pitch and proper drainage of the upper surface **112** of the shower module floor **110** to the drain aperture **130**. Thus, to insure even cooling, it is important that the overall thickness of material be kept within certain limits. For example, the vertical distances in each of the four situations described below should be four inches or less:

[0069] (i) From the bottom edge **122** of each support rib **120** on the lower surface **114** to the upper surface **112** of the floor **110**;

[0070] (ii) From the bottom edge **122** of each support rib **120** on the lower surface **114** to the top edge **123** of each pitching rib **121** on the upper surface **112** of the floor **110**;

[0071] (iii) From the lower surface of the bottom panel **160** to the top edge **123** of each pitching rib **121** on the upper surface **112** of the floor **110**; and

[0072] (iv) From the lower surface of the bottom panel **160** to the upper surface **112** of the floor **110**.

[0073] Additionally, the difference between any two vertical distances described in each of the four (4) following situations should be three inches or less:

[0074] (i) The largest vertical distance from the bottom edge **122** of any portion of any support rib **120** on the lower surface **114** of the floor **110** to the upper surface

112 of the floor 110, and the shortest vertical distance from the bottom edge 122 of any portion of any support rib 120 on the lower surface 114 of the floor 110 to the upper surface 112 of the floor 110;

[0075] (ii) The largest vertical distance from the bottom edge 122 of any portion of any support rib 120 on the lower surface 114 of the floor to the top edge 123 of any pitching rib 121 on the upper surface 112 of the floor 110, and the shortest distance from the bottom edge 122 of any portion of any support rib 120 on the lower surface 114 of the floor 110 to the top edge 123 of any pitching rib 121 on the upper surface 112 of the floor 110;

[0076] (iii) The largest vertical distance from the lower surface of bottom panel 160 to the upper surface 112 of the floor 110, and the shortest vertical distance from the lower surface of the bottom panel 160 to the upper surface 112 of the floor 110; and

[0077] (iv) The largest vertical distance from the lower surface of bottom panel 160 to the top edge 123 of any pitching rib 121 on the upper surface 112 of the floor 110, and the shortest vertical distance from the lower surface of the bottom panel 160 to the top edge 123 of any pitching rib 121 on the upper surface 112 of the floor 110.

[0078] The thickness of any sidewall 101, 102, 103, 104 should be equal to or greater than $\frac{3}{8}$ inches to insure that the polymeric material properly flows throughout the cavity of the tool. Each sidewall 101, 102, 103, 104 may be connected to the floor 110 such that the orientation of the sidewall 101, 102, 103, 104 is within 10° of vertical to the common horizontal plane defined by the termination of the support ribs 120.

[0079] Additionally, in a preferred embodiment, the orientation of the support ribs 120 should not impede the direction of flow of the polymeric material during injection molding. For example, the support ribs 120 may run parallel to, perpendicular to, or at an acute angle to, the direction of flow of material. The important consideration is that the ribs are constructed in such a manner that the material flows relatively evenly through the tool, does not back up during the injection molding process, and does not create voids in the finished product. In alternative embodiments, the support ribs 120 may be arranged in a variety of configurations, such as a sunburst pattern 124 (see FIG. 7), a diamond pattern 125 (see FIG. 8), and a honeycomb pattern (see FIG. 9).

[0080] In an alternative embodiment, as shown in FIGS. 11-13, at least one peripheral edge of the floor 110 is not connected to a sidewall. The absence of at least one wall allows the shower module 1100, 1200 to provide access to physically impaired persons and meets requirements established by the Americans with Disabilities Act (ADA), 42 U.S.C. §§12101-12213 (2000). Any sidewall 104 or combination of sidewalls 101, 102, 103, 104 may be partially or completely omitted by placing at least one insert into the cavity of the tool prior to injecting the polymeric material, at a location corresponding to a sidewall 104 of the ADA shower module 1100, 1200. The insert fills all or a portion of the entire void in the tool intended to form the corresponding sidewall 104, thereby preventing polymeric material from flowing into the void and forming the sidewall 104. In this manner, the manufacturer may create a variety of shower modules 100, 1100, 1200 from the same tool, with the only difference being which portion of an entire sidewall 101, 102,

103, 104 is not included (e.g., a sidewall 103 along a longer side of the shower module 1100, a sidewall 104 along a shorter side of the shower module 1200, two sidewalls 102, 104 on opposite edges of the floor 110 to create a "pass-through" shower module (not shown), or two adjacent sidewalls 101, 102 to create a corner shower module (not shown)). The floor 110 of the ADA shower module 1100, 1200 at the entrance to the shower, after having tile installed on the upper surface 112, is virtually flush with the floor of the bathroom in which the shower module 110, 1200 is installed, or slightly raised. Further, the shower module 1100, 1200 is pitched from the peripheral edges of the floor 110 to the drain aperture 130. In this manner, a wheelchair or other mobility-assisting apparatus (e.g., a walker, crutches, a cane, etc.) may freely enter and exit the shower enclosure.

[0081] Because the ADA shower modules 1100 have all or a portion of at least one sidewall completely removed, the edges of the sidewalls 101, 103 adjacent to the removed sidewall are unsupported, which creates potential problems when transporting the shower module 1100 prior to installation. In addition, shower modules 1400, 1500 (See FIGS. 14-15) with an integrated curb 140 which is lower than one or more adjacent sidewalls 101, 102, 103, 104 likewise have portions of sidewalls that are not fully supported by adjacent sidewalls. These unsupported or not fully supported sidewall edges may break if the shower module 1100, 1200, 1400, 1500 is accidentally dropped or mishandled. To provide temporary support, removable support bars 150, 152 are connected between the upper edge of each sidewall 101, 103 and the peripheral edge of the floor 110 along the side missing a sidewall (or between the upper edge of each sidewall and the curb 140 for those modules 1400, 1500 having an integrated curb 140 with a lower height than an adjacent sidewall). These support bars 150, 152 may be diagonal beams, or solid shapes (e.g., triangular, rectangular, etc.) created during the molding process, or added after the shower module 1110 has been formed. In the event that the support bars 150, 152 are created during the molding process, they may include fatigue lines along the intersection created between the support bar 150, 152 and the sidewall 101, 103, and the intersection between the support bar 150, 152 and the floor 110. Alternatively, the fatigue lines may be created by the manufacturer by scoring the support bars 150, 152 along the above described intersections. Implementation of the fatigue lines allow an installer to easily and conveniently break the support bars 150, 152 away from the shower module 1100 after the shower module has been set in place in the area intended for a shower enclosure. Thus, the possibility that the edges of the sidewalls 101, 103 become damaged prior to installation is greatly reduced. Alternatively, the installer may simply cut the support bars 150, 152 away from the shower module 1100 after installation.

[0082] In a similar manner as described above, the height of a sidewall 104 or combination of sidewalls 101, 102, 103, 104 may be lowered to a height suitable for installing a modular curb 300 adjacent to the shower module 100. At least one insert that runs the entire length of a sidewall 101, 102, 103, 104, or any portion thereof, is placed inside the cavity of the tool prior to injecting the polymeric material, at a location corresponding to a sidewall 104 of the ADA shower module 1100, 1200. The height of the insert corresponds to the difference in height between a full sidewall 101, 102, 103 and the lowered sidewall 104. The insert partially fills the void in the tool intended to form the corresponding sidewall 104, thereby

preventing polymeric material from flowing into the void and forming a sidewall **104** having a lowered height. Inserts may be placed within the tool at locations corresponding to any sidewall or combination of sidewalls, thus allowing the manufacturer to create a variety of shower modules with a single tool.

[0083] In another alternative embodiment, as depicted in FIGS. **14-16**, at least one side wall **104** may include an integrated curb **140** that is molded into the shower module **1500** during fabrication. Similar to the methods described above, the tool may contain voids in the cavity and core, proximate to the location of any sidewall, corresponding to the shape of the integrated curb **140**. The manufacturer merely has to place inserts into the tool at the location of the unwanted curb to prevent the integrated curb from forming.

[0084] The use of inserts within the tool allows the manufacturer the flexibility of creating a wide variety of shower modules from a single tool. Each tool is an expensive investment. Additional charges are incurred every time a tool is changed out on the manufacturing line. The time required to change the tool is basically wasted time as the line is shut-down in anticipation of the new tool. Placing inserts into the tool, which are comparatively much less expensive than designing and purchasing individual tools for each permutation of sidewall, also allows for a much shorter downtime during the changeover as less time is required to fit or remove an insert than to completely remove and replace the whole tool. Thus, any combination of placement of sidewalls, height of sidewalls, integrated curbs, length of the shower module, and width of the shower module, may be accomplished using a single tool.

[0085] The shower module **100** may also be constructed to assist in preventing the spread of fire between floors of a multi-leveled building. In one embodiment, the drain wall **132** and an area on the lower surface **114** of the floor **110** within a given radius (e.g., 8 inches) of the drain wall **132** is coated with a fire retardant material. Thus, in the event that a fire were to ignite in a building one level below the bathroom where the shower enclosure is installed, the fire is hampered from spreading through the opening in the floor containing the drain pipe and engulfing the shower module **100**. Alternatively, the shower module **100** may be molded from a fire-retardant polyurethane foam. In addition, the area around the drain wall **132** that sits in the plumbing hole in the subfloor can be filled with a fire-retardant material after installation of the shower module **100**.

[0086] Tile should be retained on the sidewalls **101, 102, 103, 104** and the upper surface **112** of the floor **110** using a resin based epoxy. The epoxy may contain 100% resin solids or resin solids mixed with a solvent, provided the epoxy contains 60% or more resin solids.

[0087] 2. Method of Manufacturing

[0088] FIG. **17** illustrates an exemplary logic flow diagram **1700** executed by a manufacturer to implement a method for creating improved prefabricated shower modules suitable for use in constructing a tiled shower as described above. The manufacturer provides (**1702**) a tool for creating the leak-proof shower module **100**. The tool includes a cavity and a core which define a shape corresponding to a shape of the leak-proof shower module **100**. The shower module **100** may contain any, all, or a combination of the features detailed, supra, in Section 1. For example, the manufacturer may provide indentations in the tool that result in the formation of the support ribs **120** or the pitching ribs. The manufacturer may

also place one or more inserts into a voided area of the tool (i) that corresponds to a sidewall **101, 102, 103, 104** of the shower module **100**, thereby preventing the polymeric material from filling the voided area during injection molding, or (ii) corresponds to a portion of the length or width of the shower module thereby preventing the polymeric material from filling the voided area during injection molding. In addition, the manufacturer may mold a horizontal fatigue line **108** into one or more sidewalls **101, 102, 103, 104** by creating a raised tab along the length a voided area that corresponds to the sidewall **101, 102, 103, 104** at a height suitable for removing a portion of the sidewall **101, 102, 103, 104** and attaching a modular curb **300**.

[0089] Next, the manufacturer inserts (**1704**) one or more forms into the tool between the cavity and the core at the location established for the drain aperture **130** for the purpose of forming the drain aperture **130** in the floor **110** and the drain wall **132** of the shower module **100**. The drain aperture **130** may have a uniform diameter or the drain aperture **130** may have one or more diameters along the bottom portion of the drain aperture **130** for inserting all or a portion of a drain fixture **135** for connecting to the plumbing line, and a wider diameter at the top portion of the drain aperture **130** for inserting all or a portion of a plumbing fixture to accommodate a drain fixture top having a wider or variable diameter. Thus, the form may have a uniform diameter, or may contain a first portion corresponding to a drain fixture shape suitable for connecting to a plumbing line and a second portion corresponding to a drain fixture shape suitable for accommodating the drain top of drain fixture **135**. Alternatively, two forms may be used, wherein one form corresponds to a shape suitable for connecting to a plumbing line and the second form corresponds to a shape suitable for connecting to a plumbing line. A drain aperture reinforcing structure **136** may also be placed in the drain wall **132** and the floor **110** surrounding the drain aperture **130** to strengthen the area around the drain aperture **130**.

[0090] Next, the manufacturer injects (**1706**) a polymeric material into the tool to produce the leak-proof shower module **100**. The polymeric material should be injected into the tool such that the material flows in a direction unimpeded by any support rib **120**. Thus, the polymeric material should flow in a direction parallel, perpendicular, or at an angle of 90° or less to any support rib **120** of the plurality of support ribs **120** or to any pitching ribs **121** of the plurality of pitching ribs **121**.

[0091] The shower module **100** is cooled in the tool and as it cools, the polyurethane hardens and cures. Before it is completely cooled and cured, it may be removed (**1708**) from the tool and clamped (**1710**) to a rigid surface (e.g., a table, a workbench, etc.) while the shower module continues to cool (**1712**) and cure. Thus, the possibility of warping or bowing of the lower surface **114** or the upper surface **112** of the floor **110** of the shower module **100** is minimized. Additionally, the shower module **100** may actually spend less overall time in the tool before being removed as the steps taken during post-molding decrease the effects of any warping or bowing, thus allowing the shower module **100** to be removed faster than what would typically be acceptable. Thus, the manufacturing cycle-time per unit is reduced, which may reduce the total cost of the product.

[0092] After the shower module **100** has cooled to a solid condition (before or after removing the clamps) the manufacturer may coat (**1714**) the drain wall **132** and an area on the

bottom surface **114** of the floor **110** surrounding the drain wall **132** with a fire-retardant material.

[0093] Additionally, the shower module **100** may be modified to allow a modular curb **300** to be attached to a sidewall **101, 102, 103, 104** of the shower module **100**. The modification may be made by breaking (**1716**) the selected sidewall **101, 102, 103, 104** along a horizontal fatigue line at a height sufficient to allow attachment of a modular curb **300** thereto, and removing the excess portion. Alternatively, the sidewall **101, 102, 103, 104** may be cut to the appropriate height. Finally, the modular curb **300** is attached (**1718**) to the remaining portion of the sidewall **101, 102, 103, 104** by either the manufacturer (e.g., prior to shipment) or the installer (e.g., in the field).

[0094] After fabrication of the shower module **100** having a drain aperture **130** made for a drain fixture **135**, the drain fixture **135** is inserted into the drain aperture **130** and a water-tight seal is formed at one or more of (i) the upper surface **112** of the floor **110** at or around the drain aperture **130**, (ii) the drain aperture **130**, and (iii) the lower surface **114** of the floor **110** at or around the drain aperture **130**.

[0095] In an alternative embodiment, as illustrated in FIG. **18** by the exemplary logic flow diagram **1800**, a prefabricated drain assembly **134** may be embedded within the floor **110** and drain wall **132** of the shower module **100** during injection molding. Similar to the above process, the manufacturer begins by providing (**1802**) a tool for creating the shower module **100**. The tool includes a cavity portion and a core portion which define a shape corresponding to a shape of the shower module **100**. As above, the shower module **100** may contain any, all, or a combination of the features detailed, supra, in Section 1.

[0096] Next, the manufacturer attaches (**1804**) a drain reinforcing structure **136**, which contains an opening in the center, to a prefabricated drain assembly **134** in such a manner that the edges of the interior diameter of the drain reinforcing structure **136** interfere with the outer diameter of the prefabricated drain assembly **134**. The drain assembly **134** with the attached drain reinforcing structure **136** is then inserted (**1806**) inside the tool at a location corresponding to the location of the drain aperture **134** such that the drain reinforcing structure **136** lies in a horizontal plane in an intermediary position between the cavity and the core of the tool. Next, the manufacturer injects (**1808**) a polymeric material into the tool, thereby embedding the drain reinforcement structure **136** in the shower module **100** and integrating the drain assembly **134** within the floor **110** of the shower module **100**. As above, the polymeric material should be injected into the tool such that the material flows in a direction unimpeded by any support rib **120**. The manufacturer removes (**1810**) the integrated shower module **100** from the tool, clamps (**1812**) the shower module **100** to a table (or other rigid surface) to prevent movement, and allows the integrated shower module to cool (**1814**) while still clamped to the table.

[0097] 3. The Prefabricated Modular Curb

[0098] Generally, when constructing a tiled shower enclosure, installers build a curb at the intersection of the shower enclosure and the bathroom floor that serves as a dam to prevent water from escaping onto the floor. Typically, the curb was simply constructed by vertically stacking two or three wooden 2×4" boards, covering the boards with a leak-proof liner, and applying tile on top of the liner. At least one prefabricated curb **200**, as illustrated in FIG. **19**, has previously been offered for use in construction of shower enclosures.

The prior art curb **200** simply consists of a U-shaped form having a top wall **206**, a front wall **204**, and a rear wall **208**. The distance between the front wall **204** and the rear wall **208** is approximately the width of a standard 2×4 **202**. The prior art curb **200** is typically designed to receive structural support from 2×4's **202** stacked in the same manner as when a curb is constructed manually.

[0099] An embodiment of the present invention, as shown in FIGS. **20-23**, includes an improved prefabricated modular curb **300** suitable for use in constructing a tiled shower, in conjunction with a prefabricated shower module **100**, and method of installation. The modular curb **300** includes an exterior wall **320**, a top wall **330**, and a mounting wall **310** that engages a sidewall **101, 102, 103, 104** of a shower module **100** when installed proximate to the shower module **100**. The top wall **330** extends perpendicularly from the upper edge of the exterior wall **320** to the upper edge of the mounting wall **310**. Alternatively, the exterior wall **320** may be taller than the mounting wall **310** such that the top wall **330** is pitched to slope downwards toward the sidewall **101, 102, 103, 104** of the shower module **100** when the modular curb **300** is installed adjacent to the sidewall **300**. The outer surface of the exterior wall **320** and the outer surface of the top wall **330** are suitable for retaining tile, stone, and/or marble using an epoxy containing 100% resin solids or resin solids mixed with a solvent.

[0100] The modular curb **300** may also, but not necessarily, include a bottom wall **340** that extends from the bottom edge of the exterior wall **320** to the bottom edge of the mounting wall **310**, and opposite to the top wall **330**. At least one reinforcing curb rib **350** is attached to at least one of the top wall **330**, the inner surface of the mounting wall **310**, the inner surface of the exterior wall **320**, the bottom wall **340** (if present), or any combination thereof. The reinforcing curb rib **350** runs perpendicular to, parallel to or at an acute angle to the mounting wall **310** or the exterior wall **320**.

[0101] The combination of the modular curb **300** with the shower module **100** offers significant improvements over the prior art by combining a leak-proof shower module with an attached leak-proof mounting wall, thereby maintaining the leak-proof quality of the overall shower base system. In addition, the modular curb **300** may be manufactured from a single tool using a combination of inserts. Each insert corresponds to the cross-sectional shape of the modular curb **300**, but has varying lengths. By placing or removing one or more inserts, the length of the prefabricated modular curb **300** may be customized through the manufacturing process. Alternatively, the modular curb **300** may simply be cut to the desired length after fabrication.

[0102] In one embodiment, the top wall **330** may include a horizontal lip **360** on the upper surface along the length of one or both ends. The horizontal lip **360** should be at least 1 inch tall and at least ¾ inches wide so that a standard-sized wall-board may rest on the lip **360**. Additionally, the curb **300** may include a reinforcing curb rib **350** at one or both ends, connected perpendicularly to the exterior wall **320** and to the mounting wall **310** and effectively enclosing the corresponding end.

[0103] In another embodiment, the top wall **330** extends beyond the outer surface of the mounting wall **310** to terminate in a ledge **370** having a width substantially equal to the width of the sidewall **101, 102, 103, 104** of the shower module **100** (see FIG. **22**). Thus, when the modular curb **300** is installed adjacent to the shower module **100**, the ledge **370**

extends over the top of the sidewall **101, 102, 103, 104** and the outer edge of the ledge **370** is substantially flush with the inner surface of the sidewall **101, 102, 103, 104**.

[0104] In an alternative embodiment, as shown in FIG. **23**, the modular curb **300** may also include an attachment mechanism **316, 318** located along the outer surface of the mounting wall **310** for engaging a corresponding attachment mechanism **106** in the sidewall **101, 102, 103, 104** of the shower module **100**. The modular attachment mechanism **316, 318** may be a tab, a notch, a slot, a tongue, a groove, a ridge, a peg, an aperture, an interlocking clip, or any combination thereof.

[0105] In one embodiment, the modular curb **300** may be constructed using similar polyurethane reaction injection molding techniques as described above in relation to the prefabricated shower module **100**. The process of molding the modular curb **300** faces some similar issues as when molding the shower module **100**. For instance, the direction of flow of the polymeric material should be unimpeded by the reinforcing curb ribs **350** during injection molding in order for the material to flow properly. Thus, the reinforcing curb ribs **350** should run parallel to or at an angle of 90° or less to the direction of flow of polymeric material. Additionally, to provide the proper support, the modular curb **300** should be molded from a polyurethane foam (which may also be fire-retardant) having a density of 12 pounds per cubic foot or greater.

[0106] In another alternative embodiment, as shown in FIGS. **24-24A**, a prefabricated modular curb **400** includes an outer mounting wall **410**, an inner mounting wall **480**, an exterior wall **420**, and a top wall **430**. The top wall **430** is attached substantially perpendicular to the upper edge of the exterior wall **420**, to the upper edge of the inner mounting wall, and to the upper edge of the outer mounting wall **410**. The inner mounting wall **480** is located at an intermediary point between the outer mounting wall **410** and the exterior wall **420**. The distance from the outer mounting wall **410** to the inner mounting wall **480** is slightly greater than the width of a sidewall **101, 102, 103, 104** of the shower module **100**, such that when the curb **100** is mounted adjacent to the shower module **100**, the sidewall **101, 102, 103, 104** is retained between the outer mounting wall **410** and the inner mounting wall **480**. The exterior wall **420** may be the same height or taller than the inner mounting wall **480** so that the top wall **430** is horizontal or slightly pitched towards the shower module **100** upon installation. The outer mounting wall **410** is shorter than the inner mounting wall **480** and should rest on the floor **110** of the shower module **100** upon installation. Additionally, the modular curb **400** may include reinforcing curb ribs **450** attached to at least one of the top wall **430**, the inner mounting wall **480**, and the exterior wall **420**.

[0107] FIG. **25** illustrates an exemplary logic flow diagram **2500** executed by a shower enclosure installer to implement a method for constructing a tiled shower enclosure within an area bounded by a subfloor and stud framing using a prefabricated modular curb **300** and a prefabricated shower module **100**. The subfloor includes a plumbing connection that leads to a sewer line or septic tank. The installer begins by applying **(2502)** a quantity of adhesive material on the subfloor within the area bounded by the stud framing. Next, the installer sets **(2504)** a prefabricated leak-proof shower module **100** in place on the subfloor within the area bounded by the stud framing. The shower module **100** should be positioned on the subfloor such that the support ribs **120** are in supporting engagement

with the subfloor, at least one sidewall **101, 102, 103, 104** is substantially adjacent to the stud framing, and the drain assembly **134** is in fluid communication with the subfloor plumbing connection.

[0108] The installer then installs **(2506)** a prefabricated modular curb **300** adjacent to at least one sidewall that is not adjacent to the stud framing. Exemplary methods of installing the prefabricated modular curb **300** are detailed in the logic flow diagrams of FIGS. **26** and **27**. Following the steps for implementing the method detailed by logic flow diagram **2600**, the installer applies **(2602)** a quantity of adhesive material to the outer surface of the sidewall **101, 102, 103, 104** and sets **(2604)** the modular curb beside the sidewall **101, 102, 103, 104** such that the mounting wall **310** of the modular curb **300** is proximate to the sidewall **101, 102, 103, 104** and the top wall **330** is positioned at the same level or above the top edge of the sidewall **101, 102, 103, 104**. Next, the installer seals **(2606)** any gap between the mounting wall **310** and the sidewall **101, 102, 103, 104** using an epoxy based adhesive to form a water-tight, leak-proof seal. Additionally, or alternatively, the installer may fasten **(2608)** the modular curb to the subfloor, the framing studs, or the sidewall **101, 102, 103, 104** using brackets **380** and screws **382** or any other traditional fasteners (e.g., screws, nails, rivets, etc.). In the finished tiled shower enclosure, the fasteners are completely hidden from view by the application of tile.

[0109] Alternatively, the installer may set **(2702)** the prefabricated modular curb **300** adjacent to the sidewall **101, 102, 103, 104** such that an attachment mechanism **106** (e.g., a tab, a notch, a slot, a tongue, a groove, a ridge, a peg, an aperture, an interlocking clip, etc.) along an outer surface of the sidewall **101, 102, 103, 104** engages with a corresponding attachment mechanism **316, 318** along the outer surface of the mounting wall **310** of the modular curb **300**. The installer may also connect the modular curb **300** to the sidewall **101, 102, 103, 104** of the shower module **100** by inserting one or more screws **382** through the ledge **370**, engaging the sidewall **101, 102, 103, 104**, as shown in FIG. **22**.

[0110] Referring back to FIG. **25**, after installing the modular curb **300**, the installer then attaches **(2508)** wallboard to the framing such that a lower edge of the wallboard rests above and is flush with any sidewall **101, 102, 103, 104** adjacent to the stud framing. Finally, the installer installs **(2510)** tile on the wallboard, the module sidewalls **101, 102, 103, 104**, the floor **110**, and the modular curb **300**, thereby resulting in a tiled shower.

[0111] 4. The Shower Bench and Ledge

[0112] The final component of the leak-proof modular shower enclosure system includes a shower bench or ledge, as illustrated in FIGS. **28-30**. The combination of the bench and ledge with the shower module **100** offers significant improvement over prior art by attaching a leak-proof shower bench or ledge to a leak-proof shower module, at an attachment point that is also leak-proof, thereby maintaining the leak-proof integrity of the shower base system. In addition, the shower bench and shower ledge may each be made in their own tool using a combination of inserts, which permit the shower bench and the shower ledge to be made with a variable height, variable length, and variable depth so that the shower bench and the shower ledge can be customized either through the manufacturing process or after fabrication by cutting the shower bench and the shower ledge to the desired dimensions. The term "shower ledge" includes any structure, regardless of specific height, width, or length and having a substantially

horizontal surface, for use in constructing a tiled shower enclosure. A “shower ledge” may or may not be intended to support the weight of a person or persons. Thus, the use of the term “shower bench,” as used in the context of the following discussion is interchangeable with the term “shower ledge.” Typically, a “shower bench” is simply a shorter version of a “shower ledge.”

[0113] In one embodiment, the shower bench 500 is designed for installation between the shower module 100 and a stud-framed wall of the tiled shower enclosure. The shower bench 500 may include a rectangular seating surface 510, as shown in FIG. 28, connected to an upper edge of a sidewall 520 along each peripheral edge. The length of the shower seat 500 is preferably equal to either the width or the length of the corresponding shower module 100 with which the shower bench 500 will be installed. The lower edge of each sidewall 520 terminates in a common plane that either rests on the subfloor of the shower enclosure or connects to a corresponding peripheral edge of an optional bottom plate 540.

[0114] One sidewall 520 is divided into an upper portion 522 and a lower portion 524, wherein the lower portion is set back from the upper portion 522 along the entire length of the shower bench 500. The lower portion 524 is taller than the height of a sidewall 101, 102, 103, 104 of the shower module 100, and is set back from the upper portion 522 a distance slightly greater than the thickness of the sidewall 101, 102, 103, 104 of the shower module 100. In this manner, when the shower bench 500 is installed adjacent to the sidewall 101, 102, 103, 104 of the shower module 100 such that the sidewall 101, 102, 103, 104 of the shower module 100 resides within the setback area, thereby preventing the weight of the shower bench 500 from resting on the sidewall 101, 102, 103, 104 of the shower module 100. Additionally, as shown in FIG. 30, the outer surface of the upper portion 522 of the shower bench sidewall 520 should be flush with the inner surface of the sidewall 101 so that when tile 505 is installed to form the final shower enclosure, the transition between the shower module 100 and the shower bench 500 is unnoticeable.

[0115] In an alternative embodiment, as shown in FIG. 29, the shower bench 600 includes a triangular seating surface 610 connected to an upper edge of a sidewall 620 along each peripheral edge. The seating surface 610 may be any geometric shape suitable for forming a shower enclosure. Similar to shower bench 500, one sidewall 620 is divided into an upper portion 622 and a lower portion 624, wherein the lower portion is set back from the upper portion 622 along the entire length of the shower bench 600, allowing the shower bench 600 to be installed adjacent to a prefabricated shower module 100 without the weight of the shower bench resting upon the sidewall 101, 102, 103, 104 of the shower module 100.

[0116] In one embodiment of the present invention, the shower bench 500 may include at least one support rib 530 attached to at least one of the seating surface 510, any side wall 520, and the bottom wall, or any combination thereof, and extending downward to terminate coplanar with the lower edge of each sidewall. Each support or reinforcing rib runs parallel to, perpendicular to, or at an acute angle to, any side wall 530

[0117] When installed, the seating surface 510 may be horizontal or pitched downwards toward the prefabricated shower module 100. Additionally, the seating surface 510 may include a horizontal lip 550 at least 1 inch tall and at least $\frac{3}{8}$ inches wide along at least one peripheral edge to allow for a standard-sized wallboard to rest on the lip 550.

[0118] The seating surface and at least the upper portion 522 of the sidewall 520 adjacent to the sidewall 101, 102, 103, 104 of the shower module 100 have surfaces suitable for retaining tile, stone, or marble using an epoxy containing 100% resin solids or resin solids mixed with a solvent.

[0119] In one embodiment, the shower bench 500 may be constructed using similar polyurethane reaction injection molding techniques as described above in relation to the prefabricated shower module 100 and the modular curb 300. As in the case of the shower module 100 and the modular curb 300, the direction of flow of polymeric material should be unimpeded by the support ribs 530 during injection molding in order for the material to flow properly. Thus, the support ribs 530 should run parallel to, perpendicular to, or at an angle of 90° or less to the direction of flow of polymeric material. Additionally, to provide the proper support, the shower bench 500 should be molded from a polyurethane foam (which may also be fire-retardant) having a density of 12 pounds per cubic foot or greater.

[0120] FIG. 31 illustrates an exemplary logic flow diagram 3100 executed by a shower enclosure installer to implement a method for constructing a tiled shower enclosure within an area bounded by a subfloor and stud framing using a prefabricated shower bench 500, a prefabricated shower module 100, and optionally, a prefabricated modular curb 300. FIG. 32 illustrates an exemplary finished shower enclosure created using embodiments of the prefabricated shower bench 500, the prefabricated shower module 100, and the prefabricated modular curb 300 as disclosed by the present invention. The installer begins by mounting (3102) a prefabricated shower bench 500, adjacent to the stud framing such that a bench sidewall 520 that has a lower portion 524 set back from an upper portion 522 is facing the area where the shower module 100 is to be installed. The shower bench may be fastened to the stud framing using traditional fastening techniques (e.g., braces, screws, nails, adhesives, etc.). Thus, when someone sits on the shower bench 500, the person's weight is supported by both the bench support ribs 540 and the stud framing and not distributed to the shower module 100.

[0121] Next, the installer applies (3104) a quantity of adhesive material on the subfloor within the area bounded by the stud framing and the shower bench 500, and sets (3106) the shower module 100 in place on the subfloor within the area bounded by the stud framing and the shower bench 500. The shower module 100 is positioned on the subfloor such that at least one module sidewall 101 is substantially adjacent to the stud framing, and a second module sidewall 102 rests underneath the lower portion 524 of the bench sidewall 520. The inner surface of the second module sidewall 102 is flush with an outer surface of the upper portion 522 of the bench sidewall 520, and the drain assembly is in fluid communication with the subfloor plumbing connection. The installer may also, optionally, attach a prefabricated modular curb 300 to a third sidewall 104 using techniques described, supra, in Section 3 or use a shower module 1400, 1500 with an integrated curb 140.

[0122] Finally, the installer attaches (3108) wallboard to the framing such that a lower edge of the wallboard rests above and is flush with the first module sidewall 101, and finishes the shower enclosure by installing (3110) tile, stone and/or marble on the wallboard, the module sidewalls 101, 102, 103, 104, the floor 110, the optional modular curb 300, and the prefabricated shower bench 500.

[0123] All features of the shower bench 500 and corresponding methods of installation described herein may be equally applied to creating a shower ledge simply by extending the height of the sidewalls 520.

[0124] As described above, the present invention encompasses a modular system for creating a tiled shower enclosure including one or more component pieces (e.g., a prefabricated shower module with or without an integrated curb, a prefabricated modular curb, a prefabricated shower bench, and a prefabricated ledge), and methods of manufacturing and installing the associated component pieces. With this invention, manufacturers may improve cycle times for creating component parts while reducing yield losses, thereby resulting in lower costs for higher quality products. Additionally, the system offers tremendous flexibility in creating numerous combinations of component pieces, thereby providing many more options for creating modular shower enclosures. The system may be installed in the field in a fraction of the time required using traditional prior art methods, which greatly assists installers and contractors when building multiple enclosures (e.g., newly constructed condominiums, apartment buildings, hotels, dormitories, prisons, pre-manufactured housing, etc.).

[0125] In the foregoing specification, the present invention has been described with reference to specific embodiments. However, one of ordinary skill in the art will appreciate that various modifications and changes may be made without departing from the spirit and scope of the present invention as set forth in the appended claims. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense, and all such modifications are intended to be included within the scope of the present invention.

[0126] Benefits, other advantages, and solutions to problems have been described above with regard to specific embodiments of the present invention. However, the benefits, advantages, solutions to problems, and any element(s) that may cause or result in such benefits, advantages, or solutions to become more pronounced are not to be construed as a critical, required, or essential feature or element of any or all the claims. The invention is defined solely by the appended claims including any amendments made while this application is pending and all equivalents of those claims as issued.

What is claimed:

1. A prefabricated, polyurethane reaction injection molded, leak-proof shower module suitable for use in constructing a tiled shower, the shower module comprising:

a plurality of sidewalls;

a floor having an upper surface, a lower surface, and a plurality of peripheral edges, wherein the floor is bounded along at least one peripheral edge by at least one sidewall, the at least one sidewall extending substantially vertically from the at least one peripheral edge; and a plurality of ribs connected to the floor, each rib extending one of parallel to, perpendicular to, and at an acute angle to at least one peripheral edge toward at least one drain wall defining a drain aperture, each rib terminating in an outer edge, and each outer edge laying in at least one common plane.

2. The shower module of claim 1, wherein the upper surface slopes downward from each peripheral edge toward the at least one drain wall at a pitch equal to or greater than $\frac{1}{8}$ inch per foot, and

each rib of the plurality of ribs extends downward from the lower surface, resulting in the at least one common plane extending horizontally.

3. The shower module of claim 2, further comprising:

a bottom panel connected to the at least one sidewall and the outer edge of each rib.

4. The shower module of claim 1, wherein the lower surface extends in a horizontal plane from each peripheral edge to the at least one drain wall and each rib of the plurality of ribs extends upwards from the upper surface, and wherein the at least one common plane slopes downward from at least one peripheral edge towards the at least one drain aperture at a pitch equal to or greater than $\frac{1}{8}$ inch per foot.

5. The shower module of claim 1, wherein each sidewall is connected to the floor in an orientation within 10 degrees of vertical when the shower module is installed.

6. The shower module of claim 1, wherein the largest vertical distance from any outer edge of any rib to at least one of the upper surface and the lower surface is 4 inches or less.

7. The shower module of claim 1, wherein the difference between any two vertical distances measured from any two points on the outer edge of any rib to at least one of the upper surface and the lower surface is 3 inches or less.

8. The shower module of claim 1, wherein

at least one rib of the plurality of ribs extends upwards from the upper surface and wherein the at least one common plane slopes downward from at least one peripheral edge towards the at least one drain aperture at a pitch equal to or greater than $\frac{1}{8}$ inch per foot, and

at least two ribs of the plurality of ribs extend downward from the lower surface, resulting in each outer edge of the at least two ribs laying in a common horizontal plane.

9. The shower module of claim 7, wherein the largest vertical distance from any outer edge of any rib extending from the upper surface to any outer edge of any rib extending from the lower surface is 4 inches or less.

10. The shower module of claim 7, wherein the difference between any two vertical distances measured from any two points on the outer edge of any rib extending from the upper surface to any outer edge of any rib extending from the lower surface is 3 inches or less.

11. The shower module of claim 1, wherein any rib of the plurality of ribs runs parallel to a direction of flow of material during injection molding.

12. The shower module of claim 1, wherein any rib of the plurality of ribs runs at an angle of 90° or less to a direction of flow of material during injection molding.

13. The shower module of claim 1, wherein the plurality of ribs is arranged in at least one of a sunburst pattern, a diamond pattern, and a honeycomb pattern.

14. The shower module of claim 1, wherein the shower module is formed by injecting polymeric material into one or more injection sites of a tool, the tool including a cavity and a core which define a shape corresponding to a shape of the leak-proof shower module; and whereby the polymeric material flows through the tool at one or more angles, each angle being 90 degrees or less to the flow direction of the polymeric material from the one or more injection sites.

15. The shower module of claim 1, wherein the shower module is molded from a polyurethane foam having a density equal to or greater than 12 pounds per cubic foot.

16. The shower module of claim 1, wherein the shower module is molded from a fire-retardant polyurethane foam.

17. The shower module of claim 1, wherein the floor and the at least one sidewall define surfaces suitable for retaining at least one of tile, stone, and marble installed thereon.

18. The shower module of claim 17, wherein the at least one of tile, stone, and marble are retained using an epoxy containing at least one of 100% resin solids and resin solids mixed with a solvent.

* * * * *