

(12) **United States Patent**  
**Paul**

(10) **Patent No.:** **US 10,340,675 B2**  
(45) **Date of Patent:** **Jul. 2, 2019**

(54) **WATERTIGHT ELECTRICAL COMPARTMENT FOR USE IN IRRIGATION DEVICES AND METHODS OF USE**

(71) Applicant: **Hunter Industries, Inc.**, San Marcos, CA (US)

(72) Inventor: **Michael F. Paul**, San Diego, CA (US)

(73) Assignee: **Hunter Industries, Inc.**, San Marcos, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/254,457**

(22) Filed: **Jan. 22, 2019**

(65) **Prior Publication Data**

US 2019/0157852 A1 May 23, 2019

**Related U.S. Application Data**

(60) Division of application No. 15/845,362, filed on Dec. 18, 2017, now Pat. No. 10,199,815, which is a (Continued)

(51) **Int. Cl.**

**A01G 25/16** (2006.01)

**G01F 15/14** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **H02G 3/088** (2013.01); **A01G 25/16** (2013.01); **G01F 15/14** (2013.01); **G01F 15/063** (2013.01)

(58) **Field of Classification Search**

CPC ..... H02G 3/088; A01G 25/16; G01F 15/14; G01F 15/063

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,715,994 B2\* 4/2004 Patel ..... F04B 39/121 417/12

6,716,994 B1 4/2004 Patel et al. (Continued)

OTHER PUBLICATIONS

Node Battery-Operated Controller Owner's Manual and Programming Instructions, Hunter Industries, Inc., dated May 2011, in 20 pages.

(Continued)

*Primary Examiner* — Timothy J Thompson


*Assistant Examiner* — Michael F McAllister

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear LLP

(57) **ABSTRACT**

A watertight electrical compartment for use in an irrigation device can include a compartment body having a chamber and a sealing section configured to mate with one or more sealing rings. A sealing cap can mate with the sealing section and/or the sealing rings to seal the chamber. A cap retainer can be advanced over at least a portion of the sealing cap. One of the compartment body and cap retainer can have internal threads to be screwed onto external threads of the other one of the compartment body and cap retainer. The cap retainer can also have a stopping feature to keep the sealing cap in its sealed position. The watertight electrical compartment can be used in a wireless flow sensor assembly, a battery operated irrigation controller, and/or a battery-operated central controller device, to provide irrigation control, and/or sensor information, without the need for AC power.

**20 Claims, 20 Drawing Sheets**



**Related U.S. Application Data**

continuation-in-part of application No. 15/207,323,  
filed on Jul. 11, 2016, now Pat. No. 9,859,697.

(51) **Int. Cl.**

*H02G 3/08* (2006.01)

*G01F 15/06* (2006.01)

(58) **Field of Classification Search**

USPC ..... 174/541

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,090,146 B1 \* 8/2006 Ericksen ..... B05B 3/0431  
239/200  
9,795,095 B2 \* 10/2017 Franchini ..... A01G 25/165  
9,859,697 B1 1/2018 Paul  
2006/0006252 A1 1/2006 Wilson  
2006/0222508 A1 10/2006 Cantolino et al.  
2011/0089351 A1 \* 4/2011 Spadotto ..... A01G 25/165  
251/129.15

OTHER PUBLICATIONS

Wireless Valve Controller, Multiple Station Battery Powered Irrigation Controller Owner's Manual and Installation Instructions, Hunter Industries, Inc., dated May 2006, in 16 pages.

TBOS-II Control Module Technotes, Rainbird Corporation, dated Jul. 2012, in 20 pages.

DDC WP Series Waterproof Battery Controller Installation and Operating Instructions, The Toro Company, dated Oct. 23, 2006, in 6 pages.

\* cited by examiner






FIG. 2




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 4B




FIG. 4A




FIG. 4C




FIG. 4D




FIG. 4F




FIG. 4E




FIG. 5




FIG. 6A

FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C





FIG. 8D






FIG. 10




FIG. 11B




FIG. 11A




FIG. 11D




FIG. 11C




FIG. 11F




FIG. 11E




FIG. 12




FIG. 13




FIG. 14

**WATERTIGHT ELECTRICAL  
COMPARTMENT FOR USE IN IRRIGATION  
DEVICES AND METHODS OF USE**

CROSS-REFERENCE TO RELATED  
APPLICATION

This application is a divisional application of pending U.S. patent application Ser. No. 15/845,362, filed Dec. 18, 2017, titled "WATERTIGHT ELECTRICAL COMPARTMENT FOR USE IN IRRIGATION DEVICES AND METHODS OF USE," which is a continuation-in-part of U.S. patent application Ser. No. 15/207,323, filed Jul. 11, 2016, now U.S. Pat. No. 9,859,697 and titled "WATERTIGHT ELECTRICAL COMPARTMENT FOR USE IN IRRIGATION DEVICES AND METHODS OF USE," the entirety of each application is hereby incorporated by reference in its entirety.

FIELD OF THE DISCLOSURE

This disclosure relates to irrigation devices, and more particularly, to a watertight electrical compartment for sealing a compartment to be used in irrigation devices against the entry of water, mud, sand, dirt and the like.

BACKGROUND

An automatic irrigation device saves time, water, and money. Flow sensors are typically used to measure the amount of water flowing through an automated irrigation device. The flow sensor is normally connected to a mainline pipe that provides water to irrigation valves. The flow sensor is also wired to a terminal on an irrigation controller to transmit information about the amount of water that has flowed past the sensor to the controller. The controller may be connected to an electrical circuit that operates a solenoid attached to each irrigation valve and normally determines watering start and stop times. In some irrigation devices, the flow sensor can also automatically shut down the irrigation device if an overflow condition occurs.

Subterranean plastic valve boxes are commonly used for mounting irrigation valves, the flow sensor, and pipes of an irrigation device. The irrigation valve box makes it easier to repair and replace the irrigation device. The box can be covered by a plastic lid to prevent water, mud, dirt and the like from entering the box. In some environments, however, water, dirt, mud, and other environmental hazards may enter the box and gain access to the sensors, valves, and/or other components therein.

SUMMARY

There are situations in which obtaining AC power supply is not available or wiring the flow sensor to the controller is impractical or impossible. Examples of those situations include, but are not limited to, isolated sites, power-restricted areas, municipalities where underground power lines have not been laid, newly developed houses where power supply is not yet available, mines, and forests after a forest fire. In those situations, a battery operated controller may be advantageously used to provide irrigation without the need for power connections. Further, in an area where a large number of battery operated controllers are installed and managed by a single entity, it is inconvenient for the service crew to individually turn on and off each irrigation device. For example, all the irrigation devices may need to

be turned off during the rain and to be turned back on after the rain. There may also be need to reprogram the watering times of each controller as weather patterns change throughout the year. Accordingly, there is a need to provide a wireless battery-operated central control device to centrally manage all the battery operated irrigation devices in the area from a central computer. A wireless battery-operated central control device may include a controller to turn irrigation valves on and off.

There are situations in which it is impractical to physical wire a flow sensor to an irrigation controller. Examples of these may be where hardscapes, building, mature landscaping, roadways, or water in the form of ponds, pools, or streams may be in the path of the proposed wiring which may substantially inhibit a user's ability to run the wiring. In those situations, a wireless flow sensor assembly may be used in conjunction with other irrigation devices to provide feedback regarding the operation of an irrigation system. The wireless flow sensor can be powered by battery that is housed in a separate compartment and electrically connected to the flow sensor. The battery can be replaced every one to three years.

In these applications, wireless communication can use radiofrequency signals or other known wireless technology.

Both the wireless flow sensor assembly (WFS) and the battery-operated central control device (BOCC) can include an antenna or a transmitter that may need to be installed above the ground in order to transmit and/or receive signals. The WFS and the BOCC can be mounted inside the valve box with the antenna or transmitter extending above the ground through a hole cut in the plastic lid for transmitting and/or receiving signals.

The valve boxes are often flooded during rain or irrigation. Additionally, it is common for gophers or other animals to back fill the boxes so that the boxes are filled with mud and dirt, essentially burying the devices inside. It is important that water or mud entering the box does not get inside the electrical compartment to interfere with normal functioning of the battery or other electronic components inside the electrical compartment. Accordingly, there is a need for a watertight electrical compartment that can prevent entry of water, mud, dirt and the like.

Having one or more sealing rings, such as O-rings, between an electrical compartment body and a sealing cap can be effective in sealing the electrical compartment. Nevertheless, the friction between the sealing ring and the sealing cap makes it difficult to screw the sealing cap onto the compartment body. Likewise, once the cap has been tightly screwed onto the compartment body, the sealing ring makes it difficult to unscrew the cap, thereby making it difficult to reopen the electrical compartment. However, as mentioned above, the battery in the electrical compartment may need to be replaced every one to three years; other electronic components that can be housed in the electrical compartment may also require servicing at intervals. Accordingly, there is a need for a watertight electrical compartment that has easy-to-open sealing features for replacing the battery or servicing the electrical components housed inside the compartment.

According to some embodiments, a watertight electrical compartment for use in an irrigation device can include an electrical compartment body comprising a chamber with an open end, threads, and a sealing section, the sealing section located closer to the open end of the chamber than the threads; at least one sealing ring having a diameter configured for mating with the sealing section; a cap having an open end, a closed end, and an internal diameter configured

to have a sliding fit with the sealing section and an interference fit with the sealing ring when the compartment is assembled; and a cap retainer having threads configured to threadedly mate with the threads of the compartment body, the cap retainer further having first and second ends, the cap retainer configured to receive at least a portion of the cap through the first end.

In some embodiments, the at least one sealing ring can be configured to be mounted in at least one groove. The at least one groove can be located on an inner wall of the cap or on the sealing section of the compartment body. In some embodiments, the sealing ring can be resilient.

In some embodiments, the compartment body can comprise a channel extending further away from the open end than the sealing section along a length of the compartment body, the threads of the compartment body located on a radially inwardly facing inner wall of the channel, and wherein the threads of the cap retainer can comprise external threads. An inner wall of the cap retainer can be smooth.

In some embodiment, the cap can have a reduced outer diameter on its closed end and the cap retainer has a reduced inner diameter on its second end, the reduced inner diameter of the cap retainer configured to slidably accommodate the reduced outer diameter of the cap.

In some embodiments, the cap retainer can have a shoulder at its second end having an internal diameter smaller than an outer diameter of the cap, the shoulder configured to keep the cap engaged with the sealing section when the threads of the cap retainer mates with the threads of the compartment body.

In some embodiments, a wall of the cap can further comprise at least one notch at the open end.

In some embodiments, the sealing section can comprise at least one groove configured to receive the at least one sealing ring.

In some embodiments, the compartment can further comprise a plurality of sealing rings positioned between the cap and the sealing section of the electrical compartment body.

In some embodiments, the chamber of the compartment body can be configured to house at least one battery. In some embodiments, the chamber can comprise battery contacts. In some embodiments, the chamber can comprise a DIP switch. In some embodiments, the chamber can comprise flash programming pads.

In some embodiments, the compartment can be configured to be electrically coupled to a flow sensor.

According to some embodiments, a watertight electrical compartment for use in an irrigation device can include an electrical compartment body, at least one sealing ring, a cap, and a cap retainer. The electrical compartment body can comprise a chamber with an open end, and an outer wall surface having external threads and a sealing section, the sealing section located closer to the open end of the chamber than the external threads. The at least one sealing ring can have a diameter configured for mounting on the sealing section. The cap can have an open end, a closed end, and an internal diameter configured to have a sliding fit with the sealing section and an interference fit with the sealing ring when the sealing ring is mounted on the sealing section. The cap retainer can have internal threads configured to threadedly mate with the external threads of the compartment body, the cap retainer further having first and second ends, the cap retainer configured to receive at least a portion of the cap through the first end. In some embodiments, the compartment can be configured to be electrically coupled to a flow sensor.

In some embodiments, the cap can further include a non-threaded inner wall. In some embodiment, the cap can have a reduced outer diameter on its closed end and the cap retainer has a reduced inner diameter on its second end, the reduced inner diameter of the cap retainer configured to slidably accommodate the reduced outer diameter of the cap. In some embodiments, a wall of the cap can further comprise at least one notch at the open end.

In some embodiments, the cap retainer can have an inner wall comprising a non-threaded portion further away from the first end of the cap retainer than the inner threads. In some embodiments, the cap retainer can have a shoulder at its second end having an internal diameter smaller than an outer diameter of the cap. The shoulder can be configured to keep the cap engaged with the sealing section when the internal threads of the cap retainer mates with the external threads of the compartment body.

In some embodiments, the sealing section can further comprise at least one groove configured to receive the at least one sealing ring. In some embodiments, the watertight electrical compartment can further a plurality of sealing rings positioned between the cap and the outer wall surface of the electrical compartment body. In some embodiments, the sealing ring can be resilient.

In some embodiments, the chamber of the compartment body can be configured to house at least one battery. In some embodiments, the chamber can comprise battery contacts. In some embodiments, the chamber can comprise a DIP switch. In some embodiments, the chamber can comprise flash programming pads.

In some embodiments, the watertight electrical compartment can further include an electrical wire extending through the closed end of the cap and the cap is sealed after the wire has passed through the cap.

According to some embodiments, a method of sealing a watertight electrical compartment for use in an irrigation device can comprise providing an electrical compartment body, the compartment body comprising a chamber with an open end, threads, and a sealing section, the sealing section located closer to the open end of the chamber than the threads; mounting at least one sealing ring into at least one groove, the at least one groove located on the sealing section or on an inner wall of a cap, the cap having an open end and a closed end; sliding the cap over the sealing section through the open end, the cap having an internal diameter configured to have a sliding fit with the sealing section, wherein the at least one sealing ring seals a space between the sealing section and the inner wall of the cap; sliding a cap retainer having first and second ends over at least a portion of the cap through the first end of the cap retainer, the cap retainer having a stopper on the second end for retaining the cap, the cap retainer further having threads; and turning the cap retainer relative to the compartment body so that the threads of the cap retainer mate with the threads of the compartment body to keep the cap in a sealed position.

In some embodiments, the stopper on the second end of the cap retainer can comprise a shoulder having an internal diameter smaller than an outer diameter of the cap.

In some embodiments, sliding the cap retainer over at least a portion of the cap can comprise advancing the threads of the cap retainer past the cap towards the threads of the compartment body.

In some embodiments, the compartment body can comprise a channel extending further away from the open end than the sealing section along a length of the compartment body, the threads of the compartment body located on a

radially inwardly facing inner wall of the channel, and wherein the threads of the cap retainer can comprise external threads.

According to some embodiments, a method of sealing a watertight electrical compartment for use in an irrigation device can include providing an electrical compartment body comprising a chamber with an open end, an outer wall surface having external threads and a sealing section, the sealing section located closer to the open end of the chamber than the external threads; mounting at least one sealing ring onto the sealing section; sliding a cap having an open end and a closed end over the sealing section through the open end, the cap having an internal diameter configured to have a sliding fit with the sealing section, wherein an inner wall of the cap compresses the sealing ring mounted on the sealing section; sliding a cap retainer having first and second ends over at least a portion of the cap through the first end of the cap retainer, the cap retainer having a stopper on the second end for retaining the cap, the cap retainer further having internal threads; and turning the cap retainer so that the internal threads mate with the external threads of the compartment body to keep the cap in a sealed position. In some embodiments, the method of sealing a watertight electrical compartment for use in an irrigation device can further include mounting a plurality of sealing rings onto the sealing section. In some embodiments, sliding the cap retainer over at least a portion of the cap can comprise advancing the internal threads of the cap retainer past the cap towards the external threads of the compartment body.

All of these embodiments are intended to be within the scope of the disclosure herein. These and other embodiments will become readily apparent to those skilled in the art from the following detailed description having reference to the attached figures, the disclosure not being limited to any particular disclosed embodiment(s).

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the present disclosure are described with reference to the drawings of certain embodiments, which are intended to schematically illustrate certain embodiments and not to limit the disclosure.

FIG. 1 is an exploded view of an embodiment of a watertight electrical compartment.

FIG. 2 is a cross-sectional view of an embodiment of a watertight electrical compartment.

FIG. 2A is a side view of another embodiment of a watertight electrical compartment.

FIG. 2B is a cross-sectional view of the watertight electrical compartment of FIG. 2A.

FIG. 2C is a cross-sectional view of another embodiment of a watertight electrical compartment.

FIG. 2D is a cross-sectional view of another embodiment of a watertight electrical compartment.

FIG. 3 is a perspective view of an embodiment of a wireless flow sensor assembly (WFS) having a watertight electrical compartment.

FIGS. 4A-F are top, bottom, front, back, left and right views of the WFS assembly of FIG. 3.

FIG. 5 is an exploded view of the WFS assembly of FIG. 3 with the flow sensor and the lid retainer nut removed for clarity.

FIG. 6A is a cross-sectional view of the watertight electrical compartment of the WFS assembly of FIG. 3.

FIG. 6B is a detailed view illustrating the sealing features of the watertight electrical compartment of FIG. 6A.

FIG. 7 is a top view of a compartment body of the watertight electrical compartment of the WFS assembly of FIG. 3.

FIGS. 8A-D are perspective, top, side, and bottom views of an embodiment of a battery-powered irrigation controller.

FIG. 9 is an exploded view of the battery-powered irrigation controller of FIGS. 8A-D.

FIG. 10 is a perspective view of an embodiment of a battery-powered central controller device (BOCC) including a watertight electrical compartment for use in an irrigation device.

FIGS. 11A-F are top, bottom, front, back, left and right views of the BOCC of FIG. 10.

FIG. 12 is an exploded view of the BOCC of FIG. 10.

FIG. 13 is a cross-sectional view of the electrical compartment, the transmitter housing, and the antenna of the BOCC of FIG. 10.

FIG. 14 is a perspective view of an embodiment of a sealing cap in a watertight electrical compartment with an electrical wire coupled to the sealing cap.

#### DETAILED DESCRIPTION

Although certain embodiments and examples are described below, those of skill in the art will appreciate that the disclosure extends beyond the specifically disclosed embodiments and/or uses and obvious modifications and equivalents thereof. Thus, it is intended that the scope of the disclosure herein disclosed should not be limited by any particular embodiments described below.

##### Watertight Electrical Compartment

FIG. 1 shows an embodiment of a watertight electrical compartment 10 to be used in an irrigation device. The watertight electrical compartment 10 can comprise an electrical compartment body 100, a sealing ring 120, a sealing cap 140, and/or a cap retainer 160. The electrical compartment body 100, the sealing cap 140, and the cap retainer 160 can be made of any material suitable for environments exposed to water, mud, dirt, and the like, such as plastic materials. The compartment body 100, the sealing cap 120, and the cap retainer 160 can be made of the same material or different materials. The electrical compartment 10 can be of any size depending on a user's need.

In some embodiments, the sealing ring 120 can be mounted on the sealing section 114 of the compartment body 100. The sealing cap 140 can mate with the sealing section 114 and/or the sealing ring 120 to seal the compartment body 100. The cap retainer 160 can connect to the compartment body 100 and retain the sealing cap 140 in a sealed position between the cap retainer 160 and the compartment body 100.

As shown in FIG. 1, the electrical compartment body 100 can be cylindrically shaped with an first (e.g., open) end 102 and a second (e.g., closed) end 106. The shape of the compartment body 100 is not limiting. For example, in some cases, the compartment body 100 has a polygonal cross-section, an elliptic cross-section, or some other shape. The compartment body 100 can further comprise a wall 104 between the open and closed ends 102, 106. The wall 104 can have different/varying thicknesses from the open end 102 to the closed end 106. An inner wall surface 110 and the closed end 106 can define a chamber 112. In the illustrated embodiment, the chamber 112 can be cylindrically shaped. In other embodiments, the chamber 112 can have other shapes, such as, for example, rectangular or conical. In the illustrated embodiment, the inner wall surface 110 and the

closed end **106** can be smooth. In other embodiments, the inner wall surface **110** and the closed end **106** can have irregular surfaces.

In some embodiments, the chamber **112** can house a battery. In those embodiments, the chamber **312** can have battery contacts (e.g., the batter contacts **3120** as shown in FIG. 7). In some embodiments, the chamber **312** can also house electronic components or circuitry, for example, DIP switch **3124** (shown in FIG. 7), flash programming pads **3122** (shown in FIG. 7), memory cards, and the like. The type of electronic components or circuitry housed in the chamber **112** is not limiting. Electronic components or circuitry can be embedded at the bottom of the chamber **112**, in the inner wall surface **110** of the chamber **112**, and/or in some other location. The location of the electronic components in the chamber **112** is not limiting.

Turning back to FIG. 1, a sealing section **114** can be located on an outer wall surface **108** of the compartment body **100** near the open end **102**. The wall **104** can have a first outer diameter at the sealing section **114**. In some embodiments, the sealing section **114** can have one or more grooves **116** on the outer wall surface **108**, each groove **116** configured to receive one or more sealing rings. In some embodiments, the sealing section **114** can have a plurality of grooves **116**, each groove configured for receiving a sealing ring **120**. On the outer wall surface **108**, external threads **118** can be located further away from the open end **102** than the sealing section **114**. The external threads **118** can have a major diameter that is greater than the first outer diameter of the wall **104** at the sealing section **114**. In the illustrated embodiment, a difference between the major diameter of the external threads **118** and the first outer diameter of the wall **104** is large enough to accommodate a wall thickness of the cap **140**. In some embodiments, the external threads can be custom threads having any desired size and/or tolerance. In the illustrated embodiment, the external threads **118** can be separate from the sealing section **114** so as not to interfere and/or overlap with the sealing section **114**. A portion of the compartment body **100** near the closed end **106** can have a third outer diameter that is substantially the same or greater than the major diameter of the external threads **118**. The third outer diameter can be substantially the same as an outer diameter of the cap retainer **160** to advantageously provide a smooth and esthetically pleasing outer shape of the sealed electrical compartment **10**. In some embodiments, portions of, or the entire third outer diameter are smaller than the major diameter of the external threads **118** and/or smaller than the outer diameter of the cap retainer **160**.

With continued reference to FIG. 1, the sealing ring **120** can have an inner diameter configured for being received by the sealing section **114**. In the illustrated embodiment, the sealing ring **120** can have an inner diameter configured for a tight fit between the sealing ring **120** and the groove **116**. The sealing ring **120** can also have an outer diameter that is greater than the first outer diameter of the wall **104** at the sealing section **114**. When the sealing ring **120** is received at the sealing section **114**, a portion of the sealing ring **120** can extend radially outward from the outer wall surface **108** at the sealing section **114**. The precise extent to which the sealing ring **120** extends out from the grooves **116** is not limiting. In some embodiments, the sealing ring **120** can be resilient. In some embodiments, the sealing ring **120** can be made from elastomeric materials. For example, the sealing ring **120** can be an O-ring. The resilient sealing ring **120** can advantageously conform to a space between the outer wall **104** of the compartment body **100** and an inner wall surface **142** (shown in FIG. 2) of the sealing cap **140** when the

sealing cap **140** slides over the sealing section **114**, thereby providing effective sealing of the electrical compartment **10**. In some embodiments, one sealing ring **120** can be used. In other embodiments, a plurality of sealing rings can be used. In some embodiments, grease can be applied on the sealing ring **120** to allow the sealing cap **140** to slide smoothly over the sealing ring **120** mounted on the sealing section **114** and/or to reduce wear on the sealing ring **120**.

As shown in FIG. 1, the sealing cap **140** can be cylindrically shaped, although the shape of the sealing cap **140** is not limiting. The sealing cap **140** can have a first (e.g., open) end **144**, a second (e.g., closed) end **146**, and a wall **148** between the open and closed ends **144**, **146**.

More details of the sealing cap **140** will now be described with respect to FIG. 2. FIG. 2 shows a cross-sectional view of a watertight electrical compartment **20**. The electrical compartment **20** is similar to the electrical compartment **10** except that that the electrical compartment **20** can have two sealing rings **120**. Accordingly, features of the electrical compartment **20** can be incorporated into features of the electrical compartment **10** and features of the electrical compartment **10** can be incorporated into features of the electrical compartment **20**.

As shown in FIG. 2, an inner wall surface **142** of the cap **140** can have an internal diameter configured to have a sliding fit with the sealing section **114** and an interference fit with the sealing ring **120** when the sealing ring **120** is mounted on the sealing section **114**. Also as shown in FIG. 2, the sealing ring **120** can be compressed between the groove **116** and the inner wall surface **142** of the sealing cap **140**. In the illustrated embodiments, the inner wall surface **142** is not threaded. Turning back to FIG. 1, the wall **148** of the sealing cap **140** has a greater outer diameter near its open end **144** than at its closed end **146**. As mentioned above, the thickness of the wall **148** can be defined by the difference between the greater outer diameter and the internal diameter and can be smaller than the difference between the major diameter of the external threads **118** and the first outer diameter of the wall **104** of the compartment body **100**. With reference to FIGS. 1-2, when the sealing cap **140** fits over the sealing section **114** of the compartment body **100**, an outer wall surface **149** of the sealing cap **140** can be located radially inward from the major diameter of the external threads **118**, thereby advantageously inhibiting or preventing the sealing cap **140** from blocking the cap retainer **160** from moving at least partially past the sealing cap **140** toward the second end **106** of the compartment body **100**. The outer wall surface **149** also has a reduced-diameter portion **150** extending from the closed end **146** toward the open end **144**. In some embodiments, the reduced-diameter portion **150** can have a height of about 0.1" to 0.5". In some embodiments, the reduced-diameter portion **150** can have a height of about 0.15". In the illustrated embodiments, the reduced-diameter portion **150** can be cylindrical with a substantially uniform diameter. In other embodiments, the reduced-diameter portion **150** can be tapered, with the diameter increasing, e.g. gradually, from the closed end **146** toward the open end **144**. In some embodiments, the sealing cap **140** can have one or more notches **152** at the open end **144**. The notches **152** can advantageously allow the cap **140** be pried open, e.g. with a screw driver or other tool, in case the cap **140** is stuck during removal of the cap **140** from the compartment body **100** to reopen the sealed compartment **10**.

With continued reference to FIG. 1, the cap retainer **160** can be cylindrically shaped, although the shape of the cap retainer **160** is not limiting. The cap retainer **160** can have a first end **162**, a second end **164**, and a wall **166** between the

first and second ends **162**, **164**. An inner wall surface **168** of the cap retainer **160** can have internal threads **170** configured to threadedly mate with the external threads **118** of the compartment body **100**. In some embodiments, the internal threads **170** can be located near the first end **162** (e.g., nearer the first end **162** than the second end **164**). Having the internal threads **170** on the cap retainer **160** instead of on the sealing cap **140** can advantageously allow easy turning of the cap retainer **160** because the sealing cap **140** can cover the sealing ring **120** from the cap retainer **160**. For example, the threaded engagement between the cap retainer **160** and component body **100** can be separate from the sealed engagement between the cap **140** and the body **100**. The internal threads **170** can be custom threads having any desired size and/or tolerance. The inner wall surface **168** can have an internal diameter that is bigger than the greater outer diameter of the sealing cap **140**. In some embodiments, the cap retainer **160** and the sealing cap **140** can have a sliding fit. The sliding fit can allow the cap retainer **160** and the sealing cap **140** to rotate and/or move easily against each other. In some embodiments, the cap retainer **160** and the sealing cap **140** can have a running fit. The running fit can allow the cap retainer **160** and the sealing cap **140** to rotate and/or move freely past each other.

In the illustrated embodiment, the inner wall surface **168** can also have a non-threaded portion further away from the first end **162** of the cap retainer **160** than the internal threads **170**. The non-threaded portion can advantageously allow the cap retainer **160** to smoothly move over at least a portion of the sealing cap **140**. In the illustrated embodiment, the second end **164** of the cap retainer **160** can have an opening **172** surrounded by a shoulder **174**. The opening **172** can have a diameter that is greater than the reduced diameter of the reduced-diameter portion **150** of the sealing cap **140**, but less than the greater diameter of the sealing cap **140**. As shown in FIG. 2, when the cap retainer **160** is advanced from the closed end **146** of the sealing cap to its open end **144**, the reduced-diameter portion **150** of the sealing cap **140** can pass through the opening **172**, when the rest of the sealing cap **140** can be stopped from exiting the opening **172** by the shoulder **174**. A depth of the opening **172** can be defined by a thickness of the cap retainer **160** at the second end **164**. In some embodiments, the depth of the opening **172** can be about 0.1" to 0.5". In the illustrated embodiment, the depth of the opening **172** is the substantially same as the height of the reduced-diameter portion **150** of the sealing cap **140** so that the closed end **146** of the sealing cap **140** can be substantially flush with the second end **164** of the cap retainer **160**, resulting in a smooth and esthetically pleasing shape of the electrical compartment **10** when the electrical compartment **10** is sealed. Also as shown in FIG. 2, the opening **172** through the second end **164** has a substantially uniform diameter. In other embodiments, the opening **172** can be tapered, with the diameter increasing (e.g. gradually increasing) from the second end **164** toward the first end **162**. In yet other embodiments, the opening **172** can have one or more raised bumps or grooves to snap onto one or more corresponding grooves or raised bumps on the reduced-diameter portion **150** of the sealing cap **140**. In some embodiments, the second end **164** can be closed to retain the sealing cap **140**.

The embodiment of watertight electrical compartments **10**, **20**, as shown in FIGS. 1-2 can advantageously provide effective sealing via the sealing ring **120** between the compartment body **100** and the sealing cap **140**, while still allowing easy turning of the cap retainer **160**, which is separate from the sealing cap **140** and not subject to the

friction provided by the sealing ring **120**. The cap retainer **160** can retain the sealing cap **140** in a sealed position by the mating of the internal threads **170** on the cap retainer **160** and the external threads **118** on the compartment body **100**. The cap retainer **160** can also be easily screwed on and off from the compartment body **100** to allow replacement and/or servicing of the electrical components housed inside the chamber **112**.

Turning back to FIG. 1, the outer wall surface **108** near the closed end **106** of the compartment body **100**, the outer wall surface **149** near the closed end **146** of the sealing cap **140**, and/or an outer wall surface **167** near the second end **164** of the cap retainer **160** can further have a rugged or textured surface to increase friction between the outer wall surface and a user's hand for easy gripping. In other embodiments, the entire outer wall surfaces **108**, **149**, **167** can be rugged or textured. In the illustrated embodiment, the outer wall surfaces **108**, **149**, **167** can have a plurality of vertical indentations extending down a portion of the outer wall surfaces **108**, **149**, **167**. In other embodiments, the outer wall surfaces **108**, **149**, **167** can be corrugated. In yet other embodiments, the outer wall surfaces **108**, **149**, **167** can have raised pumps.

In some embodiments, a modified watertight electrical compartment can be similar to the electrical compartment **10** and can have features of the electrical compartment **10** except as described below. The modified electrical compartment can have a compartment body with a smooth outer wall surface near its open end **102** and a sealing cap **140** with a sealing section on its inner wall for receiving at least one sealing ring.

In some embodiments, such as shown in FIGS. 2A and 2B, a modified watertight electrical compartment **22** can be similar to the electrical compartment **10**, **20** of FIGS. 1 and 2 and can have features of the compartment **10**, **20** except as described below. As shown in FIG. 2B, instead of having internal threads **170** like the cap retainer **160** of FIGS. 1 and 2, the cap retainer **260** can have external threads **270** at or near the second end **262**. Instead of having external threads **118** like the compartment body **100** of FIGS. 1 and 2, the compartment body **200** in FIGS. 2A and 2B can have a channel **219** (e.g., an annular channel) with internal threads **218** located on a radially inwardly facing inner wall of the channel **219**. The channel **219** can be substantially concentric with the wall **204** between the first (e.g., open) end **202** and the second (e.g., closed) end **206**. The channel **219** can begin near the sealing section **214** further away from the first end **202** and extend toward the second end **206** along a length of the compartment body **200**. The channel **219** can have a width configured to accommodate the threaded portion of the cap retainer **260** that includes the external threads **270**. The sealing cap **140** can mate with the sealing section **214** and/or the sealing ring **120** to seal the compartment body **100**. The external threads **270** of the cap retainer **260** can mate with the internal threads **218** of the compartment body **200** to retain the sealing cap **140** in a sealed position between the cap retainer **260** and the compartment body **200**.

In some embodiments, such as shown in FIG. 2C, another modified watertight electrical compartment **24** can be similar to the electrical compartment **22** of FIGS. 2A and 2B and can have features of the compartment **22** except as described below. As shown in FIG. 2C, the sealing section **214** of the compartment body **200** can have a smooth surface. The inner wall **242** of the sealing cap **240** can include one or more grooves **216**. Each groove **216** can be configured to receive one or more resilient sealing rings **120**. The resilient sealing

11

ring 120 can advantageously conform to a space between the sealing section 214 of the compartment body 200 and an inner wall surface 242 of the sealing cap 240 when the sealing cap 240 slides over the sealing section 214 of the compartment body 200, thereby providing sealing of the electrical compartment 24.

Having the external threads on the retainer cap and the internal threads on the compartment body can create a tortuous path for water, dirt, and/or others to enter the chamber 212. The tortuous path can reduce and/or eliminate the amount of water, dirt, and/or others that can reach and/or accumulate at or near the interface between the sealing cap and the sealing section of the compartment body.

In some embodiments, such as shown in FIG. 2D, a modified watertight electrical compartment 26 can be similar to the electrical compartment 10, 20 of FIGS. 1 and 2 and can have features of the compartment 10, 20 except as described below. As shown in FIG. 2D, the sealing section 214 of the compartment body 200 can have a smooth surface. The inner wall 242 of the sealing cap 240 can include one or more grooves 216. Each groove 216 can be configured to receive one or more resilient sealing rings 120. The resilient sealing ring 120 can advantageously seal a space between the sealing section 114 of the compartment body 100 and an inner wall surface 242 of the sealing cap 240 when the sealing cap 240 slides over the sealing section 114 of the compartment body 100, thereby providing sealing of the electrical compartment 26.

#### Methods of Sealing a Watertight Electrical Compartment

Methods of sealing a watertight electrical compartment, such as the electrical compartments 10, 20, 22, 24, 26 of FIGS. 1, 2, and 2A-2D will now be described. The electrical compartment body 100, 200 as described above can be provided for housing electronic components and/or circuitry in its chamber. A sealing ring 120 can be fitted into the groove 116, 216, which can be located on the sealing section 114 or the inner wall 242 of the sealing cap 240. As shown in FIGS. 2 and 2B-2D, a plurality (e.g., two or more) of sealing rings 120 can be used in sealing the compartment. In some embodiments, the sealing ring 120 can be resilient, for example, an O-ring. In some embodiments, such as shown in FIGS. 2 and 2B, the sealing ring 120 can be slightly expanded by a radially outward force to clear the first outer diameter of the compartment body 100, 200 and then advanced from the open end 102, 202 of the compartment body 100, 200 to the sealing section 114, 214. The radially outward force on the sealing ring 120 can then be released so that the sealing ring 120 can form a tight fit with the sealing section 114, 214. In some embodiments, the sealing ring 120 can form a tight fit with the groove 116 of the sealing section 114, 214. In some embodiments, a plurality of the sealing rings can be mounted in one groove (not shown). In some embodiments, there may be more than one groove 116 with one sealing ring 120 in each groove 116.

With continued reference to FIGS. 1, 2, and 2A-2D, the sealing cap 140, 240 as described above can be placed over the sealing section 114, 214. The sealing section 114, 214 can be directed through the open end 144 of the sealing cap 140, 240 to reach a sealed position. The inner wall surface 142, 242 of the sealing cap 140, 240 can slide over the outer wall surface 108, 208 of the sealing section 114. In some embodiments, such as shown in FIGS. 2 and 2B, the inner wall surface 142 of the sealing cap 140 can compress an outer diameter of the sealing ring 120 mounted on the sealing section 114, 214 as the sealing cap 140 moves over the sealing section 114, 214. The compressed sealing ring 120 can advantageously seal any space between the inner

12

wall surface 142 of the sealing cap 140 and the outer wall surface 108 of the sealing section 114, thereby sealing the space. In some embodiments, such as shown in FIGS. 2C and 2D, the sealing ring(s) can be positioned on the inner wall surface 142 (e.g., in grooves) prior to mating the cap 140 with the sealing section 114. Placing the sealing cap 240 over the sealing section 114, 214 of the compartment body 100, 200 can cause the sealing section 114, 214 to expand an inner diameter of the sealing ring 120 fitted in the groove 216 on the sealing cap 240. The sealing ring 120 can seal any space between the inner wall surface 242 of the sealing cap 240 and the outer wall surface of the sealing section 114, 214.

With the sealing cap 140, 240 in the sealed position, the cap retainer 160, 260 as described above can be advanced over the sealing cap 140, 240. For example, the sealing cap 140, 240 can pass through the first end 162, 262 of the cap retainer 160, 260. The wall thickness of the sealing cap 140, 240 can allow the outer wall surface 149, 249 of the sealing cap 140, 240 to be located radially inward of the outer wall surface 108 at the major diameter of the external threads 118 in FIGS. 1-2 and 2D, or radially inward of the channel 262 in FIGS. 2B and 2C. The cap retainer 160, 260 can thus be advanced over at least a portion of the sealing cap 140, 240 unhindered. In some embodiments, such as shown in FIGS. 1-2 and 2D, the cap retainer 160 can be advanced over at least a portion of the sealing cap 140, 240 unhindered until the internal threads 170 of the cap retainer 160 reach the external threads 118 of the compartment body 100. In some embodiments, such as shown in FIGS. 2B-2C, the cap retainer 260 can be advanced over at least a portion of the sealing cap 140, 240 unhindered until the external threads 270 of the cap retainer 260 reach the internal threads 218 of the compartment body 200.

The cap retainer 160, 260 can be turned so that the threads of the cap retainer and the compartment body can mate with each other to lock the cap retainer 160, 260 on the compartment body 100, 200. The cap retainer 160 can also have a stopper on the second end 164 for preventing the sealing cap 140 from disengaging the sealing section 114 and/or the sealing ring 120, thereby locking the sealing cap 140 in the sealed position. As shown in FIGS. 1-2 and 2D, the stopper can comprise the shoulder 174 as described above so that only the reduced-diameter portion 150 of the sealing cap 140 can pass through the opening 172 and the rest of the sealing cap 140 can be stopped from moving through the opening 172 by the shoulder 174 because the opening 172 can be smaller than the greater outer diameter of the sealing cap 140. However, one of ordinary skill in the art should appreciate from the disclosure herein that other types of stopper can be used to keep the sealing cap 140 in the sealed position. In some embodiments, the shoulder 174 contacts the major-diameter portion of the sealing cap 140 before all the internal threads 170 can engage the external threads 118. In other embodiments, the shoulder 174 can just contact the major-diameter portion of the sealing cap 140 as all the internal threads 170 have substantially engaged the external threads 118. As shown in FIGS. 2B-2C, the cap retainer 260 can have similar stopper features.

#### Wireless Flow Sensor Assembly (WFS)

Example applications for a watertight electrical compartment, such as the electrical compartments 10, 20, 22, 24, 26 as shown in FIGS. 1, 2, and 2A-2D, will now be described. In some embodiments, the electrical compartment 30 can be used in a wireless flow sensor assembly (WFS) in FIGS. 3-5. The electrical compartment 30 is similar to the electrical compartments 10, 20, 22, 24, 26 of FIGS. 1, 2, and 2A-2D

except as described below. Accordingly, features of the electrical compartment 30 can be incorporated into features of the electrical compartments 10, 20, 22, 24, 26 and features of the electrical compartments 10, 20, 22, 24, 26 can be incorporated into features of the electrical compartment 30.

As shown in FIGS. 3 and 4A-4F, the WFS assembly 3 can include the watertight electrical compartment 30, an antenna dome 330, a lid retainer nut 35, a flow sensor retainer cap 36, a flow sensor 32, and/or an electrical wire 34 connecting the flow sensor 32 and the electrical compartment 30. In some embodiments, two or more components in the assembly communicate via wireless connection. The sealing cap 340, sealing retainer 360, and sealing section 314 (shown in FIG. 5) of the compartment body 300 can operate in the same or in a similar manner to the operation of the sealing cap 140, sealing retainer 160, and sealing section 114 of the compartment body 100 described above.

As shown in FIG. 3, the flow sensor 32 can have an impeller 3200 on a first end 3202. The flow sensor 32 can also be electrically coupled to the wire 34 at a second end 3204. The flow sensor 32 can be installed on a water line (e.g., into a T-connector perpendicular to a main water pipe that supplies water to an irrigation device). The flow sensor retainer 36 can retain the sensor 32 onto the T-connector. In the illustrated embodiment, the wire 34 can pass through a hole 3600 of the flow sensor retainer 36. The impeller 3200 can turn as the water flows through the pipe. The flow sensor 32 can generate a signal at intervals or continuously based on the amount of flow. For example, the flow sensor 32 can generate a signal each time a predetermined volume of water has flowed past the sensor 32. The signal can be sent in a manner described below to an irrigation controller (not shown) that can interpret and respond to the signal data from the sensor 32.

As described above, the wire 34 can electrically couple the flow sensor 32 and the electrical compartment 30. FIG. 5 illustrates an exploded view of the electrical compartment 30. As shown in FIG. 5, a chamber 312 of the compartment body 300 can house a battery holder 38 or 39. In some embodiments, the battery holder 38 may house a "D" size battery. In some embodiment's, the battery holder 39 may hold one or more "AA" sized batteries. In some embodiments, the battery holder 39 may hold three "AA" size batteries. Other battery holders holding different sized batteries could be used. In some embodiments, the chamber 312 holds a battery without a separate holder. In the illustrated embodiment, the battery holders 38, 39 can have a shape complementary to a shape of the chamber 312 to advantageously minimize movements of the battery holders 38, 39 inside the chamber 312. The battery holders 38, 39 can also have two protruding longitudinal ridges 380, 390 that are not uniformly spaced around a circumference of the battery holders 38, 39. The chamber 312 can have two longitudinal notches 3126 located on the inner wall surface 310 and having substantially the same spacing as the ridges 380, 390. The ridge-notch configuration can guide a user to insert the substantially cylindrical battery holders 38, 39 into the chamber 312 only in one orientation. As shown in FIG. 5, the battery holders 38, 39 can have flat protrusions 384, 394 for easier holding of the battery holders 38 or 39 when assembling the WFS assembly 3. In some embodiments, the ridge-notch configurations of the holders 38, 39 and chamber 312 permit installation of the holders 38, 39 in a plurality of rotational orientations with respect to the chamber 312. In some embodiments, the chamber 312 may only have one notch 3126. In some embodiments, battery holders 38, 39 may only have one ridge 380, 390.

Once the battery in the battery holder 38 or 39 is positioned in the chamber 312, the electrical compartment 30 can be sealed using the cap 340 and retainer 360 in a manner described above with respect to cap 140 and retainer 160. As shown in FIGS. 6A and 6B, the inner wall surface 342 of the sealing cap 340 can compress the sealing ring 320, e.g. two O-rings, against the sealing section 314, such as the grooves 316, of the compartment body 300. The cap retainer 360 can be advanced over at least a portion of the sealing cap 340. The shoulder 374 of the cap retainer 360 can inhibit the sealing cap 340 from moving through the opening 372 of the cap retainer 360 and disengaging the sealing section 314 and/or the sealing ring 320 when the cap retainer 360 is mated with the compartment body 300. The internal threads 370 of the cap retainer 360 can mate with the external threads 318 of the compartment body 300 to lock the sealing cap 340 in its sealed position.

Turning to FIG. 7, the chamber 312 can have battery contacts 3120 at its closed end. As described above, in some embodiments, the battery can be loaded into the chamber 312 in only one orientation. The particular orientation of the battery can advantageously allow terminals of the battery to be in contact with the battery contacts 3120 when loaded into the chamber 312. The chamber 312 can also have a DIP switch 3124 and flash programming pads 3122. The battery, the DIP switch 3124, and the flash programming pads 3122 can be electrically connected, e.g. in an electrical circuit, with the battery providing power to the circuit. As shown in FIG. 5, the wire 34 can exit the compartment body 300 at a location between the open and closed ends 302, 306. The wire 34 can be electrically coupled to the battery contacts 3120 so that the battery can advantageously provide power to the flow sensor 32. The wire can also send the signals from the flow sensor 32 to the electrical circuit inside the chamber 312. The signals can then be transmitted wirelessly to an irrigation controller (not shown), thereby eliminating a possible need to physically wire the flow sensor 32 to the irrigation controller. The WFS assembly 3 can also have an antenna 330 to facilitate transmitting and/or receiving signals. In the illustrated embodiment, the antenna 330 can be dome-shaped and be attached to the closed end 306 of the compartment body 300. In some embodiments, the antenna dome 330 can also receive signals, e.g. from the controller, a remote control, and/or a computer. In some embodiments, the antenna dome 330 can both transmit and receive signals. The antenna dome 330 can communicate wirelessly with another electronic device, such as the controller, intermittently or continuously.

Turning back to FIG. 3, the lid retainer nut 35 can be used to mount the electrical compartment 30 and the antenna dome 330 on a plastic lid of a valve box (not shown), in which the flow sensor 32 can be installed. Specifically, the outer wall surface 308 of the compartment body 300 can have external threads 309. As shown in FIG. 3, the external threads 309 can be located between the external threads 318 and the antenna dome 330. The lid retainer nut 35 can have internal threads (not shown) that can threadedly mate with the external threads 309 of the compartment body 300. In some embodiments, the external threads 309 can be custom threads having any desired size and/or tolerance. For installation, the sealed electrical compartment 30 can be passed through a hole on the lid (not shown). The antenna dome 330 can be located on an outer surface of the lid and can have a diameter that is bigger than the hole on the lid so that an undersurface 332 (shown in FIG. 5) of the dome 330 can rest on the outer surface of the lid. The lid retainer nut 35 can be advanced from the sealed open end 302 of the compartment

body **300** toward the dome **330**, while the internal threads of the lid retainer nut **35** can engage the external threads **309**. The lid retainer nut **35** can stop advancing toward the dome **330** when the lid retainer nut **35** contacts an inner surface of the lid. In some embodiments, the lid retainer nut **35** can be turned another quarter to a half turn after the lid retainer nut **35** touches the inner surface of the lid to advantageously fix the lid between the dome **330** and the lid retainer nut **35**.

To reopen the installed electrical compartment **30**, the lid can be lifted open and turned over to exposed the sealed open end **302**. The cap retainer **360** can be unscrewed from the compartment body **300**. The cap retainer **360** can be easily unscrewed, not needing to overcome the friction of the sealing ring **320**. The sealing cap **340** can then be pulled away from the compartment body **300**. A tool such as a screwdriver can be used to pry open the sealing cap **340** at the notches **352** (shown in FIG. **5**) if the sealing cap **340** gets stuck with the sealing ring **320**. Once the electrical compartment **30** is reopened, the batteries can be replaced and/or electronic circuitry can be serviced.

#### Battery-Operated Controller

In some embodiments, the watertight electrical compartment can be incorporated into an irrigation controller to make a battery-operated controller **80** shown in FIGS. **8A-D** and **9**. The battery operated controller **80** is similar to the electrical compartments **10**, **20**, **22**, **24**, **26** of FIGS. **1**, **2**, and **2A-2D** except as described below. Accordingly, features of the battery operated controller **80** can be incorporated into features of the electrical compartments **10**, **20**, **22**, **24**, **26** and features of the electrical compartments **10**, **20**, **22**, **24**, **26** can be incorporated into features of the battery operated controller **80**.

As shown in FIG. **9**, the battery operated controller **80** can include a compartment body **800** having a chamber **812**, a sealing section **814**, and/or external threads **818**. The chamber **812** can accommodate batteries **892** (e.g., DC batteries). In the illustrated embodiment, the chamber **812** can have a shape that is complementary to a shape of the batteries **892** to minimize movement of the batteries **892** inside the chamber. In some embodiments, the battery operated controller **80** includes one or more battery holders configured to retain the batteries and electrically interface with one or more features of the battery operated controller **80**.

Although not shown, the chamber **812** can also include electrical circuitry for connecting with the batteries **892** so that the electrical circuitry can draw power from the batteries **892**. The battery operated controller **80** also can have at least one (e.g., one, two, three, or more) sealing ring(s) **820** to be mounted on the sealing section **814**, and a sealing cap **840** having an inner wall surface (not shown) to engage the sealing section **814** and/or the sealing ring(s) **820** to provide sealing of the battery operated controller **80**. The battery operated controller **80** can further have a cap retainer **860** to retain the sealing cap **840** in a sealed position and having internal threads **870** to engage the external threads **818** of the compartment body **800**. The sealing cap **840**, sealing retainer **860**, and sealing portions of the compartment body **800** can operate in the same or in a similar manner to the operation of the sealing cap **140**, sealing retainer **160**, and compartment body **100** described above.

Turning to FIGS. **8A-B**, the closed end **810** of the compartment body **800** can further have a user interface, including but not limited to control buttons **895** and/or a display **896**. Although not shown, the user interface of the compartment body **800** can be in an electrical connection with the circuitry and the batteries **892** in the chamber **812**. In some configurations, the battery operated controller **80**

can allow irrigation to occur without tapping into an AC power. The battery operated controller **80** can be installed in places where it is difficult to connect the battery operated controller **80** to other sources of power (e.g., power lines). The sealing features of the battery operated controller **80** can allow the battery operated controller **80** to be installed in environments exposed frequently to rain, flooding, and/or mud without affecting the electrical circuitry and the batteries **892** sealed inside the chamber **812**.  
Wireless Battery-Operated Central Controller Assembly (BOCC)

In some embodiments, the electrical compartment **101** can be used in a wireless battery-operated central controller assembly (BOCC) **11** in FIGS. **10-12**. The electrical compartment **101** is similar to the electrical compartments **10**, **20**, **22**, **24**, **26** of FIGS. **1**, **2**, and **2A-2D** except as described below. Accordingly, features of the electrical compartment **101** can be incorporated into features of the electrical compartments **10**, **20**, **22**, **24**, **26** and features of the electrical compartments **10**, **20**, **22**, **24**, **26** can be incorporated into features of the electrical compartment **101**.

As shown in FIGS. **10-12**, the BOCC **11** can include the watertight electrical compartment **101**, a transmitter housing **1085** for housing transmitters **1086** (shown in FIG. **13**) and coupled to an antenna dome **1030**, a lid retainer nut **1035**, a flow sensor retainer cap **1036**, a flow sensor **1032**, and/or an electrical wire **1034** connecting the flow sensor **1032** and the electrical compartment **101** in a manner described below. In addition, as described above, the BOCC **11** is a battery powered irrigation controller that can be used to control multiple irrigation valves to turn those irrigation valves on and off. The BOCC **11** is in wireless communication with a central computer. Irrigation programs and other commands for turning on and off the irrigation valves can be initiated from the central computer. In some embodiments, at least one irrigation program may be sent from the central computer to the BOCC **11** and the BOCC **11** may store that irrigation program for future use. In some embodiments, the BOCC **11** may turn individual valves on and off in accordance with the stored irrigation programs. In some embodiments, the BOCC **11** can consume more power than the battery operated controller **80**. In addition, the battery that can be sealed within the electrical compartment **101** can be quickly depleted and may require frequent replacements. Further, the electrical compartment **101** can already be filled with electronic components and/or circuitry possibly needed for communicating wirelessly with the central computer and have no spare space for batteries. The BOCC **11** can thus have a separate battery pack **1038** to be electrically connected to the electrical compartment **101** via an electrical wire **1080** in a manner described below to meet the power consumption need of the BOCC **11**.

As shown in FIG. **12**, the battery pack **1038** can have a container for holding a battery retainer **1039**. The battery pack **1038** and battery retainer **1039** can be constructed from a polymer, a ceramic, a metal, a combination thereof, and/or any other suitable material. The battery retainer **1039** can be sized, shaped, and configured to retain batteries having one or more different sizes and/or ratings. In the illustrated embodiment, the container and the battery retainer **1039** can have complementary shapes to minimize movement of the battery retainer **1039** inside the container. For example, the container can have tracks on its inner wall surface for guiding ridges on an outer surface of the battery retainer **1039**. The battery pack **1038** can also have a sealing cover **1033** to provide watertight sealing (e.g., with O-rings) of the container. A battery end **1087** of the wire **1080** can run

through an opening **1031** of the sealing cover **1033** to contact the battery retainer **1039**. A sealing cap end **1081** of wire **1080** can also run through an opening **1082** (shown in FIG. **14**) of the sealing cap **1040** of the electrical compartment **101** to contact the electronic components and/or circuitry in the electrical compartment **101**. As shown in FIG. **12**, the battery pack **1038** can also have a mounting ring **1037** that can be used to hang the battery pack **1138** around the transmitter housing **1085**. The mounting ring **1037** can advantageously keep the battery pack **1038** within close proximity of the electrical compartment **101**, thereby reducing the danger of the battery pack **1038** moving further away from the electrical compartment **101** and tugging on the wire **1080**.

Connection of the wire **1080** to the sealing cover **1033** and the sealing cap **1040** will now be described. FIGS. **13-14** illustrates how the sealing cap end **1081** of wire **1080** can be connected to the sealing cap **1040**. One of ordinary skill in the art would appreciate from the disclosure herein that the wire **1080** can be connected to the sealing cover **1033** in same or in a similar manner to the connection of the wire **1080** and the sealing cap **1040** as described below.

As shown in FIGS. **13-14**, the sealing cap **1040** can comprise the opening **1082** for the electrical wire **1080** to pass through. As shown in FIG. **13**, the wire **1080** can have a seal (e.g., an overmolded strain relief **1084**) covering a portion of the wire **1080** at a sealing cap end **1081** of the wire **1080**. The portion of the wire **1080** covered by the overmolded strain relief **1084** can be passed through the opening **1082** on the closed end **1046** of the sealing cap **1040**. As shown in FIGS. **13** and **14**, the sealing cap **1040** can have a filling well **1092** facing an open end **1044** of the sealing cap **1040**. After the portion of the wire **1080** covered by the overmolded strain relief **1084** is passed through the opening **1082**, the filling well **1092** can be filled with a sealing material to seal any gap between the opening **1082** and the overmolded strain relief **1084** so as to prevent water or mud ingress into the cap **1040** and to fix the wire **1080** to the sealing cap **1040**. In some embodiments, the sealing material can be a polyurethane encapsulating compound. The strain relief **1084** can advantageously provide a transition from the flexible wire **1080** to a rigid connection point at the opening **1082** of the sealing cap **1040**. More particularly, the strain relief **1084** can prevent any mechanical force applied to an exterior of the wire **1080** from being transferred to the rigid connection point at the opening **1082** of the sealing cap **1040**, thereby reducing failure of the wire **1080**. In the illustrated embodiment, the electrical wire **1080** can terminate at an electrical connector **1090** after the wire **1080** is passed through the cap **1040**. The electrical connector **1090** can be connected to electrical components or circuitry housed in the chamber. In some embodiments, the wire **1080** can advantageously deliver power to electrical components or circuitry in the chamber.

Returning to the electrical compartment as shown in FIG. **12**, besides the sealing cap **1040**, the electrical compartment **101** can have a compartment body **1000**, at least one (e.g., one, two, three, or more) sealing ring(s) **1020**, and a cap retainer **1060**. The electrical component **101** can be sealed in a manner described above in connection with the electrical compartments **10**, **20**, **22**, **24**, **26**. For example, the sealing cap **1040**, sealing retainer **1060**, and sealing portions of the compartment body **1000** can operate in the same or in a similar manner to the operation of the sealing cap **140**, sealing retainer **160**, and compartment body **100** described above.

The electrical compartment **101** can further have connecting terminals **1077** exiting from the compartment body **1000**. The connecting terminals **1077** can connect to at least one irrigation valve. In some embodiments, there may be more connecting terminals **1077** to individually connect to more irrigation valves, (e.g., two, three, four, or more irrigation valves). In some embodiments, the BOCC **11** maybe able to control each irrigation valve individually via programming or other commands sent from the central computer.

In some embodiments, the electrical compartment **101** can have connecting terminals **1079** exiting from the compartment body **1000**. In some embodiments, the connecting terminals **1079** may be supplied as a loop, or otherwise connected together, to allow the controller to operate without an optional sensor. In other embodiments, the connecting terminals **1079** may be separated and connected to an optional sensor, such as a rain shut off sensor, a temperature sensor, or other sensors that may be used to inhibit and/or allow irrigation. For example, a user may cut a looped terminal **1079** and connect the open loop to a sensor (e.g., a rain shut off sensor). The rain sensor can be configured to close the loop in the absence of rain and open the loop in the presence of rain. Opening the loop can inhibit or prevent operation of the one or more irrigation valves. This functionality can reduce the likelihood that irrigation takes place during rain. The electrical compartment **101** can further have connecting terminals embedded into the wire **1034** exiting from the compartment body **1000**. The wire **1034** can connect to a flow sensor **1032**. The flow sensor **1032** can have similar functions as the flow sensor **32** shown in FIGS. **4A-4C** and be mounted on a main water pipe as described above. The connecting terminals **1077** can also connect to other parts of the irrigation devices and/or to a central computer.

With continued reference to FIG. **12**, a first end of the transmitter housing **1085** can be position on a closed end **1006** of the compartment body **1000**. In some embodiments, the transmitter housing **1085** can form an integral part with the compartment body **1000**. In other embodiments, the transmitter housing **1085** can be mechanically coupled (e.g., welded, adhered, fastened, and/or otherwise coupled) to the compartment body **1000**. As shown in FIG. **13**, the electrical connector **1090** can connect the wire **1080** to a controller circuitry **1095** inside the water electrical compartment **101**, which can advantageously protect the controller circuitry **1095** from water, mud, dirt, and the like. In the illustrated embodiment, the controller circuitry **1095** can be attached to an inner wall of the closed end **1006** of compartment body **1000** defining a ceiling of the chamber **1012**. The controller circuitry **1095** can also be electrically coupled to the transmitters **1086**. The transmitters **1086** can advantageously send ON/OFF and/or other control signals to irrigation devices. In some embodiments, the housing **1085** can house receivers (not shown). In some embodiments, the housing **1085** can house both the transmitters and receivers, or transceivers to advantageously communicate wirelessly with irrigation devices. The BOCC **11** can have a detachable dome **1030** to facilitate mounting the BOCC **11** to a lid of an irrigation box. The detachable dome **1030** can be mechanically attached to a second end of the transmitter housing **1085**. In some embodiments, the detachable dome **1030** can incorporate internal threads that can threadedly mate with external threads **1088** on an outer wall surface of the transmitting housing **1085**.

The lid retainer nut **1035** can be used to mount the electrical compartment **101**, the transmitters **1086** in the

transmitter housing **1085**, and the detachable dome **1030** on a plastic lid of a valve box (not shown). As shown in FIG. **13**, the lid retainer nut **1035** can have internal threads **1089** that can threadedly mate with the external threads **1088** of the transmitter housing **1085**. In some embodiments, the external threads **1088** can be custom threads having any desired size and/or tolerance. Installation of the BOCC **11** may be accomplished by removing the detachable dome **1030** and inserting the transmitter housing **1085** through a hole in the lid of a valve box. The detachable dome **1030** may then be reinstalled and tightened until hand tight. Tightening of the retainer nut **1035** may be performed to complete the installation, and reopening of the electrical compartment **101** can be in similar manners as described above regarding the WFS assembly **3**.

Although this disclosure has been described in the context of certain embodiments and examples, it will be understood by those skilled in the art that the disclosure extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses and obvious modifications and equivalents thereof. In addition, while several variations of the embodiments of the disclosure have been shown and described in detail, other modifications, which are within the scope of this disclosure, will be readily apparent to those of skill in the art. Sensors other than flow sensors may be incorporated into any of the above mentioned devices. Other sensors may include soil moisture sensors, temperature, solar radiation, light, humidity, wind, and/or any other sensors that monitor irrigation efficiency, weather, plant conditions, or soil conditions. It is also contemplated that various combinations or sub-combinations of the specific features and aspects of the embodiments may be made and still fall within the scope of the disclosure. For example, features described above in connection with one embodiment can be used with a different embodiment described herein and the combination still fall within the scope of the disclosure. It should be understood that various features and aspects of the disclosed embodiments can be combined with, or substituted for, one another in order to form varying modes of the embodiments of the disclosure. Thus, it is intended that the scope of the disclosure herein should not be limited by the particular embodiments described above. Accordingly, unless otherwise stated, or unless clearly incompatible, each embodiment of this invention may comprise, additional to its essential features described herein, one or more features as described herein from each other embodiment of the invention disclosed herein.

Features, materials, characteristics, or groups described in conjunction with a particular aspect, embodiment, or example are to be understood to be applicable to any other aspect, embodiment or example described in this section or elsewhere in this specification unless incompatible therewith. All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive. The protection is not restricted to the details of any foregoing embodiments. The protection extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

Furthermore, certain features that are described in this disclosure in the context of separate implementations can also be implemented in combination in a single implemen-

tation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations, one or more features from a claimed combination can, in some cases, be excised from the combination, and the combination may be claimed as a subcombination or variation of a subcombination.

Moreover, while operations may be depicted in the drawings or described in the specification in a particular order, such operations need not be performed in the particular order shown or in sequential order, or that all operations be performed, to achieve desirable results. Other operations that are not depicted or described can be incorporated in the example methods and processes. For example, one or more additional operations can be performed before, after, simultaneously, or between any of the described operations. Further, the operations may be rearranged or reordered in other implementations. Those skilled in the art will appreciate that in some embodiments, the actual steps taken in the processes illustrated and/or disclosed may differ from those shown in the figures. Depending on the embodiment, certain of the steps described above may be removed, others may be added. Furthermore, the features and attributes of the specific embodiments disclosed above may be combined in different ways to form additional embodiments, all of which fall within the scope of the present disclosure. Also, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described components and systems can generally be integrated together in a single product or packaged into multiple products.

For purposes of this disclosure, certain aspects, advantages, and novel features are described herein. Not necessarily all such advantages may be achieved in accordance with any particular embodiment. Thus, for example, those skilled in the art will recognize that the disclosure may be embodied or carried out in a manner that achieves one advantage or a group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

Conditional language, such as “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements, and/or steps are included or are to be performed in any particular embodiment.

Language of degree used herein, such as the terms “approximately,” “about,” “generally,” and “substantially” as used herein represent a value, amount, or characteristic close to the stated value, amount, or characteristic that still performs a desired function or achieves a desired result. For example, the terms “approximately,” “about,” “generally,” and “substantially” may refer to an amount that is within less than 10% of, within less than 5% of, within less than 1% of, within less than 0.1% of, and within less than 0.01% of the stated amount. Additionally, as used herein, “gradually” has its ordinary meaning (e.g., differs from a non-continuous, such as a step-like, change).

## 21

The scope of the present disclosure is not intended to be limited by the specific disclosures of preferred embodiments in this section or elsewhere in this specification, and may be defined by claims as presented in this section or elsewhere in this specification or as presented in the future. The language of the claims is to be interpreted broadly based on the examples described in the present specification or during the prosecution of the application, which examples are to be construed as non-exclusive.

What is claimed is:

1. A method of sealing a watertight electrical compartment of an irrigation device, comprising:

providing an electrical compartment body, the electrical compartment body comprising a chamber with an open end, threads, and a sealing section, the sealing section located closer to the open end of the chamber than the threads;

mounting at least one sealing ring into at least one groove, the at least one groove located on the sealing section or on an inner wall of a cap, the cap having an open end and a closed end;

sliding the open end of the cap over the sealing section, the cap having an internal diameter configured to have a sliding fit with the sealing section, wherein the at least one sealing ring seals a space between the sealing section and the inner wall of the cap;

sliding a cap retainer having first and second ends over at least a portion of the cap so that the at least a portion of the cap passes through the first end of the cap retainer, the cap retainer having a stopper on the second end for retaining the cap, the cap retainer further having threads; and

turning the cap retainer relative to the electrical compartment body so that the threads of the cap retainer mate with the threads of the electrical compartment body to keep the cap in a sealed position.

2. The method of sealing a watertight electrical compartment of an irrigation device of claim 1, wherein the stopper on the second end of the cap retainer comprises a shoulder having an internal diameter smaller than an outer diameter of the cap, and further comprising contacting the cap with the shoulder.

3. The method of sealing a watertight electrical compartment of an irrigation device of claim 2, wherein the shoulder is configured to keep the cap engaged with the sealing section when the threads of the cap retainer mate with the threads of the compartment body.

4. The method of sealing a watertight electrical compartment of an irrigation device of claim 1, wherein sliding the cap retainer over the at least a portion of the cap comprises advancing the threads of the cap retainer past the cap towards the threads of the electrical compartment body.

5. The method of sealing a watertight electrical compartment of an irrigation device of claim 1, wherein the electrical compartment body comprises a channel extending further away from the open end than the sealing section along a length of the electrical compartment body, the threads of the electrical compartment body being located on a radially inwardly facing inner wall of the channel, and wherein the threads of the cap retainer comprise external threads.

6. The method of sealing a watertight electrical compartment of an irrigation device of claim 1, wherein the at least one groove is located on the inner wall of the cap.

7. The method of sealing a watertight electrical compartment of an irrigation device of claim 1, wherein the cap has

## 22

a reduced outer diameter on its closed end and the cap retainer has a reduced inner diameter on its second end, the reduced inner diameter of the cap retainer configured to slidably accommodate the reduced outer diameter of the cap.

8. The method of sealing a watertight electrical compartment of an irrigation device of claim 1, wherein a wall of the cap further comprises at least one notch at the open end.

9. The method of sealing a watertight electrical compartment of an irrigation device of claim 1, wherein the chamber of the electrical compartment body is configured to house at least one battery.

10. A method of sealing an electrical compartment of an irrigation device, comprising:

providing an electrical compartment body having a chamber with an open end, at least one thread, and a sealing section;

providing a cap having an open end and an internal diameter;

sliding the open end of the cap over the sealing section; providing a retainer having a stopper and at least one thread;

sliding an end of the retainer over at least a portion of the cap, and

turning the retainer relative to the electrical compartment body so that the at least one thread of the retainer mates with the at least one thread of the electrical compartment body to at least maintain a seal between the cap and the sealing section.

11. The method of sealing an electrical compartment of an irrigation device of claim 10, wherein the retainer is slid over the at least a portion of the cap before the open end of the cap is slid over the sealing section.

12. The method of sealing an electrical compartment of an irrigation device of claim 10, wherein sliding the open end of the cap over the sealing section initially creates the seal.

13. The method of sealing an electrical compartment of an irrigation device of claim 10, wherein the sealing section is located closer to the open end of the chamber than the at least one thread of the chamber.

14. The method of sealing an electrical compartment of an irrigation device of claim 10, further comprising mounting at least one sealing ring between the sealing section and the cap.

15. The method of sealing an electrical compartment of an irrigation device of claim 14, wherein at least one of the sealing section and the cap comprises a groove, and wherein mounting the at least one sealing ring comprises mounting the sealing ring in the groove.

16. The method of sealing an electrical compartment of an irrigation device of claim 15, wherein turning the retainer at least slightly compresses the at least one sealing ring disposed between the sealing section and the cap.

17. A method of sealing an electrical compartment of an irrigation device, comprising:

providing an electrical compartment having a chamber with an open end, at least one thread, and a sealing section;

providing a cap having a wall and an open end forming a receptacle;

positioning the sealing section in the receptacle; providing a retainer having a stopper and at least one thread;

sliding an end of the retainer over the cap until the at least one thread of the retainer contacts the at least one thread of the chamber; and

rotating the retainer relative to the electrical compartment so that the at least one thread of the retainer engages

with the at least one thread of the electrical compartment to at least slightly move the cap closer to the electrical compartment so as to maintain a seal therebetween.

18. The method of sealing an electrical compartment of an irrigation device of claim 17, wherein the retainer is slid over the cap before the sealing section is positioned in the cap.

19. The method of sealing an electrical compartment of an irrigation device of claim 17, wherein positioning the sealing section in the receptacle initially creates the seal.

20. The method of sealing an electrical compartment of an irrigation device of claim 17, further comprising electrically coupling the compartment to a flow sensor.

\* \* \* \* \*