






US 20130328305A1

(19) **United States**(12) **Patent Application Publication**
Chiproot(10) **Pub. No.: US 2013/0328305 A1**(43) **Pub. Date: Dec. 12, 2013**(54) **SEAL HOLDING DEVICE FOR PIPE CLAMP**(76) Inventor: **Avi Chiproot**, Kfar-Saba (IL)(21) Appl. No.: **13/494,177**(22) Filed: **Jun. 12, 2012****Publication Classification**(51) **Int. Cl.**
F16L 21/02 (2006.01)(52) **U.S. Cl.**
USPC **285/337**(57) **ABSTRACT**

A pipe clamp including an annular clamp housing having an opening for inserting therein a pipe, opposing clamp members located near ends of the annular clamp housing, one or more tightening elements for fastening and tightening the clamp members towards each other in a direction transverse to an axial length of the annular clamp housing, and an annular seal placed in an inner perimeter of the annular clamp housing, wherein one portion of the annular seal is attached to the annular clamp housing with one or more mechanical fasteners and another portion of the annular seal is slidably attached to the annular clamp housing with one or more mechanical fasteners so that the annular seal is permitted to move and expand radially about as the pipe clamp is tightened by one or more tightening elements.








FIG. 2




FIG. 2A




FIG. 2B

SEAL HOLDING DEVICE FOR PIPE CLAMP

FIELD OF THE INVENTION

[0001] The present invention relates to a coupling for pipes, and particularly to a device for holding a seal to an inner perimeter of a pipe clamp before tightening the clamp.

BACKGROUND OF THE INVENTION

[0002] Many kinds of removable band-type clamps or couplings (the terms being used interchangeably throughout) for pipes exist in the art. It is noted that throughout the specification and claims, the term “pipe” encompasses any kind of generally cylindrical object.

[0003] For example, one commercially available type of pipe coupling has an annular seal clamp housing. Clamp members are positioned face to face and a tightening element is tightened to press an annular seal (annular elastomeric band) against the outside of the pipe inserted through the seal clamp housing. This type of clamp is particularly useful for pipe repair applications, such as the pipe repair clamp described in U.S. Pat. No. 6,830,268 to Krausz, the disclosure of which is incorporated herein by reference. The present invention is not limited to these pipe clamps, however.

[0004] Initially one end of the annular seal is typically secured to the annular clamp housing and the other end is left loose, unattached to the clamp housing. This is important because when the coupling is tightened against the pipe, the ends of the annular seal abut against each other. The free end of the seal allows the seal to move and expand radially about the pipe as the coupling is tightened, so that the seal always smoothly and uniformly presses against and around the pipe. If both ends of the seal were fixed to the clamp housing, the seal would be prevented from expanding uniformly radially about the pipe as the coupling is tightened. Rather the seal would bunch up, become folded or kinked, or otherwise deform, and would not smoothly and uniformly press against and around the pipe.

[0005] However, the free end of the seal can cause another problem. When initially placing the coupling about the pipe, the free end of the seal can hang loosely out of the annular seal clamp housing. It can be cumbersome for some installers to hold the free end of the seal in the housing while at the same time placing the coupling around the pipe.

SUMMARY OF THE INVENTION

[0006] The present invention seeks to provide a device for holding a seal (in particular, the free end of the seal) to an inner perimeter of a pipe clamp before tightening the clamp, as is described more in detail further below.

[0007] There is provided in accordance with an embodiment of the present invention a pipe clamp including an annular clamp housing having an opening for inserting therein a pipe, opposing clamp members located near ends of the annular clamp housing, one or more tightening elements for fastening and tightening the clamp members towards each other in a direction transverse to an axial length of the annular clamp housing, and an annular seal placed in an inner perimeter of the annular clamp housing, wherein one portion of the annular seal is attached to the annular clamp housing with one or more mechanical fasteners and another portion of the annular seal is slidably attached to the annular clamp housing with one or more mechanical fasteners so that the annular seal is

permitted to move and expand radially about as the pipe clamp is tightened by one or more tightening elements.

[0008] In accordance with an embodiment of the present invention the annular seal is slidably attached to the annular clamp housing with the one or more mechanical fasteners passing through one or more elongate apertures formed through the annular clamp housing. The elongate apertures are elongate in a radial direction. Additionally or alternatively, the elongate apertures may be elongate in an axial direction.

[0009] In accordance with an embodiment of the present invention the one portion of the annular seal is fixedly attached to the annular clamp housing with the one or more mechanical fasteners. Alternatively, the one portion of the annular seal may be slidably attached to the annular clamp housing with the one or more mechanical fasteners.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The present invention will be understood and appreciated more fully from the following detailed description, taken in conjunction with the drawings in which:

[0011] FIGS. 1A-1B are simplified pictorial illustrations of a pipe clamp, constructed and operative in accordance with a non-limiting embodiment of the present invention;

[0012] FIG. 2 is a simplified side view illustration of the pipe clamp; and

[0013] FIGS. 2A and 2B are simplified sectional illustrations of the pipe clamp, taken along lines A-A and B-B, respectively, in FIG. 2.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0014] Reference is now made to FIGS. 1A-2B, which illustrate a pipe clamp 10, constructed and operative in accordance with a non-limiting embodiment of the present invention.

[0015] Pipe clamp 10 includes an annular clamp housing 12, typically made of a flexible metal sheet, such as but not limited to, stainless steel. Annular clamp housing 12 has an opening 14 for inserting therein a pipe (not shown). The ends of annular clamp housing 12 are provided with two (wedge-shaped) opposing clamp members 16. One or more tightening elements 18 (e.g., one or more mechanical fasteners, such as a bolt or screw and a tightening nut, and possibly washer) fasten and tighten clamp members 16 towards each other in a direction transverse to the axial length of annular clamp housing 12 so as to apply a radially-inward clamping force on the pipe inserted in opening 14.

[0016] An annular seal 20, fashioned as a flexible inner sleeve, is placed in the inner perimeter of annular clamp housing 12. Seal 20, without limitation, may be made of a rubber (e.g., EPDM (ethylene propylene diene monomer), butyl, styrene butadiene or neoprene) or a thermoplastic elastomer (e.g., polyurethane or olefin) compatible with the fluid to be carried in the pipe.

[0017] In one embodiment, annular seal 20 is one layer of an elastomer. Alternatively, as shown in the illustrated embodiment of FIG. 2A, annular seal 20 includes inner and outer sealing rings 22 and 24 radially spaced from one another. The outer sealing ring 24 includes a folded portion 26 folded over an annular abutment 28 so as to define an inner space 30, which can be in fluid communication with a fluid (not shown) flowing in the pipe. The fluid enters inner space

30 and applies pressure therein to increase tightening of the seal. The inner sealing ring **22** may be removed from or added to the outer sealing ring **24** to accommodate different pipe diameters. A type of this seal is described in U.S. Pat. No. 6,293,556 to Krausz, the disclosure of which is incorporated herein by reference; however, the invention is not limited to this type of seal.

[0018] One end or portion of seal **20** is fixedly attached to annular clamp housing **12** with one or more mechanical fasteners **32**, such as a bolt or screw and a tightening nut, which pass through a circular hole in housing **12**. In accordance with an embodiment of the present invention, another portion (e.g., the opposite end) of seal **20** is slidably attached to annular clamp housing **12** with one or more mechanical fasteners **34**, such as a bolt or screw and a tightening nut and washer. This may be accomplished by mechanical fasteners **34** passing through one or more elongate apertures **36** formed through annular clamp housing **12**. The apertures **36** are elongate in the radial direction. Alternatively, the mechanical fastener **34** can be fashioned with a sliding portion that permits the fastener along with seal **20** to slide radially.

[0019] In order to prevent the elastomeric material of seal **20** from oozing out of aperture **36** during tightening, a blocking element **39**, such as a plate or other small piece of metal sheet (e.g., stainless steel), may be placed on the inner side of housing **12** behind aperture **36**, as seen in FIGS. 2A and 2B.

[0020] When pipe clamp **10** is tightened against the pipe, the ends of annular seal **20** abut against each other. Because one end of seal **20** is attached by mechanical fasteners **34** in elongate apertures **36**, seal **20** is permitted to move and expand radially about the pipe as pipe clamp **10** is tightened. This ensures that seal **20** always smoothly and uniformly presses against and around the pipe. In addition, when initially placing pipe clamp **10** about the pipe, no portion of seal **20** will hang loosely out of clamp housing **12** because seal **20** is held by fasteners **32** and **34**. This makes placement of pipe clamp **10** around the pipe easy and fast.

[0021] Alternatively, mechanical fasteners **32** may also pass through elongate apertures, oriented in any direction, as indicated by broken lines **35** in FIG. 2.

[0022] Alternatively or additionally, elongate apertures **36** may be elongate in the axial direction, as indicated by broken lines **37** in FIG. 2. This allows seal **20** to expand axially, which may be important in certain applications in which axial forces tend to make the seal expand axially.

[0023] The scope of the present invention includes both combinations and subcombinations of the features described hereinabove as well as modifications and variations thereof which would occur to a person of skill in the art upon reading the foregoing description and which are not in the prior art.

1. A pipe clamp comprising:

an annular clamp housing having an opening for inserting therein a pipe;

opposing clamp members located near ends of said annular clamp housing;

one or more tightening elements for fastening and tightening said clamp members towards each other in a direction transverse to an axial length of said annular clamp housing; and

an annular seal placed in an inner perimeter of said annular clamp housing;

wherein one portion of said annular seal is attached to said annular clamp housing with one or more mechanical fasteners and another portion of said annular seal is slidably attached to said annular clamp housing with one or more mechanical fasteners so that said annular seal is permitted to move and expand radially about as said pipe clamp is tightened by one or more tightening elements.

2. The pipe clamp according to claim 1, wherein said annular seal is slidably attached to said annular clamp housing with said one or more mechanical fasteners passing through one or more elongate apertures formed through said annular clamp housing.

3. The pipe clamp according to claim 2, wherein said elongate apertures are elongate in a radial direction.

4. The pipe clamp according to claim 2, wherein said elongate apertures are elongate in an axial direction.

5. The pipe clamp according to claim 1, wherein said one portion of said annular seal is fixedly attached to said annular clamp housing with said one or more mechanical fasteners.

6. The pipe clamp according to claim 1, wherein said one portion of said annular seal is slidably attached to said annular clamp housing with said one or more mechanical fasteners.

7. The pipe clamp according to claim 1, wherein said annular seal comprises one layer.

8. The pipe clamp according to claim 1, wherein said annular seal comprises more than one layer.

* * * * *