

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 December 2007 (21.12.2007)

PCT

(10) International Publication Number
WO 2007/146732 A2

(51) International Patent Classification:
G06F 17/00 (2006.01)

(21) International Application Number:
PCT/US2007/070586

(22) International Filing Date: 7 June 2007 (07.06.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/811,808 8 June 2006 (08.06.2006) US

(71) Applicant (for all designated States except US): **D B INDUSTRIES, INC.** [US/US]; 3833 Sala Way, Red Wing, MN 55066-5005 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KAARTINEN, Dean, R.**; Lake City, MN (US). **UNDERWOOD, Bruce, D.** [US/US]; 9390 Livery Lane, Lakeville, MN 55044 (US).

(74) Agent: **BAUER, William, D.**; IPLM Group, P.A., Post Office Box 18455, Minneapolis, MN 55418 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF RETROFITTING SAFETY EQUIPMENT ITEMS AND DATABASE

(57) Abstract: Database and method facilitating a set of information relating to a plurality of first safety equipment items produced by a producer. One of a plurality of unique identifiers is applied to each of the plurality of first safety equipment items before the plurality of first safety equipment items leave control of the producer. A database representative of information associated with a plurality of unique identifiers and a plurality of safety equipment items is established. The one of the plurality of unique identifiers is associated with a respective one of the plurality of first safety equipment items. A plurality of second safety equipment items is retrofitted by applying one of the plurality of unique identifiers with a respective one of the plurality of second safety equipment items after the plurality of second safety equipment items leaves control of the producer. The one of the plurality of unique identifiers is associated with a respective one of the plurality of safety equipment items.



WO 2007/146732 A2

Method of Retrofitting Safety Equipment Items and Database

FIELD

- [1] The present invention relates generally to the field of safety equipment items such as safety harnesses and information related thereto.

BACKGROUND

- [2] Safety equipment items, such as safety harnesses, are important and potentially life-saving devices serving a very real purpose in the lives of those who climb or who work in environments where a fall is a significant danger.
- [3] Records of safety equipment items generally must be maintained to ensure that the safety equipment items meet applicable governmental regulations and industry standards as well as the standards of the user and organization for whom the user works. Such organization is usually, ultimately, the customer of the producer of safety equipment items, albeit sometimes through an intermediary such as a distributor.
- [4] Traditionally, records, such as inspection data, for safety equipment items are maintained manually, e.g., with a paper inspection record attached to a pocket or label attached to the safety equipment item. However, such manual paper records are prone to illegibility since such safety equipment is often subjected to adverse conditions such as dirt, oil and grease. Such adverse conditions may actually render the manual record unusable due to illegibility, thereby potentially bringing the equipment out of compliance with safety standards and threatening the safety of the user.
- [5] Further, paper records kept locally with each piece of safety equipment item are difficult to manage by an organization having a plurality or more than a few of such safety equipment items. Safety directors of such organizations often have a difficult time maintaining any sort organized data related to their safety equipment items since the records may be kept manually and locally with each piece of safety equipment item.

- [6] Even when organized records are kept by a safety director, such records are difficult to maintain and keep up to date since such equipment items may be physically disparately located and the actual record may be still be recorded manually and locally, and subject to deterioration and illegibility.

SUMMARY

- [7] To facilitate the maintenance of reliable and easily accessible information related to safety equipment, an electronic database, controlled by the producer of the safety equipment, has been created. Equipment produced by the producer is tagged with an identifier, preferably a radio frequency ID (RFID) tag with a unique ID number, and entered into the database. Alternative, equipment produced by other producers may be retroactively fitted with RFID tags and entered into the database. When the equipment is distributed to a user, the user scans the RFID tag with handheld electronic equipment, preferably an adapted personal digital assistant (PDA), which begins an electronic session relating to that particular piece of safety equipment.
- [8] In the session, the user may review information relating to the safety equipment stored on the RFID tag displayed on the PDA's screen. In addition, the user may enter new information pertaining to the equipment into the PDA's memory, including information related to where the equipment is being used, who is using it, and the occurrence and result of safety inspections of the equipment. The PDA is then placed in a docking station connected to a personal computer, which is itself connected to the internet, though applications are anticipated in which the PDA connects to the internet directly via a wireless link. The PDA is synchronized with the electronic database, and any information that had been entered is downloaded into the appropriate records in the database. Thus, after synchronization, the information becomes available to any user who has an account and access to the internet.
- [9] Because the central database is maintained by the producer of the equipment, the producer retains the ability to likewise update entries and post notices for users of particular equipment. Notices may include reminders that equipment inspections are due, or that a piece of equipment is nearing the end of its safe and useful life. In

addition, new usage guidelines may be delivered to a user in the event that such guidelines have changed.

- [10] In an embodiment, the present invention provides a method of facilitating a set of information relating to a plurality of first safety equipment items produced by a producer. One of a plurality of unique identifiers is applied to each of the plurality of first safety equipment items before the plurality of first safety equipment items leave control of the producer. A database representative of information associated with a plurality of unique identifiers and a plurality of safety equipment items is established. The one of the plurality of unique identifiers is associated with a respective one of the plurality of first safety equipment items. A plurality of second safety equipment items is retrofitted by applying one of the plurality of unique identifiers with a respective one of the plurality of second safety equipment items after the plurality of second safety equipment items leaves control of the producer. The one of the plurality of unique identifiers is associated with a respective one of the plurality of safety equipment items.
- [11] In an embodiment, the present invention provides a database system containing a set of information relating to a plurality of first safety equipment items produced by a producer. A plurality of unique identifiers is applied to each of the plurality of first safety equipment items. A database representative of information is associated with a plurality of unique identifiers and a plurality of safety equipment items. The database contains information associating the one of the plurality of unique identifiers with a respective one of the plurality of first safety equipment items. A plurality of second safety equipment items is retrofitted with one of the plurality of unique identifiers. The database contains information associating the one of the plurality of unique identifiers with a respective one of the plurality of safety equipment items.
- [12] In an embodiment, the database is controlled by the producer.
- [13] In an embodiment, the plurality of second safety equipment items has been produced by the producer.
- [14] In an embodiment, the plurality of second safety equipment items has been produced by another producer.

- [15] In an embodiment, some of the plurality of second safety equipment items have been produced by the producer and others of the plurality of second safety equipment have been produced by another producer.
- [16] In an embodiment, the database contains information associating each of the plurality of safety equipment items with a customer.
- [17] In an embodiment, a selected portion of the information related the customer is ported to the customer.
- [18] In an embodiment, at least a portion of the information is pushed to the customer without overt action by the customer for the portion of the information.
- [19] In an embodiment, the database contains information associating at least one of the safety equipment items with a location.
- [20] In an embodiment, the database contains information associating each of the plurality of safety equipment items with one of a plurality of users of the plurality of safety equipment items.
- [21] In an embodiment, the database contains information facilitating locating a selected one of the plurality of safety equipment items with an associated one of the plurality of users.
- [22] In an embodiment, the database contains information facilitating tracking at least one of movement and location of each of the plurality of safety equipment items among the plurality of customers.

DRAWINGS

- [23] **Figure 1** is a functional block diagram of a controlled database system for safety equipment items;
- [24] **Figure 2** is an elementary flow chart representation of exemplary functions of a controlled database system for safety equipment items;
- [25] **Figure 3** is a close-up screen shot of a mobile device useful in a controlled database system for safety equipment information;
- [26] **Figure 4** is a description of XML language running on mobile device;

- [27] **Figure 5** is a screen shot illustrating the step of associating safety equipment item with unique identifier;
- [28] **Figure 6** is a screen shot displaying information pertaining to users of a controlled database;
- [29] **Figure 7** is a screen shot used to associate safety equipment item with a customer;
- [30] **Figure 8** is a screen shot of a welcome screen;
- [31] **Figure 9** is a screen shot of a general information screen;
- [32] **Figure 10** is a screen shot of an equipment information screen;
- [33] **Figure 11** is a screen shot displaying safety equipment associated with a customer;
- [34] **Figure 12** is a screen shot of an inspection procedure;
- [35] **Figure 13** is a screen shot allowing input of a request for an inspection log report;
- [36] **Figure 14** is a screen shot allowing input of a request for an inventory report;
- [37] **Figure 15** is a flow chart illustrating aspects of an embodiment of a controlled database of safety equipment items;
- [38] **Figure 16** is a flow chart illustrating aspects of direct entry of data into a controlled database of safety equipment item;
- [39] **Figure 17** is a flow chart illustrating aspects of retrofit of safety equipment items with unique identifiers;
- [40] **Figure 18** is a flow chart illustrating aspects of a controlled database of safety equipment items related to inspection;
- [41] **Figure 19** is a screen shot of an assign screen;
- [42] **Figure 20** is a screen shot of an inspect screen;
- [43] **Figure 21** is a screen shot of an inspecting equipment screen;
- [44] **Figure 22** is a screen shot of an inquire screen;
- [45] **Figure 23** is a screen shot displaying the action taken during synchronization of mobile device;

- [46] **Figure 24** is a screen shot of a settings screen;
- [47] **Figure 25** is a screen shot of test connection screen;
- [48] **Figure 26** is a screen shot of a put in service screen;
- [49] **Figure 27** is a screen shot of a take out of service screen;
- [50] **Figure 28** is a screen shot displaying inspection status information; and
- [51] **Figure 29** is a screen shot of details pertaining to safety equipment.

DETAILED DESCRIPTION

- [52] **Figure 1** illustrates a functional block diagram in which a unique identifier 10, such as radio frequency identification (RFID) tag is applied, for example by permanent stitching, to safety equipment item 12. It is to be recognized and understood that unique identifier 10, in the form of radio frequency identification tag 12 may be applied to or affixed to safety equipment item 12 in a variety of manners, including, but not limited to, putting unique identifier 10 into a pouch that is then sewn onto safety equipment item 12, affixing unique identifier to safety equipment with a strap or cord, adhesively mounting unique identifier to a portion of safety equipment item 12, magnetically attached unique identifier 10 to a metallic element of safety equipment item 12, putting unique identifier 10 into a container or pouch of safety equipment item 12, attaching unique identifier 10 to a tag, label or other item attached to safety equipment item 12, or by keeping unique identifier in a container, package, case, cover or other holding or protective device associated with safety equipment item 12.
- [53] An example of an application technique for associated unique identifier 10 with safety equipment item 12 is used by EXOFIT XP™ safety harness model 1110102 manufactured by D B Industries, Inc., Red Wing, Minnesota.
- [54] Safety equipment item 12 is illustrated as a safety climbing harness. However, it is to be recognized and understood that safe equipment item 12 could be any of a variety of safety equipment including, but not limited to, anchors and anchorage connectors, body belts and harnesses, lifelines, netting systems, load arrestors and lanyards.

- [55] Radio frequency identification tag 12 provides a unique identifier 10 that can be associated with an individual one of a plurality of safety equipment items manufactured by, or produced by, producer 14. While radio frequency identification tag is preferred as the unique identifier, it is to be recognized and understood that other unique identifiers could also be utilized such as, but not limited to, bar codes and serial numbers. Radio frequency identification tag provides an advantageous unique identifier 10 since the unique identifier 10 can be readily determined using commonly available RFID scanning equipment.
- [56] Producer 14 may associate unique identifier 10 with a particular one of safety equipment items 12 manufactured by, or produced by, producer 14. Such database 16 is preferably controlled by producer 14 and may be physically located at a site of producer 14 or off-site but still controlled by producer 14 such as at a contract location.
- [57] The association between safety equipment items 12 and their respective unique identifier 10 may be stored in database 16 which is used to contain information related to safety equipment item 12. Database 16 may contain information including, but not limited to, information related to safety equipment item 12, information related to a distributor or customer of a safety equipment item 12, information related to a user of a safety equipment item 12, information related to sales of or a location of storage or use of a safety equipment item 12, information related to usage, type of usage, dates of usage or of non-use of a safety equipment item 12, information related to inspection and/or condition of a safety equipment item 12, information related to manufacture and/or sale or lease of a safety equipment item 12 and information related to an inventory of safety equipment items 12. This information may be stored in database 16 in separate tables related by type or source of information or may be at least partially combined in common tables as is appropriate.
- [58] Producer 14 may obtain information regarding a particular safety equipment item 12 by reading or scanning 18 the particular safety equipment item 12 and obtaining unique identifier 10 associated with the particular safety equipment item 12. Such reading or scanning of unique identifier 10, such as an RFID tag, may easily be accomplished in a conventional and well known manner. Information related to the

particular safety equipment item 12 may then either be obtained from database 16 or input into database 16 by producer 14 through conventional means.

- [59] Following production, producer 14 may put safety equipment item 12 into chain of commerce 20, for example, by selling or leasing safety equipment item 12 to customer 22. While the following description focuses on customer 22, it is to be recognized and understood that the term customer 22 may mean anyone or any entity downstream in chain of commerce 20 from producer 14. Customer 22, for example, may include a distributor or representative of safety equipment item 12.
- [60] Customer 22 may have electronic equipment, such as computer 24, to access a portal 26 to database 16 through a wide-area network, such as the internet. Customer 22 may access database 16 to receive information concerning safety equipment 12 associated with such customer 22 including, but not limited to, safety equipment information such as date of manufacture, service date and/or service history, size, color or other characteristic, assigned user (if any), inspection data, upcoming inspection events and/or inspection history.
- [61] Portal 26 may also be used with customer 22 to push information from producer 14 to customer 22 without any overt customer action. That is, since database 16 exists in the control of producer 14, producer 14 may utilize knowledge of association of a particular safety equipment item 12 with a particular customer 22 or user to enhance the life cycle operation of such safety equipment item 12. Information about an upcoming inspection event or due date, length of service information and the like may assist customer 22 in keeping safety equipment item 22 current, operational and safe. If safety equipment item 22 has a predetermined life usage time, then customer 22 may also be alerted relative to such usage life span, either as an alert for an upcoming expiration or as a warning of such expiration.
- [62] Portal 26 may also be utilized with customer 22 to push important technical information to customer 22 about the particular safety equipment item or items 22 associated with such customer 22. Technical bulletins specifically targeted to such safety equipment item or items 22 may be "pushed," or transmitted to customer 22 without overt action by such customer 22. If new or revised training procedures or

requirements were to be recommended or established, such new or revised training procedures could be pushed to customer 22. Different training information, such as training videos, may be delivered to each individual customer 22 based on the specific safety equipment item or items 12 associated with such customer 22. If a governmental regulatory body, such as the Occupational Safety and Health Administration (OSHA) in the United States, were to establish new or revised safety requirements or guidelines, such information, specific to the safety equipment item or items 12 associated with such customer 22 may be pushed to that customer 22. Of course, safety organizations of other countries as CSA in Canada or EN in European countries may also be used.

- [63] Further, promotional material may be pushed to customer 22, again based specifically on the safety equipment item or items 12 associated with such customer 22. This is particularly valuable to a producer 14 who only sells through an intermediary, such as a distributor, and, hence, might not otherwise know what safety equipment items 12 were associated with a particular customer 22. The knowledge gained from database 16 allows a targeted promotional focus to only those customers 22 who have a particular model, or range of models or range of build codes, of such safety equipment items 12.
- [64] Additionally, user's manuals and cleaning and storage information may be made available to customer 22 or to the user.
- [65] Customer 14 may input data relating to safety equipment items 12 associated with such customer 22 into database 16. Examples of information that customer 22 may input to database 16 include, but is not limited to, the date such safety equipment item 12 is received, date a safety equipment item 12 is placed into or taken out of service, assignment or reassignment of a safety equipment item 12 to a user of such item 22, identification or modification of a location at which such item 22 is used or stored, maintenance information such as inspection dates, inspection passes/fails, inspection results, inspection records, repairs or modifications and date of disposition and type of disposition of such item 22, such as disposal, return or sale.

- [66] It is generally recognized that customer 22 may want or need to input any or all of such data from a location that is remote from the location of computer 24. Or even at the location of computer 24, it may be easier or more desirable to use a mobile device 28 for such data input. Mobile device 28 is illustrated in **Figure 1** as a personal digital assistant which facilitates ease of data entry while allowing such data entry to occur at a location where, or near where, safety equipment items 12 are located. For example, mobile device 28 may be used by customer 22 at or near a storage area for safety equipment items 12. As such items are placed into service, assigned to users, inspected, repaired, retired, etc., mobile device 12 may be used to scan unique identifier 10 associated with each safety equipment item 12 and the pertinent data input into mobile device 28. Such scanning can be accomplished by well known scanning techniques 30 such as with RFID tags. In an embodiment, a scanning frequency of 134.2 KiloHertz is utilized for this purpose.
- [67] Mobile device 28 may then upload, or synchronize, the entered data directly to database 16 through communication link 32. Communication link 32 may be any of a number of standard, commonly available, communication links or a combination of such links. For example, mobile device 28 may communicate with a base station (not shown) using Blue Tooth or Wi-Fi networking. The base station may utilize a wide area network, such as the internet, as a portal to database 16.
- [68] In an embodiment, mobile device 28 communicates directly with database 16 controlled by producer 14. That is, customer 22 does not need to maintain a duplicate or shadow copy of database 16, or a portion thereof, in the control of customer 16. Mobile device 28 does not need to communicate through computer 24 used by customer to access portal 26 to database 16. Rather, mobile device 28 has a more direct connection with database 16. This is true even if communication link 32 has two or more technical aspects, e.g., Blue Tooth and internet. Customer 22 does not need to manipulate, screen, store (other than to synchronize) or modify the data entered into mobile device 28. Mobile device 28 only needs to act as a conduit to database 16.
- [69] Of course, it is to be recognized and understood that mobile device 28 may not be technically mobile. That is, mobile device 28 may be physically located only in one

location and may not even be portable. Mobile device 28 could be a desk top personal computer that is located conveniently to a location where data entry occurs. However, in an embodiment, mobile device 28 is a hand held PDA that is portable and may be carried to the desired data entry location. An example of a hand held PDA suitable for this purpose is a Dell X51 portable hand held marketed by Dell Computer. A distinction is that mobile device 28 does not need to be coupled with computer 24 nor perform other functions other than data entry and synchronization directly with database 16.

- [70] **Figure 2** is a flow chart representation of function associated with a safety equipment item 12 during the life cycle of such safety equipment item 12. Unique identifier 10, in this case an RFID tag, is associated (210) with safety equipment item 12 (product). This is typically done during or following completion of manufacture or production by producer 14 while safety equipment item 12 is still within the control of producer. That is, before producer 14 has placed safety equipment item 12 into a stream of commerce such as sale or lease. Although, as will be described later, unique identifier 10 may also be associated to safety equipment item 12 after such safety equipment item 12 has left the control of producer 14. This is the so-called retrofit situation. In either case, unique identifier 10 is associated with safety equipment item 12 not only physically, so that unique identifier may be subsequently recalled, but also in database 16.
- [71] When the safety equipment item 12 is placed into a stream of commerce, for example by sale, safety equipment item 12, through unique identifier 10, is associated (212) with a sales order, or, more specifically, to a customer of such sales order. If safety equipment item 12 subsequently is resold, given, traded or otherwise disposed of, data associated with the new “customer,” owner in this case, may then be “associated” with safety equipment item 12 in database 16.
- [72] Once customer 22 is associated with safety equipment item 12, customer 22 may access (214) portal 26 to database 16 to access information about safety equipment item 12. Customer 22 may also conduct (216) reporting on information contained in database 16 and/or maintenance, such as inspection, of safety equipment items for safety equipment items 12 associated with such customer 22.

- [73] **Figure 3** is a close-up screen shot 34 of mobile device 28. Mobile device 28 runs a specialized XML language program to provide the data entry fields indicated in screen shot 34. Screen shot 34 provides equipment action field 36 allowing customer 22 to select an action with respect to which data is to be entered into database 16. A user may select Assign 37 to proceed to Assign screen 31 (**Figure 19**) to assign safety equipment item 12 to an alternative user or site. A user may select Inspect 39 (**Figure 20**) to conduct and record an inspection of safety equipment item 12. Or a user may select Inquire 41 (**Figure 22**) to obtain information about safety equipment 12.
- [74] **Figure 19** depicts Assign screen 31. RFID field 38 holds the scanned value of unique identifier 10. Site field 42 is shown as a drop down selection, which may be determined by customer 22, for the location, generally the physical location, of safety equipment item 12. User field 44, also shown as a drop down selection, and which may also be determined by customer 22, associates safety equipment item 12 with a user of such safety equipment item 12.
- [75] **Figure 20** depicts Inspect screen 2110. Tag field 2112 displays the unique identifier 10 for safety equipment item 12, while drop-down type field 2114 allows the user to select the inspection that will be conducted. Once the inspection to be conducted has been selected the user taps Start Inspection button 2116 to begin the inspection and take user to Inspecting Equipment screen 2210.
- [76] **Figure 21** depicts Inspecting Equipment screen 2210. Instruction window 2212 displays step-by-step instructions for conducting the inspection chosen in drop-down type field 2114. Once each step has been conducted, the user taps the Pass or Fail button 2214, as appropriate, and a new set of instructions is displayed in Instruction window 2212 until the all steps have been completed. The instructions displayed on Inspecting Equipment screen 2210 will correspond to questions 1314 (**Figure 12**).
- [77] **Figure 22** depicts Inquire screen 2310. When a user enters unique identifier 10 of safety equipment item 12 into tag field 2312 and Find button 2316 is tapped, available information relating to safety equipment item 12 is displayed in window 2314. This information includes unique identifier 10, product type, assigned site, individual assigned to, manufacturer, model number, the date the next inspection is due, the date

the most recent inspection occurred, the result of the inspection, and the date the safety equipment item 12 was put into service.

- [78] Again in **Figure 3**, System action field 43 presents the user with options for system level activities unrelated to directly entering safety equipment item 12 information. Sync button 45 takes the user to Sync screen 33 (**Figure 23**) which allows the user to sync mobile device 28 that is interfacing with computer 24 with database 16, uploading all safety equipment item 12 information that had been loaded on mobile device 28 since the date of the last sync 59. Settings button 47 takes the user to Settings screen 35 (**Figure 24**) which allows the user to modify mobile device 28 settings such as a security key, user identification, website password, IP host address, and the language used by mobile device 28. Test Connect button 49 takes the user to Test Connection screen 2610 (**Figure 25**) after conducting a connection test with the electronic hardware controlling database 16.
- [79] **Figure 23** depicts Sync screen 33. Sync Now button 2420 allows a user to initiate the synchronization of mobile device 28 with database 16. Current Status box 2422 provides the user with information relating to the information that is being downloaded to database 16, including the number of sites loaded, workers loaded, number of unique identifier numbers 10 loaded, and the date and time of the last sync.
- [80] **Figure 24** depicts Settings screen 35. Windows 2510 display mobile device's 28 security key, the identification of the user, the password, the host of mobile device 28, and the language used by mobile device 28. These values are subject to being changed by user and saved as mobile device's 28 settings by tapping Save button 2512.
- [81] **Figure 25** depicts Test Connection screen 25. Proceeding into the Test Connection screen 25 conducts a test of the connection between mobile device 28 and the electronic equipment containing database 16. The test will check the connection to the web server, the connection to the portal, the testing login information, and will check for the latest version of the interface software, and display the results in window 2620.

- [82] Again in **Figure 3**, Service status field 57 presents the user with options for placing a particular safety equipment item 12 into service or taking it out of service. Put In button 59 brings the user to Put In Service screen 2710 (**Figure 26**), allowing the user to indicate that safety equipment item 12 is being used on a regular and ongoing basis and thus must be subjected to regular inspections, which indication is stored in database 16. Take Out button 61 brings the user to Take out of Service screen 2810 (**Figure 27**), allowing the user to take safety equipment item 12 out of service.
- [83] **Figure 26** depicts Put In Service screen 2710. When user enters unique identifier number 10 into Tag field 2712 and checks pick-box 2713 corresponding to whether the safety equipment item 12 is retrofitted with a unique identifier number 10 or not, user may enter data corresponding to unique identifier number 10 into fields 2714. By tapping save button 2716 user places safety equipment item 12 in service, and this status is stored in database 16, indicating that safety equipment item 12 must be subjected to regular safety inspections.
- [84] **Figure 27** depicts Take out of Service screen 2810. By entering unique identifier number 10 in Tag field 2812 and tapping save button 2814, the user may take the corresponding safety equipment item 12 out of service, which status will be stored in database 16.
- [85] **Figure 4** describes with particularity the XML language program running on mobile device 28. Mobile device 28 will first read information from database 16 relating to the particular safety equipment item 12 whose unique identifier has been scanned. Mobile device 28 may then perform (512) at least one of the selected action items allowed for mobile device 28 such as creating (4) a new safety equipment item 12, putting (100) a safety equipment item 12 into service, assigning (101) a safety equipment item 12 to a user, indicating (102) that a safety equipment item has failed, replacing (103) a safety equipment item 12, repairing (104) a safety equipment item 12 and taking (105) a safety equipment item 12 out of service. The input data may then be synchronized (514) with information, if any, contained in database 16.
- [86] **Figures 5 through 14, 28 and 29** illustrate screens shots of a program running on computer 24 by customer 22 or by a computer (not shown) by producer or by any

other user of database 16. **Figures 5 through 14, 28 and 29** provide an illustration of common tasks that may be performed with database 16.

- [87] **Figure 5** is a screen shot 610 illustrating the step of associating safety equipment item 12 with unique identifier 10 where producer 14 is producing safety equipment item 12 for a customer 22. This step may be accomplished by producer 14 during or following production of safety equipment item 12 such as in the factory at the completion of manufacture or production. The current ID number 612 may be the serial number of the safety equipment item 12. Screen shot 610 allows the display of data corresponding to safety equipment item 12 in fields 614 including the current work order, the current location and the current part number. The quantity of safety equipment items 12 to be scanned may be set and the quantity of safety equipment items 12 actually scanned. Generally, this screen shot may be set up for a plurality of safety equipment items 12 and then each unique identifier is scanned from each individual safety equipment item 12. Screen shot 610 displays the last action taken with respect to the scanned safety equipment item 12.
- [88] **Figure 6** is a screen shot 710 displaying information pertaining to users of database 16. Fields display the user's login key, name, email address, password, date their account was created, date of last login, date of last sync, number of sites related to the user, the number of personnel, and the number of safety equipment items 12 in the database 16.
- [89] **Figure 7** is a screen shot 810 used to associate a safety equipment item 12 with a unique identifier 10 without reference to a particular customer 22. Screen shot 810 allows for entry in fields 812 of a production lot ID number, a part number and the quantity of safety equipment items 12 to scan. Fields 814 display the total number of safety equipment items that have been scanned, corresponding unique identifier 10 and the action taken during the last scan.
- [90] **Figure 8** is a screen shot 910 of a welcome screen of a registered user of database 16 following authorized log-in to portal 26. Screen shot 910 includes customer information fields 912, including fields for the contact, the company, address, city, state/province, country, telephone number, facsimile number and email address.

Screen shot 910 also displays registered product information fields 914, including fields for the number of safety equipment items 12 associated with this customer 22, the number of such items 12 that have been assigned to a user, the number of such items 12 that have not been assigned, the number of such items 12 that have been inspected, the number of such items 12 that are past-due for inspection, and the number of sites corresponding to the user. License key field 916 displays the customer's license key.

- [91] A button may lead from screen shot 910 to screen shot 2910 (**Figure 28**), which displays inspection status information. Lines 2912 corresponding to individual safety equipment items 12 are color coded, corresponding to whether the individual safety equipment item 12 is overdue for inspection, has yet to be initially inspected, or is current on its inspections. Further, non-colored, information includes unique identifier 10, description, current site, current user, date of last inspection, and days since that inspection, for each safety equipment item 12.
- [92] **Figure 9** is a screen shot 1010 of a general information screen. Drop-down menu 1012 allows a user to select their region, and then information relating to the region is displayed in field 1014. The information may include technical support information, including contact information such as address, phone and fax numbers, email address and website links. Drop-down menu 1016 also allows a user to display information relating subjects such as advisory messages, available downloads, applicable standards, and miscellaneous welcome messages. It is contemplated that screen shot 1010 may be expanded to include step-by-step instructions for conducting all necessary inspections, as well as reviewing all recently published regulatory statutes, professional association updates, product advisories, equipment instructions and training schedules, as well as providing links to user information.
- [93] **Figure 10** is a screen shot 1110 of an equipment information screen. Fields 1112 display information related to an RFID number, i.e., unique identifier 10, safety equipment item 12 number, type of equipment, the lot number of manufacture, the manufacturer, i.e., producer, the data and/or time of manufacture, the current location, the current user and last date inspected are input/displayed. A pictorial rendering of safety equipment item 12 is displayed in window 1114. Buttons 1116 allows for the

selection and display of various notes and information relating to safety equipment item 12, including selection details, related documents, history, inspections, review standards and inspect now.

- [94] **Figures 12 and 29** provide representative examples of the screens that display data corresponding to buttons 1116 (**Figure 10**). The information is displayed in a window that drops down below screens shot 1110 (**Figure 10**). **Figure 12** is a screen shot 1310 of an inspection procedure, arrived at by clicking Inspect Now button 1116. Radio buttons 1312 correspond to questions related to the inspection, with a user selecting a radio button 1312 corresponding to the answer to each question 1314. When each question 1314 has been answered the user enters what kind of inspection had been conducted and enters any specialized comments in fields 1316. The inspection is saved by clicking button 1318.
- [95] **Figure 29** is a screen shot 3010 of details pertaining to safety equipment item 12 arrived at by clicking details button 1116. Available information may include sizes available, standards met by safety equipment item 12, and details about materials and construction.
- [96] **Figure 11** is a screen shot 1210 displaying the safety equipment items 12 associated with the customer 22. Drop-down menus 1212 allow a user to narrow the scope of a search of safety equipment items 12 by specifying all or a subset of sites, users and product types. Once the search has been conducted, relevant information is displayed in window 1214. The information includes all relevant safety equipment items 12, and their unique identifier 10, model number, description, date of manufacture or activation date, current site and current user.
- [97] **Figure 13** is a screen shot 1410 allowing input into drop-down menus 1412 a request for an inspection log report. The user may select the relevant site, personnel and product type. The user may also select the format of the report. The report may be of the same format as that displayed in window 1414. Buttons 1416 allow a user to refresh the search based on the criteria entered in drop-down menus 1412, and to print the report.

- [98] **Figure 14** is a screen shot 1510 allowing input into fields 1512 a request for an inventory report based on several criteria, such as site, personnel and product type. The data selected may then be viewed in window 1516 upon selection of the refresh button 1514.
- [99] Although the above description has mostly referred to the association of newly produced safety equipment items 12, namely safety equipment items 12 that have not yet passed out of control of producer 14 into a stream of commerce, it is to be recognized and understood that it is contemplated that safety equipment items 12 having already passed from the control of producer 14 may also be included in database 16 after having been associated with unique identifier. In an aspect, safety equipment items 12 are retrofit with a unique identifier and input into database 16, either by customer 16, by producer 14 or by another.
- [100] The apparatus for attaching unique identifier 10 to a retrofit safety equipment item 12 uniquely associates such retrofit safety equipment 12 with that unique identifier.
- [101] Retrofitting safety equipment items 12 with unique identifier 10 and including such association in database 16 achieves significant advantages. Customer 22 may immediately achieve establishment of database 16 containing not only new safety equipment items newly or recently purchased or acquired but instead allows customer 22 to move to the centralized database 16 approach to tracking or managing safety equipment items 12 without continuing to rely on old style paper records or fragmented electronic records. Without the retrofitting of existing safety equipment items 12, customer 22 would instead need to rely on other safety equipment item 12 management including management of inspection records. The necessity of having two management systems for one inventory of safety equipment items 12 would be a burden on customer 22 and might prevent customer 22 from being able to practically switch to the controlled database system described herein. Further, retrofitting existing safety equipment items 12 allows producer 14 to utilize controlled database 16 to communicate with customers 22 and users and be relatively assured that such customers 22 will receive appropriate information for all or most of their inventory of safety equipment items 12 rather than just newly produced safety equipment items 12.

- [102] Existing safety equipment items 12 manufactured or produced by producer 14 may be retrofit with unique identifier 10 and so associated in database 16. Additionally, existing or newly produced safety equipment items produced by another producer 14, i.e., by a producer not in control of database 16, may also be retrofit with unique identifier 10 and input into database 16. The retrofit of safety equipment items 12 not produced by producer 14 allows a customer 22 to include all or most of their inventory in database 16 even though not all of their inventory of safety equipment items 12 was produced by producer 14. Further, such retrofit also allows database 16 to be more of an industry-wide database utilizable across all producers. Such an industry-wide database could allow governmental agencies or industry associations to get word to the entire industry if desired or needed.
- [103] The following flow charts illustrate various aspects related to database 16 and various aspects of one or more of flow charts illustrated in **Figure 15** through **Figure 18** may include an embodiment or embodiments of the presently claimed invention.
- [104] **Figure 15** is a flow chart illustrating aspects of an embodiment of controlled database 16. Unique identifier 10 is associated (1610) with, e.g., applied or attached, to safety equipment item 12. If needed, a unique identifier 10 is associated (1612) with a customer 22 or distributor thereby associating safety equipment item 12 with such customer 22. Database 16 is established (1614) containing information related to safety equipment item 12 with unique identifier 10. Database 16 is ported (1616) to customer 22. If desired or needed, information is pushed (1618) to customer 22. If desired or needed, safety equipment item 12 may be associated (1620) with a location. If desired or needed, safety equipment item 12 may be associated (1622) with a user. Optionally, the information in database 16 may be used to locate (1624) safety equipment item 12. Optionally, customer 22 may interrogate (1626) database 16 to obtain information from database 16 relative to those safety equipment items 12 associated with that customer 22, e.g., the inventory report request illustrated in **Figure 14**. Optionally, information in database 16 may be used to track (1628) the movement of safety equipment item 12. Optionally, the information in database 16 and portal 26 may be used by producer 14 to transmit marketing information to

customer 22 such as suggesting a reorder of safety equipment item 12 or ancillary equipment.

[105] **Figure 16** is a flow chart illustrating aspects of an embodiment of controlled database 16 related to the direct entry of data into database 16. Database 16 of safety equipment information is established (1710). Safety equipment item 12 is associated (1712) with unique identifier 10. Safety equipment item 12, through unique identifier 10, is associated (1714) with a customer 22 or distributor. Optionally, such customer 22 or distributor accesses (1716) database 16 through portal 26. Customer 22 remotely enters data related to safety equipment item 12 associated with such customer 22 directly into database 16. Ideally, portal 26 need not be used for this purpose. Customer 22 does not maintain a duplicate database of information. Rather, data added or modified by customer 22 is directly entered into database 16 ensuring a common user-wide database of information related to safety equipment item 12.

[106] **Figure 17** is a flow chart illustrating aspects of an embodiment of controlled database 16 related to the retrofit of existing safety equipment items 12. Unique identifier 10 is applied (1810), preferably attached, to safety equipment item 12 under control of producer 14. Database 16 is established (1812) containing information related to safety equipment items 12 with unique identifiers 10. Safety equipment items 12 under the control of producer 14 are associated (1814) with unique identifier in database 16. If needed, safety equipment items 12 having passed from the control of producer 14 are retrofit (1816) with unique identifier 10. If needed, retrofit safety equipment items 12 are associated (1818) with unique identifier 10 in database 16. In some embodiments, safety equipment items 12 are associated (1820) with a customer and/or distributor. In some embodiments, safety equipment items 12 are associated (1822) with a user. In some embodiments, the movement or location of safety equipment items 12 are tracked (1824). If needed, such tracked or other safety equipment items 12 are associated (1826) with a location.

[107] **Figure 18** is a flow chart illustrating aspects of an embodiment of controlled database 16 related to inspection. Unique identifier 10 is associated (1910) with, e.g., applied or attached, to safety equipment item 12. If needed, a unique identifier 10 is associated (1912) with a user thereby associating safety equipment item 12 with such

user. Database 16 is established (1914) containing information related to safety equipment item 12 with unique identifier 10. An inspection history of safety equipment item 12 is maintained (1916) in database 16. User may directly enter (1918) inspection data directly into database 16 using, for example, mobile device 28. In so doing, database 16 continues to maintain (1916) an inspection history database. Optionally, user may also maintain (1920) inspection history, e.g., by marking a paper record attached to safety equipment item 12. Thus, a dual inspection history is maintained. The manual history kept locally with safety equipment item 12 as is now customary and which may still be required by governmental agencies and a more global electronic inspection history, not only for this safety equipment item 12 but also for other safety equipment items 12 associated with this user or customer 22 and even for other customers may both be kept. Both may be used, perhaps for different purposes. The manual local inspection record is familiar and can be accessed without specialized computer equipment. This may be advantageous in the field. The global electronic records is more useful for users or customers 22 having a plurality of safety equipment items 12 and enables such user or customer to have access, at once, inspection data and records on all of their safety equipment items 12 and enables such customers 22 or users to know when inspections are due and to schedule inspections accordingly. Optionally, the user may be notified (1922) of an inspection event.

What is claimed is:

1. A method of facilitating a set of information relating to a plurality of first safety equipment items produced by a producer, comprising the steps of:

applying one of a plurality of unique identifiers to each of said plurality of first safety equipment items before said plurality of first safety equipment items leave control of said producer;

establishing a database representative of information associated with a plurality of unique identifiers and a plurality of safety equipment items;

associating said one of said plurality of unique identifiers with a respective one of said plurality of first safety equipment items;

retrofitting a plurality of second safety equipment items by applying one of said plurality of unique identifiers with a respective one of said plurality of second safety equipment items after said plurality of second safety equipment items leaves control of said producer; and

associating said one of said plurality of unique identifiers with a respective one of said plurality of safety equipment items;
2. A method as in claim 1 wherein said database is controlled by said producer.
3. A method as in claim 2 wherein some of said plurality of second safety equipment items have been produced by said producer and others of said plurality of second safety equipment have been produced by another producer.
4. A method as in claim 1 further comprising the step of associating each of said plurality of safety equipment items with a customer.
5. A method as in claim 2 further comprising the step of associating at least one of said safety equipment items with a location.
6. A database system containing a set of information relating to a plurality of first safety equipment items produced by a producer, comprising:

a plurality of unique identifiers applied to each of said plurality of first safety equipment items;

a database representative of information associated with a plurality of unique identifiers and a plurality of safety equipment items;

said database containing information associating said one of said plurality of unique identifiers with a respective one of said plurality of first safety equipment items; and

a plurality of second safety equipment items retrofitted with one of said plurality of unique identifiers;

said database containing information associating said one of said plurality of unique identifiers with a respective one of said plurality of safety equipment items.

7. A database system as in claim 6 wherein said database is controlled by said producer.
8. A database system as in claim 7 wherein said plurality of second safety equipment items has been produced by said producer.
9. A database system as in claim 7 wherein said plurality of second safety equipment items has been produced by another producer.
10. A database system as in claim 7 wherein some of said plurality of second safety equipment items have been produced by said producer and others of said plurality of second safety equipment have been produced by another producer.
11. A database system as in claim 6 wherein said database contains information associating each of said plurality of safety equipment items with a customer.
12. A database system as in claim 11 wherein said database facilitates porting a selected portion of said information related to said customer to said customer.

1/17





Fig. 1

**Fig. 2**





Fig. 3

**Fig. 4**

5/17



USA - RFID SCAN FOR WO

Current Work Order Current ID 612

Current Location# Current Part#

Qty to Scan# Qty Scanned#

Input RFID Tag# 614

Previous Scans

To delete a RFID tag from this order

Fig. 5

610

Administration

Admin / Log off

Registration Maintenance

Filter by

Login


Note: To Filter, TYPE chan TAB

Login (Key)	First Name	Last Name	Company	Email	Password	Create Date	Last Login	Last Sync	# of Sites	# of Personnel	# of Equip
ICimobile (627)	Austin	Blackwell			Insulated	12/12/06	NA	NA	2	4	0
SAFE260 (509)	Travis	Groh	ADM Refinery	travis_groh@admworld.com	SAFETY	06/29/06	NA	NA	1	23	4
SAFE261 (510)	VOLMIR	MESALIRA	SER MAP	volmir@sermap.com.br	valmir	07/17/06	05/16/07 18:08:56	NA	5	0	3
SAFE261 (582)	VOLMIR	MESALIRA	SER MAP	volmir@sermap.com.br	valmir	07/17/06	05/16/07 18:08:56	05/15/07 16:27:12	1	2	0
SAFE263 (512)	STEVE	COLEMAN	Southwestern Drilling Co O	rsteve@swdip.com	SC2725228	07/19/06	NA	NA	11	60	8
SAFE266 (513)	Mark	Damon	Process Marketing	markdamon@aol.com	safety	07/20/06	05/18/07 17:01:29	NA	4	5	3
SAFE267 (516)	PAUL	LEITHNER	BERTRAM & LEITHER	BALCORPES@COMCASTNET	balco	07/25/06	05/25/07 13:52:39	05/25/07 14:05:41	4	5	11
SAFE274 (517)	BILL	CRUZ	VER SALES	wcruz@versales.com	BEACH7873	07/31/06	NA	NA	3	1	0
SAFE275 (529)	BRYON	ELUMBAUGH	NORCO	bryone@norco-inc.com	BRYON	08/01/06	NA	NA	10	14	4
SAFE277 (561)	Paul	Gott	Process Marketing	paulgott@charter.net	3030	08/01/06	NA	NA	6	4	4

Fig. 6

710

6/17



USA - RFID SCAN FOR DISPATCH

812 → Current ID/Lot
 Current Part#
 Qty to Scan# 0 Qty to Scan# 0
 Input RFID Tag# 814

Previous Scans

To delete a RFID tag from this order

Fig. 7

810

Inspect|Inventory|Information|Input|Home|Log off

Welcome to

isafe
INTELLIGENT SAFETY SYSTEM

Contact:	Mr. Bill Johnson	# of registered equipment	75
Company:	Safety Construction	# of assigned equipment	62
Address:	3833 Sala Way	# of unassigned equipment	13
City:	Red Wing		
State/ Prov:	MN	# of inspected equipment	62
Country:	US	# of past-due inspections	13
Phone:	1-204-555-1234	# of sites	43
Fax:	1-204-555-1234		
Email:	bjohnson@safetyconst.com	License Key(s):	CSG00000501

912 914 910

Fig. 8

7/17

1012

General

Inspect | Inventory | Information | Input | Home | Log off

General Information

Select Region

Contact Capital Safety
3833 Sale Way
Red Wing, MN United States
Phone 1-651-388-8282
Fax 1-651-388-5065
Email isafe@capitalsafety.com
Website United States

Select Info ☒ Advisories
Advisories
Downloads
Welcome

1014

1010

1016

Fig. 9

General

Inspect | Inventory | Information | Input | Home | Log off

☒

Tag

Manufacturer ☒

Model?#

Description

Serial#/Lot#

Product type ☒

Date/Time of MFG

Current Site ☒

Current User ☒

Last Date Inspected

1112

1116

1110

1114

Details | Documents | History | Inspections | Standards




Fig. 10

8/17

Inventory
Inspect Inventory Information Input Home Lof off
Inventory Research
1212
Site ALL Personnel ALL Product Type Harnesses Refresh

Tag	Model/#	Description	Product Type	Date of Mfg / Activation Date	Current Site	Current User
2000082065852			Harnesses	04/16/07	Capital Safety (Australia)	
22222222222222221	1110600C	Delta II Vest Style Harness	Harnesses	05/08/07		
22222222222222222	1110600C	Delta II Vest Style Harness	Harnesses	05/08/07		
982000062043835	1110990	Delta II Vest Style Harness	Harnesses	06/19/06	Airgas Russia	
982000062476754	1110990	Delta II Vest Style Harness	Harnesses	06/07/05	Houston	
982000062484760		Exofit XP Cross Over Style Harness	Harnesses	06/07/06	SC Tower Site 21	
982000062484907		Delta II Vest Style Harness	Harnesses	06/07/06	Houston	
982000062484965	1110152	Exofit XP Cross Over Style Harness	Harnesses	06/07/06	Houston	
982000062484929	1102000	Delta II Vest Style Harness	Harnesses	06/07/06	Oceanside Pier	Fraser, Cy
982000062590967	1110102	Exofit Iron Worker Harness	Harnesses	08/03/06	Capital Safety (Australia)	
9820000626255862	1100532	Exofit XP Vest Style Harness	Harnesses	07/14/06	Tool Shop	Parrish, William
982000062651279	1102000	Delta II Vest Style Harness	Harnesses	03/03/07	Safety Shop	bailey, josh
982000062651656	1102000	Delta II Vest Style Harness	Harnesses	02/07/07		
982000062651720	1102000	Delta II Vest Style Harness	Harnesses	02/07/07	Capital Safety (Australia)	Johnson, Bill
982000062652444	1102000	Delta II Vest Style Harness	Harnesses	02/07/07	AG	velasco, Pat
982000078384102	1110101	Exofit XP Vest Style Harness	Harnesses	10/10/06	Oceanside Pier	848326, PERSON

Fig. 11

Details Documents History Inspections Standards

Pass Fail Question

☐ ☐ Webbing material and stitches are not frayed, cut, broken, or pulled

☐ ☐ Webbing is free of tears, abrasions, mold, burns, or discoloration

☐ ☐ Hardware and buckles function properly and are not damaged

☐ ☐ All labels are present and fully legible

Inspect Type: Monthly

Inspection Note:

Complete Inspection

1312 1314 1316 1318 1310

Fig. 12

9/17

Inspection

Inspect | Inventory | Information | Input | Home | Log off

Print Inspection Log(s) 1412

1416 Read Only • Required • Optional

Site
 Personnel
 Product Type
 Output Type

Tag	Model/#	Product Type	Description	Description	Current User	Last Inspected
10000001				Oceanside Pier		never
1111111111	1111111111			Houston		04/29/07
1212						never
123454321111111						never
123456789876543	KB11100585					never
14257801						03/06/07
962r42wfwf						
2000082065852				Capital Safety (Australia)		never
2222222222222221	1110600C	Harnesses	Delta II Vest Style Harness			05/08/07
2222222222222222	1110600C	Harnesses	Delta II Vest Style Harness			never
982000062043835	1110990	Harnesses	Delta II Vest Style Harness	Airgas Russia		05/15/07
982000062055752	1102000	982000062055752	Delta II Vest Style Harness	Airgas Russia		05/03/07
98200006241633				Airgas Russia		never
982000062476754	1110990	Harnesses	Delta II Vest Style Harness	Houston		04/25/07

1414 1410

Fig. 13

Inventory

Inspect | Inventory | Information | Input | Home | Log off


Inventory Research 1512


1514 Site
 Personnel
 Product Type

Tag	Model/#	Description	Product Type	Date of Mig / Activation Date	Current Site	Current User
10000001				04/29/07	Oceanside Pier	
1111111111			1111111111	03/15/07	Houston	
1212				04/18/07		
123454321111111				04/04/07		
123456789876543	KB11100585			05/17/07		
14257801				02/19/07		
962r42wfwf			14257801-962r42wfwf			
2000082065852			Harnesses	04/16/07	Capital Safety (Australia)	
2222222222222221	1110600C	Delta II Vest Style Harness	Harnesses	05/08/07		
2222222222222222	1110600C	Delta II Vest Style Harness	Harnesses	05/08/07		
982000062043835	1110990	Delta II Vest Style Harness	Harnesses	06/19/06	Airgas Russia	
982000062055752	1102000	Delta II Vest Style Harness	982000062055752	07/20/06	Airgas Russia	
98200006241633				04/16/07	Airgas Russia	
982000062476754	1110990	Delta II Vest Style Harness	Harnesses	05/07/05	Houston	
982000062477237	1108575	Exofit Vest Style Harness	982000062477237	06/07/06	Houston	


1516 1510


Fig. 14

**Fig. 15**

**Fig. 16**

12/17

**Fig. 17**

**Fig. 18**




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24






Fig. 25

**Fig. 26****Fig. 27**

Inspection						
		Inspect	Inventory	Information	Input	Home
Inspection Status						
		Past Due Inspection		No Yet Inspected		Current On Inspection
Tag	Description	Current Site	Current User	Last Inspection	Days Since Inspection	
98200006206366		Houston	Kramer, Gene	02/06/07	118	
98200006206517209		Unassigned		02/06/07	118	
14257801-982042MMW		Unassigned		03/06/07	90	
982000062484907		SC Oil Rig	Coplan, Kevin	03/06/07	90	
9820039104013304	Delta II Vest Style Harness	SC Tower Site 21	Kramer, Gene	03/06/07	88	
9820000622509567	Exofit XP Vest Style Harness	Capital Safety (Australia)	Horrocks, Michael	03/12/07	84	
10000001		Oceanside Pier			NA	
1212		Unassigned			NA	
12345432111111		Unassigned			NA	
222222222222221	Delta II Vest Style Harness	Unassigned		05/08/07	27	
9820039104024490	Exofit Vest Style Harness	Tool Shop	Worth, Mary	05/08/07	28	
9820000620438335		Airgas Russia		05/15/07	20	

Fig. 28 2910

2912

- Delta No-Tangle? design for added comfort and easy donning
- Spring loaded stand-up back D-ring ensures fast, easy, and safe connections
- Tongue buckle body belt and side D-rings for added comfort, support and versatility
- Sewn-in back pad and shoulder pads for the ultimate in comfort
- Adjustable non-slip chest strap with easy to use pass-thru buckle
- Parachute buckles on lower shoulder straps for quick and easy adjustment
- Tongue buckle leg straps for fast & easy donning
- Polyester webbing construction for added durability
- Plated hardware for corrosion resistance
- Size = Large (XS - XL available)
- Meets or exceeds all applicable industry standards including OSHA, ANSI and teh stringent ANSI Z359

With the addition of a body belt and pad with side D-rings, shoulder pads, this harness is ideal for general construction applications where fall protection and positioning is needed. It provides added versatility for carrying tools, pouches, etc., and additional back support and comfort.

Every DBI/SALA harness combines maximum comfort, freedom of movement and ease of use without sacrificing safety. All harnesses are designed to securely retain you in case of a fall and distribute the impact forces throughout your body. Our exclusive Patented Delta No-Tangle? design holds the shape of the harness, adding to your comfort and making it easier to put on.

3010

Fig. 29