



US011610036B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 11,610,036 B2**
(45) **Date of Patent:** ***Mar. 21, 2023**

(54) **INTEGRATED CIRCUITS AS A SERVICE**

(71) Applicant: **SiFive, Inc.**, San Mateo, CA (US)

(72) Inventors: **Yunsup Lee**, Redwood City, CA (US);
Richard Xia, San Francisco, CA (US);
Derek Pappas, Palo Alto, CA (US);
Mark Nugent, San Mateo, CA (US);
Henry Cook, Berkeley, CA (US);
Wesley Waylon Terpstra, San Mateo,
CA (US); **Pin Hung Chen**, Cupertino,
CA (US)

(73) Assignee: **SiFive, Inc.**, San Mateo, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **17/361,238**

(22) Filed: **Jun. 28, 2021**

(65) **Prior Publication Data**

US 2021/0365609 A1 Nov. 25, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/528,911, filed on
Aug. 1, 2019, now Pat. No. 11,048,838.

(60) Provisional application No. 62/713,841, filed on Aug.
2, 2018.

(51) **Int. Cl.**

G06F 30/20 (2020.01)

G06F 30/30 (2020.01)

(52) **U.S. Cl.**

CPC **G06F 30/20** (2020.01); **G06F 30/30**
(2020.01)

(58) **Field of Classification Search**

CPC G06F 30/20

USPC 716/111

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,020,852 B2	3/2006	Oeltjen et al.	
8,484,588 B2	7/2013	Ng et al.	
9,038,004 B2 *	5/2015	Ford	G06F 30/30 716/112

2012/0017196 A1 1/2012 Ng et al.
(Continued)

OTHER PUBLICATIONS

H. Cook et al.; Diplomatic Design Patterns: A TileLink Case Study;
CARRV 17; Oct. 2017; Boston, MA; 7 pages.

(Continued)


Primary Examiner — Eric D Lee

(74) *Attorney, Agent, or Firm* — Young Basile Hanlon &
MacFarlane, P.C.

(57) **ABSTRACT**

Systems and methods are disclosed for automated genera-
tion of integrated circuit designs and associated data. These
allow the design of processors and SoCs by a single,
non-expert who understands high-level requirements; allow
the en masse exploration of the design-space through the
generation processors across the design-space via simula-
tion, or emulation; allow the easy integration of IP cores
from multiple third parties into an SoC; allow for delivery of
a multi-tenant service for producing processors and SoCs
that are customized while also being pre-verified and deliv-
ered with a complete set of developer tools, documentation
and related outputs. Some embodiments, provide direct
delivery, or delivery into a cloud hosting environment, of
finished integrated circuits embodying the processors and
SoCs.

20 Claims, 13 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0290693 A1 * 10/2013 Guerrero G06F 30/30
713/1
2016/0371407 A1 12/2016 Larzul
2018/0011948 A1 1/2018 Irissou et al.
2018/0212839 A1 7/2018 Hiers et al.
2020/0159981 A1 * 5/2020 DiCorpo G06F 30/3323

OTHER PUBLICATIONS

E. Cote; Edmond Cote's Blog: Gentle introduction to diplomacy; May 3, 2017; 3 pages. blog.edmondcote.com/2017/05/gentle-introduction-to-diplomacy.html.
P. S. Li et al.; Specification for the FIRRTL Language; Electrical Engineering and Computer Sciences, University of California at Berkeley; Feb. 24, 2016; 57 pages.

K. Asanovic et al.; The Rocket Chip Generator; Electrical Engineering and Computer Sciences, University of California at Berkeley; Apr. 15, 2016; 11 pages.

A. Izraelevitz et al.; Reusability is FIRRTL Ground: Hardware Construction Languages, Compiler Frameworks, and Transformations; Department of Electrical Engineering and Computer Sciences, University of California at Berkeley; as early as Nov. 2017; 8 pages.


Y. Lee; Free Chips Project: a nonprofit for hosting open-source RISC-V implementations, tools, code; 2016; 25 pages.

Xilinx, Vivado Design Suite User Guide, Designing IP Subsystems Using IP Integrator; UG994 (v2017.1); Apr. 5, 2017; 203 pages.

International Search Report and Written Opinion for International Application No. PCT/US2019/044610 dated Oct. 29, 2019.

P. Rigge; Designing Digital Signal Processors with RocketChip, CARRV' 18, Jun. 2018, Los Angeles, CA USA; 6 pages.

* cited by examiner

**FIG. 1**









FIG. 2





**FIG. 4**

**FIG. 5**


**FIG. 6**

**FIG. 7**

**FIG. 8**

**FIG. 9**

1000

**FIG. 10**




FIG. 11




FIG. 12




FIG. 13

1

INTEGRATED CIRCUITS AS A SERVICE**CROSS-REFERENCE TO RELATED APPLICATION(S)**

This application is a continuation of U.S. patent application Ser. No. 16/528,911, which was filed on Aug. 1, 2019, which claims priority to and the benefit of U.S. Provisional application patent Ser. No. 62/713,841, filed Aug. 2, 2018, the entire disclosure of which is hereby incorporated by reference.

TECHNICAL FIELD

This disclosure relates to automated generation of integrated circuit designs and associated data.

BACKGROUND

Integrated circuits are typically designed and tested in a multi-step process that involves multiple specialized engineers performing a variety of different design and verification tasks on an integrated circuit design. A variety of internal or proprietary (e.g. company-specific) integrated circuit design tool chains are typically used by these engineers to handle different parts of the integrated circuit design workflow of using commercial electronic design automation (EDA) tools.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure is best understood from the following detailed description when read in conjunction with the accompanying drawings. It is emphasized that, according to common practice, the various features of the drawings are not to-scale. On the contrary, the dimensions of the various features are arbitrarily expanded or reduced for clarity.

FIG. 1 is block diagram of an example of a system for facilitating design of integrated circuits.

FIG. 2 is block diagram of an example of a system for facilitating design and manufacture of integrated circuits.

FIG. 3 is block diagram of an example of a system for facilitating design of integrated circuits.

FIG. 4 is flow chart of an example of a process for facilitating design of integrated circuits.

FIG. 5 is flow chart of an example of an iterative process for facilitating design of integrated circuits.

FIG. 6 is flow chart of an example of a process for generating a register-transfer level data structure for an integrated circuit based on a design parameters data structure.

FIG. 7 is flow chart of an example of a process for generating a physical design data structure for an integrated circuit based on a register-transfer level data structure.

FIG. 8 is flow chart of an example of a process for generating documentation for an integrated circuit based on a register-transfer level data structure.

FIG. 9 is flow chart of an example of a process for generating a multi-tenant physical design specification to facilitate manufacturing of integrated circuits.

FIG. 10 is flow chart of an example of a process for facilitating manufacturing and testing of integrated circuits.

FIG. 11 is a diagram of an example display region generated for presenting a web interface to facilitate selection of a template design of an integrated circuit.

2

FIG. 12 is a diagram of an example display region generated for presenting a web interface to facilitate customized design of an integrated circuit.

FIG. 13 is a diagram of an example display region generated for presenting a web interface to facilitate access to a customized design of an integrated circuit.

DETAILED DESCRIPTION

Systems and methods for automated generation and testing of integrated circuit designs are disclosed. These systems provide a method that allows a single engineer who has an idea for a processor, or system on a chip (SoC), design to easily specify their chip requirements in terms of a handful of design parameter values (or colloquially knobs) and have the system automate the operation of many commercial electronic design automation (EDA) tools for both design and verification of the processors, or SoC, and thus accomplish with a single engineer in hours (or minutes) what traditionally has taken massive teams of specialized engineers familiar with the operation of specific EDA tools a much longer period of time.

Thus, the system and methods enable the following challenging technical problems to be addressed: (a) allow the design of processors and SoCs by a single, non-expert who understands high-level requirements, (b) easily allow the scripted exploration of the design-space through the generation of potentially thousands of alternate expressions of the requirements and simulation, or emulation, of the completed designs en masse, (c) automate the integration of intellectual property (IP) cores (or blocks) from multiple third parties with a processor design into an SoC, and (d) allow for the creation of a multi-tenant, or hosted, processor and SoC service that produces custom, yet pre-verified, processors and SoCs. In the case of (d), the service can be extended all the way to the delivery of manufactured processors or SoCs either to a user or to a cloud environment, e.g. a 3rd party receives the processor and installs it into a cloud where the user can control its operation.

One element supporting and undergirding multiple embodiments is the development and use of a number of conventions and templating to allow customer-provided parameters to dictate the delivered resource from a given service (see detailed discussion of the services, below). The conventions (e.g., think like main being the entry point for a C-program) together with the service-specific templating, or parameterization, are used to customize and then invoke commercial (and also open source) EDA tools. For example, chisel is an open source tool for hardware construction that uses a Scala program to generate register-transfer language such as Verilog. The user-defined design parameters discussed above and herein can be templated into a configuration, or provided as parameters, to say a general Chisel program for a RISC-V processor to produce a user-specific variant. The output from that can be used as design parameters for further services and so on. The point of this being that these technical approaches of conventions and templating/parameterization provide for tremendous flexibility to systematically automate a complex toolchain usage of EDA tools to produce a processor or SoC design that is verified, and potentially even emulated/simulated.

A web interface and/or a scripting application programming interface (API) may be provided for selecting a set of design parameter values associated with one or more template integrated circuit designs. The template designs may be encoded using conventions to facilitate modular design. A set of design parameter values is encoded in a design

parameters data structure and passed to an automated system for generation and testing of an integrated circuit design using the chosen design parameter values. For example the design parameters of the design parameters data structure may include whether privilege modes are supported, whether multiply extension is supported, whether floating point extension is supported, whether error-correcting codes are supported in on-chip memory, the size of an instruction cache, an associativity of the instruction cache, a size of a data subsystem in on-chip memory, whether a port (e.g., a front port, a system port, a peripheral port, or a memory port) is included, a count of memory port channels, a port communication protocol selection, a bus width, a count of physical memory protection units, whether JTAG debugging is supported, a count of hardware breakpoints, whether instruction tracing is supported, whether debug direct memory access is supported, a count of local interrupts, whether a platform level interrupt controller is supported, a count of interrupt priority levels, a count of global interrupts, whether branch prediction is supported, a count of branch target buffer entries, a count of branch history table entries, and/or a selection of a manufacturing process.

For example, a single command issued from the web interface may trigger the automatic generation of register-transfer level data, a software development kit, documentation, and a physical design file (e.g., GDSII file) for an integrated circuit that embodies the selected design parameter values. The single command may also trigger the generation an execution of a test plan for the integrated circuit design that has been generated. The resulting design data and corresponding test results may be provided to a user as, for example, a set of files, an archive, or a repository (e.g., a GitHub repository). The system may also facilitate the manufacture of an integrated circuit (e.g., a processor or system-on-a-chip (SoC)) using the resulting design by actually manufacturing the integrated circuit or forwarding the physical design to an external foundry for manufacturing and tracking the progress of the fabrication, testing, shipping, and/or installation of the manufactured chips. The system may change the way chips are designed to allow non-specialists to customize a chip by selecting relatively simple design parameters, which may enable fast design space exploration of the actual RTL or physical chip. For example, a well-designed chip can be developed from a high level set of configuration settings using a mix of Diplomacy, Chisel, FIRRTL. The system may be implemented efficiently by using a single language (e.g., Scala) to control multiple task in a design pipeline. Embedding in a functional programming language may provide more flexibility and may increase designer/user productivity.

In some implementations, field programmable gate array (FPGA) and/or other emulation models of the integrated circuit design are generated and used for testing. An FPGA model may be loaded onto a cloud-based FPGA that is used for verification testing. The system may enable easy configuration of an IP core. Feedback (e.g., performance, power, and area estimates for the integrated circuit) may be provided during the process and keeping user updated about where ordered chips are (e.g., where is my chip within the fabrication process or shipment tracking). The system may provide price estimates for a design, i.e., how much will acquiring the resulting chips cost. For example, both NRE (non-recurring engineering cost) and per unit cost estimates may be provided. The system may use a template based chip design (e.g., start with a provider or 3rd party-provided template of mix of IP/configurations. These chip or IP core

templates can be open-sourced and/or private per user preference, which will be developed with a certain NRE.

Some implementations use a version control system (e.g., Git/GitHub) to maintain template designs and to store and/or share customized integrated circuit designs and associated data. A version control system may provide source code management functions and enable further customization of designs. The version control services may be targeted for advanced users who want to further customize the chip. For example after an initial design is automatically generated based on a set on design parameter values, a controller of the system may give them a repository (e.g., a Git) with the basic building blocks wired together. The user could now add additional IP cores or customize the source code. For example, a user could incorporate their custom IP cores or change the source code. For example, a user could extend the test plan or documentation by committing specific files to the repository.

For example, the existing items discussed above may behave by conventions. So, for example, a user could add chapters to the documentation in their custom IP core directory using the right conventions. In some implementations, an "IP store" can be provided to facilitate sharing of designs, where well designed IP cores that follow the conventions can be pulled into another design and all of the above processes work in an automated fashion on it. For example, these could be a full implementation or just FPGA demos already taped out. The IP store may enable programmatic installation of 3rd party IP cores into a design. For example, a directory in Git that follows the applicable modular design conventions may be easily added/selected from a web application for the system. This ability to integrate the IP cores from multiple parties solves a challenging technical problem since cores from two different vendors might typically be pre-designed for different EDA design and verification tool usage/flows, e.g. one core may need additional different processing with EDA tools than another core.

In a first aspect, the subject matter described in this specification can be embodied in systems that include a web application server configured to generate a design parameters data structure based on input received, wherein the design parameters data structure includes values of design parameters of an integrated circuit design, and configured to display an auto-updating block diagram of a template design reflecting changes to values of the design parameters of the integrated circuit; a register-transfer level service module configured to generate a register-transfer level data structure for the integrated circuit based on the design parameters data structure; a software development kit service module configured to generate a software development kit for the integrated circuit based on the register-transfer level data structure; a physical design service module configured to generate a physical design data structure for the integrated circuit based on the register-transfer level data structure; a verification service module configured to generate a test plan for an integrated circuit based on the design parameters data structure and acceptance criteria; and a controller configured to access the design parameters data structure, invoke the register-transfer level service module with the design parameters data structure to obtain the register-transfer level data structure, invoke the software development kit service module with the register-transfer level data structure to obtain the software development kit, invoke the physical design service module with the register-transfer level data structure to obtain the physical design data structure, invoke the verification service module to obtain the test plan, and invoke

tests for the integrated circuit based on the test plan, the register-transfer level data structure, the software development kit, and the physical design data structure to obtain a set of test results.

In the first aspect, the systems may include a documentation service module configured to generate documentation for the integrated circuit based on the register-transfer level data structure. In the first aspect, the systems may include a field programmable gate array service module configured to generate a field programmable gate array emulation data structure for the integrated circuit based on the register-transfer level data structure and the software development kit. In the first aspect, the controller may be configured to invoke a test using a field programmable gate array, programmed based on the field programmable gate array emulation data structure, to obtain an emulation result, wherein the field programmable gate array is operating on a cloud server. In the first aspect, the controller may include an application programming interface that enables scripting to process multiple design parameters data structures. In the first aspect, the controller may be configured to transmit a physical design specification based on the physical design data structure to a server to invoke manufacturing of the integrated circuit. In the first aspect, the register-transfer level data structure may include a memory map, one or more port assignments, and floorplan information. In the first aspect, the register-transfer level service module may be configured to execute Scala code to read the design parameters data structure and dynamically generate a circuit graph. In the first aspect, the register-transfer level service module may be configured to invoke a Diplomacy package in Chisel to determine a bus protocol for the integrated circuit. In the first aspect, the software development kit for the integrated circuit may include loaders for a Verilog simulator and a physical field programmable gate array to be flashed. In the first aspect, the controller may be configured to update the design parameters data structure based on the test results. In the first aspect, the design parameters data structure may include a reference to a template design. In the first aspect, the integrated circuit may be an IP core. In the first aspect, the integrated circuit may be a system-on-a-chip. The first aspect may include any combination of the features described in this paragraph.

In a second aspect, the subject matter described in this specification can be embodied in methods that include accessing a design parameters data structure, wherein the design parameters data structure includes values of design parameters of an integrated circuit design; responsive to a command identifying the design parameters data structure, generating a register-transfer level data structure for an integrated circuit based on the design parameters data structure; responsive to the command identifying the design parameters data structure, generating a software development kit for the integrated circuit based on the register-transfer level data structure; responsive to the command identifying the design parameters data structure, generating a physical design data structure for the integrated circuit based on the register-transfer level data structure; responsive to the command identifying the design parameters data structure, generating a test plan for an integrated circuit based on the design parameters data structure and acceptance criteria; responsive to the command identifying the design parameters data structure, invoking tests for the integrated circuit based on the test plan, the register-transfer level data structure, the software development kit, and the physical design data structure to obtain a set of test results; and transmitting, storing, or displaying a design data struc-

ture based on the register-transfer level data structure, the software development kit, the physical design data structure, and the test results.

In the second aspect, the methods may include, responsive to the command identifying the design parameters data structure, generating documentation for the integrated circuit based on the register-transfer level data structure. In the second aspect, generating documentation for the integrated circuit may include parsing the register-transfer level data structure for the integrated circuit to identify applicable portions of a documentation framework; generating snippets of documentation based on the applicable portions identified; assembling the snippets into a dictionary; instantiating a document from a template; and merging references to the dictionary with the document. In the second aspect, the methods may include, responsive to the command identifying the design parameters data structure, generating a field programmable gate array emulation data structure for the integrated circuit based on the register-transfer level data structure and the software development kit. In the second aspect, the methods may include invoking a test using a field programmable gate array, programmed based on the field programmable gate array emulation data structure, to obtain an emulation result, wherein the field programmable gate array is operating on a cloud server. In the second aspect, the methods may include transmitting a physical design specification based on the physical design data structure to a server to invoke manufacturing of the integrated circuit. In the second aspect, the physical design specification includes designs for multiple independent integrated circuits, including the integrated circuit, and the methods may include: allocating mask area to the multiple independent integrated circuits based on a production plan; and performing design rule checks on the physical design specification. In the second aspect, the methods may include: manufacturing the integrated circuit; installing the integrated circuit in a system configured to operate the integrated circuit responsive to commands received via communications with a cloud server; and transmitting a login for accessing and controlling the integrated circuit. In the second aspect, the design parameters data structure may include a JSON file and generating the register-transfer level data structure for the integrated circuit comprises: parsing the JSON file to determine the values of the design parameters of the integrated circuit design; converting the design parameter values into input parameter values for a register-transfer level generator; and invoking the register-transfer level generator with the input parameters to obtain register-transfer level data included in the register-transfer level data structure. In the second aspect, the register-transfer level data structure may include a memory map, one or more port assignments, and floorplan information. In the second aspect, generating the register-transfer level data structure for the integrated circuit may include executing Scala code to read the design parameters data structure and dynamically generate a circuit graph. In the second aspect, generating the register-transfer level data structure for the integrated circuit may include invoking a Diplomacy package in Chisel to determine a bus protocol for the integrated circuit. In the second aspect, generating the software development kit for the integrated circuit may include generating loaders for a Verilog simulator and a physical field programmable gate array to be flashed. In the second aspect, the methods may include receiving the acceptance criteria with the design parameters data structure. In the second aspect, the methods may include updating the design parameters data structure based on the test results. In the second aspect, the design parameters data structure may

include a reference to a template design. In the second aspect, generating the physical design data structure for the integrated circuit may include: invoking source synthesis and place and route tools; invoking logical equivalent checking; and invoking a static timing analysis tool. In the second aspect, the methods may include generating the design parameters data structure based on input received via a web application that displays an auto-updating block diagram of a template design reflecting changes to values of the design parameters of the integrated circuit. In the second aspect, the methods may include generating the design parameters data structure based on input received via an application programming interface. In the second aspect, the integrated circuit may be an IP core. In the second aspect, the integrated circuit may be a system-on-a-chip. The second aspect may include any combination of the features described in this paragraph.

In a third aspect, the subject matter described in this specification can be embodied in systems that include a network interface, a memory, and a processor, wherein the memory includes instructions executable by the processor to cause the system to: access a design parameters data structure, wherein the design parameters data structure includes values of design parameters of an integrated circuit design; responsive to a command identifying the design parameters data structure, generate a register-transfer level data structure for an integrated circuit based on the design parameters data structure; responsive to the command identifying the design parameters data structure, generate a software development kit for the integrated circuit based on the register-transfer level data structure; responsive to the command identifying the design parameters data structure, generate a physical design data structure for the integrated circuit based on the register-transfer level data structure; responsive to the command identifying the design parameters data structure, generate a test plan for an integrated circuit based on the design parameters data structure and acceptance criteria; responsive to the command identifying the design parameters data structure, invoke tests for the integrated circuit based on the test plan, the register-transfer level data structure, the software development kit, and the physical design data structure to obtain a set of test results; and transmit, using the network interface, a design data structure based on the register-transfer level data structure, the software development kit, the physical design data structure, and the test results.

In the third aspect, the memory may include instructions executable by the processor to cause the system to, responsive to the command identifying the design parameters data structure, generate documentation for the integrated circuit based on the register-transfer level data structure. In the third aspect, generating documentation for the integrated circuit may include: parsing the register-transfer level data structure for the integrated circuit to identify applicable portions of a documentation framework; generating snippets of documentation based on the applicable portions identified; assembling the snippets into a dictionary; instantiate a document from a template; and merging references to the dictionary with the document. In the third aspect, the memory may include instructions executable by the processor to cause the system to: responsive to the command identifying the design parameters data structure, generate a field programmable gate array emulation data structure for the integrated circuit based on the register-transfer level data structure and the software development kit. In the third aspect, the memory includes instructions executable by the processor to cause the system to: invoke a test using a field programmable gate

array, programmed based on the field programmable gate array emulation data structure, to obtain an emulation result, wherein the field programmable gate array is operating on a cloud server. In the third aspect, the memory may include instructions executable by the processor to cause the system to: transmit a physical design specification based on the physical design data structure to a server to invoke manufacturing of the integrated circuit. In the third aspect, the physical design specification may include designs for multiple independent integrated circuits, including the integrated circuit, and the memory may include instructions executable by the processor to cause the system to: allocate mask area to the multiple independent integrated circuits based on a production plan; and perform design rule checks on the physical design specification. In the third aspect, the memory may include instructions executable by the processor to cause the system to: manufacture the integrated circuit; install the integrated circuit in a system configured to operate the integrated circuit responsive to commands received via communications with a cloud server; and transmit a login for accessing and controlling the integrated circuit. In the third aspect, the design parameters data structure may include a JSON file and generating the register-transfer level data structure for the integrated circuit may include: parsing the JSON file to determine the values of the design parameters of the integrated circuit design; converting the design parameter values into input parameter values for an register-transfer level generator; and invoking the register-transfer level generator with the input parameters to obtain register-transfer level data included in the register-transfer level data structure. In the third aspect, the register-transfer level data structure may include a memory map, one or more port assignments, and floorplan information. In the third aspect, generating the register-transfer level data structure for the integrated circuit may include: executing Scala code to read the design parameters data structure and dynamically generate a circuit graph. In the third aspect, generating the register-transfer level data structure for the integrated circuit may include: invoking a Diplomacy package in Chisel to determine a bus protocol for the integrated circuit. In the third aspect, generating the software development kit for the integrated circuit may include: generating loaders for a Verilog simulator and a physical field programmable gate array to be flashed. In the third aspect, the memory may include instructions executable by the processor to cause the system to: receive the acceptance criteria with the design parameters data structure. In the third aspect, the memory may include instructions executable by the processor to cause the system to: update the design parameters data structure based on the test results. In the third aspect, the design parameters data structure includes a reference to a template design. In the third aspect, generating the physical design data structure for the integrated circuit may include: invoking source synthesis and place and route tools; invoking logical equivalent checking; and invoking a static timing analysis tool. In the third aspect, the memory may include instructions executable by the processor to cause the system to: generate the design parameters data structure based on input received via a web application that displays an auto-updating block diagram of a template design reflecting changes to values of the design parameters of the integrated circuit. In the third aspect, the memory may include instructions executable by the processor to cause the system to: generate the design parameters data structure based on input received via an application programming interface. In the third aspect, the integrated circuit may be an IP core. In the third aspect, the integrated circuit may be a

system-on-a-chip. The third aspect may include any combination of the features described in this paragraph.

In a fourth aspect, the subject matter described in this specification can be embodied in methods that include receiving a design parameters file, wherein the design parameters file includes values of design parameters of an integrated circuit design; automatically generating a register-transfer level file, a software development kit, and a physical design file for an integrated circuit based on the design parameters file; and automatically invoking tests for the integrated circuit based on the register-transfer level file, the software development kit, and the physical design file to obtain a set of test results. In the fourth aspect, the methods may include automatically generating documentation for the integrated circuit based on the register-transfer level file. In the fourth aspect, generating documentation for the integrated circuit may include: parsing the register-transfer level file for the integrated circuit to identify applicable portions of documentation framework; generating snippets of documentation based on the applicable portions identified; assembling the snippets into a dictionary; instantiating a document from a template; and merging references to the dictionary with the document. In the fourth aspect, the methods may include automatically generating a field programmable gate array emulation file for the integrated circuit based on the register-transfer level file and the software development kit. In the fourth aspect, the methods may include invoking a test using a field programmable gate array, programmed based on the field programmable gate array emulation file, to obtain an emulation result, wherein the field programmable gate array is operating on a cloud server. In the fourth aspect, the methods may include transmitting a physical design specification based on the physical design file to a server to invoke manufacturing of the integrated circuit. In the fourth aspect, the physical design specification may include designs for multiple independent integrated circuits, including the integrated circuit, and the methods may include: allocating mask area to the multiple independent integrated circuits based on a production plan; and performing design rule checks on the physical design specification. In the fourth aspect, the methods may include manufacturing the integrated circuit; installing the integrated circuit in a system configured to operate the integrated circuit responsive to commands received via communications with a cloud server; and transmitting a login for accessing and controlling the integrated circuit. In the fourth aspect, the design parameters file may include a JSON file and generating the register-transfer level file for the integrated circuit may include: parsing the JSON file to determine the values of the design parameters of the integrated circuit design; converting the design parameter values into input parameter values for a register-transfer level generator; and invoking the register-transfer level generator with the input parameters to obtain register-transfer level data included in the register-transfer level file. In the fourth aspect, the register-transfer level file may include a memory map, one or more port assignments, and floorplan information. In the fourth aspect, generating the register-transfer level file for the integrated circuit may include: executing Scala code to read the design parameters file and dynamically generate a circuit graph. In the fourth aspect, the methods may include generating the register-transfer level file for the integrated circuit may include: invoking a Diplomacy package in Chisel to determine a bus protocol for the integrated circuit. In the fourth aspect, generating the software development kit for the integrated circuit may include: generating loaders for a Verilog simulator and a physical

field programmable gate array to be flashed. In the fourth aspect, the methods may include receiving acceptance criteria with the design parameters file. In the fourth aspect, the methods may include updating the design parameters file based on the test results. In the fourth aspect, generating the physical design file for the integrated circuit may include: invoking source synthesis and place and route tools; invoking logical equivalent checking; and invoking a static timing analysis tool. In the fourth aspect, the methods may include: generating the design parameters file based on input received via a web application that displays an auto-updating block diagram of a template design reflecting changes to values of the design parameters of the integrated circuit. In the fourth aspect, the methods may include generating the design parameters file based on input received via an application programming interface. In the fourth aspect, the integrated circuit may be an IP core. In the fourth aspect, the integrated circuit may be a system-on-a-chip. The fourth aspect may include any combination of the features described in this paragraph.

In a fifth aspect, the subject matter described in this specification can be embodied in systems that include a web application server configured to generate a design parameters data structure based on input received, wherein the design parameters data structure includes values of design parameters of an integrated circuit design, configured to display an auto-updating block diagram of a template design reflecting changes to values of the design parameters of the integrated circuit, and configured to issue a command to build the integrated circuit design; and a controller configured to, responsive to the command to build the integrated circuit design, access the design parameters data structure, invoke a register-transfer level service module with the design parameters data structure to obtain a register-transfer level data structure, invoke a software development kit service module with the register-transfer level data structure to obtain a software development kit, invoke a physical design service module with the register-transfer level data structure to obtain a physical design data structure, invoke a verification service module to obtain a test plan, and invoke tests for the integrated circuit based on the test plan, the register-transfer level data structure, the software development kit, and the physical design data structure to obtain a set of test results.

In the fifth aspect, the controller may be configured to: invoke a documentation service module with the register-transfer level data structure to obtain documentation for the integrated circuit based on the register-transfer level data structure. In the fifth aspect, the controller may be configured to: invoke a field programmable gate array service module configured to generate a field programmable gate array emulation data structure for the integrated circuit based on the register-transfer level data structure and the software development kit. In the fifth aspect, the controller may be configured to invoke a test using a field programmable gate array, programmed based on the field programmable gate array emulation data structure, to obtain an emulation result, wherein the field programmable gate array is operating on a cloud server. In the fifth aspect, the controller may include an application programming interface that enables scripting to process multiple design parameters data structures. In the fifth aspect, the controller may be configured to transmit a physical design specification based on the physical design data structure to a server to invoke manufacturing of the integrated circuit. In the fifth aspect, the register-transfer level data structure may include a memory map, one or more port assignments, and floorplan

11

information. In the fifth aspect, the register-transfer level service module may be configured to execute Scala code to read the design parameters data structure and dynamically generate a circuit graph. In the fifth aspect, the register-transfer level service module may be configured to invoke a Diplomacy package in Chisel to determine a bus protocol for the integrated circuit. In the fifth aspect, the software development kit for the integrated circuit comprises loaders for a Verilog simulator and a physical field programmable gate array to be flashed. In the fifth aspect, the controller may be configured to update the design parameters data structure based on the test results. In the fifth aspect, the design parameters data structure may include a reference to a template design. In the fifth aspect, the integrated circuit may be an IP core. In the fifth aspect, the integrated circuit may be a system-on-a-chip. The fifth aspect may include any combination of the features described in this paragraph.

While the disclosure has been described in connection with certain embodiments, it is to be understood that the disclosure is not to be limited to the disclosed embodiments but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims, which scope is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures as is permitted under the law.

FIG. 1 is block diagram of an example of a system **100** for facilitating design of integrated circuits. The system **100** includes an integrated circuit design service infrastructure **110** that processes requests received from a web client **102** and a scripting API client **104** via communications over a network **106**. For example, the integrated circuit design service infrastructure **110** may be implemented as software running on one or more networked computing devices. For example, the integrated circuit design service infrastructure **110** may be implemented on the system **300** of FIG. 3. The integrated circuit design service infrastructure **110** includes a web application server **112**; a scripting API server **114**; and a controller **120** that determines integrated circuit designs using a collection of services (**130**, **140**, **150**, **160**, **170**, and **180**) based design parameter values stored in a design parameters data structure **122**. For example, the system **100** may implement the process **400** of FIG. 4. For example, the system **100** may implement the process **400** of FIG. 4. For example, the system **100** may implement the process **500** of FIG. 5. For example, the network **106** may be a local area network or a wide array network (e.g., the Internet).

The system **100** includes a web client **102** that may be used to interact with and control the integrated circuit design service infrastructure **110**. For example, the web client **102** may include web browser software running a computing device (e.g., desktop computer, a laptop, a tablet, or a smartphone). The web client **102** may display a web interface generated by and received from the web application server **112**. For example, the web interface may include design knobs that enable a user to select design parameter values for an integrated circuit design.

The system **100** includes a scripting API client **104** that may be used to interact with and control the integrated circuit design service infrastructure **110**. For example, the scripting API client **104** may include a script (e.g., a Python script, a Java script, or a Ruby script) running a computing device (e.g., desktop computer, a laptop, a tablet, or a smartphone) that communicates with the scripting API server **114** via network communications (e.g., using a transport control protocol (TCP) session). The scripting API client **104** may generate API calls to the controller **120** and

12

use the API calls to select design parameter values for one or more integrated circuit designs that are encoded in a design parameters data structure **122** (e.g., a design parameters file) and to command the controller **120** to generate and test the one or more integrated circuit designs based on the design parameters data structure **122**. In some implementations, a script of the scripting API client **104** may be used to control iteration over a design space to test a large a large number of candidate permutations of design parameter values.

The integrated circuit design service infrastructure **110** includes a web application server **112** that generates a web interface to facilitate control of the integrated circuit design service infrastructure **110**. The web interface may include configuration knobs (e.g., icons or fields) that can be used to select design parameter values for an integrated circuit design. The web application server **112** may be configured to generate a design parameters data structure **122** (e.g., a design parameter file or a design parameters database) based on input received (e.g., caused by user interaction with configuration knobs at the web client **102**). The design parameters data structure **122** may include values of design parameters of an integrated circuit design. The design parameters data structure **122** may include a reference to a template design (e.g., a template design for an IP core), which may be modified based on the values of the design parameters. For example, the design parameters data structure **122** may include a JavaScript object notation (JSON) file with the values of the design parameters selected using knobs of the web interface. The web application server **112** may be configured to display an auto-updating block diagram of a template design reflecting changes to values of the design parameters of the integrated circuit (e.g., an IP core or a SoC). For example, the web application server **112** may generate the display region **1110** of FIG. 11. For example, the web application server **112** may generate the display region **1210** of FIG. 12. For example, the web application server **112** may generate the display region **1310** of FIG. 13. In some implementations, the web application server **112** is implemented as software (e.g., Python or Django front end tools) running on a same computing device as the controller **120**. In some implementations, the web application server **112** is implemented as software running on a separate computing device from the controller **120**. In some implementations, the web application server **112** communicates with the controller **120** via API calls and may even route the API calls to the controller via the scripting API server **114**.

The web interface generated by the web application server **112** may include knobs for selecting a wide variety of design parameter values. For example, a knob can be used to select a binary design parameter (e.g., including a multiplier block or not including a multiplier block with a check box or radial button icon). For example, a knob can be used to select from a discrete list of options for a design parameter (e.g., selecting a manufacturing process using a drop-down menu). For example, a knob can be used to select a value (quantized) that varies over a range (e.g., a number of interrupts or a clock frequency may be adjusted by entering a value in a text field or by moving a slider icon). The web application server **112** may reflect dependencies between different design parameters by altering or disabling a knob based on a selection made with another knob of the web interface. Thus the selection of a design parameter value may constrain or limit the selection of other design parameters. For example, knobs relating to data cache design parameters may be disabled (e.g., grayed out) when a knob

13

relating to a number of memory ports is used to select zero memory ports for inclusion in the integrated circuit.

The web interface generated by the web application server **112** may include an auto-updating block diagram that reflects current selections of design parameter values as the values are changed using knobs of the web interface. The auto-updating block diagram may provide a visual representation of the status of the design parameters data structure **122** that is being generated.

The web interface generated by the web application server **112** may include power, performance, and/or area estimates for a design based on current values of design parameters selected with knobs of the web interface. In some implementations, the power, performance, and/or area estimates may be updated in real-time responsive to changes made using the knobs of the web interface. For example, the web application server **112** may access a table of samples of the design space that is used as a model for power, performance, and area (PPA), and given a knob setting, these numbers may be calculated (e.g., using interpolation) from the model and instantly displayed. In some implementations, web interface generated by the web application server **112** may include power, performance, and/or area estimates that are determined based on a completely generated design available after a design based on the selected design parameter values has been generated and tested using the integrated circuit design service infrastructure **110**.

The web interface generated by the web application server **112** may include an icon that may be used to issue a command to the controller **120** to build an integrated circuit design based on a set of design parameter values encoded in a design parameters data structure. The web interface generated by the web application server **112** may provide status updates on the integrated circuit design as it is generated, tested, and/or manufactured.

The integrated circuit design service infrastructure **110** includes a scripting API server **114** that is configured to receive and convey API calls to the controller **120**. For example, the scripting API server **114** may facilitate network communications (e.g., using TCP) between the controller **120** and the scripting API client **104**. The scripting API server **114** may be used to generate a design parameters data structure **122** (e.g., a design parameter file or a design parameters database) based on input received via an application programming interface. For example, the API of the controller **120** may be a representational state transfer (REST) API. Using the scripting API may enable users to easily test a wide variety of design parameter value selections to search a design space efficiently. For example, a user can write a script to programmatically test thousands of designs in the cloud with small parameter tweaks. Automated regression testing may be enabled. Users may write customized controllers that call APIs.

The integrated circuit design service infrastructure **110** includes a controller **120** configured to generate an integrated circuit design based on a design parameters data structure **122** and test the design. For example, the controller **120** may be configured to access the design parameters data structure **122**, invoke the register-transfer level service module **130** with the design parameters data structure **122** to obtain the register-transfer level data structure **132**, invoke the software development kit service module **140** with the register-transfer level data structure **132** to obtain the software development kit **142**, invoke the physical design service module **160** with the register-transfer level data structure **132** to obtain the physical design data structure **162**, invoke the verification service module **180** to obtain the test

14

plan **182**, and invoke tests for the integrated circuit based on the test plan **182**, the register-transfer level data structure **132**, the software development kit **142**, and the physical design data structure **162** to obtain a set of test results **190**. The controller **120** may include an application programming interface that enables scripting (e.g., via the scripting API server **114**) to process multiple design parameters data structures. For example, the controller **120** may perform the actions to generate the integrated circuit design responsive to a command to build the integrated circuit design that is issued by the web application server **112** or the scripting API server **114**. For example, the controller **120** may be implemented as software running on the system **300** of FIG. 3.

For example, the controller **120** may be implemented as cloud service. The controller **120** may implement a sequenced build pipeline for an integrated circuit design based on the design parameters in a design parameter data structure (e.g., a design parameter file). For example, the integrated circuit may be an IP core. For example, the integrated circuit may be a system-on-a-chip. The controller **120** may utilize pre-configured semantics for the inputs and services that work off of the outputs of previous stages in a design building pipeline. The controller **120** may take a design parameter data structure (e.g., a JSON file) as input from the web application server **112** or the scripting API server **114** and output a design data structure (e.g., a compressed archive of design files and/or test results for an integrated circuit design) that includes outputs from various services (**130**, **140**, **150**, **160**, **170**, and/or **180**) used in the sequenced design pipeline. For example, the design pipeline implemented by the controller **120** may include four stages. In a first stage, the register-transfer level service module **130** may be invoked to generate a register-transfer level data structure **132** based on the design parameters data structure **122**. In a second stage, multiple design services that depend on the register-transfer level data structure may be invoked in parallel to generate respective design related data structures. For example, the software development kit service module **140**, the documentation service module **150**, the physical design service module **160**, and the field programmable gate array design service may be invoked in parallel or in any sequence to generate a software development kit **142**, documentation **152**, a physical design data structure (e.g., a GDSII file), and a field programmable gate array emulation data structure **172** (e.g., an FPGA emulation file) based on the register-transfer level data structure **132** and the design parameters data structure **122**. In a third stage, the verification service module **180** may be invoked to generate a test plan **182** and the test plan **182** may be executed by invoking tests to obtain test results **190** for the integrated circuit design. For example, the design verification tests may depend on the register-transfer level data structure **132**, the software development kit **142**, physical design data structure **162**, and/or the field programmable gate array emulation data structure **172**. For example, the invoked verification tests may be executed directly by the controller **120**, by the verification service module **180**, and/or by an external service (e.g., a cloud based FPGA or emulation service that is accessed via communications over the network **106**). In a fourth stage, the verified integrated circuit design may be fabricated. For example, fabrication may be initiated by sending (e.g., via communications over the network **106**) a design data structure based on the physical design data structure (e.g., a GDSII file) to a server of an integrated circuit manufacturing facility. In some implementations (not shown in FIG. 1), integrated circuit fabrication equipment

15

used to fabricate the integrated circuit may be included in the integrated circuit design service infrastructure **110**.

The controller **120** may be configured to handle reporting errors and/or feedback to the web application server **112** for relay to the web client **102**. The controller **120** may be configured to handle multiple requests from other tenants/companies/users. The controller **120** may be configured to manage workloads in the cloud. The controller **120** may be configured to inform a user where to get the results of the design pipeline (e.g., fabricated chips and/or design test results). For example, the controller **120** may be configured to orchestrate or manage launching the FPGA in a cloud environment for testing and provide login credentials back to the web application server **112** for relay to the web client **102**.

In some implementations, the controller **120** may return a generated integrated circuit design as a repository (e.g. GitHub repository) with the basic building blocks wired together. A user with access to the repository could now add additional IP cores or customize the source code. For example, a generated design data structure may be transmitted to or stored by the controller **120** to a GitHub repository and access credentials for the GitHub repository may be delivered to the user (e.g., via the web interface).

The integrated circuit design service infrastructure **110** includes a register-transfer level service module **130** configured to generate a register-transfer level data structure **132** for the integrated circuit based on the design parameters data structure **122**. For example, the register-transfer level service module **130** may be implemented as Scala code. For example, the register-transfer level service module **130** may be implemented using Scala code. For example, the register-transfer level service module **130** may be implemented using Chisel (available at <https://chisel.eecs.berkeley.edu/chisel-dac2012.pdf>). For example, the register-transfer level service module **130** may be implemented using FIRRTL (flexible intermediate representation for register-transfer level) (available at <https://aspire.eecs.berkeley.edu/wp/wp-content/uploads/2017/11/Specification-for-the-FIRRTL-Language-Izraelevitz.pdf>). For example, the register-transfer level service module **130** may be implemented using Diplomacy (available at <https://carrv.github.io/2017/papers/cook-diplomacy-carrv2017.pdf>). For example, the register-transfer level service module **130** may enable a well-designed chip to be automatically developed from a high level set of configuration settings using a mix of Diplomacy, Chisel, FIRRTL. The register-transfer level service module **130** may take the design parameters data structure **122** (e.g., a JSON file) as input and output a register-transfer level data structure (e.g., a Verilog file) for the chip and/or selected core IP per the design parameters of the design parameters data structure (e.g., as specified using configuration knobs of the web interface generated by the web application server **112**). The register-transfer level data structure may include updated configuration settings to drive future stages of the design pipeline. For example, the updated configuration settings may include a concrete memory map of the core, an actual port, a clock design, floorplan information, and/or other configuration information determined by the register-transfer level service module **130**). For example, the process **600** of FIG. **6** may be implemented to generate a register-transfer level data structure **132** for the integrated circuit based on the design parameters data structure **122**.

The integrated circuit design service infrastructure **110** includes a software development kit service module **140** configured to generate a software development kit **142** for the integrated circuit based on the register-transfer level data

16

structure **132**. For example, the software development kit service module **140** may access an existing toolchain or software development kit for a template integrated circuit design that is identified by the design parameters data structure **122**. The existing toolchain or software development kit (e.g., a RISC-V toolchain/SDK) may be set up using conventions suitable for configurability. For example, the existing toolchain or software development kit may be organized into submodules corresponding to design parameters of the design parameters data structure **122**. The software development kit service module **140** may enable generalizing the existing toolchain or software development kit to respond to values of design parameters in the design parameters data structure **122**. The software development kit service module **140** may take the register-transfer level data structure **132** as input and generate the software development kit **142** based on the register-transfer level data structure **132** and/or the design parameters data structure **122**. For example, the software development kit **142** may include a compiler, an assembler, header files, libraries, boot loaders, kernel drivers, and/or other tools for a fully functional SDK/computing environment. For example, the software development kit service module **140** may be implemented as a Python script running on the system **300** of FIG. **3**. In some implementations, the software development kit service module **140** is configured to parse the register-transfer level data structure **132**, generate options for the tools and builds, generate header files responsive to a memory map, selects appropriate examples from the existing toolchain or software development kit, generate relevant configuration files for target simulators (e.g., QEMU (Quick Emulator)) so they can run your specific design on another processor (e.g., x86), and generate loaders for Verilog simulators and physical FPGA boards to be flashed. The resulting software development kit **142** may be built and tested in the cloud (e.g., before giving to customer), which may provide high value where we know these things work in this configuration. The resulting software development kit **142** may be registered with the controller **120** for delivery to a user (e.g., via the web interface).

The integrated circuit design service infrastructure **110** includes a documentation service module **150** configured to generate documentation **152** for the integrated circuit based on the register-transfer level data structure **132**. For example, the documentation service module **150** may utilize Prince (available at <https://www.princexml.com/>). For example, the documentation service module **150** may utilize ASCII Doc (available at <http://asciidoc.org/>). For example, the documentation service module **150** may access a pre-loaded modular manual for a template integrated circuit design that is identified by the design parameters data structure **122**. The modular manual may be set up using conventions suitable for configurability. For example, the modular manual may be organized into submodules corresponding to design parameters of the design parameters data structure **122**. In some implementations, the modular manual is stored as multiple components in corresponding directories of an existing SDK for the template. The documentation service module **150** may enable generalizing the pre-loaded modular manual to respond to values of design parameters in the design parameters data structure **122**. For example, documentation **152** for a RISC-V chip without a multiplier may omit documentation about a multiplication instruction, or similarly, documentation **152** for a RISC-V chip with vector extensions may be generated to include suitable documentation for the vector extensions. The documentation service module **150** may take the register-transfer level data

structure **132** as input and generate the documentation **152** (e.g., in an HTML and/or a PDF format) based on the register-transfer level data structure **132** and/or the design parameters data structure **122**. The documentation service module **150** may correctly document the memory map/ports by working with the post-RTL output. For example, the documentation service module **150** may utilize a documentation framework similar to the React framework (e.g., a JS HTML framework). In some implementations, documentation blocks have a respective piece of python code that takes in an RTL output configuration file and breaks it down into the chunks that ASCII Doc requires and invokes content generation. For example, the documentation service module **150** may implement the process **800** of FIG. **8**. In some implementations, the documentation **152** is output in both the HTML format and in the PDF format. For example, the documentation **152** generated may be registered with the controller **120** to enable packaging for a user (e.g., for delivery in an archive or other data structure to the web client **102**).

The integrated circuit design service infrastructure **110** includes a physical design service module **160** configured to generate a physical design data structure **162** for the integrated circuit based on the register-transfer level data structure **132**. For example, the physical design service module **160** may utilize proprietary or open source synthesis and place & route tools (e.g., Synopsys, Cadence, and/or Mentor tools). For example, the physical design service module **160** may utilize Synopsys tools, including Design Compiler, IC Compiler, PrimeTime, Formality, and/or StarExtract. For example, the physical design service module **160** may implement logical equivalent checking. For example, the physical design service module **160** may utilize static timing analysis tools. For example, the physical design service module **160** may implement design rule checking (DRC) and/or layout versus schematic (LVS) checking. For example, the physical design service module **160** may enable quick iteration of a design and provide feedback (e.g., power, performance, and area estimates) to a user in a more digestible format, which may add value. For example, the physical design service module **160** may report back in less-technical terms whether there are any issues, parallelize and balance the workloads, and highlight important components of the output of the tools that are included in the physical design data structure **162**. The physical design service module **160** may take the register-transfer level data structure **132** (e.g., Verilog and/or floorplan guidance) as input and generate the physical design data structure **162** (e.g., including a GDSII file or an OASIS file) based on the register-transfer level data structure **132** and/or the design parameters data structure **122**. For example, the physical design service module **160** may implement the process **700** of FIG. **7**. In some implementations, the physical design service module **160** may manage and orchestrate physical design toolchains in a cloud. For example, the physical design service module **160** may manage license files, manage computing resources (e.g., CPU cycles, memory, and/or disk usage) and balance user willingness to pay versus speed of results, handle database movement from tool to tool, and manage access to third party IP cores (e.g., some users/tenants using the integrated circuit design service infrastructure **110** may lack access rights to some IP cores available for customization to other users/tenants). For example, a user may input service and/or pricing preferences through the web interface generated by the web application server **112**. For example, the physical design service module **160** may use templated designs, which may allow for significant

design reuse and physical design service module **160** may identify those combinations and reduce workload. For example, the physical design service module **160** may provide better or more compact error/issue reporting, by translating tool issues into manageable feedback and providing the actual error/output of tools in a deliverable format to a user (e.g., a user of the web client **102**). In some implementations, the physical design service module **160** may find common pairings (e.g., DDR control and PHY) that are commonly used across multiple designs. Physical design blocks for the identified pairings may be reused across designs to improve efficiency. In some implementations, the physical design service module **160** may be configured to learn from previous physical design attempts, and automatically adjusts certain parameters for the next attempt. For example, while being invoked to produce a chip that meets a certain performance benchmark while staying under a certain area/power consumption constraint that has not yet been met (e.g., not fast enough or too big or power hungry), the physical design service module **160** may propose suggested alternate parameters or just iterate in a direction that seeks towards closer fit to requirements.

The integrated circuit design service infrastructure **110** includes a field programmable gate array service module **170** configured to generate a field programmable gate array emulation data structure **172** for the integrated circuit based on the register-transfer level data structure **132** and the software development kit **142**. For example, the field programmable gate array service module **170** may be configured to utilize a cloud based field programmable gate array (FPGA). For example, the field programmable gate array service module **170** may be configured to utilize a cloud based FPGA synthesis tool. For example, the field programmable gate array service module **170** may be configured to utilize emulation platforms, such as, Palladium (from Cadence), Veloce (from Mentor Graphics), and/or Zebu (from Synopsys). For example, the field programmable gate array service module **170** may enable a user who lacks knowledge of how to build for these complex platforms to generate a working file for FPGA testing (e.g., in the cloud). For example, the field programmable gate array service module **170** may be configured to handle emulating devices hard drives and network devices. For example, the field programmable gate array service module **170** may provide login to a user (e.g., a user of the web client **102**) to enable the user login to a chip and run benchmarks easily. For example, the field programmable gate array service module **170** may take the register-transfer level data structure **132** and the software development kit **142** as input and generate the field programmable gate array emulation data structure **172** (e.g., an emulation file and supporting materials) based on the register-transfer level data structure **132**, the software development kit **142**, and/or the design parameters data structure **122**. Once the design is available in a register-transfer level format (e.g., as Verilog), the field programmable gate array service module **170** may generate files to enable the design to be run either in an FPGA or on an emulation platform. In some implementations, the field programmable gate array service module **170** may provide the illusion of the whole system, including peripherals, operating together (e.g., memory timing needs to be matched). For example, the peripherals emulated may be the actual peripherals a user has selected in the web interface generated by the web application server **112**. For example, if the user has selected a chip to have a 64-bit DDR interface, the FPGA service may build an FPGA model that gives the end-user the illusion that the emulated chip has a 64-bit

interface. For example, if the user has selected that the chip has a display controller, the FPGA service should provide an emulation environment with a display controller. For example, the field programmable gate array service module 170 may implement highly detailed use of existing tools based on the parameterized integrated circuit design. For example, the field programmable gate array service module 170 may be configured to use the FPGA/Emulator toolchain, be configured to setup the emulated devices, be configured to compile the emulated devices, load the emulated devices into requested cloud(s), and provides login and/or start the requested benchmarks and returns results as part of the test results 190. For example, the field programmable gate array service module 170 may register a final FPGA/emulator design and/or credentials (e.g., a login and password) back to the controller 120. In some implementations, the controller 120 is configured to invoke a test using a field programmable gate array, programmed based on the field programmable gate array emulation data structure 172, to obtain an emulation result, wherein the field programmable gate array is operating on a cloud server. For example, the controller may use the credentials to invoke the test on the field programmable gate array operating on a cloud server.

The integrated circuit design service infrastructure 110 includes a verification service module 180 configured to generate a test plan 182 for an integrated circuit based on the design parameters data structure 122 and acceptance criteria. For example, the verification service module 180 may be configured to utilize Verilog simulators (e.g., open source Verilog simulators). For example, the verification service module 180 may be configured to utilize FPGAs. For example, the verification service module 180 may be configured to utilize software simulators, such as Quick Emulator (QEMU), Spike, and/or other software simulators. In some implementations, multiple target test platforms look the same so the verification service module 180 is able to easily move the workloads across different cost options (e.g., using physical FPGAs vs. cheaper using pre-emptible cloud instances). For example, the verification service module 180 may take the register-transfer level data structure 132 (e.g., including Verilog RTL), the software development kit 142, a physical design data structure (e.g., including a GDSII file), a corpus of tests, and corresponding acceptance criteria as input and generates a test plan 182 and/or test results 190 for the integrated circuit design. For example, the inputs to the verification service module 180 may be provided by the controller 120. In some implementations, a user-defined controller or a more parameterized controller, are configured to respond to varying acceptance criteria. Given acceptance criteria and a design configuration, a test plan may be generated automatically. For example, the verification service module 180 may be configured to define environments, filter out tests it cannot run given a corpus of tests and a hardware and software design generated based on the design parameters data structure 122, generate the test plan 182 to include a sequence of selected tests for the integrated circuit design. For example, an environment may define a test platform. There may be additional components in the test bench, outside the device under test, and it may be beneficial to standardize these environments across designs. For example, a way to end a test may be standardized within a test platform. Some test platforms may define a register a CPU can write to that is defined within the test bench, while some test platforms will wiggle a general purpose input/output (GPIO) pin in a certain way. Given a test plan 182, many test platforms may be used for all tests. In some implementations, the verification service module 180 may

execute or otherwise invoke the testing in accordance with the test plan 182 and gather results to be included in the test results 190. For example, the test plan 182 and/or some or all of the test results 190 may be reported back to the controller 120.

FIG. 2 is block diagram of an example of a system 200 for facilitating design and manufacture of integrated circuits. The system 200 includes the web client 102, the scripting API client 104, the network 106, the integrated circuit design service infrastructure 110, an FPGA/emulator server 220, and a manufacturer server 230. For example, a user may utilize the web client 102 or the scripting API client 104 to command the integrated circuit design service infrastructure 110 to automatically generate an integrated circuit design based a set of design parameter values selected by the user for one or more template integrated circuit designs.

For example, the integrated circuit design service infrastructure 110 may invoke (e.g., via network communications over the network 106) testing of the resulting design that is performed by the FPGA/emulation server 220 that is running one or more FPGAs or other types of hardware or software emulators. For example, the integrated circuit design service infrastructure 110 may invoke a test using a field programmable gate array, programmed based on the field programmable gate array emulation data structure 172, to obtain an emulation result. The field programmable gate array may be operating on the FPGA/emulation server 220, which may be a cloud server. Test results may be returned by the FPGA/emulation server 220 to the integrated circuit design service infrastructure 110 and relayed in a useful format to the user (e.g., via the web client 102 or the scripting API client 104).

The integrated circuit design service infrastructure 110 may also facilitate the manufacture of integrated circuits using the integrated circuit design in a manufacturing facility associated with the manufacturer server 230. In some implementations, a physical design specification (e.g., a GDSII file) based on the physical design data structure 162 is transmitted to the manufacturer server 230 to invoke manufacturing of the integrated circuit (e.g., using manufacturing equipment of the associated manufacturer). For example, the manufacturer server 230 may host a foundry tape out website that is configured to receive physical design specifications (e.g., as a GDSII file or an OASIS file) to schedule or otherwise facilitate fabrication of integrated circuits. In some implementations, the integrated circuit design service infrastructure 110 supports multi-tenancy to allow multiple integrated circuit designs (e.g., from one or more users) to share fixed costs of manufacturing (e.g., reticle/mask generation, and/or shuttles wafer tests). For example, the integrated circuit design service infrastructure 110 may use a fixed package (e.g., a quasi-standardized packaging) that is defined to reduce fixed costs and facilitate sharing of reticle/mask, wafer test, and other fixed manufacturing costs. For example, the physical design specification may include one or more physical designs from one or more respective physical design data structures in order to facilitate multi-tenancy manufacturing. For example, the integrated circuit design service infrastructure 110 may implement the process 900 of FIG. 9 to generate a multi-tenant physical design specification.

In response to the transmission of the physical design specification, the manufacturer associated with the manufacturer server may fabricate and test integrated circuits based on the integrated circuit design. For example, the associated manufacturer (e.g., a foundry) may perform optical proximity correction (OPC) and similar post-tapeout/

pre-production processing, fabricate the integrated circuit(s), update the integrated circuit design service infrastructure 110 (e.g., via communications with the controller 120 or the web application server 112) periodically or asynchronously on the status of the manufacturing process, performs appropriate testing (e.g., wafer testing) and send to packaging house for packaging. A packaging house may receive the finished wafers or dice from the manufacturer and test materials, and update the integrated circuit design service infrastructure 110 (e.g., via communications with the controller 120 or the web application server 112) on the status of the packaging and delivery process periodically or asynchronously. In some implementations, status updates may be relayed to the user when the user checks in using the web interface and/or the controller might email the user that updates are available.

In some implementations, the resulting integrated circuits (e.g., physical chips) are delivered (e.g., via mail) to the user. In some implementations, the resulting integrated circuits (e.g., physical chips) are installed in a system controlled by a cloud server making them quickly accessible to be run remotely using network communications to control the operation of the integrated circuits. For example, a login to the cloud server controlling a manufactured integrated circuit may be sent to the integrated circuit design service infrastructure 110 and relayed to a user (e.g., via the web client 102). For example, the process 1000 of FIG. 10 may be implemented by the manufacturer.

FIG. 3 is block diagram of an example of a system 300 for facilitating design of integrated circuits. The system 300 is an example of an internal configuration of a computing device that may be used to implement the integrated circuit design service infrastructure 110 as a whole or one or more components of the integrated circuit design service infrastructure 110 of the system 100 shown in FIG. 1. The system 300 can include components or units, such as a processor 302, a bus 304, a memory 306, peripherals 314, a power source 316, a network communication interface 318, a user interface 320, other suitable components, or a combination thereof.

The processor 302 can be a central processing unit (CPU), such as a microprocessor, and can include single or multiple processors having single or multiple processing cores. Alternatively, the processor 302 can include another type of device, or multiple devices, now existing or hereafter developed, capable of manipulating or processing information. For example, the processor 302 can include multiple processors interconnected in any manner, including hardwired or networked, including wirelessly networked. In some implementations, the operations of the processor 302 can be distributed across multiple physical devices or units that can be coupled directly or across a local area or other suitable type of network. In some implementations, the processor 302 can include a cache, or cache memory, for local storage of operating data or instructions.

The memory 306 can include volatile memory, non-volatile memory, or a combination thereof. For example, the memory 306 can include volatile memory, such as one or more DRAM modules such as DDR SDRAM, and non-volatile memory, such as a disk drive, a solid state drive, flash memory, Phase-Change Memory (PCM), or any form of non-volatile memory capable of persistent electronic information storage, such as in the absence of an active power supply. The memory 306 can include another type of device, or multiple devices, now existing or hereafter developed, capable of storing data or instructions for processing by the processor 302. The processor 302 can access or

manipulate data in the memory 306 via the bus 304. Although shown as a single block in FIG. 3, the memory 306 can be implemented as multiple units. For example, a system 300 can include volatile memory, such as RAM, and persistent memory, such as a hard drive or other storage.

The memory 306 can include executable instructions 308, data, such as application data 310, an operating system 312, or a combination thereof, for immediate access by the processor 302. The executable instructions 308 can include, for example, one or more application programs, which can be loaded or copied, in whole or in part, from non-volatile memory to volatile memory to be executed by the processor 302. The executable instructions 308 can be organized into programmable modules or algorithms, functional programs, codes, code segments, or combinations thereof to perform various functions described herein. For example, the executable instructions 308 can include instructions executable by the processor 302 to cause the system 300 to automatically, in response to a command, generate an integrated circuit design and associated test results based on a design parameters data structure. The application data 310 can include, for example, user files, database catalogs or dictionaries, configuration information or functional programs, such as a web browser, a web server, a database server, or a combination thereof. The operating system 312 can be, for example, Microsoft Windows®, Mac OS X®, or Linux®; an operating system for a small device, such as a smartphone or tablet device; or an operating system for a large device, such as a mainframe computer. The memory 306 can comprise one or more devices and can utilize one or more types of storage, such as solid state or magnetic storage.

The peripherals 314 can be coupled to the processor 302 via the bus 304. The peripherals 314 can be sensors or detectors, or devices containing any number of sensors or detectors, which can monitor the system 300 itself or the environment around the system 300. For example, a system 300 can contain a geospatial location identification unit, such as a global positioning system (GPS) location unit. As another example, a system 300 can contain a temperature sensor for measuring temperatures of components of the system 300, such as the processor 302. Other sensors or detectors can be used with the system 300, as can be contemplated. In some implementations, the power source 316 can be a battery, and the system 300 can operate independently of an external power distribution system. Any of the components of the system 300, such as the peripherals 314 or the power source 316, can communicate with the processor 302 via the bus 304.

The network communication interface 318 can also be coupled to the processor 302 via the bus 304. In some implementations, the network communication interface 318 can comprise one or more transceivers. The network communication interface 318 can, for example, provide a connection or link to a network, such as the network 106, via a network interface, which can be a wired network interface, such as Ethernet, or a wireless network interface. For example, the system 300 can communicate with other devices via the network communication interface 318 and the network interface using one or more network protocols, such as Ethernet, TCP, IP, power line communication (PLC), WiFi, infrared, GPRS, GSM, CDMA, or other suitable protocols.

A user interface 320 can include a display; a positional input device, such as a mouse, touchpad, touchscreen, or the like; a keyboard; or other suitable human or machine interface devices. The user interface 320 can be coupled to the processor 302 via the bus 304. Other interface devices that

permit a user to program or otherwise use the system **300** can be provided in addition to or as an alternative to a display. In some implementations, the user interface **320** can include a display, which can be a liquid crystal display (LCD), a cathode-ray tube (CRT), a light emitting diode (LED) display (e.g., an OLED display), or other suitable display.

In some implementations, a client or server can omit the peripherals **314**. The operations of the processor **302** can be distributed across multiple clients or servers, which can be coupled directly or across a local area or other suitable type of network. The memory **306** can be distributed across multiple clients or servers, such as network-based memory or memory in multiple clients or servers performing the operations of clients or servers. Although depicted here as a single bus, the bus **304** can be composed of multiple buses, which can be connected to one another through various bridges, controllers, or adapters.

FIG. 4 is flow chart of an example of a process **400** for facilitating design of integrated circuits. The process **400** includes accessing **410** a design parameters data structure; generating **420** a register-transfer level data structure for an integrated circuit based on the design parameters data structure; generating **430** a software development kit for the integrated circuit based on the register-transfer level data structure; generating **440** a physical design data structure for the integrated circuit based on the register-transfer level data structure; generating **450** documentation for the integrated circuit based on the register-transfer level data structure; generating **460** a field programmable gate array emulation data structure for the integrated circuit based on the register-transfer level data structure and the software development kit; generating **470** a test plan for an integrated circuit based on the design parameters data structure and acceptance criteria; invoking **480** tests for the integrated circuit based on the test plan, the register-transfer level data structure, the software development kit, and the physical design data structure to obtain a set of test results; and transmitting, storing, or displaying **490** a design data structure based on the register-transfer level data structure, the software development kit, the physical design data structure, and the test results. The process **400** may automatically generate and test an integrated circuit design conforming to design parameter values in a design parameters data structure in response to a single command (e.g., a build command). For example, the process **400** may be implemented by the integrated circuit design service infrastructure **110**. For example, the process **400** may be implemented by the system **100** of FIG. 1. For example, the process **400** may be implemented by the system **300** of FIG. 3.

The process **400** includes accessing **410** a design parameters data structure (e.g., a file, a database, a repository, or a bitstream). The design parameters data structure includes values of design parameters of an integrated circuit design. For example, the integrated circuit design may be of an IP core. For example, the integrated circuit design may be of a system-on-a-chip. For example, the design parameters data structure may include a JSON file. For example the design parameters of the design parameters data structure may include whether privilege modes are supported, whether multiply extension is supported, whether floating point extension is supported, whether error-correcting codes are supported in on-chip memory, the size of an instruction cache, an associativity of the instruction cache, a size of a data subsystem in on-chip memory, whether a port (e.g., a front port, a system port, a peripheral port, or a memory port) are included, a count of memory port channels, a port

communication protocol selection, a bus width, a count of physical memory protection units, whether JTAG debugging is supported, a count of hardware breakpoints, whether instruction tracing is supported, whether debug direct memory access is supported, a count of local interrupts, whether a platform level interrupt controller is supported, a count of interrupt priority levels, a count of global interrupts, whether branch prediction is supported, a count of branch target buffer entries, a count of branch history table entries, and/or a selection of a manufacturing process. For example, the design parameters data structure may be accessed **410** by receiving the design parameters data structure (e.g., via network communications with the web client **102** or the scripting API client **104** using the network communications interface **318**). For example, the design parameters data structure may be accessed **410** by reading the design parameters data structure (e.g., reading from the memory **306** via the bus **304**).

The process **400** includes, responsive to a command identifying the design parameters data structure, generating **420** a register-transfer level data structure for an integrated circuit based on the design parameters data structure. For example, command may be a build command issued by a user through an icon of a web interface of the web application server **112** using the web client **102**. For example, command may be a build command issued by a script running on the scripting API client **104** via the scripting API server **114**. The command may identify the design parameters data structure either explicitly or implicitly. For example, the command may identify the design parameters data structure by being sent with a copy of the design parameters data structure. For example, the command may identify the design parameters data structure by including a pointer or other reference to the design parameters data structure, which has been previously stored. For example, design parameters data structure may include a JSON file listing identifiers of design parameters and corresponding values. In some implementations, the design parameters data structure also includes an indication (e.g., a pointer, a name, or another identifier) that identifies a template integrated circuit design that the design parameters modify. For example, the template integrated circuit design may include modular design data structures that adhere to conventions for facilitating modular design. For example, generating **420** the register-transfer level data structure for the integrated circuit based on the design parameters data structure may include invoking a register-transfer level service (e.g., the register-transfer level service module **130**) with data based on the design parameters data structure. For example, the process **600** of FIG. 6 may be implemented to generate **420** a register-transfer level data structure for an integrated circuit based on the design parameters data structure.

For example, the register-transfer level data structure may include one or more Verilog files. The register-transfer level data structure may include updated configuration settings to drive later stages of an integrated circuit design pipeline. In some implementations, the register-transfer level data structure includes a memory map, one or more port assignments, and floorplan information.

The register-transfer level data structure (e.g., a register-transfer level file) may be automatically generated **420** based on the design parameters data structure using tools, such as Scala, Chisel, Diplomacy, and/or FIRRTL. For example, generating **420** the register-transfer level data structure for the integrated circuit may include executing Scala code to read the design parameters data structure and dynamically generate a circuit graph. In some implementations, gener-

ating **420** the register-transfer level data structure for the integrated circuit includes invoking a Diplomacy package in Chisel to determine a bus protocol for the integrated circuit.

The process **400** includes, responsive to the command identifying the design parameters data structure, generating **430** a software development kit for the integrated circuit based on the register-transfer level data structure. In some implementations, generating **430** the software development kit for the integrated circuit includes generating loaders for a Verilog simulator and a physical field programmable gate array to be flashed. For example, generating **430** the software development kit may include accessing an existing toolchain or software development kit for a template integrated circuit design that is identified by the design parameters data structure. The existing toolchain or software development kit (e.g., a RISC-V toolchain/SDK) may be set up using conventions suitable for configurability. For example, the existing toolchain or software development kit may be organized into submodules corresponding to design parameters of the design parameters data structure. For example, the software development kit may include a compiler, an assembler, header files, libraries, boot loaders, kernel drivers, and/or other tools for a fully functional SDK/computing environment. For example, generating **430** the software development kit may include executing a Python script. In some implementations, generating **430** the software development kit includes parsing the register-transfer level data structure (e.g., a JSON file), generating options for the tools and builds, generating header files responsive to a memory map, selecting appropriate examples from the existing toolchain or software development kit, generating relevant configuration files for target simulators (e.g., QEMU (Quick Emulator)) so they can run the new design on another processor (e.g., x86), and generating loaders for Verilog simulators and physical FPGA boards to be flashed. The resulting software development kit may be built and tested in the cloud (e.g., before giving to customer). For example, generating **430** the software development kit may include invoking a software development kit service (e.g., the software development kit service module **140**) with data based on register-transfer level data structure and/or the design parameters data structure.

The process **400** includes, responsive to the command identifying the design parameters data structure, generating **440** a physical design data structure (e.g., a physical design file) for the integrated circuit based on the register-transfer level data structure. For example, generating **440** a physical design data structure for the integrated circuit may include implementing the process **700** of FIG. 7. For example, generating **440** a physical design data structure for the integrated circuit may include invoking a physical design service (e.g., the physical design service module **160**) with data based on register-transfer level data structure and/or the design parameters data structure. For example, generating **440** a physical design data structure for the integrated circuit may include invoking synthesis and place & route tools (e.g., Synopsys, Cadence, and/or Mentor tools). For example, generating **440** a physical design data structure for the integrated circuit may include performing logical equivalent checking. For example, generating **440** a physical design data structure for the integrated circuit may include invoking static timing analysis tools. For example, generating **440** a physical design data structure for the integrated circuit may include performing design rule checking (DRC) and/or layout versus schematic (LVS) checking. For example, generating **440** a physical design data structure for the integrated circuit may include determining power, per-

formance, and area estimates for the resulting integrated circuit design and providing these estimates as feedback to a user (e.g., a user of the web client **102**). For example, the physical design data structure may include in less-technical terms whether there are any issues with the physical design. For example, the physical design data structure may highlight important components of the output of the synthesis and place & route tools. For example, the physical design data structure may include a GDSII file or an OASIS file. For example, generating **440** a physical design data structure for the integrated circuit may include managing and orchestrating physical design toolchains in a cloud. For example, generating **440** a physical design data structure for the integrated circuit may include handling database movement from tool to tool, and managing access to third party IP cores. For example, generating **440** a physical design data structure for the integrated circuit may include accessing template designs, which may allow for significant design reuse. For example, generating **440** a physical design data structure for the integrated circuit may include identifying those combinations to reduce workload. For example, generating **440** a physical design data structure for the integrated circuit may provide better or more compact error/issue reporting, by translating tool issues into manageable feedback and providing the actual error/output of tools in a deliverable format to a user (e.g., a user of the web client **102**). For example, generating **440** a physical design data structure for the integrated circuit may include using physical design blocks for identified pairings of functional blocks that may be reused across designs to improve efficiency.

The process **400** includes, responsive to the command identifying the design parameters data structure, generating **450** documentation for the integrated circuit based on the register-transfer level data structure. For example, generating **450** documentation for the integrated circuit may include using Prince (available at <https://www.princexml.com/>). For example, generating **450** documentation for the integrated circuit may include using ASCII Doc (available at <http://asciidoc.org/>). For example, generating **450** documentation for the integrated circuit may include accessing a pre-loaded modular manual for a template integrated circuit design that is identified by the design parameters data structure. The modular manual may be set up using conventions suitable for configurability. For example, the modular manual may be organized into submodules corresponding to design parameters of the design parameters data structure. In some implementations, the modular manual is stored as multiple components in corresponding directories of an existing SDK for the template. Generating **450** documentation for the integrated circuit may include generalizing the pre-loaded modular manual to respond to values of design parameters in the design parameters data structure. For example, the generated **450** documentation may be in an HTML format and/or in a PDF format. In order to correctly document the memory map/ports, generating **450** documentation for the integrated circuit may include working with the post-RTL output. For example, generating **450** documentation for the integrated circuit may include utilizing a documentation framework similar to the React framework (e.g., a JS HTML framework). In some implementations, documentation blocks have a respective piece of python code that takes in an RTL output configuration file and breaks it down into the chunks that ASCII Doc requires and invokes content generation. For example, generating **450** documentation for the integrated circuit may include implementing the process **800** of FIG. 8. For example, generating **450** documentation for the integrated circuit may include invoking a documentation

service (e.g., the documentation service module **150**) with data based on register-transfer level data structure and/or the design parameters data structure.

The process **400** includes, responsive to the command identifying the design parameters data structure, generating **460** a field programmable gate array emulation data structure (e.g., a field programmable gate array emulation file) for the integrated circuit based on the register-transfer level data structure and the software development kit. For example, the field programmable gate array emulation data structure for the integrated circuit may be configured to utilize a cloud based field programmable gate array (FPGA). For example, generating **460** a field programmable gate array emulation data structure for the integrated circuit may include invoking a cloud based FPGA synthesis tool. For example, generating **460** a field programmable gate array emulation data structure for the integrated circuit may include invoking emulation platforms, such as, Palladium (from Cadence), Veloce (from Mentor Graphics), and/or Zebu (from Synopsys). For example, the field programmable gate array emulation data structure for the integrated circuit may be configured to handle emulating devices hard drives and network devices. For example, the field programmable gate array emulation data structure may include an emulation file and supporting materials. In some implementations, the field programmable gate array emulation data structure for the integrated circuit may provide for emulation of a whole system, including peripherals, operating together (e.g., memory timing needs to be matched). For example, the peripherals emulated may be the actual peripherals a user has selected in the web interface generated by the web application server **112**. For example, generating **460** a field programmable gate array emulation data structure for the integrated circuit may include highly detailed use of existing tools based on the parameterized integrated circuit design. For example, generating **460** a field programmable gate array emulation data structure for the integrated circuit may include invoking the FPGA/Emulator toolchain, setting up the emulated devices, and compiling the emulated devices. For example, generating **460** a field programmable gate array emulation data structure for the integrated circuit may include invoking a FPGA/emulation service (e.g., the field programmable gate array design service module **170**) with data based on register-transfer level data structure and/or the design parameters data structure.

The process **400** includes, responsive to the command identifying the design parameters data structure, generating **470** a test plan for an integrated circuit based on the design parameters data structure and acceptance criteria. In some implementations, the acceptance criteria are received with the design parameters data structure (e.g., received from the web client **102** or received from the scripting API client **104**). In some implementations, the acceptance criteria are read from memory (e.g., the memory **306**). For example, generating **470** a test plan for an integrated circuit may include invoking Verilog simulators (e.g., open source Verilog simulators). For example, the test plan for an integrated circuit may include utilizing FPGAs. For example, the test plan for an integrated circuit may include utilizing software simulators, such as Quick Emulator (QEMU), Spike, and/or other software simulators. In some implementations, multiple target test platforms look the same so the test plan for an integrated circuit may include moving the workloads across different cost options (e.g., using physical FPGAs vs. cheaper using pre-emptible cloud instances). For example, a test plan for an integrated circuit may be generated **470** based on the register-transfer level data structure (e.g.,

including Verilog RTL), the software development kit, the physical design data structure (e.g., including a GDSII file), a corpus of tests, and corresponding acceptance criteria. In some implementations, generating **470** a test plan for an integrated circuit may include responding to varying acceptance criteria that are user-defined. Given acceptance criteria and a design configuration, a test plan may be generated **470** automatically. For example, generating **470** a test plan for an integrated circuit may include defining environments, filtering out tests that cannot be run given a corpus of tests and a hardware and software design generated based on the design parameters data structure, and generating the test plan to include a sequence of selected tests for the integrated circuit design. For example, an environment may define a test platform. There may be additional components in a test bench, outside the device under test, and it may be beneficial to standardize these environments across designs. For example, a way to end a test may be standardized within a test platform. Some test platforms may define a register a CPU can write to that is defined within the test bench, while some test platforms will wiggle a general purpose input/output (GPIO) pin in a certain way. Given a test plan, many test platforms may be used for all tests.

The process **400** includes, responsive to the command identifying the design parameters data structure, invoking **480** tests for the integrated circuit based on the test plan, the register-transfer level data structure, the software development kit, and the physical design data structure to obtain a set of test results. For example, the invoked **480** verification tests may be executed directly by a controller (e.g., the controller **120**), by a verification service (e.g., the verification service module **180**), and/or by an external service (e.g., a cloud based FPGA or emulation service that is accessed via communications over a network). In some implementations, invoking **480** tests for the integrated circuit may include invoking a test using a field programmable gate array, programmed based on the field programmable gate array emulation data structure, to obtain an emulation result. The field programmable gate array may be operating on a cloud server. For example, invoking **480** tests for the integrated circuit may include using credentials (e.g., a login and/or password) to invoke the test on the field programmable gate array operating on a cloud server. For example, the test results may include summary information for a large number of tests, such as a binary indication of whether all acceptance criteria were met by the generated integrated circuit design, or a list of binary indications of whether individual verification tests were passed for respective verification tests included in the test plan.

The process **400** includes transmitting, storing, or displaying **490** a design data structure based on the register-transfer level data structure, the software development kit, the physical design data structure, and the test results. For example, the design data structure may be a collection of files, an archive, or a repository (e.g., a GitHub repository) that includes data from the register-transfer level data structure, the software development kit, the physical design data structure, and the test results. For example, the design data structure may also include the documentation generated **450** and/or the field programmable gate array emulation data structure generated **460**. For example, the design data structure may be transmitted **490** to an external device (e.g., a personal computing device) for display or storage. For example, the design data structure may be stored **490** in memory (e.g., the memory **306**). For example, design data structure may be displayed **490** in a user interface (e.g., the user interface **320**). For example, the design data structure

29

may be transmitted **490** via a network communications interface (e.g., the network communications interface **318**).

Although the process **400** is shown as a series of operations for clarity, implementations of the process **400** or any other technique, process, or algorithm described in connection with the implementations disclosed herein can be performed in various orders or concurrently. Additionally, operations in accordance with this disclosure can be performed with other operations not presented and described herein. For example, the process **500** of FIG. **5** may be used to iterate the process **400** with varying design parameters to search a design space. Furthermore, one or more aspects of the systems and techniques described herein can be omitted. For example, operation **450** may be omitted from the process **400**.

FIG. **5** is flow chart of an example of an iterative process **500** for facilitating design of integrated circuits. The process **500** includes accessing **510** a design parameters data structure (e.g., as described in relation to operation **410** of FIG. **4**); determining **520** (e.g., using the process **400** of FIG. **4**) a design data structure with corresponding test results for an integrated circuit based on the design parameters data structure; if (at operation **525**) the test results failed (e.g., the test results did not meet a set of acceptance criteria) and/or an iteration count is not exceeded, then updating **530** the design parameters data structure based on the test results and proceed to a next iteration; and if (at operation **525**) the test results passed (e.g., the test results met a set of acceptance criteria) and/or an iteration count is exceeded, then returning **540** the one or more design data structures that were determined **520**. In some implementations, all design data structures determined **520** with their corresponding test results are returned **540** when the process **500** terminates. In some implementations, only a last design data structure determined **520** with its corresponding test results is returned **540** when the process **500** terminates with a passing test result. In some implementations, the acceptance criteria used to determine whether an integrated circuit design has passed may include constraints on power, performance, and/or area for a physical design. For example, while being invoked to produce a chip that meets a certain performance benchmark while staying under a certain area/power consumption constraint that has not yet been met (e.g., not fast enough or too big or power hungry), design parameter values may be updated **530** in a direction that seeks towards closer fit to requirements. For example, the process **500** may be implemented using the scripting API of the controller **120**. For example, the process **500** may be implemented by the integrated circuit design service infrastructure **110**. For example, the process **500** may be implemented by the system **100** of FIG. **1**. For example, the process **500** may be implemented by the system **300** of FIG. **3**.

FIG. **6** is flow chart of an example of a process **600** for generating a register-transfer level data structure for an integrated circuit based on a design parameters data structure. For example, the design parameters data structure may include a JSON file. For example, the design parameters data structure may include design parameter values determined by a user using configuration knobs in a web interface (e.g., design knobs of the configuration pane **1220** of FIG. **12**) and/or values associated with a template integrated circuit design. The process **600** includes parsing **610** the JSON file to determine the values of the design parameters of the integrated circuit design; converting **620** the design parameter values into input parameter values for a register-transfer level generator; and invoking **630** the register-transfer level generator with the input parameters to obtain

30

register-transfer level data included in the register-transfer level data structure. For example, the register-transfer level generator may include tools, such as Scala, Chisel, Diplomacy, and/or FIRRTL. For example, the process **600** may be implemented by the integrated circuit design service infrastructure **110**. For example, the process **600** may be implemented by the system **100** of FIG. **1**. For example, the process **600** may be implemented by the system **300** of FIG. **3**.

The process **600** includes invoking **630** the register-transfer level generator with the input parameters to obtain register-transfer level data included in the register-transfer level data structure. For example, the register-transfer level generator may be a Scala program encoded in Chisel. For example, invoking **630** the register-transfer level generator may include executing Scala code to dynamically generate a circuit graph. For example, invoking **630** the register-transfer level generator may include using Chisel to generate FIRRTL based on the circuit graph. FIRRTL is an intermediate representation for the integrated circuit. For example, invoking **630** the register-transfer level generator may include invoking a FIRRTL compiler to optimize the design. For example, invoking **630** the register-transfer level generator may include invoking a FIRRTL Verilog backend invoked to output Verilog. For example, the register-transfer level data structure may include one or more Verilog files. In some implementations, the register-transfer level data structure includes a memory map, one or more port assignments, clock, floorplan information, and/or other design configuration data. For example, a clock may be specified in the register-transfer level data structure as both a netlist for the clock circuit (e.g., the RTL generator may instantiate the clocking circuits, such as PLLs and clock dividers) and a description of the clocking circuit so that it can be used within the downstream services or tools. For example, input to the RTL generator could be specified at a high level such as “add a 64-bit DDR controller”. The RTL generator may access and utilize default design parameters such as “this DDR controller is a Cadence controller with 8-bit ECC, 32-entry re-order buffer.”

FIG. **7** is flow chart of an example of a process **700** for generating a physical design data structure for an integrated circuit based on a register-transfer level data structure. The process **700** includes invoking **710** source synthesis and place and route tools; invoking **720** logical equivalent checking; invoking **730** a static timing analysis tool; invoking **740** design rule checks; and invoking **750** layout versus schematic checks. For example, example the tool chains invoked may include Synopsys tools, such as Design Compiler, IC Compiler, PrimeTime, Formality, and/or StarExtract. In some implementations, invoking **710** source synthesis and place and route tools includes managing and orchestrating physical design toolchains in a cloud. In some implementations, invoking **710** source synthesis and place and route tools includes executing physical design tool chains that are installed locally on a same computing device. For example, the process **700** may be implemented by the integrated circuit design service infrastructure **110**. For example, the process **700** may be implemented by the system **100** of FIG. **1**. For example, the process **700** may be implemented by the system **300** of FIG. **3**.

FIG. **8** is flow chart of an example of a process **800** for generating documentation for an integrated circuit based on a register-transfer level data structure. The process **800** includes parsing **810** (e.g., using Python code) the register-transfer level data structure for the integrated circuit to identify applicable portions of a documentation framework;

31

generating **820** snippets of documentation based on the applicable portions identified; assembling **830** the snippets into a dictionary; instantiating **840** a document from a template (e.g., a ASCII Doc template); and merging **850** references to the dictionary with the document. For example, the documentation framework may be similar to the React framework. In some implementations, chapters or sections may be added dynamically to the document. For example, chapter and section headings with numbering may be generated dynamically. For example, IP core documentation (e.g., 3rd party IP core documentation) may be being pulled in to documentation for a system-on-a-chip design that includes the IP core. For example, the process **800** may be implemented by the integrated circuit design service infrastructure **110**. For example, the process **800** may be implemented by the system **100** of FIG. 1. For example, the process **800** may be implemented by the system **300** of FIG. 3.

FIG. 9 is flow chart of an example of a process **900** for generating a multi-tenant physical design specification to facilitate manufacturing of integrated circuits. For example, the physical design specification may include designs for multiple independent integrated circuits. The process **900** may include allocating **910** mask area to the multiple independent integrated circuits based on a production plan; performing **920** design rule checks on the physical design specification; and transmitting **930** the physical design specification to a server to invoke manufacturing. For example, the process **900** may be implemented by the integrated circuit design service infrastructure **110**. For example, the process **900** may be implemented by the system **100** of FIG. 1. For example, the process **900** may be implemented by the system **300** of FIG. 3.

The process **900** includes allocating **910** mask area to the multiple independent integrated circuits based on a production plan. For example, the multiple independent integrated circuits may be gathered as finished physical design data structures (e.g., GDSII files or OASIS files). In some implementations, the multiple independent integrated circuits are gathered from multiple users in a multi-tenant environment. A reticle plan may be built given a specification of how many chips are requested for each of the multiple integrated circuits. For example, if there are User A—Chip 1, User B—Chip 2, and User B—Chip 3. And you want 50% Chip 1 and 25% 2 and 25% 3, the mask area may be allocated **910** accordingly.

The process **900** includes performing **920** design rule checks on the physical design specification. The physical design specification for the mask, which includes copies of the multiple independent integrated circuits, may be checked for design rule violations (e.g., to check for spacing violations between copies of the multiple independent integrated circuits). Performing **920** this top level DRC checking may serve as a final check of the deck that will be sent to the foundry for fabrication.

The process **900** includes transmitting **930** the physical design specification (e.g., a GDSII file or an OASIS file) to a server to invoke manufacturing. Transmitting **930** the physical design specification may constitute submission of a tape out form to a foundry (e.g., via a web service/API) to the fab and API. For example, the physical design specification may be transmitted **930** to a server associated with a foundry (e.g., the manufacturer server **230**). The foundry may then manufacture the multiple independent integrated circuits using the physical design specification in response to receiving the physical design specification. For example, the

32

physical design specification may be transmitted **930** via a network communications interface (e.g., the network communications interface **318**).

FIG. 10 is flow chart of an example of a process **1000** for facilitating manufacturing and testing of integrated circuits. In some implementations, manufacturing facilities may be included in an integrated circuit design service infrastructure and used to manufacture integrated circuits (e.g., chips) at the request of a user. For example, although not shown in FIG. 1, the integrated circuit design service infrastructure **110** may include a chip manufacturing service (e.g., an automated fabrication facility). The process **1000** includes manufacturing **1010** the integrated circuit; installing **1020** the integrated circuit in a system configured to operate the integrated circuit responsive to commands received via communications with a cloud server; and transmitting **1030** a login for accessing and controlling the integrated circuit. For example, the login may be transmitted **1030** via a network communications interface (e.g., the network communications interface **318**) from the controller **120** to a user that requested the manufacture if the integrated circuit (e.g., transmitted **1030** via the web application server **112** to the web client **102**). Using the process **1000** may enable a user quickly and conveniently run or test instances of their new integrated circuit from a remote location.

FIG. 11 is a diagram of an example display region **1110** generated for presenting a web interface to facilitate selection of a template design of an integrated circuit. The display region **1010** may display a list of design templates (e.g., for an IP core) that may be selected for inclusion and/or customization in an integrated circuit design. For each available design template, a design specification listing (**1120**, **1122**, and **1124**) is displayed, showing some key features and/or design parameters of the respective design template. Each design specification listing (**1120**, **1122**, and **1124**) has a template name (**1130**, **1132**, and **1134**) at the top that identifies the design template. Each design specification listing (**1120**, **1122**, and **1124**) has a customize design icon (**1140**, **1142**, and **1144**) that enables a user to select the respective template design for customization and design development.

FIG. 12 is a diagram of an example display region **1210** generated for presenting a web interface to facilitate customized design of an integrated circuit. The display region **1210** includes a configuration pane **1220** that includes design knobs that can be used to select values of design parameters for an integrated circuit design, and has a configuration pane header **1222** that shows the name of a currently displayed category of design knobs. The display region **1210** includes a configuration tabs menu **1230** that includes icons that allow a user to select a category of design knobs to be displayed in the configuration pane **1220** and available for adjustment by the user. For example, the categories of design knobs may include modes & ISA, on-chip memory, ports, security, debug, interrupts, and branch prediction. The design knobs may provide a way of displaying the design parameter values in a design parameter data structure visually and summarizing. The design knobs may facilitate easy changes to design parameter values. In some implementations, the design knobs may be updated in real-time to reflect dependencies between different design parameters by disabling or constraining the values of one design parameter based on another.

The display region **1210** includes a design block diagram **1240** that displays summary current values design parameter values that may be selected using the design knobs of the configuration pane **1220**. The design block diagram **1240**

includes a design name **1242** that identifies the current integrated circuit design. For example, the design block diagram **1240** may use color coding to reflect the presence or absence of certain features and text reflecting the values of other design parameter for an integrated circuit design. For example, the design block diagram **1240** may be an auto-updating block diagram that is updated in real-time to reflect changes in the design parameter values as they are made using the design knobs. In some implementations, a design parameters data structure is generated based on input received via a web application that displays an auto-updating block diagram **1240** of a template design reflecting changes to values of the design parameters of the integrated circuit. In some implementations, the design block diagram **1240** may display estimates of power, performance and area for an integrated circuit design based on the currently selected design parameter values. For example, the PPA (power performance area) estimates may be updated instantly in real-time in response to changes made to the design parameter values using the design knobs. This feature may provide direct feedback on how chip will perform as design changes are made.

The display region **1210** includes a build icon **1250** that may be used to issue a command to build and test and integrated circuit design based on the design parameter values selected with the design knobs and/or reflected in the design block diagram. For example, the current design parameter values when the build command is issued may be encoded in design parameters data structure (e.g., a JSON file) that is accessed by the controller **120** to start the The display region **1210** includes a status bar **1260** that indicates a current status of the design (e.g., design, review, or building). For example, the display region **1010** may be generated (e.g., by the web application server **112**) using Python and/or Django front ended tools.

FIG. **13** is a diagram of an example display region **1310** generated for presenting a web interface to facilitate access to a customized design of an integrated circuit. For example, the display region **1310** may display after a build operation is completed by the system, resulting in a design data structure that includes a set of files encoding the generated integrated circuit design and associated test results. The display region **1310** includes an asset listing **1320** with download links. The links of the asset listing **1320** enable the download (e.g., at the web client **102**) of files of the design data structure, such as an RTL source file, a test bench file, a software development kit, an FPGA bitstream, and documentation for the resulting integrated circuit design. The asset listing **1320** also includes a download all assets link **1322** that enables the download of an archive or repository including all the files of the design data structure.

The display region **1310** includes a design block diagram **1330** (e.g., the same as or similar to the design block diagram **1240** of FIG. **12**) that displays easy to read indications of the design parameter values used for the integrated circuit design. The design block diagram **1330** includes a design name **1332** displaying an identifier for the integrated circuit design.

The display region **1310** includes a build status bar **1340** that reflects a date and time when the build of the integrated circuit design was completed. Before the build is completed, the build status bar **1340** may reflect a current status of the ongoing build process running in the integrated circuit design service infrastructure **110**.

What is claimed is:

1. A method comprising:

receiving a design parameters data structure, wherein the design parameters data structure includes values of design parameters of an integrated circuit design;

receiving acceptance criteria with the design parameters data structure;

automatically generating a register-transfer level data structure, a software development kit, and a physical design data structure for an integrated circuit based on the design parameters data structure, wherein the physical design data structure encodes a layout of the integrated circuit;

automatically generating a test plan for an integrated circuit based on the design parameters data structure and the acceptance criteria; and

automatically invoking tests for the integrated circuit based on the test plan, the register-transfer level data structure, the software development kit, and the physical design data structure to obtain a set of test results.

2. The method of claim **1**, comprising:

automatically generating documentation for the integrated circuit based on the register-transfer level data structure.

3. The method of claim **2**, wherein generating documentation for the integrated circuit comprises:

parsing the register-transfer level data structure for the integrated circuit to identify applicable portions of a documentation framework;

generating snippets of documentation based on the applicable portions identified;

assembling the snippets into a dictionary;

instantiating a document from a template; and

merging references to the dictionary with the document.

4. The method of claim **1**, comprising:

automatically generating a field programmable gate array emulation data structure for the integrated circuit based on the register-transfer level data structure and the software development kit.

5. The method of claim **4**, comprising:

invoking a test using a field programmable gate array, programmed based on the field programmable gate array emulation data structure, to obtain an emulation result, wherein the field programmable gate array is operating on a cloud server.

6. The method of claim **1**, comprising:

transmitting a physical design specification based on the physical design data structure to a server to invoke manufacturing of the integrated circuit.

7. The method of claim **6**, wherein the physical design specification includes designs for multiple independent integrated circuits, including the integrated circuit, and comprising:

allocating mask area to the multiple independent integrated circuits based on a production plan; and performing design rule checks on the physical design specification.

8. The method of claim **6**, comprising:

manufacturing the integrated circuit;

installing the integrated circuit in a system configured to operate the integrated circuit responsive to commands received via communications with a cloud server; and transmitting a login for accessing and controlling the integrated circuit.

9. The method of claim **1**, comprising:

updating the design parameters data structure based on the test results.

35

10. The method of claim 1, comprising:
 generating the design parameters data structure based on
 input received via a web application that displays an
 auto-updating block diagram of a template design
 reflecting changes to values of the design parameters of
 the integrated circuit. 5
11. A system comprising:
 a network interface;
 a memory; and
 a processor, wherein the memory includes instructions 10
 executable by the processor to cause the system to:
 receive a design parameters data structure, wherein the
 design parameters data structure includes values of
 design parameters of an integrated circuit design;
 receive acceptance criteria with the design parameters 15
 data structure;
 automatically generate a register-transfer level data struc-
 ture, a software development kit, and a physical design
 data structure for an integrated circuit based on the
 design parameters data structure, wherein the physical
 design data structure encodes a layout of the integrated
 circuit;
 automatically generate a test plan for an integrated circuit
 based on the design parameters data structure and the 25
 acceptance criteria; and
 automatically invoke tests for the integrated circuit based
 on the test plan, the register-transfer level data struc-
 ture, the software development kit, and the physical
 design data structure to obtain a set of test results. 30
12. The system of claim 11, wherein the memory includes
 instructions executable by the processor to cause the system
 to:
 automatically generate a field programmable gate array
 emulation data structure for the integrated circuit based 35
 on the register-transfer level data structure and the
 software development kit; and
 invoke a test using a field programmable gate array,
 programmed based on the field programmable gate
 array emulation data structure, to obtain an emulation
 result, wherein the field programmable gate array is 40
 operating on a cloud server.
13. The system of claim 11, wherein the memory includes
 instructions executable by the processor to cause the system
 to:
 transmit a physical design specification based on the 45
 physical design data structure to a server to invoke
 manufacturing of the integrated circuit.
14. The system of claim 11, wherein the memory includes
 instructions executable by the processor to cause the system 50
 to:
 update the design parameters data structure based on the
 test results.
15. The system of claim 11, wherein the memory includes
 instructions executable by the processor to cause the system 55
 to:
 generate the design parameters data structure based on
 input received via a web application that displays an

36

- auto-updating block diagram of a template design
 reflecting changes to values of the design parameters of
 the integrated circuit.
16. A system comprising:
 a web application server configured to generate a design
 parameters data structure based on input received,
 wherein the design parameters data structure includes
 values of design parameters of an integrated circuit
 design, configured to display an auto-updating block
 diagram of a template design reflecting changes to
 values of the design parameters of the integrated cir-
 cuit, and configured to issue a command to build the
 integrated circuit design, wherein the auto-updating
 block diagram includes color coded design compo-
 nents; and
 a controller configured to, responsive to the command to
 build the integrated circuit design, access the design
 parameters data structure, invoke a register-transfer
 level service module with the design parameters data
 structure to obtain a register-transfer level data struc-
 ture, invoke a verification service module to obtain a
 test plan, and invoke tests for the integrated circuit
 based on the test plan and the register-transfer level
 data structure to obtain a set of test results.
17. The system of claim 16, wherein the controller is
 configured to:
 invoke a documentation service module with the register-
 transfer level data structure to obtain documentation for
 the integrated circuit based on the register-transfer level
 data structure.
18. The system of claim 16, wherein the controller is
 configured to:
 invoke a software development kit service module con-
 figured to generate a software development kit based on
 the register-transfer level data structure;
 invoke a field programmable gate array service module
 configured to generate a field programmable gate array
 emulation data structure for the integrated circuit based
 on the register-transfer level data structure and the
 software development kit; and
 invoke a test using a field programmable gate array,
 programmed based on the field programmable gate
 array emulation data structure, to obtain an emulation
 result, wherein the field programmable gate array is
 operating on a cloud server.
19. The system of claim 16, wherein the controller is
 configured to:
 invoke a physical design service module configured to
 generate a physical design data structure for the inte-
 grated circuit based on the register-transfer level data
 structure; and
 transmit a physical design specification based on the
 physical design data structure to a server to invoke
 manufacturing of the integrated circuit.
20. The system of claim 16, wherein the controller is
 configured to update the design parameters data structure
 based on the test results.

* * * * *