

C. SCOFIELD.
Holder for Matches, Stamps, &c.

No. 198,692.

Patented Dec. 25, 1877.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.





Fig. 6.



Fig. 7.



Witnesses:

Lewis F. Brown,
R. P. Grant

Inventor:

Chas. Scofield

by John A. Guederole,

Attorney.

UNITED STATES PATENT OFFICE.

CHARLES SCOFIELD, OF VINELAND, NEW JERSEY.

IMPROVEMENT IN HOLDERS FOR MATCHES, STAMPS, &c.

Specification forming part of Letters Patent No. **198,692**, dated December 25, 1877; application filed September 20, 1877.

To all whom it may concern:

Be it known that I, CHARLES SCOFIELD, of Vineland, in the county of Cumberland and State of New Jersey, have invented a new and useful Improvement in a Match-Box and Stamp or Ticket Holder, which improvement is fully set forth in the following specification and accompanying drawings, in which—

Figures 1 and 2 are side views of the device embodying my invention. Figs. 3 and 4 are views of opposite faces, the parts being open. Fig. 5 is a view of Fig. 2, the parts being open. Fig. 6 is a central transverse section thereof. Fig. 7 is a central longitudinal section thereof.

Similar letters of reference indicate corresponding parts in the several figures.

This invention relates to an improved match box or safe designed with receptacles for matches, stamps, or railroad-tickets.

The improvement consists, first, in a spring secured within the match-box transversely to the length of the same and of the matches placed therein, the said spring being arranged and adapted to exert a yielding pressure upon the matches stored within the receptacle; second, in an improved match-box and stamp or ticket holder having an arrangement of springs within subdivisions of one compartment for the stamps or tickets, and a centrally-located spring adapted to extend into and operate upon the matches within another compartment upon the reverse side of the case; and, third, in a match-box with a projecting rim and covering or shell, combined and adapted to operate all substantially in the manner as hereinafter more fully set forth and claimed.

Referring to the drawings, A represents a box or safe, which is pivoted to a covering or shell, B, whereby the box and its contents may be inclosed and protected when required, swung out and exposed or made accessible. C represents a spring, which is secured to the box A, and it extends transversely, or in the direction at a right angle, to the length of the matches placed in the box, and said spring is so disposed that it will exert a pressure on the matches resting on the bottom of the box, whereby the matches will not shift or fall from the box; but they may be readily removed when desired or necessary.

In order to allow the greatest freedom of motion of said spring C, and cause it to hold matches in large or small quantities, the spring is bent into the form of a loop, one end of which is secured to the box, and the other is free, and elevated so as to overhang and bear against the matches, as more clearly shown in Fig. 6.

To the bottom or back of the box there are secured transversely-extending springs D, and around the edge of said back there projects a rim, a, which constitutes the sides of a chamber, E, on said bottom, adapted for the reception of stamps or tickets, or both, which are to be held in place by the springs D, the chamber being formed in subdivisions for stamps or tickets of different denominations or characteristics, each subdivision having one or more of the springs D, for holding the stamps or tickets.

It will be seen that the matches and stamps or tickets rest on opposite sides of the bottom of the box, that they are convenient of access, and that they will be held without liability of displacement, whether they face upward or downward.

In order to remove a match or stamp, or ticket, it is simply drawn from its position, the power of the holding-spring being overcome by such act.

It will also be seen that when the box or case is swung into the covering or shell B, the matches and stamps or tickets will be inclosed, so that the device can be conveniently and safely carried in the pocket; and owing to the shell and the projecting rim a of the chamber E, the stamps, &c., in the latter are protected from warmth and moisture of the body, and consequent sticking, curling, &c.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

1. The match-box A, provided with a spring, C, secured transversely to the length of the box, and adapted to exert a spring-pressure upon the matches within the receptacle, substantially in the manner and for the purposes herein shown and set forth.

2. In a combined match-box and stamp-holder, the herein-described arrangement of

springs D D within subdivisions of a compartment upon one side of the box, and the centrally-located spring C, adapted to extend transversely across the match-compartment upon the other side of the case, all substantially as herein shown and described, and for the purposes set forth.

3. The match-box A, with projecting rim a

and covering or shell B, combined and operating substantially as and for the purpose set forth.

CHAS. SCOFIELD.

Witnesses:

IDA A. SCOFIELD,
W. A. HOUSE.