



US010398520B2

(12) **United States Patent**
Larkin et al.

(10) **Patent No.:** **US 10,398,520 B2**

(45) **Date of Patent:** ***Sep. 3, 2019**

(54) **MINIMALLY INVASIVE SURGICAL SYSTEM**

(71) Applicant: **Intuitive Surgical Operations, Inc.**,
Sunnyvale, CA (US)

(72) Inventors: **David Q. Larkin**, Menlo Park, CA
(US); **Thomas G. Cooper**, Menlo Park,
CA (US); **Catherine J. Mohr**,
Mountain View, CA (US); **David J.**
Rosa, San Jose, CA (US)

(73) Assignee: **INTUITIVE SURGICAL**
OPERATIONS, INC., Sunnyvale, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **15/963,825**

(22) Filed: **Apr. 26, 2018**

(65) **Prior Publication Data**

US 2018/0242824 A1 Aug. 30, 2018

Related U.S. Application Data

(63) Continuation of application No. 14/716,695, filed on
May 19, 2015, now Pat. No. 9,980,630, which is a
(Continued)

(51) **Int. Cl.**
A61B 1/00 (2006.01)
A61B 1/04 (2006.01)
(Continued)

(52) **U.S. Cl.**

CPC **A61B 34/30** (2016.02); **A61B 1/002**
(2013.01); **A61B 1/00087** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC A61B 1/00131; A61B 1/00133; A61B
1/00135; A61B 1/00142; A61B 1/00147;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,096,962 A 7/1963 Meijs
3,546,961 A 12/1970 Marton
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1155833 A 7/1997
CN 1486667 A 4/2004
(Continued)

OTHER PUBLICATIONS

Abbott, Daniel J. et al., "Design of an Endoluminal NOTES Robotic
System," Conference on Intelligent Robots and Systems, 2007, pp.
410-416.

(Continued)


Primary Examiner — Ryan N Henderson

(74) *Attorney, Agent, or Firm* — Haynes and Boone, LLP

(57) **ABSTRACT**

The distal end of a surgical instrument is movable in all six
Cartesian degrees of freedom independently of other com-
ponents of a telemanipulated surgical system. The surgical
instrument extends through a guide tube. The distal end is
moved by actuators that are telemanipulatively controlled.

15 Claims, 37 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/762,165, filed on Jun. 13, 2007, now Pat. No. 9,060,678.

- (60) Provisional application No. 60/813,028, filed on Jun. 13, 2006, provisional application No. 60/813,029, filed on Jun. 13, 2006, provisional application No. 60/813,030, filed on Jun. 13, 2006, provisional application No. 60/813,075, filed on Jun. 13, 2006, provisional application No. 60/813,125, filed on Jun. 13, 2006, provisional application No. 60/813,126, filed on Jun. 13, 2006, provisional application No. 60/813,129, filed on Jun. 13, 2006, provisional application No. 60/813,131, filed on Jun. 13, 2006, provisional application No. 60/813,172, filed on Jun. 13, 2006, provisional application No. 60/813,173, filed on Jun. 13, 2006, provisional application No. 60/813,198, filed on Jun. 13, 2006, provisional application No. 60/813,207, filed on Jun. 13, 2006, provisional application No. 60/813,328, filed on Jun. 13, 2006.

(51) **Int. Cl.**

A61B 1/05 (2006.01)
A61B 1/06 (2006.01)
A61B 1/002 (2006.01)
A61B 1/005 (2006.01)
A61B 1/018 (2006.01)
A61B 17/00 (2006.01)
A61B 17/34 (2006.01)
A61B 34/00 (2016.01)
A61B 34/20 (2016.01)
A61B 34/30 (2016.01)
A61B 34/37 (2016.01)
A61B 5/00 (2006.01)
A61B 8/12 (2006.01)
A61B 90/10 (2016.01)
A61B 90/00 (2016.01)

(52) **U.S. Cl.**

CPC *A61B 1/00149* (2013.01); *A61B 1/00154* (2013.01); *A61B 1/00165* (2013.01); *A61B 1/00193* (2013.01); *A61B 1/018* (2013.01); *A61B 1/04* (2013.01); *A61B 1/05* (2013.01); *A61B 1/06* (2013.01); *A61B 5/0086* (2013.01); *A61B 8/12* (2013.01); *A61B 17/00234* (2013.01); *A61B 34/37* (2016.02); *A61B 34/71* (2016.02); *A61B 34/72* (2016.02); *A61B 90/10* (2016.02); *A61B 1/0055* (2013.01); *A61B 90/361* (2016.02); *A61B 2017/0034* (2013.01); *A61B 2017/00314* (2013.01); *A61B 2017/00323* (2013.01); *A61B 2017/3447* (2013.01); *A61B 2034/2061* (2016.02); *A61B 2034/301* (2016.02); *A61B 2034/305* (2016.02); *A61B 2034/306* (2016.02)

(58) **Field of Classification Search**

CPC *A61B 1/00149*; *A61B 1/00154*; *A61B 1/0016*; *A61B 1/005*; *A61B 1/0051*; *A61B 1/0052*; *A61B 1/0053*; *A61B 1/0055*; *A61B 1/0056*; *A61B 1/0057*; *A61B 1/0058*; *A61B 1/008*; *A61B 1/01*; *A61B 1/018*; *A61B 1/313*; *A61B 1/3132*; *A61B 34/00*; *A61B 34/10*; *A61B 34/20*; *A61B 34/25*; *A61B 34/30*; *A61B 34/32*; *A61B 34/35*; *A61B 34/37*; *A61B 34/70-77*; *A61B 2034/101*; *A61B 2034/102*; *A61B*

2034/104; *A61B 2034/105*; *A61B 2034/107*; *A61B 2034/018*; *A61B 2034/2046*; *A61B 2034/2048*; *A61B 2034/2051*; *A61B 2034/2053*; *A61B 2034/2055*; *A61B 2034/2057*; *A61B 2034/2059*; *A61B 2034/2061*; *A61B 2034/2063*; *A61B 2034/2065*; *A61B 2034/2068*; *A61B 2034/207*; *A61B 2034/2072*; *A61B 2034/2074*; *A61B 2034/252*; *A61B 2034/254*; *A61B 2034/256*; *A61B 2034/258*; *A61B 2034/301-306*; *A61B 2034/715*; *A61B 2034/731*; *A61B 2034/732*; *A61B 2034/733*; *A61B 2034/741-744*; *A61B 17/00234*; *A61B 17/00292*; *A61B 17/00296*; *A61B 17/003*

See application file for complete search history.

(56)

References Cited**U.S. PATENT DOCUMENTS**

4,437,114	A	3/1984	Larussa
4,673,988	A	6/1987	Jansson et al.
4,721,097	A	1/1988	D'Amelio
4,792,715	A	12/1988	Barsky et al.
4,809,191	A	2/1989	Domeier et al.
4,949,927	A	8/1990	Madocks et al.
5,114,403	A	5/1992	Clarke et al.
5,174,276	A	12/1992	Crockard
5,251,611	A	10/1993	Zehel et al.
5,297,536	A	3/1994	Wilk
5,307,437	A	4/1994	Facq et al.
5,397,323	A	3/1995	Taylor et al.
5,417,210	A	5/1995	Funda et al.
5,429,604	A	7/1995	Hammersmark et al.
5,487,757	A	1/1996	Truckai et al.
5,617,515	A	4/1997	MacLaren et al.
5,624,380	A	4/1997	Takayama et al.
5,752,112	A	5/1998	Paddock et al.
5,755,713	A	5/1998	Bilof et al.
5,759,151	A	6/1998	Sturges
5,792,135	A	8/1998	Madhani et al.
5,797,900	A	8/1998	Madhani et al.
5,817,084	A	10/1998	Jensen
5,855,569	A	1/1999	Komi
5,868,760	A	2/1999	McGuckin, Jr.
5,876,325	A	3/1999	Mizuno et al.
5,892,860	A	4/1999	Maron et al.
5,899,425	A	5/1999	Corey, Jr. et al.
5,982,791	A	11/1999	Sorin et al.
5,999,662	A	12/1999	Burt et al.
6,030,130	A	2/2000	Paddock et al.
6,063,095	A	5/2000	Wang et al.
6,066,090	A	5/2000	Yoon
6,120,433	A	9/2000	Mizuno et al.
6,132,368	A	10/2000	Cooper
6,171,277	B1	1/2001	Ponzi
6,191,414	B1	2/2001	Ogle et al.
6,246,200	B1	6/2001	Blumenkranz et al.
6,275,628	B1	8/2001	Jones et al.
6,331,181	B1	12/2001	Tierney et al.
6,332,089	B1	12/2001	Acker et al.
6,347,892	B1	2/2002	Paddock et al.
6,352,503	B1	3/2002	Matsui et al.
6,366,722	B1	4/2002	Murphy et al.
6,371,952	B1	4/2002	Madhani et al.
6,389,187	B1	5/2002	Greenaway et al.
6,396,574	B1	5/2002	Lee et al.
6,441,577	B2	8/2002	Blumenkranz et al.
6,451,027	B1	9/2002	Cooper et al.
6,470,205	B2	10/2002	Bosselmann et al.
6,471,710	B1	10/2002	Bucholtz
6,478,028	B1	11/2002	Paolitto et al.
6,487,352	B1	11/2002	Sobiski et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,554,793 B1	4/2003	Pauker et al.	2004/0202400 A1	10/2004	Kochergin et al.
6,569,084 B1	5/2003	Mizuno et al.	2004/0249367 A1	12/2004	Saadat et al.
6,571,639 B1	6/2003	May et al.	2005/0004431 A1	1/2005	Kogasaka et al.
6,572,629 B2	6/2003	Kalloo et al.	2005/0043718 A1	2/2005	Madhani et al.
6,574,355 B2	6/2003	Green	2005/0059960 A1	3/2005	Simaan et al.
6,575,644 B2	6/2003	Paddock et al.	2005/0065397 A1	3/2005	Saadat et al.
6,578,967 B1	6/2003	Paddock et al.	2005/0065398 A1	3/2005	Adams
6,645,196 B1	11/2003	Nixon et al.	2005/0075536 A1	4/2005	Otsuka et al.
6,648,816 B2	11/2003	Irion et al.	2005/0096502 A1	5/2005	Khalili
6,671,055 B1	12/2003	Wavering et al.	2005/0102062 A1	5/2005	Green
6,671,581 B2	12/2003	Niemeyer et al.	2005/0107663 A1	5/2005	Saadat et al.
6,743,239 B1	6/2004	Kuehn et al.	2005/0131343 A1	6/2005	Abrams et al.
6,758,843 B2	7/2004	Jensen	2005/0215983 A1	9/2005	Brock
6,783,491 B2	8/2004	Saadat et al.	2005/0222554 A1	10/2005	Wallace et al.
6,790,173 B2	9/2004	Saadat et al.	2005/0234293 A1	10/2005	Yamamoto et al.
6,817,974 B2	11/2004	Cooper et al.	2005/0251176 A1	11/2005	Swanstrom et al.
6,837,847 B2	1/2005	Ewers et al.	2005/0272977 A1	12/2005	Saadat et al.
6,866,671 B2	3/2005	Tierney et al.	2005/0284221 A1	12/2005	Danisch et al.
6,902,560 B1	6/2005	Morley et al.	2006/0013523 A1	1/2006	Childlers et al.
6,936,042 B2	8/2005	Wallace et al.	2006/0025652 A1	2/2006	Vargas
6,942,613 B2	9/2005	Ewers et al.	2006/0149418 A1	7/2006	Anvari
6,960,162 B2	11/2005	Saadat et al.	2006/0161136 A1	7/2006	Anderson et al.
6,960,163 B2	11/2005	Ewers et al.	2006/0200049 A1	9/2006	Leo et al.
6,984,203 B2	1/2006	Tartaglia et al.	2006/0258938 A1	11/2006	Hoffman et al.
6,991,602 B2	1/2006	Nakazawa et al.	2007/0021738 A1	1/2007	Hasser et al.
6,994,703 B2	2/2006	Wang et al.	2007/0043338 A1	2/2007	Moll et al.
6,997,870 B2	2/2006	Couvillon, Jr.	2007/0055291 A1	3/2007	Birkmeyer et al.
7,041,052 B2	5/2006	Saadat et al.	2007/0065077 A1	3/2007	Childers et al.
7,042,573 B2	5/2006	Froggatt	2007/0089557 A1	4/2007	Solomon et al.
7,090,637 B2	8/2006	Danitz et al.	2007/0135803 A1	6/2007	Belson
7,090,683 B2	8/2006	Brock et al.	2007/0137371 A1	6/2007	Devenzenzo et al.
7,128,708 B2	10/2006	Saadat et al.	2007/0151391 A1	7/2007	Larkin et al.
7,194,118 B1	3/2007	Harris et al.	2007/0156020 A1	7/2007	Foley et al.
7,252,660 B2	8/2007	Kunz	2007/0197896 A1	8/2007	Moll et al.
7,320,700 B2	1/2008	Cooper et al.	2007/0225554 A1	9/2007	Maseda et al.
7,371,028 B2	5/2008	Gordon et al.	2007/0265503 A1	11/2007	Schlesinger et al.
7,594,912 B2	9/2009	Cooper et al.	2007/0283970 A1	12/2007	Mohr et al.
7,725,214 B2	5/2010	Diolaiti	2007/0287884 A1	12/2007	Schena
7,930,065 B2	4/2011	Larkin et al.	2007/0287889 A1	12/2007	Mohr
8,075,498 B2	12/2011	Leo et al.	2007/0287992 A1	12/2007	Diolaiti et al.
8,281,670 B2	10/2012	Larkin et al.	2008/0058861 A1	3/2008	Cooper et al.
8,784,435 B2	7/2014	Cooper et al.	2008/0064921 A1	3/2008	Larkin et al.
9,039,685 B2	5/2015	Larkin et al.	2008/0064927 A1	3/2008	Larkin et al.
9,060,678 B2	6/2015	Larkin et al.	2008/0064931 A1	3/2008	Schena et al.
9,060,793 B2	6/2015	Larkin et al.	2008/0065097 A1	3/2008	Duval et al.
9,066,739 B2	6/2015	Larkin et al.	2008/0065098 A1	3/2008	Larkin et al.
9,084,624 B2	7/2015	Larkin et al.	2008/0065099 A1	3/2008	Cooper et al.
9,101,380 B2	8/2015	Larkin et al.	2008/0065100 A1	3/2008	Larkin
9,125,679 B2	9/2015	Larkin et al.	2008/0065101 A1	3/2008	Larkin
9,241,769 B2	1/2016	Larkin et al.	2008/0065102 A1	3/2008	Cooper
9,526,583 B2	12/2016	Larkin et al.	2008/0065103 A1	3/2008	Cooper et al.
9,757,149 B2	9/2017	Cooper et al.	2008/0065104 A1	3/2008	Larkin et al.
9,883,914 B2	2/2018	Larkin et al.	2008/0065106 A1	3/2008	Larkin
9,962,066 B2	5/2018	Rogers et al.	2008/0065107 A1	3/2008	Larkin et al.
9,980,630 B2	5/2018	Larkin et al.	2008/0065109 A1	3/2008	Larkin
2001/0049509 A1	12/2001	Sekine et al.	2008/0065110 A1	3/2008	Duval et al.
2001/0055462 A1	12/2001	Seibel	2008/0071288 A1	3/2008	Larkin et al.
2002/0007110 A1	1/2002	Irion	2008/0071289 A1	3/2008	Cooper et al.
2002/0055795 A1	5/2002	Niemeyer et al.	2008/0071290 A1	3/2008	Larkin et al.
2002/0087169 A1	7/2002	Brock et al.	2008/0071291 A1	3/2008	Duval et al.
2002/0099293 A1	7/2002	Fontenot et al.	2008/0091170 A1	4/2008	Vargas et al.
2002/0120252 A1	8/2002	Brock et al.	2008/0147089 A1	6/2008	Loh
2002/0143319 A1	10/2002	Brock	2008/0151041 A1	6/2008	Shafer et al.
2002/0173786 A1	11/2002	Kortenbach et al.	2008/0156971 A1	7/2008	Ogisu et al.
2003/0050649 A1	3/2003	Brock et al.	2008/0212082 A1	9/2008	Froggatt et al.
2003/0167061 A1	9/2003	Schlegel et al.	2008/0287963 A1	11/2008	Rogers et al.
2003/0228039 A1	12/2003	Green	2009/0054728 A1	2/2009	Trusty et al.
2003/0236505 A1	12/2003	Bonadio et al.	2009/0192524 A1	7/2009	Itkowitz et al.
2004/0054355 A1	3/2004	Gerbi et al.	2009/0248040 A1	10/2009	Cooper et al.
2004/0083808 A1	5/2004	Rambow et al.	2009/0314131 A1	12/2009	Bailey
2004/0138525 A1	7/2004	Saadat et al.	2009/0322001 A1	12/2009	Luke et al.
2004/0138529 A1	7/2004	Wiltshire et al.	2009/0326322 A1	12/2009	Diolaiti
2004/0153191 A1	8/2004	Grimm et al.	2009/0326552 A1	12/2009	Diolaiti
2004/0186350 A1	9/2004	Brenneman et al.	2009/0326553 A1	12/2009	Mustufa et al.
2004/0193146 A1	9/2004	Lee et al.	2010/0170519 A1	7/2010	Romo et al.
			2010/0274087 A1	10/2010	Diolaiti et al.
			2010/0332033 A1	12/2010	Diolaiti et al.
			2011/0040305 A1	2/2011	Gomez et al.
			2011/0040404 A1	2/2011	Diolaiti et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2011/0082365 A1 4/2011 McGrogan et al.
 2011/0152879 A1 6/2011 Williams
 2011/0184241 A1 7/2011 Zubiate et al.
 2011/0196419 A1 8/2011 Cooper
 2011/0201883 A1 8/2011 Cooper et al.
 2011/0202068 A1 8/2011 Diolaiti et al.
 2011/0277576 A1 11/2011 Cooper
 2011/0277579 A1 11/2011 Anderson et al.
 2011/0277580 A1 11/2011 Cooper et al.
 2011/0277775 A1 11/2011 Holop et al.
 2011/0277776 A1 11/2011 McGrogan et al.
 2011/0282356 A1 11/2011 Solomon et al.
 2011/0282357 A1 11/2011 Rogers et al.
 2011/0282358 A1 11/2011 Gomez et al.
 2011/0282359 A1 11/2011 Duval
 2012/0010628 A1 1/2012 Cooper et al.
 2014/0296872 A1 10/2014 Cooper et al.
 2015/0250546 A1 9/2015 Larkin et al.
 2015/0374453 A1 12/2015 Larkin et al.
 2017/0071628 A1 3/2017 Cooper et al.
 2017/0354318 A1 12/2017 Rogers et al.
 2018/0193100 A1 7/2018 Larkin et al.

FOREIGN PATENT DOCUMENTS

EP 0776738 A2 6/1997
 EP 1334700 A1 8/2003
 JP S57190549 A 11/1982
 JP H06285009 A 10/1994
 JP H07504363 A 5/1995
 JP 2000093522 A 4/2000
 JP 2000166936 A 6/2000
 JP 2001327460 A 11/2001
 JP 2003275223 A 9/2003
 WO WO-9313916 A1 7/1993
 WO WO-9729690 A1 8/1997
 WO WO-0051486 A1 9/2000
 WO WO-2004052171 A2 6/2004
 WO WO-2005087128 A1 9/2005
 WO WO-2005115226 A2 12/2005
 WO WO-2006039092 A2 4/2006
 WO WO-2007120329 A2 10/2007
 WO WO-2007146987 A2 12/2007
 WO WO-2008028149 A2 3/2008
 WO WO-2009002701 A2 12/2008

OTHER PUBLICATIONS

Anisfield, Nancy; "Ascension Technology Puts Spotlight on DC Field Magnetic Motion Tracking," HP Chronicle, Aug. 2000, vol. 17, No. 9, 3 Pages.
 Ascari, Luca et al., "A New Active Microendoscope for Exploring the Sub-Arachnoid Space in the Spinal Cord," Proc. IEEE International Conference on Robotics and Automation, 2003, pp. 2657-2662, vol. 2, IEEE.
 Barnes Industries, Inc., "How a Ball Screw Works," 4 pages, Copyright 2007; Internet: <http://www.barnesballscrew.com/ball.htm>.
 Berthold III, John W., "Historical Review of Microbend Fiber-Optic Sensors," Journal of Lightwave Technology, vol. 13, No. 7, Jul. 1995, pp. 1193-1199.
 Blue Road Research, "Overview of Fiber Optic Sensors," 40 pages, first posted Dec. 8, 2004. Internet: www.bluerr.com/papers/Overview_of_FOS2.pdf.
 Cao, Caroline G.L., "Designing Spatial Orientation in Endoscopic Environments," Proceedings of the Human Factors and Ergonomics Society 45th Annual Meeting, 2001, pp. 1259-1263.
 Cao, Caroline G.L., "Disorientation in Minimal Access Surgery: A Case Study," Proceedings of the IEA 2000/HFES 2000 Congress, pp. 4-169-4-172.
 Childers, Brooks A., et al., "Use of 3000 Bragg grating strain sensors distributed on four eight-meter optical fibers during static

load tests of a composite structure," SPIE 8th International Symposium on Smart Structures and Materials, Mar. 4-8, 2001, Newport Beach, California, 10 Pages.

Choi, Dong-Geol et al., "Design of a Spring Backbone Micro Endoscope," Conference on Intelligent Robots and Systems, 2007, pp. 1815-1821.

Co-pending U.S. Appl. No. 11/762,185, filed Jun. 13, 2007.

Co-pending U.S. Appl. No. 60/813,028, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,029, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,030, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,075, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,125, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,126, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,129, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,131, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,172, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,173, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,198, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,207, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 60/813,328, filed Jun. 13, 2006.

Co-pending U.S. Appl. No. 61/334,978, filed May 14, 2010.

Cowie, Barbara M., et al., "Distributive Tactile Sensing Using Fibre Bragg Grating Sensors for Biomedical Applications," 1st IEEE / RAS-EMBS International Conference on Biomedical Robotics and Biomechanics (BioRob 2006), Feb. 2006, pp. 312-317.

Danisch, Lee et al., "Spatially continuous six degree of freedom position and orientation sensor," Sensor Review, 1999, vol. 19, Issue 2, pp. 106-112.

Dario, Paolo et al., "A Miniature Device for Medical Intracavitary Intervention," Micro Electro Mechanical Systems '91 Proc IEEE 'An Investigation of Micro Structures, Sensors, Actuators, Machines and Robots', 1991, pp. 171-175, IEEE.

Duncan, Roger, "Sensing Shape: Fiber-Bragg-grating sensor arrays monitor shape at a high resolution," 2005, pp. 18-21, SPIE.

Extended European Search Report for Application No. EP20070798487, dated Jan. 30, 2015, 8 pages.

Gagarina, T. et al., "Modeling and experimental analysis of a new bellow type actuators for active catheter end-effector," Proc. 10th IEEE International Workshop on Robot and Human Interactive Communication, 2001, pp. 612-617, IEEE.

Gander, M.J. et al., "Bend measurement using Bragg gratings in multicore fibre," Electronics Letter, Jan. 20, 2000, vol. 36, No. 2, 2 Pages.

Hill, Kenneth O., "Fiber Bragg grating technology fundamentals and overview," IEEE Journal of Lightwave Technology, vol. 15, Issue 8, Aug. 1997, pp. 1263-1276.

Ikuta, Koji et al., "Development of remote microsurgery robot and new surgical procedure for deep and narrow space," Proc. IEEE International Conference on Robotics & Automation, 2003, pp. 1103-1108, vol. 1, IEEE.

Ikuta, Koji et al., "Shape memory alloy servo actuator system with electric resistance feedback and application for active endoscope," Proc. IEEE International Conference on Robotics and Automation, 1988, pp. 427-430, vol. 1, IEEE.

International Search Report for application No. PCT/US07/71085, dated Sep. 17, 2008, 2 pages.

Jin, Long et al., "Two-dimensional bend sensing with a cantilever-mounted FBG [Fiber Bragg Grating]," Meas. Sci. Technol., 2006, pp. 168-172, vol. 17, Institute of Physics Publishing.

Kreger, Stephen et al., "Optical Frequency Domain Reflectometry for High Density Multiplexing of Multi-Axis Fiber Bragg Gratings," 16th International Conference on Optical Fiber Sensors (OFS-16), Oct. 2003, Nara, Japan, pp. 526-529.

Lertpiriyasuwat, Vatchara et al., "Extended Kalman Filtering Applied to a Two-Axis Robotic Arm with Flexible Links," International Journal of Robotics Research, 2000, vol. 19, No. 3, pp. 254-270.

Lunwei Z., et al., "FBG Sensor Devices for Spatial Shape Detection of Intelligent Colonoscope," IEEE International Conference on Robotics and Automation, Apr. 2004, New Orleans, Louisiana, pp. 835-840.

Martinez, A. et al., "Vector Bending Sensors Based on Fibre Bragg Gratings Inscribed by Infrared Femtosecond Laser," Electronics Letters, 2005, pp. 472-474, vol. 41—Issue 8.

(56)

References Cited**OTHER PUBLICATIONS**

Measurand, "ShapeTape Overview," Measurand ShapeTape Advantage, pp. 1-3, first posted Nov. 3, 2004. Internet<www.measurand.com/products/ShapeTape_overview.html>.

Meltz, Gerald, "Overview of Fiber Grating-Based Sensors," Proceedings of SPIE Distributed Multiplexed Fiber Optic Sensors VI, Nov. 27, 1996, Eds. Kersey et al., vol. 2838, pp. 2-22.

Office Action dated Jun. 17, 2014 for Japanese Application No. 20130179563 filed Aug. 30, 2013, 7 pages.

PCT/US07/71085 Written Opinion, dated Sep. 17, 2008, 5 pages.

PCT/US09/46446 International Search Report and Written Opinion of the International Searching Authority, dated Dec. 14, 2009, 21 pages.

PCT/US09/46446 Partial International Search Report and Invitation to Pay Additional Fees, dated Sep. 18, 2009, 9 pages.

PCT/US2011/035113 International Search Report and Written Opinion of the International Searching Authority, dated Aug. 4, 2011, 13 pages.

Stieber, Michael E. et al., "Vision-Based Sensing and Control for Space Robotics Applications," IEEE Transactions on Instrumentation and Measurement, Aug. 1999, vol. 48, No. 4, pp. 807-812.

Sturges, Robert H. et al., "A Flexible, Tendon-Controlled Device for Endoscopy," The International Journal of Robotics Research, 1993, pp. 121-131, vol. 12—Issue 2, SAGE Publications.

Szewczyk, Jerome et al., "An active tubular polyarticulated micro-system for flexible endoscope," Lecture Notes in Control and Information Sciences, vol. 271, Experimental Robotics VII, 2000, pp. 179-188, Springer-Verlag.

Vertut, Jean and Phillipe Coiffet, Robot Technology: Teleoperation and Robotics Evolution and Development, English translation, Prentice-Hall, Inc., Englewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages.

Wang, Yi-Ping et al., "A novel long period fiber grating sensor measuring curvature and determining bend-direction simultaneously," IEEE Sensors Journal, 2005, pp. 839-843, vol. 5—Issue: 5, IEEE.

Webster, Robert J. III et al., "Toward Active Cannulas: Miniature Snake-Like Surgical Robots," 2006, 7 pages.

Wong, Allan C. L. et al., "Multiplexed fibre Fizeau interferometer and fibre Bragg grating sensor system for simultaneous measurement of quasi-static strain and temperature using discrete wavelet transform," Measurement Science and Technology, 2006, pp. 384-392, vol. 17—Issue 2, Institute of Physics Publishing.




FIG. 1
(PRIOR ART)




FIG. 2A




FIG. 2B




FIG. 3






FIG. 4






FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 9A




FIG. 10




FIG.11




FIG.12




FIG. 11A




FIG. 11B




FIG. 12B




FIG. 12A




FIG. 13




FIG. 14




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 16




FIG. 17




FIG. 17A




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 16E




FIG. 16F




FIG. 16G




FIG. 16H




FIG. 16I




FIG. 16J




FIG. 17B




FIG. 18




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E




FIG. 18F




FIG. 18G




FIG. 19A




FIG. 19




FIG. 19K




FIG. 19B




FIG. 19C







FIG. 19D






FIG. 19H




FIG. 19I




FIG. 19J




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 20F




FIG. 21A




FIG. 21B

FIG. 21C




FIG. 22A




FIG. 22B






FIG. 23






FIG. 25A




FIG. 25B




FIG. 26A




FIG. 26B




FIG. 26C




FIG. 26D




FIG. 26E




FIG. 28B




FIG. 28A




FIG. 29A




FIG. 29B




FIG. 29C




FIG. 29D




FIG. 29E




FIG. 29F




FIG. 30




FIG. 30A




FIG. 30B




FIG. 31

MINIMALLY INVASIVE SURGICAL SYSTEM**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 14/716,695 (filed May 19, 2015), which is a continuation of U.S. patent application Ser. No. 11/762,165 (filed Jun. 13, 2007) and which claims the priority benefit of the following U.S. Provisional Patent Applications, all of which are incorporated by reference:

U.S. Patent Application No. 60/813,028 entitled "Single port system 2" filed 13 Jun. 2006 by Cooper et al.;
 U.S. Patent Application No. 60/813,029 entitled "Single port surgical system 1" filed 13 Jun. 2006 by Larkin;
 U.S. Patent Application No. 60/813,030 entitled "Independently actuated optical train" filed 13 Jun. 2006 by Larkin et al.;
 U.S. Patent Application No. 60/813,075 entitled "Modular cannula architecture" filed 13 Jun. 2006 by Larkin et al.;
 U.S. Patent Application No. 60/813,125 entitled "Methods for delivering instruments to a surgical site with minimal disturbance to intermediate structures" filed 13 Jun. 2006 by Larkin et al.;
 U.S. Patent Application No. 60/813,126 entitled "Rigid single port surgical system" filed 13 Jun. 2006 by Cooper;
 U.S. Patent Application No. 60/813,129 entitled "Minimum net force actuation" filed 13 Jun. 2006 by Cooper et al.;
 U.S. Patent Application No. 60/813,131 entitled "Side working tools and camera" filed 13 Jun. 2006 by Duval et al.;
 U.S. Patent Application No. 60/813,172 entitled "Passing cables through joints" filed 13 Jun. 2006 by Cooper;
 U.S. Patent Application No. 60/813,173 entitled "Hollow smoothly bending instrument joints" filed 13 Jun. 2006 by Larkin et al.;
 U.S. Patent Application No. 60/813,198 entitled "Retraction devices and methods" filed 13 Jun. 2006 by Larkin et al.;
 U.S. Patent Application No. 60/813,207 entitled "Sensory architecture for endoluminal robots" filed 13 Jun. 2006 by Diolaiti et al.; and
 U.S. Patent Application No. 60/813,328 entitled "Concept for single port laparoscopic surgery" filed 13 Jun. 2006 by Mohr et al.

In addition, this application is related to the following concurrently filed U.S. Patent Applications, all of which are incorporated by reference:

U.S. patent application Ser. No. 11/762,217 entitled "Retraction of tissue for single port entry, robotically assisted medical procedures" by Mohr;
 U.S. patent application Ser. No. 11/762,222 entitled "Bracing of bundled medical devices for single port entry, robotically assisted medical procedures" by Mohr et al.;
 U.S. patent application Ser. No. 11/762,231 entitled "Extendable suction surface for bracing medical devices during robotically assisted medical procedures" by Schena;
 U.S. patent application Ser. No. 11/762,236 entitled "Control system configured to compensate for non-ideal actuator-to-joint linkage characteristics in a medical robotic system" by Diolaiti et al.;

U.S. patent application Ser. No. 11/762,185 entitled "Surgical instrument actuation system" by Cooper et al.;
 U.S. patent application Ser. No. 11/762,172 entitled "Surgical instrument actuator" by Cooper et al., now abandoned;
 U.S. patent application Ser. No. 11/762,165 entitled "Minimally invasive surgical system" by Larkin et al.;
 U.S. patent application Ser. No. 11/762,161 entitled "Minimally invasive surgical instrument advancement" by Larkin et al., now abandoned;
 U.S. patent application Ser. No. 11/762,158 entitled "Surgical instrument control and actuation" by Cooper et al.;
 U.S. patent application Ser. No. 11/762,154 entitled "Surgical instrument with parallel motion mechanism" by Cooper;
 U.S. patent application Ser. No. 11/762,149 entitled "Minimally invasive surgical apparatus with side exit instruments" by Larkin;
 U.S. patent application Ser. No. 11/762,170 entitled "Minimally invasive surgical apparatus with side exit instruments" by Larkin;
 U.S. patent application Ser. No. 11/762,143 entitled "Minimally invasive surgical instrument system" by Larkin;
 U.S. patent application Ser. No. 11/762,135 entitled "Side looking minimally invasive surgery instrument assembly" by Cooper et al.;
 U.S. patent application Ser. No. 11/762,132 entitled "Side looking minimally invasive surgery instrument assembly" by Cooper et al.;
 U.S. patent application Ser. No. 11/762,127 entitled "Guide tube control of minimally invasive surgical instruments" by Larkin et al.;
 U.S. patent application Ser. No. 11/762,123 entitled "Minimally invasive surgery guide tube" by Larkin et al.;
 U.S. patent application Ser. No. 11/762,120 entitled "Minimally invasive surgery guide tube" by Larkin et al.;
 U.S. patent application Ser. No. 11/762,118 entitled "Minimally invasive surgical retractor system" by Larkin;
 U.S. patent application Ser. No. 11/762,114 entitled "Minimally invasive surgical illumination" by Schena et al.;
 U.S. patent application Ser. No. 11/762,110 entitled "Retrograde instrument" by Duval et al.;
 U.S. patent application Ser. No. 11/762,204 entitled "Retrograde instrument" by Duval et al.;
 U.S. patent application Ser. No. 11/762,202 entitled "Preventing instrument/tissue collisions" by Larkin;
 U.S. patent application Ser. No. 11/762,189 entitled "Minimally invasive surgery instrument assembly with reduced cross section" by Larkin et al.;
 U.S. patent application Ser. No. 11/762,191 entitled "Minimally invasive surgical system" by Larkin et al.;
 U.S. patent application Ser. No. 11/762,196 entitled "Minimally invasive surgical system" by Duval et al.; and
 U.S. patent application Ser. No. 11/762,200 entitled "Minimally invasive surgical system" by Diolaiti, issued as U.S. Pat. No. 7,725,215 on May 25, 2010.

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT

None.

BACKGROUND

1. Field of Invention

Aspects of the invention are associated with systems and procedures used for minimally invasive surgery, and more particularly to telemanipulative systems used for such surgery.

2. Background Art

Minimally invasive surgery is known under various names (e.g., endoscopy, laparoscopy, arthroscopy, endovascular, keyhole, etc.), often specific to the anatomical area in which work is done. Such surgery includes the use of both hand-held and teleoperated/telemanipulated/telepresence (robot assisted/telerobotics) equipment, such as the da Vinci® Surgical System made by Intuitive Surgical, Inc. of Sunnyvale, Calif. Both diagnostic (e.g., biopsy) and therapeutic procedures are done. Instruments may be inserted into a patient percutaneously via surgical incision or via natural orifice. A new, experimental minimally invasive surgery variation is Natural Orifice Transluminal Endoscopic Surgery (NOTES), in which instruments enter via a natural orifice (e.g., mouth, nostril, ear canal, anus, vagina, urethra) and continue to a surgical site via a transluminal incision (e.g., in a gastric or colonic wall) within the body. Although teleoperative surgery using the da Vinci® Surgical System provides great benefits over, for instance, many hand-held procedures, for some patients and for some anatomical areas the da Vinci® Surgical System is unable to effectively access a surgical site. In addition, further reducing the size and number of incisions aids patient recovery and helps reduce patient trauma and discomfort.

The number of degrees of freedom (DOFs) is the number of independent variables that uniquely identify the pose/configuration of a system. Since robotic manipulators are kinematic chains that map the (input) joint space into the (output) Cartesian space, the notion of DOF can be expressed in any of these two spaces. In particular, the set of joint DOFs is the set of joint variables for all the independently controlled joints. Without loss of generality, joints are mechanisms that provide a single translational (prismatic joints) or rotational (revolute joints) DOF. Any mechanism that provides more than one DOF motion is considered, from a kinematic modeling perspective, as two or more separate joints. The set of Cartesian DOFs is usually represented by the three translational (position) variables (e.g., surge, heave, sway) and by the three rotational (orientation) variables (e.g. Euler angles or roll/pitch/yaw angles) that describe the position and orientation of an end effector (or tip) frame with respect to a given reference Cartesian frame.

For example, a planar mechanism with an end effector mounted on two independent and perpendicular rails has the capability of controlling the x/y position within the area spanned by the two rails (prismatic DOFs). If the end effector can be rotated around an axis perpendicular to the plane of the rails, then there are then three input DOFs (the two rail positions and the yaw angle) that correspond to three output DOFs (the x/y position and the orientation angle of the end effector).

Although the number of Cartesian DOFs is at most six, a condition in which all the translational and orientational variables are independently controlled, the number of joint DOFs is generally the result of design choices that involve considerations of the complexity of the mechanism and the task specifications. Accordingly, the number of joint DOFs can be more than, equal to, or less than six. For non-redundant kinematic chains, the number of independently controlled joints is equal to the degree of mobility for the end effector frame. For a certain number of prismatic and revolute joint DOFs, the end effector frame will have an equal number of DOFs (except when in singular configurations) in Cartesian space that will correspond to a combination of translational (x/y/z position) and rotational (roll/pitch/yaw orientation angle) motions.

The distinction between the input and the output DOFs is extremely important in situations with redundant or “defective” kinematic chains (e.g., mechanical manipulators). In particular, “defective” manipulators have fewer than six independently controlled joints and therefore do not have the capability of fully controlling end effector position and orientation. Instead, defective manipulators are limited to controlling only a subset of the position and orientation variables. On the other hand, redundant manipulators have more than six joint DOFs. Thus, a redundant manipulator can use more than one joint configuration to establish a desired 6-DOF end effector pose. In other words, additional degrees of freedom can be used to control not just the end effector position and orientation but also the “shape” of the manipulator itself. In addition to the kinematic degrees of freedom, mechanisms may have other DOFs, such as the pivoting lever movement of gripping jaws or scissors blades.

It is also important to consider reference frames for the space in which DOFs are specified. For example, a single DOF change in joint space (e.g., the joint between two links rotates) may result in a motion that combines changes in the Cartesian translational and orientational variables of the frame attached to the distal tip of one of the links (the frame at the distal tip both rotates and translates through space). Kinematics describes the process of converting from one measurement space to another. For example, using joint space measurements to determine the Cartesian space position and orientation of a reference frame at the tip of a kinematic chain is “forward” kinematics. Using Cartesian space position and orientation for the reference frame at the tip of a kinematic chain to determine the required joint positions is “inverse” kinematics. If there are any revolute joints, kinematics involves non-linear (trigonometric) functions.

SUMMARY

An object of aspects of the invention is to provide multiple telemanipulated surgical instruments, each surgical instrument working independently of the other and each having an end effector with at least six actively controlled degrees of freedom in Cartesian space (i.e., surge, heave, sway, roll, pitch, yaw), via a single entry port in a patient.

A further object of aspects of the invention is to provide multiple telemanipulated surgical instruments, each surgical instrument working independently of the other and each having an end effector with at least six actively controlled degrees of freedom in Cartesian space (i.e., surge, heave, sway, roll, pitch, yaw), via a single entry port in a patient and past intermediate tissue that restricts lateral movement of a rigid instrument body.

In accordance with aspects of the invention, a surgical instrument is inserted through a guide tube. The distal end of the surgical instrument is movable, and actuators can move the distal end in all six Cartesian degrees of freedom. These six degrees of freedom are independent of motions of the guide tube. The actuators are telemanipulatively controlled.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagrammatic view of a minimally invasive surgical instrument and its motion about a pivot point represented by an incision or natural orifice.

FIG. 2A is a diagrammatic view of another minimally invasive surgical instrument and its motion.

FIG. 2B is a diagrammatic view of yet another minimally invasive surgical instrument and its motion.

FIG. 3 is a schematic view of a minimally invasive surgical instrument.

FIG. 4 is a schematic view that illustrates aspects of a minimally invasive surgical instrument assembly.

FIGS. 4A and 4B are diagrammatic perspective views that illustrate aspects of a removable instrument that is held in place within guide tube.

FIG. 5 is a schematic view that illustrates aspects of a second minimally invasive surgical instrument assembly.

FIG. 6 is a schematic view that illustrates aspects of a third minimally invasive surgical instrument assembly.

FIG. 7 is a schematic view that illustrates aspects of a fourth minimally invasive surgical instrument assembly.

FIG. 8 is a schematic view that illustrates aspects of a fifth minimally invasive surgical instrument assembly.

FIG. 9 is a schematic view that illustrates aspects of a sixth minimally invasive surgical instrument assembly.

FIG. 9A is a schematic view that illustrates a detail of an alternate aspect of FIG. 9.

FIG. 10 is a schematic view that illustrates aspects of a seventh minimally invasive surgical assembly.

FIG. 11 is a schematic view that illustrates aspects of an eighth minimally invasive surgical assembly.

FIGS. 11A and 11B are diagrammatic end views of surgical instrument assemblies.

FIG. 12 is a schematic view that illustrates aspects of a ninth minimally invasive surgical instrument assembly.

FIGS. 12A and 12B are diagrammatic views of retroflexive positions.

FIG. 13 is a schematic view that illustrates aspects of a tenth minimally invasive surgical instrument assembly.

FIG. 14 is a schematic view that illustrates aspects of an eleventh minimally invasive surgical instrument assembly.

FIGS. 15A-15D are schematic views that illustrate aspects of inserting a flexible, steerable surgical instrument and surgical instrument assembly.

FIG. 16 is a schematic view that illustrates a twelfth aspect of a minimally invasive surgical instrument assembly.

FIG. 16A is a side elevation view of an embodiment of the distal portion of a minimally invasive surgical instrument that includes a parallel motion mechanism.

FIG. 16B is a perspective view, and FIG. 16C is a cross-sectional view, of an embodiment of joints in a parallel motion mechanism.

FIGS. 16D and 16E are schematic views that illustrate design and operation aspects of a parallel motion mechanism.

FIGS. 16F and 16G are diagrammatic end views of link disks in a parallel motion mechanism.

FIGS. 16H and 16I are diagrammatic perspective views of stiffening brackets in a parallel motion mechanism.

FIG. 16J is a diagrammatic end view of a stiffening bracket.

FIG. 17 is a schematic view that illustrates aspects of a thirteenth minimally invasive surgical instrument assembly.

FIG. 17A is a schematic side view of a detail of FIG. 17.

FIG. 17B is a diagrammatic perspective view of a surgical instrument assembly.

FIG. 18 is a schematic view that illustrates aspects of a fourteenth minimally invasive surgical instrument assembly.

FIG. 18A is a schematic view that illustrates aspects of an imaging system at the distal end of an instrument assembly.

FIG. 18B is a schematic view that shows that illustrates aspects of imaging system movement.

FIG. 18C is a diagrammatic perspective view of a minimally invasive surgical instrument assembly.

FIG. 18D is a diagrammatic perspective view that illustrates how a distal end of a surgical instrument assembly pitches up and down.

FIG. 18E is another diagrammatic perspective view of a minimally invasive surgical instrument assembly.

FIG. 18F is a diagrammatic plan view of a surgical instrument assembly with a movable imaging system at the distal tip of a guide tube, and FIG. 18G is a diagrammatic detail that shows an alternate aspect of the surgical instrument assembly shown in FIG. 18F.

FIG. 19 is a diagrammatic perspective view that illustrates aspects of a fifteenth minimally invasive surgical instrument assembly.

FIG. 19A is another diagrammatic perspective view of the embodiment depicted in FIG. 19.

FIG. 19B is a plan view of a surgical instrument assembly.

FIG. 19C is another plan view of the surgical instrument assembly shown in FIG. 19B.

FIG. 19D is an exploded perspective view that illustrates aspects of a surgical instrument mechanism.

FIG. 19E is a perspective view of cable guide tubes.

FIG. 19F is an end elevation view of cable guide tubes.

FIG. 19G is a perspective view of a cable guide piece.

FIG. 19H is a perspective view that illustrates aspects of a surgical instrument passing through and exiting from a guide tube.

FIG. 19I is a perspective view that illustrates aspects of a surgical instrument's motion after exiting from a guide tube.

FIG. 19J is a perspective view that illustrates aspects of a surgical instrument assembly with two retrograde surgical instruments.

FIG. 19K is a plan view of a surgical instrument assembly.

FIG. 20A is an end elevation view of the distal end face of a guide tube.

FIG. 20B is an end elevation view of the distal end face of guide tube shown in FIG. 20A, with an imaging system and two surgical instruments.

FIG. 20C is an end elevation view that illustrates a guide tube with an instrument channel that includes grooves arranged in a "V" shape.

FIGS. 20D, 20E, and 20F are each end elevation views that illustrate other guide tube channel configurations.

FIG. 21A is a schematic view of a robot-assisted minimally invasive telesurgical system.

FIGS. 21B and 21C are schematic views of a patient side support system in a telesurgical system.

FIG. 22A is a diagrammatic view of a centralized motion control system for a minimally invasive telesurgical system.

FIG. 22B is a diagrammatic view of a distributed motion control system for a minimally invasive telesurgical system.

FIG. 23 is a schematic view of an interface between a surgical instrument assembly and an actuator assembly.

FIG. 24A is a perspective view of the proximal segment of a minimally invasive surgical instrument.

FIG. 24B is a perspective view of a segment of an actuator assembly 2420 that mates with and actuates the instrument shown in FIG. 24A.

FIG. 25A is a diagrammatic perspective view that illustrates mounting minimally invasive surgical instruments and actuator assemblies at the end of a setup arm.

FIG. 25B is another diagrammatic perspective view that illustrates mounting minimally invasive surgical instruments and actuator assemblies at the end of a setup arm.

FIG. 26A is a diagrammatic end view of instrument transmission mechanisms and a guide tube.

FIGS. 26B, 26C, and 26D are diagrammatic end views of transmission mechanisms spaced around a guide tube.

FIG. 26E is a diagrammatic exploded perspective view of an actuator housing and an instrument.

FIG. 27 is a diagrammatic view of transmission mechanisms associated with flexible coaxial guide tubes and instruments.

FIG. 28A is a diagrammatic view of multi-port surgery.

FIG. 28B is another diagrammatic view of multi-port surgery.

FIGS. 29A and 29B are diagrammatic views of minimally invasive surgical instrument assembly position sensing.

FIGS. 29C-29E are diagrammatic plan views that illustrate further aspects of preventing undesired instrument collision with tissue.

FIG. 29F is a diagrammatic view of an image mosaiced output display for a surgeon.

FIG. 30 is a schematic view of a mechanism for automatically exchanging minimally invasive surgical instruments.

FIG. 30A is a schematic view of storing an instrument or other component on a drum.

FIG. 30B is a schematic view of storing automatically replaceable instruments on spools.

FIG. 31 is a diagrammatic perspective view of an illustrative minimally invasive surgical instrument assembly that includes a multi-jointed instrument dedicated to retraction.

DETAILED DESCRIPTION

This description and the accompanying drawings that illustrate aspects and embodiments of the present invention should not be taken as limiting—the claims define the protected invention. Various mechanical, compositional, structural, electrical, and operational changes may be made without departing from the spirit and scope of this description and the claims. In some instances, well-known circuits, structures, and techniques have not been shown in detail in order not to obscure the invention. Like numbers in two or more figures represent the same or similar elements.

Further, this description's terminology is not intended to limit the invention. For example, spatially relative terms—such as “beneath”, “below”, “lower”, “above”, “upper”, “proximal”, “distal”, and the like—may be used to describe one element's or feature's relationship to another element or feature as illustrated in the figures. These spatially relative terms are intended to encompass different positions and orientations of the device in use or operation in addition to the position and orientation shown in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be “above” or “over” the other elements or features. Thus, the exemplary term “below” can encompass both positions and orientations of above and below. The

device may be otherwise oriented (rotated 90 degrees or at other orientations), and the spatially relative descriptors used herein interpreted accordingly. Likewise, descriptions of movement along and around various axes include various special device positions and orientations. In addition, the singular forms “a”, “an”, and “the” are intended to include the plural forms as well, unless the context indicates otherwise. And, the terms “comprises”, “comprising”, “includes”, and the like specify the presence of stated features, steps, operations, elements, and/or components but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups. Components described as coupled may be electrically or mechanically directly coupled, or they may be indirectly coupled via one or more intermediate components.

Telemanipulation and like terms generally refer to an operator manipulating a master device (e.g., an input kinematic chain) in a relatively natural way (e.g., a natural hand or finger movement), whereupon the master device movements are made into commands that are processed and transmitted in real time to a slave device (e.g., an output kinematic chain) that reacts nearly instantaneously to the commands and to environmental forces. Telemanipulation is disclosed in U.S. Pat. No. 6,574,355 (Green), which is incorporated by reference.

To avoid repetition in the figures and the descriptions below of the various aspects and illustrative embodiments, it should be understood that many features are common to many aspects and embodiments. Omission of an aspect from a description or figure does not imply that the aspect is missing from embodiments that incorporate that aspect. Instead, the aspect may have been omitted for clarity and to avoid prolix description.

Accordingly, several general aspects apply to various descriptions below. For example, at least one surgical end effector is shown or described in various figures. An end effector is the part of the minimally invasive surgical instrument or assembly that performs a specific surgical function (e.g., forceps/graspers, needle drivers, scissors, electrocautery hooks, staplers, clip applicators/removers, etc.). Many end effectors have a single DOF (e.g., graspers that open and close). The end effector may be coupled to the surgical instrument body with a mechanism that provides one or more additional DOFs, such as “wrist” type mechanisms. Examples of such mechanisms are shown in U.S. Pat. No. 6,371,952 (Madhani et al.) and in U.S. Pat. No. 6,817,974 (Cooper et al.), both of which are incorporated by reference, and may be known as various Intuitive Surgical, Inc. Endowrist® mechanisms as used on both 8 mm and 5 mm instruments for the da Vinci® Surgical System. Although the surgical instruments described herein generally include end effectors, it should be understood that in some aspects an end effector may be omitted. For example, the distal tip of an instrument body shaft may be used to retract tissue. As another example, suction or irrigation openings may exist at the distal tip of a body shaft or the wrist mechanism. In these aspects, it should be understood that descriptions of positioning and orienting an end effector include positioning and orienting the tip of a surgical instrument that does not have an end effector. For example, a description that addresses the reference frame for a tip of an end effector should also be read to include the reference frame of the tip of a surgical instrument that does not have an end effector.

Throughout this description, it should be understood that a mono- or stereoscopic imaging system/image capture component/camera device may be placed at the distal end of an instrument wherever an end effector is shown or

described (the device may be considered a “camera instrument”), or it may be placed near or at the distal end of any guide tube or other instrument assembly element. Accordingly, the terms “imaging system” and the like as used herein should be broadly construed to include both image capture components and combinations of image capture components with associated circuitry and hardware, within the context of the aspects and embodiments being described. Such endoscopic imaging systems (e.g., optical, infrared, ultrasound, etc.) include systems with distally positioned image sensing chips and associated circuits that relay captured image data via a wired or wireless connection to outside the body. Such endoscopic imaging systems also include systems that relay images for capture outside the body (e.g., by using rod lenses or fiber optics). In some instruments or instrument assemblies a direct view optical system (the endoscopic image is viewed directly at an eyepiece) may be used. An example of a distally positioned semiconductor stereoscopic imaging system is described in U.S. patent application Ser. No. 11/614,661 “Stereoscopic Endoscope” (Shafer et al.), which is incorporated by reference. Well-known endoscopic imaging system components, such as electrical and fiber optic illumination connections, are omitted or symbolically represented for clarity. Illumination for endoscopic imaging is typically represented in the drawings by a single illumination port. It should be understood that these depictions are exemplary. The sizes, positions, and numbers of illumination ports may vary. Illumination ports are typically arranged on multiple sides of the imaging apertures, or completely surrounding the imaging apertures, to minimize deep shadows.

In this description, cannulas are typically used to prevent a surgical instrument or guide tube from rubbing on patient tissue. Cannulas may be used for both incisions and natural orifices. For situations in which an instrument or guide tube does not frequently translate or rotate relative to its insertion (longitudinal) axis, a cannula may not be used. For situations that require insufflation, the cannula may include a seal to prevent excess insufflation gas leakage past the instrument or guide tube. For example, for thoracic surgery that does not require insufflation, the cannula seal may be omitted, and if instruments or guide tube insertion axis movement is minimal, then the cannula itself may be omitted. A rigid guide tube may function as a cannula in some configurations for instruments that are inserted relative to the guide tube. Cannulas and guide tubes may be, e.g., steel or extruded plastic. Plastic, which is less expensive than steel, may be suitable for one-time use.

Various instances and assemblies of flexible surgical instruments and guide tubes are shown and described. Such flexibility, in this description, is achieved in various ways. For example, a segment or an instrument or guide tube may be a continuously curving flexible structure, such as one based on a helical wound coil or on tubes with various segments removed (e.g., kerf-type cuts). Or, the flexible part may be made of a series of short, pivotally connected segments (“vertebrae”) that provide a snake-like approximation of a continuously curving structure. Instrument and guide tube structures may include those in U.S. Patent Application Pub. No. US 2004/0138700 (Cooper et al.), which is incorporated by reference. For clarity, the figures and associated descriptions generally show only two segments of instruments and guide tubes, termed proximal (closer to the transmission mechanism; farther from the surgical site) and distal (farther from the transmission mechanism; closer to the surgical site). It should be understood that the instruments and guide tubes may be divided

into three or more segments, each segment being rigid, passively flexible, or actively flexible. Flexing and bending as described for a distal segment, a proximal segment, or an entire mechanism also apply to intermediate segments that have been omitted for clarity. For instance, an intermediate segment between proximal and distal segments may bend in a simple or compound curve. Flexible segments may be various lengths. Segments with a smaller outside diameter may have a smaller minimum radius of curvature while bending than segments with a larger outside diameter. For cable-controlled systems, unacceptably high cable friction or binding limits minimum radius of curvature and the total bend angle while bending. The guide tube’s (or any joint’s) minimum bend radius is such that it does not kink or otherwise inhibit the smooth motion of the inner surgical instrument’s mechanism. Flexible components may be, for example, up to approximately four feet in length and approximately 0.6 inches in diameter. Other lengths and diameters (e.g., shorter, smaller) and the degree of flexibility for a specific mechanism may be determined by the target anatomy for which the mechanism has been designed.

In some instances only a distal segment of an instrument or guide tube is flexible, and the proximal segment is rigid. In other instances, the entire segment of the instrument or guide tube that is inside the patient is flexible. In still other instances, an extreme distal segment may be rigid, and one or more other proximal segments are flexible. The flexible segments may be passive or they may be actively controllable (“steerable”). Such active control may be done using, for example, sets of opposing cables (e.g., one set controlling “pitch” and an orthogonal set controlling “yaw”; three cables can be used to perform similar action). Other control elements such as small electric or magnetic actuators, shape memory alloys, electroactive polymers (“artificial muscle”), pneumatic or hydraulic bellows or pistons, and the like may be used. In instances in which a segment of an instrument or guide tube is fully or partially inside another guide tube, various combinations of passive and active flexibility may exist. For instance, an actively flexible instrument inside a passively flexible guide tube may exert sufficient lateral force to flex the surrounding guide tube. Similarly, an actively flexible guide tube may flex a passively flexible instrument inside it. Actively flexible segments of guide tubes and instruments may work in concert. For both flexible and rigid instruments and guide tubes, control cables placed farther from the center longitudinal axis may provide a mechanical advantage over cables placed nearer to the center longitudinal axis, depending on compliance considerations in the various designs.

The flexible segment’s compliance (stiffness) may vary from being almost completely flaccid (small internal frictions exist) to being substantially rigid. In some aspects, the compliance is controllable. For example, a segment or all of a flexible segment of an instrument or guide tube can be made substantially (i.e., effectively but not infinitely) rigid (the segment is “rigidizable” or “lockable”). The lockable segment may be locked in a straight, simple curve or in a compound curve shape. Locking may be accomplished by applying tension to one or more cables that run longitudinally along the instrument or guide tube that is sufficient to cause friction to prevent adjacent vertebrae from moving. The cable or cables may run through a large, central hole in each vertebra or may run through smaller holes near the vertebra’s outer circumference. Alternatively, the drive element of one or more motors that move one or more control cables may be soft-locked in position (e.g., by servocontrol) to hold the cables in position and thereby prevent instrument

11

or guide tube movement, thus locking the vertebrae in place. Keeping a motor drive element in place may be done to effectively keep other movable instrument and guide tube components in place as well. It should be understood that the stiffness under servocontrol, although effective, is generally less than the stiffness that may be obtained with braking placed directly on joints, such as the braking used to keep passive setup joints in place. Cable stiffness generally dominates because it is generally less than servosystem or braked joint stiffness.

In some situations, the compliance of the flexible segment may be continuously varied between flaccid and rigid states. For example, locking cable tension can be increased to increase stiffness but without locking the flexible segment in a rigid state. Such intermediate compliance may allow for telesurgical operation while reducing tissue trauma that may occur due to movements caused by reactive forces from the surgical site. Suitable bend sensors incorporated into the flexible segment allow the telesurgical system to determine instrument and/or guide tube position as it bends. U.S. Patent Application Pub. No. US 2006/0013523 (Childers et al.), which is incorporated by reference, discloses a fiber optic position shape sensing device and method. U.S. patent application Ser. No. 11/491,384 (Larkin et al.), which is incorporated by reference, discloses fiber optic bend sensors (e.g., fiber Bragg gratings) used in the control of such segments and flexible devices.

A surgeon's inputs to control aspects of the minimally invasive surgical instrument assemblies, instruments, and end effectors as described herein are generally done using an intuitive, camera referenced control interface. For example, the da Vinci® Surgical System includes a Surgeon's console with such a control interface, which may be modified to control aspects described herein. The surgeon manipulates one or more master manual input mechanisms having, e.g., 6 DOFs to control the slave instrument assembly and instrument. The input mechanisms include a finger-operated grasper to control one or more end effector DOFs (e.g., closing grasping jaws). Intuitive control is provided by orienting the relative positions of the end effectors and the endoscopic imaging system with the positions of the surgeon's input mechanisms and image output display. This orientation allows the surgeon to manipulate the input mechanisms and end effector controls as if viewing the surgical work site in substantially true presence. This teleoperation true presence means that the surgeon views an image from a perspective that appears to be that of an operator directly viewing and working at the surgical site. U.S. Pat. No. 6,671,581 (Niemeyer et al.), which is incorporated by reference, contains further information on camera referenced control in a minimally invasive surgical apparatus.

FIG. 1 is a diagrammatic view of a minimally invasive surgical instrument 1 and its motion. As shown in FIG. 1, surgical instrument 1 is a straight, rigid instrument that is inserted via a small incision 2 into a body cavity (e.g., the abdominal cavity) or lumen 3. Incision 2 is made in a relatively thin body wall tissue structure 4, such as the abdominal wall. A surgeon moves instrument 1 either by hand (e.g., by operating a conventional laparoscopic instrument) or by robotic teleoperation (e.g., using Intuitive Surgical, Inc.'s da Vinci® Surgical System). Since instrument 1 is straight, its movement is partially constrained by incision 2. Instrument 1 may be translated in the direction of its longitudinal axis (inserted or withdrawn) and may be rotated around its longitudinal axis. Instrument 1 also pivots at a center point 5, which is approximately at incision 2, to

12

sweep an end effector 7 through a volume 6. An optional wrist mechanism (not shown) at the distal end of instrument 1 may be used to control end effector 7's orientation. In some situations, however, an intermediate tissue structure (e.g., an organ or vessel, a thick tissue wall 4, a curving body lumen wall, etc.) prevents instrument 1 from pivoting around its center point 5 at incision 2 in some or all directions, which prevents a surgeon from reaching a desired surgical site.

If a minimally invasive surgical instrument is designed to bend between the position at which it enters the patient and the surgical site, then the intermediate tissue structure does not constrain positioning of the instrument's end effector. Such bending may be done in two ways. First, two or more long, rigid body segments are each coupled together by a joint. Second, a flexible mechanism as described above is used. The position of the rigid body segment(s) and the flexible mechanism are actively controlled to position and orient the end effector at the instrument's distal end.

FIG. 2A is a diagrammatic view of another minimally invasive surgical instrument 10 and its motion in accordance with aspects of the invention. As shown in FIG. 2A, instrument 10 includes an illustrative proximal instrument body segment 10a and an illustrative distal instrument body segment 10b. In some aspects, more than two body segments may be used. As depicted, both proximal and distal body segments 10a, 10b are straight and rigid. Alternatively, one or both body segments 10a, 10b could be curved for a particular path or task. The two body segments 10a, 10b are coupled at a joint 11 that allows distal body segment 10b to move. In some aspects joint 11 allows segment 10b to move with a single DOF with reference to segment 10a, and in other aspects joint 11 allows segment 10b to move with two DOFs with reference to segment 10a segment. Instrument 10 can be translated along its longitudinal (insertion) axis. In some aspects, proximal segment 10a can be rolled around its longitudinal axis. Accordingly, end effector 7 positioned at the distal end of distal body segment 10b can be positioned within a volume 12. In some aspects joint 11 provides a single DOF, and so end effector 7 sweeps along a planar curve that rotates as proximal segment 10a rotates around its longitudinal axis. In some aspects joint 11 provides two DOFs, and so end effector 7 sweeps along a curved surface. The height of volume 12 depends on the amount of instrument 10's insertion. Volume 12 is shown as an illustrative cylinder with concave/convex ends. Other volume shapes are possible, depending on the segments and joint motions at instrument 10's distal end. For example, in some aspects distal segment 10b may be displaced by an angle θ from segment 10a's longitudinal axis that is larger than 90 degrees (this bending back on itself is termed "retroflexive"). An optional wrist mechanism (not shown) may be used to change end effector 7's orientation.

Unlike instrument 1 shown in FIG. 1, instrument 10 is not constrained by a pivot point at a body wall because joint 11 is located deep within the patient. Therefore, instrument 10 can be inserted into a patient past intermediate tissue structures 13 that would otherwise constrain instrument 1's motion (e.g., the esophagus, if gastric surgery is to be performed) or that cannot be disturbed (e.g., brain tissues if neurosurgery is to be performed). Accordingly, aspects of surgical instrument 10 allow a surgeon to reach tissue that cannot be reached or operated upon by using instrument 1. Removing the constraint that the surgical instrument segments be straight and rigid allows even more surgical access to tissue structures.

13

Instead of using only rigid instrument body segments, one or more flexible segments may be used. FIG. 2B is a diagrammatic view of another minimally invasive surgical instrument 15 and its motion in accordance with aspects of the invention. As shown in FIG. 2B, surgical instrument 15 has a proximal instrument body segment 15a and a distal instrument body segment 15b. Instead of being straight and rigid, distal body segment 15b is flexible as described above. In some aspects flexible distal segment 15b is coupled to straight (or, alternatively, curved), rigid proximal segment 15a at an intermediate position 15c. In other aspects, both proximal instrument body segment 15a and distal instrument body segment 15b are flexible, and intermediate instrument body position 15c is illustrative of the position at which the two segments are jointed. Instrument body segment 15b is shown with an illustrative simple curve. In other aspects as discussed below body segment 15b may be a compound curve in either two or three dimensions.

During surgery, instrument 15 positions end effector 7 at various positions in illustrative volume 16. Instrument body segment 15a remains constrained by intermediate tissue structures 13 and instrument body segment 15b flexes. Distal segment 15b's length and bend radius determines if instrument 15 can operate retroflexively. It can be seen that compound bending of instrument body segment 15b will allow a surgeon to maneuver around another intermediate tissue structure 13a within volume 16. (A similar action may be performed if instrument 10 (FIG. 2A) has two or more distal segments.) An optional wrist mechanism (not shown) is used to control end effector 7's orientation. In addition, in some aspects if flexible segment 15b is designed to transmit roll, then end effector 7 can be rolled by rolling instrument 15 (either with or without a wrist mechanism).

The surgical instruments 10 and 15 illustrated in FIGS. 2A and 2B are not limited to single instruments. The architectures illustrated by instruments 10 and 15 may be applied to assemblies that combine one or more of various guide tubes, surgical instruments, and guide probes such as those described below. And, one or more imaging systems (endoscopes) may be added to such instruments and instrument assemblies. The aspects described below in association with the figures are illustrative of aspects generally described in FIGS. 2A and 2B. Therefore, aspects of the invention provide multiple telemanipulated surgical instruments, each surgical instrument working independently of the other and each having an end effector with at least six actively controlled DOFs in Cartesian space (i.e., surge, heave, sway, roll, pitch, yaw), via a single entry port in a patient. Further, aspects of the invention provide multiple telemanipulated surgical instruments, each surgical instrument working independently of the other and each having an end effector with at least six actively controlled DOFs in Cartesian space (i.e., surge, heave, sway, roll, pitch, yaw), via a single entry port in a patient and past intermediate tissue that restricts lateral movement of a rigid instrument body. The end effectors' six DOFs in Cartesian space are in addition to DOFs provided by, e.g., moving a guide tube through which the instruments extend to reach a surgical site.

Surgical Instrument Assemblies

FIG. 3 is a schematic view of a minimally invasive surgical instrument 300. Surgical instrument 300 is typically inserted into a patient's body via a cannula 302 or via a natural orifice or incision. An end effector 304 is mounted at the end of instrument 300. In some instances instrument 300's body is passively flexible along its entire length in a manner similar to existing flexible minimally invasive sur-

14

gical instruments. For example, a cable axially runs through a helical wound wire coil and outer sheath that protects the cable, and the cable translates within the coil to operate the end effector (e.g., a "Bowden" cable). As another example, a series of small, annular vertebra segments may be used to make instrument 300 flexible. In other instances, instrument 300's body may be separated into a proximal segment 306 and a distal segment 308. Each instrument body segment 306, 308 may be rigid, passively flexible, or actively flexible. Flexible segments may be made rigid ("rigidizable" or "lockable") in various straight or curved positions. As shown in FIG. 3, for example, proximal segment 306 may be inherently or lockably rigid, and distal segment 308 may be passively or actively flexible. In other instances, both proximal and distal segments 306, 308 (essentially the entire segment of instrument 302 that is inside the patient's body) may be passively or actively flexible and rigidizable in various combinations.

The surgical instrument 300 shown in FIG. 3 provides various degrees of freedom for end effector 304. To control end effector 304's position, for example, a combination of instrument 300 insertion and distal segment 308 bending is specified. To control end effector 304's orientation, a combination of instrument 300 roll and distal segment 308 bending is specified. Accordingly, if distal segment 308 can only be placed in a simple curve (as illustrated by alternate position 310), then 4 DOFs are available. If end effector 304 position is specified, then end effector 304 pitch and yaw is a function of the position. If end effector 304 orientation is specified, then the heave and sway position is a function of the orientation. Therefore, a distal wrist mechanism is added to control end effector 304's orientation so that both position and orientation may be specified. If distal segment 308 can be placed in a compound curve (as illustrated by alternate position 312), then 6 DOFs are available, and end effector 304's position and orientation may be specified. Even though end effector 304's position and orientation may be independently specified in such a 6 DOF instrument, a distal wrist mechanism may be added to provide enhanced control over end effector 304's orientation. This enhanced control allows, e.g., a pitch and yaw displacement that is larger than provided by the various poses that distal segment 308 can assume, pitch and yaw displacement while distal segment 308 remains in a particular pose, and pitch and yaw displacement in surgical situations where tissue constrains the shape of distal segment 308's pose.

FIG. 4 is a schematic view that illustrates aspects of a minimally invasive surgical instrument assembly 400. Instrument assembly 400 includes a surgical instrument 402, which may be similar to surgical instrument 300 as described with reference to FIG. 3, and a guide tube 404. Guide tube 404 has at least one longitudinal channel 406, which may be fully or partially enclosed, that runs from proximal end 408 to distal end 410. Surgical instrument 402 runs through channel 406 and may be, for example, snap-fitted into a non-rotating socket to maintain position within guide tube 404. Guide tube 404 may have other channels (not shown) through which, e.g., irrigation or suction may be provided to a surgical site, in addition to channels associated with active control mechanisms (e.g., cables for steering or locking). End effector 412 is coupled to the distal end of surgical instrument 402. Instrument assembly 400 is inserted into a patient via cannula 414 or via natural orifice or incision. In some instances, a cannula-type guide may be used to assist insertion via natural orifice. Cannula 414 and such cannula-type guides may be straight or curved to facilitate insertion (e.g., for laryngeal surgery). Surgical

instrument assembly 400's cross section may be circular or other shape (e.g., elliptical, rounded polygon). Various combinations of surgical instrument 402 and guide tube 404 may be rigid, passively flexible, and actively flexible, as well as variably compliant and/or lockable, as described above. In some instances, an optional endoscopic imaging system (not shown) may be at the distal end of guide tube 404.

Just as some or all of surgical instrument 300 (FIG. 3) may be flexed to move its end effector to various positions and orientations, surgical instrument assembly 400 may be similarly flexed to move end effector 412 to various positions and orientations. Distal end segment 416, or the entire length of instrument assembly 400, may be actively flexed to heave and/or sway end effector 412. Combinations of bending and rolling may also be used to displace end effector 412. Compound bends may prevent end effector 412 from pitching and/or yawing during lateral translations as described above. Alternate positions 418 and 420 illustrate these active flexings. In accordance with an aspect of the invention, in some instances distal segment 416 of guide tube 404 provides small, wrist-like pitch and yaw orientation for end effector 412. Other segments of instrument assembly 400 provide end effector roll and position.

Surgical instrument assembly 400 potentially provides more DOFs, some redundant, for end effector 412 than surgical instrument 300 provides for end effector 304, as described with reference to FIG. 3. As shown in FIG. 4, in some aspects surgical instrument 402 may rotate within guide tube 404, and/or guide tube 404 may rotate within cannula 414 (or the natural orifice), to cause end effector 412 to be displaced in roll around instrument assembly 400's longitudinal axis. Instrument 402 may translate within guide tube 404, and/or guide tube 404 may translate within cannula 414, to cause end effector 412 to be displaced (surged) along instrument assembly 400's longitudinal axis. Alternatively, instrument 402 is held in position within guide tube 404 as described below. The lateral bending force that the guide tube's distal segment 416 exerts on the surgical instrument's distal end 402 is sufficiently strong to allow end effector 412 to perform its surgical task. In some instances, end effector 412 may be coupled to the distal end of surgical instrument 402 via a wrist mechanism that provides one or more additional DOFs (e.g., roll, pitch, yaw).

FIG. 4 also illustrates that when a guide tube bends, the bend must not bind operation of an instrument or another guide tube that runs inside it. For instance, guide tube 404 must not bend in such a way that a cable operating end effector 412 is frictionally bound or permanently kinked. In some aspects the radius of curvature is mechanically limited by, e.g., the structure of the individual vertebrae that make up the flexible guide tube. In other aspects the radius of curvature is limited by a control system, described below, to provide, e.g., a smoother behavior during actuation. Further, in some aspects cables for inner instruments or guide tubes must not shift to a shorter path between their proximal and distal ends so that the components they control are not affected as the guide tube bends (such shifting may be compensated for by using distal bend/shape sensors and a control system that maintains proper cable length). Cable path lengths may be stabilized by using sheathes (e.g. Bowden cables) for cables running through the center of the flexible joints or by routing cables through the joint peripheries as described below for virtual pivot point joints.

In some instances surgical instrument 402 is removable and may be replaced with a different surgical instrument that has a structure similar to instrument 402 but a different end effector so as to perform a different surgical task. Accord-

ingly, a single guide tube 404 may be used to provide wrist-like DOFs for one or more interchangeable surgical instruments 402. In some instances the surgical instruments may be interchanged while guide tube 404 remains in the patient. Such interchangeability is described in more detail below. The guide tube allows the newly inserted instrument to be positioned directly at the surgical site, regardless of the trajectory. And, one guide tube 404 may be withdrawn and replaced with another during surgery, either with or without an instrument 402 fully or partially inserted. Since some or all of the controllable DOFs are in the guide tube, in some aspects the instrument can be inexpensively made and therefore disposable, and the guide tube can be made sterilizable and reusable.

FIGS. 4A and 4B are diagrammatic perspective views that illustrate aspects of a removable instrument that is held in place within guide tube 440. The distal end 442 of guide tube 440 has an opening 444 through which the distal end of the instrument passes. Opening 444 is optionally made non-round to prevent the instrument from rolling within guide tube 440. An optional fitting 446 (e.g., a spring that snaps into a detent, etc.) holds the instrument's end effector 448 in position to keep the instrument from translating through the guide tube. A round opening 444 allows the instrument to roll while fitting 446 keeps the instrument from translating. When the fitting 446 releases the instrument (e.g., when sufficient pulling force is applied), the instrument may be withdrawn from the guide tube. Distal end 442 may be a wrist mechanism for the instrument's end effector in some aspects. The roll prevention configuration and the fitting are illustratively shown at the distal end of the guide tube but may be placed at various positions (e.g., at the insertion end of the guide tube). The roll prevention configuration and the fitting can be used in the various aspects described below for other instrument and guide tube combinations, with the understanding that the roll preventing configuration and the fitting will remove a redundant insertion DOF and/or a redundant roll DOF.

Instrument assembly 400 may be inserted in a rigidized or locked state, or it may be actively steered during insertion in order to reach a target surgical site. In some aspects instrument 402 and guide tube 404 are alternatively coaxially advanced. For example, instrument 402 is actively steered part way along the trajectory to the surgical site and then locked (only the distal section of the instrument (or guide tube) need be actively steerable; the more proximal sections may be passive or may use curve propagation as the instrument (or guide tube) advances). Curve propagation is disclosed in, e.g., Ikuta, K. et al., "Shape memory alloy servo actuator system with electric resistance feedback and application for active endoscope," 1988 IEEE International Conference on Robotics and Automation, Apr. 24-29, 1988, Vol. 1, pages 427-430, which is incorporated by reference. Guide tube 404 is then passively advanced to the distal end of instrument 402 and locked to support further advancement of instrument 402. The coaxial alternating advancing and locking continues until the surgical site is reached along the desired trajectory. Alternatively, guide tube 404 is actively steerable and lockable, and instrument 402 is passively advanced and locked within guide tube until the surgical site is reached. If both surgical instrument 402 and guide tube 404 are actively steerable, then they may "leapfrog" each other as they coaxially advance and lock along the trajectory to the surgical site. Such coaxial insertion may also be used with any combination of two or more instruments and guide tubes described herein.

17

FIG. 5 is a schematic view that illustrates aspects of a second minimally invasive surgical instrument assembly 500. Surgical instrument assembly 500 illustrates that two or more surgical instruments 502a, 502b may be surrounded by a single guide tube 504. Surgical instruments 502a, 502b may run longitudinally through guide tube 504 in a single channel 506. Or, surgical instruments 502a, 502b may each run through guide tube 504 in unique, individual channels 506a, 506b. End effectors 508a, 508b are each coupled to the distal ends of instruments 502a, 502b. Instrument assembly 500 is inserted via cannula 510 and as described above. Instrument assembly 500's cross section may be circular, elliptical, or other shape (e.g., rounded rectangle or other polygon). Various combinations of surgical instruments 502a, 502b and guide tube 504 may be rigid, passively flexible, and actively flexible, as well as lockable, as described above. An illustrative optional imaging system 511 (e.g., one or more image capture chips with associated optics and electronics) is positioned at the distal end of guide tube 504. The imaging system 511 has a field of view that may be used to assist advancing guide tube 504 and that allows a surgeon to view end effectors 508a, 508b working at a surgical site.

Surgical instrument assembly 500 operates in a manner similar to that of surgical instrument assembly 400 (FIG. 4), except that it is illustrative of aspects in which two or more surgical instruments extend through a single guide tube from a proximal to a distal end. Accordingly, the descriptions above of additional channels, active and passive flexibility, locking/rigidizing, various DOFs, the optional use of wrist mechanisms, instrument interchangeability, alternating coaxial advancing, and cannulas apply to instrument assembly 500. Distal end segment and entire assembly flexibility are illustrated by alternate position lines 512 and 514, similar to those shown in the preceding figures as described above. Compound bending of guide tube 504 provides at least 6 DOFs for end effectors 508a, 508b as described above. Alternating coaxial advancement may be done as described above. Various ways of such advancing are possible. For example, in some aspects both instruments may be used and the guide tube slides over both instruments; in other aspects first one instrument is advanced and locked, then the guide tube is advanced and locked, then the other instrument is advanced and locked, etc.

FIG. 6 is a schematic view that illustrates aspects of a third minimally invasive surgical instrument assembly 600. Surgical instrument assembly 600 operates in a manner similar to that of surgical instrument assembly 400 (FIG. 4), except that it is illustrative of aspects in which a surgical instrument 602's actively flexible distal segment 604 extends beyond the distal end of guide tube 606. Active flexibility of guide tube 606's distal end segment 608 and/or of the entire guide tube 606 are illustrated by alternate position lines 610 and 612. Active flexibility of instrument 602's distal segment 604 moves end effector 614 to illustrative alternate position 616. Accordingly, end effector 614 experiences wrist-like DOFs (e.g., roll, pitch, yaw) from the movement of instrument 602's distal segment 604, from the movement of guide tube 606's distal segment 608, and/or from a combination of movements by distal segments 604, 608. Thus, instrument assembly 600 illustrates aspects in which combinations of instruments and guide tubes provide redundant position and orientation DOFs for end effector 614. The descriptions above of additional channels, active and passive flexibility, locking/rigidizing, various degrees of freedom, increased lateral force application and stiffness, the optional use of wrist mechanisms and imaging systems,

18

instrument interchangeability, alternating coaxial advancing, and cannulas apply to instrument assembly 600.

FIG. 7 is a schematic view that illustrates aspects of a fourth minimally invasive surgical instrument assembly 700. As shown in FIG. 7, surgical instrument 702 extends through primary guide tube 704 along instrument assembly 700's longitudinal axis. In addition, primary guide tube 704 extends through secondary guide tube 706 along the longitudinal axis. In some instances surgical instrument assembly 700 may rotate via a cannula 708. End effector 710 is coupled to the distal end of surgical instrument 702 so that it extends just beyond primary guide tube 704's distal end.

End effector 710's redundant DOFs, other than the inherent one or more DOFs associated with its specific task (e.g., gripping), are provided in various ways. Surgical instrument 702 may rotate within primary guide tube 704, and/or primary guide tube 704 may rotate within secondary guide tube 706, and/or secondary guide tube 706 may rotate within cannula 708 (or a natural orifice or incision), which causes end effector 710 to be displaced in roll around instrument assembly 700's longitudinal axis. Surgical instrument 702 may translate within primary guide tube 704, and/or primary guide tube 704 may translate within secondary guide tube 706, and/or secondary guide tube 706 may translate within cannula 708, to displace (surge) end effector 710 along instrument assembly 700's longitudinal axis.

As shown in FIG. 7, an actively flexible distal segment 712 of primary guide tube 704 extends beyond secondary guide tube 706's distal end. Distal segment 712 may cause end effector 710 to be heaved and/or swayed (with incidental pitch and yaw as discussed above), adding one or two additional degrees of freedom as illustrated by alternate position 714. Similarly, an actively flexible distal segment 716 of secondary guide tube 706, or the entire secondary guide tube 706, may cause end effector 710 to be heaved and/or swayed, adding one or two more degrees of freedom as illustrated by alternate positions 718 and 720. Since instrument assembly 700 provides various combinations of roll, heave, and sway displacements for end effector 710, a wrist-type mechanism may not be required to couple end effector 710 to surgical instrument 702, although such a mechanism may be used to provide an additional one or more degrees of freedom (e.g., roll, pitch, yaw).

As indicated by the alternate position lines in FIG. 7, the primary and secondary guide tubes can maneuver end effector 710 with various combinations of simple and compound bends. In one illustrative embodiment, secondary guide tube 702's active flexibility is used for relatively large movements of end effector 710, and primary guide tube distal segment 712's active flexibility is used for relatively small, wrist-type movements of end effector 710. The amount of such motion depends on the distance that distal segment 712 extends beyond secondary guide tube 706, and so may provide motion similar to that described in FIG. 2B.

In some instances surgical instrument 702 may extend beyond primary guide tube 704 as described in FIG. 6. The descriptions above of additional channels, active and passive flexibility, locking/rigidizing, various DOFs, increased lateral force application and stiffness, instrument interchangeability, alternating coaxial advancing, and cannulas apply to instrument assembly 700. In addition, since secondary guide tube 706 has an even greater outer diameter than primary guide tube 704, actuation and locking mechanisms for secondary guide tube 706 may provide an increased lateral force and stiffness against reaction forces than either instrument 702 or primary guide tube 704 may provide alone or together.

FIG. 8 is a schematic view that illustrates aspects of a fifth minimally invasive surgical instrument assembly **800**. Surgical instrument assembly **800** illustrates that two or more primary guide tubes **802a,802b** may be surrounded by a single secondary guide tube **804**. An illustrative surgical instrument **806a,806b** runs through each of primary guide tubes **802a,802b**. The primary guide tubes **802a,802b** have an architecture generally similar to surgical instrument assembly **400** (FIG. 4). In some instances, however, one or more primary guide tubes **802** may have an architecture similar to surgical instrument assembly **500** (FIG. 5) or surgical instrument assembly **600** (FIG. 6). Active flexibility of the distal segments of primary guide tubes **802a,802b** that extend beyond the distal end of secondary guide tube **804** are illustrated by alternate position lines **808a,808b**. The distal segments of primary guide tubes **802a,802b** can move end effectors **809a,809b** adjacent one another at various positions at a surgical site within a patient so as to perform various surgical tasks. Various active flexibilities of secondary guide tube **804** are illustrated by alternate position lines **810a,810b**. The descriptions above of additional channels, active and passive flexibility, locking/rigidizing, various DOFs, increased lateral force application and stiffness, the optional use of wrist mechanisms, instrument interchangeability, alternating coaxial advancing, and cannulas apply to instrument assembly **800**.

In some instances an endoscopic imaging system **812**, represented schematically by a dashed box, is positioned at secondary guide tube **804**'s distal end. Imaging system **812** may be mono- or stereoscopic as described above and may have a viewing angle aligned with or angled (e.g., 30 degrees) from instrument assembly **800**'s longitudinal axis. In some instances imaging system **812** is positioned between primary guide tubes **802a,802b**. In other instances imaging system **812** is positioned above, below, or to the side of primary guide tubes **802a,802b** to make secondary guide tube **804**'s cross section more compact (e.g., one stereoscopic lens window above and one below the primary guide tubes **802a,802b**; camera referenced control for this configuration is made possible if the primary guide tubes bend out and then inwards towards the surgical site roughly coplanar with the interpupillary axis).

FIG. 9 is a schematic view that illustrates aspects of a sixth minimally invasive surgical instrument assembly **900**. Instrument assembly **900** is similar to instrument assembly **800** (FIG. 8), except that an illustrative additional surgical instrument **902** extends through secondary guide tube **904**, but surgical instrument **902** is not surrounded by a primary guide tube. Accordingly, the relationship between surgical instrument **902** and secondary guide tube **904** is similar to that described between the surgical instruments and guide tubes as shown in FIGS. 4 and 6. The relationship between the primary guide tube **906a,906b** and instrument **908a,908b** assemblies is similar to that described for aspects illustrated by FIGS. 7 and 8. Instrument assembly **900** is illustrative of a secondary guide tube through which extend various combinations of one or more primary guide tube and instrument assemblies as well as one or more instruments without guide tubes.

In some instances surgical instrument **902** is rigid or passively flexible and its end effector **910** is used to grasp and pull tissue to assist the surgical tasks that end effectors **912a,912b** at the ends of instruments **908a,908b** perform. Although rigid or passively flexible, instrument **902** is capable of pulling with considerable force. In other instances surgical instrument may perform other functions, such as retraction, irrigation, suction, etc. Further, if an endoscopic

imaging system is placed at the distal end of secondary guide tube **904**, as illustrated by instrument assembly **800** (FIG. 8), then instrument **902** may be used to service (e.g., clean with a jet of fluid) the imaging system's window(s).

In still other instances, as mentioned above, surgical instrument **902**'s distal end is actively flexible, and end effector **910** is replaced by an endoscopic imaging system **914** as shown in FIG. 9A. In these instances a distal imaging device may be coupled to the actively flexible end of surgical instrument **902** with a wrist-type mechanism **916** that provides at least a DOF in pitch. Such an architecture allows the image sensing device to be moved out from between the distal ends of primary guide tubes **906a,906b** and then the viewing angle is pitched (and/or yawed) to align the center of the visual field with the area at which the end effectors **912a,912b** are working. This architecture enables a surgeon to work, at a surgical site via a single entry port into the body, with two independently actuated surgical end effectors and an endoscopic imaging system that is independent of the surgical instruments. Another benefit of the independently controlled imaging system illustrated in FIG. 9A is tissue retraction, as shown and described more fully with reference to FIG. 17A below.

In accordance with aspects described above, one or more surgical instruments exit at the distal end of an guide tube, which may be a flat face or other shape, square or inclined to the assembly's longitudinal axis. In accordance with other aspects, one or more surgical instruments exit from the side of a guide tube. FIG. 10 is a schematic view that illustrates such aspects in a seventh minimally invasive surgical assembly **1000**.

As shown in FIG. 10, two surgical instruments **1002a, 1002b** (illustrative of two or more instruments) extend longitudinally through guide tube **1004**. Instruments **1002a, 1002b** exit guide tube **1004**'s distal segment **1006** via side exit ports **1008a,1008b** instead of at guide tube **1004**'s extreme distal end. The side exit ports **1008a,1008b** may be oriented to be generally opposite each other (i.e., displaced approximately 180 degrees from each other) or they may be separated by a lesser angle (e.g., 120 degrees). And, the side exit ports may have various angular orientations around distal segment **1006** in aspects in which more than two exit ports are used for one, two, or more than two instruments **1002**. In one aspect, one side exit port is farther from guide tube **1004**'s distal tip than another side exit port. Instrument **1002a**'s distal segment **1010a** and instrument **1002b**'s distal segment **1010b** are each independently actively flexible so as to move end effectors **1012a,1012b** for work at a surgical site. Various combinations of simple or compound bending with instrument roll and insertion, along with optional wrist mechanisms, provide the required end effector DOFs. An endoscopic imaging system **1014** is positioned at the distal end of guide tube **1004**. Imaging system **1014**'s viewing angle may be aligned with instrument assembly **1000**'s longitudinal axis, or the viewing angle may be angled (e.g., 30 degrees) from the longitudinal axis. In some aspects the viewing angle may be actively changed during a surgical procedure using, e.g., one or more movable reflecting surfaces (mirrors, prisms). The descriptions above of additional channels, active and passive flexibility, locking/rigidizing, various DOFs, increased lateral force and stiffness, the optional use of wrist mechanisms, instrument interchangeability, and cannulas apply to instrument assembly **1000**.

Surgical assembly **1000** is inserted into a patient via incision or natural orifice, in some instances through cannula **1016** or a similar guiding structure as described above. As

guide tube **1004** is inserted, in some instances surgical instruments **1002a,1002b** are either fully or partly retracted so that they do not extend beyond openings **1008a,1008b** as guide tube **1004** advances towards a surgical site. Images from imaging system **1014** may assist advancement. Once guide tube **1004** is in position at the surgical site, instruments **1002a,1002b** may then be inserted and/or advanced within guide tube **1004** to reach the surgical site. Guide tube **1004** may be actively flexed during a surgical procedure to provide gross movements at the surgical site while instrument distal segments **1010a,1010b** perform fine movements to complete the surgical task, as illustrated by alternate position lines **1018a,1018b**. The surgeon views images from imaging system **1014** while performing surgical tasks with end effectors **1012a,1012b**. Since the surgeon cannot see images from imaging system **1014** of distal segments **1010a,1010b** as they exit side ports **1008a,1008b**, in some aspects a control system, described below, controls distal segments **1010a,1010b** as they exit from guide tube **1004** so that they curve to meet in front of imaging system **1014**. In other aspects, a luminal space is mapped as described below, and the control system uses the mapping data to guide the end effectors into imaging system **1014**'s field of view. In still other aspects the distal end of the guide tube may be moved, e.g., to the left from a known space, thereby allowing the right instrument to be inserted into the "safe" space to the right of the guide tube. Then, likewise, the distal end of guide tube is moved to the right and the left instrument is moved into the "safe" space to the left of the guide tube. For aspects in which the distal end of the guide tube moves upward independently of the part of the guide tube at which the instruments exit, the instruments may be similarly inserted into the "safe" space underneath the upwardly displaced distal end of the guide tube. For withdrawal, or subsequent large repositioning, instruments **1002a,1002b** may be withdrawn through side exit ports **1008a,1008b**, either partially into or entirely from guide tube **1004**.

FIG. **11** is a schematic view that illustrates aspects of an eighth minimally invasive surgical assembly **1100**. As shown in FIG. **11**, surgical instrument **1102a** extends through primary guide tube **1104a** along its longitudinal axis. Likewise, surgical instrument **1102b** extends through primary guide tube **1104b** along its longitudinal axis. End effectors **1106a,1106b** are coupled to the distal ends of instruments **1102a,1102b**. Primary guide tubes **1104a,1104b** extend longitudinally through secondary guide tube **1108**. In a manner similar to the way surgical instruments **1002a,1002b** exit side ports **1008a,1008b** of guide tube **1004**'s distal segment **1106**, primary guide tubes **1104a,1104b** exit side ports **1110a,1110b** of secondary guide tube **1108**. The distal segments **1112a,1112b** of primary guide tubes **1104a,1104b** actively flex to move end effectors **1106a,1106b**, as illustrated by alternate position lines **1114a,1114b**. An endoscopic imaging system **1116** is positioned at secondary guide tube **1108**'s distal end. The descriptions above of additional channels, active and passive flexibility, locking/rigidizing, various DOFs, increased lateral force application and stiffness, the optional use of wrist mechanisms, instrument interchangeability, cannulas, and endoscopic imaging systems apply to instrument assembly **1100**.

Instrument assembly **1100** operates in a manner similar to instrument assembly **1000** (FIG. **10**). The principal difference between the two aspects is the use of both secondary and primary guide tubes in assembly **1100**. The relationship between instrument assemblies **1100** and **1000** is therefore akin to the relationship between instrument assemblies **800** (FIG. **8**) and **500** (FIG. **5**). The descriptions above of

insertion, full or partial instrument retraction during insertion and repositioning, use of the imaging system, use of primary and secondary guide tubes, and controlled extension of instruments apply to aspects of instrument assembly **1100**.

FIGS. **11A** and **11B** are diagrammatic end views of surgical instrument assemblies, and they illustrate that a side-exit assembly such as assemblies **1000** (FIG. **10**) and **1100** (FIG. **11**) may be used to reduce the overall cross-sectional area of a guide tube or secondary guide tube. FIG. **11A** is an illustrative view of an assembly, such as assembly **800** (the circular cross-sectional shape is merely illustrative), in which instrument/guide tube combinations **802a,806a** and **802b,806b** exit from the distal end of a guide tube or secondary guide tube. In this illustrative example, imaging system **812** is a stereoscopic imaging system with an interpupillary distance **1120** between imaging ports and an illustrative illumination port **1122**. As shown in FIG. **11B**'s illustrative example, the side-exit assembly's instrument/distal guide tube segment combinations **1102a,1112a** and **1102b,1112b** have the same cross-sectional dimensions as combinations **802a,806a** and **802b,806b** shown in FIG. **11A**. And, illustrative stereoscopic imaging system **1116** has the same interpupillary distance **1120** as imaging system **812** as shown in FIG. **11A**. If the endoscopic image is captured and digitized at the distal end of the guide tube, then the guide tube area proximal of the image capture and digitizing components can be used for instruments and actuation instead of for optics (e.g., fiber bundles, rod lenses, etc.). Consequently, the oblong-shaped cross-sectional area of FIG. **11B**'s side-exit guide tube is smaller than the cross-sectional area of FIG. **11A**'s end-exit guide tube, and the imaging system's interpupillary distance is the same. This reduced cross-sectional area may be an advantage for, e.g., the size and location of an incision to be used, for the size of a particular natural orifice, or for the position of intermediate tissue between the entry port and the surgical site. Such an oblong cross-sectional shape can be used in other instrument assembly guide tubes described herein.

FIG. **12** is a schematic view that illustrates aspects of a ninth minimally invasive surgical instrument assembly **1200**. Instrument assembly **1200** is similar to instrument assembly **1100**, with an additional surgical instrument **1202** that extends from the distal end of secondary guide tube **1204**. Surgical instrument **1202** operates in a manner similar to surgical instrument **902** (FIG. **9**), being in some aspects rigid and in others passively or actively flexible as described above. And, end effector **1206** may be replaced with an endoscopic imaging system as described with reference to FIGS. **9** and **9A** or FIGS. **17** and **17A** so that in some aspects instrument assembly **1200** has an independently operated, optionally wrist-mounted, endoscopic imaging system **1208** as illustrated in FIG. **12**.

FIGS. **12A** and **12B** are diagrammatic views of embodiments that illustrate retroflexive positions in examples of side-exit guide tubes, similar to retroflexive movement for end-exit guide tubes discussed above. FIG. **12A** illustrates that in one aspect the side-exit instrument assembly **1220** actively bends in a plane that is approximately coplanar with the side exit ports **1222a** and **1222b** (yaw with reference to the visual field reference). FIG. **12B** illustrates that in another aspect the side exit instrument assembly **1230** actively bends in a plane that is approximately perpendicular to the side exit ports **1232a** and **1232b** (hidden) (pitch with reference to the visual field reference). Assembly **1230**'s bend radius may be smaller than assembly **1220**'s bend radius, other dimensions being substantially the same, due to

the mechanical structure. In some aspects the side-exit instrument assembly may simultaneously yaw and pitch, and the assembly may yaw/pitch distally of the side exit ports.

FIGS. 13 and 14 are schematic views that illustrate tenth and eleventh aspects of minimally invasive surgical instrument assemblies 1300 (FIG. 13) and 1400 (FIG. 1400). Surgical instrument assemblies 1300 and 1400 combine aspects of surgical instrument assemblies illustrated in FIGS. 3-12B and the associated descriptions. Specifically, instrument assembly 1300 illustrates aspects in which one or more surgical instruments 1302 exit the end of a distal segment 1304 of a guide tube 1306, and one or more other surgical instruments 1308 exit from a side exit port 1310 at guide tube 1306's distal segment 1304. Likewise, instrument assembly 1400 illustrates aspects in which one or more surgical instruments 1402 run coaxially within one or more primary guide tubes 1404 that exit the end of a distal segment 1406 of a secondary guide tube 1408, and one or more other surgical instruments 1410 run coaxially through one or more other primary guide tubes 1412 that run coaxially within secondary guide tube 1408 and exit from one or more side exit ports 1414 at secondary guide tube 1408's distal segment 1406. The descriptions above of additional channels, active and passive flexibility, locking/rigidizing, various DOFs, increased lateral force application and stiffness, the optional use of wrist mechanisms, instrument interchangeability, cannulas, and endoscopic imaging systems apply to instrument assemblies 1300 and 1400.

In many instances an instrument or instrument assembly as described herein can be actively or passively positioned at a surgical site. A sufficiently flexible and maneuverable surgical instrument or surgical instrument assembly, such as those described herein, may be inserted with one or more segments of the instrument or assembly functioning in accordance with the insertion description below. In some instances, however, a guide probe can be used to initially define some or all of the trajectory between the entry port and the surgical site. The guide probe may be maneuvered using, e.g., image data from an imaging system at the guide probe's distal tip, real time image data from an external imaging system (e.g., ultrasound, fluoroscopy, MRI), pre-operative image data and computer analysis of likely trajectory, and various combinations of these data.

FIGS. 15A-15D are schematic views that illustrate aspects of inserting a flexible, steerable surgical instrument and surgical instrument assembly, such as those described herein, by using a guide probe to maneuver past intermediate tissue structures so as to reach a surgical site within a patient. Insertion may be via natural orifice or incision, either with or without using a cannula (not shown) as described above. As shown in FIG. 15A, a first intermediate tissue structure 1502 prevents a surgical instrument or surgical instrument assembly from operating with a pivoting center point generally where it enters the body, as shown in FIG. 1. In addition, a second intermediate tissue structure 1504 exists between the position where the instrument or instrument assembly passes the first intermediate tissue structure 1502 and the target surgical site 1506, as shown in FIG. 2B. An instrument or instrument assembly must be guided between and around the intermediate tissue structures to reach the surgical site.

As shown in FIG. 15A, in one aspect a guide probe 1508 is inserted past first intermediate structure 1502 and is then actively maneuvered around second intermediate tissue structure 1504 to reach surgical site 1506 or another desired position. The guide probe's primary function is to establish a trajectory to the surgical site. An optional endoscopic

imaging system 1509 may be mounted at guide probe 1508's distal tip. In some aspects curve propagation as described above is used during insertion—curves initially formed by steering the distal end are automatically propagated in a proximal direction on the guide probe as it is advanced towards the surgical site. Such curve propagation is done using, e.g., control systems as described below. Once at its desired position, guide probe 1508 is then rigidized so as to maintain its two- or three-dimensional curved shape. Next, a guide tube 1510 is inserted coaxially over guide probe 1508, as shown in FIG. 15B. The guide tube 1510 may be inserted to an intermediate position as shown, or it may be inserted and maneuvered to a position at surgical site 1506 as shown by the alternate position lines. In some aspects, the guide probe and guide tube may be coaxially inserted, first one, then the other in a repeated, alternating way. Guide tube 1510 is illustrative of various primary and secondary guide tubes, such as those shown in FIGS. 4-14. Once in a desired position, guide tube 1510 is then rigidized to maintain the shape defined by guide probe 1508, which is then withdrawn as shown in FIG. 15C. After the guide probe is withdrawn, a surgical instrument or surgical instrument assembly 1512 may then be inserted through guide tube 1510 to reach surgical site 1506, as shown in FIG. 15D.

To facilitate guide tube insertion, in one aspect the guide probe extends beyond the coaxial guide tube by a distance sufficient to allow the guide probe to enter a patient and reach the surgical site. Then, the guide probe is coaxially inserted. In an alternate aspect, a proximal portion (e.g., the transmission mechanism; see FIG. 27 for an illustrative view) of the guide probe is removable to allow the guide tube to be coaxially inserted over the guide probe.

As an illustrative example in accordance with surgical instrument assembly 400 (FIG. 4), a guide probe is inserted, guide tube 404 is inserted over the guide probe, the guide probe is withdrawn, and then surgical instrument 402 is inserted through guide tube 404. A similar procedure can be used for guide tubes with multiple instrument channels, such as surgical instrument assembly 500 (FIG. 5). As another illustrative example in accordance with surgical instrument assembly 700 (FIG. 7), a guide probe is inserted, primary guide tube 704 is inserted over the guide probe, secondary guide tube 706 is inserted over primary guide tube 704, the guide probe is withdrawn, and instrument 702 is inserted through primary guide tube 704. Alternately, a guide probe having a relatively larger outer diameter is inserted, secondary guide tube 706 is inserted over the guide probe, the guide probe is withdrawn, and primary guide tube 704 and instrument 706 are then inserted through secondary guide tube 706. A similar procedure can be used for secondary guide tubes that have two or more primary guide tube and/or instrument channels. As yet another illustrative example, guide tube 1510 is analogous to cannula 708, and instrument assembly 700 is inserted through guide tube 1510. Many variations in insertion order are possible and are within the scope of the invention.

Referring again to FIG. 2A, it can be seen that a rigid distal segment of a minimally invasive surgical instrument can also provide access to a large volume deep within the body that is accessed through an intermediate tissue structure. Such mechanisms may be mechanically simpler to build and operate, and therefore may be less expensive and easier to control than systems that use flexible technology. And, in some aspects such mechanisms may work back on themselves to provide a capability similar to the retroflexive bending described above.

FIG. 16 is a schematic view that illustrates aspects of a twelfth minimally invasive surgical instrument assembly 1600. As shown in FIG. 16, two surgical instruments 1602a, 1602b extend through channels 1604a, 1604b that extend longitudinally through rigid guide tube 1606. In some aspects guide tube 1606 is straight and in others it is curved to accommodate a particular insertion port (the instruments are similarly curved to facilitate insertion). Guide tube 1606 may have various cross-sectional shapes (e.g., circular, oval, rounded polygon), and various numbers of surgical instruments and channels may be used. Some optional working channels may be used to provide supporting surgical functions such as irrigation and suction. In some aspects an endoscopic imaging system (e.g., mono- or stereoscopic image capture or direct view) is at guide tube 1606's distal end 1610. In one aspect guide tube 1606 is inserted into a patient via an incision (e.g., approximately 2.0 cm at the umbilicus) or natural orifice, either with or without the use of a cannula 1612 or similar guiding structure. In some aspects guide tube 1606 may rotate within cannula 1612.

As shown in FIG. 16, surgical instruments 1602a and 1602b function in a like manner, and many instrument functions (body roll, wrist operation, end effector operation, etc.) are similar to the surgical instruments used in the da Vinci® Surgical System (both 8 mm and 5 mm instrument body diameters). In other aspects the instruments may function differently and/or have capabilities not embodied in da Vinci® Surgical System instruments (e.g., one instrument may be straight, one instrument may be jointed, one instrument may be flexible, etc.). In the illustrative aspect shown in FIG. 16, instrument 1602a includes a transmission portion (not shown) at its proximal end, an elongated instrument body 1614, one of various surgical end effectors 1630, and a snake-like, two degree of freedom wrist mechanism 1626 that couples end effector 1630 to instrument body 1614. As in the da Vinci® Surgical Systems, in some aspects the transmission portion includes disks that interface with electrical actuators (e.g., servomotors) permanently mounted on a support arm so that instruments may easily be changed. Other linkages such as matching gimbal plates and levers may be used to transfer actuating forces at the mechanical interface. Mechanical mechanisms (e.g., gears, levers, gimbals) in the transmission portion transfer the actuating forces from the disks to cables, wires, and/or cable, wire, and hypotube combinations that run through one or more channels in instrument body 1614 (which may include one or more articulated segments) to control wrist 1626 and end effector 1630 movement. In some aspects, one or more disks and associated mechanisms transfer actuating forces that roll instrument body 1614 around its longitudinal axis 1619 as shown. In some aspects the actuators for a particular instrument are themselves mounted on a single linear actuator that moves instrument body 1614 longitudinally as shown within channel 1604a. The main segment of instrument body 1614 is a substantially rigid single tube, although in some aspects it may be slightly resiliently flexible. This small flexibility allows a proximal body segment 1620 proximal of guide tube 1606 (i.e., outside the patient) be slightly flexed so that several instrument bodies can be spaced more closely within guide tube 1606 than their individual transmission segment housings would otherwise allow, like several cut flowers of equal length being placed in a small-necked vase. This flexing is minimal (e.g., less than or equal to about a 5-degree bend angle in one embodiment) and does not induce significant friction because the bend angle for the control cables and hypotubes inside the instrument body is small.

As shown in FIG. 16, instruments 1602a and 1602b each include a proximal body segment that extends through the guide tube and at least one distal body segment that is positioned beyond the guide tube's distal end. For example, instrument 1602a includes proximal body segment 1620 that extends through guide tube 1606, a distal body segment 1622 that is coupled to proximal body segment 1620 at a joint 1624, a wrist mechanism 1626 that is coupled to distal body segment 1622 at another joint 1628 (the coupling may include another, short distal body segment), and an end effector 1630. In some aspects the distal body segment 1622 and joints 1624 and 1628 function as a parallel motion mechanism 1632 in which the position of a distal reference frame at the distal end of parallel motion mechanism 1632 may be changed with respect to a proximal reference frame at the proximal end of parallel motion mechanism 1632 without changing the orientation of the distal reference frame.

FIG. 16A is a side elevation view of an embodiment of the distal end of instrument 1602a, which includes parallel motion mechanism 1632, wrist mechanism 1626, and end effector 1630. In this illustrative embodiment, parallel motion mechanism 1632's diameter is approximately 7 mm, and wrist 1626's diameter is approximately 5 mm. FIG. 16A shows that joints 1624 and 1628 each have two hinges that pivot around orthogonal axes. As one hinge pivots in joint 1624, the corresponding hinge pivots an equal amount in the opposite direction in joint 1628. Accordingly, as distal body segment 1622 moves, the orientation of wrist 1626 and end effector 1630 remain essentially unaffected. The hinges are constructed with rolling contact so that cable lengths on each side of the pivot remain balanced ("virtual pivot points"); details are disclosed in U.S. Pat. No. 6,817,974 (Cooper et al.), which is incorporated by reference. U.S. Pat. No. 6,817,974 further discloses details about the Yaw-Pitch-Pitch-Yaw (YPPY; alternately PYYP) arrangement of the hinges in parallel motion mechanism 1632 (wrist 1626 is similarly configured), which provides a constant velocity roll configuration. Consequently, roll of proximal body segment 1620 is smoothly transferred to end effector 1630. Cables, wires, or bendable hypotubes are routed through a center channel in body segments 1620, 1622, in joints 1624, 1628, and in wrist 1626 to operate end effector 1630 (e.g., opening and closing jaws in a gripper as shown). Cables that operate parallel motion mechanism 1632 and wrist 1626 are routed through openings near the periphery of the joints. FIG. 16B is a perspective view, and FIG. 16C is a cross-sectional view, of an illustrative embodiment of joints 1624, 1628.

As described herein, parallel motion mechanism 1632 includes two joints 1624 and 1628. Since the joints 1624, 1628 are coupled together, however, they do not operate independently of one another. Therefore, in joint space the entire parallel motion mechanism 1632 may be considered a single joint with two degrees of freedom (i.e., pitch and yaw) if "joints" 1624 and 1628 each have two orthogonal hinges (the position of the distal end of the mechanism may change in 3D Cartesian space), or as a single joint with one degree of freedom (i.e., pitch or yaw) if "joints" 1624 and 1628 each have a single hinge (the position of the distal end of the mechanism may change only in 2D Cartesian space). If parallel motion mechanism 1632 has two DOFs in joint space, then it functions as a constant velocity joint and transmits roll. Mechanism 1632's motion is "parallel" because the relative orientations of the proximal and distal ends (frames) of the mechanism remain constant as the mechanism changes the distal end's (frame's) position.

FIGS. 16D and 16E are schematic views that illustrate aspects of parallel motion mechanism 1632's design and operation principles. For clarity, only one set (i.e., PP or YY) of corresponding pivoting hinges is shown. The other set of hinges works the same way. Each hinge has a proximal link disk and a distal link disk. As shown in FIG. 16D, a first set of cables 1640a, 1640b are positioned on opposite sides of parallel motion mechanism 1632 and couple the proximal link disk in hinge 1624a to the distal link disk in hinge 1628b. The two cables 1640a, 1640b are illustrative of various combinations of cables that may be used (e.g., two cables on each side for increased strength; three cables spaced approximately 120 degrees apart will maintain parallelism in both planes; etc.). A second set of cables 1642a, 1642b are coupled to the distal link disk of hinge 1624a and run back through proximal body segment 1620 to the transmission mechanism (not shown). Other cables that control wrist mechanism 1626 and end effector 1630 are illustrated by a third set of cables 1644a, 1644b.

As shown in FIG. 16E, when the transmission mechanism applies a tensile force on cable 1642a (cable 1642b is allowed to pay out), hinge 1624a pivots. The cable 1640a, 1640b coupling between the proximal link disk of hinge 1624a and the distal link disk of hinge 1628a causes hinge 1628a to pivot an equal amount in the opposite direction. Consequently, wrist 1626 and end effector 1630 are laterally displaced away from longitudinal axis 1619 of proximal body segment 1620. The lengths of cables 1644a, 1644b are unaffected by the movement because of the hinge design, and so wrist 1626 and end effector 1630 orientation are also unaffected by the movement. If proximal instrument body segment 1620 were to remain stationary, then end effector 1630 translates slightly in a direction aligned with longitudinal axis 1619 (surged) in the patient's reference frame. Therefore, the control system, described below, compensates for this small movement by moving proximate body segment 1620 by an amount necessary to keep end effector 1630 at a constant insertion depth in the patient's reference frame.

In some instances when transmitting roll to the end effector is not required (e.g., for suction or irrigation tools, for an imaging system), each joint in the parallel movement mechanism may have only a single pivoting hinge. Further, skilled artisans will understand that if keeping end effector orientation is not required, then the parallel motion mechanism may be omitted. For instance, a proximal instrument body segment may be coupled to a distal instrument body segment at a joint with a single pivoting axis so that the proximal body segment must be rolled to move an end effector at the distal end of the distal body segment from side to side. Or, two or more elongated distal body segments may be used. If roll is not required, then the cross section of the body segments does not have to be round. In some aspects, the wrist mechanism may be eliminated.

FIG. 16F is a diagrammatic end view of a link disk, and it illustrates aspects of cable routing in a parallel motion mechanism. As shown in FIG. 16F, twelve cable routing holes are placed near the outside perimeter of link disk 1650. The cable routing holes are spaced 22.5 degrees apart from one another between the 3, 6, 9, and 12 O'clock positions on link disk 1650. Holes are not placed at the 3, 6, 9, and 12 O'clock positions because of the hinge components (not shown) on the obverse and reverse sides of link disk 1650. Starting at the 12 O'clock position, the holes are labeled 1652a-1652l. Four sets of three cables each are dedicated to four functions. A first set of cables maintains the parallel function in the parallel motion mechanism and are routed

through holes 1652a, 1652e, and 1652i. A second set of cables are used to move a distal part of a wrist mechanism (e.g., wrist mechanism 1626) and are routed through holes 1652b, 1652f, and 1652j. A third set of cables are used to move the parallel motion mechanism and are routed through holes 1652c, 1652g, and 1652k. A fourth set of cables are used to move a proximal part of the wrist mechanism and are routed through holes 1652d, 1652h, and 1652l. Cables and other components associated with an end effector are routed through central hole 1654 in link disk 1650.

FIG. 16G is another diagrammatic end view of a link disk, and it illustrates further aspects of cable routing in a parallel motion mechanism. As shown in FIG. 16G, a first set of 12 cable routing holes are placed around the outside perimeter of link disk 1660 in a manner similar to those shown in FIG. 16F. In addition, a second set of 12 cable routing holes are placed around a concentric circle inside the first set of holes. Starting at the 12 O'clock position, the outer ring of cable routing holes are labeled 1662a-1662l, and the inner ring of holes are labeled 1664a-1664l. Cables associated with the parallel motion mechanism are routed through the outer ring of holes 1662, and cables associated with the wrist mechanism are routed through the inner ring of holes 1664. A first set of three cable pairs maintains the parallel function in the parallel motion mechanism and are routed through adjacent holes 1662a and 1662l, 1662d and 1662e, and 1662h and 1662i. A second set of three cable pairs are used to move the parallel motion mechanism and are routed through adjacent holes 1662b and 1662c, 1662f and 1662g, and 1662j and 1662k. A third set of three cable pairs is used to move a proximal part of the wrist mechanism and are routed through adjacent holes 1664a and 1664l, 1664d and 1664e, and 1664h and 1664i. A fourth set of three cable pairs are used to move a distal part of the wrist mechanism and are routed through adjacent holes 1664b and 1664c, 1664f and 1664g, and 1664j and 1664k. Cables and other components associated with an end effector are routed through central hole 1666 in link disk 1660.

The use of cable pairs as illustrated in FIG. 16G increases actuation stiffness above the stiffness of using a single cable. The increased stiffness allows the instrument components to be more accurately positioned during movement (e.g., the increased stiffness helps to reduce motion hysteresis). In one example, such cable pairs are used for an instrument with a parallel motion mechanism that is approximately 7 mm in diameter. Instruments with smaller diameters (e.g., approximately 5 mm in diameter), however, may not have sufficient internal space to accommodate cable pairs. In these situations, single cables routed in accordance with FIG. 16F may be coupled to a cable on the opposite side of the parallel motion mechanism. Aspects of such coupling are illustrated in FIGS. 16H-16J.

FIG. 16H is a diagrammatic perspective view of a stiffening bracket 1670 that couples cables routed on opposite sides of a parallel motion mechanism's body segment 1622. Bracket 1670 has a cross piece 1672 and two parallel support members 1674 attached (e.g., welded) on opposite sides of cross piece 1672. A hypotube 1676 is attached (e.g., welded) to each support member so that the hypotubes are parallel to each other. The hypotubes 1676 are spaced apart a distance slightly less than the free space distance between the two cables to be coupled. The cable 1678 that maintains the parallel motion mechanism's parallel function is threaded through its associated hypotube 1676 as the cable extends between its two anchor points in the parallel motion mechanism. The hypotube 1676 is crimped to keep cable 1678 in place. The end of cable 1680 that is used to move the parallel

motion mechanism is threaded into its associated hypotube **1676**, which is crimped to keep cable **1680** in place. Consequently, the distal end of cable **1680** is anchored to a middle position (not necessarily halfway) of cable **1678**. Referring to FIG. **16F**, cables running through holes **1652a** and **1652g** are coupled together, cables running through holes **1652c** and **1652i** are coupled together, and cables running through holes **1652e** and **1652k** are coupled together. FIG. **16I** illustrates an aspect of how multiple brackets **1670** may be positioned within the body of a parallel motion mechanism. That is, each cable that is associated with moving the parallel motion mechanism is coupled to an opposite side cable associated with maintaining the parallel function of the parallel motion mechanism.

Due to the way the hinges are constructed, described above, the cables that maintain the parallel function move within the body of the parallel motion mechanism, even though they are anchored at either end of the parallel motion mechanism. Therefore, for a given motion of the parallel motion mechanism, the cable coupling requires that the cables **1680**, which move the parallel motion mechanism, move twice as far as they would if they were anchored to the parallel motion mechanism's body segment as illustrated in, e.g., FIGS. **16D-16E**. The effect of this coupling increases joint stiffness approximately four times more than non-coupled cables because the cable moves twice as far, and because the load on the cable is half as great for a given joint torque.

FIG. **16J** is a diagrammatic end view of a stiffening bracket **1670**. As shown in FIG. **16J**, cross piece **1672** is hollow so that cables and other components associated with an end effector may be routed through the cross piece. In one aspect, cross piece **1672** is made using electrical discharge machining. Referring again to FIG. **16**, the proximal body portion, parallel motion mechanism, wrist, and end effector are aligned along longitudinal axis **1619** to allow the instrument to be inserted and withdrawn through guide tube **1606**. Accordingly, two or more independently operating, exchangeable instruments, each with parallel motion mechanisms, can be simultaneously inserted via guide tube **1606** to allow a surgeon to enter a patient via a single entry port and work within a large volume deep within a patient. Each independent instrument's end effector has a full 6 DOF in Cartesian space (instrument insertion and the parallel motion mechanism provide the translation DOFs, and instrument body roll and the wrist mechanism provide the orientation DOFs). Further, the instruments **1602a, 1602b** may be partially withdrawn so that, e.g., only the wrist and end effectors extend from the guide tube **1606**'s distal end **1610**. In this configuration, the one or more wrists and end effectors can perform limited surgical work.

FIG. **17** is a schematic view that illustrates aspects of a thirteenth minimally invasive surgical instrument assembly **1700**. Surgical instrument assembly **1700** is similar to instrument assembly **1600** (FIGS. **16-16J**) in that surgical instruments **1702a, 1702b** function similarly to instruments **1602a, 1602b** as described above, but instead of a fixed endoscopic imaging system at the end of the guide tube, assembly **1700** has an independently operating endoscopic imaging system **1704**.

In one aspect, imaging system **1704** is mechanically similar to surgical instruments **1602** as described above. Summarizing these aspects as shown in FIG. **17**, optical system **1704** includes a substantially rigid elongate tubular proximal body segment **1706** that extends through guide tube **1708**, and at proximal body segment **1706**'s distal end there is coupled a 1 or 2 DOF parallel motion mechanism

1712 that is similar to parallel motion mechanism **1622** (FIGS. **16-16J**). Parallel motion mechanism **1712** includes a first joint **1714**, an intermediate distal body segment **1716**, and a second joint **1718**. As shown in FIG. **17**, in some aspects a wrist mechanism or other active joint (e.g., one DOF to allow changing pitch angle; two DOFs to allow changing pitch and yaw angles) **1720** couples an image capture component **1722** to second joint **1718**. Alternatively, in another aspect joint **1714** is an independently controllable one or two DOF joint (pitch/yaw), joint **1718** is another independently controllable one or two DOF joint (e.g., pitch/yaw), and image capture component **1722** is coupled directly at the distal end of the joint **1718** mechanism. An example of a suitable stereoscopic image capture component is shown in U.S. patent application Ser. No. 11/614,661, incorporated by reference above. In some aspects imaging system **1704** moves longitudinally (surges) inside guide tube **1708**. Control of imaging system **1704** is further described in concurrently filed U.S. patent application Ser. No. 11/762,236, issued as U.S. Pat. No. 8,419,717 to Diolaiti et al., and entitled "Control System Configured to Compensate for Non-Ideal Actuator-to-Joint Linkage Characteristics in a Medical Robotic System", which is incorporated by reference. In some aspects, roll may be undesirable because of a need to preserve a particular field of view orientation. Having heave, sway, surge, yaw, and pitch DOFs allows the image capture component to be moved to various positions while preserving a particular camera reference for assembly **1700** and viewing alignment for the surgeon.

FIG. **17A** is, for illustrative purposes only, a side view schematic to FIG. **17**'s plan view schematic. FIG. **17A** shows that parallel motion mechanism **1712** moves image capture component **1722** away from surgical instrument assembly **1700**'s longitudinal centerline. This displacement provides an improved view of surgical site **1724** because some or all of the instrument body distal segment ends are not present in the image output to the surgeon as would occur in, e.g., instrument assembly **1600** (FIG. **16**). The pitch of parallel motion mechanism **1712** and of image capture component **1722** is controllable, as illustrated by the arrows.

FIG. **17B** is a diagrammatic perspective view that illustrates an embodiment of surgical instrument assembly **1700**. As shown, two independently teleoperated surgical instruments **1740a, 1740b** (each instrument is associated with a separate master—e.g. one left hand master for the left instrument and one right hand master for the right instrument) run through and emerge at the distal end of a rigid guide tube **1742**. Each instrument **1740a, 1740b** is a 6 DOF instrument, as described above, and includes a parallel motion mechanism **1744a, 1744b**, as described above, with wrists **1746a, 1746b** and end effectors **1748a, 1748b** attached. In addition, an independently teleoperated endoscopic imaging system **1750** runs through and emerges at the distal end of guide tube **1742**. In some aspects imaging system **1750** also includes a parallel motion mechanism **1752**, a pitch-only wrist mechanism **1754** at the distal end of the parallel motion mechanism **1752** (the mechanism may have either one or two DOFs in joint space), and a stereoscopic endoscopic image capture component **1756** coupled to wrist mechanism **1754**. In other aspects, wrist mechanism **1754** may include a yaw DOF. In yet another aspect, the proximal and distal joints in imaging system **1750** are independently controlled. In an illustrative use, parallel motion mechanism **1752** heaves and sways image capture component **1756** up and to the side, and wrist mechanism **1754** orients image capture component **1756** to place the center of the field of

view between the instrument tips if the instruments are working to the side of the guide tube's extended centerline. In another illustrative use, the distal body segment of imaging system is independently pitched up (in some aspects also independently yawed), and image capture component **1756** is independently pitched down (in some aspects also independently yawed). As discussed above and below, imaging system **1750** may be moved to various places to retract tissue.

Also shown is an auxiliary channel **1760**, through which, e.g., irrigation, suction, or other surgical items may be introduced or withdrawn. In some aspects, one or more small, steerable devices (e.g., illustrated by instrument **902** in FIG. **9**) may be inserted via auxiliary channel **1760** to spray a cleaning fluid (e.g., pressurized water, gas) and/or a drying agent (e.g., pressurized air or insufflation gas) on the imaging system's windows to clean them. In another aspect, such a cleaning wand may be a passive device that attaches to the camera before insertion. In yet another aspect, the end of the wand is automatically hooked to the image capture component as the image capture component emerges from the guide tube's distal end. A spring gently pulls on the cleaning wand so that it tends to retract into the guide tube as the imaging system is withdrawn from the guide tube.

FIG. **17A** further illustrates that as image capture component **1722** is moved away from assembly **1700**'s centerline it may press against and move an overlying tissue structure surface **1726**, thereby retracting the tissue structure from the surgical site as shown. The use of imaging system **1704** to retract tissue is illustrative of using other surgical instruments, or a device specifically designed for the task, to retract tissue. Such "tent-pole" type retraction may be performed by any of the various movable components described herein, such as the distal end exit or side exit flexible devices and the parallel motion mechanisms on the rigid body component devices, as well as other devices discussed below (e.g., with reference to FIG. **31**).

In some aspects, one or more surgical instruments may exit from a guide tube generally aligned with the guide tube's longitudinal axis but not at the guide tube's distal end. FIG. **18** is a schematic view that illustrates aspects of a fourteenth minimally invasive surgical instrument assembly **1800**. As shown in FIG. **18**, a first surgical instrument **1802** runs coaxially through primary guide tube **1804**, and a second surgical instrument **1806** runs coaxially through primary guide tube **1808**. Instrument and primary guide tube combinations **1802,1804** and **1806,1808** are illustrative of the various flexible and rigid instruments and instrument/guide tube combinations described above. Instrument/guide tube combination **1802,1804** extends through and exits at secondary guide tube **1810**'s extreme distal end **1812**. Instrument/guide tube combination **1806,1808** extends through secondary guide tube **1810** and exits at an intermediate position **1814** that is proximally spaced from extreme distal end **1812**. In contrast to the side exits that direct instruments away from the guide tube's longitudinal axis as shown in, e.g., assemblies **1300** (FIG. **13**) and **1400** (FIG. **14**), instrument/guide tube combination **1806,1808** exits generally aligned with secondary guide tube **1810**'s longitudinal axis **1816**. The distal and intermediate position guide tube face angles may be other than perpendicular to axis **1816**.

FIG. **18** also shows that endoscopic imaging system **1818** is positioned on secondary guide tube **1810** between extreme distal end **1812** and intermediate position **1814**. Imaging system **1818**'s field of view is directed generally perpendicular to longitudinal axis **1816**. During surgery (e.g.,

within a long, narrow space), the surgical site is located within imaging system **1818**'s field of view and instrument/guide tube combinations **1802,1804** and **1806,1808** (working somewhat retrograde from its distal end **1812** exit) are moved to work at the surgical site. Imaging system **1818** is, in some aspects, an electronic stereoscopic image capture system. In some aspects, a second imaging system **1820** (e.g., a monoscopic system with lower resolution than imaging system **1818**) is located to have a field of view generally aligned with axis **1816** to assist instrument assembly **1800** insertion. It can be seen that the architecture illustrated in FIG. **18** allows the guide tube's cross section to be relatively small—enough to accommodate the instruments and/or guide tubes that run through it (see e.g., FIG. **11B** and associated description)—but the imaging system dimensions (e.g., the interpupillary distance in a stereoscopic system) can be larger than if positioned at the guide tube's distal end face.

FIG. **18A** is a schematic view that illustrates further aspects of an imaging system at the distal end of an illustrative instrument assembly **1801**. As shown in FIG. **18A**, one or more instruments and/or instrument/guide tube combinations exit from guide tube **1811**'s intermediate position **1814** as described above. Guide tube **1811**'s distal end segment **1822** is pivotally mounted so that it can be pitched in relation to guide tube **1811**'s main segment as shown by alternate position lines **1823**, although not necessarily pivoting near the intermediate position as depicted. Alternate position **1823** is illustrative of various movements and mechanisms. For example, in one aspect a parallel motion mechanism as described above is used to displace imaging system **1818**. In another example, alternate position **1823** represents positioning and orienting imaging system **1818** with two independently controllable 1 or 2 DOF joints. Other combinations of joints and links may be used. Accordingly, imaging system **1818**'s field of view direction can be altered, space permitting in the surgical site's vicinity. Distal end **1822** may be positioned above the exit ports as shown in FIG. **18A**, or it may be positioned between the exit ports to provide a smaller instrument assembly cross section as illustrated by FIG. **18F**.

FIG. **18B** is another schematic view which shows that an imaging system **1824** may pivot in distal end segment **1822**, as shown by the alternate position lines and arrow. Pivoting imaging system **1824** may be at the extreme distal end of the guide tube, or it may be positioned somewhat proximally from the extreme distal end (in which case in some aspects the second imaging system **1820** can be positioned at the distal end to provide viewing along the instrument assembly's longitudinal axis while imaging system **1824** is viewing to the side).

FIG. **18C** is a diagrammatic perspective view of an embodiment of a minimally invasive surgical instrument assembly that incorporates aspects of instrument assemblies **1800** and **1801**. As shown in FIG. **18C**, two surgical instruments **1830a,1830b**, each with rigid, movable distal links, extend from intermediate position **1832** on guide tube **1834**. Each instrument **1830a,1830b** includes an upper arm link **1836**, a lower arm link **1838**, and an end effector **1840** (illustrative grippers are shown). A shoulder joint **1842** couples upper arm link **1836** to the instrument body (not shown) that extends back through guide tube **1834**. An elbow joint **1844** couples upper arm link **1836** to lower arm link **1838**, and a wrist joint **1846** couples lower arm link **1838** to the end effector **1840**. In some aspects, parallel motion mechanisms as described above with reference to FIGS. **16A-16J** may be used, and in other aspects the

33

shoulder and elbow joints may be independently controlled, as are the wrist joints **1846**. In some aspects only a single arm link is used; in others more than two arm links are used. In some aspects, one or both shoulder joints **1842** are fixed to guide tube **1834** so that there is no associated instrument body.

FIG. **18C** further shows that a stereoscopic imaging system **1850** is mounted near the extreme distal end **1852** of guide tube **1834**. As shown, imaging system **1850** includes right and left image capture elements **1854a, 1854b**, which may be positioned behind protective imaging ports, and illumination output ports (LEDs, optical fiber ends, and/or associated prisms that direct illumination light as desired) **1856**. As described above, imaging system **1850**'s field of view is generally perpendicular to guide tube **1834**'s longitudinal axis so that a surgeon clearly sees end effectors **1840** working at a surgical site to the side of guide tube **1834**'s distal end. And, the axis between the imaging apertures is preferably generally parallel to a line between the surgical instrument tips, an alignment that presents to the surgeon an orientation in which the instrument tips map into natural and comfortable hand positions at the master console. In some aspects, as illustrated in FIG. **18A**, guide tube **1834**'s distal end pivots at a joint **1858** so that imaging system **1850**'s field of view direction can be changed, as described above. Joint **1858** may be positioned at various locations on guide tube **1834**. In one aspect, guide tube **1834** is approximately 12 mm outer diameter, the instruments are approximately 5 mm outer diameter, and imaging system **1850**'s lenses are about 3 mm across with an interpupillary distance of about 5 mm. FIG. **18D** is a diagrammatic perspective view that illustrates how the distal end pitches up and down so that imaging system **1850** can look forwards (toward the distal direction; anterograde viewing) or backwards (toward the proximal direction; retrograde viewing).

As mentioned elsewhere in this description, although many aspects and embodiments are shown and described as having instruments and/or guide tubes that extend through other guide tubes, in other aspects instruments and/or guide tubes may be fixed at the end of, or at intermediate positions on, an instrument assembly structure so as to be integral with that structure. In some aspects, the fixed instruments and/or guide tubes may, however, be replaceable in vitro if the structure is removed from a patient. For example, a surgeon may remove the instrument assembly from the patient, replace one or more instruments that are attached (e.g., using known mechanisms) at the end or at an intermediate position with one or more other instruments, and then reinsert the instrument assembly.

FIG. **18E** is a diagrammatic perspective view of an embodiment of a minimally invasive surgical instrument in which a movable surgical instrument **1860** (e.g., a U-Turn instrument as described below, a flexible arm, a multilink arm, and the like) is fixed at the extreme distal end **1861** of a guide tube **1862**. Thus, the combination of guide tube **1862** and instrument **1860** functions in a manner similar to segments **15a** and **15b** of instrument **15** as shown and described in FIG. **2B**. In addition, a second surgical instrument **1864** is either fixed at an intermediate position **1866** on guide tube **1862** or is removable as described above. And, as described above, an imaging system **1868** with a field of view direction generally perpendicular to guide tube **1862**'s longitudinal axis is positioned near guide tube **1862**'s distal end.

During insertion, in one aspect instrument **1860** is straightened to be generally aligned with the longitudinal axis, and instrument **1864** is either similarly aligned with the

34

longitudinal axis (if fixed; if removably attached) or is at least partially withdrawn into the guide tube. Alternatively, in another aspect instrument **1860** may be retroflexively folded back against guide tube **1862**. An optional second imaging system **1870** positioned at distal end **1861** may be used to assist insertion as described above.

FIG. **18F** is an illustrative diagrammatic plan view of another aspect of a surgical instrument assembly with a movable imaging system at the distal tip of a guide tube. As depicted in FIG. **18F**, an endoscopic image capture component **1880** is at the distal end of parallel motion mechanism **1884**, which is coupled at the distal end of guide tube **1882**. As shown, parallel motion mechanism **1884** has a single DOF in joint space so that it moves image capture component **1880** out of the page, towards the person looking at the figure. In some aspects, parallel motion mechanism may be thinner (between the two instruments) than shown in the figure since it has only one DOF as shown. In other aspects, parallel motion mechanism **1884** may have two DOFs as described above. Alternatively, two independently controllable joints may be used, with each joint generally placed where the hinges are shown in parallel motion mechanism **1884**. In one aspect guide tube **1882** has an oblong cross section, as illustrated by FIG. **11B**.

Additional DOFs may be used to orient image capture component **1880**. For example, FIG. **18G** illustrates that an independent yaw joint **1886** may be placed between parallel motion mechanism **1884** and image capture component **1880**. Joint **1886** is illustrative of various single and multiple DOF joints that may be used (e.g., pitch or pitch/yaw). As illustrated below in FIG. **19J**, in one aspect a flexible arm may be used instead of parallel motion mechanism **1884**. Optics in image capture component **1880** may provide a down looking angle (e.g., 30 degrees).

FIG. **18F** further shows that in one aspect parallel motion mechanism **1884** is long enough to allow the parallel motion mechanisms, wrist mechanisms, and end effectors of independently controllable instruments **1888a** and **1888b** to extend through intermediate position exit ports **1890a** and **1890b** in guide tube **1882** and move while image capture component **1880** is still aligned with the center of guide tube **1882**. When parallel motion mechanism **1884** moves image capture component **1880** away from being aligned with guide tube **1882**, instruments **1888a** and **1888b** can extend underneath image capture component **1880** to reach a surgical site.

FIG. **19** is a diagrammatic perspective view that illustrates aspects of a fifteenth minimally invasive surgical instrument assembly, showing an illustrative distal segment **1900** of the assembly. This assembly **1900**, like some of the variations of assembly **1800** (FIGS. **18-18G**), is primarily intended for surgical work to be performed generally to the side of the assembly rather than in front of its distal end. In the embodiment shown in FIG. **19**, a first surgical instrument **1902**, a second surgical instrument **1904**, and an imaging system **1906** extend through a guide tube **1908**. Various combinations of instruments and imaging systems may be used, either removable or fixed as described above. Surgical instrument **1902** generally works like the various instruments described above, its distal segment **1902a** being rigid or flexible as described. And, instrument **1902** is illustrative of aspects in which is used a primary guide tube and instrument combination as described above. Guide tube **1908** may be rigid or flexible as described above. The surgical instrument bodies are, e.g., about 7 mm in diameter.

The image capture system in imaging system **1906** has a field of view that is generally perpendicular to instrument

assembly **1900**'s longitudinal axis so that the surgeon can work at a site located to the side of the assembly. Imaging system **1906** may translate longitudinally (surge) within a channel defined in guide tube **1908**, may be fixed to the distal end of guide tube **1908**, or may be an integral part of guide tube **1908** as illustrated by aspects of assembly **1800** (FIGS. **18-18G**). In some aspects with a round instrument body, imaging system **1906** may roll within the channel. The round instrument body must be large enough to accommodate, e.g., sensor data wiring (unless a wireless link is used) and an optical fiber illumination bundle. In other aspects the distal end **1912** alone may roll about imaging system **1906**'s longitudinal axis, as shown by the arrows, so as to place the surgical site within the field of view. If the distal end **1912** alone rolls, then an interface allows the sensor data wiring (unless a wireless link is used) and, e.g., power wires or optical fibers for illumination to bend to accommodate the roll.

Surgical instrument **1904** is designed to work primarily in retrograde. As shown in FIG. **19**, the distal segment **1904a** of instrument **1904** is joined to a body segment **1904b** by a U-Turn mechanism **1904c**. Components (such as, e.g., levers, pulleys, gears, gimbals, cables, cable guide tubes, and the like) inside U-turn assembly **1904c** transmit mechanical forces (e.g., from cable or cable/hypotube combinations) around the U-turn (not necessarily 180 degrees as shown; other turn angles may be used) to move distal segment **1904a** and an optional wrist mechanism, and to operate an end effector (not shown). U-Turn mechanism **1904c** is distinguished from flexible mechanical structures because, e.g., it transmits mechanical forces through a radius of curvature that is significantly less than the minimum radius of curvature of equivalently sized flexible mechanical structures. Further, since the U-Turn mechanism does not itself move, the distance between a point where an actuating force enters the U-Turn mechanism and the point where the actuating force exits the U-Turn mechanism is unchangeable. For aspects in which a joint is placed in body segment **1904b** so that it is divided into proximal and distal segments, and if instrument body roll is not transmitted through the joint, then the distal tip **1904d** may be configured to rotate around the distal segment's longitudinal axis.

FIG. **19A** is another diagrammatic perspective view of the embodiment depicted in FIG. **19**, and it illustrates that during surgical work the distal ends of instruments **1902** and **1904** are generally within imaging system **1906**'s field of view to the side of assembly **1900**.

FIGS. **19** and **19A** further show that in some aspects the surgical instrument distal ends are coupled to the main bodies at a single pivot point **1914**. Movement in more than one plane is facilitated by, e.g., a ball and socket type joint as illustrated above in FIG. **18C** (**1842**) and below in FIGS. **19B** and **19C**. In other aspects, joints such as those shown in FIGS. **16A-C** are used. End effectors (not shown) may be coupled directly or via wrist mechanisms at the extreme distal ends **1916**.

FIG. **19B** is a plan view of a surgical instrument assembly embodiment that incorporates a U-turn surgical instrument **1920**. Distal instrument forearm segment **1922** is coupled to instrument main body segment **1924** via U-Turn mechanism **1926** and an illustrative controllable ball joint **1928**. Wrist **1930** (ball and annular segment flexible mechanism is shown for illustration; other wrist mechanisms may be used as described above) couples end effector **1932** to the distal end of forearm segment **1922**. Cables (not shown) that move forearm **1922**, wrist **1930**, and end effector **1932** are routed through individual cable guides in U-Turn mechanism **1926**,

as described in more detail below. The alternate position lines **1934** illustrate that in some instances wrist **1930** can bend at least 135 degrees in three dimensions to enable end effector **1932** to be oriented in various useful ways. An embodiment of such a wrist may incorporate, e.g., three 2-DOF joints of two hinges each, as described above with reference to FIGS. **16A-C**. Each 2-DOF joint allows about 45 degrees of pitch and yaw from being aligned with forearm link **1922**'s longitudinal axis. In some aspects, rather than using the indexed joints as shown, a parallel motion mechanism and wrist combination as described above may be used. The surgical instrument assembly shown in FIG. **19C** also incorporates a second surgical instrument **1936** that operates similarly to instrument **1920**, except that it does not incorporate the U-Turn mechanism.

FIG. **19C** is another plan view of the surgical instrument assembly embodiment shown in FIG. **19B**, with surgical instrument **1920** extended farther out of guide tube **1938**. In FIG. **19B**, the end effectors are working close to and pointing generally at imaging system **1940**. In FIG. **19C**, the end effectors are still working close to imaging system **1940**, but they are now pointing generally perpendicular to imaging system **1940**'s viewing angle. Thus FIG. **19C** illustrates that instrument **1920**'s extension distance from guide tube **1938** may depend on the end effector angle commanded by a master input control. It can also be seen that in some aspects if a command is given to change the end effector's orientation while maintaining its position, then the instrument body and forearm link must be moved to a new pose.

FIG. **19D** is an exploded perspective view that illustrates aspects of routing cables (the term "cable" is illustrative of various filars (herein, the term "filars" should be broadly construed and includes, e.g., single- and multi-strand threads or even very fine hypotubes) that may be used) that control distal instrument components through a U-Turn mechanism. As shown in FIG. **19D**, actuator cables **1950** for, e.g., forearm link **1922**, wrist **1930**, and end effector **1932** run through instrument main body segment **1924** and are routed through individual cable guide tubes **1952**, which route cables **1950** around the U-Turn. The cable guide tubes are, e.g., stainless steel hypotubes. Brace **1954** clamps and therefore stabilizes both ends of the cable guide tubes **1952**. Alternatively, or in addition, the cable guide tubes may be soldered or brazed. An outer cover may cover and protect the cable guide tubes and also any tissue against which the U-Turn instrument may press as it extends from its guide tube. In the embodiment shown, each individual cable guide tube is approximately the same length and has approximately the same bend radius (there are some small differences, as shown in the Figures). The approximately equal length and bend radius tubes make each cable's compliance, a function of diameter and length, approximately the same. Friction depends on the load and total bend angle of each cable.

In this illustrative embodiment, 18 cable guide tubes are shown. To control distal DOFs, the theoretical minimum number of tension cables is DOFs+1. More cables can be used for simplicity, to increase strength or stiffness, or to constrain joint behavior. In an illustrative 5 mm wrist mechanism as shown above, for example, two of the hinges are slaved through cables to two other hinges. In this example, 18 cables would be used to control 4 distal DOFs plus end effector grip. In some embodiments there is no roll control for the wrist mechanism. End effector roll is provided by rolling the instrument body shaft inside the guide

tube. With coordinated movement of the other joints, rolling the instrument body shaft will roll the end effector around its end point.

FIG. 19E is a perspective view of an illustrative embodiment of the cable guide tubes **1952**. A total of 18 cable guide tubes are shown. The cable guide tubes are arranged so as to form a central channel **1955**, through which may be routed control cables for an end effector, surgical implements for suction, irrigation, or electrocautery, and the like. An optional sleeve (not shown) may be inserted within channel **1955** to reduce friction. Other numbers of guide tubes (e.g., 9) may be used.

FIG. 19F is an end elevation view that shows the arrangement of guide tubes **1952** around the central channel **1955**.

FIG. 19G is a perspective view of an illustrative embodiment of an alternate way of routing cables around the U-Turn. Instead of using the multiple cable guide tubes **1952** and brace **1954**, they are constructed as a single part **1956**. Metal casting or rapid metal prototyping is used to make the part, which includes individual channels **1957** through which the cables are routed, and a central channel **1958** through which other components may be routed as discussed above.

FIG. 19H is a perspective view that illustrates aspects of a surgical instrument with a U-Turn mechanism passing through and exiting from a guide tube. A single channel **1960** in guide tube **1962** is shaped to accommodate both the instrument's main body segment **1924** and the retrograde segment **1964** (only the control cables for the retrograde segment are shown; see e.g., FIG. 19B), which is folded back towards the main body segment as the instrument moves within the channel. The channel is pinched in the middle, so that when the U-Turn mechanism and retrograde segment exit the guide tube, the portion of the channel through which the main body segment passes still securely holds the main body segment. The single piece U-Turn part **1956** is also pinched as shown so that they slide within channel **1960**. Once retrograde segment **1964** has exited guide tube **1962**, a second instrument may be inserted through the portion of channel **1960** through which retrograde segment **1964** passed. Various other channel shapes that allow multiple instruments to be inserted through the guide tube are described in more detail below.

FIG. 19I is a perspective view that illustrates that once the U-Turn instrument exits the guide tube it may be rolled within the channel, and then the forearm link can be moved so that the end effector is positioned within the imaging system's field of view. In one aspect, keeping the end effector in position and rolling the instrument body within the guide tube rolls the end effector, as shown by the rotational arrows, because of the nature of the joints.

FIG. 19J is a perspective view that illustrates aspects of a surgical instrument assembly embodiment that uses more than one U-Turn retrograde surgical instrument. Using two U-Turn instruments allows the end effectors to work back closely to the guide tube. In order to provide image capture for the surgeon, an illustrative independent imaging system **1970** is shown with an image capture component **1972** mounted at the end of an illustrative flexible mechanism **1979**. A U-Turn mechanism or a series of rigid links may be used instead of a flexible mechanism. Retroflexing the imaging system allows image capture component **1972**'s field of view to encompass the two U-Turn instrument end effectors. Alternatively, an imaging system **1976** may be positioned at the side of the guide tube if the end effectors are to work generally to the side of the instrument assembly.

FIG. 19K is a plan view that illustrates another aspect of the U-turn mechanism **1990**, which uses small levers, for example, to transmit forces from the main instrument body to the distal forearm link, wrist mechanism, and end effector.

Various cables, wires, rods, hypotubes, and the like, and combinations of these components, may be used in the main body and forearm and are coupled to the force transmission components.

Depending on the location of the surgical work site in relation to the instrument assembly and instruments to be used, illumination for the imaging system may be positioned at various places in side- and retroflexive-working systems. In addition to, or instead of, having one or more illumination output ports near the image capture component as described above, one or more illumination LEDs may be placed on the body of the retroflexive tool. Referring to FIG. 19C, for example, one or more LEDs may be placed at an illustrative position **1942**, along instrument main body segment **1924**. Or, LEDs may be placed along the forearm segment at, e.g., **1938** as shown in FIG. 19B. Likewise, LEDs may be placed at the inner curve of a retroflexing flexible mechanism, such as at positions **1978** shown in FIG. 19J. An advantage of placing additional illumination some distance away from the imaging apertures is that the additional illumination may provide shadows, which provides better depth cues. Illumination near or surrounding the imaging apertures, however, prevents the shadows from becoming so deep that details are not visible in the shadowed areas. Accordingly, in some aspects illumination both near to and far from the imaging apertures is used.

One or more channels, illustrated by dashed lines **1944** (FIG. 19C) or **1980** (FIG. 19J), in the structure on which the LEDs are mounted may carry cooling fluid (e.g., water) past the LEDs. The LED die (or multiple LED die) can be mounted on the obverse side of a thermally conductive substrate (e.g., an aluminum plate, a plated ceramic), which is bonded to the cooling channel so that the reverse side of the substrate is exposed to the cooling flow. Techniques for bonding LEDs to substrates are well known and can be adapted for use with liquid cooling. The cooling fluid may circulate in a closed system, or it may empty either inside or outside the patient. For an open cooling system that empties into the patient, a sterile, biocompatible fluid (e.g., sterile isotonic saline) is used. Suction may be used to remove the cooling fluid from the patient. In addition, the cooling fluid discharged into the patient may be used to perform other functions. For example, the discharged cooling fluid may be directed across the imaging lenses. The fluid may clean the lenses or prevent body fluids, smoke, or surgical debris from sticking to the lenses.

The amount of cooling fluid to keep an LED within an acceptable temperature range is fairly small. For example, an LED that dissipates about 4 Watts of electrical power as heat can be cooled with a flow of about 0.1 cc/sec of water through 0.020-inch OD plastic tubing (e.g., 12 feet total length; 6 feet supply and 6 feet return), and the water will experience only about a 10-degree Celsius temperature rise.

The use of LEDs as described above is an example of alternative illumination placement on the instruments. In some aspects, fiber light guides may be used, in which case cooling considerations do not apply.

As discussed above, in some aspects the cross-sectional area of a guide tube must accommodate instruments which themselves have distal portions with a relatively large cross-sectional area. In order to minimize the guide tube's cross-sectional area, in one aspect more than one instrument is inserted through a single specially shaped channel.

FIG. 20A is an end elevation view of the distal end face of illustrative guide tube **2002**. Guide tube **2002**'s lateral cross section is similarly configured (i.e., the channels depicted extend through the entire guide tube). As shown in FIG. 20A, guide tube **2002** has three channels (more or fewer channels may be used). Channel **2004** accommodates an endoluminal imaging system and may have various cross-sectional shapes (e.g., round, oval, rounded polygon, etc.). The shape illustrated in FIG. 20A is a circle overlaid and centered on a rounded rectangle. The circular bore **2004a** of channel **2004** accommodates the imaging system's body (illustrated by dashed lines), and the slots **2004b** (the ends of the rounded rectangle) on either side of the circular bore **2004a** allow the image capture element, which is wider than the cylindrical body segment, to pass through channel **2004**. Since the circular bore **2004a** has a slightly larger diameter than slots **2004b** (the channel **2004** cross section is an oblong, biconvex shape), the imaging system's body segment is held in place within channel **2004** after the image capture element exits guide tube **2002**'s distal end.

Channel **2006**, depicted as a single, circular bore, is an optional auxiliary channel and may be used for irrigation, suction, small (e.g., 3 mm diameter) instruments, etc.

Channel **2008** is uniquely shaped to simultaneously accommodate two surgical instruments in which one has a distal end segment larger than its body segment, such as instruments **1902** and **1904** (FIG. 19). As shown in FIG. 20A, channel **2008**'s cross-sectional shape is generally oblong with a pinched center across the major axis (the cross section is an oblong, biconcave shape). Channel **2008** includes two cylindrical bores **2008a**, **2008b** through which cylindrical instrument bodies are inserted. The bores **2008a**, **2008b** are interconnected by a slot **2008c**. As an instrument body (illustrated by the circular dashed line **2009a**) is inserted through bore **2008a**, for example, the instrument's distal portion, which is larger than its proximal body segment, passes through at least part of slot **2008c** and possibly some or all of bore **2008b**. FIG. 19H illustrates this aspect. Once the instrument's distal portion has been inserted beyond the guide tube's distal end, the instrument's proximal body segment is rotated within bore **2008a**, which holds the proximal body segment in place. Consequently, another instrument (illustrated by the circular dashed line **2009b**), either cylindrical or with an enlarged distal portion that fits through slot **2008c**, can be inserted through bore **2008b**. This channel configuration and insertion process can be used for various instruments with odd-shaped distal portions, such as staplers, clip applicators, and other special task instruments, as well as for the retrograde working instruments described herein. In addition, an imaging device having a distal image capture component cross section larger than its body cross section and shaped to pass through the channel's oblong cross section may be similarly inserted, followed by one or more other instruments. The lip **2011** of channel **2008**, or any channel, is in some instances rounded or beveled as shown to facilitate instrument withdrawal into the guide tube.

FIG. 20B is an end elevation view of the distal end face of guide tube **2002** with an illustrative imaging system **2010** and two surgical instruments **2012**, **2014**, all extending from their insertion channels **2004**, **2008**. Instrument **2012** is a U-Turn mechanism type retrograde working instrument, similar to the illustrative embodiment shown in FIGS. 19 and 19A. Instrument **2014** is generally circular in cross section during insertion, although during insertion a portion of instrument **2014** may extend into any portion of slot **2008c** that instrument **2012** does not occupy. As another

example, an instrument with the multiple cable guide tube U-Turn mechanism, similar to the embodiments shown in FIGS. 19B-19I, may be inserted through channel **2008**, with the body and distal portions of the instrument passing through the bores and the pinched portion of the U-Turn mechanism passing through the slot between the bores.

The channel topography illustrated in FIG. 20A can be adapted to allow, e.g., two instruments with large distal ends to be inserted through a guide tube, possibly adding a third instrument as well. FIG. 20C is an end elevation view that illustrates aspects in which an instrument channel includes bores arranged in a "V" shape, although the "V" may be flattened so that three or more channel bores are side-by-side in a line. As shown, channel **2020** includes three cylindrical bores **2020a**, **2020b**, **2020c**, with slot **2020d** joining bores **2020a** and **2020b**, and slot **2020e** joining bores **2020b** and **2020c**. Bores **2020a** and **2020c** are shown at the ends of the "V" shape, and bore **2020b** is shown at the vertex of the "V" shape. Illustratively, a first retrograde working instrument with a U-Turn mechanism is inserted via bores **2020a** and **2020b**, and then a second retrograde working instrument with a U-Turn mechanism is inserted via bores **2020c** and **2020b**. Once inserted, the three bores allow either of the instruments to be independently removed—one instrument does not have to be removed to allow the other instrument to be removed. An optional third instrument may be inserted via bore **2020b** once two other instruments are inserted with their proximal body segments held in place within bores **2020a** and **2020c**. It can be seen that two large-ended instruments and an optional third instrument may be inserted via channel **2020** in various combinations. An imaging system may be inserted via channel **2022**, which may be a rounded rectangle as shown, circular, or various other shapes as illustrated herein (e.g., **2004** in FIG. 20A). Alternatively, if an imaging system has a suitably shaped distal end, it may be inserted via channel **2020**. An assembly with two retrograde working instruments and an imaging system is illustrated in FIG. 19J.

FIGS. 20D, 20E, and 20F are each end elevation views that illustrate aspects of other channel configurations that may be used to accommodate one or more instruments with large distal ends. FIG. 20D shows channel **2030** with three bores **2030a**, **2030b**, **2030c** in a triangular arrangement. The slots that interconnect adjacent bores merge into a single opening that connects each bore with the other two (i.e., the top of the "V" shape illustrated in FIG. 20C is joined by a third slot. The channel has a generally triangular cross section, and the bores are at the triangle's vertices). Also shown is an illustrative spacer **2032**, shown centered in channel **2030**, which helps keep the instrument bodies in their bores or positioned at their vertexes if the channel sides between the bores are not sufficiently pinched to hold the instrument bodies in place within the bores. FIG. 20E illustrates that the channel can have any number of bores to accept surgical instruments (four are shown with the bores arranged at the corners of a square). FIG. 20F illustrates a channel with a "T" shape, the bores for the instruments being the three ends of the "T". A spacer such as shown in FIG. 20D may be used to keep instruments properly positioned within the "T", or the connecting openings between the bores may be slightly pinched to keep the instruments in their bores. Other cross-sectional channel shapes (e.g., a cross or "X" shape; it can be seen that a "T" shape is part of such a cross or "X" shape) may be used with a cross-sectional configuration or a separate component that keeps a surgical instrument's body or shaft in place within the channel.

In FIGS. 20A-20F, the bores that hold the proximal segments of the instrument and imaging system bodies are shown as circular, which allows the bodies to roll within the bores. In some aspects, however, some or all the bores may have non-circular cross sections to prevent the body segments from rolling within the bores. For example, one non-circular bore may be dedicated to holding the proximal body segment of an imaging system, which is kept from rolling. Or, specifically shaped bores may be used to ensure that only a particular device may be inserted into a particular bore. In some aspects, however, any surgical instrument or imaging system may be inserted via any bore.

Support and Control Aspects

FIG. 21A is a schematic view that illustrates aspects of a robot-assisted (telem manipulative) minimally invasive surgical system that uses aspects of the minimally invasive surgical instruments, instrument assemblies, and manipulation and control systems described herein. This system's general architecture is similar to the architecture of other such systems such as Intuitive Surgical, Inc.'s da Vinci® Surgical System and the Zeus® Surgical System. The three main components are a surgeon's console 2102, a patient side support system 2104, and a video system 2106, all interconnected 2108 by wired or wireless connections as shown. One or more electronic data processors may be variously located in these main components to provide system functionality.

The surgeon's console 2102 includes, e.g., multiple DOF mechanical input ("master") devices that allow the surgeon to manipulate the surgical instruments, guide tubes, and imaging system ("slave") devices as described herein. These input devices may in some aspects provide haptic feedback from the instruments and instrument assembly components to the surgeon. Console 2102 also includes a stereoscopic video output display positioned such that images on the display are generally focused at a distance that corresponds to the surgeon's hands working behind/below the display screen. These aspects are discussed more fully in U.S. Pat. No. 6,671,581, which is incorporated by reference above. Control during insertion may be accomplished, for example, in a manner similar to telem manipulated endoscope control in the da Vinci® Surgical System—in one aspect the surgeon virtually moves the image with one or both of the masters; she uses the masters to move the image side to side and to pull it towards herself, consequently commanding the imaging system and its associated instrument assembly (e.g., a flexible guide tube) to steer towards a fixed center point on the output display and to advance inside the patient. In one aspect the camera control is designed to give the impression that the masters are fixed to the image so that the image moves in the same direction that the master handles are moved, as in the da Vinci® surgical system. This design causes the masters to be in the correct location to control the instruments when the surgeon exits from camera control, and consequently it avoids the need to clutch (disengage), move, and declutch (engage) the masters back into position prior to beginning or resuming instrument control. In some aspects the master position may be made proportional to the insertion velocity to avoid using a large master workspace. Alternatively, the surgeon may clutch and declutch the masters to use a ratcheting action for insertion. In some aspects, insertion (e.g., past the glottis when entering via the esophagus) may be controlled manually (e.g., by hand operated wheels), and automated insertion (e.g., servomotor driven rollers) is then done when the distal end of the surgical instrument assembly is near the surgical site. Pre-operative or real time image data (e.g., MRI, X-ray) of the

patient's anatomical structures and spaces available for insertion trajectories may be used to assist insertion.

The patient side support system 2104 includes a floor-mounted base 2110, or alternately a ceiling mounted base 2112 as shown by the alternate lines. The base may be movable or fixed (e.g., to the floor, ceiling, or other equipment such as an operating table). In one embodiment the manipulator arm assembly is a modified da Vinci® Surgical System arm assembly. The arm assembly includes two illustrative passive rotational setup joints 2114a, 2114b, which allow manual positioning of the coupled links when their brakes are released. A passive prismatic setup joint (not shown) between the arm assembly and the base may be used to allow for large vertical adjustments. In addition, the arm assembly includes illustrative active roll joint 2116a and active yaw joint 2116b. Joints 2116c and 2116d act as a parallel mechanism so that a guide tube (of a surgical instrument assembly) held by guide manipulator 2118 moves around remote center 2120 at an entry port, such as patient 1222's umbilicus. An active prismatic joint 2124 is used to insert and withdraw the guide tube. One or more surgical instruments and an endoscopic imaging system are independently mounted to guide manipulator 2118. The various setup and active joints allow the manipulators to move the guide tube, instruments, and imaging system when patient 2122 is placed in various positions on movable table 2126.

FIGS. 21B and 21C are schematic side and front elevation views of another illustrative embodiment of a patient side support system. Base 2150 is fixed (e.g., floor or ceiling mounted). Link 2152 is coupled to base 2150 at passive rotational setup joint 2154. As shown, joint 2154's rotational axis is aligned with remote center point 2156, which is generally the position at which a guide tube (of a surgical instrument assembly; not shown) enters the patient (e.g., at the umbilicus for abdominal surgery). Link 2158 is coupled to link 2152 at rotational joint 2160. Link 2162 is coupled to link 2158 at rotational joint 2164. Link 2166 is coupled to link 2162 at rotational joint 2168. The guide tube is mounted to slide through the end 2166a of link 2166. Manipulator platform 2170 is supported and coupled to link 2166 by a prismatic joint 2172 and a rotational joint 2174. Prismatic joint 2172 inserts and withdraws the guide tube as it slides along link 2166. Joint 2174 includes a bearing assembly that holds a "C" shaped ring cantilever. As the "C" ring slides through the bearing it rotates around a center point inside the "C", thereby rolling the guide tube. The opening in the "C" allows guide tubes to be mounted or exchanged without moving overlying manipulators. Manipulator platform 2170 supports multiple manipulators 2176 for surgical instruments and an imaging system, described below.

These illustrative manipulator arm assemblies are used, for example, for instrument assemblies that include a rigid guide tube and are operated to move with reference to a remote center. Certain setup and active joints in the manipulator arm may be omitted if motion around a remote center is not required. It should be understood that manipulator arms may include various combinations of links, passive, and active joints (redundant DOFs may be provided) to achieve a necessary range of poses for surgery.

Referring again to FIG. 21A, video system 2106 performs image processing functions for, e.g., captured endoscopic imaging data of the surgical site and/or preoperative or real time image data from other imaging systems external to the patient. Imaging system 2106 outputs processed image data (e.g., images of the surgical site, as well as relevant control

and patient information) to the surgeon at the surgeon's console **2102**. In some aspects the processed image data is output to an optional external monitor visible to other operating room personnel or to one or more locations remote from the operating room (e.g., a surgeon at another location may monitor the video; live feed video may be used for training; etc.).

FIG. **22A** is a diagrammatic view that illustrates aspects of a centralized motion control and coordination system architecture for minimally invasive telesurgical systems that incorporate surgical instrument assemblies and components described herein. A motion coordinator system **2202** receives master inputs **2204**, sensor inputs **2206**, and optimization inputs **2208**.

Master inputs **2204** may include the surgeon's arm, wrist, hand, and finger movements on the master control mechanisms. Inputs may also be from other movements (e.g., finger, foot, knee, etc. pressing or moving buttons, levers, switches, etc.) and commands (e.g., voice) that control the position and orientation of a particular component or that control a task-specific operation (e.g., energizing an electrocautery end effector or laser, imaging system operation, and the like).

Sensor inputs **2206** may include position information from, e.g., measured servomotor position or sensed bend information. U.S. patent application Ser. No. 11/491,384 (Larkin, et al.) entitled "Robotic surgery system including position sensors using fiber Bragg gratings", incorporated by reference, describes the use of fiber Bragg gratings for position sensing. Such bend sensors may be incorporated into the various instruments and imaging systems described herein to be used when determining position and orientation information for a component (e.g., an end effector tip). Position and orientation information may also be generated by one or more sensors (e.g., fluoroscopy, MRI, ultrasound, and the like) positioned outside of the patient, and which in real time sense changes in position and orientation of components inside the patient.

As described below, the user interface has three coupled control modes: a mode for the instrument (s), a mode for the imaging system, and a mode for the guide tube. These coupled modes enable the user to address the system as a whole rather than directly controlling a single portion. Therefore, the motion coordinator must determine how to take advantage of the overall system kinematics (i.e., the total DOFs of the system) in order to achieve certain goals. For example, one goal may be to optimize instrument workspace for a particular configuration. Another goal may be to keep the imaging system's field of view centered between two instruments. Therefore, optimization inputs **2208** may be high-level commands, or the inputs may include more detailed commands or sensory information. An example of a high level command would be a command to an intelligent controller to optimize a workspace. An example of a more detailed command would be for an imaging system to start or stop optimizing its camera. An example of a sensor input would be a signal that a workspace limit had been reached.

Motion coordinator **2202** outputs command signals to various actuator controllers and actuators (e.g., servomotors) associated with manipulators for the various telesurgical system arms. FIG. **22A** depicts an example of output signals being sent to two instrument controllers **2210**, to an imaging system controller **2212**, and to a guide tube controller **2214**. Other numbers and combinations of controllers may be used.

As an example, such a motion coordination system may be used to control surgical instrument assembly **1700** (FIG. **17**). Instrument controllers **2210** are associated with instruments **1702a, 1702b**, imaging system controller **2212** is associated with imaging system **1704**, and guide tube controller **2214** is associated with guide tube **1708**. Accordingly, in some aspects the surgeon who operates the telesurgical system will simultaneously and automatically access at least the three control modes identified above: an instrument control mode for moving the instruments, an imaging system control mode for moving the imaging system, and a guide tube control mode for moving the guide tube. A similar centralized architecture may be adapted to work with the various other mechanism aspects described herein.

FIG. **22B** is a diagrammatic view that illustrates aspects of a distributed motion control and coordination system architecture for minimally invasive telesurgical systems that incorporate surgical instrument assemblies and components described herein. In the illustrative aspects shown in FIG. **22B**, control and transform processor **2220** exchanges information with two master arm optimizer/controllers **2222a, 2222b**, with three surgical instrument optimizer/controllers **2224a, 2224b, 2224c**, with an imaging system optimizer/controller **2226**, and with a guide tube optimizer/controller **2228**. Each optimizer/controller is associated with a master or slave arm (which includes, e.g., the camera (imaging system) arm, the guide tube arm, and the instrument arms) in the telesurgical system. Each of the optimizer/controllers receives arm-specific optimization goals **2230a-2230g**.

The double-headed arrows between control and transform processor **2220** and the various optimizer/controllers represents the exchange of Following Data associated with the optimizer/controller's arm. Following Data includes the full Cartesian configuration of the entire arm, including base frame and distal tip frame. Control and transform processor **2220** routes the Following Data received from each optimizer/controller to all the optimizer/controllers so that each optimizer/controller has data about the current Cartesian configuration of all arms in the system. In addition, the optimizer/controller for each arm receives optimization goals that are unique for the arm. Each arm's optimizer/controller then uses the other arm positions as inputs and constraints as it pursues its optimization goals. In one aspect, each optimization controller uses an embedded local optimizer to pursue its optimization goals. The optimization module for each arm's optimizer/controller can be independently turned on or off. For example, the optimization module for only the imaging system and the guide tube may be turned on.

The distributed control architecture provides more flexibility than the centralized architecture, although with the potential for decreased performance. It is easier to add in a new arm and to change the overall system configuration if such a distributed control architecture is used rather than if a centralized architecture is used. In this distributed architecture, however, the optimization is local versus the global optimization that can be performed with the centralized architecture, in which a single module is aware of the full system's state.

FIG. **23** is a schematic view that illustrates aspects of an interface between surgical instrument assembly **2302**, which represents flexible and rigid mechanisms as variously described herein, and an illustrative actuator assembly **2304**. For the purposes of this example, instrument assembly **2302** includes surgical instrument **2306**, primary guide tube **2308** that surrounds instrument **2306**, and secondary guide tube **2310** that surrounds primary guide tube **2308**.

As shown in FIG. 23, a transmission mechanism is positioned at the proximal ends of each instrument or guide tube: transmission mechanism **2306a** for instrument **2306**, transmission mechanism **2308a** for primary guide tube **2308**, and transmission mechanism **2310a** for secondary guide tube **2310**. Each transmission mechanism is mechanically and removably coupled to an associated actuator mechanism: transmission mechanism **2306a** to actuator mechanism **2312**, transmission mechanism **2308a** to actuator mechanism **2314**, transmission mechanism **2310a** to actuator mechanism **2316**. In one aspect, mating disks are used as in the da Vinci® Surgical System instrument interface, as shown in more detail below. In another aspect, mating gimbal plates and levers are used. Various mechanical components (e.g., gears, levers, cables, pulleys, cable guides, gimbals, etc.) in the transmission mechanisms are used to transfer the mechanical force from the interface to the controlled element. Each actuator mechanism includes at least one actuator (e.g., servomotor (brushed or brushless)) that controls movement at the distal end of the associated instrument or guide tube. For example, actuator **2312a** is an electric servomotor that controls surgical instrument **2306**'s end effector **2306b** grip DOF. An instrument (including a guide probe as described herein) or guide tube (or, collectively, the instrument assembly) may be decoupled from the associated actuator mechanism(s) and slid out as shown. It may then be replaced by another instrument or guide tube. In addition to the mechanical interface there is an electronic interface between each transmission mechanism and actuator mechanism. This electronic interface allows data (e.g., instrument/guide tube type) to be transferred.

In some instances one or more DOFs may be manually actuated. For instance, surgical instrument **2306** may be a passively flexible laparoscopic instrument with a hand-actuated end effector grip DOF, and guide tube **2308** may be actively steerable to provide wrist motion as described above. In this example, the surgeon servocontrols the guide tube DOFs and an assistant hand controls the instrument grip DOF.

In addition to the actuators that control the instrument and/or guide tube elements, each actuator assembly may also include an actuator component (e.g., motor-driven cable, lead screw, pinion gear, etc.; linear motor; and the like) that provides motion along instrument assembly **2302**'s longitudinal axis (surge). As shown in the FIG. 23 example, actuator mechanism **2312** includes linear actuator **2312b**, actuator mechanism **2314** includes linear actuator **2314b**, and actuator mechanism **2316** includes linear actuator **2316b**, so that instrument **2306**, primary guide tube **2308**, and secondary guide tube **2310** can each be independently coaxially moved. As further shown in FIG. 23, actuator assembly **2316** is mounted to setup arm **2318**, either passively or actively as described above. In active mounting architectures, the active mounting may be used to control one or more component DOFs (e.g., insertion of a rigid guide tube).

Control signals from control system **2320** control the various servomotor actuators in actuator assembly **2304**. The control signals are, e.g., associated with the surgeon's master inputs at input/output system **2322** to move instrument assembly **2302**'s mechanical slave components. In turn, various feedback signals from sensors in actuator assembly **2304**, and/or instrument assembly **2302**, and/or other components are passed to control system **2320**. Such feedback signals may be pose information, as indicated by servomotor position or other position, orientation, and force information, such as may be obtained with the use of fiber

Bragg grating-based sensors. Feedback signals may also include force sensing information, such as tissue reactive forces, to be, e.g., visually or haptically output to the surgeon at input/output system **2322**.

Image data from an endoscopic imaging system associated with instrument assembly **2302** are passed to image processing system **2324**. Such image data may include, e.g., stereoscopic image data to be processed and output to the surgeon via input/output system **2322** as shown. Image processing may also be used to determine instrument position, which is input to the control system as a form of distal position feedback sensor. In addition, an optional sensing system **2326** positioned outside and near the patient may sense position or other data associated with instrument assembly **2302**. Sensing system **2326** may be static or may be controlled by control system **2320** (the actuators are not shown, and may be similar to those depicted or to known mechanical servo components), and it may include one or more actual sensors positioned near the patient. Position information (e.g., from one or more wireless transmitters, RFID chips, etc.) and other data from sensing system **2326** may be routed to control system **2320**. If such position information or other data is to be visually output to the surgeon, control system **2320** passes it in either raw or processed form to image processing system **2324** for integration with the surgeon's output display at input/output system **2322**. Further, any image data, such as fluoroscopic or other real-time imaging (ultrasound, X-ray, MRI, and the like), from sensing system **2326** are sent to image processing system **2324** for integration with the surgeon's display. And, real-time images from sensing system **2326** may be integrated with preoperative images accessed by image processing system **2324** for integration with the surgeon's display. In this way, for instance, preoperative images of certain tissue (e.g., brain tissue structures) are received from a data storage location **2328**, may be enhanced for better visibility, the preoperative images are registered with other tissue landmarks in real time images, and the combined preoperative and real time images are used along with position information from instrument and actuator assemblies **2302**, **2304** and/or sensing system **2326** to present an output display that assists the surgeon to maneuver instrument assembly **2302** towards a surgical site without damaging intermediate tissue structures.

FIG. 24A is a perspective view of the proximal portion of a minimally invasive surgical instrument **2402**. As shown in FIG. 24A, instrument **2402** includes a transmission mechanism **2404** coupled to the proximal end of an instrument body tube **2406**. Components at body tube **2406**'s distal end **2408** are omitted for clarity and may include, e.g., the 2 DOF parallel motion mechanism, wrist, and end effector combination as described above; joints and an endoscopic imaging system as described above; etc. In the illustrative embodiment shown, transmission mechanism **2404** includes six interface disks **2410**. One or more disks **2410** are associated with a DOF for instrument **240**. For instance, one disk may be associated with instrument body roll DOF, and a second disk may be associated with end effector grip DOF. As shown, in one instance the disks are arranged in a hexagonal lattice for compactness—in this case six disks in a triangular shape. Other lattice patterns or more arbitrary arrangements may be used. Mechanical components (e.g., gears, levers, gimbals, cables, etc.) inside transmission mechanism **2404** transmit roll torques on disks **2410** to e.g., body tube **2406** (for roll) and to components coupled to distal end mechanisms. Cables and/or cable and hypotube combinations that control distal end DOFs run through body tube **2406**. In one

instance the body tube is approximately 7 mm in diameter, and in another instance it is approximately 5 mm in diameter. Raised pins **2412**, spaced eccentrically, provide proper disk **2410** orientation when mated with an associated actuator disk. One or more electronic interface connectors **2414** provide an electronic interface between instrument **2402** and its associated actuator mechanism. In some instances instrument **2402** may pass information stored in a semiconductor memory integrated circuit to the control system via its associated actuator mechanism. Such passed information may include instrument type identification, number of instrument uses, and the like. In some instances the control system may update the stored information (e.g., to record number of uses to determine routine maintenance scheduling or to prevent using an instrument after a prescribed number of times). U.S. Pat. No. 6,866,671 (Tierney et al.), which discusses storing information on instruments, is incorporated by reference. The electronic interface may also include power for, e.g., an electrocautery end effector. Alternately, such a power connection may be positioned elsewhere on instrument **2402** (e.g., on transmission mechanism **2404**'s housing). Other connectors for, e.g., optical fiber lasers, optical fiber distal bend or force sensors, irrigation, suction, etc. may be included. As shown, transmission mechanism **2404**'s housing is roughly wedge- or pie-shaped to allow it to be closely positioned to similar housings, as illustrated below.

FIG. **24B** is a perspective view of a portion of an actuator assembly **2420** that mates with and actuates components in surgical instrument **2402**. Actuator disks **2422** are arranged to mate with interface disks **2410**. Holes **2424** in disks **2422** are aligned to receive pins **2412** in only a single 360-degree orientation. Each disk **2422** is turned by an associated rotating servomotor actuator **2426**, which receives servo-control inputs as described above. A roughly wedge-shaped mounting bracket **2428**, shaped to correspond to instrument **2402**'s transmission mechanism housing, supports the disks **2422**, servomotor actuators **2426**, and an electronic interface **2430** that mates with instrument **2402**'s interface connectors **2414**. In one instance instrument **2402** is held against actuator assembly **2420** by spring clips (not shown) to allow easy removal. As shown in FIG. **24B**, a portion **2432** of actuator assembly housing **2428** is truncated to allow instrument body tube **2406** to pass by. Alternatively, a hole may be placed in the actuator assembly to allow the body tube to pass through. Sterilized spacers (reusable or disposable; usually plastic) may be used to separate the actuator assembly and the instrument's transmission mechanism to maintain a sterile surgical field. A sterile thin plastic sheet or "drape" (e.g., 0.002-inch thick polyethylene) is used to cover portions of the actuator assembly not covered by the spacer, as well as to cover portions of the manipulator arm. U.S. Pat. No. 6,866,671, incorporated by reference above, discusses such spacers and drapes.

FIG. **25A** is a diagrammatic perspective view that illustrates aspects of mounting minimally invasive surgical instruments and their associated actuator assemblies at the end of a setup/manipulator arm. As shown in FIG. **25A**, surgical instrument **2502a** is mounted on actuator assembly **2504**, so that the transmission mechanism mates with the actuator assembly (optional spacer/drape is not shown) as described above. Instrument **2502a**'s body tube **2506** extends past actuator assembly **2504** and enters a port in rigid guide tube **2508**. As depicted, body tube **2506**, although substantially rigid, is bent slightly between the transmission mechanism housing and the guide tube as discussed above with reference to FIG. **16**. This bending

allows the instrument body tube bores in the entry guide to be spaced closer than the size of their transmission mechanisms would otherwise allow. Since the bend angle in the rigid instrument body tube is less than the bend angle for a flexible (e.g., flaccid) instrument body, cables can be stiffer than in a flexible body. High cable stiffness is important because of the number of distal DOFs being controlled in the instrument. Also, the rigid instrument body is easier to insert into a guide tube than a flexible body. In one embodiment the bending is resilient so that the body tube assumes its straight shape when the instrument is withdrawn from the guide tube (the body tube may be formed with a permanent bend, which would prevent instrument body roll). Actuator assembly **2504** is mounted to a linear actuator **2510** (e.g. a servocontrolled lead screw and nut or a ball screw and nut assembly) that controls body tube **2506**'s insertion within guide tube **2508**. The second instrument **2502b** is mounted with similar mechanisms as shown. In addition, an imaging system (not shown) may be similarly mounted.

FIG. **25A** further shows that guide tube **2508** is removably mounted to support platform **2512**. This mounting may be, for example, similar to the mounting used to hold a cannula on a da Vinci® Surgical System manipulator arm. Removable and replaceable guide tubes allow different guide tubes that are designed for use with different procedures to be used with the same telemanipulative system (e.g., guide tubes with different cross-sectional shapes or various numbers and shapes of working and auxiliary channels). In turn, actuator platform **2512** is mounted to robot manipulator arm **2514** (e.g., 4 DOF) using one or more additional actuator mechanisms (e.g., for pitch, yaw, roll, insertion). In turn, manipulator arm **2514** may be mounted to a passive setup arm, as described above with reference to FIG. **21A**.

FIG. **25B** is a diagrammatic perspective view that illustrates aspects shown in FIG. **25A** from a different angle and with reference to a patient. In FIG. **25B**, arm **2514** and platform **2512** are positioned so that guide tube **2508** enters the patient's abdomen at the umbilicus. This entry is illustrative of various natural orifice and incision entries, including percutaneous and transluminal (e.g., transgastric, transcolonic, transrectal, transvaginal, transrectouterine (Douglas pouch), etc.) incisions. FIG. **25B** also illustrates how the linear actuators for each instrument/imaging system operate independently by showing imaging system **2518** inserted and instruments **2502a, 2502b** withdrawn. These aspects may apply to other surgical instrument assemblies described herein (e.g., flexible guide tubes with end- or side-exit ports, side working tools, etc.). It can be seen that in some instances the manipulator arm moves to rotate guide tube **2508** around a remote center **2520** at the entry port into a patient. If intermediate tissue restricts movement around a remote center, however, the arm can maintain guide tube **2508** in position.

As discussed above, in one aspect the instruments and their transmission mechanisms are arranged around a guide tube in a generally pie-wedge layout as shown in FIG. **26A**, which is a diagrammatic end view of instrument transmission mechanisms and a guide tube (the vertices of the wedge shapes are oriented towards an extended centerline of the guide tube). The vertices of the wedge shapes are shown slightly truncated; the wedge shape should be understood to be broadly construed and to include both acute and obtuse vertex angles. Instrument transmission mechanisms **2602a, 2602b** transfer control forces from servomotors to instruments inserted via guide tube **2604**'s working channels **2606a, 2606b**. Imaging system transmission mechanism **2608** transfers control forces from servomotors to the multi-

DOF imaging system instrument inserted via guide tube **2604**'s imaging system channel **2606c**. One or more optional guide tube channels **2604d** allow for manually inserting an instrument, irrigation, suction, etc. FIGS. **26B** and **26C** are similar diagrammatic end views and illustrate that transmission mechanisms may be spaced around the guide tube in other configurations, such as four wedges **2608** spaced 360-degrees around the guide tube (FIG. **26B**), or two half-circle shaped housings **2610** (FIG. **26C**). It can also be seen from the aspects illustrated in FIGS. **25A**, **25B**, **26A**, **26B**, and **26C** that transmission assemblies can not only be spaced around the guide tube but can be stacked one above or behind the other as FIG. **23** schematically illustrates. FIG. **26D** is another diagrammatic end view that illustrates that actuator mechanisms **2620** may be placed farther from guide tube **2622**'s extended centerline than the instrument/guide tube and imaging system transmission mechanisms **2624**.

FIG. **26E** is a diagrammatic exploded perspective view that illustrates that actuator mechanisms for more than one component may be placed in a single housing. As shown in FIG. **26E**, actuator mechanism housing **2630** includes servomotors and associated components (not shown) used to move guide tube **2632**. Housing **2630** also includes servomotors and associated components used to operate instrument **2634**. Instrument **2634**'s body and distal segments are inserted through housing **2630** as shown, and interface components **2636** on housing **2630** connect with corresponding components (e.g., disks **2410** (FIG. **24**)) on instrument **2634**. Such an arrangement may be used for, e.g., the side exit surgical instrument assemblies described herein, in which there are two housings **2634**, each associated with one of the side exiting instruments or guide tubes.

Details about the mechanical and electrical interfaces for the various instruments, guide tubes, and imaging systems, and also about sterile draping to preserve the sterile field, are discussed in U.S. Pat. No. 6,866,671 (Tierney et al.) and U.S. Pat. No. 6,132,368 (Cooper), both of which are incorporated by reference. Mechanical interface mechanisms are not limited to the disks shown and described. Other mechanisms such as rocking plates, gimbals, moving pins, levers, cable latches, and other removable couplings may be used.

FIG. **27** is a diagrammatic view that illustrates aspects of transmission mechanisms associated with flexible coaxial guide tubes and instruments. FIG. **27** shows primary guide tube **2702** running coaxially through and exiting the distal end of secondary guide tube **2704**. Likewise, secondary guide tube **2704** runs coaxially through and exits the distal end of tertiary guide tube **2706**. Transmission and actuator mechanism **2708** is associated with tertiary guide tube **2706**. Transmission and actuator mechanism **2710** is associated with secondary guide tube **2704**, and a proximal segment of guide tube **2704** extends through (alternatively, adjacent to) transmission and actuator mechanism **2710** before entering tertiary guide tube **2706**. Likewise, transmission and actuator mechanism **2712** is associated with primary guide tube **2702**, and a proximal segment of guide tube **2702** extends through (alternatively, adjacent to) transmission and actuator mechanisms **2708**, **2710** before entering secondary and tertiary guide tubes **2704**, **2706**. Transmission mechanisms for instruments and an imaging system (not shown) running through and exiting the distal ends of channels **2714** in primary guide tube **2702** may be similarly stacked generally along the instrument assembly's longitudinal axis, or they may be arranged around guide tube **2702**'s extended longitudinal axis at its proximal end as described above. Or, the controller positions may be combined side-by-side and stacked, such as for a side-exit assembly in which transmis-

sion mechanisms for the side-exiting components are positioned side-by-side, and both are stacked behind the guide tube transmission mechanism. Intermediate exit assemblies may be similarly configured. Instrument and/or imaging system actuators and controls may also be combined within the same housing as an actuator and transmission mechanism for a guide tube.

In many aspects the devices described herein are used as single-port devices—all components necessary to complete a surgical procedure enter the body via a single entry port. In some aspects, however, multiple devices and ports may be used. FIG. **28A** is a diagrammatic view that illustrates multi-port aspects as three surgical instrument assemblies enter the body at three different ports. Instrument assembly **2802** includes a primary guide tube, a secondary guide tube, and two instruments, along with associated transmission and actuator mechanisms, as described above. In this illustrative example, instrument assembly **2804** includes a primary guide tube, a secondary guide tube, and a single instrument, along with associated transmission and actuator mechanisms, as described above. Imaging system assembly **2806** includes a guide tube and an imaging system, along with associated transmission and actuator mechanisms, as described above. Each of these mechanisms **2802**, **2804**, **2806** enters the body **2808** via a separate, unique port as shown. The devices shown are illustrative of the various rigid and flexible aspects described herein.

FIG. **28B** is another diagrammatic view that illustrates multi-port aspects. FIG. **28B** shows three illustrative instruments or assemblies **2810** entering different natural orifices (nostrils, mouth) and then continuing via a single body lumen (throat) to reach a surgical site.

FIGS. **29A** and **29B** are diagrammatic views that illustrate further aspects of minimally invasive surgical instrument assembly position sensing and motion control. As shown in FIG. **29A**, the distal end **2902** of a surgical instrument device or assembly is advanced within the walls **2904** of a body lumen or other cavity towards surgical site **2906**. Distal end **2902** is illustrative of various components, such as a guide probe or guide tube as described above. As distal end **2902** advances it is moved (flexed as shown, or pivoted at a joint) up and down and side to side, as depicted by the alternate position lines. As the tip of distal end **2902** touches, or comes close to touching, a position on walls **2904**, actuator control system **2908** records the tip's position and stores the position data in memory **2910**. Tip position information may come directly from the surgical instrument assembly or from an external sensor **2912**, as described above. The tip may be bent in various 3-dimensional directions so that it touches or nearly touches walls **2904** in various patterns (e.g., a series of rings, a helix, a series of various crosses or stars, etc.), either under a surgeon's direct control or under automatic control by control system **2908**. Once the lumen's or cavity's interior space is mapped, the space information is used to assist advancing subsequent surgical instrument assembly components, as illustrated in FIG. **29B**. As an example, a secondary guide tube **2912** with side exit ports is shown, and control system **2908** uses the map information to prevent primary guide tubes **2914a**, **2914b** and their associated end effectors from interfering with walls **2904** as they are advanced towards surgical site **2906**.

FIGS. **29C-29E** are diagrammatic plan views that illustrate further aspects of preventing undesired instrument collision with tissue. Instruments may collide with patient tissue outside of an imaging system's field of view in spaces confined by patient anatomy (e.g., laryngeal surgery). Such collisions may damage tissue. For multi-DOF surgical

instruments, some DOFs may be inside the field of view while other, more proximal DOFs may be outside the field of view. Consequently, a surgeon may be unaware that tissue damage is occurring as these proximal DOFs move. As shown in FIG. 29C, for example, an endoscopic imaging system 2920 extends from the end of guide tube 2922. The left side working instrument 2924a is placed so that all DOFs are within imaging system 2920's field of view 2926 (bounded by the dashed lines). The right side working instrument 2924b, however, has proximal DOFs (an illustrative parallel motion mechanism as described above and wrist are shown) that are outside field of view 2926, even though instrument 2924b's end effector is within field of view 2926. This instrument position is illustrative of tasks such as tying sutures.

In one aspect, field of view boundaries can be determined when the camera is manufactured so that the boundaries are known in relation to the camera head (image capture component). The boundary information is then stored in a nonvolatile memory associated with the imaging system that incorporates the camera head. Consequently, the control system can use the imaging system instrument's kinematic and joint position information to locate the camera head relative to the working instruments, and therefore the control system can determine the field of view boundaries relative to the working instruments. Instruments are then controlled to work within the boundaries.

In another aspect for stereoscopic imaging systems, field of view boundaries can be determined relative to the instruments by using machine vision algorithms to identify the instruments and their positions in the field of view. This "tool tracking" subject is disclosed in U.S. Patent Application Publication No. US 2006/0258938 A1 (Hoffman et al.), which is incorporated by reference.

As shown in FIG. 29D, imaging system 2920 is placed so that the camera head is just at the distal end of guide tube 2922. Instruments 2924a and 2924b are extended from the distal end of the guide tube and within imaging system 2920's field of view. An "Allowable Volume" is defined to be coincident with the field of view boundaries. The control system prevents any part of instruments 2924a and 2924b from moving outside the Allowable Volume. Since the surgeon can see all distal moving parts of instruments 2924a and 2924b, the surgeon then moves the instruments without colliding with surrounding tissue. The instrument movements are recorded, and an "Instrument Volume" 2928 (bounded by the dotted lines), which is bounded by the farthest movements of the instruments, is determined. The Instrument Volume is a convex volume within which instruments may be moved without colliding with tissue.

Next, imaging system 2920 is inserted as shown in FIG. 29E. As a result, field of view 2926 is also inserted, and parts of instruments 2924a, 2924b are outside of the inserted field of view 2926. A new Allowable Volume is determined to be the newly inserted field of view plus the previously determined Instrument Volume that is outside of the field of view. Therefore, the control system will allow the surgeon to move an instrument anywhere within the new Allowable Volume. The process may be repeated for further field of view insertions or for guide tube 2922 movements. This scheme allows a surgeon to define the allowable instrument range of motion in real time without requiring a tissue model. The surgeon is only required to trace the boundaries of the instrument range of motion inside the field of view, and the control system will record this information as the field of view is changed.

Another way to prevent unwanted instrument/tissue collision is by using image mosaicing. FIG. 29F is a diagrammatic view of a display (e.g., stereoscopic) that a surgeon sees during a surgical procedure. As shown in FIG. 29F, the image from the new, more inserted field of view 2940 (bounded by the dashed lines) is registered and mosaiced with the image from the old, more withdrawn field of view 2942. Image mosaicing is known (see e.g., U.S. Pat. No. 4,673,988 (Jansson et al.) and U.S. Pat. No. 5,999,662 (Burt et al.)), which are incorporated by reference) and has been applied to medical equipment (see e.g., U.S. Pat. No. 7,194,118 (Harris et al.)), which is incorporated by reference). As a result, the surgeon sees an area larger than the current, more inserted field of view. A kinematically accurate graphical simulation of the instruments is shown in the old field of view 2942 so that the surgeon can see possible collisions in this region as the instruments move.

In some aspects, minimally invasive surgical instrument assembly components may be replaced by hand during surgery. In other aspects, components may be automatically replaced. FIG. 30 is a schematic view that illustrates a mechanism for automatically exchanging minimally invasive surgical instruments (e.g., those of approximately 3 mm diameter, such as flexible laparoscopic instruments with a single grip DOF) during surgery. As shown in FIG. 30, an instrument magazine 3002 has several instruments 3004a, 3004b, 3004c stored (e.g., three, as depicted). The instruments may be stored on a drum, linearly extended, or otherwise. In some aspects, the instruments in magazine 3002 are selected for each surgical procedure—that is, the surgeon determines the instruments to be used for a specific procedure, and magazine 3002 is configured accordingly. As FIG. 30 illustrates, magazine 3002 is positioned to allow actuator control system 3006 to advance instrument 3004a into guide tube 3008. To exchange an instrument, control system 3006 withdraws instrument 3004a from guide tube 3008 and repositions magazine 3002 to advance either instrument 3004b or 3004c into guide tube 3008. The magazine, instruments, and guide tube shown in FIG. 30 are illustrative of various components described herein (e.g., instruments, primary and secondary guide tubes, guide probes, imaging systems (optical, infrared, ultrasound), and the like).

FIG. 30A is a schematic view that illustrates aspects of storing an instrument or other component on a drum. Instrument 3004 is extended as drum 3020 rotates inside magazine housing 3022. Actuator 3006 for instrument 3004's end effector 3008 is positioned on drum 3020. Actuator 3006 is illustrative of other actuator assemblies that may be used if, for example, a steerable guide tube is to be advanced instead. Instrument 3004 is coiled loosely enough so that the cable actuator for end effector 3008 does not bind within its flexible cover. FIG. 30B is a schematic view that illustrates aspects of storing automatically replaceable instruments on spools 3030 mounted on individual capstans 3032.

FIG. 31 is a diagrammatic perspective view that shows aspects of an illustrative minimally invasive surgical instrument assembly that includes a multi-jointed instrument dedicated to retraction. As shown in FIG. 31, guide tube 3102 includes a channel 3104, through which an imaging system is inserted, and three channels 3106a, 3106b, 3106c, through which surgical instruments may be inserted. Retraction instrument 3108 is shown extending through channel 3106c.

As depicted, retraction instrument 3108 includes a proximal instrument body 3110 and four serial links 3112a-d. Four joints 3114a-d couple proximal instrument body 3110

and links **3112a-d** together. In one aspect, each joint **3114a-d** is an independently controllable single DOF pitch joint. In other aspects the joints may have additional DOFs. An actively controlled (either hand or telemanipulated) gripper **3116** is mounted at the distal end of the most distal link **3112d** via a passive roll joint **3118**. In some aspects other end effectors, or none, may be substituted for the gripper. In one aspect the combined length of links **3112a-d** and gripper **3116** is sufficient to retract tissue beyond the working envelope of instruments that extend through channels **3106a** and **3106b**. For example, the combined lengths of the links and the gripper may be approximately equal to the full insertion range (e.g., approximately 5 inches) of the instruments. Four links and joints are shown, and other numbers of links and joints may be used. Retraction is done using various combinations of pitching joints **3114a-d** and rolling instrument **3108** within channel **3106c**.

For retraction, instrument **3108** is inserted so that each joint **3114a-d** is exposed one after the other. Insertion depth may be varied so that retraction can begin at various distances from the distal end of the guide tube with various numbers of joints as the joints exit from the guide tube's distal end. That is, for example, retraction may begin as soon as joint **3114d** is inserted past the distal end of the guide tube. For retraction, gripper **3116** may grip tissue. Passive roll joint **3118** prevents the gripped tissue from being torqued as instrument **3108** is rolled within channel **3106c**. In one aspect, the control system couples the motions of instrument **3108** and guide tube **3102**. This coupled control of motion allows tissue to be held in place by gripper **3116** as the guide tube is moved to the left or right "underneath" the retracted tissue. For example, as the distal end of guide tube **3102** is moved to the left, instrument **3108** is rolled (and joint **3114a-d** pitch may be changed) to move gripper **3116** to the right.

FIG. 31 further illustrates an aspect of instrument position and control within guide tubes. The working surgical instruments need not be inserted through guide tube channels that correspond to or are aligned with their working position. For example, as shown in FIG. 31 the left side working instrument does not have to be inserted through the left-most channel **3106c**. Instead, the left side working instrument may be inserted via the "bottom" channel **3106b**. The right side working instrument may then be inserted via the right-most channel **3106a**. Then, the left and right side working instruments may be controlled to work at a surgical site in alignment with the field of view of an imaging system inserted via channel **3104** that has not been rolled or yawed. Stated another way, the left-right axis between the working instruments' insertion channels does not have to be aligned with the left-right axis between the working instruments' end effectors at the surgical site or with the left-right axis inter pupillary axis of the stereoscopic imaging system. Further, by the control system recognizing which instrument is coupled to each particular actuator, left-right instrument position may be varied. For example, retraction instrument **3108** may be inserted via channel **3106a**, the right side working instrument may be inserted via channel **3106b**, and the left side working instrument may be inserted via channel **3106c**. In some aspects, with appropriately shaped channels and/or imaging systems, the imaging system may be inserted via one of several channels. For example, "top" channel **3104** and "bottom" channel **3106b** may be oblong shaped with a center bore that holds a cylindrical instrument body, as shown in FIG. 20A. Consequently, an imaging system

may be inserted via the "top" or "bottom" channel, and a working instrument may be inserted via the other "top" or "bottom" channel.

These descriptions of examples of various minimally invasive surgical systems, assemblies, and instruments, and of the associated components, are not to be taken as limiting. It should be understood that many variations that incorporate the aspects described herein are possible. For example, various combinations of rigid and flexible instruments and instrument components, and of guide tubes and guide tube components, fall within the scope of this description. The claims define the invention.

We claim:

1. A patient side support system comprising:
 - a base;
 - a first link coupled to the base at a first rotational joint, the first rotational joint having a rotational axis around which the first rotational joint rotates;
 - a platform supported by the first link, the platform having a roll axis around which the platform rotates;
 - a plurality of manipulator assemblies coupled to the platform;
 - a plurality of instruments, each of the plurality of instruments being coupled to a different one of the plurality of manipulator assemblies, each of the plurality of instruments including a body and a shaft, the shaft extending from the body; and
 - a rigid guide tube common to the plurality of instruments; wherein a first part of the shaft of each individual one of the plurality of instruments extends between the body and the rigid guide tube, and a second part of the shaft of each individual one of the plurality of instruments extends through the rigid guide tube;
 - wherein the rigid guide tube is positioned so that a remote center of motion point of the platform is located on the rigid guide tube, the remote center of motion point being adjacent a location at which the rigid guide tube is configured to enter a patient;
 - wherein the rotational axis of the first rotational joint is vertically aligned with and extends through the remote center of motion point;
 - wherein the roll axis of the platform is aligned with and extends through the remote center of motion point; and
 - wherein the first part of the shaft of one or more of the plurality of instruments being resiliently bent between the body of the one of the plurality of instruments and the rigid guide tube.
2. The patient side support system of claim 1, one of the plurality of instruments further comprising a parallel motion mechanism and an end component;
 - the parallel motion mechanism comprising:
 - a first joint connected to a distal end of the second part of the shaft of the one of the plurality of instruments,
 - an elongate rigid body segment connected to the first joint, and
 - a second joint connected to the elongate rigid body segment and coupled to the end component,
 - wherein the first and second joints are coupled by cables, and
 - wherein moving the parallel motion mechanism heaves and sways the end component with reference to a longitudinal axis of the second part of the shaft of the one of the plurality of instruments without changing pitch and yaw of the end component.
3. The patient side support system of claim 2, wherein the end component comprises an end effector.

55

4. The patient side support system of claim 2, wherein the end component comprises an image capture component.

5. The patient side support system of claim 2, the one of the plurality of instruments further comprising a wrist mechanism mounted between the parallel motion mechanism and the end component.

6. The patient side support system of claim 2, another one of the plurality of instruments further comprising an image capture unit coupled to a distal end of the second part of the shaft of the another one of the plurality of instruments.

7. The patient side support system of claim 2, another one of the plurality of instruments further comprising a second parallel motion mechanism and a second end component; the second parallel motion mechanism comprising:

a third joint connected to a distal end of the second part of the shaft of the another one of the plurality of instruments,

a second elongate rigid body segment connected to the third joint, and

a fourth joint connected to the second elongate rigid body segment and coupled to the second end component,

wherein the third and fourth joints are coupled by cables, and

wherein moving the second parallel motion mechanism heaves and sways the second end component with reference to a longitudinal axis of the second part of the shaft of the another one of the plurality of instruments without changing pitch and yaw of the second end component.

8. The patient side support system of claim 7, the rigid guide tube further comprising a distal end, a third parallel motion mechanism, and an image capture component,

the third parallel motion mechanism comprising:

a fifth joint connected to the distal end of the rigid guide tube,

a third elongate rigid body segment connected to the fifth joint, and

a sixth joint connected to the third elongate rigid body segment and coupled to the image capture component,

wherein the fifth and sixth joints are coupled by cables, and

wherein moving the parallel motion mechanism heaves and sways the image capture component with refer-

56

ence to a longitudinal axis of the rigid guide tube without changing pitch and yaw of the image capture component.

9. The patient side support system of claim 7, another one of the plurality of instruments further comprising an image capture unit coupled to a distal end of the second part of the shaft of the another one of the plurality of instruments.

10. The patient side support system of claim 7, the rigid guide tube further comprising a distal end and an image capture component, the image capture component being mounted in the distal end of the rigid guide tube.

11. The patient side support system of claim 1, the rigid guide tube further comprising a distal end and an image capture component, the image capture component being mounted in the distal end of the rigid guide tube.

12. The patient side support system of claim 1, the rigid guide tube further comprising a distal end, a parallel motion mechanism, and an image capture component, the parallel motion mechanism comprising:

a first joint connected to a distal end of the rigid guide tube,

an elongate rigid body segment connected to the first joint, and

a second joint connected to the elongate rigid body segment and coupled to the image capture component,

wherein the first and second joints are coupled by cables, and

wherein moving the parallel motion mechanism heaves and sways the image capture component with reference to a longitudinal axis of the rigid guide tube without changing pitch and yaw of the image capture component.

13. The patient side support system of claim 12, further comprising a wrist mechanism mounted between the parallel motion mechanism and the image capture component.

14. The patient side support system of claim 1, one of the plurality of instruments further comprising an image capture unit coupled to a distal end of the second part of the shaft of the one of the plurality of instruments.

15. The patient side support system of claim 1, one of the plurality of instruments further comprising an end effector coupled to a distal end of the second part of the shaft of the one of the plurality of instruments.

* * * * *