



US009172759B2

(12) **United States Patent**
Logue et al.

(10) **Patent No.:** **US 9,172,759 B2**
(45) **Date of Patent:** **Oct. 27, 2015**

(54) **FABRIC NETWORK**

(71) Applicant: **Google Inc.**, Mountain View, CA (US)

(72) Inventors: **Jay D. Logue**, San Jose, CA (US);
Grant M. Erickson, Sunnyvale, CA
(US); **Zachary B. Smith**, San Francisco,
CA (US); **Osborne B. Hardison**, Palo
Alto, CA (US); **Richard J. Schultz**,
Mountain View, CA (US); **Sunny P.**
Gujjaru, Sunnyvale, CA (US); **Matthew**
G. Neeley, San Mateo, CA (US)

(73) Assignee: **Google Inc.**, Mountain View, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/504,296**

(22) Filed: **Oct. 1, 2014**

(65) **Prior Publication Data**

US 2015/0019650 A1 Jan. 15, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/926,302, filed on
Jun. 25, 2013.

(51) **Int. Cl.**

G06F 15/16 (2006.01)

H04L 29/08 (2006.01)

H04L 12/931 (2013.01)

(Continued)

(52) **U.S. Cl.**

CPC **H04L 67/147** (2013.01); **G06Q 10/107**
(2013.01); **H04L 12/2807** (2013.01); **H04L**
29/06 (2013.01); **H04L 43/0805** (2013.01);
H04L 49/20 (2013.01); **H04L 49/355**
(2013.01); **H04L 61/2069** (2013.01); **H04L**
67/10 (2013.01); **H04L 69/22** (2013.01); **H04L**
61/6018 (2013.01)

(58) **Field of Classification Search**

USPC 709/203, 206–207, 217–218, 223–229,
709/250

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,539,567 B1 9/2013 Logue et al.
2003/0088697 A1* 5/2003 Matsuhira 709/238

(Continued)

FOREIGN PATENT DOCUMENTS

WO 20060135758 A1 12/2006

OTHER PUBLICATIONS


U.S. Appl. No. 13/926,335, filed Jun. 25, 2013, Grant M. Erickson.
(Continued)

Primary Examiner — Zarni Maung

(57) **ABSTRACT**

Systems and methods relating to communication within a fabric network are presented. The fabric network includes one or more logical networks that enables devices connected to the fabric to communicate with each other using various profiles known to the devices. A device sending a message may follow a general message format to encode the message so that other devices in the fabric may understand the message regardless of which logical networks the devices are connected to. Within the message format, a payload of data may be included for the receiving device to forward, store, or process the message. The format and the contents of the payload may vary according to a header within the payload that indicates a profile and a message type within the profile. Using the profile and message type, the receiving devices may decode the message to process the message.

20 Claims, 22 Drawing Sheets



2007/0253431	A1 *	11/2007	Park et al.	370/395.52
2007/0291789	A1 *	12/2007	Kutt et al.	370/467
2008/0188963	A1	8/2008	McCoy	
2009/0052409	A1 *	2/2009	Chen et al.	370/338
2009/0323688	A1 *	12/2009	Torii	370/390
2010/0232317	A1	9/2010	Jing et al.	
2013/0083805	A1	4/2013	Lu et al.	
2013/0204703	A1 *	8/2013	Carlson et al.	705/14.56
2014/0089671	A1	3/2014	Logue et al.	
2014/0282923	A1	9/2014	Narayan et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0022257	A1 *	2/2004	Green et al.	370/401
2004/0024903	A1 *	2/2004	Costatino et al.	709/238
2006/0271682	A1 *	11/2006	Choo et al.	709/226
2007/0165625	A1 *	7/2007	Eisner et al.	370/389

OTHER PUBLICATIONS

PCT ISR & WO for Application No. PCT/US2014/043695 mailed Sep. 11, 2014.

* cited by examiner





FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49

FABRIC NETWORK**CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a Continuation Application of, and claims priority to, U.S. patent application Ser. No. 13/926,302, filed Jun. 25, 2013, entitled "Fabric Network", in the name of Jay D. Logue et al., the entirety of which is incorporated by reference herein for all purposes.

BACKGROUND

This disclosure relates to a fabric network that couples electronic devices using one or more network types.

This section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present techniques, which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present disclosure. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art.

Network-connected devices appear throughout homes. Some of these devices are often capable of communicating with each other through a single network type (e.g., WiFi connection) using a transfer protocol. It may be desired to use less power intensive connection protocols for some devices that are battery powered or receive a reduced charge. However, in some scenarios, devices connected to a lower power protocol may not be able to communicate with devices connected to a higher power protocol (e.g., WiFi).

SUMMARY

A summary of certain embodiments disclosed herein is set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of these certain embodiments and that these aspects are not intended to limit the scope of this disclosure. Indeed, this disclosure may encompass a variety of aspects that may not be set forth below.

Embodiments of the present disclosure relate to systems and methods a fabric network that includes one or more logical networks that enables devices connected to the fabric to communicate with each other using a list of protocols and/or profiles known to the devices. The communications between the devices may follow a typical message format that enables the devices to understand communications between the devices regardless of which logical networks the communicating devices are connected to in the fabric. Within the message format, a payload of data may be included for the receiving device to store and/or process. The format and the contents of the payload may vary according to a header within the payload that indicates a profile (including one or more protocols) and/or a type of message that is being sent according to the profile.

According to some embodiments, two or more devices in a fabric may communicate using status reporting protocols or profiles. For example, in certain embodiments, a status reporting protocol or schema may be included in a core profile that is available to devices connected to the fabric. Using the status reporting protocol, devices may send or request status information to or from other devices in the fabric.

Similarly, in certain embodiments, two or more devices in a fabric may communicate using update software protocols or profiles. In some embodiments, the update software protocol

or schema may be included in a core profile that is available to devices connected to the fabric. Using the update software protocol, devices may request, send, or notify the presence of updates within the fabric.

In certain embodiments, two or more devices in a fabric may communicate using data management protocols or profiles. In some embodiments, the data management protocol or schema may be included in a core profile that is available to devices connected to the fabric. Using the update data management protocol, devices may request, view, or track node-resident information that is stored in other devices.

Furthermore, in certain embodiments, two or more devices in a fabric may transfer data using bulk data transfer protocols or profiles. In some embodiments, the bulk data transfer protocol or schema may be included in a core profile that is available to devices connected to the fabric. Using the bulk data transfer protocol, devices may initiate, send, or receive bulk data using any logical networks in the fabric. In certain embodiments, either a sending or a receiving device using the bulk data transfer protocol may be able to "drive" a synchronous transfer between the devices. In other embodiments, the bulk transfer may be performed with an asynchronous transfer.

Various refinements of the features noted above may exist in relation to various aspects of the present disclosure. Further features may also be incorporated in these various aspects as well. These refinements and additional features may exist individually or in any combination. For instance, various features discussed below in relation to one or more of the illustrated embodiments may be incorporated into any of the above-described aspects of the present disclosure alone or in any combination. The brief summary presented above is intended only to familiarize the reader with certain aspects and contexts of embodiments of the present disclosure without limitation to the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

Various aspects of this disclosure may be better understood upon reading the following detailed description and upon reference to the drawings in which:

FIG. 1 is a block diagram of an electronic device having that may be interconnected with other devices using a fabric network, in accordance with an embodiment;

FIG. 2 illustrates a block diagram of a home environment in which the general device of FIG. 1 may communicate with other devices via the fabric network, in accordance with an embodiment;

FIG. 3 illustrates a block diagram of an Open Systems Interconnection (OSI) model that characterizes a communication system for the home environment of FIG. 2, in accordance with an embodiment;

FIG. 4 illustrates the fabric network having a single logical network topology, in accordance with an embodiment;

FIG. 5 illustrates the fabric network having a star network topology, in accordance with an embodiment;

FIG. 6 illustrates the fabric network having an overlapping networks topology, in accordance with an embodiment;

FIG. 7 illustrates a service communicating with one or more fabric networks, in accordance with an embodiment;

FIG. 8 illustrates two devices in a fabric network in communicative connection, in accordance with an embodiment;

FIG. 9 illustrates a unique local address format (ULA) that may be used to address devices in a fabric network, in accordance with an embodiment;

FIG. 10 illustrates a process for proxying periphery devices on a hub network, in accordance with an embodiment;

FIG. 11 illustrates a tag-length-value (TLV) packet that may be used to transmit data over the fabric network, in accordance with an embodiment;

FIG. 12 illustrates a general message protocol (GMP) that may be used to transmit data over the fabric network that may include the TLV packet of FIG. 11, in accordance with an embodiment;

FIG. 13 illustrates a message header field of the GMP of FIG. 12, in accordance with an embodiment;

FIG. 14 illustrates a key identifier field of the GMP of FIG. 12, in accordance with an embodiment;

FIG. 15 illustrates an application payload field of the GMP of FIG. 12, in accordance with an embodiment;

FIG. 16 illustrates a status reporting schema that may be used to update status information in the fabric network, in accordance with an embodiment;

FIG. 17 illustrates a profile field of the status reporting schema of FIG. 16, in accordance with an embodiment;

FIG. 18 illustrates a protocol sequence that may be used to perform a software update between a client and a server, in accordance with an embodiment;

FIG. 19 illustrates an image query frame that may be used in the protocol sequence of FIG. 18, in accordance with an embodiment;

FIG. 20 illustrates a frame control field of the image query frame of FIG. 19, in accordance with an embodiment;

FIG. 21 illustrates a product specification field of the image query frame of FIG. 19, in accordance with an embodiment;

FIG. 22 illustrates a version specification field of the image query frame of FIG. 19, in accordance with an embodiment;

FIG. 23 illustrates a locale specification field of the image query frame of FIG. 19, in accordance with an embodiment;

FIG. 24 illustrates an integrity types supported field of the image query frame of FIG. 19, in accordance with an embodiment;

FIG. 25 illustrates an update schemes supported field of the image query frame of FIG. 19, in accordance with an embodiment;

FIG. 26 illustrates an image query response frame that may be used in the protocol sequence of FIG. 18, in accordance with an embodiment;

FIG. 27 illustrates a uniform resource identifier (URI) field of the image query response frame of FIG. 26, in accordance with an embodiment;

FIG. 28 illustrates an integrity specification field of the image query response frame of FIG. 26, in accordance with an embodiment;

FIG. 29 illustrates an update scheme field of the image query response frame of FIG. 26, in accordance with an embodiment;

FIG. 30 illustrates a sequence used to employ a data management protocol to manage data between devices in the fabric network, in accordance with an embodiment;

FIG. 31 illustrates a snapshot request frame that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 32 illustrates an example profile schema that may be accessed using the snapshot request frame of FIG. 31, in accordance with an embodiment;

FIG. 33 is a binary format of a path that may indicate a path in a profile schema, in accordance with an embodiment;

FIG. 34 illustrates a watch request frame that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 35 illustrates a periodic update request frame that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 36 illustrates a refresh request frame that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 37 illustrates a cancel view request that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 38 illustrates a view response frame that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 39 illustrates an explicit update request frame that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 40 illustrates a view update request frame that may be used in the sequence of FIG. 30, in accordance with an embodiment;

FIG. 41 illustrates an update item frame that may be updated using the sequence of FIG. 30, in accordance with an embodiment;

FIG. 42 illustrates an update response frame that may be sent as an update response message in the sequence FIG. 30, in accordance with an embodiment;

FIG. 43 illustrates a communicative connection between a sender and a receiver in a bulk data transfer, in accordance with an embodiment;

FIG. 44 illustrates a SendInit message that may be used to initiate the communicative connection by the sender of FIG. 43, in accordance with an embodiment;

FIG. 45 illustrates a transfer control field of the SendInit message of FIG. 44, in accordance with an embodiment;

FIG. 46 illustrates a range control field of the SendInit message of FIG. 45, in accordance with an embodiment;

FIG. 47 illustrates a SendAccept message that may be used to accept a communicative connection proposed by the SendInit message of FIG. 44 sent by the sender of FIG. 44, in accordance with an embodiment;

FIG. 48 illustrates a SendReject message that may be used to reject a communicative connection proposed by the SendInit message of FIG. 44 sent by the sender of FIG. 44, in accordance with an embodiment; and

FIG. 49 illustrates a ReceiveAccept message that may be used to accept a communicative connection proposed by the receiver of FIG. 44, in accordance with an embodiment.

DETAILED DESCRIPTION

One or more specific embodiments of the present disclosure will be described below. These described embodiments are only examples of the presently disclosed techniques. Additionally, in an effort to provide a concise description of these embodiments, all features of an actual implementation may not be described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but may nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

When introducing elements of various embodiments of the present disclosure, the articles "a," "an," and "the" are intended to mean that there are one or more of the elements. The terms "comprising," "including," and "having" are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it

5

should be understood that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features.

Embodiments of the present disclosure relate generally to an efficient fabric network that may be used by devices and/or services communicating with each other in a home environment. Generally, consumers living in homes may find it useful to coordinate the operations of various devices within their home such that all of their devices are operated efficiently. For example, a thermostat device may be used to detect a temperature of a home and coordinate the activity of other devices (e.g., lights) based on the detected temperature. In this example, the thermostat device may detect a temperature that may indicate that the temperature outside the home corresponds to daylight hours. The thermostat device may then convey to the light device that there may be daylight available to the home and that thus the light should turn off.

In addition to operating these devices efficiently, consumers generally prefer to use user-friendly devices that involve a minimum amount of set up or initialization. That is, consumers may generally prefer to purchase devices that are fully operational after performing a few number initialization steps that may be performed by almost any individual regardless of age or technical expertise.

With the foregoing in mind, to enable to effectively communicate data between each other within the home environment, the devices may use a fabric network that includes one or more logical networks to manage communication between the devices. That is, the efficient fabric network may enable numerous devices within a home to communicate with each other using one or more logical networks. The communication network may support Internet Protocol version 6 (IPv6) communication such that each connected device may have a unique local address (LA). Moreover, to enable each device to integrate with a home, it may be useful for each device to communicate within the network using low amounts of power. That is, by enabling devices to communicate using low power, the devices may be placed anywhere in a home without being coupled to a continuous power source (e.g., battery-powered).

I. Fabric Introduction

By way of introduction, FIG. 1 illustrates an example of a general device **10** that may that may communicate with other like devices within a home environment. In one embodiment, the device **10** may include one or more sensors **12**, a user-interface component **14**, a power supply **16** (e.g., including a power connection and/or battery), a network interface **18**, a processor **20**, and the like. Particular sensors **12**, user-interface components **14**, and power-supply configurations may be the same or similar with each devices **10**. However, it should be noted that in some embodiments, each device **10** may include particular sensors **12**, user-interface components **14**, power-supply configurations, and the like based on a device type or model.

The sensors **12**, in certain embodiments, may detect various properties such as acceleration, temperature, humidity, water, supplied power, proximity, external motion, device motion, sound signals, ultrasound signals, light signals, fire, smoke, carbon monoxide, global-positioning-satellite (GPS) signals, radio-frequency (RF), other electromagnetic signals or fields, or the like. As such, the sensors **12** may include temperature sensor(s), humidity sensor(s), hazard-related sensor(s) or other environmental sensor(s), accelerometer(s), microphone(s), optical sensors up to and including camera(s) (e.g., charged coupled-device or video cameras), active or passive radiation sensors, GPS receiver(s) or radiofrequency

6

identification detector(s). While FIG. 1 illustrates an embodiment with a single sensor, many embodiments may include multiple sensors. In some instances, the device **10** may include one or more primary sensors and one or more secondary sensors. Here, the primary sensor(s) may sense data central to the core operation of the device (e.g., sensing a temperature in a thermostat or sensing smoke in a smoke detector), while the secondary sensor(s) may sense other types of data (e.g., motion, light or sound), which can be used for energy-efficiency objectives or smart-operation objectives.

One or more user-interface components **14** in the device **10** may receive input from the user and/or present information to the user. The user-interface component **14** may also include one or more user-input components that may receive information from the user. The received input may be used to determine a setting. In certain embodiments, the user-input components may include a mechanical or virtual component that responds to the user's motion. For example, the user can mechanically move a sliding component (e.g., along a vertical or horizontal track) or rotate a rotatable ring (e.g., along a circular track), the user's motion along a touchpad may be detected, or motions/gestures may be detected using a contactless gesture detection sensor (e.g., infrared sensor or camera). Such motions may correspond to a setting adjustment, which can be determined based on an absolute position of a user-interface component **104** or based on a displacement of a user-interface components **104** (e.g., adjusting a setpoint temperature by 1 degree F. for every 10° rotation of a rotatable-ring component). Physically and virtually movable user-input components can allow a user to set a setting along a portion of an apparent continuum. Thus, the user may not be confined to choose between two discrete options (e.g., as would be the case if up and down buttons were used) but can quickly and intuitively define a setting along a range of possible setting values. For example, a magnitude of a movement of a user-input component may be associated with a magnitude of a setting adjustment, such that a user may dramatically alter a setting with a large movement or finely tune a setting with a small movement.

The user-interface components **14** may also include one or more buttons (e.g., up and down buttons), a keypad, a number pad, a switch, a microphone, and/or a camera (e.g., to detect gestures). In one embodiment, the user-input component **14** may include a click-and-rotate annular ring component that may enable the user to interact with the component by rotating the ring (e.g., to adjust a setting) and/or by clicking the ring inwards (e.g., to select an adjusted setting or to select an option). In another embodiment, the user-input component **14** may include a camera that may detect gestures (e.g., to indicate that a power or alarm state of a device is to be changed). In some instances, the device **10** may have one primary input component, which may be used to set various types of settings. The user-interface components **14** may also be configured to present information to a user via, e.g., a visual display (e.g., a thin-film-transistor display or organic light-emitting-diode display) and/or an audio speaker.

The power-supply component **16** may include a power connection and/or a local battery. For example, the power connection may connect the device **10** to a power source such as a line voltage source. In some instances, an AC power source can be used to repeatedly charge a (e.g., rechargeable) local battery, such that the battery may be used later to supply power to the device **10** when the AC power source is not available. In certain embodiments, the power supply component **16** may include intermittent or reduced power connections that may be less than that provided via an AC plug in the

home. In certain embodiments, devices with batteries and/or intermittent or reduced power may be operated as “sleepy devices” that alternate between an online/awake state and an offline/sleep state to reduce power consumption.

The network interface **18** may include one or more components that enable the device **10** to communicate between devices using one or more logical networks within the fabric network. In one embodiment, the network interface **18** may communicate using an efficient network layer as part of its Open Systems Interconnection (OSI) model. In certain embodiments, one component of the network interface **18** may communicate with one logical network (e.g., WiFi) and another component of the network interface may communicate with another logical network (e.g., 802.15.4). In other words, the network interface **18** may enable the device **10** to wirelessly communicate via multiple IPv6 networks. As such, the network interface **18** may include a wireless card, Ethernet port, and/or other suitable transceiver connections.

The processor **20** may support one or more of a variety of different device functionalities. As such, the processor **20** may include one or more processors configured and programmed to carry out and/or cause to be carried out one or more of the functionalities described herein. In one embodiment, the processor **20** may include general-purpose processors carrying out computer code stored in local memory (e.g., flash memory, hard drive, random access memory), special-purpose processors or application-specific integrated circuits, other types of hardware/firmware/software processing platforms, and/or some combination thereof. Further, the processor **20** may be implemented as localized versions or counterparts of algorithms carried out or governed remotely by central servers or cloud-based systems, such as by virtue of running a Java virtual machine (JVM) that executes instructions provided from a cloud server using Asynchronous Javascript and XML (AJAX) or similar protocols. By way of example, the processor **20** may detect when a location (e.g., a house or room) is occupied, up to and including whether it is occupied by a specific person or is occupied by a specific number of people (e.g., relative to one or more thresholds). In one embodiment, this detection can occur, e.g., by analyzing microphone signals, detecting user movements (e.g., in front of a device), detecting openings and closings of doors or garage doors, detecting wireless signals, detecting an IP address of a received signal, detecting operation of one or more devices within a time window, or the like. Moreover, the processor **20** may include image recognition technology to identify particular occupants or objects.

In some instances, the processor **20** may predict desirable settings and/or implement those settings. For example, based on presence detection, the processor **20** may adjust device settings to, e.g., conserve power when nobody is home or in a particular room or to accord with user preferences (e.g., general at-home preferences or user-specific preferences). As another example, based on the detection of a particular person, animal or object (e.g., a child, pet or lost object), the processor **20** may initiate an audio or visual indicator of where the person, animal or object is or may initiate an alarm or security feature if an unrecognized person is detected under certain conditions (e.g., at night or when lights are off).

In some instances, devices may interact with each other such that events detected by a first device influences actions of a second device using one or more common profiles between the devices. For example, a first device can detect that a user has pulled into a garage (e.g., by detecting motion in the garage, detecting a change in light in the garage or detecting opening of the garage door). The first device can transmit this information to a second device via the fabric network, such

that the second device can, e.g., adjust a home temperature setting, a light setting, a music setting, and/or a security-alarm setting. As another example, a first device can detect a user approaching a front door (e.g., by detecting motion or sudden light pattern changes). The first device may cause a general audio or visual signal to be presented (e.g., such as sounding of a doorbell) or cause a location-specific audio or visual signal to be presented (e.g., to announce the visitor’s presence within a room that a user is occupying).

With the foregoing in mind, FIG. 2 illustrates a block diagram of a home environment **30** in which the device **10** of FIG. 1 may communicate with other devices via the fabric network. The depicted home environment **30** may include a structure **32** such as a house, office building, garage, or mobile home. It will be appreciated that devices can also be integrated into a home environment that does not include an entire structure **32**, such as an apartment, condominium, office space, or the like. Further, the home environment **30** may control and/or be coupled to devices outside of the actual structure **32**. Indeed, several devices in the home environment **30** need not physically be within the structure **32** at all. For example, a device controlling a pool heater **34** or irrigation system **36** may be located outside of the structure **32**.

The depicted structure **32** includes multiple rooms **38**, separated at least partly from each other via walls **40**. The walls **40** can include interior walls or exterior walls. Each room **38** can further include a floor **42** and a ceiling **44**. Devices can be mounted on, integrated with and/or supported by the wall **40**, the floor **42**, or the ceiling **44**.

The home environment **30** may include multiple devices, including intelligent, multi-sensing, network-connected devices that may integrate seamlessly with each other and/or with cloud-based server systems to provide any of a variety of useful home objectives. One, more or each of the devices illustrated in the home environment **30** may include one or more sensors **12**, a user interface **14**, a power supply **16**, a network interface **18**, a processor **20** and the like.

Example devices **10** may include a network-connected thermostat **46** that may detect ambient climate characteristics (e.g., temperature and/or humidity) and control a heating, ventilation and air-conditioning (HVAC) system **48**. Another example device **10** may include a hazard detection unit **50** that can detect the presence of a hazardous substance and/or a hazardous condition in the home environment **30** (e.g., smoke, fire, or carbon monoxide). Additionally, entryway interface devices **52**, which can be termed a “smart doorbell”, can detect a person’s approach to or departure from a location, control audible functionality, announce a person’s approach or departure via audio or visual means, or control settings on a security system (e.g., to activate or deactivate the security system).

In certain embodiments, the device **10** may include a light switch **54** that may detect ambient lighting conditions, detect room-occupancy states, and control a power and/or dim state of one or more lights. In some instances, the light switches **54** may control a power state or speed of a fan, such as a ceiling fan.

Additionally, wall plug interfaces **56** may detect occupancy of a room or enclosure and control supply of power to one or more wall plugs (e.g., such that power is not supplied to the plug if nobody is at home). The device **10** within the home environment **30** may further include an appliance **58**, such as refrigerators, stoves and/or ovens, televisions, washers, dryers, lights (inside and/or outside the structure **32**), stereos, intercom systems, garage-door openers, floor fans, ceiling fans, whole-house fans, wall air conditioners, pool heaters **34**, irrigation systems **36**, security systems, and so

forth. While descriptions of FIG. 2 may identify specific sensors and functionalities associated with specific devices, it will be appreciated that any of a variety of sensors and functionalities (such as those described throughout the specification) may be integrated into the device 10.

In addition to containing processing and sensing capabilities, each of the example devices described above may be capable of data communications and information sharing with any other device, as well as to any cloud server or any other device that is network-connected anywhere in the world. In one embodiment, the devices 10 may send and receive communications via a fabric network discussed below. In one embodiment, fabric may enable the devices 10 to communicate with each other via one or more logical networks. As such, certain devices may serve as wireless repeaters and/or may function as bridges between devices, services, and/or logical networks in the home environment that may not be directly connected (i.e., one hop) to each other.

In one embodiment, a wireless router 60 may further communicate with the devices 10 in the home environment 30 via one or more logical networks (e.g., WiFi). The wireless router 60 may then communicate with the Internet 62 or other network such that each device 10 may communicate with a remote service or a cloud-computing system 64 through the Internet 62. The cloud-computing system 64 may be associated with a manufacturer, support entity or service provider associated with a particular device 10. As such, in one embodiment, a user may contact customer support using a device itself rather than using some other communication means such as a telephone or Internet-connected computer. Further, software updates can be automatically sent from the cloud-computing system 64 or devices in the home environment 30 to other devices in the fabric (e.g., when available, when purchased, when requested, or at routine intervals).

By virtue of network connectivity, one or more of the devices 10 may further allow a user to interact with the device even if the user is not proximate to the device. For example, a user may communicate with a device using a computer (e.g., a desktop computer, laptop computer, or tablet) or other portable electronic device (e.g., a smartphone) 66. A webpage or application may receive communications from the user and control the device 10 based on the received communications. Moreover, the webpage or application may present information about the device's operation to the user. For example, the user can view a current setpoint temperature for a device and adjust it using a computer that may be connected to the Internet 62. In this example, the thermostat 46 may receive the current setpoint temperature view request via the fabric network via one or more underlying logical networks.

In certain embodiments, the home environment 30 may also include a variety of non-communicating legacy appliances 68, such as old conventional washer/dryers, refrigerators, and the like which can be controlled, albeit coarsely (ON/OFF), by virtue of the wall plug interfaces 56. The home environment 30 may further include a variety of partially communicating legacy appliances 70, such as infra-red (IR) controlled wall air conditioners or other IR-controlled devices, which can be controlled by IR signals provided by the hazard detection units 50 or the light switches 54.

As mentioned above, each of the example devices 10 described above may form a portion of a fabric network. Generally, the fabric network may be part of an Open Systems Interconnection (OSI) model 90 as depicted in FIG. 4. The OSI model 90 illustrates functions of a communication system with respect to abstraction layers. That is, the OSI model may specify a networking framework or how communica-

tions between devices may be implemented. In one embodiment, the OSI model may include six layers: a physical layer 92, a data link layer 94, a network layer 96, a transport layer 98, a platform layer 100, and an application layer 102. Generally, each layer in the OSI model 90 may serve the layer above it and may be served by the layer below it.

Keeping this in mind, the physical layer 92 may provide hardware specifications for devices that may communicate with each other. As such, the physical layer 92 may establish how devices may connect to each other, assist in managing how communication resources may be shared between devices, and the like.

The data link layer 94 may specify how data may be transferred between devices. Generally, the data link layer 94 may provide a way in which data packets being transmitted may be encoded and decoded into bits as part of a transmission protocol.

The network layer 96 may specify how the data being transferred to a destination node is routed. The network layer 96 may also provide a security protocol that may maintain the integrity of the data being transferred. The efficient network layer discussed above corresponds to the network layer 96. In certain embodiments, the network layer 96 may be completely independent of the platform layer 100 and include any suitable IPv6 network type (e.g., WiFi, Ethernet, HomePlug, 802.15.4, etc.).

The transport layer 98 may specify a transparent transfer of the data from a source node to a destination node. The transport layer 98 may also control how the transparent transfer of the data remains reliable. As such, the transport layer 98 may be used to verify that data packets intended to transfer to the destination node indeed reached the destination node. Example protocols that may be employed in the transport layer 98 may include Transmission Control Protocol (TCP) and User Datagram Protocol (UDP).

The platform layer 100 includes the fabric network and establishes connections between devices according to the protocol specified within the transport layer 98 and may be agnostic of the network type used in the network layer 96. The platform layer 100 may also translate the data packets into a form that the application layer 102 may use. The application layer 102 may support a software application that may directly interface with the user. As such, the application layer 102 may implement protocols defined by the software application. For example, the software application may provide services such as file transfers, electronic mail, and the like.

II. Fabric Device Interconnection

As discussed above, a fabric may be implemented using one or more suitable communications protocols, such as IPv6 protocols. In fact, the fabric may be partially or completely agnostic to the underlying technologies (e.g., network types or communication protocols) used to implement the fabric. Within the one or more communications protocols, the fabric may be implemented using one or more network types used to communicatively couple electrical devices using wireless or wired connections. For example, certain embodiments of the fabric may include Ethernet, WiFi, 802.15.4, ZigBee®, ISA100.11a, WirelessHART, MiWi™, power-line networks, and/or other suitable network types. Within the fabric devices (e.g., nodes) can exchange packets of information with other devices (e.g., nodes) in the fabric, either directly or via intermediary nodes, such as intelligent thermostats, acting as IP routers. These nodes may include manufacturer devices (e.g., thermostats and smoke detectors) and/or customer devices (e.g., phones, tablets, computers, etc.). Additionally, some devices may be "always on" and continuously powered using electrical connections. Other devices may have partially

11

reduced power usage (e.g., medium duty cycle) using a reduced/intermittent power connection, such as a thermostat or doorbell power connection. Finally, some devices may have a short duty cycle and run solely on battery power. In other words, in certain embodiments, the fabric may include heterogeneous devices that may be connected to one or more sub-networks according to connection type and/or desired power usage. FIGS. A-C illustrate three embodiments that may be used to connect electrical devices via one or more sub-networks in the fabric.

A. Single Network Topology

FIG. 4 illustrates an embodiment of the fabric **1000** having a single network topology. As illustrated, the fabric **1000** includes a single logical network **1002**. The network **1002** could include Ethernet, WiFi, 802.15.4, power-line networks, and/or other suitable network types in the IPv6 protocols. In fact, in some embodiments where the network **1002** includes a WiFi or Ethernet network, the network **1002** may span multiple WiFi and/or Ethernet segments that are bridged at a link layer.

The network **1002** includes one or more nodes **1004**, **1006**, **1008**, **1010**, **1012**, **1014**, and **1016**, referred to collectively as **1004-1016**. Although the illustrated network **1002** includes seven nodes, certain embodiments of the network **1002** may include one or more nodes interconnected using the network **1002**. Moreover, if the network **1002** is a WiFi network, each of the nodes **1004-1016** may be interconnected using the node **1016** (e.g., WiFi router) and/or paired with other nodes using WiFi Direct (i.e., WiFi P2P).

B. Star Network Topology

FIG. 5 illustrates an alternative embodiment of fabric **1000** as a fabric **1018** having a star network topology. The fabric **1018** includes a hub network **1020** that joins together two periphery networks **1022** and **1024**. The hub network **1020** may include a home network, such as WiFi/Ethernet network or power line network. The periphery networks **1022** and **1024** may additional network connection types different of different types than the hub network **1020**. For example, in some embodiments, the hub network **1020** may be a WiFi/Ethernet network, the periphery network **1022** may include an 802.15.4 network, and the periphery network **1024** may include a power line network, a ZigBee® network, a ISA100.11a network, a WirelessHART, network, or a MiWi™ network. Moreover, although the illustrated embodiment of the fabric **1018** includes three networks, certain embodiments of the fabric **1018** may include any number of networks, such as 2, 3, 4, 5, or more networks. In fact, some embodiments of the fabric **1018** include multiple periphery networks of the same type.

Although the illustrated fabric **1018** includes fourteen nodes, each referred to individually by reference numbers **1024-1052**, respectively, it should be understood that the fabric **1018** may include any number of nodes. Communication within each network **1020**, **1022**, or **1024**, may occur directly between devices and/or through an access point, such as node **1042** in a WiFi/Ethernet network. Communications between periphery network **1022** and **1024** passes through the hub network **1020** using inter-network routing nodes. For example, in the illustrated embodiment, nodes **1034** and **1036** are be connected to the periphery network **1022** using a first network connection type (e.g., 802.15.4) and to the hub network **1020** using a second network connection type (e.g., WiFi) while the node **1044** is connected to the hub network **1020** using the second network connection type and to the periphery network **1024** using a third network connection type (e.g., power line). For example, a message sent from

12

node **1026** to node **1052** may pass through nodes **1028**, **1030**, **1032**, **1036**, **1042**, **1044**, **1048**, and **1050** in transit to node **1052**.

C. Overlapping Networks Topology

FIG. 6 illustrates an alternative embodiment of the fabric **1000** as a fabric **1054** having an overlapping networks topology. The fabric **1054** includes networks **1056** and **1058**. As illustrated, each of the nodes **1062**, **1064**, **1066**, **1068**, **1070**, and **1072** may be connected to each of the networks. In other embodiments, the node **1072** may include an access point for an Ethernet/WiFi network rather than an end point and may not be present on either the network **1056** or network **1058**, whichever is not the Ethernet/WiFi network. Accordingly, a communication from node **1062** to node **1068** may be passed through network **1056**, network **1058**, or some combination thereof. In the illustrated embodiment, each node can communicate with any other node via any network using any network desired. Accordingly, unlike the star network topology of FIG. 5, the overlapping networks topology may communicate directly between nodes via any network without using inter-network routing.

D. Fabric Network Connection to Services

In addition to communications between devices within the home, a fabric (e.g., fabric **1000**) may include services that may be located physically near other devices in the fabric or physically remote from such devices. The fabric connects to these services through one or more service end points. FIG. 7 illustrates an embodiment of a service **1074** communicating with fabrics **1076**, **1078**, and **1080**. The service **1074** may include various services that may be used by devices in fabrics **1076**, **1078**, and/or **1080**. For example, in some embodiments, the service **1074** may be a time of day service that supplies a time of day to devices, a weather service to provide various weather data (e.g., outside temperature, sunset, wind information, weather forecast, etc.), an echo service that “pings” each device, data management services, device management services, and/or other suitable services. As illustrated, the service **1074** may include a server **1082** (e.g., web server) that stores/accesses relevant data and passes the information through a service end point **1084** to one or more end points **1086** in a fabric, such as fabric **1076**. Although the illustrated embodiment only includes three fabrics with a single server **1082**, it should be appreciated that the service **1074** may connect to any number of fabrics and may include servers in addition to the server **1082** and/or connections to additional services.

In certain embodiments, the service **1074** may also connect to a consumer device **1088**, such as a phone, tablet, and/or computer. The consumer device **1088** may be used to connect to the service **1074** via a fabric, such as fabric **1076**, an Internet connection, and/or some other suitable connection method. The consumer device **1088** may be used to access data from one or more end points (e.g., electronic devices) in a fabric either directly through the fabric or via the service **1074**. In other words, using the service **1074**, the consumer device **1088** may be used to access/manage devices in a fabric remotely from the fabric.

E. Communication Between Devices in a Fabric

As discussed above, each electronic device or node may communicate with any other node in the fabric, either directly or indirectly depending upon fabric topology and network connection types. Additionally, some devices (e.g., remote devices) may communicate through a service to communicate with other devices in the fabric. FIG. 8 illustrates an embodiment of a communication **1090** between two devices **1092** and **1094**. The communication **1090** may span one or more networks either directly or indirectly through additional

13

devices and/or services, as described above. Additionally, the communication **1090** may occur over an appropriate communication protocol, such as IPv6, using one or more transport protocols. For example, in some embodiments the communication **1090** may include using the transmission control protocol (TCP) and/or the user datagram protocol (UDP). In some embodiments, the device **1092** may transmit a first signal **1096** to the device **1094** using a connectionless protocol (e.g., UDP). In certain embodiments, the device **1092** may communicate with the device **1094** using a connection-oriented protocol (e.g., TCP). Although the illustrated communication **1090** is depicted as a bi-directional connection, in some embodiments, the communication **1090** may be a uni-directional broadcast.

i. Unique Local Address

As discussed above, data transmitted within a fabric received by a node may be redirected or passed through the node to another node depending on the desired target for the communication. In some embodiments, the transmission of the data may be intended to be broadcast to all devices. In such embodiments, the data may be retransmitted without further processing to determine whether the data should be passed along to another node. However, some data may be directed to a specific endpoint. To enable addressed messages to be transmitted to desired endpoints, nodes may be assigned identification information.

Each node may be assigned a set of link-local addresses (LLA), one assigned to each network interface. These LLAs may be used to communicate with other nodes on the same network. Additionally, the LLAs may be used for various communication procedures, such as IPv6 Neighbor Discovery Protocol. In addition to LLAs, each node is assigned a unique local address (ULA).

FIG. 9 illustrates an embodiment of a unique local address (ULA) **1098** that may be used to address each node in the fabric. In certain embodiments, the ULA **1098** may be formatted as an IPv6 address format containing 128 bits divided into a global ID **1100**, a subnet ID **1102**, and an interface ID **1104**. The global ID **1100** includes 40 bits and the subnet ID **1102** includes 16 bits. The global ID **1100** and subnet ID **1102** together form a fabric ID **1103** for the fabric.

The fabric ID **1103** is a unique 64-bit identifier used to identify a fabric. The fabric ID **1103** may be generated at creation of the associated fabric using a pseudo-random algorithm. For example, the pseudo-random algorithm may 1) obtain the current time of day in 64-bit NTP format, 2) obtain the interface ID **1104** for the device, 3) concatenate the time of day with the interface ID **1104** to create a key, 4) compute and SHA-1 digest on the key resulting in 160 bits, 5) use the least significant 40 bits as the global ID **1100**, and 6) concatenate the ULA and set the least significant bit to 1 to create the fabric ID **1103**. In certain embodiments, once the fabric ID **1103** is created with the fabric, the fabric ID **1103** remains until the fabric is dissolved.

The global ID **1100** identifies the fabric to which the node belongs. The subnet ID **1102** identifies logical networks within the fabric. The subnet ID **F3** may be assigned monotonically starting at one with the addition of each new logical network to the fabric. For example, a WiFi network may be identified with a hex value of 0x01, and a later connected 802.15.4 network may be identified with a hex value of 0x02 continuing on incrementally upon the connection of each new network to the fabric.

Finally, the ULA **1098** includes an interface ID **1104** that includes 64 bits. The interface ID **1104** may be assigned using a globally-unique 64-bit identifier according to the IEEE EUI-64 standard. For example, devices with IEEE 802 net-

14

work interfaces may derive the interface ID **1104** using a burned-in MAC address for the devices "primary interface." In some embodiments, the designation of which interface is the primary interface may be determined arbitrarily. In other embodiments, an interface type (e.g., WiFi) may be deemed the primary interface, when present. If the MAC address for the primary interface of a device is 48 bits rather than 64-bit, the 48-bit MAC address may be converted to a EUI-64 value via encapsulation (e.g., organizationally unique identifier encapsulating). In consumer devices (e.g., phones or computers), the interface ID **1104** may be assigned by the consumer devices' local operating systems.

ii. Routing Transmissions between Logical Networks

As discussed above in relation to a star network topology, inter-network routing may occur in communication between two devices across logical networks. In some embodiments, inter-network routing is based on the subnet ID **1102**. Each inter-networking node (e.g., node **1034** of FIG. 5) may maintain a list of other routing nodes (e.g., node B **14** of FIG. 5) on the hub network **1020** and their respective attached periphery networks (e.g., periphery network **1024** of FIG. 5). When a packet arrives addressed to a node other than the routing node itself, the destination address (e.g., address for node **1052** of FIG. 5) is compared to the list of network prefixes and a routing node (e.g., node **1044**) is selected that is attached to the desired network (e.g., periphery network **1024**). The packet is then forwarded to the selected routing node. If multiple nodes (e.g., **1034** and **1036**) are attached to the same periphery network, routing nodes are selected in an alternating fashion.

Additionally, inter-network routing nodes may regularly transmit Neighbor Discovery Protocol (NDP) router advertisement messages on the hub network to alert consumer devices to the existence of the hub network and allow them to acquire the subnet prefix. The router advertisements may include one or more route information options to assist in routing information in the fabric. For example, these route information options may inform consumer devices of the existence of the periphery networks and how to route packets the periphery networks.

In addition to, or in place of route information options, routing nodes may act as proxies to provide a connection between consumer devices and devices in periphery networks, such as the process **1105** as illustrated in FIG. 10. As illustrated, the process **1105** includes each periphery network device being assigned a virtual address on the hub network by combining the subnet ID **1102** with the interface ID **1104** for the device on the periphery network (block **1106**). To proxy using the virtual addresses, routing nodes maintain a list of all periphery nodes in the fabric that are directly reachable via one of its interfaces (block **1108**). The routing nodes listen on the hub network for neighbor solicitation messages requesting the link address of a periphery node using its virtual address (block **1110**). Upon receiving such a message, the routing node attempts to assign the virtual address to its hub interface after a period of time (block **1112**). As part of the assignment, the routing node performs duplicate address detection so as to block proxying of the virtual address by more than one routing node. After the assignment, the routing node responds to the neighbor solicitation message and receives the packet (block **1114**). Upon receiving the packet, the routing node rewrites the destination address to be the real address of the periphery node (block **1116**) and forwards the message to the appropriate interface (block **1118**).

iii. Consumer Devices Connecting to a Fabric

To join a fabric, a consumer device may discover an address of a node already in the fabric that the consumer

device wants to join. Additionally, if the consumer device has been disconnected from a fabric for an extended period of time may need to rediscover nodes on the network if the fabric topology/layout has changed. To aid in discovery/rediscovery, fabric devices on the hub network may publish Domain Name System-Service Discovery (DNS-SD) records via mDNS that advertise the presence of the fabric and provide addresses to the consumer device

III. Data Transmitted in the Fabric

After creation of a fabric and address creation for the nodes, data may be transmitted through the fabric. Data passed through the fabric may be arranged in a format common to all messages and/or common to specific types of conversations in the fabric. In some embodiments, the message format may enable one-to-one mapping to JavaScript Object Notation (JSON) using a TLV serialization format discussed below. Additionally, although the following data frames are described as including specific sizes, it should be noted that lengths of the data fields in the data frames may be varied to other suitable bit-lengths.

It should be understood that each of the following data frames, profiles, and/or formats discussed below may be stored in memory (e.g., memory of the device 10) prior to and/or after transmission of a message. In other words, although the data frame, profiles, and formats may be generally discussed as transmissions of data, they may also be physically stored (e.g., in a buffer) before, during, and/or after transmission of the data frame, profiles, and/or formats. Moreover, the following data frames, profiles, schemas, and/or formats may be stored on a non-transitory, computer-readable medium that allows an electronic device to access the data frames, profiles, schemas, and/or formats. For example, instructions for formatting the data frames, profiles, schemas, and/or formats may be stored in any suitable computer-readable medium, such as in memory for the device 10, memory of another device, a portable memory device (e.g., compact disc, flash drive, etc.), or other suitable physical device suitable for storing the data frames, profiles, schemas, and/or formats.

A. Security

Along with data intended to be transferred, the fabric may transfer the data with additional security measures such as encryption, message integrity checks, and digital signatures. In some embodiments, a level of security supported for a device may vary according to physical security of the device and/or capabilities of the device. In certain embodiments, messages sent between nodes in the fabric may be encrypted using the Advanced Encryption Standard (AES) block cipher operating in counter mode (AES-CTR) with a 128-bit key. As discussed below, each message contains a 32-bit message id. The message id may be combined with a sending nodes id to form a nonce for the AES-CTR algorithm. The 32-bit counter enables 4 billion messages to be encrypted and sent by each node before a new key is negotiated.

In some embodiments, the fabric may insure message integrity using a message authentication code, such as HMAC-SHA-1, that may be included in each encrypted message. In some embodiments, the message authentication code may be generated using a 160-bit message integrity key that is paired one-to-one with the encryption key. Additionally, each node may check the message id of incoming messages against a list of recently received ids maintained on a node-by-node basis to block replay of the messages.

B. Tag Length Value (TLV) Formatting

To reduce power consumption, it is desirable to send at least a portion of the data sent over the fabric that compactly while enabling the data containers to flexibly represents data

that accommodates skipping data that is not recognized or understood by skipping to the next location of data that is understood within a serialization of the data. In certain embodiments, tag-length-value (TLV) formatting may be used to compactly and flexibly encode/decode data. By storing at least a portion of the transmitted data in TLV, the data may be compactly and flexibly stored/sent along with low encode/decode and memory overhead, as discussed below in reference to Table 7. In certain embodiments, TLV may be used for some data as flexible, extensible data, but other portions of data that is not extensible may be stored and sent in an understood standard protocol data unit (PDU).

Data formatted in a TLV format may be encoded as TLV elements of various types, such as primitive types and container types. Primitive types include data values in certain formats, such as integers or strings. For example, the TLV format may encode: 1, 2, 3, 4, or 8 byte signed/unsigned integers, UTF-8 strings, byte strings, single/double-precision floating numbers (e.g., IEEE 754-1985 format), boolean, null, and other suitable data format types. Container types include collections of elements that are then sub-classified as container or primitive types. Container types may be classified into various categories, such as dictionaries, arrays, paths or other suitable types for grouping TLV elements, known as members. A dictionary is a collection of members each having distinct definitions and unique tags within the dictionary. An array is an ordered collection of members with implied definitions or no distinct definitions. A path is an ordered collection of members that described how to traverse a tree of TLV elements.

As illustrated in FIG. 11, an embodiment of a TLV packet 1120 includes three data fields: a tag field 1122, a length field 1124, and a value field 1126. Although the illustrated fields 1122, 1124, and 1126 are illustrated as approximately equivalent in size, the size of each field may be variable and vary in size in relation to each other. In other embodiments, the TLV packet 1120 may further include a control byte before the tag field 1122.

In embodiments having the control byte, the control byte may be sub-divided into an element type field and a tag control field. In some embodiments, the element type field includes 5 lower bits of the control byte and the tag control field occupies the upper 3 bits. The element type field indicates the TLV element's type as well as the how the length field 1124 and value field 1126 are encoded. In certain embodiments, the element type field also encodes Boolean values and/or null values for the TLV. For example, an embodiment of an enumeration of element type field is provided in Table 1 below.

TABLE 1

Example element type field values.							
7	6	5	4	3	2	1	0
		0	0	0	0	0	Signed Integer, 1 byte value
		0	0	0	0	1	Signed Integer, 2 byte value
		0	0	0	1	0	Signed Integer, 4 byte value
		0	0	0	1	1	Signed Integer, 8 byte value
		0	0	1	0	0	Unsigned Integer, 1 byte value
		0	0	1	0	1	Unsigned Integer, 2 byte value
		0	0	1	1	0	Unsigned Integer, 4 byte value
		0	0	1	1	1	Unsigned Integer, 8 byte value
		0	1	0	0	0	Boolean False
		0	1	0	0	1	Boolean True
		0	1	0	1	0	Floating Point Number, 4 byte value

17

TABLE 1-continued

Example element type field values.							
7	6	5	4	3	2	1	0
		0	1	0	1	1	Floating Point Number, 8 byte value
		0	1	1	0	0	UTF8-String, 1 byte length
		0	1	1	0	1	UTF8-String, 2 byte length
		0	1	1	1	0	UTF8-String, 4 byte length
		0	1	1	1	1	UTF8-String, 8 byte length
	1	0	0	0	0	0	Byte String, 1 byte length
	1	0	0	0	0	1	Byte String, 2 byte length
	1	0	0	1	0	0	Byte String, 4 byte length
	1	0	0	1	1	1	Byte String, 8 byte length
	1	0	1	0	0	0	Null
	1	0	1	0	1	0	Dictionary
	1	0	1	1	0	0	Array
	1	0	1	1	1	1	Path
	1	1	0	0	0	0	End of Container

The tag control field indicates a form of the tag in the tag field **1122** assigned to the TLV element (including a zero-length tag). Examples, of tag control field values are provided in Table 2 below.

TABLE 2

Example values for tag control field.							
7	6	5	4	3	2	1	0
0	0	0					Anonymous, 0 bytes
0	0	1					Context-specific Tag, 1 byte
0	1	0					Core Profile Tag, 2 bytes
0	1	1					Core Profile Tag, 4 bytes
1	0	0					Implicit Profile Tag, 2 bytes
1	0	1					Implicit Profile Tag, 4 bytes
1	1	0					Fully-qualified Tag, 6 bytes
1	1	1					Fully-qualified Tag, 8 bytes

In other words, in embodiments having a control byte, the control byte may indicate a length of the tag.

In certain embodiments, the tag field **1122** may include zero to eight bytes, such as eight, sixteen, thirty two, or sixty four bits. In some embodiments, the tag of the tag field may be classified as profile-specific tags or context-specific tags. Profile-specific tags identify elements globally using a vendor Id, a profile Id, and/or tag number as discussed below. Context-specific tags identify TLV elements within a context of a containing dictionary element and may include a single-byte tag number. Since context-specific tags are defined in context of their containers, a single context-specific tag may have different interpretations when included in different containers. In some embodiments, the context may also be derived from nested containers.

In embodiments having the control byte, the tag length is encoded in the tag control field and the tag field **1122** includes a possible three fields: a vendor Id field, a profile Id field, and a tag number field. In the fully-qualified form, the encoded tag field **1122** includes all three fields with the tag number field including 16 or 32 bits determined by the tag control field. In the implicit form, the tag includes only the tag number, and the vendor Id and profile number are inferred from the protocol context of the TLV element. The core profile form includes profile-specific tags, as discussed above. Context-specific tags are encoded as a single byte conveying the tag number. Anonymous elements have zero-length tag fields **1122**.

In some embodiments without a control byte, two bits may indicate a length of the tag field **1122**, two bits may indicate a

18

length of the length field **1124**, and four bits may indicate a type of information stored in the value field **1126**. An example of possible encoding for the upper 8 bits for the tag field is illustrated below in Table 3.

TABLE 3

Tag field of a TLV packet									
	Byte								
	0								
	7	6	5	4	3	2	1	0	Description
10	0	0	—	—	—	—	—	—	Tag is 8 bits
	0	1	—	—	—	—	—	—	Tag is 16 bits
	1	0	—	—	—	—	—	—	Tag is 32 bits
	1	1	—	—	—	—	—	—	Tag is 64 bits
15	—	—	0	0	—	—	—	—	Length is 8 bits
	—	—	0	1	—	—	—	—	Length is 16 bits
	—	—	1	0	—	—	—	—	Length is 32 bits
	—	—	1	1	—	—	—	—	Length is 64 bits
20	—	—	—	—	0	0	0	0	Boolean
	—	—	—	—	0	0	0	1	Fixed 8-bit Unsigned
	—	—	—	—	0	0	1	0	Fixed 8-bit Signed
	—	—	—	—	0	0	1	1	Fixed 16-bit Unsigned
25	—	—	—	—	0	1	0	0	Fixed 16-bit Signed
	—	—	—	—	0	1	0	1	Fixed 32-bit Unsigned
	—	—	—	—	0	1	1	0	Fixed 32-bit Signed
	—	—	—	—	0	1	1	1	Fixed 64-bit Unsigned
30	—	—	—	—	1	0	0	0	Fixed 64-bit Signed
	—	—	—	—	1	0	0	1	32-bit Floating Point
	—	—	—	—	1	0	1	0	64-bit Floating Point
	—	—	—	—	1	0	1	1	UTF-8 String
30	—	—	—	—	1	1	0	0	Opaque Data
	—	—	—	—	1	1	0	1	Container

As illustrated in Table 3, the upper 8 bits of the tag field **1122** may be used to encode information about the tag field **1122**, length field **1124**, and the value field **1126**, such that the tag field **112** may be used to determine length for the tag field **122** and the length fields **1124**. Remaining bits in the tag field **1122** may be made available for user-allocated and/or user-assigned tag values.

The length field **1124** may include eight, sixteen, thirty two, or sixty four bits as indicated by the tag field **1122** as illustrated in Table 3 or the element field as illustrated in Table 2. Moreover, the length field **1124** may include an unsigned integer that represents a length of the encoded in the value field **1126**. In some embodiments, the length may be selected by a device sending the TLV element. The value field **1126** includes the payload data to be decoded, but interpretation of the value field **1126** may depend upon the tag length fields, and/or control byte. For example, a TLV packet without a control byte including an 8 bit tag is illustrated in Table 4 below for illustration.

TABLE 4

Example of a TLV packet including an 8-bit tag			
Tag	Length	Value	Description
0x0d	0x24		
0x09	0x04	0x42 95 00 00	74.5
0x09	0x04	0x42 98 66 66	76.2
0x09	0x04	0x42 94 99 9a	74.3
0x09	0x04	0x42 98 99 9a	76.3
0x09	0x04	0x42 95 33 33	74.6
0x09	0x04	0x42 98 33 33	76.1

As illustrated in Table 4, the first line indicates that the tag field **1122** and the length field **1124** each have a length of 8 bits. Additionally, the tag field **1122** indicates that the tag type is for the first line is a container (e.g., the TLV packet). The tag

field 1124 for lines two through six indicate that each entry in the TLV packet has a tag field 1122 and length field 1124 consisting of 8 bits each. Additionally, the tag field 1124 indicates that each entry in the TLV packet has a value field 1126 that includes a 32-bit floating point. Each entry in the value field 1126 corresponds to a floating number that may be decoded using the corresponding tag field 1122 and length field 1124 information. As illustrated in this example, each entry in the value field 1126 corresponds to a temperature in Fahrenheit. As can be understood, by storing data in a TLV packet as described above, data may be transferred compactly while remaining flexible for varying lengths and information as may be used by different devices in the fabric. Moreover, in some embodiments, multi-byte integer fields may be transmitted in little-endian order or big-endian order.

By transmitting TLV packets in using an order protocol (e.g., little-endian) that may be used by sending/receiving device formats (e.g., JSON), data transferred between nodes may be transmitted in the order protocol used by at least one of the nodes (e.g., little endian). For example, if one or more nodes include ARM or ix86 processors, transmissions between the nodes may be transmitted using little-endian byte ordering to reduce the use of byte reordering. By reducing the inclusion of byte reordering, the TLV format enable devices to communicate using less power than a transmission that uses byte reordering on both ends of the transmission. Furthermore, TLV formatting may be specified to provide a one-to-one translation between other data storage techniques, such as JSON+ Extensible Markup Language (XML). As an example, the TLV format may be used to represent the following XML Property List:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE plist PUBLIC "-//Apple Computer//DTD PLIST 1.0//EN"
"http://www.apple.com/DTDs/PropertyList-1.0.dtd">
<plist version="1.0">
<dict>
  <key>OfflineMode</key>
  <false/>
  <key>Network</key>
  <dict>
    <key>IPv4</key>
    <dict>
      <key>Method</key>
      <string>dhcp</string>
    </dict>
    <key>IPv6</key>
    <dict>
      <key>Method</key>
      <string>auto</string>
    </dict>
  </dict>
  <key>Technologies</key>
  <dict>
    <key>wifi</key>
    <dict>
      <key>Enabled</key>
      <true/>
      <key>Devices</key>
      <dict>
        <key>wifi_18b4300008b027</key>
        <dict>
          <key>Enabled</key>
          <true/>
        </dict>
      </dict>
    </dict>
    <key>Services</key>
    <array>
      <string>wifi_18b4300008b027_3939382d3320416c70696e652054657272616365</string>
    </array>
  </dict>
  <key>802.15.4</key>
```

-continued

```
<dict>
  <key>Enabled</key>
  <true/>
  <key>Devices</key>
  <dict>
    <key>802.15.4_18b4300000002fac4</key>
    <dict>
      <key>Enabled</key>
      <true/>
    </dict>
  </dict>
  <key>Services</key>
  <array>
    <string>802.15.4_18b4300000002fac4_3939382d3320416c70696e6520546572</string>
  </array>
</dict>
</dict>
<key>Services</key>
<dict>
  <key>wifi_18b4300008b027_3939382d3320416c70696e6520546572
72616365</key>
  <dict>
    <key>Name</key>
    <string>998-3 Alpine Terrace</string>
    <key>SSID</key>
    <data>3939382d3320416c70696e652054657272616365
</data>
    <key>Frequency</key>
    <integer>2462</integer>
    <key>AutoConnect</key>
    <true/>
    <key>Favorite</key>
    <true/>
    <key>Error</key>
    <string/>
    <key>Network</key>
    <dict>
      <key>IPv4</key>
      <dict>
        <key>DHCP</key>
        <dict>
          <key>LastAddress</key>
          <data>0a02001e</data>
        </dict>
      </dict>
      <key>IPv6</key>
      <dict>
        </dict>
      </dict>
    </dict>
    <key>802.15.4_18b4300000002fac4_3939382d3320416c70696e
6520546572</key>
    <dict>
      <key>Name</key>
      <string>998-3 Alpine Ter</string>
      <key>EPANID</key>
      <data>3939382d3320416c70696e6520546572</data>
      <key>Frequency</key>
      <integer>2412</integer>
      <key>AutoConnect</key>
      <true/>
      <key>Favorite</key>
      <true/>
      <key>Error</key>
      <string/>
      <key>Network</key>
      <dict>
        </dict>
      </dict>
    </dict>
  </dict>
</plist>
```

As an example, the above property list may be represented in tags of the above described TLV format (without a control byte) according to Table 5 below.

21

TABLE 5

Example representation of the XML Property List in TLV format		
XML Key	Tag Type	Tag Number
OfflineMode	Boolean	1
IPv4	Container	3
IPv6	Container	4
Method	String	5
Technologies	Container	6
WiFi	Container	7
802.15.4	Container	8
Enabled	Boolean	9
Devices	Container	10
ID	String	11
Services	Container	12
Name	String	13
SSID	Data	14

22

TABLE 5-continued

Example representation of the XML Property List in TLV format		
XML Key	Tag Type	Tag Number
EPANID	Data	15
Frequency	16-bit Unsigned	16
AutoConnect	Boolean	17
Favorite	Boolean	18
Error	String	19
DHCP	String	20
LastAddress	Data	21
Device	Container	22
Service	Container	23

15 Similarly, Table 6 illustrates an example of literal tag, length, and value representations for the example XML Property List.

TABLE 6

Example of literal values for tag, length, and value fields for XML Property List			
Tag	Length	Value	Description
0x40 01	0x01	0	OfflineMode
0x4d 02	0x14		Network
0x4d 03	0x07		Network.IPv4
0x4b 05	0x04	“dhcp”	Network.IPv4.Method
0x4d 04	0x07		Network.IPv6
0x4b 05	0x04	“auto”	Network.IPv6.Method
0x4d 06	0xd6		Technologies
0x4d 07	0x65		Technologies.wifi
0x40 09	0x01	1	Technologies.wifi.Enabled
0x4d 0a	0x5e		Technologies.wifi.Devices
0x4d 16	0x5b		Technologies.wifi.Devices.Device.[0]
0x4b 0b	0x13	“wifi_18b43 . . . ”	Technologies.wifi.Devices.Device.[0].ID
0x40 09	0x01	1	Technologies.wifi.Devices.Device.[0].Enabled
0x4d 0c	0x3e		Technologies.wifi.Devices.Device.[0].Services
0x0b	0x3c	“wifi_18b43 . . . ”	Technologies.wifi.Devices.Device.[0].Services.[0]
0x4d 08	0x6b		Technologies.802.15.4
0x40 09	0x01	1	Technologies.802.15.4.Enabled
0x4d 0a	0x64		Technologies.802.15.4.Devices
0x4d 16	0x61		Technologies.802.15.4.Devices.Device.[0]
0x4b 0b	0x1a	“802.15.4_18 . . . ”	Technologies.802.15.4.Devices.Device.[0].ID
0x40 09	0x01	1	Technologies.802.15.4.Devices.Device.[0].Enabled
0x4d 0c	0x3d		Technologies.802.15.4.Devices.Device.[0].Services
0x0b	0x3b	“802.15.4_18 . . . ”	Technologies.802.15.4.Devices.Device.[0].Services.[0]
0x4d 0c	0xcb		Services
0x4d 17	0x75		Services.Service.[0]
0x4b 0b	0x13	“wifi_18b43 . . . ”	Services.Service.[0].ID
0x4b 0d	0x14	“998-3 Alp . . . ”	Services.Service.[0].Name
0x4c 0f	0x28	3939382d . . .	Services.Service.[0].SSID
0x45 10	0x02	2462	Services.Service.[0].Frequency
0x40 11	0x01	1	Services.Service.[0].AutoConnect
0x40 12	0x01	1	Services.Service.[0].Favorite
0x4d 02	0x0d		Services.Service.[0].Network
0x4d 03	0x0a		Services.Service.[0].Network.IPv4
0x4d 14	0x07		Services.Service.[0].Network.IPv4.DHCP
0x45 15	0x04	0x0a02001e	Services.Service.[0].Network.IPv4.LastAddress
0x4d 17	0x50		Services.Service.[1]
0x4b 0b	0x1a	“802.15.4_18 . . . ”	Services.Service.[1].ID
0x4c 0d	0x10	“998-3 Alp . . . ”	Services.Service.[1].Name
0x4c 0f	0x10	3939382d . . .	Services.Service.[1].EPANID
0x45 10	0x02	2412	Services.Service.[1].Frequency
0x40 11	0x01	1	Services.Service.[1].AutoConnect
0x40 12	0x01	1	Services.Service.[1].Favorite

The TLV format enables reference of properties that may also be enumerated with XML, but does so with a smaller storage size. For example, Table 7 illustrates a comparison of data sizes of the XML Property List, a corresponding binary property list, and the TLV format.

TABLE 7

Comparison of the sizes of property list data sizes.		
List Type	Size in Bytes	Percentage of XML Size
XML	2,199	—
Binary	730	~66.8%
TLV	450	~79.5%

By reducing the amount of data used to transfer data, the TLV format enables the fabric **1000** transfer data to and/or from devices having short duty cycles due to limited power (e.g., battery supplied devices). In other words, the TLV format allows flexibility of transmission while increasing compactness of the data to be transmitted.

C. General Message Protocol

In addition to sending particular entries of varying sizes, data may be transmitted within the fabric using a general message protocol that may incorporate TLV formatting. An embodiment of a general message protocol (GMP) **1128** is illustrated in FIG. **12**. In certain embodiments, the general message protocol (GMP) **1128** may be used to transmit data within the fabric. The GMP **1128** may be used to transmit data via connectionless protocols (e.g., UDP) and/or connection-oriented protocols (e.g., TCP). Accordingly, the GMP **1128** may flexibly accommodate information that is used in one protocol while ignoring such information when using another protocol. Moreover, the GMP **1226** may enable omission of fields that are not used in a specific transmission. Data that may be omitted from one or more GMP **1226** transfers is generally indicated using grey borders around the data units. In some embodiments, the multi-byte integer fields may be transmitted in a little-endian order or a big-endian order.

i. Packet Length

In some embodiments, the GMP **1128** may include a Packet Length field **1130**. In some embodiments, the Packet Length field **1130** includes 2 bytes. A value in the Packet Length field **1130** corresponds to an unsigned integer indicating an overall length of the message in bytes, excluding the Packet Length field **1130** itself. The Packet Length field **1130** may be present when the GMP **1128** is transmitted over a TCP connection, but when the GMP **1128** is transmitted over a UDP connection, the message length may be equal to the payload length of the underlying UDP packet obviating the Packet Length field **1130**.

ii. Message Header

The GMP **1128** may also include a Message Header **1132** regardless of whether the GMP **1128** is transmitted using TCP or UDP connections. In some embodiments, the Message Header **1132** includes two bytes of data arranged in the format illustrated in FIG. **13**. As illustrated in FIG. **13**, the Message Header **1132** includes a Version field **1156**. The Version field **1156** corresponds to a version of the GMP **1128** that is used to encode the message. Accordingly, as the GMP **1128** is updated, new versions of the GMP **1128** may be created, but each device in a fabric may be able to receive a data packet in any version of GMP **1128** known to the device. In addition to the Version field **1156**, the Message Header **1132** may include an S Flag field **1158** and a D Flag **1160**. The S Flag **1158** is a single bit that indicates whether a Source Node Id (discussed below) field is included in the transmitted packet. Similarly,

the D Flag **1160** is a single bit that indicates whether a Destination Node Id (discussed below) field is included in the transmitted packet.

The Message Header **1132** also includes an Encryption Type field **1162**. The Encryption Type field **1162** includes four bits that specify which type of encryption/integrity checking applied to the message, if any. For example, 0x0 may indicate that no encryption or message integrity checking is included, but a decimal 0x1 may indicate that AES-128-CTR encryption with HMAC-SHA-1 message integrity checking is included.

Finally, the Message Header **1132** further includes a Signature Type field **1164**. The Signature Type field **1164** includes four bits that specify which type of digital signature is applied to the message, if any. For example, 0x0 may indicate that no digital signature is included in the message, but 0x1 may indicate that the Elliptical Curve Digital Signature Algorithm (ECDSA) with Prime256v1 elliptical curve parameters is included in the message.

iii. Message Id

Returning to FIG. **12**, the GMP **1128** also includes a Message Id field **1134** that may be included in a transmitted message regardless of whether the message is sent using TCP or UDP. The Message Id field **1134** includes four bytes that correspond to an unsigned integer value that uniquely identifies the message from the perspective of the sending node. In some embodiments, nodes may assign increasing Message Id **1134** values to each message that they send returning to zero after reaching 2^{32} messages.

iv. Source Node Id

In certain embodiments, the GMP **1128** may also include a Source Node Id field **1136** that includes eight bytes. As discussed above, the Source Node Id field **1136** may be present in a message when the single-bit S Flag **1158** in the Message Header **1132** is set to 1. In some embodiments, the Source Node Id field **1136** may contain the Interface ID **1104** of the ULA **1098** or the entire ULA **1098**. In some embodiments, the bytes of the Source Node Id field **1136** are transmitted in an ascending index-value order (e.g., EU1[0] then EU1[1] then EU1[2] then EU1[3], etc.).

v. Destination Node Id

The GMP **1128** may include a Destination Node Id field **1138** that includes eight bytes. The Destination Node Id field **1138** is similar to the Source Node Id field **1136**, but the Destination Node Id field **1138** corresponds to a destination node for the message. The Destination Node Id field **1138** may be present in a message when the single-bit D Flag **1160** in the Message Header **1132** is set to 1. Also similar to the Source Node Id field **1136**, in some embodiments, bytes of the Destination Node Id field **1138** may be transmitted in an ascending index-value order (e.g., EU1[0] then EU1[1] then EU1[2] then EU1[3], etc.).

vi. Key Id

In some embodiments, the GMP **1128** may include a Key Id field **1140**. In certain embodiments, the Key Id field **1140** includes two bytes. The Key Id field **1140** includes an unsigned integer value that identifies the encryption/message integrity keys used to encrypt the message. The presence of the Key Id field **1140** may be determined by the value of Encryption Type field **1162** of the Message Header **1132**. For example, in some embodiments, when the value for the Encryption Type field **1162** of the Message Header **1132** is 0x0, the Key Id field **1140** may be omitted from the message.

An embodiment of the Key Id field **1140** is presented in FIG. **14**. In the illustrated embodiment, the Key Id field **1140** includes a Key Type field **1166** and a Key Number field **1168**. In some embodiments, the Key Type field **1166** includes four

bits. The Key Type field **1166** corresponds to an unsigned integer value that identifies a type of encryption/message integrity used to encrypt the message. For example, in some embodiments, if the Key Type field **1166** is 0x0, the fabric key is shared by all or most of the nodes in the fabric. However, if the Key Type field **1166** is 0x1, the fabric key is shared by a pair of nodes in the fabric.

The Key Id field **1140** also includes a Key Number field **1168** that includes twelve bits that correspond to an unsigned integer value that identifies a particular key used to encrypt the message out of a set of available keys, either shared or fabric keys.

vii. Payload Length

In some embodiments, the GMP **1128** may include a Payload Length field **1142**. The Payload Length field **1142**, when present, may include two bytes. The Payload Length field **1142** corresponds to an unsigned integer value that indicates a size in bytes of the Application Payload field. The Payload Length field **1142** may be present when the message is encrypted using an algorithm that uses message padding, as described below in relation to the Padding field.

viii. Initialization Vector

In some embodiments, the GMP **1128** may also include an Initialization Vector (IV) field **1144**. The IV field **1144**, when present, includes a variable number of bytes of data. The IV field **1144** contains cryptographic IV values used to encrypt the message. The IV field **1144** may be used when the message is encrypted with an algorithm that uses an IV. The length of the IV field **1144** may be derived by the type of encryption used to encrypt the message.

ix. Application Payload

The GMP **1128** includes an Application Payload field **1146**. The Application Payload field **1146** includes a variable number of bytes. The Application Payload field **1146** includes application data conveyed in the message. The length of the Application Payload field **1146** may be determined from the Payload Length field **1142**, when present. If the Payload Length field **1142** is not present, the length of the Application Payload field **1146** may be determined by subtracting the length of all other fields from the overall length of the message and/or data values included within the Application Payload **1146** (e.g., TLV).

An embodiment of the Application Payload field **1146** is illustrated in FIG. 15. The Application Payload field **1146** includes an APVersion field **1170**. In some embodiments, the APVersion field **1170** includes eight bits that indicate what version of fabric software is supported by the sending device. The Application Payload field **1146** also includes a Message Type field **1172**. The Message Type field **1172** may include eight bits that correspond to a message operation code that indicates the type of message being sent within a profile. For example, in a software update profile, a 0x00 may indicate that the message being sent is an image announce. The Application Payload field **1146** further includes an Exchange Id field **1174** that includes sixteen bits that corresponds to an exchange identifier that is unique to the sending node for the transaction.

In addition, the Application Payload field **1146** includes a Profile Id field **1176**. The Profile Id **1176** indicates a “theme of discussion” used to indicate what type of communication occurs in the message. The Profile Id **1176** may correspond to one or more profiles that a device may be capable of communicating. For example, the Profile Id **1176** may indicate that the message relates to a core profile, a software update profile, a status update profile, a data management profile, a climate and comfort profile, a security profile, a safety profile, and/or other suitable profile types. Each device on the fabric may

include a list of profiles which are relevant to the device and in which the device is capable of “participating in the discussion.” For example, many devices in a fabric may include the core profile, the software update profile, the status update profile, and the data management profile, but only some devices would include the climate and comfort profile. The APVersion field **1170**, Message Type field **1172**, the Exchange Id field, the Profile Id field **1176**, and the Profile-Specific Header field **1176**, if present, may be referred to in combination as the “Application Header.”

In some embodiments, an indication of the Profile Id via the Profile Id field **1176** may provide sufficient information to provide a schema for data transmitted for the profile. However, in some embodiments, additional information may be used to determine further guidance for decoding the Application Payload field **1146**. In such embodiments, the Application Payload field **1146** may include a Profile-Specific Header field **1178**. Some profiles may not use the Profile-Specific Header field **1178** thereby enabling the Application Payload field **1146** to omit the Profile-Specific Header field **1178**. Upon determination of a schema from the Profile Id field **1176** and/or the Profile-Specific Header field **1178**, data may be encoded/decoded in the Application Payload sub-field **1180**. The Application Payload sub-field **1180** includes the core application data to be transmitted between devices and/or services to be stored, rebroadcast, and/or acted upon by the receiving device/service.

x. Message Integrity Check

Returning to FIG. 12, in some embodiments, the GMP **1128** may also include a Message Integrity Check (MIC) field **1148**. The MIC field **1148**, when present, includes a variable length of bytes of data containing a MIC for the message. The length and byte order of the field depends upon the integrity check algorithm in use. For example, if the message is checked for message integrity using HMAC-SHA-1, the MIC field **1148** includes twenty bytes in big-endian order. Furthermore, the presence of the MIC field **1148** may be determined by whether the Encryption Type field **1162** of the Message Header **1132** includes any value other than 0x0.

xi. Padding

The GMP **1128** may also include a Padding field **1150**. The Padding field **1150**, when present, includes a sequence of bytes representing a cryptographic padding added to the message to make the encrypted portion of the message evenly divisible by the encryption block size. The presence of the Padding field **1150** may be determined by whether the type of encryption algorithm (e.g., block ciphers in cipher-block chaining mode) indicated by the Encryption Type field **1162** in the Message Header **1132** uses cryptographic padding.

xii. Encryption

The Application Payload field **1146**, the MIC field **1148**, and the Padding field **1150** together form an Encryption block **1152**. The Encryption block **1152** includes the portions of the message that are encrypted when the Encryption Type field **1162** in the Message Header **1132** is any value other than 0x0.

xiii. Message Signature

The GMP **1128** may also include a Message Signature field **1154**. The Message Signature field **1154**, when present, includes a sequence of bytes of variable length that contains a cryptographic signature of the message. The length and the contents of the Message Signature field may be determined according to the type of signature algorithm in use and indicated by the Signature Type field **1164** of the Message Header **1132**. For example, if ECDSA using the Prime256v1 elliptical curve parameters is the algorithm in use, the Message Signature field **1154** may include two thirty-two bit integers encoded in little-endian order.

IV. Profiles and Protocols

As discussed above, one or more schemas of information may be selected upon desired general discussion type for the message. A profile may consist of one or more schemas. For example, one set of schemas of information may be used to encode/decode data in the Application Payload sub-field **1180** when one profile is indicated in the Profile Id field **1176** of the Application Payload **1146**. However, a different set of schemas may be used to encode/decode data in the Application Payload sub-field **1180** when a different profile is indicated in the Profile Id field **1176** of the Application Payload **1146**.

Additionally, in certain embodiments, each device may include a set of methods used to process profiles. For example, a core protocol may include the following profiles: GetProfiles, GetSchema, GetSchemas, GetProperty, GetProperties, SetProperty, SetProperties, RemoveProperty, RemoveProperties, RequestEcho, NotifyPropertyChanged, and/or NotifyPropertiesChanged. The Get Profiles method may return an array of profiles supported by a queried node. The GetSchema and GetSchemas methods may respectively return one or all schemas for a specific profile. GetProperty and GetProperties may respectively return a value or all value pairs for a profile schema. SetProperty and SetProperties may respectively set single or multiple values for a profile schema. RemoveProperty and RemoveProperties may respectively attempt to remove a single or multiple values from a profile schema. RequestEcho may send an arbitrary data payload to a specified node which the node returns unmodified. NotifyPropertyChange and NotifyPropertiesChanged may respectively issue a notification if a single/multiple value pairs have changed for a profile schema.

To aid in understanding profiles and schemas, a non-exclusive list of profiles and schemas are provided below for illustrative purposes.

A. Status Reporting

A status reporting schema is presented as the status reporting frame **1182** in FIG. **16**. The status reporting schema may be a separate profile or may be included in one or more profiles (e.g., a core profile). In certain embodiments, the status reporting frame **1182** includes a profile field **1184**, a status code field **1186**, a next status field **1188**, and may include an additional status info field **1190**.

i. Profile Field

In some embodiments, the profile field **1184** includes four bytes of data that defines the profile under which the information in the present status report is to be interpreted. An embodiment of the profile field **1184** is illustrated in FIG. **17** with two sub-fields. In the illustrated embodiment, the profile field **1184** includes a profile Id sub-field **1192** that includes sixteen bits that corresponds to a vendor-specific identifier for the profile under which the value of the status code field **1186** is defined. The profile field **1184** may also include a vendor Id sub-field **1194** that includes sixteen bits that identifies a vendor providing the profile identified in the profile Id sub-field **1192**.

ii. Status Code

In certain embodiments, the status code field **1186** includes sixteen bits that encode the status that is being reported. The values in the status code field **1186** are interpreted in relation to values encoded in the vendor Id sub-field **1192** and the profile Id sub-field **1194** provided in the profile field **1184**. Additionally, in some embodiments, the status code space may be divided into four groups, as indicated in Table 8 below.

TABLE 8

Status Code Range Table		
Range	Name	Description
0x0000 . . . 0x0010	success	A request was successfully processed.
0x0011 . . . 0x0020	client error	An error has or may have occurred on the client-side of a client/server exchange. For example, the client has made a badly-formed request.
0x0021 . . . 0x0030	server error	An error has or may have occurred on the server side of a client/server exchange. For example, the server has failed to process a client request to an operating system error.
0x0031 . . . 0x0040	continue/redirect	Additional processing will be used, such as redirection, to complete a particular exchange, but no errors yet.

Although Table 8 identifies general status code ranges that may be used separately assigned and used for each specific profile Id, in some embodiments, some status codes may be common to each of the profiles. For example, these profiles may be identified using a common profile (e.g., core profile) identifier, such as 0x00000000.

iii. Next Status

In some embodiments, the next status code field **1188** includes eight bits. The next status code field **1188** indicates whether there is following status information after the currently reported status. If following status information is to be included, the next status code field **1188** indicates what type of status information is to be included. In some embodiments, the next status code field **1188** may always be included, thereby potentially increasing the size of the message. However, by providing an opportunity to chain status information together, the potential for overall reduction of data sent may be reduced. If the next status field **1186** is 0x00, no following status information field **1190** is included. However, non-zero values may indicate that data may be included and indicate the form in which the data is included (e.g., in a TLV packet).

iv. Additional Status Info

When the next status code field **1188** is non-zero, the additional status info field **1190** is included in the message. If present, the status item field may contain status in a form that may be determined by the value of the preceding status type field (e.g., TLV format).

B. Software Update

The software update profile or protocol is a set of schemas and a client/server protocol that enables clients to be made aware of or seek information about the presence of software that they may download and install. Using the software update protocol, a software image may be provided to the profile client in a format known to the client. The subsequent processing of the software image may be generic, device-specific, or vendor-specific and determined by the software update protocol and the devices.

i. General Application Headers for the Application Payload

In order to be recognized and handled properly, software update profile frames may be identified within the Application Payload field **1146** of the GMP **1128**. In some embodiments, all software update profile frames may use a common Profile Id **1176**, such as 0x0000000C. Additionally, software update profile frames may include a Message Type field **1172**

that indicates additional information and may be chosen according to Table 9 below and the type of message being sent.

TABLE 9

Software update profile message types	
Type	Message
0x00	image announce
0x01	image query
0x02	image query response
0x03	download notify
0x04	notify response
0x05	update notify
0x06 . . . 0xff	reserved

Additionally, as described below, the software update sequence may be initiated by a server sending the update as an image announce or a client receiving the update as an image query. In either embodiment, an Exchange Id **1174** from the initiating event is used for all messages used in relation to the software update.

ii. Protocol Sequence

FIG. **18** illustrates an embodiment of a protocol sequence **1196** for a software update between a software update client **1198** and a software update server **1200**. In certain embodiments, any device in the fabric may be the software update client **1198** or the software update server **1200**. Certain embodiments of the protocol sequence **1196** may include additional steps, such as those illustrated as dashed lines that may be omitted in some software update transmissions.

1. Service Discovery

In some embodiments, the protocol sequence **1196** begins with a software update profile server announcing a presence of the update. However, in other embodiments, such as the illustrated embodiment, the protocol sequence **1196** begins with a service discovery **1202**, as discussed above.

2. Image Announce

In some embodiments, an image announce message **1204** may be multicast or unicast by the software update server **1200**. The image announce message **1204** informs devices in the fabric that the server **1200** has a software update to offer. If the update is applicable to the client **1198**, upon receipt of the image announce message **1204**, the software update client **1198** responds with an image query message **1206**. In certain embodiments, the image announce message **1204** may not be included in the protocol sequence **1196**. Instead, in such embodiments, the software update client **1198** may use a polling schedule to determine when to send the image query message **1206**.

3. Image Query

In certain embodiments, the image query message **1206** may be unicast from the software update client **1198** either in response to an image announce message **1204** or according to a polling schedule, as discussed above. The image query message **1206** includes information from the client **1198** about itself. An embodiment of a frame of the image query message **1206** is illustrated in FIG. **19**. As illustrated in FIG. **19**, certain embodiments of the image query message **1206** may include a frame control field **1218**, a product specification field **1220**, a vendor specific data field **1222**, a version specification field **1224**, a locale specification field **1226**, an integrity type supported field **1228**, and an update schemes supported field **1230**.

a. Frame Control

The frame control field **1218** includes 1 byte and indicates various information about the image query message **1204**. An

example of the frame control field **1218** is illustrated in FIG. **20**. As illustrated, the frame control field **1218** may include three sub-fields: vendor specific flag **1232**, locale specification flag **1234**, and a reserved field **S3**. The vendor specific flag **1232** indicates whether the vendor specific data field **1222** is included in the message image query message. For example, when the vendor specific flag **1232** is 0 no vendor specific data field **1222** may be present in the image query message, but when the vendor specific flag **1232** is 1 the vendor specific data field **1222** may be present in the image query message. Similarly, a 1 value in the locale specification flag **1234** indicates that a locale specification field **1226** is present in the image query message, and a 0 value indicates that the locale specification field **1226** is not present in the image query message.

b. Product Specification

The product specification field **1220** is a six byte field. An embodiment of the product specification field **1220** is illustrated in FIG. **21**. As illustrated, the product specification field **1220** may include three sub-fields: a vendor Id field **1236**, a product Id field **1238**, and a product revision field **1240**. The vendor Id field **1236** includes sixteen bits that indicate a vendor for the software update client **1198**. The product Id field **1238** includes sixteen bits that indicate the device product that is sending the image query message **1206** as the software update client **1198**. The product revision field **1240** includes sixteen bits that indicate a revision attribute of the software update client **1198**.

c. Vendor Specific Data

The vendor specific data field **1222**, when present in the image query message **1206**, has a length of a variable number of bytes. The presence of the vendor specific data field **1222** may be determined from the vendor specific flag **1232** of the frame control field **1218**. When present, the vendor specific data field **1222** encodes vendor specific information about the software update client **1198** in a TLV format, as described above.

d. Version Specification

An embodiment of the version specification field **1224** is illustrated in FIG. **22**. The version specification field **1224** includes a variable number of bytes sub-divided into two sub-fields: a version length field **1242** and a version string field **1244**. The version length field **1242** includes eight bits that indicate a length of the version string field **1244**. The version string field **1244** is variable in length and determined by the version length field **1242**. In some embodiments, the version string field **1244** may be capped at 255 UTF-8 characters in length. The value encoded in the version string field **1244** indicates a software version attribute for the software update client **1198**.

e. Locale Specification

In certain embodiments, the locale specification field **1226** may be included in the image query message **1206** when the locale specification flag **1234** of the frame control **1218** is 1. An embodiment of the locale specification field **1226** is illustrated in FIG. **23**. The illustrated embodiment of the locale specification field **1226** includes a variable number of bytes divided into two sub-fields: a locale string length field **1246** and a locale string field **1248**. The locale string length field **1246** includes eight bits that indicate a length of the locale string field **1248**. The locale string field **1248** of the locale specification field **1226** may be variable in length and contain a string of UTF-8 characters encoding a local description based on Portable Operating System Interface (POSIX) locale codes. The standard format for POSIX locale codes is

31

[language[_territory]][.codeset][[@modifier]] For example, the POSIX representation for Australian English is en_AU.UTF8.

f. Integrity Types Supported

An embodiment of the integrity types field **1228** is illustrated in FIG. **24**. The integrity types supported field **1228** includes two to four bytes of data divided into two sub-fields: a type list length field **1250** and an integrity type list field **1252**. The type list length field **1250** includes eight bits that indicate the length in bytes of the integrity type list field **1252**. The integrity type list field **1252** indicates the value of the software update integrity type attribute of the software update client **1198**. In some embodiments, the integrity type may be derived from Table 10 below.

TABLE 10

Example integrity types	
Value	Integrity Type
0x00	SHA-160
0x01	SHA-256
0x02	SHA-512

The integrity type list field **1252** may contain at least one element from Table 10 or other additional values not included.

g. Update Schemes Supported

An embodiment of the schemes supported field **1230** is illustrated in FIG. **25**. The schemes supported field **1230** includes a variable number of bytes divided into two sub-fields: a scheme list length field **1254** and an update scheme list field **1256**. The scheme list length field **1254** includes eight bits that indicate a length of the update scheme list field in bytes. The update scheme list field **1256** of the update schemes supported field **1222** is variable in length determined by the scheme list length field **1254**. The update scheme list field **1256** represents an update schemes attributes of the software update profile of the software update client **1198**. An embodiment of example values is shown in Table 11 below.

TABLE 11

Example update schemes	
Value	Update Scheme
0x00	HTTP
0x01	HTTPS
0x02	SFTP
0x03	Fabric-specific File Transfer Protocol (e.g., Bulk Data Transfer discussed below)

Upon receiving the image query message **1206**, the software update server **1200** uses the transmitted information to determine whether the software update server **1200** has an update for the software update client **1198** and how best to deliver the update to the software update client **1198**.

4. Image Query Response

Returning to FIG. **18**, after the software update server **1200** receives the image query message **1206** from the software update client **1198**, the software update server **1200** responds with an image query response **1208**. The image query response **1208** includes either information detailing why an update image is not available to the software update client **1198** or information about the available image update to enable to software update client **1198** to download and install the update.

32

An embodiment of a frame of the image query response **1208** is illustrated in FIG. **26**. As illustrated, the image query response **1208** includes five possible sub-fields: a query status field **1258**, a uniform resource identifier (URI) field **1260**, an integrity specification field **1262**, an update scheme field **1264**, and an update options field **1266**.

a. Query Status

The query status field **1258** includes a variable number of bytes and contains status reporting formatted data, as discussed above in reference to status reporting. For example, the query status field **1258** may include image query response status codes, such as those illustrated below in Table 12.

TABLE 12

Example image query response status codes		
Profile	Code	Description
0x00000000	0x0000	The server has processed the image query message 1206 and has an update for the software update client 1198.
0x0000000C	0x0001	The server has processed the image query message 1206, but the server does not have an update for the software update client 1198.
0x00000000	0x0010	The server could not process the request because of improper form for the request.
0x00000000	0x0020	The server could not process the request due to an internal error

b. URI

The URI field **1260** includes a variable number of bytes. The presence of the URI field **1260** may be determined by the query status field **1258**. If the query status field **1258** indicates that an update is available, the URI field **1260** may be included. An embodiment of the URI field **1260** is illustrated in FIG. **27**. The URI field **1260** includes two sub-fields: a URI length field **1268** and a URI string field **1270**. The URI length field **1268** includes sixteen bits that indicates the length of the URI string field **1270** in UTF-8 characters. The URI string field **1270** and indicates the URI attribute of the software image update being presented, such that the software update client **1198** may be able to locate, download, and install a software image update, when present.

c. Integrity Specification

The integrity specification field **1262** may variable in length and present when the query status field **1258** indicates that an update is available from the software update server **1198** to the software update client **1198**. An embodiment of the integrity specification field **1262** is illustrated in FIG. **28**. As illustrated, the integrity specification field **1262** includes two sub-fields: an integrity type field **1272** and an integrity value field **1274**. The integrity type field **1272** includes eight bits that indicates an integrity type attribute for the software image update and may be populated using a list similar to that illustrated in Table 10 above. The integrity value field **1274** includes the integrity value that is used to verify that the image update message has maintained integrity during the transmission.

d. Update Scheme

The update scheme field **1264** includes eight bits and is present when the query status field **1258** indicates that an update is available from the software update server **1198** to the software update client **1198**. If present, the update scheme field **1264** indicates a scheme attribute for the software update image being presented to the software update server **1198**.

33

e. Update Options

The update options field **1266** includes eight bits and is present when the query status field **1258** indicates that an update is available from the software update server **1198** to the software update client **1198**. The update options field **1266** may be sub-divided as illustrated in FIG. **29**. As illustrated, the update options field **1266** includes four sub-fields: an update priority field **1276**, an update condition field **1278**, a report status flag **1280**, and a reserved field **1282**. In some embodiments, the update priority field **1276** includes two bits. The update priority field **1276** indicates a priority attribute of the update and may be determined using values such as those illustrated in Table 13 below.

TABLE 13

Example update priority values	
Value	Description
00	Normal - update during a period of low network traffic
01	Critical - update as quickly as possible

The update condition field **1278** includes three bits that may be used to determine conditional factors to determine when or if to update. For example, values in the update condition field **1278** may be decoded using the Table 14 below.

TABLE 14

Example update conditions	
Value	Description
0	Update without conditions
1	Update if the version of the software running on the update client software does not match the update version.
2	Update if the version of the software running on the update client software is older than the update version.
3	Update if the user opts into an update with a user interface

The report status flag **1280** is a single bit that indicates whether the software update client **1198** should respond with a download notify message **1210**. If the report status flag **1280** is set to 1 the software update server **1198** is requesting a download notify message **1210** to be sent after the software update is downloaded by the software update client **1200**.

If the image query response **1208** indicates that an update is available. The software update client **1198** downloads **1210** the update using the information included in the image query response **1208** at a time indicated in the image query response **1208**.

5. Download Notify

After the update download **1210** is successfully completed or failed and the report status flag **1280** value is 1, the software update client **1198** may respond with the download notify message **1212**. The download notify message **1210** may be formatted in accordance with the status reporting format discussed above. An example of status codes used in the download notify message **1212** is illustrated in Table 15 below.

TABLE 15

Example download notify status codes		
Profile	Code	Description
0x00000000	0x0000	The download has been completed, and integrity verified

34

TABLE 15-continued

Example download notify status codes		
Profile	Code	Description
0x0000000C	0x0020	The download could not be completed due to faulty download instructions.
0x0000000C	0x0021	The image query response message 1208 appears proper, but the download or integrity verification failed.
0x0000000C	0x0022	The integrity of the download could not be verified.

In addition to the status reporting described above, the download notify message **1208** may include additional status information that may be relevant to the download and/or failure to download.

6. Notify Response

The software update server **1200** may respond with a notify response message **1214** in response to the download notify message **1212** or an update notify message **1216**. The notify response message **1214** may include the status reporting format, as described above. For example, the notify response message **1214** may include status codes as enumerated in Table 16 below.

TABLE 16

Example notify response status codes		
Profile	Code	Description
0x00000000	0x0030	Continue- the notification is acknowledged, but the update has not completed, such as download notify message 1214 received but update notify message 1216 has not.
0x00000000	0x0000	Success - the notification is acknowledged, and the update has completed.
0x0000000C	0x0023	Abort - the notification is acknowledged, but the server cannot continue the update.
0x0000000C	0x0031	Retry query - the notification is acknowledged, and the software update client 1198 is directed to retry the update by submitting another image query message 1206.

In addition to the status reporting described above, the notify response message **1214** may include additional status information that may be relevant to the download, update, and/or failure to download/update the software update.

7. Update Notify

After the update is successfully completed or failed and the report status flag **1280** value is 1, the software update client **1198** may respond with the update notify message **1216**. The update notify message **1216** may use the status reporting format described above. For example, the update notify message **1216** may include status codes as enumerated in Table 17 below.

TABLE 17

Example update notify status codes		
Profile	Code	Description
0x00000000	0x0000	Success - the update has been completed.
0x0000000C	0x0010	Client error - the update failed due to a problem in the software update client 1198.

In addition to the status reporting described above, the update notify message **1216** may include additional status information that may be relevant to the update and/or failure to update.

35

C. Data Management Protocol

Data management may be included in a common profile (e.g., core profile) used in various electronic devices within the fabric or may be designated as a separate profile. In either situation, the device management protocol (DMP) may be used for nodes to browse, share, and/or update node-resident information. A sequence **1284** used in the DMP is illustrated in FIG. **30**. The sequence **1284** illustrates a viewing node **1286** that requests to view and/or change resident data of a viewed node **1288**. Additionally, the viewing node **1286** may request to view the resident data using one of several viewing options, such as a snapshot request, a watching request that the viewing persists over a period of time, or other suitable viewing type. Each message follows the format for the Application Payload **1146** described in reference to FIG. **15**. For example, each message contains a profile Id **1176** that corresponds to the data management profile and/or the relevant core profile, such as 0x235A0000. Each message also contains a message type **1172**. The message type **1172** may be used to determine various factors relating the conversation, such as viewing type for the view. For example, in some embodiments, the message type field **1172** may be encoded/decoded according to Table 18 below.

TABLE 18

Example software update profile message types	
Type	Message
0x00	snapshot request
0x01	watch request
0x02	periodic update request
0x03	refresh update
0x04	cancel view update
0x05	view response
0x06	explicit update request
0x07	view update request
0x08	update response

i. View Request

Although a view request message **1290** requests to view node-resident data, the type of request may be determined by the message type field **1172**, as discussed above. Accordingly each request type may include a different view request frame.

1. Snapshot Request

A snapshot request may be sent by the viewing node **1286** when the viewing node **1286** desires an instantaneous view into the node-resident data on the viewed node **1288** without requesting future updates. An embodiment of a snapshot request frame **1292** is illustrated in FIG. **31**.

As illustrated in FIG. **31**, the snapshot request frame **1292** may be variable in length and include three fields: a view handle field **1294**, a path length list field **1296**, and a path list field **1298**. The view handle field **1294** may include two bits that provide a “handle” to identify the requested view. In some embodiments, the view handle field **1294** is populated using a random 16-bit number or a 16-bit sequence number along with a uniqueness check performed on the viewing node **1286** when the request is formed. The path list length field **1296** includes two bytes that indicate a length of the path list field **1298**. The path list field **1298** is variable in length and indicated by the value of the path list length field **1296**. The value of the path list field **1298** indicates a schema path for nodes.

A schema path is a compact description for a data item or container that is part of a schema resident on the nodes. For example, FIG. **32** provides an example of a profile schema

36

1300. In the illustrated profile schema **1300**, a path to data item **1302** may be written as “Foo:bicycle:mountain” in a binary format. The binary format of the path may be represented as a profile binary format **1304**, as depicted in FIG. **33**.

The profile binary format **1304** includes two sub-fields: a profile identifier field **1306** and a TLV data field **1308**. The profile identifier field **1306** identifies which profile is being referenced (e.g., Foo profile). The TLV data field **1308** path information. As previously discussed TLV data includes a tag field that includes information about the enclosed data. Tag field values used to refer to the Foo profile of FIG. **32** may be similar to those values listed in Table 19.

TABLE 19

Example tag values for the Foo profile	
Name	Tag
animal	0x4301
fish	0x4302
fowl	0x4303
medium	0x4304
size	0x4305
bicycle	0x4306
road	0x4307
mountain	0x4308
track	0x4309
# of gears	0x430A
weight	0x430B

Using Table 19 and the Foo profile of FIG. **32**, a binary string in TLV format representing the path “Foo:bicycle:mountain” may be represented as shown in Table 20 below.

TABLE 20

Example binary tag list for a schema path			
Profile ID	Tag and Length (TL)	“bicycle”	“mountain”
CD:AB:00:00	0D:02	06:43	08:43

If the viewing node **1286** desires to receive an entire data set defined in a profile schema (e.g. Foo profile schema of FIG. **33**), the view request message **1290** may request a “nil” item (e.g., 0x0D00 TL and an empty length referring to the container).

2. Watch Request

If the viewing node **1286** desires more than a snapshot, the viewing node **1286** may request a watch request. A watch request asks the viewed node **1288** to send updates when changes are made to the data of interest in viewed node **1288** so that viewing node **1286** can keep a synchronized list of the data. The watch request frame may have a different format than the snapshot request of FIG. **31**. An embodiment of a watch request frame **1310** is illustrated in FIG. **34**. The watch request frame **1310** includes four fields: a view handle field **1312**, a path list length field **1314**, a path list field **1316**, and a change count field **1318**. The view handle field **1312**, the path list length field **1314**, and the path list field may be respectively formatted similar to the view handle field **1294**, the path list length field **1296**, and the path list field **1298** of the snapshot request of FIG. **31**. The additional field, the change count field **1318**, indicates a threshold of a number of changes to the requested data at which an update is sent to the viewing node **1286**. In some embodiments, if the value of the change count field **1318** is 0, the viewed node **1288** may determine when to send an update on its own. If the value of

the change count field **1318** is nonzero then after a number of changes equal to the value, then an update is sent to the viewing node **1286**.

3. Periodic Update Request

A third type of view may also be requested by the viewing node **1286**. This third type of view is referred to as a periodic update. A periodic update includes a snapshot view as well as periodic updates. As can be understood, a periodic update request may be similar to the snapshot request with additional information determining the update period. For example, an embodiment of a periodic update request frame **1320** is depicted in FIG. **35**. The periodic update request frame **1320** includes four fields: a view handle field **1322**, a path list length field **1324**, a path list field **1326**, and an update period field **1328**. The view handle field **1322**, the path list length field **1324**, and the path list field **1326** may be formatted similar to their respective fields in the snapshot request frame **1292**. The update period field **1328** is four bytes in length and contains a value that corresponds to a period of time to lapse between updates in a relevant unit of time (e.g., seconds).

4. Refresh Request

When the viewing node **1286** desires to receive an updated snapshot, the viewing node **1286** may send a view request message **1290** in the form of a refresh request frame **1330** as illustrated in FIG. **36**. The refresh request frame **1330** essentially resends a snapshot view handle field (e.g., view handle field **1294**) from a previous snapshot request that the viewed node **1288** can recognize as a previous request using the view handle value in the refresh request frame **1330**.

5. Cancel View Request

When the viewing node **1286** desires to cancel an ongoing view (e.g., periodic update or watch view), the viewing node **1286** may send a view request message **1290** in the form of a cancel view request frame **1332** as illustrated in FIG. **37**. The cancel view request frame **1332** essentially resends a view handle field from a previous periodic update or watch view (e.g., view handle fields **1310**, or **1322**) from a previous request that the viewed node **1288** can recognize as a previous request using the view handle value in the refresh request frame **1330** and to cancel a currently periodic update or watch view.

ii. View Response

Returning to FIG. **30**, after the viewed node **1288** receives a view request message **1290**, the viewed node **1288** responds with a view response message **1334**. An example of a view response message frame **1336** is illustrated in FIG. **38**. The view response message frame **1336** includes three fields: a view handle field **1338**, a view request status field **1340**, and a data item list **1242**. The view handle field **1338** may be formatted similar to any of the above referenced view handle fields **1338**. Additionally, the view handle field **1338** contains a value that matches a respective view handle field from the view request message **1290** to which the view response message **1334** is responding. The view request status field **1340** is a variable length field that indicates a status of the view request and may be formatted according to the status updating format discussed above. The data item list field **1342** is a variable length field that is present when the view request status field **1340** indicates that the view request was successful. When present, the data item list field **1342** contains an ordered list of requested data corresponding to the path list of the view request message **1290**. Moreover, the data in the data item list field **1342** may be encoded in a TLV format, as discussed above.

iii. Update Request

As discussed above, in some embodiments, the viewed node **1288** may send updates to the viewing node **1286**. These

updates may be sent as an update request message **1344**. The update request message **1344** may include a specified format dependent upon a type of update request. For example, an update request may be an explicit update request or a view update request field that may be identified by the Message Id **1172**.

1. Explicit Update Request

An explicit update request may be transmitted at any time as a result of a desire for information from another node in the fabric **1000**. An explicit update request may be formatted in an update request frame **1346** illustrated in FIG. **39**. The illustrated update request frame **1346** includes four fields: an update handle field **1348**, a path list length field **1350**, a path list field **1352**, and a data item list field **1354**.

The update handle field **1348** includes two bytes that may be populated with random or sequential numbers with uniqueness checks to identify an update request or responses to the request. The path list length field **1350** includes two bytes that indicate a length of the path list field **1352**. The path list field **1352** is a variable length field that indicates a sequence of paths, as described above. The data item list field **1354** may be formatted similar to the data item list field **1242**.

2. View Update Request

A view update request message may be transmitted by a node that has previously requested a view into a schema of another node or a node that has established a view into its own data on behalf of another node. An embodiment of a view update request frame **1356** illustrated in FIG. **40**. The view update request frame **1356** includes four fields: an update handle field **1358**, a view handle field **1360**, an update item list length field **1362**, and an update item list field **1364**. The update handle field **1358** may be composed using the format discussed above in reference to the update handle field **1348**. The view handle field **1360** includes two bytes that identify the view created by a relevant view request message **1290** having the same view handle. The update item list length field **1362** includes two bytes and indicates the number of update items that are included in the update item list field **1364**.

The update item list field **1364** includes a variable number of bytes and lists the data items constituting the updated values. Each updated item list may include multiple update items. The individual update items are formatted accordingly to the update item frame **1366** illustrated in FIG. **41**. Each update item frame **1366** includes three sub-fields: an item index field **1368**, an item timestamp field **1370**, and a data item field **1372**. The item index field **1368** includes two bytes that indicate the view under which the update is being requested and the index in the path list of that view for the data item field **1372**.

The item timestamp field **1370** includes four bytes and indicates the elapsed time (e.g., in seconds) from the change until the update being communicated was made. If more than one change has been made to the data item, the item timestamp field **1370** may indicate the most recent or the earliest change. The data item field **1372** is a variable length field encoded in TLV format that is to be received as the updated information.

iv. Update Response

After an update is received, a node (e.g., viewing node **1286**) may send an update response message **1374**. The update response message **1374** may be encoded using an update response frame **1376** illustrated in FIG. **42**. The update response frame **1376** includes two fields: an update handle field **1378** and an update request status field **1380**. The update handle field **1378** corresponds to an update handle field value of the update request message **1344** to which the update response message **1374** is responding. The update request

status field **1380** reports a status of the update in accordance with the status reporting format discussed above. Additionally, a profile using the DMP (e.g., a core profile or a data management profile) may include profile-specific codes, such as those enumerated in Table 21 below.

TABLE 21

Example of status codes for a profile including the DMP		
Name	Value	Description
success	0x0000	Request successfully processed
ill-formed request	0x0010	Received request was unparseable (e.g., missing fields, extra fields, etc.)
invalid path	0x0011	A path from the path list of the view or update request did not match a node-resident schema of the responding device.
unknown view handle	0x0012	The view handle in the update request did not match a view on the receiving node.
illegal read request	0x0013	The node making a request to read a particular data item does not have permission to do so.
illegal write request	0x0014	The node making the request to write a particular data item does not have permission to do so.
internal server error	0x0020	The server could not process the request because of an internal error.
out of memory	0x0021	The update request could not be executed because it would overrun the available memory in the receiving device.
continue	0x0030	The request was successfully handled but more action by the requesting device may occur.

D. Bulk Transfer

In some embodiments, it may be desirable to transfer bulk data files (e.g., sensor data, logs, or update images) between nodes/services in the fabric **1000**. To enable transfer of bulk data, a separate profile or protocol may be incorporated into one or more profiles and made available to the nodes/services in the nodes. The bulk data transfer protocol may model data files as collections of data with metadata attachments. In certain embodiments, the data may be opaque, but the metadata may be used to determine whether to proceed with a requested file transfer.

Devices participating in a bulk transfer may be generally divided according to the bulk transfer communication and event creation. As illustrated in FIG. **43**, each communication **1400** in a bulk transfer includes a sender **1402** that is a node/service that sends the bulk data **1404** to a receiver **1406** that is a node/service that receives the bulk data **1404**. In some embodiments, the receiver may send status information **1408** to the sender **1402** indicating a status of the bulk transfer. Additionally, a bulk transfer event may be initiated by either the sender **1402** (e.g., upload) or the receiver **1406** (e.g., download) as the initiator. A node/service that responds to the initiator may be referred to as the responder in the bulk data transfer.

Bulk data transfer may occur using either synchronous or asynchronous modes. The mode in which the data is transferred may be determined using a variety of factors, such as the underlying protocol (e.g., UDP or TCP) on which the bulk data is sent. In connectionless protocols (e.g., UDP), bulk data may be transferred using a synchronous mode that allows one of the nodes/services ("the driver") to control a rate at which the transfer proceeds. In certain embodiments, after each message in a synchronous mode bulk data transfer, an acknowledgment may be sent before sending the next message in the bulk data transfer. The driver may be the sender **1402** or the receiver **1406**. In some embodiments, the driver may toggle between an online state and an offline mode while

sending messages to advance the transfer when in the online state. In bulk data transfers using connection-oriented protocols (e.g., TCP), bulk data may be transferred using an asynchronous mode that does not use an acknowledgment before sending successive messages or a single driver.

Regardless of whether the bulk data transfer is performed using a synchronous or asynchronous mode, a type of message may be determined using a Message Type **1172** in the Application Payload **1146** according to the Profile Id **1176** in the Application Payload. Table 22 includes an example of message types that may be used in relation to a bulk data transfer profile value in the Profile Id **1176**.

TABLE 22

Examples of message types for bulk data transfer profiles		
Message Type	Message	
0x01	SendInit	
0x02	SendAccept	
0x03	SendReject	
0x04	ReceiveInit	
0x05	ReceiveAccept	
0x06	ReceiveReject	
0x07	BlockQuery	
0x08	Block	
0x09	BlockEOF	
0x0A	Ack	
0x0B	Block EOF	
0x0C	Error	

i. SendInit

An embodiment of a SendInit message **1420** is illustrated in FIG. **44**. The SendInit message **1420** may include seven fields: a transfer control field **1422**, a range control field **1424**, a file designator length field **1426**, a proposed max block size field **1428**, a start offset field **1430**, length field **1432**, and a file designator field **1434**.

The transfer control field **1422** includes a byte of data illustrated in FIG. **45**. The transfer control field includes at least four fields: an Asynch flag **1450**, an RDrive flag **1452**, an SDrive flag **1454**, and a version field **1456**. The Asynch flag **1450** indicates whether the proposed transfer may be performed using a synchronous or an asynchronous mode. The RDrive flag **1452** and the SDrive flag **1454** each respectively indicates whether the receiver **1406** is capable of transferring data with the receiver **1402** or the sender **1408** driving a synchronous mode transfer.

The range control field **1424** includes a byte of data such as the range control field **1424** illustrated in FIG. **46**. In the illustrated embodiment, the range control field **1424** includes at least three fields: a BigExtent flag **1470**, a start offset flag **1472**, and a definite length flag **1474**. The definite length flag **1474** indicates whether the transfer has a definite length. The definite length flag **1474** indicates whether the length field **1432** is present in the SendInit message **1420**, and the Big-Extent flag **1470** indicates a size for the length field **1432**. For example, in some embodiments, a value of 1 in the BigExtent flag **1470** indicates that the length field **1432** is eight bytes. Otherwise, the length field **1432** is four bytes, when present. If the transfer has a definite length, the start offset flag **1472** indicates whether a start offset is present. If a start offset is present, the BigExtent flag **1470** indicates a length for the start offset field **1430**. For example, in some embodiments, a value of 1 in the BigExtent flag **1470** indicates that the start offset field **1430** is eight bytes. Otherwise, the start offset field **1430** is four bytes, when present.

Returning to FIG. 44, the file designator length field 1426 includes two bytes that indicate a length of the file designator field 1434. The file designator field 1434 which is a variable length field dependent upon the file designator length field 1426. The max block size field 1428 proposes a maximum size of block that may be transferred in a single transfer.

The start offset field 1430, when present, has a length indicated by the BigExtent flag 1470. The value of the start offset field 1430 indicates a location within the file to be transferred from which the sender 1402 may start the transfer, essentially allowing large file transfers to be segmented into multiple bulk transfer sessions.

The length field 1432, when present, indicates a length of the file to be transferred if the definite length field 1474 indicates that the file has a definite length. In some embodiments, if the receiver 1402 receives a final block before the length is achieved, the receiver may consider the transfer failed and report an error as discussed below.

The file designator field 1434 is a variable length identifier chosen by the sender 1402 to identify the file to be sent. In some embodiments, the sender 1402 and the receiver 1406 may negotiate the identifier for the file prior to transmittal. In other embodiments, the receiver 1406 may use metadata along with the file designator field 1434 to determine whether to accept the transfer and how to handle the data. The length of the file designator field 1434 may be determined from the file designator length field 1426. In some embodiments, the SendInit message 1420 may also include a metadata field 1480 of a variable length encoded in a TLV format. The metadata field 1480 enables the initiator to send additional information, such as application-specific information about the file to be transferred. In some embodiments, the metadata field 1480 may be used to avoid negotiating the file designator field 1434 prior to the bulk data transfer.

ii. SendAccept

A send accept message is transmitted from the responder to indicate the transfer mode chosen for the transfer. An embodiment of a SendAccept message 1500 is presented in FIG. 47. The SendAccept message 1500 includes a transfer control field 1502 similar to the transfer control field 1422 of the SendInit message 1420. However, in some embodiments, only the RDrive flag 1452 or the SDrive 1454 may have a nonzero value in the transfer control field 1502 to identify the sender 1402 or the receiver 1406 as the driver of a synchronous mode transfer. The SendAccept message 1500 also includes a max block size field 1504 that indicates a maximum block size for the transfer. The block size field 1504 may be equal to the value of the max block field 1428 of the SendInit message 1420, but the value of the max block size field 1504 may be smaller than the value proposed in the max block field 1428. Finally, the SendAccept message 1500 may include a metadata field 1506 that indicates information that the receiver 1506 may pass to the sender 1402 about the transfer.

iii. SendReject

When the receiver 1206 rejects a transfer after a SendInit message, the receiver 1206 may send a SendReject message that indicates that one or more issues exist regarding the bulk data transfer between the sender 1202 and the receiver 1206. The send reject message may be formatted according to the status reporting format described above and illustrated in FIG. 48. A send reject frame 1520 may include a status code field 1522 that includes two bytes that indicate a reason for rejecting the transfer. The status code field 1522 may be decoded using values similar to those enumerated as indicated in the Table 23 below.

TABLE 23

Example status codes for send reject message		
Status Code	Description	
0x0020	Transfer method not supported	
0x0021	File designator unknown	
0x0022	Start offset not supported	
0x0011	Length required	
0x0012	Length too large	
0x002F	Unknown error	

In some embodiments, the send reject message 1520 may include a next status field 1524. The next status field 1524, when present, may be formatted and encoded as discussed above in regard to the next status field 1188 of a status report frame. In certain embodiments, the send reject message 1520 may include an additional information field 1526. The additional information field 1526, when present, may store information about an additional status and may be encoded using the TLV format discussed above.

iv. ReceiveInit

A ReceiveInit message may be transmitted by the receiver 1206 as the initiator. The ReceiveInit message may be formatted and encoded similar to the SendInit message 1480 illustrated in FIG. 44, but the BigExtent field 1470 may be referred to as a maximum length field that specifies the maximum file size that the receiver 1206 can handle.

v. ReceiveAccept

When the sender 1202 receives a ReceiveInit message, the sender 1202 may respond with a ReceiveAccept message. The ReceiveAccept message may be formatted and encoded as the ReceiveAccept message 1540 illustrated in FIG. 49. The ReceiveAccept message 1540 may include four fields: a transfer control field 1542, a range control field 1544, a max block size field 1546, and sometimes a length field 1548. The ReceiveAccept message 1540 may be formatted similar to the SendAccept message 1502 of FIG. 47 with the second byte indicating the range control field 1544. Furthermore, the range control field 1544 may be formatted and encoded using the same methods discussed above regarding the range control field 1424 of FIG. 46.

vi. ReceiveReject

If the sender 1202 encounters an issue with transferring the file to the receiver 1206, the sender 1202 may send a ReceiveReject message formatted and encoded similar to a SendReject message 48 using the status reporting format, both discussed above. However, the status code field 1522 may be encoded/decoded using values similar to those enumerated as indicated in the Table 24 below.

TABLE 24

Example status codes for receive reject message		
Status Code	Description	
0x0020	Transfer method not supported	
0x0021	File designator unknown	
0x0022	Start offset not supported	
0x0013	Length too short	
0x002F	Unknown error	

vii. BlockQuery

A BlockQuery message may be sent by a driving receiver 1202 in a synchronous mode bulk data transfer to request the next block of data. A BlockQuery impliedly acknowledges receipt of a previous block of data if not explicit Acknowledgment.

43

edgement has been sent. In embodiments using asynchronous transfers, a BlockQuery message may be omitted from the transmission process.

viii. Block

Blocks of data transmitted in a bulk data transfer may include any length greater than 0 and less than a max block size agreed upon by the sender **1202** and the receiver **1206**.

ix. BlockEOF

A final block in a data transfer may be presented as a Block end of file (BlockEOF). The BlockEOF may have a length between 0 and the max block size. If the receiver **1206** finds a discrepancy between a pre-negotiated file size (e.g., length field **1432**) and the amount of data actually transferred, the receiver **1206** may send an Error message indicating the failure, as discussed below.

x. Ack

If the sender **1202** is driving a synchronous mode transfer, the sender **1202** may wait until receiving an acknowledgment (Ack) after sending a Block before sending the next Block. If the receiver is driving a synchronous mode transfer, the receiver **1206** may send either an explicit Ack or a BlockQuery to acknowledge receipt of the previous block. Furthermore, in asynchronous mode bulk transfers, the Ack message may be omitted from the transmission process altogether.

xi. AckEOF

An acknowledgement of an end of file (AckEOF) may be sent in bulk transfers sent in synchronous mode or asynchronous mode. Using the AckEOF the receiver **1206** indicates that all data in the transfer has been received and signals the end of the bulk data transfer session.

xii. Error

In the occurrence of certain issues in the communication, the sender **1202** or the receiver **1206** may send an error message to prematurely end the bulk data transfer session. Error messages may be formatted and encoded according to the status reporting format discussed above. For example, an error message may be formatted similar to the SendReject frame **1520** of FIG. **48**. However, the status codes may be encoded/decoded with values including and/or similar to those enumerated in Table 25 below.

TABLE 25

Example status codes for an error message in a bulk data transfer profile	
Status code	Description
0x001F	Transfer failed unknown error
0x0011	Overflow error

The specific embodiments described above have been shown by way of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover all modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

What is claimed is:

1. An electronic device configured to send or receive messages to other electronic devices over a platform layer, wherein the messages to cause an operation to occur at the electronic device or at the other electronic devices, wherein the messages comprise:

44

a message format comprising:

- a message type field, wherein the message type field is configured to indicate a message operation code that specifies a type of message being sent;
- an exchange ID field immediately following the message type field, wherein the exchange ID field is configured to uniquely identify a discussion in which the message occurs for the electronic device;
- a profile ID field immediately following the exchange ID field, wherein the profile ID field indicates a profile of a plurality of profiles that enables a receiving device to interpret the message type field and identify at least one schema of a plurality of schemas for transmitted data, wherein each schema of the plurality of schemas indicates an encoding format according to the profile and schema; and
- an application payload field following the profile id, wherein the application payload field comprises data associated with an application layer of the electronic device.

2. The electronic device of claim 1, comprising a profile-specific header field that immediately follows the profile ID field and immediately precedes the application payload field, wherein the profile-specific header is included in the message format when the profile field indicates that a profile is included that uses additional information to process the application payload.

3. The electronic device of claim 1, wherein each profile of the plurality of profiles comprises a set of schema of the plurality of schemas.

4. The electronic device of claim 1, wherein the indicated profile comprises:

- a core profile comprising a set of basic schemas available to the electronic device;
- a data management profile comprising a set of data management schemas that enables the electronic device to access data located on the other electronic devices;
- a bulk data transfer profile comprising a set of bulk data transfer schemas that enables the electronic device to transfer bulk data to the other electronic devices or from the electronic devices;
- a status reporting profile comprising a set of status reporting schemas that enables the electronic device to send or receive status information from the other electronic devices; or
- a software update profile comprising a set of software update schemas that enables the electronic device to send or receive software update images from the other electronic devices.

5. The electronic device of claim 1, wherein the message format comprises a version field configured to indicate a version of the message format being used to format the message, wherein the message type field immediately follows the version field, wherein the version field comprises 8 bits of data.

6. The electronic device of claim 1, wherein the message type field comprises 8 bits of data.

7. The electronic device of claim 1, wherein the exchange ID field comprises 16 bits of data.

8. A non-transitory, computer-readable medium having stored thereon message comprising a message format, wherein the message format causes an operation to occur at the electronic device having the non-transitory, computer-readable medium, wherein the message format comprises:

- a message type field, wherein the message type field is configured to indicate a message operation code that specifies a type of message being sent;

45

an exchange ID field immediately following the message type field, wherein the exchange ID field is configured to uniquely identify a discussion in which the message occurs;

a profile ID field immediately following the exchange ID field, wherein the profile ID field indicates a profile of a plurality of profiles that enables a receiving device to interpret the message type field and identify at least one schema of a plurality of schemas for transmitted data, wherein each schema of the plurality of schemas indicates an encoding format according to the profile and schema; and

an application payload field following the profile id, wherein the application payload field comprises data associated with an application layer.

9. The non-transitory, computer-readable medium of claim 8, wherein the message format comprises a profile-specific header field, wherein the profile-specific header field is used in identifying the schema.

10. The non-transitory, computer-readable medium of claim 8, wherein the profile ID field comprises 32 bits of data.

11. The non-transitory, computer-readable medium of claim 8, wherein the application payload field comprises a variable length of data.

12. The non-transitory, computer-readable medium of claim 8, wherein the application payload field comprises data formatted in a tag-length-value format.

13. The non-transitory, computer-readable medium of claim 8, wherein each profile of the plurality of profiles comprises a schema of the plurality of schemas.

14. A method for sending and receiving messages between devices in a fabric network, wherein the messages cause an operation to occur at an electronic device of the devices, wherein the method comprises:

sending or receiving a message using a message format, wherein the message format comprises:

a message type field, wherein the message type field is configured to indicate a message operation code that specifies a type of message being sent;

an exchange ID field immediately following the message type field, wherein the exchange ID field is configured to uniquely identify a discussion in which the message occurs;

a profile ID field immediately following the exchange ID field, wherein the profile ID field indicates a profile of a plurality of profiles that enables a receiving device to interpret the message type field and identify at least

46

one schema of a plurality of schemas for transmitted data, wherein each schema of the plurality of schemas indicates an encoding format according to the profile and schema; and

an application payload field following the profile id, wherein the application payload field comprises data associated with an application layer.

15. The method of claim 14, wherein the message format comprises a profile-specific header field that immediately follows the profile ID field and immediately precedes the application payload field, wherein the profile-specific header is included in the message format when the profile field indicates that a profile is included that uses additional information to process the application payload.

16. The method of claim 14, wherein each profile of the plurality of profiles comprises a set of schema of the plurality of schemas.

17. The method of claim 14, wherein the indicated profile comprises:

a core profile comprising a set of basic schemas available to the electronic device;

a data management profile comprising a set of data management schemas that enables the electronic device to access data located on the other electronic devices;

a bulk data transfer profile comprising a set of bulk data transfer schemas that enables the electronic device to transfer bulk data to the other electronic devices or from the electronic devices;

a status reporting profile comprising a set of status reporting schemas that enables the electronic device to send or receive status information from the other electronic devices; or

a software update profile comprising a set of software update schemas that enables the electronic device to send or receive software update images from the other electronic devices.

18. The method of claim 14, wherein the message format comprises a version field configured to indicate a version of the message format being used to format the message, wherein the message type field immediately follows the version field, wherein the version field comprises 8 bits of data.

19. The method of claim 14, wherein the message type field comprises 8 bits of data.

20. The method of claim 14, wherein the exchange ID field comprises 16 bits of data.

* * * * *