




(22) Date de dépôt/Filing Date: 2011/07/11
(41) Mise à la disp. pub./Open to Public Insp.: 2012/01/12
(45) Date de délivrance/Issue Date: 2020/10/27
(62) Demande originale/Original Application: 2 804 864
(30) Priorité/Priority: 2010/07/09 (US61/363,092)

(51) Cl.Int./Int.Cl. G06F 8/60 (2018.01),
G06F 15/16 (2006.01), H04L 12/28 (2006.01),
H04L 9/32 (2006.01)
(72) Inventeurs/Inventors:
MCCARTHY, CHRISTOPHER, US;
SULLIVAN, KEVIN, US;
KRISHNAN, REJITH, US
(73) Propriétaire/Owner:
STATE STREET CORPORATION, US
(74) Agent: KIRBY EADES GALE BAKER

(54) Titre : SYSTEMES ET PROCEDES POUR UNE INFORMATIQUE EN NUAGE PRIVE
(54) Title: SYSTEMS AND METHODS FOR PRIVATE CLOUD COMPUTING



(57) Abrégé/Abstract:

A system and method are disclosed for private cloud computing and for the development and deployment of cloud applications in the private cloud. The private cloud computing system and method of the present invention include as components at least a cloud controller, a cloud stack, Service Registry, and a cloud application builder.

ABSTRACT

A system and method are disclosed for private cloud computing and for the development and deployment of cloud applications in the private cloud. The private cloud computing system and method of the present invention include as components at least a cloud controller, a cloud stack, Service Registry, and a cloud application builder.

SYSTEMS AND METHODS FOR PRIVATE CLOUD COMPUTING

Related Applications

[0001] This is a division of Canadian Patent No. 2,804,864 from PCT/US2011/043604, filed July 11, 2011 and published on January 12, 2012.

Field of the Invention

[0002] The present invention relates to computer-based systems and methods for cloud computing, and more specifically to computer-based systems and methods for private cloud computing and for cloud application development and deployment within a private cloud.

Background of the Invention

[0003] Generally, cloud computing refers to the use and access of multiple server-based computational resources using a digital network, such as the Internet. Cloud system users access the web server services of the cloud using client devices, such as a desktop computer, laptop computer, tablet computer, smartphone, personal digital assistant (PDA), or similar type device (hereinafter collectively referred to as a "client device" or "client devices").

[0004] In cloud computing, applications are provided and managed by a cloud server and data is stored remotely in a cloud database. Typically, cloud system users do not download and install applications that exist in the cloud on their own computing device because processing and storage is maintained by the cloud server and cloud database, respectively.

[0005] Typically, online services are provided by a cloud provider or private organization. This obviates the need for cloud system users to install application software on their own separate client devices. As such, cloud computing differs from the classic client-server model by providing applications on a cloud server that are executed and managed by a client service with no installed client version of the application being required on the client device. The centralization of cloud services gives a cloud service provider control over versions of the browse-based applications provided to clients. This also removes the need for version upgrades of applications on individual client devices

[0006] In operation, the cloud system user will log onto a public or private cloud. Computing is then carried out on a client/server basis using web browser protocols. The cloud provides server-based applications and all data services to the cloud system user with the results then being displayed on the client device. As such, the cloud system user will have access to desired applications running remotely in a database which displays the work being done using the cloud application on the client device.

[0007] Cloud database storage allocated client devices is used to make applications appear on the client device display. However, all computations and changes are recorded by the cloud server, and files that are created and altered are permanently stored in the cloud database storage.

[0008] Cloud computing, when implemented, includes provisioning of dynamically scalable and virtualized resources. This may be carried out by cloud providers without cloud system users' knowledge of the physical location and configuration of the system that delivers the requested services. As such, cloud computing infrastructures consist of services delivered through shared data centers. However, from the client side, the cloud appears as a single point of access.

[0009] A generic cloud architecture includes an architecture of hardware and software systems involved in the delivery of the cloud computing services. Two significant components of the cloud computing architecture are the "front-end" and "back-end." The front-end is what is seen by the cloud system user at his/her client device. This would include the client device application used to access the cloud via the user interface, such as a web browser. The back end of the cloud computing architecture is the cloud itself consisting of various computers, servers, and data storage devices of which the cloud system user has no knowledge.

[0010] The shared services within a typical cloud computing environment are shown in Figure 1 generally at 100. Client 102 is the client device with its internal software that relies on cloud computing for application delivery through web services. Cloud application 104 is cloud application services also referred to as "Software as a Service (SaaS)." This is the delivery of software over the Internet that eliminates the need to install and run an application on the cloud system user's computing device. Since the applications are cloud applications, maintenance and support of these applications is greatly simplified.

[0011] Cloud platform 106 is cloud platform services also referred to as “Platform as a Service (PaaS).” PaaS is the delivery of a computing platform and/or solution stack as a service that uses the cloud infrastructure and cloud applications. This facilitates the deployment of applications from the cloud.

[0012] Cloud infrastructure 108 is cloud infrastructure services also referred to as “Infrastructure as a Service (IaaS).” IaaS is the delivery of computer infrastructure as a service typically in the form of platform virtualization. Cloud infrastructure services may be in the form of data centers operating virtual machines that run on physical machines.

[0013] Server 110 refers to the server layer of the cloud. This includes computer hardware and software for delivery of cloud services to client 102.

[0014] As previously stated, the cloud may be a public or private cloud. There are also other cloud configurations that may involve elements of both. Some of the well known cloud types will now be briefly discussed.

[0015] A “public cloud” is a cloud in which resources are dynamically provisioned over the Internet using web applications and services from a third-party provider.

[0016] A “community cloud” is one that is established where several organizations have similar requirements and seek to share infrastructure to realize the benefits of cloud computing.

[0017] A “hybrid cloud” is one that recognizes the need of companies to deliver services in a traditional way to some in-house operating methods and provide technology to manage the complexity in managing the performance, security and privacy concerns that result from the fixed delivery methods of the company. A hybrid cloud uses a combination of public and private storage clouds.

[0018] A “combined cloud” is one in which two clouds are joined together. In such a configuration, there will be multiple internal and/or external cloud providers.

[0019] A “private cloud” is essentially the emulation of a public cloud operating on a private network. Through virtualization, a private cloud gives an enterprise the ability to host applications on virtual machines enterprise-wide. This provides benefits of shared hardware costs, better service recovery, and the ability to scale up or scale down depending on demand.

[0020] However, there is a need in computer-based private cloud systems for implementation of better systems and methods for cloud computing and cloud application development and deployment on an enterprise-wide basis. The system and method of the present invention solves these needs.

Summary of the Invention

[0021] The present invention is a computer-based system and method for cloud computing and cloud application development and deployment in a private cloud within an enterprise. Further, the present invention is directed to computer-based systems and methods for private cloud computing that allow the cloud infrastructure to adapt or respond automatically to changes caused by the deployment and use of cloud applications developed for the private cloud system. The private cloud computing system and method of the present invention may be implemented in the higher-level layers, such as the application and services layers that may be incorporated as part of application layer 104 shown in Figure 1.

[0022] The private cloud computing system and method of the present invention preferably includes a Cloud Controller, Cloud Stack, Service Registry, and Cloud Application Builder. The Cloud Controller provides the intelligence for the private cloud. The Cloud Controller includes a rules engine that is used to analyze information collected and stored in the cloud database. This database stores cloud application binaries, as well as monitoring information. Therefore, rather than the cloud applications being stored in a file system, as is typical, the computer-based private cloud system of the present invention stores cloud applications in a database so that they may be consistently maintained across the cloud in an easy efficient manner.

[0023] The Cloud Stack includes the operating software for the cloud. For example, the Cloud Stack may include the operating system software, virtual machine software, web server software, application server software, network security software, web access management software, database driver software, application builder runtime software, and third-party libraries.

[0024] The Service Registry contains a register of web services for at least the cloud applications deployed in the private cloud. The web services are searchable by a number of different methods so that developers can view the web services and their detailed information

for possible reuse with cloud applications they are developing for deployment in the private cloud.

[0025] The Cloud Application Builder provides the means for developers to build applications that are deployed in the private cloud using Cloud Controller. The Cloud Application Builder preferably includes tools to create the components of a cloud application. These components preferably include a web service, a user interface, and jobs for each cloud application to be deployed in the private cloud. As such, the cloud application building tools include, but are not limited to, tools to develop the web services, tools for developing a user interface and registering the web services in the Service Registry so the level of access to cloud applications is controlled, and tools to develop jobs. Using these tools, each cloud application that is developed and deployed will include a user interface for managing foreground tasks, data storage, and background tasks; however, it is understood that more or less than these tools may be used and it will still be within the scope of the present invention.

[0026] With regard to building cloud applications, preferably, there are two distinct parts. The first will be the development time to build the cloud application and the second will be the cloud application framework. The development time will involve the use of the Cloud Application Builder to build an application according to the cloud application framework. The cloud application framework along with the resulting cloud application components are deployed in the private cloud.

[0027] The system and method of the present invention includes enterprise Security Foundation (“eSF”) software that manages the user roles that authorize cloud application access. Accordingly, through eSF, access security is provided to the private cloud of the present invention.

[0028] According to the system and method of the present invention, the cloud infrastructure resources are managed by load balancing incoming requests from client devices to use cloud applications and web services by routing these requests to the various web servers and application servers in the private cloud.

[0029] Inside the private cloud of the present invention, there also can be the creation of business rules that relate to web services for cloud applications. These provide greater flexibility, management, and control of cloud applications that are developed and deployed in the private cloud.

[0030] The private cloud computing system and method of the present invention supports external services. Accordingly, provisioning services for the cloud database may be accomplished using a self-service application for access and control of such external services.

[0031] The private cloud computing system and method of the present invention contemplates cloud monitoring services to analyze the usage data in log files and health records associated with the cloud applications running in the private cloud. The results of the analysis are used to scale up or scale down the cloud infrastructure, control alert processes, and facilitate capacity planning.

[0032] The computer-based private cloud computing system and method of the present invention provides for the development and deployment of cloud applications and web services within an enterprise.

[0033] The computer-based private cloud computing system and method of the present invention also may be implemented using a Cloud Controller, Cloud Stack, Service Registry, and a Cloud Application Builder. In carrying out this implementation, the Cloud Application Builder builds the cloud application according to the cloud application framework. Once the cloud application is built, the Cloud Controller with the Cloud Stack and Service Registry is used to deploy the cloud application in the private cloud.

[0034] The computer-based private cloud computing system and method of the present invention further provides a PaaS through the Cloud Stack to extend the IaaS by anticipating enterprise system needs, which assists in standardizing the cloud application development and deployment process for the enterprise.

[0034a] In one aspect it is provided a computer-based system having a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising: at least one system user interface connected to the cloud computing environment, with the at least one system user interface initiating a virtual machine environment in the cloud computing environment by transmitting requests to the cloud computing environment to access and use applications and/or virtual machine services accessible through the cloud computing environment; at least one provisioner in the cloud computing environment that is connected to the at least one system user interface, with the at least one provisioner for balancing a distribution of the requests for applications and/or virtual machine services from the at least one user interface among a plurality of activated first server types and a plurality of activated second server types in the cloud computing environment; at least one activated first server type connected to the provisioner for at least routing requests received from the at least one system user interface for accessing and/or using virtual machine services stored in or accessible through the cloud computing environment; a plurality of second server types connected to the at least one activated first server type, with the second server types for routing requests for applications and/or virtual machine services received from the at least one system user interface; and a cloud database connected to the second server types and the at

least one system user interface, with the cloud database receiving requests for access to virtual machine services in the cloud database and making the requested virtual machine services available for the at least one system user interface to run in a virtual machine environment in the cloud computing environment, wherein the virtual machine environment is associated with the activated first-server type and one or more activated second server types.

[0034b] In another aspect it is provided a computer-based system having a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising: a plurality of system user interfaces connected to the cloud computing environment, with each system user interface initiating a virtual machine environment in the cloud computing environment by transmitting requests to the cloud computing environment to access and use applications and/or virtual machine services accessible through the cloud computing environment; at least one provisioner in the cloud computing environment that is connected to the plurality of system user interfaces, with the at least one provisioner for balancing a distribution of the requests for applications and/or virtual machine services from the plurality of user interfaces among a plurality of activated first server types and a plurality of activated second server types in the cloud computing environment; a plurality of first server types connected to the provisioner, with each activated first server type of the plurality of the first server types for at least routing requests for applications and/or virtual machine services received from the plurality system user interfaces for accessing and/or using applications and/or virtual machine services stored in or accessible through the cloud computing environment that have been provisioned by the provisioner to each activated first server type; and a plurality of second server types connected to each first server type, with each activated second server type of the plurality of second server types for routing requests for applications and/or virtual machine services received from the plurality of system user interfaces to a plurality of hosted web services in each activated second server type and with the hosted web services being selected according to requests for applications and/or virtual machine services from each of the plurality of system user interfaces.

[0034c] In another aspect it is provided a computer-based system virtual machine infrastructure for provisioning a plurality of virtual machine environments in a cloud computing environment, comprising: a provisioner in the cloud computing environment that receives a plurality of requests for desktop applications from a plurality of system user interfaces, with the provisioner for balancing a distribution of the requests for desktop applications from the plurality of user interfaces among a plurality of activated first server types and a plurality of activated second server types according to the number of requests received from the plurality of system user interfaces for operating one or more virtual machine environments in the cloud environment that are associated with activated first server types and activated second server types; a cluster of a plurality of first server types connected to the provisioner, with each of the plurality of first

server types of being capable of being activated and deactivated by the provisioner and when activated to process one or more requests for desktop applications from the plurality of system user interfaces according to the distribution of such requests by the provisioner and each activated first server type shall be associated with a virtual machine environment running in the cloud environment; and a cluster of a plurality of second server types, wherein the cluster is connected to each of the plurality of first server types, with each of the plurality of second server types being capable of being activated and deactivated by the provisioner and when activated to process one or more requests for desktop applications from the plurality of system user interfaces according to the distribution of such requests by the provisioner and each activated second server type along with the connected activated first server type shall be associated with a virtual machine environment in the cloud environment.

[0034d] In another aspect it is provided a computer-based system having a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising: a plurality of system user interfaces connected to the cloud computing environment, with each system user interface initiating a virtual machine environment by transmitting requests to the cloud computing environment to access and use applications and/or virtual machine services in the cloud computing environment; provisioning services of a cloud controller connected to the plurality of system user interfaces for receiving the requests for applications and/or virtual machine services from the plurality of system user interfaces and provisioning virtual machine environments and associated virtual machine environment controls in the cloud computing environment according to the number of requests received from the plurality of system user interfaces; a plurality of virtual machine environments and associated virtual machine environment controls that are activated and deactivated by the provisioning services, with each activated virtual machine environment and associated virtual machine environment controls running web server instances and application instances in the cloud computing environment according to the requests for applications and/or virtual machine services provisioned to each activated virtual machine environment and associated virtual machine environment controls by the provisioning services; monitoring services of the cloud controller connected to the provisioning services for monitoring the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces and controlling the provisioning services to activate or deactivate certain of the plurality of virtual machine environments and associated virtual machine environment controls according to the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces; and a cloud database for storing virtual machine services that can be retrieved and/or run in activated virtual machine environments as controlled by associated virtual machine environment controls according to the requests for applications and/or virtual machine services received from the plurality of system user interfaces.

[0034e] In another aspect it is provided a computer-based method for operation of a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising the steps of: (a) a plurality of system user interfaces transmitting requests for applications and/or web services to the cloud computing environment; (b) provisioning services of the cloud computing environment receiving the requests for applications and/or virtual machine services from the plurality of system user interfaces and activating or deactivating virtual machine environments and associated virtual machine environment controls according to the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces; (c) activated virtual machine environments and associated virtual machine environment controls running web server instances and application instances according to the requests for applications and/or virtual machine services that have been provisioned to each activated virtual machine environment and associated virtual machine environment controls; and (d) monitoring services of the cloud computing environment monitoring the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces at a given point in time and controlling the provisioning services to activate or deactivate one or more virtual machine environments and associated virtual machine environment controls according to the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces.

[0035] The computer-based private cloud computing system and method of the present invention will be described in greater detail in the remainder of the specification referring to the drawings.

Brief Description of the Drawings

[0036] Figure 1 shows a representative drawing of a layered structure within which services may be shared in a cloud environment.

[0037] Figure 2A shows a representative diagram of the physical structure of the computer-based private cloud computing system of the present invention.

[0038] Figure 2B shows a representative diagram of a logical structure of the computer-based private cloud computing system of the present invention shown in Figure 2A.

[0039] Figure 3 shows a representative drawing of the cloud components of the computer-based private cloud computing system of the present invention.

[0040] Figure 4 shows a representative drawing of the logical architecture of the components of the private cloud computing system of the present invention.

[0041] Figure 5 shows a representative diagram for cloud user interface management of foreground tasks, data storage, and background tasks according to the computer-based computing system of the present invention.

[0042] Figure 6 shows a representative diagram of the logical architecture of the private cloud computing system of the present invention that includes the service registry.

[0043] Figure 7 shows a representative diagram of service registry architecture of the computer-based private cloud computing system of the present invention.

[0044] Figure 8 shows a representative graphical drawing of the process for development of a web service component of a cloud application according to the computer-based private cloud computing system of the present invention.

[0045] Figure 9 shows a representative diagram for background job development and handling according to the computer-based private cloud computing system of the present invention.

[0046] Figure 10 shows a representative diagram for implementing eSF security.

[0047] Figure 11 shows a representative diagram related to function group formation for a cloud application and the services to which such formed function groups have access.

[0048] Figure 12 shows a representative diagram relating to cloud application roles that are used for defining function groups.

[0049] Figure 13 shows a representative diagram of an cSF entitlement map for an administrator role shown in Figure 12.

[0050] Figure 14 shows a representative diagram of an eSF entitlement map for the system user role shown in Figure 12.

[0051] Figures 15-22 show representative screen displays for creating a cloud application profile and changing the status of the cloud application from DRAFT to PUBLISHED.

[0052] Figure 23A shows a representative diagram relating to actions associated with the application of Auto-Audit rules.

[0053] Figure 23B shows a representative list of Auto-Audit rules that are checked when a cloud application profile status is changed.

[0054] Figure 24 shows a representative display screen of a Dashboard according to the computer-based private cloud system of the present invention.

[0055] Figure 25 shows a representative service registry display screen according to the computer-based private cloud system of the present invention.

[0056] Figure 26 shows a representative web services detail display screen according to the computer-based private cloud system of the present invention.

[0057] Figures 27-32 show representative drawings relating to cloud application deployment workflows.

Detailed Description of the Present Invention

[0058] The present invention is directed to a computer-based system and method for cloud computing and cloud application development and deployment in a private cloud within an enterprise. The present invention is also directed to computer-based systems and methods for private cloud computing in which the cloud infrastructure adapts or responds automatically or substantially automatically to changes caused by the deployment and use of cloud applications developed for the private cloud system. The private cloud computing systems and methods of the present invention are embodied in the higher-level layers, such as the application and services layers that may be incorporated as part of application layer 104 shown in Figure 1.

[0059] Referring to Figure 2, generally at 200, a representative diagram of the physical structure of the computer-based private cloud computing system of the present invention is

shown. In Figure 2, the cloud cluster and router that form the cloud application server are shown at 202. This cluster shows four server computers forming the cloud application server. As such, any one may be provisioned to handle a request for a cloud application or web services because of the load balancing features of the private cloud of the present invention through provisioning services. However, the cluster may include more or less than four server computers and still be within the scope of the present invention.

[0060] External cloud services 204 are connected to cloud application server 202. The external cloud services that are shown include cloakware server 206 that are used to provide network security to the cloud. External cloud services 204 also include messaging server 208 for controlling internal and external messaging associated with the private cloud of the present invention.

[0061] External cloud services 204 include file transfer services 210. The services handled by file transfer services 210 include, but are not limited to, client device--cloud, cloud--external system, and intra-cloud file transfers. It is within the scope of the present invention that these files transfers may be encrypted for security purposes.

[0062] The last server shown in external cloud services 204 is e-mail server 212. This server is for sending e-mail messages to, and receiving and processing e-mail messages from, client devices. More specifically, the email messages contemplated to be handled by this server include e-mail messages from the private cloud to external systems to inform, for example, of alert conditions or service level objective ("SLO") violations within the private cloud.

[0063] Cloud application server 202 connects to application database 214. Preferably, this database stores cloud application data, which includes, for example, application transaction data, reports, and warehouse data.

[0064] Web server 216 connects to cloud application server 202 and is disposed between client device 222 and cloud application server 202. Web server 216 operates conventionally to provide content to client devices and processes requests from client devices directed to cloud application server 202. Web server 216 also connects to SiteMinder® server 218. Preferably, SiteMinder® server 218 provides web access management for web server 216 in the form of authentication services.

[0065] Load balancer 220 disposed between client device 222 and web server 216 provides provisioning services for balancing the distribution of cloud applications running in the cloud among the cloud infrastructure. More particularly, load balancer 220 load balances incoming HTTP requests among a number of web servers of which only one is shown in Figure 2B.

[0066] Referring to Figure 2B, generally at 230, a representative diagram of a logical structure of the computer-based private cloud computing system of the present invention shown in Figure 2A is shown. Load balancer 220 balances the incoming HTTP requests to a pool of web servers and scales the cloud infrastructure, such as the web servers, up and down to meet the traffic needs. Web server 216/218 performs the functions of a web server and an authentication agent on a single sign-on basis.

[0067] The web server routes requests to the application router. The application router is in the form of a cluster of routers that are part of application server 202. The application router route requests to web services in the cloud application server cluster, which is also part of cloud application server 202. Each service is identified by a unique ID.

[0068] The application server cluster hosts web services and receives the requests for such services from the application router cluster. The application server cluster also contains jobs. The jobs are batch jobs that are part of the cloud application that reside in the application server cluster.

[0069] The web services in the application server cluster connect to application database 214 that includes enterprise data. The application database resides outside the private cloud. The enterprise data includes online transaction processing (“OLTP”) and warehouse data that are stored separately. Preferably, replicated instances, which are shown as Oracle instances, keep the data for the OLTP.

[0070] Referring to Figure 3, generally at 300, the components of the computer-based private cloud computing system of the present invention are shown. These components will now be discussed.

[0071] The main components of the computer-based private cloud computing system of the present invention include Cloud Controller 302, Cloud Stack 324, Service Registry 345, and Cloud Application Builder 350. As stated, Cloud Controller 302 provides intelligence to

the computer-based private cloud computing system of the present invention. The general functions of Cloud Controller 302 are to handle the deployment workflow, set the time and date for cloud application deployment, scale up and scale down platform needs depending on the cloud applications that are to be run, set the time and date for checking the physical and virtual machines, set the time and date for scanning the cloud application logs, set the time and date for monitoring cloud application transactions, and send alerts when errors occur within the private cloud. The deployment workflow will be discussed in greater detail subsequently with respect to Figures 27-32.

[0072] Change Control services 308 of Cloud Controller 302 are associated with cloud application setup. Change Control services 308 accept bundled binaries created for cloud applications, and permit an authorized system user to create and update a cloud application profile and to browse information about a particular cloud application. The creation of a cloud application profile is for a cloud application that has already been deployed in the private cloud and specifies the appropriate cloud application that is to be run.

[0073] Change Control services 308 permit an authorized user to copy the description of an existing profile without the identification fields so that it may be used to describe the new cloud application. Change Control services 308 also permit authorized users to browse existing cloud application profiles and review the information they contain. Further, Change Control services 308 permits authorized users to modify an existing application profile including associated application binaries.

[0074] Change Control services 308 permit an authorized user to change the status of an application profile. For example, using this capability, the authorized user could change the status of a cloud application from “DRAFT” to “PUBLISHED.” It is recognized, however, other status changes can be made and still be within the scope of the present invention.

[0075] Change Control services 308 enable an authorized system user to browse the application status log for cloud applications to review the current and previous statuses for cloud applications. Change Control services 308 also enable authorized system users to browse properties associated with cloud applications and edit those properties.

[0076] The features of Change Control services 308 just described are preferable features only. It is contemplated that Change Control services 308 may have more or less of the features described and still be within the scope of the present invention.

[0077] Again referring to Cloud Controller 302, Auto-Audit rules are shown at 310. Auto-Audit rules 310 are directed to specific rules that are checked when a cloud application profile status is changed. Auto-Audit rules 310 are configured for the system and typically only the cloud manager can change these rules. Audit-Audit rules 310, preferably, include a set of rules that are applied to every change made to a cloud application profile. Alerts are generated for every Auto-Audit rule that fails. Auto-Audit rules 310 are discussed in more detail with respect to Figures 23A and 23B.

[0078] Cloud Controller 302 shows Provisioning services at 312. Provisioning services 312 are responsible for executing the deployment related commands issued by the rules engine of the Cloud Controller. Provisioning services 312 will automatically create, shut down, and restart cloud application instances, in which an instance is a single copy of a running application. Provisioning services 312 interact with the platform infrastructure to carry out provisioning. In operation, prior to running a cloud application, Provisioning services 312 will determine the assets needed to run the cloud application and provision the infrastructure accordingly.

[0079] The features of Provisioning services 312 just described are preferable features only. It is contemplated that Provisioning services 312 may have more or less of the features described and still be within the scope of the present invention.

[0080] Cloud controller 302 shows Monitoring services at 314. Monitoring services 314 capture the information with regard to at least the operational performance of various cloud applications, and the user interface, through the Application Control Panel and Dashboard, make the captured information visible to the system user on his/her client device. Further, the information may be made visible by zone. A zone is created by an authorized user and for purposes of the present invention a zone is defined as a predetermined group of computers. Such computers could be grouped regionally, by divisions of an enterprise or other type of grouping. As such, zones, for example, are a means to segregate and distinguish segments of a cloud for the isolation of environments like deployment, system testing, system user acceptance testing and production; identifying different physical locations and data centers; and enabling quick disaster relief.

[0081] Monitoring services 314 also permit authorized users to browse cloud server configurations by zone in a detailed format and browse a list of transactions that show how

cloud applications are being used by zone or other user-defined criteria. Further, Monitoring services 314 permit authorized users to view the activity logs that show what particular cloud users have been doing with respect to the private cloud. Authorized users can also view a graphical depiction of data on physical and virtual machines with respect to the cloud and data on SLO violations. Monitoring services 314 permit authorized users to browse information relating to cloud applications that are stored in the private cloud, browse information relating to currently active cloud applications, and browse historical data with respect to cloud applications. Yet further, Monitoring services 314 permit authorized users to set and update SLO thresholds, review SLO statistics, and take actions based on how errors are occurring in cloud applications.

[0082] The features of Monitoring services 314 just described are preferable features only. It is contemplated that Monitoring services 314 may have more or less of the features described and still be within the scope of the present invention.

[0083] Alert services 316 of Cloud Controller 302 are generated to indicate a status change in a cloud application in the development and deployment process. Alerts generated by Alert services 316 are associated with Auto-Audit rules. Alerts are classified as “INFO,” “WARN,” “ERROR,” and “FATAL” alerts. In the development of cloud applications, the developer of the cloud application and approvers (cloud managers) can view alerts associated with every change in a cloud application profile status. In the deployment process, all alerts require approval by a cloud manager. However, it is understood that the cloud manager may include one or more levels of approvers and it will still be within the scope of the present invention.

[0084] The cloud manager may accept or decline an alert after review. If the cloud manager chooses to accept the alert, the cloud application will move forward. However, if the cloud manager declines an alert, it will move the cloud application backwards by setting the status of the cloud application profile to DRAFT and the reason will be “rejected.”

[0085] Alert services 316 permit authorized users to configure profile change alerts for cloud applications by zone. Alerts may be sent out by Alert services 316, for example, when a cloud application scales up, when a predetermined number of health checks fail in a predetermined amount of time, or when SLO violations go above an average. Alerts may be generated manually or automatically sent out under predetermined conditions, for example by

email. Alerts with respect to Auto-Audit rules will be discussed in greater detail subsequently with regard to Figures 23A, 23B, and 32.

[0086] The features of Alert services 316 just described are preferable features only. It is contemplated that Alert services 316 may have more or less of the features described and still be within the scope of the present invention.

[0087] SLO watch and compliance services 318 of Cloud Controller 302 permit authorized system users to view a summary of all SLO violations by individual cloud applications or by zone. SLO watch and compliance services 318 also permit authorized system users to view individual violations for a summary value. Further, SLO watching and compliance services 318 allow authorized system users to view a log of individual transaction violations. Yet further, SLO watching and compliance services 318 permit authorized users to filter violations by user, zone, cloud application, web service, or other predetermined criteria.

[0088] The features of SLO watching and compliance services 318 just described are preferable features only. It is contemplated that SLO watching and compliance services 318 may have more or less of the features described and still be within the scope of the present invention.

[0089] Log Scanning services 320 of Cloud Controller 302 permit an authorized system user to view the activity relating to a cloud application, an instance, a hypervisor in control of a virtual machine, or other cloud elements. Using the Log Scanning services, an authorized system user can request an on-demand log scan of any cloud application or component. Further, using Log Scanning Services 320, an authorized system user can view the activities relating to a deployed cloud application.

[0090] Thread Analyzer services 322 permit authorized system users to view transactions that take place within the private cloud with respect to particular nodes that relate to a cloud application that is running.

[0091] Transaction Browser 323 permits authorized system users to filter transactions by user, zone, cloud application, web service, or other predetermined criteria. Transaction Browser 323 allows authorized system users to group transactions together to understand macro behavior, view time statistics by cloud application and zone, and compare response

time statistics for a current cloud application and zone with typical time statistics for cloud applications and zones.

[0092] The features of Thread Analyzer services 322 and Transaction Browser 323 just described are preferable features only. It is contemplated that Thread Analyzer services 322 and Transaction Browser 323 may have more or less of the features described and still be within the scope of the present invention.

[0093] Cloud Stack 324 includes the software stack for the private cloud. Cloud Stack 324 includes operating system software 326, which is preferably Linux software. Further, Cloud Stack 324 includes virtual machine operating software 328 for use by the virtual machines running in the cloud that are managed by hypervisors. Preferably this software is Java® Development Kit ("JDK") software from Sun Microsystems, Inc/Oracle, Inc.

[0094] Cloud Stack 324 includes web server software 330, which preferably is Apache Web server software from the Apache Software Foundation. Cloud Stack 324 also includes application server software 332. Preferably, the application server software is JBoss® software that includes a Tomcat servlet container. The JBoss® software is from Red Hat, Inc. and the Tomcat servlet container software is from the Apache Software Foundation.

[0095] Cloud Stack 324 includes network security software 334, which preferably is Cloakware software from Irdeto B.V. The next software in Cloud Stack 324 is web access management software 336, which is preferably SiteMinder® software from Computer Associates, Inc.

[0096] Cloud Stack 324 includes database access drivers 338, which preferably are Java® Database Connectivity (JDBC) drivers. Cloud Stack 324 also includes Cloud Application Builder runtime software 340 that is the cloud application framework software that will be deployed in the private cloud.

[0097] Finally, Cloud Stack 324 includes third-party libraries 342. The number of library can include one or more such third-party libraries and still be within the scope of the present invention.

[0098] Service Registry 345, which has been described previously, contains a register of at least the web services for the cloud applications that are deployed in the private cloud. The

Service Registry operates cooperatively with Cloud Controller 302 and Cloud Stack 324 for the deployment of developed cloud applications in the private cloud.

[0099] Preferably, Cloud Controller 302, which includes the services described above, and Cloud Stack 324, which includes the software stack described above, form the runtime components along with the cloud application framework that was leveraged to build the cloud application to prepare the cloud application for deployment in the private cloud. With respect to Cloud Controller 302 and Cloud Stack 324, certain components have been specified above; however, it is understood that more or less than these components may make up Cloud Controller 302 and Cloud Stack 324, and they will still be within the scope of the present invention.

[0100] Cloud Application Builder 350 is used to develop cloud applications and web services for deployment in the private cloud of the present invention. Cloud Application Builder 350 includes service development toolkit 352, which is primarily used for the development of web services for cloud applications to be deployed in the private cloud. This service development toolkit includes at least tools for use in the development of web services and the user interface components for a cloud application being developed according to the cloud application framework.

[0101] Cloud Development Toolkit (“CDT”) 354 of Cloud Application Builder 350 is for the development of user interfaces associated with cloud applications to be deployed in the private cloud.

[0102] Cloud Application Builder 350 includes software 356 for developing in web applications. Preferably, application development software 356 is Eclipse from the Eclipse Foundation, which provides the integrated development environment (“IDE”) for application development, plus the Google web toolkit (“GWT”) from Google Inc.

[0103] Cloud Application Builder 350 includes testing software 358, which preferably is JUnit software from JUnit.org. Finally, Cloud Application Builder 350 includes web server servlet software 360, which is used for creating dynamic content for the web server for cloud applications being developed for deployment in the cloud. Preferably, the web server servlet software is Apache Tomcat from the Apache Software Foundation.

[0104] Referring to Figure 4, generally 400, a representative drawing of the logical architecture of the components of the private cloud computing system of the present invention is shown. User interface 402 is the user interface of a client device. The interface will include application control panel 404 that will include the dashboard 406. A representative application control panel is shown in Figure 15 and a representative dashboard is shown in Figure 24.

[0105] Application control panel 404 enables developers, managers of cloud applications, owners of cloud applications, software quality assurance (“SQA”), system users, and others to view, use, and manipulate cloud applications in the cloud. Dashboard 406 enables authorized users to manage infrastructure components. User interface 402 is bidirectionally connected to CLDB 410 for accessing cloud applications and associated information, and other data and information stored in CLDB 410.

[0106] User interface 402 also connects to Cloud Controller 408 for the purpose of sending messages to the Cloud Controller. Preferably, these messages will include, but are not limited to, requests for access to particular cloud applications and web services, and SLO monitoring.

[0107] eSF proxy 412 with eSF database 413 provides security to the cloud. eSF proxy 412 and eSF database 413 provide permissions for cloud application and web services access based on data groups, function groups, and user roles. Data groups, function groups, and user roles are discussed in greater detail with regard to Figures 11-14.

[0108] The permissions include, but are not limited to, what users have access to particular cloud applications and web services in the cloud, what users can carry out certain functions, for example, providing approvals, changing cloud application profiles, or deleting cloud applications from CLDB 410. Moreover, eSF 412/413 is capable of providing a security infrastructure that will contain and satisfy all of the security requirements for cloud applications that are run in the private cloud, as well as, for the private cloud itself. At least part of the security eSF provides is function level entitlements and the eSF also contains the data to support such security offerings. It is understood that the permissions just described are not exhaustive and there may be additional permissions and it still will be within the scope of the present invention.

[0109] Service registry 415 connects to Cloud Controller 408. Service registry 415, which will be discussed in greater detail subsequently, enables developers to search for web services registered for the private cloud and view detailed information about them.

[0110] In processing a request from user interface 402 for a particular cloud application or web services, Cloud Controller 408 sends a request to Provisioning services 414. Provisioning services 414 provisions hypervisors and virtual machines that they control to accommodate the needs of client devices running cloud applications in the cloud. As shown in Figure 4, hypervisor 420 manages web server instance 422, application instance 424, and application instance 426. Each of these software instances is running in a virtual machine instance supervised by hypervisor 420. The private cloud computing system of the present invention can have one or more hypervisors that control cloud application and web server instances that are running in virtual machine instances and still be within the scope of the present invention.

[0111] Referring to Figure 4 at 416, it shows the Build.xml. Build.xml refers to the application build framework that enables developers to build cloud applications using Cloud Application Builder 350 (Figure 3) and its associated runtime libraries. When such cloud applications are built, the binaries associated with the cloud application are provided to binaries bundler 418. The binaries are then sent for storage in CLDB 410 and provided to Provisioning services 414 for provisioning with a hypervisor so that it will be available to the system users, which include client devices for running the cloud application, and authorized system users with permissions to manipulate the cloud application.

[0112] Monitoring services 428 include health check services 430 and log scanning services 432. Health check services 430 monitor the physical and virtual resources of the private cloud. Log scanning services 432 perform automatic and on-demand scans of logs for cloud applications and cloud infrastructure components looking for SLO violations. The information that is determined by health check services 430 and log scanning services 432 is stored on CLDB 410.

[0113] Before describing the development of a cloud application, the user interface management of each cloud application will be discussed referring to Figure 5.

[0114] Figure 5 at 500 shows a representative diagram for user interface management of foreground tasks, data storage, and background tasks for cloud applications on the private

cloud. Service consumers 502 are consumers of services that are inside or outside the cloud. An example of a consumer of services outside the private cloud includes services running on a client device, such as those shown at 504.

[0115] Data access 506 is directed to foreground services, such as those shown at 508 and 510 that are created for the user interface to access the private cloud. For example, developers could create lightweight user interface components in HTML, Adobe Flash, AJAX, and other tools for this purpose. However, it is understood that other services could be created and still be within the scope of the present invention.

[0116] Data storage 512 is directed to online transaction processing (“OLTP”) data that is stored in application database 214 separate from warehouse data. Accordingly, the OLTP data is associated with performing database transactions. Examples of OLTP data is shown at 514 and 516 of data storage 512. In data storage 512, mainframe customer information control system (“CICS”) 514 will leverage conventional CICS functions for purposes of data storage according to the present invention. Data storage 512 also shows RDBMS 516, which is a relational database management system. For purposes of the present invention RDBMS will leverage conventional relational database management functions for purposes of data storage according to the present invention. However, it is understood that the system of the present invention may include other OLTP data components and still be within the scope of the present invention.

[0117] Background 518 is used to create background processes, such as jobs 520 and 522, and manage warehouse data. The creation of jobs will be discussed in greater detail subsequently.

[0118] eSF 526, as stated previously, provides security to the cloud. eSF 526 includes what is shown at 412 and 413 in Figure 4. Through the user interface, eSF 526 is directed to entitlement enforcement. As such, with regard to data access 506 and background 518, eSF 526 controls authorizations to access and use cloud applications and web services by assigning user roles, which preferably are devised by associating stored data with functions within an enterprise.

[0119] Service registry 524 refers to the service registry of the private cloud. The service registry enables developers to search for web services and view detailed information about them. Accordingly, the user interface can be used to browse the service registry for web

services that can be reused. Further, service registry 524 performs the function of bringing applications and web services into the private cloud and monitoring their SLO compliance and usage. The service registry will be discussed in greater detail with regard to Figure 6.

[0120] Figure 6, generally at 600, shows a representative diagram of the architecture of the private cloud computing system of the present invention that shows service registry 524. In Figure 6, Provisioning Services 312, Monitoring Services 314, SLO watch and compliance services 318, Log Scanning Services 320, and Transaction Browser 323 (not shown) are components of Cloud Controller 302 shown in Figure 3, and have been previously described. User interface 406 is shown in Figure 4 and has previously been described. It is understood that Transaction Browser 323 may be shown in Figure 6 and it would still be within the scope of the present invention.

[0121] In the center of Figure 6 is a persistence state 606, which includes audit trail 608, data integrity 610, security 612, and scheduler 614. Audit trail 608 is for tracking changes with respect to cloud applications. Data integrity 610 is for placing constraints on the application database to ensure data integrity within the database. Scheduler 614 is for scheduling jobs. Security 612 is eSF access security.

[0122] Rules engine 602, which is part of the private cloud (the Cloud Controller), will be created by the cloud manager and it will include rules for the operation of cloud applications running within the private cloud. These rules may include, for example, scale-up or scaled-down rules, alert rules, or zone rules. It may contain other rules and still be within the scope of the present invention.

[0123] Again referring to Figure 6, each of the elements is shown connected within messaging environment 604. This enables communications among the various elements.

[0124] Referring to Service Registry 524 in Figure 6, it is contemplated the services registry provides at least four services; however, it is understood that it may provide more or less than four and still be within the scope of the present invention.

[0125] The first service that service registry 524 preferably provides is for servicing application programming interfaces (“APIs”) for authorized developers to create and manipulate metadata relating to web services. This enables authorized users to create or

update the metadata and information on functions and function groups. The APIs reference this information, which preferably is web service details in a service inventory file.

[0126] The second service is a search catalog service. The search catalog service enables authorized system users to search for and discover web services on a catalog search page of the service registry.

[0127] Third service of service registry 524 is a browse category service. This service enables authorized system users to drill down from cloud application function group to a list of constituent web services on an application browser page of the service registry.

[0128] The fourth service of the service registry is a web service details service. This service provides metadata and other information that authorized system users can access on the various tabs of the web services details dialog box of the user interface as shown in Figure 26.

[0129] Referring to Figure 7, generally at 700, representative service registry architecture is shown. Service registry 524 (Figure 5) connects to Cloud Controller 408 (Figure 4). As shown, both Cloud Controller 408 and service registry 524 are within the private cloud. Also connected to service registry 524 from outside the cloud is service metadata repository 704, which is a metadata database. Further, eSF 412/413 (Figure 4) connects to Cloud Controller 408 from outside the cloud. Although not shown, eSF proxy 412 will be disposed between eSF database 413 and Cloud Controller 408, but in the private cloud.

[0130] Cloud Controller 408 connect to browser client (user interface) 402. Browser client 402 provides content to users 706 and permits them to access service registry 524.

[0131] The integration of eSF with service registry 524 insures access to cloud applications, web services, and user interface items, such as button and menu options, is restricted to only authorized system users. This is based on carefully defined roles that determine access for developers and users. Examples of this access control will be discussed subsequently.

[0132] The components of a cloud application to be developed in the cloud include a user interface, registered web services that offer potential reuse, and registry of background jobs that can be reused. The developer that is creating cloud application for deploying in the

private cloud also may create business rules and/or Java® classes that relate to web services and jobs. Once the components of the cloud application are created, they can be stored in CLDB 410. The creation of these components may take place within the private cloud environment.

[0133] In developing the web services, user interface components, and batch jobs, there will be a requirements analysis done by the developer with regard to a cloud application to identify the web services that embody his/her application, the user interface components needed to accomplish the tasks of the cloud application, and the batch jobs needed to store the data for the cloud application. In performing these tasks, in the Cloud Controller the developer can browse and look up registered services in the service registry to see if any can be reused in his/her cloud application.

[0134] According to the system and method of the present invention, before web services can be created for a cloud application, the developer must obtain an application identifier that includes a cloud application code and its extension. This will track an application through the development process including the creation of cloud application profile for the cloud application. Preferably, before the cloud application can be moved further toward the private cloud environment, the source code for the cloud application is placed in a source code control system. Once this task has been performed, the cloud application and its components can be developed using Cloud Application Builder 350 (Figure 3).

[0135] With regard to a particular cloud application, the development of the web service component will include the developer creating metadata for the service definition and completing the service inventory file for the cloud application. Each cloud application will have a service inventory file associated with it that describes the function groups in all member web services. Cloud Controller 302 (Figure 3) uses this data to update the service registry automatically when a cloud application is deployed.

[0136] Preferably, the developer builds separate .war ("web archive") files for foreground and background processes (see Figure 5), bundles the binaries associated with the cloud application, and then creates a cloud application profile. The binaries that are associated with the foreground processes relate to web services and the user interface components. The binaries that are associated with the background processes relate to jobs. However, before the developer can deploy the web service for use in the cloud, the appropriate approvals must

be obtained, which will trigger service registry updates and adjustment to the associated eSF roles stored in the eSF. This process of development is shown graphically in Figure 8.

[0137] Figure 8, generally at 800, shows a representative drawing of the process for development of a web service component for a cloud application to be deployed in the private cloud. As part of cloud application development and deployment process, developer 801 will develop the web service at 804 that is associated with the cloud application. When the web service is developed, at 806, the developer will update the metadata in the service definition that will be used at 808 to update the service inventory file. This completes the portion of web service development associated with cloud application development.

[0138] Following the update of the service inventory file at 808, the developer builds an application binary file for the foreground and background processes at 810. The binaries associated with the cloud application are bundled, and at 812, a request to deploy the web services is made using the cloud application profile that has been created for the cloud application. This request is sent by the developer using a client device user interface to Cloud Controller 814. At 816, approvals by the appropriate authorized users are requested. If the approval is denied, then notification is sent back to the developer via appropriate messaging. However, if approval is granted, there is an update sent to the service registry for the web service at 818 and there is an update of the eSF at 820 with the appropriate permissions for the use of the web service. Following this, the web service is provided live at 822 in the private cloud. Preferably, the private cloud uses the metadata in the service definition and the service inventory file to automatically update the service registry when the web service is deployed.

[0139] As stated, a user interface also is a component of a cloud application. Cloud Application Builder 350, through CDT 354 and appropriate panels on the user interface, develop the user interface component that is to be associated with a particular cloud application. This toolkit permits developers to extend the web services associated with cloud application to the user interface. Preferably, the toolkit will support Flash and Microsoft Office based user interface development.

[0140] Cloud applications deployed in the private cloud can be embedded in non-cloud web pages. If this is done, all the functionality of the cloud application can be accessed from

that webpage with the user interface as a pop-up, but the web services will be running in the private cloud.

[0141] The last component of a cloud application is background jobs. These jobs are batch jobs that run in the background and store information in the cloud and other databases. The background jobs for a cloud application can run in two instances that can be located on different machines. For example, these jobs are run active-active in two separate data centers. Background jobs can involve processing that helps the cloud application server handle scalability without hanging up threads in the foreground.

[0142] Referring to Figure 9, generally at 900, a representative diagram is shown for background job development and handling. In Figure 9, external services 902 connect to background cloud 909. External services 902 include RDBMS 904, messaging 906, and file transfer service 908. Each of these has been previously described with regard to other figures, and, as such, those descriptions apply equally here.

[0143] Background cloud 909 includes three representative cloud application instances at 910, 916, and 922, respectively. Application instance 910 shows batch jobs 912 and 914; application instance 916 shows batch jobs 918 and 920; and application instance 922 shows batch jobs 924 and 926. A scheduler, not shown, manages the jobs and handles multiple application instances, such as those shown in Figure 9. The batch jobs that are shown in background cloud 909 can be bundled in a separate .war file that can contain multiple jobs. These jobs can then be stored in CLDB 410 and be associated with the appropriate cloud application.

[0144] As stated previously, eSF handles cloud application security. Preferably, cloud application developers will set up eSF roles and use an eSF proxy API to secure protected items. The use of eSF security will be explained in greater detail referring to Figure 10.

[0145] Referring to Figure 10, generally at 1000, a representative diagram for implementing eSF security is shown. When a system user requests cloud application or web services access, the system user, shown as service consumer 1002, must be authenticated. As such, SiteMinder® 1004 will check the system user's authentication by querying eDirectory 1006. If authentication is confirmed, then requested web service 1008 associated with a cloud application communicates with eSF proxy 1010 to check the system user's eSF entitlements in eSF database 1012. These entitlements will include whether the system user

is authorized to perform the function specified in the service request. If the system user is authorized, then the system user will have access through the web service to database information at 1014. If the system user is not authorized, then access will be denied.

[0146] Previously, it has been discussed that access to cloud applications and web services may be based on the roles. For purposes of the present invention, function groups are a collection of functions that enable an authorized system user to perform operations on whatever data that relates to that system user's job description. Preferably, function groups will have access to particular data defined by the cloud application developer. The function groups and functions will be defined in the service inventory file and be deployed as part of the application binary files that will update the service registry and eSF database. An example of the formation of functional groups and the services to which these function groups will have access is shown in Figure 11.

[0147] Figure 11, generally at 1100, shows a diagram of function groups related to a cloud application and the services to which each of these groups have access. At cloud application block 1102, it shows a cloud application titled "Master Feeder." The developer of the Master Feeder cloud application 1104 has defined two function groups at function groups block 1106. The first function group at 1108 is defined with administrative functions and the second function group at 1110 is defined with browse functions.

[0148] At services block 1112, the registered services for Master Feeder cloud application 1104 are shown. With regard to the first function group at 1108, this function group is permitted to perform the services that are registered as 791002, 791003, and 791004. This will permit the first function group to Create Master, Add Feeder, and Remove Feeder, respectively.

[0149] With regard to the second function group at 1110, this function group is permitted to perform the services that are registered as 792001 and 792002. This will permit the second function group to Find Master and to Get Feeders, respectively. It is noted that the second function group would not be permitted to have access to the services authorized for the first function group.

[0150] The defining of function groups is based on cloud application roles. Referring to Figure 12, the method by which these roles define function groups will be discussed.

[0151] Referring to Figure 12, generally at 1200, the use of cloud application roles to define function groups is shown. Cloud application block 1202 shows a cloud application titled “Master Feeder.” At cloud application roles templates block 1206, the application developer has defined the roles associated with the Master Feeder cloud application. These roles are Master Feeder Administrator at 1208 and Master Feeder User at 1210. Preferably, the cloud application roles templates are constructed by evaluating the functions that a system user must perform, assembling these functions in a function group, and identifying the data group that contains all the data that may be manipulated by the system user.

[0152] As shown in Figure 12 at functions groups block 1214, the role of a Master Feeder Administrator shown at 1208 may be separated into two function groups. The first function group would be one in which the system user would be permitted the administrative functions at 1216 and the second would be only the browsc functions at 1218.

[0153] As stated, the cloud application roles defined by the developer of the cloud application also provide for the Master Feeder User at 1210. The function group that is assigned to this role would be permitted the browsc functions at 1220. These browsc functions may be the same or different from those for a Master Feeder Administrator and still be within the scope of the present invention.

[0154] The cloud application role templates will be part of the service inventory file and will update the eSF when the cloud application is deployed in the private cloud.

[0155] Figure 13, generally at 1300, shows an eSF entitlement map for an administrator role shown in Figure 12. In functions block 1302, it shows the functions that are available for the first function group at 1316 and the second function group at 1318 in function groups block 1314. As shown, the first function group at 1316 is permitted the functions of Edit Master at 1304, Add Feeder at 1306, and Remove Feeder at 1308. In a similar fashion, the second function group at 1318 is permitted the functions of Browse Master at 1310 and Browse Feeders at 1312.

[0156] At roles block 1320, it shows that the role at 1322 is for an administrator at ABC Corporation. At data groups block 1324, it shows that the administrator receives data regarding ABC Corporation’s funds at 1326, which may be mutual funds for example. Data block 1328, which may be a repository of specific data regarding ABC Corporation’s funds, include ABC1 data at 1330, ABC2 data at 1332, and ABC3 data at 1334 to which the

administrator at 1322 will have access through data groups block 1324 at 1326. In reviewing the entitlement map with regard to the Master Feeder cloud application, the restrictions based on function groups is enforced according to the map.

[0157] Figure 14, generally at 1400, it shows an eSF entitlement map for the user role shown in Figure 12. In functions block 1402, it shows the functions that are available for first function group at 1416 and the second function group at 1418 in function groups block 1414. As shown, the first function group at 1416 is permitted the functions of Edit Master at 1404, Add Feeder at 1406, and Remove Feeder at 1408. In a similar fashion, the second function group at 1418 is permitted the functions of Browse Master at 1410 and Browse Feeders at 1412.

[0158] At roles block 1420, it shows that the role at 1422 is for a system user at ABC Corporation. At data groups block 1424, it shows that the system user receives data regarding ABC Corporation's funds at 1426, which, as in Figure 13, may be mutual funds. Data block 1428, which may be a repository of specific data regarding ABC Corporation's funds, include ABC1 data at 1430, ABC2 data at 1432, and ABC3 data at 1434 to which the system user at 1422 will have access through data groups block 1424 at 1426. In reviewing the entitlement map with regard to the Master Feeder cloud application, the restrictions based on function groups is enforced according to the map. As such, since the role at roles block 1420 is only for a system user, the system user is only permitted the browse function at 1418 in functions group block 1414. As part of this function group, the system user is only permitted to Browse a Master at 1410 and Browse Feeders at 1412 of functions block 1402.

[0159] Previously, with regard to Figure 8, the process for developing and deploying a cloud application in the private cloud was discussed. That process will now be described in greater detail referring to Figures 15-22.

[0160] Preferably, there are five main steps for deploying a cloud application in the private cloud. This process may be referred to as the cloud application promotion process. The five main steps include bundling application binaries and exporting the bundled application binaries to the private cloud, creating and editing a cloud application profile for deploying the cloud application in the private cloud, obtaining the appropriate approvals for deploying the cloud application in the private cloud, performing a certified build of the application so that it can be promoted to user acceptance testing ("UAT"), and setting and

changing system properties in the cloud application profile for cloud application promotion to the private cloud.

[0161] Prior to beginning the cloud application promotion process by deploying the cloud application to the development (“DEV”) environment, preferably, the developer will obtain the previously discussed application identifier for the application. Further, the developer will have requested that the appropriate Cloud Controller access eSF role entitlements be set up in eSF for the developer so that the developer has the appropriate roles to deploy the cloud application. The developer will create a build project for the cloud application in the Cloud Application Builder 350 (Figure 3) and run appropriate tests on the cloud application. Then, the developer will build the cloud application in the cloud application builder so that the developer is ready to bundle the binaries associated with the cloud application for export to the private cloud.

[0162] Once the above steps have been accomplished, the cloud application binaries are bundled and the Cloud Controller promotes the approved and secure web services associated with the cloud application to the private cloud. According to the present invention, the binaries bundler can be invoked from the developer’s client device after a build for proof of concept (“POC”), DEV, and System Integration (“SYS”) deployments. However, the binaries bundler can only be invoked by higher-level build machines, for example, ClearCase build machines or other certified build machines, for the UAT and Production (“PROD”) deployments.

[0163] For purposes of the present invention, in POC and DEV deployments, the developer can build the .war file from his/her client device. In SYS, to promote a cloud application image to UAT, preferably, it will be done from designated machines, such as certified machines where the developer can run ClearCase build scripts or other change control mechanism.

[0164] Cloud applications for UAT and PROD deployment do not go directly to the private cloud from a build. When the developer creates a cloud application profile for UAT, the developer picks a cloud application that was built for SYS on a certified build machine, preferably, where ClearCase build scripts can run. For PROD, the developer picks a cloud application that was promoted to UAT. As such, this makes the cloud application deployed in UAT and PROD the same as the cloud application that was tested in the previous

environment in the application promotion process. Although, what has just been described as the preferred method for application promotion, it is understood that other methods are possible and can still be within the scope of the present invention.

[0165] The four deployment environments discussed above will now be discussed in view of the promotion process as it relates to the creation of cloud application profiles.

[0166] DEV – After the developer has done development and testing of the cloud application, he/she can export the cloud application's .war file to the private cloud. The developer using the user interface can select Application Profile tab on the user interface. The cloud application's initial status is DRAFT. The developer will provide the appropriate information for completing the cloud application profile and select a cloud application for association with it. The developer will then change the status to PUBLISHED. The developer's cloud application will run in the DEV environment upon approval by the appropriate level cloud manager.

[0167] SYS – Only cloud applications running in DEV can be promoted to SYS. In SYS, a cloud application may be built on a certified build machine, for example, a build machine running ClearCase build scripts.

[0168] UAT – Only cloud applications running in SYS can be promoted to UAT.

[0169] PROD – Only cloud applications running in UAT can be promoted to PROD, where such cloud applications will be run live on the private cloud.

[0170] The method for creating a cloud application profile and changing the status of the cloud application from DRAFT to PUBLISHED will now be described referring to Figures 15-22.

[0171] Referring to Figure 15, generally at 1500, a representative cloud application control panel is shown at 1502. To generate a new application profile, Application Profiles tab 1504 is activated which will provide the lower screen that has Add Application Profile tab 1506. As seen at status line 1508, the initial status is always DRAFT. When Add New button 1510 is activated, it will cause Add New Application Profile window 1600 to be displayed.

[0172] Referring to Figure 16, in Add New Application Profile 1600, the name of the cloud application is entered in the name field 1602. Then, in App Code field 1604, the button is selected to provide the drop-down list and the appropriate application identifier is selected that has been assigned to this particular cloud application. It is now necessary to complete the remainder of the profile.

[0173] First, the version of the application is entered in Version field 1606. Then, in Zone Environment field 1608, the button is selected to provide the drop-down list and the appropriate environment for deployment is selected. Similarly, in Zone Code field 1610, the button is selected to provide the drop-down list, such as the drop-down list shown in Figure 17, generally at 1700. When the appropriate Zone Code is selected, it will populate Zone Code field 1610.

[0174] Next, an effective date and time are selected in Effective Date field 1612. The selection of a future date enables the approval process to complete and this will be the date on which the private cloud will start running the cloud application. If the effective date passes without approval, the private cloud will start running the cloud application when the approval process is complete. The Expire Date field 1614 may be completed but it is optional.

[0175] Context field 1616 will include the context for the cloud application. For example, the context field will provide the fully qualified path for a cloud application, such as, for example, [http://Cloud.statestreet.com/App1/\[default\]](http://Cloud.statestreet.com/App1/[default]).

[0176] In Requests Pattern field 1618, the service request prefix or other characters are added. For example, the service request prefix for routing that is found in this field is provided by the Cloud Controller.

[0177] In order to populate App Image field 1620, button 1622 is activated which will open Image Browser Dialogue window 1800 in Figure 18. Here, the appropriate cloud application is selected. By selecting the information icon at 1802, the dialogue window shown at 1900 in Figure 19 is displayed, which shows the cloud application details. Once it is confirmed that the cloud application details are correct, Related Images tab 1902 is activated which will open the display window at 2000 in Figure 20. After the information in the display window shown in Figure 20 is verified, this window is closed along with the Image Browser window shown in Figure 19. Then, the select image button at 1804 in Figure 18 is activated and then the Save button at 1624 in Figure 16 is activated to save the new

application profile. When the save is complete, the status of the cloud application is set to DRAFT.

[0178] To change the status from DRAFT to PUBLISHED, it is necessary to activate button 1628 in Status field 1626 in Figure 16. This will open the App Change Profile Status display window shown in Figure 21 at 2100. In New Status field 2102, the button at 2104 is selected to provide the drop-down list and the appropriate status is selected, which in this example is PUBLISHED.

[0179] Next, the View Alerts button at 2106 is activated which will open Alerts dialog window 2200 shown in Figure 22. If the alerts are accepted, then the Accept button at 2202 is activated and the status of the cloud application is changed to PUBLISHED, and it can go live in the private cloud once all the approvals are obtained. If however the Decline button at 2204 is activated because of the nature of the alerts, then the status of the application will not be changed to PUBLISHED and it will not go live on the private cloud.

[0180] Alerts have been discussed generally with respect to their use in the development and deployment of cloud applications. Now, alerts will be discussed in greater detail.

[0181] Cloud application developers can make changes to a cloud application profile while the cloud application profile is in DRAFT status. Auto-Audit services are a set of rules applied to every change made to a cloud application profile.

[0182] Alerts are generated for every Auto-Audit rule that fails. As stated previously alerts are classified as INFO, WARN, ERROR, and FATAL. Preferably, a developer will review the alerts associated with each cloud application profile change. Further, the appropriate approvers, cloud managers, must review the alerts when they are non-INFO alerts associated with a particular cloud application profile before the cloud application can be advanced to being provided live on the private cloud.

[0183] As described previously, approvers can accept or decline the alerts after review. If the approver accepts the alerts the cloud application will move forward in the development and deployment process. However if the approver declines the alerts the cloud application moves backwards by setting the status of the cloud application profile to REJECTED with the reason code as DECLINED ALERTS. Alerts that are generated can be automatically sent to

approvers by email or other messaging method so that they will be alerted to the generation of such alerts.

[0184] Generally, the Auto-Audit mechanism is for identifying issues and problems in a cloud application profile. This Auto-Audit mechanism includes rules that will generate auto alerts when any of the rules that are checked result in a failure. The Auto-Audit rules are created by the cloud manager.

[0185] Alerts are associated with issues and problems in the cloud application profile, and once generated must be accepted or declined by an appropriate level approver of the cloud manager. If the cloud manager accepts the alerts associated with a cloud application profile, then the cloud application will move forward in the process toward being displayed live in the private cloud. If the alert is declined, the cloud application is rejected and the cloud application profile status is changed to DRAFT. If this is the case, the developer must fix the problem before the application can be moved forward to being PUBLISHED.

[0186] Referring to Figure 23A, generally at 2250, a representative diagram relating to actions associated with the application of Auto-Audit rules application is shown. At 2252, Auto-Audit rules are applied to a cloud application when the associated cloud application profile is changed while it is in the DRAFT status. In the “detect” phase, alerts are generated for every Auto-Audit rule that fails. As stated previously, the alerts are classified as INFO, WARN, ERROR, or FATAL.

[0187] In the “review” phase at 2254, developers will review the alerts after every change to a cloud application profile. An approver of the cloud manager reviews every alert. In the “control” phase, approvers of the cloud manager must accept or decline the alerts after review.

[0188] A representative set of Auto-audit rules is shown in Figure 23B generally at 2300. Referring to Figure 23B, a representative set of Auto-Audit rules is shown at 2302. There are 10 rules shown but this set of 10 is only exemplary. With respect to each rule, there is a severity of the rule that is shown at 2304. The severity is defined by one of the four alert states, namely, INFO, WARN, ERROR, and FATAL. At 2306, there is an explanation of the alert. Accordingly, when there is a change to any cloud application profile status, each of the Auto-Audit rules is checked and to the extent that there are any violations, alerts will be lodged against that cloud application. It is only upon the acceptance of these alerts by the

appropriate approvers that the cloud application can move forward in the development and deployment process.

[0189] In Figure 4, a user interface 402 shows dashboard 406. A representative dashboard display is shown in Figure 24 generally at 2400. As shown, a cloud application and zones can be viewed in detail or graphically to enable a survey of a cloud application's health. In Figure 24, for the cloud application shown at 2401, application details are shown at 2402, virtual machine details are shown at 2406, and virtual details are shown at 2408. Further, the graphical display of zones is shown at 2410.

[0190] The graphical display of zones at 2410 shows the health with regard to TX/SLO (Transaction/SLO) at 2412 and users at 2418 to be very good since the indicator arrow is well into the Green area. The health of physical machines shown at 2416 is not as good because the indicator arrow is close to the Yellow or warning area. Finally, the health of virtual machines shown at 2414 is not good because the indicator arrow is in the Red area. Preferably, because the indicator arrow is in the Red area, cloud managers will be alerted to this and, if possible, correct the loading problem associated with the virtual machines.

[0191] It is understood, that there may be the selection of the various tabs shown on dashboard display 2400 and this will provide additional health information with regard to the system applications and infrastructure.

[0192] In describing service registry 524 with respect to Figures 6 and 7, the content of the service registry was discussed but not shown. Further, there has been previous discussion that through the service registry authorized system users would have access to web services details related to service registry entries. In Figures 25 and 26, representative screen displays of a service registry window and a web services detail window are shown.

[0193] Referring to Figure 25, generally at 2500, a representative service registry display window is shown. As shown at 2502, each registry entry has a number, name, description, and additional information relating to the service. This information makes the services searchable by authorized system users. If an authorized system user desires detailed information with regard to a specific entry in the service registry, it may be obtained by selecting that service entry which will open a web services detail window, such as the one shown in Figure 26.

[0194] Referring to Figure 26, generally at 2600, a service registry display 2602 with a web services detail display 2604 window is shown. If an authorized system user selects service registry no. 511446 in service registry window 2602, it will open web services detail display window 2604 for service registry no. 511446 to provide specific detail with regard to that registry number. In display window 2604 the basic information about service registry no. 511446 is shown; however, by selecting any of the additional tabs, additional detailed information will be provided about this registry number.

[0195] Referring to Figures 27-32, representative cloud application deployment workflows will be described.

[0196] Referring to Figure 27, generally at 2700, a cloud application deployment workflow is shown for the POC/DEV/SYS environments. Collectively, POC/DEV/SYS form a zone. This Figure shows the process a cloud application profile must go through when a cloud application is being deployed to the POC, DEV, and SYS environments.

[0197] At 2702, a developer will have access to a cloud application profile to edit the fields of the profile file as long as it has the DRAFT status, as shown at 2704. Once the developer is satisfied with the changes to the cloud application profile, the status in the cloud application profile will be changed to PUBLISHED at 2706.

[0198] Next, preferably, a lead developer will review the application profile and when satisfied with it, he/she will change the status of the cloud application to LEAD APPROVAL, as shown at 2208. If, however, the lead developer is not satisfied, he/she can reject the application as shown as REJECTED at 2710, which will return the status of cloud application profile to DRAFT.

[0199] If the lead developer approves the cloud application, the cloud application profile will be forwarded to the Cloud Controller at 2711. The Cloud Controller, having taken over at this point, validates the cloud application profile and changes the status of the cloud application profile to SCHEDULED, as shown at 2712. The application profile will stay in the status until it is time for deployment to the private cloud.

[0200] Typically, the time to deploy a cloud application is indicated in the cloud application profile. When the deployment time comes, the Cloud Controller changes the status of the cloud application profile to INSTALLING at 2713, while at the same time

carrying out provisioning to install the cloud application. The Cloud Controller will extract the service inventory file, read the service metadata and access control information, UPDATE eSF at 2715, and UPDATE SERVICE REGISTRY at 2714. Once installation is complete, the status of the cloud application profile is changed to RUNNING at 2716. Preferably, RUNNING means the cloud application is running live in the private cloud.

[0201] Referring to Figure 28, generally at 2800, a cloud application deployment workflow is shown for POC/DEV/SYS environments. Collectively, UAT/PREP/PROD form a zone. In Figure 28 the workflow processes that relate to DRAFT at 2704, PUBLISHED at 2706, LEAD APPROVAL at 2708, REJECTED at 2710, SCHEDULED at 2712, INSTALLING at 2713, UPDATE eSF at 2715, and UPDATE REGISTRY at 2714 are the same as those in Figure 27. Accordingly, the descriptions of these items with respect to Figure 27 apply equally here.

[0202] When deploying the cloud application to the UAT and PROD environments, the workflow requires three additional approvals after the LEAD APPROVAL at 2708. These approvals include the MANAGER APPROVAL at 2802, SQA APPROVAL at 2804, and BUSINESS APPROVAL at 2810. There can be more or less than these additional approvals and it will still be within the scope of the present invention.

[0203] Referring to Figure 29, generally at 2900, a cloud application deployment workflow is shown for emergency conditions. In Figure 29, the workflow processes that relate to DRAFT at 2704, PUBLISHED at 2706, LEAD APPROVAL at 2708, REJECTED at 2710, MANAGER APPROVAL at 2802, SQA APPROVAL at 2804, BUSINESS APPROVAL at 2810, and SCHEDULED at 2712, are the same as those in Figure 28, except LEAD APPROVAL at 2708 and MANAGER APPROVAL at 2802 are part of developer 2702, and SQA APPROVAL at 2804 and BUSINESS APPROVAL at 2810 are grouped in alternative flow 2902 that includes EMERGENCY APPROVAL 2904. Accordingly, the descriptions of these items with respect to Figure 28 apply equally here.

[0204] If the developer requests that the cloud application profile be moved as an emergency deployment, the workflow of Figure 29 will be used. In the emergency deployment workflow, the SQA and BUSINESS APPROVAL may be skipped by an authorized person who has access to EMERGENCY APPROVAL at 2904. Preferably, the

emergency workflow is for deploying unexpected but critical technical changes that need to be moved forward urgently to deployment.

[0205] Referring to Figure 30 generally at 3000, a moratorium cloud application deployment workflow is shown. In Figure 29, the workflow processes that relate to DRAFT at 2704, PUBLISHED at 2706, LEAD APPROVAL at 2708, REJECTED at 2710, MANAGER APPROVAL at 2802, SQA APPROVAL at 2804, BUSINESS APPROVAL at 2810, SCHEDULED at 2712, and EMERGENCY APPROVAL at 2904 are the same as those in Figure 29. Accordingly, the descriptions of these items with respect to Figure 29 apply equally here.

[0206] A moratorium deployment workflow is used when cloud applications need to be moved during a monthly moratorium or other fixed period of time. For example, it could coincide with the last and first business days of a month. During this time, changes to live cloud applications are restricted.

[0207] According to Figure 30, alternative workflow 2902 includes MORATORIUM APPROVAL 1 at 3002 and MORATORIUM APPROVAL 2 at 3004. These latter approvals are acquired from high-level entities within the enterprise.

[0208] Referring to Figure 31, generally at 3100, shows a cloud application deployment workflow for backing an application out of the deployment process. When a cloud application deployment results in an unexpected malfunction in the cloud application, it may be necessary for the version of the cloud application that was deployed to be backed out of the private cloud.

[0209] When a problem is detected in a deployed cloud application, a decision will be made whether to back the application out. This can be done by the creation of an application "backout" file. This file may be created with the binaries for the cloud application that were deployed before the cloud application had problems. A backout profile is created by the developer using these binaries.

[0210] Again referring to Figure 31, the backout application deployment workflow is shown graphically. At 3102, once there is a problem detected with a deployed version of the cloud application, a decision must be made whether or not to create and use a backout profile.

[0211] If it is decided to create a backout profile, the process proceeds to 3104. At 3104, the backout profile can be created using the Application Control Panel. In creating the backout profile, only previously deployed cloud applications can be used. Further, once the backout profile is created it cannot be changed. An activity log keeps track of the history related to the backout profile.

[0212] Once the backout file is created, the process moves to 3106, where it is necessary to get the appropriate approvals. These approvals are obtained in a manner consistent with the workflows shown in at least Figures 27-30 and 32.

[0213] Referring to Figure 32, generally at 3200, and alternative cloud application deployment workflow shown in which Auto-Alerts are incorporated. In Figure 32, the workflow processes that relate to DRAFT at 2704, PUBLISHED at 2706, LEAD APPROVAL at 2708, REJECTED at 2710, MANAGER APPROVAL at 2802, SQA APPROVAL at 2804, BUSINESS APPROVAL at 2810, and SCHEDULED at 2712 are the same as those in Figure 29. Accordingly, the descriptions of these items with respect to Figure 29 apply equally here.

[0214] The workflow shown in Figure 32 incorporates the use of Auto-Audit rules at each stage. At 2704, a cloud application with a DRAFT status has its cloud application profile changed at 3202, then the Auto-Audit rules evaluate the change at 3204. This will generate application profile alerts at 3206. The developer then fixes the problems at 3208 that caused the alerts. If the fixes are deemed appropriate, then the cloud application is PUBLISHED at 2706. However, at each stage in the alternative workflow at 3205, each approval level must accept the alerts, as shown at 3010, 3012, 3014, and 3016, for the application to move to the next approval stage. If at any of the approved stages the alerts are declined, the workflow moves to decline alerts at 3218, and the application is rejected at 2710. When the application is rejected in this manner, its status will be reverted back to DRAFT and the process must begin again to move the cloud application to deployment in the private cloud.

[0215] The embodiments or portions thereof of the system and method of the present invention may be implemented in computer hardware, firmware, and/or computer programs executing on programmable computers or servers that each includes a processor and a storage medium readable by the processor (including volatile and non-volatile memory and/or

storage elements). Any computer program may be implemented in a high-level procedural or object-oriented programming language to communicate within and outside of computer-based systems.

[0216] Any computer program may be stored on an article of manufacture, such as a storage medium (e.g., CD-ROM, hard disk, or magnetic diskette) or device (e.g., computer peripheral), that is readable by a general or special purpose programmable computer for configuring and operating the computer when the storage medium or device is read by the computer to perform the functions of the embodiments. The embodiments, or portions thereof, may also be implemented as a machine-readable storage medium, configured with a computer program, where, upon execution, instructions in the computer program cause a machine to operate to perform the functions of the embodiments described above.

[0217] The embodiments, or portions thereof, of the system and method of the present invention described above may be used in a variety of applications. Although the embodiments, or portions thereof, are not limited in this respect, the embodiments, or portions thereof, may be implemented with memory devices in microcontrollers, general purpose microprocessors, digital signal processors (DSPs), reduced instruction-set computing (RISC), and complex instruction-set computing (CISC), among other electronic components. Moreover, the embodiments, or portions thereof, described above may also be implemented using integrated circuit blocks referred to as main memory, cache memory, or other types of memory that store electronic instructions to be executed by a microprocessor or store data that may be used in arithmetic operations.

[0218] The descriptions are applicable in any computing or processing environment. The embodiments, or portions thereof, may be implemented in hardware, software, or a combination of the two. For example, the embodiments, or portions thereof, may be implemented using circuitry, such as one or more of programmable logic (e.g., an ASIC), logic gates, a processor, and a memory.

[0219] Various modifications to the disclosed embodiments will be apparent to those skilled in the art, and the general principals set forth below may be applied to other embodiments and applications. Thus, the present invention is not intended to be limited to the embodiments shown or described herein.

Claims:

1. A computer-based system having a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising:
 - at least one system user interface connected to the cloud computing environment, with the at least one system user interface initiating a virtual machine environment in the cloud computing environment by transmitting requests to the cloud computing environment to access and use applications and/or virtual machine services accessible through the cloud computing environment;
 - at least one provisioner in the cloud computing environment that is connected to the at least one system user interface, with the at least one provisioner for balancing a distribution of the requests for applications and/or virtual machine services from the at least one user interface among a plurality of activated first server types and a plurality of activated second server types in the cloud computing environment;
 - at least one activated first server type connected to the provisioner for at least routing requests received from the at least one system user interface for accessing and/or using virtual machine services stored in or accessible through the cloud computing environment;
 - a plurality of second server types connected to the at least one activated first server type, with the second server types for routing requests for applications and/or virtual machine services received from the at least one system user interface; and
 - a cloud database connected to the second server types and the at least one system user interface, with the cloud database receiving requests for access to virtual machine services in the cloud database and making the requested virtual machine services available for the at least one system user interface to run in a virtual machine environment in the cloud computing environment, wherein the virtual machine environment is associated with the activated first-server type and one or more activated second server types.
2. The system as recited in claim 1, wherein the cloud computing environment includes a public cloud.
3. The system as recited in claim 2, wherein the at least one system user interface includes being wired or wirelessly connected to the cloud computing environment.
4. The system as recited in claim 1, wherein the cloud computing environment includes a private cloud.
5. The system as recited in claim 4, wherein the cloud computing environment includes an enterprise-wide private cloud.

6. The system as recited in claim 4, wherein the at least one system user interface includes being wired or wirelessly connected to the cloud computing environment.
7. The system as recited in claim 1, wherein the at least one system user interface includes a personal computer, personal digital assistant, tablet device, or smart phone.
8. The system as recited in claim 1, wherein the provisioner includes a load balancer for providing provisioning services for balancing the distribution of requests for applications and/or virtual machine services from the at least one system user interface among a plurality of first server types and second server types.
9. The system as recited in claim 8, wherein the plurality of first server types includes at least two web servers and the load balancer balances distribution of requests for applications and/or virtual machine services from the at least one system user interface between the two web servers.
10. The system as recited in claim 1, wherein the requests transmitted from the at least one system user interface to the cloud computing environment include requests formatted according to a hypertext transfer protocol (HTTP).
11. The system as recited in claim 1, wherein the first server type includes a web server.
12. The system as recited in claim 1, wherein the second server type includes an application server.
13. The system as recited in claim 1, wherein virtual machine services include virtual desktop services.
14. A computer-based system having a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising:
 - a plurality of system user interfaces connected to the cloud computing environment, with each system user interface initiating a virtual machine environment in the cloud computing environment by transmitting requests to the cloud computing environment to access and use applications and/or virtual machine services accessible through the cloud computing environment;
 - at least one provisioner in the cloud computing environment that is connected to the plurality of system user interfaces, with the at least one provisioner for balancing a distribution of the requests for applications and/or virtual machine services from the plurality of user interfaces among a plurality of activated first server types and a plurality of activated second server types in the cloud computing environment;

a plurality of first server types connected to the provisioner, with each activated first server type of the plurality of the first server types for at least routing requests for applications and/or virtual machine services received from the plurality system user interfaces for accessing and/or using applications and/or virtual machine services stored in or accessible through the cloud computing environment that have been provisioned by the provisioner to each activated first server type; and

a plurality of second server types connected to each first server type, with each activated second server type of the plurality of second server types for routing requests for applications and/or virtual machine services received from the plurality of system user interfaces to a plurality of hosted web services in each activated second server type and with the hosted web services being selected according to requests for applications and/or virtual machine services from each of the plurality of system user interfaces.

15. The system as recited in claim 14, wherein the cloud computing environment includes a public cloud.

16. The system as recited in claim 15, wherein each of the plurality of system user interfaces includes being wired or wirelessly connected to the cloud computing environment.

17. The system as recited in claim 14, wherein the cloud computing environment includes a private cloud.

18. The system as recited in claim 17, wherein the cloud computing environment includes an enterprise-wide private cloud.

19. The system as recited in claim 17, wherein each of the plurality system user interfaces includes being wired or wirelessly connected to the cloud computing environment.

20. The system as recited in claim 14, wherein each of the plurality of system user interfaces includes a personal computer, personal digital assistant, tablet device, or smart phone.

21. The system as recited in claim 14, wherein the provisioner includes a load balancer for providing provisioning services for balancing the distribution of requests for applications and/or virtual machine services from the plurality of system user interfaces among a plurality of first server types and second server types.

22. The system as recited in claim 21, wherein the plurality of first server types includes at least two web servers and the load balancer balances distribution of requests for applications and/or web services from the plurality of system user interfaces between the two web servers.
23. The system as recited in claim 14, wherein the requests transmitted from the plurality of system user interfaces to the cloud computing environment include requests formatted according to a hypertext transfer protocol (HTTP).
24. The system as recited in claim 14, wherein each of the plurality of first server types includes a web server.
25. The system as recited in claim 14, wherein each of the plurality of second server types includes an application server.
26. The system as recited in claim 14, wherein the system further includes a monitor for monitoring the number of requests the cloud computing environment receives from the plurality of system user interfaces for applications and/or virtual machine services for controlling a number of first server types and second server types that are activated and available to the provisioner for transmitting requests from the plurality of system user interfaces for applications and/or virtual machine services.
27. The system as recited in claim 14, wherein virtual machine services include virtual desktop services.
28. A computer-based system virtual machine infrastructure for provisioning a plurality of virtual machine environments in a cloud computing environment, comprising:
 - a provisioner in the cloud computing environment that receives a plurality of requests for desktop applications from a plurality of system user interfaces, with the provisioner for balancing a distribution of the requests for desktop applications from the plurality of user interfaces among a plurality of activated first server types and a plurality of activated second server types according to the number of requests received from the plurality of system user interfaces for operating one or more virtual machine environments in the cloud environment that are associated with activated first server types and activated second server types;
 - a cluster of a plurality of first server types connected to the provisioner, with each of the plurality of first server types of being capable of being activated and deactivated by the provisioner and when activated to process one or more requests for desktop applications from the plurality of system user interfaces according to the distribution of such requests by

the provisioner and each activated first server type shall be associated with a virtual machine environment running in the cloud environment; and

a cluster of a plurality of second server types, wherein the cluster is connected to each of the plurality of first server types, with each of the plurality of second server types being capable of being activated and deactivated by the provisioner and when activated to process one or more requests for desktop applications from the plurality of system user interfaces according to the distribution of such requests by the provisioner and each activated second server type along with the connected activated first server type shall be associated with a virtual machine environment in the cloud environment.

29. The system as recited in claim 28, wherein the cloud computing environment includes a public cloud.

30. The system as recited in claim 29, wherein each of the plurality of system user interfaces includes being wired or wirelessly connected to the cloud computing environment.

31. The system as recited in claim 28, wherein the cloud computing environment includes a private cloud.

32. The system as recited in claim 31, wherein the cloud computing environment includes an enterprise-wide private cloud.

33. The system as recited in claim 31, wherein each of the plurality system user interfaces includes being wired or wirelessly connected to the cloud computing environment.

34. The system as recited in claim 28, wherein the provisioner includes a load balancer for providing provisioning services for the plurality first server types and the plurality second server types for balancing the distribution of requests for desktop applications from the plurality of system user interfaces among the plurality of first server types and second server types.

35. The system as recited in claim 28, wherein each of the plurality of first server types includes a web server.

36. The system as recited in claim 35, wherein the plurality of first server types includes at least two web servers and the load balancer balances distribution of requests for desktop applications from the plurality of system user interfaces between the two web servers.

37. The system as recited in claim 36, wherein the plurality of second server types includes a cluster of application servers, with a cluster of application servers being connected to each of the web servers.

38. The system as recited in claim 30, wherein the system further includes a monitor for monitoring the number of requests the cloud computing environment receives from the plurality of system user interfaces for desktop applications and for controlling a number of activated first server types and activated second server types that are available to the provisioner for transmitting requests from the plurality of system user interfaces for desktop applications.

39. A computer-based system having a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising:

- a plurality of system user interfaces connected to the cloud computing environment, with each system user interface initiating a virtual machine environment by transmitting requests to the cloud computing environment to access and use applications and/or virtual machine services in the cloud computing environment;
- provisioning services of a cloud controller connected to the plurality of system user interfaces for receiving the requests for applications and/or virtual machine services from the plurality of system user interfaces and provisioning virtual machine environments and associated virtual machine environment controls in the cloud computing environment according to the number of requests received from the plurality of system user interfaces;
- a plurality of virtual machine environments and associated virtual machine environment controls that are activated and deactivated by the provisioning services, with each activated virtual machine environment and associated virtual machine environment controls running web server instances and application instances in the cloud computing environment according to the requests for applications and/or virtual machine services provisioned to each activated virtual machine environment and associated virtual machine environment controls by the provisioning services;
- monitoring services of the cloud controller connected to the provisioning services for monitoring the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces and controlling the provisioning services to activate or deactivate certain of the plurality of virtual machine environments and associated virtual machine environment controls according to the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces; and

a cloud database for storing virtual machine services that can be retrieved and/or run in activated virtual machine environments as controlled by associated virtual machine environment controls according to the requests for applications and/or virtual machine services received from the plurality of system user interfaces.

40. The system as recited in claim 39, wherein the cloud computing environment includes a public cloud.

41. The system as recited in claim 40, wherein each of the plurality of system user interfaces includes being wired or wirelessly connected to the cloud computing environment.

42. The system as recited in claim 39, wherein the cloud computing environment includes a private cloud.

43. The system as recited in claim 42, wherein the cloud computing environment includes an enterprise-wide private cloud.

44. The system as recited in claim 42, wherein each of the plurality system user interfaces includes being wired or wirelessly connected to the cloud computing environment.

45. The system as recited in claim 39, wherein the provisioning services include a load balancer for balancing the distribution of requests for applications and/or virtual machine services from the plurality of system user interfaces among the plurality of activated virtual machine environments and associated virtual machine environment controls.

46. The system as recited in claim 39, wherein virtual machine environment controls includes a hypervisor for controlling an associated virtual machine environment.

47. The system as recited in claim 39, wherein virtual machine services include virtual desktop services.

48. A computer-based method for operation of a virtual machine infrastructure for hosting a plurality of virtual machine environments in a cloud computing environment, comprising the steps of:

(a) a plurality of system user interfaces transmitting requests for applications and/or web services to the cloud computing environment;

(b) provisioning services of the cloud computing environment receiving the requests for applications and/or virtual machine services from the plurality of system user interfaces and activating or deactivating virtual machine environments and associated virtual

machine environment controls according to the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces;

(c) activated virtual machine environments and associated virtual machine environment controls running web server instances and application instances according to the requests for applications and/or virtual machine services that have been provisioned to each activated virtual machine environment and associated virtual machine environment controls; and

(d) monitoring services of the cloud computing environment monitoring the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces at a given point in time and controlling the provisioning services to activate or deactivate one or more virtual machine environments and associated virtual machine environment controls according to the number of requests for applications and/or virtual machine services received from the plurality of system user interfaces.

49. The method according to claim 48, wherein virtual machine environment controls include a hypervisor for controlling an associated virtual machine environment.

50. The method as recited in claim 48, wherein the provisioning services include a load balancer for balancing the distribution of requests for applications and/or virtual machine services from the plurality of system user interfaces among the plurality of activated virtual machine environments and associated virtual machine environment controls.

51. The method as recited in claim 48, wherein virtual machine services include virtual desktop services.




FIG. 1




FIG. 2A

SUBSTITUTE SHEET (RULE 26)




FIG. 2B

SUBSTITUTE SHEET (RULE 26)




FIG. 3

SUBSTITUTE SHEET (RULE 26)

4/28




FIG. 4

SUBSTITUTE SHEET (RULE 26)




FIG. 5




FIG. 6

6/28




FIG. 7




FIG. 8

SUBSTITUTE SHEET (RULE 26)

7/28




FIG. 9






FIG. 10

SUBSTITUTE SHEET (RULE 26)

8/28



SUBSTITUTE SHEET (RULE 26)

9/28




FIG. 13

SUBSTITUTE SHEET (RULE 26)

10/28




FIG. 14

SUBSTITUTE SHEET (RULE 26)

11/28

App Control Panel									
Home		Cloud	Service Registry	Application Profiles					
My Dashboard		Application Profiles		Transactions		SLA Violations		Log Browser	
A	U	App Code	Version	App Name	Status	Virtual Count	Effective Date	Zone Env	Zone Code
COH W00259	1.9.6	Test Hwd		LEAD APP...	0	Jun 09, 2011 15:15:48	PROD	GDC-PROD	
COH W00259	1.9.5	Test Hdw		LEAD APP...	0	Jun 09, 2011 15:07:17	PROD	GDC-PROD	
COH W00259	1.9.4	Test Hdw		PUBLISHED	0	Jun 09, 2011 12:33:48	PROD	GDC-PROD	
②	COH W00259	1.5.4	Demo App	RUNNING	2	Jun 09, 2011 08:24:25	DEV1	GDC-DC	
COH W00259	0.0.0b	Test		PUBLISHED	0	May 26, 2011 09:02:33	UAT	GDC-DC	
COH W00259	1.5.1	Test Hello World		PUBLISHED	0	May 19, 2011 10:54:01	DEV1	GDC-DC	
COH W00259	1.1.5	Hello world may 19		DRAFT	0	May 19, 2011 10:45:57	DEV1	GDC-DC	
<input type="button" value="Add Application Profile"/> <input type="button" value="Add New"/> <input type="button" value="Delete"/> <input type="button" value="Edit"/> <input type="button" value="View"/> <input type="button" value="Print"/> <input type="button" value="Export"/> <input type="button" value="Import"/> <input type="button" value="Help"/>									
Displaying 1 - 25 of 32 <input type="button" value="First"/> <input type="button" value="Previous"/> <input type="button" value="Next"/> <input type="button" value="Last"/> <input type="button" value="First"/> <input type="button" value="Previous"/> <input type="button" value="Next"/> <input type="button" value="Last"/>									

Configuration		INFO		Action	
Status:		DRAFT		<input type="button" value="Edit"/> <input type="button" value="Delete"/>	
Name:		Effective Date:		Expire Date:	
App Code:		Cluster Name:		Context:	
Version:		Request Pattern:		Workflow:	
Zone Env:		Workflow:		App Image:	
Zone Code:		App Image:		<input type="button" value="Add New"/> <input type="button" value="Delete"/> <input type="button" value="Edit"/> <input type="button" value="View"/> <input type="button" value="Print"/> <input type="button" value="Export"/> <input type="button" value="Import"/> <input type="button" value="Help"/>	

SUBSTITUTE SHEET (RULE 26)

1510 FIG. 15

12/28

1600 →

1628 →

Add New Application Profile	
Configuration ▾ Info ▾ Action ▾	
Status:	DRAFT
1602 Name:	...
1604 App Code:	...
1606 Version:	...
1608 Zone Env.:	...
1610 Zone Code:	...
1612 Is Backout:	...
1614 Effective Date:	06/10/2011 10:51
1616 Expire Date:	...
1618 Cluster Name:	...
1620 Context:	...
1622 Request Pattern:	...
1624 Workflow:	Normal
1626 App Image:	...
<input type="button" value="Add New"/> <input type="button" value="Close"/> <input type="button" value="Save"/>	

FIG. 16

SUBSTITUTE SHEET (RULE 26)

13/28

1700

CLD-NA
GDC-DC
GDC-DEV
GDC-PROD
GDC-SYS
GDC-UAT
IGB-DC
IGB-DEV
IGB-PROD
IGB-SYS
IGB-UAT
GDC-DC

FIG. 17

1800

Image Browser							
Name	Version	Description	Type	Checksum	File Name	App Code	Build Date
MyHelloWorld.war	10.56...	MyHelloWorld 01	WAR	136	MyHelloWorld.war	OSA_ABC	Nov 30, 2010 06:52:59
MyHelloWorld.war	10.56...	MyHelloWorld 01	WAR	136	MyHelloWorld.war	OSA_ABC	Nov 30, 2010 05:09:48

1804

FIG. 18

SUBSTITUTE SHEET (RULE 26)

14/28

FIG. 19

SUBSTITUTE SHEET (RULE 26)

15/28




FIG. 20

SUBSTITUTE SHEET (RULE 26)

16/28




FIG. 21

SUBSTITUTE SHEET (RULE 26)

17/28

Alerts for SY510SA SUP v5.8.987 (ID 1008289903)	
Alert Level:	<input type="checkbox"/> WARN, <input checked="" type="checkbox"/> ERROR, <input type="checkbox"/> FATAL
	<input type="checkbox"/> Text
<input type="checkbox"/> WARN	App will be deployed immediately after all approvals are in
<input checked="" type="checkbox"/> FATAL	App is being deployed with NO testing in UA environment
<input type="checkbox"/> WARN	App will be deployed immediately after all approvals are in
<input checked="" type="checkbox"/> FATAL	App is being deployed with NO testing in UA environment
Date:	11/30/10 <input type="button" value="q"/> <input type="button" value="30"/> <input type="button" value="▼"/>
<input type="button" value="Go"/> Additional Info	
[<] [>]	
<input type="button" value="Accept"/> <input type="button" value="Decline"/>	
Displaying 1 - 4 of 4	
118*	
2202 2204	

FIG. 22

SUBSTITUTE SHEET (RULE 26)




FIG. 23A

SUBSTITUTE SHEET (RULE 26)

19/28

#	RULE	SEVERITY	ALERT
1	EFFECTIVE DATE IS IN THE PAST	WARN	APP WILL BE DEPLOYED IMMEDIATELY AFTER ALL APPROVALS ARE IN PLACE WHICH COULD RESULT IN APP BEING DOWN DURING BUSINESS HOURS
2	EFFECTIVE DATE DURING BUSINESS HOURS	FATAL	APP WILL BE DEPLOYED DURING BUSINESS HOURS RESULTING IN DOWNTIME DURING BUSINESS
3	EFFECTIVE DATE DURING MORATORIUM	FATAL	APP WILL BE DEPLOYED DURING MORATORIUM AND HENCE REQUIRE ADDITIONAL APPROVALS
4	EFFECTIVE DATE IS TWO WEEKS AWAY	WARN	APP WILL NOT BE DEPLOYED WITHIN TWO WEEKS
5	APP IMAGE WAS DECLINED BEFORE DUE TO BUGS	WARN	APP IMAGE MIGHT HAVE BUGS. THE IMAGE ASSOCIATED WITH THE APP WAS DECLINED IN THE PAST DUE TO BUGS
6	APP IMAGE WAS NEVER DEPLOYED IN UA	FATAL	APP IS BEING DEPLOYED WITH NO TESTING IN UA ENVIRONMENT
7	APP IMAGE WAS ONLY DEPLOYED IN UA FORN HOURS (WHERE N < 24)	WARN	APP IS BEING DEPLOYED WITHOUT SUFFICIENT TESTING
8	APP IMAGE SHOULD CONTAIN ONLY AUTHORIZED THIRD-PARTY LIBRARIES	FATAL	UNAUTHORIZED THIRD-PARTY LIBRARY FOUND IN IMAGE ASSOCIATED WITH THE APP
9	APP IMAGE SHOULD NOT CONTAIN ANY LIBRARIES THAT ARE PART OF THE STACK	FATAL	DUPLICATE LIBRARY FOUND IN IMAGE ASSOCIATED WITH THE APP
10	APP IMAGE BUILD SHOULD NOT HAVE SECURITY VIOLATIONS DURING STATIC ANALYSIS	FATAL	SECURITY VIOLATIONS FOUND IN IMAGE ASSOCIATED WITH THE APP

FIG. 23B

SUBSTITUTE SHEET (RULE 26)

20/28

2400

2401

2402

2406

2408

2410

2412

2414

2416

2418

2420

2422

2424

2426

2428

2430

2432

2434

2436

2438

2440

2442

2444

2446

2448

2450

2452

2454

2456

2458

2460

2462

2464

2466

2468

2470

2472

2474

2476

2478

2480

2482

2484

2486

2488

2490

2492

2494

2496

2498

2500

2502

2504

2506

2508

2510

2512

2514

2516

2518

2520

2522

2524

2526

2528

2530

2532

2534

2536

2538

2540

2542

2544

2546

2548

2550

2552

2554

2556

2558

2560

2562

2564

2566

2568

2570

2572

2574

2576

2578

2580

2582

2584

2586

2588

2590

2592

2594

2596

2598

2600

2602

2604

2606

2608

2610

2612

2614

2616

2618

2620

2622

2624

2626

2628

2630

2632

2634

2636

2638

2640

2642

2644

2646

2648

2650

2652

2654

2656

2658

2660

2662

2664

2666

2668

2670

2672

2674

2676

2678

2680

2682

2684

2686

2688

2690

2692

2694

2696

2698

2700

2702

2704

2706

2708

2710

2712

2714

2716

2718

2720

2722

2724

2726

2728

2730

2732

2734

2736

2738

2740

2742

2744

2746

2748

2750

2752

2754

2756

2758

2760

2762

2764

2766

2768

2770

2772

2774

2776

2778

2780

2782

2784

2786

2788

2790

2792

2794

2796

2798

2800

2802

2804

2806

2808

2810

2812

2814

2816

2818

2820

2822

2824

2826

2828

2830

2832

2834

2836

2838

2840

2842

2844

2846

2848

2850

2852

2854

2856

2858

2860

2862

2864

2866

2868

2870

2872

2874

2876

2878

2880

2882

2884

2886

2888

2890

2892

2894

2896

2898

2900

2902

2904

2906

2908

2910

2912

2914

2916

2918

2920

2922

2924

2926

2928

2930

2932

2934

2936

2938

2940

2942

2944

2946

2948

2950

2952

2954

2956

2958

2960

2962

2964

2966

2968

2970

2972

2974

2976

2978

2980

2982

2984

2986

2988

2990

2992

2994

2996

2998

3000

3002

3004

3006

3008

3010

3012

3014

3016

3018

3020

3022

3024

3026

3028

3030

3032

3034

3036

3038

3040

3042

3044

3046

3048

3050

3052

3054

3056

3058

3060

3062

3064

3066

3068

3070

3072

3074

3076

3078

3080

3082

3084

3086

3088

3090

3092

3094

3096

3098

3100

3102

3104

3106

3108

3110

3112

3114

3116

3118

3120

3122

3124

3126

3128

3130

3132

3134

3136

3138

3140

3142

3144

3146

3148

3150

3152

3154

3156

3158

3160

3162

3164

3166

3168

3170

3172

3174

3176

3178

3180

3182

3184

3186

3188

3190

3192

3194

3196

3198

3200

3202

3204

3206

3208

3210

3212

3214

3216

3218

3220

3222

3224

3226

3228

3230

3232

3234

3236

3238

3240

3242

3244

3246

3248

3250

3252

3254

3256

3258

3260

3262

3264

3266

3268

3270

3272

3274

3276

3278

3280

3282

3284

3286

3288

3290

3292

3294

3296

3298

3300

3302

3304

3306

3308

3310

3312

3314

3316

3318

3320

3322

3324

3326

3328

3330

3332

3334

3336

3338

3340

3342

3344

3346

3348

3350

3352

3354

3356

3358

3360

3362

3364

3366

3368

3370

3372

3374

3376

3378

3380

3382

3384

3386

3388

3390

3392

3394

3396

3398

3400

3402

3404

3406

3408

3410

3412

3414

3416

3418

3420

3422

3424

3426

3428

3430

3432

3434

3436

3438

3440

3442

3444

3446

3448

3450

3452

3454

3456

3458

3460

3462

3464

3466

3468

3470

3472

3474

3476

3478

3480

3482

3484

3486

3488

3490

3492

3494

3496

3498

3500

3502

3504

3506

3508

3510

3512

3514

3516

3518

3520

3522

3524

3526

3528

3530

3532

3534

3536

3538

3540

3542

3544

3546

3548

3550

3552

3554

3556

3558

3560

3562

3564

3566

3568

3570

3572

3574

3576

3578

3580

3582

3584

3586

3588

3590

3592

3594

3596

3598

3600

3602

3604

3606

3608

3610

3612

3614

3616

3618

3620

3622

3624

3626

3628

3630

3632

3634

3636

3638

3640

3642

3644

3646

3648

3650

3652

3654

3656

3658

3660

3662

3664

3666

3668

3670

3672

3674

3676

3678

3680

3682

3684

3686

3688

3690

3692

3694

3696

3698

3700

3702

3704

3706

3708

3710

3712

3714

3716

3718

3720

3722

3724

3726

3728

3730

3732

3734

3736

3738

3740

3742

3744

3746

3748

3750

3752

3754

3756

3758

3760

3762

3764

3766

3768

3770

3772

3774

3776

3778

3780

3782

3784

3786

3788

3790

3792

3794

3796

3798

3800

3802

3804

3806

3808

3810

3812

3814

3816

3818

3820

3822

3824

3826

3828

3830

3832

3834

3836

3838

3840

3842

3844

3846

3848

3850

3852

3854

3856

3858

3860

3862

3864

3866

3868

3870

3872

3874

3876

3878

3880

3882

3884

3886

3888

3890

3892

3894

3896

3898

3900

3902

3904

3906

3908

3910

3912

3914

3916

3918

3920

3922

3924

3926

3928

3930

3932

3934

3936

3938

3940

3942

3944

3946

3948

3950

3952

3954

3956

3958

3960

3962

3964

3966

3968

3970

3972

3974

3976

3978

3980

3982

3984

3986

3988

3990

3992

3994

3996

3998

4000

4002

4004

4006

4008

4010

4012

4014

4016

4018

4020

4022

4024

4026

4028

4030

4032

4034

4036

4038

4040

4042

4044

4046

4048

4050

4052

4054

4056

4058

4060

4062

4064

4066

4068

4070

4072

4074

4076

4078

4080

4082

4084

4086

4088

4090

4092

4094

4096

4098

4100

4102

4104

4106

4108

4110

4112

4114

4116

4118

4120

4122

4124

4126

4128

4130

4132

4134

4136

4138

4140

4142

4144

4146

4148

4150

4152

4154

4156

4158

4160

4162

4164

4166

4168

4170

4172

4174

4176

4178

4180

4182

4184

4186

4188

4190

4192

4194

4196

4198

4200

4202

4204

4206

4208

4210

4212

4214

4216

4218

4220

4222

4224

4226

4228

4230

4232

4234

4236

4238

4240

4242

4244

4246

4248

4250

4252

4254

4256

4258

4260

4262

4264

4266

4268

4270

4272

4274

4276

4278

4280

4282

4284

4286

4288

4290

4292

4294

4296

4298

4300

4302

4304

4306

4308

4310

4312

4314

4316

4318

4320

4322

4324

4326

4328

4330

4332

4334

4336

4338

4340

4342

4344

4346

4348

4350

4352

4354

4356

4358

4360

4362

4364

4366

4368

4370

4372

4374

4376

4378

4380

4382

4384

4386

4388

4390

4392

4394

4396

4398

4400

4402

4404

4406

4408

4410

4412

4414

4416

4418

4420

4422

4424

4426

4428

4430

4432

4434

4436

4438

4440

4442

4444

4446

4448

4450

4452

4454

4456

4458

4460

4462

4464

4466

4468

4470

4472

4474

4476

4478

4480

4482

4484

4486

4488

4490

4492

4494

4496

4498

4500

4502

4504

4506

4508

4510

4512

4514

4516

4518

4520

4522

4524

4526

4528

4530

4532

4534

4536

4538

4540

4542

4544

4546

4548

4550

4552

4554

4556

4558

4560

4562

4564

4566

4568

4570

4572

4574

4576

4578

4580

4582

4584

4586

4588

4590

4592

4594

4596

4598

4600

4602

4604

4606

4608

4610

4612

4614

4616

4618

4620

4622

4624

4626

4628

4630

4632

4634

4636

4638

4640

4642

4644

4646

4648

4650

4652

4654

4656

4658

4660

4662

4664

4666

4668

4670

4672

4674

4676

4678

4680

4682

4684

4686

4688

4690

4692

4694

4696

4698

4700

4702

4704

4706

4708

4710

4712

4714

4716

4718

4720

4722

4724

4726

4728

4730

4732

4734

4736

4738

4740

4742

4744

4746

4748

4750

4752

4754

4756

4758

4760

4762

4764

4766

4768

4770

4772

4774

4776

4778

4780

4782

4784

4786

4788

4790

4792

4794

4796

4798

4800

4802

4804

4806

4808

4810

4812

4814

4816

4818

4820

4822

4824

4826

4828

4830

4832

4834

4836

4838

4840

4842

4844

4846

4848

4850

4852

4854

4856

4858

4860

4862

4864

4866

4868

4870

4872

4874

4876

4878

4880

21/28





FIG. 25

SUBSTITUTE SHEET (RULE 26)

22/28



EIG 26

SUBSTITUTE SHEET (RULE 26)

23/28





FIG. 27

SUBSTITUTE SHEET (RULE 26)

24/28



EIG. 28

SUBSTITUTE SHEET (RULE 26)

25/28




FIG. 29

SUBSTITUTE SHEET (RULE 26)




FIG. 30.

SUBSTITUTE SHEET (RULE 26)




FIG. 31

SUBSTITUTE SHEET (RULE 26)

28/28




FIG. 32

SUBSTITUTE SHEET (RULE 26)

