

Australia

Patents act 1990

NOTICE OF ENTITLEMENT

Australian Application
No. 13033/97

I, Albertus Wilhelmus Joannes ZEESTRATEN
of Carel van Bylandtlaan 30, 2596 HR The Hague, the Netherlands

being authorised by the Applicant(s)/Nominated Person(s) in respect of an application entitled:

FLAMELESS COMBUSTOR

state the following:-

1. The Applicant(s)/Nominated Person(s) has/have, for the following reasons, gained entitlement from the actual inventor(s):-

By virtue of an agreement between the Applicant/Nominated Person and the assignee of the actual inventor(s)

~~2a.* The Applicant(s)/Nominated Person(s) is/are the applicant(s) of the basic application(s) listed* on the Patent Request/* in the Declaration under Article 8 of the PCT.~~

- 2b.* The Applicant(s)/Nominated Person(s) is/are entitled to rely on the basic application(s) listed* on the Patent Request/* in the Declaration under Article 8 of the PCT as follows:

By virtue of an agreement between the Applicant/Nominated Person and the assignee of the basic applicant(s).

- 3.* The basic application(s) listed *on the Patent Request/ *in the Declaration under Article 8 of the PCT is/are the application(s) first made in a Convention Country in respect of the invention.

~~4a.* The Applicant(s)/Nominated Person(s) is/are the depositor(s) of the deposit(s) listed in the Schedule hereto.~~

~~4b.* The Applicant(s)/Nominated Person(s) has/have the consent of _____ of~~

~~_____ the depositor(s) of the deposit(s) listed in the Schedule hereto, to rely on that/those deposit(s).~~

DATED this 29th day of May 1998

(Signature)

Albertus Wilhelmus Joannes ZEESTRATEN

(Name & Title) (special proxy)

* Delete if not applicable.



AU9713033

(12) PATENT ABRIDGMENT (11) Document No. AU-B-13033/97
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 696743

- (54) Title
FLAMELESS COMBUSTOR
- International Patent Classification(s)
(51)⁶ **E21B 036/02**
- (21) Application No. : **13033/97** (22) Application Date : **17.12.96**
- (87) PCT Publication Number : **WO97/24509**
- (30) Priority Data
- | | | |
|---------------|-----------------|------------------------------------|
| (31) Number | (32) Date | (33) Country |
| 009345 | 27.12.95 | US UNITED STATES OF AMERICA |
- (43) Publication Date : **28.07.97**
- (44) Publication Date of Accepted Applcation : **17.09.98**
- (71) Applicant(s)
SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.
- (72) Inventor(s)
THOMAS MIKUS; JOHN MICHAEL KARANIKAS; HAROLD J. VINEGAR; SCOTT LEE WELLINGTON
- (74) Attorney or Agent
SPRUSON & FERGUSON , GPO Box 3898, SYDNEY NSW 2001
- (56) Prior Art Documents
US 5404952
US 4445570
- (57) Claim

1. A flameless combustor comprising:

- an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;
- a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices located along the fuel conduit, each of the orifices separated by an interval distance wherein the oxidant can pass through the combustion chamber and mix with fuel passing through the orifices from the fuel volume as the oxidant passes from the inlet end to the combustion product outlet;
- a catalytic surface located within the axial combustion chamber, the catalytic surface effective to reduce the autoignition temperature of a mixture of fuel and oxidant from a noncatalysed autoignition temperature to a catalysed autoignition temperature; and
- electrical heating means for ignition of the mixture of oxidant and fuel within the axial combustion chamber;

characterised in that the electrical heating means comprise an electrical power supply effective to pass electrical current through the fuel conduit in an amount effective to heat the fuel conduit in the vicinity of at least one orifice to a temperature above a temperature at which the fuel will ignite when the fuel passes through the orifices.

10. A flameless combustor comprising:

an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;

a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices along the fuel conduit wherein the fuel conduit comprises an electrically conductive material; and

electrical heating means for ignition of the mixture of oxidant and fuel within the axial combustion chamber;

characterised in that the electrical heating means comprise an electrical power supply effective to pass electrical current through the fuel conduit in an amount effective to heat the fuel conduit in the vicinity of at least one orifice to a temperature above a temperature at which the fuel will ignite when the fuel passes through the orifices.

13. A method to ignite a flameless combustor comprising:

providing an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;

providing a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices located along the fuel conduit;

passing an oxidant to the combustion chamber;

passing a stream of fuel to the fuel volume; and

heating the stream of fuel, oxidant, or both the stream of fuel and oxidant to a temperature that results in reaction of the oxidant and the fuel when fuel combines with the oxidant;

characterised in that the oxidant is selected from the group comprising nitrous oxide and supplemental oxygen and that the method further comprises:

continuing to pass the oxidant to the combustion chamber and fuel to the fuel conduit until the temperature within the combustion chamber exceeds an autoignition temperature of the fuel in air; and

replacing the oxidant with air after the temperature within the combustion chamber exceeds the autoignition temperature of the fuel in air.

OPI DATE 28/07/97 APPLN. ID 13033/97
AOJP DATE 18/09/97 PCT NUMBER PCT/EP96/05753



IN

AU9713033

(51) International Patent Classification 6 :

E21B 36/02

A1

(11) International Publication Number:

WO 97/24509

(43) International Publication Date:

10 July 1997 (10.07.97)

(21) International Application Number: PCT/EP96/05753

(22) International Filing Date: 17 December 1996 (17.12.96)

(30) Priority Data:

60/009,345

27 December 1995 (27.12.95)

US

(71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA).

(72) Inventors: KARANIKAS, John, Michael; 4655 Wild Indigo, No. 302, Houston, TX 77027 (US). MIKUS, Thomas; 906 Coachlight Drive, Houston, TX 77077 (US). VINEGAR, Harold, J.; 5219 Yarwell, Houston, TX 77096 (US). WELLINGTON, Scott, Lee; 2111 Shadybar Drive, Houston, TX 77077 (US).

(81) Designated States: AL, AU, BB, BG, BR, CA, CN, CU, CZ, EE, FI, GE, HU, IL, IS, JP, KE, KP, KR, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SD, SG, SI, SK, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

With international search report.

(54) Title: FLAMELESS COMBUSTOR

(57) Abstract

A combustor method and apparatus is provided. The method utilizes flameless combustion with one or more of three improvements to enhance ignition of the flameless combustor. A catalytic surface can be provided within a combustion chamber to provide flameless combustion at least in the vicinity of the catalytic surface at a temperature that is much lower than the autoignition temperature of fuel in air without the presence of the catalytic surface. Nitrous oxide or supplemental oxygen may also be used as an oxidant either instead of air or with air to reduce ignition temperatures. Further, electrical energy can be passed through the fuel conduit, raising the temperature of the conduit to a temperature above which the fuel will ignite when combined with the oxidant.



FLAMELESS COMBUSTOR

This invention relates to a combustor apparatus and method.

U.S. Patent Nos. 4,640,352 and 4,886,118 disclose conductive heating of subterranean formations of low permeability that contain oil to recover oil therefrom. Low permeability formations include diatomites, lipid coals, tar sands, and oil shales. Formations of low permeability are not amiable to enhanced oil recovery methods such as steam, carbon dioxide, or fire flooding. Flooding materials tend to penetrate formations that have low permeabilities preferentially through fractures. The injected materials bypass most of the formation hydrocarbons. In contrast, conductive heating does not require fluid transport into the formation. Oil within the formation is therefore not bypassed as in a flooding process. When the temperature of a formation is increased by conductive heating, vertical temperature profiles will tend to be relatively uniform because formations generally have relatively uniform thermal conductivities and specific heats. Transportation of hydrocarbons in a thermal conduction process is by pressure drive, vaporization, and thermal expansion of oil and water trapped within the pores of the formation rock. Hydrocarbons migrate through small fractures created by thermal stress and by the expansion and vaporization of the oil and water.

U.S. Patent Nos. 3,113,623 and 3,181,613 disclose gas fired heat injection burners for heating subterranean formations. These burners utilize porous materials to hold a flame and thereby spreading the flame out over an extended length. Radiant heat transfer from a flame to

- 2 -

the casing is avoided by providing the porous medium to hold the flame. But for combustion to take place in the porous medium, the fuel gas and the combustion air must be premixed. If the premixed fuel gas and combustion air were at a temperature above the autoignition temperature of the mixture, they would react upon being premixed instead of within the porous medium. The formations utilized as examples of these inventions are only up to about 15 m thick and below only about 4.5 m of overburden. The fuel gas and the combustion air are therefore relatively cool when they reach the burner. The burner would not function as it was intended if the formation being heated were significantly deeper.

U.S. Patent No. 5,255,742 discloses a flameless combustor useful for heating subterranean formations that utilizes preheated fuel gas and/or combustion air wherein the fuel gas is combined with the combustion air in increments that are sufficiently small that flames are avoided. Creation of NO_x is almost eliminated, and cost of the heaters can be significantly reduced because of less expensive materials of construction. Preheating the fuel gas in accordance with the teachings of this prior art reference results in coke formation unless CO_2 , H_2 , steam, or some other coke suppressant is added to the fuel gas. Further, start-up of this known heater is a time consuming process because it must operate at temperatures above the autoignition temperature of the fuel gas mixture. Start-up requires long periods of very low flow-rate operation before temperatures would be sufficiently high for normal operation.

Catalytic combustors are also known. For example, U.S. Patent No. 3,928,961 discloses a catalytically-supported thermal combustion apparatus wherein formation of NO_x is eliminated by combustion at temperatures above auto-ignition temperatures of the fuel, but less than

those temperatures at which result in substantial formation of oxides of nitrogen.

5 Metal coated surfaces coated with oxidation catalyst are disclosed in, for example, U.S. Patent Nos. 5,355,668 and 4,065,917. These patents suggests catalytic coated surfaces on components of a gas turbine engine. Said U.S. Patent 4,065,917 suggests use of catalytic coated surfaces for start-up of the turbine, and suggests a mass transfer control limited phase in the start-up operation.

10 A flameless combustor and ignition method in accordance with the preamble of claims 1, 10 and 13 is known from US Patent 5,404,952. In the known combustor and ignition method coiled electrical resistor wires are suspended within the combustion chamber at a distance
15 away from the orifices, which may retard and complicate ignition.

It is therefore an object of the present invention to provide a combustion method and apparatus which is flameless, and can be easily ignited and brought up to
20 operating temperatures. In another aspect of the present invention, it is an object to provide a combustion method and apparatus wherein formation of NO_x is minimal. It is another object of the present invention to provide a method which has a high level of thermal efficiency.

25 In accordance with one aspect of the present invention a flameless combustor comprises:

an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;

30 a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of



orifices located along the fuel conduit, each of the orifices separated by an interval distance wherein the oxidant can pass through the combustion chamber and mix with fuel passing through the orifices from the fuel volume as the oxidant passes from the inlet end to the combustion product outlet;

a catalytic surface located within the axial combustion chamber, the catalytic surface effective to reduce the autoignition temperature of a mixture of fuel and oxidant from a non-catalyzed autoignition temperature to a catalyzed autoignition temperature; and

an electrical power supply effective to pass electrical current through the fuel conduit in an amount effective to heat the fuel conduit in the vicinity of at least one orifice to temperature above a temperature at which the fuel will ignite when the fuel passes through the orifices.

Preferably the catalytic surface comprises an outer surface of the fuel conduit and/or an inner surface of the combustion chamber. It is also preferred that the catalytic surface comprises palladium.

In accordance with another aspect of the present invention a flameless combustor comprises:

an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;

a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices along the fuel conduit wherein the fuel conduit comprises an electrically conductive material; and



AMENDED SHEET
12/2/83

5 an electrical power supply effective to pass
electrical current through the fuel conduit in an amount
effective to heat the fuel conduit in the vicinity of at
least one orifice to temperature above a temperature at
which the fuel will ignite when the fuel passes through
the orifices.

10 Suitably the combustor is located within an
underground wellbore and the fuel conduit is a tubular
suspended from a wellhead; electrical power is applied at
the wellhead; the fuel conduit is of a lesser thickness
in the vicinity of the orifices than above the orifices;

MCS15/TH0601PC2



AMENDED SHEET
IPE/EP

- 5 -

and the fuel conduit is grounded from a point below at least one orifice.

The invention further relates to a method to ignite a flameless combustor. The method comprises:

5 providing an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;

10 providing a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices located along the fuel conduit;

15 passing an oxidant selected from the group comprising nitrous oxide and supplemental oxygen to the combustion chamber;

passing a stream of fuel to the fuel volume;

20 heating the stream of fuel, oxidant, or both the stream of fuel and oxidant to a temperature that results in reaction of the oxidant and the fuel when fuel combines with the oxidant;

25 continuing to pass the oxidant to the combustion chamber and fuel to the fuel conduit until the temperature within the combustion chamber exceeds an autoignition temperature of the fuel in air; and

replacing the oxidant with air after the temperature within the combustion chamber exceeds the autoignition temperature of the fuel in air.

30 Suitably, the method according to the invention further comprises the step of passing an amount of electricity through the fuel conduit sufficient to cause the fuel conduit, for at least a portion of the conduit in the vicinity of at least one orifice, to heat to a temperature of at least 260 °C.

- 6 -

It is preferred that the method according to the invention further comprises the step of providing a catalytic surface within the combustion chamber, the catalytic surface effective to reduce the temperature at which the fuel and oxidant react in the vicinity of the catalytic surface.

Suitable fuels for use during the start-up phase of the method according to the present invention are hydrogen and a hydrogen and carbon monoxide mixture, which fuels have a low ignition temperature.

The flameless combustion method and combustor of the present invention result in minimal production of nitrous oxides. Other measures to remove or prevent the formation of nitrous oxides are therefore not required.

The invention will now be described in more detail with reference to the accompanying drawings, in which

FIG. 1 shows a combustor suitable for use in the present invention.

FIG. 2 is a plot of amount of fuel consumed in a burner that demonstrates workability of the present invention vs. temperature.

A flameless combustor that can be utilized, with improvement according to the present invention is disclosed in U.S. Patent No. 5,255,742, the disclosure of which is incorporated herein by reference. The improvements of the present invention include three improvements related to the start-up of such a combustor. The three improvements may be used individually, but are preferably used in combination with at least two utilized. The three improvements of the present invention include: use of the fuel gas conduit as a resistance heater to provide heat for start-up; use of a catalytic surface within the combustion chamber to lower temperatures at which oxidation of the fuel will occur;

- 7 -

and use of oxidants other than air, or along with air, to lower autoignition temperatures during start-up.

An important feature of the flameless combustor of the present invention is that heat is removed along the axis of the combustion chamber so that a temperature is maintained that is significantly below what an adiabatic combustion temperature would be. This almost eliminates formation of NO_x s, and also significantly reduces metallurgical requirements resulting in a relatively inexpensive combustor.

Generally, flameless combustion is accomplished by preheating combustion air and fuel gas sufficiently that when the two streams are combined the temperature of the mixture exceeds the autoignition temperature of the mixture, but to a temperature less than that which would result in the oxidation upon mixing being limited by the rate of mixing. Preheating of the streams to a temperature between about 815 °C and about 1260 °C and then mixing the fuel gas into the combustion air in relatively small increments will result in flameless combustion. The increments in which the fuel gas is mixed with the combustion gas stream preferably result in about a 10 to 110 °C temperature rise in the combustion gas stream due to the combustion of the fuel.

Referring to FIG. 1, a heat injection well and combustor capable of carrying out the present invention are shown. A formation to be heated, 1, is below an overburden, 2. A wellbore, 3, extends through the overburden and to a position in or near the bottom of the formation to be heated. A vertical well is shown, but the wellbore could be deviated or horizontal. Horizontal heat injector wells may be provided in formations that fracture horizontally to recover hydrocarbons by a parallel drive process. Shallow oil shale formations are examples of such formations. Horizontal heaters may also

- 8 -

effectively be used in thin beds to limit heat loss to overburden and base rock. In the embodiment shown in FIG. 1, the wellbore is cased with a casing, 4. The lower portion of the wellbore may be cemented with a cement, 7, having characteristics suitable for withstanding elevated temperatures and transferring heat. A cement which is a good thermal insulator, 8, is preferred for the upper portion of the wellbore to prevent heat loss from the system. An oxidant conduit, 10, extends from the wellhead (not shown) to the lower portion of the wellbore. A fuel conduit, 12, also extends from the wellhead to the bottom of the wellbore. The fuel conduit defines a fuel volume within the fuel conduit. The fuel volume is in communication with a fuel supply, and is in communication with a combustion chamber surrounding the fuel conduit through a plurality of orifices.

High temperature cements suitable for cementing casing and conduits within the high temperature portions of the wellbore are available. Examples are disclosed in U.S. Patent Nos. 3,507,332 and 3,180,748. Alumina contents above about 50 percent by weight based on cements slurry solids are preferred.

In shallow formations, it may be advantageous to hammer-drill the heater directly into the formation. When the heater is hammer-drilled directly into the formation, cementing of the heater in the formation is not required, but an upper portion of the heater may be cemented to prevent fluid loss to the surface.

Choice of a diameter of the casing, 4, in the embodiment of FIG. 1 is a trade off between the expense of the casing, and the rate at which heat may be transferred into the formation. The casing, due to the metallurgy required, is generally the most expensive component of the injection well. The heat that can be

- 9 -

transferred into the formation increases significantly with increasing casing diameter. A casing of between about 10 and about 20 cm in internal diameter will typically provide an optimum trade-off between initial cost and heat transfer.

The fuel gas conduit contains a plurality of orifices, 13, (eight shown) along the length of the conduit within the formation to be heated. The orifices are separated by an interval distance that is sufficient to allow both significant reaction of the oxidant and fuel between orifices, and removal of heat from the heater along the length of the combustion chamber between the orifices. The orifices 13 provide communication between the volume defined by the fuel conduit 12 and the axial combustion chamber. A plurality of orifices provide for distribution of heat release within the formation to be heated. Staging release of fuel into the oxidant/combustion product stream results in staged generation of heat, and with uniform transfer of heat from the wellbore as in the embodiment of FIG. 1, temperatures within the wellbore are well below adiabatic combustion temperatures. Avoiding high temperatures significantly reduces metallurgical requirements, and thus cost of the facility. Additionally, temperatures well below adiabatic combustion temperatures avoids creation of NO_xs.

The orifices are sized to accomplish a nearly even temperature distribution within the casing. A nearly even temperature profile within the casing results in more uniform heat distribution within the formation to be heated. A nearly uniform heat distribution within the formation will result in more efficient utilization of heat in a conductive heating hydrocarbon recovery process. A more even temperature profile will also result in lower maximum temperatures for the same heat

- 10 -

release. Because the materials of construction of the burner and well system dictate the maximum temperatures, even temperature profiles will increase the heat release possible for the same materials of construction. The number of orifices is limited only by size of orifices which are to be used. If more orifices are used, they must generally be of a smaller size. Smaller orifices will plug more easily than larger orifices. The number of orifices is a trade-off between evenness of the temperature profile and the possibility of plugging.

The number, size, and spacing of the orifices along with the heat removal from the combustion chamber are preferably such that the maximum temperatures within the combustor are less than about 1100 °C. This results in long service lives for commercially available materials.

It is important in the operation of a combustor of the present invention that heat be removed from the combustion chamber between fuel orifices. In the application of the present invention to a wellbore heat injector, heat is transferred to the formation around the wellbore. The heater of the present invention could also be used in other applications, such as steam generation and chemical industry or refinery process heaters.

Alternatively, air and/or another oxidant could be staged into fuel by providing orifices in the combustion air conduit instead of the fuel conduit.

Fuel and oxidant transported to bottom of the wellbore combine and react within the wellbore volume surrounding the conduits, 14, forming combustion products. This volume is the axial combustion chamber of the present invention. The combustion products travel up the wellbore and out an exhaust vent at the wellhead. The combustion products may be treated to remove pollutants, and energy recovery from the combustion

- 11 -

products by an expander turbine or heat exchanger may also be desirable.

As the combustion products rise in the wellbore above the formation being heated, heat is exchanged between the oxidant and the fuel travelling down the flow conduits and the combustion products. This heat exchange not only conserves energy, but permits the desirable flameless combustion of the present invention. The fuel and the oxidant are preheated as they travel down the respective flow conduits sufficiently that the mixture of the two streams at the ultimate mixing point is at a temperature above the autoignition temperature of the mixture.

Flameless combustion results, avoiding a flame as a radiant heat source. Heat is therefore transferred from the wellbore in an essentially uniform fashion.

An electrical lead 15 can be connected with a clamp 16 or other connection to the fuel line 12 near the wellhead below an electrically insulating coupling to supply electrical energy for initial heating and start-up of the combustor. Electrical ground can be provided near the bottom of the borehole with one or more electrically conducting centralizers around the fuel conduit 17 and around the oxidant conduit 18. Centralizers on the fuel conduit above the electrically grounding centralizers are electrically insulating centralizers. Wall thickness of the fuel conduits are preferably decreased in the vicinity of the orifices so that application of electrical energy to the fuel gas conduit results in negligible resistance heating above the orifices, and significant heating below the orifices. Sufficient heat is preferably applied to result in fuel exiting the orifices into a flowing oxidant (or air) stream being is at or above the autoignition temperature of the fuel-oxidant mixture as the fuel mixes with the oxidant. Most preferably, the mixture of fuel and oxidant is above

- 12 -

the autoignition temperature of the mixture at these start-up conditions. Thus, the fuel would ignite when it passes through the orifices and mixe with oxidant between orifices.

5 Autoignition temperature of the fuel-oxidant mixture is preferably lowered by provision of a catalytic surface 19 in the vicinity of the orifices. This catalytic surface is preferably provided on the inside surface of the oxidant conduit 10. Alternatively, either the fuel 10 conduit could be provided with such a surface, or a tubular or catalyst containing surface could be separately placed within the oxidant conduit. Other catalytic surfaces could be provided, for example in the combustion product annulus outside of the oxidant 15 conduit. This additional catalytic surface could ensure that complete combustion occurred within the wellbore. The catalytic surface can also significantly increase the temperature range within which the combustor can operate by decreasing the temperature at which oxidation of the 20 fuel occurs.

Start up of the flameless combustor of the present invention can be further enhanced by provision of supplemental oxidants during the start-up phase, and/or by use of a fuel that has a lower autoignition 25 temperature such as, for example, hydrogen. Preferred oxidants include supplemental oxygen and nitrous oxide. Hydrogen could be provided along with a natural gas stream, and could be provided as shift gas, with carbon monoxide present and/or carbon dioxide present. Presence 30 of carbon dioxide would not be preferably, but may be tolerable and removal of some carbon dioxide may not be economically justifiable.

Acceptable catalyst materials include noble metals, semi-precious metals, and transition metal oxides. 35 Generally, known oxidation catalysts are useful in the

- 13 -

present invention. Mixtures of such metals or metal oxides could also be useful.

5 Start-up oxidants and/or fuels are preferably only used until the combustor has been heated to a temperature sufficient to enable operation with methane (natural gas) as fuel and air as the oxidant (i.e., the combustor has heated to a temperature above the autoignition temperature of methane in air).

10 The preheating of fuel gases such as methane to obtain flameless combustion could result in significant generation of carbon within the fuel conduit unless a carbon formation suppressant is included in the fuel stream. The carbon formation suppressant may be carbon dioxide, steam, hydrogen or mixtures thereof. Carbon
15 dioxide and steam are preferred due to the generally higher cost of hydrogen.

Flameless combustion generally occurs when a reaction between an oxidant stream and a fuel is not limited by mixing and the mixed stream is at a temperature higher
20 than the autoignition temperature of the mixed stream. This is accomplished by avoiding high temperatures at the point of mixing and by mixing relatively small increments of fuel into the oxidant containing stream. The existence of flame is evidenced by an illuminate
25 interface between unburned fuel and the combustion products. To avoid the creation of a flame, the fuel and the oxidant are preferably heated to a temperature of between about 815 °C and about 1260 °C prior to mixing. The fuel is preferably mixed with the oxidant stream in
30 relatively small increments to enable more rapid mixing. For example, enough fuel may be added in an increment to enable combustion to raise the temperature of the stream by about 28 to about 56 °C.

35 Use of the fuel conduit as a resistance heater to provide initial heat for start up of the flameless

- 14 -

combustor of the present invention is a significant improvement because the fuel conduit is present anyway, will generally be made of an electrically conductive material, and being a relatively thick metal, would be expected to be a reliable heater. Thickness of the fuel conduit can be varied to result in release of heat at preselected segments of the length of the fuel conduit. For example, in a well heat injector application, it may be desirable to electrically heat the lowermost portion of the wellbore in order to ignite the mixed gas stream at the highest concentration of fuel, and to burn the fuel before exhaust gasses are passed back up through the wellbore. Electrical energy can be connected to the fuel conduit at the wellhead, and the fuel conduit supported by an insulating hanger, and kept centralized within the air supply conduit with insulating centralizers. The fuel conduit is then grounded below the segment which is to be used as a heater.

Catalytic metals such as palladium or platinum can be coated, preferably by brush electroplating, onto a surface within the combustion chamber to enhance oxidation of the fuel at lower temperatures. Such catalytic surface has been found to be extremely effective in promoting oxidation of methane in air at temperatures as low as 260 °C. This reaction rapidly occurs on the catalyst surface, and generally, gasses in the boundary layer adjacent to the catalytic surface quickly become fully reacted. An advantage of having a significant catalytic surface within the combustion chamber is that the temperature range within which the flameless combustor can operate can be significantly increased.

EXAMPLES

A thermal reactor was used to establish temperatures at which oxidation reactions would occur with various

- 15 -

combinations of fuels, oxidants and catalyst surfaces. The reactor was a 2.54 cm stainless steel pipe wrapped with an electrical resistance heating coil, and covered with insulation. A thermocouple for temperature control was placed underneath the insulation adjacent to the outer surface of the pipe. Thermocouples were also provided inside the pipe at the inlet, at the middle, and at the outlet. Test ribbons of noble metals or stainless steel strips with noble metal coatings were hung in the pipe to test catalytic activity. Air preheated to a temperature somewhat below the desired temperature of the test was injected into the electrically heated test section of the pipe. Electrical power to the electrical resistance heater was varied until the desired temperature in the test section was obtained and a steady state, as measured by the thermocouples mounted inside the pipe, was achieved. Fuel was then injected through a mixing tee into the stream of preheated air and allowed to flow into the electrically heated test section. Four platinum ribbons 0.32 cm wide and about 40 cm long or a stainless steel strip 0.95 cm wide and about 0.16 cm thick and about 40 cm long coated on both sides with either platinum or palladium were suspended within the pipe to test catalytic activity. When the test section contained a catalyst coated strip or ribbon of noble metal and was at or above the catalyzed autoignition temperature, the addition of fuel caused a temperature increase at the inside middle and outlet thermocouples. Below the catalyzed autoignition temperature, such a temperature was not observed. When no catalytic coated strips or noble metal ribbons were present, the test section had to be heated to the autoignition temperature of the fuel before a temperature increase was observed. The non-catalyzed and catalyzed autoignition temperatures as measured are summarized in the TABLE, with the

- 16 -

measured non-catalyzed or catalyzed autoignition temperature referred to as the measured autoignition temperature.

TABLE

FUEL	MEASURED AUTO- IGNITION TEMP. °C	AIR FLOW RATE CC/MIN	FUEL CONC. % OF AIR VOL. %	ACCEL. % OF AIR VOL%	CATALYST
NAT. GAS	788	380	10.5		
NAT. GAS	732	380	2.6	N ₂ O/21	
NAT. GAS	677	380	2.6	O ₂ /40	
DIMETHYL ETHER	510	380	2.6		
DIMETHYL ETHER	316	380	2.6	N ₂ O/21	
H ₂	659	380	13		
H ₂	49	380	13		Pt
66.6%H ₂ 33.3%CO	676	380	13		
66.6%H ₂ 33.3%CO	213	380	13		Pt
66.6%H ₂ 33.3%CO	211	380	13	N ₂ O/44.7	Pt
66.6%H ₂ 33.3%CO	149	0	13	380CC/MIN 100% N ₂ O	Pt
Methane	310	380	13	-	Pd
H ₂	149	380	13	-	Pd
66.6%H ₂ 33.3%CO	154	380	13	-	Pd

5

From the TABLE it can be seen that addition of N₂O to the fuel stream greatly reduces the measured autoignition temperature of the mixtures. Further, inclusion of

- 17 -

hydrogen as a fuel and presence of the catalytic surface also significantly reduces the dynamic auto-ignition temperatures.

A 3.048 m long test combustor was used to test the results of the one inch reactor in a distributed combustor application. A 2.54 cm outer diameter fuel gas line was provided within a 5.08 cm internal diameter combustion line. The fuel injection line provided a conduit for fuel to a fuel injection port located near an inlet end of the combustion line. The combustion line was placed within an insulated pipe, and thermocouples were placed along the fuel supply line. Two different combustion lines were utilized. One combustion line was fabricated from a strip of "HAYNES 120" alloy. The strip was electro brush plated on one side with palladium to an average thickness of 0.000254 cm. The strip was then break formed, swedged and welded in to a 3.048 m long pipe with the palladium coating on the inside surface. The other combustion line was a standard 7.62 cm pipe of "HAYNES 120" alloy. A "MAXON" burner was used to supply combustion gases to the 3.048 m long combustion pipe, and varying amounts of air and/or other additives are mixed with the exhaust from the "MAXON" burner in a mixing section between the burner and the combustion line. To maintain a uniform temperature within the combustion line, three electric heaters, each with its own controller, were placed outside and along the length of the combustion line.

A series of tests were run, one with the palladium coated combustion line and one with the combustion line that was not palladium coated. When measured at a temperature of about 15 °C and at a pressure of 1 atmosphere fuel gas was injected through the fuel gas injection port at a rate of about 0.635 m³/hour and about 374 m³/hour of air was injected, including the burner air

- 18 -

and the secondary air. Enough fuel gas was provided to the burner to provide a target temperature at the inlet of the combustion line. Percentage of the injected methane that was burned is shown as a function of the combustion line inlet temperature in FIG. 2 for catalyzed configuration (line A) and noncatalyzed configuration (line B). From FIG. 2 it can be seen that at the lowest temperatures at which the apparatus can be operated is about 260 °C, 55% of the methane was oxidized with the palladium coated combustion line. The lowest temperature of operation might be somewhat below 260 °C but the equipment available was not capable of operation at lower temperature. When the combustion line without the palladium coating was used, some oxidation of methane occurred at about 704 °C, and oxidation of methane occurs rapidly at temperatures of about 816 °C. At temperatures of 871 °C and above, the presence of the palladium surface has no effect because oxidation of methane is rapid and complete either with or without the palladium surface.

The temperature independence of the methane oxidized below 704 °C tends to verify that the methane within the boundary layer at the surface of the palladium surface oxidizes rapidly, and that transportation of methane to this boundary layer, and not kinetics, dictates the extent to which methane is oxidized. At temperatures of about 704 °C and greater, thermal oxidation becomes prevalent, and a temperature dependence is due to this thermal oxidation.

The claims defining the invention are as follows:

1. A flameless combustor comprising:
 - an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;
 - 5 a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices located along the fuel conduit, each of the orifices separated by an interval distance wherein the oxidant can pass through the combustion chamber and mix with fuel passing through the orifices from the fuel volume as the oxidant passes from the inlet end to the combustion product outlet;
 - 10 a catalytic surface located within the axial combustion chamber, the catalytic surface effective to reduce the autoignition temperature of a mixture of fuel and oxidant from a noncatalysed autoignition temperature to a catalysed autoignition temperature; and
 - 15 electrical heating means for ignition of the mixture of oxidant and fuel within the axial combustion chamber;
 - characterised in that the electrical heating means comprise an electrical power supply effective to pass electrical current through the fuel conduit in an amount effective to heat the fuel conduit in the vicinity of at least one orifice to a temperature above a temperature at which the fuel will ignite when the fuel passes through the orifices.
2. The combustor of claim 1 wherein the catalytic surface comprises an outer surface of the fuel conduit.
3. The combustor of claim 1 wherein the catalytic surface comprises an inner surface of the combustion chamber.
4. The combustor of claim 1 wherein the combustion chamber is defined by an inside surface of a tubular within a wellbore.
5. The combustor of claim 1 further comprising a means to remove heat from the interval of the combustion chamber between at least two orifices, the means to remove heat capable of removing an amount of heat that results in the temperature within the combustion chamber being, when in a steady state, greater than the autoignition temperature of the fuel in air, but less than about 1100°C.
6. The combustor of claim 5 wherein the means to remove heat from an interval of the combustion chamber between at least two of the orifices comprises the formation to which heat can be transferred from the combustion chamber by convection and conduction through an annular space surrounding the combustion chamber.
7. The combustor of claim 1 wherein the catalytic surface comprises palladium.
8. The combustor of claim 1 wherein the combustor is within a wellbore.
9. The combustor of claim 8 wherein the fuel conduit is a tubular suspended from a wellhead and the combustor further comprises a means to apply electrical power to the fuel conduit at the wellhead; and the fuel conduit is of a lesser thickness in the vicinity of the orifices than above



the orifices and the fuel conduit is grounded from a point below at least one orifice.

10. A flameless combustor comprising:

an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;

5 a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices along the fuel conduit wherein the fuel conduit comprises an electrically conductive material; and

10 electrical heating means for ignition of the mixture of oxidant and fuel within the axial combustion chamber;

characterised in that the electrical heating means comprise an electrical power supply effective to pass electrical current through the fuel conduit in an amount effective to heat the fuel conduit in the vicinity of at least one orifice to a temperature above a temperature at which the fuel will ignite when the fuel passes through the orifices.

15 11. The combustor of claim 10 wherein the combustor is within a wellbore.

12. The combustor of claim 11 wherein the fuel conduit is a tubular suspended from a wellhead; electrical power is applied at the wellhead; the fuel conduit is of a lesser thickness in the vicinity of the orifices than above the orifices; and the fuel conduit is grounded from a point below at least one orifice.

20 13. A method to ignite a flameless combustor comprising:

providing an axial combustion chamber in communication with an inlet for oxidant at one end and in communication with a combustion product outlet at the other end;

25 providing a fuel conduit within the axial combustion chamber, the fuel conduit defining a fuel volume, the fuel volume in communication with a fuel supply, and in communication with the combustion chamber through a plurality of orifices located along the fuel conduit;

passing an oxidant to the combustion chamber;

passing a stream of fuel to the fuel volume; and

heating the stream of fuel, oxidant, or both the stream of fuel and oxidant to a temperature that results in reaction of the oxidant and the fuel when fuel combines with the oxidant;

30 characterised in that the oxidant is selected from the group comprising nitrous oxide and supplemental oxygen and that the method further comprises:

continuing to pass the oxidant to the combustion chamber and fuel to the fuel conduit until the temperature within the combustion chamber exceeds an autoignition temperature of the fuel in air; and

35 replacing the oxidant with air after the temperature within the combustion chamber exceeds the autoignition temperature of the fuel in air.

14. The method of claim 13 further comprising the step of passing an amount of electricity through the fuel conduit sufficient to cause the fuel conduit, for at least a portion of the conduit in the vicinity of at least one orifice, to heat to a temperature of at least 260°C.

15. The method of claim 13 further comprising the step of providing a catalytic surface



within the combustion chamber, the catalytic surface effective to reduce the temperature at which the fuel and oxidant react in the vicinity of the catalytic surface.

16. The method of claim 13 wherein the fuel is hydrogen.
17. The method of claim 13 wherein the fuel comprises hydrogen and carbon monoxide.
- 5 18. A flameless combustor, substantially as hereinbefore described with reference to the accompanying drawings.
19. A method to ignite a flameless combustor, substantially as hereinbefore described with reference to the accompanying drawings.

Dated 23 July, 1998

10


Shell Internationale Research Maatschappij B.V.

**Patent Attorneys for the Applicant/Nominated Person
SPRUSON & FERGUSON**




13033/97

FIG.1



2/2



INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 96/05753

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 E21B36/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 404 952 A (VINEGAR ET AL.) 11 April 1995 see column 5, line 24 - column 7, line 2 see column 8, line 29 - line 45; figures ---	1-18
A	US 4 445 570 A (RETALLICK) 1 May 1984 -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *I* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

11 April 1997

Date of mailing of the international search report

17.04.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2044, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

J.-P. Deutsch

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter national Application No

PCT/EP 96/05753

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5404952 A	11-04-95	NONE	
US 4445570 A	01-05-84	NONE	