

(12) **United States Patent**
Arnel et al.

(10) **Patent No.:** **US 9,820,508 B2**
(45) **Date of Patent:** **Nov. 21, 2017**

- (54) **WEARABLE ELECTRONIC SIMULATED SMOKING DEVICE**
- (71) Applicants: **Scott M. Arnel**, Oyster Bay, NY (US);
Eric Schmiesing, Syosset, NY (US)
- (72) Inventors: **Scott M. Arnel**, Oyster Bay, NY (US);
Eric Schmiesing, Syosset, NY (US)

5,622,293 A	4/1997	Lefevre	
6,854,470 B1	2/2005	Pu	
8,156,944 B2	4/2012	Han	
8,205,622 B2	6/2012	Pan	
8,490,628 B2	7/2013	Hon	
8,511,318 B2	8/2013	Hon	
8,528,569 B1	9/2013	Newton	
2004/0031488 A1*	2/2004	Terada A61M 11/005 128/203.15
2010/0163027 A1*	7/2010	Hyde A61B 5/0484 128/203.12
2010/0200006 A1	8/2010	Robinson et al.	
2011/0265806 A1	11/2011	Alarcon et al.	
2011/0277764 A1	11/2011	Terry et al.	
2011/0277780 A1	11/2011	Terry et al.	
2012/0118301 A1	5/2012	Montaser	

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 820 days.

(21) Appl. No.: **14/223,421**

(22) Filed: **Mar. 24, 2014**

(65) **Prior Publication Data**
US 2015/0264978 A1 Sep. 24, 2015

(51) **Int. Cl.**
A24F 47/00 (2006.01)
A44C 9/00 (2006.01)
A44C 5/00 (2006.01)

(52) **U.S. Cl.**
CPC **A24F 47/002** (2013.01); **A24F 47/008** (2013.01); **A44C 5/0007** (2013.01); **A44C 9/0053** (2013.01)

(58) **Field of Classification Search**
CPC A41D 1/00; A41D 1/04; A41D 2200/20; A24F 47/008; A61L 9/03; A42B 1/048
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

839,047 A	12/1906	Sylvester	
4,265,236 A *	5/1981	Pacella A61M 15/08 128/202.13

OTHER PUBLICATIONS


International Search Result From US/RO Regarding a Counterpart PCT Application.

Primary Examiner — Michael H Wilson
Assistant Examiner — Dionne Walls Mayes
(74) *Attorney, Agent, or Firm* — Rosenberg, Klein & Lee

(57) **ABSTRACT**

A wearable electronic simulated smoking device (**100, 100', 100''**) is provided for delivery of a desired active ingredient responsive to a user's inhalation through the device (**100, 100', 100''**). The device (**100, 100', 100''**) includes an elongated tubular member (**110**) having at least one reversibly bendable portion (**112, 112a, 112b**) to at least partially encompass a portion of a user's body and is releasably retainable thereat. Device (**100, 100', 100''**) includes a nebulization chamber **140** supplied with a liquid smoking composition (**132**) held in a fluid container (**130**) and enabled by a controller (**150**) responsive to detection of a user's inhalation through the device (**100, 100', 100''**).

6 Claims, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0138637	A1*	6/2012	Ciavarella	A44C 5/0023 222/175
2012/0204889	A1	8/2012	Xiu	
2012/0214380	A1	8/2012	Vine, III	
2012/0234315	A1*	9/2012	Li	A24F 47/008 128/200.21
2013/0247924	A1	9/2013	Scatterday et al.	
2014/0007891	A1	1/2014	Lin	

* cited by examiner





FIG. 1






FIG. 3




FIG. 4








FIG. 5








FIG. 10




FIG. 11




FIG. 12

1

WEARABLE ELECTRONIC SIMULATED SMOKING DEVICE

BACKGROUND OF THE INVENTION

This disclosure directs itself to a wearable electronic simulated smoking device that provides convenient storage and use as an alternative to inhalation of the smoke from burning a composition containing a desired active ingredient. More in particular, the disclosure is directed to a wearable electronic simulated smoking device that includes a tubular body that is configured to at least partially encompass a portion of a user's body and thereby be easily transported by the user. Still further, the disclosure is directed to a wearable electronic simulated smoking device where the tubular body has at least a portion thereof which is reversibly bendable into, or out of, an arcuate contour. Further, the tubular body may include at least one portion having a fixed contour as well as at least one portion that is reversibly bendable.

Electronic simulated smoking devices, commonly known as e-cigarettes or e-cigs, came into being in the early 1960's. These simulated smoking devices have grown in acceptance and popularity because it is believed that they are less toxic to the user than the conventional method of inhaling a desired active ingredient through burning a source of that ingredient and inhaling the products of that combustion, including carcinogens. Without the toxic products of combustion being present, there is a greatly reduced concern about "secondhand smoke," as well. They have also grown in popularity due to people's fascination with gadgetry.

Nevertheless, there has not been a new or fashionable way of transporting or storing these devices on one's person. They are often carried loose or in cases that are put in a user's pocket or handbag. Unlike a conventional cigarette, cigar or pipe that typically and most easily is ignited and burned until the substance carrying the active ingredient is substantially consumed, the e-cigarette can be used intermittently. The e-cigarette is inactive whenever no inhalations are being made through the device and can be stored on the user's person. Thus, there is a need for a more convenient storage and transport mechanism for electronic simulated smoking devices.

SUMMARY OF THE INVENTION

A wearable electronic simulated smoking device is provided that includes an elongated tubular body, having at least a portion thereof that is reversibly bendable for the tubular body to at least partially encompass a portion of a user's body. The tubular body has an air inlet formed therein, a suction opening, and a fluid flow path therebetween. The smoking device also includes a fluid reservoir disposed in the tubular body for providing a supply of a liquid smoking composition. Further, the smoking device includes a nebulization chamber disposed in fluid communication with the fluid reservoir and the fluid flow path for dispensing a vapor of the liquid smoking composition to the fluid flow path. The smoking device further includes a sensor disposed in fluid communication with the fluid flow path for detecting an inhalation by the user. Still further, the wearable electronic simulated smoking device includes a controller coupled to the sensor and the nebulization chamber. The controller is configured to activate the nebulization chamber responsive to the sensor detecting inhalation by the user to add the vapor of the smoking liquid composition to air drawn

2

through the fluid flow path. The smoking device still further includes a power supply coupled to the controller.

From another aspect, a wearable electronic simulated smoking device is provided that includes an elongated tubular body configured to at least partially encompass a portion of a user's body and is releasably retained thereat. The tubular body has at least one arcuate shaped portion. The tubular body further has an air inlet formed therein, a suction opening, and a fluid flow path therebetween. The smoking device further includes a fluid reservoir disposed in the tubular body for providing a supply of a liquid smoking composition. The smoking device also includes a nebulization chamber disposed in fluid communication with the fluid reservoir and the fluid flow path for dispensing the liquid smoking composition to the fluid flow path. Further, the wearable electronic simulated smoking device includes a sensor disposed in fluid communication with the fluid flow path for detecting an inhalation by the user. Still further, the smoking device includes a controller coupled to the sensor and the nebulization chamber. The controller is configured to activate the nebulization chamber responsive to the sensor detecting inhalation by the user to add the vapor of the smoking liquid composition to air drawn through the fluid flow path. The smoking device still further includes a power supply coupled to the controller.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration, partially cut-away, of a configuration of the present invention;

FIG. 2 is a schematic illustration, partially cut-away, of another configuration of the present invention in a bent contour;

FIG. 2A is an illustration of the configuration shown in FIG. 2 in a straightened contour;

FIG. 3 is an enlarged partial view taken along the section line 3-3 in FIG. 2 showing an alternate structure of the tubular body;

FIG. 4 is an enlarged partial view taken along the section line 4-4 in FIG. 2 showing another alternate structure of the tubular body;

FIG. 5 is an enlarged partial view taken along the section line 5-5 in FIG. 2 showing an alternate coupling structure of the tubular body;

FIG. 6 is an enlarged partial view taken along the section line 6-6 in FIG. 2 showing another alternate coupling structure of the tubular body;

FIG. 7 is an enlarged partial view taken along the section line 7-7 in FIG. 2 showing a further alternate coupling structure of the tubular body;

FIG. 8 is a cross-sectional view taken along the section line 8-8 of FIG. 2 showing a further alternate structure of the tubular body;

FIG. 9 is an illustration of a modification of the configuration shown in FIG. 1 to be worn on a user's wrist;

FIG. 10 is a schematic illustration, partially cut-away, of a further configuration of the present invention in a bent contour;

FIG. 11 is an illustration of the configuration shown in FIG. 10 being worn on a user's finger; and

FIG. 12 is a sectional view taken along the section line 12-12 in FIG. 2 showing an alternate liquid container arrangement.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIGS. 1-12, there is shown a wearable electronic simulated smoking device 100, 100', 100" for

convenient storage and use as an alternative to inhalation of the smoke from burning a composition containing a desired active ingredient. Wearable electronic simulated smoking device **100**, **100'**, **100''** includes a unique housing in the form of a tubular body **110** that is configured to at least partially encompass a portion of a user's body and thereby be easily transported by the user. While being worn, wearable electronic simulated smoking device **100**, **100'**, **100''**, in some instances, can be used to deliver a desired active ingredient through inhalation by the user through that device.

Referring now to FIGS. **2** and **2A**, there is shown schematic illustrations of a wearable electronic simulated smoking device **100**. Wearable electronic simulated smoking device **100** includes an elongated tubular housing **110**, a portion of which **112** is reversibly bendable into, or out of, an arcuate contour. In the particular configuration shown, the bendable portion **112** is defined by substantially the entire extent of the tubular body **110**. As will be described in following paragraphs, the bendable portion **112** of tubular body **110** may be formed of various plastic or metallic materials having properties and/or structural arrangements providing the necessary pliancy to be reversibly bendable, either elastically or inelastically.

FIG. **2A** illustrates the wearable electronic simulated smoking device **100** arranged for use. The tubular body **110** is straightened longitudinally from its arcuate storage configuration shown in FIG. **2**, allowing a user to easily access the mouthpiece portion **120**. The user can then inhale through the suction opening **126** to obtain delivery of a liquid smoking composition in the form of an aerosol or vapor carried by air drawn into the tubular body through the air inlet opening **122**. Each time a user inhales through the suction opening **126**, the light transmissive end cap **170** is illuminated in correspondence therewith.

The operation of wearable electronic simulated smoking device **100** is best understood by referring back to FIG. **2**. Wearable electronic simulated smoking device **100** includes a hollow tubular body **110** housing the components that store a smoking liquid composition **132** and provide the means to deliver the composition **132** to the air inhaled through the device by the user. The components that are combined to form an electronic simulated smoking device, commonly referred to as an e-cig or e-cigarette, are well known in the art and thus their particular structures will not be described in detail, other than where modifications have been incorporated therein to accommodate the bendability of the tubular body **110** or portions thereof.

Wearable electronic simulated smoking device **100** includes a supply of a smoking liquid composition **132** within a fluid container **130**. The smoking liquid composition contains an active ingredient intended to be inhaled, such as a nicotine solution, a mixture of nicotine and flavorings and/or aromatic compositions, and where legally permitted, a tetrahydrocannabinol (THC) solution, a mixture of THC and flavorings and/or aromatic compositions, and combinations thereof, as examples. The supply of the smoking liquid composition **132** may be stored as liquid within fluid container **130** or absorbed in a porous material disposed in fluid container **130**. Fluid container **130** is formed of a flexible plastic material so that it is able to conform to the contour of the internal bore **1101** of the bendable portion **112** of tubular body **110** when that portion is bent into an arcuate contour. The outer diameter of the fluid container **130** is sufficiently smaller than the inner diameter of internal bore **1101** so that air drawn therein through the air inlet opening **122** can pass by the fluid container. Alternately or in addition thereto, the wall of fluid container **130** may be

formed with longitudinally extending air channels. The smoking liquid composition **132** is output to the nebulization chamber **140** through a flexible conduit **134**. As is known in the art, the flow of the liquid smoking composition to or within the nebulization chamber is controlled by a valve (demand type or controlled by the controller **150**) or through the use of a wick that supplies the liquid through capillary action on, for all practical purposes, a demand basis.

The flexible conduit **134** may be formed of a flexible material, such as silicone, polyvinyl chloride, nylon, neoprene, polyurethane, or natural and synthetic rubber, to name a few. More rigid materials can be made sufficiently flexible by constructing conduit **134** with an accordion or bellows type wall contour, as illustrated in FIG. **2**. As an alternative to a single flexible fluid container **130**, a segmented fluid container **130'**, shown in FIG. **12**, may be substituted. Fluid container **130'** consists of container sections **136** fluidly connected in series by respective flexible container conduits **138**. Each flexible container conduit **138** may be formed of like materials and/or constructed as was described for flexible conduit **134**, including provisions for allowing air to pass along the outer sides of the container walls.

As used herein, the term "nebulization" refers to a process for conversion of a liquid into a spray, aerosol, mist or vapor, by either atomization or vaporization mechanisms. Nebulization chamber **140** may be of the type that vaporizes the liquid smoking composition **132** supplied thereto through the use of an internal heating element, or the type that atomizes the liquid smoking composition **132** using an ultrasonic transducer, such as a piezoelectric transducer, to create an aerosol. Both types of nebulization chambers are well known in the electronic cigarette art and thus the internal structure and theory of operation are not being described herein. Nebulization chamber **140** is disposed in the internal bore **1101** of tubular body **110** and is sufficiently smaller in diameter than internal bore **1101** to be accommodated therein when such is disposed in an arcuate contour. As is typical for such devices, nebulization chamber **140** is provided with air inlet openings on a rear portion thereof (not shown) and the portion of internal bore **1101** in which nebulization chamber **140** is disposed is defined as the fluid flow path. Fluid flow path **124** extends from the air inlet opening **122**, past the outer wall of the fluid container **130**, **130'**, through the nebulization chamber **140** to the suction opening **126**. An annular seal **144** encompasses the nebulization chamber **140** to block air from bypassing passage through nebulization chamber **140**.

A controller **150** is provided to control the operation of the nebulization chamber **140** in response to inhalation by a user. Such controllers are commonly used in conventional e-cigarettes and may be in the form of a microprocessor or a digital, analog or hybrid system on chip (SOC). Controller **150** has an input coupled to a sensor **152** via a pair of the plurality electrical wires **156** connected to controller **150**. The sensor **152** is located in fluid communication with the fluid flow path **124** for detecting a reduction in air pressure in fluid flow path **124**, as an indication of a user drawing in air from the suction opening **126**. Responsive to detection of the pressure drop, controller **150** energizes the nebulization chamber **140** through the electrical wires **142** to deliver the liquid smoking composition/air mixture to the user as the user inhales through the suction opening **126** of the mouthpiece **120**. The mouthpiece **120** may be connected to the tubular body **110** or integrally formed therewith.

Responsive to the detection of a user's inhalation through the device **100**, controller **150** energizes a light emitting diode (LED) **154** via another pair of the plurality electrical

5

wires 156 connected to controller 150. LED 154 is disposed at the distal end 1102 of tubular body 110, but could be located at any desired location. End cap 170 is coupled to the distal end 1102 of tubular body 110 and is light transmissive to serve to both permit visualization of illumination from LED 154 and provide releasable coupling with the opposing proximal end 1104 of tubular body 110, to be further described in following paragraphs. The optical property of end cap 170 may range from transparent to varying levels of translucency. To enable the energization of the nebulization chamber 140 and LED 154, a power supply 160 is connected to controller 150 by means of a pair of wires 158. Power supply 160 is formed by a plurality of batteries or cells 162 that may be connected in series, parallel or a combination of series and parallel by means of one or more interconnection leads 164 (depending on the connection arrangement of the batteries). Each interconnection lead 164 is a flexible electrical wire having a stranded or braided construction to allow for displacement of the batteries 162 when the contour of the internal bore 1101 changes in response to bending tubular body 110.

A tubular body 110 with one or more bendable portions 112 provides the ability of the electronic simulated smoking device 100 to be formed by a user into a contour that at least partially encompasses a portion of the user's body so that it can be worn as an ornament or an accessory. Depending upon the length and/or diameter of tubular body 110, device 100 can be worn about such body portions as the neck, wrist, or finger, as examples. It is contemplated that anywhere a user wears ornamentation or accessories, device 100 can be configured to be similarly worn thereat.

As shown in FIG. 2, tubular body 110 may be reversibly bent into an annulus to encompass such bodily structures as a user's neck or wrist. The tubular body is maintained about the user using a releasable coupling 280 formed by complementary elements at the opposing end portions 1102 and 1104 of tubular member 110 and is releasably retainable thereat. End cap 170 is formed with an end portion 171 having a contour corresponding to an internal contour of the suction opening 126 of the mouthpiece portion 120 to be received therein. End cap 170 has a projection 172 extending therefrom with a locking head portion 174 at the distal end thereof. When the end portion 171 of end cap 170 is received in the suction opening 126, the projection 172 locates the locking head 174 so that it releasably lockingly engages the mouthpiece through opening 128. By this arrangement, the electronic simulated smoking device 100 can be conveniently carried by a user on the user's person; worn as a fashion accessory when not in use.

Other complementary elements at the opposing end portions 1102 and 1104 of tubular member 110 can be utilized to provide a releasable coupling 280 to maintain the tubular body 110 about a portion of the user's body. For example, as shown in FIG. 5, the proximal end 1104 of tubular body 110 may be coupled to a mouthpiece 120' formed of a metallic composition containing a ferrous metal. The opposing distal end 1102 of tubular body 110 is fitted with an end cap 170' formed by a light transmissive tubular member 176. The light transmissiveness of tubular member 176 can range from transparent to varying levels of translucency. Tubular member 176 is coupled to the distal end 1102 of tubular member 110 by means of a coupling sleeve 178 affixed within the internal bore 1101 of tubular member 110 and extending into the internal bore 1766 of tubular member 176 to be affixed thereat. Within the internal bore 1766 of tubular member 176 adjacent the receiving end 1762 there is disposed an annular magnet 190. Thus, the mouthpiece 120' is

6

inserted into the opening 192 at the receiving end 1762 of tubular member 170' to be magnetically held thereat. A user is able to release the coupling of the distal end 1104 of tubular body 110 from the tubular member 176 by applying a sufficient tensile force therebetween to overcome the magnetic attraction between the annular magnet 190 and the metallic mouthpiece 120'. When device 100 is in use, illumination from LED 154 is emitted through the opening 192 and an illumination region 1764 located between a rear end of the annular magnet 190 and, at least, a tubular member facing end of the coupling sleeve 178. The illumination region 1764 may be expanded in size through the use of a coupling sleeve 178 formed of a light transmissive material.

Another alternative arrangement of releasable coupling 280 is shown in FIG. 6. Here, the end cap 170' includes a tubular member 176 having an internal bore 1766 into which the distal end 1102 of the tubular body 110 is received and affixed thereat. As in the example of FIG. 5, tubular member 176 is formed of a material that has a light transmissiveness that can range from transparent to varying levels of translucency to emit illumination from the LED 154. The mouthpiece 120 portion of tubular body 110 at the proximal end 1104 thereof is insertable into the opening 175 to be received and frictionally engaged within the internal bore 1766 of the tubular member 176. A user is able to easily release the coupling of the distal end 1104 of tubular body 110 from the tubular member 176 by applying a sufficient tensile force therebetween to overcome the frictional engagement between the tubular member 176 and the mouthpiece 120.

A further alternative arrangement of releasable coupling 280 is shown in FIG. 7. The arrangement illustrated in FIG. 7 is particularly useful where the bendable portion 112 of tubular body 110 is formed of a metallic material. Here, an end cap 170" provides threaded releasable engagement with a connector 200 affixed to the proximal end 1104 of tubular member 110. End cap 170" includes a coupling 194 rotatably affixed to the distal end 1102 of tubular body 110. The proximal end 1104 of tubular body 110 is coupled to a connector 200 from which the mouthpiece 120 extends. Connector 200 has external threads 202 formed thereon.

The opposing distal end 1102 of tubular body 110 has a fixing ring 1114 affixed to, and circumscribing, the outer surface thereof. The end cap 170" is formed with an internal annular groove 196 into which the fixing ring 1114 is received to thereby establish a rotatable connection to the distal end 1102 of tubular body 110. End cap 170" is formed of a plastic material with a light transmissiveness ranging from transparent to varying levels of translucency to thereby emit illumination from the LED 154. The end cap 170" may be formed of a plastic material that is sufficiently elastic to permit the fixing ring 1114 to "snap" into the annular groove 196. Where a less elastic material is used, the end cap 170" may have two longitudinally separate halves that are assembled to the distal end 1102 of tubular body 110 and joined together thereat by any of a plurality of conventional means. Accordingly, to couple the opposing ends 1102 and 1104 of tubular body 110, the mouthpiece 120 is inserted into the internal bore 1766 of the end cap 170" through the opening 195, as indicated by directional arrow 103, and the end cap 170" is rotated to engage the internal threads 198 thereof with the external threads 202 of the connector 200. To uncouple the ends 1102 and 1104 of tubular body 110, the user simply rotates the end cap 170" in the opposite direction to thereby disengage the threaded connection.

The bendable portion 112 of tubular body 110 may be formed of a variety of plastic or metallic materials and may

encompass the entirety of tubular body **110**. As shown in FIG. **8**, the strength and/or elasticity of the bendable portion **112** of tubular body **110** may be improved by embedding a plurality of longitudinally extended wire members **1110** in the plastic wall **1100** to extend axially therein. The number, diameter, and material of wire members **1110** is selected as a function of the characteristics to be achieved.

Referring to FIG. **3**, the wearable electronic simulated smoking device **100** may include a bendable portion **112'** of a tubular body **110'** formed of a metallic material where a strip of metal **1126** is helically wound in a partially overlapping manner to form the annular wall of the flexible tube. This type of construction is commonly referred to as a "gooseneck" tube or conduit. Where the "gooseneck" structure is being used, the air inlet opening **122** is formed through one of the metal strips **1126**.

Another metallic construction is illustrated in FIG. **4**. Here, the wearable electronic simulated smoking device **100** has bendable portions **112"** of a tubular body **110"** formed of at least two helical springs **1106** and **1108**. Each spring **1106**, **1108** when oriented for use of the device **100** is unbent and each spring has sufficient bias force between the helical turns of the wire **1105** to be substantially impervious to air when a user inhales through the tubular body **110"**. The two springs **1106** and **1108** are joined by an inlet connector **180**. Inlet connector **180** has a cylindrical tubular contour with a through bore **186**. The air inlet opening **122** is formed through the wall of inlet connector **180** and is in open communication with the through bore **186**. Opposing ends of through bore **186** each have internal threads **182** and **184** into which the helically wound wire **1105** of the springs **1108** and **1106** are respectively threadedly engaged. The internal threads **184** may be right hand threads and the internal threads **186** may be left hand threads. The springs **1106** and **1108** are correspondingly wound (opposite to one another) so that both springs are simultaneously threadedly engaged responsive to rotation of the inlet connector **180** being rotated in one direction relative to both springs **1106** and **1108**, as is done with a turnbuckle. Other methods of securing the inlet connector **180** to springs **1106** and **1108**, such as adhesive bonding, welding, swaging, and the like may alternately be used. Similar methods may be employed to join the mouthpiece connector and end cap to the free ends of the springs **1106** and **1108**.

Turning now to FIG. **1**, there is shown a wearable electronic simulated smoking device **100'** that has a configuration where at least a portion of the tubular body **110** has a fixed contour and at least another portion is bendable to change the contour thereof. The wearable electronic simulated smoking device **100'** has a tubular body formed by bendable portions **112a**, **112b** and the portions **114a**, **114b** having a fixed arcuate contour. The fixed contour portions **114a**, **114b** may be formed of plastic or metallic materials, as can the bendable portions **112a**, **112b**, which bendable portions may be formed of materials and structures as previously described in preceding paragraphs. By that arrangement, the device **100'** is able to at least partially encompass a portion of the user's body and be releasably retainable thereat to thereby provide both the electronic smoking function as well as serve as a fashionable ornament or accessory.

The operational components of wearable electronic simulated smoking device **100'** are distributed within the internal bore **1101a**, **1101b** of the tubular portions **114a** and **114b**. The portions **114a** and **114b** are joined by a mouthpiece connector **118** that has a connector body **117** from which the mouthpiece **120** extends. Within the internal bore **1101b** of

arcuate portion **114b** there is disposed a fluid container **130** with a supply of a liquid smoking composition **132** therein. The fluid container **130** is fluidly coupled to a nebulization chamber **140** by a flexible conduit **134**. Nebulization chamber **140** is disposed in the fluid flow path **124** that extends from the air inlet opening **122**, through the through bore **119** of mouthpiece connector **118**, to the suction opening **126**. As previously described, nebulization chamber **140** is provided with air inlet openings on a rear portion thereof (not shown) to allow air to be drawn therethrough. An annular seal **144** encompasses the nebulization chamber **140** to block air from bypassing passage through nebulization chamber **140**. The descriptions of the components **130**, **132**, **134**, and **140** and alternatives thereto apply to device **100'** as well.

Within the internal bore **1101a** of arcuate portion **114a** there is disposed a sensor **152** in open fluid communication with the fluid flow path **124** for detecting a reduction in air pressure in fluid flow path **124** as an indication of a user drawing in air from the suction opening **126** of mouthpiece **120**. Also in proximity to the fluid flow path **124** is an LED **154**, which is illuminated when the sensor detects a user's inhalation and operation of the nebulization chamber **140** is initiated. The sensor **152** and LED **154** are connected to a controller **150** via corresponding pairs of a plurality of electrical wires **156**. The controller **150** is provided to control the operation of the nebulization chamber **140** in response to inhalation by a user, as was described in preceding paragraphs and thus not repeated here. To enable the energization of the nebulization chamber **140** and LED **154**, a power supply **160** is connected to controller **150** by means of a pair of electrical wires **158**. Power supply **160** is formed by a plurality of batteries or cells **162** that may be connected in series, parallel, or a combination of series and parallel by means of one or more interconnection leads **164**, as appropriate to the battery connection arrangement. Each interconnection lead **164** is a flexible electrical wire having a stranded or braided construction.

The mouthpiece connector **118** may be formed of a plastic material with a light transmissiveness ranging from transparent to varying levels of translucency to thereby emit illumination from the LED **154**. Alternately, mouthpiece connector **118** may be formed of a metallic material with a light transmissive plastic insert incorporated therein to permit visualization of illumination from LED **154**. The proximal end **115a** of the arcuate portion **114a** of tubular member **110** is received into the through bore **119** of the connector body **117** of mouthpiece connector **118** from one side thereof, and the proximal end **115b** of arcuate portion **114b** of tubular member **110** is likewise received into the through bore **119** from the opposing side of connector body **117**. By that arrangement, the through bore **119** and the suction opening **126** therewith are placed in open communication with the fluid flow path **124** and the internal bore **1101a** of the arcuate portion **114a** of tubular member **110** so that the sensor **152** is able to sense air pressure changes in fluid flow path **124**.

The mouthpiece **120** extending from the connector body **117** may be disposed at any angle relative to the plane established by the tubular body **110**. When the electronic simulated smoking device **100'** is to be worn about a user's neck, the angle of the mouthpiece **120** relative to the plane established by tubular body **110** is desirable to be within a range of 0 degrees, as illustrated in FIG. **1**, to 180 degrees. If the diameter of the arcuate contour of the tubular body **110** is sufficiently large, the wearable electronic simulated smoking device **100'** can conveniently be used without removal from the user's neck for an orientation of mouthpiece **120**

relative to the plane established by tubular body **110** within a range of 0 degrees to 90 degrees. With reference to FIG. **9**, when electronic simulated smoking device **100'** is sized to be worn around a user's wrist **106** or finger **108**, the angle of the mouthpiece **120** relative to the plane established by tubular body **110** is desirable to be within a range of 90 degrees to 270 degrees. A most convenient orientation for mouthpiece **120** in that application is at a substantially 180 degree angle, extending from the convex side of the arcuate contour of the tubular body **110**.

Referring to both FIGS. **1** and **9**, the bendable portions **112a** and **112b** respectively extend from the distal ends **116a** and **116b** of the arcuate portions **114a** and **114b**. Each of the bendable portions **112a**, **112b** have a proximal end **1122a**, **1122b** secured to the distal end **116a**, **116b** of the corresponding arcuate portion **114a**, **114b**. Each bendable portion **112a**, **112b** has a closed distal end **1124a**, **1124b**. The bendable portions **112a** and **112b** may be formed of the same materials and/or structure as the bendable portion of electronic simulated smoking device **100** discussed in preceding paragraphs. Accordingly, when a user wishes to encompass a portion of their body, such as their neck, wrist or finger, with the electronic simulated smoking device **100'**, the user bends the portions **112a** and **112b** outwardly, as indicated by direction arrows **102** and **104**, and passes the tubular body **110** around the selected portion of the user's body. Once positioned, the user either releases the bendable portions **112a** and **112b** to return to their original arcuate contour and at least partially encompass the selected portion of the user's body, when bendable portions **112a** and **112b** have an elastic property, or manually bend the bendable portions **112a** and **112b** back into an arcuate contour sufficient to at least partially encompass the selected portion of the user's body and maintain the electronic simulated smoking device **100'** thereat.

Turning now to FIGS. **10** and **11**, there is shown wearable electronic simulated smoking device **100''**. The electronic simulated smoking device **100''** is structurally identical to electronic simulated smoking device **100**, previously described, but with a tubular body **110** that is elongated to a greater extent than would be the case for device **100** for use with the same selected portion of the user's body, and without the components that form the releasable coupling **280**. Hence, a light transmissive end cap **170'** is coupled to the distal end **1102** of tubular body **110** and a mouthpiece **120** is provided at the opposing end **1104**. The extended length of tubular body **110** and the bendable portion **112** therewith, the bendable portion **112** being essentially coextensive with the entire tubular body **110**, permits a user to wrap the tubular body **110** to form a closed loop about selected portions of the user's body and thereby is releasably retainable thereat. Thus, the tubular body **110** is able to fully encompass exemplary selected portions of the user's body as the neck, wrist or finger. As an example of the application of electronic simulated smoking device **100''**, FIG. **11** shows the device **100''** being worn about a user's finger **108**. As the releasable coupling is not required to retain the tubular body **110** about the user's finger **108**, the user is able to easily access the mouthpiece **120** without the necessity of removing it from their finger.

The descriptions above are intended to illustrate possible implementations of the present invention and are not restrictive. While this invention has been described in connection with specific forms and embodiments thereof, it will be appreciated that various modifications other than those discussed above may be resorted to without departing from the spirit or scope of the invention. Such variations, modifications, and alternatives will become apparent to the skilled artisan upon review of the disclosure. For example, functionally equivalent elements may be substituted for those specifically shown and described, and certain features may be used independently of other features. In certain cases, particular locations of elements may be reversed or interposed, all without departing from the spirit or scope of the invention as defined in the appended Claims. The scope of the invention should therefore be determined with reference to the description above, the appended claims and drawings, along with their full range of equivalents.

What is being claimed is:

1. A wearable electronic simulated smoking device, comprising:
 - an elongated tubular body configured to form an arcuate shape at least partially encompassing a portion of a user's body, said tubular body having at least one fixedly arcuate shaped portion, said tubular body further having an air inlet formed therein, a suction opening, and a fluid flow path therebetween;
 - a fluid reservoir disposed in said tubular body for providing a supply of a liquid smoking composition;
 - a nebulization chamber disposed in said tubular body in fluid communication with said fluid reservoir and said fluid flow path;
 - a sensor disposed in fluid communication with said fluid flow path for detecting an inhalation by the user;
 - a controller coupled to said sensor and said nebulization chamber, said controller being configured to activate said nebulization chamber responsive to said sensor detecting inhalation by the user to generate vapor from said liquid smoking composition and add said vapor to air drawn through said fluid flow path; and
 - a power supply coupled to said controller.
2. The wearable electronic simulated smoking device as recited in claim 1, where said arcuate shaped portion of said tubular body has opposing ends thereof respectively joined to a reversibly bendable portion to provide releasable retention of said device about the user's body.
3. The wearable electronic simulated smoking device as recited in claim 2, where each said bendable portion has an annular wall formed of a flexible material.
4. The wearable electronic simulated smoking device as recited in claim 2, where each said bendable portion has an annular wall formed to define a flexible structure.
5. The wearable electronic simulated smoking device as recited in claim 1, where said suction opening is formed in a mouthpiece member coupled to said arcuate shaped portion of said tubular body.
6. The wearable electronic simulated smoking device as recited in claim 5, where said mouthpiece member is formed of a light transmissive material for viewing illumination from an indicator located internal to said tubular body.

* * * * *