

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 October 2009 (22.10.2009)

PCT

(10) International Publication Number
WO 2009/129388 A1

(51) International Patent Classification:

C07C 37/08 (2006.01) C07C 39/04 (2006.01)
C07C 45/53 (2006.01) C07C 49/08 (2006.01)

(21) International Application Number:

PCT/US2009/040804

(22) International Filing Date:

16 April 2009 (16.04.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2008115046 16 April 2008 (16.04.2008) RU
12/424,447 15 April 2009 (15.04.2009) US

(71) Applicant (for all designated States except US): **SABIC INNOVATIVE PLASTICS IP B.V** [NL/NL]; Plastic-slaan 1, NL-4612 PX Bergen Op Zoom (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NELSON, Mark, E.** [US/US]; 310 East 3rd Street, Mount Vernon, IN 47620 (US). **SAMUILOVICH, Dykman, Arkady** [RU/RU]; Pr. Engelsa 126, Bd.1, App. 87, St. Petersburg, 194356 (RU). **VLADIMIROVICH, Zinenkov, Andrey** [RU/RU]; Pr. Gagarina 14, Bd.5, App. 103, St. Petersburg, 196211 (RU). **VLADIMIROVICH, Pinson, Victor** [RU/RU]; Primorskii Pr., 41, App. 10, St. Petersburg, 197183 (RU). **NIKOLAYEVICH, Grebenshchikov, Ilja**

[RU/RU]; Tramvainiy Pr. 21, Bd.1, App. 40, St. Petersburg, 198216 (RU).

(74) Agent: **DESIMONE, Patricia, S.**; Cantor Colburn LLP, 20 Church St., 22nd Floor, Hartford, CT 06103 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD FOR PRODUCING PHENOL AND ACETONE

(57) Abstract: A method for producing phenol and acetone in a multi-stage process from a cumene hydroperoxide mixture comprising cumene, comprises the steps of: a) distilling an amount of cumene from the cumene hydroperoxide mixture until the cumene mass% is 0 to 7 mass% relative to the total mass of the cumene hydroperoxide mixture, b) reacting the cumene hydroperoxide mixture with an acid catalyst form to a second mixture comprising phenol, acetone and dicumyl peroxide in a first stage, and c) decomposing the second mixture in a second stage to produce phenol and acetone, wherein an amount of phenol approximately equal to the amount of distilled from the cumene hydroperoxide mixture is added to the cumene hydroperoxide mixture before the reacting step b). The amount of hydroxyacetone is reduced, thereby, improving the quality of commercial-grade phenol and the products made from the phenol.



WO 2009/129388 A1

METHOD FOR PRODUCING PHENOL AND ACETONE

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to Russian Application Serial No. 2008115046, filed April 16, 2008. This disclosure is hereby fully incorporated herein by reference.

BACKGROUND

[0002] The present invention relates to the field of industrial organic synthesis, particularly to the production of phenol and acetone by the cumene method.

[0003] A well-known method for producing phenol and acetone by the oxidation of cumene with atmospheric oxygen, followed by the acid-catalyzed decomposition of cumene hydroperoxide, makes it possible to obtain both target products (phenol and acetone) at a high yield (Khruzhalov B.D., Golovanenko B.N., Co-production of phenol and acetone, Moscow, GosKhimIzdat, 1964). However, the yield of heavy byproducts, so-called “phenol resins,” of this process remains considerable.

[0004] There are known methods of producing phenol and acetone in which, in order to reduce the yield of phenol resins (also referred to as “heavies”), cumene oxidation products containing cumene hydroperoxide (CHP), cumene, and dimethylphenylcarbinol (DMPC, also referred to as dimethylbenzyl alcohol (DMBA)) are cleaved in two stages in the presence of sulfuric acid. The first stage involves decomposition of most (97 to 99%) of the CHP and synthesis of dicumyl peroxide (DCP) from DMPC and CHP at 55 to 80°C. The second stage involves adding acetone to the resulting reaction mixture containing phenol, acetone, DMPC, and DCP at a temperature of 80 to 120°C. The acetone is added in an amount equal to 1.5 to 1.8 times its initial concentration. This process is accompanied by the cleavage of the DCP formed in the first stage, decomposition of the residual CHP, and dehydration of a portion of the residual DMPC (Russian patent Nos. 2,068,404 and 2,121,477).

[0005] The aforementioned methods make it possible to markedly reduce the amount of byproducts in comparison with the one-stage decomposition processes (resin yield: 25 kg/t of phenol). At the same time, the amount of the hydroxyacetone (HA) byproduct remains high in these improved two stage processes (for example, more than 1000 ppm).

[0006] Hydroxyacetone is a source of 2-methylbenzofuran, which is difficult to separate from phenol and which has an adverse effect on the color indexes of products made

from impure commercial-grade phenol. Hydroxyacetone can be removed from phenol, for example, by an alkaline treatment, but this makes the technology of the process more complicated (Vasilieva I.I., Zakhoshansky V.M., Collection of articles titled "Petrochemical and Oil Refining Processes," SPb, Giord, 2005, p. 344).

[0007] A method is known for decomposing technical-grade CHP in a medium composed of reaction products containing up to 13 mass% of cumene at a phenol/acetone molar ratio of greater than 1 and a sulfuric acid concentration of 0.003 to 0.015 mass% (Russian Patent No. 2,291,852). The decomposition process is carried out in two stages. In the first stage, technical-grade CHP is decomposed in at least two serially connected reactors while the reaction mass is circulated at 40 to 65°C in the presence of the sulfuric acid catalyst having a concentration of 0.003 to 0.015 mass% in the reaction mass (depending on the temperature in the reactors and the phenol/acetone ratio). The volume in which the raw material (CHP) is introduced should not be more than 10%, and in embodiments is preferably less than 5%, of the circulation volume of the reaction mass, while the circulation factor (ratio of the flow rate of the circulating mass to the flow rate of the technical-grade CHP fed as a raw material) is from 8 to 50. If the CHP conversion is equal to 95 to 99.8% under these conditions, the CHP decomposes to give phenol and acetone, and DCP is synthesized from CHP and DMPC.

[0008] In the second stage, the synthesized DCP and the residual CHP are decomposed in the final reactor at a temperature of 90 to 140°C while half of the added sulfuric acid is first neutralized with ammonia. The hydroxyacetone yield decreases from a level of greater than 0.1 mass% (1000 parts per million part by weight (ppm)) to 0.04 mass% (400 ppm, as mentioned in Russian Patent No. 2,291,852). However, application of this method is premised on the use of phenol that has been purified in a phenol purification system, and the purification of phenol involves additional manufacturing steps and power consumption.

[0009] Another method of CHP decomposition is a method that is carried out in two stages according to Russian Patent No. 2,142,932. This CHP decomposition process is carried out in three serially arranged mixing reactors in the first stage, and a displacement reactor in the second stage. The CHP is decomposed in the first stage under conditions close to isothermal (that is, at a temperature of 47 to 50°C and a concentration of 0.018 to 0.020 mass% for the sulfuric acid catalyst), while the reaction mass is additionally diluted with

acetone in an amount equal to 5 to 8 mass% relative to the amount of CHP supplied. Almost all of the CHP reacts in the process, and DCP forms from part of the CHP and DMPC.

[0010] The process in the second stage is carried out while the sulfuric acid is partially neutralized with ammonia to form ammonium hydrosulfate at 120 to 140°C, and while some water is added. The concentration of acid is 0.009 to 0.010 mass%. The CHP and DCP are decomposed in a reaction medium containing phenol and acetone, both of which have formed from the CHP. Additional acetone may optionally be added to the reactor if desired.

[0011] A disadvantage of the prior-art method is the presence of hydroxyacetone in the resulting phenol. The presence of hydroxyacetone has an adverse effect on the phenol quality. There is a need for a method to further reduce the amount of hydroxyacetone in the resulting phenol produced.

SUMMARY OF THE INVENTION

[0012] Some or all of the above-described deficiencies are addressed by a method for producing phenol and acetone in a multi-stage process at an elevated temperature from a cumene hydroperoxide mixture comprising cumene, the method comprising the steps of:

- a) distilling an amount of cumene from the cumene hydroperoxide mixture until the cumene mass% is 0 to 7 mass% relative to the total mass of the cumene hydroperoxide mixture,
- b) reacting the cumene hydroperoxide mixture with an acid catalyst form to a second mixture comprising phenol, acetone and dicumyl peroxide in a first stage, and
- c) decomposing the second mixture in a second stage to produce phenol and acetone, wherein an amount of phenol approximately equal to the amount of distilled cumene from the cumene hydroperoxide mixture is added to the cumene hydroperoxide mixture before the reacting step b).

[0013] In another embodiment, a method for producing phenol and acetone from a cumene hydroperoxide mixture in a multi-stage process at an elevated temperature, comprises the steps of:

- a) adding an amount of phenol to the cumene hydroperoxide mixture and distilling the cumene from the cumene hydroperoxide mixture until the cumene mass% is 0 to 7 mass% relative to the total mass of the cumene hydroperoxide mixture,

- b) reacting the cumene hydroperoxide mixture with an acid catalyst to form a second mixture comprising dicumyl peroxide in a first stage, and
- c) decomposing the second mixture in a second stage to produce phenol and acetone.

[0014] In another embodiment, a method for producing phenol and acetone from a cumene hydroperoxide mixture in a multi-stage process at an elevated temperature, comprises the steps of:

- a) distilling an amount of cumene from the cumene hydroperoxide mixture,
- b) reacting the cumene hydroperoxide mixture with an acid catalyst to form a second mixture comprising dicumyl peroxide in a first stage, and
- c) decomposing the second mixture in a second stage to produce a third mixture comprising phenol, acetone, and hydroxyacetone,

wherein an amount of phenol approximately equal to the amount of cumene distilled from the cumene hydroperoxide mixture is added to the cumene hydroperoxide mixture before the reacting step b),

and wherein the amount of hydroxyacetone in the third mixture is less than or equal to 300 ppm.

BRIEF DESCRIPTION OF THE DRAWING

[0015] The Figure is a process flow diagram of an embodiment of the two-stage cleavage process of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0016] The inventors have found a way to further reduce the amount of hydroxyacetone in the decomposition products (phenol and acetone) of technical-grade CHP by adding an amount of phenol to the reaction prior to the decomposition step. The CHP concentration remains unchanged in the process, and the level or amount of hydroxyacetone in the decomposition products is reduced. This process forms CHP having a low level (less than 7.0 mass% residual cumene), which is then decomposed in a second step.

[0017] In embodiments, the reacting in the first stage is at a temperature of 47 to 50°C, and the decomposing in the second stage is at a temperature of 120 to 140°C.

[0018] As used herein, technical-grade cumene hydroperoxide (CHP) refers to CHP having a CHP concentration of 50 to 92 mass%, specifically 65 to 85 mass%, more specifically 80 to 84 mass%, relative to the total mass of the technical-grade CHP. The actual

CHP concentration is not critical, as long as the amount of cumene can be reduced to less than 7 mass% prior to the decomposition step.

[0019] The phenol can be added to the CHP mixture prior to the step of distilling the cumene from the cumene hydroperoxide mixture, during the distilling step, or after the distilling step, as long as it is added before the decomposition step. In an embodiment, the phenol is added to the CHP mixture just prior to the distilling step to facilitate cumene removal.

[0020] The low-cumene containing CHP resulting mixture is decomposed in two stages. The raw material (technical-grade CHP) is diluted in the first stage with acetone in an amount equal to 5 to 8 mass% relative to the amount of the supplied CHP, at a temperature of 47 to 50°C and a sulfuric acid concentration of 0.007 to 0.018 mass% relative to the amount of the supplied CHP. The volume in which the raw material CHP is fed must not exceed 10% of the volume of the circulating reaction mass while the circulation factor (ratio of the flow rate of the circulating mass to the flow rate of the raw material being fed) is kept at 8 to 50. Under these conditions, CHP decomposes to form phenol and acetone, and DCP is synthesized from CHP and DMPC, at a CHP conversion rate of 95 to 99.8%. An aqueous ammonia solution is added to the resulting reaction mass in an amount necessary to neutralize approximately half of the supplied sulfuric acid. Acetone is also added in an amount of 50 to 80 mass% relative to the acetone content of the reaction mixture. The partially neutralized and diluted reaction mass is fed to the second-stage reactor, where the remaining DCP is decomposed at 120 to 140°C.

[0021] While sulfuric acid is used as the catalyst in an embodiment, other catalysts may also be used. Examples of other catalysts include: hydroxy aromatic sulfonic acids or mixtures of hydroxy aromatic sulfonic acids. The hydroxy aromatic sulfonic acids may be made by, for example, a reaction of a phenol or para-cumyl phenol, with sulfuric acid (see, for example, US Patent Nos. 7,485,758 and 7,482,493). In an embodiment, the sulfuric acid used is a sulfuric acid solution comprising at least 75 wt.% sulfuric acid, specifically at least 90 wt.%, more specifically at least 90 to 95 wt.% sulfuric acid.

[0022] CHP oxidate formed in the cumene oxidation reactors has a concentration of 15 to 30 mass % CHP. By distillation (or stripping/concentrating), this mixture is concentrated by cumene removal to form technical-grade CHP having between 50 and 92 mass% CHP. It is important to maintain the cumene level in the technical-grade CHP at an optimum level, as low as possible or practical. In an embodiment, the cumene level is

maintained at a level of 0 to no more than 7.0 mass%. As required, this is accomplished by the addition of phenol in the distillation process and then removing additional cumene to the desired level. The amount of phenol added is approximately equal to the amount of cumene to be removed from the starting technical-grade CHP. The cumene level is maintained as low as possible. One skilled in the art will recognize that the lower the cumene level, the lower the resulting hydroxyacetone levels that can be achieved, but levels less than 5 mass% cumene are not as practical on a commercial scale.

[0023] Using technical-grade CHP, where the cumene level has been reduced to the desired level, for example, no more than 7.0 mass% cumene by distillation (stripping), it is possible to significantly reduce the hydroxyacetone yield, for example, 0.12 to 0.03 or even 0.02 mass% (1200 ppm to 300 ppm, or even 200 ppm), compared to methods where technical-grade CHP having higher levels (such as more than 12 mass%) of cumene is used the feed material to first stage cleavage. Reducing the level of hydroxyacetone has a marked effect on the quality of commercial-grade phenol, particularly the color of products made from the resulting phenol, such as bisphenol A and polycarbonate.

[0024] Concentration by distillation of the CHP oxidate from cumene oxidation reactors becomes more difficult as the mass% CHP increases due to safety concerns. To facilitate the safe concentration of CHP while reducing the residual cumene content to no more than 7.0 mass% cumene, phenol may be added prior to the final concentration step. Alternatively, phenol may be added after the residual cumene content has been reduced to no more than 7.0 mass%. Phenol substitution for cumene allows for lower reboiler temperatures and increased safety. The phenol is added prior to cleavage (decomposition step), but it is not critical when it is added and may be added at different times, as desired, as long as it has been added before cleavage (decomposition). In some embodiments, it is desired to add the phenol in the last concentration step. The amount of phenol added is approximately equal to the amount of cumene to be removed from the starting technical-grade CHP. For example, if 6 mass% cumene is to be removed from CHP having a starting cumene level of 13 mass%, therefore bringing the cumene level to 7 mass%, then 6 mass% phenol is added.

[0025] The Figure shows a process flow diagram of an embodiment of a typical two-stage CHP decomposition/cleavage process. In the first step, the raw material CHP (technical-grade CHP having a CHP level of 50 to 92 mass%) is fed to a first-stage reactor. In an embodiment, the first-stage reactor is a series of serially connected reactors, such as at least two serially connected reactors, specifically at least three serially connected reactors,

although a single reactor may also be used. Efficiency and heat transfer is improved with multiple reactors serially connected. Excess acetone and catalyst (such as sulfuric acid) are fed to the reactors. The CHP is diluted with the excess acetone in an amount equal to 5 to 8 mass% relative to the amount of the CHP in the feed stream. The stream is fed through the one or more reactors, and the catalyst is also fed into the stream to form the reaction mass. An aqueous ammonia solution is added to the resulting reaction mass to neutralize half of the supplied sulfuric acid. The partially neutralized and diluted reaction mass is fed to the second-stage reactor or reactors, where the remaining DCP is decomposed. In an embodiment, one reactor is used in the second stage, although more than one may be used if desired.

[0026] The method is illustrated by the following non-limiting examples.

EXAMPLES

Comparative Example (CEx)

[0027] A raw material for decomposition was prepared using technical-grade CHP by adding 21.7 g of acetone and 1.2 g of water to 250 g of the technical-grade CHP (having the composition shown in Table 1) form a mixture. The resulting mixture was used as a starting material to obtain phenol and acetone by CHP decomposition.

[0028] CHP was decomposed in a pilot unit composed of two reactors: a first-stage reactor having a volume of 12 mL, and a second-stage displacement reactor having a volume of 7 mL. The reaction mass from the first-stage reactor was partially fed to the second reactor and was partially returned to the inlet of the first reactor, whereby the reaction mass was circulated. The feed rate of the raw material (CHP) was 30 mL/h. Sulfuric acid was fed as a catalyst into the first reactor such that the sulfuric acid concentration in the reaction mass was maintained at 180 to 200 ppm of sulfuric acid on average. The circulation rate of the reaction mass was 500 mL/h. The reactor jacket was heated in order to maintain the temperature at 47 to 50°C. The stream exiting the first-stage reactor was fed to an intermediate vessel having a capacity of 5 mL, and a 1.64% ammonia solution and acetone were fed to the vessel at the rates of 25 μ L/h and 8 mL/h, respectively, to partially neutralize and dilute the reaction mass, such that approximately half of the sulfuric acid is neutralized. The partially neutralized and diluted reaction mass was fed to the second-stage reactor, which was heated to a temperature of 140°C. The stream exiting the second-stage reactor was cooled to room temperature, neutralized with sodium hydrocarbonate, and analyzed by gas

liquid chromatography. The hydroxyacetone content of the reaction mass was 0.12 mass% (1200 ppm).

Example 1 (Ex1)

[0029] 33 g of phenol was added to 250 g of technical-grade CHP having the composition shown in Table 1 to form a mixture. Cumene was distilled off from the resulting mixture at a residual pressure of 4 to 6 mm Hg. A fraction having a boiling point of 40 to 60°C and containing 99.04% of cumene, 0.9% of phenol, and 0.06% of methylstyrene (as indicated by the results of gas liquid chromatography) was obtained as a distillate in an amount of 33.5 g. The composition of the bottom product is shown in Table 2. To the resulting bottom product, 21.7 g of acetone and 1.2 g of water were added to form a mixture. The resulting mixture, which contained 0.88 mass% cumene, was used as a starting material to obtain phenol and acetone by CHP decomposition.

[0030] CHP was decomposed in a pilot unit composed of two reactors: a first-stage reactor having a volume of 12 mL, and a second-stage displacement reactor having a volume of 7 mL. The reaction mass from the first-stage reactor was partially fed to the second reactor and was partially returned to the inlet of the first reactor, whereby the reaction mass was circulated. The feed rate of the raw material (CHP) was 30 mL/h. Sulfuric acid was fed as a catalyst into the first reactor such that the sulfuric acid concentration in the reaction mass was maintained at 70 ppm of sulfuric acid on average. The circulation rate of the reaction mass was 500 mL/h. The reactor jacket was heated in order to maintain the temperature at 47 to 50°C. The stream exiting the first-stage reactor was fed to an intermediate vessel having a capacity of 5 mL, and a 1.64% ammonia solution and acetone were fed to the vessel at the rates of 10 µL/h and 8 mL/h, respectively, to partially neutralize and dilute the reaction mass, such that approximately half of the sulfuric acid is neutralized. The partially neutralized and diluted reaction mass was fed to the second-stage reactor, which was heated to a temperature of 140°C. The stream exiting the second-stage reactor was cooled to room temperature, neutralized with sodium hydrocarbonate, and analyzed by gas liquid chromatography. The hydroxyacetone content of the reaction mass was 0.02 mass% (200 ppm).

Table 1. Composition of the starting technical-grade CHP

Component	Composition, mass%
Cumene hydroperoxide	79.23
Cumene	12.86
Phenol	0.08
α -Methylstyrene	0.05
Acetophenone	1.14
Dimethyl phenyl carbinol	5.21
Dicumyl peroxide	0.77
Unidentified products	0.66

Table 2. Composition of bottom product of Example 1 after adding phenol and distilling off cumene

Component	Composition, mass%
Cumene hydroperoxide	78.36
Cumene	0.88
Phenol	13.1
α -Methylstyrene	0.08
Acetophenone	0.99
Dimethyl phenyl carbinol	5.06
Dicumyl peroxide	0.78
Unidentified products	0.75

Example 2 (Ex2)

[0031] In this example, only half as much phenol was added to the technical-grade CHP. 16.5 g of phenol was added to 250 g of technical-grade CHP (having the composition shown in Table 1). Residual cumene was removed using the same process as described in Example 1. As a result, a bottom product having the composition shown in Table 3 was obtained (which contained 6.87 mass% cumene).

[0032] Acetone was added to the resulting bottom product in the same amounts as in Example 1, and decomposition was carried out under the conditions described in Example 1.

The hydroxyacetone content of the resulting decomposition mass was 0.03 mass% (300 ppm).

Table 3. Composition of bottom product of Example 2 after adding phenol and distilling cumene

Component	Composition, mass%
Cumene hydroperoxide	78.8
Cumene	6.87
Phenol	6.59
α -Methylstyrene	0.06
Acetophenone	1.06
Dimethyl phenyl carbinol	5.13
Dicumyl peroxide	0.78
Unidentified products	0.70

[0033] The Examples and Tables show that when cumene is first removed from technical-grade CHP before cleavage (using the two-step process) into phenol and acetone, there was a significant reduction of hydroxyacetone yield. In the Comparative Example, no phenol was added to the starting raw material (technical-grade CHP), while in Examples 1 and 2, phenol was added (33 g in Example 1, and 16.5 g in Example 2, to 250 g of CHP starting material, with a cumene content of 32.2 g). The addition of the phenol significantly reduced the level of hydroxyacetone in the final product, as shown in Table 4. Although twice as much phenol was added in Example 1 compared to Example 2, the reduction in the level of hydroxyacetone was much less than the reduction seen from the Comparative Example to Example 2.

Table 4. Yield of Hydroxyacetone (when comparing added phenol).

	Cumene (g)	Phenol (g)	Mass% Hydroxyacetone	ppm Hydroxyacetone
CEx	32.2	0	0.12	1200
Ex2	32.2	16.5	0.03	300
Ex1	32.2	33.0	0.02	200

[0034] The Examples were performed in at laboratory scale, but they are intended to represent a plant setting with varying configurations and numbers of reactors. Examples of varying configurations may include, but are not limited to, a cumene stripping operation, varying number of columns used for distillation, such as a single reactor or multiple columns in series, oxidation of cumene to form CHP prior to distillation, and the like. One skilled in the art will appreciate the varying configurations that may be used to achieve the same outcome.

[0035] While the invention has been described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims. One skilled in the art would recognize that in a reaction conducted using a feedstock of a different composition than the starting composition used in the experiments, the results may differ from those given in the Examples of the present invention, but the positive effect of using this invention would be retained.

CLAIMS

1. A method for producing phenol and acetone in a multi-stage process at an elevated temperature from a cumene hydroperoxide mixture comprising cumene, the method comprising the steps of:

- a) distilling an amount of cumene from the cumene hydroperoxide mixture until the cumene mass% is 0 to 7 mass% relative to the total mass of the cumene hydroperoxide mixture,
- b) reacting the cumene hydroperoxide mixture with an acid catalyst form to a second mixture comprising phenol, acetone and dicumyl peroxide in a first stage, and
- c) decomposing the second mixture in a second stage to produce phenol and acetone, wherein an amount of phenol approximately equal to the amount of distilled from the cumene hydroperoxide mixture is added to the cumene hydroperoxide mixture before the reacting step b).

2. The method of claim 1, wherein the reacting in the first stage is at a temperature of 47 to 50°C, and the decomposing in the second stage is at a temperature of 120 to 140°C.

3. The method of claim 1 or 2, wherein the acid catalyst is sulfuric acid.

4. The method of claim 1, 2, or 3, wherein the cumene hydroperoxide mixture comprises between 50 mass% and 92 mass% cumene hydroperoxide relative to the total mass of the cumene hydroperoxide mixture.

5. The method of claim 1, 2, or 3, wherein the cumene hydroperoxide mixture comprises between 65 mass% and 85 mass% cumene hydroperoxide relative to the total mass of the cumene hydroperoxide mixture.

6. The method of claim 1, 2, or 3, wherein the cumene hydroperoxide mixture comprises between 80 mass% and 84 mass% cumene hydroperoxide relative to the total mass of the cumene hydroperoxide mixture.

7. The method of any of claims 1-6, wherein the step of reacting the cumene hydroperoxide is in at least two serially connected reactors.

8. A method for producing phenol and acetone from a cumene hydroperoxide mixture in a multi-stage process at an elevated temperature, the method comprising the steps of:

- a) adding an amount of phenol to the cumene hydroperoxide mixture and distilling the cumene from the cumene hydroperoxide mixture until the cumene mass% is 0 to 7 mass% relative to the total mass of the cumene hydroperoxide mixture,

b) reacting the cumene hydroperoxide mixture with an acid catalyst to form a second mixture comprising dicumyl peroxide in a first stage, and

c) decomposing the second mixture in a second stage to produce phenol and acetone.

9. The method of claim 8, wherein the reacting in the first stage is at a temperature of 47 to 50°C, and the decomposing in the second stage is at a temperature of 120 to 140°C.

10. The method of claim 8 or 9, wherein the acid catalyst is sulfuric acid.

11. The method of any of claims 8 - 10, wherein the step of reacting the cumene hydroperoxide is in at least two serially connected reactors.

12. A method for producing phenol and acetone in a multi-stage process at an elevated temperature from a cumene hydroperoxide mixture comprising cumene, the method comprising the steps of:

a) distilling an amount of cumene from the cumene hydroperoxide mixture,

b) reacting the cumene hydroperoxide mixture with an acid catalyst to form a second mixture comprising dicumyl peroxide in a first stage, and

c) decomposing the second mixture in a second stage to produce a third mixture comprising phenol, acetone, and hydroxyacetone,

wherein an amount of phenol approximately equal to the amount of cumene distilled from the cumene hydroperoxide mixture is added to the cumene hydroperoxide mixture before the reacting step b),


and wherein the amount of hydroxyacetone in the third mixture is less than or equal to 300 ppm.

13. The method of claim 12, wherein the reacting in the first stage is at a temperature of 47 to 50°C, and the decomposing in the second stage is at a temperature of 120 to 140°C.

14. The method of claim 12 or 13, wherein the amount of hydroxyacetone in the third mixture is less than or equal to 200 ppm.

15. The method of claim 12, 13, or 14, wherein the cumene mass% in the cumene hydroperoxide is reduced in the distilling step to 0 to 7 mass% relative to the total mass of the cumene hydroperoxide mixture

FIGURE – 2-Stage Cleavage Process Flow



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2009/040804

A. CLASSIFICATION OF SUBJECT MATTER

INV. C07C37/08 C07C45/53 C07C39/04 C07C49/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, BEILSTEIN Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 057 483 A (ZAKOSHANSKY VLADIMIR MIKHAILOV [US] ET AL) 2 May 2000 (2000-05-02) cited in the application claims 1,3,8 example 3 page 11; tables 1, 2; entry 3	1-15
A	GB 721 700 A (RHONE POULENC SA) 12 January 1955 (1955-01-12) claims 1,4-6 page 2, lines 69-80 page 3; examples I,II ----- -/--	1-15

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

16 June 2009

Date of mailing of the international search report

26/06/2009

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Guazzelli, Giuditta

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2009/040804

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2005/097720 A (GEN ELECTRIC [US]; TATAKE PRASHANT ANIL [IN]; KUMBHAR PRAMOD SHANKAR []) 20 October 2005 (2005-10-20) claims 1,3 page 8; table 1 page 8, lines 1,2 -----	1-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2009/040804

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6057483	A	02-05-2000	RU 2142932 C1	20-12-1999
GB 721700	A	12-01-1955	NONE	
WO 2005097720	A	20-10-2005	CN 1938250 A	28-03-2007
			EP 1732869 A1	20-12-2006
			KR 20070002039 A	04-01-2007
			US 2005222466 A1	06-10-2005