



US012225475B2

(12) **United States Patent**
Abdelmonem et al.

(10) **Patent No.:** **US 12,225,475 B2**

(45) **Date of Patent:** ***Feb. 11, 2025**

(54) **METHOD AND APPARATUS FOR INCREASING PERFORMANCE OF COMMUNICATION LINKS OF COOPERATIVE COMMUNICATION NODES**

(52) **U.S. Cl.**
CPC **H04W 52/241** (2013.01); **H04J 11/005** (2013.01); **H04J 11/0066** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **H04W 52/241**; **H04W 52/243**; **H04W 72/541**; **H04W 72/542**; **H04W 24/02**;
(Continued)

(71) Applicant: **ISCO International, LLC**,
Schaumburg, IL (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,732,500 A 5/1973 Dishal
3,781,705 A 12/1973 Dishal
(Continued)

(72) Inventors: **Amr Abdelmonem**, Northbrook, IL (US); **Jorge Seoane**, Algonquin, IL (US); **Mikhail Galeev**, Palatine, IL (US); **Krishna Komoravolu**, Aurora, IL (US); **Zhigang Wang**, Batavia, IL (US); **Gordon Reichard, Jr.**, Inverness, IL (US)

FOREIGN PATENT DOCUMENTS

CA 2260653 1/2000
CA 2288633 4/2000
(Continued)

(73) Assignee: **ISCO International, LLC**,
Schaumburg, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

International Preliminary Report on Patentability for PCT/US2019/030835 mailed Feb. 18, 2021; pp. 1-7.

(Continued)

(21) Appl. No.: **18/528,049**

(22) Filed: **Dec. 4, 2023**

Primary Examiner — Gbemileke J Onamuti

(74) *Attorney, Agent, or Firm* — Guntin & Gust, PLC;
Ralph Trementozzi

(65) **Prior Publication Data**

US 2024/0121723 A1 Apr. 11, 2024

(57) **ABSTRACT**

A system that incorporates aspects of the subject disclosure may perform operations including, for example, monitoring performance parameters in a communications network, identifying a degradation in performance of one or more nodes of the communications network according to the monitored performance parameters, and initiating corrective action to mitigate the degradation in performance of the one or more nodes of the communications network. Other embodiments are disclosed.


Related U.S. Application Data

(63) Continuation of application No. 18/148,640, filed on Dec. 30, 2022, now Pat. No. 11,877,247, which is a (Continued)

(51) **Int. Cl.**
H04W 24/08 (2009.01)
H04J 11/00 (2006.01)

(Continued)

20 Claims, 27 Drawing Sheets



Related U.S. Application Data

continuation of application No. 17/153,499, filed on Jan. 20, 2021, now Pat. No. 11,570,719, which is a continuation of application No. 16/744,688, filed on Jan. 16, 2020, now Pat. No. 10,959,185, which is a continuation of application No. 16/242,665, filed on Jan. 8, 2019, now Pat. No. 10,575,260, which is a continuation of application No. 16/020,076, filed on Jun. 27, 2018, now Pat. No. 10,231,190, which is a continuation of application No. 15/688,010, filed on Aug. 28, 2017, now Pat. No. 10,039,061, which is a continuation of application No. 14/690,765, filed on Apr. 20, 2015, now Pat. No. 9,775,116.

- (60) Provisional application No. 61/988,712, filed on May 5, 2014, provisional application No. 62/010,305, filed on Jun. 10, 2014, provisional application No. 62/091,033, filed on Dec. 12, 2014.

(51) **Int. Cl.**

H04L 5/00 (2006.01)
H04W 24/02 (2009.01)
H04W 24/10 (2009.01)
H04W 52/24 (2009.01)
H04W 72/08 (2009.01)
H04W 72/541 (2023.01)
H04W 72/542 (2023.01)
H04W 88/08 (2009.01)

(52) **U.S. Cl.**

CPC **H04L 5/0021** (2013.01); **H04L 5/0023** (2013.01); **H04L 5/006** (2013.01); **H04L 5/0073** (2013.01); **H04W 24/02** (2013.01); **H04W 24/08** (2013.01); **H04W 24/10** (2013.01); **H04W 52/243** (2013.01); **H04W 72/541** (2023.01); **H04W 72/542** (2023.01); **H04W 88/08** (2013.01)

(58) **Field of Classification Search**

CPC H04W 24/08; H04W 24/10; H04J 11/005; H04J 11/0066; H04L 5/0021; H04L 5/0023; H04L 5/0006; H04L 5/0073
 USPC 370/329
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,783,397 A 1/1974 Dishal
 3,887,222 A 6/1975 Hammond
 3,911,366 A 10/1975 Baghdady
 4,027,264 A 5/1977 Gutleber
 4,137,532 A 1/1979 Taylor et al.
 4,328,591 A 5/1982 Baghdady
 4,513,249 A 4/1985 Baghdady
 4,648,124 A 3/1987 Denny et al.
 4,712,235 A 12/1987 Jones
 4,761,829 A 8/1988 Lynk et al.
 4,859,958 A 8/1989 Myers
 4,992,747 A 2/1991 Myers
 5,038,115 A 8/1991 Myers
 5,038,145 A 8/1991 DeCesare et al.
 5,048,015 A 9/1991 Zilberfarb
 5,168,508 A 12/1992 Iwasaki
 5,185,762 A 2/1993 Schilling
 5,226,057 A 7/1993 Boren
 5,263,048 A 11/1993 Wade
 5,282,023 A 1/1994 Scarpa
 5,301,197 A 4/1994 Yamada et al.
 5,303,413 A 4/1994 Braegas
 5,307,517 A 4/1994 Rich

5,325,204 A 6/1994 Scarpa
 5,339,184 A 8/1994 Tang
 5,343,496 A 8/1994 Honig
 5,381,150 A 1/1995 Hawkins et al.
 5,475,868 A 12/1995 Duque-Anton et al.
 5,497,505 A 3/1996 Koohgoli et al.
 5,500,872 A 3/1996 Kinney
 5,541,959 A 7/1996 Myers
 5,570,350 A 10/1996 Myer
 5,596,600 A 1/1997 Dimos
 5,640,146 A 6/1997 Campana
 5,640,385 A 6/1997 Long
 RE35,650 E 11/1997 Partyka
 5,703,874 A 12/1997 Schilling
 5,721,733 A 2/1998 Wang et al.
 5,731,993 A 3/1998 Wachs et al.
 5,757,246 A 5/1998 Johnson et al.
 5,758,275 A 5/1998 Cox
 5,822,373 A 10/1998 Addy
 5,838,742 A 11/1998 Abu-Dayya
 5,852,630 A 12/1998 Langberg
 5,857,143 A 1/1999 Kataoka
 5,926,761 A 7/1999 Reed et al.
 5,947,505 A 9/1999 Martin
 5,949,368 A 9/1999 DeCesare
 5,960,329 A 9/1999 Ganesh et al.
 5,966,657 A 10/1999 Sporre
 5,970,105 A 10/1999 Dacus
 5,974,101 A 10/1999 Nago
 5,978,362 A 11/1999 Lee
 5,991,273 A 11/1999 Abu-Dayya et al.
 5,999,574 A 12/1999 Sun et al.
 6,005,899 A 12/1999 Khayrallah
 6,009,129 A 12/1999 Kenney et al.
 6,020,783 A 2/2000 Coppola
 6,035,213 A 3/2000 Tokuda
 6,038,250 A 3/2000 Shou et al.
 6,047,175 A 4/2000 Trompower
 6,052,158 A 4/2000 Nielsen
 6,104,934 A 8/2000 Patton
 6,115,409 A 9/2000 Upadhyay
 6,115,580 A 9/2000 Chuprun et al.
 6,118,805 A 9/2000 Bergstrom et al.
 6,122,309 A 9/2000 Bergstrom et al.
 6,125,139 A 9/2000 Hendrickson et al.
 6,127,962 A 10/2000 Martinson
 6,130,907 A 10/2000 Chen
 6,133,942 A 10/2000 Lee
 6,167,240 A 12/2000 Carlsson et al.
 6,167,244 A 12/2000 Tomoe
 6,205,334 B1 3/2001 Dent
 6,208,629 B1 3/2001 Jaszewski et al.
 6,215,812 B1 4/2001 Young
 6,289,004 B1 9/2001 Mesecher et al.
 6,313,620 B1 11/2001 Richardson
 6,327,245 B1 12/2001 Satyanarayana et al.
 6,327,312 B1 12/2001 Jovanovich
 6,360,077 B2 3/2002 Mizoguchi
 6,377,606 B1 4/2002 Toskala et al.
 6,393,284 B1 5/2002 Dent
 6,400,306 B1 6/2002 Nohara et al.
 6,405,043 B1 6/2002 Jensen et al.
 6,421,077 B1 7/2002 Reed et al.
 6,426,983 B1 7/2002 Rakib et al.
 6,430,164 B1 8/2002 Jones
 6,470,047 B1 10/2002 Kleinerman et al.
 6,490,460 B1 12/2002 Soliman
 6,577,670 B1 6/2003 Roberts
 6,580,899 B1 6/2003 Dalgleish et al.
 6,590,833 B1 7/2003 Teller
 6,621,454 B1 9/2003 Reudink et al.
 6,631,264 B1 10/2003 Tat et al.
 6,631,266 B1 10/2003 Lee et al.
 6,671,338 B1 12/2003 Gamal et al.
 6,678,520 B1 1/2004 Wang et al.
 6,704,378 B2 3/2004 Jagger
 6,718,166 B2 4/2004 Cordone
 6,791,995 B1 9/2004 Azenkot et al.
 6,807,405 B1 10/2004 Jagger

(56)

References Cited

U.S. PATENT DOCUMENTS

6,843,819 B2	1/2005	Suzuki et al.	10,327,255 B2	6/2019	Abdelmonem et al.
6,850,764 B1	2/2005	Patel	10,517,101 B2	12/2019	Abdelmonem et al.
6,920,424 B2	7/2005	Padmanabhan	10,609,582 B2	3/2020	Hannan et al.
6,959,170 B2	10/2005	Vannatta	10,609,651 B2	3/2020	Abdelmonem et al.
6,975,673 B1	12/2005	Rouquette et al.	10,652,835 B2	5/2020	Tacconi et al.
6,976,044 B1	12/2005	Kilani	10,652,901 B2	5/2020	Galeev et al.
7,003,310 B1	2/2006	Youssefmir et al.	10,834,684 B2	11/2020	Abdelmonem et al.
7,031,266 B1	4/2006	Patel et al.	10,880,901 B2	12/2020	Abdelmonem et al.
7,054,396 B2	5/2006	Shan	10,952,155 B2	3/2021	Tacconi et al.
7,089,008 B1	8/2006	Bäck et al.	2001/0046867 A1	11/2001	Mizoguchi
7,103,316 B1	9/2006	Hall	2002/0057751 A1	5/2002	Jagger
7,215,659 B1	5/2007	Chen et al.	2002/0110206 A1	8/2002	Becker et al.
7,317,698 B2	1/2008	Jagger	2002/0155812 A1	10/2002	Takada
7,346,134 B2	3/2008	Smith	2002/0159506 A1	10/2002	Alamouti et al.
7,359,691 B2	4/2008	Adachi et al.	2002/0173272 A1	11/2002	Liang et al.
7,408,907 B2	8/2008	Diener et al.	2002/0173341 A1	11/2002	Abdelmonem et al.
7,424,002 B2	9/2008	Barratt et al.	2002/0193140 A1	12/2002	Behrens et al.
7,424,268 B2	9/2008	Diener et al.	2003/0081277 A1	5/2003	Corbeil et al.
7,457,382 B1	11/2008	Jones	2003/0123530 A1	7/2003	Maeda
7,477,915 B2	1/2009	Leinonen et al.	2003/0142759 A1	7/2003	Anderson et al.
7,525,942 B2	4/2009	Cordone	2003/0193366 A1	10/2003	Barksdale
7,656,936 B2	2/2010	Li et al.	2003/0216122 A1	11/2003	Cordone
7,903,024 B2	3/2011	Tietjen et al.	2004/0042561 A1	3/2004	Ho et al.
7,929,953 B2	4/2011	Jiang	2004/0048574 A1	3/2004	Walker et al.
8,054,088 B2	11/2011	Delforce et al.	2004/0088637 A1	5/2004	Wada
8,055,191 B2	11/2011	Unger	2004/0160927 A1	8/2004	Yang et al.
8,098,748 B1	1/2012	Mansour et al.	2004/0162093 A1	8/2004	Bevan et al.
8,219,105 B2	7/2012	Kronstedt et al.	2004/0198451 A1	10/2004	Varghese
8,229,368 B1	7/2012	Immendorf et al.	2004/0202136 A1	10/2004	Attar et al.
8,238,954 B2	8/2012	Liu et al.	2004/0223484 A1	11/2004	Xia et al.
8,290,503 B2	10/2012	Sadek et al.	2005/0078734 A1	4/2005	Baker
8,412,256 B2	4/2013	Lee et al.	2005/0117676 A1	6/2005	Liu
8,422,469 B2	4/2013	Guvenc	2005/0201498 A1	9/2005	Nakai
8,478,342 B2	7/2013	Vedantham et al.	2005/0271009 A1	12/2005	Shirakabe et al.
8,483,741 B1	7/2013	Hussain et al.	2006/0025127 A1	2/2006	Cromer et al.
8,503,938 B2	8/2013	Laroia et al.	2006/0068849 A1	3/2006	Bernhard et al.
8,583,170 B2	11/2013	Sundström et al.	2006/0094372 A1	5/2006	Ahn et al.
8,605,686 B2	12/2013	Lundby et al.	2006/0105769 A1	5/2006	Flondro et al.
8,694,017 B2	4/2014	Bhushan	2006/0136603 A1	6/2006	Morvan et al.
8,718,024 B2	5/2014	Jagger et al.	2006/0153283 A1	7/2006	Scharf et al.
8,767,576 B2	7/2014	Aguiire et al.	2006/0171445 A1	8/2006	Batra et al.
8,781,044 B2	7/2014	Cordone et al.	2006/0183493 A1	8/2006	Ma et al.
8,811,213 B1	8/2014	Rai et al.	2006/0210001 A1	9/2006	Li et al.
8,811,552 B2	8/2014	Bayesteh et al.	2006/0211389 A1	9/2006	Lin et al.
8,874,125 B2	10/2014	Khojastepour et al.	2006/0246938 A1	11/2006	Hulkkonen et al.
8,942,117 B2	1/2015	Tamaki et al.	2007/0014254 A1	1/2007	Chung et al.
8,970,426 B1	3/2015	Stockmann et al.	2007/0025455 A1	2/2007	Greenwood et al.
8,989,235 B2	3/2015	Myers et al.	2007/0047494 A1	3/2007	Cordone
8,989,954 B1	3/2015	Addepalli et al.	2007/0091896 A1	4/2007	Liu
9,008,680 B2	4/2015	Abdelmonem	2007/0105520 A1	5/2007	Van Houtum
9,042,497 B2	5/2015	Wong et al.	2007/0115878 A1	5/2007	Ashish et al.
9,071,343 B2	6/2015	Abdelmonem	2007/0129071 A1	6/2007	Shapira et al.
9,209,857 B2	12/2015	Galeev et al.	2007/0173252 A1	7/2007	Jiang
9,226,303 B2	12/2015	Kronstedt	2007/0178914 A1	8/2007	Montenegro
9,231,650 B2	1/2016	Abdelmonem et al.	2007/0183483 A1	8/2007	Narayan
9,369,909 B2	6/2016	Wong et al.	2007/0189225 A1	8/2007	Qian et al.
9,397,923 B2	7/2016	Otonari et al.	2007/0197251 A1	8/2007	Das et al.
9,413,677 B1	8/2016	Vargantwar et al.	2007/0207740 A1	9/2007	Dickey
9,438,285 B2	9/2016	Wyville et al.	2007/0258411 A1	11/2007	Trigui
9,521,603 B2	12/2016	Yamazaki et al.	2007/0274279 A1	11/2007	Wood
9,548,775 B2	1/2017	Smith	2008/0040037 A1	2/2008	De et al.
9,642,155 B2	5/2017	Sandrasegaran et al.	2008/0043612 A1	2/2008	Geile
9,647,720 B2	5/2017	Abdelmonem et al.	2008/0043657 A1	2/2008	Ishii et al.
9,654,170 B2	5/2017	Abdelmonem et al.	2008/0081655 A1	4/2008	Shin et al.
9,668,223 B2	5/2017	Abdelmonem et al.	2008/0089296 A1	4/2008	Kazmi et al.
9,729,301 B2	8/2017	Galeev et al.	2008/0107217 A1	5/2008	Vrcelj et al.
9,742,547 B2	8/2017	Wang et al.	2008/0160916 A1	7/2008	Jagger et al.
9,768,812 B1	9/2017	Tsui et al.	2008/0166976 A1	7/2008	Rao et al.
9,814,044 B1	11/2017	Sevindik	2008/0176519 A1	7/2008	Kwak et al.
9,853,747 B2	12/2017	Shariat et al.	2008/0205500 A1	8/2008	C-liu et al.
10,079,667 B2	9/2018	Galeev et al.	2008/0285526 A1	11/2008	Gorokhov et al.
10,117,142 B2	10/2018	Padfield et al.	2008/0292032 A1	11/2008	Belogolovy et al.
10,244,483 B2	3/2019	Abdelmonem et al.	2008/0304553 A1	12/2008	Zhao et al.
10,284,257 B2	5/2019	Maxson et al.	2009/0082053 A1	3/2009	Wei et al.
10,314,052 B2	6/2019	Anderson et al.	2009/0086841 A1	4/2009	Guo et al.
			2009/0096662 A1	4/2009	Wang et al.
			2009/0131067 A1	5/2009	Aaron et al.
			2009/0161614 A1	6/2009	Grandblaise
			2009/0233544 A1	9/2009	Oyman et al.

(56)		References Cited	
U.S. PATENT DOCUMENTS			
2009/0233568	A1	9/2009	Zhang
2009/0245331	A1	10/2009	Palanki et al.
2009/0245409	A1	10/2009	Kandukuri Narayan et al.
2009/0247107	A1	10/2009	Roy et al.
2009/0290632	A1	11/2009	Wegener
2009/0310561	A1	12/2009	Grob et al.
2009/0325509	A1	12/2009	Mattisson et al.
2010/0002575	A1	1/2010	Eichinger et al.
2010/0029289	A1	2/2010	Love et al.
2010/0046374	A1	2/2010	Ludwig et al.
2010/0054373	A1	3/2010	Reial et al.
2010/0061244	A1	3/2010	Meier et al.
2010/0075709	A1	3/2010	Nakano et al.
2010/0085884	A1	4/2010	Srinivasan et al.
2010/0098051	A1	4/2010	Uemura
2010/0099415	A1	4/2010	Li et al.
2010/0099449	A1	4/2010	Borran et al.
2010/0118921	A1	5/2010	Abdelmonem et al.
2010/0119020	A1	5/2010	Bhukania et al.
2010/0157934	A1	6/2010	Tanno et al.
2010/0159858	A1	6/2010	Dent et al.
2010/0167778	A1	7/2010	Raghothaman et al.
2010/0202400	A1	8/2010	Richardson
2010/0214931	A1	8/2010	Wigren
2010/0220670	A1	9/2010	Teo et al.
2010/0220780	A1	9/2010	Peng et al.
2010/0227613	A1	9/2010	Kim et al.
2010/0227637	A1	9/2010	Kwon et al.
2010/0246503	A1	9/2010	Fox et al.
2010/0246512	A1	9/2010	Kawamura et al.
2010/0248736	A1	9/2010	Hulkkonen et al.
2010/0254292	A1	10/2010	Kim et al.
2010/0255868	A1	10/2010	Lee et al.
2010/0267408	A1	10/2010	Lee et al.
2010/0279724	A1	11/2010	Li et al.
2010/0303183	A1	12/2010	Desai
2010/0304681	A1	12/2010	Ghassemzadeh et al.
2010/0304742	A1	12/2010	Tsuda
2010/0309864	A1	12/2010	Tamaki et al.
2010/0310026	A1	12/2010	Sikri et al.
2010/0315970	A1	12/2010	Ramamurthi et al.
2010/0330919	A1	12/2010	Gurney et al.
2011/0014938	A1	1/2011	Shekalim
2011/0032849	A1	2/2011	Yeung et al.
2011/0044188	A1	2/2011	Luo et al.
2011/0045856	A1	2/2011	Feng et al.
2011/0075754	A1	3/2011	Smith et al.
2011/0096703	A1	4/2011	Nentwig et al.
2011/0110251	A1	5/2011	Krishnamurthy et al.
2011/0117967	A1	5/2011	Vedantham et al.
2011/0130098	A1	6/2011	Madan et al.
2011/0136497	A1	6/2011	Youtz et al.
2011/0143656	A1	6/2011	Dankberg et al.
2011/0149764	A1	6/2011	Wietfeldt et al.
2011/0164659	A1	7/2011	Kawamura et al.
2011/0170440	A1	7/2011	Gaal et al.
2011/0183679	A1	7/2011	Moon et al.
2011/0188544	A1	8/2011	Ponnuswamy et al.
2011/0200126	A1	8/2011	Bontu et al.
2011/0217947	A1	9/2011	Czaja et al.
2011/0222591	A1	9/2011	Furudate et al.
2011/0244905	A1	10/2011	Burstroem et al.
2011/0258678	A1	10/2011	Cowling et al.
2011/0275399	A1	11/2011	Englund et al.
2011/0305306	A1	12/2011	Hu et al.
2011/0310747	A1	12/2011	Seo et al.
2012/0021753	A1	1/2012	Damnjanovic et al.
2012/0028663	A1	2/2012	Nejatian et al.
2012/0032854	A1	2/2012	Bull et al.
2012/0051315	A1	3/2012	Wang et al.
2012/0069806	A1	3/2012	Norlén et al.
2012/0082050	A1	4/2012	Lysejko et al.
2012/0082055	A1	4/2012	Seyama
2012/0083218	A1	4/2012	Gossain et al.
2012/0088535	A1	4/2012	Wang et al.
2012/0094702	A1	4/2012	Furueda et al.
2012/0113844	A1	5/2012	Krishnamurthy
2012/0122495	A1	5/2012	Weng et al.
2012/0134280	A1	5/2012	Rotvold et al.
2012/0135763	A1	5/2012	Johnsson et al.
2012/0149413	A1	6/2012	Pedersen et al.
2012/0163223	A1	6/2012	Lo et al.
2012/0164950	A1	6/2012	Nentwig et al.
2012/0182857	A1	7/2012	Bertrand et al.
2012/0182930	A1	7/2012	Sawai et al.
2012/0195216	A1	8/2012	Wu et al.
2012/0207038	A1	8/2012	Choi et al.
2012/0213116	A1	8/2012	Koo et al.
2012/0236731	A1	9/2012	Beaudin
2012/0276937	A1	11/2012	Astely et al.
2012/0281731	A1	11/2012	Jagger et al.
2012/0282889	A1	11/2012	Tanaka et al.
2012/0282943	A1	11/2012	Hsiao et al.
2012/0295558	A1	11/2012	Wang et al.
2012/0307770	A1	12/2012	Kubota
2012/0315935	A1	12/2012	Wang Helmersson et al.
2012/0322453	A1	12/2012	Weng et al.
2012/0327822	A1	12/2012	Arakawa
2013/0012134	A1	1/2013	Jin et al.
2013/0012138	A1	1/2013	Zhang et al.
2013/0017794	A1	1/2013	Kloper et al.
2013/0029658	A1	1/2013	Jagger et al.
2013/0051317	A1	2/2013	Ji et al.
2013/0058300	A1	3/2013	Perets et al.
2013/0071112	A1	3/2013	Melester et al.
2013/0077670	A1	3/2013	Wang et al.
2013/0090125	A1	4/2013	Clifton et al.
2013/0094374	A1	4/2013	Zhou et al.
2013/0095846	A1	4/2013	Brisebois et al.
2013/0107737	A1	5/2013	Lee et al.
2013/0115988	A1	5/2013	Sun et al.
2013/0115998	A1	5/2013	Lamm et al.
2013/0115999	A1	5/2013	Sirotkin et al.
2013/0142136	A1	6/2013	Pi et al.
2013/0142288	A1	6/2013	Dinan
2013/0143592	A1	6/2013	Brisebois et al.
2013/0150106	A1	6/2013	Bucknell et al.
2013/0163570	A1	6/2013	Zhang et al.
2013/0165169	A1	6/2013	Lee et al.
2013/0170574	A1	7/2013	Fleming et al.
2013/0170829	A1	7/2013	Khatana
2013/0171955	A1	7/2013	Makhlouf et al.
2013/0173802	A1	7/2013	Saffre et al.
2013/0194982	A1	8/2013	Fwu et al.
2013/0242791	A1	9/2013	Lim et al.
2013/0242939	A1	9/2013	Wagner
2013/0250885	A1	9/2013	Davydov et al.
2013/0260807	A1	10/2013	Suresh et al.
2013/0287077	A1	10/2013	Fernando et al.
2013/0310023	A1	11/2013	Bevan et al.
2013/0316710	A1	11/2013	Maaref et al.
2013/0343291	A1	12/2013	Gao et al.
2014/0004866	A1	1/2014	Dalsgaard et al.
2014/0029524	A1	1/2014	Dimou et al.
2014/0059103	A1	2/2014	Kawabata
2014/0071933	A1	3/2014	Lee et al.
2014/0086191	A1	3/2014	Berntsen et al.
2014/0086367	A1	3/2014	Azadet et al.
2014/0098695	A1	4/2014	Jeong et al.
2014/0105136	A1	4/2014	Tellado et al.
2014/0105262	A1	4/2014	Alloin et al.
2014/0106695	A1	4/2014	Luz et al.
2014/0106697	A1	4/2014	Wang et al.
2014/0126403	A1	5/2014	Siomina
2014/0153418	A1	6/2014	Hariharan et al.
2014/0153433	A1	6/2014	Zhou
2014/0160955	A1	6/2014	Lum et al.
2014/0169232	A1	6/2014	Aggarwal et al.
2014/0169279	A1	6/2014	Song et al.
2014/0170965	A1	6/2014	Li et al.
2014/0187255	A1	7/2014	Dimou et al.
2014/0206339	A1	7/2014	Lindoff et al.
2014/0212129	A1	7/2014	Huang et al.
2014/0218255	A1	8/2014	Sanford et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0241293	A1	8/2014	Luo et al.	2017/0064571	A1	3/2017	Kusashima et al.
2014/0256322	A1	9/2014	Zhou et al.	2017/0064576	A1	3/2017	Kusashima et al.
2014/0269318	A1	9/2014	Hasarchi et al.	2017/0104522	A1	4/2017	Zinevich
2014/0269374	A1	9/2014	Abdelmonem et al.	2017/0118758	A1	4/2017	Li
2014/0269850	A1	9/2014	Abdelmonem et al.	2017/0126298	A1	5/2017	Einhaus et al.
2014/0274094	A1	9/2014	Abdelmonem et al.	2017/0188363	A1	6/2017	Ellinikos et al.
2014/0274100	A1	9/2014	Galeev et al.	2017/0188374	A1	6/2017	Galeev
2014/0315593	A1	10/2014	Vrzic et al.	2017/0196013	A1	7/2017	Shin et al.
2014/0378077	A1	12/2014	Din	2017/0207816	A1	7/2017	Abdelmonem et al.
2015/0071239	A1	3/2015	Zhang et al.	2017/0215096	A1	7/2017	Moon et al.
2015/0092621	A1	4/2015	Jalloul	2017/0215197	A1	7/2017	Sagong et al.
2015/0099527	A1	4/2015	Zhuang	2017/0230128	A1	8/2017	Abdelmonem et al.
2015/0105903	A1	4/2015	Denny et al.	2017/0230983	A1	8/2017	Abdelmonem et al.
2015/0212210	A1	7/2015	Hwang	2017/0272185	A1	9/2017	Reddy
2015/0222371	A1	8/2015	Afkhami et al.	2017/0280464	A1	9/2017	Jagger
2015/0236814	A1	8/2015	Liu et al.	2017/0289011	A1	10/2017	Johnsson et al.
2015/0236882	A1	8/2015	Bertrand et al.	2017/0294994	A1	10/2017	Shor et al.
2015/0244413	A1	8/2015	Baudin et al.	2017/0302332	A1	10/2017	Abdelmonem et al.
2015/0249965	A1	9/2015	Dussmann et al.	2017/0310450	A1	10/2017	Galeev
2015/0249998	A1	9/2015	Long et al.	2017/0317807	A1	11/2017	Abdelmonem et al.
2015/0257165	A1	9/2015	Gale et al.	2017/0324469	A1	11/2017	Jalali
2015/0263844	A1	9/2015	Kinnunen	2017/0353929	A1	12/2017	Tacconi et al.
2015/0264703	A1	9/2015	Ratasuk et al.	2017/0374625	A1	12/2017	Abdelmodem et al.
2015/0280840	A1	10/2015	Li	2017/0374626	A1	12/2017	Abdelmonem et al.
2015/0280848	A1	10/2015	Castelain	2018/0020462	A1	1/2018	Xiong et al.
2015/0282206	A1	10/2015	Kalhan et al.	2018/0063799	A1	3/2018	Sadek et al.
2015/0295695	A1	10/2015	Davydov et al.	2018/0069682	A1	3/2018	Abdelmonem et al.
2015/0296523	A1	10/2015	Joshi et al.	2018/0076910	A1	3/2018	Zhang et al.
2015/0303950	A1	10/2015	Shattil	2018/0124813	A1	5/2018	Li et al.
2015/0304885	A1	10/2015	Jalali	2018/0139004	A1	5/2018	Abdelmonem et al.
2015/0318944	A1	11/2015	Wigren et al.	2018/0167189	A9	6/2018	Abdelmonem et al.
2015/0318945	A1	11/2015	Abdelmonem et al.	2018/0206240	A1	7/2018	Abdelmonem
2015/0318946	A1	11/2015	Abdelmonem et al.	2018/0220377	A1	8/2018	Abdelmonem et al.
2015/0318964	A1	11/2015	Abdelmonem et al.	2018/0254878	A1	9/2018	Abdelmonem et al.
2015/0319763	A1	11/2015	Abdelmonem et al.	2018/0287660	A1	10/2018	Arambepola et al.
2015/0319768	A1	11/2015	Abdelmonem et al.	2018/0287696	A1	10/2018	Barbieri et al.
2015/0349819	A1	12/2015	Meng	2018/0294827	A1	10/2018	Abdelmonem
2015/0350931	A1	12/2015	Dillinger et al.	2018/0294903	A1	10/2018	Goodman et al.
2015/0350940	A1	12/2015	Wilson et al.	2018/0294908	A1	10/2018	Abdelmonem
2015/0351106	A1	12/2015	Wijetunge et al.	2018/0294932	A1	10/2018	Abdelmonem
2016/0006468	A1	1/2016	Gale et al.	2018/0295020	A1	10/2018	Mo et al.
2016/0029236	A1	1/2016	Sudo	2018/0295553	A1	10/2018	Abdelmonem
2016/0029277	A1	1/2016	Li et al.	2018/0295588	A1	10/2018	Abdelmonem
2016/0050031	A1	2/2016	Hwang et al.	2018/0295617	A1	10/2018	Abdelmonem
2016/0094318	A1	3/2016	Shattil	2018/0295632	A1	10/2018	Goodman et al.
2016/0105903	A1	4/2016	Hessler et al.	2018/0295633	A1	10/2018	Abdelmonem
2016/0119846	A1	4/2016	Chou et al.	2018/0324710	A1	11/2018	Abdelmonem et al.
2016/0135061	A1	5/2016	Abdelmonem	2018/0324812	A1	11/2018	Abdelmonem et al.
2016/0142229	A1	5/2016	Bevan et al.	2018/0332487	A1	11/2018	Beck et al.
2016/0192362	A1	6/2016	Galeev et al.	2018/0332593	A1	11/2018	Galeev et al.
2016/0198353	A1	7/2016	Abdelmonem	2018/0332594	A1	11/2018	Abdelmonem et al.
2016/0248487	A1	8/2016	Sun	2018/0375546	A1	12/2018	Abdelmonem et al.
2016/0249364	A1	8/2016	Siomina	2018/0376431	A1	12/2018	Abdelmonem et al.
2016/0249367	A1	8/2016	Abdelmonem	2019/0052294	A1	2/2019	Abdelmonem
2016/0254840	A1	9/2016	Abdelmonem et al.	2019/0052381	A1	2/2019	Abdelmonem
2016/0254886	A1	9/2016	Bontu et al.	2019/0053247	A1	2/2019	Abdelmonem et al.
2016/0295574	A1	10/2016	Papasakellariou	2019/0082394	A1	3/2019	Abdelmonem et al.
2016/0295601	A1	10/2016	Fang	2019/0116603	A1	4/2019	Abdelmonem et al.
2016/0302125	A1	10/2016	Tejedor et al.	2019/0141641	A1	5/2019	Abdelmonem et al.
2016/0302209	A1	10/2016	Behravan et al.	2019/0150099	A1	5/2019	Abdelmonem
2016/0316396	A1	10/2016	Yu et al.	2019/0158258	A1	5/2019	Abdelmonem
2016/0323086	A1	11/2016	Abdelmonem et al.	2019/0173593	A1	6/2019	Chapman et al.
2016/0330011	A1	11/2016	Lee et al.	2019/0182133	A1	6/2019	Gupta et al.
2016/0353455	A1	12/2016	Jagger	2019/0207735	A1	7/2019	Abdelmonem
2016/0360370	A1	12/2016	Edge et al.	2019/0222243	A1	7/2019	Abdelmonem
2016/0360490	A1	12/2016	Henia	2019/0222329	A1	7/2019	Abdelmonem
2016/0366605	A1	12/2016	Tsui et al.	2019/0230546	A1	7/2019	Takahashi et al.
2016/0366622	A1	12/2016	Yang et al.	2019/0239234	A1	8/2019	Abdelmonem et al.
2016/0374096	A1	12/2016	Lindoff et al.	2019/0253108	A1	8/2019	Zhang et al.
2016/0381680	A1	12/2016	Yasukawa et al.	2019/0253878	A1	8/2019	Yu et al.
2017/0026158	A1	1/2017	Burström et al.	2019/0254041	A1	8/2019	Abdelmonem et al.
2017/0026866	A1	1/2017	Sandberg et al.	2019/0349102	A1	11/2019	Hasarchi et al.
2017/0034693	A1	2/2017	Ono et al.	2019/0364571	A1	11/2019	Abdelmonem
2017/0048734	A1	2/2017	Kusashima et al.	2019/0372613	A1	12/2019	Abdelmonem
2017/0063470	A1	3/2017	Smith et al.	2020/0015238	A1	1/2020	Abdelmonem et al.
				2020/0037262	A1	1/2020	Abdelmonem et al.
				2020/0059258	A1	2/2020	Goodman et al.
				2020/0076711	A1	3/2020	Li et al.
				2020/0084775	A1	3/2020	Abdelmonem et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2020/0092824	A1	3/2020	Abdelmonem et al.
2020/0136664	A1	4/2020	Goodman et al.
2020/0137764	A1	4/2020	Abdelmonem et al.
2020/0154365	A1	5/2020	Abdelmonem et al.
2020/0154366	A1	5/2020	Abdelmonem et al.
2020/0163091	A1	5/2020	Abdelmonem
2020/0163092	A1	5/2020	Abdelmonem et al.
2020/0177292	A1	6/2020	Abdelmonem
2020/0186312	A1	6/2020	Mochizuki et al.
2020/0236630	A1	7/2020	Tacconi et al.
2020/0236686	A1	7/2020	Galeev et al.
2020/0236687	A1	7/2020	Abdelmonem et al.
2020/0244295	A1	7/2020	Abdelmonem
2020/0252943	A1	8/2020	Abdelmonem et al.
2020/0275384	A1	8/2020	Abdelmonem et al.
2020/0343922	A1	10/2020	Abdelmonem
2020/0343930	A1	10/2020	Ditommaso et al.
2020/0412395	A1	12/2020	Abdelmonem
2020/0412396	A1	12/2020	Abdelmonem
2021/0007109	A1	1/2021	Abdelmonem
2021/0022085	A1	1/2021	Abdelmonem et al.
2021/0022086	A1	1/2021	Abdelmonem et al.
2021/0058935	A1	2/2021	Abdelmonem et al.
2021/0083785	A1	3/2021	Abdelmonem
2021/0084661	A1	3/2021	Abdelmonem et al.
2021/0105035	A1	4/2021	Abdelmonem
2021/0105786	A1	4/2021	Abdelmonem et al.
2021/0144650	A1	5/2021	Abdelmonem et al.
2021/0152203	A1	5/2021	Abdelmonem
2021/0153216	A1	5/2021	Abdelmonem et al.
2021/0168730	A1	6/2021	Tacconi et al.
2021/0242893	A1	8/2021	Goodman et al.
2021/0345353	A1	11/2021	Abdelmonem et al.
2021/0368511	A1	11/2021	Abdelmonem
2022/0022194	A1	1/2022	Abdelmonem et al.
2022/0232484	A1	7/2022	Tacconi et al.
2023/0156763	A1	5/2023	Abdelmonem et al.
2023/0224820	A1	7/2023	Abdelmonem et al.
2023/0239908	A1	7/2023	Abdelmonem et al.
2023/0247660	A1	8/2023	Abdelmonem et al.
2024/0205955	A1	6/2024	Abdelmonem et al.
2024/0306180	A1	9/2024	Abdelmonem et al.

FOREIGN PATENT DOCUMENTS

CN	1173101	2/1998
EP	0704986	4/1996
EP	0812069	12/1997
EP	2288061 A1	2/2011
EP	2800412 A1	11/2014
EP	2955862 A1	12/2015
EP	3091779 A2	11/2016
GB	2304000 A	3/1997
JP	06-061876	3/1994
JP	09-326713	12/1997
JP	2018074296 A	5/2018
WO	1998/10514	3/1998
WO	2000/46929	8/2000

WO	2000/046929	8/2000
WO	2007/063514	6/2007
WO	2008033369 A2	3/2008
WO	2009005420 A1	1/2009
WO	2009/019074	2/2009
WO	2012/0116755	9/2012
WO	2012158046	11/2012
WO	2012/172476	12/2012
WO	2015002584 A1	1/2015
WO	20170210056	12/2017

OTHER PUBLICATIONS

Article 34 Amendment for PCT/US17/34237 filed , Mar. 28, 2018.

International Search Report and Written Opinion for PCT/US2019/030835 mailed , Aug. 22, 2019.

International Search Report and Written Opinion for PCT/US2017/034237 mailed , Aug. 7, 2017.

“Excel Average Formula/Function without including Zeros”, Ozgrid.com, Aug. 8, 2011 , 3 pages.

“International Preliminary Report on Patentability”, PCT/US2018/045606, IPRP, Mailed Aug. 26, 2019 , 24pgs.

“International Preliminary Report on Patentability”, PCT/US2016/026212 , Nov. 16, 2017 , 9 pages.

“International Search Report & Written Opinion”, PCT/US01/11351 , Apr. 2002 , 11 pages.

“PCT/US16/26212 International Search Report mailed Jun. 7, 2016.”, , Jun. 7, 2016.

“U.S. Appl. No. 13/956,690, filed Aug. 1, 2013, pp. 4-10”.

Alemseged, Yohannes D., et al. , “Modeling and Mitigation of Narrowband Interference for Transmitted-Reference UWB Systems”, IEEE Journal of Selected Topics in Signal Processing, vol. 1, No. 3 , Oct. 3, 2007 , 14 pages.

Berlemann , et al. , “Cognitive Radio and Management of Spectrum and Radio Resources in Reconfigurable Networks”, Wireless World Research Forum, Working Group 6 White Paper , 2005.

Kim, Kihong , “Interference Mitigation in Wireless Communications”, , Aug. 23, 2005 , 133 pages.

Milstein , “Interference Rejection Techniques in Spread Spectrum Communications”, Proceedings of the IEEE, vol. 76, No. 6, Jun. 1988.

Patent Cooperation Treaty , “International Search Report and Written Opinion date Jun. 1, 2010, International Application No. PCT/US2009/064191”.

Patent Cooperation Treaty , “International Search Report and Written Opinion dated Jun. 1, 2010, from International Application No. PCT/US2009/064191”.

Poor , et al. , “Narrowband Interference Suppression in Spread Spectrum COMA”, IEEE Personal Communications Magazine, Third Quarter, 1994, pp. 14-27.

Salgado-Galicia, Hector , et al. , “A Narrowband Approach to Efficient PCS Spectrum Sharing Through Decentralized DCA Access Policies”, IEEE Personal Communications , 24-34, Feb. 1997.

Tacconi, Pablo , et al. , “Method and Apparatus for Performing Signal Conditioning to Mitigate Interference Detected in a Communication System”, U.S. Appl. No. 15/603,851, filed May 24, 2017.

Zyren, Jim , et al. , “Overview of the 3GPP Long Term Evolution Physical Layer”, Freescale Semiconductor Jul. 2007 , 27 pages.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8






FIG. 9

FIG. 10





FIG. 11






FIG. 12




FIG. 13




FIG. 14





FIG. 15

500
FIG. 16






FIG. 17





FIG. 18



700
FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24





FIG. 25






FIG. 26B

Independently
Operating Cell Sites




FIG. 26C

Cooperating
Cell Sites






FIG. 26D



900
FIG. 27



1000
FIG. 28

**METHOD AND APPARATUS FOR
INCREASING PERFORMANCE OF
COMMUNICATION LINKS OF
COOPERATIVE COMMUNICATION NODES**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. application Ser. No. 18/148,640, filed Dec. 30, 2022, which is a continuation of U.S. application Ser. No. 17/153,499 (now U.S. Pat. No. 11,570,719), filed Jan. 20, 2021, which is a continuation of U.S. application Ser. No. 16/744,688, filed Jan. 16, 2020 (now U.S. Pat. No. 10,959,185), which is a continuation of U.S. application Ser. No. 16/242,665, filed Jan. 8, 2019 (now U.S. Pat. No. 10,575,260), which is a continuation of U.S. application Ser. No. 16/020,076, filed Jun. 27, 2018 (now U.S. Pat. No. 10,231,190), which is a continuation of U.S. application Ser. No. 15/688,010, filed Aug. 28, 2017 (now U.S. Pat. No. 10,039,061), which is a continuation of U.S. application Ser. No. 14/690,765, filed Apr. 20, 2015 (now U.S. Pat. No. 9,775,116), which claims the benefit of U.S. Provisional Application No. 61/988,712, filed May 5, 2014, U.S. Provisional Application No. 62/010,305, filed Jun. 10, 2014, and U.S. Provisional Application No. 62/091,033, filed Dec. 12, 2014. All sections of the aforementioned application(s) and/or patent(s) are incorporated herein by reference in their entirety.

FIELD OF THE DISCLOSURE

The subject disclosure is related to a method and apparatus for increasing performance of communication links of communication nodes.

BACKGROUND

In most communication environments involving short range or long range wireless communications, interference from unexpected wireless sources can impact the performance of a communication system leading to lower throughput, dropped calls, reduced bandwidth which can cause traffic congestion, or other adverse effects, which are undesirable.

Some service providers of wireless communication systems have addressed interference issues by adding more communication nodes, policing interferers, or utilizing antenna steering techniques to avoid interferers.

BRIEF DESCRIPTION OF THE DRAWINGS

Reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

FIG. 1 depicts an illustrative embodiment of a communication system;

FIG. 2 depicts an illustrative embodiment of a frequency spectrum of a four carrier CDMA signal;

FIG. 3 depicts an illustrative embodiment of a frequency spectrum of a four carrier CDMA signal showing unequal power balancing between the four CDMA carriers and including an interferer;

FIG. 4 depicts an illustrative embodiment of a base station of FIG. 1;

FIG. 5 depicts an illustrative embodiment of a frequency spectrum of a four carrier CDMA signal having four CDMA carriers with suppression of an interferer that results in falsing;

FIG. 6 depicts an illustrative embodiment of an interference detection and mitigation system;

FIG. 7 depicts an illustrative embodiment of an interference detection and mitigation system;

FIG. 8 depicts an illustrative embodiment of signal processing module of FIG. 7;

FIG. 9 depicts an illustrative embodiment of plots of a spread spectrum signal;

FIG. 10 depicts an illustrative embodiment of a method for interference detection;

FIG. 11 depicts illustrative embodiments of the method of FIG. 10;

FIG. 12 depicts illustrative embodiments of a series of spread spectrum signals intermixed with an interference signal;

FIG. 13 depicts an illustrative embodiment of a graph depicting interference detection efficiency of a system of the subject disclosure;

FIG. 14 depicts illustrative embodiments of Long Term Evolution (LTE) time and frequency signal plots;

FIG. 15 depicts illustrative embodiments of LTE time and frequency signal plots intermixed with interference signals;

FIG. 16 depicts an illustrative embodiment of a method for detecting and mitigating interference signals shown in FIG. 15;

FIG. 17 depicts an illustrative embodiment of adaptive thresholds used for detecting and mitigating interference signals shown in FIG. 15;

FIG. 18 depicts an illustrative embodiment of resulting LTE signals after mitigating interference according to the method of FIG. 16;

FIG. 19 depicts an illustrative embodiment of a method for mitigating interference;

FIG. 20 depicts an illustrative embodiment of a network design;

FIG. 21 depicts an illustrative embodiment of an Open Systems Interconnect (OSI) model;

FIG. 22 depicts an illustrative embodiment of a relationship between SINR and data throughput and performance;

FIG. 23 depicts an illustrative embodiment of a closed loop process;

FIG. 24 depicts an illustrative embodiment of a spectral environment of a wireless channel;

FIG. 25 depicts an illustrative embodiment of examples of spectral environments for various frequency bands;

FIG. 26A depicts an illustrative embodiment of a method for link management in a communication system;

FIG. 26B depicts an illustrative embodiment of a centralized system managing cell sites according to aspects of the subject disclosure;

FIG. 26C depicts an illustrative embodiment of independently operating cell sites according to aspects of the subject disclosure;

FIG. 26D depicts an illustrative embodiment of cell sites cooperating with each other according to aspects of the subject disclosure;

FIG. 27 depicts an illustrative embodiment of a communication device that can utilize in whole or in part embodiments of the subject disclosure for detecting and mitigating interference; and

FIG. 28 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions, when executed, may cause the machine to perform any one or more of the methods described herein.

DETAILED DESCRIPTION

The subject disclosure describes, among other things, illustrative embodiments for detecting and mitigating interference signals. Other embodiments are included in the subject disclosure.

One embodiment of the subject disclosure includes a method for determining at least one threshold for detecting signal interference in a first plurality of resource blocks occurring in a first radio frequency spectrum of a first wireless communication system, and detecting signal interference in a first resource block of the first plurality of resource blocks according to the at least one threshold. Responsive to determining that traffic utilization of the first plurality of resource blocks in the first radio frequency spectrum does not cause an inability to redirect at least a portion of the data traffic within the first plurality of resource blocks to avoid the signal interference, initiating a redirection of at least the portion of data traffic to a second resource block of the first plurality of resource blocks. Responsive to determining that traffic utilization of the first plurality of resource blocks in the first radio frequency spectrum causes an inability to redirect at least the portion of the data traffic within the first plurality of resource blocks to avoid the signal interference, determining that a second wireless communication system has a second plurality of resource blocks available to transport at least the portion of the data traffic, and initiating a redirection at least the portion of the data traffic to the second plurality of resource blocks of the second wireless communication system.

One embodiment of the subject disclosure includes a machine-readable storage medium, comprising instructions, which when executed by a processor, cause the processor to perform operations including detecting signal interference in a segment of a first plurality of segments occurring in a first radio frequency spectrum of a first wireless communication system, where the signal interference is intermixed with signals transmitted by a transmitter, and where the signals comprise data traffic. Responsive to determining that traffic utilization of the first plurality of segments in the first radio frequency spectrum does not cause an inability to redirect at least a portion of the data traffic within the first plurality of segments to avoid the signal interference, initiating a redirection of at least the portion of data traffic to a second segment of the first plurality of segments. Responsive to determining that traffic utilization of the first plurality of segments in the first radio frequency spectrum causes an inability to redirect at least the portion of the data traffic within the first plurality of segments to avoid the signal interference, determining that a second wireless communication system operating at a second radio frequency spectrum has a second plurality of segments available to transport at least the portion of the data traffic, wherein the first radio frequency spectrum and the second radio frequency spectrum do not overlap, determining that the second wireless communication system is in a communication range of the transmitter transmitting the signals in the first plurality of segments, and initiating a redirection of at least the portion of the data traffic to the second plurality of segments of the second wireless communication system to avoid the signal interference.

One embodiment of the subject disclosure includes a system having a memory to store instructions, and a processor coupled to the memory. Upon execution of the instructions by the processor, the processor performs operations including receiving signal interference information from a plurality of communication systems that detect signal

interference according to at least one threshold, monitoring a location of each of a plurality of communication devices communicatively coupled to the plurality of communication systems, detecting a first communication device of the plurality of communication devices experiencing a degradation in communications with a first communication system of the plurality of communication systems, and facilitating the first communication device to initiate communications with a second communication system of the plurality of communication systems according to the signal interference information and the location of the first communication device, wherein the second communication system is in a communication range of the first communication device, and wherein the second communication system can provide an alternate communication channel to the first communication device with at least less degradation in communications than the first communication system.

As shown in FIG. 1, an exemplary telecommunication system 10 may include mobile units 12, 13A, 13B, 13C, and 13D, a number of base stations, two of which are shown in FIG. 1 at reference numerals 14 and 16, and a switching station 18 to which each of the base stations 14, 16 may be interfaced. The base stations 14, 16 and the switching station 18 may be collectively referred to as network infrastructure.

During operation, the mobile units 12, 13A, 13B, 13C, and 13D exchange voice, data or other information with one of the base stations 14, 16, each of which is connected to a conventional land line communication network. For example, information, such as voice information, transferred from the mobile unit 12 to one of the base stations 14, 16 is coupled from the base station to the communication network to thereby connect the mobile unit 12 with, for example, a land line telephone so that the land line telephone may receive the voice information. Conversely, information, such as voice information may be transferred from a land line communication network to one of the base stations 14, 16, which in turn transfers the information to the mobile unit 12.

The mobile units 12, 13A, 13B, 13C, and 13D and the base stations 14, 16 may exchange information in either narrow band or wide band format. For the purposes of this description, it is assumed that the mobile unit 12 is a narrowband unit and that the mobile units 13A, 13B, 13C, and 13D are wideband units. Additionally, it is assumed that the base station 14 is a narrowband base station that communicates with the mobile unit 12 and that the base station 16 is a wideband digital base station that communicates with the mobile units 13A, 13B, 13C, and 13D.

Narrow band format communication takes place using, for example, narrowband 200 kilohertz (KHz) channels. The Global system for mobile phone systems (GSM) is one example of a narrow band communication system in which the mobile unit 12 communicates with the base station 14 using narrowband channels. Alternatively, the mobile units 13A, 13B, 13C, and 13D communicate with the base stations 16 using a form of digital communications such as, for example, code-division multiple access (CDMA), Universal Mobile Telecommunications System (UMTS), 3GPP Long Term Evolution (LTE), or other next generation wireless access technologies. CDMA digital communication, for instance, takes place using spread spectrum techniques that broadcast signals having wide bandwidths, such as, for example, 1.2288 megahertz (MHz) bandwidths.

The switching station 18 is generally responsible for coordinating the activities of the base stations 14, 16 to ensure that the mobile units 12, 13A, 13B, 13C, and 13D are constantly in communication with the base station 14, 16 or with some other base stations that are geographically dis-

persed. For example, the switching station **18** may coordinate communication handoffs of the mobile unit **12** between the base stations **14** and another base station as the mobile unit **12** roams between geographical areas that are covered by the two base stations.

One particular problem that may arise in the telecommunication system **10** is when the mobile unit **12** or the base station **14**, each of which communicates using narrowband channels, interferes with the ability of the base station **16** to receive and process wideband digital signals from the digital mobile units **13A**, **13B**, **13C**, and **13D**. In such a situation, the narrowband signal transmitted from the mobile unit **12** or the base station **14** may interfere with the ability of the base station **16** to properly receive wideband communication signals.

As will be readily appreciated, the base station **16** may receive and process wideband digital signals from more than one of the digital mobile units **13A**, **13B**, **13C**, and **13D**. For example, the base station **16** may be adapted to receive and process four CDMA carriers **40A-40D** that fall within a multi-carrier CDMA signal **40**, as shown in FIG. **2**. In such a situation, narrowband signals transmitted from more than one mobile units, such as, the mobile unit **12**, may interfere with the ability of the base station **16** to properly receive wideband communication signals on any of the four CDMA carriers **40A-40D**. For example, FIG. **3** shows a multi-carrier CDMA signal **42** containing four CDMA carriers **42A**, **42B**, **42C** and **42D** adjacent to each other wherein one of the CDMA carriers **42C** has a narrowband interferer **46** therein. As shown in FIG. **3**, it is quite often the case that the signal strengths of the CDMA carrier signals **42A-42D** are not equal.

As disclosed in detail hereinafter, a system and/or a method for multiple channel adaptive filtering or interference suppression may be used in a communication system. In particular, such a system or method may be employed in a communication system to protect against, or to report the presence of, interference, which has deleterious effects on the performance of the communication system. Additionally, such a system and method may be operated to eliminate interference in CDMA carriers having other CDMA carriers adjacent thereto.

The foregoing system and methods can also be applied to other protocols such as AMPS, GSM, UMTS, LTE, VoLTE, 802.11xx, 5G, next generation wireless protocols, and so on. Additionally, the terms narrowband and wideband referred to above can be replaced with sub-bands, concatenated bands, bands between carrier frequencies (carrier aggregation), and so on, without departing from the scope of the subject disclosure. It is further noted that the term interference can represent emissions within band (narrowband or wideband), out-of-band interferers, interference sources outside cellular (e.g., TV stations, commercial radio or public safety radio), interference signals from other carriers (inter-carrier interference), interference signals from user equipments (UEs) operating in adjacent base stations, and so on. Interference can represent any foreign signal that can affect communications between communication devices (e.g., a UE served by a particular base station).

As shown in FIG. **4**, the signal reception path of the base station **16**, which was described as receiving interference from the mobile unit **12** in conjunction with FIG. **1**, includes an antenna **50** that provides signals to an amplifier **52**. The output of the amplifier **52** is coupled to a diplexer **54** that splits the signal from the amplifier **52** into a number of different paths, one of which may be coupled to an adaptive front end **56** and another of which may be coupled to a

receiver A **57**. The output of the adaptive front end **56** is coupled to a receiver B **58**, which may, for example, be embodied in a CDMA receiver or any other suitable receiver B. Although only one signal path is shown in FIG. **4**, it will be readily understood to those having ordinary skill in the art that such a signal path is merely exemplary and that, in reality, a base station may include two or more such signal paths that may be used to process main and diversity signals received by the base station **16**.

It will be readily understood that the illustrations of FIG. **4** can also be used to describe the components and functions of other forms of communication devices such as a small cell base station, a microcell base station, a picocell base station, a femto cell, a WiFi router or access point, a cellular phone, a smartphone, a laptop computer, a tablet, or other forms of wireless communication devices suitable for applying the principles of the subject disclosure. Accordingly, such communication devices can include variants of the components shown in FIG. **4** and perform the functions that will be described below. For illustration purposes only, the descriptions below will address the base station **16** with an understanding that these embodiments are exemplary and non-limiting to the subject disclosure.

Referring back to FIG. **4**, the outputs of the receiver A **57** and the receiver B **58** can be coupled to other systems within the base station **16**. Such systems may perform voice and/or data processing, call processing or any other desired function. Additionally, the adaptive front end module **56** may also be communicatively coupled, via the Internet, telephone lines, cellular network, or any other suitable communication systems, to a reporting and control facility that is remote from the base station **16**. In some networks, the reporting and control facility may be integrated with the switching station **18**. The receiver A **57** may be communicatively coupled to the switching station **18** and may respond to commands that the switching station **18** issues.

Each of the components **50-58** of the base station **16** shown in FIG. **4**, except for the adaptive front end module **56**, may be found in a conventional cellular base station **16**, the details of which are well known to those having ordinary skill in the art. It will also be appreciated by those having ordinary skill in the art that FIG. **4** does not disclose every system or subsystem of the base station **16** and, rather, focuses on the relevant systems and subsystems to the subject disclosure. In particular, it will be readily appreciated that, while not shown in FIG. **4**, the base station **16** can include a transmission system or other subsystems. It is further appreciated that the adaptive front end module **56** can be an integral subsystem of a cellular base station **16**, or can be a modular subsystem that can be physically placed in different locations of a receiver chain of the base station **16**, such as at or near the antenna **50**, at or near the amplifier **52**, or at or near the receiver B **58**.

During operation of the base station **16**, the antenna **50** receives CDMA carrier signals that are broadcast from the mobile unit **13A**, **13B**, **13C** and **13D** and couples such signals to the amplifier **52**, which amplifies the received signals and couples the amplified signals to the diplexer **54**. The diplexer **54** splits the amplified signal from the amplifier **52** and essentially places copies of the amplified signal on each of its output lines. The adaptive front end module **56** receives the signal from the diplexer **54** and, if necessary, filters the CDMA carrier signal to remove any undesired interference and couples the filtered CDMA carrier signal to the receiver B **58**.

As noted previously, FIG. **2** illustrates an ideal frequency spectrum **40** of a CDMA carrier signal that may be received

at the antenna 50, amplified and split by the amplifier 52 and the diplexer 54 and coupled to the adaptive front end module 56. If the CDMA carrier signal received at the antenna 50 has a frequency spectrum 40 as shown in FIG. 2 without any interference, the adaptive front end will not filter the CDMA carrier signal and will simply couple the signal directly through the adaptive front end module 56 to the receiver B 58.

However, as noted previously, it is possible that the CDMA carrier signal transmitted by the mobile units 13A-13D and received by the antenna 50 has a frequency spectrum as shown in FIG. 3 which contains a multi-carrier CDMA signal 42 that includes not only the four CDMA carriers 42A, 42B, 42C and 42D from the mobile units 13A, 13B, 13C and 13D having unequal CDMA carrier strengths, but also includes interferer 46, as shown in FIG. 3, which in this illustration is caused by mobile unit 12. If a multi-carrier CDMA signal having a multi-carrier CDMA signal 42 including interferer 46 is received by the antenna 50 and amplified, split and presented to the adaptive front end module 56, it will filter the multi-carrier CDMA signal 42 to produce a filtered frequency spectrum 43 as shown in FIG. 5.

The filtered multi-carrier CDMA signal 43 has the interferer 46 removed, as shown by the notch 46A. The filtered multi-carrier CDMA signal 43 is then coupled from the adaptive front end module 56 to the receiver B 58, so that the filtered multi-carrier CDMA signal 43 may be demodulated. Although some of the multi-carrier CDMA signal 42 was removed during filtering by the adaptive front end module 56, sufficient multi-carrier CDMA signal 43 remains to enable the receiver B 58 to recover the information that was broadcast by mobile unit(s). Accordingly, in general terms, the adaptive front end module 56 selectively filters multi-carrier CDMA signals to remove interference therefrom. Further detail regarding the adaptive front end module 56 and its operation is provided below in conjunction with FIGS. 6-21.

FIG. 6 depicts another example embodiment of the adaptive front end module 56. As noted earlier, the adaptive front end module 56 can be utilized by any communication device including cellular phones, smartphones, tablets, small base stations, femto cells, WiFi access points, and so on. In the illustration of FIG. 6, the adaptive front end module 56 can include a radio 60 comprising two stages, a receiver stage 62 and a transmitter stage 64, each coupled to an antenna assembly 66, 66', which may comprise one of more antennas for the radio 60. The radio 60 has a first receiver stage coupled to the antenna assembly 66 and includes an adaptive front-end controller 68 that receives the input RF signal from the antenna and performs adaptive signal processing on that RF signal before providing the modified RF signal to an analog-to-digital converter 70, which then passes the adapted RF signal to a digital RF tuner 72.

As shown in FIG. 6, the adaptive front end controller 68 of the receiver stage 62 includes two RF signal samplers 74, 76 connected between an RF adaptive filter stage 78 that is controlled by controller 80. The adaptive filter stage 78 may have a plurality of tunable digital filters that can sample an incoming signal and selectively provide bandpass or band-stop signal shaping of an incoming RF signal, whether it is an entire communication signal or a sub-band signal or various combinations of both. A controller 80 is coupled to the samplers 74, 76 and filter stage 78 and serves as an RF link adapter that along with the sampler 74 monitors the input RF signal from the antenna 66 and determines various RF signal characteristics such as the interferences and noise

within the RF signal. The controller 80 is configured to execute any number of a variety of signal processing algorithms to analyze the received RF signal, and determine a filter state for the filter stage 78.

By providing tuning coefficient data to the filter stage 78, the adaptive front end controller 68 acts to pre-filter the received RF signal before the signal is sent to the RF tuner 72, which analyzes the filtered RF signal for integrity and/or for other applications such as cognitive radio applications. After filtering, the radio tuner 72 may then perform channel demodulation, data analysis, and local broadcasting functions. The RF tuner 72 may be considered the receiver side of an overall radio tuner, while RF tuner 72' may be considered the transmitter side of the same radio tuner. Prior to sending the filtered RF signal, the sampler 76 may provide an indication of the filtered RF signal to the controller 80 in a feedback manner for further adjusting of the adaptive filter stage 78.

In some examples, the adaptive front-end controller 68 is synchronized with the RF tuner 72 by sharing a master clock signal communicated between the two. For example, cognitive radios operating on a 100 μ s response time can be synchronized such that for every clock cycle the adaptive front end analyzes the input RF signal, determines an optimal configuration for the adaptive filter stage 78, filters that RF signal into the filtered RF signal and communicates the same to the radio tuner 72 for cognitive analysis at the radio. By way of example, cellular phones may be implemented with a 200 μ s response time on filtering. By implementing the adaptive front end controller 68 using a field programmable gate array configuration for the filter stage, wireless devices may identify not only stationary interference, but also non-stationary interference, of arbitrary bandwidths on that moving interferer.

In some implementations, the adaptive front-end controller 68 may filter interference or noise from the received incoming RF signal and pass that filtered RF signal to the tuner 72. In other examples, such as cascaded configurations in which there are multiple adaptive filter stages, the adaptive front-end controller 68 may be configured to apply the filtered signal to an adaptive bandpass filter stage to create a passband portion of the filtered RF signal. For example, the radio tuner 72 may communicate information to the controller 68 to instruct the controller that the radio is only looking at a portion of an overall RF spectrum and thus cause the adaptive front-end controller 68 not to filter certain portions of the RF spectrum and thereby bandpass only those portions. The integration between the radio tuner 72 and the adaptive front-end controller 68 may be particularly useful in dual-band and tri-band applications in which the radio tuner 72 is able to communicate over different wireless standards, such as GSM, UMTS, or LTE standards.

The algorithms that may be executed by the controller 80 are not limited to interference detection and filtering of interference signals. In some configurations the controller 80 may execute a spectral blind source separation algorithm that looks to isolate two sources from their convolved mixtures. The controller 80 may execute a signal to interference noise ratio (SINR) output estimator for all or portions of the RF signal. The controller 80 may perform bidirectional transceiver data link operations for collaborative retuning of the adaptive filter stage 78 in response to instructions from the radio tuner 72 or from data the transmitter stage 64. The controller 80 can determine filter tuning coefficient data for configuring the various adaptive filters of stage 78 to properly filter the RF signal. The controller 80 may also include a data interface communicating the tuning

coefficient data to the radio tuner **72** to enable the radio tuner **72** to determine filtering characteristics of the adaptive filter **78**.

In one embodiment the filtered RF signal may be converted from a digital signal to an analog signal within the adaptive front-end controller **68**. This allows the controller **68** to integrate in a similar manner to conventional RF filters. In other examples, a digital interface may be used to connect the adaptive front-end controller **68** with the radio tuner **72**, in which case the ADC **70** would not be necessary.

The above discussion is in the context of the receiver stage **62**. Similar elements are shown in the transmitter stage **64**, but bearing a prime. The elements in the transmitter stage **64** may be similar to those of the receiver **62**, with the exception of the digital to analog converter (DAC) **70'** and other adaptations to the other components shown with a prime in the reference numbers. Furthermore, some or all of these components may in fact be executed by the same corresponding structure in the receiver stage **62**. For example, the RF receiver tuner **72** and the transmitter tuner **72'** may be performed by a single tuner device. The same may be true for the other elements, such as the adaptive filter stages **78** and **78'**, which may both be implemented in a single FPGA, with different filter elements in parallel for full duplex (simultaneous) receive and transmit operation.

FIG. 7 illustrates another example implementation of an adaptive front-end controller **100**. Input RF signals are received at an antenna (not shown) and coupled to an initial analog filter **104**, such as low noise amplifier (LNA) block, then digitally converted via an analog to digital converter (ADC) **106**, prior to the digitized input RF signal being coupled to a field programmable gate array (FPGA) **108**. The adaptive filter stage described above may be implemented within the FPGA **108**, which has been programmed to contain a plurality of adaptive filter elements tunable to different operating frequencies and frequency bands, and at least some being adaptive from a bandpass to a bandstop configuration or vice versa, as desired. Although an FPGA is illustrated, it will be readily understood that other architectures such as an application specific integrated circuit (ASIC) or a digital signal processor (DSP) may also be used to implement a digital filter architecture described in greater detail below.

A DSP **110** is coupled to the FPGA **108** and executes signal processing algorithms that may include a spectral blind source separation algorithm, a signal to interference noise ratio (SINR) output estimator, bidirectional transceiver data line operation for collaborative retuning of the adaptive filter stage in response to instructions from the tuner, and/or an optimal filter tuning coefficients algorithm.

FPGA **108** is also coupled to a PCI target **112** that interfaces the FPGA **108** and a PCI bus **114** for communicating data externally. A system clock **118** provides a clock input to the FPGA **108** and DSP **110**, thereby synchronizing the components. The system clock **118** may be locally set on the adaptive front-end controller, while in other examples the system clock **118** may reflect an external master clock, such as that of a radio tuner. The FPGA **108**, DSP **110**, and PCI target **112**, designated collectively as signal processing module **116**, will be described in greater detail below. In the illustrated example, the adaptive front-end controller **100** includes a microcontroller **120** coupled to the PCI bus **114** and an operations, alarms and metrics (OA&M) processor **122**. Although they are shown and described herein as separate devices that execute separate software instructions, those having ordinary skill in the art will readily appreciate that the functionality of the microcontroller **120** and the

OA&M processor **122** may be merged into a single processing device. The microcontroller **120** and the OA&M processor **122** are coupled to external memories **124** and **126**, respectively. The microcontroller **120** may include the ability to communicate with peripheral devices, and, as such, the microcontroller **120** may be coupled to a USB port, an Ethernet port, or an RS232 port, among others (though none shown). In operation, the microcontroller **120** may locally store lists of channels having interferers or a list of known typically available frequency spectrum bands, as well as various other parameters. Such a list may be transferred to a reporting and control facility or a base station, via the OA&M processor **122**, and may be used for system diagnostic purposes.

The aforementioned diagnostic purposes may include, but are not limited to, controlling the adaptive front-end controller **100** to obtain particular information relating to an interferer and retasking the interferer. For example, the reporting and control facility may use the adaptive front-end controller **100** to determine the identity of an interferer, such as a mobile unit, by intercepting the electronic serial number (ESN) of the mobile unit, which is sent when the mobile unit transmits information on the channel. Knowing the identity of the interferer, the reporting and control facility may contact infrastructure that is communicating with the mobile unit (e.g., the base station) and may request the infrastructure to change the transmit frequency for the mobile unit (i.e., the frequency of the channel on which the mobile unit is transmitting) or may request the infrastructure to drop communications with the interfering mobile unit altogether.

Additionally, in a cellular configuration (e.g., a system based on a configuration like that of FIG. 1) diagnostic purposes may include using the adaptive front-end controller **100** to determine a telephone number that the mobile unit is attempting to contact and, optionally handling the call. For example, the reporting and control facility may use the adaptive front-end controller **100** to determine that the user of the mobile unit was dialing 911, or any other emergency number, and may, therefore, decide that the adaptive front-end controller **100** should be used to handle the emergency call by routing the output of the adaptive front-end controller **100** to a telephone network.

The FPGA **108** can provide a digital output coupled to a digital to analog converter (DAC) **128** that converts the digital signal to an analog signal which may be provided to a filter **130** to generate a filtered RF output to be broadcast from the base station or mobile station. The digital output at the FPGA **108**, as described, may be one of many possible outputs. For example, the FPGA **108** may be configured to output signals based on a predefined protocol such as a Gigabit Ethernet output, an open base station architecture initiative (OBSAI) protocol, or a common public radio interface (CPRI) protocol, among others.

It is further noted that the aforementioned diagnostic purposes may also include creating a database of known interferers, the time of occurrence of the interferers, the frequency of occurrence of the interferers, spectral information relating to the interferers, a severity analysis of the interferers, and so on. The identity of the interferers may be based solely on spectral profiles of each interferer that can be used for identification purposes. Although the aforementioned illustrations describe a mobile unit **12** as an interferer, other sources of interference are possible. Any electronic appliance that generates electromagnetic waves such as, for example, a computer, a set-top box, a child monitor, a wireless access point (e.g., WiFi, ZigBee, Bluetooth, etc.) can be a source of interference. In one embodiment, a

database of electronic appliances can be analyzed in a laboratory setting or other suitable testing environment to determine an interference profile for each appliance. The interference profiles can be stored in a database according to an appliance type, manufacturer, model number, and other parameters that may be useful in identifying an interferer. Spectral profiles provided by, for example, the OA&M processor **108** to a diagnostic system can be compared to a database of previously characterized interferers to determine the identity of the interference when a match is detected.

A diagnostic system, whether operating locally at the adaptive front end controller, or remotely at a base station, switching station, or server system, can determine the location of the interferer near the base station (or mobile unit) making the detection, or if a more precise location is required, the diagnostic system can instruct several base stations (or mobile units) to perform triangulation analysis to more precisely locate the source of the interference if the interference is frequent and measureable from several vantage points. With location data, interference identity, timing and frequency of occurrence, the diagnostic system can generate temporal and geographic reports showing interferers providing field personnel a means to assess the volume of interference, its impact on network performance, and it may provide sufficient information to mitigate interference by means other than filtering, such as, for example, interference avoidance by way of antenna steering at the base station, beam steering, retasking an interferer when possible, and so on.

FIG. **8** illustrates further details of an example implementation of a signal processing module **116** that may serve as another embodiment of an adaptive front end controller, it being understood that other architectures may be used to implement a signal detection algorithm. A decoder **150** receives an input from the ADC **106** and decodes the incoming data into a format suitable to be processed by the signal processing module **116**. A digital down converter **152**, such as a polyphase decimator, down converts the decoded signal from the decoder **150**. The decoded signal is separated during the digital down conversion stage into a complex representation of the input signal, that is, into In-Phase (I) and Quadrature-Phase (Q) components which are then fed into a tunable infinite impulse response (IIR)/finite impulse response (FIR) filter **154**. The IIR/FIR filter **154** may be implemented as multiple cascaded or parallel IIR and FIR filters. For example, the IIR/FIR filter **154** may be used with multiple filters in series, such as initial adaptive bandpass filter followed by adaptive bandstop filter. For example, the bandpass filters may be implemented as FIR filters, while the bandstop filters may be implemented as IIR filters. In an embodiment, fifteen cascaded tunable IIR/FIR filters are used to optimize the bit width of each filter. Of course other digital down converters and filters such as cascaded integrator-comb (CIC) filters may be used, to name a few. By using complex filtering techniques, such as the technique described herein, the sampling rate is lowered thereby increasing (e.g., doubling) the bandwidth that the filter **154** can handle. In addition, using complex arithmetic also provides the signal processing module **116** the ability to perform higher orders of filtering with greater accuracy.

The I and Q components from the digital down converter **152** are provided to the DSP **110** which implements a detection algorithm and in response provides the tunable IIR/FIR filter **154** with tuning coefficient data that tunes the IIR and/or FIR filters **154** to specific notch (or bandstop) and/or bandpass frequencies, respectively, and specific bandwidths. The tuning coefficient data, for example, may

include a frequency and a bandwidth coefficient pair for each of the adaptive filters, which enables the filter to tune to a frequency for bandpass or bandstop operation and the bandwidth to be applied for that operation. The tuning coefficient data corresponding to a bandpass center frequency and bandwidth may be generated by the detection algorithm and passed to a tunable FIR filter within the IIR/FIR filter **154**. The filter **154** may then pass all signals located within a passband of the given transmission frequency. Tuning coefficient data corresponding to a notch (or bandstop) filter may be generated by the detection algorithm and then applied to an IIR filter within the IIR/FIR filter **154** to remove any interference located within the passband of the bandpass filter. The tuning coefficient data generated by the detection algorithm are implemented by the tunable IIR/FIR filters **154** using mathematical techniques known in the art. In the case of a cognitive radio, upon implementation of the detection algorithm, the DSP **110** may determine and return coefficients corresponding to a specific frequency and bandwidth to be implemented by the tunable IIR/FIR filter **154** through a DSP/PCI interface **158**. Similarly, the transfer function of a notch (or bandstop) filter may also be implemented by the tunable IIR/FIR filter **154**. Of course other mathematical equations may be used to tune the IIR/FIR filters **154** to specific notch, bandstop, or bandpass frequencies and to a specific bandwidth.

After the I and Q components are filtered to the appropriate notch (or bandstop) or bandpass frequency at a given bandwidth, a digital upconverter **156**, such as a polyphase interpolator, converts the signal back to the original data rate, and the output of the digital upconverter is provided to the DAC **128**.

A wireless communication device capable to be operated as a dual- or tri-band device communicating over multiple standards, such as over UMTS and LTE may use the adaptive digital filter architecture embodiments as described above. For example, a dual-band device (using both LTE and UMTS) may be preprogrammed within the DSP **110** to transmit first on LTE, if available, and on UMTS only when outside of a LTE network. In such a case, the IIR/FIR filter **154** may receive tuning coefficient data from the DSP **110** to pass all signals within a LTE range. That is, the tuning coefficient data may correspond to a bandpass center frequency and bandwidth adapted to pass only signals within the LTE range. The signals corresponding to a UMTS signal may be filtered, and any interference caused by the UMTS signal may be filtered using tuning coefficients, received from the DSP **110**, corresponding to a notch (or bandstop) frequency and bandwidth associated with the UMTS interference signal.

Alternatively, in some cases it may be desirable to keep the UMTS signal in case the LTE signal fades quickly and the wireless communication device may need to switch communication standards rapidly. In such a case, the UMTS signal may be separated from the LTE signal, and both passed by the adaptive front-end controller. Using the adaptive digital filter, two outputs may be realized, one output corresponding to the LTE signal and one output corresponding to a UMTS signal. The DSP **110** may be programmed to again recognize the multiple standard service and may generate tuning coefficients corresponding to realize a filter, such as a notch (or bandstop) filter, to separate the LTE signal from the UMTS signal. In such examples, an FPGA may be programmed to have parallel adaptive filter stages, one for each communication band.

To implement the adaptive filter stages, in some examples, the signal processing module **116** is pre-pro-

grammed with general filter architecture code at the time of production, for example, with parameters defining various filter types and operation. The adaptive filter stages may then be programmed, through a user interface or other means, by the service providers, device manufactures, etc., to form the actual filter architecture (parallel filter stages, cascaded filter stages, etc.) for the particular device and for the particular network(s) under which the device is to be used. Dynamic flexibility can be achieved during runtime, where the filters may be programmed to different frequencies and bandwidths, each cycle, as discussed herein.

One method of detecting a signal having interference is by exploiting the noise like characteristics of a signal. Due to such noise like characteristics of the signal, a particular measurement of a channel power gives no predictive power as to what the next measurement of the same measurement channel may be. In other words, consecutive observations of power in a given channel are un-correlated. As a result, if a given measurement of power in a channel provides predictive power over subsequent measurements of power in that particular channel, thus indicating a departure from statistics expected of a channel without interference, such a channel may be determined to contain interference.

FIG. 9 illustrates an IS-95 CDMA signal **202**, which is a generic Direct Sequence Spread Spectrum (DSSS) signal. The CDMA signal **202** may have a bandwidth of 1.2288 MHz and it may be used to carry up to 41 channels, each of which has a bandwidth of 30 kHz. One way to identify interference affecting the CDMA signal **202** may be to identify any of such 41 channels having excess power above an expected power of the CDMA signal **202**. FIG. 9 also illustrates the probability distribution functions (PDFs) **204** of a typical DSSS signal and a complementary cumulative distribution functions (CCDFs) **206** of a typical DSSS signal, which may be used to establish a criteria used to determine channels disposed within a signal and having excess power.

Specifically, the PDFs **204** include probability distribution of power in a given channel, which is the likelihood $p(x)$ of measuring a power x in a given channel, for a DSSS signal carrying one mobile unit (**212**), for a DSSS signal carrying ten mobile units (**214**), and for a DSSS signal carrying twenty mobile units (**210**). For example, for the PDF **212**, representing a DSSS signal carrying one mobile unit, the distribution $p(x)$ is observed to be asymmetric, with an abbreviated high power tail. In this case, any channel having power higher than the high power tail of the PDF **212** may be considered to have an interference signal.

The CCDFs **206** denote the likelihood that a power measurement in a channel will exceed a given mean power α , by some value α/σ , wherein σ is standard deviation of the power distribution. Specifically, the CCDFs **206** include an instance of CCDF for a DSSS signal carrying one mobile unit (**220**), an instance of CCDF for a DSSS signal carrying ten mobile units (**222**), and an instance of CCDF for a DSSS signal carrying twenty mobile units (**224**). Thus, for example, for a DSSS signal carrying one mobile unit, the likelihood of any channel having the ratio α/σ of 10 dB or more is 0.01%. Therefore, an optimal filter can be tuned to such a channel having excess power.

One method of detecting such a channel having interference is by exploiting the noise like characteristic of a DSSS signal. Due to such noise like characteristic of DSSS signal, a particular measurement of a channel power gives no predictive power as to what the next measurement of the same measurement channel may be. In other words, consecutive observations of power in a given channels are

un-correlated. As a result, if a given measurement of power in a channel provides predictive power over subsequent measurements of power in that particular channel, thus indicating a departure from statistics expected of a channel without interference, such a channel may be determined to contain interference.

FIG. 10 illustrates a flowchart of an interference detection program **300** that may be used to determine location of interference in a DSSS signal. At block **302** a series of DSSS signals can be scanned by the adaptive front end controller described above and the observed values of the signal strengths can be stored for each of various channels located in the DSSS signal. For example, at block **302** the adaptive front end controller may continuously scan the 1.2288 MHz DSSS signal for each of the 41 channels dispersed within it. The adaptive front end controller may be implemented by any well-known analog scanner or digital signal processor (DSP) used to scan and store signal strengths in a DSSS signal. The scanned values of signal strengths may be stored in a memory of such DSP or in any other computer readable memory. The adaptive front end controller may store the signal strength of a particular channel along with any information, such as a numeric identifier, identifying the location of that particular channel within the DSSS signal.

At block **304** the adaptive front end controller can determine the number of sequences m of a DSSS signal that may be required to be analyzed to determine channels having interference. A user may provide such a number m based on any pre-determined criteria. For example, a user may provide m to be equal to four, meaning that four consecutive DSSS signals need to be analyzed to determine if any of the channels within that DSSS signal spectrum includes an interference signal. As one of ordinary skill in the art would appreciate, the higher is the selected value of m , the more accurate will be the interference detection. However, the higher the number m is, the higher is the delay in determining whether a particular DSSS signal had an interference present in it, subsequently, resulting in a longer delay before a filter is applied to the DSSS signal to remove the interference signal.

Generally, detection of an interference signal may be performed on a rolling basis. That is, at any point in time, m previous DSSS signals may be used to analyze presence of an interference signal. The earliest of such m interference signals may be removed from the set of DSSS signals used to determine the presence of an interference signal on a first-in-first-out basis. However, in an alternate embodiment, an alternate sampling method for the set of DSSS signals may also be used.

At block **306** the adaptive front end controller can select x channels having the highest signal strength from each of the m most recent DSSS signals scanned at the block **302**. The number x may be determined by a user. For example, if x is selected to be equal to three, the block **306** may select three highest channels from each of the m most recent DSSS signals. The methodology for selecting x channels having highest signal strength from a DSSS signal is described in further detail in FIG. 11 below. For example, the adaptive front end controller at block **306** may determine that the first of the m DSSS signals has channels 10, 15 and 27 having the highest signal strengths, the second of the m DSSS channels has channels 15 and 27 and 35 having the highest signal strengths, and the third of the m DSSS channels has the channels 15, 27 and 35 having the highest signal strength.

After having determined the x channels having the highest signal strengths in each of the m DSSS signals, at block **308** the adaptive front end controller can compare these x

channels to determine if any of these highest strength channels appear more than once in the m DSSS signals. In case of the example above, the adaptive front end controller at block 308 may determine that the channels 15 and 27 are present among the highest strength channels for each of the last three DSSS signals, while channel 35 is present among the highest strength channels for at least two of the last three DSSS signals.

Such consistent appearance of channels having highest signal strength over subsequent DSSS signals indicate that channels 15 and 27, and probably the channel 35, may have an interference signal super-imposed on them. At block 310 the adaptive front end controller may use such information to determine which channels may have interference. For example, based on the number of times a given channel appears in the selected highest signal strength channels, the adaptive front end controller at block 310 may determine the confidence level that may be assigned to a conclusion that a given channel contains an interference signal.

Alternatively, at block 310 the adaptive front end controller may determine a correlation factor for each of the various channels appearing in the x selected highest signal strength channels and compare the calculated correlation factors with a threshold correlation factor to determine whether any of the x selected channels has correlated signal strengths. Calculating a correlation factor based on a series of observations is well known to those of ordinary skill in the art and therefore is not illustrated in further detail herein. The threshold correlation factor may be given by the user of the interference detection program 300.

Note that while in the above illustrated embodiment, the correlation factors of only the selected highest signal strength channels are calculated, in an alternate embodiment, correlation factors of all the channels within the DSSS signals may be calculated and compared to the threshold correlation factor.

Empirically, it may be shown that when m is selected to be equal to three, for a clean DSSS signal, the likelihood of having at least one match among the higher signal strength channels is 0.198, the likelihood of having at least two matches among the higher signal strength channels is 0.0106, and the likelihood of having at least three matches among the higher signal strength channels is 9.38×10^{-2} . Thus, the higher the number of matches, the lesser is the likelihood of having a determination that one of the x channels contains an interference signal (i.e., a false positive interference detection). It may be shown that if the number of scans m is increased to, say four DSSS scans, the likelihood of having such matches in m consecutive scans is even smaller, thus providing higher confidence that if such matches are found to be present, they indicate presence of interference signal in those channels.

To identify the presence of interference signals with even higher level of confidence, at block 312 the adaptive front end controller may decide whether to compare the signal strengths of the channels determined to have an interference signal with a threshold. If at block 312 the adaptive front end controller decides to perform such a comparison, at block 314 the adaptive front end controller may compare the signal strength of each of the channels determined to have an interference with a threshold level. Such comparing of the channel signal strengths with a threshold may provide added confidence regarding the channel having an interference signal so that when a filter is configured according to the channel, the probability of removing a non-interfering signal is reduced. However, a user may determine that such added confidence level is not necessary and thus no such compari-

son to a threshold needs to be performed. In which case, at block 316 the adaptive front end controller stores the interference signals in a memory.

After storing the information about the channels having interference signals, at block 318 the adaptive front end controller selects the next DSSS signal from the signals scanned and stored at block 302. At block 318 the adaptive front end controller may cause the first of the m DSSS signals to be dropped and the newly added DSSS signal is added to the set of m DSSS signals that will be used to determine presence of an interference signal (first-in-first-out). Subsequently, at block 306 the process of determining channels having interference signals is repeated by the adaptive front end controller. Finally, at block 320 the adaptive front end controller may select and activate one or more filters that are located in the path of the DSSS signal to filter out any channel identified as having interference in it.

Now referring to FIG. 11, a flowchart illustrates a high strength channels detection program 350 that may be used to identify various channels within a given scan of the DSSS signal that may contain an interference signal. The high strength channels detection program 350 may be used to implement the functions performed at block 306 of the interference detection program 300. In a manner similar to the interference detection program 300, the high strength channels detection program 350 may also be implemented using software, hardware, firmware or any combination thereof.

At block 352 the adaptive front end controller may sort signal strengths of each of the n channels within a given DSSS signal. For example, if a DSSS signal has 41 channels, at block 352 the adaptive front end controller may sort each of the 41 channels according to its signal strengths. Subsequently, at block 354 the adaptive front end controller may select the x highest strength channels from the sorted channels and store information identifying the selected x highest strength channels for further processing. An embodiment of the high strength channels detection program 350 may simply use the selected x highest strength channels from each scan of the DSSS signals to determine any presence of interference in the DSSS signals. However, in an alternate embodiment, additional selected criteria may be used.

Subsequently, at block 356 the adaptive front end controller can determine if it is necessary to compare the signal strengths of the x highest strength channels to any other signal strength value, such as a threshold signal strength, etc., where such a threshold may be determined using the average signal strength across the DSSS signal. For example, at block 356 the adaptive front end controller may use a criterion such as, for example: "when x is selected to be four, if at least three out of four of the selected channels have also appeared in previous DSSS signals, no further comparison is necessary." Another criterion may be, for example: "if any of the selected channels is located at the fringe of the DSSS signal, the signal strengths of such channels should be compared to a threshold signal strength." Other alternate criteria may also be provided.

If at block 356 the adaptive front end controller determines that no further comparison of the signal strengths of the selected x channels is necessary, at block 358 the adaptive front end controller stores information about the selected x channels in a memory for further processing. If at block 356 the adaptive front end controller determines that it is necessary to apply further selection criteria to the selected x channels, the adaptive front end controller returns

to block 360. At block 360 the adaptive front end controller may determine a threshold value against which the signal strengths of each of the x channels are compared based on a predetermined methodology.

For example, in an embodiment, at block 360 the adaptive front end controller may determine the threshold based on the average signal strength of the DSSS signal. The threshold signal strength may be the average signal strength of the DSSS signal or a predetermined value may be added to such average DSSS signal to derive the threshold signal strength.

Subsequently, at block 362 the adaptive front end controller may compare the signal strengths of the selected x channels to the threshold value determined at block 360. Only the channels having signal strengths higher than the selected threshold are used in determining presence of interference in the DSSS signal. Finally, at block 364 the adaptive front end controller may store information about the selected x channels having signal strengths higher than the selected threshold in a memory. As discussed above, the interference detection program 300 may use such information about the selected channels to determine the presence of interference signal in the DSSS signal.

The interference detection program 300 and the high strength channel detection program 350 may be implemented by using software, hardware, firmware or any combination thereof. For example, such programs may be stored on a memory of a computer that is used to control activation and deactivation of one or more notch filters. Alternatively, such programs may be implemented using a digital signal processor (DSP) which determines the presence and location of interference channels in a dynamic fashion and activates/de-activates one or more filters.

FIG. 12 illustrates a three dimensional graph 370 depicting several DSSS signals 372-374 over a time period. A first axis of the graph 370 illustrates the number of channels of the DSSS signals 372-374, a second axis illustrates time over which a number of DSSS signals 372-374 are scanned, and a third axis illustrates the power of each of the channels. The DSSS signals 372-374 are shown to be affected by an interference signal 378.

The interference detection program 370 may start scanning various DSSS signals 372-374 starting from the first DSSS signal 372. As discussed above at block 304 the adaptive front end controller determines the number m of the DSSS signals 372-374 that are to be scanned. Because the interference signal 378 causes the signal strength of a particular channel to be consistently higher than the other channels for a number of consecutive scans of the DSSS signals 372-374 at block 210 the adaptive front end controller identifies a particular channel having an interference signal present. Subsequently, at block 320 the adaptive front end controller will select and activate a filter that applies the filter function as described above, to the channel having interference.

The graph 370 also illustrates the average signal strengths of each of the DSSS signals 372-374 by a line 376. As discussed above, at block 362 the adaptive front end controller may compare the signal strengths of each of the x selected channels from the DSSS signals 372-374 with the average signal strength, as denoted by line 376, in that particular DSSS signal.

Now referring to FIG. 13, a graph 380 illustrates interference detection success rate of using the interference detection program 370, as a function of strength of an interference signal affecting a DSSS signal. The x-axis of the graph 380 depicts the strength of interference signal relative to the strength of the DSSS signal, while the y-axis depicts

the detection success rate in percentages. As illustrated, when an interference signal has a strength of at least 2 dB higher than the strength of the DSSS signal, such an interference signal is detected with at least ninety five percent success rate.

The foregoing interference detection and mitigation embodiments can further be adapted for detecting and mitigating interference in long-term evolution (LTE) communication systems.

LTE transmission consists of a combination of Resource Blocks (RBs) which have variable characteristics in frequency and time. A single RB can be assigned to a user equipment, specifically, a 180 KHz continuous spectrum utilized for 0.5-1 msec. An LTE band can be partitioned into a number of RBs which could be allocated to individual communication devices for specified periods of time for LTE transmission. Consequently, an LTE spectrum has an RF environment dynamically variable in frequency utilization over time. FIG. 14 depicts an illustrative LTE transmission.

LTE utilizes different media access methods for downlink (orthogonal frequency-division multiple access; generally, referred to as OFDMA) and uplink (single carrier frequency-division multiple access; generally, referred to as SC-FDMA). For downlink communications, each RB contains 12 sub-carriers with 15 KHz spacing. Each sub-carrier can be used to transmit individual bit information according to the OFDMA protocol. For uplink communications, LTE utilizes a similar RB structure with 12 sub-carriers, but in contrast to downlink, uplink data is pre-coded for spreading across 12 sub-carriers and is transmitted concurrently on all 12 sub-carriers.

The effect of data spreading across multiple sub-carriers yields a transmission with spectral characteristics similar to a CDMA/UMTS signal. Hence, similar principles of interference detection can be applied within an instance of SC-FDMA transmission from an individual communication device—described herein as user equipment (UE). However, since each transmission consists of unknown RB allocations with unknown durations, such a detection principle can only be applied separately for each individual RB within a frequency and specific time domain. If a particular RB is not used for LTE transmission at the time of detection, the RF spectrum will present a thermal noise which adheres to the characteristics of a spread spectrum signal, similar to a CDMA/UMTS signal.

Co-channel, as well as other forms of interference, can cause performance degradation to SC-FDMA and OFDMA signals when present. FIG. 15 depicts an illustration of an LTE transmission affected by interferers 402, 404, 406 and 408 occurring at different points in time. Since such LTE transmissions do not typically have flat power spectral densities (see FIG. 14), identification of interference as shown in FIG. 15 can be a difficult technical problem. The subject disclosure, presents a method to improve the detection of interference in SC-FDMA/OFDM channels through a time-averaging algorithm that isolates interference components in the channel and ignores the underlying signal.

Time averaging system (TAS) can be achieved with a boxcar (rolling) average, in which the TAS is obtained as a linear average of a Q of previous spectrum samples, with Q being a user-settable parameter. The Q value determines the “strength” of the averaging, with higher Q value resulting in a TAS that is more strongly smoothed in time and less dependent on short duration transient signals. Due to the frequency-hopped characteristic of SC-FDMA/OFDMA signals, which are composed of short duration transients, the TAS of such signals is approximately flat. It will be approx-

ciated that TAS can also be accomplished by other methods such as a forgetting factor filter.

In one embodiment, an adaptive threshold can be determined by a method **500500** as depicted in FIG. 16. Q defines how many cycles of t_i to use (e.g., 100 cycles can be represented by t_1 thru t_{100}). The adaptive front end module **56** of FIG. 6 can be configured to measure power in 30 KHz increments starting from a particular RB and over multiple time cycles. For illustration purposes, the adaptive front end module **56** is assumed to measure power across a 5 MHz spectrum. It will be appreciated that the adaptive front end module **56** can be configured for other increments (e.g., 15 KHz or 60 KHz), and a different RF spectrum bandwidth. With this in mind, the adaptive front end module **56** can be configured at frequency increment f_1 to measure power at t_1 , t_2 , thru t_q (q representing the number of time cycles, i.e., Q). At f_1+30 KHz, the adaptive front end module **56** measures power at t_1 , t_2 , thru t_n . The frequency increment can be defined by $f_0+(z-1)*30$ KHz= f_z , where f_0 is a starting frequency, where $z=1 \dots x$, and z defines increments of 30 KHz increment, e.g., $f_1=f(z=1)$ first 30 KHz increment, $f_2=f(z=2)$ second 30 KHz increment, etc.

The adaptive front end module **56** repeats these steps until the spectrum of interest has been fully scanned for Q cycles, thereby producing the following power level sample sets:

$$S_{f_1} (t_1 \text{ thru } t_q): s_{1,t_1,f_1}, s_{2,t_2,f_1}, \dots, s_{q,t_q,f_1}$$

$$S_{f_2} (t_1 \text{ thru } t_q): s_{1,t_1,f_2}, s_{2,t_2,f_2}, \dots, s_{q,t_q,f_2}$$

...

$$S_{f_x} (t_1 \text{ thru } t_q): s_{1,t_1,f_x}, s_{2,t_2,f_x}, \dots, s_{q,t_q,f_x}$$

The adaptive front end module **56** in step **504**, calculates averages for each of the power level sample sets as provided below:

$$a1(f_1)=(s_{1,t_1,f_1}+s_{2,t_2,f_1} \dots +s_{q,t_q,f_1})/q$$

$$a2(f_2)=(s_{1,t_1,f_2}+s_{2,t_2,f_2} \dots +s_{q,t_q,f_2})/q$$

...

$$ax(f_x)=(s_{1,t_1,f_x}+s_{2,t_2,f_x} \dots +s_{q,t_q,f_x})/q$$

In one embodiment, the adaptive front end module **56** can be configured to determine at step **506** the top “m” averages (e.g., the top 3 averages) and dismiss these averages from the calculations. The variable “m” can be user-supplied or can be empirically determined from field measurements collected by one or more base stations utilizing an adaptive front end module **56**. This step can be used to avoid skewing a baseline average across all frequency increments from being too high, resulting in a threshold calculation that may be too conservative. If step **506** is invoked, a baseline average can be determined in step **508** according to the equation: Baseline Avg= $(a1+a2+ \dots +ax-$ averages that have been dismissed $)/(x-m)$. If step **506** is skipped, the baseline average can be determined from the equation: Baseline Avg= $(a1+a2+ \dots +ax)/x$. Once the baseline average is determined in step **508**, the adaptive front end module **56** can proceed to step **510** where it calculates a threshold according to the equation: Threshold= y dB offset+Baseline Avg. The y dB offset can be user defined or empirically determined from field measurements collected by one or more base stations utilizing an adaptive front end module **56**.

Once a cycle of steps **502** through **510** have been completed, the adaptive front end module **56** can monitor at step **512** interference per frequency increment of the spectrum

being scanned based on any power levels measured above the threshold **602** calculated in step **510** as shown in FIG. 17. Not all interferers illustrated in FIG. 17 exceed the threshold, such as the interferer with reference **610**. Although this interferer has a high power signature, it was not detected because it occurred during a resource block (R4) that was not in use. As such, the interferer **510** fell below the threshold **602**. In another illustration, interferer **s 612** also fell below the threshold **602**. This interferer was missed because of its low power signature even though the RB from which it occurred (R3) was active.

Method **500** can utilize any of the embodiments in the illustrated flowcharts described above to further enhance the interference determination process. For example, method **500** of FIG. 16 can be adapted to apply weights to the power levels, and/or perform correlation analysis to achieve a desired confidence level that the proper interferers are addressed. For example, with correlation analysis, the adaptive front end module **56** can be configured to ignore interferers **614** and **616** of FIG. 17 because their frequency of occurrence is low. Method **500** can also be adapted to prioritize interference mitigation. Prioritization can be based on frequency of occurrence of the interferers, time of day of the interference, the affect the interference has on network traffic, and/or other suitable factors for prioritizing interference to reduce its impact on the network. Prioritization schemes can be especially useful when the filtering resources of the adaptive front end module **56** can only support a limited number of filtering events.

When one or more interferers are detected in step **512**, the adaptive front end module **56** can mitigate the interference at step **514** by configuring one or more filters to suppress the one or more interferers as described above. When there are limited resources to suppress all interferers, the adaptive front end module **56** can use a prioritization scheme to address the most harmful interference as discussed above. FIG. 18 provides an illustration of how the adaptive front end module **56** can be suppress interferers based on the aforementioned algorithms of the subject disclosure. For example, interferers **612**, **614** and **616** can be ignored by the adaptive front end module **56** because their correlation may be low, while interference suppression is applied for all other interferers as shown by reference **650**.

In one embodiment, the adaptive front end module **56** can submit a report to a diagnostic system that includes information relating to the interferers detected. The report can including among other things, a frequency of occurrence of the interferer, spectral data relating to the interferer, an identification of the base station from which the interferer was detected, a severity analysis of the interferer (e.g., bit error rate, packet loss rate, or other traffic information detected during the interferer), and so on. The diagnostic system can communicate with other base stations with other operable adaptive front end module **56** to perform macro analysis of interferers such as triangulation to locate interferers, identity analysis of interferers based on a comparison of spectral data and spectral profiles of known interferers, and so on.

In one embodiment, the reports provided by the adaptive front end module **56** can be used by the diagnostic system to in some instance perform avoidance mitigation. For example, if the interferer is known to be a communication device in the network, the diagnostic system can direct a base station in communication with the communication device to direct the communication device to another channel so as to remove the interference experienced by a neighboring base station. Alternatively, the diagnostic sys-

tem can direct an affected base station to utilize beam steering and or mechanical steering of antennas to avoid an interferer. When avoidance is performed, the mitigation step 514 can be skipped or may be invoked less as a result of the avoidance steps taken by the diagnostic system.

Once mitigation and/or an interference report has been processed in steps 514 and 516, respectively, the adaptive front end module 56 can proceed to step 518. In this step, the adaptive front end module 56 can repeat steps 502 thru 510 to calculate a new baseline average and corresponding threshold based on Q cycles of the resource blocks. Each cycle creates a new adaptive threshold that is used for interference detection. It should be noted that when Q is high, changes to the baseline average are smaller, and consequently the adaptive threshold varies less over Q cycles. In contrast, when Q is low, changes to the baseline average are higher, which results in a more rapidly changing adaptive threshold.

Generally speaking, one can expect that there will be more noise-free resource blocks than resource blocks with substantive noise. Accordingly, if an interferer is present (constant or ad hoc), one can expect the aforementioned algorithm described by method 500 will produce an adaptive threshold (i.e., baseline average+offset) that will be lower than interferer's power level due to mostly noise-free resource blocks driving down baseline average. Although certain communication devices will have a high initial power level when initiating communications with a base station, it can be further assumed that over time the power levels will be lowered to a nominal operating condition. A reasonably high Q would likely also dampen disparities between RBs based on the above described embodiments.

It is further noted that the aforementioned algorithms can be modified while maintaining an objective of mitigating detected interference. For instance, instead of calculating a baseline average from a combination of averages $a_1(f_1)$ through $a_x(f_x)$ or subsets thereof, the adaptive front end controller 56 can be configured to calculate a base line average for each resource block according to a known average of adjacent resource blocks, an average calculated for the resource block itself, or other information that may be provided by, for example, a resource block scheduler that may be helpful in calculating a desired baseline average for each resource block or groups of resource blocks. For instance, the resource block schedule can inform the adaptive front end module 56 as to which resource blocks are active and at what time periods. This information can be used by the adaptive front end module 56 determine individualized baseline averages for each of the resource blocks or groups thereof. Since baseline averages can be individualized, each resource block can also have its own threshold applied to the baseline average of the resource block. Accordingly, thresholds can vary between resource blocks for detecting interferers.

It is further noted that the aforementioned mitigation and detection algorithms can be implemented by any communication device including cellular phones, smartphones, tablets, small base stations, macro base stations, femto cells, WiFi access points, and so on. Small base stations (commonly referred to as small cells) can represent low-powered radio access nodes that can operate in licensed and/or unlicensed spectrum that have a range of 10 meters to 1 or 2 kilometers, compared to a macrocell (or macro base station) which might have a range of a few tens of kilometers. Small base stations can be used for mobile data offloading as a more efficient use of radio spectrum.

FIG. 19 depicts an illustrative embodiment of a method 700 for mitigating interference such as shown in FIG. 15. Method 700 can be performed singly or in combination by a mobile communication device, a stationary communication device, base stations, and/or a system or systems in communication with the base stations and/or mobile communication devices. Method 700 can begin with step 702, where interference is detected in one or more segments of a first communication system. A communication system in the present context can represent a base station, such as a cellular base station, a small cell (which can represent a femto cell, or a smaller more portable version of a cellular base station), a WiFi router, a cordless phone base station, or any other form of a communication system that can provide communication services (voice, data or both) to fixed or mobile communication devices. The terms communication system and base station may be used interchangeably below. In either instance, such terms are to be given a broad interpretation such as described above. A segment can represent a resource block or other subsets of communication spectrum of any suitable bandwidth. For illustration purposes only, segments will be referred to henceforth as resource blocks. In addition, reference will be made by a mobile communication device affected by the interference. It is to be understood that method 700 can also be applied to stationary communication devices.

Referring back to step 702, the interference occurring in the resource block(s) can be detected by a mobile communication device utilizing the adaptive thresholds described in the subject disclosure. The mobile communication device can inform the first communication system (herein referred to as first base station) that it has detected such interference. The interference can also be detected by a base station that is in communication with the mobile communication device. The base station can collect interference information in a database for future reference. The base station can also transmit the interference information to a centralized system that monitors interference at multiple base stations. The interference can be stored and organized in a system-wide database (along with the individual databases of each base station) according to time stamps when the interference occurred, resource blocks affected by the interference, an identity of the base station collecting the interference information, an identity of the mobile communication device affected by the interference, frequency of occurrence of the interference, spectral information descriptive of the interference, an identity of the interferer if it can be synthesized from the spectral information, and so on.

At step 704, a determination can be made as to the traffic utilization of resource blocks affected by the interference and other resource blocks of the first base station that may be unaffected by interference or experiencing interference less impactful to communications. In this step a determination can be made as to the availability of unused bandwidth for redirecting data traffic of the mobile communication device affected by the interference to other resource blocks. Data traffic can represent voice only communications, data only communications, or a combination thereof. If other resource blocks are identified that can be used to redirect all or a portion of the data traffic with less interference or no interference at all, then a redirection of at least a portion of the data traffic is possible at step 706.

At step 708 a further determination can be made whether interference suppression by filtering techniques described in the subject disclosure can be used to avoid redirection and continued use of the resource blocks currently assigned to the mobile communication device. Quality of Service (QoS),

data throughput, and other factors as defined by the service provider or as defined in a service agreement between a subscriber of the mobile communication device and the service provider can be used to determine whether noise suppression is feasible. If noise suppression is feasible, then one or more embodiments described in the subject disclosure can be used in step 710 to improve communications in the existing resource blocks without redirecting data traffic of the mobile communication device.

If, however, noise suppression is not feasible, then the mobile communication device can be instructed to redirect at least a portion of data traffic to the available resource blocks of the first base station identified in step 706. The first base station providing services to the mobile communication device can provide these instructions to the mobile communication device. However, prior to instructing the mobile communication device to redirect traffic, the base station can retrieve interference information from its database to assess the quality of the available resource blocks identified in step 706. If the available resource blocks have less interference or no interference at all, then the base station can proceed to step 712. If, however, there are no available resource blocks at step 706, or the available resource blocks are affected by equal or worse noise, then method 700 continues at step 714.

In one embodiment, steps 702, 704, 706, 708, 710, and 712 can be performed by a base station. Other embodiments are contemplated.

In step 714, a second communication system (referred to herein as second base station) in a vicinity of the mobile communication device can be detected. Step 714 can represent the base station that detected the interference in step 702 informing a central system overlooking a plurality of base stations that filtering or redirection of traffic of the affected mobile communication device is not possible. The detection of the second communication system can be made by the mobile communication device, or a determination can be made by the central system monitoring the location of the affected mobile communication device as well as other mobile communication devices according to coordinate information provided by a GPS receiver of the mobile communication devices, and knowledge of a communication range of other base stations. At step 716, resource blocks of the second base station can be determined to be available for redirecting at least a portion of the data traffic of the mobile communication device. At step 718, interference information can be retrieved from a system-wide database that stores interference information provided by base stations, or the interference information can be retrieved from or by the second base station from its own database. At step 720 a determination can be made from the interference information whether the resource blocks of the second base station are less affected by interference than the interference occurring in the resource blocks of the first base station. This step can be performed by a central system that tracks all base stations, or by the affected mobile communication device which can request the interference information from the central system, access the system-wide database, or access the database of the second base station.

If the interference information indicates the interference in the resource blocks of the second base station tend to be more affected by interference than the resource blocks of the first base station, then method 700 can proceed to step 714 and repeat the process of searching for an alternate base station in a vicinity of the mobile communication device, determining availability of resource blocks for transporting at least a portion of the data traffic of the mobile communication device, and determining whether noise in these

resource blocks is acceptable for redirecting the traffic. It should be noted that the mobile communication device can perform noise suppression as described in step 710 on the resource blocks of the second base station. Accordingly, in step 720 a determination of whether the interference is acceptable in the resource blocks of the second base station can include noise suppression analysis based on the embodiments described in the subject disclosure. If an alternate base station is not found, the mobile communication device can revert to step 710 and perform noise suppression on the resource blocks of the first base station to reduce packet losses and/or other adverse effects, and if necessary increase error correction bits to further improve communications.

If, on the other hand, at step 722 the interference in the resource blocks of the second base station is acceptable, then the mobile communication device can proceed to step 724 where it initiates communication with the second base station and redirects at least a portion (all or some) of the data traffic to the resource blocks of the second base station at step 726. In the case of a partial redirection, the mobile communication device may be allocating a portion of the data traffic to some resource blocks of the first base station and the rest to the resource blocks of the second base station. The resource blocks of the first base station may or may not be affected by the interference detected in step 702. If the resource blocks of the first base station being used by the mobile communication device are affected by the interference, such a situation may be acceptable if throughput is nonetheless increased by allocating a portion of the data traffic to the resource blocks of the second base station.

It should be further noted that a determination in step 720 of an acceptable interference level can be the result of no interference occurring in the resource blocks of the second base station, or interference being present in the resource blocks of the second base station but having a less detrimental effect than the interference experienced in the resource blocks of the first base station. It should be also noted that the resource blocks of the second base station may experience interference that is noticeably periodic and not present in all time slots. Under such circumstances, the periodicity of the interference may be less harmful than the interference occurring in the resource blocks of the first base station if such interference is more frequent or constant in time. It is further noted, that a resource block scheduler of the second base station may assign the resource blocks to the mobile communication device according to a time slot scheme that avoids the periodicity of the known interference.

It is contemplated that the steps of method 700 can be rearranged and/or individually modified without departing from the scope of the claims of the subject disclosure. Consequently, the steps of method 700 can be performed by a mobile communication device, a base station, a central system, or any combination thereof.

Operating a wireless network can require a significant amount of effort to deploy and maintain it successfully. An additional complication involves the addition of new cell sites, sector splits, new frequency bands, technology evolving to new generations, user traffic patterns evolving and growing, and customer expectations for coverage and accessibility increasing. Such complexities in network design, optimization and adaptation are illustrated by way of example in FIG. 20. The underlying physical link that supports such networks is negatively impacted by changing weather, construction of new buildings, and an increase in operators offering services and devices using the wireless spectrum.

All of these challenges which can impact the operations of a network combine to make it harder for users to make calls, transfer data, and enjoy wireless applications. Wireless customers do not necessarily understand the complexity that makes a communication network work properly. They just expect it to always work. The service provider is left having to design the best network it can, dealing with all of the complexity described above. Tools have been developed to manage in part this complexity, but the wireless physical link requires special expertise. The underlying foundation of the performance of the wireless network is the physical link, the foundation that services rely upon. Typically, networks are designed to use the OSI seven layer model (shown in FIG. 21), which itself requires a reliable physical layer (referred to herein as the RF link) as a necessary element to achieve a desirable performance design. Without the RF link network communications would not be possible.

The RF link is characterized at a cell site deployment stage when cell sites are selected and antenna heights and azimuths are determined. Dimensioning and propagation along with user traffic distribution are a starting point for the RF link. Once a cell site is built and configured, further optimization falls into two major categories: RF optimization/site modifications (e.g., involving adjusting azimuth or tilting antennas, adding low noise amplifiers or LNAs, etc.), and real-time link adaptation (the way an eNodeB and user equipment (UE) are constantly informing each other about link conditions and adjusting power levels, modulation schemes, etc.).

The network design along with RF optimization/site modifications are only altered occasionally and most changes are expensive. Real-time link adaptation, on the other hand, has low ongoing costs and to the extent possible can be used to respond in real-time to changes experienced by an RF link (referred to herein as the "link condition"). The aspects of designing, optimizing and running a network are vital and a priority for network operators and wireless network equipment makers. Between network design and real-time adaptation a wide variety of manual and autonomous changes take place as part of network optimization and self-organizing networks.

In addition to the issues described above, there is an unsolved problem impacting the RF link that is not being addressed well with today's solutions, which in turn impacts network performance and the resulting customer experience. The subject disclosure addresses this problem by describing embodiments for improving the RF physical layer autonomously without relying on traditional cell site modifications. The subject disclosure also describes embodiments for monitoring link conditions more fully and over greater time windows than is currently performed. Currently, Service Overlay Networks (SON) focus only on downlink conditioning. The systems and methods of the subject disclosure can be adapted to both uplink and the downlink conditioning. Improvements made to an uplink by a base station, for example, can be shared with the SON network to perform downlink conditioning and thereby improve downlink performance. For example, if the performance of an uplink is improved, the SON can be notified of such improvements and can be provided uplink performance data. The SON network can use this information to, for example, direct the base station to increase coverage by adjusting a physical position of an antenna (e.g., adjust tilt of the antenna).

Additionally, the systems and methods of the subject disclosure can be adapted to demodulate a transmit link (downlink) to obtain parametric information relating to the downlink (e.g., a resource block or RB schedule, gain being

used on the downlink, tilt position of the antenna, etc.). In an embodiment, the systems and methods of the subject disclosure can be adapted to obtain the downlink parametric information without demodulation (e.g., from a functional module of the base station). The systems and methods of the subject disclosure can in turn use the downlink parametric information to improve uplink conditioning. In an embodiment, systems and methods of the subject disclosure can use gain data associated with a downlink, a tilt position or adjustments of the downlink antenna, to improve uplink conditioning. In an embodiment, the systems and methods of the subject disclosure can be adapted to use the RB schedule to determine which RBs are to be observed/measured (e.g., RBs in use by UEs) and which RBs are to be ignored (e.g., RBs not in use by UEs) when performing uplink conditioning.

Additionally, in a closed-loop system, the embodiments of the subject disclosure can be adapted to balance performance between an uplink and downlink contemporaneously or sequentially. For example, when an antenna is physically adjusted (e.g., tilted) the embodiments of the subject disclosure can be adapted to determine how such an adjustment affects the uplink. If the adjustment is detrimental to the uplink, it can be reversed in whole or in part. If the adjustment has a nominal adverse impact on the uplink, the adjustment can be preserved or minimally adjusted. If the adjustment has an adverse impact on the uplink that is not detrimental but significant, changes to the uplink (e.g., increasing gain, filter scheme on uplink, requesting UEs to change MCS, etc.) can be identified and initiated to determine if the adjustment to the antenna can be preserved or should be reversed in whole or in part. In an embodiment, a combination of a partial reversal to the adjustment of the antenna and adjustments to the uplink can be initiated to balance a performance of both the uplink and downlink. Closed-loop concepts such as these can also be applied to the uplink. In an embodiment, for example, the downlink can be analyzed in response to changes to the uplink, and adjustments can be performed to the downlink and/or the uplink if the effects are undesirable.

In an embodiment, closed-loop system(s) and method(s) that perform link conditioning on both the uplink and downlink can be adapted to identify a balanced ("sweet spot") performance between the uplink and the downlink such that neither the uplink nor the downlink is at optimal (or maximum) performance. In an embodiment, a closed-loop system and method can be performed by the SON network by receiving conditioning information relating to an uplink and/or a downlink from cell sites and by directing a number of such cell sites to perform corrective actions on the uplink, the downlink, or both to balance performance therebetween. In an embodiment, a closed-loop system and method for balancing performance between uplinks and downlinks can be performed by cell sites independently, UEs independently, cell sites cooperating with UEs, cell sites cooperating among each other, UEs cooperating among each other, or combinations thereof with or without assistance of a SON network by analyzing link conditioning performed on the uplinks and/or downlinks.

In one embodiment, the subject disclosure describes embodiments for improving network performance by analyzing information collected across several RF links to holistically improve communications between eNodeBs and UEs. In one embodiment, the subject disclosure describes embodiments for obtaining a suite of spectral KPIs (key performance indicators) which better capture the conditions of an RF environment. Such data can be used in self-

optimizing networks to tune the RF link that supports the UE/eNodeB relationship. In addition, measurements and adjustments can be used to provide self-healing capabilities that enable the RF link of a UE/eNodeB RF to be adapted in real-time.

In one embodiment, signal to interference plus noise ratio (SINR) is an indicator that can be used to measure a quality of wireless communications between mobile and stationary communication devices such as base station(s). A base station as described in the subject disclosure can represent a communication device that provides wireless communication services to mobile communication devices. A base station can include without limitation a macro cellular base station, a small cell base station, a micro cell base station, a femtocell, a wireless access point (e.g., WiFi, Bluetooth), a Digital Enhanced Cordless Telecommunications (DECT) base station, and other stationary or non-portable communication services devices. The term “cell site” and base station may be used interchangeably. A mobile or portable communication device can represent any computing device utilizing a wireless transceiver for communicating with a base station such as a cellular telephone, a tablet, a laptop computer, a desktop computer, and so on.

For illustration purposes only, the embodiments that follow will be described in relation to cellular base stations and mobile cellular telephones. It is submitted, however, that the embodiments of the subject disclosure can be adapted for use by communication protocols and communication devices that differ from cellular protocols and cellular communication devices.

In communication systems such as LTE networks, achieving a target SINR may enable the coverage area of a cell site to achieve its design goals and allow the cell site to utilize higher modulation and coding schemes (MCS), which can result in higher spectral density—a desirable goal for LTE networks. Delivering desirable throughput rates in LTE systems can require higher SINR than in 3G systems. Performance of LTE systems can suffer as SINR falls, whether due to lower signal and/or higher interference and noise. FIG. 22 depicts the impact of SINR on throughput and therefore capacity.

In one embodiment, SINR can be improved by collecting information from each cell site (e.g., on a sector and/or resource block basis), compiling an estimated SINR from such information, and adjusting RF parameters of the RF link to improve an overall network performance of the cell site. In one embodiment, SINR can be described according to the following equation:

$$SINR = \frac{\text{Signal}}{\text{Interference} + \text{Noise}} = \frac{S}{N + N_c + N_{adj} + N_{comp} + N_{out} + \sum I} \quad (\text{EQ 1})$$

where S is the received signal level, N is the thermal noise, and N_c is in-band co-channel interference, N_{adj} is the adjacent band noise in guard bands or the operator's other carriers, N_{comp} is interference in the same overall frequency band from other operators, N_{out} is the out-of-band noise, and $\sum I$ is the summation of the inter-cell interference contributed from surrounding cell sites. Some prior art systems consider in-band co-channel interference N_c , the adjacent interference noise N_{adj} , the competitors' transmissions N_{comp} , and the out of band noise N_{out} to be very small. This assumption is generally not accurate, particularly for cell sites where performance is a challenge. In practice, I is proportional to the quality and strength of the signal (S) from neighboring

sites; particularly, in dense networks or near cell edges, where one site's signal is another site's interference.

By describing SINR in its constituent parts as depicted in the above equation, specific actions can be taken to improve SINR and consequently performance of one or more RF links, which in turn improves performance of the network. An RF signal received by a cell site can be improved in a number of ways such as by selective filtering, adding gain or amplification, increasing attenuation, tilting antennas, and adjusting other RF parameters. RF parameters of an RE link can be modified in ways that improves overall network performance within a specific cell site and in some cases across multiple inter-related cell sites.

To achieve improvements in one or more cell sites, a matrix of SINRs can be created that includes an estimate for SINR at a path level for each node (cell site) or sector in the network. Optimization scenarios can be achieved by analyzing a network of cell sites collectively using linear programming for matrix optimization. By making adjustments to an uplink, one can create a weighted maximization of the SINR matrix with element δ added to each SINR element. Each point in the matrix with index i and j can consist of $SINR_{i,j} + \delta_{i,j}$ for a particular node. In one embodiment, SINR can be optimized for each cell site, within an acceptable range of $SINR_{i,j} \pm \delta_{i,j}$, where $\delta_{i,j}$ is lower than some specified δ . The term $\delta_{i,j}$ can represent a threshold range of performance acceptable to a service provider. A SINR outside of the threshold range can be identified or flagged as an undesirable SINR. The threshold range $\delta_{i,j}$ can be the same for all base stations, paths, sectors, or clusters thereof, or can be individualized per base station, path, sector, or clusters thereof. The term Δ can represent a maximum threshold range which the threshold range $\delta_{i,j}$ cannot exceed. This maximum threshold range Δ can be applied the same to all base stations, sectors, paths, or clusters thereof. Alternatively, the term Δ can differ per base station, sector, path, or cluster thereof. In one embodiment, the objective may not necessarily be to optimize SINR of a particular cell site. Rather the objective can be to optimize SINR of multiple nodes (cell sites and/or sectors) in a network. Below is an equation illustrating a matrix for optimizing SINR of one or more nodes (cell sites).

$$\begin{bmatrix} SINR_{1,1} \pm \delta_{1,1} & \dots & SINR_{1,j} \pm \delta_{1,j} \\ \vdots & \ddots & \vdots \\ SINR_{i,1} \pm \delta_{i,1} & \dots & SINR_{i,j} \pm \delta_{i,j} \end{bmatrix} \times \begin{bmatrix} \text{Transformation} \\ \text{matrix} \end{bmatrix} = \begin{bmatrix} \text{Optimized} \\ SINR + \delta \end{bmatrix} \quad (\text{EQ 2})$$

In one embodiment, for a particular cell site and sector i,j, SINR can be estimated on a resource-block level basis as $SINR_{i,j,k}$ (where i, and j are the site and sector indices that refer to the site location with respect to the surrounding sites and k is the index that refers to a particular resource block within the LTE system). The overall channel SINR_{i,j} can be calculated by averaging the SINR_{i,j,k} over all the resource blocks, e.g., $SINR_{i,j} = \sum_{k=1}^N SINR_{i,j,k}$, where N can be, for example, 50.

Improving SINR of one or more the nodes in a network using the above analysis, can in turn improve the throughput and capacity of the network, thereby enabling higher modulation and coding schemes (MCS) as shown in FIG. 22. The improved link performance of cell site(s) can help achieve design goals set by service providers for coverage area and capacity of the cell site(s). Achieving these design goals

results in improved (and at times optimal) throughput and cell coverage as measured by data rate, accessibility/retainability, and reduction of time UEs are not on LTE commonly referred to as measure of TNOL (or similarly increase time UEs are on LTE).

In one embodiment, a closed loop process can be used for adjusting the condition of an RF link of a node (or cell site) to improve performance of one or more other nodes in a network. Such a process is depicted in FIG. 23. This process can be described as follows.

Measure: collect a set of RF KPIs (Key Performance Indicators) across multiple categories to more fully reflect the frequently changing conditions of the underlying RF physical link of one or more nodes.

Analyze: compare current RF link conditions and trends against network KPIs and the SINR matrix to determine changes that can be implemented to improve the conditions of the RF physical link

Do: perform changes to adjust the RF link conditions of one or more nodes.

Check: confirm that the changes that were made have had the desired effect. To achieve a closed loop process, the results derived from the "Check" step can be provided to the "Measure" step in subsequent iterations to drive continuous improvement.

Together the steps of FIG. 23 provide a useful approach for analyzing an RF link and for taking appropriate steps to improve its condition. The steps of FIG. 23 are discussed in greater detail below.

Measurement. Understanding the current conditions of an RF link is an important step to improving network performance. Today's networks make available a variety of KPIs that reflect network performance, many focused on specific layer(s) of the OSI model shown in FIG. 21. To better improve link conditioning, the subject disclosure introduces a new set of KPIs that can provide a more complete "spectral portrait" that describes the RF environment that the RF link depends upon.

There can be several aspects of the RF spectrum that can impact an RF link, as shown in FIG. 24. For example, one aspect of the RF spectrum that can impact the RF link involves the condition of a particular frequency band used for a desired signal. Other co-channel signals in the same frequency band can have an impact on the RF link, whether due to inter-cell interference from neighboring cell sites or external foreign interference from faulty systems and unintentional radiators. Each desired frequency band also has neighbors ranging from guard bands left open to provide isolation, additional carriers used by the same wireless operator (e.g., multiple UMTS bands or LTE neighboring CDMA), competing carriers operating in near adjacent bands, other systems operating in adjacent bands, and so on.

Each of four different RF categories measured during link conditioning (enumerated as 1-4 in FIG. 24) can provide important RF information that can directly impact a condition of the RF link and ultimately the UE-eNB relationship. Link conditioning as described by the subject disclosure provides a holistic spectral portrait enabling more insight than what is provided by OEM (Original Equipment Manufacturer) equipment which collects RSSI information and carrier power information in band (e.g., only 1 of the 4 groups), but doesn't give an operator visibility into what is happening in adjacent bands, out of band, or unused spectrum. Prior art OEM equipment also does not provide a comparison between expected, averages and daily measurements, which if available would provide a service provider a way to measure network performance.

Co-channel signals in an operating band can be filtered using the filtering techniques described earlier in the subject disclosure. FIG. 25 describes the four categories of bands in each of current US spectrums. In some instances these classes of RF segments are presently impacting the performance of the underlying RF link and therefore the overall network performance. To support active conditioning of an RF link, the new KPIs introduced above along with SINR monitoring can provide visibility to parameters not currently available, and can be used to mitigate spectrum and link conditions that may be undesirable. Such parameters can include absolute nominal values for each RF technology such as, for example, SINR targets based on nominal values and site-specific values based on particular conditions of a cell site. For example, some sites can have a target SINR higher than others due to the nature of traffic the sites support and/or because of network design considerations.

A network is a dynamic entity that changes continuously due to software upgrades, traffic volumes and pattern changes, seasonality and environmental conditions, just to name a few. Monitoring these variations and then adjusting the RF link to accurately compensate for such variations enables cell sites to consistently operate with a desired performance. In addition to monitoring and adjusting variations in an RF link, in one embodiment, nominal spectral values and RF statistics can be recorded in an ongoing basis (daily, hourly, according to moving averages, etc.).

Occasionally there can be significant differences between real-time, short-term averages and longer-term design parameters that can cause degradation of cell site metrics, which may negatively impact customer experience, and which can result in lost revenue for a service provider if not counteracted. When such issues are identified a next step can be to understand why the issues arose by analyzing spectral insights gained through the analysis of signals impacting SINR.

In one embodiment, link conditioning can be performed based on a number of metrics that can include without limitation:

RSSI_{OUT}—RSSI in the neighboring frequency bands (out of band). For example, TV channel 51 adjacent to the lower 700 MHz LTE bands or SMR and public safety bands adjacent to the 800 MHz cellular bands. This

metric is proportional to N_{out} ①
 RSSI_{CB} and RSSI_{CM}—RSSI per carrier during busy hour and during maintenance window which can be used to

help estimate S. ②

RSSI_c—RSSI in carrier's used spectrum. This metric is proportional to $S+N_c$. ②

RSSI_{ADJ}—RSSI in band in the carrier's unused spectrum.

This metric is proportional to N_{adj} . ③
 RSSI_{COMP}—RSSI of competing wireless carriers occupying adjacent spectrum, not filtered by front end. This

metric is proportional to N_{comp} . ④
 SINR—the signal to noise plus interference ratio of the resource blocks.

To gain a better understanding of the above metrics, the reference numbers 1-4 used in the above listing can be cross-referenced with the reference numbers 1-4 in FIGS. 24-25. These metrics can be measured on a path-by-path basis and can be used to drive optimization of one or more cell sites. As the environment changes, so can the performance of a network which can be reflected in these metrics. Using these metrics and correlating them against spectral

KPIs can reveal vital information that can be used to improve an RF link's performance.

Analysis. As variations of RSSI and SINR data are collected RF statistics relating to these metrics can be generated and used to mine a data set for trends, outliers, and abnormalities across cell sites and frequency bands. By analyzing such information, a network and its corresponding cell sites can be monitored for changes over time, and corresponding mitigation steps can be taken when necessary.

Recall equation EQ1 above,

$$SINR = \frac{\text{Signal}}{\text{Interference} + \text{Noise}} = \frac{S}{N + N_c + N_{adj} + N_{comp} + N_{out} + \sum I}$$

where S is the received signal level, N is the thermal noise, and N_c is in-band co-channel interference, N_{adj} is the adjacent band noise, N_{comp} is interference from other operators, N_{out} is the out-of-band noise, and $\sum I$ is the summation of the inter-cell interference contributed from all the surrounding cells. If SINR of a given sector or node is lower than expected a number of causes and solutions can be applied, based on a deeper understanding of the RF environment and its contribution to SINR. Below are non-limiting illustrations and corresponding recommended solutions to improve SINR.

1. N_{out} is high, the solution may be to provide better filtering or diversity optimization
2. N_{comp} is high, the solution may be to incorporate dynamic filtering to eliminate those sources
3. N_{adj} is high, the solution may be to incorporate dynamic filtering to eliminate those sources or 3G service optimization (e.g., pilot power reduction or antenna tilt)
4. N_c is high, the solution may in band mitigation using filtering techniques described in the subject disclosure
5. $\sum I$ is high, the solution may involve reducing overall gain to minimize intra-cell site noise
6. S is low, the solution may be to increase uplink gain to improve the RF link of the UE

The above listing provides illustrations for initiating mitigating actions based on spectral analysis, which can be implemented with closed loop control so that ongoing performance improvements can be maintained.

Mitigation (Do). RF link mitigation can be initiated from an analysis of spectral data that leads to a set of specific recommended actions. There are many aspects of the RF link that can be modified as part of a link mitigation strategy, including without limitation:

Filtering adjacent signals: If adjacent signals are detected at the eNodeB at higher levels than expected, antennas can be tilted away from adjacent systems and/or digital filtering can be applied to the uplink to provide additional adjacent channel selectivity.

Adding gain: Based on traffic conditions or trends. For example, cell sites can be directed to increase uplink gain, effectively improving SINR for received signals or expanding coverage of a cell site.

Attenuating high signal power: In situations involving high traffic or locations of certain types of traffic leading to high signal power in-band, base station transceivers (BTS) can be instructed to reduce uplink signal power, which can improve an eNodeBs operating performance.

Interference suppression: in-band uplink filtering techniques described in the subject disclosure can be used to remove external interference within the carrier's active channel.

Diversity optimization: picking the better signal of a main and diversity receive antennas.

3G service optimization: Adjusting 3G pilot power or 3G antennas to minimize interference.

Adjusting mobile transmit parameters: Working with SON interfaces and eNodeB to adjust target power levels to modify cell coverage or reduce inter-cell interference.

Tilting antennas to reshape coverage: As traffic moves and capacity demand shifts, providing control of antenna tilt or input to antenna SON algorithms can enable the network to adjust coverage to address traffic demands. Coordinating across multiple sites, link conditioning algorithms can adjust positions of antennas (e.g., tilt down) on one site to reduce coverage and focus capacity while simultaneously up-tilting antennas of neighboring sites to fill in coverage gaps. This can shift traffic reducing the interference from UEs serviced by neighboring sites.

Check and Reporting. As changes are made to the network parameters based on any of the mitigation actions described above, the changes can be verified to determine whether such mitigation actions in fact improved network performance. Additionally, the SON network can be informed of these changes on the uplink for possible use in downlink conditioning as previously described. In addition, relevant data can be logged to guide future enhancement cycles.

As noted earlier, verification of the changes to the RF link can be implemented by way of a closed loop confirmation process which can provide input to the SON network to ensure that the network as a whole is operating according to up-to-date settings and the same or similar RF data. Reports generated in the verification step may include information relating to external interference that was detected, resource block utilization, multiple channel power measurements, etc.

As part of the ongoing adaptation of the link conditioning cycle, all changes can be logged, statistics can be updated and metadata can be generated and/or assigned to logged changes to ensure all changes can be understood and analyzed by personnel of a service provider. Such reports can also be used by future applications which can be adapted to "learn" from historical data generated from many cycles of the process described above. Implementing a link conditioning process based on real-world conditions as described above provides an enhanced and optimized RF physical layer performance. Ongoing link conditioning also enables operators to rely less on designing cell sites to worst-case conditions or anticipated network coverage.

The embodiments of the subject disclosure provide a unique focus on the RF physical layer according to a collective analysis of RF links across multiple cell sites. These embodiments enable systems to extract insight from spectral information, historical trends and network loading, while simultaneously optimizing RF parameters of multiple sites with live network traffic, thereby improving communications between eNodeBs and the UEs.

FIG. 26A depicts non-limiting illustrative embodiments of a method 800 for implementing link management in a communication system. In one embodiment, method 800 can be performed by a centralized system 832 that coordinates SINR measurements and corrective actions between cell sites as depicted in FIG. 26B. In an alternate embodiment, method 800 can be performed independently by each cell site without regard to adverse effects that may be caused by a particular cell site on neighboring cell site(s) as depicted in FIG. 26C. In another alternate embodiment,

method **800** can be performed by each cell site, each communicating with one or more neighboring cell sites to reduce adverse effects caused by a particular cell site on neighboring cell site(s) as depicted in FIG. 26D. The embodiments of FIGS. 26B-26D can be combined in any fashion in relation to applications of method **800**. For example, suppose method **800** is implemented independently by cell sites depicted in FIG. 26C. Further suppose the centralized system **832** of FIG. 26B receives SINR results from each of the cell sites performing method **800**. In this illustration, the centralized system **832** can be configured to reverse or modify some (or all) of the independent actions of the cell sites of FIG. 26C depending on SINR measurements received by the centralized system **832** from the cell sites. Other combinations of FIGS. 26B-26D are possible and should be considered in relation to method **800**.

For illustration purposes only, method **800** will now be described according to the centralized system **832** of FIG. 26B. Method **800** can begin at step **802** where a SINR measurement can be made by each cell site on a corresponding sector and/or path. Cell sites can be configured to perform SINR measurements over several iterations which can be averaged over time. Each cell site can share SINR measurements with the centralized system **832**. The SINR measurements can include a SINR measurement for the cell site, a SINR measurement for each sector, a SINR measurement for each path, or combinations thereof. The SINR measurement for a sector can be an average of SINR measurements for the paths of the sector. The SINR measurement for the cell site can be an average of SINR measurements of multiple sectors, or SINR measurements of multiple paths. When SINR measurements have been shared by all cell sites, a determination can be made by the centralized system **832** at step **804** as to which of the cell sites, sectors, or paths has the lowest SINR measurement. The minimum SINR measurement can then be compared by the centralized system **832** in step **806** to one or more thresholds which may be established by a service provider as a minimum expected SINR performance for any particular cell site, sector, and/or path. If the minimum SINR measurement is not below the threshold, the centralized system **832** can proceed to step **802** and reinitiate measurements of SINR across multiple cell sites and corresponding sectors and/or paths.

If, however, the minimum SINR measurement of a particular cell site, sector or path is below the threshold, then corrective action can be taken by the centralized system **832** at step **808** to improve the SINR measurement of the cell site, sector or path in question. The corrective action can include, without limitation, filtering adjacent signals, adding gain, attenuating high signal power, filtering interference signals according to the embodiments of the subject disclosure, utilizing diversity optimization, utilizing 3G service optimization, adjusting mobile transmit parameters, tilting antennas to reshape cell site coverage, or any combination thereof.

Once corrective action has been executed by a cell site and/or UE, a determination can be made by the centralized system **832** at step **810** as to whether the SINR of the cell site, sector or path in question has improved. If there's no improvement, the corrective action can be reversed in whole or in part by the centralized system **832** at step **812**, and measurements of SINR per cell site, sector and/or path can be repeated beginning from step **802**. If, however, the corrective action did improve the SINR of the cell site, sector or path in question, then a determination can be made by the centralized system **832** at step **814** as to whether the

corrective action implemented by the cell site and/or UE has had an adverse effect on other paths or sectors of the same cell site or neighboring cell sites.

In one embodiment, this determination can be made by the centralized system **832** by requesting SINR measurements from all cell sites, sectors, and/or paths after the corrective action has been completed. The centralized system **832** can then be configured to determine an average of the SINRs for all the cell sites, sectors, and/or paths for which the corrective action of step **808** was not applied. For ease of description, the cell site that initiated corrective action will be referred to as the "corrected" cell site, while cell sites not participating in the corrective action will be referred to as the "uncorrected" cell sites.

With this in mind, at step **816**, the centralized system **832** can determine whether the SINR averages from the uncorrected cell sites, sectors or paths are the same or similar to the SINR averages of the uncorrected cell sites, sectors, and/or paths prior to the corrective action. If there's no adverse effect or a nominal adverse effect, then the centralized system **832** can be configured to maintain the corrective action initiated by the corrected cell site, sector and/or path and proceed to step **802** to repeat the process previously described. If, on the other hand, the average of the SINRs of the uncorrected cell sites, sectors or paths for which corrective action was not taken has been reduced below the SINR averages of these sites, sectors or paths prior to the corrective action (or below the threshold at step **806** or different threshold(s) established by the service provider), then the corrective action initiated by the corrective cell site, sector or path can be reversed in whole or in part by the centralized system **832** at step **812**.

In another embodiment, step **816** can be implemented by establishing a minimum SINR values that are unique to each cell site, sector, and/or path. If after the corrective action the SINR measurements of the corrected cell site, sector and/or path has improved at step **810** and the SINR measurements of the uncorrected cell sites, sectors and/or paths are above the unique SINR values established therefor, then the corrective action can be maintained by the centralized system **832** and the process can be reinitiated at step **802**. If, on the other hand, the SINR measurement of the corrected cell site, sector or path has not improved after the corrective action, or the SINR measurements of one or more uncorrected cell sites, sectors, and/or paths are below the unique SINR values established therefor, then the corrective action taken can be reversed in whole or in part by the centralized system **832** at step **812**.

Method **800** can be adapted to use different sampling rates for SINR, and/or different thresholds. The sampling rates and/or thresholds can be temporally dependent (e.g., time of day profiles—morning, afternoon, evening, late evening, early morning, etc.). SINR profiles can be used to account for anomalous events (e.g., a sporting event, a convention, etc.) which may impact traffic conditions outside the norm of regular traffic periods. Thresholds used by method **800** can include without limitation minimum thresholds used for analyzing SINRs of cell sites, sectors and/or paths prior to corrective action; corrective thresholds used for analyzing SINRs of corrected cell sites, sectors and/or paths, consistency thresholds used for analyzing SINRs from uncorrected cell sites, sectors and/or paths after corrective action, and so on. Method **800** can also be adapted to use other KPIs such as dropped calls, data throughput, data rate, accessibility and retainability, RSSI, density of user equipment (UEs), etc. Method **800** can also be adapted to ignore or exclude control channels when determining SINR measurements. That

power levels from control channels can be excluded from SINR measurements. Method **800** can also be adapted to perform closed-loop methods for balancing uplink and downlink performance as described earlier for SON networks, cell sites, UEs, or combinations thereof. Method **800** can be adapted to obtain the noise components of SINR (EQ1) from power measurements described in the subject disclosure. Referring to FIG. **24**, the RSSI measurements shown in FIG. **24** can be determined by measuring power levels at different spectral locations in the spectral components shown in FIG. **24**.

As noted earlier, method **800** can also be adapted to the architectures of FIGS. **26C** and **26D**. For example, method **800** can be adapted for use by each cell site of FIG. **26C**. In this embodiment, each cell site can independently perform SINR measurements per sector and/or path, perform analysis based on expected SINR threshold(s), mitigate below performance SINRs, verify corrective actions, and reverse when necessary corrective measures in whole or in part as described earlier. A distinct difference between this embodiment and that described for the centralized system **832** of FIG. **26B** is that in this embodiment, each cell site can take corrective action without regard to adverse effects that may be caused to neighboring cell site(s) shown in FIG. **26C**.

In the case of FIG. **26D**, method **800** can be adapted for use by each cell site with the additional feature that each cell site can be adapted to cooperate with its neighboring cell sites to avoid as much as possible adverse effects caused by corrective actions taken by any of the cell sites. In this embodiment, a corrected cell site can request SINR measurements of neighboring (uncorrected) cell sites, sectors or paths from the uncorrected cell sites themselves or a centralized system monitoring SINR measurements. Such requests can be made before or after correction action is performed by the corrected cell site. For example, before corrective action is taken, a cell site that needs correction can determine whether the SINR measurements of one or more neighboring cell sites, sectors or paths are marginal, average or above average when compared to expected SINR performance threshold(s). The cell site to be corrected can use this information to determine how aggressive it can be when initiating corrective action. After corrective action is taken, the corrected cell site can request updated SINR measurements from neighboring cell sites which it can then compare to threshold(s) established for the neighboring cell sites and determine therefrom whether to reverse the corrective action in whole or in part.

It is further noted that method **800** can be adapted to combine one or more of the foregoing embodiments for performing link conditioning in any one of the embodiments FIGS. **26B**, **26C**, and **26D** such that combined implementations of method **800** are used to achieve a desirable RF link performance for clusters of cell sites in a network.

It is further noted that the methods and systems of the subject disclosure can be used in whole or in part by a cellular base station (e.g., macro cell site, micro cell site, pico cell site, a femto cell site), a wireless access point (e.g., a WiFi device), a mobile communication device (e.g., a cellular phone, a laptop, a tablet, etc.), a commercial or utility communication device such as a machine-to-machine communications device (e.g., a vending machine with a communication device integrated therein, an automobile with an integrated communication device), a meter for measuring power consumption having an integrated communication device, and so on. Additionally, such devices can be adapted according to the embodiments of the subject disclosure to communicate with each other and share para-

metric data with each other to perform in whole or in part any of embodiments of the subject disclosure.

It is further noted that the methods and systems of the subject disclosure can be adapted to receive, process, and/or deliver information between devices wirelessly or by a tethered interface. For example, SINR information can be provided by the cell sites to a system by way of a tethered interface such as an optical communication link conforming to a standard such as a common public radio interface (CPRI) referred to herein as a CPRI link. In another embodiment, a CPRI link can be used to receive digital signals from an antenna system of the base station for processing according to the embodiments of the subject disclosure. The processed digital signals can in turn be delivered to other devices of the subject disclosure over a CPRI link. Similar adaptations can be used by any of the embodiments of the subject disclosure.

An illustrative embodiment of a communication device **900** is shown in FIG. **27**. Communication device **900** can serve in whole or in part as an illustrative embodiment of the devices depicted in FIGS. **1**, **4**, and **6-8**. In one embodiment, the communication device **900** can be configured, for example, to perform operations such as measuring a power level in at least a portion of a plurality of resource blocks occurring in a radio frequency spectrum, where the measuring occurs for a plurality of time cycles to generate a plurality of power level measurements, calculating a baseline power level according to at least a portion of the plurality of power levels, determining a threshold from the baseline power level, and monitoring at least a portion of the plurality of resource blocks for signal interference according to the threshold. Other embodiments described in the subject disclosure can be used by the communication device **900**.

To enable these features, communication device **900** can comprise a wireline and/or wireless transceiver **902** (herein transceiver **902**), a user interface (UI) **904**, a power supply **914**, a location receiver **916**, a motion sensor **918**, an orientation sensor **920**, and a controller **906** for managing operations thereof. The transceiver **902** can support short-range or long-range wireless access technologies such as Bluetooth, ZigBee, WiFi, DECT, or cellular communication technologies, just to mention a few. Cellular technologies can include, for example, CDMA-1X, UMTS/HSDPA, GSM/GPRS, TDMA/EDGE, EV/DO, WiMAX, SDR, LTE, as well as other next generation wireless communication technologies as they arise. The transceiver **902** can also be adapted to support circuit-switched wireline access technologies (such as PSTN), packet-switched wireline access technologies (such as TCP/IP, VoIP, etc.), and combinations thereof.

The UI **904** can include a depressible or touch-sensitive keypad **908** with a navigation mechanism such as a roller ball, a joystick, a mouse, or a navigation disk for manipulating operations of the communication device **900**. The keypad **908** can be an integral part of a housing assembly of the communication device **900** or an independent device operably coupled thereto by a tethered wireline interface (such as a USB cable) or a wireless interface supporting for example Bluetooth. The keypad **908** can represent a numeric keypad commonly used by phones, and/or a QWERTY keypad with alphanumeric keys. The UI **904** can further include a display **910** such as monochrome or color LCD (Liquid Crystal Display), OLED (Organic Light Emitting Diode) or other suitable display technology for conveying images to an end user of the communication device **900**. In an embodiment where the display **910** is touch-sensitive, a

portion or all of the keypad **908** can be presented by way of the display **910** with navigation features.

The display **910** can use touch screen technology to also serve as a user interface for detecting user input. As a touch screen display, the communication device **900** can be adapted to present a user interface with graphical user interface (GUI) elements that can be selected by a user with a touch of a finger. The touch screen display **910** can be equipped with capacitive, resistive or other forms of sensing technology to detect how much surface area of a user's finger has been placed on a portion of the touch screen display. This sensing information can be used to control the manipulation of the GUI elements or other functions of the user interface. The display **910** can be an integral part of the housing assembly of the communication device **900** or an independent device communicatively coupled thereto by a tethered wireline interface (such as a cable) or a wireless interface.

The UI **904** can also include an audio system **912** that utilizes audio technology for conveying low volume audio (such as audio heard in proximity of a human ear) and high volume audio (such as speakerphone for hands free operation). The audio system **912** can further include a microphone for receiving audible signals of an end user. The audio system **912** can also be used for voice recognition applications. The UI **904** can further include an image sensor **913** such as a charged coupled device (CCD) camera for capturing still or moving images.

The power supply **914** can utilize common power management technologies such as replaceable and rechargeable batteries, supply regulation technologies, and/or charging system technologies for supplying energy to the components of the communication device **900** to facilitate long-range or short-range portable applications. Alternatively, or in combination, the charging system can utilize external power sources such as DC power supplied over a physical interface such as a USB port or other suitable tethering technologies.

The location receiver **916** can utilize location technology such as a global positioning system (GPS) receiver capable of assisted GPS for identifying a location of the communication device **900** based on signals generated by a constellation of GPS satellites, which can be used for facilitating location services such as navigation. The motion sensor **918** can utilize motion sensing technology such as an accelerometer, a gyroscope, or other suitable motion sensing technology to detect motion of the communication device **900** in three-dimensional space. The orientation sensor **920** can utilize orientation sensing technology such as a magnetometer to detect the orientation of the communication device **900** (north, south, west, and east, as well as combined orientations in degrees, minutes, or other suitable orientation metrics).

The communication device **900** can use the transceiver **902** to also determine a proximity to a cellular, WiFi, Bluetooth, or other wireless access points by sensing techniques such as utilizing a received signal strength indicator (RSSI) and/or signal time of arrival (TOA) or time of flight (TOF) measurements. The controller **906** can utilize computing technologies such as a microprocessor, a digital signal processor (DSP), programmable gate arrays, application specific integrated circuits, and/or a video processor with associated storage memory such as Flash, ROM, RAM, SRAM, DRAM or other storage technologies for executing computer instructions, controlling, and processing data supplied by the aforementioned components of the communication device **400**.

Other components not shown in FIG. **27** can be used in one or more embodiments of the subject disclosure. For instance, the communication device **900** can include a reset button (not shown). The reset button can be used to reset the controller **906** of the communication device **900**. In yet another embodiment, the communication device **900** can also include a factory default setting button positioned, for example, below a small hole in a housing assembly of the communication device **900** to force the communication device **900** to re-establish factory settings. In this embodiment, a user can use a protruding object such as a pen or paper clip tip to reach into the hole and depress the default setting button. The communication device **400** can also include a slot for adding or removing an identity module such as a Subscriber Identity Module (SIM) card. SIM cards can be used for identifying subscriber services, executing programs, storing subscriber data, and so forth.

The communication device **900** as described herein can operate with more or less of the circuit components shown in FIG. **27**. These variant embodiments can be used in one or more embodiments of the subject disclosure.

It should be understood that devices described in the exemplary embodiments can be in communication with each other via various wireless and/or wired methodologies. The methodologies can be links that are described as coupled, connected and so forth, which can include unidirectional and/or bidirectional communication over wireless paths and/or wired paths that utilize one or more of various protocols or methodologies, where the coupling and/or connection can be direct (e.g., no intervening processing device) and/or indirect (e.g., an intermediary processing device such as a router).

FIG. **28** depicts an exemplary diagrammatic representation of a machine in the form of a computer system **1000** within which a set of instructions, when executed, may cause the machine to perform any one or more of the methods described above. One or more instances of the machine can operate, for example, as the devices of FIGS. **1**, **4**, and **6-8**. In some embodiments, the machine may be connected (e.g., using a network **1026**) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client user machine in server-client user network environment, or as a peer machine in a peer-to-peer (or distributed) network environment.

The machine may comprise a server computer, a client user computer, a personal computer (PC), a tablet PC, a smart phone, a laptop computer, a desktop computer, a control system, a network router, switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. It will be understood that a communication device of the subject disclosure includes broadly any electronic device that provides voice, video or data communication. Further, while a single machine is illustrated, the term "machine" shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methods discussed herein.

The computer system **1000** may include a processor (or controller) **1002** (e.g., a central processing unit (CPU), a graphics processing unit (GPU, or both), a main memory **1004** and a static memory **1006**, which communicate with each other via a bus **1008**. The computer system **1000** may further include a display unit **1010** (e.g., a liquid crystal display (LCD), a flat panel, or a solid state display. The computer system **1000** may include an input device **1012** (e.g., a keyboard), a cursor control device **1014** (e.g., a

mouse), a disk drive unit **1016**, a signal generation device **1018** (e.g., a speaker or remote control) and a network interface device **1020**. In distributed environments, the embodiments described in the subject disclosure can be adapted to utilize multiple display units **1010** controlled by two or more computer systems **1000**. In this configuration, presentations described by the subject disclosure may in part be shown in a first of the display units **1010**, while the remaining portion is presented in a second of the display units **1010**.

The disk drive unit **1016** may include a tangible computer-readable storage medium **1022** on which is stored one or more sets of instructions (e.g., software **1024**) embodying any one or more of the methods or functions described herein, including those methods illustrated above. The instructions **1024** may also reside, completely or at least partially, within the main memory **1004**, the static memory **1006**, and/or within the processor **1002** during execution thereof by the computer system **1000**. The main memory **1004** and the processor **1002** also may constitute tangible computer-readable storage media.

Dedicated hardware implementations including, but not limited to, application specific integrated circuits, programmable logic arrays and other hardware devices that can likewise be constructed to implement the methods described herein. Application specific integrated circuits and programmable logic array can use downloadable instructions for executing state machines and/or circuit configurations to implement embodiments of the subject disclosure. Applications that may include the apparatus and systems of various embodiments broadly include a variety of electronic and computer systems. Some embodiments implement functions in two or more specific interconnected hardware modules or devices with related control and data signals communicated between and through the modules, or as portions of an application-specific integrated circuit. Thus, the example system is applicable to software, firmware, and hardware implementations.

In accordance with various embodiments of the subject disclosure, the operations or methods described herein are intended for operation as software programs or instructions running on or executed by a computer processor or other computing device, and which may include other forms of instructions manifested as a state machine implemented with logic components in an application specific integrated circuit or field programmable gate array. Furthermore, software implementations (e.g., software programs, instructions, etc.) including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein. It is further noted that a computing device such as a processor, a controller, a state machine or other suitable device for executing instructions to perform operations or methods may perform such operations directly or indirectly by way of one or more intermediate devices directed by the computing device.

While the tangible computer-readable storage medium **622** is shown in an example embodiment to be a single medium, the term “tangible computer-readable storage medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term “tangible computer-readable storage medium” shall also be taken to include any non-transitory medium that is capable of storing or encoding a set of instructions for execution by the machine and that

cause the machine to perform any one or more of the methods of the subject disclosure.

The term “tangible computer-readable storage medium” shall accordingly be taken to include, but not be limited to: solid-state memories such as a memory card or other package that houses one or more read-only (non-volatile) memories, random access memories, or other re-writable (volatile) memories, a magneto-optical or optical medium such as a disk or tape, or other tangible media which can be used to store information. Accordingly, the disclosure is considered to include any one or more of a tangible computer-readable storage medium, as listed herein and including art-recognized equivalents and successor media, in which the software implementations herein are stored.

Although the present specification describes components and functions implemented in the embodiments with reference to particular standards and protocols, the disclosure is not limited to such standards and protocols. Each of the standards for Internet and other packet switched network transmission (e.g., TCP/IP, UDP/IP, HTML, and HTTP) represent examples of the state of the art. Such standards are from time-to-time superseded by faster or more efficient equivalents having essentially the same functions. Wireless standards for device detection (e.g., RFID), short-range communications (e.g., Bluetooth, WiFi, ZigBee), and long-range communications (e.g., WiMAX, GSM, CDMA, LTE) can be used by computer system **1000**.

The illustrations of embodiments described herein are intended to provide a general understanding of the structure of various embodiments, and they are not intended to serve as a complete description of all the elements and features of apparatus and systems that might make use of the structures described herein. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The exemplary embodiments can include combinations of features and/or steps from multiple embodiments. Other embodiments may be utilized and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. Figures are also merely representational and may not be drawn to scale. Certain proportions thereof may be exaggerated, while others may be minimized. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

Although specific embodiments have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, can be used in the subject disclosure.

The Abstract of the Disclosure is provided with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, it can be seen that various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separately claimed subject matter.

What is claimed is:

1. A device comprising:
 - a processing system including a processor; and
 - a memory that stores executable instructions that, when executed by the processing system, facilitate performance of operations comprising:
 - obtaining a plurality of Signal to Interference plus Noise Ratio (SINR) measurements from each of a plurality of cell sites in communication with the processing system;
 - identifying a cell site with a lowest SINR measurement, resulting in an identified cell site;
 - based on a determination that the lowest SINR measurement is less than a first SINR threshold, initiating an action to affect SINR associated with the identified cell site; and
 - transmitting information to one or more other cell sites of the plurality of cell sites that enables the one or more other cell sites to counteract the action.
2. The device of claim 1, wherein the action comprises adjusting one or more key performance indicators (KPIs) associated with the plurality of cell sites.
3. The device of claim 1, wherein the operations further comprise reversing, at least in part, the action responsive to determining that SINR associated with the identified cell site has not improved.
4. The device of claim 1, wherein the operations further comprise reversing, at least in part, the action responsive to determining that the action has had an adverse effect on another cell site of the plurality of cell sites.
5. The device of claim 4, wherein as a result of the action, the other cell site has a SINR measurement below a second SINR threshold.
6. The device of claim 5, wherein the second SINR threshold is determined according to a time of day.
7. The device of claim 5, wherein the second SINR threshold is determined according to a key performance indicator (KPI) associated with the plurality of cell sites.
8. The device of claim 1, wherein each of the plurality of cell sites is configured to perform iterated SINR measurements that are averaged over time.
9. The device of claim 1, wherein each of the plurality of SINR measurements comprises an interference component based on measurements of signals that exceed an inter-cell threshold.
10. The device of claim 1, wherein the action comprises filtering adjacent signals, adjusting gain of an uplink, filtering interference signals, utilizing diversity signal paths, adjusting a pilot signal, adjusting transmit parameters, adjusting receive parameters, adjusting a modulation scheme, adjusting a coding scheme, adjusting a position of an antenna, or a combination thereof.
11. A method comprising:
 - obtaining, by a processing system including a processor, a plurality of Signal to Interference plus Noise Ratio (SINR) measurements from each of a plurality of cell sites in communication with the processing system;
 - identifying, by the processing system, a cell site of the plurality of cell sites with a lowest SINR measurement, resulting in an identified cell site;

- based on a determination that the lowest SINR measurement is less than a first SINR threshold, causing, by the processing system, an action to be performed so as to affect SINR associated with the identified cell site; and
 - causing, by the processing system, data to be provided to one or more other cell sites of the plurality of cell sites that enables the one or more other cell sites to reverse the action.
12. The method of claim 11, wherein the action comprises adjusting one or more key performance indicators (KPIs) associated with the plurality of cell sites.
 13. The method of claim 11, further comprising reversing, by the processing system, the action at least in part, responsive to determining that SINR of the identified cell site has not improved.
 14. The method of claim 11, further comprising reversing, by the processing system, the action at least in part, responsive to determining that the action has had an adverse effect on another cell site of the plurality of cell sites.
 15. The method of claim 14, wherein as a result of the action, the other cell site has a SINR measurement below a second SINR threshold.
 16. A non-transitory machine-readable medium comprising executable instructions that, when executed by a processing system including a processor, facilitate performance of operations comprising:
 - obtaining a plurality of Signal to Interference plus Noise Ratio (SINR) measurements from each of a plurality of cell sites in communication with the processing system, each of the plurality of SINR measurements comprising an interference component;
 - identifying a cell site with a lowest SINR measurement, resulting in an identified cell site;
 - based on a determination that the lowest SINR measurement is less than a first SINR threshold, initiating an action to affect SINR associated with the identified cell site; and
 - providing information to one or more other cell sites of the plurality of cell sites that enables the one or more other cell sites to reverse the action.
 17. The non-transitory machine-readable medium of claim 16, wherein the action comprises adjusting one or more key performance indicators (KPIs) associated with the plurality of cell sites.
 18. The non-transitory machine-readable medium of claim 16, wherein the operations further comprise reversing the action at least in part, responsive to determining that SINR of the identified cell site has not improved.
 19. The non-transitory machine-readable medium of claim 16, wherein the operations further comprise reversing the action at least in part, responsive to determining that the action has had an adverse effect on another cell site of the plurality of cell sites.
 20. The non-transitory machine-readable medium of claim 19, wherein as a result of the action, the other cell site has a SINR measurement below a second SINR threshold.