

US00931155B2

(12) **United States Patent**
Smith

(10) **Patent No.:** **US 9,931,155 B2**
(45) **Date of Patent:** ***Apr. 3, 2018**

(54) **SURGICAL MULTI-TOOL AND METHOD OF USE**

(71) Applicant: **Divyze, Inc.**, Wellington, NV (US)

(72) Inventor: **Ryan D. Smith**, Wellington, NV (US)

(73) Assignee: **Divyze, Inc.**, Wellington, NV (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/206,598**

(22) Filed: **Jul. 11, 2016**

(65) **Prior Publication Data**
US 2017/0128125 A1 May 11, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/721,812, filed on May 26, 2015, now Pat. No. 9,393,066, which is a (Continued)

(51) **Int. Cl.**
A61B 18/14 (2006.01)
A61B 17/3201 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 18/1442** (2013.01); **A61B 17/00234** (2013.01); **A61B 17/3201** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 18/085; A61B 18/1442; A61B 18/1445; A61B 2018/00607;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

462,270 A 11/1891 McConnaughey
2,895,478 A 7/1959 Post
(Continued)

FOREIGN PATENT DOCUMENTS

JP H10 24177 1/1998
WO WO 01/66025 9/2001
WO WO 2015/077350 5/2015

OTHER PUBLICATIONS

European Search Report for EP Application No. 14864016.2, dated Jul. 20, 2017.

(Continued)


Primary Examiner — Thomas Giuliani

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

Surgical tools and methods are disclosed. The surgical tool has a first tip comprising a first tip longitudinal axis and a second tip. The surgical tool has a first configuration wherein the first and second tips operate as forceps. The surgical tool has a second configuration wherein the first and second tips operate as scissors, wherein the surgical tool is configured to transition between the first configuration and the second configuration, at least in part, by rotation of the first tip about the first tip longitudinal axis.

18 Claims, 10 Drawing Sheets



Related U.S. Application Data

	continuation of application No. 14/547,748, filed on Nov. 19, 2014, now Pat. No. 9,050,101.	6,391,043 B1 *	5/2002	Moll	A61B 17/295 30/134
(60)	Provisional application No. 61/906,337, filed on Nov. 19, 2013.	6,458,129 B2	10/2002	Scarfi	
		6,592,603 B2	7/2003	Lasner	
		6,773,434 B2	8/2004	Ciarrocca	
		6,976,992 B2	12/2005	Sachatello et al.	
		7,208,005 B2 *	4/2007	Frecker	A61B 17/29 606/167
(51)	Int. Cl.	7,410,494 B2 *	8/2008	Kalman	A61B 17/29 606/174
	<i>A61B 18/12</i> (2006.01)	7,544,195 B2	6/2009	Lunsford et al.	
	<i>A61B 17/00</i> (2006.01)	8,114,074 B1	2/2012	Slater	
	<i>A61B 18/00</i> (2006.01)	8,398,673 B2 *	3/2013	Hinchliffe	A61B 17/1608 606/205
(52)	U.S. Cl.	8,597,293 B2	12/2013	Falkenstein et al.	
	CPC <i>A61B 18/1206</i> (2013.01); <i>A61B 18/1445</i> (2013.01); <i>A61B 2017/00353</i> (2013.01); <i>A61B 2018/0091</i> (2013.01); <i>A61B 2018/00595</i> (2013.01); <i>A61B 2018/126</i> (2013.01); <i>A61B 2018/146</i> (2013.01); <i>A61B 2018/1457</i> (2013.01)	9,050,101 B1 *	6/2015	Smith	A61B 17/3201
		9,393,066 B2 *	7/2016	Smith	A61B 17/3201
		2003/0073987 A1	4/2003	Sakurai et al.	
		2003/0073991 A1	4/2003	Francischelli	
		2006/0167450 A1 *	7/2006	Johnson	A61B 18/1445 606/48
(58)	Field of Classification Search	2007/0118111 A1	5/2007	Weinberg	
	CPC A61B 2018/0063; A61B 2018/1457; A61B 2018/1452; A61B 2018/146; A61B 2018/1462; A61B 2018/0091; A61B 2018/126; A61B 17/30; A61B 2017/00353	2007/0244515 A1	10/2007	Fanou	
	USPC 606/41, 50-52, 174, 206, 207	2010/0023001 A1	1/2010	Hosaka et al.	
	See application file for complete search history.	2011/0238066 A1 *	9/2011	Olson	A61B 17/295 606/51
		2012/0083827 A1	4/2012	Artale	
		2012/0209305 A1	8/2012	Deodhar et al.	
		2013/0178852 A1	7/2013	Allen et al.	
		2015/0141992 A1	5/2015	Smith	
		2015/0327911 A1	11/2015	Smith	

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,651,811 A	3/1972	Hildebrandt et al.	
3,977,410 A	8/1976	Huston et al.	
4,478,221 A	10/1984	Heiss	
4,669,470 A	6/1987	Brandfield	
4,819,636 A	4/1989	Gerich et al.	
5,047,049 A	9/1991	Salai	
5,637,111 A *	6/1997	Sutcu	A61B 18/1445 606/174
6,096,059 A	8/2000	Kuzma	
6,106,542 A	8/2000	Toybin et al.	
6,283,963 B1	9/2001	Regula	

OTHER PUBLICATIONS

Surgical Neurology International, 2012, vol. 3, No. 152, pp. 1-3, published Dec. 14, 2012.
 Written Opinion of the International Searching Authority for PCT/US2014/066432, dated Mar. 13, 2015 in 6 pages.
 Matsumura, Nobuhisa, A new bayonet spring microsurgical instrument handle 1-21 with a bar for microneurosurgery, Surgical Neurology International, 2012, vol. 3, No. 152, pp. 1-3 (internal).
 Written Opinion of the International Searching Authority for PCT/US2017/038381, dated Sep. 19, 2017 in 13 pages.

* cited by examiner




Fig. 1




Fig. 2A





Fig. 2B






Fig. 5A





Fig. 5B



SECTION B-B
SCALE 2 : 1




Fig. 6A




Fig. 6B

Forcep

Fig. 7A






Fig. 7B



SECTION D-D
SCALE 2 : 1

Fig. 7C



VIEW G-G
SCALE 2 : 1

Scissor

Fig. 8A






Fig. 8B



SECTION P-P
SCALE 2 : 1

Fig. 8C



VIEW T-T
SCALE 2 : 1




Fig. 9A

Fig. 9B

Fig. 9C

Fig. 9D

SECTION K-K
SCALE 2 : 1

Fig. 10A




Fig. 10B





Fig. 10C



1

SURGICAL MULTI-TOOL AND METHOD OF USE

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 14/721,812, filed May 26, 2015, issued as U.S. Pat. No. 9,393,066 on Jul. 19, 2016 which is a continuation of U.S. patent application Ser. No. 14/547,748, filed Nov. 19, 2014, issued as U.S. Pat. No. 9,050,101 on Jun. 9, 2015, which claims priority benefit under 35 U.S.C. § 119(e) of U.S. Provisional Patent Application No. 61/906,337 filed Nov. 19, 2013, the disclosures of each are incorporated by reference herein in their entirety.

BACKGROUND OF THE INVENTION

Field of the Invention

The present application relates to the field of medical devices, and encompasses apparatuses for use during surgery and surgical methods. In particular, the application relates to surgical hand tools having a plurality of configurations including a forceps configuration and a scissors configuration.

Description of the Related Art

Surgical tools typically serve a single function. Surgical scissors are useful for cutting tissue. Surgical forceps are useful for manipulating tissues. Electrosurgical devices are useful for cauterization, hemostasis, and for tissue dissection. Electrosurgical devices most commonly involve radiofrequency (RF) energy wherein a voltage gradient is produced between two points and current flows through the tissue, dissipating energy as heat. This in turn allows refolding of protein and coagulation or dissection of tissue.

Each surgical tool has limitations. For instance, in relation to electrosurgical devices, the passage of current through the tissue does not allow cutting of all tissues. This limitation is pronounced when the distance between the two contact points of the device is increased. Furthermore, tissue cutting can be accomplished more quickly with scissors in many instances where cauterization is not needed for hemostasis.

SUMMARY OF THE INVENTION

In some embodiments, a surgical tool (sometimes referred to as a hand tool) is provided. The surgical tool can include a first handle comprising a proximal portion and a distal portion and a first recess in the distal portion. The surgical tool can include a second handle comprising a proximal portion and a distal portion and a second recess in the distal portion. The surgical tool can include a first tip disposed in the first recess and extending distally therefrom, the first tip having a first external surface and a first internal surface. The surgical tool can include a second tip disposed in the second recess and extending distally therefrom, the second tip having a second external surface and a second internal surface. In some embodiments, the surgical tool has a first configuration wherein the first and second tips operate as forceps. In some embodiments, the surgical tool has a second configuration wherein the first and second tips operate as scissors. In some embodiments, rotation of the first tip and the second tip within their respective recesses transitions the surgical tool between the first configuration and the second configuration.

In some embodiments, the first inner surface and the second inner surface are configured to abut each other

2

during rotation of the first tip and the second tip within their respective recesses to transition the surgical tool between the first configuration and the second configuration. In some embodiments, the second tip comprises a pin extending from the second external surface, and rotation of the pin relative to the second handle causes rotation of the second tip relative to the second recess and transitions the surgical tool between the first configuration and the second configuration. In some embodiments, rotation of the pin relative to the second handle rotates the first tip relative to the first recess. In some embodiments, the pin is substantially perpendicular to a longitudinal axis of the second tip. In some embodiments, the first tip comprises a first electrode and the second tip comprises a second electrode. In some embodiments, the first tip and the second tip are configured to interact as electrocautery bipolar forceps in the first configuration. In some embodiments, in the second configuration, the first and second inner surfaces are configured to shear past each other. In some embodiments, one of the first tip and the second tip comprises a recess and the other of the first tip and the second tip comprises a protrusion, wherein the protrusion is configured to be received relative to the recess in the second configuration to provide an axis about which the tips can rotate. In some embodiments, the surgical tool can include a sleeve surrounding at least a portion of the first tip. In some embodiments, the surgical tool can include a locking mechanism configured to prevent rotation of the second tip. In some embodiments, the first handle is coupled to the second handle near a proximal end of the surgical tool. In some embodiments, the surgical tool can include one or more springs attached to the handles to bias the first and second tips to a neutral position.

In some embodiments, a method of using a surgical tool is provided. The method can include the step of providing a first handle and a second handle coupled to each other, the first handle having a first tip extending distally therefrom and the second handle having a second tip extending distally therefrom, wherein the first and second tips are configured for use as forceps. The method can include the step of rotating the first tip relative to the first handle and rotating the second tip relative to the second handle, wherein the rotation reconfigures the first and second tips for use as scissors.

The method can include the step of bringing inner surfaces of the first and second tips into contact with each other so that longitudinal axes of the first and second tips are aligned, and then rotating the first tip relative to the first handle and rotating the second tip relative to the second handle. In some embodiments, after rotating the first tip relative to the first handle and rotating the second tip relative to the second handle, the inner surfaces of the first and second tips are configured to shear past each other. The method can include the step of rotating a pin extending from one of the first tip and the second tip to rotate the first tip relative to the first handle and rotate the second tip relative to the second handle. The method can include the step of applying electrical energy to tissue with the first tip and the second tip. In some embodiments, rotating the first tip relative to the first handle and the second tip relative to the second handle further comprises rotating the first tip ninety degrees and rotating the second tip ninety degrees.

In some embodiments, a surgical tool is provided. The surgical tool can include a first handle. The surgical tool can include a first tip coupled to the first handle and configured to rotate relative to the first handle, the first tip having a first internal surface. The surgical tool can include a second handle. The surgical tool can include a second tip coupled to

3

the second handle and configured to rotate relative to the second handle, the second tip having a second internal surface. In some embodiments, the surgical tool has a first configuration wherein the first internal surface and the second internal surface are generally vertical. In some embodiments, movement of the first handle or the second handle changes the distance between the first tip and the second tip in the first configuration. In some embodiments, the surgical tool has a second configuration wherein the first internal surface and the second internal surface are generally horizontal. In some embodiments, movement of the first handle or the second handle shears an edge of the first tip past an edge of the second tip in the second configuration. In some embodiments, the tips are configured to rotate to transition between the first configuration and the second configuration.

In some embodiments, a surgical tool is provided. The surgical tool can include a first handle and a second handle. In some embodiments, the first handle and the second handle are configured to have a first configuration and a second configuration. In some embodiments, in the first configuration the tool operates as forceps and in the second configuration the tool operates as scissors.

The surgical tool or hand tool can be used in surgical sites with limited lateral access and substantial depth. The multiple configurations can allow for tissue dissection by cutting and electrocautery. The interchangeability of the hand tool limits the number of times the hand tool would need to be removed, exchanged, and re-inserted into the surgical site. The interchangeability can limit the potential for injury, while improving usability and efficiency.

The surgical tool or hand tool of certain embodiments advantageously provides multiple functional configurations that are easily interchanged by the user. The hand tool is capable of use in open microsurgery, minimally invasive surgery, and other surgical environments. The hand tool may be a single handheld device, which allows the interchangeability of configurations without the user removing the device from the local surgical field.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the invention disclosed herein are described below with reference to the drawings of preferred embodiments, which are intended to illustrate and not to limit the invention. Additionally, from figure to figure, the same reference numerals have been used to designate the same components of an illustrated embodiment. The following is a brief description of each of the drawings.

FIG. 1 is an exploded view of a hand tool.

FIG. 2A is a perspective view of the hand tool of FIG. 1 in the forceps configuration.

FIG. 2B is a top view of the hand tool of FIG. 1 in the forceps configuration.

FIG. 3 is a perspective view of the hand tool of FIG. 1, wherein the tips are brought together to change configurations.

FIG. 4 is a perspective view of the hand tool of FIG. 1 in the scissors configuration.

FIG. 5A is a front view of the hand tool of FIG. 1 in the forceps configuration; FIG. 5B is a cross-sectional view taken along line B-B in FIG. 5A.

FIG. 6A is a front view of the hand tool of FIG. 1 in the scissors configuration; FIG. 6B is a cross-sectional view taken along line M-M in FIG. 6A.

4

FIG. 7A is a side view of the hand tool of FIG. 1 in the forceps configuration; FIG. 7B is a cross-sectional view taken along line D-D in FIG. 7A; FIG. 7C is a cross-sectional view taken along line G-G in FIG. 7A.

FIG. 8A is a side view of the hand tool of FIG. 1 in the scissors configuration; FIG. 8B is a cross-sectional view taken along line P-P in FIG. 8A; FIG. 8C is a cross-sectional view taken along line T-T in FIG. 8A.

FIG. 9A is a perspective view of a hand tool in the scissors configuration with a sleeve; FIG. 9B is a top view of the hand tool of FIG. 9A; FIG. 9C is side view of the hand tool of FIG. 9A; and FIG. 9D is a cross-sectional view taken along line K-K in FIG. 9A.

FIG. 10A is a perspective view of the hand tool in the scissors configuration with a locking mechanism; FIG. 10B is a top view of the hand tool of FIG. 10A; FIG. 10C is a side view of the hand tool of FIG. 10A.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the surgical hand tool include two sections used together to perform a function. One or more of the sections can comprise segments, portions, components, or subcomponents. However, the use of the term “section” does not imply any particular structure or configuration. In some embodiments, the right section or components thereof are mirror image, identical, or substantially similar to the left section or components thereof. The sections or components thereof may be any suitable shape that permits the function of the hand tool, for instance perform the function of scissors and forceps. Certain embodiments are illustrated and/or described herein.

With reference to FIGS. 1-2A, a hand tool **100** is shown. The hand tool **100** can also be referred to as a surgical multi-tool. The hand tool **100** comprises two sections: a left section **102** and a right section **202**. In the illustrated configuration, the left section **102** includes multiple components and the right section **202** includes multiple components as described further below. The left section **102** interacts with the right section **202** to perform one or more functions, such as operating as forceps and scissors as described in detail below. The hand tool **100** has a longitudinal axis **106** that extends between a proximal end **116** and a distal end **118**. The left section **102** can be on the left side of the longitudinal axis **106** when the hand tool **100** is viewed from the top. The right section **202** can be on the right side of the longitudinal axis **106** when the hand tool **100** is viewed from the top.

The surgical hand tool **100** can transition between functional configurations. As illustrated in FIGS. 1 and 2A, the left section **102** can comprise a left handle **132** and a left tip **160** extending distally from the left handle **132**. The right section **202** can comprise a right handle **232** and a right tip **260** extending distally from the right handle **232**. The surgical hand tool can operate as forceps, which can also be referred to as the forceps configuration, with the left tip **160** and the right tip **260** providing the grasping ends of the forceps. In this and other configurations, the surgical hand tool **100** can also include electrodes. For example, the surgical hand tool of FIGS. 1 and 2A can function as electrocautery bipolar forceps, as described further below. The surgical hand tool can further be configured to operate as scissors, which can also be referred to as the scissors configuration. FIG. 4, described in more detail below, illustrates a scissors configuration where the tips **160**, **260** slide and pivot relative to each other to cut tissue. The scissors can

be utilized to more quickly cut tissue. The multiple configurations allow for the use of multiple surgical techniques at the discretion of the user. Other functional configurations are possible.

Referring now to FIGS. 2A-4, the hand tool 100 is designed to transition between the forceps configuration and the scissors configuration. The forceps configuration is shown in FIG. 2A and the scissors configuration is shown in FIG. 4. The intermediate configuration is shown in FIG. 3. The hand tool 100 permits the switching between the forceps configuration and the scissors configuration. The hand tool 100 can transition between these configurations by rotation of the tips 160, 260 of the hand tool 100, as described further below. The tips 160, 260 are rotated approximately 90 degrees between the forceps configuration shown in FIG. 2A and the scissors configuration shown in FIG. 4. The tips can be brought together as shown in FIG. 3 during the transition between the forceps configuration and the scissors configuration.

Components of the Hand Tool

In some embodiments, the forceps configuration as shown in FIG. 2A can operate as bipolar electrocautery forceps. For instance, the hand tool 100 can include one or more electrodes located on the tips of the hand tool. The hand tool 100 can be designed to supply electrical energy to the electrodes. In some embodiments, the hand tool 100 can optionally include an electrical connection 110. The electrical connection 110 can include a left lead 112 and a right lead 212. The electrical connection 110 can enable the electrodes to be supplied with electrical energy. In the illustrated configuration, the electrical connection 110 can be near the proximal end 116 of the hand tool 100.

In some embodiments, the hand tool 100 can include a mechanical connector 122. The mechanical connector 122 can function to electrically isolate the incoming electrical leads 112, 212. The mechanical connector 122 can function to couple the left section 102 and the right section 202.

The left lead 112 can include a receptacle 114. The receptacle 114 can be sized to accept the left spring 124. The left section 102 can include a left spring 124 that extends along the longitudinal axis 106. The left spring 124 can be coupled to the mechanical connector 122. In some embodiments, the left spring 124 can have an external shape that complements the shape of a receptacle 126 in the mechanical connector 122. In the illustrated embodiment, the shape of the left spring 124 is rectangular and the shape of the receptacles 126 is rectangular. Other shapes are contemplated (e.g., wedge, oval, triangular, elliptical, polygonal, etc.). The left spring 124 can be coupled to the mechanical connector 122 by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. The left spring 124 can be coupled to the left lead 112 of the electrical connection 110. In the illustrated embodiment, the left spring 124 is coupled to the left lead 112 within the mechanical connector 122. The left spring 124 can be coupled to the left lead 112 by welding, fasteners or other fixation method.

The left spring 124 can include a bend 128. The bend 128 can function to extend the distal end of the left spring 124 away from the longitudinal axis 106. The bend 128 can function to curve the left spring 124 outward from the mechanical connector 122. The bend 128 of the left spring 124 can function to increase the distance between the left section 102 and the right section 202. The left spring 124 can include a concave portion. The concave portion can be near

the proximal end of the left spring 124. The left spring 124 can include a convex portion. In the illustrated embodiment, the convex portion can be near the distal end of the left spring 124. The left spring 124 can include one or more flat portions 120, 130. In the illustrated embodiment, the flat portion 120 can be disposed within the receptacle 114. In other configurations the flat portion can be near the proximal end, distal end, or in between the proximal and distal end of the left spring 124. Other configuration of the spring can be contemplated (e.g., multiple bends, flat portions, multiple layers, thicknesses, varying thickness, height and length, etc.).

The distal end of the left spring 124 can be coupled to a left handle 132. In some embodiments, the left spring 124 can have an external shape that complements the shape of a receptacle 134 in the left handle 132. In the illustrated embodiment, the flat portion 130 can be disposed within the receptacle 134. In the illustrated embodiment, the shape of the left spring 124 is rectangular and the shape of the receptacle 134 is rectangular. Other configurations are contemplated (e.g., wedge, oval, triangular, elliptical, polygonal, etc.). The left spring 124 can be coupled to the left handle 132 by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. In the illustrated embodiment, the receptacle 134 is a slot that extends from the top of the left handle 132 to the bottom of the left handle 132, or a portion thereof. In some embodiments, the left spring 124 can be adjustable within the receptacle 134 of the left handle 132. In some embodiments, the left spring 124 can be adjusted to a number of discrete positions with the receptacle 134 (e.g., two, three, four, five, etc.). In some embodiments, the left spring 124 can be adjusted to an infinite number of positions with the receptacle 134. The left spring 124 can remain movable, releasably retained or fixedly retained in position.

The left handle 132 can include one or more finger grips 136 (see FIG. 9A). In the illustrated embodiment, two finger grips 136 are shown. Other numbers of finger grips are contemplated (e.g., one, two, three, four, five, etc.). Both of the finger grips 136 are shown on the exterior surface of the left handle 132. Other locations are possible (e.g., top surface, bottom surface, interior surface, at least one grip on the exterior surface, at least one grip on the top surface, a grip on the top surface and a grip on the exterior surface, etc.).

The left handle 132 can have a bayonet configuration. The left handle 132 can include a longitudinally extending portion 138 and a vertically extending portion 140. The longitudinally extending portion 138 can extend generally along the longitudinal axis 106. The vertically extending portion 140 can extend upward from the longitudinally extending portion 138. The vertically extending portion 140 can improve the line of sight for the user. The user's hand can engage the longitudinally extending portion 138. The vertically extending portion 140 can raise the distal end 118 of the hand tool 100 away from the user's hand. The user's hand does not obstruct the line of sight to the distal end 118 of the hand tool 100. In the illustrated embodiment, the vertically extending portion 140 forms an angle 142 with the longitudinally extending portion 138. The angle 142 can be 90° or greater than 90° (e.g., 100°, 110°, 120°, 130°, 140°, 150°, 160°, 170°, etc.). The angle 142 can be obtuse. Other configurations are possible. The angle 142 can provide a more ergonomic grip to the user.

The left section 102 can include a left hub 144. The left hub 144 can extend from the vertically extending portion 140. In some embodiments, the left hub 144 can be a unitary

structure with the vertically extending portion **140** of the left handle **132**. The left hub **144** and the left handle **132** can be monolithically formed.

In other embodiments, the left hub **144** is a separate component from the left handle **132**. The vertically extending portion **140** can include a recess **146**. The left hub **144** can be coupled to the recess **146** by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. In some embodiments, the left hub **144** is removable from the vertically extending portion **140**. For instance, the left hub **144** can be removed to permit sterilization of the left tip **160**. The left hub **144** can be removed to replace the left tip **160**.

The left hub **144** can include a proximal portion **148**. The proximal portion **148** of the left hub **144** can be received within the recess **146** of the vertically extending portion **140**. The recess **146** can be shaped to complement the external surface of the proximal portion **148**. The proximal portion **148** can be any cross-sectional shape including semi-circular, triangular, rectangular, etc. In some embodiments, the proximal portion **148** can extend the entire length of the vertically extending portion **140**. The edge **150** of the proximal portion **148** can be angled to match the angle **142**.

The left hub **144** can include a distal portion **152**. The distal portion **152** can extend from the vertically extending portion **140**. The distal portion **152** can extend from the recess **162** when proximal portion **148** is received within the recess **162**. The edge **154** of the distal portion **152** can include a hub recess **156**. The distal portion **152** can be a portion of a cylinder. The distal portion **152** can be any cross-sectional shape including semi-circular. In some embodiments, the proximal portion **148** and the distal portion **152** have the same cross-sectional shape. In other embodiments, the proximal portion **148** and the distal portion **152** have different cross-sectional shapes. In some embodiments, the proximal portion **148** and the distal portion **152** can have the same diameter. In other embodiments, the proximal portion **148** and the distal portion **152** have different diameters.

The left hub **144** can define a left tip axis **158**. The left tip axis **158** can be the axis upon which the left tip **160** rotates. The distal portion **152** of the left hub **144** can function to support the left tip **160** during rotation. The hub recess **156** can be aligned with the left tip axis **158**. The hub recess **156** can function to maintain alignment of the left tip **160** during rotation. In some methods of assembly, the left hub **144** is coupled to the vertically extending portion **140**. This can create a channel between the external surface of the left hub **144** and the internal surface of the recess **162**. A portion of the left tip **160** can rotate within this channel.

The left tip **160** can include a proximal portion **164**. The proximal portion **164** of the left tip **160** can be supported by the left hub **144**. The proximal portion **164** of the left tip **160** can rotate about the left hub **144**. At least a portion of the proximal portion **164** of the left tip **160** can be received within the recess **162** of the vertically extending portion **140**.

In the illustrated embodiment, the recess **162** of the vertically extending portion **140** can include a first portion **166** and a second portion **168**. The first portion **166** can have a circular cross-section and the second portion **168** can have a circular cross-section. The first portion **166** can have a semi-circular cross-section and the second portion **168** can have a semi-circular cross-section. The cross-sectional shapes of the first portion **166** and the second portion **168** can permit rotation of the left tip **160** within the recess **162**.

The first portion **166** can have a first diameter and the second portion **168** can have a second diameter. The first

diameter can be smaller than the second diameter. The first portion **166** can be located distal to the second portion **168**. The first portion **166** of the recess **162** can be closer to the distal end **118**. The second portion **168** can be located proximal to the first portion **166**. The second portion **168** of the recess **162** can be closer to the proximal end **116**. The difference in diameter between the first portion **166** and the second portion **168** of the recess **162** can create a lip.

The recess **162** can have any number of portions (e.g., two, three, four, five, six, etc.). Each portion can have a diameter that is either the same or different than one or more other portions. At least two of the portions have unequal diameters. Of the at least two portions, a portion near the distal end can have a smaller diameter than another portion near the proximal end. The difference in diameter between the portions of the recess **162** can create a lip.

In the illustrated embodiment, the left tip **160** can include a ridge **174** which can interact with the lip. The ridge **174** can extend from the external surface of the proximal portion **164** of the left tip **160**. The ridge **174** can be sized to be received within the second portion **168** of the recess **162**. For instance, the ridge **174** and the second portion **168** can have the same or similar diameter. The ridge **174** can have a larger diameter than the first portion **166**. The ridge **174** can abut the lip created by the first portion **166** and the second portion **168**. The ridge **174** can reduce axial translation of the left tip **160** when the left tip **160** is received within the recess **162**. The ridge **174** can reduce the longitudinal movement of the left tip **160** when the ridge **174** is received within the recess **162**. The ridge **174** can prevent disengagement between the vertically extending portion **140** and the left tip **160** by the application of axial force.

The proximal portion **164** of left tip **160** can include a left extension **178** which can interact with the hub **144**. The left extension **178** can be a portion of a cylinder. In some embodiments, the left extension **178** can have a quarter-circular cross-section (e.g., encompasses 90 degrees). The left extension **178** can have a convex external surface. The convex external surface can be complementary to the second portion **168**. The left extension **178** can have a concave internal surface **180**. The concave internal surface **180** can be complementary to the external surface of the distal portion **152** of the left hub **144**.

The proximal portion **164** of left tip **160** can include a protrusion **172** which can interact with the hub recess **156**. The protrusion **172** is sized to be received within the hub recess **156**. For instance, the protrusion **172** and the hub recess **156** can have the same or similar diameter. The protrusion **172** can extend along the left tip axis **158** when the ridge **174** is received within the recess **162**. The protrusion **172** and the hub recess **156** can provide a pivot for the left tip **160** as the left tip **160** rotates.

The left tip **160** can include a distal portion **170**. The distal portion **170** of the left tip **160** can include a longitudinally extending portion **182**. The longitudinally extending portion **182** can be a portion of a cylinder. In some embodiments, the longitudinally extending portion **182** can have a semi-circular cross-section (e.g., encompasses 180 degrees). The longitudinally extending portion **182** can have a convex external surface. The distal **170** and longitudinally extending **182** portions can have other cross-sectional shapes (e.g., circular, elliptical, square, rectangular, triangular, polygonal, sigmoid, etc.).

The distal portion **170** of the left tip **160** can include a conical portion **186**. The conical portion **186** can extend to a distal tip **188**. The conical portion **186** and distal tip **188** can interact with the right section **202** to function as forceps.

The conical portion **186** can include a cutting edge **190**. The cutting edge **190** can interact with the right section **202** to function as scissors. The cutting edge **190** can be the same material as the distal portion **170** of the left tip **160**. The cutting edge **190** can be the same material as the left tip **160**. The cutting edge **190** can be a different material than the distal portion **170** of the left tip **160**. The cutting edge **190** can be a different material than the left tip **160**. The cutting edge **190** can be integrally or monolithically formed with the left tip **160**. The cutting edge **190** can be a separate component and coupled to the left tip **160**.

The distal portion **170** of the left tip **160** can have a flat internal surface **184**. The flat internal surface **184** can be complementary to an internal surface of the right section **202**. The flat internal surface **184** can extend the length of the longitudinally extending portion **182**. The flat internal surface **184** can extend the length of the conical portion **186**. The flat internal surface **184** can abut a flat internal surface of the right tip. Other cross-sectional shapes of the internal surface can be contemplated (e.g., circular, elliptical, square, rectangular, triangular, polygonal, sigmoid etc.). These can be complimentary, mirror or rotationally similar to the right tip **260**.

The distal portion **170** of the left tip **160** can include an electrode **192**. In some embodiments, the longitudinally extending portion **182** can include the electrode **192**. In some embodiments, the conical portion **186** can include the electrode **192**. In some embodiments, the distal tip **188** can include the electrode **192**. In some embodiments, the flat internal surface **184** can include the electrode **192**. In some embodiments, the external surface of the left tip **160** can include the electrode **192**. The electrode **192** can interact with the right section **202**. The right section **202** can include a ground or another electrode. The left tip **160** can interact with the right section to function as an electrosurgical device. The electrode **192** can be activated by electrical energy supplied to the hand tool **100**. The electrode **192** can be activated when the hand tool **100** is in the forceps configuration. In some embodiments, electrical energy is prevented from being supplied when the hand tool **100** is in the scissors configuration. The electrode **192** can be the same material as the distal portion **170** of the left tip **160**. The electrode **192** can be the same material as the left tip **160**. The electrode **192** can be a different material than the distal portion **170** of the left tip **160**. The electrode **192** can be a different material than the left tip **160**. The electrode **192** can be integrally or monolithically formed with the left tip **160**. The electrode **192** can be a separate component and coupled to the left tip **160**.

In some embodiments, the left lead **112** can pass through a channel in the left spring **124**. The left lead **112** can pass through a channel in the left handle **132**. The left lead **112** can pass through a channel in the left tip **160**. The channels in any of the components in the left section **102** can be insulated.

In some methods of assembly, the left tip **160** is inserted within the recess **162**. Then the left hub **144** is coupled to the vertically extending portion **140**. The left tip **160** is placed in the recess prior to coupling of the left hub **144**. The left tip **160** can be retained within the recess **162** by a retention mechanism (not shown). In some embodiments, the left hub **144** is removable. The left hub **144** can be removed to replace the left tip **160**. The left hub **144** can be removed to sterilize or replace the left tip **160**.

In some embodiments, the left hub **144** is integrally formed with the vertically extending portion **140**. Then the left tip **160** is inserted within the recess **162**. The ridge **174**

is aligned with the second portion **168** the recess **162** in the vertically extending portion **140**. The internal surface **180** of the left extension **178** is aligned with the external surface of the left hub **144**. The protrusion **172** of the left tip **160** is aligned with the hub recess **146**. From this position, the left tip **160** can be rotated about the left tip axis **158**. The left tip **160** can be rotated until the ridge **174** is received within the second portion **168** of the recess **162**. In this position, the internal surface **180** of the left extension **178** can be in contact with the external surface of the left hub **144**. In this position, protrusion **172** can be received within the hub recess **146**.

In some embodiments, the left section **102** and the right section **202** each form of a symmetrical, opposed half. The right section **202** can be a mirror image of the left section **102**. The right section **202** can include substantially similar or identical components. In some embodiments, the right section **202** may have a different shape or configuration to enhance ergonomics for the user.

The right lead **212** can include a receptacle **214**. The receptacle **214** can be sized to accept the right spring **224**. The right section **202** can include a right spring **224** that extends along the longitudinal axis **106**. The right spring **224** can be coupled to the mechanical connector **122**. In some embodiments, the right spring **224** can have an external shape that complements the shape of a receptacle **226** in the mechanical connector **122**. In the illustrated embodiment, the shape of the right spring **224** is rectangular and the shape of the receptacles **226** is rectangular. Other configurations are contemplated (e.g., wedge, oval, triangular, elliptical, polygonal, etc.). The right spring **224** can be coupled to the mechanical connector **122** by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. The right spring **224** can be coupled to the right lead **212** of the electrical connection **110**. In the illustrated embodiment, the right spring **224** is coupled to the right lead **212** within the mechanical connector **122**. The right spring **224** can be coupled to the right lead **212** by welding, fasteners or other fixation method.

The right spring **224** can include a bend **228**. The bend **228** can function to extend the distal end of the right spring **224** away from the longitudinal axis **106**. The bend **228** can function to curve the right spring **224** outward from the mechanical connector **122**. The bend **228** of the right spring **224** can function to increase the distance between the left section **102** and the right section **202**. The right spring **224** can include a concave portion. The concave portion can be near the proximal end of the right spring **224**. The right spring **224** can include a convex portion. In the illustrated embodiment, the convex portion can be near the distal end of the right spring **224**. The right spring **224** can include one or more flat portions **220**, **230**. In the illustrated embodiment the flat portion **220** can be disposed within the receptacle **214**. In other configurations the flat portion can be near the proximal end, distal end, or in between the proximal and distal end of the right spring **224**. The right spring **224** can provide the same or different resistance as the left spring **124**. The right spring **224** can provide the same or different shape as the left spring **124**. The right spring **224** can be a mirror image of the left spring **124**.

The distal end of the right spring **224** can be coupled to a right handle **232**. In some embodiments, the right spring **224** can have an external shape that complements the shape of a receptacle **234** in the right handle **232**. In the illustrated embodiment the flat portion **230** can be disposed within the receptacle **234**. In the illustrated embodiment, the shape of the right spring **224** is rectangular and the shape of the

receptacle **234** is rectangular. Other configurations are contemplated (e.g., wedge, oval, triangular, elliptical, polygonal, etc.). In the illustrated embodiment, the receptacle **234** is a slot that extends from the top of the right handle **232** to the bottom of the right handle **232**, or a portion thereof. In some embodiments, the right spring **224** is coupled to the right handle **232** by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. In some embodiments, the right spring **224** is adjustable within the receptacle **234** of the right handle **232**. In some embodiments, the right spring **224** can be adjusted to a number of discrete positions with the receptacle **234** (e.g., two, three, four, five, etc.). In some embodiments, the right spring **224** can be adjusted to an infinite number of positions with the receptacle **234**. The right spring **224** can remain movable, releasably retained or fixedly retained in position. In some embodiments, the right spring **224** is movable and the left spring **124** is fixed. At least one spring **124**, **224** can be movable to accommodate the user's hand. In some embodiments, both springs **124**, **224** are movable to accommodate the user's hand.

The right handle **232** can include one or more finger grips **236**. In the illustrated embodiment, two finger grips **236** are shown but other configurations are contemplated (e.g., one, two, three, four, five, etc.). Both of the finger grips **236** are shown on the exterior surface of the right handle **232**. Other locations are possible (e.g., top surface, bottom surface, interior surface, at least one grip on the exterior surface, at least one grip on the top surface, a grip on the top surface and a grip on the exterior surface, etc.). The finger grips **236** can have the same or different configuration as the finger grips **136**. For instance, one set of finger grips can be shaped for the index finger and the other set of grips can be shaped for the thumb. The finger grips **136**, **236** can be positioned based on the manner in which the user is expected to hold the hand tool **100**. The finger grips **136**, **236** can be positioned based on right handed use. The finger grips **136**, **236** can be positioned based on left handed use. The finger grips **136**, **236** can be positioned based on ambidextrous use.

The right handle **232** can have a bayonet configuration. The right handle **232** can include a longitudinally extending portion **238** and a vertically extending portion **240**. The longitudinally extending portion **238** can extend generally along the longitudinal axis **106**. The vertically extending portion **240** can extend upward from the longitudinally extending portion **238**. The vertically extending portion **240** can improve the line of sight for the user. The user's hand can engage the longitudinally extending portion **238**. The vertically extending portion **240** can raise the distal end **118** of the hand tool **100** away from the user's hand. The user's hand does not obstruct the line of sight to the distal end **118** of the hand tool **100**. In the illustrated embodiment, the vertically extending portion **240** forms an angle **242** with the longitudinally extending portion **238**. The angle **242** can be 90° or greater than 90° (e.g., 100°, 110°, 120°, 130°, 140°, 150°, 160°, 170°, etc.). The angle **242** can be obtuse. The angle **242** can be the same as angle **142**. In other embodiments, the angle **242** is different than angle **142** based on the manner in which the user is expected to hold the hand tool **100**. The angle **242** can be selected to better complement the grip of the user (e.g., based on the anatomy of the human hand). Other configurations are possible.

The right section **202** can include a right hub **244**. The right hub **244** can extend from the vertically extending portion **240**. In some embodiments, the right hub **244** can be a unitary structure with the vertically extending portion **240**

of the right handle **234**. The right hub **244** and the right handle **232** can be monolithically formed.

In other embodiments, the right hub **244** is a separate component from the right handle **232**. The vertically extending portion **240** can include a recess **246**. The right hub **244** can be coupled to the recess **246** by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. In some embodiments, the right hub **244** is removable from the vertically extending portion **240**. For instance, the right hub **244** can be removed to permit sterilization of the right tip **260**. The right hub **244** can be removed to replace the right tip **260**.

The right hub **244** can include a proximal portion **248**. The proximal portion **248** of the right hub **244** can be received within the recess **246** of the vertically extending portion **240**. The recess **246** can be shaped to complement the external surface of the right hub **244**. The proximal portion **248** of the right hub **244** can be any cross-sectional shape including semi-circular, triangular, rectangular, etc. In some embodiments, the proximal portion **248** can extend the entire length of the vertically extending portion **240**. The edge **250** of the proximal portion **248** can be angled to match the angle **242**.

The right hub **244** can include a distal portion **252**. The distal portion **252** can extend from the vertically extending portion **240**. The distal portion **252** can extend from the recess **262** when proximal portion **248** is received within the recess **262**. The edge **254** of the distal portion **252** can include a hub recess **256**. The distal portion **252** can be a portion of a cylinder. The distal portion **252** can be any cross-sectional shape including semi-circular. In some embodiments, the distal portion **248** and the distal portion **252** have the same cross-sectional shape. In other embodiments, the proximal portion **248** and the distal portion **252** have different cross-sectional shapes. In some embodiments, the proximal portion **248** and the distal portion **252** can have the same diameter. In other embodiments, the proximal portion **248** and the distal portion **252** have different diameters.

The right hub **244** can define a right tip axis **258**. The right tip axis **258** can be the axis upon which the right tip **260** rotates. The distal portion **252** of the right hub **244** can function to support the right tip **260** during rotation. The hub recess **256** can be aligned with the right tip axis **258**. The hub recess **256** can function to maintain alignment of the right tip **260** during rotation. In some methods of assembly, the right hub **244** is coupled to the vertically extending portion **240**. This can create a channel between the external surface of the right tip **260** and the internal surface of the recess **262**. A portion of the right tip **260** can rotate within this channel.

The right tip **260** can include a proximal portion **264**. The proximal portion **264** of the right tip **260** can be supported by the right hub **244**. The proximal portion **264** of the right tip **260** can rotate about the right hub **244**. At least a portion of the proximal portion **264** of the right tip **260** can be received within the recess **262** of the vertically extending portion **240**.

In the illustrated embodiment, the recess **262** of the vertically extending portion **240** can include a first portion **266** and a second portion **268** (not shown). The first portion **266** can be similar or a mirror image of first portion **166**. The second portion **268** can be similar or a mirror image of second portion **168**. The first portion **266** can have a circular cross-section and the second portion **268** can have a circular cross-section. The first portion **266** can have a semi-circular cross-section and the second portion **268** can have a semi-circular cross-section. The cross-sectional shapes of the first

13

portion 266 and the second portion 268 can permit free rotation of the right tip 260 within the recess 262.

The first portion 266 can have a first diameter and the second portion 268 can have a second diameter. The first diameter can be smaller than the second diameter. The first portion 266 can be located distal to the second portion 268. The first portion 266 of the recess 262 can be closer to the distal end 118. The second portion 268 can be located proximal to the first portion 266. The second portion 268 of the recess 262 can be closer to the proximal end 116. The difference in diameter between the first portion 266 and the second portion 268 of the recess 262 can create a lip.

The recess 262 can have any number of portions (e.g., two, three, four, five, six, etc.). Each portion can have a diameter that is either the same or different than one or more other portions. At least two of the portions have unequal diameters. Of the at least two portions, a portion near the distal end can have a smaller diameter than another portion near the proximal end. The difference in diameter between the portions of the recess 262 can create a lip.

In the illustrated embodiment, the right tip 260 can include a ridge 274 which can interact with the lip. The ridge 274 can extend from the external surface of the proximal portion 264 of the right tip 260. The ridge 274 can be sized to be received within the second portion 268 of the recess 262. For instance, the ridge 274 and the second portion 268 can have the same or similar diameter. The ridge 274 can have a larger diameter than the first portion 266. The ridge 274 can abut the lip created by the first portion 266 and the second portion 268. The ridge 274 can reduce axial translation of the right tip 260 when the right tip 260 is received within the recess 262. The ridge 274 can reduce the longitudinal movement of the right tip 260 when the ridge 274 is received within the recess 262. The ridge 274 can prevent disengagement between the vertically extending portion 240 and the right tip 260 by the application of axial force.

The proximal portion 164 of right tip 260 can include a right extension 278 which can interact with the hub 244. The right extension 278 can be a portion of a cylinder. In some embodiments, the right extension 278 can have a quarter-circular cross-section (e.g., encompasses 90 degrees). The right extension 278 can have a convex external surface. The convex external surface can be complementary to the second portion 268. The right extension 278 can have a concave internal surface 280. The concave internal surface 280 can be complementary to the external surface of the distal portion 252 of the right hub 244.

The proximal portion 264 of right tip 260 can include a protrusion 272 which can interact with the hub recess 256. The protrusion 272 is sized to be received within the hub recess 256. For instance, the protrusion 272 and the hub recess 256 can have the same or similar diameter. The protrusion 272 can extend along the right tip axis 258 when the ridge 274 is received within the recess 262. The protrusion 272 and the hub recess 256 can provide a pivot for the right tip 260 as the right tip 260 rotates.

The right tip 260 can include a distal portion 270. The distal portion 270 of the right tip 260 can include a longitudinally extending portion 282. The longitudinally extending portion 282 can be a portion of a cylinder. In some embodiments, the longitudinally extending portion 182 can have a semi-circular cross-section (e.g., encompasses 180 degrees). The longitudinally extending portion 282 can have a convex external surface. The distal 270 and longitudinally extending 282 portions can have other cross-sectional shapes (e.g., circular, elliptical, square, rectangular, triangular, polygonal, sigmoid, etc.).

14

The distal portion 270 of the right tip 260 can include a conical portion 286. The conical portion 286 can extend to a distal tip 288. The distal tip 288 can interact with the left section 102 to function as forceps. The conical portion 286 can include a cutting edge 290. The cutting edge 290 can interact with the left section 102 to function as scissors. The cutting edge 290 can be the same material as the distal portion 270 of the right tip 260. The cutting edge 290 can be the same material as the right tip 260. The cutting edge 290 can be a different material than the distal portion 270 of the right tip 260. The cutting edge 290 can be a different material than the right tip 260. The cutting edge 290 can be integrally or monolithically formed with the right tip 260. The cutting edge 290 can be a separate component and coupled to the right tip 260.

The distal portion 270 of the right tip 260 can have a flat internal surface 284. The flat internal surface 284 can be complementary to an internal surface of the left section 102. The flat internal surface 284 can extend the length of the longitudinally extending portion 282. The flat internal surface 284 can extend the length of the conical portion 286. The flat internal surface 284 can abut a flat internal surface of the left tip 160. Other cross-sectional shapes of the internal surface can be contemplated (e.g., circular, elliptical, square, rectangular, triangular, polygonal, sigmoid, etc.). These can be complimentary, mirror or rotationally similar to the right tip 160.

The distal portion 270 of the right tip 260 can include an electrode 292. In some embodiments, the longitudinally extending portion 282 can include the electrode 292. In some embodiments, the conical portion 286 can include the electrode 292. In some embodiments, the distal tip 288 can include the electrode 292. In some embodiments, the flat internal surface 284 can include the electrode 292. In some embodiments, the external surface of the right tip 260 can include the electrode 292. The electrode 292 can interact with the left section 102. The left section 102 can include a ground or another electrode. The right tip 260 can interact with the left section 102 function as an electrosurgical device. The electrode 292 can be activated by electrical energy supplied to the hand tool 100. The electrode 292 can be activated when the hand tool 100 is in the forceps configuration. In some embodiments, electrical energy is prevented from being supplied when the hand tool 100 is in the scissors configuration. The electrode 292 can be the same material as the distal portion 270 of the right tip 260. The electrode 292 can be the same material as the right tip 260. The electrode 292 can be a different material than the distal portion 270 of the right tip 260. The electrode 292 can be a different material than the right tip 260. The electrode 292 can be integrally or monolithically formed with the right tip 260. The electrode 292 can be a separate component and coupled to the right tip 260.

In some embodiments, the right lead 212 can pass through a channel in the right spring 224. The right lead 212 can pass through a channel in the right handle 232. The right lead 212 can pass through a channel in the right tip 260. The channels in any of the components in the right section 202 can be insulated.

In some methods of assembly, the right tip 260 is inserted within the recess 262. Then the right hub 244 is coupled to the vertically extending portion 240. The right tip 260 is placed in the recess 262 prior to coupling of the right hub 244. The right tip 260 can be retained within the recess 262 by a retention mechanism (not shown). In some embodiments, the right hub 244 is removable. The right hub 244 can be

15

removed to replace the right tip 260. The right hub 244 can be removed to sterilize the right tip 260.

In some methods of assembly, the right hub 244 is coupled to the vertically extending portion 240. This creates a channel between the external surface of the right hub 244 and the internal surface of the recess 262. In some embodiments, the right hub 244 is integrally formed with the vertically extending portion 240. Then the right tip 260 is inserted within the recess 262. The ridge 274 is aligned with the second portion 268 the recess 262 in the vertically extending portion 240. The internal surface 280 of the right extension 278 is aligned with the external surface of the right hub 244. The protrusion 272 of the right tip 260 is aligned with the hub recess 246.

From this position, the right tip 260 can be rotated about the right tip axis 258. The right tip 260 can be rotated until the ridge 274 is received within the second portion 268 of the recess 162. In this position, the internal surface 280 of the right extension 278 can be in contact with the external surface of the right hub 244. In this position, the protrusion 272 can be received within the hub recess 256.

As shown in FIG. 1, the hand tool 100 can include a pin 296 coupled to a portion of the right tip 260. The pin 296 can be positioned on the right extension 278. The pin 296 can extend from an external surface of the right extension 278. The pin 296 can extend radially outward from the outer surface of the right extension 278. In the illustrated embodiment, the pin 296 extends at an angle to the right tip axis 158. The angle may be substantially perpendicular or perpendicular. The pin 296 can extend transverse to the right tip axis 258.

The pin 296 can be a separate component coupled to the right tip 260. The pin 296 can be coupled by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. The pin 296 can be integrally or monolithically formed with the right tip 260. The pin 296 can interact with a mechanism 300, as discussed in greater detail below.

In an alternative embodiment, a pin can be coupled to a portion of the left tip 160 rather than the right tip 260. The pin can be a mirror image of the pin 296. The pin can be positioned on the left extension 178. The pin can extend from an external surface of the left extension 178. The pin can extend radially outward from the outer surface of the left extension 178. The pin 296 can be positioned on either extension 178, 278. The pin 296 can be positioned on either tip 160, 260.

In some embodiments, one of the tips 160, 260 can have a protrusion 294 and the other tip can have a recess 194. Referring to FIGS. 2B, 7C, and 8C, the left tip 160 can have the recess 194 and the right tip 260 can have the protrusion 294. In other embodiments, the left tip 160 can have the protrusion 294 and the right tip 260 can have the recess 194. The protrusion 294 can extend perpendicularly from the flat internal surface 284 of the right tip 260. The protrusion 294 can be located near the longitudinally extending portion 282 or the conical portion 286 of the right tip 260. The recess 194 can extend perpendicularly from the flat internal surface 184 of the left tip 160. The recess 194 can be located near the longitudinally extending portion 182 or the conical portion 186 of the left tip 160. The protrusion 294 and the recess 194 can be located near the distal end 118 of the hand tool 100.

The protrusion 294 can be sized to fit within the recess 194. The protrusion 294 or the recess 194 can include features to facilitate insertion of the protrusion 294 within the recess 194. In some embodiments, the edges of the protrusion 294 are rounded to facilitate insertion. The pro-

16

trusion 294 can provide a pivot for the tips 160, 260 to rotate relative to each other. The protrusion 294 and the recess 194 can provide an axis 198 upon which the tips 160, 260 can pivot relative to each other. The protrusion 294 can engage the recess 194 when the hand tool 100 is in the scissor configuration. The protrusion 294 can engage the recess 194 when the hand tool 100 is in the intermediate configuration.

Each tip 160, 260 can include a cutting edge 190, 290. The cutting edges 190, 290 can be located on the conical portions 186, 286. The cutting edges 190, 290 can be located on the longitudinally extending portions 182, 282. Each tip 160, 260 can include one cutting edge, similar to a pair of scissors. The cutting edges 190, 290 can have a range of motion from a closed position to an open position. In some embodiments, the angle formed between the cutting edges 190, 290 is ninety degrees in the open position. When the cutting edges 190, 290 are being closed, the cutting edges 190, 290 can shear relative to each other. This action can cut tissue. In some embodiments, each tip 160, 260 can include two or more cutting edges.

The springs 124, 224 can be designed to return each handle 132, 232 to a neutral position. In some embodiments, the neutral position can include a separation between the conical portions 186, 286. In some embodiments, the neutral position can include a separation between the longitudinally extending portions 182, 282. In some embodiments, the neutral position can include a separation between the handles 132, 232. In other configurations, the hand tool 100 can include one spring (e.g., either the left spring 124 or the right spring 224). For instance, the hand tool 100 can include the right spring 224. The longitudinally extending portion 128 of the left handle 132 can extend to the mechanical connector 122. The right handle 232 can be manipulated to move the right tip 260 relative to the left tip 160.

In some embodiments, the longitudinally extending portions 128, 228 are curved or substantially curved (e.g., concave, convex, bent, etc.). In other configurations, the longitudinally extending portions 128, 228 are straight or substantially straight. In some embodiments, the conical portions 186, 286 are curved or substantially curved (e.g., concave, convex, bent, etc.). In other configurations, the conical portions 186, 286 are straight or substantially straight.

In some embodiments, the handles 132, 232 of the hand tool 100 can extend substantially along the longitudinal axis 106. The recesses 162, 262 can extend along the longitudinal axis 106. The handles 132, 232 can have any cross-sectional shape including rectangular, square, polygonal, etc. In some embodiments, the handles 132, 232 are straight or substantially straight. In some embodiments, the handles 132, 232 are curved or substantially curved (e.g., concave, convex, bent, etc.).

In some embodiments, electrical energy is supplied at a location along the length of the hand tool 100. For instance, electrical energy can be supplied to each handle 132, 232 of hand tool 100. The lead 112 can be coupled to the left handle 132 and the lead 212 can be coupled to the right handle 232. The distance between the handles 132, 232 can function as an electrical isolator. For instance, electrical energy can be supplied to each hub 144, 244 of hand tool 100. The lead 112 can be coupled to the left hub 144 and the lead 212 can be coupled to the right hub 244. The distance between the hubs 144, 244 can function as an electrical isolator. For instance, electrical energy can be supplied to each tip 160, 260 of hand tool 100. The lead 112 can be coupled to the left tip 160 and

17

the lead 212 can be coupled to the right tip 260. The distance between the tips 160, 260 can function as an electrical isolator.

Each tip 160, 260 can include electrode 192, 292 for bipolar electrocautery. The electrodes 192, 292 can be located on the longitudinally extending portion 182, 282. The electrodes 192, 292 can be located on the conical portion 186, 286. The electrodes 192, 292 can be located on an external surface of the tips 160, 260. The electrodes 192, 292 can be located on an internal surface of the tips 160, 260 for instance the flat surfaces 184, 284. The electrodes 192, 292 can be configured for cauterization, hemostasis, and tissue dissection.

The hand tool 100 can allow current to flow from the location where electrical energy is supplied to the electrodes 192, 292. The hand tool 100 can have a current passage that allows current to flow through the hand tool 100 and to the electrodes 192, 292. The hand tool 100 can be sufficiently insulated to prevent the dissipation of electrical energy. The hand tool 100 can be grounded. The hand tool 100 can be designed to operate in conjunction with currently available current generators.

The hand tool 100 can have a fluid passage having a fluid inlet and a fluid outlet. The fluid inlet can be located near a proximal end 116 of the hand tool 100. The fluid inlet can be connectable to a fluid source. The fluid outlet can be located near the distal end 118 of the hand tool 100. In some embodiments, the hand tool 100 can have more than one fluid outlet. The fluid outlet can be in fluid communication with the fluid inlet, such that fluid can travel through the fluid passage of the hand tool 100. The fluid outlet can be located on the longitudinally extending portion 182, 282. The fluid outlet can be located on the conical portion 186, 286. The fluid outlet can be located on an external surface of the tips 160, 260. The fluid outlet can be located on an internal surface of the tips 160, 260, for instance the flat surfaces 184, 284. The fluid outlet can be located near the electrodes 192, 292. The fluid can be a coolant, a medication, or any substance selected to be delivered to the surgical site. The hand tool 100 can be designed to operate in conjunction with currently available fluid systems.

Operation of the Hand Tool

The hand tool 100 can transition between at least two functional configurations, as shown generally in FIGS. 2A and 4. These configurations are referred to as the forceps configuration and the scissors configuration. In some embodiments, the forceps configuration includes a bipolar electrocautery forceps configuration. In some embodiments, the scissors configuration includes a microscissors configuration. In some embodiments, the scissors configuration and the forceps configuration are mutually exclusive functional configurations.

FIG. 2A shows the hand tool 100 in the forceps configuration. The springs 124, 224 bias the handles 132, 232 away from each other. The distal tips 188, 288 can be separated in the neutral position. The user can apply a force to the handles 132, 232 to move the distal tips 188, 288 toward each other. The user can release the force to the handles 132, 232 and the distal tips 188, 288 can return to the neutral position.

FIG. 3 shows the hand tool 100 in the intermediate configuration. In order to change configurations, the handles 132, 232 are moved toward each other. The user applies a force to overcome the biasing force of the springs 124, 224. The internal surface of the handles 132, 232 can abut. The

18

left tip 160 and the right tip 260 can be brought together. The tips 160, 260 can abut. The internal flat surfaces 184, 284 can abut. The left tip axis 158 and the right tip axis 258 can align along the longitudinal axis 106. The protrusion 294 can engage the recess 194. The intermediate configuration permits the transition from the forceps configuration to the scissors configuration. The intermediate configuration permits the transition from the scissors configuration to the forceps configuration.

FIG. 4 shows the hand tool 100 in the scissors configuration. The springs 124, 224 bias the handles 132, 232 away from each other. The distal tips 188, 288 can be separated in the neutral position. The user can apply a force to the handles 132, 232 to move the distal tips 188, 288 toward each other. The user can apply a force to the handles 132, 232 to pivot the distal tips 188, 288 about the axis 198. The user can apply a force to the handles 132, 232 to shear the cutting edges 190, 290 past each other. The user can release the force to the handles 132, 232 and the distal tips 188, 288 can return to the neutral position.

In both the forceps and the scissors configuration, the proximal portion 164 of the left tip 160 is retained within the recess 162. In both the forceps and the scissors configuration, the proximal portion 264 of the right tip 260 is retained within the recess 262. In both the forceps and the scissors configuration, the ridge 174 is retained within the recess 162. In both the forceps and the scissors configuration, the ridge 274 is retained within the recess 262.

In the forceps configuration, the internal flat surfaces 184, 284 are vertical or substantially vertical. In the scissors configuration, the internal flat surfaces 184, 284 are horizontal or substantially horizontal. In the forceps configuration, the right tip 260 can be horizontally offset from the left tip 160. The right tip 260 can be toward the right and the left tip 160 can be toward the left. In the scissors configuration, the right tip 260 can be generally over top the left tip 160. In the scissors configuration, the left tip 160 can be generally underneath the right tip 260.

As shown in FIGS. 1-4, the hand tool 100 can include a mechanism 300 that enables the user to transition between the forceps configuration and the scissors configuration. In the illustrated embodiment, the mechanism 300 is located on the right handle 232. The mechanism 300 can interact with the pin 296. The mechanism 300 can be located as part of the same section as the pin 296. In the illustrated embodiment, the pin 296 is located on the right section 202. In the illustrated embodiment, the mechanism 300 is located on the right section 202.

The mechanism 300 can include a slide 302. The slide 302 can be coupled to the vertically extending portion 240. In the illustrated embodiment, the vertically extending portion 140 can include a retaining hole 298. The slide 302 can include a guide slot 310. The guide slot 310 can engage the retaining hole 298. For instance, the retaining hole 270 can engage a screw (not shown). The screw can translate within the guide slot 310 when the slide 302 translates. In some embodiments, the slide 302 can be coupled via a rail, protrusion, detent, ratchet, etc. The slide 302 is designed to translate along a portion of the vertically extending portion 240. The slide 302 is capable of sliding upward and downward relative to the right handle 232. The slide 302 can be less than the total height of the vertically extending portion 240 or a percentage of the total height (e.g., 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, etc.). The slide 302 can be less than the total width of the vertically extending portion 240 or a percentage of the total width (e.g., 20%, 30%, 40%, 50%, 60%, 70%, 80%, 90%, etc.). The slide 302 can be

19

greater than the total width of the vertically extending portion 240 (e.g., 110%, 120%, 130%, 140%, 150%, 160%, 170%, 180%, 190%, 200%, 300% etc.).

The slide 302 can include a lower portion 304 and an upper portion 306. The lower portion 304 can be approximately the same length as the vertically extending portion 240. The upper portion 306 can be a greater length than the vertically extending portion 240. The upper portion 306 can extend distally from the vertically extending portion 240 near the upper edge of the slide 302. In some embodiments, the upper portion 306 can include a housing 308. The housing 308 can extend distally from the vertically extending portion 240 near the upper edge of the slide 302. The housing 308 can have a greater width than the width of the lower portion 304. The housing 308 can be convex. The housing 308 can have a non-symmetrical shape. In the illustrated embodiment, the slide 302 can include at least a portion that extends distally from the vertically extending portion 240. The housing 308 can include any shape (e.g., circular, elliptical, square, rectangular, triangular, polygonal, sigmoid, etc.).

The mechanism 300 can include a grip 312. The grip 312 can be located near an edge of the slide 302. The grip 312 can be located proximally from the vertically extending portion 240. In the illustrated embodiment, the grip 312 is located near the proximal end of the slide 302. Other configurations are contemplated (e.g., near the top of the slide 302, near the bottom of the slide 302, on an external surface of the slide 302, etc.). The grip 312 can include one or more ridges to facilitate the movement of the slide 302. Other configurations are contemplated (e.g., roughened surfaces, protrusions, etc.).

The mechanism 300 can include a slot 314. The slot 314 provides a path for the pin 296 as the slide 302 is translated. The slot 314 can be within the housing 308. The outer perimeter of the slot 314 can be within or smaller than the outer perimeter of the housing 308. The housing 308 can have a width sufficient to enclose the pin 296. The housing 308 can have an area of increased thickness near the slot 314. The increased thickness can facilitate repeated movements against the pin 296 without deformation of the housing 308. In some embodiments, the slot 314 is covered. The slot 314 can be covered by an external surface of the housing 308. In other embodiments, the slot 314 is exposed to the user.

In some embodiments, the slot 314 is linear. In other embodiments, the slot 314 is non-linear. The slot 314 can have a variety of shapes including curved, s-shaped, bow-tie shaped, sloped, stepped, etc. The slot 314 can have any shape that allows the slot 314 to function as a guide for the pin 296. The slot 314 can be integrally formed with the slide 302. The slot 314 can be formed by any machining, casting or forming processes.

The slot 314 can function to guide the pin 296. The pin 296, as discussed above, is coupled to the right tip 260. In the illustrated embodiment, the pin 296 extends from an external surface of the right extension 278. An edge of the slot 314 pushes the pin 296 as the slide 302 is moved. The shape of the slot 314 permits the pin to rotate about the right tip axis 258 as the slide 302 is moved. In some embodiments, the pin 296 can be adjusted to a number of discrete positions within the slot 314 (e.g., two, three, four, five, etc.). In some embodiments, the pin 296 can be adjusted to an infinite number of positions within the slot 314.

The slide 302 can be coupled to the hand tool 100 at two points of contact. The slide 302 can be coupled to the vertically extending portion 140 with the retaining hole 298

20

and the guide 310. The slide 302 can be coupled to the tip 260 with the pin 296 and the slot 314. As the slide 302 translates, the screw (not shown) in the retaining hole 298 translates within the guide 310. As the slide 302 translates, the pin 296 translates within the slot 314.

The mechanism 300 can have a first position and a second position. The first position can correspond to forceps configuration. The second position can correspond to the scissor configuration. In the illustrated embodiments, the mechanism 300 can be in the first position when the slide 302 is lower on the vertically extending portion 240. There can be a larger separation between the top surface of the slide 302 and the top surface of the vertically extending portion 240. There can be a smaller separation between the bottom surface of the slide 302 and the bottom surface of the vertically extending portion 240. The bottom surface of the slide 302 and the bottom surface of the vertically extending portion 240 can be aligned. FIG. 2A shows the mechanism 300 in the first position. When the mechanism 300 is in the first position, the left tip 160 and the right tip 260 can be used as forceps.

In the illustrated embodiments, the mechanism 300 can be in the second position when the slide 302 is higher on the vertically extending portion 240. There can be a smaller separation between the top surface of the slide 302 and the top surface of the vertically extending portion 240. The top surface of the slide 302 and the top surface of the vertically extending portion 240 can be aligned. There can be a larger separation between the bottom surface of the slide 302 and the bottom surface of the vertically extending portion 240. FIG. 4 shows the mechanism 300 in the second position. When the mechanism 300 is in the second position, the left tip 160 and the right tip 260 can be used as scissors.

FIGS. 5A and 5B show the mechanism 300 in the first position. FIG. 5A shows the front view of the hand tool 100 and FIG. 5B shows a cross-section view along line B-B. In the first position, the pin 296 is near the lower end of the slot 314. The pin 296 is retained within the slot 314. In the illustrated embodiment, the pin 296 is not being acted on by any edge of the slot 314.

FIGS. 6A and 6B show the mechanism 300 in the second position. FIG. 6A shows the front view of the hand tool 100 and FIG. 6B shows a cross-section view along line M-M. In the second position, the pin 296 is near the upper end of the slot 314. As the slide 302 is moved upward along the vertically extending portion 240, an edge of the slot 314 can come into contact with the pin 296. Further upward movement of the slide 302 can cause the edge of the slot 314 to exert a force on the pin 296. This force can cause the pin 296 to rotate about the right tip axis 258. Further upward movement of the slide 302 can cause the pin to rotate a quarter turn (e.g., 90°) or approximately a quarter turn (e.g., 80°, 85°, 90°, 95°, 100°, etc.). Rotation of the pin 296 can cause the right tip 260 to rotate within the recess 262 of the vertically extending portion 240. Rotation of the right tip 260 can exert a force on the left tip 160. The force exerted by the right tip 260 can be directly exerted on the left tip 160. As the right tip 260 is rotated within the recess 262, the left tip 160 can rotate within the recess 162.

FIGS. 7A-7C show the mechanism 300 in the first position. FIG. 7A shows the side view of the hand tool 100. FIG. 7B shows a cross-section view along line D-D. FIG. 7C shows a cross-section view along line G-G. In the illustrated embodiment, the first position corresponds to the slide 302 being in a lower position as shown in FIG. 7A.

The pin 296 can extend from the right extension 278 as shown in FIG. 7B. The pin 296 can be retained within the

slot 314. In the illustrated embodiment, the slot 314 is formed in a portion of the housing 308. The pin 296 can have a sufficient size to extend past the vertically extending portion 240 and into the housing 308. The pin 296 can have a greater dimension than the width of the vertically extending portion 240. The pin 296 can be positioned at an angle 202. The angle 202 can be approximately 45° from the vertical plane of the hand tool 100. Other angles are possible (e.g., 0°, 5°, 10°, 15°, 20°, 25°, 30°, 35°, 40°, 45°, 50°, 55°, 60°, 65°, 70°, 75°, 80°, 85°, 90°, etc.). The protrusion 294 can be received in the recess 194 as shown in FIG. 7C.

FIGS. 8A-8C show the mechanism 300 in the second position. FIG. 8A shows the side view of the hand tool 100. FIG. 8B shows a cross-section view along line P-P. FIG. 8C shows a cross-section view along line T-T. In the illustrated embodiment, the second position corresponds to the slide 302 being in a higher position as shown in FIG. 8A.

The pin 296 can be rotated as shown in FIG. 8B. The pin 296 can be positioned at an angle 204. The angle 204 can be approximately 45° from the vertical plane of the hand tool 100. Other angles are possible (e.g., 0°, 5°, 10°, 15°, 20°, 25°, 30°, 35°, 40°, 45°, 50°, 55°, 60°, 65°, 70°, 75°, 80°, 85°, 90°, etc.) The pin 296 can rotate approximately 90° as the mechanism 300 is moved from the first position to the second position. The pin 296 can rotate approximately 90° as the hand tool 100 is transitioned between the forceps configuration and the scissors configuration. Other ranges of motion of the pin 296 are possible (e.g., 80°, 85°, 90°, 95°, 100°).

The protrusion 294 can be received in the recess 194 as shown in FIG. 8C. The protrusion 294 can extend from the internal flat surface 284 of the right tip 260. The recess 194 can extend into the internal flat surface 184 of the left tip 160. The tips 160, 260 can rotate or pivot about the protrusion 294. The tips 160, 260 can rotate or pivot about the axis 198. The protrusion 294 can extend downward such that gravity aids in the retention of the protrusion 294 within the recess 194.

The functional configuration of the hand tool 100 is selected by the user by manipulating the mechanism 300. The user can slide a finger to move the slide 312. The user can manipulate the mechanism 300 while holding the hand tool 100. The slide 312 can change the position of the slot 314 relative to the pin 296. The mechanism 300 can exert a force on the pin 296 to rotate the pin 296. In the illustrated embodiment, an edge of the slot 314 of the mechanism 300 can act on the pin 296. The rotation of the pin 296 can rotate both tips 160, 260. The tips 160, 260 can rotate approximately 90° as the hand tool 100 is transitioned between the forceps configuration and the scissors configuration. Other ranges of motion of the tips 160, 260 are possible (e.g., 80°, 85°, 90°, 95°, 100°).

The mechanism 300 can convert translational motion of the slide 312 into rotational motion of pin 296. When the slide 312 is moved upward, the mechanism 300 can apply a rotational force to the pin 296. The pin 296 can be coupled to the right extension 278. The right extension 278 can have a cross-sectional shape of roughly a quarter-circle. The right extension 278 can rotate within the recess 262 of the vertically extending portion 240 as the pin 296 is rotated. The right extension 278 can rotate about the right hub 244 as the pin 296 is rotated. The right hub 244 can provide support to the right tip 260 as the pin 296 is rotated. The protrusion 272 and the hub recess 256 can maintain alignment of the right tip 260 as the right tip 260 is rotated. The right tip 260 can rotate about the right tip axis 258. The right tip 260 can rotate about the longitudinal axis 106.

The left extension 178 can have a cross-sectional shape of roughly a quarter-circle. The left extension 178 can rotate within the recess 162 of the vertically extending portion 140 as the pin 296 is rotated. The left extension 178 can rotate about the left hub 144 as the pin 296 is rotated. The left hub 144 can provide support to the left tip 260 as the pin 296 is rotated. The protrusion 172 and the hub recess 156 can maintain alignment of the left tip 160 as the left tip 160 is rotated. The left tip 160 can rotate about the left tip axis 158. The left tip 160 can rotate about the longitudinal axis 106.

Both tips 160, 260 can rotate the same direction. In the illustrated embodiment, the right tip 260 rotates clockwise along the right hub 244 when the hand tool 100 transitions from the forceps configuration to the scissors configuration. The right tip 260 rotates counter-clockwise along the right hub 244 when the hand tool 100 transitions from the scissors configuration to the forceps configuration. In the illustrated embodiment, the left tip 160 rotates clockwise along the left hub 144 when the hand tool 100 transitions from the forceps configuration to the scissors configuration. The left tip 160 rotates counter-clockwise along the left hub 144 when the hand tool 100 transitions from the scissors configuration to the forceps configuration. The rotation in the clockwise direction is shown in FIGS. 7B and 8B. Other configurations are possible, where the mechanism rotates the tips clockwise to embody the transitions from the scissors configuration to the forceps configuration and counterclockwise to transitions from the forceps configuration to the scissors configuration.

In some embodiments, one mechanism 300 is provided. In the illustrated embodiment, the mechanism 300 is coupled to the right handle 232 and the pin 296 is provided on the right tip 260. The right tip 260 is the leader and the left tip 160 is the follower. The tips 160, 260 can be brought together and into contact in the intermediate configuration. In the intermediate configuration, movement of the right tip 260 can impart a force on the left tip 160 to cause rotation. In some embodiments, the mechanism 300 is coupled to the left handle 132 and the pin 296 is provided on the left tip 160. The left tip 160 can be the leader and the right tip 260 can be the follower. In some embodiments, more than one mechanism 300 is provided. One mechanism 300 is coupled to the right handle 232 and the pin 296 is provided on the right tip 260. Another mechanism is coupled to the left handle 132 and another pin is provided on the left tip 160. The user can move one or both mechanisms 300 to rotate the tips 160, 260.

The user selects the configuration of the hand tool 100 by movement of the mechanism 300. In some embodiments, the mechanism 300 is moved by a finger of the hand in which the hand tool 100 is held. In some embodiments, the mechanism 300 is moved by the thumb of the hand in which the hand tool 100 is held. In some embodiments, the mechanism 300 is moved by a finger or thumb of the hand not holding the hand tool 100. The mechanism 300 allows the user to select between functional configurations with relative ease. The movement of the mechanism 300 can be intuitive to the user.

The hand tool 100 does not need to be removed from the surgical site to switch configurations. The mechanism 300 can be manipulated while the tips 160, 260 remain within the surgical site. The hand tool 100 requires the user to collapse the hand tool 100 in the intermediate configuration. This requires less space than either the forceps configuration or the scissors configuration. Once in the intermediate configuration, the user can transition between the forceps configura-

ration and the scissors configuration. The hand tool **100** does not require any large movements to switch configurations.

Once the hand tool **100** is in the desired configuration, the scissors or forceps are operated conventionally. In the forceps configuration, movement of the handles **132**, **232** causes the forceps to come together. The springs **124**, **224** can return the handles **132**, **232** to a neutral position. In the scissors configuration, movement of the handles **132**, **232** causes the cutting edges of the tips **160**, **260** to shear with respect to each other. The springs **124**, **224** return the handles **132**, **232** to a neutral position.

Component to Facilitate Scissor Function

The hand tool **100** can include a component to maintain alignment of the tips **160**, **260** in the scissors configuration. This component can ensure engagement between the cutting edges **190**, **290** to allow the tips **160**, **260** to cut tissue. In the illustrated embodiment, the component is a sleeve **400**. The sleeve **400** can extend along the length of one of the tips **160**, **260** in the forceps configuration. The sleeve **400** can extend along the length of both tips **160**, **260** in the scissors configuration. Other mechanisms are contemplated which function to hold the tips **160**, **260** together in the scissors configuration.

FIGS. 9A-9D show an embodiment of the sleeve **400**. FIG. 9A shows the perspective view of the hand tool **100** with the sleeve **400**. FIG. 9B shows a top view and FIG. 9C shows a side view. FIG. 9D shows a cross-section view along line K-K. In FIG. 9A, the right handle **232** is removed. The sleeve **400** is coupled to the left handle **132**. The sleeve **400** can be coupled to the left handle **132** by welding, fasteners, glue, friction fit, pawl and ratchet, detent and protrusion, or other fixation method. In the illustrated embodiment, the sleeve **400** is coupled to the vertically extending portion **140**. The sleeve **400** extends from the vertically extending portion **140**. The sleeve **400** extends along the left tip axis **158**.

The sleeve **400** can include a proximal portion **402** near the vertically extending portion **140**. The proximal portion **402** can be flat or substantially flat. The proximal portion **402** can be offset from the left tip **160**. In some embodiments, the proximal portion **402** is not in contact with the left tip **160**.

The sleeve **400** can include a distal portion **404**. The distal portion **404** can have an internal surface **406** and an external surface **408**. The internal surface **406** can be concave. The internal surface **406** can be sized to complement the external shape of the left tip **160**. The diameter of the internal surface **406** can be equal or approximately equal to the diameter of the left tip **160**. The diameter of the internal surface **406** can be slightly larger than the diameter of the external surface of the left tip **160** or a percentage thereof (e.g., 105%, 110%, 115%, 120%, 125%, 130%, 140%, 145%, 150%, etc.). The internal surface **406** can complement the external shape of the left tip **160** in the forceps configuration. The internal surface **406** can also complement the external shape of a portion of the left tip **160** and a portion of the right tip **260** in the scissors configuration. The external surface **408** of the distal portion **404** can be convex. The external surface **408** can have any shape (e.g., elliptical, oval, rectangular, square, etc.).

The sleeve **400** can include a middle portion **410** that transitions between the proximal portion **402** and the distal portion **404**. The sleeve **400** can be tapered as shown in FIG. 9B. The proximal portion **402** can surround a smaller portion

of the left tip **160**. The distal portion **404** can surround a larger portion of the left tip **160**.

The sleeve **400** can extend along a portion of the tip **160**. In the illustrated embodiment, the conical portion **186** extends distally from the sleeve **400** as shown in FIG. 9C. The sleeve **400** is sized to permit movement of the tips **160**, **260** in the forceps configuration and the scissors configuration.

In the forceps configuration (not shown), the distal portion **404** surrounds the left tip **160**. The internal surface **406** can be adjacent to the left tip **106**. The internal surface **406** can be in contact with or abut the left tip **106**. The distal portion **404** can surround the entire left tip **160** or a portion thereof. The distal portion **404** can extend beyond the left tip **160**. In the illustrated embodiment, the distal portion **404** can be semi-circular. The left tip **160** can be semi-circular.

In the scissors configuration shown in FIG. 9D, the distal portion **404** surrounds a portion of the left tip **160** and a portion of the right tip **260**. The internal surface **406** can be adjacent to a portion of the left tip **160** and a portion of the right tip **260**. The internal surface **406** can be in contact with or abut a portion of the left tip **160** and a portion of the right tip **260**. The distal portion **404** can surround a percentage of the left tip **160** (e.g., 30%, 40%, 50%, 60%, 70%, etc.). The distal portion **404** can surround a percentage of the right tip **260** (e.g., 30%, 40%, 50%, 60%, 70%, etc.). The distal portion **404** can surround half of the left tip **160** and half of the right tip **260**. In the illustrated embodiment, the internal surface **406** can be semi-circular. The external surface of the left tip **160** and the right tip **260** can be semi-circular. The internal surface **406** allow the free rotation of the left tip **160** and the right tip **260** there within. The internal surface **406** can take other shapes or combination of shapes (e.g., semi-circular and flat, rectangular, circular, elliptical, square, rectangular, triangular, polygonal, sigmoid, etc.).

FIG. 9D shows the sleeve **400** contacting both tips **160**, **260** in the scissors configuration. The sleeve **400** can function to hold the tips **160**, **260** together in the scissors configuration. The sleeve **400** can function to prevent separation of the tips **160**, **260** in the scissors configuration. The sleeve **400** can function to prevent separation of the protrusion **294** and the recess **194** in the scissors configuration. The movement of the right tip **260** upward is reduced or prevented by the sleeve **400**. The movement of the left tip **160** downward is reduced or prevented by the sleeve **400**. Other mechanisms are contemplated which function to hold the tips **160**, **260** together in the scissors configuration.

Locking Component to Maintain Functional Configuration

The hand tool **100** can include a locking mechanism **500**. The locking mechanism **500** can function to reduce or prevent rotational movement of one or more of the extensions **178**, **278**. The locking mechanism **500** can function to reduce or prevent rotational movement of one or more of the tips **160**, **260**. The locking mechanism **500** can be locked when the hand tool **100** is in the forceps configuration, as shown in FIG. 2A. The locking mechanism **500** can be locked when the hand tool **100** is in the scissors configuration, as shown in FIG. 4. The locking mechanism **500** can be unlocked when the hand tool **100** is in the intermediate configuration, as shown in FIG. 3.

FIGS. 10A-10C show an embodiment of the locking mechanism **500**. The locking mechanism **500** can include a bar **502**. The bar **502** can be any shape (e.g., straight, curved, bent, s-shape etc.). In the illustrated embodiment, the bar

25

502 has a bend. The bar 502 can be retained within a slot. The bar 502 can move within the slot in a direction perpendicular or substantially perpendicular to the right tip axis 258. In the illustrated embodiment, the slot can be located in the right hub 244. The slot can be located in the proximal portion 248 or the distal portion 252 of the right hub 244. In the illustrated embodiment, the slot can be located in the proximal portion 248. In some embodiments, the slot is within the right handle 232.

The bar 502 can be coupled to a pin 504. The pin 504 can be any shape (e.g., curved, straight, u-shaped, slanted, etc.). In the illustrated embodiment, the pin 504 is u-shaped. The pin 504 can include a proximal end which engages the bar 502. The pin 504 can include a distal end which engages the extension 278. In the illustrated embodiment, the pin 504 can engage a recess in the extension 278. In the illustrated embodiment, the pin 504 has two prongs. The upper prong of the pin 504 can engage the recess when the hand tool 100 is in the scissors configuration, as shown in FIGS. 10A-10C. The lower prong of the pin 504 can engage the recess when the hand tool 100 is in the forceps configuration. The pin 504 can prevent rotation of the extension 278 when a prong of the pin 504 engages the recess of the extension 278.

The bar 502 can extend from an internal surface of the handle 232. The action of abutting the handles 132, 232 can cause the bar 502 to move within the slot. This action can unlock the locking mechanism 500. The locking mechanism 500 can be unlocked when the handles 132, 232 are brought toward each other. In some embodiments, the left handle 132 will exert a force on the bar 502. In some embodiments, the hub 144 will exert a force on the bar 502. The bar 502 can move outward from the longitudinal axis 106. The bar 502 can move toward the handle 232. The shape of the bar 502 can cause the pin 504 to be moved along the right tip axis 258. The pin 504 can translate toward the proximal end 116 as the bar 502 is moved toward the handle 232. The pin 504 can disengage the recess of the extension 278 when the pin 504 translates proximally. The upper prong of the pin 504 can disengage the recess when the pin 504 translates proximally. The lower prong of the pin 504 can disengage the recess when the pin 504 translates proximally. The tips 160, 260 can be rotated when the pin 504 disengages the recess in the right extension 278.

The locking mechanism 500 can have a neutral position. The neutral position can be the locked position. In the neutral position, a prong of the pin 504 can engage the recess in the extension 278. The locking mechanism 500 can return to the neutral position via a spring. In other embodiments, the locking mechanism 500 can be returned to the neutral position by other means (e.g., magnets, gravity, manually force, etc.). The locking mechanism 500 can be manually moved by the user. The locking mechanism 500 can be returned to the neutral position by the action of separating the handles 132, 232.

In some embodiments, the locking mechanism 500 is placed within the recess 262 in the vertically extending portion 240. The locking mechanism 500 would block the rotational movement of the right extension 278 in the recess 262. In some embodiments, the locking mechanism 500 is placed within the recess 162 in the vertically extending portion 140. The locking mechanism 500 would block the rotational movement of the left extension 178 in the recess 162. In some embodiments, the locking mechanism 500 can remain in one recess 162, 262. In some embodiments, a locking mechanism 500 can be provided for each recess 162, 262. In some embodiments, the locking mechanism 500 can move between the recesses 162, 262. For instance, the

26

locking mechanism 500 can be located in the recess 262 when the hand tool 100 is in the forceps configuration. The locking mechanism 500 can rotate into the recess 162 when the hand tool 100 is in the scissors configuration.

In the illustrated embodiment, the locking mechanism 500 can be included in the right section 202. In some embodiments, the locking mechanism 500 can be included in the left section 102. In some embodiments, the locking mechanism 500 can be included in both the left section 102 and the right section 202. Other embodiments are contemplated to prevent the extensions 178, 278 from rotating (e.g., spring, detent, magnet, etc.).

In other embodiments, the user can manipulate an interface (not shown) to unlock the locking mechanism 500. The neutral position can be that the locking mechanism 500 is locked. For instance, the interface (not shown) can be a button that when depressed would unlock the locking mechanism 500. The interface (not shown) can be a slide that can have a position when the locking mechanism 500 is locked and a position when the locking mechanism 500 is unlocked. Other configurations of interfaces (not shown) are contemplated.

The hand tool 100 can be generally composed of metal alloys, plastic, or other suitable biocompatible material. The hand tool 100 can be made by conventional machining and metal fabrication techniques, plastic fabrication techniques, and finishing processes including but not limited to milling, lathing, electrodischarge and welding, injection molding, powder coating and painting. The hand tool 100 can be optionally coated with one or more coatings, including but not limited to plastic, rubber, powder coat and paint or any combination thereof. The hand tool 100 can comprise multiple parts assembled and delivered to its intended user. The hand tool 100 can be sterilized before it is provided to the intended user.

Different methods of switching configurations, different mechanism for rotating the tips, different configurations of the pin are contemplated. Further, the hand tool 100 may be configured to provide different tool functions than forceps and scissors described herein. Further, the hand tool 100 may have additional functional configurations corresponding to different tools. The hand tool 100 may be used in conjunction with other tools, for instance an operating microscope.

Other embodiments of the hand tool are shown in U.S. Provisional Patent Application No. 61/906,337 filed Nov. 19, 2013, the disclosures of which is incorporated by reference herein in its entirety. The hand tool 100 described herein can have any of the features, components, or sub-components described in the provisional application. In the illustrated embodiment of FIGS. 1-9 in the provisional application, the handle 132 can include an additional longitudinally extending portion located distal of the vertically extending portions 140, 240. This additional longitudinally extending portion is shown in FIGS. 1-3 of U.S. Provisional Patent Application No. 61/906,337. The additional longitudinally extending portion of the left handle 132 can include the recess 162. The recess 162 can be enclosed or partially enclosed by the additional longitudinally extending portion. The recess 162 can be semi-circular as described herein. The recess 162 can be sized to receive the left extension 178.

In some embodiments, the right handle 232 can be a mirror image of the left handle 132. The right handle 232 can include an additional longitudinally extending portion. The additional longitudinally extending portion can include the recess 262. The recess 262 can be enclosed or partially enclosed by the additional longitudinally extending portion.

The recess **262** can be semi-circular as describe herein. The recess **262** can be sized to receive the right extension **278**.

The tips **160**, **260** can include a respective longitudinally extending portion **182**, **282**, as shown in FIG. 5 of U.S. Provisional Patent Application No. 61/906,337. The longitudinally extending portion **182**, **282** can be semi-circular. The tips **160**, **260** can include a respective conical portion **186**, **286**. The tips **160**, **260** can include a respective extension **178**, **278**. The extensions **178**, **278** can be quarter-circular. At least one of the extensions **178**, **278** can include an engaging surface. The engaging surface can be a pin. The pin can extend parallel or substantially parallel to the tip axis **158**, **258**. The engaging surface can be rotated to the extensions **178**, **278** within the recesses **162**, **262**. The engaging surface can be rotated to transition the hand tool between a forceps configuration and a scissors configuration.

The mechanism **300** can include a slide **302** as shown in FIG. 6 of U.S. Provisional Patent Application No. 61/906,337. The slide **312** can include a slot **314** configured to interact with the pin. The slide is configured to move upward and downward. The movement of the slide can rotate the engaging surface. The engaging surface can rotate the extension **178**, **278** to which the engaging surface is attached. The extension can rotate one of the tips **160**, **260** which can impart a force of the other of the tips **160**, **260**.

Although this disclosure has been described in the context of certain embodiments and examples, it will be understood by those skilled in the art that the disclosure extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses and obvious modifications and equivalents thereof. In addition, while several variations of the embodiments of the disclosure have been shown and described in detail, other modifications, which are within the scope of this disclosure, will be readily apparent to those of skill in the art. It is also contemplated that various combinations or sub-combinations of the specific features and aspects of the embodiments may be made and still fall within the scope of the disclosure. For example, features described above in connection with one embodiment can be used with a different embodiment described herein and the combination still fall within the scope of the disclosure. It should be understood that various features and aspects of the disclosed embodiments can be combined with, or substituted for, one another in order to form varying modes of the embodiments of the disclosure. Thus, it is intended that the scope of the disclosure herein should not be limited by the particular embodiments described above.

What is claimed is:

1. A surgical tool comprising:

a first tip comprising a first tip longitudinal axis; and
a second tip comprising a second tip longitudinal axis;
wherein the surgical tool has a first configuration wherein
the first and second tips operate as forceps;
wherein the surgical tool has a second configuration
wherein the first and second tips operate as scissors;
wherein the surgical tool is configured to transition
between the first configuration and the second configuration,
at least in part, by rotation of the first tip about
the first tip longitudinal axis and by rotation of the
second tip about the second tip longitudinal axis.

2. The surgical tool of claim **1**, wherein the first tip is coupled to a first handle.

3. The surgical tool of claim **1**, wherein the first tip is coupled to a first handle and the second tip is coupled to a second handle.

4. The surgical tool of claim **1**, wherein the first and second tips operate as bipolar forceps in the first configuration.

5. The surgical tool of claim **1**, wherein the surgical tool is configured to transmit or conduct electricity.

6. The surgical tool of claim **1**, further comprising a mechanism configured to cause the rotation of the first tip and the second tip.

7. The surgical tool of claim **1**, wherein the first tip or the second tip is configured to conduct electrical energy.

8. The surgical tool of claim **1**, wherein the first tip and the second tip are configured to conduct electrical energy.

9. The surgical tool of claim **1**, further comprising a mechanism configured to retain the first tip and the second tip in proximity to each other.

10. The surgical tool of claim **1**, further comprising a mechanism configured to selectively allow movement of at least one of the first tip and the second tip.

11. The surgical tool of claim **1**, further comprising a mechanism configured to selectively couple the first tip and the second tip.

12. The surgical tool of claim **1**, further comprising a mechanism configured to selectively allow movement of at least one of the first tip and the second tip in at least one direction.

13. The surgical tool of claim **1**, further comprising a mechanism configured to selectively restrict movement of at least one of the first tip and the second tip in at least one direction.

14. A method of using a surgical tool comprising:
providing a first tip and a second tip coupled to each other,
the first tip comprising a first tip longitudinal axis, the
second tip comprising a second tip longitudinal axis,
wherein the first and second tips are configured for use
as forceps in a first configuration; and
reconfiguring the first and second tips, such that after
reconfiguration, the first and second tips are configured
for use as scissors in a second configuration, wherein
the surgical tool is configured to transition between the
first configuration and the second configuration, at least
in part, by rotation of the first tip about the first tip
longitudinal axis and by rotation of the second tip about
the second tip longitudinal axis.

15. The method of claim **14**, further comprising conducting electrical current to an electrode in the first tip or the second tip.

16. The method of claim **15**, further comprising conducting electrical current to the electrode when the first and second tips are configured for use as forceps.

17. The method of claim **14**, further comprising applying electrical energy with the first tip or the second tip.

18. The method of claim **14**, further comprising bringing the first and second tips into proximity or contact with each other, prior to the rotation of the first tip and the second tip.