



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C11D 3/18, 3/43, 10/04	A1	(11) International Publication Number: WO 93/18128 (43) International Publication Date: 16 September 1993 (16.09.93)
(21) International Application Number: PCT/GB93/00450 (22) International Filing Date: 4 March 1993 (04.03.93) (30) Priority data: 9204976.6 6 March 1992 (06.03.92) GB 9217001.8 11 August 1992 (11.08.92) GB (71) Applicant (for AU CA only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB). (71) Applicant (for all designated States except AU CA): UNIL- EVER NV [NL/NL]; Weena 455, NL-3013 AL Rotter- dam (NL). (72) Inventors: GARRETT, Peter, Robert ; Charlesville, Cilcain Road, Pantymwyn, Clwyd, Wales (GB). INSTONE, Ter- ry ; 11 Foxall Way, Great Sutton, South Wirral, Cheshire L66 2GT (GB). PUERARI, Fransco, Maria ; Via Rabbo- ni 20, I-26100 Cremona (IT). ROSCOE, David ; 20 Brookside Avenue, Waterloo, Liverpool L22 3YD (GB). SAMS, Philip, John ; Cranford, Briardale Road, Willas- ton, South Wirral, Cheshire (GB).		(74) Agent: ELLIOTT, Peter, William; Unilever plc, Colworth House, Sharnbrook, Bedford MK44 1LQ (GB). (81) Designated States: AU, BR, CA, CZ, HU, JP, KR, PL, SK. Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>
(54) Title: LOW-FOAMING, LIQUID CLEANING COMPOSITIONS (57) Abstract A liquid composition comprising a solubilised hydrophobic oil and a first surfactant characterised in that: (a) the hydrophobic oil is a saturated hydrocarbon with a 50%wt loss boiling point in the range 170-300 °C, (b) the first surfactant forms a calcium salt which is no more than sparingly soluble in aqueous solution, and, (c) the composition comprises, in weight excess over the first surfactant, a second, foaming surfactant which is different from the first surfactant.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

- 1 -

LOW-FOAMING, LIQUID CLEANING COMPOSITIONSTechnical Field

5

The present invention relates to surfactant containing, liquid compositions which show a reduced tendency to form a stable foam. Such compositions are of particular utility in the cleaning of hard surfaces such as floors, walls, kitchen or bathroom surfaces and in cleaning soft
10 furnishings such as upholstery, carpets, curtains etc.

While other and broader use of such compositions is not excluded, such as use of the compositions in the
15 manufacture of wood pulp and paper and generally in chemical processing, the compositions will be described with particular reference to hard surface cleaners.

20 Background

The tendency to form a stable foam is a known problem with known hard surface cleaning compositions. While the formation of foam is desirable with many personal washing
25 products, such as shampoos, bath additives and bar soaps,

- 2 -

the presence of foam is often undesirable in fabric washing and surface cleaning operations. As a consequence, considerable effort has been directed toward the investigation of antifoaming systems for fabric washing powders (so-called 'Automatic' powders) and in low-foaming carpet and hard surface cleaners.

Antifoaming surfactant compositions are known which comprise mixtures of hydrophobic oils, such as silicone oils, together with particles, such as hydrophobic silica particles or occasionally alumina or titania particles. A large number of patents have been filed in this technical field. In practice antifoaming components are either added to the surfactant compositions during manufacture or shortly before use of said compositions. The step of adding the antifoam component just prior to use is more common with carpet cleaning compositions (which tend to be liquids) than with fabric washing powders. In washing powder technology it is virtually unknown in practice to mix components shortly before use. One reason for the late addition of the antifoam systems to liquid compositions is believed to be the tendency for insoluble particulate matter to settle out of solutions on storage. However, it has also been suggested, in GB 1407997 (P&G), that silicone antifoams are progressively deactivated if allowed to contact surfactants during processing and storage and complex encapsulation routes have been proposed to overcome these difficulties.

The use of hydrocarbons and calcium sensitive, fatty acid soaps as antifoam systems for powder compositions has been disclosed in GB 1099562 (Unilever: 1964). In that citation are disclosed powdered detergent compositions which comprise anionic sulphate or sulphonate detergents, alkaline polyphosphates and a 'suds-depressant' mixture of

- 3 -

a hydrocarbon and a fatty acid having from 12 to 31 carbon atoms. The hydrocarbon is broadly defined, as including straight or branched chain alkanes (liquid paraffin oils in 1:1 admixture with high melting paraffin waxes having a boiling point above 90°C), alkenes, alkylated benzene, condensed aromatics such as naphthalene and anthracene and their alkylated derivatives and alicyclic hydrocarbons, including terpenes and like compounds. Preferred hydrocarbons include those materials having a boiling point above 90°C, such as the aforementioned mixtures of paraffin oils and waxes, dodecyl benzene and turpentine oil.

The use of the combination of solvents, soaps and selected terpene solvents as antifoam systems for liquid hard surface cleaning compositions is further disclosed in EP 0080749 (P&G: 1982). In these compositions, unlike the carpet cleaning compositions mentioned above, it is particularly desirable that the product can be used at will without the step of adding a separate antifoam component. More specifically, EP 0080749 teaches the use of mono (two isoprene units) or sesqui- (three isoprene unit) terpenes in combination with both a specified solvent (2-(2-butoxy-ethoxy) ethanol: available in the marketplace as BUTYL CARBITOL [RTM]) and 0.05-2%wt of one or more of the alkali, ammonium and alkanol-ammonium soaps of C13-C24 fatty acids as an antifoam system. In this citation, these three components are said to interact so as to have an antifoaming activity. The preferred terpenes as disclosed in this citation are the mono and bi-cyclic terpenes of the 'hydrocarbon class' of terpenes such as terpinenes, terpinolenes, limonenes, pinenes and the so-called 'orange' terpenes as obtained from the skins of oranges. Other terpenes including the terpene alcohols, aldehydes and ketones are less preferred.

SUBSTITUTE SHEET

- 4 -

Terpenes and related compounds suffer from the general disadvantage that they are odiferous compounds and generally lend a pine-like or lemon-like odour to products. It is desirable that the base formulation of cleaning compositions should have a low odour or be odour free. Moreover, it is advantageous for some uses that compositions should also be free of solvents such as butyl carbitol.

10

Summary of the Invention

According to the present invention there is provided a liquid composition comprising a solubilised hydrophobic oil and a first surfactant CHARACTERISED IN THAT:

- a) the hydrophobic oil is a saturated hydrocarbon with a 50%wt loss boiling point in the range 170-300°C,
- 20 b) the first surfactant forms a calcium salt which is no more than sparingly soluble in aqueous solutions of a second foaming surfactant, and,
- c) the composition comprises, in weight excess over the first surfactant, a second, foaming surfactant which is different from the first surfactant.

25

30

Detailed Description of the Invention

Without wishing to be bound by any theory of operation, it is believed that the concentrated compositions of the present invention comprise the hydrocarbon oil solubilised in micelles. As the composition is diluted with water of a hardness >1 French at least a part of the saturated

35

- 5 -

hydrocarbon is dissolubilised of solution along with at least a part of the calcium sensitive surfactant.

It is further believed that the synergistic interaction of hydrophobic particles formed on dilution (i.e. the insoluble portion of the calcium salt of the first surfactant) and the hydrocarbon droplets lead to an effective foam control as regards the second surfactant.

Accordingly, a further aspect of the present invention subsists in the use, as an antifoaming additive in a liquid cleaning composition comprising at least one foaming surfactant of a mixture of saturated hydrocarbon with a 50%wt loss boiling point in the range 170-300°C, and a surfactant other than the first above-mentioned surfactant which forms a calcium salt which is no more than sparingly soluble in aqueous solution.

A particular advantage of such use of a hydrocarbon and a calcium sensitive surfactant, as an antifoam system for addition to or incorporation in a foaming cleaning composition, is that no particles are present in the initial system prior to dilution and consequently settling or other phase separation of these particles does not lead to the separation on storage difficulties mentioned above.

Consequently, compositions according to the present invention are generally isotropic. An advantage of isotropic compositions, in which the hydrocarbon is initially solubilised, is that they need not be shaken or prepared by mixing shortly before use, whereas previous products either needed to be shaken before use, or, where suspensions of relatively large (silicone or fatty) oil droplets were employed, prior products required a high viscosity with the associated disadvantages of opacity and

- 6 -

poor dosing/mixing properties. Isotropic compositions are also believed to have an improved temperature stability as compared with non-isotropic compositions.

5 In the context of the present invention, a surfactant which forms an insoluble or sparingly soluble calcium salt in aqueous solution of foaming surfactants is generally one where the Krafft temperature of the calcium salt is above 45°C and the solubility product of the calcium salt
10 is generally less than 10^{-8} Moles³ Litre⁻³. It is not intended that this limitation should be held to indicate that all surfactants with a solubility product in an aqueous solution of less than 10^{-8} Moles³ Litre⁻³ are suitable, but only those surfactants which form a calcium
15 salt which will still precipitate from a solution of foaming surfactant. It is believed that surfactants which form an insoluble or sparingly soluble calcium salt having a solubility product in a aqueous solution of foaming surfactant is greater than 10^{-8} Moles³ Litre⁻³ would be
20 unsuitable.

Preferably, compositions according to the present invention are transparent.

25 Hydrocarbon

As mentioned above, the hydrophobic oil is a saturated hydrocarbon with a 50%wt loss boiling point in the range 170-300°C.

30 In the context of the present invention the term 50% loss boiling point is intended to indicate that 50% of the weight of the paraffin can be distilled-off at a temperature within this range under a pressure of one
35 atmosphere.

- 7 -

Preferably the hydrocarbon is a paraffin.

In general, the limits of boiling points of hydrocarbons, preferably paraffins, suitable for use in the composition of the present invention lie between 171 and 250°C.

We have found that the isoparaffins, i.e. branched chain paraffins, are particularly effective.

A further advantage associated with formulations based on the isoparaffins is that the compositions are essentially odour free.

The hydrocarbon content of compositions embodying the present invention is typically in the range 0.2-10wt%, more preferably, 0.5-5wt, most preferably 0.5-2.0wt%.

Compositions according to the present invention can be free of terpenes and related aromatic compounds.

20

First Surfactant

As mentioned above, it is essential that the first surfactant forms a calcium salt which is no more than sparingly soluble in aqueous solutions of foaming surfactants.

The insoluble or sparingly soluble calcium salt-forming surfactant content of embodiments of the invention is preferably 0.2-45wt on product: the upper levels of this range being used for more highly concentrated compositions.

- 8 -

Preferably the insoluble calcium salt-forming surfactant content is in the range 0.2-3.0%wt, most preferably in the range 0.6-2.0%wt.

- 5 Surfactants which form insoluble or sparingly soluble calcium salts as hereinbefore defined include carboxylates and their salts, preferably fatty acids, soluble salts of fatty acids (traditional 'soaps') with a suitable cation, preferably derived from fatty acids having an average
10 carbon chain length in the range 8-24.

More preferably, the first surfactant is an alkali metal salt of saturated fatty acids having an average carbon chain length in the range 12-16. The sodium and potassium
15 salts are most preferred.

Alternative calcium-sensitive surfactants include calcium sensitive surfactant phosphates, sulphates and
20 sulphonates. These share the common feature that they are anionic surfactants of which the calcium salt has a Krafft temperature above typical product use temperature.

The use of carboxylates as the first surfactant, preferably fatty acids, and/or phosphates as the first
25 surfactant is particularly preferred, with the fatty acid soaps being the most preferred first surfactant.

The preferred ratio of insoluble calcium salt forming surfactant to the hydrocarbon is in the range 0.4-2:1.
30 The most preferred ratios being in the range 0.9:1-1:0.9.

Second Surfactant

It is essential that the second surfactant, which can be a
35 mixture of surfactant species is a foaming surfactant (or


- 9 -

contains at least one foaming surfactant) and is different from the first surfactant.

Typically, the second surfactant is selected from the group comprising, primary and secondary alcohol sulphate, alkyl aryl sulphonates, alkoxyated alcohols, primary and secondary alkane sulphonates, lactobionamides, alkyl polyglucosides, polyhydroxyamides, alkyl glucamides, alkoxyated carboxylates, mono- or di- alkyl sulphosuccinates, alkyl carboxylic acid ester sulphonates, alkyl isethionates and derivatives thereof and mixtures thereof.

Preferably the second surfactant comprises one or more of the group comprising: primary alcohol sulphates, alkoxyated alcohols, alkane sulphonates and alkyl aryl sulphonates. More preferably the second surfactant comprises a mixture of primary alcohol sulphates and alkoxyated alcohols. More preferably the primary alcohol sulphates and alkoxyated alcohols are present in a ratio of from 3:1 to 1:1 with a ratio of around 2:1 being particularly preferred.

The preferred primary alcohol sulphate (PAS) comprises a mixture of materials of the general formulation:



wherein R is a C₈ to C₁₈ primary alkyl group and X is a solubilising cation. Suitable cations include sodium, magnesium, potassium, ammonium and mixtures thereof.


Particularly preferred PAS molecules are those with a major proportion of C₁₀-C₁₄ alkyl residues.

- 10 -

These surfactants can be obtained by forming the primary alcohol sulphate from fatty acids obtained from renewable resources such as coconut oil although they can also be obtained from synthetic alcohol sources. These
5 surfactants show very acceptable biodegradation behaviour.

The preferred alkoxyalated alcohols are selected from the group comprising ethoxylated alcohols of the general formula:

10



wherein R_1 is straight or branched, C_8 to C_{18} alkyl and the average degree of ethoxylation m is 1-14, preferably 3-8.

15

The starting materials for the synthesis of these ethoxylated alcohols are available from both natural and synthetic sources.

20 Solvents

Compositions according to the present invention can further comprise a solvent, preferably, when present, at level of 5-15%wt on product.

25

It is believed that the presence of the solvent assists in the solubilisation of the hydrocarbon into micelles. However, as will be shown hereinafter by way of example, the presence of solvents is not a necessary feature of the
30 compositions according to the present invention.

Preferably, any solvent present is selected from:
propylene glycol mono n-butyl ether, dipropylene glycol mono n-butyl ether, propylene glycol mono t-butyl ether,
35 dipropylene glycol mono t-butyl ether, diethylene glycol

- 11 -

hexyl ether, ethyl acetate, methanol, ethanol, isopropyl alcohol, ethylene glycol monobutyl ether, di-ethylene glycol monobutyl ether and mixtures thereof.

- 5 Most, preferably the solvent is a glycol ether or C₂-C₅ alcohol solvent.

Particularly preferred solvents are selected from the group comprising ethanol (preferably as industrial
10 methylated spirits), propylene glycol mono n-butyl ether (available as 'Dowanol PnB' [RTM]) and di-ethylene glycol monobutyl ether (available in the marketplace both as 'Butyl Digol' [RTM] or 'Butyl Carbitol' [RTM]).

15 Minors

The compositions of the invention can further comprise other components selected from the group comprising: perfumes, colours and dyes, hygiene agents, viscosity
20 modifying agents, antioxidants, buffers and mixtures thereof. These minor components are not essential for the performance of the invention but the presence of one or more of these components is preferred in practical embodiments of the invention.

25

It is preferable, where primary alcohol sulphate is present as surfactant that compositions according to the invention comprise a potassium salt as a minor ingredient. It is believed that the presence of such salts improves
30 the low temperature stability of the products.

Particularly preferred compositions according to the present invention comprise:

- 12 -

- a) 15-30%wt primary alcohol sulphate (i) and 5-15% nonionic surfactant (ii) wherein the ratio of (i):(ii) falls in the range 3:1 to 1:1,
- 5 b) 1-5%wt potassium carbonate,
- c) 5-15%wt glycol ether or C₂-C₅ alcohol solvent,
- 10 d) 0.2-5%wt of a paraffin with a 50%wt loss boiling point in the range 170-300 Celsius, and,
- e) 0.2-5%wt of a salt of saturated fatty acids having an average carbon chain length in the range 12-16.

15

EXAMPLES

In order that the present invention may be further understood it will be illustrated hereafter by way of non-limiting examples.

20

EXAMPLES 1-14

In the following examples the effectiveness of an antifoaming composition was evaluated against comparative examples both by a 'cylinder shaking' test method and a 'bowl-filling' test method.

25

In the 'cylinder-shaking' test method, 1.5 ml of product was introduced into 50mls of water in a 100ml stoppered measuring cylinder and shaken vigorously 40 times by hand. In order to maintain the vigour of the action, the hand was changed after 20 shakes. Each shake involved a vertical up/down motion of 30cm and, on average, twenty shakes occurred every 5 seconds. After shaking the

30

35

- 13 -

stoppers were removed and the initial foam height was measured. The maximum foam volume could be calculated from this. The 'decay time', i.e. the time taken for the foam to collapse to a level at which less than 5 ml
5 remained was also determined and recorded. The source of water used was varied and is noted below.

The 'bowl-filling' test method approximates the process of filling a bucket for floor cleaning. 5 litres of water
10 was fed into a 10 litre bowl containing 30mls of product from a 60° semi-angle funnel through a 20cm by 13mm diameter pipe with its end 30cm above the floor of the bowl. Local well water (12-15 French) was used. Foam collapse as 'half-life' was measured by the time taken for
15 the foam volume to fall such that 50% by area of the air water interface was clear of foam.

The bowl filling test is considered to be a more accurate test of the performance of the products in actual use than
20 the cylinder shaking test.

As a comparative example, paired comparison examples were repeated with a control formulation and a commercially available floor cleaning composition (AJAX CITRON VERT)
25 [RTM], which is believed to employ a terpene-perfume/soap based antifoam system stabilised as a microemulsion in the concentrated (neat) product. In addition comparative examples were performed with terpenes and similar perfume components replacing the hydrocarbon.

30 The BASE formulation as used in the following examples employed linear alkylbenzene sulphonate (sodium salt of DOBS [RTM] 102) and alcohol ethoxylate (IMBENTIN [RTM] 91-35 OFA) as a surfactant system. The base formulation was
35 as follows:

SUBSTITUTE SHEET

- 14 -

TABLE 1

	C10-C12 LABS	4.6%wt
	C9-C11 Alcohol 5EO	3.5%wt
5	Butyl Digol	5.0%wt
	Sodium Carbonate	0.5%wt
	Perfume	0.6%wt
	Formaldehyde	0.03%wt
10	Distilled water	to 100%

It will be noted that the BASE composition is free of both hydrophobic hydrocarbon oil and the calcium sensitive surfactant.

For the CONTROL used in the experiments, 0.4% Coconut Soap (Sodium Salt) was added to the BASE formulation. Coconut soap is a calcium sensitive surfactant.

In the SOLVENT BASE formulation mentioned below the formulation of the composition was as given above for the BASE, except that 1.0% ISOPAR-L (RTM, ex Exxon), commercially available, odour free, branched hydrocarbon with a boiling point range of 171-191°C was added to the BASE formulation. This was solubilised by the surfactant present to form a clear solution.

Various levels of Coconut soap were added to the SOLVENT BASE as detailed in the tables below, in order that the synergistic effects of the calcium sensitive soap and the hydrophobic oil could be demonstrated.

- 15 -

The formulation of EXAMPLE 2 comprised 0.5% ISOPAR-L added to the CONTROL formulation (i.e. 0.5% oil plus 0.4% soap).

5 In EXAMPLE 3 mentioned below, the formulation of the composition was as given above for the CONTROL, except that 1% ISOPAR-M (RTM, ex Exxon), a branched hydrocarbon with a boiling point range of 207-256°C was added to the CONTROL formulation (i.e. 1% oil plus 0.4%wt soap).

10 In EXAMPLE 4, 0.25% ISOPAR-M was added to the CONTROL formulation (i.e. 0.25% oil plus 0.4% soap).

15 In EXAMPLE 5, 1.0% n-decane (boiling point 174°C) was added to the CONTROL formulation (i.e. 1.0% oil plus 0.4% soap).

In EXAMPLE 6, 1.0% n-tetradecane (boiling point 254°C) was added to the CONTROL formulation (i.e. 1.0% oil plus 0.4% soap).

20 In EXAMPLE 7, 1.0% of ISOPAR-G (RTM ex. Exxon), a branched hydrocarbon with a boiling point range of 155-175°C was employed.

25 In EXAMPLES 8-14, 1.0% of one of the following odiferous essential oils and similar compounds, each commonly used as a perfume or perfume ingredient in cleaning compositions was substituted for the hydrocarbon:

30

- 16 -

TABLE 2

EXAMPLE	INGREDIENT	TYPE
8	Limonene	Monoterpene
9	Linalool	Terpenoid
10	Citronellal	Terpenoid
11	Cyclohexanol	Cycloalkanol
12	Benzyl alcohol	Aromatic alcohol
13	Menthol	Terpenoid
14	Glycerol triacetate	Triglyceride

The following averaged or ranged results were obtained with the controls and formulations given below in repeated experiments taking the average of 4-5 duplicates in each instance:

- 17 -

TABLE 3: CYLINDER-SHAKING

	MAX. VOLUME	DECAY TIME
25 French Water at 21°C		
5 CONTROL (soap, no solvent)	45	3 min 33 sec
'AJAX'	24	0 min 31 sec
SOLVENT BASE + 0.4% SOAP	32	0 min 21 sec
Demineralised water		
10 CONTROL (soap, no solvent)	-	>20 min (stable)
'AJAX'	-	>20 min (stable)
SOLVENT BASE + 0.4% SOAP	-	3-4 min

15

From the results given in Table 3 it can be seen that the
embodiments of the present invention show an improvement
over controls with hard water and a very significant
20 improvement with 'very soft' water.

In particular, the hydrocarbon-based systems of the
present invention show a significant improvement over the
terpene-based systems of the prior art under the worst
25 possible, (i.e. using de-ionised water) circumstances.

- 18 -

TABLE 4: BOWL FILLING

		Foam 'half-life'
	BASE (no HC, no soap)	>300 sec
5	CONTROL (soap, no HC)	>300 sec
	'AJAX' (terpene, soap)	102-201 sec
	SOLVENT BASE (HC, no soap)	>300 sec
	SOLVENT BASE + 0.1% soap	>300 sec
10	SOLVENT BASE + 0.2% soap	>300 sec
	SOLVENT BASE + 0.4% soap	32-108 sec
	SOLVENT BASE + 0.6% soap	19-34 sec
	SOLVENT BASE + 0.8% soap	27-37 sec
15	SOLVENT BASE + 1.0% soap	51-55 sec
	EXAMPLE 2 (half solvent level)	c. 60 sec
	EXAMPLE 3 (Isopar M)	26-34 sec
	EXAMPLE 4 (Isopar M)	120-180 sec
20	EXAMPLE 5 (n-decane)	60-120 sec
	EXAMPLE 6 (n-tetradecane)	60-120 sec
	EXAMPLE 7 (isododecane)	>300 sec
	EXAMPLE 8 (Limonene)	>200 sec
25	EXAMPLE 9 (Linalool)	>200 sec
	EXAMPLE 10 (Citronellal)	>200 sec
	EXAMPLE 11 (Cyclohexanol)	>200 sec
	EXAMPLE 12 (Benzyl alcohol)	>200 sec
	EXAMPLE 13 (Menthol)	>200 sec
30	EXAMPLE 14 (Glycerol Triacetate)	>200 sec

SUBSTITUTE SHEET

- 19 -

From the results given in Table 4 can be seen that under these harsher test conditions that significant effects were obtained with additions of upwards of 0.4% soap to the control formulation. In the presence of neither
5 solvent or soap, in the presence of solvent without soap or in the presence of soap without solvent, foam control was inadequate.

In the presence of around 0.5-1.0%wt soap, with 1wt%
10 hydrocarbon in formulations according to the present invention, product performance in 12-15 French water was comparable with the commercial product based on terpenes. From Table 4 it can also be seen that where other hydrocarbons were used (see comparative EXAMPLE 7) or
15 terpene or related compounds were used (comparative EXAMPLES 8-14) product performance was poor as compared with embodiments of the present invention (EXAMPLE 2-6 and examples with SOLVENT BASE plus 0.4-1.0%wt soap).
Limonene, while showing acceptable behaviour in cylinder-
20 shaking tests, showed poor behaviour in the bowl filling test (EXAMPLE 8).

EXAMPLE 15

25 The following formulation was prepared by mixing of the components as listed in Table 5. The components are identified as follows:

30 Sodium PAS: LIAL-123S (RTM ex. Enichem), a sodium salt of primary alcohol sulphate having an average alkyl chain length in the range C₁₂-C₁₃;

35 Nonionic: BIODAC L5-S52 (RTM: ex DAC), alcohol ethoxylate;

- 20 -

Solvent: Butyl Carbitol (RTM: ex Union Carbide);

Table 5

5

10

15

COMPONENT	EXAMPLE
Sodium PAS	18.5%wt
Nonionic	9.5%wt
Coconut fatty acid	1.4%wt
Solvent	8.0%wt
Perfume	1.5%wt
Isoparaffin	1.5%wt
Potassium Carbonate	3.0%wt
Sodium Hydroxide	to pH 11
Distilled water	to 100% wt

20

25

30

The product showed excellent cleaning performance and low foaming. In addition when the formulation of EXAMPLE 15 was cooled to 0°C and stored for 24 hours at that temperature, before re-heating to room temperature, the composition formed a semi-liquid slurry when cold, but when re-heated to room temperature the slurry became liquid without any phase separation. Even after multiple freeze/thaw cycles or prolonged storage at -15°C there was no irreversible phase separation.

EXAMPLES 16-23

The formulations of Examples 16-23, as given in Table 6, illustrate the behaviour of the antifoaming compositions

- 21 -

according to the present invention in the absence of the solvents/hydrotroping agents mentioned in EP 0080749. Components are identified as follows:

- 5 SAS: SAS-30 [RTM]; secondary alkyl sulphonate,
 anionic surfactant ex. Hoechst.
- AEO: IMBENTIN 91-35 [RTM]; alcohol ethoxylate,
 nonionic surfactant.
- 10 Soap: Coconut soap, sodium salt of coco fatty
 acids.

 Compositions were prepared by simple mixing of the
15 components. All were clear, isotropic liquids.

Results are given for foam collapse time in a bowl filling experiment as described above.

- 22 -

TABLE 6

EXAMPLE	16	17	18	19	20	21	22	23
COMPONENT								
SAS	4	4	4	4	-	-	-	-
AEO	8	8	8	8	16	16	16	16
Soap	1	1	-	-	1.2	-	1.2	-
Isopar-L	1	-	1	-	2	2	-	-
Collapse time (sec)	20	150	>300	>300	5	>300	120	>300

Examples 16-19 employ a SAS/Alcohol ethoxylate surfactant system whereas examples 20-21 employ a main surfactant system consisting solely of alcohol ethoxylate.

From Table 6 it can be seen that compositions which comprise both the paraffin hydrocarbon and the fatty acid soap (Examples 16 and 20) show a very acceptable foam collapse time in the absence of the solvent component, whereas the omission of either the hydrocarbon (Examples 17 and 22) or the soap (Examples 18 and 21), or both soap and hydrocarbon (Examples 19 and 23) resulted in an unacceptably long foam collapse time. All percentages are by weight.

- 23 -

CLAIMS

1. A liquid aqueous composition comprising a solubilised hydrophobic oil and a first surfactant CHARACTERISED IN THAT:
- 5
- a) the hydrophobic oil is a saturated hydrocarbon with a 50%wt loss boiling point in the range 170-300°C,
- 10
- b) the first surfactant forms a calcium salt which is no more than sparingly soluble in aqueous solution of a second foaming surfactant, and,
- 15
- c) the composition comprises, in weight excess over the first surfactant, a second, foaming surfactant which is different from the first surfactant.
- 20
2. Composition according to claim 1 wherein the hydrocarbon content is 0.4-5.0wt% on product.
3. Composition according to claim 1 wherein the first surfactant content is 0.2-5.0wt% on product.
- 25
4. Composition according to claim 1 further comprising a 5-15%wt of a solvent on product.
5. Composition according to claim 1 wherein the first surfactant is an alkali metal salt of saturated fatty acids having an average carbon chain length in the range 12-16.
- 30

- 24 -

6. Composition according to claim 1 wherein the ratio of first surfactant to hydrocarbon is in the range 0.4-2:1.
- 5 7. Composition according to claim 1 wherein the second surfactant is selected from the group comprising, primary and secondary alkyl sulphates, alkyl aryl sulphates, alkoxyated alcohols, primary and secondary alkane sulphates, lactobionamides, alkyl polyglucosides, polyhydroxyamides, alkyl glucamides, 10 alkoxyated carboxylates, mono- or di- alkyl sulphosuccinates, alkyl carboxylic acid ester sulphates, alkyl isethionates and derivatives thereof and mixtures thereof.
- 15 8. Composition according to claim 7 wherein the second surfactant comprises a primary alcohol sulphate.
9. Composition according to claim 8 wherein the second 20 surfactant comprises a mixture of primary alcohol sulphates and alkoxyated alcohols in a ratio of from 3:1 to 1:1
10. Composition according to claim 4 wherein the solvent 25 is selected from the group comprising propylene glycol mono n-butyl ether, dipropylene glycol mono n-butyl ether, propylene glycol mono t-butyl ether, dipropylene glycol mono t-butyl ether, diethylene glycol hexyl ether, ethyl acetate, methanol, ethanol, 30 isopropyl alcohol, ethylene glycol monobutyl ether, di-ethylene glycol monobutyl ether and mixtures thereof.
11. Composition according to claim 10 wherein the solvent 35 is a glycol ether or C₂-C₅ alcohol solvent.

SUBSTITUTE SHEET

- 25 -

12. Composition according to claim 8 further comprising a potassium salt.
13. Composition according to claim 12 comprising:
- 5
- a) 15-30%wt primary alcohol sulphate (i) and 5-15% nonionic surfactant (ii) wherein the ratio of (i):(ii) falls in the range 3:1 to 1:1,
- 10
- b) 1-5%wt potassium carbonate,
- c) 5-15%wt glycol ether or C₂-C₅ alcohol solvent,
- d) 0.2-5%wt of a paraffin with a 50%wt loss boiling point in the range 170-300 Celsius, and,
- 15
- e) 0.2-5%wt of a salt of saturated fatty acids having a carbon chain length in the range 12-16.
- 20
14. The use, as an antifoaming additive in a liquid cleaning composition comprising at least one foaming surfactant of a 0.4-2.1 ratio mixture of saturated hydrocarbon with a 50%wt loss boiling point in the range 170-300°C, and a surfactant other than the
- 25
- first above-mentioned surfactant which forms a calcium salt which is no more than sparingly soluble in aqueous solution of the first above-mentioned surfactant.
- 30

INTERNATIONAL SEARCH REPORT

PCT/GB 93/00450

International Application No

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 C11D3/18; C11D3/43; C11D10/04		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	C11D	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ^o	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	EP,A,0 137 616 (THE PROCTER & GAMBLE CO.) 17 April 1985	1-8, 10-12
A	see claims 1-9; examples ---	9,13,14
X	DATABASE WPIL Section Ch, Derwent Publications Ltd., London, GB; Class A97, AN 83-739842 [33] & SU,A,965 456 (PLETNEV ET AL.) 15 October 1982	1,3,5,7
A	see abstract ---	14
X	DATABASE WPI Section Ch, Derwent Publications Ltd., London, GB; Class D15, AN 70-50617R [28] & JP,A,45 019 974 (LION FAT AND OIL CO. LTD.)	1,5,6, 10,11
A	see abstract ---	14
	-/--	
^o Special categories of cited documents : ¹⁰ "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
14 JUNE 1993	0 2. 07. 93	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	SERBETSOGLOU A.	

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category °	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
X	US,A,2 751 358 (CAVIET M.) 19 June 1956 see the whole document ---	1,7,14
X	CHEMICAL ABSTRACTS, vol. 99, no. 2, July 1983, Columbus, Ohio, US; abstract no. 7217d, page 79 ; see abstract & DD,A,158 510 (HOFFMANN M. ET AL.) 19 January 1983 ---	1,14
X	US,A,3 657 136 (H. LIEBERMAN ET AL.) 18 April 1972 see claims ---	1,3,5,7
A	EP,A,0 080 749 (THE PROCTER & GAMBLE CO.) 8 June 1983 cited in the application see the whole document ---	1,4,5, 10,14
A	CA,A,874 943 (BETZ LABORATORIES) 6 July 1971 see claims -----	1,14

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.**

GB 9300450
SA 70897

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14/06/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0137616	17-04-85	CA-A- 1236372	10-05-88
		DE-A- 3469037	03-03-88
		JP-A- 60106898	12-06-85

US-A-2751358		DE-C- 855688	

US-A-3657136	18-04-72	None	

EP-A-0080749	08-06-83	CA-A- 1202858	08-04-86
		JP-A- 58132097	06-08-83

CA-A-874943		None	
