

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 534 780 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
12.06.1996 Bulletin 1996/24

(51) Int Cl.⁶: **F23G 7/06**, F23G 5/46,
F23M 9/06

(21) Application number: **92308760.5**

(22) Date of filing: **25.09.1992**

(54) **Flame fired heat exchanger**

Mit einer Flamme beheizter Wärmetauscher

Echangeur de chaleur chauffé par une flamme

(84) Designated Contracting States:
**AT BE CH DE DK ES FR GB GR IE IT LI LU NL PT
SE**

(30) Priority: **27.09.1991 US 776714**

(43) Date of publication of application:
31.03.1993 Bulletin 1993/13

(73) Proprietor: **HEAT AND CONTROL, INC.**
South San Francisco CA 94080-6684 (US)

(72) Inventors:
• **Caridis, Andrew A.**
San Carlos, California 94070 (US)

• **Klein, Lawrence F.**
Hillsborough, California 94010 (US)

(74) Representative: **Bayliss, Geoffrey Cyril et al**
BOULT, WADE & TENNANT
27 Furnival Street
London EC4A 1PQ (GB)

(56) References cited:
EP-A- 0 342 365 **BE-A- 630 381**
DE-B- 1 112 243 **US-A- 2 177 573**

EP 0 534 780 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

This invention pertains to flame fired heat exchangers for cooking systems where atmospheric pollutants are generated from the cooking process and are circulated to the heat exchanger for treatment.

The cooking of potato chips, corn chips, chicken, meat balls and the like in a hot oil bath causes a mist to be generated over the bath. This mist includes hydrocarbons, particulates, oil droplets, smoke, water released from the food product as well as fats and other carbonaceous and odor creating elements released during the cooking process. These will be called "pollutants" below. While at one time it was common to release such pollutants to the atmosphere, today's clean air requirements prescribe that a plant operator minimize to a high extent the amount of pollutants released into the environment.

To achieve a minimal release of pollutants it has been observed that improvements are required to heat exchangers used in food cooking systems for remote heating of either a cooking fluid such as oil or water or the heating of a heat transfer fluid such as a thermal oil. Such improvements should produce a result that the odors emitted from the system are greatly reduced, if not undetectable, which is the most desirable condition indicating that pollutants are at a very low acceptable level. It is believed that the delivery of a large amount of the pollutants from the cooker to the heat exchanger combustion chamber often times passes through the combustion chamber and out the exhaust stack leaving a telltale smell in the vicinity of the plant and this is objectionable. The flow of gases in the combustion chamber, it is believed, is in a laminar pattern which tends to minimize mixing of the pollutants with the combustion gases. Thus, improvements in the combustion chamber design should ideally give a higher measure of mixing such as generating a greater amount of turbulent flow of the pollutant vapors and the combustion products so that a very minimum of odor is detectable issuing from the heat exchanger stack. A known parameter for dwell time or residence time of gases in a combustion chamber is three-tenths of a second at 760°C (1400°F) and, when products are held for this time in the combustion chamber, thorough treatment and odor reduction is achieved provided there is sufficient turbulence to ensure mixing of the pollutants and combustion gases.

A flame fired heat exchanger for coupling to a system for cooking a food product in a cooking fluid in which cooking vapors and odour pollutants released during cooking are retrieved and circulated to a flame burner of the heat exchange for incineration serving to reduce the pollutants released to the atmosphere is known from EP-A-0 342 365 This known arrangement includes a housing enclosing a tube array for a heat transfer or a cooking fluid to be heated for cooking the food product, and a combustion chamber, a burner arranged on the housing to project a flame into the combustion chamber,

and a plenum proximate the burner means and equipped to receive cooking vapors from the cooking system and having a discharge opening serving to release such vapors and odour pollutants into the combustion chamber.

The present invention provides a flame fired heat exchanger for coupling to a system for cooking a food product in a cooking fluid thereby generating cooking vapors and odor pollutants released during cooking which are retrieved and circulated to the flame burner of the heat exchanger for incineration serving to reduce the pollutants released to the atmosphere, and comprises: housing means enclosing a tube array for a heat transfer or a cooking fluid to be heated for cooking the food product, and a combustion chamber, burner means arranged on the housing to project a flame centrally into the combustion chamber, plenum means proximate the burner means and equipped to receive cooking vapors from the cooking system and having a discharge opening serving to release such vapors and odor pollutants into the combustion chamber for entrainment into the flow of the products of combustion from the burner, baffle means mounted in the combustion chamber and extending there across in a plane generally normal to the principal axis of the burner, the baffle means having a central opening therein serving to pass combustion gases therethrough along the path towards the tube array to an exhaust discharge from the heat exchanger, and a frusto-conically shaped, turbulence increasing body mounted in the combustion chamber spaced apart from the baffle means so as to define an annular flow slot along the sidewalls of the body through the opening in the baffle means, the body being arranged to project towards the burner flame with the larger base disposed away from the burner and having a central flow passageway extending therethrough.

In the accompanying drawings:

FIG. 1 is a schematic view of a food cooking system wherein the cooking fluid is heated in a pollution-controlled heat exchanger;

FIG. 2 is a view taken in the direction of the arrows 2-2 of FIG. 1;

FIG. 3 is a view taken in the direction of the arrows 3-3 of FIG. 2;

FIG. 4 is a sectional view taken in the direction of the arrows 4-4 of FIG. 1; and

FIG. 5 is a view taken in the direction of the arrows 5-5 of FIG. 4.

As shown in FIG. 1 of the drawings, a flame fired heat exchanger 10 is arranged in a system 11 for cooking a food product in a cooker 12. The cooker 12 may be equipped for cooking potato chips, corn chips, chicken parts, meat balls and the like and, to this end, is provided with a cooking fluid or heat transfer fluid maintained by the heat exchanger 10 in the desired cooking range typically from about 82° (180°F) to about 204°C

(400°F) and in the case of a heat transfer fluid in a range of from 204°C (400°F) to about 315°C (600°F). One or more oil outlets 13 from the cooker 12 deliver oil to a fines removal unit 14 where solids are removed from the cooking oil before delivery to a main system pump 16 which delivers oil in the direction of the arrows 15 to a heating tube bundle 17 of the heat exchanger 10 for re-heating. The oil emerges from the tube bundle 17 and is delivered by a conduit 18 through one or more oil inlets 19 into the cooker 12.

To prevent vapor emissions from the cooker 12 from polluting the atmosphere surrounding the plant where the system 11 is installed, the pollutants generated in the cooking process within the cooker 12 are collected from a cooker exhaust 21. A fan 22 creates a draft or a negative pressure over the cooking fluid in the cooker 12 so that the vapors from the cooking products are drawn through the exhaust 21, first encountering an oil mist eliminator 23 which serves to remove oil droplets from the cooker exhaust for reuse of the oil in the process. A control 24 is interposed in the cooker exhaust line 21 ahead of the fan 22 so that the cooker exhaust may be delivered to a plenum 26 downstream of the fan 22, the plenum being equipped to exhaust vapors from the cooker 12 to a location within the heat exchanger 10 adjacent to a burner 34 for entrainment into the turbulent flow of the products of combustion. An air dilution stream including fresh air and exhaust from the heat exchanger is delivered through a conduit 28 into the cooker exhaust 21 flow and is controlled by regulators 29 and a barometric damper 30 to ensure that the necessary volume mixture and temperature of the mixtures reaches the plenum 26 and discharges into a combustion chamber 31 of the heat exchanger 10.

The heat exchanger 10, shown schematically in FIG. 1, is generally L-shaped having a generally horizontally disposed combustion chamber 31 arranged at a right angle to a tube bundle compartment 32 which houses the tube bundle 17. The walls of the heat exchanger 10 are formed from steel and are well-insulated as indicated by the cross-hatching in FIG. 1 with use of refractories 33 well-known in the industry. The burner 34 is mounted at one end of the combustion chamber 31 and may burn either liquid or gaseous fuel as dictated by fuel availability and cost. The burner is arranged to project a flame 27 axially along the center portion of the combustion chamber 31 towards a baffle 36 having a central orifice 37 through which the combustion gases must flow from the combustion chamber 31 to an exhaust 38 of heat exchanger 10.

So as to increase turbulence for mixing and reduce laminar gas flow within the combustion chamber, there is mounted in a substantially occluding relationship with respect to the aperture or orifice 37 a frusto-conically shaped body 41 mounted with the larger base disposed away from the flame and the narrower base disposed closer to the flame 27, FIGS. 4 and 5. The conical-like member 41 is supported from the baffle plate 36 by one

or more gusset plates 42 and is arranged concentric with the orifice 37 so as to provide, as viewed in FIG. 4, an annular slot 44 through which the combustion gases flow. In other words, the conical body 41 serves somewhat as a plug or target within the combustion chamber for increasing the turbulence, uniformity of gas temperature and uniformity of gaseous mixing between the pollution gases introduced into the combustion chamber from the plenum 26 and the products of combustion released by the burner 34. The plug or target 41 has a centrally arranged opening 46 which serves as a gas passageway into the tube chamber 32. Thus, the flow of heating gases from the combustion chamber to the tube chamber takes place through the annular slot 44 and through the cylindrical opening 46. The presence of the opening serves to reduce laminar flow along the conical surface of the body 41 and to reduce the stagnation zone of gas flow behind or downstream of the body 41.

A typical effective relationship between the inside radius "A" of the combustion chamber 31, the radius "B" of the orifice 37 and the radius "C" of the base of the plug 41 is as follows: A = 0.91 m (36 in); B = 0.57 m (22.5 in); and C = 0.53 m (21 in). The distance from the baffle plate 36 to the base of the plug 41 can be about 0.41 m (16 in).

These dimensions were selected so as to create a condition within the combustion chamber of reduced laminar gaseous flow and increased turbulent flow. At typical firing rates to maintain a combustion chamber temperature of about 760°C (1400°F), the gas flow across the target or plug 41 as indicated generally by the arrows in FIG. 5 generates a *vena contracta* which is larger in area than the orifice 37 and which dwells a distance upstream from the baffle plate 36. Gas flow through the orifice 37 generates a *vena contracta* which is smaller in area than the orifice 37 and which dwells a distance downstream from the baffle plate 36. This serves to create a more turbulent condition and to hold the gases in the combustion chamber a somewhat longer time than if the foregoing structures were absent. One important result is a decrease in laminar flow through the combustion chamber with increased temperature and mixing uniformity of the pollutants with the combustion gases to achieve a more complete incineration of the pollutants, reaching the desired low level of pollutant emissions into the atmosphere from the heat exchanger exhaust 38.

So that the position of the plug or target body 41 may be optimized with respect to the most desirable position as to the selected temperature zone of the flame and its location on the orifice plate 36, one or more of the gusset members 42 and supports 43 are provided with a series of openings and fasteners whereby different positions may be selected for adjustment of the body 41.

The baffle 36 is supported from the steel sidewall 35 of the heat exchanger by arcuately-spaced gussets 48 as shown in FIG. 4. Slots 49 are cut in the baffle plate

36 opening into the orifice 37 so as to accommodate for expansion and contraction of the baffle plate in accordance with the heat load imposed upon it.

Referring more particularly to FIGS. 2 and 3, the plenum 26 is equipped with a drain 51 and discharge valve 52 so that any liquid collected therein may be removed. It will be seen that the neck 53 of the plenum enshrouds the burner flame 27, thus ensuring that pollution products delivered by the pollution fan to the plenum will be introduced into the combustion chamber in pattern concentric with the burner flame 27.

Claims

1. A flame fired heat exchanger (10) for coupling to a system (11) for cooking a food product in a cooking fluid thereby generating cooking vapors and odor pollutants released during cooking which are retrieved and circulated to the flame burner of the heat exchanger for incineration serving to reduce the pollutants released to the atmosphere, and comprising:

housing means (32) enclosing a tube array (17) for a heat transfer or a cooking fluid to be heated for cooking the food product, and a combustion chamber (31),

burner means (34) arranged on the housing to project a flame (27) centrally into the combustion chamber (31),

plenum means (26) proximate the burner means (34) and equipped to receive cooking vapors from the cooking system and having a discharge opening (53) serving to release such vapors and odor pollutants into the combustion chamber (31) for entrainment into the flow of the products of combustion from the burner, characterised in that

baffle means (36) are mounted in the combustion chamber (31) and extend there across in a plane generally normal to the principal axis of the burner, the baffle means (36) having a central opening (37) therein serving to pass combustion gases therethrough along the path towards the tube array (17) to an exhaust discharge (38) from the heat exchanger (10), and a frusto-conically shaped, turbulence increasing body (41) is mounted in the combustion chamber (31) spaced apart from the baffle means (36) so as to define an annular flow slot (44) along the sidewalls of the body (41) through the opening (37) in the baffle means (36), the body (41) being arranged to project towards the burner flame (27) with the larger base disposed away from the burner and having a central flow passageway (46) extending therethrough.

2. A heat exchanger as claimed in claim 1, characterised in that means (42,43) are provided for mounting the frusto-conically shaped body (41) in a manner for spacing the body at selected distances from the baffle means (36) for changing the size of and the flow rates through the annular slot (44).

3. A heat exchanger as claimed in claim 1, characterised in that the turbulence increasing body (41) is positioned a distance with respect to the baffle means (36) with the major base of the body closest to and generally parallel with the baffle means (36), and the diameter of the major base being selected so that a **vena contracta** created by gas flow with respect to the body (41) upstream of the baffle means is larger in diameter than the diameter of the central opening (37) in the baffle means (36).

4. A heat exchanger as claimed in claim 1, 2 or 3, characterised in that the minor base of the turbulence increasing body (41) has an opening (46) for gas flow therethrough serving to improve mixing of the pollutants and combustion gases.

5. A heat exchanger as claimed in claim 3, characterised in that the diameter of the major base of the body (41) is selected so that the said **vena contracta** larger in diameter than a **vena contracta** created by gas flow through the central opening (37) of the baffle means (36) downstream of the baffle means.

6. A cooking apparatus incorporating a heat exchanger as claimed in any preceding claim.

Patentansprüche

1. Flammenbeheizter Wärmeaustauscher (10) für eine Koppelung mit einem System (11) zum Kochen eines Nahrungsmittels in einem Kochfluid, wodurch Kochdämpfe und während des Kochens freigesetzte Geruchsverunreinigungsstoffe erzeugt werden, die wiedergewonnen und zu dem Flammenbrenner des Wärmeaustauschers für eine Verbrennung umgewälzt werden, die zur Reduzierung der an die Atmosphäre abgegebenen Verunreinigungen dient,

- mit einer Gehäuseeinrichtung (32), die eine Rohranordnung (17) für ein Wärmeaustauschfluid oder für ein zum Kochen des Nahrungsmittels zu erhitzendes Kochfluid sowie eine Verbrennungskammer (31) umschließt,
- mit einer Brenneinrichtung (34), die an dem Gehäuse zum Ausstoßen einer Flamme (27) zentral in die Verbrennungskammer (31) angeordnet ist,
- mit in der Nähe der Brenneinrichtung (34) angeordneten Kammereinrichtungen (26), die für

die Aufnahme von Kochdämpfen aus dem Kochsystem ausgerüstet sind und eine Abführöffnung (53) haben, die zur Abgabe solcher Dämpfe und Geruchsverunreinigungsstoffe in die Verbrennungskammer (31) zum Mitreißen in den Strom der Verbrennungsprodukte aus dem Brenner dient,

dadurch gekennzeichnet,

- daß in der Verbrennungskammer (31) Trenneinrichtungen (36) angeordnet sind und sich quer in einer Ebene erstrecken, die insgesamt senkrecht zur Hauptachse des Brenners ist, wobei die Trenneinrichtungen (36) eine zentrale Öffnung (37) aufweisen, die dazu dient, Verbrennungsgase durch sie hindurch längs des Weges zu der Rohranordnung (17) hin zu einer Abgasabführung (38) aus dem Wärmeaustauscher (10) zu führen, und
 - daß in der Verbrennungskammer (31) im Abstand von den Trenneinrichtungen (36) ein kegelstumpfförmiger, die Turbulenz erhöhender Körper (41) so angeordnet ist, daß längs der Seitenwände des Körpers (41) durch die Öffnung (37) in den Trenneinrichtungen (36) hindurch ein ringförmiger Strömungsschlitz (44) gebildet wird,
 - wobei der Körper (41) so angeordnet ist, daß er zur Brennerflamme (27) vorsteht, daß seine größere Grundfläche von dem Brenner weg angeordnet ist und daß er einen zentralen Strömungsdurchlaß (46) hat, der sich durch ihn hindurch erstreckt.
2. Wärmeaustauscher nach Anspruch 1, dadurch gekennzeichnet, daß Einrichtungen (42, 43) für ein solches Anbringen des kegelstumpfförmigen Körpers (41) vorgesehen sind, daß der Körper mit ausgewählten Abständen von den Trenneinrichtungen (36) zur Änderung der Größe des ringförmigen Schlitzes (44) und zur Änderung der Durchsätze durch den ringförmigen Schlitz (44) angeordnet wird.
3. Wärmeaustauscher nach Anspruch 1, dadurch gekennzeichnet, daß der die Turbulenz erhöhende Körper (41) in einem Abstand bezüglich der Trenneinrichtungen (36) angeordnet ist, wobei sich die größere Grundfläche des Körpers am nächsten bezüglich der Trenneinrichtungen (36) und insgesamt parallel dazu befindet, und daß der Durchmesser der größeren Grundfläche so gewählt ist, daß eine von dem Gasstrom bezüglich des Körpers (41) stromauf von den Trenneinrichtungen erzeugte Einschnürung im Durchmesser größer als der Durchmesser der zentralen Öffnung (37) in den Trenneinrichtungen (36) ist.

4. Wärmeaustauscher nach Anspruch 1, 2 oder 3, dadurch gekennzeichnet, daß die kleinere Grundfläche des die Turbulenz erhöhenden Körpers (41) eine Öffnung (46) für einen Gasdurchstrom hat und dazu dient, das Vermischen der Verunreinigungsstoffe und der Verbrennungsgase zu verbessern.

5. Wärmeaustauscher nach Anspruch 3, dadurch gekennzeichnet, daß der Durchmesser der größeren Grundfläche des Körpers (41) so gewählt wird, daß die erwähnte Einschnürung im Durchmesser größer ist als eine Einschnürung, die von dem Gasstrom durch die zentrale Öffnung (37) der Trenneinrichtungen (36) stromab von den Trenneinrichtungen erzeugt wird.

6. Kochvorrichtung mit einem Wärmeaustauscher nach irgendeinem vorhergehenden Anspruch.

Revendications

1. Echangeur de chaleur (10) chauffé par une flamme, destiné à être raccordé à un système (11) de cuisson d'un produit alimentaire dans un fluide de cuisson, de sorte que des vapeurs de cuisson et des polluants dégagant une odeur, libérés pendant la cuisson sont générés et sont récupérés et remis en circulation pour être dirigés sur le brûleur à flamme de l'échangeur de chaleur pour y être incinérés afin de réduire les polluants libérés dans l'atmosphère, et comprenant :

un moyen de logement (32) enveloppant un ensemble de tubes (17) pour un transfert de chaleur ou pour un fluide de cuisson devant être chauffé pour cuire le produit alimentaire, ainsi qu'une chambre de combustion (31),
 un moyen de brûleur (34) disposé sur le logement pour projeter une flamme (27) centralement dans la chambre de combustion (31),
 un moyen collecteur d'insufflation (26) proche du moyen de brûleur (34) et conçu pour recevoir du système de cuisson les vapeurs de cuisson et comportant un orifice de décharge (53) servant à diriger ces vapeurs et polluants dégagant une odeur dans la chambre de combustion (31) afin qu'ils soient entraînés dans le flux des produits de combustion du brûleur, caractérisé en ce que
 des moyens de chicane (36) sont montés dans la chambre de combustion (31) et y sont disposés transversalement dans un plan sensiblement perpendiculaire à l'axe principal du brûleur, les moyens de chicane (36) comportant un trou central (37) servant à y faire passer les gaz de combustion le long du trajet allant vers l'ensemble de tubes (17) jusqu'à une décharge

(38) d'évacuation de l'échangeur de chaleur (10) et

en ce qu'un corps de forme tronconique (41) accroissant la turbulence est monté dans la chambre de combustion (31) à distance des moyens de chicane (36) de façon à délimiter une fente annulaire de circulation (44) le long des parois latérales du corps (41) par le trou (37) des moyens de chicane (36), le corps (41) étant disposé de manière à être saillant vers la flamme du brûleur (27) en ayant la grande base disposée du côté opposé à celui du brûleur et comportant un passage central de circulation (46) qui le traverse.

15

2. Echangeur de chaleur selon la revendication 1, caractérisé en ce que des moyens (42, 43) sont prévus pour monter le corps de forme tronconique (41) de manière à mettre le corps à des distances sélectionnées des moyens de chicane (36) afin de modifier la dimension de, et le débit passant par, la fente annulaire (44).

20

3. Echangeur de chaleur selon la revendication 1, caractérisé en ce que le corps (41) accroissant la turbulence est placé à distance des moyens de chicane (36) de façon que la grande base du corps soit la plus proche des, et sensiblement parallèle aux, moyens de chicane (36) et en ce que le diamètre de la grande base est choisi de façon qu'une veine étranglée créée par la circulation du gaz par rapport au corps (41) en amont des moyens de chicane, ait un diamètre plus grand que le diamètre du trou central (37) des moyens de chicane (36).

25

30

35

4. Echangeur de chaleur selon la revendication 1, 2 ou 3, caractérisé en ce que la petite base du corps (41) accroissant la turbulence est traversée par un trou (46) de circulation de gaz qui sert à améliorer le mélange des polluants et des gaz de combustion.

40

5. Echangeur de chaleur selon la revendication 3, caractérisé en ce que le diamètre de la grande base du corps (41) est choisi de façon que ladite veine contractée ait un diamètre plus grand qu'une veine étranglée créée en aval des moyens de chicane par la circulation des gaz par le trou central (37) des moyens de chicane (36).

45

6. Appareil de cuisson équipé d'un échangeur de chaleur selon l'une quelconque des revendications précédentes.

50

55





