



(22) Date de dépôt/Filing Date: 2009/01/26

(41) Mise à la disp. pub./Open to Public Insp.: 2009/08/11

(30) Priorité/Priority: 2008/02/11 (US61/065,371)

(51) Cl.Int./Int.Cl. *C10G 1/04* (2006.01),  
*B03B 9/02* (2006.01)

(71) Demandeur/Applicant:  
EXXONMOBIL UPSTREAM RESEARCH COMPANY,  
US

(72) Inventeurs/Inventors:  
SURY, KEN N., CA;  
FEIMER, JOSEPH L., CA;  
SUTTON, CLAY R., US


(74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : AMELIORATION DU BITUME DANS UN PROCEDE DE TRAITEMENT DE L'ECUME PARAFFINIQUE

(54) Title: UPGRADING BITUMEN IN A PARAFFINIC FROTH TREATMENT PROCESS

(57) **Abrégé/Abstract:**

The invention relates to an improved bitumen recovery process. The process includes adding water to a bitumen-froth/solvent system containing asphaltenes and mineral solids. The addition of water in droplets increases the settling rate of asphaltenes and mineral solids to more effectively treat the bitumen for pipeline transport, further enhancement, refining, or any other application of reduced-solids bitumen.



**ABSTRACT**

The invention relates to an improved bitumen recovery process. The process includes adding water to a bitumen-froth/solvent system containing asphaltenes and mineral solids. The addition of water in droplets increases the settling rate of asphaltenes and mineral solids to more effectively treat the bitumen for pipeline transport, further enhancement, refining, or any other application of reduced-solids bitumen.

2008EM037

**UPGRADING BITUMEN IN A PARAFFINIC FROTH TREATMENT PROCESS****CROSS-REFERENCE TO RELATED APPLICATION**

[0001] This application claims the benefit of U.S. Provisional Patent Application 61/065,371 filed February 11, 2008.

5

**FIELD OF THE INVENTION**

[0002] The present invention relates generally to producing hydrocarbons. More specifically, the invention relates to methods and systems for upgrading bitumen in a solvent based froth treatment process.

**BACKGROUND OF THE INVENTION**

10 [0003] The economic recovery and utilization of heavy hydrocarbons, including bitumen, is one of the world's toughest energy challenges. The demand for heavy crudes such as those extracted from oil sands has increased significantly in order to replace the dwindling reserves of conventional crude. These heavy hydrocarbons, however, are typically located in geographical regions far removed from existing refineries. Consequently, the  
15 heavy hydrocarbons are often transported via pipelines to the refineries. In order to transport the heavy crudes in pipelines they must meet pipeline quality specifications.

[0004] The extraction of bitumen from mined oil sands involves the liberation and separation of bitumen from the associated sands in a form that is suitable for further processing to produce a marketable product. Among several processes for bitumen  
20 extraction, the Clark Hot Water Extraction (CHWE) process represents an exemplary well-developed commercial recovery technique. In the CHWE process, mined oil sands are mixed with hot water to create slurry suitable for extraction as bitumen froth.

[0005] The addition of paraffinic solvent to bitumen froth and the resulting benefits are described in Canadian Patent Nos. 2,149,737 and 2,217,300. According to Canadian  
25 Patent No. 2,149,737, the contaminant settling rate and extent of removal of contaminants present in the bitumen froth generally increases as (i) the carbon number or molecular weight of the paraffinic solvent decreases, (ii) the solvent to froth ratio increases, and (iii) the amount of aromatic and naphthene impurities in the paraffinic solvent decreases. Further, a temperature above about 30 degrees Celsius (°C) during settling is preferred.

30 [0006] In many instances, it may be advantageous to observe the particle size distribution (PSD) in a particular bitumen-froth mixture. This may be done to ensure that the resulting heavy hydrocarbon product meets pipeline specifications and other requirements and lead to adjustments in the recovery process. Various techniques such as optical, laser diffraction, electrical counting, and ultrasonic techniques have been used to determine PSD.

2008EM037

[0007] One reason for processing the heavy hydrocarbon product in such a process is to eliminate enough of the solids to meet pipeline transport specifications and the specifications of the refining equipment. For example, the sediment specification of the bitumen product as measured by the filterable solids test (ASTM-D4807) may be used to  
 5 determine if the product is acceptable. As such, a higher settling rate of solid particles including mineral solids and asphaltenes from the froth-treated bitumen is desirable.

[0008] Methods to improve the settling rate of the minerals can significantly impact the efficiency of heavy hydrocarbon (e.g. bitumen) recovery processes. There exists a need in the art for a low cost method to produce bitumen which meets various sediment  
 10 specifications.

### SUMMARY OF THE INVENTION

[0009] In one aspect of the invention, a method of recovering hydrocarbons is provided. The method includes providing a bitumen froth emulsion containing asphaltenes and mineral solids; adding a solvent to the bitumen froth emulsion to induce a rate of settling  
 15 of at least a portion of the asphaltenes and mineral solids from the bitumen froth emulsion and generate a solvent bitumen-froth mixture; and adding water droplets to the solvent bitumen-froth mixture to increase the rate of settling of the at least a portion of the asphaltenes and mineral solids. In one aspect, the solvent may be a paraffinic solvent.

[0010] In another aspect of the invention, a system for recovering hydrocarbons is  
 20 provided. The system includes a bitumen recovery plant configured to treat a froth-treated bitumen. The plant includes a froth separation unit having a bitumen froth inlet and a diluted bitumen outlet; and a water droplet production unit configured to add water droplets to the froth-treated bitumen.

### BRIEF DESCRIPTION OF THE DRAWINGS

25 [0011] The foregoing and other advantages of the present invention may become apparent upon reviewing the following detailed description and drawings of non-limiting examples of embodiments in which:

[0012] FIG. 1 is a schematic of an exemplary prior art bitumen froth treatment plant layout;

30 [0013] FIG. 2 is a flow chart of an exemplary bitumen froth treatment process including at least one aspect of the present invention;

[0014] FIG. 3 is a schematic of an exemplary bitumen froth treatment plant layout including at least one aspect of the present invention;

2008EM037

[0015] FIG. 4 is a schematic illustration of the experimental apparatus utilized with the present invention as disclosed in FIGs. 2 and 3;

[0016] FIG. 5 is an image of asphaltene-mineral aggregates obtained with a JM Canty Microflow Particle Sizing System; and

5 [0017] FIGs. 6A-6B are images of asphaltene-mineral-water aggregates obtained after the addition of water to the bitumen-froth-solvent mixture.

#### DETAILED DESCRIPTION

[0018] In the following detailed description section, the specific embodiments of the present invention are described in connection with preferred embodiments. However, to the extent that the following description is specific to a particular embodiment or a particular use  
10 of the present invention, this is intended to be for exemplary purposes only and simply provides a description of the exemplary embodiments. Accordingly, the invention is not limited to the specific embodiments described below, but rather, it includes all alternatives, modifications, and equivalents falling within the true spirit and scope of the appended claims.

15 [0019] The term “asphaltenes” as used herein refers to hydrocarbons, which are the n-heptane insoluble, toluene soluble component of a carbonaceous material such as crude oil, bitumen or coal. Generally, asphaltenes have a density of from about 0.8 grams per cubic centimeter (g/cc) to about 1.2 g/cc. Asphaltenes are primarily comprised of carbon, hydrogen, nitrogen, oxygen, and sulfur as well as trace vanadium and nickel. The carbon to  
20 hydrogen ratio is approximately 1:1.2, depending on the source.

[0020] The term “mineral solids” as used herein refers to “clumps” of non-volatile, non-hydrocarbon solid minerals. Depending on the deposit, these mineral solids may have a density of from about 2.0 g/cc to about 3.0 g/cc and may comprise silicon, aluminum (e.g. silicas and clays), iron, sulfur, and titanium and range in size from less than 1 micron ( $\mu\text{m}$ ) to  
25 about 1,000 microns (in diameter).

[0021] The term “fine solids” as used herein refers to either or both of asphaltenes and mineral solids, but does not generally refer to sand and clumps of clay, rock and other solids larger than about one hundred (100) microns.

[0022] The term “aggregates” as used herein generally refers to a group of solids  
30 comprising “asphaltenes” and “mineral solids”.

[0023] The term “bitumen” as used herein refers to heavy oil having an API gravity of about 12° or lower. In its natural state as oil sands, bitumen generally includes fine solids such as mineral solids and asphaltenes, but as used herein, bitumen may refer to the natural

2008EM037

state or a processed state in which the fine solids have been removed and the bitumen has been treated to a higher API gravity.

**[0024]** The term "paraffinic solvent" (also known as aliphatic) as used herein means solvents containing normal paraffins, isoparaffins and blends thereof in amounts greater than  
5 50 weight percent (wt%). Presence of other components such as olefins, aromatics or naphthenes counteract the function of the paraffinic solvent and hence should not be present more than 1 to 20 wt% combined and preferably, no more than 3 wt% is present. The paraffinic solvent may be a C4 to C20 paraffinic hydrocarbon solvent or any combination of iso and normal components thereof. In one embodiment, the paraffinic solvent comprises  
10 pentane, iso-pentane, or a combination thereof. In one embodiment, the paraffinic solvent comprises about 60 wt% pentane and about 40 wt% iso-pentane, with none or less than 20 wt% of the counteracting components referred above.

**[0025]** The invention relates to processes and systems for recovering hydrocarbons. In one aspect, the invention is a process to partially upgrade a bitumen or heavy crude and is  
15 particularly suited for bitumen froth generated from oil sands which contain bitumen, water, asphaltenes and mineral solids. The process includes extracting bitumen having asphaltenes and mineral solids from a reservoir in the form of a bitumen froth, adding a solvent to the bitumen-froth, then adding water droplets to the solvent bitumen-froth mixture to enhance the settling rate of asphaltenes and mineral solids from the bitumen-froth.

**[0026]** In another aspect, the invention relates to a system for recovering hydrocarbons. The system may be a plant located at or near a bitumen (e.g. heavy hydrocarbon) mining or recovery site or zone. The plant may include at least one froth separation unit (FSU) having a bitumen froth inlet for receiving bitumen froth (or a solvent froth-treated bitumen mixture) and a diluted bitumen outlet for sending diluted bitumen from  
25 the FSU. The plant further includes a water droplet production unit configured to add water droplets to the solvent froth-treated bitumen mixture, one or more of the FSU's and/or the diluted bitumen from at least one of the FSU's. The plant may also include at least one tailings solvent recovery unit (TSRU), solvent storage unit, pumps, compressors, and other equipment for treating and handling the heavy hydrocarbons and byproducts of the recovery  
30 system.

**[0027]** Referring now to the figures, FIG. 1 is a schematic of an exemplary prior art paraffinic froth treatment system. The plant **100** receives bitumen froth **102** from a heavy hydrocarbon recovery process (e.g., CHWE). The bitumen froth **102** is fed into a first froth separation unit (FSU) **104** and solvent-rich oil **120** is mixed with the bitumen froth **102**. A

2008EM037

diluted bitumen stream **106** and a tailings stream **114** are produced from the FSU **104**. The diluted bitumen stream **106** is sent to a solvent recovery unit (SRU) **108**, which separates bitumen from solvent to produce a bitumen stream **110** that meets pipeline specifications. The SRU **108** also produces a solvent stream **112**, which is mixed with tailings **114** from the first FSU **104** and fed into a second froth separation unit **116**. The second FSU **116** produces a solvent rich oil stream **120** and a tailings stream **118**. The solvent rich oil stream **120** is mixed with the incoming bitumen froth **102** and the tailings stream is sent to a tailings solvent (TSRU) recovery unit **122**, which produces a tailings stream **124** and a solvent stream **126**.

**[0028]** In an exemplary embodiment of the process the bitumen froth **102** may be mixed with a solvent-rich oil stream **120** from FSU **116** in FSU **104**. The temperature of FSU **104** may be maintained at about 60 to 80 degrees Celsius ( $^{\circ}\text{C}$ ), or about  $70^{\circ}\text{C}$  and the target solvent to bitumen ratio is about 1.4:1 to 2.2:1 by weight or about 1.6:1 by weight. The overflow from FSU **104** is the diluted bitumen product **106** and the bottom stream **114** from FSU **104** is the tailings substantially comprising water, mineral solids, asphaltenes, and some residual bitumen. The residual bitumen from this bottom stream is further extracted in FSU **116** by contacting it with fresh solvent (from e.g. **112** or **126**), for example in a 25:1 to 30:1 by weight solvent to bitumen ratio at, for instance, 80 to  $100^{\circ}\text{C}$ , or about  $90^{\circ}\text{C}$ . The solvent-rich overflow **120** from FSU **116** is mixed with the bitumen froth feed **102**. The bottom stream **118** from FSU **116** is the tailings substantially comprising solids, water, asphaltenes, and residual solvent. The bottom stream **118** is fed into a tailings solvent recovery unit (TSRU) **122**, a series of TSRUs or by another recovery method. In the TSRU **122**, residual solvent is recovered and recycled in stream **126** prior to the disposal of the tailings in the tailings ponds (not shown) via a tailings flow line **124**. Exemplary operating pressures of FSU **104** and FSU **116** are respectively 550 thousand Pascals gauge (kPag) and 600 kPag. FSUs **104** and **116** are typically made of carbon-steel but may be made of other materials.

**[0029]** FIG. 2 is an exemplary flow chart of a process for recovering hydrocarbons utilizing at least a portion of the equipment disclosed in FIG. 1. As such, FIG. 2 may be best understood with reference to FIG. 1. The process **200** begins at block **202**, then includes extraction of a heavy hydrocarbon to form a bitumen froth emulsion or mixture **204**. After extraction, the mixture is added to a froth separation unit (FSU) **206**, solvent is added to the mixture **208**, and water droplets are added to the solvent bitumen-froth mixture **210**. Steps **206**, **208**, and **210** may be done concurrently or in sequence in any order. This will promote precipitation and settling of asphaltenes and mineral solids (and aggregates thereof) out of the solvent bitumen-froth mixture **212** to produce a diluted bitumen **214**. Solvent is then

2008EM037

recovered from the diluted bitumen **216** to produce bitumen **218**. The process **200** may be repeated as necessary or desired **220**.

**[0030]** Still referring to FIGs. 1 and 2, the step of extracting the heavy hydrocarbon (e.g. bitumen) **204** may include using a froth treatment resulting in a bitumen-froth mixture.

5 An exemplary composition of the resulting bitumen froth **102** is about 60 wt% bitumen, 30 wt% water and 10 wt% solids, with some variations to account for the extraction processing conditions. In such an extraction process oil sands are mined, bitumen is extracted from the sands using water (e.g. the CHWE process or a cold water extraction process), and the bitumen is separated as a froth comprising bitumen, water, solids and air. In the extraction  
 10 step **204** air is added to the bitumen/water/sand slurry to help separate bitumen from sand, clay and other mineral matter. The bitumen attaches to the air bubbles and rises to the top of the separator (not shown) to form a bitumen-rich froth **102** while the sand and other large particles settle to the bottom. Regardless of the type of water based oil sand extraction process employed, the extraction process **204** will typically result in the production of a  
 15 bitumen froth product stream **102** comprising bitumen, water and fine solids (including asphaltenes, mineral solids) and a tailings stream **114** consisting essentially of water and mineral solids and some fine solids.

**[0031]** In one embodiment of the process **200** solvent **120** is added to the bitumen-froth **102** after extraction and the mixture is pumped to another separation vessel (froth  
 20 separation unit or FSU **104**). The addition of solvent **120** helps remove the remaining fine solids and water. Put another way, solvent addition increases the settling rate of the fine solids and water out of the bitumen mixture. In one embodiment of the recovery process **200** a paraffinic solvent is used to dilute the bitumen froth **102** before separating the product bitumen by gravity in a device such as FSU **104**. Where a paraffinic solvent is used (e.g.  
 25 when the weight ratio of solvent to bitumen is greater than 0.8), a portion of the asphaltenes in the bitumen are rejected thus achieving solid and water levels that are lower than those in existing naphtha-based froth treatment (NFT) processes. In the NFT process, naphtha may also be used to dilute the bitumen froth **102** before separating the diluted bitumen by centrifugation (not shown), but not meeting pipeline quality specifications.

30 **[0032]** Adding water droplets **210** to the bitumen froth mixture **102** helps increase the settling rate of the fine solids including asphaltenes, making the process **200** more efficient and allowing higher throughputs of bitumen to be treated and recovered or permitting smaller FSU's **104** and **116** to be used. This result is counterintuitive because it calls for adding water to the bitumen froth solvent mixture **102** even though bitumen froth already contains

2008EM037

large quantities of water (e.g., 30-40% or more depending on the extraction process). Note, the process calls for adding “droplets,” which may vary in size, but as used in this application, a droplet is generally a volume of water small enough to maintain droplet form when falling through air and does not include water “slugs.”

5 **[0033]** The water droplets may be added before mixing the froth treated bitumen with solvent, may be added in the first FSU **104** and/or the second FSU **116** (note, some plants **100** may include three or more FSU’s, any of which may include water droplet addition, depending on the plant **100** and process **200** parameters). The water may also be added above or below a feed injection point in the first or second FSU **104, 116**. The water droplet  
 10 addition increases the propensity of the mineral solids and asphaltenes to attach to each other to create larger particles. The larger particles then settle faster than smaller particles resulting in an increase in the settling rate of greater than a factor of two. The amount of water added can be optimized to enhance the settling rate of the minerals and asphaltenes. Higher settling rates may also permit reduction of the size and cost of the FSU vessels **104, 116** required to  
 15 meet the pipeline sediment specification. For example, the vessels **104, 116** may have an eight to twelve meter diameter rather than an 18 to 22 meter diameter. The addition of water can also be used to optimize an existing paraffinic froth-treatment by increasing the production rate and/or improving the product quality.

**[0034]** As would be expected with any process, the optimum conditions would be  
 20 preferred to produce the largest particle size distribution and subsequently the fastest settling time. Variables may be optimized include, but are not limited to; water-to-bitumen ratio (e.g. from 0.01 weight percent (wt%) to 10 wt%), mixing energy, water droplet size, temperature, solvent addition, and location of water addition. Water may be added either to the FSU feed streams **102, 114** and/or internally within the FSU vessels **104, 116**. Within the  
 25 FSU vessels the water can be added either above and/or below the feed injection point. Further, the type of water used will depend on the available water sources, but is preferably one of fresh river water, distilled water from a solvent recovery unit **108**, recycled water, rain water, or aquifer water.

**[0035]** FIG. 3 is an exemplary schematic of a bitumen froth treatment plant layout  
 30 utilizing the process of FIG. 2. As such, FIG. 3 may be best understood with reference to FIG. 2. The plant **300** includes a bitumen froth input stream **302** input to a froth separation unit (FSU) **304**, which separates stream **302** into a diluted bitumen component **306** comprising bitumen and solvent and a froth treatment tailings component **312** substantially comprising water, mineral solids, precipitated asphaltenes (and aggregates thereof), solvent,

2008EM037

and small amounts of unrecovered bitumen. The tailings stream **312** may be withdrawn from the bottom of FSU **304**, which may have a conical shape at the bottom. A water droplet production unit **303** is also included, which produces water droplets **305a**, **305b**, **305c** and/or **305d** for addition to, respectively, the bitumen froth input stream **302**, FSU **304**, tailings stream **312**, or FSU **320**.

**[0036]** In one embodiment, the water droplet production unit **303** may be a spray nozzle system. The unit **303** may produce droplets at a concentration of at least about 0.01 weight percent (wt%) relative to bitumen to at most about 10 wt% relative to bitumen depending on the composition of the bitumen, size of the handling units (e.g. FSU's) and other factors. Further, the droplets may be produced at a size of from at least about 5 microns ( $\mu\text{m}$ ) in diameter to about 1,000 microns in diameter, although a range of from about 5 microns to about 500 microns is preferred. The added water may be fresh river water, distilled water from a solvent recovery unit **308**, recycled water, rain water or aquifer water.

**[0037]** The diluted bitumen component **306** is passed through a solvent recovery unit, SRU **308**, such as a conventional fractionation vessel or other suitable apparatus in which the solvent **314** is flashed off and condensed in a condenser **316** associated with the solvent flashing apparatus and recycled/reused in the process **300**. The solvent free bitumen product **310** is then stored or transported for further processing in a manner well known in the art. Froth treatment tailings component **312** may be passed directly to the tailings solvent recovery unit (TSRU) **330** or may first be passed to a second FSU **320**.

**[0038]** In one embodiment, FSU **304** operates at a temperature of about 60°C to about 80°C, or about 70°C. In one embodiment, FSU **304** operates at a pressure of about 700 to about 900 kPa, or about 800 kPa. Diluted tailings component **312** may typically comprise approximately 50 to 70 wt% water, 15 to 25 wt% mineral solids, and 5 to 25 wt% hydrocarbons. The hydrocarbons comprise asphaltenes (for example 2.0 to 12 wt% or 9 wt% of the tailings), bitumen (for example about 7.0 wt% of the tailings), and solvent (for example about 8.0 wt% of the tailings). In additional embodiments, the tailings comprise greater than 1.0, greater than 2.0, greater than 3.0, greater than 4.0, greater than 5.0, greater than 10.0 wt% asphaltenes, or about 15.0 wt% asphaltenes.

**[0039]** Still referring to FIG. 3, FSU **320** performs generally the same function as FSU **304**, but is fed the tailings component **312** rather than a bitumen froth feed **302**. The operating temperature of FSU **320** may be higher than that of FSU **304** and may be between about 80°C and about 100°C, or about 90°C. In one embodiment, FSU **320** operates at a pressure of about 700 to about 900 kPa, or about 800 kPa. A diluted bitumen component

2008EM037

stream **322** comprising bitumen and solvent is removed from FSU **320** and is either sent to FSU **304** via feed **324** for use as solvent to induce asphaltene separation or is passed to SRU **308** via feed **325** or to an another SRU (not shown) for treatment in the same way as the diluted bitumen component **306**. The ratio of solvent: bitumen in diluted bitumen component **322** may be, for instance, 1.4 to 30:1, or about 20:1. Alternatively, diluted bitumen component **322** may be partially passed to FSU **304** via line **324** and partially passed to SRU **308** via line **325**, or to another SRU (not shown). Solvent **314** from SRU **308** may be combined with the diluted tailing stream **312** into FSU **320**, shown as stream **318**, or returned to a solvent storage tank (not shown) from where it is recycled to make the diluted bitumen froth stream **302**. Thus, streams **322** and **318** show recycling. In the art, solvent or diluted froth recycling steps are known such as described in U.S. Patent No. 5,236,577.

**[0040]** In the exemplary system of FIG. 3, the froth treatment tailings **312** or tailings component **326** (with a composition similar to underflow stream **312** but having less bitumen and solvent), may be combined with dilution water **327** to form diluted tailings component **328** and is sent to TSRU **330**. Diluted tailings component **328** may be pumped from the FSU **320** or FSU **304** (for a single stage FSU configuration) to TSRU **330** at the same temperature and pressure in FSU **320** or FSU **304**. A backpressure control valve **329** may be used before an inlet into TSRU **330** to prevent solvent flashing prematurely in the transfer line between FSU **320** and TSRU **330**.

**[0041]** Flashed solvent vapor and steam (together **334**) is sent from TSRU **330** to a condenser **336** for condensing both water **338** and solvent **340**. Recovered solvent **340** may be reused in the bitumen froth treatment plant **300**. Tailings component **332** may be sent directly from TSRU **330** to a tailings storage area (not shown) for future reclamation or sent to a second TSRU (not shown) or other devices for further treatment. Tailings component **332** contains mainly water, asphaltenes, mineral matter, and small amounts of solvent as well as unrecovered bitumen. A third TSRU (not shown) could also be used in series and, in each subsequent stage, the operating pressure may be lower than the previous one to achieve additional solvent recovery. In fact, more than three TSRU's could be used, depending on the quality of bitumen, pipeline specification, size of the units and other operating factors.

### **30 Examples**

**[0042]** Experiments were conducted to test the effectiveness of water droplet addition to the bitumen froth streams. The experiments were designed to take small samples of bitumen froth streams, add some water droplets in accordance with the present invention and capture images of the bitumen froth streams before and after addition of the water droplets.

2008EM037

**[0043]** FIG. 4 is a schematic illustration of the experimental apparatus utilized with the present invention as disclosed in FIGs. 2 and 3. Hence, FIG. 4 may be best understood with reference to FIGs. 2 and 3. The experimental setup **400** includes a vessel **402** with a stirrer **404** holding a sample of bitumen froth **405**. The vessel is connected to a particle size analyzer apparatus **406**, which includes a particle sizing computer system **408**, an image analyzer **410**, a variable width flow cell **412**, and a light source **414**. The particle size analyzer apparatus **406** is then connected to a pinch clamp **416** and a beaker **418** for receiving the analyzed samples **405**.

#### Example 1

**[0044]** In the first example, the bitumen froth sample **405** was 75 grams of Syncrude bitumen froth (60 wt% bitumen, 30 wt% water and 10 wt% mineral matter). The bitumen froth **405** was added to 400 ml of 60/40 pentane/iso-pentane solvent and stirred with the stirrer **404** in the vessel **402**. This particular bitumen froth **405** was chosen because its composition is representative of produced bitumen froth **102** or **302**. The stirrer **404** was used to mix the contents and keep the solids suspended in solution. The bitumen solvent mixture **405** was fed by gravity to the particle size analyzer apparatus **406**. In this case, a JM Canty Microflow Particle Size system (Model # MIC-LG2K11B11GZ) was used. The sample **405** was fed to the flow cell **412** at approximately 150 ml/min. The gap in the flow cell **412** was set at an optimum width of 300 micrometers ( $\mu\text{m}$ ). Too large a gap did not provide enough light to resolve the particles while too small a gap restricted the flow of the particles. Images were taken by the image analyzer **410** and recorded by the computer system **408**.

**[0045]** FIG. 5 is an image of asphaltene-mineral aggregates obtained with the particle size analyzer apparatus **406** with no water addition to the bitumen-froth-solvent mixture **405**. The scale of the image **500** is shown on the image by a 100 micro-meter (micron or  $\mu\text{m}$ ) line **502**. As can be seen, numerous particles less than 100  $\mu\text{m}$  in size are observed.

#### Example 2

**[0046]** In a second test, the bitumen froth sample **405** was 75 grams of Syncrude bitumen froth (60 wt% bitumen, 30 wt% water and 10 wt% mineral matter). The bitumen froth **405** was added to 400 ml of 60/40 pentane/iso-pentane solvent and stirred with the stirrer **404** in the vessel **402**. The stirrer **404** was used to mix the contents and keep the solids suspended in solution for a few minutes. Then, about 50 grams of water was added to the bitumen froth-solvent mixture **405** while the stirrer **404** continued to mix the solution. The bitumen-solvent-water mixture was fed by gravity to the flow cell **412** at approximately 150

2008EM037

ml/min. The gap in the flow cell was set at an optimum width of 300  $\mu\text{m}$ . Images were taken by the image analyzer **410** and recorded by the computer system **408**.

**[0047]** FIGs. 6A-6B are images of asphaltene-mineral-water aggregates obtained after the addition of water to the bitumen-froth-solvent mixture **405**. In FIG. 6A, the scale of the image **600** is shown by a 100 micron line **602**. As shown, particles significantly greater than 100 microns are generated. In comparison to the image **500**, there appear to be more large particles. FIG. 6B shows a magnified image **610** of the particulates bounded with water droplets **612**. The image **610** is magnified to show more clearly the presence and location of water droplets **612**. The scale of the image **610** is shown by a 100 micron line **614**.

**[0048]** While the present invention may be susceptible to various modifications and alternative forms, the exemplary embodiments discussed above have been shown only by way of example. However, it should again be understood that the invention is not intended to be limited to the particular embodiments disclosed herein. Indeed, the present invention includes all alternatives, modifications, and equivalents falling within the true spirit and scope of the appended claims.

2008EM037

**CLAIMS**

What is claimed is:

1. A method of recovering hydrocarbons, comprising:
  - providing a bitumen-froth emulsion containing asphaltenes and mineral solids;
  - 5 adding a solvent to the bitumen-froth emulsion to induce a rate of settling of at least a portion of the asphaltenes and mineral solids from the bitumen-froth emulsion and generate a solvent bitumen-froth mixture; and
    - adding water droplets to the solvent bitumen-froth mixture to increase the rate of settling of the at least a portion of the asphaltenes and mineral solids.
- 10 2. The method of claim 1, wherein the solvent is a paraffinic solvent to form a paraffinic froth-treated (PFT) bitumen stream.
3. The method of claim 1, further comprising processing the solvent bitumen-froth mixture in at least a first separation vessel to form a processed solvent bitumen-froth mixture and a separation tailings stream.
- 15 4. The method of claim 3, further comprising processing the separation tailings stream in at least a second separation vessel.
5. The method of claim 3, wherein the water droplets are added to the solvent bitumen-froth mixture before the solvent bitumen-froth mixture is processed in the first separation vessel.
- 20 6. The method of claim 3, wherein the water droplets are added to the separation tailings stream before the separation tailings stream is added to the second separation vessel.
7. The method of claim 3, wherein the water droplets are added in one of the first separation vessel and the second separation vessel.
8. The method of claim 3, wherein the water is added above or below a feed injection
  - 25 point in the first or second separation vessel.
9. The method of any one of claims 3-8, wherein the water droplets are formed by a spray nozzle system.
10. The method of claim 9, wherein the water droplets are one of fresh river water, distilled water from a solvent recovery unit, recycled water, rain water, or aquifer water.
- 30 11. The method of claim 1, wherein the addition of the water droplets increases the rate of settling by a factor of greater than two.
12. The method of claim 1, wherein the addition of the water droplets increases the size of the asphaltenes from about 10 microns to at least about 1,000 microns.

2008EM037

13. The method of claim 1, wherein the water droplets are added in a concentration of from about 0.01 weight percent (wt%) relative to bitumen to about 10 wt% relative to bitumen.

14. The method of claim 1 further comprising: optimizing a variable selected from the group consisting of: water-to-bitumen ratio, water droplet size, temperature, solvent addition rate, location of water addition, mixing energy, and any combination thereof.

15. A system for recovering hydrocarbons, comprising:

a bitumen recovery plant configured to treat a froth-treated bitumen, the plant comprising:

10 a froth separation unit having a bitumen froth inlet and a diluted bitumen outlet; and

a water droplet production unit configured to add water droplets to the froth-treated bitumen.

16. The system of claim 15, wherein the water droplet production unit is configured to add water droplets to the froth-treated bitumen to at least one of the bitumen froth inlet and the froth separation unit.

17. The system of any one of claims 15-16, wherein the water droplets are added in a concentration of from about 0.01 weight percent (wt%) relative to bitumen to about 10 wt% relative to bitumen.

20 18. The system of any one of claims 15-16, wherein the water droplets are produced at a size of at least about 10 microns to about 1,000 microns.

19. The system of claim 15, further comprising a solvent addition unit configured to add solvent to the froth-treated bitumen, wherein the solvent addition is configured to provoke a rate of settling of asphaltenes and mineral solids from the froth-treated bitumen.

25 20. The system of claim 19, wherein the water addition is configured to increase the rate of settling of asphaltenes and mineral solids from the froth-treated bitumen.

21. The system of claim 20, wherein the increase in the rate of settling is by a factor of at least two.

22. The system of claim 15, comprising two froth separation units (FSU), wherein one of 30 the two FSU's receives a recycle stream from a solvent recovery unit.

Application number / numéro de demande: 2651155

Figures: 5, 6A, 6B

Pages: 4/5, 5/5

Unscannable item(s)  
received with this application

To inquire if you can order a copy of the unscannable items, please visit the  
CIPO WebSite at [HTTP://CIPO.GC.CA](http://CIPO.GC.CA)

Item(s) ne pouvant être balayés

Documents reçus avec cette demande ne pouvant être balayés.

Pour vous renseigner si vous pouvez commander une copie des items ne  
pouvant être balayés, veuillez visiter le site web de l'IPC au [HTTP://CIPO.GC.CA](http://CIPO.GC.CA)




FIG. 3




FIG. 4