



(86) Date de dépôt PCT/PCT Filing Date: 2000/02/08
(87) Date publication PCT/PCT Publication Date: 2000/08/17
(85) Entrée phase nationale/National Entry: 2001/07/19
(86) N° demande PCT/PCT Application No.: EP 00/00985
(87) N° publication PCT/PCT Publication No.: WO 00/47316
(30) Priorité/Priority: 1999/02/08 (90346) LU

(51) Cl.Int.⁷/Int.Cl.⁷ B01J 2/06, B01D 21/00, C21B 3/08


(71) Demandeur/Applicant:
PAUL WURTH S.A., LU

(72) Inventeurs/Inventors:
GOFFIN, ROBERT G., CA;
FABER, ERNEST, LU;
ULVELING, LEON, LU

(74) Agent: GOWLING LAFLEUR HENDERSON LLP

(54) Titre : INSTALLATION POUR LA GRANULATION AQUEUSE

(54) Title: INSTALLATION FOR AQUEOUS GRANULATION



(57) Abrégé/Abstract:

An installation for aqueous granulation of a product, comprising a granulation basin (10) fitted for the injection of granulation water and a sedimentation basin (12) that is separate from the granulation basin (10), in addition to a distributor (26) for the introduction of a mixture of water/granules from the granulation tank (10) into the sedimentation basin (12). The sedimentation basin (12) consists of several concentration vats (30) that are suspended in a support structure. The concentration vats (30) are funnel-shaped and lead into an exit line (32) that is provided with an obturation element (33). The sedimentation basin (12) also has a peripheral wall (34) that is provided with at least one overflow outlet (36).





DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITE DE COOPERATION EN MATIÈRE DE BREVETS (PCT)

(51) Classification internationale des brevets ⁷ : B01J 2/06, C21B 3/08, B01D 21/00	A1	(11) Numéro de publication internationale: WO 00/47316 (43) Date de publication internationale: 17 août 2000 (17.08.00)
--	-----------	---

(21) Numéro de la demande internationale: PCT/EP00/00985

(22) Date de dépôt international: 8 février 2000 (08.02.00)

(30) Données relatives à la priorité:
90346 8 février 1999 (08.02.99) LU

(71) Déposant (pour tous les Etats désignés sauf US): PAUL WURTH S.A. [LU/LU]; 32, rue d'Alsace, L-1122 Luxembourg (LU).

(72) Inventeurs; et

(75) Inventeurs/Déposants (US seulement): ULVELING, Léon [LU/LU]; 30, rue Dr. Jos Peffer, L-2319 Luxembourg-Howald (LU). FABER, Ernest [LU/LU]; 24, rue Hicht, L-6212 Consdorf (LU). GOFFIN, Robert, G. [CA/CA]; 212 Caithness East, P.O. Box 482, Caledonia, Ontario N0A 1A0 (CA).

(74) Mandataires: SCHMITT, Armand etc.; Office Ernest T. Freylinger S.A., B.P. 48, L-8001 Strassen (LU).

(81) Etats désignés: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, brevet ARIPO (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), brevet eurasién (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), brevet européen (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), brevet OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Publiée


Avec rapport de recherche internationale.

(54) Title: INSTALLATION FOR AQUEOUS GRANULATION

(54) Titre: INSTALLATION POUR LA GRANULATION AQUEUSE

(57) Abstract

An installation for aqueous granulation of a product, comprising a granulation basin (10) fitted for the injection of granulation water and a sedimentation basin (12) that is separate from the granulation basin (10), in addition to a distributor (26) for the introduction of a mixture of water/granules from the granulation tank (10) into the sedimentation basin (12). The sedimentation basin (12) consists of several concentration vats (30) that are suspended in a support structure. The concentration vats (30) are funnel-shaped and lead into an exit line (32) that is provided with an obturation element (33). The sedimentation basin (12) also has a peripheral wall (34) that is provided with at least one overflow outlet (36).



(57) Abrégé

Une installation pour la granulation aqueuse d'un produit comprend un bassin de granulation (10) équipé pour l'injection d'eau de granulation, un bassin de décantation (12) séparé du bassin de granulation (10) et un distributeur (26) pour l'introduction du mélange eau/granules du bassin de granulation (10) dans le bassin de décantation (12). Le bassin de décantation (12) se compose de plusieurs bacs de concentration (30) suspendus dans une structure de support. Les bacs de concentrations (30) ont une forme d'entonnoir débouchant dans une conduite de sortie (32) équipée d'un organe d'obturation (33). Le bassin de décantation (12) possède également une paroi (34) périphérique, munie d'au moins une ouverture de débordement (36).

UNIQUEMENT A TITRE D'INFORMATION

Codes utilisés pour identifier les Etats parties au PCT, sur les pages de couverture des brochures publiant des demandes internationales en vertu du PCT.

AL	Albanie	ES	Espagne	LS	Lesotho	SI	Slovénie
AM	Arménie	FI	Finlande	LT	Lituanie	SK	Slovaquie
AT	Autriche	FR	France	LU	Luxembourg	SN	Sénégal
AU	Australie	GA	Gabon	LV	Lettonie	SZ	Swaziland
AZ	Azerbaïdjan	GB	Royaume-Uni	MC	Monaco	TD	Tchad
BA	Bosnie-Herzégovine	GE	Géorgie	MD	République de Moldova	TG	Togo
BB	Barbade	GH	Ghana	MG	Madagascar	TJ	Tadjikistan
BE	Belgique	GN	Guinée	MK	Ex-République yougoslave de Macédoine	TM	Turkménistan
BF	Burkina Faso	GR	Grèce	ML	Mali	TR	Turquie
BG	Bulgarie	HU	Hongrie	MN	Mongolie	TT	Trinité-et-Tobago
BJ	Bénin	IE	Irlande	MR	Mauritanie	UA	Ukraine
BR	Brésil	IL	Israël	MW	Malawi	UG	Ouganda
BY	Bélarus	IS	Islande	MX	Mexique	US	Etats-Unis d'Amérique
CA	Canada	IT	Italie	NE	Niger	UZ	Ouzbékistan
CF	République centrafricaine	JP	Japon	NL	Pays-Bas	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norvège	YU	Yougoslavie
CH	Suisse	KG	Kirghizistan	NZ	Nouvelle-Zélande	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	République populaire démocratique de Corée	PL	Pologne		
CM	Cameroun	KR	République de Corée	PT	Portugal		
CN	Chine	KZ	Kazakhstan	RO	Roumanie		
CU	Cuba	LC	Sainte-Lucie	RU	Fédération de Russie		
CZ	République tchèque	LI	Liechtenstein	SD	Soudan		
DE	Allemagne	LK	Sri Lanka	SE	Suède		
DK	Danemark	LR	Libéria	SG	Singapour		
EE	Estonie						

AQUEOUS GRANULATION PLANT

This invention relates to an aqueous granulation plant.

5 In aqueous granulation, the product for granulation (for example, molten slag, a molten alloy, copper matte) is placed in a powerful flow of water. This flow of water granulates, solidifies and cools the product. The granules are then removed from the granulation water.

10 Such aqueous granulation plants comprise a granulation tank fitted for injection of granulation water and also a device for removing the granules from the granulation water. A conventional granule removal device comprises a sedimentation tank, separate from the granulation tank, in which the granules settle.

15 Patent application DE-A-3207215 describes a slag granulation plant without a sedimentation tank. A distribution tank distributes the granulated slag between two storage hoppers connected in parallel.

20 Patent application DE-A-3503035 describes a sedimentation unit for glass or stone dust in suspension in a cooling fluid from glass or stone ware machining tools. This is a compact single-piece sedimentation unit into which are integrated a number of sedimentation tanks of decreasing size, arranged in series.

25 Patent application US-A-4,242,142 describes a blast furnace granulate processing plant in which the largest granules settle in a classifier 10 and the fines settle in a sedimentation tank 25 connected in series with the classifier 10. From the sedimentation tank 25 the water overflows into a cooling tank and finally into a pumping tank.

The object of the present invention is the design of a simple granulation plant which facilitates granule removal. According to the invention this aim is attained by an aqueous granulation plant according to claim 1.

5 The aqueous granulation plant according to the invention comprises, in a recognised manner, a granulation tank fitted for injection of granulation water in order to granulate the molten product, a sedimentation tank separate from the granulation tank, in which the granulated product settles in granule form and a distributor to transfer the water/granule mixture from the granulation tank into the sedimentation tank. According to an important aspect of this invention, the
10 sedimentation tank comprises a number of concentration tanks. It will be seen that when the water is fed into the sedimentation tank by the distributor, it is distributed among the various concentration tanks in which the granules settle according to their specific weight. Concentration of the granules in the concentration tanks according to their specific weight makes removal easier. Its
15 modular design also enables the configuration of the sedimentation tank to be optimised for the product to be granulated.

In a preferred embodiment the sedimentation tank comprises a supporting structure and concentration tanks suspended from the supporting structure.

20 The concentration tanks are advantageously in the shape of a hopper with a horizontal top edge, allowing them to be suspended from the supporting structure. These edges are the only contact area between the supporting structure and the concentration tanks.

25 Two adjoining concentration tanks are advantageously arranged so that their top edges are adjacent. The water can then flow from one tank to the other over these adjacent top edges.

The sedimentation tank advantageously has a peripheral wall that rises above the top edges of the concentration tanks. This peripheral wall, however,

comprises one or more overflow openings to allow the clarified granulation water to flow out of the sedimentation tank.

Partitions rising above the top edges can be erected between two concentration tanks. By means of such partitions, different paths can be defined for the water/granule mixture in the sedimentation tank. For example, a longer path can be arranged to favour settlement of fines.

The hopper-shaped concentration tanks advantageously discharge into a delivery pipe fitted with a sealing device. This enables either the material flow to be halted or the concentration tank to be emptied.

A water removal device may be fitted upstream of the sealing device. This water removal device comprises for example a filter sleeve separating a central duct from an annular water collecting chamber. The granulation water can thus be filtered by the filter sleeve and escape via the water collecting chamber, while the granules pass through the central duct after the sealing device opens.

In a first embodiment, the concentration tanks nearest to the distributor are connected to a draining drum. The granules that gather in these concentration tanks are discharged to the draining drum for separation of the granules from the granulation water.

The concentration tanks farthest from the distributor can then be connected to a hydrocyclone in order to extract the fines from the granulation water.

In a second embodiment, at least one conveyor is positioned underneath the concentration tanks to collect the said granules that gather in the said concentration tanks when the sealing devices are open, at least one said conveyor being for example fitted with a perforated belt to allow the granulation water to drain away.

Further special features and characteristics of the invention will become clear from the detailed description of some advantageous embodiments which follows, by way of illustration, with reference to the drawings attached. These show:

- 5 Fig. 1: synoptic illustration of an aqueous granulation plant with a
 draining drum and hydrocyclone;
- Fig. 2: sectional view of a concentration tank;
- Fig. 3: view of a supporting structure;
- Fig. 4: sectional view of a beam supporting two concentration tanks;
- 10 Fig. 5: sectional view of a beam sideways on;
- Fig. 6: synoptic illustration of an aqueous granulation plant with
 conveyor;
- Figs. 7 to 10: views of different sedimentation tanks.

- 15 In the drawings the same reference numbers denote identical or similar components.

Figure 1 shows a plant for aqueous granulation of slag. This principally comprises a granulation tank 10 and a sedimentation tank 12 which is separate from the granulation tank 10.

- 20 The granulation tank 10 is an oblong-shaped tank having a front wall 14, a back wall 16 and two side walls 18 and 20. The bottom of the granulation tank 10 is stepped with sloping steps, the lowest step being in contact with the back wall 16. Slag is poured into the granulation tank 10 through a hot channel 22 located beside the front wall 14. The granulation tank 10 is fitted with means
- 25 of injecting granulation water (not shown). The granulation water is injected at a rate of approximately 10 m/s. The quantity of water required is around 15 to

25 kg per kg of slag poured. In the granulation tank 10 the molten slag is carried along by the granulation water and is then granulated and solidified. The more turbulent the flow of water in the granulation tank 10, the less the risk of explosion due to release of hydrogen and superheated steam.

5 A pipe 24 carries the water/granule mixture from the granulation tank 10 to a distributor 26 which is arranged at one end 28 of the sedimentation tank 12. In the configuration shown in figure 1, this sedimentation tank 12 comprises two rows of four concentration tanks 30. These concentration tanks 30 are identical in dimensions and take the form of square-section hoppers. They discharge
10 into a delivery pipe 32 fitted with a sealing device 33. A peripheral wall 34 rises above the top edges of the concentration tanks 30 to hold the liquid inside the sedimentation tank 12. Two overflow outlets 36 are provided in the shorter side farthest from the granulation tank 10.

 Let us assume a water/granule mixture comprising granules of different
15 sizes and densities, therefore distinguished by different weights. On clarifying such a mixture, the heaviest granules have the fastest settling rate and the lightest granules (fines, for example) have a very slow settling rate, remaining in suspension in the granulation water for a long time.

 The water/granule mixture is fed in via the distributor 26 and the granules
20 therefore have a horizontal rate due to the flow current in the sedimentation tank 12 as well as a vertical settling rate. The composition of these two rates causes the granules to be distributed in the concentration tanks 30. The granules with the fastest settling rate, in other words the heaviest, settle in the concentration tanks 30 nearest to the distributor 26. The lightest granules, on
25 the other hand, settle in the concentration tanks 30 farthest from the distributor 26. The fines settle in the last of the concentration tanks. The clarified granulation water flows through the overflow holes 36 and is sent to a collecting tank 38. The content of the concentration tanks 30 in fact depends on the distance between them and the distributor 26. Likewise, the concentration
30 tanks 30 that are the same distance from the distributor 26 will contain granules of similar particle size.

At this point it is interesting to take a closer look at the characteristics of a concentration tank 30. Figure 2 shows a sectional view of a concentration tank in the form of a square-section hopper through which the material flows into a delivery pipe 32. It will be seen that the concentration tank has horizontal top edges 40 allowing it to rest on a supporting structure (see fig. 3). The delivery pipe 32 is fitted with a sealing device 33 which halts the passage of material in the delivery pipe 32. Upstream of this sealing device 33 the delivery pipe 32 is fitted with a water extraction device 42, equipped with a filter sleeve 44 and an annular water collecting chamber 46. The granulation water is filtered through the filter sleeve 44, which holds back the granules, before being discharged via the water collecting chamber 46. The granules can then flow through the delivery pipe 32 when the sealing device 33 is open. It will also be noted that a water injection device 48 is also included. This is a pipe discharging in two places in one of the walls of the concentration tank 30. It sometimes happens that granules which have gathered do not flow through the delivery pipe 32 when the sealing device 33 is open. A movement has to be initiated in the heap of granules to set the flow in motion. This is the purpose of the water injection device 48, which gets the heap of granules moving by injecting water into the concentration tank 30 in the direction of the arrow 50 to enable the concentration tank 30 to be emptied.

Figure 3 shows a preferred embodiment of a supporting structure. The rows are delimited by three horizontal beams 52, 54 and 56, the same distance apart, supported by pillars 58. The concentration tanks 30' and 30" (similar to the concentration tank 30 in fig. 3) can slide within a row defined by 2 beams (52, 54; 54, 56). This is an advantage of such a supporting structure, which readily allows the size of the sedimentation tank 12 to be altered. The presence of the peripheral wall 34 may also be noted.

Figure 4 shows a preferred method of fastening the two concentration tanks 30' and 30" in fig. 3. The top flange of the beam 54 is covered by a thick rubber cushion 60. The top edges 40 of the two concentration tanks 30' and 30" rest on the cushion 60. Care has been taken to allow a space between the

adjacent top edges 40, which is filled with rubber. Holes 62, 64 serve to fasten the top edges 40 of the concentration tanks 30' and 30" firmly to the flange of the beam 54 by means of screws and bolts (not shown).

Figure 5 shows a preferred method of fastening a concentration tank 30 to the exterior beam 52. One top edge 40 of a concentration tank 30 rests virtually on the whole surface of the top flange of the beam 52. A rubber cushion 66 is inserted between the web of the beam 52 and the top edge 40. Two holes 68, 70 are made to enable the concentration tank 30 to be fastened to the beam 52. The peripheral wall 34 is welded perpendicular to the top flange of the beam 52. Care has been taken to allow a space between the peripheral wall 34 and the top edge 40. This space is filled with rubber.

In figure 1, the delivery pipes 32 are not fitted with water extraction devices 42, but only with sealing devices 33. Downstream of these sealing devices 33, the first four concentration tanks 30, in other words those arranged nearest to the distributor 26, are connected to a draining drum 72. The granulation water recovered from the draining drum 72 is sent to the collecting tank 38; the drained granules are sent to a pile 74. The last four concentration tanks 30 are connected to a hydrocyclone 76, to separate the finest granules from the granulation water. The water is sent to the collecting tank 38 and the granules are sent to the pile 74.

Another possibility for draining the concentration tanks is illustrated in figure 6. A filtering belt conveyor 80, 82 has been arranged underneath each row of concentration tanks 30. A water extraction device 42 with a filter sleeve 44 and water collecting chamber 46 is installed upstream of each sealing device 33, according to figure 2. The granulation water in the concentration tanks 30 is removed by the water extraction device 42. The sealing device 33 is then opened to allow the granules to drop on to the conveyor 80, 82. The granules removed are sent directly to the pile 74. It will be noted that the granulation water flowing through the overflow holes 36 or filtered through the filter sleeves 44 is collected in the collecting tank 38.

Figures 7, 8 and 9 show three embodiments of sedimentation tanks 12 which can readily be implemented in a supporting structure that has 3 beams, as shown in figure 3.

Figure 7 shows a sedimentation tank 12 similar to that in figures 1 and 6. The peripheral wall 34 has two overflow holes 36. The water/granule mixture is fed in via a distributor 26 across the whole width of the sedimentation tank 12 at one end, and the overflow holes 36 are located at the opposite end. The length of the path followed by the mixture in the sedimentation tank 12 is the same as the length of the tank.

In figure 8, the distributor 26 and the overflow hole 36 are diagonally opposite each other. Partitions 84 have been arranged to define a zigzag path through the sedimentation tank 12. The length of the path followed by the mixture is twice the length of the sedimentation tank 12.

In figure 9, the distributor 26 and the overflow hole 36 are in the upper part of the sedimentation tank 12. The partitions 84 are arranged so as to define a U-shaped path through the sedimentation tank 12. The distance covered by the mixture is likewise twice the length of the sedimentation tank 12.

It can thus be seen that by means of the partitions 84 the distance travelled by the mixture in the sedimentation tank 12 can be increased, so facilitating the settling of small granules.

Obviously, the number of concentration tanks 30, the number of rows and the number of partitions 84 can be altered to obtain various configurations. It will thus be understood that the modular design of the sedimentation tank 12 enables the path travelled by the water/granule mixture to be optimised according to the type of granules. The granules settle in the concentration tanks 30 according to their specific weight and are thus directly sorted during sedimentation, thereby saving on a subsequent sorting stage. Moreover, the use of identical concentration tanks 30, which can be slotted anywhere into the supporting structure, allows the configuration of the sedimentation tank 12 to be

changed easily and quickly. It is also to be noted that the latter can contain concentration tanks of different shapes. However, in order to preserve the modular properties of the sedimentation tank, it is preferable to use removable concentration tanks of standardised shape, which slot into an appropriate supporting structure. The concentration tanks will therefore preferably have simple exterior shapes (square or rectangular), allowing them to be fitted into the supporting structure.

It is even possible to operate with a sedimentation tank divided into two autonomous sedimentation units. This is the configuration shown in figure 10. The tank comprises two rows of two concentration tanks 30 separated by a central partition 84. There is a peripheral wall 34 and each row has an overflow hole 36. By using a distributor 26 with a slewable duct, the water/granule mixture can be fed selectively into either row.

It will be noted that it is preferable to empty the concentration tanks 30 in sequence. This procedure has the advantage of enabling any concentration tanks 30 that are blocked to be located. The concentration tanks 30 nearest to the distributor 26 will generally have to be emptied most often.

CLAIMS

1. Plant for aqueous granulation of a product, comprising:

5 a granulation tank (10) fitted for injection of granulation water in order to granulate the product;

a sedimentation tank (12) separate from the granulation tank (10), in which the granulated product settles in the form of granules;

a distributor (26) to transfer the water/granule mixture from the granulation tank (10) into the sedimentation tank (12);

10 **characterised in that**

said sedimentation tank (12) comprises a supporting structure (52-58) and a number of separate concentration tanks (30) which can be arranged in modular fashion within said supporting structure (52-58) in order to define a flow path through a number of concentration tanks (30)
15 for the water/granule mixture delivered by said distributor (36).
2. Granulation plant according to claim 1, characterised in that said concentration tanks (30) are in the shape of a hopper with a horizontal top edge (40), allowing them to be suspended from the supporting structure.
- 20 3. Granulation plant according to claim 2, characterised in that two adjoining concentration tanks (30) have their horizontal top edges (40) adjacent, so that the water/granule mixture can flow over those top edges from one concentration tank (30) to the other.
- 25 4. Granulation plant according to claim 3, characterised in that the sedimentation tank (12) comprises a peripheral wall (34) that rises above


the top edges (40) of the concentration tanks, said wall (34) comprising at least one overflow hole (36).

- 5 5. Granulation plant according to claim 4, characterised by a partition (84) rising above the top edges (40) of two adjacent concentration tanks (30) so as to define a flow path.
6. Granulation plant according to any one of claims 1 to 5, characterised in that the concentration tanks (30) are in the form of a hopper, the bottom end of which discharges into a delivery pipe (32) fitted with a sealing device (33).
- 10 7. Granulation plant according to claim 6, characterised by a water extraction device (42) fitted upstream of said sealing device (33).
8. Granulation plant according to claim 7, characterised in that said water extraction device (42) comprises a filter sleeve (44) separating a central duct from an annular water collecting chamber (46).
- 15 9. Granulation plant according to any one of the previous claims, characterised in that the distributor (26) feeding in the water/granule mixture is arranged at one end of the sedimentation tank (12).
- 20 10. Granulation plant according to any one of the previous claims, further characterised by a draining drum (72), the concentration tanks (30) nearest to said distributor (26) being connected to said draining drum (72), so that the granules that gather in these concentration tanks (30) can be discharged to said draining drum (72).
- 25 11. Granulation plant according to any one of the previous claims, further characterised by a hydrocyclone (76), the concentration tanks (30) farthest from said distributor (26) being connected to said hydrocyclone (76) so that the content of these concentration tanks (30) can be discharged to said hydrocyclone (76).

12. Granulation plant according to any one of claims 1 to 8, characterised by at least one conveyor (80, 82) arranged underneath the concentration tanks (30).
- 5 13. Granulation plant according to any one of claims 4 to 12, characterised in that said distributor (26) feeds in the water across the whole width of one side of the sedimentation tank (12), and in that the overflow hole (36) is located across the whole width of the opposite side.
- 10 14. Granulation plant according to any one of claims 5 to 12, characterised in that said sedimentation tank (12) has at least two rows of concentration tanks (30), partitions (84) being arranged so as to define a flow path through the sedimentation tank (12).
- 15 15. Granulation plant according to any one of claims 5 to 12, characterised in that said sedimentation tank (12) comprises at least two rows of concentration tanks (30), each row being separated from the adjoining row by a partition (84), so as to define separate flow paths within said sedimentation tank (12), said distributor (26) comprising means of selectively feeding the water/granule mixture into either row.

1 / 5

Fig. 1



2 / 5




Fig. 2




Fig. 3

FEUILLE DE REMPLACEMENT (REGLE 26)

3 / 5




Fig. 4





Fig. 5

4 / 5

Fig. 6



5 / 5




Fig. 7




Fig. 8




Fig. 9




Fig. 10

FEUILLE DE REMPLACEMENT (REGLE 26)

