

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2019384229 B2**

(54) Title
Direct current electric appliance control method and direct current electric appliance

(51) International Patent Classification(s)
G01R 31/00 (2006.01)

(21) Application No: **2019384229**

(22) Date of Filing: **2019.07.22**

(87) WIPO No: **WO20/103481**

(30) Priority Data

(31) Number
201811378033.4

(32) Date
2018.11.19

(33) Country
CN

(43) Publication Date: **2020.05.28**

(44) Accepted Journal Date: **2022.06.09**

(71) Applicant(s)
Gree Electric Appliances, Inc., of Zhuhai

(72) Inventor(s)
WANG, Jing;JIANG, Shiyong;LIU, Keqin;WEN, Wu;ZHANG, Xuefen;REN, Peng

(74) Agent / Attorney
Madderns Pty Ltd, GPO Box 2752, Adelaide, SA, 5001, AU

(56) Related Art
US 2013/0007473 A1
US 2015/0333553 A1

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局

(43) 国际公布日
2020 年 5 月 28 日 (28.05.2020)



(10) 国际公布号
WO 2020/103481 A1

(51) 国际专利分类号:
G01R 31/00 (2006.01)

(21) 国际申请号: PCT/CN2019/097052

(22) 国际申请日: 2019 年 7 月 22 日 (22.07.2019)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:
201811378033.4 2018 年 11 月 19 日 (19.11.2018) CN

(71) 申请人: 珠海格力电器股份有限公司 (GREE ELECTRIC APPLIANCES, INC., OF ZHUHAI) [CN/CN]; 中国广东省珠海市前山金鸡西路, Guangdong 519070 (CN)。

(72) 发明人: 王京 (WANG, Jing); 中国广东省珠海市前山金鸡西路, Guangdong 519070 (CN)。 蒋世用 (JIANG, Shiyong); 中国广东省珠海市前山金鸡西路, Guangdong 519070 (CN)。 刘克勤 (LIU, Keqin); 中国广东省珠海市前山金鸡西路, Guangdong 519070 (CN)。 文武 (WEN, Wu); 中国广东省珠海市前山金鸡西路, Guangdong 519070 (CN)。 张雪芬 (ZHANG, Xuefen); 中国广东省珠海市前山金鸡西路, Guangdong 519070 (CN)。 任鹏 (REN, Peng); 中国广东省珠海市前山金鸡西路, Guangdong 519070 (CN)。

(74) 代理人: 北京康信知识产权代理有限公司 (KANGXIN PARTNERS, P.C.); 中国北京市海淀区知春路甲 48 号盈都大厦 A 座 16 层, Beijing 100098 (CN)。

(54) Title: DIRECT CURRENT ELECTRIC APPLIANCE CONTROL METHOD AND DIRECT CURRENT ELECTRIC APPLIANCE

(54) 发明名称: 直流电器控制方法及直流电器




图 1

- S102 Acquire input parameters of a power source of a direct current electric appliance
- S104 Identify the type of the power source according to the input parameters
- S106 Determine a direct current electric appliance operation mode corresponding to the type of the power source, and control the operation of the direct current electric appliance according to the operation mode

(57) Abstract: A direct current electric appliance control method and a direct current electric appliance. Said method comprises: acquiring input parameters of a power source of a direct current electric appliance (S102); identifying the type of the power source according to the input parameters (S104); and determining a direct current electric appliance operation mode corresponding to the type of the power source, and controlling the operation of the direct current electric appliance according to the operation mode (S106). The present invention improves the universality and operation performance of a direct current electric appliance.

(81) 指定国 (除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW。

(84) 指定国 (除另有指明, 要求每一种可提供的地区保护): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), 欧亚 (AM, AZ, BY, KG, KZ, RU, TJ, TM), 欧洲 (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG)。

本国际公布:

— 包括国际检索报告 (条约第21条(3))。

(57) 摘要: 一种直流电器控制方法及直流电器, 该方法包括: 获取直流电器的电源的输入参数 (S102); 根据输入参数识别电源的类型 (S104); 确定电源的类型对应的直流电器的工作模式, 按照工作模式控制直流电器的工作 (S106); 提高了直流电器的通用性和运行性能。

DIRECT CURRENT ELECTRIC APPLIANCE CONTROL METHOD AND DIRECT CURRENT ELECTRIC APPLIANCE

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to Chinese Patent Application No. 201811378033.4, filed on November 19, 2018, entitled “CONTROL METHOD FOR DIRECT CURRENT ELECTRICAL DEVICE AND DIRECT CURRENT ELECTRICAL DEVICE”, the entire content of which is incorporated herein in its entirety.

TECHNICAL FIELD

[0002] The present application relates to a technical field of direct current electrical device, and in particular, relates to a control method for a direct current electrical device, and a direct current electrical device.

BACKGROUND

[0003] At present, high-voltage direct current transmission technology is being closely implemented. Direct current (DC) distribution networks and DC electrical devices are also current research focus, and represent the development direction of DC transmission, DC distribution, and DC power consumption.

[0004] For DC power device, the progress of research, development and promotion of the DC electrical devices is also very fast. Currently, many DC electrical devices have appeared in the market. However, the existing DC electrical devices are mainly concentrated in some special application conditions, such as those powered by a single battery, or directly connected to a DC power supply line of some systems, or directly connected to a photovoltaic power generation system. DC electrical devices like these also operate in specific conditions. If the DC electrical devices are directly changed to operate in other workplaces, they will not operate normally, or operating efficiency thereof will be greatly reduced, which is a great disadvantage for the universality of the DC electrical devices.

[0005] In view of the problems that available power supplies for the DC electrical devices in related art are fixed, and that the DC electrical devices have low universality, no effective solutions have been proposed yet.

SUMMARY

[0006] The present invention provides a control method for a direct current electrical device and a direct current electrical device to address the problems that available power supplies for the direct current electrical device in related art are fixed, and that the DC electrical device has low universality.

[0007] In order to solve the above technical problems, according to an aspect of the embodiments of the present application, a control method for a direct current electrical device is provided, and the method includes: obtaining input parameters of a power supply of the direct current electrical device, identifying a type of the power supply according to the input parameters, and determining an operation mode of the direct current electrical device corresponding to the type of the power supply, and controlling an operation of the direct current electrical device according to the operation mode.

[0008] Optionally, the input parameters of the power supply include at least an input voltage and an input power. The identifying the type of the power supply according to the input parameters includes: adjusting the input voltage, detecting whether the input power changes, and determining the type of the power supply according to whether the input power changes.

[0009] Optionally, the type of the power supply includes an adjustable power supply and a non-adjustable power supply. The adjustable power supply is a photovoltaic power. The non-adjustable power supply is a battery or a DC busbar.

[0010] Optionally, the determining the type of the power supply according to whether the input power changes includes: when the input power changes, determining the type of the power supply as the adjustable power supply, and when the input power remains unchanged, determining the type of the power supply as the non-adjustable power supply.

[0011] Optionally, the operation mode includes an adjustable mode and a fixed mode.

[0012] Optionally, the determining the operation mode of the direct current electrical device corresponding to the type of the power supply includes: when the type of the power supply is the adjustable power supply, determining the operation mode as the adjustable mode, and when the type of the power supply is the non-adjustable power supply, determining the operation mode as the fixed mode.

[0013] Optionally, the controlling the operation of the direct current electrical device according to the operation mode includes: when the operation mode is the adjustable mode, detecting the input parameters of the power supply in real time, determining real-time operating parameters of the direct current electrical device according to the input parameters, and controlling the operation of

the direct current electrical device according to the real-time operating parameters, when the operation mode is the fixed mode, determining the operating parameters of the direct current electrical device as common operating parameters of the direct current electrical device according to the input parameters of the power supply, and controlling the operation of the direct current electrical device according to the common operating parameters.

[0014] According to another aspect of the embodiments of the present invention, a direct current electrical device is provided, and includes: an energy source characteristic identification module configured to obtain input parameters of a power supply of the direct current electrical device, and identify a type of the power supply according to the input parameters, and an operation mode configuration module configured to determine an operation mode of the direct current electrical device corresponding to the type of the power supply, and control an operation of the direct current electrical device according to the operation mode.

[0015] Optionally, the direct current electrical device further includes a direct current interface configured to receive an external direct current power supply, and a direct current electrical device body configured to realize kinetic energy of the direct current electrical device.

[0016] Optionally, the input parameters of the power supply include at least an input voltage and an input power. The energy source characteristic identification module includes: an adjusting unit configured to adjust the input voltage, a detecting unit configured to detect whether the input power changes, and a determining unit configured to determine the type of the power supply according to whether the input power changes.

[0017] Optionally, the type of the power supply includes an adjustable power supply and a non-adjustable power supply. The operation mode configuration module includes: a first operation mode determining unit configured to determine the operation mode as an adjustable mode when the type of the power supply is the adjustable power supply; a second operation mode determining unit configured to determine the operation mode as a fixed mode when the type of the power supply is the non-adjustable power supply; a first controlling unit configured to, when the operation mode is the adjustable mode, detect the input parameters of the power supply in real time, determine real-time operating parameters of the direct current electrical device according to the input parameters, and control the operation of the direct current electrical device according to the real-time operating parameters; and a second controlling unit configured to, when the operation mode is the fixed mode, determine operating parameters of the direct current electrical device as common operating parameters of the direct current electrical device according to the input parameters of the power supply, and control the operation of the direct current electrical device

according to the common operating parameters.

[0018] According to yet another aspect of the embodiments of the present invention, a computer device is provided, and includes a memory, a processor, and computer programs stored in the memory and executed by the processor. The programs, when executed by the processor, cause the processor to perform the control method for the direct current electrical device described above.

[0019] According to yet another aspect of the embodiments of the present invention, a storage medium containing computer executable instructions is provided. The computer executable instructions, when executed by a computer processor, cause the computer processor to perform the control method for the direct current electrical device as described above.

[0020] In the present application, the input parameters of the power supply of the DC electrical device are obtained, the type of the power supply is identified according to the input parameters, and the operation mode of the DC electrical device corresponding to the type of the power supply is determined, and the operation of the DC electrical device is controlled according to the operation mode. By means of such a control method, the universality of the DC electrical device can be greatly improved. In a condition whether the DC voltage is adjustable or non-adjustable, the DC electrical device can perform the identification, and the operation mode is automatically configured to achieve the optimal operating state.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] FIG. 1 is an optional flowchart of a control method for a direct current electrical device according to an embodiment of the present invention;

[0022] FIG. 2 is another optional flowchart of a control method for the direct current electrical device according to an embodiment of the present invention; and

[0023] FIG. 3 is an optional block diagram of the direct current electrical device according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0024] Exemplary embodiments will be described in detail herein, and examples thereof are shown in the accompanying drawings. When the following description refers to the accompanying drawings, unless otherwise indicated, identical reference signs in different drawings represent the same or similar elements. The embodiments described in the exemplary embodiments below do not represent all implementations consistent with the present invention. On the contrary, they are only examples of devices and methods consistent with some aspects of the present invention described in

detail in the appended claims.

[0025] First Embodiment

[0026] In a preferred first embodiment of the present invention, a control method for a direct current (DC) electrical device is provided. The control method can be directly applied to various DC electrical devices or other devices with partial functions of the DC electrical devices. In specific implementation, the method can be implemented by installing software or an APP on the DC electrical device or other devices, or writing corresponding programs into a controller. Specifically, FIG. 1 shows an optional flowchart of the method. As shown in FIG. 1, the method includes the following steps S102 to S106.

[0027] S102: Obtaining input parameters of a power supply of a DC electrical device;

[0028] S104: Identifying a type of the power supply according to the input parameters; and

[0029] S106: Determining an operation mode of the DC electrical device corresponding to the type of the power supply, and controlling an operation of the DC electrical device according to the operation mode.

[0030] In the foregoing embodiment, the input parameters of the power supply of the DC electrical device are obtained, the type of the power supply is identified according to the input parameters, and the operation mode of the DC electrical device corresponding to the type of the power supply is determined, and the operation of the DC electrical device is controlled according to the operation mode. By means of such a control method, the universality of the DC electrical device can be greatly improved. In a condition whether the DC voltage is adjustable or non-adjustable, the DC electrical device can perform the identification, and the operation mode is automatically configured to achieve the optimal operating state.

[0031] In a preferred embodiment of the present invention, the input parameters of the power supply include at least an input voltage and an input power. The identifying the type of the power supply according to the input parameters includes adjusting the input voltage, detecting whether the input power changes, and determining the type of the power supply according to whether the input power changes.

[0032] The DC electrical device is currently widely used in a new energy field and other DC power supply fields. In different application conditions, different DC power supplies have different output characteristics. For example, power-voltage (P-V) output characteristics of the photovoltaic panel have a characteristic curve low at two ends and high in the middle. The output power has a smaller output when the voltage is smaller. As the voltage increases, the output power gradually increases, and the output power reaches the maximum when the voltage reaches a certain value,

then, as the voltage continues to increase, the output power decreases instead. This is a unique output curve of the photovoltaic panel. The output characteristic curve of an energy storage battery or a DC busbar is represented by a stable straight line. Along with a gradual release of energy, the voltage of the battery slowly decreases. The output voltage of the battery is only related to its own characteristics and has no relation with a load. Therefore, if the DC electrical device cannot identify a type and output characteristics of the energy source and cannot configure the operation mode according to different types of the energy source, it is difficult for the DC electrical device to operate in the most efficient state.

[0033] It is known from the above analysis that the input parameters of the DC electrical device are divided into an adjustable type and a non-adjustable type. An adjustable power supply is a photovoltaic power. A non-adjustable power supply is a battery or a DC busbar.

[0034] According to the characteristics of the input parameters of the power supply, the power of the adjustable power supply changes as the voltage changes, while the power of the non-adjustable power supply does not change as the voltage changes. Therefore, the determining the type of the power supply according to whether the input power changes includes: when the input power changes, determining the type of the power supply as the adjustable power supply; and when the input power remains unchanged, determining the type of the power supply as the non-adjustable power supply.

[0035] After identifying the type of the power supply, the operation modes of the DC electrical device corresponding to different types of power supply are determined, and the operation modes include an adjustable mode and a fixed mode. When the type of the power supply is the adjustable power supply, the operation mode is determined as the adjustable mode. When the type of the power supply is the non-adjustable power supply, the operation mode is determined as the fixed mode.

[0036] When the operation mode is the adjustable mode, the input parameters of the power supply are detected in real time. Real-time operating parameters of the DC electrical device are determined according to the input parameters. The operation of the DC electrical device is controlled according to the real-time operating parameters. Preferably, a maximum power point tracking (MPPT) control can be adopted to control the operation, thereby improving operating efficiency of the system.

[0037] When the operation mode is the fixed mode, the operating parameters of the DC electrical device are determined to be common operating parameters of the DC electrical device according to the input parameters of the power supply. The operation of the DC electrical device is controlled according to the common operating parameters. Since the common operating parameters are determined according to the unchanged parameters of the power supply, the common operating

parameters, as fixed operating parameters, can prevent conflicts in control.

[0038] In the preferred first embodiment of the present invention, another control method for the DC electrical device is further provided. FIG. 2 shows an optional flowchart of the method. As shown in FIG. 2, the method includes the following steps S202 to S212.

[0039] S202: Start operating;

[0040] S204: Collecting a DC input voltage and a DC input power;

[0041] S206: Controlling the DC voltage to increase;

[0042] S208: Detecting whether the input power decreases; if yes, proceeding step S210; if not, proceeding step S212;

[0043] S210: Turning on an MPPT control for an operation; then returning to step S202; and

[0044] S212: Turning off an MPPT control for an operation; then returning to step S202.

[0045] In the foregoing embodiment, the input parameters of the power supply of the DC electrical device are obtained, the type of the power supply is identified according to the input parameters, and the operation mode of the DC electrical device corresponding to the type of the power parameters, and the operation mode of the DC electrical device corresponding to the type of the power supply is determined, and the operation of the DC electrical device is controlled according to the operation mode. After the DC electrical device is controlled in this way, the universality of DC electrical device is greatly improved. In the condition whether the DC voltage is adjustable or non-adjustable, the DC electrical device can perform the identification, and the operation mode is automatically configured, thereby achieving the optimal operating state.

[0046] When the DC electrical device starts to operate, firstly, the DC input voltage and the DC input power are collected. Then, the DC input voltage is controlled to increase by means of an internal DC/DC circuit, to detect whether the input power decreases, or whether the input power increases. If yes, it reveals that the type of the connected energy source is adjustable, then an adjustable operation mode may be performed, and the MPPT control is turned on to control the operation, thereby improving the operating efficiency of the system. If the input power remains unchanged, and the input voltage is not adjustable to a certain extent, it reveals that the type of the connected energy source, for example, a constant voltage power supply device such as a battery, has non-adjustable voltage. Then, the MPPT control for the operation is turned off, so as to prevent conflicts in control.

[0047] By adding the function of identifying the type of the energy source, the DC electrical device can identify different types of the energy source. For different types of energy sources, the DC electrical device can automatically configure the operation mode according to the identified

type of the energy source, thereby effectively solving the problem that the available power supplies of the DC electrical device are fixed, and that the universality of the DC electrical is low, and improving the universality of the DC electrical device.

[0048] Second Embodiment

[0049] Based on the method of the foregoing first embodiment, a DC electrical device is further provided in a preferred second embodiment of the present application. Specifically, FIG. 3 shows an optional block diagram of the DC electrical device. As shown in FIG. 3. The DC electrical device includes:

[0050] an energy source characteristic identification module configured to obtain input parameters of a power supply of the DC electrical device, and identify a type of the power supply according to the input parameters. During a promotion process of the DC electrical device, it is very necessary to improve the universality of the DC electrical device, therefore, the energy source characteristic identification module needs to be integrated in the DC electrical device, so as to identify different types of energy sources, and automatically configure its own operation mode according to different transmission characteristics, thereby matching the best operating state, and

[0051] an operation mode configuration module configured to determine an operation mode of the DC electrical device corresponding to the type of the power supply, and control an operation of the DC electrical device according to the operation mode thereof.

[0052] In the foregoing embodiment, the input parameters of the power supply of the DC electrical device are obtained, the type of the power supply is identified according to the input parameters, and the operation mode of the DC electrical device corresponding to the type of the power supply is determined, and the operation of the DC electrical device is controlled according to the operation mode. After the DC electrical device is controlled in this way, the universality of the DC electrical device can be greatly improved. In a condition whether the DC voltage is adjustable or non-adjustable, the DC electrical device can perform the identification, and the operation mode is automatically configured to achieve the optimal operating state.

[0053] The DC electrical device further includes: a DC interface configured to receive an external DC power supply, and a DC electrical device body configured to realize the kinetic energy of the DC electrical device.

[0054] In a preferred implementation of the present invention, the input parameters of the power supply include at least an input voltage and an input power. The energy source characteristic identification module includes: an adjusting unit configured to adjust the input voltage, where the adjusting unit may be implemented by a DC/DC, a detecting unit configured to detect whether the

input power changes, and a determining unit configured to determine the type of the power supply according to whether the input power changes.

[0055] The input parameters of the DC electrical device are divided into adjustable type and non-adjustable type. An adjustable power supply is a photovoltaic power supply. A non-adjustable power supply is a battery or a DC busbar.

[0056] According to the characteristics of the input parameters of the power supply, the power of the adjustable power supply changes as the voltage changes, while the power of the non-adjustable power supply does not change as the voltage changes. Therefore, the determining unit includes: a first determining sub-unit configured to determine the type of the power supply as the adjustable power supply when the input power changes, and a second determining sub-unit configured to determine the type of the power supply as the non-adjustable power supply when the input power remains unchanged.

[0057] After the type of the power supply is identified, the operation modes of the DC electrical device corresponding to different types of power supply are optionally determined, and the operation modes include an adjustable mode and a fixed mode. The operation mode configuration module includes: a first operation mode determining unit configured to determine that the operation mode is the adjustable mode when the type of the power supply is the adjustable power supply, and a second operation mode determining unit configured to determine that the operation mode is the fixed mode when the type of the power supply is the non-adjustable power supply.

[0058] The operation mode configuration module further includes a first controlling unit. The first controlling unit is configured to, when the operation mode is the adjustable mode, detect the input parameters of the power supply in real time, determine real-time operating parameters of the DC electrical device according to the input parameters, and control the operation of the DC electrical device according to the real-time operating parameters. Preferably, a MPPT control can be adopted to control the operation, thereby improving operating efficiency of the system. The operation mode configuration module further also includes a second controlling unit. The second controlling unit is configured to, when the operation mode is the fixed mode, determine the operating parameters of the DC electrical device to be common operating parameters of the DC electrical device according to the input parameters of the power supply, and control the operation of the DC electrical device according to the common operating parameters. Since the common operating parameters are determined according to the unchanged parameters of the power supply, the common operating parameters, as fixed operating parameters, can prevent conflicts in control.

[0059] By adding the function of identifying the type of the energy source, the DC electrical

device can identify different types of the energy source. For different types of energy sources, the DC electrical device can automatically configure the operation mode according to the identified type of the energy source, thereby effectively solving the problem that the available power supplies of the DC electrical device are fixed, and that the universality of the DC electrical is low, and improving the universality of the DC electrical device.

[0060] Regarding the device of the foregoing embodiment, the specific means by which each unit and each module perform operations have been described in detail in the embodiments of the related method, which will not be elaborated herein.

[0061] Third Embodiment

[0062] Based on the control method for the DC electrical device of the foregoing first embodiment, a computer device is further provided in the preferred third embodiment of the present invention. The computer device includes a memory, a processor, and computer programs stored in the memory and executable by the processor. The programs, when executed by the processor, cause the processor to perform the control method for the DC electrical device as described above.

[0063] In the foregoing embodiment, input parameters of the power supply of the DC electrical device are obtained. The type of the power supply is identified according to the input parameters, and the operation mode of the DC electrical device corresponding to the type of the power supply is determined. The operation of the DC electrical device is controlled according to the operation mode. After the DC electrical device is controlled in this way, the universality of the DC electrical device is greatly improved. In a condition whether the DC voltage is adjustable or non-adjustable, the DC electrical device can perform the identification, and the operation mode is automatically configured, thereby achieving the optimal operating state.

[0064] Fourth Embodiment

[0065] Based on the control method for the DC electrical device of the foregoing first embodiment, a storage medium containing computer executable instructions is further provided in the preferred fourth embodiment of the present invention. The computer executable instructions, when executed by a computer processor, cause the computer processor to perform the control method for the DC electrical device as described above.

[0066] In the foregoing embodiment, input parameters of the power supply of the DC electrical device are obtained. The type of the power supply is identified according to the input parameters, and the operation mode of the DC electrical device corresponding to the type of the power supply is determined. The operation of the DC electrical device is controlled according to the operation mode. After the DC electrical device is controlled in this way, the universality of the DC electrical device

is greatly improved. In a condition whether the DC voltage is adjustable or non-adjustable, the DC electrical device can perform the identification, and the operation mode is automatically configured, thereby achieving the optimal operating state.

[0067] Other embodiments of the present invention will be apparent to those skilled in the art from considering the description and practicing the disclosure disclosed herein. This application intends to cover any variations, uses, or adaptive changes of the present invention. These variations, uses, or adaptive changes follow the general principles of the present invention and encompass common knowledge or conventional technical means in the technical field which are not disclosed by the present invention. The description and the embodiments are to be considered exemplary only, and the true scope and spirit of the present invention are defined by the appended claims.

[0068] It should be understood that the present invention is not limited to the precise structures described above and shown in the accompanying drawings, and various modifications and changes can be made without departing from the scope of the present invention. The scope of the present invention is limited only by the appended claims.

[0069] Industrial Applicability

[0070] The solutions provided by the embodiments of the present application can be used to determine the operation mode of the DC electrical device corresponding to the type of the power supply, and control the operation of the DC electrical device according to the determined operation mode. The technical solutions provided in the embodiments of the present application can be applied to the DC electrical device. During the operation of the DC electrical device, the input parameters of the power supply of the DC electrical device are obtained. The type of the power supply is identified according to the input parameters, and the operation mode of the DC electrical device corresponding to the type of the power supply is determined. The operation of the DC electrical device is controlled according to the operation mode. By means of such a controlling method, the universality of the DC electrical device is greatly improved. In a condition whether the DC voltage is adjustable or non-adjustable, the DC electrical device can perform the identification, and the operation mode is automatically configured, thereby achieving the optimal operating state.

[0071] The reference to any prior art in this specification is not, and should not be taken as, an acknowledgement or any form of suggestion that such prior art forms part of the common general knowledge.

[0072] It will be understood that the terms “comprise” and “include” and any of their derivatives (e.g. comprises, comprising, includes, including) as used in this specification, and the claims that follow, is to be taken to be inclusive of features to which the term refers, and is not meant to exclude the presence of any additional features unless otherwise stated or implied.

What is claimed is:

1. A control method for a direct current electrical device, characterized by comprising:
obtaining input parameters of the direct current electrical device from a power supply, wherein the input parameters from the power supply comprise at least an input voltage and an input power;
adjusting the input voltage;
detecting whether the input power changes;
determining the type of the power supply according to whether the input power changes; and
determining an operation mode of the direct current electrical device corresponding to the type of the power supply, and controlling an operation of the direct current electrical device according to the operation mode.
2. The control method according to claim 1, characterized in that: the type of the power supply comprises an adjustable power supply and a non-adjustable power supply; the adjustable power supply is a photovoltaic power; and the non-adjustable power supply is a battery or a DC busbar.
3. The control method according to claim 2, characterized in that the determining the type of the power supply according to whether the input power changes comprises:
when the input power changes, determining the type of the power supply as the adjustable power supply; and
when the input power remains unchanged, determining the type of the power supply as the non-adjustable power supply.
4. The control method according to claim 2, characterized in that the operation mode comprises an adjustable mode and a fixed mode.
5. The control method according to claim 4, characterized in that the determining the operation mode of the direct current electrical device corresponding to the type of the power supply comprises:
when the type of the power supply is the adjustable power supply, determining the operation mode as the adjustable mode; and
when the type of the power supply is the non-adjustable power supply, determining the operation mode as the fixed mode.

6. The control method according to claim 5, characterized in that the controlling the operation of the direct current electrical device according to the operation mode comprises:

when the operation mode is the adjustable mode, detecting the input parameters of the power supply in real time, determining real-time operating parameters of the direct current electrical device according to the input parameters, and controlling the operation of the direct current electrical device according to the real-time operating parameters;

when the operation mode is the fixed mode, determining the operating parameters of the direct current electrical device as common operating parameters of the direct current electrical device according to the input parameters of the power supply, and controlling the operation of the direct current electrical device according to the common operating parameters.

7. A direct current electrical device, characterized by comprising:

an energy source characteristic identification module configured to obtain input parameters of the direct current electrical device from a power supply, the input parameters of the power supply comprising at least an input voltage and an input power, the energy source characteristic identification device comprising: an adjusting device configured to adjust the input voltage; a detecting device configured to detect whether the input power changes; and a determining device configured to determine the type of the power supply according to whether the input power changes; and

an operation mode configuration module configured to determine an operation mode of the direct current electrical device corresponding to the type of the power supply, and control an operation of the direct current electrical device according to the operation mode.

8. The direct current electrical device according to claim 7, characterized in that the type of the power supply comprises an adjustable power supply and a non-adjustable power supply, and the operation mode configuration module comprises:

a first operation mode determining unit configured to determine the operation mode as an adjustable mode when the type of the power supply is the adjustable power supply;

a second operation mode determining unit configured to determine the operation mode as a fixed mode when the type of the power supply is the non-adjustable power supply;

a first controlling unit configured to, when the operation mode is the adjustable mode, detect the

input parameters of the power supply in real time, determine real-time operating parameters of the direct current electrical device according to the input parameters, and control the operation of the direct current electrical device according to the real-time operating parameters; and a second controlling unit configured to, when the operation mode is the fixed mode, determine operating parameters of the direct current electrical device as common operating parameters of the direct current electrical device according to the input parameters of the power supply, and control the operation of the direct current electrical device according to the common operating parameters.

9. A computer device, characterized by comprising a memory, a processor, and computer programs stored in the memory and executable by the processor, wherein the programs, when executed by the processor, cause the processor to perform the control method for the direct current electrical device according to any one of claims 1 to 6.

10. A non-transitory computer readable medium containing computer executable instructions, characterized in that the computer executable instructions, when executed by a processor, cause the computer processor to perform the control method for the direct current electrical device according to any one of claims 1 to 6.




FIG. 1




FIG. 2




FIG. 3