

**(12) STANDARD PATENT  
(19) AUSTRALIAN PATENT OFFICE**

(11) Application No. AU 2003258142 B2

(54) Title  
**Method and apparatus for variable accuracy inter-picture timing specification for digital video encoding with reduced requirements for division operations**

(51) International Patent Classification(s)  
**H04N 7/26** (2006.01)                    **H04N 7/36** (2006.01)  
**G06T 9/00** (2006.01)

(21) Application No: **2003258142**                    (22) Date of Filing: **2003.08.07**

(87) WIPO No: **WO04/054257**

(30) Priority Data

(31) Number **10/313,773**                    (32) Date **2002.12.06**                    (33) Country **US**

(43) Publication Date: **2004.06.30**  
(43) Publication Journal Date: **2004.08.05**  
(44) Accepted Journal Date: **2009.03.05**

(71) Applicant(s)  
**Apple Inc.**

(72) Inventor(s)  
**Pari, Atul; Haskell, Barin G.; Singer, David W.; Dumitras, Adriana**

(74) Agent / Attorney  
**FB Rice & Co, Level 23 200 Queen Street, Melbourne, VIC, 3000**

(56) Related Art  
**US 6 297 852**  
**US 6 108 047**  
**US 6 072 834**  
**US 5 737 023**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number  
**WO 2004/054257 A1**

(51) International Patent Classification<sup>7</sup>: **H04N 7/12**, (74) Agent: **JOHANSEN, Dag**; StattlerJohansen & Adeli LLP, P.O. Box 51860, Palo Alto, CA 94303-0728 (US).

(21) International Application Number: **PCT/US2003/024953**

(22) International Filing Date: 7 August 2003 (07.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 10/313,773 6 December 2002 (06.12.2002) US

(71) Applicant: **APPLE COMPUTER, INC. [US/US]**; One Infinite Loop, Mail Stop: 38-PAT, Cupertino, CA 95014 (US).

(72) Inventors: **HASKELL, Barin, G.**; 1190 Fairbrook Dr., Mountain View, CA 94040-3960 (US). **SINGER, David, W.**; 268 Wawona Street, San Francisco, CA 94127-1328 (US). **DUMITRAS, Adriana**; 250 W. El Camino Real, Apt. 2403, Sunnyvale, CA 94087 (US). **PARI, Atul**; 19500 Pruneridge Ave, #4203, Cupertino, CA 95014-0632 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, IIR, IIU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR VARIABLE ACCURACY INTER-PICTURE TIMING SPECIFICATION FOR DIGITAL VIDEO ENOCODING WITH REDUCED REQUIREMENTS FOR DIVISION OPERATIONS



(57) Abstract: A method and apparatus for performing motion estimation in a digital video system is disclosed (Fig.1). Specifically, the present invention discloses a system that quickly calculates estimated motion vectors in a very efficient manner (Fig.1, item 160). In one embodiment, a first multiplicand is determined by multiplying a first display time difference between a first video picture and a second video picture by a power of two scale value (Fig.1, items 150, 160). This step scales up a numerator for a ratio (Fig.1, item 120). Next, the system determines a scaled ratio by dividing that scaled numerator by a second first display time difference between the second video picture and a third video picture. The scaled ratio is then stored calculating motion vector estimations. By storing the scaled ratio, all the estimated motion vectors can be calculated quickly with good precision since the scaled ratio saves significant bits and reducing the scale is performed by simple shifts (Fig.1, item 180).

WO 2004/054257 A1

**Method and Apparatus for Variable Accuracy Inter-Picture Timing  
Specification for Digital Video Encoding With Reduced Requirements  
for Division Operations**

5 **RELATED APPLICATIONS**

This patent application claims the benefit of an earlier filing date under title 35, United States Code, Section 120 to the United States Patent Application having serial number 10/313,773 filed on December 6, 2002.

10

**FIELD OF THE INVENTION**

The present invention relates to the field of multimedia compression systems. In particular the present invention discloses methods and systems for specifying 15 variable accuracy inter-picture timing with reduced requirements for processor intensive division operation.

**BACKGROUND OF THE INVENTION**

20 Digital based electronic media formats are finally on the cusp of largely replacing analog electronic media formats. Digital compact discs (CDs) replaced analog vinyl records long ago. Analog magnetic cassette tapes are becoming increasingly rare. Second and third generation digital audio systems such as Mini-discs and MP3 (MPEG Audio - layer 3) are now taking market share from the first generation digital audio 25 format of compact discs.

The video media formats have been slower to move to digital storage and digital transmission formats than audio media. The reason for this slower digital adoption has been largely due to the massive amounts of digital information required to 5 accurately represent acceptable quality video in digital form and the fast processing capabilities needed to encode compressed video. The massive amounts of digital information needed to accurately represent video require very high-capacity digital storage systems and high-bandwidth transmission systems.

10            However, video is now rapidly moving to digital storage and transmission formats. Faster computer processors, high-density storage systems, and new efficient compression and encoding algorithms have finally made digital video transmission and storage practical at consumer price points. The DVD (Digital Versatile Disc), a digital video system, has been one of the fastest selling consumer electronic products in years.

15            DVDs have been rapidly supplanting Video-Cassette Recorders (VCRs) as the pre-recorded video playback system of choice due to their high video quality, very high audio quality, convenience, and extra features. The antiquated analog NTSC (National Television Standards Committee) video transmission system is currently in the process of being replaced with the digital ATSC (Advanced Television Standards Committee) video 20 transmission system.

Computer systems have been using various different digital video encoding formats for a number of years. Specifically, computer systems have employed different video coder/decoder methods for compressing and encoding or decompressing

and decoding digital video, respectively. A video coder/decoder method, in hardware or software implementation, is commonly referred to as a "CODEC".

Among the best digital video compression and encoding systems used by 5 computer systems have been the digital video systems backed by the Motion Pictures Expert Group commonly known by the acronym MPEG. The three most well known and highly used digital video formats from MPEG are known simply as MPEG-1, MPEG-2, and MPEG-4. VideoCDs (VCDs) and early consumer-grade digital video editing systems use the early MPEG-1 digital video encoding format. Digital Versatile Discs (DVDs) and 10 the Dish Network brand Direct Broadcast Satellite (DBS) television broadcast system use the higher quality MPEG-2 digital video compression and encoding system. The MPEG-4 encoding system is rapidly being adapted by the latest computer based digital video encoders and associated digital video players.

15 The MPEG-2 and MPEG-4 standards compress a series of video frames or video fields and then encode the compressed frames or fields into a digital bitstream. When encoding a video frame or field with the MPEG-2 and MPEG-4 systems, the video frame or field is divided into a rectangular grid of pixelblocks. Each pixelblock is independently compressed and encoded.

20

When compressing a video frame or field, the MPEG-4 standard may compress the frame or field into one of three types of compressed frames or fields: Intra-frames (I-frames), Unidirectional Predicted frames (P-frames), or Bi-Directional Predicted frames (B-frames). Intra-frames completely independently encode an 25 independent video frame with no reference to other video frames. P-frames define a

video frame with reference to a single previously displayed video frame. B-frames define a video frame with reference to both a video frame displayed before the current frame and a video frame to be displayed after the current frame. Due to their efficient usage of redundant video information, P-frames and B-frames generally provide the 5 best compression.

Any discussion of documents, acts, materials, devices, articles or the like which has been included in the present specification is solely for the purpose of providing a context for the present invention. It is not to be taken as an admission that any or all of these matters form part of the prior art base or were common general knowledge in the 10 field relevant to the present invention as it existed before the priority date of each claim of this application.

Throughout this specification the word "comprise", or variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated element, integer or step, or group of elements, integers or steps, but not the exclusion of 15 any other element, integer or step, or group of elements, integers or steps.

**Summary of the Invention**

In a first embodiment, the present invention provides a method of performing motion estimation in a digital video system, said method comprising:

5 determining a first multiplicand by multiplying a first display time difference between a first video picture and a second video picture by a power of two value;

determining a scaled ratio by dividing said multiplicand by a second display time difference between said second video picture and a third video picture; and  
storing said scaled ratio for calculating motion vector estimations.

In a second embodiment, the present invention provides for a stream comprising  
10 a first video picture, a second video picture, and a third video picture, a method comprising:

computing a scaling value that is based on (i) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (ii) a second order difference value between an order value for the  
15 second video picture and the order value for the first video picture; and

computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture, wherein computing the particular motion vector comprises performing a bit shifting operation.

In a further embodiment, the present invention provides for a stream comprising first, second, and third video pictures, a method comprising:

computing a scaling value that is based on (i) a power of two value, (ii) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (iii) a second order difference value between an order value for the second video picture and the order value for the first video picture;  
25 and

computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture.

In a yet further embodiment, the present invention provides a computer readable medium storing a computer program that is executable by at least one processor, the  
30 computer program for processing a stream comprising first, second and third video pictures, the computer program comprising sets of instructions for:

computing a scaling value that is based on (i) a power of two value, (ii) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (iii) a second order difference value between an  
35 order value for the second video picture and the order value for the first video picture;  
and

computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture.

In a yet further embodiment, the present invention provides a computer readable medium storing a computer program that is executable by at least one processor, the 5 computer program for processing a stream comprising a first video picture, a second video picture, and a third video picture, the computer program comprising sets of instructions for:

computing a scaling value that is based on (i) a first order difference value between an order value for the third video picture and an order value for the first 10 video picture, and (ii) a second order difference value between an order value for the second video picture and the order value for the first video picture; and

computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture, wherein computing the particular motion vector comprises performing a division by a power of two value.

15 In another embodiment, the present invention provides a method comprising:

computing a scaling value based on (i) a first order difference value between an order value for a first video picture and an order value for a second video picture, and (ii) a particular value that is based on a power of two value and a second order 20 difference value between an order value for a third video picture and the order value for the second video picture; and

using said scaling value to compute a motion vector.

In a yet further embodiment, the present invention provides a computer readable medium storing a computer program that is executable by at least one processor, the computer program comprising sets of instructions for:

25 computing a scaling value based on (i) a first order difference value between an order value for a first video picture and an order value for a second video picture and (ii) a particular value that is based on a power of two value and a second order difference value

between an order value for a third video picture and the order value for the 30 second video picture; and

using said scaling value to compute a motion vector.

In another embodiment, the present invention provides a computer readable medium storing a computer program that is executable by at least one processor, the computer program comprising sets of instructions for:

receiving a plurality of video pictures and at least one order value; and  
computing an implicit B prediction block weighting for a video picture based  
on said at least one order value.

In a yet further embodiment, the present invention provides a method  
5 comprising:

decoding a plurality of video pictures by using at least one order value, said  
order value is for establishing an ordering for reference video picture selection; and  
outputting the decoded video pictures based on the order value.

In a yet further embodiment, the present invention provides for a bitstream  
10 comprising a first video picture, a second video picture, and a third video picture, a method  
comprising:

computing a scaling value that is based on (i) a power of two value, (ii) a first order  
difference value between an order value for the third video picture and an order value for  
the first video picture, and (iii) a second order difference value between an order value for  
15 the second video picture and the order value for the first video picture, wherein an order  
value for a particular video is representative of a position for the particular video picture in  
a sequence of video pictures; and

computing a particular motion vector for the second video picture from the scaling  
value and a motion vector for the third video picture, wherein computing the particular  
20 motion vector comprises performing a bit shifting operation.

In a yet further embodiment, the present invention provides a method  
comprising:

determining a scaling value by multiplying (i) a particular picture order count  
difference value between a picture order count for a first video picture and a picture order  
25 count for a second video picture by (ii) a particular value that is defined by a power of two  
value and another picture order count difference value between a picture order count for a  
third video picture and the picture order count for the second video picture; and  
using said scaling value to calculate a motion vector.

In a yet further embodiment, the present invention provides a computer  
30 readable medium storing a computer program that is executable by at least one processor,  
the computer program for processing a stream comprising a first video picture, a second  
video picture, and a third video picture, the computer program comprising sets of  
instructions for:

computing a scaling value that is based on (i) a first order difference value between  
35 an order value for the third video picture and an order value for the first video picture, and

(ii) a second order difference value between an order value for the second video picture and the order value for the first video picture; and

computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture, wherein computing the

5 particular motion vector comprises performing a bit shifting operation.

Other features and advantages of the present invention will be apparent from the accompanying drawings and from the following detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects, features, and advantages of the present invention will be apparent to one skilled in the art, in view of the following detailed description in which:

5

**Figure 1** illustrates a high-level block diagram of one possible digital video encoder system.

10 **Figure 2** illustrates a series of video pictures in the order that the pictures should be displayed wherein the arrows connecting different pictures indicate inter-picture dependency created using motion compensation.

15 **Figure 3** illustrates the video pictures from **Figure 2** listed in a preferred transmission order of pictures wherein the arrows connecting different pictures indicate inter-picture dependency created using motion compensation.

**Figure 4** graphically illustrates a series of video pictures wherein the distances between video pictures that reference each other are chosen to be powers of two.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A method and system for specifying Variable Accuracy Inter-Picture Timing in a multimedia compression and encoding system with reduced requirements for division operations is disclosed. In the following description, for purposes of explanation, specific nomenclature is set forth to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that these specific details are not required in order to practice the present invention. For example, the present invention has been described with reference to the MPEG multimedia compression and encoding system. However, the same techniques can easily be applied to other types of compression and encoding systems.

**Multimedia Compression and Encoding Overview**

Figure 1 illustrates a high-level block diagram of a typical digital video encoder 100 as is well known in the art. The digital video encoder 100 receives an incoming video stream of video frames 105 at the left of the block diagram. The digital video encoder 100 partitions each video frame into a grid of pixelblocks. The pixelblocks are individually compressed. Various different sizes of pixelblocks may be used by different video encoding systems. For example, different pixelblock resolutions include 8x8, 8x4, 16x8, 4x4, etc. Furthermore, pixelblocks are occasionally referred to as 'macroblocks.' This document will use the term pixelblock to refer to any block of pixels of any size.

A Discrete Cosine Transformation (DCT) unit **110** processes each pixelblock in the video frame. The frame may be processed independently (an intra-frame) or with reference to information from other frames received from the motion compensation unit (an inter-frame). Next, a Quantizer (Q) unit **120** quantizes the 5 information from the Discrete Cosine Transformation unit **110**. Finally, the quantized video frame is then encoded with an entropy encoder (H) unit **180** to produce an encoded bitstream. The entropy encoder (H) unit **180** may use a variable length coding (VLC) system.

10 Since an inter-frame encoded video frame is defined with reference to other nearby video frames, the digital video encoder **100** needs to create a copy of how each decoded frame will appear within a digital video decoder such that inter-frames may be encoded. Thus, the lower portion of the digital video encoder **100** is actually a digital video decoder system. Specifically, an inverse quantizer ( $Q^{-1}$ ) unit **130** reverses the 15 quantization of the video frame information and an inverse Discrete Cosine Transformation ( $DCT^{-1}$ ) unit **140** reverses the Discrete Cosine Transformation of the video frame information. After all the DCT coefficients are reconstructed from inverse Discrete Cosine Transformation ( $DCT^{-1}$ ) unit **140**, the motion compensation unit will use that information, along with the motion vectors, to reconstruct the encoded video frame. 20 The reconstructed video frame is then used as the reference frame for the motion estimation of the later frames.

The decoded video frame may then be used to encode inter-frames (P-frames or B-frames) that are defined relative to information in the decoded video frame. 25 Specifically, a motion compensation (MC) unit **150** and a motion estimation (ME) unit

**160** are used to determine motion vectors and generate differential values used to encode inter-frames.

A rate controller **190** receives information from many different components in a digital video encoder **100** and uses the information to allocate a bit budget for each video frame. The rate controller **190** should allocate the bit budget in a manner that will generate the highest quality digital video bit stream that complies with a specified set of restrictions. Specifically, the rate controller **190** attempts to generate the highest quality compressed video stream without overflowing buffers (exceeding the amount of available memory in a video decoder by sending more information than can be stored) or underflowing buffers (not sending video frames fast enough such that a video decoder runs out of video frames to display).

#### **Digital Video Encoding With Pixelblocks**

15

In some video signals the time between successive video pictures (frames or fields) may not be constant. (Note: This document will use the term video pictures to generically refer to video frames or video fields.) For example, some video pictures may be dropped because of transmission bandwidth constraints. Furthermore, the video timing may also vary due to camera irregularity or special effects such as slow motion or fast motion. In some video streams, the original video source may simply have non-uniform inter-picture times by design. For example, synthesized video such as computer graphic animations may have non-uniform timing since no arbitrary video timing is imposed by a uniform timing video capture system such as a video camera system. A

flexible digital video encoding system should be able to handle non-uniform video picture timing.

As previously set forth, most digital video encoding systems partition

5 video pictures into a rectangular grid of pixelblocks. Each individual pixelblock in a video picture is independently compressed and encoded. Some video coding standards, e.g., ISO MPEG or ITU H.264, use different types of predicted pixelblocks to encode video pictures. In one scenario, a pixelblock may be one of three types:

1. I-pixelblock – An Intra (I) pixelblock uses no information from any other video

10 pictures in its coding (it is completely self-defined);

2. P-pixelblock – A unidirectionally predicted (P) pixelblock refers to picture information from one preceding video picture; or
3. B-pixelblock – A bi-directional predicted (B) pixelblock uses information from one preceding picture and one future video picture.

15

If all the pixelblocks in a video picture are Intra-pixelblocks, then the video picture is an Intra-frame. If a video picture only includes unidirectional predicted macro blocks or intra-pixelblocks, then the video picture is known as a P-frame. If the video picture contains any bi-directional predicted pixelblocks, then the video picture is

20 known as a B-frame. For the simplicity, this document will consider the case where all pixelblocks within a given picture are of the same type.

An example sequence of video pictures to be encoded might be represented as:

25

I<sub>1</sub> B<sub>2</sub> B<sub>3</sub> B<sub>4</sub> P<sub>5</sub> B<sub>6</sub> B<sub>7</sub> B<sub>8</sub> B<sub>9</sub> P<sub>10</sub> B<sub>11</sub> P<sub>12</sub> B<sub>13</sub> I<sub>14</sub>...

where the letter (I, P, or B) represents if the video picture is an I-frame, P-frame, or B-frame and the number represents the camera order of the video picture in the sequence of video pictures. The camera order is the order in which a camera recorded the video pictures and thus is also the order in which the video pictures should be displayed (the display order).

5

The previous example series of video pictures is graphically illustrated in **Figure 2**. Referring to **Figure 2**, the arrows indicate that pixelblocks from a stored picture (I-frame or P-frame in this case) are used in the motion compensated prediction of other pictures.

10

In the scenario of **Figure 2**, no information from other pictures is used in the encoding of the intra-frame video picture  $I_1$ . Video picture  $P_5$  is a P-frame that uses video information from previous video picture  $I_1$  in its coding such that an arrow is drawn from video picture  $I_1$  to video picture  $P_5$ . Video picture  $B_2$ , video picture  $B_3$ , video picture  $B_4$  all use information from both video picture  $I_1$  and video picture  $P_5$  in their coding such that arrows are drawn from video picture  $I_1$  and video picture  $P_5$  to video picture  $B_2$ , video picture  $B_3$ , and video picture  $B_4$ . As stated above the inter-picture times are, in general, not the same.

15

20

Since B-pictures use information from future pictures (pictures that will be displayed later), the transmission order is usually different than the display order. Specifically, video pictures that are needed to construct other video pictures should be transmitted first. For the above sequence, the transmission order might be:

25

$I_1 P_5 B_2 B_3 B_4 P_{10} B_6 B_7 B_8 B_9 P_{12} B_{11} I_{14} B_{13} \dots$

**Figure 3** graphically illustrates the preceding transmission order of the video pictures from **Figure 2**. Again, the arrows in the figure indicate that pixelblocks from a stored video picture (I or P in this case) are used in the motion compensated prediction of other video pictures.

Referring to **Figure 3**, the system first transmits I-frame  $I_1$  which does not depend on any other frame. Next, the system transmits P-frame video picture  $P_5$  that depends upon video picture  $I_1$ . Next, the system transmits B-frame video picture  $B_2$  after video picture  $P_5$  even though video picture  $B_2$  will be displayed before video picture  $P_5$ . The reason for this is that when it comes time to decode video picture  $B_2$ , the decoder will have already received and stored the information in video pictures  $I_1$  and  $P_5$  necessary to decode video picture  $B_2$ . Similarly, video pictures  $I_1$  and  $P_5$  are ready to be used to decode subsequent video picture  $B_3$  and video picture  $B_4$ . The receiver/decoder reorders the video picture sequence for proper display. In this operation I and P pictures are often referred to as stored pictures.

The coding of the P-frame pictures typically utilizes Motion Compensation, wherein a Motion Vector is computed for each pixelblock in the picture. Using the computed motion vector, a prediction pixelblock (P-pixelblock) can be formed by translation of pixels in the aforementioned previous picture. The difference between the actual pixelblock in the P-frame picture and the prediction pixelblock is then coded for transmission.

P-Pictures

The coding of P-Pictures typically utilize Motion Compensation (MC), wherein a Motion Vector (MV) pointing to a location in a previous picture is computed for each pixelblock in the current picture. Using the motion vector, a prediction

5 pixelblock can be formed by translation of pixels in the aforementioned previous picture. The difference between the actual pixelblock in the P-Picture and the prediction pixelblock is then coded for transmission.

10 Each motion vector may also be transmitted via predictive coding. For example, a motion vector prediction may be formed using nearby motion vectors. In such a case, then the difference between the actual motion vector and the motion vector prediction is coded for transmission.

B-Pictures

15 Each B-pixelblock uses two motion vectors: a first motion vector referencing the aforementioned previous video picture and a second motion vector referencing the future video picture. From these two motion vectors, two prediction pixelblocks are computed. The two predicted pixelblocks are then combined together, using some function, to form a final predicted pixelblock. As above, the difference  
20 between the actual pixelblock in the B-frame picture and the final predicted pixelblock is then encoded for transmission.

As with P-pixelblocks, each motion vector (MV) of a B-pixelblock may be transmitted via predictive coding. Specifically, a predicted motion vector is formed using

nearby motion vectors. Then, the difference between the actual motion vector and the predicted is coded for transmission.

However, with B-pixelblocks the opportunity exists for interpolating  
5 motion vectors from motion vectors in the nearest stored picture pixelblock. Such motion vector interpolation is carried out both in the digital video encoder and the digital video decoder.

This motion vector interpolation works particularly well on video pictures  
10 from a video sequence where a camera is slowly panning across a stationary background. In fact, such motion vector interpolation may be good enough to be used alone. Specifically, this means that no differential information needs be calculated or transmitted for these B-pixelblock motion vectors encoded using interpolation.

15 To illustrate further, in the above scenario let us represent the inter-picture display time between pictures  $i$  and  $j$  as  $D_{i,j}$ , i.e., if the display times of the pictures are  $T_i$  and  $T_j$ , respectively, then

$$D_{i,j} = T_i - T_j \quad \text{from which it follows that}$$

$$D_{i,k} = D_{i,j} + D_{j,k}$$

$$20 \quad D_{i,k} = -D_{k,i}$$

Note that  $D_{i,j}$  may be negative in some cases.

Thus, if  $MV_{5,1}$  is a motion vector for a  $P_5$  pixelblock as referenced to  $I_1$ , then for the corresponding pixelblocks in  $B_2$ ,  $B_3$  and  $B_4$  the motion vectors as referenced to  $I_1$  and  $P_5$ , respectively would be interpolated by

$$5 \quad \begin{aligned} MV_{2,1} &= MV_{5,1} * D_{2,1} / D_{5,1} \\ MV_{5,2} &= MV_{5,1} * D_{5,2} / D_{5,1} \end{aligned}$$

$$\begin{aligned} MV_{3,1} &= MV_{5,1} * D_{3,1} / D_{5,1} \\ MV_{5,3} &= MV_{5,1} * D_{5,3} / D_{5,1} \end{aligned}$$

$$10 \quad \begin{aligned} MV_{4,1} &= MV_{5,1} * D_{4,1} / D_{5,1} \\ MV_{5,4} &= MV_{5,1} * D_{5,4} / D_{5,1} \end{aligned}$$

Note that since ratios of display times are used for motion vector prediction, absolute display times are not needed. Thus, relative display times may be used for  $D_{i,j}$  inter-picture display time values.

15

This scenario may be generalized, as for example in the H.264 standard. In the generalization, a P or B picture may use any previously transmitted picture for its motion vector prediction. Thus, in the above case picture  $B_3$  may use picture  $I_1$  and picture  $B_2$  in its prediction. Moreover, motion vectors may be extrapolated, not just interpolated. Thus, in this case we would have:

$$MV_{3,1} = MV_{2,1} * D_{3,1} / D_{2,1}$$

Such motion vector extrapolation (or interpolation) may also be used in the prediction process for predictive coding of motion vectors.

### Encoding Inter-Picture Display Times

The variable inter-picture display times of video sequences should be encoded and transmitted in a manner that renders it possible to obtain a very high coding efficiency and has selectable accuracy such that it meets the requirements of a video decoder. Ideally, the encoding system should simplify the tasks for the decoder such that relatively simple computer systems can decode the digital video.

The variable inter-picture display times are potentially needed in a number of different video encoding systems in order to compute differential motion vectors, Direct Mode motion vectors, and/or Implicit B Prediction Block Weighting.

The problem of variable inter-picture display times in video sequences is intertwined with the use of temporal references. Ideally, the derivation of correct pixel values in the output pictures in a video CODEC should be independent of the time at which that picture is decoded or displayed. Hence, timing issues and time references should be resolved outside the CODEC layer.

There are both coding-related and systems-related reasons underlying the desired time independence. In a video CODEC, time references are used for two purposes:

- (1) To establish an ordering for reference picture selection; and
- (2) To interpolate motion vectors between pictures.

To establish an ordering for reference picture selection, one may simply send a relative position value. For example, the difference between the frame position N in decode order

and the frame position M in the display order, i.e., N-M. In such an embodiment, time-stamps or other time references would not be required. To interpolate motion vectors, temporal distances would be useful if the temporal distances could be related to the interpolation distance. However, this may not be true if the motion is non-linear.

- 5 Therefore, sending parameters other than temporal information for motion vector interpolation seems more appropriate.

In terms of systems, one can expect that a typical video CODEC is part of a larger system where the video CODEC coexists with other video (and audio) CODECs.

- 10 In such multi-CODEC systems, good system layering and design requires that general functions, which are logically CODEC-independent such as timing, be handled by the layer outside the CODEC. The management of timing by the system and not by each CODEC independently is critical to achieving consistent handling of common functions such as synchronization. For instance in systems that handle more than one stream
- 15 simultaneously, such as a video/audio presentation, timing adjustments may sometimes be needed within the streams in order to keep the different streams synchronized.

Similarly, in a system that handles a stream from a remote system with a different clock timing adjustments may be needed to keep synchronization with the remote system. Such timing adjustments may be achieved using time stamps. For example, time stamps that

- 20 are linked by means of "Sender Reports" from the transmitter and supplied in RTP in the RTP layer for each stream may be used for synchronization. These sender reports may take the form of:

Video RTP TimeStamp X is aligned with reference timestamp Y

Audio RTP TimeStamp W is aligned with reference timestamp Z

Wherein the wall-clock rate of the reference timestamps is known, allowing the two streams to be aligned. However, these timestamp references arrive both periodically and separately for the two streams, and they may cause some needed re-alignment of the two streams. This is generally achieved by adjusting the video stream to match the audio or 5 vice-versa. System handling of time stamps should not affect the values of the pixels being displayed. More generally, system handling of temporal information should be performed outside the CODEC.

#### A Specific Example

10 As set forth in the previous section, the problem in the case of non uniform inter-picture times is to transmit the inter-picture display time values  $D_{i,j}$  to the digital video receiver in an efficient manner. One method of accomplishing this goal is to have the system transmit the display time difference between the current picture and the most recently transmitted stored picture for each picture after the first picture. For error 15 resilience, the transmission could be repeated several times within the picture. For example, the display time difference may be repeated in the slice headers of the MPEG or H.264 standards. If all slice headers are lost, then presumably other pictures that rely on the lost picture for decoding information cannot be decoded either.

20 Thus, with reference to the example of the preceding section, a system would transmit the following inter-picture display time values:

$D_{5,1} D_{2,5} D_{3,5} D_{4,5} D_{10,5} D_{6,10} D_{7,10} D_{8,10} D_{9,10} D_{12,10} D_{11,12} D_{14,12} D_{13,14} \dots$

25 For the purpose of motion vector estimation, the accuracy requirements for the inter-picture display times  $D_{i,j}$  may vary from picture to picture. For example, if there is only a

single B-frame picture  $B_6$  halfway between two P-frame pictures  $P_5$  and  $P_7$ , then it suffices to send only:

$$D_{7,5} = 2 \text{ and } D_{6,7} = -1$$

where the  $D_{i,j}$  inter-picture display time values are relative time values.

5

If, instead, video picture  $B_6$  is only one quarter the distance between video picture  $P_5$  and video picture  $P_7$  then the appropriate  $D_{i,j}$  inter-picture display time values to send would be:

$$D_{7,5} = 4 \text{ and } D_{6,7} = -1$$

10 Note that in both of the preceding examples, the display time between the video picture  $B_6$  and video picture  $P_7$  (inter-picture display time  $D_{6,7}$ ) is being used as the display time “unit” value. In the most recent example, the display time difference between video picture  $P_5$  and picture video picture  $P_7$  (inter-picture display time  $D_{6,7}$ ) is four display time “units” ( $4 * D_{6,7}$ ).

15

#### Improving Decoding Efficiency

In general, motion vector estimation calculations are greatly simplified if divisors are powers of two. This is easily achieved in our embodiment if  $D_{i,j}$  (the inter-picture time) between two stored pictures is chosen to be a power of two as graphically 20 illustrated in **Figure 4**. Alternatively, the estimation procedure could be defined to truncate or round all divisors to a power of two.

25 In the case where an inter-picture time is to be a power of two, the number of data bits can be reduced if only the integer power (of two) is transmitted instead of the full value of the inter-picture time. **Figure 4** graphically illustrates a case wherein the

distances between pictures are chosen to be powers of two. In such a case, the  $D_{3,1}$  display time value of 2 between video picture  $P_1$  and picture video picture  $P_3$  is transmitted as 1 (since  $2^1 = 2$ ) and the  $D_{7,3}$  display time value of 4 between video picture  $P_7$  and picture video picture  $P_3$  can be transmitted as 2 (since  $2^2 = 4$ ).

5

Alternatively, the motion vector interpolation or extrapolation operation can be approximated to any desired accuracy by scaling in such a way that the denominator is a power of two. (With a power of two in the denominator division may be performed by simply shifting the bits in the value to be divided.) For example,

$$10 \quad D_{5,4}/D_{5,1} \sim Z_{5,4}/P$$

Where the value  $P$  is a power of two and  $Z_{5,4} = P*D_{5,4}/D_{5,1}$  is rounded or truncated to the nearest integer. The value of  $P$  may be periodically transmitted or set as a constant for the system. In one embodiment, the value of  $P$  is set as  $P = 2^8 = 256$ .

15

The advantage of this approach is that the decoder only needs to compute  $Z_{5,4}$  once per picture or in many cases the decoder may pre-compute and store the  $Z$  value. This allows the decoder to avoid having to divide by  $D_{5,1}$  for every motion vector in the picture such that motion vector interpolation may be done much more efficiently. For example, the normal motion vector calculation would be:

$$20 \quad MV_{5,4} = MV_{5,1} * D_{5,4}/D_{5,1}$$

But if we calculate and store  $Z_{5,4}$  wherein  $Z_{5,4} = P*D_{5,4}/D_{5,1}$  then

$$MV_{5,4} = MV_{5,1} * Z_{5,4}/P$$

But since the  $P$  value has been chosen to be a power of two, the division by  $P$  is merely a simple shift of the bits. Thus, only a single multiplication and a single shift are required to calculate motion vectors for subsequent pixelblocks once the  $Z$  value has been

calculated for the video picture. Furthermore, the system may keep the accuracy high by performing all divisions last such that significant bits are not lost during the calculation. In this manner, the decoder may perform exactly the same as the motion vector interpolation as the encoder thus avoiding any mismatch problems that might otherwise 5 arise.

Since division (except for division by powers of two) is a much more computationally intensive task for a digital computer system than addition or multiplication, this approach can greatly reduce the computations required to reconstruct 10 pictures that use motion vector interpolation or extrapolation.

In some cases, motion vector interpolation may not be used. However, it is still necessary to transmit the display order of the video pictures to the receiver/player system such that the receiver/player system will display the video pictures in the proper 15 order. In this case, simple signed integer values for  $D_{i,j}$  suffice irrespective of the actual display times. In some applications only the sign (positive or negative) may be needed to reconstruct the picture ordering.

The inter-picture times  $D_{i,j}$  may simply be transmitted as simple signed 20 integer values. However, many methods may be used for encoding the  $D_{i,j}$  values to achieve additional compression. For example, a sign bit followed by a variable length coded magnitude is relatively easy to implement and provides coding efficiency.

One such variable length coding system that may be used is known as UVLC (Universal Variable Length Code). The UVLC variable length coding system is given by the code words:

1 = 1  
5 2 = 0 1 0  
3 = 0 1 1  
4 = 0 0 1 0 0  
5 = 0 0 1 0 1  
6 = 0 0 1 1 0  
10 7 = 0 0 1 1 1  
8 = 0 0 0 1 0 0 0...

Another method of encoding the inter-picture times may be to use arithmetic coding. Typically, arithmetic coding utilizes conditional probabilities to effect 15 a very high compression of the data bits.

Thus, the present invention introduces a simple but powerful method of encoding and transmitting inter-picture display times and methods for decoding those inter-picture display times for use in motion vector estimation. The encoding of inter-picture display times can be made very efficient by using variable length coding or 20 arithmetic coding. Furthermore, a desired accuracy can be chosen to meet the needs of the video codec, but no more.

The foregoing has described a system for specifying variable accuracy 25 inter-picture timing in a multimedia compression and encoding system. It is

contemplated that changes and modifications may be made by one of ordinary skill in the art, to the materials and arrangements of elements of the present invention without departing from the scope of the invention.

## THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. For a stream comprising a first video picture, a second video picture, and a third video picture, a method comprising:
  - 5 computing a scaling value that is based on (i) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (ii) a second order difference value between an order value for the second video picture and the order value for the first video picture; and computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture, wherein computing the particular motion vector comprises performing a bit shifting operation.
  - 10 2. The method of claim 1, wherein an order value for a particular video picture is representative of a temporal relationship for the particular video picture with respect to another video picture.
  - 15 3. The method of claim 1, wherein an order value for a particular video picture is representative of a position for the particular video picture in a sequence of video pictures.
  4. The method of claim 3, wherein the position for the particular video picture is an output position.
  - 20 5. The method of claim 1, wherein performing a bit shifting operation comprises shifting a bit value by eight bits.
  6. The method of claim 1 further comprising decoding the second video picture by using the computed motion vector.
  - 25 7. The method of claim 1, wherein the order value is representative of a time value.
  8. The method of claim 1, wherein the order value is not representative of a time value.
  9. The method of claim 1, wherein the order value is derived from a value that is stored in a slice header associated with the second video picture.
  - 30 10. The method of claim 1, wherein the scaling value is further based on a power of two value.
  11. The method of claim 1, wherein the first video picture is an I video picture.
  12. The method of claim 1, wherein the second video picture is a B video picture.
  13. The method of claim 1, wherein computing the motion vector comprises 35 performing an interpolation operation.

14. The method of claim 1, wherein computing the motion vector comprises performing an extrapolation operation.
15. The method of claim 1, wherein a sequence of order values is non-uniform.
16. The method of claim 1, wherein a particular order value is in a compressed format.
- 5 17. The method of claim 16, wherein the particular order value is compressed by using variable length coding.
18. The method of claim 16, wherein the particular order value is compressed by using arithmetic coding.
- 10 19. The method of claim 1, wherein a particular order value is derived from a value that is stored in a bitstream more than once.
20. For a stream comprising first, second, and third video pictures, a method comprising:
  - 15 computing a scaling value that is based on (i) a power of two value, (ii) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (iii) a second order difference value between an order value for the second video picture and the order value for the first video picture; and
  - 20 computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture.
21. The method of claim 20 further comprising decoding the second video picture by using the computed motion vector.
22. The method of claim 20, wherein the scaling value is proportional to the second order difference value
- 25 23. The method of claim 20, wherein the scaling value is inversely proportional to the first order difference value.
24. The method of claim 20, wherein computing the particular motion vector comprises performing a division by a particular power of two value.
25. The method of claim 20, wherein computing the particular motion vector 30 comprises performing a mathematical operation that is equivalent to performing a division by a particular power of two value.
26. The method of claim 20, wherein computing the particular motion vector comprises performing a mathematical operation that is equivalent to performing a bit shifting operation.
- 35 27. A computer readable medium storing a computer program that is executable by at least one processor, the computer program for processing a stream comprising first,

second and third video pictures, the computer program comprising sets of instructions for:

computing a scaling value that is based on (i) a power of two value, (ii) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (iii) a second order difference value between an order value for the second video picture and the order value for the first video picture; and

computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture.

10 28. The computer readable medium of claim 27, wherein the computer program further comprises a set of instructions for decoding the second video picture by using the computed motion vector.

15 29. A computer readable medium storing a computer program that is executable by at least one processor, the computer program for processing a stream comprising a first video picture, a second video picture, and a third video picture, the computer program comprising sets of instructions for:

20 computing a scaling value that is based on (i) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (ii) a second order difference value between an order value for the second video picture and the order value for the first video picture; and

computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture, wherein computing the particular motion vector comprises performing a division by a power of two value.

30. A method comprising:

25 computing a scaling value based on (i) a first order difference value between an order value for a first video picture and an order value for a second video picture, and (ii) a particular value that is based on a power of two value and a second order difference value between an order value for a third video picture and the order value for the second video picture; and

30 using said scaling value to compute a motion vector.

31. The method of claim 30, wherein using the scaling value comprises computing a scaled motion vector by multiplying said scaling value by a motion vector associated with said third video picture.

35 32. The method of claim 31, wherein computing the scaled motion vector comprises performing a division by a particular power of two value.

33. The method of claim 32, wherein the particular power of two value is two-hundred and fifty-six.
34. The method of claim 31, wherein computing the scaled motion vector comprises performing a bit shifting operation.
- 5 35. A computer readable medium storing a computer program that is executable by at least one processor, the computer program comprising sets of instructions for:
  - computing a scaling value based on (i) a first order difference value between an order value for a first video picture and an order value for a second video picture and (ii) a particular value that is based on a power of two value and a second order
  - 10 difference value between an order value for a third video picture and the order value for the second video picture; and
  - using said scaling value to compute a motion vector.
36. The computer readable medium as claimed in claim 35, wherein the set of
- 15 instructions for computing the scaling value comprises a set of instructions for performing a bit shifting operation.
37. The method of claim 1, wherein performing a bit shifting operation comprises performing a division by a power of two value.
38. The method of claim 1, wherein performing a bit shifting position comprises
- 20 performing a mathematical operation that is equivalent to performing a division by a power of two value.
39. The method of claim 20, wherein an order value of a particular video picture is representative of a temporal relationship for the particular video picture with respect to another video picture.
- 25 40. The method of claim 20 is representative of a position for the particular video picture in a sequence of video pictures.
41. The method of claim 40, wherein the sequence is a sequence for outputting video pictures.
42. The method of claim 20, wherein computing the particular motion vector
- 30 comprises performing a bit shifting operation.
43. The method of claim 42, wherein performing the bit shifting operation comprises shifting a bit value by a total of eight bits.
44. The method of claim 20, wherein the order value for the second video picture is derived from a value stored in a slice header that is associated with the second video
- 35 picture.

45. The computer readable medium of claim 27, wherein an order value for a particular video picture is representative of a temporal relationship for the particular video picture with respect to another video picture.
46. The computer readable medium of claim 27, wherein an order value for a particular video picture is representative of a position for the particular video picture in a sequence of video pictures.
47. The computer readable medium of claim 27, wherein the set of instructions for computing the particular motion vector comprises a set of instructions for performing a bit shifting operation.
48. The computer readable medium of claim 27, wherein the set of instructions for computing the particular motion vector comprises a set of instructions for performing a division by a power of two value.
49. The computer readable medium of claim 27, wherein the set of instructions for computing the particular motion vector comprises a set of instructions for performing a mathematical operation that is equivalent to performing a division by a power of two value.
50. The computer readable medium of claim 27, wherein the set of instructions for computing the particular motion vector comprises a set of instructions for performing a mathematical operation that is equivalent to performing a bit shifting operation.
51. The computer readable medium of claim 29, wherein an order value for a particular video picture specifies an output order for the particular video picture in a sequence of video pictures.
52. The computer readable medium of claim 29, wherein the set of instructions for performing the division comprises a set of instructions for performing a mathematical operation that is equivalent to performing a bit shifting operation.
53. The method of claim 30, wherein an order value for a particular video picture is representative of a temporal relationship for the particular video picture with respect to another video picture.
54. The method of claim 30, wherein an order value for a particular video picture is representative of a position for the particular video picture in a sequence of video pictures.
55. The method of claim 30, wherein said scaling value is truncated.
56. The method of claim 30, wherein said scaling value is rounded to a nearest integer.
57. The computer readable medium is claimed in claim 35, wherein the set of instructions for using the scaling value comprises a set of instructions for determining a scaled motion vector by multiplying said scaling value by a motion vector associated with said third video picture.

58. The computer readable medium as claimed in claim 57, wherein the set of instructions for determining the scaled motion vector comprises a set of instructions for performing a division by a particular power of two value.

59. The computer readable medium of claim 35, wherein a particular order value for a particular video picture specifies a display order for the particular video picture in a sequence of video pictures.

60. The computer readable medium of claim 35, wherein the first video picture is for decoding after a decoding of the second video picture.

61. For a bitstream comprising a first video picture, a second video picture, and a third video picture, a method comprising:

- 10 computing a scaling value that is based on (i) a power of two value, (ii) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (iii) a second order difference value between an order value for the second video picture and the order value for the first video picture, wherein an order value for a particular video is representative of a position for the particular video picture in a sequence of video pictures; and
- 15 computing a particular motion vector for the second video picture from the scaling value and a motion vector for the third video picture, wherein computing the particular motion vector comprises performing a bit shifting operation.

20 62. A method comprising:

- 25 determining a scaling value by multiplying (i) a particular picture order count difference value between a picture order count for a first video picture and a picture order count for a second video picture by (ii) a particular value that is defined by a power of two value and another picture order count difference value between a picture order count for a third video picture and the picture order count for the second video picture; and
- 30 using said scaling value to calculate a motion vector.

63. The method of claim 62, wherein using said scaling value comprises determining a scaled motion vector by multiplying said scaling value by a motion vector associated with said third video picture.

30 64. The method of claim 63, wherein determining the scaled motion vector comprises performing a division by a particular power of two value.

65. The method of claim 63, wherein determining the scaled motion vector comprises performing a bit shifting operation.

66. The method of claim 64, wherein the particular power of two value comprises two-hundred and fifty-six.

67. The method of claim 63, wherein a particular picture order count for a particular video picture specifies a display order for the particular video picture in a sequence of video pictures.
68. The method of claim 63, wherein the first video picture is for decoding after a decoding of the second video picture.
69. A computer readable medium storing a computer program that is executable by at least one processor, the computer program for processing a stream comprising a first video picture, a second video picture, and a third video picture, the computer program comprising sets of instructions for:
  - 10 computing a scaling value that is based on (i) a first order difference value between an order value for the third video picture and an order value for the first video picture, and (ii) a second order difference value between an order value for the second video picture and the order value for the first video picture; and
  - 15 computing a particular motion vector for the second video picture based on the scaling value and a motion vector for the third video picture, wherein computing the particular motion vector comprises performing a bit shifting operation.
70. The computer readable medium of claim 69, wherein the computer program further comprises a set of instructions for decoding the second video picture by using the computed motion vector.




Figure 1




Figure 2




Figure 3




Figure 4