



US008327852B2

(12) **United States Patent**  
**Nikolchev et al.**

(10) **Patent No.:** **US 8,327,852 B2**  
(45) **Date of Patent:** **Dec. 11, 2012**

(54) **OCCLUSION DEVICES AND METHODS**

(75) Inventors: **Julian N. Nikolchev**, Portola Valley, CA (US); **Dai T. Ton**, San Jose, CA (US); **Ashish Khara**, San Francisco, CA (US); **Donnell W. Gurskis**, Pleasanton, CA (US); **Steven Bacich**, Half Moon Bay, CA (US)

(73) Assignee: **Conceptus, Inc.**, Mountain View, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/294,758**

(22) Filed: **Nov. 11, 2011**

(65) **Prior Publication Data**

US 2012/0055491 A1 Mar. 8, 2012

**Related U.S. Application Data**

(63) Continuation of application No. 12/908,756, filed on Oct. 20, 2010, now Pat. No. 8,171,936, which is a continuation of application No. 10/600,298, filed on Jun. 20, 2003, now abandoned, which is a continuation-in-part of application No. 09/093,835, filed on Jun. 8, 1998, now Pat. No. 6,705,323, and a continuation-in-part of application No. 08/475,252, filed on Jun. 7, 1995, now abandoned, and a continuation-in-part of application No. 08/474,779, filed on Jun. 7, 1995, now Pat. No. 6,176,240.

(60) Provisional application No. 60/059,861, filed on Sep. 24, 1997.

(51) **Int. Cl.**  
**A61F 6/06** (2006.01)

(52) **U.S. Cl.** ..... **128/830**; 128/831

(58) **Field of Classification Search** ..... 128/830–841;  
606/151, 191

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,102,270 A 12/1937 Hyams  
2,365,296 A 12/1944 Schimpf  
3,042,030 A 7/1962 Read

(Continued)

FOREIGN PATENT DOCUMENTS

AU 32520/78 7/1979

(Continued)

OTHER PUBLICATIONS

Brueschke, et al., "A Steerable Hysteroscopic and Mechanical Tubal Occlusive Devices", *Advances in Female Sterilization Techniques*, Eds., Harper & Row, Publishers, 1976, pp. 182-198.

(Continued)

*Primary Examiner* — Michael A. Brown

(74) *Attorney, Agent, or Firm* — Blakely, Sokoloff, Taylor & Zafman LLP

(57) **ABSTRACT**

The invention provides intrafallopian devices and non-surgical methods for their placement to prevent conception. The efficacy of the device is enhanced by forming the structure at least in part from copper or copper alloy. The device is anchored within the fallopian tube by a lumen-traversing region of the resilient structure which has helical outer surface, together with a portion of the resilient structure which is biased to form a bent secondary shape, the secondary shape having a larger cross-section than the fallopian tube. The resilient structure is restrained in a straight configuration and transcervically inserted within the fallopian tube, where it is released. Optionally, permanent sterilization is effected by passing a current through there resilient structure to the tubal walls.

**15 Claims, 15 Drawing Sheets**



U.S. PATENT DOCUMENTS					
3,334,629 A	8/1967	Cohn	4,808,399 A	2/1989	Rypacek et al.
3,404,682 A	10/1968	Waldron	4,821,741 A	4/1989	Mohajer
3,405,711 A	10/1968	Bakunin	4,824,434 A	4/1989	Seitz, Jr.
3,422,813 A	1/1969	Braley, Jr. et al.	4,846,834 A	7/1989	von Recum et al.
3,463,141 A	8/1969	Mozolf	4,932,421 A	6/1990	Kaali et al.
3,467,090 A	9/1969	Zollett	4,932,422 A	6/1990	Ragheb
3,561,438 A	2/1971	Canel	4,937,254 A	6/1990	Sheffield et al.
3,563,235 A	2/1971	Zipper	4,943,290 A	7/1990	Rexroth et al.
3,598,115 A	8/1971	Horne, Jr.	4,969,458 A	11/1990	Wiktor
3,620,212 A	11/1971	Fannon et al.	4,970,298 A	11/1990	Silver et al.
3,675,639 A	7/1972	Cimber	4,983,177 A	1/1991	Wolf
3,675,642 A	7/1972	Lord	4,994,069 A	2/1991	Ritchart et al.
3,680,542 A	8/1972	Cimber	5,002,552 A	3/1991	Casey
3,687,129 A	8/1972	Nuwayser	5,065,751 A	11/1991	Wolf
3,722,500 A	3/1973	Robinson	5,071,407 A	12/1991	Termin et al.
3,760,806 A	9/1973	Leeper	5,095,917 A	3/1992	Vancaillie
3,763,856 A	10/1973	Blomberg	5,108,420 A	4/1992	Marks
3,768,102 A	10/1973	Kwan-Gett et al.	5,122,136 A	6/1992	Guglielmi et al.
3,774,600 A	11/1973	Cognat	5,122,137 A	6/1992	Lennox
3,803,308 A	4/1974	Zipper	5,133,709 A	7/1992	Prince
3,805,767 A	4/1974	Erb	5,147,353 A	9/1992	Everett et al.
3,840,016 A	10/1974	Lindemann	5,147,370 A	9/1992	McNamara et al.
3,858,571 A	1/1975	Rudolph	5,163,958 A	11/1992	Pinchuk
3,858,586 A	1/1975	Lessen	5,176,692 A	1/1993	Wilk et al.
3,868,956 A	3/1975	Alfidi et al.	5,192,301 A	3/1993	Kamiya et al.
3,895,634 A	7/1975	Berger et al.	5,195,964 A	3/1993	Kletzky et al.
3,918,431 A	11/1975	Sinnreich	5,197,978 A	3/1993	Hess
3,926,195 A	12/1975	Bleier et al.	5,207,684 A	5/1993	Nobles
3,938,527 A	2/1976	Rioux et al.	5,222,964 A	6/1993	Cooper
3,973,560 A	8/1976	Emmett	5,226,911 A	7/1993	Chee et al.
3,982,542 A	9/1976	Ford et al.	5,234,437 A	8/1993	Sepetka
4,003,380 A	1/1977	Wien	5,244,096 A	9/1993	Stoner
RE29,345 E	8/1977	Erb	5,250,071 A	10/1993	Palermo
4,040,417 A	8/1977	Zipper	5,254,132 A	10/1993	Barley et al.
4,057,063 A	11/1977	Gieles et al.	5,259,836 A	11/1993	Thurmond et al.
4,085,743 A	4/1978	Yoon	5,261,916 A	11/1993	Engelson
4,111,196 A	9/1978	Emmett	5,303,719 A	4/1994	Wilk et al.
4,135,495 A	1/1979	Borgen	5,304,194 A	4/1994	Chee et al.
4,136,695 A	1/1979	Dafoe	5,304,195 A	4/1994	Twyford, Jr. et al.
4,140,126 A	2/1979	Choudhury	5,304,228 A	4/1994	Prince
4,143,656 A	3/1979	Holmes	5,312,415 A	5/1994	Palermo
4,158,050 A	6/1979	Zipper	5,330,483 A	7/1994	Heaven et al.
4,160,446 A	7/1979	Barrington	5,342,348 A	8/1994	Kaplan
4,181,725 A	1/1980	Voorhees et al.	5,346,498 A	9/1994	Greelis et al.
4,185,618 A	1/1980	Corey	5,350,397 A	9/1994	Palermo et al.
4,207,891 A	6/1980	Boldue	5,354,295 A	10/1994	Guglielmi et al.
4,245,623 A	1/1981	Erb	5,354,309 A	10/1994	Schnepp-Pesch et al.
4,246,896 A	1/1981	Horne, Jr. et al.	5,356,388 A	10/1994	Sepetka et al.
4,326,511 A	4/1982	Zimmerman	5,364,393 A	11/1994	Auth et al.
4,353,363 A	10/1982	Sopena Quesada	5,366,472 A	11/1994	Hillstead
4,365,621 A	12/1982	Brundin	5,377,668 A	1/1995	Ehmsen et al.
4,374,523 A	2/1983	Yoon	5,382,259 A	* 1/1995	Phelps et al. .... 606/151
4,416,660 A	11/1983	Dafoe	5,382,260 A	1/1995	Dormandy et al.
4,478,837 A	10/1984	Schenker	5,382,261 A	1/1995	Palmaz
4,485,814 A	12/1984	Yoon	5,389,089 A	2/1995	Bauer et al.
4,503,569 A	3/1985	Dotter	5,389,100 A	2/1995	Bacich et al.
4,509,504 A	4/1985	Brundin	5,411,549 A	5/1995	Peters
4,523,590 A	6/1985	Roth et al.	5,423,829 A	6/1995	Pham et al.
4,537,186 A	8/1985	Verschoof et al.	5,423,849 A	6/1995	Engelson et al.
4,572,162 A	2/1986	Livesay et al.	5,433,708 A	7/1995	Nichols et al.
4,574,806 A	3/1986	McCarthy	5,443,500 A	8/1995	Sigwart
4,579,110 A	4/1986	Hamou	5,458,636 A	10/1995	Brancato
4,595,000 A	6/1986	Hamou	5,469,867 A	11/1995	Schmitt
4,601,698 A	7/1986	Moulding, Jr.	5,474,089 A	12/1995	Waynant
4,606,336 A	8/1986	Zeluff	5,499,995 A	3/1996	Teirstein
4,612,924 A	9/1986	Cimber	5,507,768 A	4/1996	Lau et al.
4,628,924 A	12/1986	Cimber	5,514,176 A	5/1996	Bosley, Jr.
4,638,803 A	1/1987	Rand	5,522,822 A	6/1996	Phelps et al.
4,655,771 A	4/1987	Wallsten	5,522,836 A	6/1996	Palermo
4,700,701 A	10/1987	Montaldi	5,534,007 A	7/1996	St. Germain et al.
4,715,365 A	12/1987	Cimber	5,545,210 A	8/1996	Hess et al.
4,717,387 A	1/1988	Inoue et al.	5,549,624 A	8/1996	Mirigian et al.
4,724,832 A	2/1988	Strubel et al.	5,555,896 A	9/1996	Cimber
4,727,866 A	3/1988	Livesay et al.	5,556,396 A	9/1996	Cohen et al.
4,731,052 A	3/1988	Seitz, Jr.	5,562,641 A	10/1996	Flomenblit et al.
4,733,665 A	3/1988	Palmaz	5,562,654 A	10/1996	Smith
4,788,966 A	12/1988	Yoon	5,569,245 A	10/1996	Guglielmi et al.
4,805,618 A	2/1989	Ueda et al.	5,578,074 A	11/1996	Mirigian
			5,582,619 A	12/1996	Ken

5,601,593 A	2/1997	Freitag	2002/0072744 A1	6/2002	Harrington et al.
5,601,600 A	2/1997	Ton	2003/0015203 A1	1/2003	Makower et al.
5,624,449 A	4/1997	Pham et al.	2003/0029457 A1	2/2003	Callister et al.
5,624,461 A	4/1997	Mariant	2003/0051735 A1	3/2003	Pavcnik et al.
5,630,797 A	5/1997	Diedrich et al.	2003/0199913 A1	10/2003	Dubrul et al.
5,634,877 A	6/1997	Salama	2003/0220636 A1	11/2003	Bowman et al.
5,656,036 A	8/1997	Palmaz	2004/0172051 A1	9/2004	Ravikumar
5,662,712 A	9/1997	Pathak et al.	2004/0202694 A1	10/2004	Burbank et al.
5,690,666 A	11/1997	Berenstein et al.	2004/0204720 A1	10/2004	Harrington et al.
5,690,842 A	11/1997	Panchinson	2004/0220585 A1	11/2004	Nikolchev
5,718,711 A	2/1998	Berenstein et al.	2004/0255958 A1	12/2004	Harrington et al.
5,725,777 A	3/1998	Taylor	2005/0033281 A1	2/2005	Bowman et al.
5,743,905 A	4/1998	Eder et al.	2005/0045183 A1	3/2005	Callister et al.
5,746,692 A	5/1998	Bacich et al.	2005/0192616 A1	9/2005	Callister et al.
5,746,769 A	5/1998	Ton et al.	2005/0217680 A1	10/2005	Callister et al.
5,749,915 A	5/1998	Slepian			
5,755,773 A	5/1998	Evans et al.			
5,766,160 A	6/1998	Samson et al.			
5,766,203 A	6/1998	Imran et al.	CN	1047447	5/1990
5,772,669 A	6/1998	Vrba	CN	1073088 A	6/1993
5,795,288 A	8/1998	Cohen et al.	DE	2404605 A1	8/1975
5,807,236 A	9/1998	Bacich et al.	DE	2525650 A1	12/1976
5,843,158 A	12/1998	Lenker et al.	DE	2537620 A1	2/1977
5,876,398 A	3/1999	Mulier et al.	DE	2635863 A1	2/1977
5,885,601 A	3/1999	Sokal	DE	28 03 685 A1	8/1979
5,895,749 A	4/1999	Alvarez	DE	2913036 A1	10/1980
5,897,551 A	4/1999	Everett et al.	EP	0 010 812	5/1980
5,925,059 A	7/1999	Palermo et al.	EP	0105669 B1	9/1983
5,935,137 A	8/1999	Saadat et al.	EP	0183372 A1	10/1985
5,935,145 A *	8/1999	Villar et al. .... 606/191	EP	0241971 B1	3/1987
5,954,715 A	9/1999	Harrington et al.	EP	0421966 A1	9/1990
5,968,052 A	10/1999	Sullivan, III et al.	EP	0541258 A1	5/1993
5,976,162 A	11/1999	Doan et al.	EP	0686382 A1	12/1995
5,979,446 A	11/1999	Loy	EP	0739608	10/1996
6,019,757 A	2/2000	Scheldrup	EP	0 891 757 A2	1/1999
6,042,590 A	3/2000	Sporri et al.	GB	1460077	12/1976
6,066,139 A	5/2000	Ryan et al.	GB	1530565	11/1978
6,068,626 A	5/2000	Harrington et al.	GB	2 010 728	7/1979
6,080,152 A	6/2000	Nardella et al.	GB	2 038 186	7/1980
6,096,052 A	8/2000	Callister et al.	GB	2150439 A	7/1985
6,143,007 A *	11/2000	Mariant et al. .... 606/151	GB	2 211 095	6/1989
6,145,505 A	11/2000	Nikolchev et al.	JP	1-113045	5/1989
6,156,742 A	12/2000	Mackenzie	JP	5-269197	10/1993
6,164,280 A	12/2000	Everett et al.	NL	7810696	4/1980
6,176,240 B1	1/2001	Nikolchev et al.	WO	WO 80/02369	11/1980
6,178,354 B1	1/2001	Gibson	WO	WO 83/00011 A1	1/1983
6,187,027 B1	2/2001	Mariant et al.	WO	WO 88/09648 A1	12/1988
6,270,495 B1	8/2001	Palermo	WO	WO 93/06884	4/1993
6,286,510 B1	9/2001	Ray et al.	WO	WO 94/06503	3/1994
6,309,384 B1	10/2001	Harrington et al.	WO	WO 94/07560	4/1994
6,346,102 B1	2/2002	Harrington et al.	WO	WO 94/10936	5/1994
6,357,443 B1	3/2002	Loy	WO	WO 94/11051	5/1994
6,371,118 B1	4/2002	Ray et al.	WO	WO 94/24944 A1	11/1994
6,401,719 B1	6/2002	Farley et al.	WO	WO 94/26175	11/1994
6,432,116 B1	8/2002	Callister et al.	WO	WO 95/01123	1/1995
6,513,528 B2	2/2003	Burton et al.	WO	WO 95/25490 A1	9/1995
6,526,979 B1	3/2003	Nikolchev et al.	WO	WO 96/22122 A1	7/1996
6,550,480 B2	4/2003	Feldman et al.	WO	WO 96/40023	12/1996
6,585,663 B1	7/2003	Coley et al.	WO	WO 96/40024	12/1996
6,599,299 B2	7/2003	Schultz	WO	WO 97/08997	3/1997
6,634,361 B1	10/2003	Nikolchev et al.	WO	WO 97/12569 A1	4/1997
6,679,266 B2	1/2004	Nikolchev et al.	WO	WO 97/13451	4/1997
6,684,884 B2	2/2004	Nikolchev et al.	WO	WO 97/27893	8/1997
6,705,323 B1	3/2004	Nikolchev et al.	WO	WO 97/46175 A1	12/1997
6,712,810 B2	3/2004	Harrington et al.	WO	WO 97/49345 A1	12/1997
6,726,682 B2	4/2004	Harrington et al.	WO	WO 98/26737	6/1998
6,758,831 B2	7/2004	Ryan	WO	WO 98/31308 A1	7/1998
6,780,182 B2	8/2004	Bowman et al.	WO	WO 98/55046	12/1998
6,802,825 B2	10/2004	Ackerman et al.	WO	WO 99/15116	4/1999
6,871,650 B1	3/2005	Nikolchev et al.	WO	WO 00/13624	3/2000
7,073,504 B2	7/2006	Callister et al.	WO	WO 00/44323 A1	8/2000
7,428,904 B2	9/2008	Nikolchev et al.	WO	WO 01/37760 A2	5/2001
7,686,020 B2	3/2010	Nikolchev et al.	WO	WO 03/088879	10/2003
7,921,848 B2	4/2011	Nikolchev et al.	WO	WO 2004/098469	11/2004
8,066,007 B2	11/2011	Nikolchev et al.			
8,171,936 B2	5/2012	Nikolchev et al.			
2001/0016738 A1	8/2001	Harrington et al.			
2001/0041900 A1	11/2001	Callister et al.			
2002/0013589 A1	1/2002	Callister et al.			

FOREIGN PATENT DOCUMENTS

CN	1047447	5/1990
CN	1073088 A	6/1993
DE	2404605 A1	8/1975
DE	2525650 A1	12/1976
DE	2537620 A1	2/1977
DE	2635863 A1	2/1977
DE	28 03 685 A1	8/1979
DE	2913036 A1	10/1980
EP	0 010 812	5/1980
EP	0105669 B1	9/1983
EP	0183372 A1	10/1985
EP	0241971 B1	3/1987
EP	0421966 A1	9/1990
EP	0541258 A1	5/1993
EP	0686382 A1	12/1995
EP	0739608	10/1996
EP	0 891 757 A2	1/1999
GB	1460077	12/1976
GB	1530565	11/1978
GB	2 010 728	7/1979
GB	2 038 186	7/1980
GB	2150439 A	7/1985
GB	2 211 095	6/1989
JP	1-113045	5/1989
JP	5-269197	10/1993
NL	7810696	4/1980
WO	WO 80/02369	11/1980
WO	WO 83/00011 A1	1/1983
WO	WO 88/09648 A1	12/1988
WO	WO 93/06884	4/1993
WO	WO 94/06503	3/1994
WO	WO 94/07560	4/1994
WO	WO 94/10936	5/1994
WO	WO 94/11051	5/1994
WO	WO 94/24944 A1	11/1994
WO	WO 94/26175	11/1994
WO	WO 95/01123	1/1995
WO	WO 95/25490 A1	9/1995
WO	WO 96/22122 A1	7/1996
WO	WO 96/40023	12/1996
WO	WO 96/40024	12/1996
WO	WO 97/08997	3/1997
WO	WO 97/12569 A1	4/1997
WO	WO 97/13451	4/1997
WO	WO 97/27893	8/1997
WO	WO 97/46175 A1	12/1997
WO	WO 97/49345 A1	12/1997
WO	WO 98/26737	6/1998
WO	WO 98/31308 A1	7/1998
WO	WO 98/55046	12/1998
WO	WO 99/15116	4/1999
WO	WO 00/13624	3/2000
WO	WO 00/44323 A1	8/2000
WO	WO 01/37760 A2	5/2001
WO	WO 03/088879	10/2003
WO	WO 2004/098469	11/2004

OTHER PUBLICATIONS

Brueschke, Erich E., "Reversible Occlusive Devices," J. Reproductive Medicine for the Obstetrician and Gynecologist, vol. 17, No. 2 (Aug. 1976).

- Brundin J., "Ch. 31: Hydrogel Tubal Blocking Device: P-Block," *Female Transcervical Sterilization* (Gerald Zatuchni, M.D. et al., eds., Harper & Row 1983).
- Brundin, J., "Hysteroscopy for Sterilization," *Contraceptive Delivery Systems: An International Journal* (1982).
- Brundin, J., "Observations on the mode of action of an intratubal device, the P-block," *Am. J. of Obst. & Gyn.*, (1987).
- Cooper, "Hysteroscopic Sterilization," *Fertility Control*, 1985, Corson, et al., Eds., Little, Brown & Co. Boston, First Edition, pp. 119-131.
- Corfman, "An Instrument for Transcervical Treatment of the Oviducts and Uterine Comua", *Obstetrics and Gynecology*, 1996, 27(6):880-884.
- Darabi, et al., "Collaborative Study on Hysteroscopic Sterilization Procedures: Final Report", *Risks, Benefits, and Controversies in Fertility Control*, 1978, Eds., Harper & Row, New York, pp. 81-101.
- EPO Search Report for European Divisional Patent Application No. 07002727.1, mailed May 30, 2007, total 8 pages.
- Fischer, Michael E. et al., "Silicone Devices for Tubal Occlusion: Radiographic Description and Evaluation," *Radiology* (Jun. 1984).
- Free, Michael J. et al., "Technology for Mechanical Fallopian Tube-Blocking Device," *Advances in Female Sterilization Techniques* (Harper & Row 1976).
- Hamou, J. et al., "Hysteroscopic Placement of Nylon Intratubal Devices for Potentially Reversible Sterilization," *The Fallopian Tube: Basic Studies and Clinical Contributions* (1986).
- Hayashi, Motoyuki, "Ch. 28: Tubal Sterilization by Cornual Coagulation Under Hysteroscopy," *Human Sterilization* (Ralph Richart et al., eds. 1972).
- Hosseinian, Abdol "31: Hysteroscopically Delivered Tubal Plugs," *Reversal of Sterilization* (John Sciarra et al., eds. Harper & Row 1978).
- Hosseinian, et al., "Hysteroscopic Implantation of Uterotubal Junction Blocking Devices", *Advances in Female Sterilization Techniques*, 1976, Sciarra, et al., Eds., Harper & Row, New York, pp. 169-175.
- J.F. Huka & K.F. Omran, "Ch. 27: Cauterization for Tubal Sterilization," *Human Sterilization* (Ralph Richart et al., eds. 1972).
- Jay Cooper & Richard Houck, "Ch. 33: Study Protocol, Criteria, and Complications of the Silicone Plug Procedure," *Female Transcervical Sterilization* (Gerald Zatuchni, M.D. et al., eds., Harper & Row 1983).
- Jay M. Cooper, "Hysteroscopic Sterilization," *Clinical Obstetrics and Gynecology*, vol. 35, No. 2 (Jun. 1992).
- Kerin, J.F., "New Methods for Transcervical Cannulation of the Fallopian Tube," *International Journal of Gynecology and Obstetrics* 51 Suppl. 1 (1995) pp. S29-S39.
- Leonard, Fred "Ch. 14: Polymer Implants," *Female Sterilization* (Ralph Richart et al., eds. 1972).
- Luukkainen, Tapani et al., "15: Five Years' Experience with the Nova-T and T-Cu IUDs," *Intrauterine Contraception* (Gerald Zatuchni et al., 1984).
- Malinak, Russell, M.D. et al., "Oviduct Occlusion Following Implantation of Proplast," *Advances in Female Sterilization Techniques* (John Sciarra et al., eds. Harper & Row 1976).
- Manganiello, Paul D. et al., "A Bipolar Radiofrequency Catheter Fails to Occlude a Feline Uterine Horn: A Model for Fallopian Tube Occlusion," *The Journal of the American Association of Gynecologic Laparoscopists*, vol. 5, No. 3 (Aug. 1998).
- Medical News, "Hysteroscope simplifies sterilization," *J. of Am. Med. Assn.*, vol. 225, No. 6 (Aug. 6, 1973).
- Neuwirth, Robert S. et al., "Hysteroscopic Sterilization," *Hysteroscopic Sterilization* (John Sciarra et al. eds., 1974).
- PCT Notification of Transmittal of International Preliminary Examination Report, PCT/US98/20031 dated Jun. 30, 2000, 5 pages.
- PCT Notification of Transmittal of the International Preliminary Examination Report, PCT/US96/07486 dated Sep. 8, 1997.
- PCT Notification of Transmittal of the International Search Report or the Declaration PCT/US96/07483 dated Sep. 5, 2006, 5 pages.
- PCT Notification of Transmittal of the International Search Report or the Declaration PCT/US96/07486 dated Sep. 5, 1996, 5 pages.
- PCT Notification of Transmittal of the International Search Report, PCT/US98/20031 dated Jan. 20, 1999, 5 pages.
- PCT Written Opinion PCT/US96/07483 dated Jun. 20, 1997, 4 pages.
- PCT Written Opinion PCT/US96/07486 dated May 19, 1997, 4 pages.
- PCT Written Opinion PCT/US98/20031 dated Aug. 31, 1999, 4 pages.
- Richard Houck & Jay Cooper, "Hysteroscopic Tubal Occlusion With Formed-In-Place Silicone Plugs: A Clinical Review," *Obst. & Gyn.*, vol. 62, No. 5 (Nov. 1983).
- Richart et al., "Evaluation of Polymer Flock and Metal Alloy Intra-Tubal Device in Pigtail Monkeys", *Contraception*, 1978, 18(5):459-468.
- Risque, Francisco, et al., "Transcervical Tubal Cannulation, Past, Present, and Future," *Fertility and Sterility*, (1993) pp. 211-226.
- Robert Neuwirth, Richard Levine, and Ralph Richart, "Hysteroscopic tubal sterilization," *Am. J. of Obst. and Gyn.*, vol. 116, No. 1 (May 1, 1973).
- Schmitz-Rode, Thomas et al., "Experimental Nonsurgical Female Sterilization: Transcervical Implantation of Microspindles in Fallopian Tubes," *Journal of Vascular and Interventional Radiology*, vol. 5, No. 6 (Nov.-Dec. 1994).
- Sciarra, "Heteroscopic Approaches for Tubal Closure", *Research Frontiers in Fertility Regulation*, 1980, Zatuchni, et al., Eds. Harper & Row, New York, pp. 270-286.
- Sonmez et al., "Sterilization with fibrin sealant in a rabbit uterine horn model," *Am J Obstet Gynecol.*, vol. 177, issue 3, 1997, pp. 573-578.
- Sugimoto, Osamu, "Hysteroscopic Sterilization by Electrocoagulation," *Hysteroscopic Sterilization* (John Sciarra et al., eds., 1973).
- Swope, C.H. "Ch. 23: Production of Clinically Useful Interactions of Laser Radiation With Tissue," *Human Sterilization* (Ralph Richart et al., eds. 1972).
- Theodore Reed & Robert Erb, "Hysteroscopic Tubal Occlusion With Silicone Rubber," *Obst. & Gyn.*, vol. 61, No. 3 (1983).
- Thompson, Horace et al., "Evaluation of Experimental Methods of Occluding the Uterotubal Junction," *Female Sterilization: Prognosis for Simplified Outpatient Procedures* (Gordon Duncan et al, eds. 1972).
- V. Rimkus & K. Semm, "Hysteroscopic Sterilization—a Routine Method?" *Int'l. J. Fertility* vol. 22 (1977).
- Vancaillie, et al. "A New Method of Transcervical Female Sterilization: Preliminary Results in Rabbits," *Fertility and Sterility* vol. 51, No. 2, Feb. 1989, pp. 335-338.
- Wilson, E.W., "Sterilization" *Baillière's Clinical Obstetrics and Gynecology*, vol. 10, No. 1, Apr. 1996, pp. 103-119.
- Wilson, E.W., "The Evolution of Methods for Female Sterilization," *International Journal of Gynecology and Obstetrics* 51 Suppl. 1 (1995) pp. S3-S13.
- Zipper, J. et al., "Suppression of fertility by intrauterine copper and zinc in rabbits," *Am. J. of Obstetrics and Gynecology* (Oct. 15, 1969).
- Sciarra, J.J., et al., eds., *Advances in Female Sterilization Techniques*, Harper & Row, Publishers, 1976, Title page and Table of Contents are enclosed herewith, pp. 169-181, 186-189.
- Stephoe, P.C., "The Potential Use of Intratubal Stents for Reversible Sterilization," *Laparoscopy*, pp. 91-99, circa 1976.
- Brueschke, E.E., et al. "Transcervical tubal occlusion with a steerable hysteroscope: Implantation of devices into extirpated human uteri," *Am. J. Obstet. Gynecol.* vol. 127, No. 2, pp. 118-124, 1977.
- Brundin, J., Transcervical sterilization in the human female by hysteroscopic application of hydrogelic occlusive devices into the intramural parts of the Fallopian tubes: 10 years experience of the P-block, *European Journal of Obstetrics & Gynecology and Reproductive Biology*, vol. 39, pp. 41-49, 1991.
- Complete Chinese-to-English translation of Chinese Patent Publication No. CN 1047447A.
- Conceptus Annual Report (1995) pp. 3, 5, 7, 9, 13-14 and 22.
- Conceptus Annual Report (1996) pp. x, 3, 9 and 13-14.
- Erb, R.A. et al. "Hysteroscopic Oviductal Blocking with Formed-in-Place Silicone Rubber Plugs," *The Journal of Reproductive Medicine*, pp. 65-68, Aug. 1979.
- Gordon, A.G., et al., *Atlas of Gynecologic Endoscopy*, Mosby-Wolfe Press, 2nd Edition, 1995 (Title page and Table of Contents are enclosed herewith).

Gupta, D.N. et al. "Antifertility Effect of an Intrafallopian Tubal Copper Device," *Indian J. Exp. Biol.*, vol. 14, pp. 316-319, May 1976.  
Hamou, J. et al. "Hysteroscopic Reversible Tubal Sterilization," *ACTA Europaea Fertilitatis*, vol. 15, No. 2, 1984.  
Reed, T.P., et al., "Tubal Occlusion with Silicone Rubber," *The Journal of Reproductive Medicine*, pp. 25-28, Jul. 1980.  
Ross, P.L. et al., "Transcatheter Tubal Sterilization in Rabbits," *Investigative Radiology*, vol. 29, No. 5, pp. 570-573, 1994.

Quinones et al., "Hysteroscopic Sterilization", *Int. J. Gynaecol. Obstet.*, 1976, 14:28-34.

Quinones, Rodolfo et al., "Tubal Electrocoagulation Under Hysteroscopic Control," *Hysteroscopic Sterilization* (John Sciarra et al., eds. 1973).

\* cited by examiner




FIG. 1.




FIG. 2.




FIG. 3.



FIG. 4.




FIG. 5.




FIG. 8.




FIG. 6.




FIG. 7.




FIG. 9.




FIG. 10.



FIG. 11A.




FIG. 11B.




FIG. 11C.




FIG. 11D.




FIG. 12A.




FIG. 12B.



FIG. 12C.




FIG. 12D.




FIG. 12E.




FIG. 13.




FIG. 14.




FIG. 14A.




FIG. 14B.




FIG. 14C.




FIG. 14D.




FIG. 14E.




FIG. 14F.




FIG. 14G.








FIG. 14H.






FIG. 15E.




FIG. 16.







FIG. 17.






FIG. 19A.









FIG. 19B.



**OCCLUSION DEVICES AND METHODS****CROSS-REFERENCES TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 12/908,756 filed on Oct. 20, 2010, now U.S. Pat. No. 8,171,936 which is a continuation of U.S. patent application Ser. No. 10/600,298 filed on Jun. 20, 2003, now abandoned, which is a continuation-in-part of U.S. patent application Ser. No. 09/093,835, filed Jun. 8, 1998, now U.S. Pat. No. 6,705,323, which claims the benefit of priority from U.S. Provisional Application No. 60/059,861, filed Sep. 24, 1997, and is also a continuation-in-part of U.S. patent application Ser. No. 08/475,252 filed Jun. 7, 1995, now abandoned, and a continuation-in-part of U.S. patent application Ser. No. 08/474,779 filed Jun. 7, 1995, now U.S. Pat. No. 6,176,240. The full disclosures of U.S. patent application Ser. Nos. 09/093,835, 60/059,861 and 08/475,252 are incorporated herein by reference.

**BACKGROUND OF THE INVENTION****1. Field of the Invention**

The present invention relates generally to contraception, and more particularly to intrafallopian contraceptive devices and nonsurgical methods for their delivery.

Worldwide demand exists for safe, effective methods of both contraception and permanent sterilization. Although a variety of contraception and sterilization methods are available, all of the existing methods have limitations and disadvantages. Thus, the need for additional safe, low cost, reliable methods of contraception and permanent sterilization, both in developed and less developed countries, is widely recognized.

Many presently available contraception methods require significant user involvement, and user non-compliance results in quite high rates of failure. While the theoretical effectiveness of existing contraceptives, including barrier methods and hormonal therapies, is well established, overcoming user noncompliance to improve overall efficacy has proven difficult.

One form of contraception which is less susceptible to user noncompliance is the intrauterine device (IUD). IUDs have been found to have higher rates of reliability, and are effective for a longer period of time, than most other commercially available contraceptives. Unfortunately, IUDs are also associated with serious infectious complications. For this reason, the use of IUDs within the United States has decreased dramatically. Additionally, IUDs are subject to unplanned expulsion, and must be removed due to excessive pain or bleeding in a percentage of cases, further reducing the acceptance of the IUD as a contraceptive method. Interestingly, the efficacy of copper IUDs appears to be higher than that of non-metallic IUDs. The reason for this has not been fully explained.

Commercially available options for permanent sterilization include fallopian tube ligation and vasectomy. These methods are surgical, are difficult to reverse, and are not available to many people in the world. It is common knowledge that fertilization occurs in the fallopian tubes where the sperm and ovum meet. Tubal ligation avoids this by complete occlusion of the fallopian tubes.

It has previously been proposed to reversibly occlude the fallopian tubes, for example, by in vitro formation of an elastomeric plug, or otherwise anchoring a device on either side of the narrowest region of fallopian tube, called the

“isthmus.” Such fallopian tube occlusion methods appear promising; however, an unacceptably high percentage of the non-surgical devices proposed to date have become dislodged during previous studies. Even where non-surgical intrafallopian devices have remained in place, they have been found to be only moderately effective at preventing conception.

For these reasons, it would be desirable to provide effective, reliable intrafallopian devices for contraception and sterilization. It would be particularly desirable to provide highly effective intrafallopian devices which did not require surgery for placement. It would be especially desirable if such devices and methods allowed easy placement of the device, but were less susceptible to being dislodged than previously proposed non-surgical intrafallopian devices.

**2. Description of the Related Art**

The experimental use of a stainless steel intrafallopian device is described in Transcatheter Tubal Sterilization in Rabbits, Penny L. Ross, RT 29 “Investigative Radiology”, pp. 570-573 (1994). The experimental use of an electrolytically pure copperwire as a surgical contraceptive intrafallopian device in rats was described in “Antifertility Effect of an Intrafallopian Tubal Copper Device”, D. N. Gupta, 14 Indian Journal of Experimental Biology, pp. 316-319 (May 1976).

U.K. Patent Application Pub. No. 2,211,095 describes a uterine screw plug for blocking the fallopian tube. European Patent Application Pub. No. 0,010,812 describes a device for placement in the oviducts having enlargements at either end for anchoring the device. The same device appears to be described in Netherlands Patent No. 7,810,696.

The use of tubal occlusion devices is described in “Hysteroscopic Oviduct Blocking With Formed-in-Place Silicone Rubber Plugs”, Robert A. Erb, Ph.D., et al., The Journal of Reproductive Medicine, pp. 65-68 (August 1979). A formed-in-place elastomeric tubal occlusion device is described in U.S. Pat. No. 3,805,767, issued to Erb. U.S. Pat. No. 5,065,751, issued to Wolf, describes a method and apparatus for reversibly occluding a biological tube. U.S. Pat. No. 4,612,924, issued to Cimber, describes an intrauterine contraceptive device which seals the mouths of the fallopian tubes.

German Patent No. 28 03 685, issued to Brundin, describes a device for plugging a body duct with a device which swells when in contact with a body fluid.

Alternative contraceptive devices are disclosed in co-pending U.S. patent application Ser. No. 08/474,779, the full disclosure of which is herein incorporated by reference.

**SUMMARY OF THE INVENTION**

The present invention provides intrafallopian devices and methods for their placement to prevent conception. The intrafallopian devices of the present invention are transcervically delivered and mechanically anchored within the fallopian tube to provide long term contraception, or alternatively permanent sterilization, without the need for surgical procedures or the risks of increased bleeding, pain, and infection associated with intrauterine devices (IUDs).

The intrafallopian devices of the present invention will often comprise a structure having a lumen-traversing region with a helical outer surface. The helical surface is mechanically anchored by a resilient portion of the structure which is biased to form an enlarged secondary shape, preferably forming distal and proximal anchoring loops. The anchoring loops help prevent the helical outer surface from rotating out of position, and also directly deter axial motion within the fallopian tube. In alternative embodiments, anchoring may be provided by a straight coil which is resiliently deflected by the axial curvature of the tortuous fallopian tube, and a radially

expandable braid, malecott, or some other tubular structure may help affix the device within the fallopian tube.

The use of copper in the intrafallopian device of the present invention improves its efficacy as a contraceptive method. Devices formed from plastically deformable materials, however, are less readily restrained in the fallopian tube. Apparently, the large variation in the actual shape and dimensions of fallopian tubes does not provide reliable anchoring for a pre-formed deformable intrafallopian device. The intrafallopian device of the present invention therefore often comprises a resilient structure, usually a metallic coil, which includes a copper alloy or plating, ideally comprising an alloy including at least 75% copper. The coil material typically includes beryllium, zinc, stainless steel, platinum, a shape memory alloy, such as Nitinol®, or the like. Preferably, the coil is composed of an alloy of beryllium and copper.

Although the present device will generally result in occlusion, it need not completely occlude the fallopian tube to prevent the meeting of the sperm and ovum. Instead, in some embodiments, the presence of the copper on the resilient structure is sufficient to provide effective contraception. Hence, contraception can be provided by disrupting the normal architecture and/or function of the fallopian tube, despite the presence of an open lumen. This concept is referred to herein as “functional occlusion”. As used herein, functional occlusion means that the device, when implanted in the fallopian tube, disrupts the normal architecture and/or functioning of the fallopian tube so as to inhibit fertilization and/or conception.

Conveniently, the present invention further comprises non-surgical placement of such intrafallopian devices by transcervical introduction. The resilient structure is restrainable in a straight configuration, e.g., by use of a corewire, greatly facilitating and reducing the risks of introduction. Thus, the cost and dangers associated with existing surgical contraceptive and sterilization procedures are avoided. The resilient structure will often comprise a coil. In some embodiments, an element is disposed along the coil, and is adapted to incite a tissue reaction in the tubal tissues which inhibits conception. A distal anchor of the coil may be inserted into the ampulla, distal of the isthmus, while a proximal anchor is located in the ostium. These anchors prevent rotation of the device, and also help avoid axial movement. Alternatively, at least one of the anchors may be positioned anywhere past the ostium and within the fallopian tube, while the other extends into the uterus, depending on their length and configuration. Preferably, at least some anchoring is provided along the intramural to isthmus region of the fallopian tube. In some embodiments, electrosurgical attachment of an intraluminal device to a surrounding luminal wall may provide effective anchoring even without loops and other anchoring structures. Electrical current may also be used to decouple the intrafallopian device from the delivery system, typically by electrolytically dissolving a solder bond. Current may also actuate an anchor, such as by releasing a resilient radially expandable tubular structure within the fallopian tube.

The present invention also provides improved contraceptive devices which incite a tissue reaction within the fallopian tube to prevent conception. This group of intrafallopian devices will often make use of a highly flexible coil structure to avoid damaging or penetrating through the delicate tubal tissues. The desired tissue reaction may be the result of the material of intrafallopian device, or may be incited by a coating, a surface treatment, a mechanical interaction between the device and the surrounding tubal wall, or the like. The tissue will often help impede conception by occluding the fallopian tube, by interrupting the transport mechanisms

of the tubal tissues, and/or by restraining the intrafallopian tubal device within the tube. Specific tissue reactions which may provide these intended results include tissue ingrowth into the contraceptive device and/or the tubal lumen, scar tissue formation, sclerosing of the tubal tissues, and the like.

In one aspect, the invention provides a tissue reaction contraceptive device for use in a fallopian tube. The contraceptive device comprises a coil having a proximal end and a distal end and defining an axis therebetween. The coil is axially flexible and has a cross-section suitable for insertion into the fallopian tube. An element disposed along the coil is adapted to incite a tissue reaction in the tubal tissues adjacent the coil so as to inhibit conception.

In some embodiments, the element may promote ingrowth of the tubal tissues into the contraceptive device. For example, the element may include a braided or woven polyester, a micro-porous material or surface treatment, or the like. Alternatively, a sharp edged helical ribbon or other mechanical interaction element may incite the formation of scar tissue, or a surface coating of the coil may sclerose the tubal tissues, exciting formation of tough fibrous connective tissues which interfere with conceptive transport. In many embodiments, the presence of the contraceptive device in combination with the tissue reaction can provide effective contraception without having to rely on total occlusion of the fallopian tube.

In another aspect, the present invention provides a tissue ingrowth contraceptive device for use in a fallopian tube. The contraceptive device comprises a tubular retention structure having a proximal end, a distal end and an axis therebetween. The retention structure is axially flexible, and is insertable within the fallopian tube. A material which can incite ingrowth of the tubal tissue is attached to, and exposed radially from, the retention structure.

In the exemplary embodiment, the retention structure comprises a helical coil in which the ingrowth material is disposed. Such helical coils may optionally be radially expandable within the fallopian tube, thereby allowing the device to accommodate a wide variety of tubal physiologies. The ingrowth material may be in the form of braided or woven fibers of polyester, P.T.F.E., or the like.

In another aspect, the present invention provides a tissue ingrowth contraceptive device for use in a fallopian tube. The contraceptive device comprises a resilient elongate body having a proximal end and a distal end and defining an axis therebetween. A retention structure is disposed along the resilient body. The retention structure is adapted to restrain the resilient body within the fallopian tube. A bond affixes the retention structure to the resilient body. At least one of the resilient body, the retention structure, and the bond comprises a micro-porous material which promotes tissue ingrowth therein.

In another aspect, the present invention provides a contraceptive method comprising transcervically inserting a contraceptive device within a fallopian tube. The device is inserted by resiliently deflecting a distal body of the contraceptive device against a tubal wall, so that the distal body guides the contraceptive device axially along the fallopian tube. A tissue reaction is incited with an element of the contraceptive device in the tubal tissues. This tissue reaction affixes the contraceptive device within the fallopian tube.

The present invention also provides improved contraceptive devices, systems, and methods adapted for use in the widely varying geometry of the fallopian tube. In recognition of the wide variations in tubal physiology, the contraceptive structures of the present invention are radially expandable within the fallopian tube to engage the tubal wall. Surpris-

5

ingly, the contraceptive devices of the present invention will often make use of tubular structures such as resilient helical coils. Such tubular devices will often effect contraception by disrupting the architecture and/or transport mechanisms of the tubal tissues, rather than relying entirely on total blockage of the tube. The passages through the tubular contraceptive devices of the present invention may optionally be occluded by promoting tissue ingrowth within the device, for example, by including woven or braided polyester fibers within a helical coil. Regardless, such tubular retention structures are capable of radially expanding against tubal walls throughout a wide range of tubal sizes to safely anchor the contraceptive device, without having to resort to protruding barbs or the like.

In one aspect, the present invention provides a contraceptive device for use in fallopian tube having a tubal wall. The contraceptive device comprises a tubular retention structure having a proximal end, a distal end, and an axis therebetween. The retention structure is radially expandable in situ from a narrow configuration (in which the retention structure has a first diameter which is suitable for axial insertion into the fallopian tube) so as to define a second, enlarged diameter. The expanded retention structure is adapted to engage the surrounding tubal wall and retain the contraceptive device within the fallopian tube.

In another aspect, the present invention provides a contraceptive device for use in a fallopian tube having a tubal wall. The contraceptive device comprises a conception inhibiting body which defines an axis. A helical coil is disposed about the body. A portion of the helical coil is movable relative to the body so that the helical coil can expand resiliently throughout a range of tubal cross-sectional sizes. Hence, the coil can radially engage the surrounding tubal wall and safely affix the contraceptive device within the fallopian tube.

The present invention also provides intrafallopian contraceptive devices having elongate coils which are substantially straight. Surprisingly, when such straight coils are positioned axially within the tortuous fallopian tubes, the bends imposed on the coil by the fallopian tube can result in resilient anchoring of the coil. Such straight coils are also highly advantageous when advancing the contraceptive device into (and within) the fallopian tube. Straight resilient coils can act as an integral guidewire during transcervical deployment of the device within the fallopian tube, thereby avoiding the delay associated with the sequential use of guidewires, tubal axis catheters, and the like.

The present invention provides an intrafallopian contraceptive device for use in a fallopian tube. The contraceptive device comprises an elongate coil having a proximal end, a distal end, and an axis therebetween. The axis is substantially straight when the coil is at rest, and the coil is axially resilient to facilitate insertion of the body axially into the tube. The device is adapted to be retained within the fallopian tube so as to inhibit conception.

In another aspect, the present invention provides an intrafallopian contraceptive device for use in a fallopian tube. The tube has a tubal wall with a tubal cross-section and an axial curvature. The contraceptive device comprises an elongate body having a proximal end and a distal end and defining an axis therebetween. The body has a cross-section suitable for axial insertion within the tubal cross-section. At least a portion of the body is straighter than the axial curvature of the fallopian tube. The body is sufficiently flexible to deflect against the tubal wall without injuring the tubal wall. The body is also sufficiently resilient to impose an anchoring force against the tubal wall when the straight portion flexes along the axial curvature of the fallopian tube.

6

In another aspect, the present invention provides a contraceptive device for use in a fallopian tube having an axis. The contraceptive device comprises a structure having a proximal end, a distal end, and an axis therebetween. The structure is adapted to provide effective tubal occlusion when disposed substantially coaxially within the fallopian tube. An elongate member is affixed to the occlusion structure. The member extends distally of the occlusion structure and is sufficiently flexible and axially resilient to help guide distal advancement of the occlusion structure within the fallopian tube.

In a contraceptive method provided by the present invention, an elongate resilient body is transcervically inserted into an axially curving fallopian tube so that the fallopian tube imposes an axial bend on the body. The bent body imposes an anchoring force which helps anchor the bent body within the fallopian tube. The body is anchored within the fallopian tube so that the affixed resilient body inhibits conception.

In another aspect, the present invention provides a contraceptive method comprising transcervically inserting an intrafallopian contraceptive device along the fallopian tube by guiding the contraceptive device with a distal guidewire-like structure of the contraceptive device. The device, including at least a portion of the guidewire-like structure, is retained within the fallopian tube so that the device inhibits conception.

In another aspect, the present invention provides a contraceptive kit. The kit comprises an intrafallopian contraceptive device and instructions for its use. The instructions describe and/or set forth the method steps of transcervically introducing the contraceptive device into a fallopian tube and affixing the contraceptive device within the tube. Optionally, a variety of delivery structures may also be provided in the kit, including guidewires, corewires, delivery catheters, and the like.

In yet another aspect, the invention provides an intrafallopian contraceptive system comprising an elongate delivery body having a proximal end and a distal end. A first energy conduit extends therebetween, and an intrafallopian structure near the distal end has a first cross-section. An energy source is coupled to the structure by the first conduit. Energy from the energy source reconfigures the structure to a second cross-section to restrain the structure within a fallopian tube and inhibit conception.

In a final aspect, the invention provides an elongate delivery body having proximal and distal ends with first and second conductors extending therebetween. An intrafallopian contraceptive structure is near the distal end of the delivery body. An electrical power supply can be coupled to the structure by the first and second conductors. This advantageous bipolar arrangement can, for example, allow actuation of a shape-memory alloy structure by transmitting current through at least a portion of the structure from a hand-held battery.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a first embodiment of a contraceptive intrafallopian device according to the present invention.

FIG. 2 illustrates a primary coil used in the contraceptive intrafallopian device of FIG. 1.

FIG. 3 illustrates a secondary coil which has been imposed on a primary coil as used in the contraceptive intrafallopian device of FIG. 1.

FIG. 4 illustrates a corewire for use with the contraceptive intrafallopian device of FIG. 1.

FIG. 5 is a cross-sectional view of a contraceptive delivery system having the contraceptive intrafallopian device of FIG. 1.

FIG. 6 illustrates an alternative embodiment of the present contraceptive intrafallopian device.

FIG. 7 illustrates a primary coil used in the contraceptive intrafallopian device of FIG. 6.

FIG. 8 schematically illustrates a contraceptive delivery system including the contraceptive intrafallopian device of FIG. 6.

FIGS. 9 and 10 illustrate a method of delivery of a contraceptive intrafallopian device according to the present invention.

FIGS. 11 A-D illustrate intrafallopian contraceptive devices having straight primary coils, together with associated delivery devices and systems.

FIGS. 12A-E illustrate a variety of intrafallopian contraceptive devices which are adapted to promote a tissue reaction that enhances the contraceptive efficacy of the device.

FIG. 13 illustrates a method for introducing a dense braid of fiber material into a helical coil of a contraceptive device.

FIGS. 14-14H illustrate helical coils which adapt to varying tubal sizes to enhance retention of the contraceptive device within the fallopian tube.

FIG. 15A-D illustrate cross-sectional views through the fallopian tube before, during, and after delivery of a contraceptive device having a radially expandable helical coil, and also illustrates the enhanced efficacy provided by tissue reactions such as tissue ingrowth into and around the helical coil.

FIG. 15E illustrates the self-guiding capabilities of a contraceptive device having a straight primary coil.

FIG. 16 illustrates a contraceptive delivery system having a detachable distal corewire.

FIG. 17 schematically illustrates a kit including a contraceptive delivery system and instructions for its use.

FIGS. 18A-C schematically illustrate alternative tubular radially expandable retention structures which can mechanically anchor a contraceptive device in the fallopian tube.

FIGS. 19A and B illustrate an intrafallopian contraceptive system in which a hand-held battery electrically actuates the retention structure by transmitting a current which heats a shape-memory alloy of the retention structure.

FIGS. 20A and B illustrate an intrafallopian contraceptive device and method for its use to support a coil comprising copper within the utero-tubal junction.

FIGS. 21 A-C illustrate alternative structures comprising copper and methods for their use to inhibit conception, according to the principles of the present invention.

#### DESCRIPTION OF THE SPECIFIC EMBODIMENTS

The present invention encompasses a contraceptive intrafallopian device which can alternatively be used as both a permanent and a reversible means of contraception. The present contraceptive methods and devices minimize the danger of non-use which has limited the efficacy of prior art contraceptive techniques. Moreover, the location of the present devices within the fallopian tubes provides a reduced risk of the infectious complications, increased bleeding, and pelvic pain associated with intrauterine devices (IUDs). The location and the novel shape of the present intrafallopian device provides significant advantages over IUDs, which have been found to be susceptible to unplanned expulsion and removal due to excessive pain and bleeding. The present invention takes advantage of the increase in effectiveness associated with copper IUDs, providing a resilient structure including copper which may be transcervically positioned without the need for surgery.

Although the present contraceptive method is included within a group of contraceptive techniques generally referred to as fallopian tube occlusion methods, the present invention does not necessarily rely solely on blocking the fallopian tube to prevent fertilization. Instead, contraception is apparently provided by disrupting of ovum transport, the process of fertilization, and/or cleavage of the ovum. While the effect that copper has on these processes is not fully understood, it does appear that copper intrafallopian devices offer potentially significant increases in effectiveness over intrafallopian devices formed of other materials. Contraception may alternatively be provided or enhanced by a spermicidal agent attached to the device. Optionally, the present invention further encompasses devices which promote the growth of tissue within the tube to induce tubal occlusion, further inhibiting conception. In some embodiments, polyester fibers such as Dacron®, Rayon®, or the like, are bonded to the surface of the coil using a polymeric adhesive. The polyester fibers promote increased tissue growth around the coil, thus further reducing the possibility of expulsion of the device from the fallopian tube.

Conveniently, the present resilient structures are adapted to be releasably affixed over a corewire, the corewire restraining the resilient structure in a straight configuration. As the resilient structure has an outer diameter when in the straight configuration which is less than the inner diameter of the fallopian tube, the catheter containing the present intrafallopian device is easily transcervically introduced.

The present invention may be anchored within the isthmus of the fallopian tube, overcoming the unintended expulsion of the device and the resulting failure of the contraceptive method. Such intrafallopian device expulsion has been the single greatest factor limiting the efficacy of easily positioned intrafallopian contraceptive techniques. The present intrafallopian devices are generally elongate resilient structures performed into secondary shapes. These secondary shapes will preferably form anchors proximally and distally of the narrowest portion of the fallopian tube, called the isthmus. The secondary shape preferably has a larger outer diameter than the inner diameter of the isthmus. Anchoring may also be possible with a structure spanning other portions of the tubal lumen, often between the ostial opening and the isthmus.

The present device is generally readily removed by snaring the resilient structure near the proximal end and pulling proximally on the resilient structure, thereby straightening the resilient structure and allowing it to be withdrawn without injuring the fallopian tube. Alternatively, an electrical current is applied to the device after it is positioned within the fallopian tube, providing permanent sterilization. Electrical current might also effect detachment of the device from the delivery system using a system similar to that described in U.S. Pat. No. 5,624,449, the full disclosure of which is incorporated herein by reference. In situ actuation of an anchor might be effected by releasing a resilient structure to expand in situ with a similar mechanism, or by a current induced phase change of a shape memory alloy (for example, causing a straight Nitinol® ribbon to curl within the fallopian tube with a current).

Referring now to FIG. 1, a first embodiment of the present contraceptive intrafallopian device 10 is formed from a resilient primary coil 12. Primary coil 12 has a proximal end 14 and a distal end 16, the latter having an atraumatic endcap 18. Primary coil 12 further includes three portions: a proximal anchor portion 20, a distal anchor portion 22, and a lumen-traversing region 24. Proximal and distal anchors 20, 22 are biased to form anchoring loops 26, as described hereinbelow.

Lumen-traversing region **24** comprises a substantially straight portion of primary coil **12**. A ribbon **28** is wound over the outer surface of primary coil **12** to provide a helical shape. Ribbon **28** includes sharp outer edges **29**, which firmly anchor lumen-traversing region **24** in the fallopian tube wall when torque is applied to intrafallopian device **10**. The ribbon is preferably formed of a high strength biocompatible metal, ideally being stainless steel. The ribbon is attached to primary coil **12** at a proximal joint **30** and a distal joint **32**, which may be formed of solder, heat-shrink tubing, or the like.

Referring now to FIG. **2**, primary coil **12** is most easily formed in a straight configuration as a cylindrical coil or spring, preferably having an outer diameter in the range from 0.005 inch to 0.05 inch, and having a length in the range from 20 mm to 150 mm. Ideally, primary coil **12** has an outer diameter in the range from 0.01 inch to 0.05 inch and a length in the range from 30 mm to 125 mm.

Preferably, primary coil **12** is formed from a beryllium copper alloy wire. Beryllium copper provides the resilience necessary to avoid expulsion of the device, and also provides the increased effectiveness of a copper contraceptive intrafallopian device. Such a beryllium copper wire will typically have a diameter from 0.002 inch to 0.01 inch. To provide the increased efficacy of a copper intrafallopian device, primary coil **12** preferably comprises an alloy including 75% copper. Alternatively, primary coil **12** is formed from a resilient metal, such as stainless steel, platinum, a shape memory alloy, or the like. If such materials are used, primary coil **12** is preferably plated with copper or a copper alloy or otherwise has copper attached.

Primary coil **12** includes a body winding **42** and a thread winding **44**. Body winding **42** is formed with the minimum possible pitch to increase the stiffness of primary coil **12**. Thread winding **44** will typically comprise from 0.1 cm to 2.0 cm adjacent to proximal end **14**, and will have a pitch roughly twice that of body winding **42**.

Referring now to FIG. **3**, the proximal and distal anchors are formed by imposing a bent secondary shape on selected portions of primary coil **12**. The secondary shape preferably comprises loops **26** formed by bending primary coil **12**, and heat treating the primary coil while it is bent. A wide variety of secondary shapes may be used, including sinusoidal curves, alternating loops, or loops separated by straight sections so as to form a "flower coil," as more fully described in co-pending U.S. patent application Ser. No. 08/474,779, the full disclosure of which is herein incorporated by reference. In most cases, the bent secondary shape will have an outer cross-section **46** which is larger than the fallopian tube to provide effective anchoring.

Referring now to FIG. **4**, a corewire **50** for use with intrafallopian device **10** (FIG. **1**) comprises a resilient wire **52** which tapers towards a distal end **54**. Wire **52** is sufficiently stiff to restrain intrafallopian device **10** in a straight configuration, typically comprising stainless steel, platinum, or the like. A short section of coil forms corewire threads **56** attached at threadjoint **58**. Threads **56** match the windings and pitch of threadwindings **44** of primary coil **12**.

Referring now to FIG. **5**, an intrafallopian contraceptive system **60** comprises corewire **50** inserted within a lumen **62** through intrafallopian device **10**. Intrafallopian device **10** is releasably attached by engaging thread windings **44** with threads **56**. Thus, intrafallopian device **10** is disengaged by torquing a proximal end of corewire **50** once intrafallopian device **10** is in position.

Referring now to FIG. **6**, an alternative embodiment of the present intrafallopian device is again formed from a resilient primary coil **112** having a proximal end **114** and a distal end

**116**. The former includes a friction fitting **115**. Primary coil **112** again includes three portions: a proximal anchor portion **120**, a distal anchor portion **122**, and a lumen-traversing region **124**. Proximal and distal anchors **120**, **122** are here biased to form opposed anchoring loops **26**, thereby increasing the relaxed overall cross-section of the proximal and distal anchors. A ribbon **128** is wound over the outer surface of primary coil **112** to provide a helical shape, as described above.

Referring now to FIG. **7**, primary coil **112** comprises a uniform body winding **142**. The secondary shape is imposed on the straight cylindrical coil as opposed loops **126**, or alternatively as multiple loops of a flower coil.

Referring now to FIG. **8**, an intrafallopian contraceptive system using alternative intrafallopian device **100** includes a corewire **152** which tapers towards a distal end **154**. Friction fitting **115** fittingly engages corewire **152**, which restrains primary coil **112** in a straight configuration. A release catheter **164** is slidably disposed over corewire **152** proximally of alternative intrafallopian device **100**, allowing the device to be released by withdrawing corewire **152** relative to the release catheter.

Use of the present contraceptive intrafallopian device will be described with reference to FIGS. **9** and **10**. A uterine introducer cannula **70** is inserted transcervically through a uterus **72** to the region of an ostium **74**. Alternatively, a hysteroscope may be used in place of cannula **70**, or an echogenic and/or radiopaque device might be placed under sonographic or radiopaque guidance.

Intrafallopian contraceptive system **60** is advanced distally of introducer cannula **70** and maneuvered through the fallopian tube, preferably until intrafallopian device **10** extends distally of the isthmus. Optionally, intrafallopian contraceptive system **60** is self-guided, with corewire **52** bent near distal end **54** to assist intraluminal maneuvering. Alternatively, a guide wire and catheter are advanced into the fallopian tube first, and the guide wire is replaced with intrafallopian contraceptive system **60**. In either case, the intrafallopian device will generally be axially positioned with lumen-traversing region **24** within a target region **84** adjacent to isthmus **80**. Preferably, at least one loop of distal anchor **22** is distal of target region **84**, and at least one loop of proximal anchor **20** is proximal of target region **84** to form the distal and proximal anchor bends.

Once intrafallopian device **10** is properly positioned, corewire **50** is torqued to set ribbon **28** in the tubal wall. The corewire may then be unthreaded from intrafallopian device **10** by rotating the corewire in the opposite direction, disengaging threads **56** from thread windings **44**. The corewire is then free to slide proximally, releasing the primary coil. As the distal end of the primary coil is released, a distal anchor bend **90** is formed. Similarly, a proximal loop forms a proximal anchor bend **92**. The anchor bends help to axially restrain the device within the fallopian tube, and also prevent rotation around the helical shape of lumen-traversing region **24**. As seen in FIG. **10**, the loops need not assume their relaxed form to provide effective distal or proximal anchors.

The present invention further encompasses permanent sterilization by passing a current through the corewire to the intrafallopian device prior to withdrawing the corewire. Fallopian tube tissue in contact with the intrafallopian device is desiccated, and thus attached to the present intrafallopian device. This action also causes permanent tubal damage, leading to the formation of scar tissue which encapsulates the intrafallopian device and causes permanent occlusion of the

tubal lumen. Clearly, the corewire/primary coil interface must be conductive to allow the present non-surgical method of permanent sterilization.

The intrafallopian contraceptive methods and devices of the present invention can provide highly effective contraception even when the contraceptive device does not totally occlude the lumen of the fallopian tube. To minimize distention of the delicate tubal tissue, the present invention will often leave some open lumen within the fallopian tube, at least when initially deployed. In fact, these contraceptive devices will often comprise perforate tubular structures having lumens. Nonetheless, contraception can be provided by disrupting the normal architecture and/or function of the fallopian tube, despite the presence of an open lumen. This concept is referred to herein as “functional occlusion”. As used herein, a device which provides functional occlusion means that the device, when implanted in the fallopian tube, disrupts the normal architecture and/or functioning of the fallopian tube so as to inhibit fertilization and/or conception.

The size of an occlusive device required to provide functional occlusion may depend on the material of the device, the position the device is to be deployed within the fallopian tube, the interaction between the device and the surrounding tubal wall, and the like. For example, intrafallopian contraceptive structures which include fibers of polyester may incite ingrowth of the tubal tissues into the device. As a result of this tissue/device interaction, a relatively small device which promotes ingrowth may be capable of providing effective occlusion. In fact, such a device may be capable of providing total occlusion by inciting sufficient ingrowth so that the hyperplastic tubal walls, in combination with the device, block all passage through the tubal lumen. Hence, relatively small, easily inserted structures may effectively inhibit conception without the danger of distending the tubal wall.

One easily inserted intrafallopian contraceptive structure which may be capable of providing effective tubal occlusion is illustrated in FIG. 11A. A straight contraceptive device **200** includes a straight primary coil **202** around which is disposed a secondary helical coil **204** as described above. Secondary coil **204** is affixed to primary, coil **202** at a pair of bonds **206**. As illustrated above in FIG. 6, the secondary helical coil may have an inner surface which is larger than the outer surface of primary coil **202**, which may facilitate embedding the corners of the secondary coil in the surrounding tubular wall. However, unlike the intrafallopian devices described hereinabove, straight device **200** remains substantially straight between a proximal end **208** and a distal end **210** when the primary coil is at rest.

Primary coil **202** will typically be formed from wire having a diameter of between about 0.002 and 0.009 inches, by winding the wire to form a coil having a diameter between about 0.010 and 0.040 inches. Primary coil **202** will often have a length of between 2.9 and 3.5 cm. The ribbon used to form secondary helical coil **204** will generally have a width between about 0.005 and 0.020 inches, and a thickness of between about 0.0005 and 0.005 inches.

In the exemplary embodiment, straight device **200** includes a primary coil **202** having a total length of between about 3.0 and 3.35 cm. The exemplary primary coil **202** is wound from platinum wire, the platinum wire having a thickness of 0.005 inches, which is wound to provide a primary coil having an outer diameter of about 0.018 inches and a length of about 3.0 cm. Secondary coil **204** is formed from a platinum ribbon having a width of 0.012 inches and a thickness of 0.002 inches. Bonds **206** comprise gold solder and secondary coil **204** has a length of about 0.5 to 1.0 cm and an outer diameter

of between about 0.035 to 0.040 inches when affixed to the primary coil **202**. Solder is also used to form an atraumatic tip at distal end **210**.

Referring now to FIGS. 11B and 11C, a self-guiding contraceptive delivery system **212** includes straight contraceptive device **200** and a flexible tip corewire **214**. As described above, threads **216** on flexible tip corewire **214** mate with the proximal end **208** of straight contraceptive device **200**, the threads ideally comprising a stainless steel coil having approximately the same dimensions as primary coil **202** and affixed to the corewire with yet another gold solder joint **206**.

Advantageously, distal end **218** of corewire **214** need not have sufficient stiffness and strength to restrain a coil biased to form a bent secondary shape. As a result, the thickness of corewire **214** may be optimized to enhance the trackability and pushability of self-guided contraceptive system **212**, thereby enhancing the ability of the contraceptive system to act as its own guidewire.

Delivery of the contraceptive device is facilitated by using a corewire having a relatively long, stiff proximal section and a relatively short, flexible section, the flexible section typically being tapered as illustrated. The thickness and material properties of these sections are selected to provide enough column strength to allow corewire **214** to advance straight device **200** within the fallopian tube, but enough flexibility at the distal end of the delivery system for distal end **210** to navigate the tortuous fallopian tube. A relatively thick proximal section also improves the torque transmission capabilities of the wire, particularly for torquing and embedding the outer coil against the tubal wall.

Proximal section **220** of corewire **214** will preferably be flexible enough for delivery through a flexible catheter and/or through the working channel of an endoscope. The corewire will generally comprise a material which resists kinking and resiliently returns to its original shape, ideally comprising a shape memory alloy such as Nitinol® or a treated stainless steel. Such resilience may be tailored to enhance the ability of the delivery system to access the tubal ostium and advance the contraceptive device into the fallopian tube. In some embodiments, corewire **214** will be capable of transmitting heat, electrical current, and/or some other energy which induces scarring, electrocautery, or the like, so as to attach the contraceptive device within the fallopian tube. Alternatively, the transmitted energy may decouple the device from the corewire, for example, by melting a coupler.

In a particularly advantageous aspect, threads **216** of delivery system **200** may be adapted to enhance visualization of the detachment process. For example, a first portion of the threads **222** may be a first color (such as green) while a second portion of the threads **224** may be a second color which contrasts sharply with the first color (such as red). As they are near the proximal end of the device, threads **216** will often be more visible than the remainder of the contraceptive device. The threads may even protrude through the tubal os into the uterus for viewing through the hysteroscope. By visually monitoring highly contrasting colors of the thread portions through the hysteroscope, the attending physician will be provided with direct feedback on the decoupling process. The thread portions may be colored by coating, anodizing, oxidation, polishing, the use of differing materials, or the like. A stripe or other mark may also be provided on the delivery wire to help monitor rotation. Alternative embodiments may use threads having high contrast under imaging.

Still further capabilities may be incorporated into the delivery system. For example, a “smart” delivery device may be able to sense its position within the fallopian tube magnetically, electrically, optically, ultrasonically, or the like. Simi-

larly, the deployed device may incorporate structures which allow the physician to remotely verify the position and presence of the device without having to access the fallopian tube (e.g., using a magnetic sensor, impedance, and/or radio activity).

In the exemplary embodiment, corewire **214** comprises a shape memory alloy such as Nitinol®. Proximal portion **220** of corewire **214** has a thickness of between about 0.018 and 0.040 inches, ideally being about 0.035 cm, and the corewire tapers over a length of about 5.0 cm to a minimum thickness of between about 0.002 and 0.008 inches, typically about 0.003 inches at distal end **218**.

One method for attaching polyester fibers **226** to straight contraceptive device **200** is illustrated in FIG. **11D**. As described above, such polyester fibers promote tissue ingrowth, which can help affix the device within the fallopian tube. Additionally, such tissue ingrowth may also help to further occlude the lumen of the fallopian tube. Fibers **226** are shown tied in loops around the secondary coil, ideally using between about 5 and 7 loops and fiber.

A wide variety of alternative mechanisms may be employed to incite a tissue reaction which enhances the functional occlusion of the intrafallopian contraceptive device. For example, materials such as collagen, hydroxyapatite, solid or fibrous PTFE, or the like may be used. Biodegradable coatings may cause tissue ingrowth or scarring, and then degrade to leave a fully or partially occluded lumen. In some embodiments, the engagement between outer coil **204** and the tubal wall injures the epithelial tissues, and the healing process results in the formation of scar tissues which interfere with the functioning of the fallopian tube.

A variety of alternative ingrowth promoting intrafallopian contraceptive devices are illustrated in FIGS. **12A-E**. Generally, each of these devices includes some element which promotes ingrowth of tubal tissues therein. A porous secondary coil **230** may be formed of a porous metal, ideally comprising a micro-porous shape memory alloy such as Nitinol®. In some embodiments, ingrowth bonds **232** may be formed of, or coated with, a material such as bioglass, ceramics, or the like so as to promote tissue ingrowth, so that the entire device may promote ingrowth. Surface treatments may also encourage ingrowth. For example, blasting a surface with small particulates can create a somewhat divoted and porous texture. Such porous textures at the surface, with micron-sized pores, may produce the desired tissue reaction. Alternative embodiments may include an open cell ingrowth promoting structure, such as the open cell foams used to attach some breast implants.

In some embodiments, discrete bodies **234** may be formed as rings or annular beads using any of the above listed tissue ingrowth materials, coatings, or treatments. Wound, wrapped, or braided fiber material **236** may also be disposed between the primary and secondary coils, the fiber material typically comprising a polyester such as Dacron®, Vicril®, or the like. Dense fiber materials within the device may enhance the reaction and/or ingrowth of the surrounding tubal tissues, and also decreases the amount of open space within the device, thereby minimizing any prosthetic lumen. Fiber material **236** may also be in the form of a thick felt, or may simply be spun with several layers of windings.

Still further alternative ingrowth promoting elements are possible, such as tubular fabric **238** of felt, braided or woven material, or the like. Tubular fabric **238** provides an open conduit at the proximal end of the device to avoid impeding with the removal of the corewire, and the outer diameter of the tubular fabric will preferably be less than the outer diameter of the secondary coil. In some embodiments, simply provid-

ing an internal fabric **240** in the form of a textile mesh or felt inside the primary coil may be sufficient to incite ingrowth of the tubal tissues into the coil, affixing the coil in place and providing functional occlusion of the fallopian tube.

Referring now to FIG. **13**, a particularly advantageous method for producing a contraceptive device having a dense fiber braid **250** is illustrated. Dense fiber braid **250** is initially formed by wrapping several layers of fiber around a mandrel. After about fifteen layers of fiber have been wrapped over the mandrel, the wound fiber is slid off the mandrel, and the windings are processed to form the braid. The braid is affixed to contraceptive device **200** adjacent one of the bonds, and the fiber braid is then wound between the windings of secondary coil **204**. As a result, at least a portion of fiber tube **250** is disposed in the annular space between the primary coil and secondary coil **204**. Often times, some portion of the fiber will also extend radially beyond secondary coil **204**, as illustrated.

The use of dense fiber braid **250** provides a much greater amount of fiber and a more radially compact, easily deployable assembly than a structure which includes loops tied radially around the secondary coil. Such densely packed fiber thereby makes use of an otherwise open space, and the enhanced amount of fiber should provoke a more robust tissue reaction. Specifically, dense fiber braid **250** will have a smaller pore size, which is generally advantageous for tissue ingrowth. This combination of an enhanced tissue reaction, with a less axially open design, would appear to provide significant advantages for functional occlusion of the fallopian tube.

A still further alternative intrafallopian contraceptive device **200'** is illustrated in FIG. **14**. Alternative device **200'** includes several of the same primary structures described hereinabove regarding straight contraceptive device **200**, but makes use of a fiber tube **252** to provide the advantages of high fiber density and a small radial package. In this embodiment, the fiber is again wrapped around a mandrel several times (ideally about 15 times) and then removed as a fiber tube. Tube **252** is slid off the mandrel and onto the primary coil. The tube may be positioned before or after secondary coil **204** is attached at bond **206**, and will generally occupy the annular space between the primary and secondary coils. The ends of tube **252** can be tied to keep the tube in position during delivery.

Alternative contraceptive device **200'** also differs from the previous structures in that secondary coil **204** has a free end **254** which is not affixed to primary coil **202**. As free end **254** can move relative to primary coil **200**, secondary coil **204** can expand radially well beyond bond **206**, and can also be radially compressed to provide a very small outer diameter during delivery of the device. Hence, the diameter of secondary coil **204** in alternative device **200'** provides a highly radially variable tubular structure which can easily adapt to a wide variety of tubal lumen cross-sectional sizes to retain the contraceptive device within the fallopian tube.

A highly radially expandable tubular retention structure has several significant advantages. First, the structure can be inserted in a narrow profile configuration and radially expanded within the fallopian tube to provide a secure anchor with minimal danger of protruding through the delicate tubal wall. Additionally, the stiffness of the helical secondary coil can be tailored to provide the appropriate engagement force and/or damage to the wall tissue so as to provoke the desired tissue reaction, whether it be scar tissue formation, ingrowth, or the like. Torquing of a free ended helical coil may also be used to adjust the outer diameter during delivery.

The enhanced variability in outer diameter provided by an outer coil **204** having a free end **254** can be understood with reference to FIGS. **14A-C**. Generally, outer coil **204** will here have an outer diameter of over about 0.080 mm in its relaxed state, the outer diameter of the secondary coil preferably being biased to form a helix with an outer diameter of about 1.0 mm when at rest, and will ideally be compressible to an outer diameter of 0.1 mm for insertion. Outer coil **204** of alternative device **200'** may be easily radially compressed by drawing free end **254** proximally away from bond **206**, by wrapping the free end around primary coil **202**, or by some combination of both.

As illustrated in FIGS. **14B** and **C**, the device may be restrained in a small diameter configuration by a delivery catheter **256**, by articulatable jaws **258**, or the like. Regardless, secondary coil **204** will generally be restrained until the device is positioned within the fallopian tube, and will then be released in situ by axially withdrawing catheter **256**, articulating jaws **258**, or the like. Still further alternative in situ release mechanisms are possible, such as dissolving or dissipating a crystal or electrolytic coating which radially restrains the secondary coil, a phase change in a shape memory alloy, or the like, as described above. It should be noted that the free ended secondary coil is illustrated in FIGS. **14A-C** without the optional dense fiber tube of FIG. **14A** for clarity. Nonetheless, the enhanced radial variability provided by a free ended helical coil (or by other perforate tubular structures) may be either used alone or combined with other tissue reaction structures described hereinabove to provide functional occlusion and contraception.

Alternative helical retention structures are illustrated in FIGS. **14D** and **14E**. A tapered coil **203** may be advanced distally, either axially or by rotationally threading the device, to embed the structure into a tapering portion of the tubal wall. The device can accommodate a variety of tubal sizes, as it need only be advanced until proper engagement has been achieved. Variable stiffness along the outer coil may be provided by a coil formed with a tapering ribbon **207**, or the like.

Alternative structures for releasably restraining secondary coil **204** are illustrated in FIGS. **14F-H**. In the embodiments of FIGS. **14F** and **G**, corewire **152** is rotationally coupled to primary coil **202**, and hence to the distal portion of secondary coil **204** by bond **206** (see FIG. **14C**). A tab **259** is affixed to a proximal end of secondary coil **204**, the tab preferably protruding radially inwardly from the coil, the tab ideally comprising a small diameter annulus or collar having an axis parallel to the secondary coil axis. Tab **259** is releasably received by a keyhole slot **257** in delivery catheter **256**. The tab is axially restrained in the slot when the tab engages one side of the slot, but is free to slide axially from the slot when rotationally disengaged or pressed against the other side.

Prior to delivery, secondary coil **204** is restrained in a small diameter configuration by engagement between tab **259** and slot **257**. Secondary coil **204** is tightly wound down, so that the secondary coil biases the tab toward the restrained position. The proximal portions of the corewire and delivery catheter can be rotationally affixed to each other (ideally by a Tohey-Borst valve) to restrain the device in the small configuration. This may also prevent distal movement of the contraceptive device from the catheter and corewire.

Once the device is positioned, allowing the proximal portions of the corewire and catheter to rotate relative to each other (by releasing the Tohey-Borst valve or the like), and/or actively rotating one of these structures, can unwind the secondary coil and allow tab **259** to slide axially free of the catheter. Optionally, as shown in FIG. **14G**, an alternative keyhole slot **263** having an angled or radiused proximal sur-

face may be used to urge tab **259** toward a release portion **261** of the slot by pushing the surface distally against the tab.

Still further release mechanisms are possible, including the system illustrated in FIG. **14H**. A proximally inwardly tapering body or brake **265** is affixed to primary coil **202**, and is fittingly received by a tapering receptacle at the distal end of delivery catheter **267** when a proximal portion of secondary coil **204** is disposed therebetween. Secondary coil **204** may optionally be held in its wound-down configuration at the proximal end of the delivery system by a Tohey-Borst valve, and can be released to unwind by moving the catheter proximally relative to corewire **152** (and hence primary coil **202** and body **265**), and/or by releasing the Tohey-Borst valve.

The use of a tubular, radially expandable intrafallopian device, and also the significance of tissue reaction in providing functional occlusion, can be further understood with reference to FIGS. **15A-D**. A lumen **L** of a fallopian tube **F** is largely a potential space, much like a deflated balloon. Tubal wall **W** can expand around structures which are inserted into lumen **L**, such as around catheter **256** which radially restrains a free ended secondary coil **204**. Hence, the size of the irregular luminal cross-section may be measured by the diameter of a device it can accommodate.

Work in connection with the present invention has found that fallopian tubes can vary significantly in inner lumen cross-sectional sizes. The maximum diameter of a device which a fallopian tube can accommodate at its smallest point can range anywhere from 0.2 to 1.5 mm. For devices having a fixed cross-section, relatively large diameters will make the device more difficult to deliver. However, if the device is made too small, it can be more easily ejected from the fallopian tube. While fixed cross-sectional devices may still be effective (for example, by providing a range of different device sizes), the use of a radially expandable tubular structure such as free ended helical coil **204** allows the device to compensate for the substantially anatomical differences between users.

As generally described above, catheter **256** may optionally be positioned by first accessing the fallopian tube with a guidewire, and then advancing the catheter over the positioned guidewire. Alternatively, the catheter and contraceptive device may be advanced distally using the distal end of the primary coil as a guidewire. Regardless, once the contraceptive device is positioned at the desired axial location (generally from adjacent the isthmus to the intraluminal region, but optionally anywhere from the corneal area to adjacent the distal fimbria), catheter **256** is withdrawn proximally while restraining the contraceptive device axially with the proximal end of corewire **214**. As catheter **256** is withdrawn, secondary coil **204** expands radially and engages the surrounding tubal wall **W**, as illustrated in FIG. **15C**. Secondary coil **204** may optionally be torqued against the surrounding tubal wall from the proximal end of corewire **214**, after which the corewire is unthreaded from the contraceptive device and removed.

Although the tissues of the tubal wall protrude between the windings of secondary coil **204**, a significant portion of lumen **L** remains open. Nonetheless, functional occlusion is provided so long as the deployed device adequately interferes with fertilization so as to inhibit conception. Functional occlusion may be enhanced by the formation of scar tissues and the growth of tissues from the tubal wall so as to occlude lumen **L** (ideally both inside and outside of the tubular retention structure), as illustrated in FIG. **15D**. Such scar tissue formation will also aid in anchoring the device.

As can be understood with reference to FIG. **15D** and FIG. **16**, open areas within the contraceptive device along the axis of fallopian tube **F** can present some risk of providing a

passageway for fertilization. To avoid providing a prosthetic lumen defined by the inner surface of primary coil **202** after corewire **214** is removed, a detachable delivery wire **260** is formed in two pieces. Distal delivery wire **264** is coupled to 10 proximal delivery wire **262** by a threaded fastener **266**. Fastener **266** provides column strength to the detachable delivery wire. This allows the distal portion of the delivery wire to remain within the primary coil when the contraceptive device is detached. Clearly, a wide variety of coupling mechanisms might be used. Advantageously, a threaded coupler allows the device to be torqued in one direction and detached by rotating the proximal delivery wire **262** in the other direction, generally as described above.

The use of primary coil **202** (in combination with corewire **214**) as a guidewire can be understood with reference to FIG. **15E**. The good proximal column strength of the corewire and the distally increasing flexibility of the combined corewire and primary coil at the distal end of the delivery device greatly facilitates axially advancing the device within fallopian tube **F**. The ability of the corewire **214** to transmit torque can also help advance the delivery system distally, as well as allowing the user to embed secondary coil **204** into the surrounding tubal wall. As can also be understood with reference to FIG. **15E**, the use of a straight primary coil in a portion of the fallopian tube having significant axial curvature results in resilient engagement of the coil against the tubal wall, and can thereby provide anchoring similar to that described above for pre-bent coils in straight lumens.

Referring now to FIG. **17**, a kit **300** includes contraceptive system **212** (in which straight contraceptive device **200** is mounted on corewire **214**) within a sterile package **302**. Also included in kit **300** are instructions **304**, the sterile package and instructions being disposed in packaging **306**. The instructions may set forth any of the method steps for using a contraceptive system as described hereinabove. Delivery system **212** may be protected by a protective sheath **308**, and other system components described hereinabove may also be included. Also visible in FIG. **17** is the proximal torquable handle **310** of the delivery system.

Instructions **304** will often comprise printed material, and may be found in whole or in-part on packaging **306** or sterile packaging **302**. Alternatively, instructions **304** may be in the form of a recording disk or other computer readable data, a video tape, a sound recording, or the like.

Alternative radially expandable retention structures are illustrated in FIGS. **18A** through **C**. A slotted tube retention structure **320** can shorten and expand within the fallopian tube. In general, such expansion may be the result of external forces (such as actuation of a two part delivery system **322**), or the retention structure may self-expand when released in situ. Forcibly expanded retention structures may have a latching mechanism which prevents collapse when the device is detached from the delivery system in the fallopian tube, and such detachment may be effected by any of the mechanisms described hereinabove.

Still further alternative retention structures may be used in place of helical secondary coil **204** and slotted tube **320**. For example, a Malecott retention structure **324** or a braided filament retention structure **326** might be expanded to engage a surrounding tubal wall. In some cases, tubal anchoring may be enhanced by including two or more retention structures, or by providing small barbs which extend axially and/or radially from the expanded retention structure to prevent axial migration. Preferably, such barbs would be too short to perforate through the tubal wall. A wide variety of alternative radially expandable structures which might be adapted for use as a

retaining structure in the present intrafallopian contraceptive device are described with reference to vascular stents.

An intrafallopian device having a retaining structure comprising a shape memory alloy is illustrated in FIGS. **19A** and **B**. In general, the system applies energy to the contraceptive device so that the device expands from a low profile (for delivery) to a deployed profile so as to hold the device in place. The device may be heated by transmitting current along two electrically isolated conductors to primary coil **202**. Corewire **152** here has an insulating layer **271** and is coupled to a first portion of the coil, while a conductor **269** in delivery catheter **256** is coupled to another portion of the coil. The resistance of the coil to a small current is sufficient to heat and reconfigure the retaining structure. Electrical energy from a common 9-volt hand-held battery within energy source will be sufficient to reconfigure secondary coil **204**, which will generally remain in the deployed configuration at body temperature. Alternative energizing systems may use heated saline or the like.

As described above, copper may enhance the efficacy of an intrafallopian contraceptive device **400**. **A1** illustrated in FIGS. **20A** and **B**, a copper body (for example, in the form of copper coil **402**) may extend proximally into and/or through the utero-tubal junction from the fallopian tube. As can be seen in FIGS. **21A** and **C**, the copper may alternatively be in the form of copper beads **404**, which may be used to form bonds, ingrowth structures, or the like. The copper may be in the form of a plating **406** over a core material **408** for use in the primary coil, secondary coil, or the like.

The release rate of copper is often closely related to the surface area of copper on the device. A total copper surface area over 100 mm<sup>2</sup>, and most often in a range from about 300 mm<sup>2</sup> to about 400 mm<sup>2</sup> will be preferred to provide contraception.

The total volume of copper will affect the duration of the enhanced efficacy the copper provides. To provide lifelong contraception, we should provide sufficient copper for about 25 years (based on the fertility life of a woman). For an exposed copper surface area of 400 mm<sup>2</sup>, average copper release rates may be about 25 micrograms per day, based on intrauterine device studies. To allow our intrafallopian contraceptive devices to release copper at this rate for 25 years, we will preferably include at least 0.23 grams or 25.6 mm<sup>3</sup> of total copper. To provide a reasonable safety factor, a 25-year device may include at least about 0.34 grams or 38.4 mm<sup>2</sup> of copper volume. These quantities may be provided by each device, or by two devices (in the left and right fallopian tubes) in combination. Similar calculations may be performed for year devices (using the same exposed area and at least 1/5 of the above volume), or to adjust for differing release/areal efficacy resulting from the copper structures being carried in different regions of the fallopian tubes.

In conclusion, the present invention provides a contraceptive intrafallopian device which may be positioned without surgery. While the above is a complete description of the preferred embodiments of the invention, various alternatives, modifications, and equivalents may be used. For example, a wide variety of secondary shapes, including open loops, continuous bends, sinusoidal curves, or the like, may be imposed on the primary coil. Additionally, aspects of these intrafallopian contraceptive devices which are described separately may often be combined (for example, a self-guiding device may also promote ingrowth to affix the device in the fallopian tube). Therefore, the above description should not be taken as limiting the scope of the invention, which is defined instead solely by the appended claims.

## 19

What is claimed is:

1. An occlusion device comprising:  
an inner coil;  
an element which supports tissue ingrowth positioned  
around the inner coil; and  
an outer coil affixed to the inner coil and positioned around  
the inner coil and the element which supports tissue  
ingrowth.
2. The occlusion device of claim 1, wherein a body winding  
pitch of the outer coil is greater than a body winding pitch of  
the inner coil.
3. The occlusion device of claim 1, wherein the element  
comprises a polymer.
4. The occlusion device of claim 1, wherein the inner coil  
comprises platinum.
5. The occlusion device of claim 4, wherein the inner coil  
is formed from a wire having a diameter between about 0.002  
and 0.009 inches.
6. The occlusion device of claim 4, wherein the inner coil  
has a diameter between about 0.010 and 0.040 inches.
7. The occlusion device of claim 1, wherein the outer coil  
comprises platinum.
8. The occlusion device of claim 1, further comprising an  
atraumatic tip at a distal end of the inner coil.
9. The occlusion device of claim 1, wherein the inner coil  
is longer than the outer coil.

## 20

10. A method of forming an occlusion device comprising:  
positioning an element which supports tissue ingrowth  
around an inner coil; and  
affixing an outer coil to the inner coil such that the outer  
coil is positioned around the inner coil and the element  
which supports tissue ingrowth.
11. The method of claim 10, further comprising winding  
the outer coil over the inner coil and the element.
12. The method of claim 10, further comprising forming an  
atraumatic tip at a distal end of the inner coil.
13. The method of claim 10, wherein the element com-  
prises a polymer.
14. A method for occluding a body lumen comprising:  
advancing a catheter to a target region within an body  
lumen; and  
deploying an occluding device from the catheter at the  
target region of the body lumen, wherein the occluding  
device comprises:  
an inner coil;  
an element which supports tissue ingrowth positioned  
around the inner coil; and  
an outer coil affixed to the inner coil and positioned  
around the inner coil and the element which supports  
tissue ingrowth.
15. The method of claim 14, further comprising accessing  
the body lumen with a guidewire, and then advancing the  
catheter over the guidewire.

\* \* \* \* \*