



(51) International Patent Classification:

C10G 69/06 (2006.01) C10G 3/00 (2006.01)
C10G 69/12 (2006.01)

(21) International Application Number:

PCT/EP2016/061105

(22) International Filing Date:

18 May 2016 (18.05.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15168583.1 21 May 2015 (21.05.2015) EP

(71) Applicant: NESTE OYJ [FI/FI]; Keilaranta 21, 02150 Espoo (FI).

(72) Inventors: HAKOLA, Maija; c/o NESTE OYJ, Keilaranta 21, Espoo 02150 (FI). NYMAN, Tomi; c/o NESTE OYJ, Keilaranta 21, 02150 Espoo (FI).

(74) Agent: TBK; Bavariaring 4 - 6, 80336 Munich (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD FOR PRODUCING BIO HYDROCARBONS BY THERMALLY CRACKING A BIO-RENEWABLE FEEDSTOCK CONTAINING AT LEAST 65 WT.% ISO-PARAFFINS

FIG. 1



(57) Abstract: The present invention relates to a method of producing biohydrocarbons comprising the steps of (1) providing an isomeric raw material obtained from a bio-renewable feedstock, preferably by deoxygenation, hydrodeoxygenation, hydrotreatment or hydrocracking, and containing at least 65wt.% iso-paraffins, and (2) thermally cracking the isomeric raw material to produce biohydrocarbons at a temperature (coil outlet temperature) of at most 825°C. The biohydrocarbons can further be polymerized to obtain bio-polymers such as polyolefins, polypropylene, polyethylene or copolymers such as polyethylene terephthalate. The invention further relates to biohydrocarbons obtainable by the method.

Description

METHOD FOR PRODUCING BIO HYDROCARBONS BY THERMALLY CRACKING A
BIO-RENEWABLE FEEDSTOCK CONTAINING AT LEAST 65 WT.% ISO-PARAFFINS

5 **Technical Field**

The present invention relates to a method of producing biohydrocarbons. Further, the invention relates to biohydrocarbons obtainable by the methods of the invention and to a method of producing polymers.

10 **Background of the Invention**

Production of biohydrocarbons from biomass is of increasing interests since they are produced from a sustainable source of organic compounds. Such hydrocarbons are valuable in the chemical industry as base materials for several processes, in particular as monomers or monomer precursors in
15 polymer chemistry.

Biopolymers are of great worldwide interest as they could give a sustainable alternative to traditional fossil based polymers (e.g. PE, PP, PET, ABS). However, finding a biopolymer with properties which are comparable to
20 those of traditional polymers is very challenging. So far, large scale applications have been created only for polylactic acid (PLA). Replacing traditional polymers is not easy, as their product properties are rather unique, the processing of the polymers is highly developed and the processing machinery cannot be easily applied to novel polymers as such.

25

US 2012/0053379 A1 discloses a method of producing biohydrocarbons using catalytic deoxygenation of tall oil components and steam cracking a liquid fraction derived from the deoxygenation step.

30 **Summary of Invention**

The present invention was made in view of the above-mentioned problems and it is an object of the present invention to provide an improved process for producing bio-renewable materials (biohydrocarbons) offering a wide range of applications.

35

In brief, the present invention relates to one or more of the following items:

1. A method for producing biohydrocarbons, the method comprising:

a step of providing an isomeric raw material obtained from a bio-renewable
5 feedstock and containing at least 65 wt.-% iso-paraffins, and

a cracking step of thermally cracking the isomeric raw material to produce
biohydrocarbons,

wherein the thermal cracking in the cracking step is conducted at a
temperature (coil outlet temperature COT) of at most 825°C.

2. The method according to item 1, wherein the isomeric raw material
contains at least 68 wt.-%, preferably at least 70 wt.-%, more preferably at
least 75 wt.-%, more preferably at least 80 wt.-%, more preferably at least 85
15 wt.-%, more preferably at least 90 wt.-% iso-paraffins.

3. The method according to item 1 or 2, wherein the thermal cracking in
the cracking step is conducted at a temperature (coil outlet temperature COT)
of at most 820°C, preferably at most 810°C, preferably at most 800°C, at
most 790°C, or at most 780°C.

4. The method according to any one of the preceding items, wherein the
thermal cracking in the cracking step is conducted at a temperature (coil
outlet temperature COT) of at least 700°C, preferably at least 720°C, at least
740°C, at least 750°C, or at least 760°C.

5. The method for producing biohydrocarbons according to any one of the
preceding items, wherein the step of providing the isomeric raw material
comprises a preparation step of preparing a hydrocarbon raw material from
the bio-renewable feedstock, and optionally an isomerization step of
30 subjecting at least straight chain hydrocarbons in the hydrocarbon raw
material to an isomerization treatment to prepare the isomeric raw material.

6. The method according to item 5, wherein the preparation step comprises
a step of deoxygenating the bio-renewable feedstock.

7. The method according to item 6, wherein the step of deoxygenating the bio-renewable feedstock is a hydrotreatment step.

5 8. The method according to item 6 or 7, wherein the step of deoxygenating the bio-renewable feedstock is a hydrodeoxygenation step.

10 9. The method according to any one of items 5 to 8, wherein the preparation step comprises a step of hydrocracking hydrocarbons in the hydrocarbon raw material.

10

10. The method according to any one of the preceding items, wherein the bio-renewable feedstock comprises at least one of vegetable oil, vegetable fat, animal oil and animal fat and is subjected to hydrotreatment before the cracking step.

15

11. The method according to any one of the preceding items, wherein the isomeric raw material comprises at least one of a diesel range fraction and a naphtha range fraction and at least the diesel range fraction and/or the naphtha range fraction is subjected to thermal cracking.

20

12. The method according to item 11, wherein only the diesel range fraction and/or the naphtha range fraction, preferably only the diesel range fraction, is subjected to thermal cracking.

25 13. The method according to any one of the preceding items, wherein the isomeric raw material is preferably selected from one of fractions A and B, wherein

30 Fraction A comprises more than 50 wt.-%, preferably 75 wt.-% or more, more preferably 90 wt.-% or more of C10-C20 hydrocarbons (based on the organic components), the content of even-numbered hydrocarbons in the C10-C20 range (i.e. C10, C12, C14, C16, C18 and C20) being preferably more than 50 wt.-%, and the fraction A containing 1.0 wt.-% or less, preferably 0.5 wt.-% or less, more preferably 0.2 wt.-% or less aromatics, and less than 2.0, preferably 1.0 wt.-% or less, more preferably 0.5 wt.-% or less of olefins, and

Fraction B comprises more than 50 wt.-%, preferably 75 wt.-% or more, more preferably 90 wt.-% or more of C5-C10 hydrocarbons (based on the organic components), and the fraction B containing 1.0 wt.-% or less, preferably 0.5 wt.-% or less, more preferably 0.2 wt.-% or less aromatics, and less than 2.0, preferably 1.0 wt.-% or less, more preferably 0.5 wt.-% or less of olefins.

14. The method according to any one of the preceding items, wherein the isomeric raw material contains at least 70 wt.-% iso-paraffins.

15. The method according to any one of the preceding items, wherein the isomeric raw material contains at most 1 wt.-% oxygen based on all elements constituting the isomeric raw material, as determined by elemental analysis.

16. The method according to any one of the preceding items, wherein the thermal cracking in the cracking step comprises steam cracking.

17. The method according to item 16, wherein the steam cracking is performed at a flow rate ratio between water and the isomeric raw material (H_2O flow rate [kg/h] / iso-HC flow rate [kg/h]) of 0.05 to 1.20.

18. The method according item 17, wherein the flow rate ratio between water and the isomeric raw material is at least 0.10, preferably at least 0.20, more preferably at least 0.25, even more preferably at least 0.30.

19. The method according to item 16 or 17, wherein the flow rate ratio between water and the isomeric raw material is at most 1.00, preferably at most 0.80, more preferably at most 0.70, at most 0.60, or at most 0.50.

20. The method according to any one of the preceding items, wherein the biohydrocarbons comprise at least 15 wt.-% propene.

21. The method according to any one of the preceding items, wherein the biohydrocarbons comprise at least 16 wt.-%, preferably at least 17 wt.-%,

preferably at least 18 wt.-%, preferably at least 19 wt.-%, preferably at least 20 wt.-%, preferably at least 21 wt.-% propene.

22. A method for producing biohydrocarbons, the method comprising:

5 a preparation step of preparing a hydrocarbon raw material from a bio-renewable feedstock,

an isomerization step of subjecting at least straight chain hydrocarbons in the hydrocarbon raw material to an isomerization treatment to prepare an isomeric raw material, and

10 a cracking step of thermally cracking the isomeric raw material to produce biohydrocarbons, wherein the thermal cracking in the cracking step is conducted at a temperature (coil outlet temperature COT) of at most 825°C.

23. The method according to item 22, wherein the isomeric raw material
15 contains at least 65 wt.-%, preferably at least 68 wt.-% iso-paraffins.

24. The method according to item 22 or 23, wherein the isomeric raw material contains at least 70 wt.-%, preferably at least 75 wt.-%, preferably at least 80 wt.-%, more preferably at least 85 wt.-%, most preferably at least
20 90 wt.-% iso-paraffins.

The additional features of items 2 to 21 are applicable to the method of any one of items 22 to 24 as well.

25. A method of producing a polymer, comprising producing biohydrocarbons according to the method of any one of items 1 to 24, optionally purifying and/or chemically modifying at least a part of the biohydrocarbons to provide biomonomers, and polymerizing the biomonomers to obtain a polymer.

26. The method according to item 25, wherein the polymer is a polyolefin, such as polypropylene and polyethylene, or a copolymer comprising propylene units and/or polyethylene units, such as polyethylene terephthalate (PET), or a derivative thereof.

27. The method according to item 25 or 26, wherein the method employs at least 50 wt.-%, preferably at least 80 wt.-%, more preferably at least 90 wt.-%, more preferably at least 95 wt.-%, more preferably more than 99 wt.-%, even more preferably 100 wt.-% of monomers derived from bio-renewable raw materials, relative to all monomers constituting the polymer.

28. The method according to any one of items 25 to 27, wherein the method further comprises forming an article, such as a film, beads, or a molded article from the polymer.

29. A mixture of biohydrocarbons obtainable by the method according to any one of items 1 to 24.

Brief Description of Drawings

Figure 1 shows a laboratory scale steam cracking setup used in the Examples of the invention.

Figure 2 shows a GC×GC set-up (cf. Beens, J.; Brinkman, U. A. T., Comprehensive two-dimensional gas chromatography-a powerful and versatile technique. Analyst 2005, 130, (2), 123-127).

Figure 3 shows a GC×GC output in a 2D (grayscale) plot, in a 2D contour plot and in a 3D plot, respectively (cf. Adahchour, M.; Beens, J.; Vreuls, R. J. J.; Brinkman, U. A. T., Recent developments in comprehensive two-dimensional gas chromatography (GC×GC) II. Modulation and detection. Trends in Analytical Chemistry 2006, 25, (6), 540-553).

Figure 4 shows reference components for GC×GC analysis

Detailed description of the invention

The present invention relates to a method of producing biohydrocarbons, the method comprising thermally cracking an iso-paraffin composition (in the following: isomeric raw material) having a high content of iso-paraffins. The isomeric raw material may be obtained by isomerization of a hydrocarbon raw material derived from a bio-renewable feedstock.

In general, the present invention relates to a method of producing hydrocarbons derived from a bio-renewable feedstock (biohydrocarbons), thus

contributing to environmental sustainability of industry depending on petrochemical products, specifically polymer industry and fuel industry. The product resulting from the method of the invention preferably has a high content of polypropylene.

5

The present invention provides a method for producing biohydrocarbons, the method comprising a step of providing an isomeric raw material having a high iso-paraffin content, and a cracking step of thermally cracking the isomeric raw material at relatively low temperature.

10

The isomeric raw material preferably contains at least 65 wt.-%, more preferably at least 68 wt.-%, further preferably at least 70 wt.-%, at least 75 wt.-%, at least 80 wt.-%, at least 85 wt.-%, or at least 90 wt.-% iso-paraffins.

15

The higher the amount of iso-paraffins, the higher the propylene yield in the thermal cracking step, which is of particular value in polymer chemistry. Therefore, it is particularly preferable that the isomeric raw material preferably contains at least 70 wt.-% iso-paraffins.

20

Using the method of the present invention, it is possible to convert a bio-renewable feedstock into a petrochemical raw material containing a high amount of propylene (propene) as well as ethylene (ethene) and BTX (benzene, toluene, xylenes) which are particularly suited for further production of polymer materials. As a matter of course, other product components are useful as well, e.g. as solvents, binders, modifiers or in fuel industry.

25

In the present invention, iso-paraffins are branched alkanes having a carbon number of preferably at most C₂₄, while n-paraffins are straight-chain alkanes having a carbon number of preferably at most C₂₆.

30

The specific method steps employed in the present invention and the intermediate and end products resulting from these method steps will be explained in more detail below. However, the present invention is not limited to the below preferred embodiments.

35

Bio-renewable feedstock

In the present invention, the bio-renewable feedstock may be derived from any bio-renewable source, such as plants or animals, including fungi, yeast, algae and bacteria, wherein the plants and the microbial source may be gene-manipulated. In particular, the bio-renewable feedstock preferably may comprise fat, such as vegetable fat or animal fat, oil (in particular fatty oil), such as vegetable oil or animal oil, or any other feedstock that can be subjected to biomass gasification or BTL (biomass to liquid) methods. The bio-renewable feedstock may be subjected to an optional pre-treatment before preparation of a hydrocarbon raw material or of the isomeric raw material. Such pre-treatment may comprise purification and/or chemical modification, such as saponification or transesterification. If the bio-renewable raw material is a solid material, it is useful to chemically modify the material so as to derive a liquid bio-renewable feedstock.

Preferably, the bio-renewable feedstock comprises at least one of vegetable oil, vegetable fat, animal oil and animal fat. These materials are preferred, since they allow providing a feedstock having a predictable composition which can be adjusted as needed by appropriate selection and/or blending of the natural oil(s) or fat(s).

Isomeric raw material

The isomeric raw material of the present invention contains at least 65 wt.-%, more preferably at least 68 wt.-%, further preferably at least 70 wt.-%, or at least 75 wt.-% iso-paraffins. Further the content may be at least 80 wt.-%, at least 85 wt.-%, or at least 90 wt.-% iso-paraffins. The higher the iso-paraffin content of the isomeric raw material, the higher the amount of propylene resulting from thermal cracking (steam cracking). In the present invention, the content of iso-paraffins in the isomeric raw material is determined relative to all organic material which is fed to the cracker (i.e. relative to all organic material in the isomeric raw material). The content of iso-paraffins may be determined using GCxGC analysis, as explained in the Examples, or by any other suitable method.

In general, any isomeric raw material as defined above can be used in the present invention. Nevertheless, two specific iso-paraffin fractions (A and B) are to be mentioned, which provide particularly desirable product distribution and which are favorable in view of HSE (health, environment, safety).

5

Fraction A comprises more than 50 wt.-%, preferably 75 wt.-% or more, more preferably 90 wt.-% or more of C10-C20 hydrocarbons (based on the organic components). The content of even-numbered hydrocarbons in the C10-C20 range (i.e. C10, C12, C14, C16, C18 and C20) is preferably more
10 than 50 wt.-%. The fraction A contains 1.0 wt.-% or less, preferably 0.5 wt.-% or less, more preferably 0.2 wt.-% or less aromatics, and less than 2.0, preferably 1.0 wt.-% or less, more preferably 0.5 wt.-% or less of olefins.

Fraction B comprises more than 50 wt.-%, preferably 75 wt.-% or more,
15 more preferably 90 wt.-% or more of C5-C10 hydrocarbons (based on the organic components). The fraction B contains 1.0 wt.-% or less, preferably 0.5 wt.-% or less, more preferably 0.2 wt.-% or less aromatics, and less than 2.0, preferably 1.0 wt.-% or less, more preferably 0.5 wt.-% or less of olefins.

20 In any case, the isomeric raw material preferably contains at most 1 wt.-% oxygen based on all elements constituting the isomeric raw material, as determined by elemental analysis. A low oxygen content of the isomeric raw material (i.e. the organic material fed to thermal cracking) allows carrying out the cracking in a more controlled manner, thus resulting in a more favorable
25 product distribution.

Hydrocarbon raw material and preparation step

The isomeric raw material of the present invention may be provided by isomerizing a hydrocarbon raw material obtained from the bio-renewable
30 feedstock.

Generally, the hydrocarbon raw material may be produced from the bio-renewable feedstock using any known method. Specific examples of a method for producing the hydrocarbon raw material are provided in the European

Patent application EP 1741768 A1. It is also possible to employ another BTL method, such as biomass gasification followed by a Fischer-Tropsch method.

A preparation step of preparing the hydrocarbon raw material preferably comprises a step of deoxygenating the bio-renewable feedstock, since most bio-renewable raw materials have a high content of oxygen which is unsuited for the thermal cracking (preferably steam cracking) step of the present invention. That is, although steam cracking of oxygen-containing bio-renewable raw material was reported before, the product distribution is undesirable and unpredictable. The present invention, on the other hand, allows producing a biohydrocarbon composition which can be readily integrated into the value-added chain of conventional petrochemistry. In the present invention, the deoxygenating method is not particularly limited and any suitable method may be employed. Suitable methods are, for example, hydrotreating, such as catalytic hydrodeoxygenation (catalytic HDO), and catalytic cracking (CC) or a combination of both. Other suitable methods include decarboxylation/decarbonylation reactions either alone or in combination with hydrotreating.

Preferably, the step of deoxygenating the bio-renewable feedstock is a hydrotreatment step, preferably a hydrodeoxygenation (HDO) step which preferably uses a HDO catalyst. This is the most common way of removing oxygen and was extensively studied and optimized. However, the present invention is not limited thereto.

As the HDO catalyst, a hydrogenation metal supported on a carrier may be used. Examples include a HDO catalyst comprising a hydrogenation metal selected from a group consisting of Pd, Pt, Ni, Co, Mo, Ru, Rh, W or a combination of these. Alumina or silica is suited as a carrier, among others. The hydrodeoxygenation step may for example be conducted at a temperature of 100-500 °C and at a pressure of 10-150 bar (absolute).

The step of preparing the hydrocarbon raw material may comprise a step of hydrocracking hydrocarbons in the hydrocarbon raw material. Thus, the chain

length of the hydrocarbon raw material can be adjusted and the product distribution of the biohydrocarbons can be indirectly controlled.

5 The hydrotreatment step and an isomerization step may be conducted in the same reactor.

10 Water and light gases may be separated from the hydrotreated or hydrocracked composition and/or from the isomeric raw material with any conventional means, such as distillation, before thermal cracking. After or along with removal of water and light gases, the composition may be fractionated to one or more fractions, each of which may be used as the isomeric raw material in the thermal cracking step or as the hydrocarbon raw material in the isomerization step. The fractionation may be conducted by any conventional means, such as distillation. Purification and/or fractionation
15 allows better control of product properties.

In the present invention, it is preferable that a bio-renewable feedstock comprising at least one of vegetable oil, vegetable fat, animal oil and animal fat is subjected to hydrotreatment and isomerization to prepare an isomeric
20 raw material comprising at least one of a diesel range fraction (boiling point: 180-360°C) and a naphtha range fraction (boiling point: 30-180°C) and at least the diesel range fraction and/or the naphtha range fraction is then subjected to thermal cracking (steam cracking). Preferably, only the diesel range fraction, only the naphtha range fraction or only a mixture of the diesel
25 range fraction and the naphtha range fraction is subjected to thermal cracking. Most preferably, the diesel range fraction is subjected to thermal cracking. Using these fractions and in particular such fractions derived from oil and/or fat allows good control of the composition of the isomeric raw material and thus of the biohydrocarbons produced by the method of the present invention.

30

Isomerization step

The isomeric raw material of the present invention may be provided by isomerizing a hydrocarbon raw material as described above. In the isomerization step, isomerization is carried out which causes branching of the
35 hydrocarbon chain and results in improved performance of the product oil at

low temperatures. Usually, isomerization produces predominantly methyl branches. The severity of isomerization conditions and choice of catalyst controls the amount of methyl branches formed and their distance from each other and thus influences the product distribution obtained after thermal cracking.

The isomerization step preferably comprises subjecting at least a part of the straight chain alkanes in the hydrocarbon raw material to an isomerization treatment to prepare the isomeric raw material. The straight chain alkanes may be separated from the remainder of the hydrocarbon raw material, subjected to isomerization treatment and then optionally re-unified with the remainder of the hydrocarbon raw material. Alternatively, all of the hydrocarbon raw material may be subjected to isomerization treatment. The isomerization treatment is not particularly limited and is preferably a catalytic isomerization treatment.

It is preferred that only a part of the hydrocarbon raw material is subjected to an isomerization step, preferably the part of the hydrocarbon raw material corresponding to the heavy fraction boiling at or above a temperature of 300°C. In this case, the isomerization step may preferably be combined with a catalytic cracking step. The high boiling point part of the hydrocarbon raw material, after optional catalytic cracking, results mainly in a diesel range fraction after isomerization, leading to improved product distribution.

The isomerization step may be carried out in the presence an isomerization catalyst and optionally in the presence of hydrogen. Suitable isomerisation catalysts contain a molecular sieve and/or a metal selected from Group VIII of the Periodic Table and optionally a carrier. Preferably, the isomerization catalyst contains SAPO-11 or SAPO-41 or ZSM-22 or ZSM-23 or ferrierite and Pt, Pd or Ni and Al₂O₃ or SiO₂. Typical isomerization catalysts are, for example, Pt/SAPO-11/Al₂O₃, Pt/ZSM-22/Al₂O₃, Pt/ZSM-23/Al₂O₃ and Pt/SAPO-11/SiO₂. The catalysts may be used alone or in combination. The presence of hydrogen is particularly preferable to reduce catalyst deactivation. Particularly preferable, the isomerization catalyst may be a noble metal bifunctional

catalyst, such as Pt-SAPO and/or Pt-ZSM-catalyst, which is used in combination with hydrogen.

The isomerization step may for example be conducted at a temperature of 200-500°C, preferably 280-400°C, and at a pressure of 20-150 bar, preferably 30-100 bar (absolute).

The isomerization step may comprise further intermediate steps such as a purification step and a fractionation step.

Incidentally, the isomerization step of the present invention is a step which predominantly serves to isomerize the hydrocarbon raw material composition. That is, while most thermal or catalytic conversions (such as HDO) result in a minor degree of isomerization (usually less than 5 wt.-%), the isomerization step which may be employed in the present invention is a step which leads to a significant increase in the content of iso-paraffins. Specifically, it is preferred that the content (wt.-%) of iso-paraffins is increased by the isomerization step by at least 30 percentage points, more preferably at least 50 percentage points, further preferably at least 60 percentage points, most preferably at least 70 percentage points. To be specific, assuming that the iso-paraffin content of the hydrocarbon raw material (organic material in the liquid component) is 1 wt.-%, then the iso-paraffin content of the intermediate product after isomerization is most preferably at least 71 wt.-% (an increase of 70 percentage points).

An isomeric raw material obtained by an isomerization step as described above can be fed directly to the thermal cracking procedure. In other words, no purification is necessary after the isomerization step, so that the efficiency of the process can be further improved.

Cracking step

In the present invention, the thermal cracking in the cracking step is conducted at a temperature (coil outlet temperature COT) of at most 825°C. The COT is usually the highest temperature in the cracker. A temperature of at most 825°C allows producing the biohydrocarbons having a high propylene

content. A higher temperature shifts the product distribution and decreases the content of desired propylene. Preferably, the thermal cracking in the cracking step is conducted at a temperature of at least 740°C, more preferably at least 760°C. Highest propylene yields are achieved in the temperature range of 780-820°C, which is therefore preferable. On the other hand, even lower temperatures provide high propylene yields, while the amount of un-reacted educts increases. Thus, when recycling the un-reacted products to the thermal cracking, very high overall yields of propylene can be achieved.

Hence, the thermal cracking in the cracking step may preferably be conducted at a temperature of at most 820°C, at most 810°C, at most 800°C, further preferably at most 790°C, even further preferably at most 780°C.

The thermal cracking preferably comprises steam cracking, since steam cracking facilities are widely used in petrochemistry and the processing conditions are well known, thus requiring only few modifications of established processes. Thermal cracking is preferably carried out without catalyst. However, additives such as DMDS (dimethyl disulfide) may be used in the cracking step to reduce coke formation.

Steam cracking is preferably performed at a flow rate ratio between water and the isomeric raw material (H_2O flow rate [kg/h] / iso-HC flow rate [kg/h]) of 0.01 to 5.00. Preferably, the flow rate ratio is at least 0.05, preferably at least 0.10, more preferably at least 0.20, even more preferably at least 0.25. Preferably, the flow rate ratio is at most 3.00, preferably at most 1.50, more preferably at most 1.00, even more preferably at most 0.70, or at most 0.50. In the present invention, a medium range flow rate ratio, e.g. in the range of 0.25 to 0.70, is favorable since it allows production of the desired products with high yield.

In general, the pressure in the thermal cracking step is in the range of 0.9 to 3.0 bar (absolute), preferably at least 1.0 bar, more preferable at least 1.1 bar or 1.2 bar, and preferably at most 2.5 bar, more preferably 2.2 bar or 2.0 bar.

In the present invention, the biohydrocarbons produced by the method of the present invention preferably comprise at least 15 wt.-% propylene, since propylene is well suited for the production of petrochemical raw materials and in particular as a monomer or a monomer precursor in polymer industry. The present invention provides a significant improvement over conventional methods, not only from an environmental aspect, but also in view of product distribution since the present invention may provide propylene yields which are even higher than achieved by conventional methods. The biohydrocarbons preferably comprise at least 16 wt.-%, preferably at least 17 wt.-%, more preferably at least 18 wt.-%, at least 19 wt.-%, at least 20 wt.-%, or at least 21 wt.-% propylene.

As already said above, the products (biohydrocarbons) of the method of the present invention are particularly suitable as raw materials for conventional petrochemistry, and in particular polymer industry. Specifically, the products obtained from the present invention show a product distribution which is similar to, and even favorable over, the product distribution obtained from thermal (steam) cracking of conventional (fossil) raw material. Thus, these products can be added to the known value-added chain while no significant modifications of production processes are required. In effect, it is thus possible to produce polymers, especially polyolefins and/or PET, derived exclusively from bio-renewable material.

The present invention further provides a method of producing a polymer using the method of producing biohydrocarbons of the present invention. The polymer production method optionally comprises a step of purifying the biohydrocarbons to provide biomonomers for polymerization. The method further optionally comprises a step of chemically modifying the biohydrocarbons or a part thereof to provide biomonomers for polymerization. The method comprises polymerizing at least a part of the biomonomers to obtain a polymer. In the present invention, the polymer is preferably a polyethylene terephthalate (PET), a polyolefin, or a derivative thereof.

Further, the present invention provides a mixture of biohydrocarbons obtainable by the method of the present invention. The mixture of

hydrocarbons corresponds to the mixture which is directly obtained after thermal cracking without further purification. Accordingly, although the product distribution is similar to that of thermal cracking of fossil raw materials, the use of bio-renewable raw materials leaves a fingerprint (mainly in the high molecular weight products, but also to a minor degree in the medium molecular weight products) so that a distinction from conventional products is possible, e.g. using GC×GC analysis.

Examples

Laboratory scale experiments were carried out using the equipment shown in Fig. 1. In the apparatus of Fig. 1, hydrocarbons and water are provided in reservoir 2 and 3, respectively. Mass flow is determined using an electronic balance 1. Water and hydrocarbons are pumped into evaporators 7 via valves 6 using a water pump 5 and a peristaltic pump 4, respectively. Evaporated materials are mixed in mixer 8 and fed to the reactor 9 having sensors to determine temperatures T1 to T8. Coil inlet pressure (CIP) and coil outlet pressure (COP) are determined using sensors (CIP, COP) at appropriate positions. Reaction products are input into a GC×GC-FID/TOF-MS 13 via heated sampling oven after having been admixed with an internal standard 10, the addition amount of which is controlled using a coriolis mass flow controller 11. Internal pressure of the reaction system is adjusted using the outlet pressure restriction valve 14. Further, water cooled heat exchanger 15, gas/liquid separator 16, dehydrator 17, refinery gas analyzer 18, and condensate drum 19 are provided to further analyze and recover the products.

Measurement of isomerization degree

The isomerization degree of the isomeric raw material is measured by GC×GC analysis as disclosed by Van Geem et.al., "On-line analysis of complex hydrocarbon mixtures using comprehensive two-dimensional gas chromatography" in Journal of Chromatography A, 2010, vol. 1217, issue 43, p. 6623-6633.

Specifically, comprehensive 2D gas chromatography (GC×GC) is used to determine the detailed composition of the isomeric raw material. GC×GC

differs from two-dimensional GC, since not only a few fractions of the eluent from the first column but the entire sample is separated on two different columns. Compared to one-dimensional GC, GC×GC offers an improved resolution for all the components of interest, without loss of time. The signal-to-noise ratio (and sensitivity) is also significantly enhanced resulting in improved accuracy.

The GC×GC set-up is shown in the left part of Figure 2. In Fig. 2, (S0) shows the general set-up of a dual-jet cryogenic modulator; in (S1) the right-hand-side jet traps eluent from 1st dimension column; in (S2) cold spot heats up and analyte pulse into 2nd dimension column + left-hand-side jet switch on; (S3) shows the next modulation cycle.

In detail, two distinctly different separation columns are used which are based on two statistically independent separation mechanisms, so-called orthogonal separations. The first column contains a non-polar stationary phase (separation based on volatility), the second column is much shorter and narrower and contains a (medium) polar stationary phase (separation based on analyte-stationary phase interaction). One advantage of orthogonal separation is that ordered structures for structurally related components show up in the GC×GC chromatograms. Between the two columns an interface, a cryogenic modulator, is present (cf. right part of Figure 2). Its main role is to trap adjacent fractions of the analyte eluting from the first-dimension column by cryogenic cooling, and heating-up these cold spots rapidly to release them as refocused analyte pulses into the second-dimension column. To prevent leakage of the first column material, two jets are used that each in turn collect the 1st dimension eluent.

The second-dimension separation must be completed before the next fraction is injected to avoid wrap-around. Wrap-around occurs when second-dimension peaks show up in a later modulation than in which they were injected. This explains the shorter and narrower second-dimension column as compared to the first one.

The most common ways of visualization of the GC×GC chromatograms are a 2D color or grayscale plot, a contour plot and a 3D plot, see Figure 3. Two dimensional chromatograms can be obtained because the second-dimension separation time equals the modulation time.

5

In order to maintain the separation obtained in the first-dimension column, the narrow fractions trapped by the modulator and released in the 2nd column should be no wider than one quarter of the peak widths in the 1st dimension. The term "comprehensive" refers to this aspect of comprehensive GC×GC. As
10 a consequence of this characteristic and since the modulation time must equal the 2nd dimension run time, second-dimension separations should be very fast, in the order of 2 to 8 seconds. This will render very narrow 2nd dimension peaks and a demand of correspondingly fast detectors, like an FID (flame ionization detector) for quantitative analysis or a TOF-MS (time-of-flight mass
15 spectrometer) for qualitative analysis.

A quantitative analysis of a sample is carried out with the use of a GC×GC-FID. This analysis is based on the peak volumes. The peak volume in a chromatogram is proportional to the quantity of the corresponding component.
20 Hence, integration of the peaks observed in the chromatogram makes it possible to obtain a quantitative analysis of the sample.

A detailed qualitative sample characterization is obtained using information from the sample's GC×GC-TOF-MS spectrum, the molecular library and the
25 Kovats retention indices. Operation of the GC×GC-TOF-MS is computer controlled, with GC peaks automatically detected as they emerge from the column. Each individual mass spectrum is directly recorded onto the hard disk for subsequent analysis. This technique provides information on the identity of every individual component obtained by chromatographic separation by taking
30 advantage of the common fragmentation pathways for individual substance classes. The interpretation of the mass spectra and library search using e.g. the XCalibur software allows the identification of various peaks observed in the chromatogram.

In the Exmaples, the data obtained with TOF-MS was acquired using Thermo Scientific's Xcalibur software. The raw GC×GC data files were processed using HyperChrom, i.e. the Chrom-Card extension for GC×GC data handling that enables 3D representation as well as the common color plot
 5 representation of the data. HyperChrom also allows automatic 3D peak quantification and identification. The latter is accomplished by cross referencing the measured mass spectra to the spectra in the available MS libraries.

Concerning the off-line GC×GC analysis of complex hydrocarbon mixtures, each peak is assigned a unique name, or is classed into a certain group of components, based on the ordered retention of components and MS confirmation. Only components with identical molecular mass are possibly grouped. To each (grouped) component a weight fraction was assigned by
 15 internal normalization:

$$x_i = \frac{f_i \cdot V_i}{\sum_{i=1}^n f_i \cdot V_i}$$

where f_i is the relative response factor for component i , used to correct the corresponding total peak volume V_i obtained with FID. It has been demonstrated that various isomeric hydrocarbons, produce only slightly
 20 different relative FID responses, so that a fair approximation of the relative response factor may be written as:

$$f_i = \frac{M_i}{N_{C,i}} \cdot \frac{1}{M_{CH_4}}$$

where M_i is the molecular mass of component i with $N_{C,i}$ carbon atoms.

25 **Effluent analysis**

Effluent analysis of the cracking product is performed using the procedure described by Pyl et.al. (Pyl, S. P.; Schietekat, C. M.; Van Geem, K. M.; Reyniers, M.-F.; Vercammen, J.; Beens, J.; Marin, G. B., Rapeseed oil methyl ester pyrolysis: On-line product analysis using comprehensive two-dimensional
 30 gas chromatography. J. Chromatogr. A 2011, 1218, (21), 3217-3223).

Specifically, the quantification of the reactor effluent is done using an external standard (N₂) which is added to the reactor effluent in the sampling oven. In order to combine the data of the various instruments, having both TCD and FID detectors, multiple reference components were used. This is schematically presented in Figure 4.

The fraction of the reactor effluent containing the permanent gasses and the C4-hydrocarbons is injected on the refinery gas analyzer (RGA). N₂, H₂, CO, CO₂, CH₄, ethane, ethene and acetylene are detected with a TCD. The mass flow rate of these species, $\dot{m}_i$ /dt, can be determined based on the known mass flow rate of N₂ using the following equation where A_i represents the surface area obtained by the detector. The response factor for each C4-species, f_i, was determined using a calibration mixture provided by Air Liquide, Belgium.

$$\dot{m}_i = \frac{f_i A_i}{f_{N_2} A_{N_2}} \dot{m}_{N_2}$$

A FID detector on the RGA analyzes C1 to C4 hydrocarbons. Methane, detected on the TCD detector, acts as a secondary internal standard in order to quantify the other detected molecules using the following equation:

$$\dot{m}_i = \frac{f_i A_i}{f_{CH_4} A_{CH_4}} \dot{m}_{CH_4}$$

Settings of the RGA are shown in Table 1.

The GC×GC -FID allows quantification of the entire effluent stream, aside from N₂, H₂, CO, CO₂ and H₂O. Methane was used as secondary internal standard. The mass flow rates of the detected species were calculated using the above equation, response factors were calculated using the effective carbon number method. Settings of the GC×GC are shown in Table 2.

Table 1 (refinery gas analyzer settings):

		RGA		
		channel 1	channel 2	channel 3
Detector		FID, 200°C	TCD, 160°C	TCD, 160°C
Injection (gas)		50 µl, 80°C	250 µl, 80°C	250 µl, 80°C
Carrier gas		He	He	N ₂
Column	Pre	Rtx-1 ^a	Hayesep Q	Hayesep T
	Analytical	Rt-Al BOND ^b	Hayesep N Molsieve 5A	Carbosphere
Oven temperature		50 → 120°C (5°C/min)	80°C	80°C

^a dimethyl polysiloxane (*Restek*); ^b divinylbenzene ethylene glycol/dimethylacrylate (*Restek*), ^c 100% divinylbenzene (*Restek*)

Table 2 (GC×GC settings):

		GC×GC
Detectors		FID, 300°C TOF-MS, 35-400 amu
Injection	Off-line	0.2µl, split flow 150 ml/min, 300°C
	On-line	250 µl (gas), split flow 20 ml/min, 300°C
Carrier gas		He
Column	First	Rtx-1 PONA ^a
	Second	BPX-50 ^b
Oven temperature	Off-line	40°C → 250°C (3°C/min)
	On-line	-40°C (4 min hold) → 40°C (5°C/min) → 300°C (4°C/min)
Modulation Period		5s

^a dimethyl polysiloxane (*Restek*); ^b 50% phenyl polysilphenylene-siloxane (*SGE*)

5 Raw Material Composition C1:

A mixture (isomeric raw material) comprising 89 wt.-% iso-alkanes (i-paraffins) and 11 wt.-% n-alkanes (n-paraffins) is provided. The average molecular weight is 227 g/mol. The composition of the mixture is analyzed by GC×GC analysis and the results are shown in Table 3. The composition corresponds to a hydrocarbon composition (diesel fraction) derived from a bio-renewable feedstock which is subjected to hydrotreating and isomerization.

Raw Material Composition C2 (comparative):

This mixture comprises about 49 wt.-% iso-alkanes and 51 wt.-% n-alkanes. The average molecular weight is 230 g/mol. The composition of the mixture is analyzed by GC-GC analysis and the results are shown in Table 3.

5

The composition corresponds to a hydrocarbon composition (diesel fraction) derived from a bio-renewable feedstock which is subjected to hydrotreating isomerization, but to a lower degree than in composition C1.

10 Table 3:

Carbon number	C1		C2	
	i-paraffins	n-paraffins	i-paraffins	n-paraffins
C5	0.01	0.01	0	0
C6	0.07	0.01	0	0.01
C7	0.08	0.05	0.19	0.08
C8	0.24	0.13	0.24	0.12
C9	0.65	0.22	0.29	0.14
C10	1.02	0.22	0.36	0.14
C11	1.15	0.19	0.41	0.15
C12	1.23	0.18	0.48	0.21
C13	1.42	0.19	0.53	0.29
C14	2.06	0.36	1.06	0.6
C15	9.46	1.56	6.53	6.92
C16	19.35	2.34	13.62	16.41
C17	20.95	2.47	9.87	7.89
C18	29.93	2.78	14.35	17.88
C19	0.62	0.05	0.28	0.11
C20	0.58	0	0.2	0.18
C21	0.1	0.02	0.05	0.02
C22	0.11	0.01	0.05	0.03
C23	0.04	0.01	0.04	0.02
C24	0.04	0	0.03	0.03
C25	0	0	0.01	0
C26	0	0	0.04	0
Sum	89.11 wt%	10.80 wt%	48.63 wt%	51.23 wt%

Example 1

Steam cracking was carried out in laboratory scale using raw material composition C1 at a temperature (coil outlet temperature, COT) of 780°C and a dilution of 0.5 (flow rate ratio of water to raw material composition C1;

15

water [kg/h] / C1 [kg/h]) at 1.7 bar (absolute) in a 1.475 m long tubular reactor made of Incoloy 800HT steel (30-35 wt.-% Ni, 19-23 wt.-% CR, >39.5 wt.-% Fe) having an inner diameter of 6 mm. The raw material composition flow rate was fixed at 150 g/h. The coil outlet temperature (COT) was measured at a position 1.24 m downstream the inlet of the reactor, which corresponds to the region having the highest temperature in the reactor.

The product mixture (biohydrocarbons) was analyzed by GC×GC, as mentioned above. The results are shown in Table 4.

Examples 2 to 10 and Comparative Examples 11 to 20

Steam cracking was carried out similar to Example 1, except for changing raw material composition, COT and dilution, as indicated in Tables 4 and 5. The product mixtures were analyzed by GC×GC, and the results are shown in Tables 4 and 5.

Table 4:

Example #	1	2	3	4	5	6	7	8	9	10
Raw Mat.	C1	C1	C1	C1	C1	C1	C1	C1	C1	C1
COT (°C)	780	800	820	840	860	780	800	820	840	860
H ₂ O g/h	75	75	75	75	75	52	52	52	52	52
Dilution	0.5	0.5	0.5	0.5	0.5	0.35	0.35	0.35	0.35	0.35
Methane	8.17	9.71	10.48	11.11	12.25	9.14	9.65	10.31	10.79	13.45
Ethene	31.22	32.46	32.98	33.57	33.74	29.35	31.67	32.17	33.15	33.32
Propene	23.06	23.10	20.47	18.16	13.97	21.85	21.71	18.99	16.28	13.39
Butene	10.29	9.44	10.18	7.24	3.39	13.28	12.14	9.30	5.65	2.20
Butadiene	5.27	6.13	6.17	5.80	4.44	5.02	5.52	5.31	4.23	3.94
C5	5.61	5.41	4.38	3.80	2.52	5.71	5.11	4.43	3.40	3.02
Benzene	2.09	3.31	5.03	6.59	8.26	3.29	4.14	7.00	7.85	9.19
C7	1.50	1.76	2.21	2.52	2.76	2.06	2.07	2.74	2.95	3.21
C8	0.50	0.52	0.77	1.06	1.67	0.70	0.68	1.14	1.43	1.78
others	12.28	8.15	7.34	10.16	17.00	9.60	7.32	8.61	14.27	16.50
BTX total	3.25	4.96	7.34	9.25	11.27	5.19	6.34	9.88	11.03	12.63
unconverted	2.08	0.00	0.00	0.00	0.00	1.12	0.00	0.00	0.00	0.00

Table 5:

Comparative Example #	11	12	13	14	15	16	17	18	19	20
Raw Mat.	C2	C2	C2	C2	C2	C2	C2	C2	C2	C2
COT (°C)	780	800	820	840	860	780	800	820	840	860
H₂O g/h	75	75	75	75	75	52	52	52	52	52
Dilution	0.5	0.5	0.5	0.5	0.5	0.35	0.35	0.35	0.35	0.35
Methane	7.00	8.65	10.19	11.96	12.86	8.46	10.32	11.15	14.36	15.00
Ethene	31.95	35.67	37.34	39.04	39.55	32.57	35.03	36.25	38.14	39.46
Propene	20.22	21.34	19.82	17.66	14.71	21.15	20.92	18.98	15.93	13.38
Butene	8.00	6.97	4.94	3.00	1.98	7.48	6.48	4.12	2.27	1.96
Butadiene	4.75	5.82	5.91	5.42	4.69	5.12	5.47	5.32	4.76	4.21
C5	5.79	4.76	3.92	2.92	2.86	5.89	3.27	3.85	2.49	2.46
Benzene	1.81	3.13	4.57	6.09	7.84	3.22	4.44	5.79	7.45	8.65
C7	1.48	1.28	1.44	1.78	2.13	1.77	1.65	1.93	2.23	2.44
C8	2.42	0.89	0.88	1.01	1.29	1.13	0.84	0.98	1.26	1.37
others	16.59	11.50	10.99	11.12	12.09	13.21	11.57	11.64	11.12	11.07
BTX total	2.68	4.38	6.18	8.07	10.22	4.76	6.30	7.95	9.96	11.43
unconverted	6.75	1.14	0.40	0.12	0.00	1.54	0.11	0.10	0.00	0.00

As can be seen from the above results, a high degree of desirable BTX products (i.e. benzene, toluene, xylenes) can be produced at temperatures of 780°C or more, in particular 800°C or more. Surprisingly, high isomerization of the raw material composition results in increased amount of BTX products and also in higher overall conversion rates (lower amount of unconverted products) even in the intermediate temperature range of 800-840°C.

Claims

1. A method for producing biohydrocarbons, the method comprising:
a step of providing an isomeric raw material obtained from a bio-renewable
5 feedstock and containing at least 65 wt.-% iso-paraffins, and
a cracking step of thermally cracking the isomeric raw material to produce
biohydrocarbons,
wherein the thermal cracking in the cracking step is conducted at a
temperature (coil outlet temperature COT) of at most 825°C.

10 2. The method according to claim 1, wherein the isomeric raw material
contains at least 68 wt.-%, preferably at least 70 wt.-%, more preferably at
least 75 wt.-%, more preferably at least 80 wt.-%, more preferably at least 85
wt.-%, more preferably at least 90 wt.-% iso-paraffins.

15 3. The method according to claim 1 or 2, wherein the thermal cracking in
the cracking step is conducted at a temperature (coil outlet temperature COT)
of at most 820°C, preferably at most 810°C, preferably at most 800°C, at
most 790°C, or at most 780°C.

20 4. The method according to any one of the preceding claims, wherein the
thermal cracking in the cracking step is conducted at a temperature (coil
outlet temperature COT) of at least 700°C, preferably at least 720°C, at least
740°C, at least 750°C, or at least 760°C.

25 5. The method for producing biohydrocarbons according to any one of the
preceding claims, wherein the step of providing the isomeric raw material
comprises a preparation step of preparing a hydrocarbon raw material from
the bio-renewable feedstock, and optionally an isomerization step of
30 subjecting at least straight chain hydrocarbons in the hydrocarbon raw
material to an isomerization treatment to prepare the isomeric raw material.

6. The method according to claim 5, wherein the preparation step
comprises a step of deoxygenating the bio-renewable feedstock,

wherein the step of deoxygenating the bio-renewable feedstock preferably is a hydrotreatment step, preferably a hydrodeoxygenation step.

7. The method according to claim 5 or 6, wherein the preparation step
5 comprises a step of hydrocracking hydrocarbons in the hydrocarbon raw material.

8. The method according to any one of the preceding claims, wherein the
10 isomeric raw material comprises at least one of a diesel range fraction and a naphtha range fraction and at least the diesel range fraction and/or the naphtha range fraction is subjected to thermal cracking.

9. The method according to any one of the preceding claims, wherein the isomeric raw material is selected from one of fractions A and B, wherein.

15 Fraction A comprises more than 50 wt.-%, preferably 75 wt.-% or more, more preferably 90 wt.-% or more of C10-C20 hydrocarbons, the content of even-numbered hydrocarbons in the C10-C20 range being preferably more than 50 wt.-%, and the fraction A containing 1.0 wt.-% or less, preferably 0.5 wt.-% or less, more preferably 0.2 wt.-% or less aromatics, and less than 2.0,
20 preferably 1.0 wt.-% or less, more preferably 0.5 wt.-% or less of olefins, and

Fraction B comprises more than 50 wt.-%, preferably 75 wt.-% or more, more preferably 90 wt.-% or more of C5-C10 hydrocarbons, and the fraction B containing 1.0 wt.-% or less, preferably 0.5 wt.-% or less, more preferably 0.2 wt.-% or less aromatics, and less than 2.0, preferably 1.0 wt.-% or less,
25 more preferably 0.5 wt.-% or less of olefins.

10. The method according to any one of the preceding claims, wherein the thermal cracking in the cracking step comprises steam cracking, and

wherein the steam cracking is preferably performed at a flow rate ratio
30 between water and the isomeric raw material (H_2O flow rate [kg/h] / iso-HC flow rate [kg/h]) of 0.05 to 1.20, and

wherein the flow rate ratio between water and the isomeric raw material is preferably at least 0.10, further preferably at least 0.20, more preferably at least 0.25, or at least 0.30, and

wherein the flow rate ratio between water and the isomeric raw material is preferably at most 1.00, further preferably at most 0.80, more preferably at most 0.70, at most 0.60, or at most 0.50.

5 11. The method according to any one of the preceding claims, wherein the biohydrocarbons comprise at least 15 wt.-%, preferably at least 16 wt.-%, preferably at least 17 wt.-%, preferably at least 18 wt.-%, preferably at least 19 wt.-%, at least 20 wt.-%, or at least 21 wt.-% propene.

10 12. A method of producing a polymer, comprising producing biohydrocarbons according to the method of any one of claims 1 to 11, optionally purifying and/or chemically modifying at least a part of the biohydrocarbons to provide biomonomers, and polymerizing the biomonomers to obtain a polymer.

15

13. The method according to claim 12, wherein the polymer is a polyolefin, such as polypropylene and polyethylene, or a copolymer comprising propylene units and/or polyethylene units, such as polyethylene terephthalate, or a derivative thereof, and/or

20

wherein the method employs at least 50 wt.-%, preferably at least 80 wt.-%, more preferably at least 90 wt.-%, more preferably at least 95 wt.-%, more preferably more than 99 wt.-%, even more preferably 100 wt.-% of monomers derived from bio-renewable raw materials, relative to all monomers constituting the polymer.

25

14. The method according to claims 12 or 13, wherein the method further comprises forming an article, such as a film, beads, or a molded article from the polymer.

30

15. A mixture of biohydrocarbons obtainable by the method according to any one of claims 1 to 11.

FIG. 2




FIG. 3




FIG. 4

RGA (TCD)	H ₂	CO ₂	C ₂ H ₄	C ₂ H ₆	C ₂ H ₂	N ₂	CH ₄	CO
RGA (FID)	CH ₄	C ₂ H ₆	C ₂ H ₄	C ₂ H ₂	C ₃ H ₆	C ₃ H ₈	C ₄	
GCxGC (FID)	CH ₄	C ₂	C ₃	C ₄	...	C ₆ H ₆	C ₇ H ₈	...

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/061105

A. CLASSIFICATION OF SUBJECT MATTER
INV. C10G69/06 C10G69/12 C10G3/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C10G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2011/230632 A1 (ABHARI RAMIN [US]) 22 September 2011 (2011-09-22) paragraphs [0013], [0018], [0028], [0032], [0034], [0045]; claim 1; tables 2-4	1-15
A	US 2010/292517 A1 (DEBUISSCHERT QUENTIN [FR] ET AL) 18 November 2010 (2010-11-18) the whole document	1-15
A	US 2009/250376 A1 (BRANDVOLD TIMOTHY A [US] ET AL) 8 October 2009 (2009-10-08) the whole document	1-15
A	US 2009/158637 A1 (MCCALL MICHAEL J [US] ET AL) 25 June 2009 (2009-06-25) the whole document	1-15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

22 July 2016

Date of mailing of the international search report

03/08/2016

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Gzil, Piotr

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2016/061105

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2011230632 A1	22-09-2011	EP 2547704 A2	23-01-2013
		EP 3012273 A1	27-04-2016
		SG 184029 A1	30-10-2012
		US 2011230632 A1	22-09-2011
		US 2013144093 A1	06-06-2013
		US 2013331620 A1	12-12-2013
		WO 2011115966 A2	22-09-2011

US 2010292517 A1	18-11-2010	CN 101778928 A	14-07-2010
		CN 104725177 A	24-06-2015
		EP 2162508 A2	17-03-2010
		FR 2917424 A1	19-12-2008
		US 2010292517 A1	18-11-2010
		WO 2009004181 A2	08-01-2009

US 2009250376 A1	08-10-2009	NONE	

US 2009158637 A1	25-06-2009	NONE	
