




(86) Date de dépôt PCT/PCT Filing Date: 2000/01/06
(87) Date publication PCT/PCT Publication Date: 2000/07/13
(45) Date de délivrance/Issue Date: 2005/08/23
(85) Entrée phase nationale/National Entry: 2000/12/08
(86) N° demande PCT/PCT Application No.: US 2000/000299
(87) N° publication PCT/PCT Publication No.: 2000/040833
(30) Priorités/Priorities: 1999/01/06 (60/114,875) US;
1999/12/29 (09/473,782) US

(51) Cl.Int.⁷/Int.Cl.⁷ E21B 17/10, E21B 31/03, E21B 41/00
(72) Inventeurs/Inventors:
MOORE, NORMAN BRUCE, US;
FULLER, ANDREW DALE, US
(73) Propriétaire/Owner:
WESTERN WELL TOOL, INC., US
(74) Agent: OYEN WIGGS GREEN & MUTALA LLP

(54) Titre : DISPOSITIF DE PROTECTION DE TIGE DE FORAGE
(54) Title: DRILL PIPE PROTECTOR ASSEMBLY



(57) **Abrégé/Abstract:**

A drill pipe protector assembly for providing hydraulic lift and improved sliding lubrication to a drill string. The protector defines a tubular sleeve that is attached to a section of drill pipe and resides over the outer diameter of the drill pipe while moving within an associated well casing or well hole. The sleeve is adapted to provide hydraulic lift and sliding lubrication relative to the well casing and thus, increase the proclivity of the drill pipe to slide down the hole while also reducing the development of cutting dams. The sleeve includes a plurality of radially oriented openings which direct drilling mud from the annular space between the sleeve and drill pipe to the annular space between the sleeve and the casing or outer well wall. The sleeve also includes a plurality of wedge shaped longitudinal channels in communication with the radial openings. The channels direct the longitudinal flow of the drilling fluid along the outside of the sleeve to lubricate the outer surface of the sleeve and create hydraulic lift. The sleeve also includes a number of raised curvature surfaces having low coefficient of friction inserts located on the curved surfaces.



PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : E21B 17/10, 31/03, 41/00	A1	(11) International Publication Number: WO 00/40833 (43) International Publication Date: 13 July 2000 (13.07.00)
(21) International Application Number: PCT/US00/00299 (22) International Filing Date: 6 January 2000 (06.01.00) (30) Priority Data: 60/114,875 6 January 1999 (06.01.99) US Not furnished 29 December 1999 (29.12.99) US (71) Applicant (for all designated States except US): WESTERN WELL TOOL, INC. [US/US]; 9758 Whithorn Drive, Houston, TX 77095 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): MOORE, Norman, Bruce [US/US]; 7 Rosy Finch Lane, Aliso Viejo, Ca 92656 (US). FULLER, Andrew, Dale [US/US]; 1549 Placentia Avenue, Apt. 123, Newport Beach, CA 92663 (US). (74) Agent: LAMPERT, Gregory, S.; Christie, Parker & Hale, LLP, P.O. Box 7068, Pasadena, CA 91109-7068 (US).		(81) Designated States: AU, BR, CA, GB, NO, US. Published <i>With international search report.</i>
(54) Title: DRILL PIPE PROTECTOR ASSEMBLY (57) Abstract A drill pipe protector assembly for providing hydraulic lift and improved sliding lubrication to a drill string. The protector defines a tubular sleeve that is attached to a section of drill pipe and resides over the outer diameter of the drill pipe while moving within an associated well casing or well hole. The sleeve is adapted to provide hydraulic lift and sliding lubrication relative to the well casing and thus, increase the proclivity of the drill pipe to slide down the hole while also reducing the development of cutting dams. The sleeve includes a plurality of radially oriented openings which direct drilling mud from the annular space between the sleeve and drill pipe to the annular space between the sleeve and the casing or outer well wall. The sleeve also includes a plurality of wedge shaped longitudinal channels in communication with the radial openings. The channels direct the longitudinal flow of the drilling fluid along the outside of the sleeve to lubricate the outer surface of the sleeve and create hydraulic lift. The sleeve also includes a number of raised curvature surfaces having low coefficient of friction inserts located on the curved surfaces.		

WO 00/40833

PCT/US00/00299

1

DRILL PIPE PROTECTOR ASSEMBLY

FIELD OF THE INVENTION

5 This invention relates generally to non-rotating drill pipe protectors attached to a drill string, and more particularly, to drill pipe protectors that provide hydraulic lift and/or improved sliding lubrication when moving in a borehole.

BACKGROUND OF THE INVENTION

10 The drilling of holes or bores into underground formations and particularly, the drilling of oil and gas wells, is typically accomplished using a drill bit which is attached to the lower end of an elongated drill string. The drill string is constructed from a number of sections of tubular drill pipe which are coupled at their ends to form the "drill string." The drill string extends from the drilling surface into a well or "wellbore" which is formed by the rotating drill bit. As the drill bit penetrates deeper or further into an underground formation, additional sections of drill pipe
15 are added to the drill string.

Casing is generally installed in the wellbore from the drilling surface to various depths. The casing lines the wellbore to prevent the wall of the wellbore from caving in and to prevent seepage of fluids from the surrounding formations from entering the wellbore. The casing also provides a means for recovering the petroleum if the well is found to be productive.

20 A drill string is relatively flexible, being subject to lateral deflection, especially at the regions between joints or couplings. In particular, the application of weight onto the drill string or resistance from the drill bit can cause axial forces which in turn can cause lateral deflections. These deflections can result in portions of the drill string contacting the casing or wellbore. In addition, the drilling operation may be along a curved or angled path, commonly known as
25 "directional drilling." Directional drilling also causes potential contact between portions of the drill string and the casing or well bore.

Contact between the drill string and the casing and well bore creates frictional torque and drag. In fact, a considerable amount of torque can be produced by the effects of frictional forces developed between the rotating drill pipe and the casing or the wall of the well bore. During
30 drilling operations, additional torque is required while rotating the drill string to overcome this resistance. In addition, the drill string is subjected to increased shock and abrasion whenever the drill string comes into contact with the wall of the well bore or, where lined, the casing. Drilling tools and associated drill string devices encounter similar problems.

35 To alleviate these problems, drill pipe protectors are typically spaced apart along the length of the drill pipe. These drill pipe protectors were originally made from sleeves of rubber or other elastomeric material which were placed over the drill pipe to keep the drill pipe and its connections away from the walls of the casing and/or formation. Rubber or other elastomeric materials were used because of their ability to absorb shock and impart minimal wear.

Previously available drill pipe protectors have an outside diameter (O.D.) greater than that of the drill pipe joints, and were installed or clamped rigidly onto the drill pipe at a point near the joint connections of each length of drill pipe. The O.D. is specifically sized to be larger than the tool joint, but not too large as to restrict returning fluids which could result in "pistoning" of the protector in the hole. Such an installation allows the protector only to rub against the inside wall of the casing as the drill pipe rotates. Although wear protection for the casing is the paramount objective when using such drill pipe protectors, they can produce a significant increase in the rotary torque developed during drilling operations. In instances where there may be hundreds of these protectors in the wellbore at any one time, they can generate sufficient accumulative torque or drag to adversely affect drilling operations if the power required to rotate the drill pipe approaches or exceeds the supply power available.

In response to the problems of wear protection and torque build up, improvements have been directed toward producing drill pipe/casing protectors from various low friction materials in different configurations. However, such an approach again has only been marginally effective, and oil companies still are in need of an effective means to greatly reduce the wear and frictionally-developed torque normally experienced particularly when drilling deeper wells and deviated wells.

U.S. Patent No. 5,069,297 to Krueger, et al., assigned to the assignee of the present application, discloses a drill pipe/casing protector assembly which has successfully addressed the problems of providing wear protection for the casing and reduced torque build up caused by the drill pipe protectors during drilling operations. The protector sleeve in the '297 patent rotates with the drill pipe during normal operations in which there is an absence of contact between the protector sleeve and the casing, but the protector sleeve stops rotating, or rotates very slowly, while allowing the drill pipe to continue rotating within the sleeve unabated upon frictional contact between the sleeve and the casing. Thrust bearings are rigidly affixed to the drill pipe at opposite ends of the protector sleeve, and these, in combination with the internal configuration of the protector sleeve, produce a fluid bearing effect in the space between the inside of the sleeve and the outside of the drill pipe. The fluid bearing effect is produced by circulating drilling fluid through the space between the sleeve and the drill pipe so that it reduces frictional drag between the rotating drill pipe and the sleeve when the sleeve stops rotating from contact with the casing.

U.S. Patent No. 5,803,193, to Krueger, et al., assigned to the assignee of the present application, discloses a drill pipe/casing protector assembly which provides an enhanced fluid bearing effect that reduces frictional drag between the rotating drill string and the protector sleeve during use.

Although modern drill string protector designs have improved the lubrication and protection of both the drill string and the casing, there is still a need for improved sliding lubrication. In addition, there is a need for hydraulic lift to overcome the heavy normal forces

WO 00/40833

PCT/US00/00299

1 and torques encountered by the operating drill string. This problem is especially significant in
extended reach drilling. In long holes and as depth increases, the friction of the drill string
against the hole wall increases resulting in difficulty in putting weight on the drill bit or a
tendency for the weight to surge forward then reduce in a "stickion" type process. Thus, a drill
5 pipe protector that both reduces the torque from the drill string and increases the sliding ability
of the drill string against the casing is highly desirable.

SUMMARY OF THE INVENTION

10 The present invention overcomes the aforementioned problems by providing in one
embodiment a drill pipe protector assembly that provides hydraulic lift and improved sliding
lubrication to a drill string. The creation of hydraulic lift and forced lubrication reduces wear on
the protector and on the casing or well wall as well as reducing sliding friction of the drill
pipe/protector combination relative to the casing or well wall.

15 By providing a drill pipe protector assembly having a fluid pathway which directs a
portion of the drilling mud moving through the annular space between the drill pipe protector and
the drill pipe to the annular space between the protector and the casing or outer well wall,
hydraulic lift is created and sliding lubrication is achieved. By providing shaped channels along
the longitudinal length of the outer surface of the protector, increased hydraulic lift is developed.

20 In one embodiment, the present invention is generally directed to a drill pipe protector
which defines a tubular sleeve that fits over the drill pipe. The sleeve is attached to a section of
drill pipe and resides over the drill pipe. The sleeve is positioned between the outer diameter of
the drill pipe and an associated well casing or well hole. The sleeve is adapted to provide
hydraulic lift and lubrication relative to the well casing and thus, increase the proclivity of the
drill pipe to slide down the hole while also reducing the development of cutting dams.

25 More specifically, the drill pipe protector assembly comprises a tubular body having an
inner surface and an outer surface and extends along a longitudinal axis between a first end and
a second end. The tubular body is adapted to be disposable about the outside of a drill string and
within the wellbore or casing. A channel is formed on the outer surface of the body and extends
substantially along the longitudinal axis from the first end to the second end. The channel directs
30 the flow of drilling fluid between the outer surface and the inside surface of the casing. An
opening extends radially from the inner surface to the outer surface of the tubular body. The
opening allows the passage of the drilling fluid from the inner surface to the outer surface.

35 In this embodiment the protector is a generally cylindrical shaped tubular body having a
plurality of spaced apart channels along its outer surface. The outer surface includes a plurality
of radially outwardly protruding ridges which extend substantially along the longitudinal axis.
The ridges are spaced apart sufficient so as to form the described channels therebetween. At least
one, and preferably, all of the channels include an opening which allows the drilling fluid to pass
from the inner surface to within the channel.

The sleeve includes a plurality of spaced apart radial openings or diffuser ports which directs a portion of the drilling mud moving longitudinally through the annular space between the inside of the sleeve and drill pipe to the annular space between the outside of the sleeve and the casing or outer well wall. The outside surface of the sleeve also includes a plurality of shaped channels which are in communication with these radial openings. The channels direct the flowing mud to lubricate the outer surface of the sleeve and create hydraulic lift relative to the casing wall.

In a second embodiment of the present invention, the drill pipe protector assembly is a tubular sleeve having a plurality of longitudinally extending and radially protruding ridges formed on its outer surface. The ridges or ribs are spaced apart to define channels therebetween and at least some of the channels are configured to define a longitudinally extending channel having a double wedge shape. The double wedge shaped channels form passageways for the longitudinal flow of the drilling mud along the outer surface of the sleeve. Each channel or passageway includes a radially oriented internal passageway that interconnects the drilling fluid passing through the annular space between the sleeve and the drill pipe and the annular space between the outside of the sleeve and the casing. Each double wedge shaped channel defines an increasingly narrower and shallower passageway which transitions to a increasingly wider and deeper passageway along its longitudinal length. The double wedge shape accelerates and then decelerates the flow to create a hydraulic lift relative to the casing wall and also enhance the flow of the drilling mud therebetween.

In another aspect of the present invention, the protector assembly includes a tubular sleeve for use with drill tool assemblies, such as a logging line stand off protector. The sleeve includes channels formed on the outer surface for directing the flow of mud in the annular space between the channels and the casing. In addition, the sleeve includes a plurality of spaced apart radially oriented internal passageways that interconnects the drilling mud passing through the annular space between the sleeve and the drill pipe and the annular space between the outside of the sleeve and the casing.

In another embodiment of the present invention, the protector incorporates low-friction material pads on the external surfaces. The pads are made of Teflon™ composites.

These and other features and advantages of the invention will be apparent and more fully understood by those of skill in the art by referring to the following detailed description of the preferred embodiments which is made in reference to the accompanying drawings, a brief description of which is provided below.

DESCRIPTION OF THE DRAWINGS

FIG.1 is a schematic side elevational view, partly in cross-section, showing a string of drill pipe having drill pipe/casing protector assemblies according to this invention installed between tool joints of the drill pipe in a deviated well being drilled in an underground formation;

WO 00/40833

PCT/US00/00299

1 FIG. 2 is a detail view of FIG. 1 illustrating one drill pipe joint and one drill pipe protector;

FIG. 3A is a front cross-sectional view of a first embodiment of a hydrolift drill pipe protector assembly constructed according to the principles of the present invention;

5 FIG. 3B is a side cross-sectional view of the drill pipe protector assembly of FIG. 3A. showing diffuser exit ports;

FIG. 4 is a cross-sectional view of an alternative embodiment hydrolift drill pipe protector;

FIG. 5A is a side view of the protector of FIG. 4;

FIG. 5B is a cross-sectional view of the diffuser of FIG. 5A;

10 FIG. 6 is a detail view showing different cross-sectional configurations of the diffuser ports;

FIG. 7 is a perspective view of a wedgelift type drill pipe protector constructed according to the principles of the present invention;

15 FIG. 8 is a partial perspective view of a first alternative wedgelift type drill pipe protector shown mounted over a section of drill pipe;

FIG. 9 is a partial perspective view of a second alternative embodiment of a wedgelift type drill pipe protector shown mounted over a section of drill pipe and positioned in a section of casing;

20 FIG. 10 is a perspective view of a drill pipe tool joint constructed according to the principles of the present invention and showing the wedgelift configuration on the external surface;

FIG. 11 is a partial perspective view of a drill pipe protector constructed according to the principles of the present invention and showing a hydrolift type opening and a wedgelift configuration on the external surface;

25 FIG. 12 is a side cross sectional view of the drill pipe protector assembly of FIG. 10 showing the hydrolift ports and the wedgelift channels on the external surface;

FIG. 13 is a cross-sectional view of a four-sided low friction non-rotating drill pipe protector of the present invention;

30 FIG. 14 is a cross-sectional view of a two-sided low friction non-rotating drill pipe protector of the present invention;

FIG. 15 is a partial cross section of a wedgelift type drill pipe protector incorporation low friction pads; and

FIG. 16 is a partial cross section of a wedgelift type drill pipe protector incorporating low friction studs.

35 DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a well drilling system for drilling a well in an underground formation 10. A rotary drill string comprises a plurality of elongated tubular drill pipe sections 12 which drill

1 a well bore 14 with a drilling tool 15 installed at the bottom of the drill string. An elongated
cylindrical tubular casing 16 can be cemented in the well bore to isolate and/or support
formations around the bore. The invention is depicted in a deviated well which is drilled initially
5 along a somewhat straight path and then curves near the bottom and to the side in a dog leg
fashion. It is the drilling of wells of this type that can substantially increase the torque applied
to the drill string during use, and where the present invention, by reducing the amount of torque
build up, makes it possible to drill such deviated wells to greater depths and to drill them more
efficiently while preventing damage to the casing and drill pipe.

The invention is further described herein with respect to its use inside a casing in a well
10 bore, but the invention also can be used to protect the drill pipe from damage caused by contact
with the wall of a bore that does not have a casing. Therefore, in the description and claims to
follow, where references are made to contact with the wall or inside diameter (I.D.) of a casing,
the description also applies to contact with the wall of the well bore, and where references are
made to contact with a bore, the bore can be the wall of a well bore or the I.D. of a casing.

15 As illustrated, separate longitudinally spaced apart drill pipe protector assemblies 18 are
mounted along the length of a drill string to protect the casing from damage that can occur when
rotating the drill pipe inside the casing. The sections of the drill pipe are connected together in
the drill string by separate drill pipe tool joints 20 which are conventional in the art. The drill
pipe can produce both torque and drill pipe casing wear and resistance to sliding of the drill string
20 in the hole. The separate drill pipe protectors 18 are mounted to the drill string 12 adjacent to
each of the tool joints to reduce drill string torque, reduce sliding friction forces, reduce shock
and vibration to the drill string and abrasion to the inside wall of the casing.

When the drill pipe is rotated inside the casing, its tool joints would normally be the first
to rub against the inside of the casing, and this rubbing action will tend to wear away either the
25 casing, or the outside diameter of the drill pipe, or its tool joints, which can greatly reduce the
protection afforded the well or the strength of the drill pipe or its tool joints. To prevent this
damage from occurring, the outside diameter of the drill pipe protector sleeve, which is normally
made from rubber or a low friction polymeric material, is greater than that of the drill pipe and
its tool joints. Such an installation allows the protector sleeve only to rub against the casing.
30 Although they are useful in wear protection, these protectors can generate substantial cumulative
torque along the length of the drill pipe, particularly when the hole is deviated from vertical as
shown in FIG. 1. This adversely affects drilling operations, primarily by producing friction
which reduces the rotation and torque valve generated at the surface and which is then translated
to the drill bit. The present invention provides a solution to this problem.

35 FIG. 2 further schematically illustrates a drill pipe protector assembly of the present
invention. Drill pipe protector 18 is sandwiched loosely between upper and lower thrust bearings
22 and 24 which are rigidly affixed to the O.D. of the drill pipe section 12. A small gap exists
between the drill pipe protector and the thrust bearings. The drill pipe protector is mounted to

the drill pipe using techniques which hold the protector on the drill pipe and which allow the sleeve to normally rotate with the drill pipe during drilling operations; but when the drill pipe protector sleeve comes into contact with the casing 16, the sleeve stops rotating, or at least slows down substantially, while allowing the drill pipe to continue rotating inside the drill pipe protector. This change in point of rotation from the outside diameter, i.e., O.D. of the protector to the O.D. of the drill pipe, in effect, reduces the distance at which the friction associated with drill pipe rotation is applied to the drill pipe.

HYDROLIFT TYPE DRILL PIPE PROTECTOR

Referring now to FIGs. 3A and 3B, a hydrolift type non-rotating drill pipe protector 30 is shown.

The hydrolift non-rotating drill pipe protector 30 comprises an elongated tubular sleeve made from a suitable protective material, such as, a low coefficient of friction, polymeric material, metal or rubber material. A presently preferred material is a high density polyurethane or rubber material. The sleeve has an inside diameter (I.D.) 32 in a generally circular configuration. The I.D. further includes a plurality of elongated longitudinally extending, straight, parallel axial grooves 35 spaced apart circumferentially around the I.D. of the sleeve. The grooves are open ended in the sense that they open through an annular first end 34 and annular opposite second end 36 of the sleeve.

The inside wall of the sleeve is divided into intervening wall sections between adjacent pairs of the grooves 35. Each wall section has an inside bearing surface. For polyurethane or rubber sleeves, a metal reinforcement cage 38 is embedded within the sleeve between the I.D. wall 32 and the outer diameter (O.D.) wall 40. The metal reinforcing cage 38 has a retainer hinge 42 for attaching the protector 30 to the drill pipe 12. In the embodiment shown in FIGs. 3A and 3B the wall thickness of the protector 30 varies between the I.D. and the O.D. so that the protector is egg shaped in cross section. Located at the base of the egg shaped protector is a diffuser 44. The diffuser 44 has a plurality of exit ports 46a-46f which, with the exception of port 46f, extend from the I.D. 32 to the O.D. 40. The diffuser 44 can be rigidly connected to cage 38 by fasteners 48 or alternatively can be integrally molded into the sleeve.

The wall thickness of the protector 30 is such that the drill pipe protector has an O.D. greater than the O.D. of the adjacent drill pipe tool joints 20. The annular first 34 and second 36 edges of the protector sleeve have a configuration that functions to draw fluid between the sleeve and the collar, thereby assisting in the formation of a fluid bearing between the I.D. of the protector and the O.D. of the drill pipe 12. The first edge 34 includes a generally flat annular inside edge section 50 extending horizontally and generally at a right angle to the vertical inside wall of the sleeve. The edge section 50 has a beveled edge section 52 leading to the vertical inside wall to prevent or reduce the wear to the drill pipe brought about by the action of axial

WO 00/40833

PCT/US00/00299

1 forces. The angular section 52 works to reduce wear experienced on the ends of the protector sleeve and the drill pipe when acted upon by heavy axial loading.

5 The drill pipe protector sleeve 30 is split longitudinally to provide a means for spreading apart opposite sides of the sleeve when mounting the sleeve to the O.D. of the drill pipe. FIG. 3A illustrates a pair of diametrically opposed vertically extending edges 54 that define the ends of a longitudinal split that splits the sleeve into halves. The sleeve is split longitudinally and is fastened by a latch pin 56 which extends through retainer hinge 42. Alternatively, the sleeve halves may be hinged along one side and releasably fastened on an opposite side by a latch pin, or they may be secured along both opposite sides by bolts. The metal cage 38 forms an annular reinforcing ring embedded in the molded body of the sleeve. (A protector sleeve made of metal includes no reinforcing cage). The purpose of the cage is to reinforce the strength of the sleeve. The cage can absorb the compressive, tensile and shear forces experienced by the sleeve when operating in the casing or wellbore. The reinforcing cage can be made from expanded metal, metal sheet stock, or metal strips or composite (fiber). One presently preferred technique is to form the reinforcing member from a steel sheet stock with holes uniformly distributed throughout the sheet.

10 The confronting top and bottom thrust bearings 22 and 24 as described in FIG. 2 have adjacent annular end surfaces confronting the top and bottom annular end surfaces of the sleeve at essentially the same angular orientations. The upper and lower thrust bearings 22 and 24 are rigidly affixed to the O.D. of the drill pipe above and below the drill pipe protector sleeve. The thrust bearings (also referred to as collars) are metal collars made of a material such as aluminum, or a hard plastic material, such as, composites of Teflon™ $\frac{1}{3}$ - $\frac{3}{8}$ graphite fibers to encircle the drill pipe and project outwardly from the drill pipe. The collars project a sufficient axial distance along the drill pipe to provide a means for retaining the sleeve in an axially affixed position on the drill pipe, restrained between the two thrust bearings. The thrust bearings are rigidly affixed to the drill pipe and rotate with the drill pipe during use. The means for securing the thrust bearings to opposite ends of the sleeve can be similar to fastening means shown in U.S. Patent No. 5,069,297. The upper and lower thrust bearings are affixed to the drill pipe to provide a very narrow upper working clearance between the bottom of the upper thrust bearing and the annular top edge of the sleeve and a separate lower working clearance between the top of the lower thrust bearing and the bottom annular edge of the sleeve. The lower clearance can be narrow, such as one quarter of an inch or a clearance as much as one inch. The bearings are preferably split and bolted or hinged and bolted with spaced apart cap screws on outer flanges of the collar.

20 25 30 35 During use, when the rotary drill pipe is rotated within the casing or well, the outer surface of the drill pipe protector sleeve comes into contact with the interior surface of the casing or wellbore. The sleeve, which is normally fixed in place on the drill pipe, rotates with the drill pipe during normal drilling operations. However, under contact with the inside wall of the casing, the sleeve stops rotating, or its rotational speed is greatly reduced, while allowing the drill pipe to

WO 00/40833

PCT/US00/00299

1 continue rotating inside the sleeve. The configuration of the I.D. of the sleeve is such that the
drill pipe can continue rotating while the sleeve is nearly stopped or rotating slightly and yet its
stoppage exerts minimal frictional drag on the O.D. of the rotating drill pipe. The inside bearing
5 surface of the sleeve, in combination with the axial grooves, induces the circulating drilling mud
within the annulus between the casing and the drill pipe to flow under pressure at one end of the
sleeve through the parallel grooves to the opposite end of the sleeve. This produces a circulating
flow of drilling mud under pressure at the interface of the sleeve and the drill pipe and this fluid
becomes forced into the bearing surfaces between the grooves. This deforms or spreads apart the
10 bearing surface regions to produce a pressurized thin film of lubricating fluid between the sleeve
I.D. and the drill pipe O.D. which reduces frictional drag between these two surfaces. This action
of the lubrication being forced into the region between the sleeve and the drill pipe acts as a fluid
bearing to force the two surfaces apart, and such action thereby reduces the friction that would
normally be experienced both on the O.D. of the drill pipe and the I.D. of the sleeve due to the
15 fact that a thin film of fluid is separating the two surfaces. Since the fluid separates these two
surfaces the torque developed as a result of the rotation is greatly reduced.

In addition the thrust bearings at opposite ends of the sleeves, which retain the sleeves
position on the drill part, also assist in producing a further fluid bearing effect at the ends of the
sleeve.

As previously stated pressure is generated by the hydraulic bearing formed in the space
20 58 between the O.D. of the drill pipe and the I.D. of the protector. The pressure is directed to the
diffuser exit ports 46a-46f that delivers fluid to the region between the protector 30 and the
internal surface of the casing 16. The pressurized fluid tends to exit the diffuser tending to lift
the protector and simultaneously lubricate the interface of the sleeve to the casing. The fluid
movement through the exit ports also tends to clean cuttings from the bottom of the hole thus
25 helping to prevent "stuck pipe" conditions. The pressure at which the hydraulic bearing fluid
exits the diffuser exit ports can be varied by the speed at which the drill pipe is rotated. For
example rotating the pipe more rapidly increases the pressure thus improving sliding and lifting
of the drill pipe. The number of exit ports also can be varied to adjust the desired lift. The
geometrical configuration of the exit ports 46a-46f can include circular, rectangular or other
30 specialized shapes. Although the exit ports direct fluid in between the outer surface of the
diffuser and the inner surface of the casing, the exit ports can be placed on the ends of the sleeve
to direct fluid towards the collar to improve life of the collar through reduced loads and improve
lubrication. For example, exit port 46f directs fluid towards the collar.

The protector 30 incorporates an egg shaped configuration so that during lateral drilling
35 the diffuser exit ports are always positioned at the bottom of the hole to lift the drill pipe off of
the casing.

An alternative embodiment hydrolift non-rotating drill pipe protector 60 is shown in
FIGs. 4 and 5. In this embodiment, protector 60 is eccentric relative to the drill pipe 12 resulting

1 in less wall thickness near wear pads 62 and a greater wall thickness at the region near the
retainer hinge 63. This configuration results in a self-positioning of the diffuser 64 at the lowest
portion of the casing 16. Having a thinner area opposite the hinge 63 also facilitates in opening
of the sleeve for installation onto the pipe. The region near the hydrolift exit ports 66a-66j thus
5 substantially becomes the portion of the protector that interfaces with the casing. In this
embodiment the thinner diffuser portion can be made from low friction material to improve
sliding or alternatively the entire protector can be made from a low friction material.

The protector 60 has two types of reinforcements, a metal reinforcement cage 68 and
reinforcement tubes 70. The reinforcement tubes can run the entire length of the protector or
10 only portions of its length. The reinforcement tubes may be open to the drilling mud to aid in
returning the mud to the annulus between the protector and the casing. Alternatively, a portion
of the drilling mud in the reinforcement tubes can be redirected through feeder tubes 72 to the
bearing surface between the I.D. of the protector and the O.D. of the drill pipe, thus replenishing
regions of the sleeve that deplete fluid through the hydrolift exit ports. The tubes can be a simple
15 void, or lined with tubing of various types such as aluminum or composite tubing. When the
reinforcement tubes are properly spaced i.e. 20-80% of cross-sectional area, the resulting
composite sleeve has enhanced bearing resistance. Protector 60 has an I.D. configuration similar
to protector 30 which creates a hydraulic bearing is created by drilling mud moving between the
sleeve and the fluid bearing surface as discussed with respect to protector 30. A hydraulic
20 bearing is created by drilling mud moving between the I.D. of the sleeve and the O.D. of the drill
pipe by drilling mud flowing through the axial grooves 74 on the I.D. of the protector or feeder
lines 72 from reinforcement tubes 70.

The placement of the diffuser 64 and exit ports 66a-66j is to allow the continuous
operation of the hydraulic bearing as well as the operation of the diffuser. It is this combination
25 which provides the benefits of reduced drilling torque and reduced sliding resistance. The
hydrolift bearings can also be placed on the ends of the sleeve, pressurized by the thrust bearings,
thus providing additional lubrication as well as some lift-off from the collar thus increasing the
wear life of the ends of the sleeve. Numerous configurations of hydrolift diffuser and exit port
configurations are possible as shown in FIG. 6., but is not limited to these configurations, as
30 someone skilled in the art would know. Configurations 74 and 76 are based upon a thrust bearing
principle whereas configurations 78-84 are designed to primarily offer improved lubrication.

TABLE 1
HydroLift Design Computations

1	Input	
	Safety factor	1.1
5	Fluid Thickness layer for lift	0.01 in
	Fluid Viscosity	20 cp
	Fluid Density	9.5 lb/gal
	Radius of Port	0.1 in
	Radius of Lift	1 in
	Lift Required	350 lbs
10	Diameter of Pipe	5 in
	Length of Section	10 in
	Eccentricity	0.0625 in
	Diametrical Clearance	0.012 in
	RPM	120 rpm
	Coefficient of side leakage (n)	0.77
	Bearing Operation Characteristic(A)	12
	Angle between load and entering edge of mud	50 deg
15	Differential Pressure from Pump	2000 psid
	Required Pump Capacity	450 gpm
	Acceptable Pump Capacity Loss	15%
	<i>Calculated Inputs</i>	
	Number of Hydrolift required	5
20	Fluid Density	0.041 lb/in ³
	Eccentricity Ratio (e)	10.417 Ratio of eccentricity to radial clearance
	Diametrical Clearance Ratio(m)	0.002 Ratio of diametrical clearance/diameter

Using the hydrolift design computation table recited above, the benefits of the hydrolift design are seen. For 9.5 lb/gal drilling mud operating the hydrolift protector on a 5 in. drill pipe and rotating at 120 rpm, the hydrolift protector provides approximately 350 lbs of lift, thus reducing the normal weight of the pipe at the sleeve and improving sliding. The benefits of improved lubrication improve sliding characteristics substantially.

The use of the reinforcement tubes effectively reduces the amount of material needed to construct the sleeve. Specifically, the protector shown in FIGs. 4 and 5 use approximately 35% less material than existing sleeve designs. FIG. 5 illustrates that the sleeve is approximately twice as long as prior existing sleeves, however, because of the reduced material used in the hydrolift protector, the sleeve is only 25% heavier but is 100% longer than conventional designs. The hydrolift protector can be made from various materials for different applications. For cased holes, the hydrolift protector could be a polymer material, using special low friction polymers for open-hole designs, or the sleeve could be coated with a low friction metal such as amorphous titanium.

Configurations for the diffuser design balance the features of hydraulic lift of the pipe from the casing and the lubrication of the pipe to the casing. Because lift is provided by pressure,

WO 00/40833

PCT/US00/00299

1 increasing the lift requires increasing the pressurized area. Typical hydraulic bearings produce
pressure of 10-50 psi per inch of length for the range of typical pipe diameters. Thus, if the
hydrolift diffuser has a normal area to the pipe of 0.1 sq. in. and the pressure is 40 psi, the lifting
force is 4 pounds. If the area of the diffuser is increased to 1 in and the pressure remain constant.
5 the lifting force is 40 lbs. per diffuser. Since a joint of 5-in. drill pipe typically weights
approximately 660 lbs., then a hydrolift protector with 15 diffusers could effectively reduce the
drill string drag observed at the rig floor.

This is of substantial importance to drilling operations. Because the normal force resulting
from the pipe weight that produces the wear on the pipe on the casing, the effective weight
10 reduction facilitates sliding in and out of the hole. The hydrolift protector provides the lift at
exactly the point where it is required thus maximizing the benefits received.

The second factor of consideration for the hydrolift diffuser is lubrication. The result of
improved lubrication and lift is to allow the hydrolift protector to act as a hydraulic bearing with
resulting improved sliding friction. Typically protectors have a sliding friction that is dependent
15 upon the coefficient of friction between the protector and the casing or formation. For steel
casing and rubber traditional protectors, the coefficient of friction is between 0.25-0.35. The
hydrolift protector of the present invention provides a lubrication film and hydraulic lift which
results in a coefficient of friction of 0.05-0.1. The result is that ease of sliding into the hole is
achieved. As drill string rpm increases, the lubrication benefit and the lifting benefit become
20 more pronounced.

An associated benefit in the hydrolift protector design is hole cleaning. Typically in ERD
wells as the build angle exceeds 55-60° cuttings have a tendency to settle out and fall to the low
side of the casing. The result is cuttings dams and many associated problems. The hydrolift
protector design allows the pressurized fluid to wash away the dams from the bottom of the
25 casing and back into the fluid stream. Thus three benefits of the hydrolift protector are provided
being lift, lubrication, and hole cleaning.

WEDGELIFT TYPE DRILL PIPE PROTECTOR

Referring now to FIGS. 7-12 a wedgelift type non-rotating drill pipe protector is shown
30 in various views and embodiments.

FIG. 7 illustrates a wedgelift drill pipe protector 90 which preferably comprises an
elongated tubular sleeve made from a suitable protective material, such as, a low coefficient of
friction, polymeric material, metal or rubber material. A presently preferred material is a high
density polyurethane or rubber material. The sleeve has an inside diameter having a plurality of
35 elongated, longitudinally extending, straight, parallel axial grooves 92 spaced apart
circumferentially around the I.D. of the sleeve. The grooves are preferably spaced uniformly
around the I.D. of the sleeve, extend vertically, and are open-ended in the sense that they open
to an annular first end 94 and an opposite annular second end 96 of the sleeve.

1 The inside wall of the sleeve is divided into intervening wall sections of substantially uniform width extending parallel to one another between adjacent pairs of grooves 92. Each wall section has an inside bearing surface which can be a curved or a flat surface.

5 The wall thickness of the sleeve is such that the drill pipe protector 90 has an O.D. greater than the O.D. of the adjacent drill pipe tool joints. The O.D. of the sleeve includes a plurality of circumferentially spaced apart longitudinally extending, parallel outer flutes 98 extending from end to end of the sleeve. The flutes are substantially wider than the grooves 92 inside the sleeve. Positioned between adjacent flutes 98 are wedge shaped channels 100. Intervening outer wall sections 102 formed by the O.D. wall of the sleeve between the flutes and the wedge shaped channels form wide parallel outer ribs with curved outer surfaces along the outside of the sleeve.

10 The wedge shaped channels provide hydraulic lift and improved sliding lubrication reducing the effective coefficient of friction between the drill pipe and the casing and increase the proclivity to slide down the hole. The wedge shaped channel located on the outer periphery of the sleeve generates a hydraulic bearing between the sleeve and the casing. Drilling mud is directed to the wedge shaped channels by the ribs of the outer wall sections 102 into the increasingly narrower and shallower wedge shaped channel. The outer ridges provide the dual function of directing the fluid flow and providing appropriate support for the drill string when at rest. The width, height and depth of the channel and outer ribs can be varied based upon the amount of deformation of the tool under resting loads. The design of the wedge shaped channel and outer ribs can be adjusted to the required size of pressurized region and expected loads by varying the width, depth, length and taper of the channel. The fluid tends to move into the narrowing channel resulting in a region with elevated pressure, thus lifting and lubricating the region between the protector sleeve and the casing wall. Multiple wedge shaped channel configurations can be placed on the same tool in various configurations such as more than one along the same line, along multiple parallel lines or along single or multiple spiral lines.

25 The wedge shaped channels 100 can be placed in a back-to-back configuration as shown in FIG. 7 thus allow the fluid movement through the channels facing the direction of movement and allowing drill cuttings to exit from the back side of the sleeve. In addition placing the wedge shaped channels in a back-to-back configuration allows reversibility of the tool.

30 The momentum of sliding into the hole actually helps to continue the sliding. This is of substantial importance to drilling operations considering the normal force resulting from frictional drag resistance of the pipe becomes increasingly greater at greater depths thus making tripping into and out of the hole increasingly difficult. Improved lubrication and lift allows the wedgelift protector to act as a hydraulic bearing with resulting improved sliding friction. For steel casing and traditional rubber protectors, the coefficient of friction is between 0.25-0.35. The wedgelift protector provides a lubrication film and hydraulic lift thereby reducing the coefficient of friction to between 0.05-0.1. Another benefit of the wedgelift protector is hole cleaning as previously discussed with respect to the hydrolift protector.

WO 00/40833

PCT/US00/00299

1 Referring again to FIG. 7 the wedgelift protector 90 is split longitudinally to provide a means for spreading apart opposite sides of the sleeve when mounting the sleeve to the O.D. of the drill pipe. The sleeve is split longitudinally along one edge 104 which is fastened by a latch pin 106 as is typical in the art. In this version, the sleeve is simply spread apart along the edge
 5 104 when installed. Alternatively, the sleeve halves may be hinged along one side and releasably fastened on an opposite side by a latch pin or they may be secured along both opposite sides by bolts. A metal cage (not shown) forms an annular reinforcing ring embedded in the molded body of the sleeve as discussed above.

10 Top and bottom thrust bearings 22 and 24 as described in FIG. 2 maintain the protector 90 along the length of the drill pipe.

An alternative wedgelift protector 110 is shown in FIG. 8. In this embodiment the O.D. of the protector is "egg" shaped wherein the wedge shaped channels 112 are positioned on the bottom surface of the protector. The wedge shaped channels are separated by outer ribs 114. Flutes 116 are positioned on the top surface of protector 110. The egg shaped protector
 15 configuration allows the non-rotating protector to orient the wedgelift channels on the bottom of the hole thus properly orienting the protector within the casing. The protector 110 may also include flow channels 118 to assist in the return of drilling mud to the annulus between the protector and the casing. FIG. 9 illustrates a second alternative embodiment for the wedgelift protector 120 having an eccentric configuration. As with the embodiment shown in FIG. 9 the
 20 wedge shaped channels 122 are positioned on the bottom of the protector and are separated by ribs 124. Flutes 126 are positioned on the upper surface of the protector. In this eccentric configuration the wall thickness is thinner at the bottom where the wedge shaped channels are located than at the top where the flutes are located. In this configuration the design tends to force the wedge shaped channels onto the bottom of the hole thus properly orienting the protector.

25 FIG. 10 illustrates the wedgelift concept as incorporated into the drill pipe tool joint 130. In this embodiment the wedge shaped channels 132 are milled into a drill pipe tool joint 134. The wedgelift configuration could be applied to virtually any type of down hole tool that needs assistance in sliding such as rotating drill pipe protectors, or integral to drill collars, stabilizers, drill pipe, or other down hole tools.

30 FIGs. 11 and 12 show yet another embodiment of the present invention incorporating both the wedgelift and hydrolift concepts. The protector 140 is similar to the protector shown in FIG. 7 which includes a plurality of wedge shaped channels 142 separated by ribs 144 on the O.D. of the drill pipe protector. The protector also includes a hydrolift exit port 146 extending from the I.D. 148 of the protector to the wedge shaped channels. Protector 140 is particularly
 35 useful in connection with starting of sliding of the drill pipe down the hole. As static is typically greater than the sliding friction, it can be difficult to start the sliding of the drill string after stopping to make or break a drill pipe joint (or stand). If the rig has the capability to rotate as well as lower or raise the pipe, as is frequently the case with rigs with top drive systems, then

rotating the drill pipe will pump pressurized fluid from the I.D. of the sleeve to the O.D. of the protector. This pressurized fluid would enter the wedgelift configuration at its center, providing pressurized lubrication at the exact point of contact. The combination of fresh and pressurized lubrication would assist the overcoming of the static friction and assist the function of the wedgelift in the remainder of the movement of the drill pipe.

MULTI-SIDED LOW-FRICTION SLIP-SURFACE NON-ROTATING DRILL PIPE PROTECTOR

Referring now to FIGs. 13-19, multi-sided low friction slip-surface non-rotating drill pipe protectors are illustrated. FIG.13 illustrates a four-sided low friction non-rotating drill pipe protector 150. As with all the multi-sided low-friction slip-surface non-rotating drill pipe protectors, protector 150 comprises an elongated tubular sleeve made from a suitable protective material, such as a low coefficient of friction, polymeric material, metal or rubber material. A presently preferred material is a high density polyurethane having a metal reinforcing cage as previously discussed. Other materials can be a cage-reinforced rubber of various types including NBR (Nitrile Butadiene Rubber hydrogenated or nonhydrogenated), Aflas™ (fluorethylene rubber), with and without additives to improve performance, in addition to various other types of thermally and chemically stable plastics may be used. Protector 150 has an inside diameter in a generally polygonal or a curved shaped configuration. The I.D. wall 152 includes a plurality of elongated, longitudinally extending, straight, parallel axial grooves 154. The grooves are preferably spaced uniformly around the I.D. of the sleeve and extend vertically from end to end of the sleeve. The metal reinforcing cage 156 is embedded between the I.D. wall 152 and the O.D. wall 158.

Protector 150 includes a first section 160 and a second section 162 connected by a hinge 164 at one end and a latch pin 165 at an end opposite from the hinge 164. Four spaced apart flutes 166, 168, 170 and 172 are spaced around the perimeter and located on the O.D. wall 158 of the protector. Unlike conventional drill pipe protectors that typically have an external radius that is approximately circular with respect to the drill pipe, protector 150 includes an outer surface having four distinct curves that are designed to contour the common casing size, thus increasing sliding contact surface area. Each section 160 and 162 includes two sides 174 and 176, and 178 and 180, respectively. By having multiple high radius external curved surfaces allows more even distribution of the weight of the drill string through the protector's sliding surfaces. A more uniform weight distribution results in more uniform friction along the sleeve. Each of the four sides 174-180 includes low coefficient of friction inserts 182a-h positioned on the wear areas of the sides. The low coefficient of friction inserts preferably include the use of a base material of polyurethane with Teflon™ bonded to its exterior. Other Teflon™ composites, coated aluminum or other low friction material also could be used as the insert material. The inserts may be attached by an adhesive after the sleeve body is molded or inserted during the

molding process. The inserts may contain beveled edges 184 or holes 186 to create a mechanical bond with the sleeve body. The inserts can be flush with the O.D. of the protector or can be raised .02-.03 inches as shown with insert 182g to assist in wiping of the casing during operation and extend wear life.

5 More preferably the low coefficient friction inserts are made from a bronze impregnated Teflon™ (trade name Rulon 142) having a coefficient of friction of 0.10-0.12 against steel casing in drilling mud. As previously discussed the inserts may be held in place with high-strength high temperature adhesive, by molding into the urethane, mechanical bonds in the shape of rivets, or
10 by mechanically connecting the inserts to the metal reinforcement cage. Preferably the inserts are bonded to the protector as strips with a typical thickness of 0.090 inches. The surfaces of the inserts are typically beveled to allow smooth transition between the inserts and the O.D. wall of the protector. A suitable adhesive is Tristar TCE211™ which has suitable mechanical bonding strength at elevated temperatures.

15 An advantage of using bronze impregnated Teflon™ as the inserts or other similar material such as glass or graphite filled Teflon™ is that the inserts will actually reduce the coefficient of friction in the casing. As the inserts wear against the casing, they leave small deposits of bronze impregnated Teflon™ in the casing. Therefore, as more and more protectors slide over a particular torturous portion of the casing, the surface becomes impregnated into the casing and tends to reduce the coefficient of friction of subsequent protectors that slide over the
20 region. The use of Teflon™ as the inserts also demonstrates the lowest coefficient of friction on dry or nearly dry surfaces. In instances when the slide loads on the protector are so significant that the protector wipes the side of the casing, the Teflon™ inserts reduces encroachment of the drilling mud and reduces the coefficient of friction between the protector and the casing.

FIG. 14 illustrates an alternative low friction non-rotating drill pipe protector 190 having
25 a two-sided 192 and 194 low-friction slip-surface configuration. Protector 190 includes 4 axial flutes 196, 198, 200 and 202. Although the protector 190 is illustrated with four axial flutes, it is to be understood that other numbers of flutes such as 2, 6 or 8 are also possible combinations. The advantage of a two-sided low friction non-rotating drill pipe protector is that two sides provide for greater wear surface to be in contact with the casing.

30 FIGs. 15 and 16 illustrate the use of low coefficient of friction inserts in combination with the wedgelift protector previously discussed. FIG.15 illustrates protector 210 having low coefficient of friction inserts 212 positioned adjacent the wedge shaped channels 214. Also shown in the reinforcement cage 216 embedded in the protector 210. The ends 218 of the cage 216 are curved over substantially (up to 200 degrees) by having multiple split sections around
35 the circumference. The curved end sections allow better bonding between the sleeve material and the cage, which is especially useful in sleeves that are sliding within casing as better gripping between the cage and the protector material is achieved. Protector 220 shown in FIG. 16 illustrates the use of low coefficient of friction studs 222 positioned adjacent the wedge shaped

WO 00/40833

PCT/US00/00299

1 channels 224. A plurality of aluminum studs with amorphous titanium coatings or other friction
reducing coatings can be molded into the material or physically attached to the cage. The tips
of the studs extend beyond the O.D. of the protector providing a multiplicity of extensions for
the protector to slide upon. Extended tips can be placed in a variety of arrays that tend to
5 maximize life and minimize potential damage to the casing. Alternatively, either bars or plates
could be used with the coatings applied to produce long life low coefficient of friction surfaces.
Other variations could include the use of continuous ribs or bars of aluminum or similar material
instead of short studs. Use of bars has the advantage of longer surface area, thus fewer
tendencies to damage the casing.

10 Also shown in Figure 16 is an alternative materials configuration for the protector 220.
Material 226 is placed on the interior surface of the protector 220. Material 228 is placed on the
exterior surface of the protector 220. Material 226 has relatively lower hardness (75 and less
Shore A) than the exterior material 228 (75 Shore A). Preferably, material 226 has Shore A
hardness of 75 and material 228 has hardness of 90. Material 226 and 228 may be the same
15 material with different hardness or different materials, such as polyurethane with different
hardnesses resulting from different amounts of plasticizer. Alternatively, the materials 226 and
228 may be substantially different such as Aluminum for material 228 and rubber for material
226. One skilled in the art can see the wide range of material combinations that satisfy this
design. The material 226 and material 228 may be chemically bonded, mechanically bonded,
20 thermally bonded, or various combinations. The advantage of this design is that the interior
material 226 is capable of flexing around debris caught between the protector 220 and the drill
pipe without abrading the drill pipe substantially. The exterior material 228 with its greater
hardness is more resistant to abrasion between the exterior of the protector 220 and the casing
or borehole wall.

25 Although the present invention has been discussed with various embodiments thereof, it
is to be understood that it is not to be so limited since changes and modifications can be made
which are within the full intended scope as hereinafter claimed.

WHAT IS CLAIMED IS:

1. An underground drilling system comprising:
 - a wellbore in an underground formation;
 - 5 a fixed tubular casing installed in the wellbore;
 - a rotary drill pipe extending through the casing and having an outer diameter spaced from an inside diameter of the casing or wellbore during normal drilling operations;
 - 10 a protective sleeve mounted around the drill pipe and spaced from the inside diameter of the casing or bore for preferentially contacting the inside diameter of the casing or bore when the drill pipe deflects off-center in the casing or bore to protect the casing or bore from contact with the drill pipe or its tool joints during rotation of the drill pipe;
 - 15 thrust bearing collars rigidly affixed to the drill pipe above and below the sleeve for maintaining the sleeve in a fixed axial position on the drill pipe;
 - the protective sleeve mounted to the drill pipe via an internal sleeve inside diameter configuration that substantially reduces the rotational rate of the sleeve upon frictional contact of the sleeve with the inside diameter of the casing or bore, while allowing the rotary drill pipe to continue rotating within the sleeve at a rotation rate
 - 20 sufficient to conduct drilling operations in the formation;
 - said internal configuration comprising longitudinally extending and circumferentially spaced apart axial grooves formed in an inside diameter wall of the sleeve for allowing fluid to circulate through a space formed between the inside diameter of the sleeve and the outer diameter of the drill pipe;
 - 25 a diffuser region having at least one diffuser exit port for allowing fluid under pressure to exit through the space formed between the inside diameter of the sleeve and the outer diameter of the drill pipe to lift the sleeve off the casing.
2. The drilling system of claim 1 wherein the sleeve has a plurality of diffuser exit ports.
- 30 3. The drilling system of claim 1 wherein the sleeve has a circular outer diameter.
4. The drilling system of claim 1 wherein the sleeve has a non-circular outer diameter.
- 35 5. The drilling system of claim 4 wherein the sleeve includes wear pads positioned on the outer diameter of the sleeve adjacent the diffuser exit ports.

6. The drilling system of claim 1 wherein the sleeve includes a plurality of channels formed on the outer diameter of the sleeve.
- 5 7. The drilling system of claim 6 wherein the channels are formed between an adjacent pair of spaced apart ridges extending radially outward from the outer diameter of the sleeve.
8. The drilling system of claim 6 wherein at least one of the channels is wedge shaped and narrows in width and depth from a first end to a second end of the channel.
- 10 9. The drilling system of claim 8 wherein the wedge shaped channel is in fluid communication with the diffuser exit port.
10. The drilling system of claim 8 wherein low coefficient of friction wear pads are inserted on the outer diameter of the sleeve adjacent the at least one wedge shaped channel.
- 15 11. The drilling system of claim 1 wherein the protective sleeve has a reinforcement cage embedded within the sleeve wherein the cage includes curved end portions.
12. The drilling system of claim 1 wherein at least a portion of the inside diameter of the sleeve has a lower hardness than an outer diameter of the sleeve.
- 20 13. A drill pipe protector for use on a drill string in a wellbore comprising:
a cylindrical sleeve having an inside diameter for placement around the drill string and an outer diameter;
25 a plurality of channels extending around the outer diameter of the sleeve between radially extending ridges wherein at least one of the channels is wedge shaped which narrows in width and depth from a first end to a second end of the channel to generate a hydraulic bearing between the sleeve and adjacent wall of the wellbore.
- 30 14. The protector of claim 13 wherein the outer diameter of the sleeve is circular.
15. The protector of claim 13 wherein the outer diameter is non-circular.
- 35 16. The protector of claim 13 wherein two wedge shaped channels are positioned in a back-to-back configuration on the outer diameter of the sleeve.

17. The protector of claim 13 wherein low coefficient of friction inserts are positioned adjacent the wedge shaped channel.
- 5 18. The protector of claim 13 wherein the sleeve includes a plurality of low coefficient of friction studs adjacent the wedge shaped channels.
- 10 19. The protector of claim 13 wherein the sleeve includes a diffuser portion having at least one exit port extending through the diffuser between the inside diameter and the outer diameter of the sleeve for the passage of pressurized fluid to lift the protector away from a wall of the wellbore.
20. The protector of claim 19 wherein the diffuser portion has a plurality of exit ports.
- 15 21. The protector of claim 19 wherein the diffuser exit port is located in the wedge shaped channel.
22. A non-rotating drill pipe protector for use in a wellbore, the drill pipe protector comprising:
 - 20 a cylindrical sleeve sized to be placed around a drill string;
 - said sleeve having an inside diameter having a plurality of grooves for generating a fluid bearing between the inside diameter and the drill pipe;
 - the sleeve having an outer diameter including multiple distinct radius external curved surfaces contoured for increasing sliding contact surface area, said contoured surfaces separated by channels on the outer diameter; and
 - 25 at least one low coefficient of friction insert positioned on each curved surface.
23. The protector of claim 22 wherein there are four external curved surfaces and at least four channels.
- 30 24. The protector of claim 22 wherein there are two external curved surfaces and at least two channels.
25. The protector of claim 22 wherein the inserts are raised above a surface of the outer diameter of the sleeve.
- 35 26. The protector of claim 22 further comprising a metal reinforcing cage embedded within the sleeve between the outer diameter and the inside diameter

27. The protector of claim 26 wherein the inserts are fastened to the cage.
28. The protector of claim 26 wherein the metal inserts are plates.
- 5 29. The protective sleeve of claim 11 wherein at least a portion of an inside diameter of the sleeve has a lower hardness than an outer diameter of the sleeve.
30. The drill pipe protector of claim 13 wherein the sleeve has a reinforcement cage embedded within the sleeve wherein the cage includes curved end portions.
- 10 31. The drill pipe protector of claim 13 wherein at least a portion of the inside diameter of the sleeve has a lower hardness than an outer diameter of the sleeve.
- 15 32. The drill pipe protector of claim 22 wherein the sleeve has a reinforcement cage embedded within the sleeve wherein the cage includes curved end portions.
33. The drill pipe protector of claim 22 wherein at least a portion of the inside diameter of the sleeve has a lower hardness than an outer diameter of the sleeve.


FIG. 1


FIG. 2




FIG. 3A**FIG. 3B**

FIG. 4



60 *FIG. 5A*




FIG. 5B




FIG. 6







FIG. 7

FIG. 8**FIG. 9**






FIG. 11**FIG. 12**

FIG. 13




FIG. 14





FIG. 15*FIG. 16*