


(No Model.)

F. WAITE.
PRINTER'S QUOIN.

No. 540,286.

Patented June 4, 1895.



Witnesses:-

W. K. Boulter

A. L. Northrup

Inventor:

Fred Waite,

By Wm. E. Boulter,

Attorney

UNITED STATES PATENT OFFICE.

FRED WAITE, OF OTLEY, ENGLAND, ASSIGNOR TO WAITE & SAVILLE,
LIMITED, OF SAME PLACE.

PRINTER'S QUOIN.

SPECIFICATION forming part of Letters Patent No. 540,286, dated June 4, 1895.

Application filed October 29, 1894. Serial No. 527,306. (No model.)

To all whom it may concern:

Be it known that I, FRED WAITE, a subject of the Queen of England, residing at Otley, England, have invented certain new and useful Improvements in Printers' Quoins, of which the following is a specification.

This invention relates to improvements in printers' quoins, and its object is to provide a simple and readily adjustable quoin without loose parts and free from any liability to slip or shake loose. For this purpose I employ a guide piece having parallel guides between or upon which guides a sliding or adjustable block is fitted. This sliding block is adjusted within the said guides—to expand or contract the quoin—by means of a screw fitting a female screw thread cut in the block. To keep the sliding block in position in the guide piece the head of the screw operating the sliding block may lie in a recess in the said guide piece and be so arranged that while it is perfectly free to be rotated, to turn the screw, it is prevented from longitudinal movement in relation to the guide piece.

Reference is to be had to the accompanying sheet of drawings, forming a part of this specification, in which similar letters of reference indicate corresponding parts in each of the figures.

Figure 1 represents a plan view of my improved quoin. Fig. 2 represents a side view, and Fig. 3 an end view, of the same. Fig. 4 represents a sectional view on the broken line *a b*, Fig. 1. Figs. 5 and 6 respectively represent a separate plan view of the guide-piece and the sliding block.

The guide piece A is provided with parallel guides B, B between which the sliding block C is fitted. Said piece A has the transverse portions A', A². The screw D fits the female screw thread cut in the hole E through the block C and its head F lies in the opening or recess G formed in the guide piece A between the transverse portions A' A² and the screw is thereby confined longitudinally. Holes H are drilled through the head of the

screw to admit the end of a lever to tighten up the screw when the quoin is in position. The under side of the sliding piece is preferably a little above the under side of the guide piece so as to allow it to slide freely in or out when in position; and to maintain the sliding block in this position in relation to the guide piece the sliding block is provided with lateral lips J, J arranged to rest upon the top of the guides B, B.

I claim—

1. In a printer's quoin, the combination with the guide piece A provided with parallel guides B, B, of the sliding block C fitted and adapted to slide between said guides, the bottom of the block being above the bottom of the guide piece, for the purpose specified.

2. In a printer's quoin, the combination with the guide piece A provided with parallel guides B, B, of the sliding block C fitted and adapted to slide between said guides, the bottom of the block being above the bottom of the guide piece, and the lateral lips J, J, on the block C resting upon the upper face of the guides, as and for the purpose specified.

3. In a printer's quoin, the combination with the guide piece A provided with parallel guides B, B, the transverse portions A' A² on said guide piece, the latter having an opening G between said portions, the sliding block C fitted and adapted to slide between said guides and having a threaded opening, and the portion A' being provided with an opening and a headed screw working in the opening in block C and passing through the opening in the portion A' and the head of the screw lying within the opening G between the portions A' A² of the guide piece, as and for the purpose specified.

In witness whereof I have hereunto set my hand in the presence of the two subscribing witnesses.

FRED WAITE.

Witnesses:

DAVID NORVELL,
SAMUEL A. DEACUP.