



US00RE39776E

(19) **United States**
(12) **Reissued Patent**
Kato et al.

(10) **Patent Number:** **US RE39,776 E**
(45) **Date of Reissued Patent:** **Aug. 21, 2007**

(54) **VACUUM PROCESSING APPARATUS AND OPERATING METHOD WITH WAFERS, SUBSTRATES AND/OR SEMICONDUCTORS**

(75) Inventors: **Shigekazu Kato**, Kudamatsu (JP);
Kouji Nishihata, Tokuyama (JP);
Tsunehiko Tsubone, Hikari (JP);
Atsushi Itou, Kudamatsu (JP)

(73) Assignee: **Hitachi, Ltd.**, Tokyo (JP)

(21) Appl. No.: **10/062,618**

(22) Filed: **Feb. 5, 2002**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,263,588**
Issued: **Jul. 24, 2001**
Appl. No.: **09/614,770**
Filed: **Jul. 12, 2000**

U.S. Applications:

(62) Division of application No. 09/552,572, filed on Apr. 19, 2000, now Pat. No. 6,301,801, which is a division of application No. 09/461,432, filed on Dec. 16, 1999, now Pat. No. 6,330,755, which is a continuation of application No. 09/177,495, filed on Oct. 23, 1998, now Pat. No. 6,012,235, which is a continuation of application No. 09/061,062, filed on Apr. 16, 1998, now Pat. No. 5,950,330, which is a continuation of application No. 08/882,731, filed on Jun. 26, 1997, now Pat. No. 5,784,799, which is a division of application No. 08/593,870, filed on Jan. 30, 1996, now Pat. No. 5,661,913, which is a continuation of application No. 08/443,039, filed on May 17, 1995, now Pat. No. 5,553,396, which is a division of application No. 08/302,443, filed on Sep. 9, 1994, now Pat. No. 5,457,896, which is a continuation of application No. 08/096,256, filed on Jul. 26, 1993, now Pat. No. 5,349,762, which is a continuation of application No. 07/751,951, filed on Aug. 29, 1991, now Pat. No. 5,314,509.

(30) **Foreign Application Priority Data**

Aug. 29, 1990 (JP) 02-225321

(51) **Int. Cl.**
F26B 5/04 (2006.01)

(52) **U.S. Cl.** **34/417; 34/229**


(58) **Field of Classification Search** 34/406,
34/417, 92, 228, 229; 414/939, 940; 134/902;
156/345, 345 C, 345 PC; 118/723 F, 723 I,
118/730, 719

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,652,444 A	3/1972	Lester et al.	
3,981,791 A	9/1976	Rosvold	
4,138,306 A	2/1979	Niwa	156/345
4,226,897 A	10/1980	Coleman	
4,311,427 A	1/1982	Coad et al.	
4,313,783 A	2/1982	Davies et al.	
4,313,815 A	2/1982	Graves, Jr. et al.	
4,318,767 A	3/1982	Hijikata et al.	
4,449,885 A	5/1984	Hertel et al.	
4,457,661 A	7/1984	Flint et al.	
4,534,314 A	8/1985	Ackley	
4,563,240 A	1/1986	Shibata et al.	
4,576,698 A	3/1986	Gallagher et al.	
4,634,331 A	1/1987	Hertel	
4,643,629 A	2/1987	Takahashi et al.	
4,705,951 A	11/1987	Layman et al.	
4,715,764 A	12/1987	Hutchinson	
4,824,309 A	4/1989	Kakehi et al.	
4,836,733 A	6/1989	Hertel et al.	
4,836,905 A	6/1989	Davis et al.	
4,851,101 A	7/1989	Hutchinson	
4,895,107 A	1/1990	Yano et al.	
4,902,934 A	2/1990	Miyamura et al.	
4,903,937 A	2/1990	Jakubiec et al.	
4,909,695 A	3/1990	Hurwitt et al.	
4,911,597 A	3/1990	Maydan et al.	
4,915,564 A	4/1990	Eror et al.	
4,917,556 A	4/1990	Stark et al.	
4,923,584 A	5/1990	Bramhall, Jr. et al.	
4,924,890 A	5/1990	Giles et al.	
4,936,329 A	6/1990	Michael et al.	
4,951,601 A	8/1990	Maydan et al.	
4,969,790 A	11/1990	Petz et al.	
5,007,981 A	4/1991	Kawasaki et al.	
5,014,217 A	5/1991	Savage	
5,186,718 A	2/1993	Tapman et al.	
5,292,393 A	3/1994	Maydan et al.	
5,351,415 A	10/1994	Brooks et al.	



5,436,848 A	7/1995	Nishida et al.	
5,452,166 A	9/1995	Aylwin et al.	
5,462,397 A	10/1995	Iwabuchi	
5,504,033 A	4/1996	Bajor et al.	
5,504,347 A	4/1996	Jovanovic et al.	
5,509,771 A	4/1996	Hiroki	414/217
5,556,714 A	9/1996	Fukuyama et al.	
5,651,858 A	7/1997	Lin	
5,675,461 A	10/1997	Aylwin et al.	
5,685,684 A	11/1997	Kato et al.	414/217
6,007,675 A	12/1999	Toshima	419/939 X

FOREIGN PATENT DOCUMENTS

EP	20246453	4/1987
EP	0246453	11/1987
EP	20381338	5/1990
EP	0381338	8/1990
JP	57-29577	2/1982
JP	58-93321	6/1983
JP	58-108641	6/1983
JP	59-094435	5/1984
JP	60-52574	3/1985
JP	60-246635	12/1985
JP	SHO-61-173445	8/1986
JP	61-250185	11/1986
JP	62-44571	2/1987
JP	62-50463	3/1987
JP	62-89881	4/1987
JP	62-132321	6/1987
JP	62-207866	9/1987
JP	62-216315	9/1987
JP	63-133521	6/1988
JP	63-153270	6/1988
JP	636582	1/1989
JP	6412037	1/1989
JP	131970	2/1989
JP	131971	2/1989
JP	1-120811	5/1989
JP	1-135015	5/1989
JP	1-170013	6/1989
JP	1-251734	10/1989
JP	1-258438	10/1989
JP	1-298180	12/1989
JP	1-310553	12/1989
JP	1-316957	12/1989
JP	2-52449	2/1990
JP	261064	3/1990
JP	265252	3/1990
JP	02-065252	3/1990
JP	2-94647	4/1990
JP	2-106037	4/1990
JP	02-178946	7/1990
JP	2-178946	7/1990
JP	2-224242	9/1990
JP	3-19252	1/1991
JP	430549	4/1992
JP	63-153270	6/1998
WO	870309	5/1987
WO	87/07309	12/1987

OTHER PUBLICATIONS

Terminological Dictionary of Semiconductor Equipment, Edited by Semiconductor Equipment Association of Japan, Published by Nikkan Kogyo Shinbun sha Inc. (1987) p. 183 (PTR).

Semicon News, Apr. 1987 (pp. 38-43) (PTR).

VLSI Processing Equipment handbook, Ph. D. Kazuo Maeda (6-90), pp. 158 (PTR).

Latest trend of process automation (Realize, Inc.) (1986), pp. 202 and 203.

Semicon News, Semicon/East '84, Dec. 1984, vol. 13., p. 199.

"Semiconductor World", Sep. 1990, Published by Press Journal, Inc., pp. 136-137 (FTR).

R.P.H. Chang, "Multipurpose plasma reactor for materials research processing", J. Vac. Sci. Technol., vol. 14, No. 1, Jan./Feb. 1977, pp. 278-280.

Electronic Parts and Materials, 1989, vol. 28, No. 3, pp. 22-29.

Solid State Technology, Oct. 1990, pp. 35-41.

Solid State Technology, Dec. 1990, pp. 37-47.

Semiconductor World, pp. 106-111, Sep. 1990.

Semiconductor World, pp. 122-125, Sep. 1990.

Semiconductor World, pp. pp. 110-113, Oct. 1989.

Semiconductor World, pp. 52-53, Aug. 1991.

European Search Report, Jan. 1992, re 91307625.3.

European Search Report, Apr. 1998, re 97111628.0.

European Search Report, Mar. 1999, re 981061625.

JP application No. 3-234408, Notification of Reasons for Refusal, Jan. 28, 1997 (TR).

JP application No. 2646905, Notification Reasons for Revocation Dec. 15, 1998 (TR).

JP application No. 2646905, Notice of Reasons for Revocation Jul. 21, 1999 (TR).

Decision for Patent Opposition, Opposition No. 10-70995 (Oct. 1999) (TR).

JP application No. 2-225321, Notification of Reasons for Refusal Oct. 15, 1996 (TR).

JP application No. 8-335329, Interview Record (TR).

JP application No. 8-335329, Notification of Reasons for Refusal Sep. 30, 1997 (TR).

JP application No. 8-335329, Notification of Reasons for Refusal Apr. 7, 1998 (TR).

JP patent No. 2816139, Notice of Reasons for Revocation Nov. 21, 1999 (TR).

Official Decision on Opposition to Grant of Patent 1999-71584 Jan. 12, 2001 (TR).

JP application No. 9-329873, Notification of Reasons for Refusal Jul. 24, 1998 (TR).

JP application No. 9-329873, Notification of Reasons for Refusal Nov. 10, 1998 (TR).

JP patent No. 2942527, Notice of Reasons for Revocation Jun. 27, 2000 (TR).

Decision on Opposition to the Grant of a Patent 2000-70844 Jan. 12, 2001 (TR).

JP application No. 11-001263, Notification of Reasons for Refusal Feb. 2, 2000 (TR).

JP application No. 2000-05449, Notification of Reasons for Refusal Sep. 6, 2000 (TR).

JP application No. 2000-054450, Notification of Reasons for Refusal Sep. 6, 2000 (TR).

JP application No. 2000-054451, Notification of Reasons for Refusal Sep. 6, 2000 (TR).

JP application No. 2000-054452, Notification of Reasons for Refusal Sep. 6, 2000 (TR).

EP91307625, Office Action Oct. 11, 1993.

EP91307625, Summons to attend oral proceedings Dec. 9, 1999.

EP91307625, Communication of a notice of opposition Nov. 19, 1998.

EP91307625, Interlocutory decision in Opposition proceeding, May 16, 2000.

EP91307625, Minutes of the oral proceedings, Mar. 9, 2000.
 EP97111628, Office action Dec. 1999.
 EP97111628, Office action Nov. 2000.
 EP97111628, Office action Jun. 2001.
 EP98106162, Office action Nov. 2000.
 EP98106162, Office action Jun. 2001.
 KR application No. 14984/91, Preliminary Notice of Ground(s) for Rejection (TR).
 KR application No. 184682-00-00 Notice of Decision on Opposition to the Granted Patent Oct. 4, 2000 (TR).
 KR application No. 184682, Trial Decision Aug. 1, 2000 (TR).
 KR application No. 46756/98, Preliminary Notice of Ground(s) for Rejection Jan. 20, 1999 (TR).
 KR application No. 212874, Dec. 22, 2000, Notice of Decision on Opposition to the Granted Patent.
 KR application No. 46757/98, Preliminary Notice of Ground(s) for Rejection Jan. 20, 1999 (TR).
 KR application No. 212819, Dec. 22, 2000, Notice of Decision on Opposition to the Granted Patent (TR).
 JP patent No. 3145359, Notice of Reasons for Revocation Dec. 18, 2001 (TR).
 JP patent No. 3145375, Notice of Reasons for Revocation Dec. 18, 2001 (TR).
 JP patent No. 3147230, Notice of Reasons for Revocation Dec. 18, 2001 (TR).
 JP application No. 2000-338177, Decision of Refusal Apr. 16, 2002 (FTR).
 Decision on Opposition No. 2001.72514 relating to JP 3145359, Patentee Hitachi, Ltd., pp. 1-27, Nov. 20, 2002.
 Decision on Opposition No. 2001.72518 relating to JP 3145375, Patentee Hitachi, Ltd., pp. 1-28, Nov. 20, 2002.
 Decision on Opposition No. 2001.72519 relating to JP 3145376, Patentee Hitachi, Ltd., pp. 1-23, Nov. 20, 2002.
 Decision on Opposition No. 2001.72574 relating to JP 3147230, Patentee Hitachi, Ltd., pp. 1-22, Nov. 20, 2002.
 Office Action dated Sep. 3, 2002, in corresponding Japanese Patent Application 2000-040579.

Decision of the Tokyo High Court, Case No. 58, on oral proceedings, dated Sep. 17, 2002.
 Office Action dated Sep. 3, 2002, in corresponding Japanese Patent Application 2000-040580.
 Semiconductor Equipment Association of Japan, "Terminological Dictionary of Semiconductor Equipment", front, table, p. 183, back, Nov. 20, 1987.
 Semiconductor Equipment Association of Japan, "Semiconductor News", vol. 4, pp. 38-43, Apr. 10, 1987 (w/translation).

Primary Examiner—Ira S. Lazarus

Assistant Examiner—Kathryn S. O'Malley

(74) *Attorney, Agent, or Firm*—Antonelli, Terry, Stout and Kraus, LLP.

(57)

ABSTRACT

This invention relates to a vacuum processing apparatus having vacuum processing chambers the insides of which must be dry cleaned, and to a method of operating such an apparatus. When the vacuum processing chambers are dry-cleaned, dummy substrates are transferred into the vacuum processing chamber by substrates conveyor means from dummy substrate storage means which is disposed in the air atmosphere together with storage means for storing substrates to be processed, and the inside of the vacuum processing chamber is dry-cleaned by generating a plasma. The dummy substrate is returned to the dummy substrate storage means after dry cleaning is completed. Accordingly, any specific mechanism for only the cleaning purpose is not necessary and the construction of the apparatus can be made simple. Furthermore, the dummy substrates used to dry cleaning and the substrates to be processed do not coexist, contamination of the substrates to be processed due to dust and remaining gas can be prevented and the production yield can be high.

17 Claims, 1 Drawing Sheet

FIG. 1





FIG. 2



**VACUUM PROCESSING APPARATUS AND
OPERATING METHOD WITH WAFERS,
SUBSTRATES AND/OR SEMICONDUCTORS**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a Divisional application of application Ser. No. 09/552,572, filed Apr. 19, 2000 *now U.S. Pat. No. 6,301,801* which is a Divisional application of application Ser. No. 09/461,432, filed Dec. 16, 1999 *now [abandoned] U.S. Pat. No. 6,330,755*, which is a Continuation application of application Ser. No. 09/177,495, filed Oct. 23, 1998 *now U.S. Pat. No. 6,012,235*, which is a Continuation application of application Ser. No. 09/061,062, filed Apr. 16, 1998 *now U.S. Pat. No. 5,950,330*, which is a Continuation application of application Ser. No. 08/882,731, filed Jun. 26, 1997 *now U.S. Pat. No. 5,784,799*, which is a Divisional application of application Ser. No. 08/593,870, filed Jan. 30, 1996 *now U.S. Pat. No. 5,661,913*, which is a Continuing application of application Ser. No. 08/443,039, filed May 17, 1995 *now U.S. Pat. No. 5,553,396*, which is a Divisional application of application Ser. No. 08/302,443, filed Sep. 9, 1994 *now U.S. Pat. No. 5,457,896*, which is a Continuing application of application Ser. No. 08/096,256, filed Jul. 26, 1993 *now U.S. Pat. No. 5,349,762*, which is a Continuing application of application Ser. No. 07/751,951, filed Aug. 29, 1991 *now U.S. Pat. No. 5,314,509*.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to a vacuum processing apparatus and operating method therefor. More specifically, the present invention relates to a vacuum processing apparatus having vacuum processing chambers the inside of which must be cleaned, and its operating method.

2. Description of the Prior Art

In a vacuum processing apparatus such as a dry etching apparatus, a CVD apparatus or a sputtering apparatus, a predetermined number of substrates to be treated are stored as one unit (which is generally referred to as a "lot") in a substrate cassette and are loaded in the apparatus. The substrates after being processed are likewise stored in the same unit in the substrate cassette and are recovered. This is an ordinary method of operating these apparatuses to improve the productivity.

In such a vacuum processing apparatus described above, particularly in an apparatus which utilizes a reaction by an active gas, as typified by a dry etching apparatus and a CVD apparatus, reaction products adhere to and are deposited on a vacuum processing chamber with the progress of processing. For this reason, problems such as degradation of vacuum performance, the increase of dust, the drop of the levels of optical monitoring signals occur. To solve these problems, conventionally the insides of the vacuum processing chambers are cleaned periodically. Cleaning operations include so-called "wet cleaning" which is wiping-off of the adhering matters by use of an organic solvent, etc., and so-called "dry cleaning" in which an active gas or plasma is used for decomposing adhering matters. Dry cleaning is superior from the aspect of the working factor and efficiency. These features of the dry cleaning have become essential with the progress in automation of production lines.

An example of vacuum processing apparatuses having such a dry cleaning function is disclosed in Japanese Utility

Model Laid-Open No. 127125/1988. This apparatus includes a preliminary vacuum chamber for introducing wafers to be treated into a processing chamber from an atmospheric side to a vacuum side, which is disposed adjacent to the processing chamber through a gate valve, dummy wafers are loaded in the preliminary vacuum chamber and are transferred into the processing chamber by exclusive conveyor means before the processing chamber is subjected to dry cleaning, and the dummy wafer is returned to the vacuum preparatory chamber by the conveyor means after dry cleaning is completed.

SUMMARY OF THE INVENTION

In the prior art technology described above, the structure of the vacuum processing apparatus is not much considered. The preliminary vacuum chamber for storing the dummy wafers must have a large capacity, the exclusive conveyor means is necessary for transferring the dummy wafers and thus, the apparatus is complicated in structure.

Dummy wafers used for plasma cleaning are again returned to the preliminary vacuum chamber and are made to stand by. In this instance, reaction products generated during plasma cleaning and residual gas used for plasma cleaning adhere on the used dummy wafers. Thereafter, normal processing for wafers is resumed. Therefore, the used dummy wafers and unprocessed wafers exist in mixture inside the preliminary vacuum chamber and this state is not desirable from the aspect of contamination of unprocessed wafers.

The present invention provides a vacuum processing apparatus which solves the problems described above, is simple in structure, prevents contamination of unprocessed substrates and accomplishes a high production yield. A vacuum processing apparatus having vacuum processing chambers the insides of which are dry-cleaned after substrates to be treated are processed in vacuum is provided with first storage means for storing substrates to be treated, second storage means for storing dummy substrates, the first and second storage means being disposed in the air, conveyor means for transferring the substrates to be processed between the first storage means and the vacuum processing chambers and for transferring the dummy substrates between the second storage means and the vacuum processing chambers, and control means for controlling the conveyor means so as to transfer the dummy substrates between the second storage means and the vacuum processing chambers before and after dry cleaning of the vacuum processing chambers. A method of operating a vacuum processing apparatus having vacuum processing chambers the insides of which are dry-cleaned after substrates to be processed are processed in vacuum comprises the steps of disposing first storage means for storing the substrates to be processed together with second storage means for storing dummy substrates in the air atmosphere, transferring the substrates to be processed between the first storage means and the vacuum processing chambers and vacuum-processing the substrates to be processed, and transferring the dummy substrates between the second storage means and the vacuum processing chambers before and after dry-cleaning of the vacuum processing chambers.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a plan view of a dry etching apparatus as an embodiment of a vacuum processing apparatus in accordance with the present invention; and

FIG. 2 is a vertical sectional view taken along line 1-1 of FIG. 1.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

As substrates to be processed are processed in a vacuum processing apparatus, reaction products adhere to and are deposited in vacuum processing chambers. The reaction products adhering to and deposited in the vacuum processing chambers are removed by disposing dummy wafers inside the vacuum processing chambers and by conducting dry-cleaning. To carry out dry cleaning, the timings of dry cleaning of the vacuum processing chambers are determined and during or after the processing of a predetermined number of substrates to be processed, dummy substrates are conveyed by substrate conveyor means from dummy substrate storage means disposed in the air atmosphere together with processed substrate storage means, and are then disposed inside the vacuum processing chambers. After the dummy substrates are thus disposed, a plasma is generated inside each of the vacuum processing chambers to execute dry-cleaning inside the vacuum processing chamber. After dry-cleaning inside the vacuum processing chambers is completed, the dummy substrates are returned from the vacuum processing chambers to the dummy substrate storage means by the substrate conveyor means. In this manner, a preliminary vacuum chamber and an exclusive transfer mechanism both necessary in prior art techniques become unnecessary, and the apparatus structure gets simplified. The dummy substrates used for the dry-cleaning and the substrates to be processed do not co-exist inside the same chamber, so that contamination of substrates to be processed due to dust and remaining gas is prevented and a high production yield can be achieved.

Hereinafter, an embodiment of the present invention will be explained with reference to FIGS. 1 and 2.

FIGS. 1 and 2 show a vacuum processing apparatus of the present invention which is, in this case, a dry-etching apparatus for etching wafers, i.e., substrates to be processed by plasma.

Cassette tables 2a to 2c are disposed in an L-shape in this case in positions such that they can be loaded into and unloaded from the apparatus without changing their positions and postures. In other words, the cassettes 1a to 1c are fixed always in predetermined positions on a substantially horizontal plane, while the cassette tables 2a and 2b are disposed adjacent to and in parallel with each other on one or the sides of the L-shape. The cassette table 2c is disposed on the other side of the L-shape. The cassettes 1a and 1b are for storing unprocessed wafers and for recovering the processed wafers. They can store a plurality (usually 25) of wafers 20 as the substrates to be treated. The cassette 1c in this case is for storing the dummy wafers for effecting dry-cleaning using plasma (hereinafter referred to as "plasma-cleaning") and recovering the dummy wafers after plasma-cleaning. It can store a plurality of (usually twenty-five pieces) dummy wafers 30.

A load lock chamber 5 and unload lock chamber 6 are so disposed as to face the cassette tables 2a and 2b, and a conveyor 13 is disposed between the cassette tables 2a, 2b and the load lock chamber 5 and the unload lock chamber 6. The load lock chamber 5 is equipped with an evacuating device 3 and a gas introduction device 4, and can load unprocessed wafers in the vacuum apparatus through a gate valve 12a. The unload lock chamber 6 is similarly equipped with the evacuating device 3 and the gas introduction device 4, and can take out processed wafers to the atmosphere through a gate valve 12d. The conveyor 13 is equipped with a robot having X, Y, Z and axes, which operates so as to

deliver and receive the wafers 20 between the cassettes 1a, 1b and the load lock and unload lock chambers 5 and 6 and the dummy wafers 30 between the cassette 1c and the load lock and unload lock chambers 5 and 6.

The load lock chamber 5 and the unload lock chamber 6 are connected to a transfer chamber 16 through the gate valves 12b and 12c. The transfer chamber 16 is rectangular, in this case, and etching chambers 11a, 11b and 11c are disposed on the three side walls of the transfer chamber 16 through gate valves 15a, 15b and 15c, respectively. A conveyor 14 capable of delivering the wafers 20 or the dummy wafers 30 from the load lock chamber 5 to the etching chambers 11a, 11b, 11c and of delivering them from the chambers 11a, 11b, 11c to the unload lock chamber 6 is disposed inside the transfer chamber 16. The transfer chamber 16 is equipped with an evacuating device 17 capable of independent evacuation.

The etching chambers 11a, 11b, 11c have the same structure and can make the same processing. The explanation will be given on the etching chamber 11b by way of example. The etching chamber 11b has a sample table 8b for placing the wafers 20 thereon, and a discharge chamber is so provided as to define a discharge portion 7b above the sample table 8b. The etching chamber 11b includes a gas introduction device 10b for introducing a processing gas in the discharge portion 7b and an evacuating device 9b for decreasing the internal pressure of the etching chamber 11b to a predetermined pressure. The etching chamber 11b further includes generation means for generating a microwave and a magnetic field for converting processing gas in the discharge portion 7b to plasma.

A sensor 18 for measuring the intensity of plasma light is disposed at an upper part of the etching chamber. The measured value of the sensor 18 is inputted to a controller 19. The controller 19 compares the measured value from the sensor 18 with a predetermined one and determines the timing of cleaning inside the etching chamber. The controller 19 controls the conveyors 13 and 14 to control the transfer of the dummy wafers 30 between the cassette 1c and the etching chambers 11a to 11c.

In a vacuum processing apparatus having the construction described above, the cassettes 1a, 1b storing unprocessed wafers are first placed onto the cassette tables 2a, 2b by a line transfer robot which operates on the basis of the data sent from a host control apparatus, or by an operator. On the other hand, the cassette 1c storing the dummy wafers is placed on the cassette table 2c. The vacuum processing apparatus executes the wafer processing or plasma cleaning on the basis of recognition by itself of the production data provided on the cassettes 1a to 1c, of the data sent from the host control apparatus, or of the command inputted by an operator.

For instance, the wafers 20 are sequentially loaded in the order from above into the etching chambers 11a, 11b, 11c by the conveyors 13 and 14, and are etched. The etched wafers are stored in their original positions inside the cassette 1a by the conveyors 14 and 13. In this case, from the start to the end of the operation, without changing the position and posture of the cassettes, the unprocessed wafers are taken out from the cassettes and are returned in their original positions where the wafers have been stored, and are stored there. In this manner, the apparatus can easily cope with automation of the production line, contamination of the wafers due to dust can be reduced and high production efficiency and high production yield can thus be accomplished.

As etching is repeated, the reaction products adhere to and are deposited on the inner wall of the etching chambers 11a to 11c. Therefore, the original state must be recovered by removing the adhering matters by plasma cleaning. The controller 19 judges the timing of this plasma cleaning. In this case, a portion through which the plasma light passes is provided in each of the etching chambers 11a to 11c. The sensor 18 measures the intensity of the plasma light passing through this portion and when the measured value reaches a predetermined one, the start timing of plasma cleaning is judged. Alternatively, the timing of plasma cleaning may be judged by counting the number of wafers processed in each etching chamber by the controller 19 and judging the timing when this value reaches a predetermined value. The actual timing of plasma cleaning that is carried out may be during a processing of a predetermined number of wafers in the cassette 1a or 1b, after the processing of all the wafers 20 in a cassette is completed and before the processing of wafers in the next cassette.

Plasma cleaning is carried out in the following sequence. In this case, the explanation will be given about a case where the etching chambers 11a to 11c are subjected to plasma cleaning by using three dummy wafers 30 among the dummy wafers 30 (twenty-five dummy wafers are stored in this case) stored in the cassette 1c.

Dummy wafers 30 which are stored in the cassette 1c and are not used yet or can be used because the number of times of use for plasma cleaning is below a predetermined one are drawn by the conveyor 13. At this time, dummy wafers 30 stored in any position in the cassette 1c may be used but in this case, the position numbers of the dummy wafers in the cassette and their number of times of use are stored in the controller 19, and accordingly dummy wafers having smaller numbers of times of use are drawn preferentially. Then, the dummy wafers 30 are loaded in the load lock chamber 5 disposed on the opposite side to the cassette 1a by the conveyor 13 through the gate valve 12a in the same way as the transfer at the time of etching of wafers 20. After the gate valve 12a is closed, the load lock chamber 5 is evacuated to a predetermined pressure by the vacuum exhaust device 3 and then the gate valve 12b and 15a are opened. The dummy wafers 30 are transferred by the conveyor 14 from the load lock chamber 5 to the etching chamber 11a through the transfer chamber 16 and are placed on the sample table 8a. After the gate valve 15a is closed, plasma cleaning is carried out in the etching chamber 11a in which the dummy wafers 30 are disposed, under a predetermined condition.

In the interim, the gate valves 12a, 12b are closed and the pressure of the load lock chamber 5 is returned to the atmospheric pressure by the gas introduction device 4. Next, the gate valve 12a is opened and the second dummy wafer 30 is loaded in the load lock chamber 5 by the conveyor 13 in the same way as the first dummy wafer 30, and evacuation is effected again by the evacuating device 3 to a predetermined pressure after closing the gate valve 12a. Thereafter, the gate valves 12b and 15b are opened and the second dummy wafer 30 is transferred from the load lock chamber 5 to the etching chamber 11b through the transfer chamber 16 by the conveyor 14. Plasma cleaning is started after the gate valve 15b is closed.

In the interim, the third dummy wafer 30 is transferred into the etching chamber 11c in the same way as the second dummy wafer 30 and plasma cleaning is carried out.

After plasma cleaning is completed in the etching chamber 11a in which the first dummy wafer 20 is placed, the gate

valves 15a and 12c are opened. The used dummy wafer 30 is transferred from the etching chamber 11a to the unload lock chamber 6 by the conveyor 14. Then, the gate valve 12c is closed. After the pressure of the unload lock chamber 6 is returned to the atmospheric pressure by the gas introduction device 4, the gate valve 12d is opened. The used dummy wafer 30 transferred to the unload lock chamber 6 is taken out in the air by the conveyor 13 through the gate valve 12d and is returned to its original position in the cassette 1c in which it is stored at the start.

When plasma cleaning of the etching chambers 11b and 11c is completed, the second and third dummy wafers 20 are returned to their original positions in the cassette 1c.

In this way, the used dummy wafers 30 are returned to their original positions in the cassette 1c and the dummy wafers 30 are always stocked in the cassette 1c. When all the dummy wafers 30 in the cassette 1c are used for plasma cleaning or when the numbers of times of use of the wafers 30 reach the predetermined ones after the repetition of use, the dummy wafers 30 are replaced as a whole together with the cassette 1c. The timing of this replacement of the cassette is managed by the controller 19 and the replacement is instructed to the host control apparatus for controlling the line transfer robot or to the operator.

Although the explanation given above deals with the case where the etching chambers 11a to 11c are continuously plasma-cleaned by the use of three dummy wafers 30 among the dummy wafers 30 in the cassette 1c, other processing methods may be employed, as well.

For example, the etching chambers 11a to 11c are sequentially plasma-cleaned by the use of one dummy wafer 30. In the case of such plasma cleaning, unprocessed wafers 20 can be etched in etching chambers other than the one subjected to plasma cleaning, and plasma cleaning can thus be carried out without interrupting etching.

If the processing chambers are different, for example, there are an etching chamber, a post-processing chamber and a film-formation chamber, and wafers are sequentially processed while passing through each of these processing chambers, each of the processing chambers can be subjected appropriately to plasma cleaning by sending dummy wafers 30 during the processing of the wafers 20 which are stored in the cassette 1a or 2a and drawn and sent sequentially, by passing merely the dummy wafers 30 through the processing chambers for which plasma cleaning is not necessary, and by executing plasma cleaning only when the dummy wafers 30 reach the processing chambers which need plasma cleaning.

According to the embodiment described above, the cassette storing the dummy wafers and the cassettes storing the wafers to be processed are disposed together in the air, the dummy wafers are loaded from the cassette into the apparatus by the same conveyor as the conveyor for transferring the wafers, at the time of cleaning, and the used dummy wafers are returned to their original positions in the cassette. In this way, a mechanism for conducting exclusively plasma cleaning need not be provided, and the construction of the apparatus can be simplified. It is not necessary to handle plasma cleaning as a particular processing sequence, but the plasma cleaning can be incorporated in an ordinary etching processing and can be carried out efficiently in a series of operations.

The dummy wafers used for plasma cleaning are returned to their original positions in the cassette placed in the air. Accordingly, the used dummy wafers and the wafers before and after processing do not exist mixedly in the vacuum chamber, so that contamination of wafers due to dust and remaining gas does not occur unlike conventional apparatuses.

The used dummy wafers are returned to their original positions in the cassette and the numbers of times of their use is managed. Accordingly, it is possible to prevent the confusion of the used dummy wafers with the unused dummy wafers and the confusion of the dummy wafers having small numbers of times of use with the dummy wafers having large numbers of times of use. For these reasons, the dummy wafers can be used effectively without any problem when plasma cleaning is carried out.

Furthermore, in accordance with the present invention, the apparatus can have a plurality of processing chambers and can transfer wafers and dummy wafers by the same conveyor. Since plasma cleaning can be carried out by managing the timing of cleaning of each processing chamber by the controller, the cleaning cycle can be set arbitrarily, dry cleaning can be carried out without interrupting the flow of the processing, the processing can be efficiently made and the productivity can be improved.

As described above, according to the present invention, there are effects that the construction of the apparatus is simple, the substrates to be processed are free from contamination and the production yield is high.

What is claimed is:

1. A method of transferring a substrate, using an atmospheric loader comprising:

- (1) a single atmospheric transferring device for carrying in and carrying out, one by one, substrates between a cassette which receives plural substrates and two lock chambers;
- (2) opening and closing devices, provided at said two lock chambers and being opened and closed every carrying-in said substrate to one of the two lock chambers and very carrying-out said substrate from one of the two lock chambers; and
- (3) a cassette table for mounting said cassette at a position of which an upper region thereof is open to a cassette transferring path,

wherein the method comprises the steps of:

using said single atmospheric transferring device, taking out, one by one, said substrate from said cassette which is mounted on said cassette table, at said position, and carrying in, one by one, said substrate to one of said two lock chambers; and

using said single atmospheric transferring device, taking out, one by one, said substrate from one of said two [load] lock chambers, and carrying in said substrate to said cassette, wherein said opening and closing devices are opened and closed every carrying-in of said substrate, one by one, to one of the two lock chambers, and every carrying-out of said substrate, one by one, from one of the two lock chambers.

2. A method of transferring a substrate according to claim 1, wherein a substrate which is to be subjected to processing is carried into one of said two lock chambers, and a substrate which has been subjected to processing is carried to said cassette.

3. A method of transferring a substrate according to claim 2, wherein said single atmospheric transferring device is operated substantially at a front face of said two lock chambers.

4. A method of transferring a substrate according to claim 1, wherein said single atmospheric transferring device is operated substantially at a front face of said two lock chambers.

5. A method of transferring a substrate according to claim 4, wherein said two lock chambers comprise a load lock chamber and an unload lock chamber.

6. A method of transferring a substrate according to claim 3, wherein said two lock chambers comprise a load lock chamber and an unload lock chamber.

7. A method of transferring a substrate according to claim 2, wherein said two lock chambers comprise a load lock chamber and an unload lock chamber.

8. A method of transferring a substrate according to claim 1, wherein said two lock chambers comprise a load lock chamber and an unload lock chamber.

9. A substrate transferring apparatus comprising:

an atmospheric loader having

- (1) a single atmospheric transferring device for carrying in and carrying out, one by one, substrates between (a) a cassette which receives plural substrates and (b) two lock chambers,
- (2) opening and closing devices, provided at said two lock chambers and being opened and closed every carrying-in said substrate to one of the two lock chambers and every carrying-out said substrate from one of the two lock chambers; and
- (3) a cassette table for mounting said cassette at a position of which an upper region thereof is open to a cassette transferring path,

wherein said single atmospheric transferring device has a mechanism for carrying a substrate, one by one, to and out from said cassette which is mounted on said cassette table, at said position, and a mechanism for carrying a substrate, one by one, to and out from, said two lock chambers, and

wherein said opening and closing devices have structure causing the opening and closing devices to open and close every carrying-in of a substrate, one by one, to one of the two lock chambers, and every carrying-out of a substrate, one by one, from one of the two lock chambers.

10. A substrate transferring apparatus according to claim 9, wherein the mechanism for carrying the substrate to and out from the two lock chambers carries a substrate which is to be subjected to processing to one of said two lock chambers, and carries a substrate which has been subjected to processing from the other of said two lock chambers.

11. A substrate transferring apparatus according to claim 10, wherein said atmospheric loader is located at a front face of said two lock chambers.

12. A substrate transferring apparatus according to claim 9, wherein said atmospheric loader is located at a front face of said two lock chambers.

13. A substrate transferring apparatus according to claim 12, wherein said two lock chambers comprise a load lock chamber for carrying in said substrate which is to be subjected to processing and an unload lock chamber for carrying out said substrate which has been subjected to processing.

14. A substrate transferring apparatus according to claim 11, wherein said two lock chambers comprise a load lock chamber for carrying in said substrate which is to be subjected to processing and an unload lock chamber for carrying out said substrate which has been subjected to processing.

15. A substrate transferring apparatus according to claim 10, wherein said two lock chambers comprise a load lock chamber for carrying in said substrate which is to be subjected to processing and an unload lock chamber for carrying out said substrate which has been subjected to processing.

16. A substrate transferring apparatus according to claim 9, wherein said two lock chambers comprise a load lock chamber for carrying in said substrate which is to be subjected to processing and an unload lock chamber for carrying out said substrate which has been subjected to processing.

9

17. A substrate transferring apparatus comprising:
an atmospheric loader having

- (1) a single atmospheric transferring device for carrying in and carrying out, one by one, substrates between (a) a cassette which receives plural substrates and (b) two lock chambers, 5
- (2) [a] opening and closing devices, provided respectively at said two lock chambers and being opened and closed every carrying-in said substrate to one of the two lock chambers and every carrying-out said substrate from one of the two lock chambers; and 10
- (3) a cassette table for mounting said cassette, at a position of which an upper region thereof is open to a cassette transferring path,

wherein said single atmospheric transferring device has a mechanism for carrying in and carrying out, one by

10

one, a substrate between said cassette which is mounted on said cassette table, at said position, and [said atmospheric loader, and a mechanism for carrying in and carrying out, one by one, said substrate between said atmospheric loader and said two lock chambers.] *a lock chamber of said two lock chambers*, and
wherein said opening and closing devices have structure causing the opening and closing devices to open and close every carrying-in of a substrate, one by one, to one of the two lock chambers, and every carrying out of a substrate, one by one, from one of the two lock chambers.

* * * * *