



(51) International Patent Classification:

H04W 4/22 (2009.01) H04L 12/46 (2006.01)
H04W 76/00 (2009.01) H04W 76/02 (2009.01)
H04L 29/06 (2006.01) H04W 92/02 (2009.01)
H04W 36/14 (2009.01) H04L 12/24 (2006.01)
H04W 48/18 (2009.01) H04L 29/12 (2006.01)

(21) International Application Number:

PCT/EP2016/056342

(22) International Filing Date:

23 March 2016 (23.03.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15161141.5 26 March 2015 (26.03.2015) EP

(71) Applicant: **DEUTSCHE TELEKOM AG** [DE/DE];
Friedrich-Ebert-Allee 140, 53113 Bonn (DE).(72) Inventor: **LAUSTER, Reinhard**; Südtirolerstraße 30,
3100 St. Pölten (AT).(74) Agents: **SCHWÖBEL, Thilo** et al.; Kutzenberger Wolff &
Partner, Theodor-Heuss-Ring 23, 50668 Köln (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD FOR IMPROVED HANDLING OF EMERGENCY CALLS IN A ROAMING SCENARIO, TELECOMMUNICATIONS NETWORK, PROGRAM AND COMPUTER PROGRAM PRODUCT




Fig. 1

(57) Abstract: Method for improved handling of emergency calls during roaming, wherein a user equipment is assigned to a home network, wherein a first node of the visited network communicates with a second node of the home network via an IP transportation tunnel, wherein upon establishment and/or modification of the tunnel emergency service information is transmitted to the second node of the home network, wherein in case that both • a voice call is initiated by the user equipment using a specific emergency call telephone number being a valid emergency call telephone number in the visited telecommunications network, and • the user equipment is initially handling the voice call - involving the specific emergency call telephone number - as a normal voice call, the method comprises the sequential steps of: • the voice call is initiated by the user equipment by means of transmitting a first message to the second node of the home network, the first message comprising the specific emergency call telephone number, • the specific emergency call telephone number is detected - based on the emergency service information transmitted to the second node of the home network -, by the home network, as being a valid emergency call telephone number within the visited network in relation to the voice call, • a second message is generated by the home network, the second message being transmitted to the user equipment, and comprising an indication, to

the user equipment, to trigger an emergency call procedure in accordance to the configuration of the visited network by means of a third message.

5 **METHOD FOR IMPROVED HANDLING OF EMERGENCY CALLS IN
A ROAMING SCENARIO, TELECOMMUNICATIONS
NETWORK, PROGRAM AND COMPUTER PROGRAM PRODUCT**

BACKGROUND

10 **[0001]** The present invention relates a method for improved handling of emergency
calls in a roaming scenario, wherein a user equipment is assigned to a home
telecommunications network, and connected to a visited telecommunications network,
wherein a first network node of the visited telecommunications network communicates
with a second network node of the home telecommunications network by means an IP
15 transportation tunnel, wherein an appropriate handling is provided in case that both a
voice call is initiated by the user equipment using a specific emergency call telephone
number being a valid emergency call telephone number in the visited telecommunications
network, and the user equipment initially handling the voice call – involving the specific
emergency call telephone number – as a normal voice call (non-UE detected emergency
20 call).

[0002] Furthermore, the present invention relates to a telecommunications network
and to a system for improved handling of emergency calls in a roaming scenario, wherein
a user equipment is assigned to a home telecommunications network, and connected to
a visited telecommunications network, wherein the system comprises the home
25 telecommunications network and the visited telecommunications network, wherein a first
network node of the visited telecommunications network communicates with a second
network node of the home telecommunications network by means an IP transportation
tunnel, wherein an appropriate handling is provided in case that both a voice call is
initiated by the user equipment using a specific emergency call telephone number being a
30 valid emergency call telephone number in the visited telecommunications network, and
the user equipment initially handling the voice call – involving the specific emergency call
telephone number – as a normal voice call (non-UE detected emergency call).

[0003] Additionally, the present invention relates to a program and to a computer
program product for improved handling of emergency calls in a roaming scenario.

[0004] The present invention relates to the area of both wireless and nomadic or fixed communications. To support large numbers of (roaming) subscribers – e.g. mobile subscribers or nomadic, i.e. temporarily fixed subscribers – a number of telecommunications networks such as public land mobile networks and/or stationary 5 (fixed line) networks have been established and are operative. Telecommunications networks such as public land mobile networks (PLMNs) may communicatively connect to other mobile telecommunications networks and/or to fixed, land-wired public switched telephone networks (PSTNs) and/or to data networks such as the internet (or IP-networks, internet protocol networks). User equipments (e.g. a mobile or nomadic 10 terminal) are typically assigned to a home telecommunications network, such as a home public land mobile network. In a roaming scenario, the user equipment is typically not located in reach of the home telecommunications network (or home public land mobile network) but is connected to a visited telecommunications network (or visited public land mobile network). Most modern telecommunications network (such as public land mobile 15 networks or also data networks) are packet-switched networks, in which data are routed in autonomous units called data packets. Packet-switched networks are characterized by high speed, low latency, and high network resource utilization efficiency. Two examples of packet-switched technologies are the General Packet Radio Service (GPRS) of the Global System for Mobile communications (GSM), and the Evolved Packet System 20 (EPS), also commercially known as the Long Term Evolution (LTE), of the Universal Mobile Telecommunications System (UMTS), wireless local area network (WLAN). The Internet Protocol (IP) is a widely-deployed protocol for data communications in packet-switched networks. The IP Multimedia System (IMS) is an industry standard framework for delivering voice and multimedia communications over IP networks. Communications 25 between nodes within an IMS network utilize the Session Initiation Protocol (SIP). SIP is a signaling protocol for Internet conferencing, telephony, presence, events notification, instant messaging, and the like. SIP signaling uses a long-term stable identifier, the SIP Universal Resource Indicator (URI). SIP signaling data packets in an IMS network are processed by network node of the telecommunications network, usually also called SIP 30 servers or proxies. Together, these network nodes provide a call session control function (CSCF). Different types of such CSCF network nodes perform specific functions: A proxy call session control function (P-CSCF) is a SIP proxy that is the first point of contact for a user equipment (or an IMS terminal). Typically, the proxy call session control function that a user equipment uses is located in the visited telecommunications network in case that 35 local breakout is used. In case local breakout is not used, the proxy call session control function a user equipment normally uses is located in the home telecommunications

network (i.e. the proxy call session control function is part of or is assigned to the home telecommunications network).

[0005] Also IMS enabled user equipments need to be able to place emergency calls even when located in (and connected to) a visited telecommunications network. Non-UE-5 detected emergency calls (i.e. emergency calls that are placed (or initiated) by the user equipment which are emergency calls in the network environment of the user equipment (i.e. in the visited telecommunications network) that the user equipment is unaware of, e.g. due to the use of an emergency call telephone number (valid in the visited telecommunications network) that is not maintained in a list within the user equipment) 10 are relatively easy to handle in case of using local breakout: In this case, the local proxy call session control function (i.e. the proxy call session control function of the visited telecommunications network) has a list of the local emergency numbers (of the visited telecommunications network or valid within the respective context of the user equipment in the visited telecommunications network), and is hence able to detect the call type (i.e. 15 the emergency type of an emergency call) and apply the needed procedures to guarantee successful handling of the requested emergency service.

[0006] In scenarios where no local breakout is to be used, and each call is routed to (a respective proxy call session control function within) the home telecommunications network, there is only the possibility to maintain a (normally huge) list of local emergency 20 numbers (that are applicable or valid within the different telecommunications networks of all the possible roaming partners of the home telecommunications network) with a mapping to the related uniform resource names of the emergency call telephone numbers (also called sos-uniform resource names) in the local network node or the home telecommunications network (typically a proxy call session control function of the home 25 telecommunications network). The maintenance of such a database for all roaming partners worldwide requires a considerable effort and – hence – is very costly.

SUMMARY

[0007] An object of the present invention is to provide an effective and simple 30 solution (especially reducing operational costs (OPEX costs)) to exchange local emergency call information (i.e. the emergency call telephone numbers applicable in the possible visited telecommunications networks, i.e. roaming partners of the (home) telecommunications network) such that any local emergency calls in roaming situations (without local breakout) can be treated correctly by the home telecommunications

network with a drastically reduced effort to maintain a database or a list of emergency call number information of numerous potential visited telecommunications networks, and without the need to rely on user equipment implementation, e.g. in an approach to provide (emergency call) numbers (of the local visited telecommunications network) to the user equipment.

[0008] The object of the present invention is achieved by a method for improved handling of emergency calls in a roaming scenario, wherein a user equipment is assigned to a home telecommunications network, and wherein the user equipment is connected to a visited telecommunications network, wherein a first network node of the visited telecommunications network communicates with a second network node of the home telecommunications network by means an IP transportation tunnel, wherein upon an establishment step of the IP transportation tunnel and/or upon a modification step of the IP transportation tunnel an emergency service information is transmitted to the second network node of the home telecommunications network, wherein in case that both

- a voice call is initiated by the user equipment using a specific emergency call telephone number being a valid emergency call telephone number in the visited telecommunications network, and
- the user equipment initially handling the voice call – involving the specific emergency call telephone number – as a normal voice call (non-UE detected emergency call),

the method comprises the steps of:

- in a first step, the voice call is initiated by the user equipment by means of transmitting a first message to the (second network node of the) home telecommunications network, the first message comprising the specific emergency call telephone number,
- in a second step, subsequent to the first step, the specific emergency call telephone number is detected – based on the emergency service information transmitted to the (second network node of the) home telecommunications network –, by the home telecommunications network, as being a valid emergency call telephone number within the visited telecommunications network in relation of the voice call,
- in a third step, subsequent to the second step, a second message is generated by the home telecommunications network, the second message being transmitted to the user equipment, the second message comprising an indication, to the user equipment, to trigger an emergency call procedure in accordance to the configuration of the visited telecommunications network by means of a third message.

[0009] It is thereby advantageously possible according to the present invention to identify local emergency calls in roaming scenarios without the need to rely on user equipment implementation when providing numbers to the user equipment, and drastically reducing the efforts to maintain – within the home telecommunications network 5 – a list of local emergency numbers of all roaming partners that is always up to date. According to the present invention, it is hence advantageously possible that network operators are enabled to deploy a simple, cost efficient, and network-based method with minor provisioning effort to handle non-user equipment detected emergency calls when roaming without local breakout. The transport of the emergency service information can 10 be done dynamically at bearer establishment by reusing well defined IP tunnel transport towards the home telecommunications network without an impact on potentially encrypted SIP signaling, i.e. separated from SIP signaling.

[0010] National regulation defines emergency services by the local numbering plan. If an emergency number (i.e. an emergency call telephone number) is not provisioned to 15 a user equipment (or a terminal equipment such as an IMS UE or generic SIP UE, etc) and the user dials such an unknown emergency number (i.e. a telephone number for which the user equipment is not aware that it is an emergency number), the user equipment will initiate the call setup as a normal call using the dialed telephone number. Therefore, it needs to be assured to detect that the initiated call is dedicated to an 20 emergency service, identify the service and proceed with the correct procedures related to this service, such as, e.g., assigning an sos-URN (uniform resource name of the sos top level domain, especially as defined according to the 3GPP (Third Generation Partnership Project) and/or IETF (Internet Engineering Task Force standard)) to guarantee the routing to the respective responsible public safety answering point (PSAP).

25 **[0011]** According to the present invention, an improved handling of emergency calls in a roaming scenario is possible in cases where the proxy functionality of the home telecommunications network is used in the roaming scenario, i.e. in cases without local breakout. It is therefore advantageously possible according to the present invention that the visited telecommunications network (more specifically the enhanced packet system of 30 the visited telecommunications network) is responsible to provide the necessary emergency service information pending the local emergency regulation (e.g. regarding the local numbering plan).

[0012] According to the present invention, an IP transportation tunnel is established between (at least) a first network node of the visited telecommunications network and a 35 second network node of the home telecommunications network. The IP transportation

tunnel is especially realized by means of a GTP tunnel, the term “GTP tunnel” referring to a tunnel using the GPRS Tunneling protocol (GTP). The GTP is an IP/UDP-based protocol (Internet Protocol/User Datagram Protocol) used in GSM core networks (i.e. the so-called second generation telecommunications networks, according to the Global System for Mobile Communication standard), UMTS core networks (i.e. the so-called third generation telecommunications network, according to the Universal Mobile Telecommunications System) and LTE core networks (i.e. the so-called fourth generation telecommunications network, according to the Long Term Evolution standard). The GTP is used to encapsulate user data when passing between and/or through network node of the core network, and also carries bearer specific signaling traffic between various network nodes of the core network. The GTP is typically implemented using a GTP-C part as well as a GTP-U part. The GTP-C part is the control part, used for specific signaling (e.g. bearer activation/deletion/modification, etc.) in GPRS, UMTS, and LTE / SAE (System Architecture Evolution) / EPC (Evolved Packet Core) networks. The GTP-U part is used in user plane to carry user data traffic in GPRS, UMTS and LTE networks.

Additionally, a GTP' part might be implemented, the GTP' part being used for carrying charging data. According to the present invention, the IP transportation tunnel (or a part thereof, such as the GTP-C part) can also be established – besides between the first network node of the visited telecommunications network and a second network node of the home telecommunications network (where, e.g., the GTP-U part is established) – between an additional network node (such as the responsible mobility management entity) of the visited telecommunications network and the second network node of the home telecommunications network.

[0013] The valid emergency call telephone numbers can vary from country to country and also their number and the associated or assigned emergency types of the emergency call telephone numbers. The telephone number used by the user equipment to initiate the voice call is also called the specific emergency call telephone number. The assumption is that the user equipment is not aware of the fact of using a valid emergency call telephone number, i.e. the initiated voice call is a non-user equipment detected emergency call: The user equipment initially handles the voice call – involving the specific emergency call telephone number – as a normal voice call (as at least part of the locally (in the visited telecommunications network) valid emergency call telephone numbers might not be provided or provisioned to the user equipment). According to the present invention, the inventive method comprises the user equipment initially handling the voice call (using the specific emergency telephone number) like any other voice call.

[0014] The present invention refers to a roaming situation of the user equipment, i.e. the user equipment is – while being assigned (or registered as a valid subscriber or assigned to a valid subscription) to its home telecommunications network – connected to the visited telecommunications network, i.e. the user equipment camps on the visited telecommunications network or on the access network of the visited telecommunications network. According to the present invention, the emergency service information (of the visited telecommunications network) is transmitted to the second network node of the home telecommunications network, using the IP transportation tunnel. According to the present invention, the transmission of the emergency service information is related to the existence or applicability of the) roaming situation of the user equipment in such a manner that upon invocation of the roaming situation, the emergency service information is transmitted using the IP transportation tunnel. As the IP transportation tunnel is established between (at least) a first network node of the visited telecommunications network and a second network node of the home telecommunications network, it is primary the first network node of the visited telecommunications network that transmits the emergency service information; hence, according to a preferred embodiment of the present invention, the first network node of the visited telecommunications network, or another network node (of the core network) of the visited telecommunications network, transmits the emergency service information to the second network node of the home telecommunications network. There are two main cases or scenarios: According to the first scenario, the user equipment is switched on (or a (first or initial) data connection of the user equipment is established) while being located in the coverage area of the visited telecommunications network; according to the second scenario, the user equipment enters the coverage area of the visited telecommunications network while being connected (during a point in time prior to entering the new coverage area) to the home telecommunications network (or to another visited telecommunications network). According to the present invention, it is assured (i.e. the visited telecommunications network and the home telecommunications network are configured such) that the emergency service information is transmitted to the home telecommunications network in both of the mentioned scenarios; in the first scenario, the IP transportation tunnel is generated upon the user equipment being switched on, whereas in the second scenario, the IP transportation tunnel is rather modified (instead of being completely (newly) generated) at a point in time when the user equipment is handed over (either from the home telecommunications network or from another visited telecommunications network) to the visited telecommunications network.

[0015] After the emergency service information being transmitted to the home telecommunications network, the home telecommunications network is aware of the

emergency call telephone numbers currently applicable in the visited telecommunications network, and hence, in case that (at a point in time subsequent to the transmission of the emergency service information) both the following two conditions are fulfilled:

- a voice call is initiated by the user equipment (while the user equipment still being in the coverage area of the visited telecommunications network) using a specific emergency call telephone number being a valid emergency call telephone number in the visited telecommunications network, and
- the user equipment initially handling the voice call – involving the specific emergency call telephone number – as a normal voice call (non-UE detected emergency call, i.e. the user equipment is, at least initially not aware of the used telephone number being a valid emergency call telephone number (with respect to the visited telecommunications network)),

the home telecommunications network is able to indicate to the user equipment how to behave in order to correctly treat the voice call (using the specific emergency call telephone number, i.e. a valid emergency call telephone number within the visited telecommunications network). Specifically, this is done, according to the present invention, by means of

- in a first step, the user equipment initiating the voice call by transmitting a first message to the second network node of the home telecommunications network
- in a second step, the home telecommunications network – based on the emergency service information – detecting (or recognizing) the specific emergency call telephone number as being a valid emergency call telephone number within the visited telecommunications network (i.e. by means of the emergency service information, the home telecommunications network becomes aware that the telephone number used by the user equipment corresponds to a valid emergency call telephone number within the visited telecommunications network), and
- in a third step, transmitting a second message from the home telecommunications network to the user equipment, thereby indicating to the user equipment how to behave (i.e. by means of the second message, the user equipment becomes aware of having initiated an emergency call by originally initiating the voice call and triggering the first message), i.e. comprising an indication to the user equipment to trigger an emergency call procedure in accordance to the configuration of the visited telecommunications network by means of a third message (to be sent typically from the user equipment to the visited telecommunications network). According to the present invention, the first message comprises the specific emergency call telephone number such that the home telecommunications network – based on the available emergency service information of the visited telecommunications network – is able to detect or recognize the used (i.e.

specific) emergency call telephone number as being a valid emergency call telephone number.

[0016] By means of transmitting the emergency service information from the visited telecommunications network to the home telecommunications network, it is
5 advantageously possible according to the present invention, that an updated database information regarding the current emergency call telephone numbers applicable in the visited telecommunications network can be provided for (e.g. generated) in the home telecommunications network. Relating to a certain number of (different) visited telecommunications networks, such pieces of emergency service information are
10 transmitted to the home telecommunications network for any user equipment being either switched on in the visited telecommunications network or entering the coverage area of the visited telecommunications network; hence in case such a database is maintained within the home telecommunications network, it is necessarily always automatically kept up to date. The transport of the emergency service information can be done dynamically
15 at bearer establishment by reusing well defined IP tunnel transport towards the home telecommunications network without an impact on potentially encrypted SIP signaling, i.e. separated from SIP signaling.

[0017] According to the present invention it is preferred that
-- the normal manner is a non-emergency call manner and/or that the proxy
20 functionality of the home telecommunications network is used in the roaming scenario (no local breakout)
and/or that
-- the normal voice call is a non-emergency call manner and/or that a proxy functionality of the home telecommunications network is used in the roaming scenario (no local
25 breakout).

[0018] According to a further embodiment of the present invention, the home telecommunications network comprises a home access network and a home core network, and the visited telecommunications network comprises a visited access network and a visited core network, wherein the visited access network of the visited
30 telecommunications network comprises a plurality of access entities, especially base station entities, wherein the user equipment is connected to the visited telecommunications network via one of the access entities, especially base station entities, being the serving access entity, especially the serving base station entity, of the user equipment, wherein the first network node of the visited telecommunications network
35 corresponds to the serving access entity, especially the serving base station entity, of the

user equipment and/or to a mobility management entity of the visited telecommunications network, and the second network node of the home telecommunications network corresponds to a serving gateway or to a packet data gateway of the home core network.

[0019] Thereby, it is advantageously possible according to the present invention that
5 the IP transportation tunnel is realized between, on the one hand, the serving base station entity of the user equipment and/or to the corresponding mobility management entity of the user equipment in the visited telecommunications network, and, on the other hand, the serving gateway or to the packet data gateway of the home core network. Especially, it is advantageously possible that
10 -- one part of the IP transportation tunnel, e.g. a GTP-C part, is established between the mobility management entity of (the user equipment in) the visited telecommunications network, and either the serving gateway or to the packet data gateway of the home core network and
-- another part of the IP transportation tunnel, e.g. a GTP-U part, is established
15 between the serving base station entity of the user equipment, and either the serving gateway or to the packet data gateway of the home core network.

[0020] According to a further embodiment of the present invention, it is also possible and preferred that the emergency service information comprises, especially for each of possibly a plurality of different emergency call telephone numbers being valid in the
20 visited telecommunications network:

- a uniform resource name, especially related to an emergency type and/or
- an information related to the emergency type and/or
- the emergency call telephone number,

and, wherein especially the emergency service information also comprises an information
25 identifying the visited telecommunications network.

[0021] According to the present invention, it is thereby advantageously possible – according to one variant of the present invention – that the emergency service information comprises an information identifying the visited telecommunications network – e.g. a combination of the MCC (Mobile Country Code) and the MNC (Mobile Network
30 Code) or an information encoding a combination of these data – as well as the complete list of emergency call telephone numbers, such that, for each of that list of emergency call telephone numbers, the emergency service information comprises a uniform resource name, especially related to an emergency type, and/or an information related to the emergency type and/or the emergency call telephone number.

[0022] Alternatively, according to further variants of the present invention, the emergency service information does not comprise an information identifying the visited telecommunications network, but only the complete list of emergency call telephone numbers, such that, for each of that list of emergency call telephone numbers, the
5 emergency service information comprises a uniform resource name, especially related to an emergency type, and/or an information related to the emergency type and/or the emergency call telephone number.

[0023] According to the present invention it is furthermore preferred that the second message comprises an emergency call information, wherein the emergency call
10 information comprises

- a uniform resource name, especially related to an emergency type and/or
- an information related to the emergency type and/or
- the specific emergency call telephone number.

[0024] According to the present invention, it is thereby advantageously possible
15 according to variants of the present invention, the emergency call information comprises, e.g., a uniform resource name (such as a uniform resource name that is not at all related to a specific emergency type or such as a uniform resource name that is related to a specific emergency type). According to further (alternative or cumulative) variants of the present invention, the emergency call information comprises an information related to the
20 emergency type. Furthermore, (likewise alternatively or cumulatively to the other possible parts of the emergency call information) the emergency call information comprises the specific emergency call telephone number (i.e. the one used by the user equipment when initiating the voice call (or emergency call)). Furthermore (likewise alternatively or cumulatively to the other possible parts of the emergency call information), the
25 emergency call information comprises a further specific emergency call telephone number (i.e. a different emergency call telephone number when compared to the specific emergency call telephone number).

[0025] According to a further preferred embodiment of the present invention, the home telecommunications network comprises a home access network and a home core
30 network, and the visited telecommunications network comprises a visited access network and a visited core network, wherein – within the home core network of the home telecommunications network – the emergency service information is transmitted to a further network node of the home core network, especially a network node of the IP Multimedia Subsystem (or IP Multimedia System) (IMS), wherein the further network

node of the home core network especially corresponds to the network node realizing the proxy call session control function for the voice call.

[0026] Thereby, it is advantageously possible according to the present invention that the local network node of the IMS (i.e. the local node of the IMS of the home
5 telecommunications network) is able to detect the call type and apply the needed procedures to guarantee successful handling of the call, i.e. in case of a non-UE detected emergency call in the context of the visited telecommunications network, successful handling of the requested emergency service, i.e. apply the already standardized procedures to trigger the user equipment to establish a successful emergency call in the
10 visited telecommunications network. Preferably, the second network node of the home telecommunications network (i.e. the network node of the home telecommunications network that is terminating the IP transportation tunnel upon which the emergency service information is transported, typically either a GTP-C part of that tunnel or a GTP-U part) extracts the emergency service information and transfers this information to the related
15 nodes of the IMS network (i.e. to the further network node of the home telecommunications network).

[0027] According to all embodiments of the present invention, the emergency service information is stored, in the home telecommunications network, in a database, wherein especially the database is accessible to all network nodes of the IP Multimedia
20 Subsystem (IMS) of the home telecommunications network.

[0028] It is thereby advantageously possible according to the present invention that such a database comprises all the potentially relevant sets of emergency service information, provided via the respective IP transportation tunnels in relation to all user equipments that are currently in a roaming situation with visited telecommunications
25 networks (from the point of view of the home telecommunications network). Due to the fact that the database entry regarding a specific visited telecommunications network is – at least potentially – updated any time a user equipment initiates being in a roaming situation with respect to this specific visited telecommunications network, such a database is automatically and inherently always kept up to date.

30 **[0029]** According to the present invention it is furthermore preferred that the IP transportation tunnel comprises a user plane (or user part) and a control plane (or control part), wherein the first and second message are transported using the user plane (or user part) of the IP transportation tunnel, and wherein the emergency service information is transported using the control plane (or control part) of the IP transportation tunnel.

[0030] Thereby, it is advantageously possible to use the mechanisms of the GTP as IP transportation tunnel, especially the GTP-C as the control plane or control part of the IP transportation tunnel, and the GTP-U as the user plane or user part of the IP transportation tunnel.

5 **[0031]** Furthermore, the present invention relates to a system for improved handling of emergency calls in a roaming scenario, wherein a user equipment is assigned to a home telecommunications network, and wherein the user equipment is connected to a visited telecommunications network, wherein the system comprises the home telecommunications network and the visited telecommunications network, wherein a first
10 network node of the visited telecommunications network communicates with a second network node of the home telecommunications network by means an IP transportation tunnel,
wherein upon an establishment step of the IP transportation tunnel and/or upon a modification step of the IP transportation tunnel an emergency service information is
15 transmitted to the second network node of the home telecommunications network, wherein in case that both

- a voice call is initiated by the user equipment using a specific emergency call telephone number being a valid emergency call telephone number in the visited telecommunications network, and
- 20 -- the user equipment initially handling the voice call – involving the specific emergency call telephone number – as a normal voice call (non-UE detected emergency call), the system is configured such that:
 - the voice call is initiated by the user equipment by means of transmitting a first message to the (second network node of the) home telecommunications network, the first
25 message comprising the specific emergency call telephone number,
 - the specific emergency call telephone number is detected – based on the emergency service information transmitted to the second network node of the home telecommunications network –, by the home telecommunications network, as being a valid emergency call telephone number within the visited telecommunications network in
30 relation to the voice call,
 - a second message is generated by the home telecommunications network, the second message being transmitted to the user equipment, the second message comprising an indication, to the user equipment, to trigger an emergency call procedure in accordance to the configuration of the visited telecommunications network by means of
35 a third message.

[0032] Furthermore, the present invention relates to a system for improved handling of emergency calls in a roaming scenario, wherein a user equipment is assigned to a home telecommunications network, and wherein the user equipment is connected to a visited telecommunications network, wherein the system comprises the home
5 telecommunications network, the visited telecommunications network and the user equipment, wherein a first network node of the visited telecommunications network communicates with a second network node of the home telecommunications network by means an IP transportation tunnel,
wherein upon an establishment step of the IP transportation tunnel and/or upon a
10 modification step of the IP transportation tunnel an emergency service information is transmitted to the second network node of the home telecommunications network,
wherein in case that both

- a voice call is initiated by the user equipment using a specific emergency call telephone number being a valid emergency call telephone number in the visited
15 telecommunications network, and
- the user equipment initially handling the voice call – involving the specific emergency call telephone number – as a normal voice call (non-UE detected emergency call),

the system is configured such that:

- the user equipment is adapted to initiate the voice call by means of transmitting a first
20 message to the second network node of the home telecommunications network, the first message comprising the specific emergency call telephone number,
- the home telecommunications network is adapted to detect – based on the emergency service information transmitted to the second network node of the home telecommunications network – the specific emergency call telephone number as being a
25 valid emergency call telephone number within the visited telecommunications network in relation to the voice call,
- the home telecommunications network is adapted to generate a second message, and to transmit the second message to the user equipment, the second message comprising an indication, to the user equipment, to trigger an emergency call procedure
30 in accordance to the configuration of the visited telecommunications network by means of a third message.

[0033] Thereby, it is advantageously possible to provide a system that is capable of automatically handling local emergency calls in roaming scenarios (without local breakout and without the need to rely on user equipment implementation when providing numbers
35 to the user equipment) in a correct manner, just by initially transmitting the emergency service information to the home telecommunications network. Consequently, it is advantageously possible to drastically reduce the efforts necessary to maintaining an up

to date list of local emergency numbers of all roaming partners (i.e. of all potential visited telecommunications networks) in the home telecommunications network.

[0034] According to the present invention it is furthermore preferred – especially with respect to the inventive system – that the system is configured such that the emergency service information comprises, especially for each of possibly a plurality of different emergency call telephone numbers being valid in the visited telecommunications network:

- a uniform resource name, especially related to an emergency type and/or
- an information related to the emergency type and/or
- the emergency call telephone number,

10 and, wherein especially the emergency service information also comprises an information identifying the visited telecommunications network.

[0035] Furthermore, the present invention relates to a telecommunications network for improved handling of emergency calls in a roaming scenario, wherein a user equipment is assigned to a home telecommunications network, and wherein the user equipment is connected to the telecommunications network as a visited telecommunications network, wherein a first network node of the telecommunications network communicates with a second network node of the home telecommunications network by means an IP transportation tunnel,

15 wherein upon an establishment step of the IP transportation tunnel and/or upon a modification step of the IP transportation tunnel an emergency service information is transmitted to the second network node of the home telecommunications network, wherein in case that both

- a voice call is initiated by the user equipment using a specific emergency call telephone number being a valid emergency call telephone number in the

25 telecommunications network, and

- the user equipment initially handling the voice call – involving the specific emergency call telephone number – as a normal voice call (non-UE detected emergency call),

the telecommunications network is configured such that:

- the voice call is initiated by the user equipment by means of transmitting a first

30 message to the (second network node of the) home telecommunications network, the first message comprising the specific emergency call telephone number,

- the specific emergency call telephone number is detected – based on the emergency service information transmitted to the second network node of the home telecommunications network –, by the home telecommunications network, as being a

35 valid emergency call telephone number within the telecommunications network in relation to the voice call,

-- a second message is generated by the home telecommunications network, the second message being transmitted to the user equipment, the second message comprising an indication, to the user equipment, to trigger an emergency call procedure in accordance to the configuration of the telecommunications network by means of a third 5 message.

[0036] Furthermore, the present invention relates to a telecommunications network for improved handling of emergency calls in a roaming scenario, wherein a user equipment is assigned to a home telecommunications network, and wherein the user equipment is connected to the telecommunications network as a visited 10 telecommunications network, wherein a first network node of the telecommunications network communicates with a second network node of the home telecommunications network by means an IP transportation tunnel, wherein upon an establishment step of the IP transportation tunnel and/or upon a modification step of the IP transportation tunnel an emergency service information is 15 transmitted to the second network node of the home telecommunications network, wherein in case that both

- a voice call is initiated by the user equipment using a specific emergency call telephone number being a valid emergency call telephone number in the telecommunications network, and

20 -- the user equipment initially handling the voice call – involving the specific emergency call telephone number – as a normal voice call (non-UE detected emergency call), the telecommunications network is configured such that:

- the user equipment is adapted to initiate the voice call by means of transmitting a first message to the second network node of the home telecommunications network, the first 25 message comprising the specific emergency call telephone number,
- the home telecommunications network is adapted to detect – based on the emergency service information transmitted to the second network node of the home telecommunications network – the specific emergency call telephone number as being a valid emergency call telephone number within the telecommunications network in relation 30 to the voice call,
- the home telecommunications network is adapted to generate a second message, and to transmit the second message to the user equipment, the second message comprising an indication, to the user equipment, to trigger an emergency call procedure in accordance to the configuration of the telecommunications network by means of a third 35 message.

[0037] Thereby, it is advantageously possible to provide the telecommunications network as a visited telecommunications network such that local emergency calls in roaming scenarios that do not use local breakout can be handled easily and without the need to rely on user equipment implementation when providing numbers to the user equipment.

[0038] Furthermore, the present invention relates to telecommunications network or network node within an inventive system, wherein the telecommunications network and/or the network node is either part of the home telecommunications network of the system or of the visited telecommunications network of the system.

10 **[0039]** Thereby, it is advantageously possible to provide a telecommunications network and/or a network node such that local emergency calls in roaming scenarios that do not use local breakout can be handled easily and without the need to rely on user equipment implementation when providing numbers to the user equipment.

[0040] Additionally, the present invention relates to a program comprising a
15 computer readable program code which, when executed on a computer or on a network node of a home telecommunications network or on a network node of a visited telecommunications network, or in part on the network node of the home telecommunications network and in part on the network node of the visited telecommunications network, causes the computer or the network node of the home
20 telecommunications network or the network node of the visited telecommunications network to perform the inventive method.

[0041] Still additionally, the present invention relates to a computer program product for a home telecommunications network and/or a visited telecommunications network, the computer program product comprising a computer program stored on a storage medium,
25 the computer program comprising program code which, when executed on a computer or on a network node of a home telecommunications network or on a network node of a visited telecommunications network, or in part on the network node of the home telecommunications network and in part on the network node of the visited telecommunications network, causes the computer or the network node of the home
30 telecommunications network or the network node of the visited telecommunications network to perform the inventive method.

[0042] These and other characteristics, features and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the

principles of the invention. The description is given for the sake of example only, without limiting the scope of the invention. The reference figures quoted below refer to the attached drawings.

5

BRIEF DESCRIPTION OF THE DRAWINGS

[0043] **Figure 1** schematically illustrate a system according to the present invention, comprising a first telecommunications network (or home telecommunications network) and a second telecommunications network (or visited telecommunications network), and a user equipment connected to the visited telecommunications network.

10 **[0044]** **Figure 2** schematically illustrate a communication diagram between the user equipment, the home telecommunications network and the visited telecommunications network, wherein the exchange of different messages is shown in view of initiating an emergency call.

15

DETAILED DESCRIPTION

[0045] The present invention will be described with respect to particular embodiments and with reference to certain drawings but the invention is not limited thereto but only by the claims. The drawings described are only schematic and are non-limiting. In the drawings, the size of some of the elements may be exaggerated and not
20 drawn on scale for illustrative purposes.

[0046] Where an indefinite or definite article is used when referring to a singular noun, e.g. "a", "an", "the", this includes a plural of that noun unless something else is specifically stated.

[0047] Furthermore, the terms first, second, third and the like in the description and
25 in the claims are used for distinguishing between similar elements and not necessarily for describing a sequential or chronological order. It is to be understood that the terms so used are interchangeable under appropriate circumstances and that the embodiments of the invention described herein are capable of operation in other sequences than described or illustrated herein.

[0048] In Figure 1, a first telecommunications network 100, e.g. a mobile communication network 100 such as a public land mobile network 100, and a second telecommunications network 200, likewise e.g. a mobile communication network 200 such as a public land mobile network 200, are schematically shown. The first telecommunications network 100 is associated to (or assigned to) a user equipment 20 (or the user equipment 20 is assigned to the first telecommunications network 100), resulting in the first telecommunications network 100 being the home telecommunications network 100 of the user equipment 20. The present invention relates to the situation of the user equipment 20 being in a roaming situation, i.e. the user equipment 20 being connected not to the home telecommunications network 100 but to the second telecommunications network 200, which is referred to by the term visited telecommunications network 200.

[0049] The home telecommunications network 100 comprises a first access network 110 (also called home access network 110) or access part and a first core network 120 (also called home core network 120). The home telecommunications network 100 is, e.g., a cellular telecommunications network comprising typically a plurality of network cells (not depicted in Figure 1). The first (or home) access network 110 comprises at least one first access entity 111 such as (especially in case of mobile communication networks) a base station entity enabled to serve a user equipment 20. In case of the home telecommunications network 100 being a mobile communication network, the first access entity 111 typically serves a radio cell, i.e. a radio coverage area of the access entity 111 (or base station entity 111) or associated to the first access entity 111, and the user equipment 20 is able to be connected to the first access entity 111 by means of a radio link or a wireless communication link. In case of the home telecommunications network 100 being a fixed communication network, the first access entity 111 is typically a network access point to which the user equipment 20 is able to be connected by a wireline connection, or the first access entity 111 is connected to a local wireless access point, providing the possibility for the user equipment 20 to be connected to the first access entity 111 via a wireless communication link. The visited telecommunications network 200 comprises a second access network 210 (also called visited access network 210) or access part and a second core network 220 (also called visited core network 220). The visited telecommunications network 200 is, e.g., a cellular telecommunications network comprising typically a plurality of network cells (not depicted in Figure 1). The second access network 210 comprises at least one second access entity 211 such as (especially in case of mobile communication networks) a base station entity enabled to serve the user equipment 20. In case of the visited telecommunications network 200 being a mobile communication network, the second access entity 211 typically serves a

radio cell, i.e. a radio coverage area of the second access entity 211 (or base station entity 211) or associated to the second access entity 211, and the user equipment 20 is able to be connected to the second access entity 211 by means of a radio link or wireless communication link. In case of the visited telecommunications network 200 being a fixed communication network, the second access entity 211 is typically a network access point to which the user equipment 20 is able to be connected by a wireline connection, or the second access entity 211 is connected to a local wireless access point, providing the possibility for the user equipment 20 to be connected to the first access entity 111 via a wireless communication link.

10 **[0050]** In the exemplary representation of a roaming situation depicted in Figure 1, the user equipment 20 is connected – while being assigned (or associated) to the home telecommunications network 100 – to the second access entity 211 of the visited telecommunications network 200. Furthermore, a further access entity 212 is schematically shown in Figure 1 as being part of the visited telecommunications network
15 200.

[0051] In such a roaming situation of the user equipment 20, in case that a type of call handling involving local breakout is used (i.e. the proxy functionality of the visited telecommunications network 200 (and not of the home telecommunications network 100) is used), a network node of the visited telecommunications network 200 is primarily used
20 for call handling, such as a proxy call session control function of the visited telecommunications network 200. In such a situation, such a network node of the visited telecommunications network 200 should know any valid emergency call telephone numbers that can be used within the visited telecommunications network 200.

[0052] However, in case that a type of call handling avoiding local breakout is used
25 (typically this means that the proxy functionality of the home telecommunications network 100 is used), either the user equipment 20 would normally need to be provisioned with the valid emergency call telephone numbers that can be used within the visited telecommunications network 200, or a network node of the home telecommunications network 100 would need to have (or at least be able to easily access) this information, i.e.
30 the valid emergency call telephone numbers that can be used within this visited telecommunications network 200, but – as the user equipment 20 is typically able to roam on a multitude of potential visited telecommunications networks – also the valid emergency call telephone numbers of any other possible visited telecommunications network of any roaming partner of the home telecommunications network 100. The
35 maintenance efforts of such a database are typically quite important, especially for

network operators having a comparatively important number of roaming partners, especially in case that the such an information is not provided automatically to the home telecommunications network 100.

[0053] The present invention solves this problem by automatically providing or
5 completing the information, towards the home telecommunications network 100, about the valid emergency call telephone numbers that can be used within the visited telecommunications network 200. According to the present invention, a mechanism is provided that delivers local emergency service information (i.e. the information about the valid emergency call telephone numbers in the visited telecommunications network 200)
10 to the IMS of the home telecommunications network (when the user equipment is roaming in scenarios without local breakout). According to the present invention, it is taken advantage that during bearer setup procedures for IMS signaling, an IP tunnel (or IP transportation tunnel) is established (or modified) from the visited telecommunications network 200 towards the home telecommunications network 100: Using this IP
15 transportation tunnel, an emergency service information is transmitted to the home telecommunications network 100 by means of, preferably, a network node of the enhanced packet system in the visited telecommunications network 200 putting the emergency service information of this network into the signaling procedures of the IP (transportation) tunnel.

20 **[0054]** In Figure 1, an IP (transportation) tunnel 25 is schematically shown. The IP (transportation) tunnel 25 is shown as being established between the second access entity 211 at one end of the IP transportation tunnel 25, and a second network node 121 of the home telecommunications network 100. In the context of the present invention, the second access entity 211 is also called the first network node of the visited
25 telecommunications network 200, and the IP transportation tunnel 25 is established (at least) between the first network node (or second access entity) 211 of the visited telecommunications network 200 and the second network node 121 of the home telecommunications network 100.

[0055] According to the present invention, the IP transportation tunnel 25 is
30 especially realized by means of a GTP tunnel, the term "GTP tunnel" referring to a tunnel using the GPRS Tunneling protocol (GTP). The GTP is an IP/UDP-based protocol used in GSM, UMTS, and LTE core networks. The GTP is typically implemented using a GTP-C part as well as a GTP-U part, the GTP-C part being the control part, used for specific signaling (e.g. bearer activation/deletion/modification, etc.), and the GTP-U part being
35 used in user plane to carry user data traffic. According to the present invention, the IP

transportation tunnel 25 (or a part thereof, such as the GTP-C part) can also be established – besides between the first network node 211 of the visited telecommunications network 200 and a second network node 121 of the home telecommunications network 100 (where, e.g., the GTP-U part is established) – between an additional network node 213 (such as the responsible mobility management entity) of the visited telecommunications network 200 and the second network node 121 of the home telecommunications network 100. This second branch or part of the IP transportation tunnel 25 is schematically represented by means of a dashed line in Figure 1.

10 **[0056]** Upon the user equipment 20 initiating a voice call using an emergency call telephone number (among the (possibly numerous) valid emergency call telephone numbers accessible in the visited telecommunications network 200), hereinafter also called specific emergency call telephone number, the user equipment 20 is not necessarily aware of the fact that this voice call relates to a valid emergency call
15 telephone number within the visited telecommunications network 200 (non-UE detected emergency call). As a consequence, the user equipment 20 handles the voice call as a normal voice call.

[0057] According to the present invention, by means of initially transmitting the emergency service information to the home telecommunications network 100 (using the
20 IP transportation tunnel 25) the information about the specific emergency call telephone number being a valid emergency call telephone number (within the visited telecommunications network 200) is already known to the home telecommunications network 100 prior to the user equipment 20 initiating the voice call. Thus, despite the fact that the proxy functionality of the home telecommunications network 100 is used for
25 processing the voice call, – on the basis of the emergency service information – the home telecommunications network 100 is able to request the user equipment 20 to trigger an emergency call procedure towards the visited telecommunications network 200. Hence, according to the present invention, local breakout is not used and local emergency numbers are not provided to the user equipment 20. As the home telecommunications
30 network 100 is able to detect that the initiated voice call is emergency related, a network node in the home telecommunications network 100 is able to detect a call setup as an emergency call by analyzing the requested number (of the voice call). This node in the home telecommunications network 100 typically assigns a corresponding sos-URN (uniform resource name of the sos top level domain).

[0058] This inventive method is represented schematically in greater detail in Figure 2.

[0059] In a preliminary step the emergency service information 250 (of the visited telecommunications network 200) is transmitted to the second network node 121 of the home telecommunications network 100, using the IP transportation tunnel 25. According to the present invention, the transmission of the emergency service information 250 is related to the (existence or applicability of the) roaming situation of the user equipment 20 in such a manner that upon invocation of the roaming situation, the emergency service information 250 is transmitted using the IP transportation tunnel 25. In a first situation, the user equipment 20 is switched on (or a (first or initial) data connection of the user equipment 20 is established) while being located in the coverage area of the visited telecommunications network 200; according to a second situation, the user equipment 20 enters the coverage area of the visited telecommunications network 200 while being connected to the home telecommunications network 100 (or to another visited telecommunications network which is not depicted in the figures). Both the visited telecommunications network 200 and the home telecommunications network 100 are configured such that the emergency service information 250 is initially transmitted to the home telecommunications network 100 in both of the mentioned situations (i.e. the IP transportation tunnel 25 is either generated or modified and the emergency service information 250 transmitted). After the emergency service information 250 being transmitted to the home telecommunications network 100, the home telecommunications network 100 is aware of the emergency call telephone numbers currently applicable in the visited telecommunications network 200, and hence, in case that (at a point in time subsequent to the transmission of the emergency service information 250) a voice call is initiated by the user equipment 20 using the specific emergency call telephone number and the user equipment 20 is not aware of the used telephone number being a valid emergency call telephone number, the home telecommunications network 100 is able to indicate to the user equipment 20 how to behave in order to correctly treat the voice call.

[0060] According to the present invention, in a first step, the user equipment 20 initiates the voice call by means of transmitting a first message 310 to the home telecommunications network 100 (thereby typically also using the IP transportation tunnel 25, i.e. transferring the first message 310 between the first network node 211 of the visited telecommunications network 200 to the second network node 121 of the home telecommunications network 100). In a second step, the home telecommunications network 100 – based on the emergency service information 250 – detects the specific emergency call telephone number (used by the user equipment 20) as being a valid

emergency call telephone number within the visited telecommunications network 200, and, in a third step, transmits a second message 302 from the home telecommunications network 100 to the user equipment 20, thereby indicating to the user equipment how to behave (i.e. by means of the second message 302, the user equipment 20 becomes
5 aware of having initiated an emergency call by originally initiating the voice call and triggering the first message 301), i.e. comprising an indication to the user equipment to trigger an emergency call procedure in accordance to the configuration of the visited telecommunications network 200 by means of a third message 303 (to be sent typically from the user equipment 20 to the visited telecommunications network 200). According to
10 the present invention, the first message 301 comprises the specific emergency call telephone number. The second message 302 comprises an emergency call information 251, wherein the emergency call information 251 especially comprises a uniform resource name, especially related to an emergency type, and/or an information related to the emergency type and/or the specific emergency call telephone number.

15 **[0061]** According to the present invention, it is preferred that the enhanced packet system in the visited telecommunications network 200 can put a list of all local emergency information (numbers+mapping to sos-URNs), i.e. the emergency service information 250, into the transmission of signaling information during IP tunnel (GTP) establishment towards the home telecommunications network 100. It is advantageously
20 possible that this network node of the enhanced packet system in the visited telecommunications network 200 adds an identifier of the visited telecommunications network 200 to the list of local emergency service information 250 into the signaling via the IP tunnel 25 towards the home telecommunications network 100. A network node of the enhanced packet system in home telecommunications network 100 (typically the
25 second network node 121 of the home telecommunications network 100) extracts the emergency service list (or emergency service information 250) and provides it to the related P-CSCF node in IMS home network. The respective (first) network node 121 in the home telecommunications network 100 can additionally add information identifying the visited telecommunications network 200. According to the present invention, this
30 information (i.e. the information identifying the visited telecommunications network 200) was either included in the emergency service list (emergency service information 250) send from the visited telecommunications network 200 or is deduced from other parameters at the home telecommunications network (e.g. from parameters such as the IP-addrss, the (IP) Port etc...). The home telecommunications network 100 can
35 advantageously also store received emergency service information 250 in a database which is accessible for related IMS nodes (e.g. P-CSCF).

[0062] According to the present invention, the emergency service information 250 comprises (or consists of) a list of all local (i.e. in the visited telecommunications network 200) emergency numbers and the related mapping to corresponding sos-URNs. Additionally this list of emergency service information 250 can be extended with an element identifying the visited telecommunications network 200. The IP tunnel including this information (emergency service information) is routed via various interconnections to the home telecommunications network 100 of the user equipment 20. In the home telecommunications network 100 at the network node (e.g. PDN) terminating the GTP (signaling) tunnel, this emergency service list is extracted and transferred to the related nodes of the IMS network. Optionally, an information of the identity of visited telecommunications network 200 can be deduced at home telecommunications network 100 and stored within the emergency service list (emergency service information 250). Additionally this emergency service information 250 can be stored and updated in a database which is accessible for all related IMS nodes. At the IMS network, the assigned P-CSCF can now use this information to identify non-UE-detected emergency calls of the user equipment 20 in the visited telecommunications network 200 and apply the already standardized procedures to trigger the user equipment 20 to establish a successful emergency call in the visited telecommunications network 200.

[0063] The transport of the emergency service information 250 can be done dynamically at bearer establishment by reusing well defined IP tunnel transport towards the home telecommunications network 100 without an impact on potentially encrypted SIP signaling. According to the present invention, this enables a flexible method – especially on a basis per user equipment 20 – to provide the actual emergency number together with the mapping to a sos-URN for the P-CSCF in the home telecommunications network 200. As the transmission of the emergency service information 250 is done automatically and for each user equipment 20 upon establishment of the respective IP tunnel 25, there is no need for the home network operator to put efforts in maintaining a huge list of local emergency numbers of all roaming partners and furthermore, no additional separate interconnection signalling is needed.

PATENT CLAIMS

1. Method for improved handling of emergency calls in a roaming scenario,
wherein a user equipment (20) is assigned to a home telecommunications
5 network (100), and wherein the user equipment (20) is connected to a visited
telecommunications network (200), wherein a first network node (211) of the
visited telecommunications network (200) communicates with a second
network node (121) of the home telecommunications network (100) by means
an IP transportation tunnel (25),
10 wherein upon an establishment step of the IP transportation tunnel (25) and/or
upon a modification step of the IP transportation tunnel (25) an emergency
service information (250) is transmitted to the second network node (121) of
the home telecommunications network (100), wherein in case that both
-- a voice call (310) is initiated by the user equipment (20) using a specific
15 emergency call telephone number being a valid emergency call telephone
number in the visited telecommunications network (200), and
-- the user equipment (20) initially handling the voice call (310) – involving
the specific emergency call telephone number – as a normal voice call (non-
UE detected emergency call),
20 the method comprises the steps of:
-- in a first step, the voice call (310) is initiated by the user equipment (20) by
means of transmitting a first message (301) to the second network node (121)
of the home telecommunications network (100), the first message (301)
comprising the specific emergency call telephone number,
25 -- in a second step, subsequent to the first step, the specific emergency call
telephone number is detected – based on the emergency service information
(250) transmitted to the second network node (121) of the home
telecommunications network (100) –, by the home telecommunications
network (100), as being a valid emergency call telephone number within the
30 visited telecommunications network (200) in relation to the voice call (310),
-- in a third step, subsequent to the second step, a second message (302) is
generated by the home telecommunications network (100), the second
message (302) being transmitted to the user equipment (20), the second
message (302) comprising an indication, to the user equipment (20), to trigger
35 an emergency call procedure in accordance to the configuration of the visited

telecommunications network (200) by means of a third message (303).

2. Method according to claim 1, wherein the normal voice call (or normal manner) is a non-emergency call manner and/or wherein a proxy functionality of the home telecommunications network (100) is used in the roaming scenario (no local breakout).
3. Method according to one of the preceding claims, wherein the home telecommunications network (100) comprises a home access network (110) and a home core network (120), and the visited telecommunications network (200) comprises a visited access network (210) and a visited core network (220), wherein the visited access network (210) of the visited telecommunications network (200) comprises a plurality of base station entities, wherein the user equipment (20) is connected to the visited telecommunications network (200) via one of the base station entities being the serving access entity (211) of the user equipment (20), wherein the first network node (211) of the visited telecommunications network (200) corresponds to the serving access entity (211) of the user equipment (20) and/or to a mobility management entity (213) of the visited telecommunications network (200), and the second network node (121) of the home telecommunications network (100) corresponds to a serving gateway or to a packet data gateway of the home core network (120).
4. Method according to one of the preceding claims, wherein the emergency service information (250) comprises, especially for each of possibly a plurality of different emergency call telephone numbers being valid in the visited telecommunications network (200):
 - a uniform resource name, especially related to an emergency type and/or
 - an information related to the emergency type and/or
 - the emergency call telephone number,and, wherein especially the emergency service information (250) also comprises an information identifying the visited telecommunications network (200).
5. Method according to one of the preceding claims, wherein the second message (302) comprises an emergency call information (251), wherein the emergency call information (251) comprises

- a uniform resource name, especially related to an emergency type and/or
- an information related to the emergency type and/or
- the specific emergency call telephone number.

- 5 6. Method according to one of the preceding claims, wherein the home telecommunications network (100) comprises a home access network (110) and a home core network (120), and the visited telecommunications network (200) comprises a visited access network (210) and a visited core network (220), wherein – within the home core network (120) of the home
- 10 telecommunications network (100) – the emergency service information (250) is transmitted to a further network node (122) of the home core network (120), especially a network node of the IP Multimedia Subsystem (IMS), wherein the further network node (122) of the home core network (120) especially corresponds to the network node realizing the proxy call session control
- 15 function for the voice call.
7. Method according to one of the preceding claims, wherein the emergency service information (250) is stored, in the home telecommunications network (100), in a database, wherein especially the database is accessible to all
- 20 network nodes of the IP Multimedia Subsystem (IMS) of the home telecommunications network (100).
8. Method according to one of the preceding claims, wherein the IP transportation tunnel (25) comprises a user plane and a control plane, wherein
- 25 the first and second message (301, 302) are transported using the user plane of the IP transportation tunnel (25), and wherein the emergency service information (250) is transported using the control plane of the IP transportation tunnel (25).
9. System for improved handling of emergency calls in a roaming scenario, wherein a user equipment (20) is assigned to a home telecommunications network (100), and wherein the user equipment (20) is connected to a visited telecommunications network (200), wherein the system comprises the home telecommunications network (100), the visited telecommunications network (200) and the user equipment (20), wherein a first network node (211) of the
- 30 visited telecommunications network (200) communicates with a second network node (121) of the home telecommunications network (100) by means
- 35

an IP transportation tunnel (25),
wherein upon an establishment step of the IP transportation tunnel (25) and/or
upon a modification step of the IP transportation tunnel (25) an emergency
service information (250) is transmitted to the second network node (121) of
5 the home telecommunications network (100), wherein in case that both
-- a voice call (310) is initiated by the user equipment (20) using a specific
emergency call telephone number being a valid emergency call telephone
number in the visited telecommunications network (200), and
-- the user equipment (20) initially handling the voice call (310) – involving
10 the specific emergency call telephone number – as a normal voice call (non-
UE detected emergency call),
the system is configured such that:
-- the user equipment (20) is adapted to initiate the voice call (310) by
means of transmitting a first message (301) to the second network node (121)
15 of the home telecommunications network (100), the first message (301)
comprising the specific emergency call telephone number,
-- the home telecommunications network (100) is adapted to detect – based
on the emergency service information (250) transmitted to the second network
node (121) of the home telecommunications network (100) – the specific
20 emergency call telephone number as being a valid emergency call telephone
number within the visited telecommunications network (200) in relation to the
voice call (310),
-- the home telecommunications network (100) is adapted to generate a
second message (302), and to transmit the second message (302) to the user
25 equipment (20), the second message (302) comprising an indication, to the
user equipment (20), to trigger an emergency call procedure in accordance to
the configuration of the visited telecommunications network (200) by means of
a third message (303).

- 30 10. System according to claim 9, wherein the system is configured such that the
emergency service information (250) comprises, especially for each of
possibly a plurality of different emergency call telephone numbers being valid
in the visited telecommunications network (200):
-- a uniform resource name, especially related to an emergency type and/or
35 -- an information related to the emergency type and/or
-- the emergency call telephone number,
and, wherein especially the emergency service information (250) also

comprises an information identifying the visited telecommunications network (200).

11. Telecommunications network (200) for improved handling of emergency calls in a roaming scenario, wherein a user equipment (20) is assigned to a home telecommunications network (100), and wherein the user equipment (20) is connected to the telecommunications network as a visited telecommunications network (200), wherein a first network node (211) of the telecommunications network (200) communicates with a second network node (121) of the home telecommunications network (100) by means an IP transportation tunnel (25), wherein upon an establishment step of the IP transportation tunnel (25) and/or upon a modification step of the IP transportation tunnel (25) an emergency service information (250) is transmitted to the second network node (121) of the home telecommunications network (100), wherein in case that both
- a voice call (310) is initiated by the user equipment (20) using a specific emergency call telephone number being a valid emergency call telephone number in the telecommunications network (200), and
 - the user equipment (20) initially handling the voice call (310) – involving the specific emergency call telephone number – as a normal voice call (non-UE detected emergency call),
- the telecommunications network (200) is configured such that:
- the user equipment (20) is adapted to initiate the voice call (310) by means of transmitting a first message (301) to the second network node (121) of the home telecommunications network (100), the first message (301) comprising the specific emergency call telephone number,
 - the home telecommunications network (100) is adapted to detect – based on the emergency service information (250) transmitted to the second network node (121) of the home telecommunications network (100) – the specific emergency call telephone number as being a valid emergency call telephone number within the telecommunications network (200) in relation to the voice call (310),
 - the home telecommunications network (100) is adapted to generate a second message (302), and to transmit the second message (302) to the user equipment (20), the second message (302) comprising an indication, to the user equipment (20), to trigger an emergency call procedure in accordance to the configuration of the telecommunications network (200) by means of a third

message (303).

- 5 12. Telecommunications network or network node within a system according to one of claims 9 or 10, wherein the telecommunications network and/or the network node is either part of the home telecommunications network (100) of the system or of the visited telecommunications network (200) of the system.
- 10 13. Program comprising a computer readable program code which, when executed on a computer or on a network node of a home telecommunications network (100) or on a network node of a visited telecommunications network (200), or in part on the network node of the home telecommunications network (100) and in part on the network node of the visited telecommunications network (200), causes the computer or the network node of the home telecommunications network (100) or the network node of the visited telecommunications network (200) to perform a method according one of claims 1 to 8.
- 15 14. Computer program product for operating a home telecommunications network (100) and/or a visited telecommunications network (200), the computer program product comprising a computer program stored on a storage medium, the computer program comprising program code which, when executed on a computer or on a network node of a home telecommunications network (100) or on a network node of a visited telecommunications network (200), or in part on the network node of the home telecommunications network (100) and in part on the network node of the visited telecommunications network (200), causes the computer or the network node of the home telecommunications network (100) or the network node of the visited telecommunications network (200) to perform a method according one of claims 1 to 8.
- 20
- 25




Fig. 1




Fig. 2

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/056342

A. CLASSIFICATION OF SUBJECT MATTER INV. H04W4/22 H04W76/00 ADD. H04L29/06 H04W36/14 H04W48/18 H04L12/46 H04W76/02 H04W92/02 H04L12/24 H04L29/12											
According to International Patent Classification (IPC) or to both national classification and IPC											
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) H04W H04L H04M Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal, WPI Data											
C. DOCUMENTS CONSIDERED TO BE RELEVANT <table border="1"> <thead> <tr> <th>Category*</th> <th>Citation of document, with indication, where appropriate, of the relevant passages</th> <th>Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td>X</td> <td> "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; IP Multimedia Subsystem (IMS) emergency sessions (Release 12)", 3GPP DRAFT; 23167-C10, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE 24 March 2015 (2015-03-24), XP050961162, Retrieved from the Internet: URL:http://www.3gpp.org/ftp/tsg_sa/WG2_Arch/Latest_SA2_Specs/Rel-12/[retrieved on 2015-03-24] </td> <td>12</td> </tr> <tr> <td>A</td> <td> Section 4.1 Section 6.1 Section 6.2.1 Section 7.1.2 -/-- </td> <td>1-11,13,14</td> </tr> </tbody> </table>			Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	X	"3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; IP Multimedia Subsystem (IMS) emergency sessions (Release 12)", 3GPP DRAFT; 23167-C10, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE 24 March 2015 (2015-03-24), XP050961162, Retrieved from the Internet: URL:http://www.3gpp.org/ftp/tsg_sa/WG2_Arch/Latest_SA2_Specs/Rel-12/[retrieved on 2015-03-24]	12	A	Section 4.1 Section 6.1 Section 6.2.1 Section 7.1.2 -/--	1-11,13,14
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.									
X	"3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; IP Multimedia Subsystem (IMS) emergency sessions (Release 12)", 3GPP DRAFT; 23167-C10, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE 24 March 2015 (2015-03-24), XP050961162, Retrieved from the Internet: URL:http://www.3gpp.org/ftp/tsg_sa/WG2_Arch/Latest_SA2_Specs/Rel-12/[retrieved on 2015-03-24]	12									
A	Section 4.1 Section 6.1 Section 6.2.1 Section 7.1.2 -/--	1-11,13,14									
☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.											
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family											
Date of the actual completion of the international search		Date of mailing of the international search report									
30 June 2016		08/07/2016									
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016		Authorized officer Krause, Sven									

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/056342

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	Section 7.3 ----- "3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Internet Protocol (IP) based IP Multimedia Subsystem (IMS) emergency sessions (Release 7)", 3GPP DRAFT; 23867-710, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE , 6 December 2005 (2005-12-06), XP050909830, Retrieved from the Internet: URL: http://www.3gpp.org/ftp/Specs/2014-12/Rel-7/23_series/ [retrieved on 2005-12-06] Section 4.1.1 - 4.1.3 Section 4.7.2 Section 5.1 Section 5.2.1 Section 5.3.1 Section 6.2.1 -----	1-14
A	HUAWEI TECHNOLOGIES: "Roaming case for IMS emergency session", 3GPP DRAFT; S2-032034, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE, vol. SA WG2, no. San Diego, USA; 20030507, 7 May 2003 (2003-05-07), XP050244605, the whole document -----	1-14
A	QUALCOMM EUROPE: "Support of Local Emergency Numbers (updated)", 3GPP DRAFT; S2-062620 (SUPPORT OF LOCAL EMERGENCY NUMBERS), 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE, vol. SA WG2, no. Sophia; 20060901, 3 August 2006 (2006-08-03), XP050432306, Section 1 Section 2, lines 1-9 ----- -/--	1-14

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/056342

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2013/160465 A2 (ERICSSON TELEFON AB L M [SE]) 31 October 2013 (2013-10-31) page 2, line 1 - page 3, line 25 page 3, line 32 - page 4, line 16 page 5, line 10 - page 6, line 7 page 7, line 22 - page 8, line 4 page 8, lines 27-32 page 10, line 24 - page 11, line 22 page 12, line 33 - page 14, line 2 page 14, lines 14-28 figures 2,3a,3b,7 -----	1-14
A	EP 2 833 656 A2 (MEDIATEK INC [TW]) 4 February 2015 (2015-02-04) abstract paragraphs [0001], [0004] - [0009] paragraphs [0019], [0025], [0027] - [0034] paragraphs [0039] - [0040], [0043] figures 2-5 -----	1-14
A	WO 2014/114777 A2 (NOKIA SOLUTIONS & NETWORKS OY [FI]) 31 July 2014 (2014-07-31) paragraphs [0015] - [0022] figures 1,3,5 paragraph [0038] paragraphs [0044] - [0046] -----	1-14
A	US 8 040 862 B1 (ROSENBERG JONATHAN D [US] ET AL) 18 October 2011 (2011-10-18) column 1, lines 17-20 column 1, line 31 - column 2, line 48 column 3, lines 27-53 column 4, line 52 - column 5, line 6 column 6, line 12 - column 7, line 61 column 11, line 7 - column 12, line 28 column 12, line 66 - column 13, line 16 -----	1-14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2016/056342

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2013160465	A2	31-10-2013	NONE
EP 2833656	A2	04-02-2015	CN 104349293 A 11-02-2015
		EP 2833656 A2	04-02-2015
		JP 2015033140 A	16-02-2015
		US 2015038108 A1	05-02-2015
WO 2014114777	A2	31-07-2014	NONE
US 8040862	B1	18-10-2011	CN 101395483 A 25-03-2009
		CN 101395932 A	25-03-2009
		CN 101395934 A	25-03-2009
		CN 101401092 A	01-04-2009
		CN 101401408 A	01-04-2009
		CN 101401463 A	01-04-2009
		CN 101496387 A	29-07-2009
		EP 1991878 A2	19-11-2008
		EP 1992156 A2	19-11-2008
		EP 1992174 A2	19-11-2008
		EP 1992178 A2	19-11-2008
		EP 1992181 A2	19-11-2008
		EP 1999618 A2	10-12-2008
		EP 1999635 A2	10-12-2008
		US 7912035 B1	22-03-2011
		US 7940722 B1	10-05-2011
		US 7944875 B1	17-05-2011
		US 7962123 B1	14-06-2011
		US 7991385 B1	02-08-2011
		US 7995990 B1	09-08-2011
		US 8040862 B1	18-10-2011
		US 8041022 B1	18-10-2011
		US 8045959 B1	25-10-2011
		US 8050391 B1	01-11-2011
		US 8160579 B1	17-04-2012
		US 8719895 B1	06-05-2014
		US 2007206515 A1	06-09-2007
		US 2007206539 A1	06-09-2007
		US 2007206556 A1	06-09-2007
		US 2007206557 A1	06-09-2007
		US 2007206617 A1	06-09-2007
		US 2007207818 A1	06-09-2007
		US 2007208855 A1	06-09-2007
		US 2007220251 A1	20-09-2007
		US 2007220588 A1	20-09-2007
		US 2015264575 A1	17-09-2015
		WO 2007103449 A2	13-09-2007
		WO 2007103450 A2	13-09-2007
		WO 2007103451 A2	13-09-2007
		WO 2007103479 A2	13-09-2007
		WO 2007103481 A2	13-09-2007
		WO 2007103484 A2	13-09-2007
		WO 2007103504 A2	13-09-2007