




- (51) International Patent Classification:
F01N 1/16 (2006.01) *F16K 1/22* (2006.01)
- (21) International Application Number:
PCT/US2017/045923
- (22) International Filing Date:
08 August 2017 (08.08.2017)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
15/238,872 17 August 2016 (17.08.2016) US
- (71) Applicant: **TENNECO AUTOMOTIVE OPERATING COMPANY INC.** [US/US]; 500 North Field Drive, Lake Forest, Illinois 60045 (US).
- (72) Inventors: **GEER, Larry J.**; 3980 Saunt Road, Jackson, Michigan 49201 (US). **PETERS, Erwin**; 14436 Limer-

ick Lane, Cement City, Michigan 49233 (US). **THOMAS, Stephen M.**; 6206 W. Grandriver Rd., Laingsburg, Michigan 48848 (US). **HILL, William E.**; 2414 Haisley Drive, Ann Arbor, Michigan 48103 (US).

- (74) Agent: **WALKER, Donald G.** et al.; HARNESS, DICKEY & PIERCE, P.L.C., P.O. Box 828, Bloomfield Hills, Michigan 48303 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,

(54) Title: FLUTTER DAMPENED EXHAUST VALVE



(57) Abstract: A snap-action valve assembly for an exhaust system is provided that includes a first conduit and a second conduit that are joined together to define an exhaust passageway. A valve flap is disposed within the exhaust passageway for controlling exhaust flow. A shaft supports the valve flap in the exhaust passageway for rotation between open and closed positions. First and second bushings support the shaft. A pad made of wire mesh is attached to the valve flap. The pad includes an end portion that contacts the first or second conduit in the closed position and side wings that contact the first or second conduit in the open position. A resilient tongue may support the pad on an angle relative to the valve flap and a mass damper may be attached to one end of the shaft. These features dampen vibration and reduce valve flap flutter.

SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

- *with international search report (Art. 21(3))*

FLUTTER DAMPENED EXHAUST VALVE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. Utility Application No. 15/238,872, filed on August 17, 2016. The entire disclosure of the above application is incorporated herein by reference.

FIELD

[0002] The subject disclosure relates to valve assemblies used in an exhaust system of a vehicle and to methods of manufacturing such valve assemblies.

BACKGROUND

[0003] This section provides background information related to the present disclosure which is not necessarily prior art.

[0004] Many vehicle exhaust systems use active and/or passive valve assemblies to alter the characteristics of exhaust flow through a conduit as the exhaust pressure increases due to increasing engine speed. Such valves can be used to reduce low frequency noise by directing exhaust through mufflers or other exhaust system components. For example, valves can direct exhaust flow past obstructions, which create vortices that absorb low frequency sound energy. Active valves carry the increased expense of requiring a specific actuating element, such as a solenoid. Passive valves utilize the pressure of the exhaust flow in the conduit to actuate the valve. Although passive valves are less expensive, traditional passive valves create unwanted back pressure when the valve is open, can be difficult to manufacture, and are susceptible to vibration related noise and excessive valve flutter caused by flowrate fluctuations in the engine's exhaust flow (i.e. exhaust pulsation). There is seen to be a need in the art for a passive valve that is relatively inexpensive to manufacture, is quieter than existing passive valves, and minimizes unwanted back pressure in the open position.

SUMMARY

[0005] This section provides a general summary of the disclosure and is not a comprehensive disclosure of its full scope or all of its features.

[0006] In accordance with one aspect of the subject disclosure, a snap-action valve assembly for an exhaust system is provided. The snap-action valve assembly includes a first conduit. The first conduit extends along a central axis to define an exhaust passageway. A valve flap is disposed within the exhaust passageway for controlling exhaust flow through the

exhaust passageway. A shaft supports the valve flap in the exhaust passageway and allows the valve flap to rotate between a closed position and an open position in the exhaust passageway about a pivot axis. The snap-action valve assembly further comprises a mass damper that is positioned external to the first conduit. The mass damper is rotatably coupled to the shaft such that the mass damper rotates with the shaft. The mass damper has a linear segment that extends along a primary mass damper axis between a pair of damper ends. The mass damper further includes a first transverse segment and a second transverse segment. The first and second transverse segments extend from the pair of damper ends. Each of the first and second transverse segments extends in a transverse direction relative to said primary mass damper axis.

[0007] In accordance with another aspect of the subject disclosure, the snap-action valve assembly includes a pad that is carried on the valve flap. The pad includes a body portion and an end portion. The end portion of the pad extends over a first arcuate edge of the valve flap. The valve flap includes a resilient tongue disposed between the valve flap and the body portion of the pad. The resilient tongue is angled up and is spaced away from the first arcuate edge of the valve flap and the pad is attached to and supported by the resilient tongue. During operation, the first angle changes as the resilient tongue deflects in response to the end portion of the pad contacting an inside surface of the first conduit when the valve flap pivots to the closed position.

[0008] In accordance with another aspect of the subject disclosure, the pad of the snap-action valve assembly includes at least one side wing that extends from the body portion of the pad and wraps around at least one linear side edge of the valve flap to a second side of the valve flap. The at least one side wing is sized to contact the inside surface of the first conduit when the valve flap is in the open position.

[0009] Advantageously, the mass damper, the resilient tongue, and the at least one wing of the pad of the snap-action valve assemblies disclosed herein provide improved dampening of vibration related harmonics and valve flutter caused by flowrate fluctuations in the engine's exhaust flow (i.e. exhaust pulsation). In addition, the disclosed snap-action valve assemblies provide reduced back pressure in the open position.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] Other advantages of the present invention will be readily appreciated, as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

[0011] Figure 1 is a side perspective view of an exemplary snap-action valve assembly that is constructed in accordance with the subject disclosure;

[0012] Figure 2 is an exploded perspective view of the exemplary snap-action valve assembly shown in Figure 1;

5 [0013] Figure 3 is a side cross-sectional view of the exemplary snap-action valve assembly shown in Figure 1 illustrating an exemplary valve flap in a closed position;

[0014] Figure 4 is a side cross-sectional view of the exemplary snap-action valve assembly shown in Figure 1 illustrating the exemplary valve flap in an open position;

10 [0015] Figure 5 is front elevation view of the exemplary snap-action valve assembly shown in Figure 1 illustrating the exemplary valve flap in the closed position;

[0016] Figure 6 is rear elevation view of the exemplary snap-action valve assembly shown in Figure 1 illustrating the exemplary valve flap in the closed position;

15 [0017] Figure 7A is a side cross-sectional view of another exemplary snap-action valve assembly that is constructed in accordance with the subject disclosure, which includes a resilient tongue attached to the first valve flap ear of an exemplary valve flap;

[0018] Figure 7B is a side cross-sectional view of another exemplary snap-action valve assembly that is constructed in accordance with the subject disclosure, which includes a resilient tongue attached to the second valve flap ear of an exemplary valve flap;

20 [0019] Figure 8 is a flow diagram illustrating an exemplary method of manufacture for the exemplary snap-action valve assemblies disclosed herein;

[0020] Figure 9 is a top cross-sectional view of an exemplary exhaust muffler that includes the exemplary snap-action valve assembly shown in Figure 1;

[0021] Figure 10 is a front elevation view of a partition within the exemplary exhaust muffler shown in Figure 9;

25 [0022] Figure 11 is a rear elevation view of the exemplary exhaust muffler shown in Figure 9;

[0023] Figure 12A is a front perspective view of another exemplary exhaust muffler that includes two of the exemplary snap-action valve assemblies illustrated in Figure 1 where the snap-action valve assemblies are shown in the closed position;

30 [0024] Figure 12B is a front perspective view of the exemplary exhaust muffler shown in Figure 12A where the snap-action valve assemblies are shown in the open position;

[0025] Figure 13A is a side perspective view of the exemplary mass damper of the snap-action valve assembly shown in Figure 2;

35 [0026] Figure 13B is a side perspective view of another exemplary mass damper constructed in accordance with the subject disclosure, which has a U-like shape;

[0027] Figure 13C is a side perspective view of another exemplary mass damper constructed in accordance with the subject disclosure, which has an imbalanced linear segment;

[0028] Figure 13D is a side elevation view of another exemplary mass damper constructed in accordance with the subject disclosure, which has a S-like shape; and

5 [0029] Figure 13E is a front elevation view of another exemplary mass damper constructed in accordance with the subject disclosure, which has a C-like shape.

DETAILED DESCRIPTION

[0030] Referring to the Figures, wherein like numerals indicate corresponding
10 parts throughout the several views, a snap-action valve assembly 20 for an exhaust system of a vehicle is disclosed.

[0031] Example embodiments are provided so that this disclosure will be thorough, and will fully convey the scope to those who are skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, and methods, to provide a
15 thorough understanding of embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different forms and that neither should be construed to limit the scope of the disclosure. In some example embodiments, well-known processes, well-known device structures, and well-known technologies are not described in detail.

[0032] The terminology used herein is for the purpose of describing particular
20 example embodiments only and is not intended to be limiting. As used herein, the singular forms "a," "an," and "the" may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms "comprises," "comprising," "including," and "having," are inclusive and therefore specify the presence of stated features, integers, steps, operations,
25 elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be
30 employed.

[0033] When an element or layer is referred to as being "on," "engaged to," "connected to," or "coupled to" another element or layer, it may be directly on, engaged, connected or coupled to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being "directly on," "directly engaged to,"
35 "directly connected to," or "directly coupled to" another element or layer, there may be no

intervening elements or layers present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., "between" versus "directly between," "adjacent" versus "directly adjacent," etc.). As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

5 **[0034]** Although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another region, layer or section. Terms such as "first," "second," and other numerical terms when used herein do not
10 imply a sequence or order unless clearly indicated by the context. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the example embodiments.

[0035] Spatially relative terms, such as "inner," "outer," "beneath," "below,"
15 "lower," "above," "upper," and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. Spatially relative terms may be intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as "below" or "beneath" other
20 elements or features would then be oriented "above" the other elements or features. Thus, the example term "below" can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

[0036] With reference to Figures 1-4, the snap-action valve assembly **20** includes
25 a first conduit **22** and a second conduit **24**. It should be appreciated that the first and second conduits **22**, **24** are two of many component parts in the exhaust system of the vehicle. Although the first and second conduits **22**, **24** may have a variety of different shapes and sizes, in the illustrated example, the first and second conduits **22**, **24** have a tubular shape and may alternatively be described as tubes or pipes. The first conduit **22** has a first conduit wall **26**
30 presenting an outside surface **28**. The first conduit wall **26** may be made from a variety of different materials. By way of non-limiting example, the first conduit wall **26** may be made from SS409 or SS439 stainless steel. In the illustrated example, the first conduit **22** is separated into a first enlarged conduit segment **30**, a second enlarged conduit segment **32**, and a neck portion **34** disposed longitudinally between the first enlarged conduit segment **30** and the second
35 enlarged conduit segment **32**. The neck portion **34** of the first conduit **22** has an inside surface

36 and the first and second enlarged conduit segments 30, 32 have inner mating surfaces 38a, 38b.

[0037] The neck portion 34 of the first conduit 22 has a first inner diameter 40 that may be measured across the inside surface 36 of the neck portion 34. The first enlarged conduit segment 30 of the first conduit 22 has a second inner diameter 42 that may be measured across the inner mating surface 38a of the first enlarged conduit segment 30. The second enlarged conduit segment 32 of the first conduit 22 has a third inner diameter 44 that may be measured across the inner mating surface 38b of the second enlarged conduit segment 32. The first inner diameter 40 of the neck portion 34 of the first conduit 22 is smaller than the second inner diameter 42 of the first enlarged conduit segment 30 and the third inner diameter 44 of the second enlarged conduit segment 32. In the illustrated example, the second inner diameter 42 of the first enlarged conduit segment 30 is equal to the third inner diameter 44 of the second enlarged conduit segment 32; however, other configurations are possible where the second inner diameter 42 of the first enlarged conduit segment 30 is different from the third inner diameter 44 of the second enlarged conduit segment 32.

[0038] The first conduit 22 includes a first transition 46 and a second transition 48 that are longitudinally spaced from each other. The first transition 46 is disposed longitudinally between the first enlarged conduit segment 30 and the neck portion 34 of the first conduit 22. The second transition 48 is disposed longitudinally between the second enlarged conduit segment 32 and the neck portion 34 of the first conduit 22. In other words, the first conduit 22 transitions from the first inner diameter 40 of the neck portion 34 to the second inner diameter 42 of the first enlarged conduit segment 30 at the first transition 46 and the first conduit 22 transitions from the first inner diameter 40 of the neck portion 34 to the third inner diameter 44 of the second enlarged conduit segment 32 at the second transition 48. The first and second transitions 46, 48 may be constructed to taper gradually or abruptly between the neck portion 34 and the first and second enlarged conduit segments 30, 32 of the first conduit 22.

[0039] Still referring to Figures 1-4, the first conduit 22 extends longitudinally along a central axis 50 from a junction end 52 at the first enlarged conduit segment 30 to a distal end 54 at the second enlarged conduit segment 32. The second conduit 24 extends longitudinally and co-axially with the central axis 50 between an insertion end 56 and a proximal end 58. The second conduit 24 has a second conduit wall 60 presenting an inner surface 62 and an outer mating surface 64. The second conduit wall 60 may be made from a variety of different materials. By way of non-limiting example, the second conduit wall 60 may also be made from SS409 or SS439 stainless steel. The second conduit 24 has an outer diameter 66 that may be measured across the outer mating surface 64 of the second conduit 24. The outer

diameter 66 of the second conduit 24 is smaller than the second inner diameter 42 of the first enlarged segment of the first conduit 22. When the snap-action valve assembly 20 is fully assembled (Figure 1), the insertion end 56 of the second conduit 24 is slidably received in the first enlarged conduit segment 30 of the first conduit 22 and the outer mating surface 64 of the second conduit 24 overlaps with and bears against the inner mating surface 38a of the first enlarged conduit segment 30 of the first conduit 22. As such, the second conduit 24 extends outwardly from the junction end 52 of the first conduit 22 and the first and second conduits 22, 24 cooperate to define an exhaust passageway 68 therein that extends longitudinally from the proximal end 58 of the second conduit 24 to the distal end 54 of the first conduit 22. During operation of the vehicle, exhaust from the vehicle's engine (not shown) can flow through the exhaust passageway 68 in the first and second conduits 22, 24. Although the first and second conduits 22, 24 can be attached in a variety of different ways to prevent separation, in one example the junction end 52 of the first conduit 22 is welded to the outer mating surface 64 of the second conduit 24. Moreover, it should be appreciated that the snap-action valve assembly 20 may be configured where exhaust flow enters through the first conduit 22 and exits through the second conduit 24 or vice versa.

[0040] As shown in Figures 1-4, a valve flap 70 is disposed within the first conduit 22. The valve flap 70 defines a valve flap plane 72 and includes a first valve flap ear 74, a second valve flap ear 76, and a curved section 78 disposed between the first valve flap ear 74 and the smaller valve flap 70 ear. The large and second valve flap ears 74, 76 extend in the valve flap plane 72. The curved section 78 defines a channel 80 therein that is spaced from and transverse to the central axis 50. The first valve flap ear 74 includes a first arcuate edge 82 and a pair of linear side edges 84. The first valve flap ear 74 extends from the curved section 78 of the valve flap 70 and terminates at the first arcuate edge 82. The second valve flap ear 76 includes a second arcuate edge 86. The second valve flap ear 76 extends from the curved section 78 of the valve flap 70 and terminates at the second arcuate edge 86. The valve flap 70 also includes a pair of bushing cut-outs 88 at the curved section 78 of the valve flap 70. The pair of bushing cut-outs 88 extend between the pair of linear side edges 84 of the first valve flap ear 74 and the second arcuate edge 86 of the second valve flap ear 76. It should be appreciated that the curved section 78 of the valve flap 70 is off-center, such that the first valve flap ear 74 has a greater surface area than the second valve flap ear 76. The valve flap 70 may be made of a variety of different materials. By way of non-limiting example, the valve flap 70 may be made from SS409 or SS439 stainless steel.

[0041] The snap-action valve assembly 20 includes a pad 94 that is carried on the valve flap 70. The pad 94 includes a body portion 96 that is attached to the first valve flap ear

74 and an end portion 98 that extends over the first arcuate edge 82 of the first valve flap ear 74. Although the pad 94 may be made of a variety of different materials and may be attached to the valve flap 70 in a number of different ways, in the illustrated example, the pad 94 is made of wire mesh and the body portion 96 of the pad 94 is attached to the first valve flap ear 74 by spot welds 100. By way of example and without limitation, the wire mesh forming the pad 94 may be made from SS316 stainless steel mesh that has a density ranging from 25-30 percent.

[0042] A shaft 102 supports the valve flap 70 in the first conduit 22 for rotation between a closed position (illustrated in Figure 3) and an open position (illustrated in Figure 4). The closed position and the open position of the valve flap 70 are separated by a valve flap travel angle 104. In the illustrated example, the valve flap travel angle 104 equals 40 degrees. When the valve flap 70 is in the closed position as shown in Figure 3, the end portion 98 of the pad 94 contacts the inside surface 36 of the neck portion 34 of the first conduit 22. When the valve flap 70 is in the open position as shown in Figure 4, the valve flap 70 is positioned such that the valve flap plane 72 is parallel to the central axis 50. It should be appreciated that the valve flap 70 obstructs exhaust flow through the exhaust passageway 68 when the valve flap 70 is in the closed position and that exhaust flow through the exhaust passageway 68 is relatively unobstructed when the valve flap 70 is in the open position. Notwithstanding, the valve flap 70 need not completely close off the exhaust passageway 68 in the closed position and the open position could be associated with other valve flap 70 orientations where the valve flap plane 72 is not parallel to the central axis 50.

[0043] Still referring to Figures 1-4, the shaft 102 supporting the valve flap 70 is separated into an axle portion 106, an external shaft segment 108, a lever arm 110, and a spring attachment arm 112. At least part of the axle portion 106 is disposed within the first conduit 22 while the external shaft segment 108, the lever arm 110, and the spring attachment arm 112 are external to the first conduit 22. The axle portion 106 of the shaft 102 extends linearly through the first conduit 22 from the external shaft segment 108 to the lever arm 110 and defines a pivot axis 114 for the valve flap 70. The pivot axis 114 is transverse to the central axis 50 and is spaced from the central axis 50 by an offset distance 116. In other words, the axle portion 106 of the shaft 102 is off-center in the first conduit 22. The valve flap 70 is carried on the axle portion 106 of the shaft 102 where at least part of the axle portion 106 of the shaft 102 is received in the channel 80 of the curved section 78 of the valve flap 70. The curved section 78 of the valve flap 70 is fixedly secured to the axle portion 106 of the shaft 102 such that the axle of the shaft 102 rotates with the valve flap 70. By way of example and without limitation, the curved section 78 of the valve flap 70 may be fixedly secured to the axle portion 106 of the shaft 102 by welding.

[0044] The spring attachment arm 112 of the shaft 102 defines a spring attachment arm axis 118 that is parallel to and spaced from the pivot axis 114. The lever arm 110 of the shaft 102 extends transversely from the axle portion 106 of the shaft 102 to the spring attachment arm 112 of the shaft 102 and defines a lever arm axis 120 that is transverse to the pivot axis 114. As best seen in Figures 3 and 4, the lever arm axis 120 is arranged at an acute angle 122 relative to the valve flap plane 72. The spring attachment arm 112 of the shaft 102 includes a plurality of knuckles 124 that protrude from the spring attachment arm 112 to define a spring attachment location 126 disposed between the plurality of knuckles 124. Of course, the spring attachment location 126 may be formed on or in the spring attachment arm 112 by alternative structure without departing from the scope of the subject disclosure. It should be appreciated that the shaft 102 may be made of a variety of different materials. By way of non-limiting example, the shaft 102 may be made from SS430 stainless steel and may have an outside diameter of 6 millimeters (mm).

[0045] The first conduit 22 includes an anchor post 128 disposed longitudinally between the junction end 52 of the first conduit 22 and the shaft 102. The anchor post 128 extends outwardly from the outside surface 28 of the first conduit 22 and terminates at a free end 130. The free end 130 of the anchor post 128 has a spring retention groove 132. The anchor post 128 defines an anchor post axis 134 that is transverse to and that intersects with the central axis 50. Although the anchor post 128 may be formed in different ways, in the illustrated example, the anchor post 128 is integral with the first conduit 22. In accordance with this arrangement, the anchor post 128 is partially cut out from the first conduit wall 26. As such, the first conduit wall 26 includes an anchor post cut-out 198. The anchor post cut-out 198 remains sealed from the exhaust passageway 68 due to the overlap between the first conduit wall 26 and the second conduit wall 60 along the first enlarged conduit segment 30 of the first conduit 22. The anchor post 128 extends from a bent transition 136 adjacent the first conduit wall 26 to the free end 130 where the spring retention groove 132 is located. Advantageously, manufacturing related speed and cost savings are realized when the anchor post 128 is cut out from the first conduit 22.

[0046] A tension spring 138 extends between and is attached to the spring attachment arm 112 of the shaft 102 on one end and the anchor post 128 on the other. Although the tension spring 138 may take a variety of different forms, in the illustrated example, the tension spring 138 has a helical main body 140 that is disposed between first and second hook ends 142a, 142b. The first hook end 142a of the tension spring 138 is retained on the spring attachment arm 112 of the shaft 102 by the plurality of knuckles 124. The second hook end 142b of the tension spring 138 is retained on the anchor post 128 by the spring retention groove

132. The tension spring **138** biases the valve flap **70** to the closed position (Figure 3). As will be explained in greater detail below, the valve flap **70** pivots open against a biasing force provided by the tension spring **138** when the pressure of the exhaust flowing through the exhaust passageway **68** on the first valve flap ear **74** exceeds the biasing force of the tension spring **138** (Figure 4). When the pressure of the exhaust flowing through the exhaust passageway **68** on the first valve flap ear **74** becomes less than the biasing force of the tension spring **138**, the valve flap **70** returns to the closed position (Figure 3). The tension spring **138** may be made of a variety of different materials. By way of non-limiting example, the tension spring **138** may be made from Inconel 718 and/or Alloy 41 metals with a proper heat treatment. Although not shown in the drawings, other spring types besides tension springs **138** may be utilized. For example, compression or torsion springs could be used with minor design modifications.

[0047] As best seen in Figure 2, the snap-action valve assembly **20** includes first and second bushings **144a**, **144b** that support the axle portion **106** of the shaft **102** on the first conduit **22**. Each of the first and second bushings **144a**, **144b** includes a shaft opening **146** where the axle portion **106** of the shaft **102** extends through the shaft openings **146** in the first and second bushings **144a**, **144b**. As a result, the first and second bushings **144** are disposed around the axle portion **106** of the shaft **102** and between the axle portion **106** of the shaft **102** and the first conduit **22**. When the snap-action valve assembly **20** is fully assembled (Figure 1), the curved second **78** of the valve flap **70** is disposed between the first and second bushings **144a**, **144b** and the first and second bushings **144a**, **144b** abut the pair of bushing cut-outs **88** in the valve flap **70**. Although the first and second bushings **144a**, **144b** may be made from a variety of different materials, in the illustrated example, the first and second bushings **144a**, **144b** are made of wire mesh. By way of example and without limitation, the wire mesh of the first and second bushings **144a**, **144b** may be SS316 stainless steel mesh with a density of approximately 40 percent. The wire mesh may optionally be impregnated with graphite.

[0048] As shown in Figures 1 and 2, the snap-action valve assembly **20** may optionally include a mass damper **148** that is rotatably coupled to the external shaft segment **108**. The mass damper **148** rotates with the shaft **102** and creates a distributed mass that is spaced from the pivot axis **114**, which functions to reduce vibration related harmonics (e.g. rattling noises) and excessive valve flutter caused by flowrate fluctuations in the engine's exhaust flow (e.g. exhaust pulsation). In one example, the mass damper **148** is welded directly to the external shaft segment **108**. In the example illustrated in Figure 2, the external shaft segment **108** includes a keyed surface **150** providing the external shaft segment **108** with a generally rectangular cross-section. The mass damper **148** has an attachment hole **152** that receives the external shaft segment **108**. The attachment hole **152** has a complementary shape to

the keyed surface **150** of the external shaft segment **108** such that the mass damper **148** rotates with the external shaft segment **108**. The mass damper **148** may have a bent configuration, including a linear segment **154**, and first and second transverse segments **156a**, **156b** giving the mass damper **148** an S-like shape. The linear segment **154** of the mass damper **148** extends
5 along a primary mass damper axis **158** between a pair of damper ends **160**. The first and second transverse segments **156a**, **156b** of the mass damper **148** extend from the pair of damper ends **160** in opposite transverse directions relative to the primary mass damper axis **158** where the primary mass damper axis **158** is transverse to the pivot axis **114**. The mass damper **148** may be made from a variety of different materials. By way of example and without limitation, the mass
10 damper **148** may be made from SS409 stainless steel.

[0049] Again referring to Figures 1-4, the first conduit **22** further includes first and second slots **162a**, **162b**. Each of the first and second slots **162a**, **162b** extends through the first conduit wall **26**, longitudinally along the first enlarged segment of the first conduit **22** from an open slot end **164** to a closed slot end **166**. Each of the first and second slots **162a**, **162b** also
15 have opposing linear edges **168** that run parallel to each other between the open slot ends **164** and the closed slot ends **166**. The open slot ends **164** are positioned at the junction end **52** of the first conduit **22** while the closed slot ends **166** are positioned between the junction end **52** and the first transition **46** of the first conduit **22**. Although the first and second slots **162a**, **162b** may be curved or extend at an angle relative to the central axis **50** without departing from the scope
20 of the subject disclosure, in the illustrated example, the first and second slots **162a**, **162b** extend parallel to one another in a slot plane **170** that is parallel to and spaced from the central axis **50** of the first conduit **22** by the offset distance **116**. As such, the pivot axis **114** of the valve flap **70** extends in the slot plane **170**. Each of the first and second slots **162a**, **162b** is sized to receive and support one of the first and second bushings **144**. Advantageous, the first and
25 second slots **162a**, **162b** provide manufacturing related speed and cost savings.

[0050] The snap-action valve assembly **20** also includes first and second bushing sleeves **172a**, **172b** that support the first and second bushings **144a**, **144b** within the first and second slots **162a**, **162b** respectively. Each of the first and second bushing sleeves **172a**, **172b** includes a bushing cavity **174** that receives and supports one of the first and second bushings
30 **144a**, **144b**. After assembly, the first and second bushings **144a**, **144b** and the first and second bushing sleeves **172a**, **172b** form first and second bushing subassemblies **173a**, **173b**. When the snap-action valve assembly **20** is fully assembled, each of the first and second bushing sleeves **172a**, **172b** is slidably received in one of the first and second slots **162a**, **162b** such that the first and second bushing sleeves **172a**, **172b** are disposed between the insertion end **56** of the second
35 conduit **24** and the closed slot ends **166**. Consequently, the first and second bushing sleeves

172a, 172b are disposed between the first and second bushings 144a, 144b on one side and the closed slot ends 166, the opposing linear edges 168 of the first and second slots 162a, 162b, and the insertion end 56 of the second conduit 24 on the other. Because the closed slot ends 166, the opposing linear edges 168, and the insertion end 56 of the second conduit 24 are relatively thin and sharp, the first and second bushing sleeves 172a, 172b protect the first and second bushings 144a, 144b from wear by these sharp edges/surfaces. The first and second bushing sleeves 172a, 172b also prevent over compression of the first and second bushings 144a, 144b when the insertion end 56 of the second conduit is inserted into the junction end 52 of the first conduit 22. It should be appreciated that while not shown in the Figures, the insertion end 56 of the second conduit 24 need not define a straight edge, but could alternatively include one or more slots, depressions, or semi-circular notches that interface with the first and second bushing sleeves 172a, 172b.

[0051] Each of the first and second bushing sleeves 172a, 172b has one or more flat portions 176 that contact the opposing linear edges 168 of the first and second slots 162a, 162b to prevent rotation of the first and second bushing sleeves 172a, 172b within the first and second slots 162a, 162b relative to the pivot axis 114. Similarly, each of the first and second bushings 144a, 144b has one or more flats 178 that contact the one or more flat portions 176 of the first and second bushing sleeves 172a, 172b. The flats 178 of the first and second bushings 144a, 144b match the flat portions 176 of the first and second bushing sleeves 172a, 172b and therefore prevent rotation of the first and second bushings 144a, 144b within the first and second bushing sleeves 172a, 172b relative to the pivot axis 114. While other configuration are possible, in the illustrated example, each of the first and second bushings 144a, 144b has two flats 178 and each of the first and second bushing sleeves 172a, 172b has two flat portions 176, giving the first and second bushings 144a, 144b and the first and second bushing sleeves 172a, 172b a generally square-shaped cross-sections.

[0052] Each of the first and second bushing sleeves 172a, 172b also has one or more protrusions 180 that extend inwardly from the first and second bushing sleeves 172a, 172b into the bushing cavities 174. The first and second bushings 144a, 144b are provided with one or more dimples 182 that are aligned with the protrusions 180 in the first and second bushing sleeves 172a, 172b. When the first and second bushing sleeves 172a, 172b are slidably received in the first and second slots 162a, 162b to form first and second bushing subassemblies 173a, 173b, the protrusions 180 of the first and second bushing sleeves 172a, 172b extend into the dimples 182 in the first and second bushings 144a, 144b. As a result, the protrusions 180 prevent axial movement of the first and second bushings 144a, 144b relative to the first and second bushing sleeves 172a, 172b along the pivot axis 114 (i.e. parallel to the pivot axis 114).

[0053] With additional reference to Figures 5 and 6, the valve flap 70 has a first side 90 and a second side 92 that is opposite the first side 90. As shown in Figures 1-6, the valve flap 70 may be arranged in the first conduit 22 such that the first side 90 of the valve flap 70 faces the junction end 52 of the first conduit 22 and the second side 92 of the valve flap 70 faces the distal end 54 of the first conduit 22 when the valve flap 70 is in the closed position (Figure 3). Alternatively, the valve flap 70 may be turned around in the first conduit 22 such that the first side 90 of the valve flap 70 faces the distal end 54 of the first conduit 22 and the second side 92 of the valve flap 70 faces the junction end 52 of the first conduit 22 when the valve flap 70 is in the closed position (not shown). Regardless of the arrangement, the pad 94 is carried on the first side 90 of the valve flap 70. The pad 94 includes first and second side wings 186a, 186b that extend from the body portion 96 of the pad 94. The first and second side wings 186a, 186b wrap around the linear side edges 84 of the valve flap ear 70 to the second side 92 of the valve flap 70. The first and second side wings 186a, 186b extend at least partially across the second side 92 of the valve flap 70 and may be attached to the second side 92 of the valve flap 70 by spot welds 100. The first and second side wings 186a, 186b of the pad 94 contact the inside surface 36 of the first conduit 22 when the valve flap 70 is in the open position (Figure 4) to dampen vibration related harmonics (e.g. rattle) and excessive valve flutter caused by flowrate fluctuations in the engine's exhaust flow (e.g. exhaust pulsation).

[0054] As best seen in Figure 4, the pad 94 is solid and has a variable thickness T that increases moving from the body portion 96 of the pad 94 to a peak 187 located along the end portion 98 of the pad 94. The variable thickness T of the pad 94 decreases moving from the peak 187 to the first arcuate edge 82 of the first valve flap ear 74 of the valve flap 70. Accordingly, the end portion 98 of the pad 94 includes an abutment surface 188 that extends from the body portion 96 of the pad 94 at a first angle 190 relative to the valve flap plane 72 and an end surface 192 that extends from the abutment surface 188 of the pad 94 to the first arcuate edge 82 of the first valve flap ear 74 of the valve flap 70 at a second angle 194 relative to the abutment surface 188 of the pad 94. The first angle 190 between the abutment surface 188 of the pad 94 and the valve flap plane 72 may be any acute angle, but in the illustrated example, the first angle 190 ranges from 13 to 18 degrees. The second angle 194 between the end surface 192 of the pad 94 and the abutment surface 188 of the pad 94 may be any acute angle, but in the illustrated example, the second angle ranges from 48 to 53 degrees.

[0055] In operation, exhaust pressure in the exhaust passageway 68 is incident on valve flap 70 from the left as viewed in Figures 1-4. When the exhaust pressure is sufficient to overcome the biasing force of tension spring 138, the valve flap 70 will start to rotate about the pivot axis 114. With reference to Figure 1, the torque on valve flap 70 is determined by the

biasing force of the tension spring 138 multiplied by distance **D**, which is the distance between a longitudinal axis **A** of the tension spring 138 and the pivot axis 114 of the valve flap 70. The biasing force increases as the valve flap 70 moves toward the open position (Figure 4) and the tension spring 138 stretches. However, distance **D** gets shorter as the valve flap 70 continues to move towards the open position resulting in the torque approaching zero as the longitudinal axis **A** of the tension spring 138 approaches an "over-center" position (i.e., as the longitudinal axis **A** of the tension spring 138 crosses the pivot axis 114 and the valve flap plane 72. This over-center positioning of the valve flap 70 results in a substantially horizontal position of the valve flap 70 when the valve flap 70 is in the open position (Figure 4). Rotating the valve flap 70 such that the tension spring 138 approaches the over center condition results in an easier maintenance of the valve flap 70 in the open position, which, in turn, minimizes back pressure in the exhaust passageway 68 when the valve flap 70 is in the open position.

[0056] Figure 7A illustrates another snap-action valve assembly 20' that is the same as the snap-action valve assembly 20 illustrated in Figures 1-6, but where the valve flap 70 and the pad 94 have been modified. In Figure 7A, a resilient tongue 195 is provided that is attached to the first side 90 of the valve flap 70. A pad 94' is attached to and supported by the resilient tongue 195. The resilient tongue 195 is bent at an angle such that an end portion 98' of the pad 94' is spaced away from the first arcuate edge 82 of the valve flap 70. The resilient tongue 195 extends from the first valve flap ear 74 at the first angle 190 relative to the valve flap plane 72. In operation, the resilient tongue 195 of the valve flap 70 deflects towards the first arcuate edge 82 of the valve flap 70 as the end portion 98' of the pad 94' makes contact with the inside surface 36 of the first conduit 22 to dampen vibration related harmonics and excessive valve flutter caused by flowrate fluctuations in the engine's exhaust flow. As such, the first angle 190 of the resilient tongue 195 changes relative to the valve flap plane 72 when the end portion 98' of the pad 94' makes contact with the inside surface 36 of the first conduit 22.

[0057] Figure 7B illustrates yet another snap-action valve assembly 20'' that is the same as the snap-action valve assembly 20' illustrated in Figure 7A, but where the valve flap 70 and the pad 94' have been modified. In Figure 7B, a resilient tongue 195' is provided that is attached to the second side 92 of the valve flap 70. A pad 94'' is attached to and supported by the resilient tongue 195'. The resilient tongue 195' is bent at an angle such that an end portion 98'' of the pad 94'' is spaced away from the second arcuate edge 86 of the valve flap 70. The resilient tongue 195' extends from the second valve flap ear 76 at a first angle 190' relative to the valve flap plane 72. In operation, the resilient tongue 195' of the valve flap 70 deflects away from the valve flap plane 72 as the end portion 98'' of the pad 94'' makes contact with the inside surface 36 of the first conduit 22 to dampen vibration related harmonics and excessive valve

flutter caused by flowrate fluctuations in the engine's exhaust flow. As such, the first angle 190' of the resilient tongue 195' changes relative to the valve flap plane 72 when the end portion 98'' of the pad 94'' makes contact with the inside surface 36 of the second conduit 24 to dampen vibration related harmonics and excessive valve flutter caused by flowrate fluctuations in the engine's exhaust flow. As such, the first angle 190' of the resilient tongue 195' changes relative to the valve flap plane 72 when the end portion 98'' of the pad 94'' makes contact with the inside surface 36 of the second conduit 24.

[0058] Although the resilient tongue 195, 195' shown in the examples illustrated in Figures 7A and 7B is a separate piece of material that is welded to the valve flap 70, the resilient tongue 195, 195' may alternatively be integral with the valve flap 70 where the valve flap 70 would have a bent or Y-shaped end. Additionally, it should be appreciated that the resilient tongue 195, 195' of the valve flap 70 may be eliminated by making the pad 94', 94'' out of a material that itself is resilient enough to deflect and then spring back to the first angle 190, 190' as the valve flap 70 is pivoted to the closed position and away from the closed position.

[0059] With reference to Figure 8, the subject disclosure further provides a method of manufacturing the snap-action valve assemblies 20 discussed above. The method includes the step illustrated by block 800 of providing a first conduit 22 with a junction end 52 and the step illustrated by block 802 of providing a second conduit 24 with an insertion end 56. The method proceeds with the step illustrated by block 804 of cutting the first and second slots 162a, 162b into the junction end 52 of the first conduit 22. In accordance with this step, each of the first and second slots 162a, 162b are cut so as to extend longitudinally along the first conduit 22 from an open slot end 164 positioned at the junction end 52 of the first conduit 22 to a closed slot end 166. Optionally, the method further comprises the step illustrated by block 806 of cutting the anchor post 128 out from the first conduit wall 26 and the step illustrated by block 808 of bending the anchor post 128 outwardly away from the first conduit 22. The method further includes the step illustrated by block 810 of placing first and second bushing sleeves 172a, 172b over first and second bushings 144a, 144b to create first and second bushing subassemblies 173a, 173b (Figure 1). The method proceeds with the step illustrated by block 812 of placing the first bushing subassembly 173a on a shaft 102 by sliding the shaft 102 through the first bushing 144a, the step illustrated by block 814 of attaching the valve flap 70 to the shaft 102, and the step illustrated by block 816 of placing the second bushing subassembly 173b on the shaft 102 by sliding the shaft 102 through the second bushing 144b to form a valve flap subassembly 196 where the valve flap 70 is positioned on the shaft 102 between the first and second bushing subassemblies 173a, 173b (Figure 1). Accordingly, the valve flap subassembly 196 that includes the valve flap 70, the shaft 102, the first and second bushings

144a, 144b, and the first and second bushing sleeves 172a, 172b (i.e. the first and second bushing subassemblies 173a, 173b). Although the step illustrated by block 814 may be performed in a number of different ways, the valve flap 70 may be attached to the shaft 102 by welding.

5 [0060] The method further comprises the step illustrated by block 818 of sliding the valve flap subassembly 196 into the first conduit 22 from the junction end 52. In accordance with this step, the shaft 102, the first and second bushing subassemblies 173a, 173b are slidably received in the first and second slots 162a, 162b until the first and second bushing sleeves 172a, 172b abut the closed slot ends 166. The method proceeds with the step illustrated by block 820 of sliding the insertion end 56 of the second conduit 24 into the junction end 52 of the first conduit 22 until the insertion end 56 of the second conduit 24 abuts the first and second bushing sleeves 172a, 172b. The method continues with the step illustrated by block 822 of securing the first conduit 22 to the second conduit 24. Although the step illustrated by block 822 may be performed in a number of different ways, the first conduit 22 may be secured to the second conduit 24 continuous or spot welds using MIG, TIG, or laser welding equipment. Optionally, the method further comprises the step illustrated by block 824 of attaching a mass damper 148 to the shaft 102 to dampen vibration related harmonics and reduce excessive valve flutter caused by flowrate fluctuations in the engine's exhaust flow (i.e. exhaust pulsation). Although the step illustrated by block 824 may be performed in a number of different ways, mass damper 148 may be attached to the shaft 102 by welding. The method may also include the optional step illustrated by block 826 of connecting a tension spring 138 between the anchor post 128 and a spring attachment arm 112 on the shaft 102 to bias the valve flap 70 to a closed position.

 [0061] With reference to Figures 9-11, an exemplary application of the snap-action valve assembly 20 described above is illustrated. An automotive exhaust system muffler 900 including a housing 902 is provided. The muffler 900 includes an outer shell 904 having a substantially oval cross-sectional shape closed at inlet and outlet ends by an inlet header 906 and an outlet header 908. A partition 910 is attached to the outer shell 904 at a position to define a first muffler chamber 912 between the inlet header 906 and the partition 910. A second muffler chamber 914 is defined as the volume between the partition 910 and the outlet header 908. The partition 910 includes a plurality of apertures 916 extending therethrough that enable fluid communication between the first muffler chamber 912 and the second muffler chamber 914. A sound absorbing material 918, such as fiberglass roving, may be positioned within the first muffler chamber 912. No sound absorbing material is placed within the second muffler chamber 914. A pipe 920 includes an inlet section 922 and an outlet section 924. The inlet header 906 includes an aperture 930 that receives the inlet section 922 of the pipe 920. The outlet section

924 of the pipe 920 is connected to the second conduit 24 of the snap-action valve assembly 20 described above. The outlet header 908 includes an aperture 932 that receives the second conduit 24 of the snap-action valve assembly 20. The pipe 920 is bent such that the inlet section 922 is centered with the housing 902 while the outlet section 924 is not centered with the housing 902. The partition 910 includes an aperture 938 that receives the pipe 920. An overlapping joint between the outlet section 924 and the second conduit 24 of the snap-action valve assembly 20 is aligned with and supported by the partition 910. The pipe 920 includes a plurality of apertures 942 that are positioned to provide fluid communication between the pipe 920 and the first muffler chamber 912.

[0062] The valve flap 70 of the snap-action valve assembly 20, as previously described in conjunction with Figures 1-6, is positioned in the second muffler chamber 914 between the partition 910 and the outlet header 908. More particularly, when the valve flap 70 is in the closed position, exhaust will enter the pipe 920, pass through the apertures 942, enter the first muffler chamber 912, pass through the apertures 916, and enter the second muffler chamber 914. When the valve flap 70 is in the closed position, a relatively small volume flow rate of exhaust passes through a gap between the valve flap 70 and an inside surface 36 of the first conduit 22. The small gap between the valve flap 70 and the inside surface 36 of the first conduit 22 functions to absorb low frequencies within the snap-action valve assembly 20. Because the first conduit 22 of the snap-action valve assembly 20 is a closed cylindrical member, exhaust does not flow through the first muffler chamber 912 and the second muffler chamber 914. Acoustical waves are present, but the volume flow rate of exhaust through the first muffler chamber 912 and the second muffler chamber 914 is minimal. In addition, the sound absorbing material 918 functions to attenuate noise regardless of the position of valve flap 70. When the exhaust pressure is high enough to overcome the biasing force of the tension spring 138, the valve flap 70 rotates toward the open position. At the open position, the valve flap 70 extends substantially horizontally within the first conduit 22 to minimize back pressure in the muffler 900. It should be appreciated that since no sound absorbing material is placed within the second muffler chamber 914, no interference between the sound absorbing material 918 and the snap-action valve assembly 20 occurs.

[0063] An upstream end 954 of a tail pipe 952 is coupled in fluid communication with the first conduit 22 of the snap-action valve assembly 20. The tail pipe 952 includes an outlet 950 in fluid communication with the atmosphere. Resonance may exist within the tail pipe 952 and the portion of the first conduit 22 that is downstream from the valve flap 70 due to standing exhaust waves that can form in this portion of the exhaust system. In previous exhaust systems, the outlet 950 of the tail pipe 952 was placed in open fluid communication with an

expanded volume inside the outer shell **904** of the muffler **900**. The expanded volume functioned to amplify and/or further excite a resonant condition within the tail pipe **952** leading to undesirable noise. In accordance with the subject disclosure, the axial position of the snap-action valve assembly **20** may be selected to minimize resonance that may occur within the tail pipe **952** and the muffler **900**. More specifically, the valve flap **70** may be positioned at the upstream end **954** of the tail pipe **952** and proximate to the outlet header **908**. More particularly, the shaft **102** of the snap-action valve assembly **20** is axially spaced from the outlet header **908** a distance less than or equal to one-quarter the distance between the inlet header **906** and the outlet header **908**. By positioning the snap-action valve assembly **20** at a location downstream from the apertures **942**, the first chamber **912** and the second muffler chamber **914** are isolated from the tail pipe **952** and undesirable resonance or "exhaust drone" is avoided. Regardless of the angular position of valve flap **70**, one hundred percent of the exhaust flows through the snap-action valve assembly **20**.

[0064] With reference to Figures 12A-B, another exemplary muffler **1000** is illustrated. The muffler **1000** includes a housing **1002**. A dividing wall **1005** is disposed within the housing **1002** that divides the muffler **1000** into a first section **1007a** and a second section **1007b**. The muffler **1000** includes first and second snap-action valve assemblies **20a**, **20b**, which are constructed in accordance with the disclosure set forth herein. The first snap-action valve assembly **20a** is disposed within the housing **1002** in the first section **1007a** of the muffler **1000** and the second snap-action valve assembly **20b** is disposed within the housing **1002** in the second section **1007b** of the muffler **1000**.

[0065] The first section **1007a** of the muffler **1000** includes a first partition **1010a** that divides the first section **1007a** of the muffler **1000** into a first muffler chamber **1012a** and a second muffler chamber **1014a**. The first snap-action valve assembly **20a** includes a first valve flap **70a** and a first mass damper **148a**, which are constructed in accordance with the disclosure set forth herein. The first snap-action valve assembly **20a** extends through the first partition **1010a** and communicates with a first inlet pipe **1022a** that extends into the first muffler chamber **1012a** and a first outlet pipe **1052a** that extends into the second muffler chamber **1014a**. A second outlet pipe **1056a** communicates with and extends into the first muffler chamber **1012a**. When the first valve flap **70a** is in a closed position (as shown in Figure 12A), exhaust cannot flow through the first snap-action valve assembly **20a** and into the first outlet pipe **1052a**. Accordingly, exhaust flow is directed into the first muffler chamber **1012a** and out through the second outlet pipe **1056a**. When the first valve flap **70a** is in an open position (as shown in Figure 12B), exhaust can flow through the first snap-action valve assembly **20a** and into the first outlet pipe **1052a**.

[0066] The second section **1007b** of the muffler **1000** includes a second partition **1010b** that divides the second section **1007b** of the muffler **1000** into a third muffler chamber **1012b** and a fourth muffler chamber **1014b**. The second snap-action valve assembly **20b** includes a second valve flap **70b** and a second mass damper **148b**, which are constructed in accordance with the disclosure set forth herein. The second snap-action valve assembly **20b** extends through the second partition **1010b** and communicates with a second inlet pipe **1022b** that extends into the second muffler chamber **1012b** and a third outlet pipe **1052b** that extends into the fourth muffler chamber **1014b**. A fourth outlet pipe **1056b** communicates with and extends into the third muffler chamber **1012b**. When the first valve flap **70b** is in a closed position (as shown in Figure 12A), exhaust cannot flow through the second snap-action valve assembly **20b** and into the third outlet pipe **1052b**. Accordingly, exhaust flow is directed into the third muffler chamber **1012b** and out through the fourth outlet pipe **1056b**. When the second valve flap **70b** is in an open position (as shown in Figure 12B), exhaust can flow through the second snap-action valve assembly **20b** and into the third outlet pipe **1052b**.

[0067] The first and third outlet pipes **1052a**, **1052b** may be connected to one another at the dividing wall **1005** and may communicate with one another to equalize exhaust gas pressure in the first and third outlet pipes **1052a**, **1052b**. From Figures 12A-B, it should be appreciated that the size and shape of the first and second mass dampers **148a**, **148b** of the first and second snap-action valve assemblies **20a**, **20b** may be dictated by the size and shape of the housing **1002** of the muffler **1000**. The goal being to place as much weight of the first and second mass dampers **148a**, **148b** near the housing **1002** of the muffler **1000** as possible without having the housing **1002** of the muffler **1000** interfere with rotation of the first and second mass dampers **148a**, **148b** as the first and second valve flaps **70a**, **70b** of the first and second snap-action valve assemblies **20a**, **20b** rotate between the open and closed positions. To this end, several possible configurations are described below.

[0068] Figure 13A illustrates the mass damper **148** of the snap-action valve assembly **20** shown in Figures 1 and 2. The shape of the mass damper **148** is important because the mass damper **148** rotates with the shaft **102** and creates a distributed mass that is spaced from the pivot axis **114** of the shaft **102**. The distributed mass created by the mass damper **148** gives the mass damper **148** a inertial value that ranges from 250 to 400 gram - square millimeters ($\text{g}\cdot\text{mm}^2$) and functions to reduce vibration related harmonics (e.g. rattling noises) and excessive valve flutter caused by flowrate fluctuations in the engine's exhaust flow (e.g. exhaust pulsation). This inertial value range strikes a balance between the dampening ability of the mass damper **148** and packaging constraints within the muffler **900**. That is, the mass damper **148** must be configured so that it does not interfere with (i.e. contact) the of the outer

shell 904, outlet header 908, or partition 910 of the muffler 900 as the valve flap 70 moves between the open and closed positions.

[0069] As shown in Figure 2, the external shaft segment 108 of the shaft 102 is received in the attachment hole 152 of the mass damper 148 when the snap-action valve assembly 20 is fully assembled. Accordingly, the pivot axis 114 extends coaxially through the attachment hole 152 in the mass damper 148. Moreover, the primary mass damper axis 158 of the linear segment 154 of the mass damper 148 is transverse to the pivot axis 114. In the configuration shown in Figures 1, 2, and 13A, the first and second transverse segments 156a, 156b are transverse to both the primary mass damper axis 158 and the pivot axis 114. More particularly, the first and second transverse segments 156 of the mass damper 148 extend from the pair of damper ends 160 in opposite transverse directions relative to the primary mass damper axis 158. The pair of damper ends 160 and the first and second transverse segments 156a, 156b of the mass damper 148 are evenly spaced from the pivot axis 114 and thus the attachment hole 152 in the mass damper 148, which balances/distributes the mass of the mass damper 148 evenly about the pivot axis 114.

[0070] In the alternative configuration shown in Figure 13B, a modified mass damper 148' is shown with first and second transverse segments 156c, 156d that are spaced apart and that extend from the pair of damper ends 160 in the same direction relative to the primary mass damper axis 158 giving the mass damper 148' a U-like shape. In accordance with this configuration, the first and second transverse segments 156c, 156d are still transverse to the primary mass damper axis 158 of the linear segment 154 of the mass damper 148', but the first and second transverse segments 156c, 156d now extend parallel to the pivot axis 114. The pair of damper ends 160 and the first and second transverse segments 156c, 156d of the mass damper 148' are evenly spaced from the pivot axis 114 and thus the attachment hole 152 in the mass damper 148', which balances/distributes the mass of the mass damper 148' evenly about the pivot axis 114.

[0071] In the alternative configuration shown in Figure 13C, a modified mass damper 148'' is shown with an imbalanced linear segment 154'. Like in the configuration shown in Figures 1, 2, and 13A, the first and second transverse segments 156a, 156b of the mass damper 148'' shown in Figure 13C extend from the pair of damper ends 160 in opposite transverse directions relative to the primary mass damper axis 158 such that the first and second transverse segments 156a, 156b are transverse to both the primary mass damper axis 158 and the pivot axis 114. The attachment hole 152 in the imbalanced linear segment 154' is off-center such that the pair of damper ends 160 and the first and second transverse segments 156a, 156b of the mass damper 148'' are unevenly spaced from the pivot axis 114 and the attachment hole

152. As a result, the mass of the mass damper **148''** is imbalanced (i.e. is unevenly distributed) about the pivot axis **114**. In accordance with this configuration, the imbalanced linear segment **154'** may include a flattened portion **198** adjacent the attachment hole **152**. The flattened portion **198** of the imbalanced linear segment **154'** has a reduced cross-sectional width compared to the rest of the imbalanced linear segment **154'**, including the portions of the imbalanced linear segment **154'** adjacent the pair of damper ends **160**. The reduced cross-sectional width of the flattened portion **198** allows the mass damper **148''** to be mounted closer to the valve flap **70** to allow for additional packaging clearance. Although the configuration shown in Figure 13C is imbalanced, packaging constraints may necessitate the use of such a design. In order to minimize uneven torque loads created by the mass damper **148''** on the shaft **102**, the mass damper **148''** may be mounted on the shaft **102** such that the primary mass damper axis **158** is vertically oriented (i.e. aligned with the direction of gravitational pull **G**) when the valve flap **70** is positioned half way between the open and closed positions. For example and without limitation, if the valve flap **70** travels 40 degrees between the open and closed positions, then the primary mass damper axis **158**, which extends coaxially through the imbalanced linear segment **154'**, will be vertically oriented when the valve flap **70** is rotated 20 degrees from the closed position. Advantageously, the inventors have found that such a configuration utilizes gravity to minimize the uneven torque loads created by the mass damper **148''** on the shaft **102**.

[0072] In the alternative configuration shown in Figure 13D, a modified mass damper **148'''** is shown with first and second transverse segments **156e**, **156f** that are spaced apart and extend from the pair of damper ends **160** in opposite directions relative to the primary mass damper axis **158**. The first and second transverse segments **156e**, **156f** are curved giving the mass damper **148'''** a S-like shape. In accordance with this configuration, the first and second transverse segments **156e**, **156f** are transverse to the primary mass damper axis **158** of the linear segment **154** of the mass damper **148'''** and scribe a packaging circumference **197** about the attachment hole **152** in the mass damper **148'''** when the mass damper **148'''** is rotated 360 degrees about the attachment hole **152**. As a result, the mass damper **148'''** illustrated in Figure 13D is particularly well suited for applications where packaging is tight and little space is available for the mass damper **148'''**.

[0073] In the alternative configuration shown in Figure 13E, a modified mass damper **148''''** is shown with first and second transverse segments **156g**, **156h** that are spaced apart and that extend from the pair of damper ends **160** in the same direction relative to the primary mass damper axis **158**. The first and second transverse segments **156g**, **156h** are curved in a common plane **P** around at least part of the first conduit **22** of the snap-action valve assembly **20** giving the mass damper **148''''** a C-like shape. The pivot axis **114** is also disposed

within the common plane **P**. In accordance with this configuration, the first and second transverse segments **156g**, **156h** are transverse to the primary mass damper axis **158** of the linear segment **154** of the mass damper **148'''** and are contained within a packaging boundary **199** that extends within common plane **P**. As a result, the mass damper **148'''** illustrated in Figure 13E is well suited for applications where packaging is tight and little space is available for the mass damper **148'''**.

[0074] Many modifications and variations of the present invention are possible in light of the above teachings and may be practiced otherwise than as specifically described while within the scope of the appended claims. These antecedent recitations should be interpreted to cover any combination in which the inventive novelty exercises its utility. With respect to the methods set forth herein, the order of the steps may depart from the order in which they appear without departing from the scope of the present disclosure and the appended method claims. Additionally, various steps of the method may be performed sequentially or simultaneously in time.

CLAIMS

What is claimed is:

1. A snap-action valve assembly for an exhaust system comprising:
5 a first conduit extending along a central axis to define an exhaust passageway therein;
a valve flap disposed within said exhaust passageway for controlling exhaust flow through said exhaust passageway;
a shaft supporting said valve flap in said exhaust passageway for rotation about a
10 pivot axis between a closed position and an open position; and
a mass damper external to said first conduit that is rotatably coupled to said shaft such that said mass damper rotates with said shaft, said mass damper including a linear segment extending along a primary mass damper axis between a pair of damper ends, a first transverse segment, and a second transverse segment, said first and second transverse segments extending
15 from said pair of damper ends, and each of said first and second transverse segments extending in a transverse direction relative to said primary mass damper axis.
2. The snap-action valve assembly of Claim 1, wherein said primary mass damper axis is transverse to said pivot axis.
20
3. The snap-action valve assembly of Claim 2, wherein said linear segment and said first and second transverse segments create a distributed mass around said pivot axis that has an inertial value that ranges from 250 to 400 gram - square millimeters.
- 25 4. The snap-action valve assembly of Claim 2, wherein said first and second transverse segments extend from said pair of damper ends in opposite transverse directions such that said first and second transverse segments are transverse to both said primary mass damper axis and said pivot axis.
- 30 5. The snap-action valve assembly of Claim 2, wherein said first and second transverse segments extend from said pair of damper ends in identical transverse directions such that said first and second transverse segments are transverse to said primary mass damper axis and parallel to said pivot axis giving said mass damper a U-like shape.

6. The snap-action valve assembly of Claim 2, wherein said first and second transverse segments extend from said pair of damper ends in opposite directions such that said first and second transverse segments are transverse to both said primary mass damper axis and said pivot axis and wherein said first and second transverse segments are curved giving said mass damper a S-like shape.

7. The snap-action valve assembly of Claim 2, wherein said first and second transverse segments extend from said pair of damper ends in a common plane and curve around at least part of said first conduit giving said mass damper a C-like shape.

8. The snap-action valve assembly of Claim 2, wherein said first and second transverse segments are equally spaced from said pivot axis.

9. The snap-action valve assembly of Claim 2, wherein said first and second transverse segments are unevenly spaced from said pivot axis.

10. The snap-action valve assembly of Claim 9, wherein said linear segment includes a flattened portion of reduced cross-sectional width between said pivot axis and said first transverse segment.

11. The snap-action valve assembly of Claim 9, wherein said linear segment is attached to said shaft such that said primary mass damper axis is vertically oriented when said valve flap is positioned half way between said closed position and said open position.

12. The snap-action valve assembly of Claim 2, wherein said shaft includes an axle portion, an external shaft segment, a lever arm, and a spring attachment arm, wherein at least part of said axle portion is disposed within said first conduit, wherein said external shaft segment, said lever arm, and said spring attachment arm are external to said first conduit, wherein said valve flap is carried on said axle portion such that said axle portion of said shaft rotates with said valve flap, wherein said axle portion is co-axially aligned with said pivot axis of said valve flap, wherein said mass damper is attached to said external shaft segment, wherein said axle portion extends between said external shaft segment and said lever arm, wherein said spring attachment arm defines a spring attachment arm axis that is parallel to and spaced from said pivot axis, wherein said lever arm extends transversely between said axle portion and said

spring attachment arm of said shaft, and wherein said first conduit includes an anchor post extending outwardly from said first conduit.

13. The snap-action valve assembly of Claim 12 further comprising:

5 a tension spring having a helical main body disposed between first and second hook ends, said first hook end of said tension spring being retained on said spring attachment arm of said shaft and said second hook end of said tension spring being retained on said anchor post, said tension spring biasing said valve flap to said closed position.

10 14. A snap-action valve assembly for an exhaust system comprising:

a first conduit extending along a central axis to define an exhaust passageway therein;

a valve flap disposed within said exhaust passageway for controlling exhaust flow through said exhaust passageway, said valve flap extending in a valve flap plane, said valve flap including a first arcuate edge;

15 a pad carried on said valve flap including a body portion and an end portion that extends over said first arcuate edge of said valve flap;

a shaft supporting said valve flap in said exhaust passageway for rotation between a closed position and an open position, said end portion of said pad contacting an inside surface of said first conduit when said valve flap is in said closed position;

20 said valve flap including a resilient tongue disposed between said valve flap and said body portion of said pad that is angled up and is spaced away from said first arcuate edge of said valve flap;

said pad being attached to and supported by said resilient tongue; and

25 said resilient tongue extending from said valve flap at a first angle relative to said valve flap plane that changes as said resilient tongue deflects in response to said end portion of said pad contacting said inside surface of said first conduit when said valve flap pivots to said closed position.

30 15. The snap-action valve assembly of Claim 14, wherein said valve flap includes a first side that faces upstream in said exhaust passageway, a second side that faces downstream in said exhaust passageway, a first valve flap ear disposed to one side of said shaft, and a second valve flap ear disposed to an opposite side of said shaft relative to said first valve flap ear, said first valve flap ear having a greater surface area than said second valve flap ear.

16. The snap-action valve assembly of Claim 15, wherein said resilient tongue is attached to said first side of said valve flap and extends from said first valve flap ear at first angle relative to said valve flap plane such that said resilient tongue deflects towards said first arcuate edge of said valve flap as said end portion of said pad makes contact with said inside surface of said first conduit to dampen vibration related harmonics and excessive valve flutter.


17. The snap-action valve assembly of Claim 15, wherein said resilient tongue is attached to said second side of said valve flap and extends from said second valve flap ear at said first angle relative to said valve flap plane such that said resilient tongue deflects away from said valve flap plane as said end portion of said pad makes contact with said inside surface of said first conduit to dampen vibration related harmonics and excessive valve flutter.

18. The snap-action valve assembly of Claim 15, wherein said shaft is mounted off-center in said exhaust passageway such that said pivot axis is spaced from said central axis of said first conduit.

19. A snap-action valve assembly for an exhaust system comprising:
a first conduit extending along a central axis to define an exhaust passageway therein;
a valve flap disposed within said first conduit for controlling exhaust flow through said exhaust passageway;
a shaft supporting said valve flap in said exhaust passageway for rotation about a pivot axis between a closed position and an open position;
said valve flap extending in a valve flap plane, said valve flap including a first arcuate edge and a pair of linear side edges;
said valve flap having a first side and a second side opposite said first side;
a pad including a body portion that is attached to said first side of said valve flap and an end portion that extends over said first arcuate edge;
said end portion of said pad contacting an inside surface of said first conduit when said valve flap is in said closed position; and
said pad including at least one side wing extending from said body portion of said pad that wraps around at least one of said linear side edges of said valve flap to said second side of said valve flap, said at least one side wing being sized for contact with said inside surface of

said first conduit when said valve flap is in said open position to dampen vibration related harmonics and valve flap flutter.

20. The snap-action valve assembly of Claim 19, wherein said pad includes first and second side wings that extend in opposite directions from said body portion of said pad, wrap
5 around said linear side edges of said valve flap, and extend at least partially across said second side of said valve flap.







Fig-2









Fig-4









Fig-7B

8/13






Fig-9




Fig-11





Fig-10






Fig-12B




Fig-13A




Fig-13B




Fig-13C




Fig-13D




Fig-13E

A. CLASSIFICATION OF SUBJECT MATTER**F01N 1/16(2006.01)i, F16K 1/22(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

F01N 1/16; F01N 1/02; F16K 15/03; F16F 7/10; F01N 1/00; F01N 7/00; F16K 1/22

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & keywords: exhaust conduit, flap valve, shaft, pivot axis, mass damper, linear segment, transverse segment, pad, resilient tongue, side wing

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 2010-135095 A2 (TENNECO AUTOMOTIVE OPERATING COMPANY INC. et al.) 25 November 2010 See paragraphs [0032]-[0037] and figure 8.	1-20
Y	US 4858738 A (NOVOA, FERNANDO) 22 August 1989 See column 6, lines 35-44 and figure 2.	1-13
Y	US 8657065 B1 (TENNECO AUTOMOTIVE OPERATING COMPANY INC.) 25 February 2014 See column 2, line 38 - column 3, line 60 and figures 1A-6	14-20
A	US 6527006 B2 (JACKSON, BENJAMIN ELLIOTT) 04 March 2003 See column 2, line 43 - column 3, line 60 and figures 1-5.	1-20
A	US 5355673 A (STERLING et al.) 18 October 1994 See column 2, line 12 - column 3, line 32 and figures 1-4.	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

17 November 2017 (17.11.2017)

Date of mailing of the international search report

17 November 2017 (17.11.2017)

Name and mailing address of the ISA/KR

International Application Division

Korean Intellectual Property Office

189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea



Facsimile No. +82-42-481-8578

Authorized officer

LEE, Dal Kyong

Telephone No. +82-42-481-8440



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2017/045923

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2010-135095 A2	25/11/2010	BR PI1007720A2 CN 102428256 A CN 102428256 B DE 112010002064 T5 JP 2012-527574 A JP 5801797 B2 KR 10-1609629 B1 KR 10-2012-0019456 A KR 10-2015-0080018 A KR 10-2016-0042155 A US 2010-0294589 A1 US 7896130 B2 WO 2010-135095 A3	31/01/2017 25/04/2012 21/05/2014 29/11/2012 08/11/2012 28/10/2015 08/04/2016 06/03/2012 08/07/2015 18/04/2016 25/11/2010 01/03/2011 03/03/2011
US 4858738 A	22/08/1989	US 5020644 A	04/06/1991
US 8657065 B1	25/02/2014	CN 104870782 A CN 104870782 B DE 112013005995 T5 JP 2016-502024 A JP 5998291 B2 KR 10-1709163 B1 KR 10-2015 0088852 A WO 2014-092947 A1	26/08/2015 13/06/2017 27/08/2015 21/01/2016 28/09/2016 22/02/2017 03/08/2015 19/06/2014
US 6527006 B2	04/03/2003	US 2003-0000582 A1	02/01/2003
US 5355673 A	18/10/1994	None	