

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number
WO 2013/093903 A1

(43) International Publication Date
27 June 2013 (27.06.2013)

W I P O | P C T

(51) International Patent Classification:
B09C 1/08 (2006.01) C01B 15/043 (2006.01)
B0W 53/62 (2006.01)

(21) International Application Number:
PCT/IL20 12/000394

(22) International Filing Date:
20 December 2012 (20.12.2012)

(25) Filing Language:
English

(26) Publication Language:
English

(30) Priority Data:
61/577,894 20 December 2011 (20.12.2011) US
61/660,819 18 June 2012 (18.06.2012) US

(71) Applicant: **YISSUM RESEARCH DEVELOPMENT COMPANY OF THE HEBREW UNIVERSITY OF JERUSALEM LTD.** [IL/IL]; Hi-tech Park, Edmond J Safra Campus, Givat Ram, P.O. Box 39135, 91390 Jerusalem (IL).

(72) Inventors: **SASSON, Yoel**; 30 HaPalmach Street, 92542 Jerusalem (IL). **STOIN, Uri**; 56/7 Netiv HaMazalot, 97830 Jerusalem (IL). **BARNEA, Zach**; 5/1 Carlebach Street, 93386 Jerusalem (IL).

(74) Agent: **PYERNIK RUTMAN**; P.O. Box 10012, 84001 Beer-Sheva (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: PREPARATION OF AN AQUEOUS REAGENT FOR THE ABSORPTION OR DESTRUCTION OF POLLUTANTS

Figure 1



(57) Abstract: Process for treating a medium by the removal or destruction of one or more undesired substances present in said medium, comprising combining hydrogen peroxide and alkali hydroxide in an aqueous solution to form superoxide, and bringing the resultant superoxide-containing solution into contact with said medium. The process is useful for the destruction of halogenated organic pollutants and also for carbon dioxide removal from flue gases. The process can also be applied for soil remediation.

WO 2013/093903 A1

Preparation of an aqueous reagent for the absorption or destruction of pollutants

The invention relates to the preparation of an aqueous reagent based on the *in-situ* generation of the superoxide radical anion (O_2^-), which has been found useful for various environmental activities, such as the destruction of halogenated organic pollutants and also for carbon dioxide removal from flue gases.

Low-molecular-weight halogenated hydrocarbons which are commonly produced and used by the chemical industry, e.g., carbon tetrachloride and dichloromethane, are considered among the most difficult contaminants to remove from groundwater and soil.

Carbon dioxide is a greenhouse gas, formed mainly by the combustion of fossil fuels, for example, in electric power generating plants. Fossil fuels combustion is responsible for releasing massive carbon dioxide amounts into the atmosphere, which immensely contributes to the global warming phenomenon. Global efforts are underway to remove CO_2 from the flue gases prior to their release to the atmosphere.

It is known that superoxide can be formed through an *in situ* electrochemical reduction of oxygen in aprotic solvents to give O_2^- . Roberts et al. [J. Am. Chem. Soc. 103, 712-714 (1981)] reported such a reaction, which took place in dimethylformamide (DMF) and dimethyl sulfoxide (Me_2SO), where the resulting superoxide reacted with chlorinated methane compounds, i.e., CCl_4 , $CHCl_3$, CH_2Cl_2 and CH_3Cl .

Superoxide is also available in the form of its solid alkali metal salts, e.g., potassium superoxide (KO_2) and sodium

superoxide (NaO_2), which are fairly stable in a solid form when kept in a dry environment. WO 2008/113061 provides a method for removing carbon dioxide from combustion exhaust, comprising capturing the carbon dioxide using either solid KO_2 (i.e., in the form of pellets) or molten KO_2 .

WO 02/40138 describes a process for removing nitrogen oxides from flue gases, following which the gas is led through a peroxide reservoir to convert some carbon dioxide to carbonate. A base may be added to the reservoir to set the pH value of the liquid at around 5 in order to allow dissolution of the carbonate.

L. Dubois et al [Chemical Engineering & Technology, vol. 33 issue 10, pp. 1601-1609, October 2010] describes the absorption of H_2S and CO_2 into solutions comprising a low concentration (i.e. up to 1.0 M) of NaOH and H_2O_2 .

Scott Elliott [Environ. Sci. Technol. 1990, 24 1, pp. 264-267] describes the hydrolysis of carbon disulfide in an aqueous alkaline solution in the presence of hydrogen peroxide.

US 2007/0269358 discloses a process for absorbing chlorine from a gas mixture containing chlorine and carbon dioxide, comprising, in a first stage, contacting the gaseous mixture with a first aqueous solution comprising a base and a reducing agent, and in a second stage, contacting the intermediate gaseous mixture obtained with a second aqueous solution comprising a base and a reducing agent. The base reacts with the carbon dioxide to form a carbonate salt, following which chlorine is reduced by the reducing agent concurrently with the release of CO_2 .

It has now been found that an aqueous solution comprising hydrogen peroxide and a base {e.g., alkali hydroxide) can be used for the absorption of carbon dioxide from flue gases. Under certain conditions, sodium (or potassium) hydroxide and hydrogen peroxide react to produce *in situ* the highly reactive superoxide anion, which in turn rapidly reacts with carbon dioxide to afford a carbonate salt.


It has also been found that when the aforementioned aqueous solution comprising hydrogen peroxide and a base (e.g., alkali hydroxide) is brought into contact with halogenated organic compounds in the presence of a phase transfer catalyst, then the pollutant undergoes rapid mineralization.

The present invention is therefore primarily directed to a process for treating a medium by the removal or destruction of one or more undesired substances present in said medium, comprising combining hydrogen peroxide and hydroxide source in an aqueous solution to form superoxide, and bringing the resultant superoxide-containing solution into contact with said medium. It should be noted that in some circumstances the medium consists solely of the undesired substance to be destroyed. In other words, in these circumstances, the undesired substance constitutes the medium itself.

Hydrogen peroxide is applied in the process in the form of an aqueous solution at a concentration which is preferably not less than 10M, e.g., between 10M and 30M. Suitable hydroxide sources to be used are alkali hydroxide, e.g., sodium hydroxide and potassium hydroxide, with sodium hydroxide being most preferred. The hydrogen peroxide and the hydroxide source are combined *in situ* at the treatment site, such that the resultant superoxide-containing aqueous solution can be put to use almost instantly, e.g., preferably within a period of time

of not more than one minute, and even more preferably within less than five seconds, e.g., within one second, following the formation of the solution. For this purpose, the hydroxide source can be added as a solid to the H₂O₂ aqueous solution under stirring. However, it is generally preferred to dissolve the hydroxide source in a separate solution and then mix together the H₂O₂ and hydroxide solutions, following which the combined stream is brought into contact with the pollutant-contaminated medium. It is also possible to inject two separate streams consisting of aqueous H₂O₂ and hydroxide solutions into the pollutant-contaminated medium.

In any case, the concentrations and relative amounts of the two reactants are suitably adjusted such that the reaction results in the *in situ* formation of the superoxide radical anion O₂⁻ by the following sequence of reactions:




wherein M denotes the alkali metal, e.g., either sodium or potassium. To this end, the hydroxide source and hydrogen peroxide are combined in an aqueous solution, with the hydroxide concentration added to the solution being not less than 1.5 M, preferably not less than 1.9 M, e.g., in the range of 2.25 to 20.0 M, and more preferably in the range of 3.0 to 9.0 M. The molar ratio between the hydrogen peroxide and the hydroxide ion combined in the solution is above 1:1, preferably above 1.1:1, more preferably above 1.2:1, e.g., in the range of 1.2:1 to 2:1, with a ratio of at least 1.4:1, e.g., from 1.4:1 to 1.6:1, and particularly around 1.5:1, being especially preferred. Under these conditions, the pH of the aqueous solution formed is preferably higher than 10.0, more preferably higher than 11.0 and most preferably higher

than 12.0, e.g., from 10.5 to 12.5, and a workable amount of the active superoxide species is formed in the solution, such that the solution can serve for the purification of a pollutant-contaminated medium.

The formation of the superoxide in the solution may be confirmed by means of Infrared spectroscopy. The characteristic IR stretching frequency of the O_2^- species is at a wavelength of about 1108 cm^{-1} [see L. Andrews, " *Infrared Spectrum, Structure, Vibrational Potential Function, and Bonding in the Lithium Superoxide Molecule LiO_2* " , Journal of Chemical Physics, 1969 Volume 50, Number 10; Lester Andrews, " *Infrared Spectra and Bonding in the Sodium Superoxide and Sodium Peroxide Molecules*" , The Journal of Physical Chemistry, 1969, Volume 78, Number 11]. Alternative methods for superoxide identification are based on Raman spectroscopy and Electron Paramagnetic Resonance spectroscopy (EPR).

The superoxide-containing aqueous solution, prepared as set out above, can be put to use for the purification of different types of pollutant-contaminated mediums. Pollutants that can be removed or destroyed by the process of the invention can generally be considered as electrophiles . Exemplary applications will be described separately in the passages that follow.

A first application relates to CO_2 absorption from gaseous streams, e.g., the pollutant-contaminated medium is a gaseous mixture which needs to be purified by means of the removal carbon dioxide. The superoxide anion rapidly reacts with carbon dioxide to afford a carbonate salt:



It should be noted that the rate of reaction of the superoxide anion with CO_2 is three orders of magnitude faster than the reaction of the latter with the hydroxide anion:



According to the process of the invention, a gaseous mixture comprising carbon dioxide, e.g., flue gases formed by the combustion of fossil fuels in electric power generating plants, is made to contact an aqueous solution of hydrogen peroxide and a hydroxide salt. The contact takes place in a gas-liquid contactor, e.g., a suitable vertical structure known in the art, namely, in a tower or a column, in which an upward flow of gases to be purified and a countercurrent of a descending liquid are allowed to mix, as described in more detail hereinafter below.

The absorption of carbon dioxide by the superoxide anion may be carried out at a broad temperature range, e.g. in the range from 5 to 80°C, e.g. from 20 to 60°C, and suitably at room temperature (20 to 25°C), at a pH value of not less than 10, e.g., in the range from 10.5-12.5.

As noted above, carbon dioxide is converted into an alkali carbonate salt (Na_2CO_3 or K_2CO_3), which can be subsequently treated with calcium hydroxide [$\text{Ca}(\text{OH})_2$] to regenerate the corresponding alkali hydroxide concurrently with the formation of the water-insoluble, easily separable calcium carbonate (CaCO_3). The latter can be treated to obtain calcium hydroxide.

The description that follows refers to Figure 1, which illustrates a flue gas scrubbing apparatus which is suitable for removing carbon dioxide from the flue gases, in accordance

with the process of the invention. The apparatus comprises a gas liquid contactor (1), which is typically in the form of a vertically positioned absorber tower, through which a gaseous stream flows in an upward direction and contacts with a countercurrent of descending liquid. For example, the gas-liquid contactor which provides the contact between CO₂ and the superoxide-containing solution is a packed scrubbing tower or a spray tower. The flue gas (2), which typically comprises from about 1% to 50% carbon dioxide, e.g., about 12% carbon dioxide, enters the tower through an inlet pipe connected to the perimeter of the tower. The flue gas is caused to flow in an upward direction through the tower using a pump (3) which may operate at throughput of about 0.1 to 5,000,000 m³/hr. Prior to being introduced into the tower, the flue gas is passed through a heat exchanger (4) where its temperature is reduced to less than 150 °C, e.g., about 70 to 150°C.

Packing material that increases the contact area between gaseous and liquid streams is conventionally mounted within the tower. For example, the tower may have a fill assembly positioned therein, which assembly is in the form of a three-dimensional matrix composed of a plurality of grids spaced from one another and disposed in perpendicular planes to form essentially cubic spaces there between, into which spaces fibrous material is introduced. In operation, the gaseous stream to be purified and the liquid absorbent are brought into intimate contact within the surfaces made by said fibrous material, which surfaces are being supported by means of said fill assembly within the tower. The spray tower is equipped with a plurality of spray headers (not shown) mounted in the internal space of the tower.

The superoxide-containing solution is produced by allowing a concentrated hydroxide solution and a concentrated hydrogen

peroxide solution to react in a mixing chamber (7), as described henceforth. A concentrated hydroxide solution is prepared *in-situ* by continuously or periodically adding a solid hydroxide salt, such as sodium or potassium hydroxide, to a first mixing chamber (5), into which water is allowed to flow, thus dissolving the salt. The concentrated hydroxide solution and a concentrated hydrogen peroxide aqueous solution are separately pumped from mixing chamber (5) and reservoir (6), respectively, into a second mixing chamber (7), wherein the superoxide anion is formed through reactions (I) and (II) mentioned above. The concentrations and relative flow rates of the two separated streams of hydroxide and hydrogen peroxide are adjusted such that the resultant concentration of hydroxide in the mixing chamber, prior to the formation of superoxide, is above 1.5 M, preferably between 1.6-20 M, and more preferably between 6 and 9 M, and the molar ratio between the hydrogen peroxide and alkali hydroxide is preferably about 3:2. The resultant concentration of superoxide in the mixing chamber is, for example, in the range of 1.5 to 6 M. The superoxide-containing solution is then directed from the mixing chamber into the upper section of the tower using a pump (8) and is dispersed in the internal section of the tower through the spray headers (not shown). The aqueous mixture flows downward due to the force of gravity, contacts with the flue gas and absorbs the carbon dioxide.

Having been subjected to the scrubbing operation in the absorber tower, the upwardly flowing, essentially CO₂-free, oxygen-enriched flue gas is released to the atmosphere through a gas outlet opening (9) positioned in the upper section of the absorber tower. A drop separator (not shown) may be mounted in upper section of the tower, such that the gas permitted to escape from the tower is free of mist. Alternatively, the scrubbed flue gas, typically containing

around 12% oxygen, may be directed back to the combustion plant (not shown) in order to facilitate the combustion process.


The aqueous solution is collected at the bottom of the tower, and is directed via pipe (10) through a centrifuge (11) wherein the solid carbonate salt is separated from the aqueous solution. Subsequently, excess water, formed during the reaction of hydroxide and hydrogen peroxide and added to the apparatus with the addition of hydrogen peroxide, is discharged via an outlet opening (12) by the use of a pump (13), in order to keep a constant volume of aqueous absorption solution within the apparatus. The aqueous absorption solution (water) is then recycled, via mixing chambers (5) and (7) by the use of a pump (14), back to the upper section of the scrubbing tower.

The continuous flow rate of the recycled aqueous solution within the apparatus, as well as the rates of addition of the concentrated hydrogen peroxide solution and the hydroxide source to the apparatus, are preferably adjusted such that carbon dioxide absorption reaches over 50%, preferably over 90% and most preferably over 95%, while maintaining a minimum amount of superoxide ion in the discharged water (12), namely, less than 1 M, and preferably less than 0.1 M.

The process of the invention can be carried out in a continuous mode of operation, wherein separate streams of alkali hydroxide solution and a hydrogen peroxide solution are fed continuously to the mixing chamber (7) of the apparatus of Figure 1. In another embodiment of the invention, the carbon dioxide absorption process is semi-continuous. According to the latter embodiment, the hydrogen peroxide and hydroxide source are added periodically to the apparatus, allowing the

formation of the superoxide anion, while the aqueous absorbent is recycled continuously through the apparatus. The frequency of addition of H_2O_2 and OH^- is adjusted to allow the superoxide anion formed to react with carbon dioxide.

It is possible, as an alternative to the continuous or semi-continuous addition of hydroxide salt to the apparatus, to recover the hydroxide salt used throughout the process by the following method. The carbonate salt formed following the reaction between carbon dioxide and sodium/potassium superoxide (see equation III above) is separated from the aqueous absorption medium and is then mixed with calcium hydroxide, preferably in a stoichiometric amount. Calcium hydroxide reacts with the carbonate salt to regenerate sodium/potassium hydroxide by the following reaction:




wherein M denotes either sodium or potassium. Calcium carbonate precipitates while the regenerated hydroxide salt is recycled back to the absorption medium.


In view of the fact that some of the sodium/potassium carbonate may exist in hydrated forms, e.g. in the form of thermonatrite $[Na_2CO_3 \cdot H_2O]$ or trona $[Na_3H(CO_3)_2 \cdot 2H_2O]$, the yield of recoverable sodium/potassium hydroxide may gradually decrease. To compensate for the loss of yield, a suitable amount of sodium/potassium hydroxide can be added to the apparatus via mixing chamber (5) in a continuous or semi-continuous manner.

The solid calcium carbonate formed simultaneously with the recovery of sodium/potassium hydroxide may be separated (e.g., by filtration) and discharged. Alternatively, it may be heated

to a temperature in the range of about 800 to 1000 °C, and preferably 900 °C, at atmospheric pressure to afford calcium oxide and liberated carbon dioxide.



Calcium oxide rapidly reacts with water to regenerate calcium hydroxide :







The regenerated calcium hydroxide thus formed may be reused for the regeneration of sodium/potassium hydroxide as described above. The chemistry of the carbon dioxide absorption process of the invention, including the regeneration of sodium/potassium hydroxide, is illustrated schematically in Figure 3.

A second application of the superoxide-containing aqueous solution of the invention relates to the destruction of halogenated organic pollutants. The term "halogenated organic pollutant" includes halogen-substituted aliphatic hydrocarbons, e.g., halogenated C1-C3 alkanes and alkenes, (especially halogenated methane, ethane and ethylene compounds, namely, CH_iX_j wherein X is independently Cl, Br or I, i≥1 and i+j=4 and C₂H_kX_m wherein X is independently Cl, Br or I, m>1 and k+m=4 or 6, including the mixed halogen-substituted compounds) and also halogen-substituted cyclic hydrocarbons, including aromatic hydrocarbons, e.g., benzene ring substituted with one or more halogen atoms. The process is especially useful for the destruction of chlorinated hydrocarbons, allowing at least the transformation of the pollutant to a more environmentally benign state, and more preferably, the mineralization of the pollutant


(mineralization is particularly achievable with respect to mono and polyhalogen methane).

The process can be applied for the destruction of halogenated organic pollutant at the bulk, i.e., water-immiscible, dense organic liquid consisting essentially of the halogenated pollutant is treated with the superoxide-containing solution of the invention. In these circumstances, the medium consists solely of the undesired substance to be destroyed. However, the process can also be applied for destroying the halogenated organic pollutant when it is present as a minor component contaminating a second organic liquid, in order to purify and recycle said second liquid.





In both cases, the *in-situ* generated superoxide-containing aqueous solution is brought into contact with the halogenated organic pollutant at ambient conditions in the presence of a phase transfer catalyst (PTC). Exemplary reactions demonstrating the complete mineralization of two pollutants by means of the aqueous solution of the invention are given by the following two sets of chemical equations:




Such that the mineralization of methyl halide is given by:



As to tetrahalomethane, e.g., tetrachloromethane, the following equations apply:



The total mineralization of methyl (tetra)halide is hence given by:



Phase transfer catalysts which are suitable for use in the reactions set forth above are composed of a nitrogen-containing cation, e.g., quaternary ammonium cation, namely, $\text{N}^+\text{R}_1\text{R}_2\text{R}_3\text{R}_4$ wherein each of R_1 , R_2 , R_3 and R_4 is independently C1-C18 alkyl group (preferably C1-C12 alkyl, which may be either linear or branched, most preferably linear) and a counter anion, which is displaceable by superoxide, e.g., halide anion (designated herein Hal^-).

Especially preferred are quaternary ammonium salts of the formula $\text{N}^+\text{CH}_3[(\text{CH}_2)_k\text{CH}_3]_3\text{Hal}^-$, wherein k is at least 5, e.g., between 5 to 9, and Hal is chloride or bromide. As an example of this preferred sub-class of quaternary ammonium salts, methyltriocetyl ammonium halide can be mentioned ($k=7$), which is commercially available in the form of its chloride salt as Aliquat 336.

Other examples include salts of the following formulas:

$\text{N}^+(\text{CH}_3)_2[(\text{CH}_2)_k\text{CH}_3]_2\text{Hal}^-$, such as didodecyldimethylarnmonium bromide (DDAB);

$\text{N}^+(\text{CH}_3)_3[(\text{CH}_2)_k\text{CH}_3]\text{Hal}^-$, such as hexadecyltrimethylammonium bromide (CTAB); and

$\text{N}^+[(\text{CH}_2)_k\text{CH}_3]_4\text{Hal}^-$, such as tetraoctylammonium bromide (TOAB).

The hydrogen peroxide aqueous solution, the alkali hydroxide, the phase transfer catalyst and the pollutant (or the pollutant-contaminated organic liquid) are vigorously mixed together in a suitable tank, as shown, for example, in Figure 12, which illustrates an apparatus for carrying out the

process of the invention for the destruction of halogenated organic pollutant at the bulk. In the specific embodiment shown in Figure 12, the destruction of carbon tetrachloride (abbreviated "CTC") is demonstrated. A similar apparatus, however, can also be used for decontaminating an organic liquid in which the halogenated pollutant is present as a minor component.

As shown in figure 12, CTC (31) is fed by means of pump (32) into a reaction chamber (33). A concentrated hydroxide solution is prepared *in-situ* by continuously or periodically adding solid hydroxide salt, such as sodium or potassium hydroxide (38), into a first reactor (37) through which water is allowed to flow continuously by means of pump (39), thus dissolving the salt. The concentrated hydroxide solution and a concentrated hydrogen peroxide aqueous solution (35) flow into a second reactor (36), wherein the superoxide anion is formed through reactions (I) and (II) mentioned above. The concentrations and relative flow rates of the two separated streams of hydroxide and hydrogen peroxide are adjusted such that the resultant concentration of hydroxide in the mixing chamber, prior to the formation of superoxide, is above 1.5 M, preferably between 1.6-20 M, and more preferably between 6 and 9 M, and the molar ratio between the hydrogen peroxide and alkali hydroxide is preferably about 3:2. The resultant concentration of superoxide in the reactor (36) is, for example, in the range of 1.5 to 6 M. The superoxide-containing solution then flows from the reactor (36) into the reaction chamber (33) by means of pump (34). Feed line (311) is used for injecting suitable amounts of a solution of the phase transfer catalyst (PTC) into the reaction chamber (33), where the aqueous solution and the CTC are vigorously mixed in the presence of the PTC. Without wishing to be bound by theory, it is believed that the halide ion of the quaternary ammonium

salt phase transfer catalyst is displaced by the superoxide anion, whereby the superoxide is being extracted to the water-miscible organic medium, where it exhibits extremely potent nucleophilic character and reacts rapidly, e.g., within minutes, at ambient conditions with the low-molecular weight halogenated compounds. The amount of phase transfer catalyst is at least 1 mol% relative to the halogenated compound to be destroyed, e.g., from 1 to 10 mol%, preferably from 4 to 6 mol%, e.g., around 5 mol%.

The apparatus shown in Figure 12 is provided with two discharge lines, through which the reaction products are withdrawn from the reaction chamber (33). A gaseous mixture comprising oxygen and chlorine produced by the reaction is released to the atmosphere (317). During the disappearance of the dense halogenated organic pollutant (i.e., the CTC), an aqueous mixture which contains the salts formed in the reaction (i.e., Na_2CO_3 and NaCl) is gradually collected at the bottom of the reaction chamber (33). This aqueous mixture also contains the PTC in the form of a separate layer disposed onto the water surface. The aqueous mixture is discharged (310) from the reaction chamber and conveyed to a separator (313). In the separator, the PTC layer is removed from the aqueous phase by techniques known in the art and is recycled, namely, directed back to the reaction chamber (33) through the feed line (311). The aqueous phase can now be treated in order to recover the water soluble sodium chloride and the partially insoluble sodium carbonate salts (315). Following the separation of the salts, the water, which is both formed during the reaction of hydroxide and hydrogen peroxide and added to the apparatus with the addition of hydrogen peroxide, is withdrawn by the use of a pump (314) and collected at a suitable tank (316). The water is recycled, via reactors (37) and (36) by the use of a pump (39).

A third application of the superoxide-containing aqueous solution of the invention relates to environmental remediation methods, e.g., for treating contaminated soil. The introduction of the combination of hydrogen peroxide and alkali hydroxide into contaminated soil, for *in-situ* chemical oxidation of toxic and persistent organic waste, can be achieved by means of suitable injection systems, adjusting injection pressure and injection depth to increase decontamination efficiency. Another aspect of the invention relates to a site remediation process, comprising injecting a first stream of hydrogen peroxide solution and a second stream of aqueous alkali hydroxide, or a combined stream of both, into halogenated organic pollutant-contaminated site (e.g., soil) such that the molar ratio between the hydrogen peroxide and the hydroxide ion is preferably above 1.1:1, more preferably above 1.2:1, e.g., in the range of 1.2:1 to 2:1, with a ratio of at least 1.4:1, e.g., from 1.4:1 to 1.6:1, and especially 1.5:1, being most preferred. The concentration of the hydrogen peroxide and alkali hydroxide in the combined aqueous stream are as set out above. The hydrogen peroxide and the hydroxide ion are delivered and distributed throughout the region to be treated. It should be noted that following the treatment, the pH of the soil is alkaline. The pH of the soil may be readily restored to a range acceptable for agricultural utilities by means of the addition of one or more acids such as nitric acid and phosphoric acid. This addition results not only in neutralizing the pH of the soil, but also in the enrichment of the soil with useful fertilizers. The soil remediation according to the invention allows the mineralization of polyhalogen (chlorinated) methane compounds, leaving no harmful products, or at least the transformation of the contaminant to a more benign substance.

In the Figures :

Figure 1 illustrates a scrubbing apparatus suitable for carrying out the absorption of CO_2 from a gaseous mixture.

Figure 2 illustrates the experimental set-up employed in the experimental work regarding CO_2 absorption.

Figure 3 is a schematic illustration of CO_2 absorption process, including the regeneration of sodium hydroxide.

Figure 4 shows the IR spectra of an aqueous absorption solution comprising sodium hydroxide and hydrogen peroxide.

Figure 5 is a graph showing the absorption of CO_2 by an aqueous hydroxide solution in the presence and absence of H_2O_2 , plotted versus time.

Figure 6 is a graph depicting the efficiency of CO_2 absorption by NaO_2 in comparison to NaOH and MEA .

Figure 7 is a graph illustrating the temperature dependence of CO_2 absorption by the superoxide anion.

Figure 8 is a graph illustrating CO_2 absorption by an aqueous solution of hydrogen peroxide and different hydroxide salts.

Figure 9 is a graph depicting CO_2 absorption at different hydroxide concentrations .

Figure 10 is a graph showing the absorption of CO_2 at various peroxide : hydroxide molar ratios.

Figure 11 illustrates a method for recycling the hydroxide used in the process of CO_2 absorption.

Figure 12 illustrates an apparatus for carrying out the destruction of CCl_4 by the process of the invention.

Figure 13 shows the degree of CCl_4 destruction as function of mineralization agent.

Figure 14 shows the degree of CH_3I destruction as function of mineralization agent.

Figure 15 is a bar diagram illustrating the effect of the presence of a phase transfer catalyst in the destruction of halogenated pollutant.

Figure 16 demonstrates the destruction of chlorobenzene .

Examples

Materials

Carbon dioxide gas cylinders 30% (w/w) in nitrogen was purchased from Maxima gas supplier, Israel.

Carbon dioxide gas cylinders 100% was purchased from Mushilion gas supplier, Israel.

30% aqueous hydrogen peroxide solution was purchased from Bio Lab ltd, Israel.

Sodium hydroxide, potassium hydroxide, lithium hydroxide, rubidium hydroxide, monoethanolamine (MEA), halogenated alkanes and alkenes (e.g., methyl iodide, carbon tetrachloride, bromotrichloro methane), Aliquat 336, CTAB, DDAB, and TOAB were purchased from Sigma Aldrich ltd, Israel.

Measurements

Gas chromatography (GC) studies were conducted using GC with FID detector Famewax™ 30m, 0.32mm ID, 0.25um, manufactured by Restek ltd, U.S.

FTIR studies were conducted using Peact IR 4000, manufactured by Metier.

XRD studies were conducted using X-ray diffractometer, Range: $110^\circ < 2\Theta < 168^\circ$, D8 advance by Bruker AXS.

CO_2 concentration was determined using a gas analyzer manufacture by Emproco ltd Israel.

CO₂ absorption measurement set-up

The experimental set-up used in the following examples is shown schematically in Figure 2. CO₂ was made to flow through a flow meter (22) at a flow rate of 1 L/minute into a gas trap (24) loaded with the aqueous absorbing solution, which was continuously stirred by a magnetic stirrer (23). The CO₂ source was a commercial 100% CO₂ or commercial 30% (w/w) CO₂ in nitrogen gas cylinder (21). The contact time between the CO₂ and the absorbing solution in the gas trap was approximately 0.01 seconds. Gases exiting the gas trap were directed through an O₂/CO₂ analyzer (25) connected to a computer (26).

The initial CO₂ concentration was measured by using a bypass (27), through which the CO₂ flows directly into the analyzer, thus determining the CO₂ concentration at time zero. Subsequently the absorber trap was connected, and the CO₂ gas concentration in the outlet of the trap was measured. The absorption yield was calculated by the following formula:

$$\% \text{absorption} = \left[\frac{C_{CO_2 \text{ Measured}}}{C_{CO_2 \text{ TimeZero}}} \right] \times 100$$
Example 1CO₂ absorption by an aqueous solution of hydrogen peroxide and sodium hydroxide

An aqueous absorption solution comprising water (30 mL), sodium hydroxide (10 grams; 0.25 mol) and 0.375 mol hydrogen peroxide (11.3 mL of 30% H₂O₂ aqueous solution) was prepared. The formation of superoxide in the solution was confirmed by Fourier transform infrared spectroscopy (FTIR). The spectrum of the absorption medium, depicted in Figure 4, includes a peak at 1108 cm⁻¹ attributed to the O₂⁻ molecule.

The absorption of CO_2 by the absorption solution was measured using the experimental set-up described above. The gas trap was loaded with the absorption solution. The experiment was allowed to continue for five minutes, during which the CO_2 absorption was measured periodically.

For the purpose of comparison, CO_2 absorption was measured under the same conditions in the absence of hydrogen peroxide, using an alkaline solution consisting of 0.25 mol (10 grams) sodium hydroxide dissolved in 30 ml of water as the absorption solution. The absorption of CO_2 by monoethanolamine (abbreviated MEA) was also tested under the same conditions using 30 mL water and 0.25 mol (15.27 grams) MEA as the absorption solution.

The results are presented graphically in Figure 5 which shows the CO_2 absorption (as percent relative to the initial CO_2 concentration) against time (in seconds) in the presence and absence of hydrogen peroxide. As shown, the absorption of CO_2 by an aqueous solution of sodium hydroxide and hydrogen peroxide reached approximately 100% for a duration of about 130 seconds. CO_2 absorption in the absence of hydrogen peroxide, in contrast, reached a maximum value of merely 20%.

Figure 6 depicts the conversion of CO_2 by the aqueous solution of sodium hydroxide and hydrogen peroxide as the absorption solution, in comparison to sodium hydroxide and MEA. It may be appreciated that the total CO_2 conversion by the absorption medium of the invention reached over 90%, in comparison to about 20% by each of the NaOH and MEA solutions.

Example 2CO₂ absorption by an aqueous solution of sodium hydroxide and hydrogen peroxide at different temperatures

The absorption of CO₂ by an aqueous solution of sodium hydroxide and hydrogen peroxide was measured using the experimental set-up described above. The gas trap was loaded with an aqueous solution consisting of water (30 mL), sodium hydroxide (10 grams; 0.25 mol) and 0.375 mol hydrogen peroxide (11.3 mL 30% H₂O₂ aqueous solution). The experiment was allowed to continue for five minutes, during which the CO₂ absorption was measured periodically.

The above experiment was carried out under the same conditions at four different temperatures (298 K, 313 K, 323 K and 353 K).

Figure 7 depicts the absorption of CO₂ over time for each of the four temperatures. As shown, the CO₂ absorption value reaches 100% throughout the entire tested temperature range.

Example 3CO₂ absorption by an aqueous solution of hydrogen peroxide and sodium or potassium hydroxide

The absorption of CO₂ by an aqueous solution of hydrogen peroxide and a hydroxide salt was measured using the experimental set-up described above. The experiment was carried out at room temperature (298 K). The gas trap was loaded with water (30 mL), 0.375 mol hydrogen peroxide (11.3 mL 30% H₂O₂ aqueous solution) and 0.25 mol of the tested hydroxide salt. The experiment was allowed to continue for

five minutes, during which the CO_2 absorption was measured periodically.

The results are graphically presented in Figure 8, where the abscissa indicates the time (seconds) and the ordinate indicates the CO_2 absorption. It may be appreciated that the two bases tested, sodium hydroxide and potassium hydroxide, are both highly effective with the former being slightly better.

Example 4

The effect of hydroxide concentration on CO_2 absorption

The absorption of CO_2 by an aqueous solution of hydrogen peroxide and sodium hydroxide was measured using the experimental set-up described above. A set of experiments was carried out using as absorption medium consisting of water {30 mL}, 0.375 mol hydrogen peroxide (11.3 mL 30% H_2O_2 aqueous solution) and various quantities of sodium hydroxide. The tested sodium hydroxide concentrations were 0.625 M, 1.25 M, 1.88M, 2.5 M, 5.0 M and 6.25 M. Each experiment was allowed to continue for five minutes, during which the CO_2 absorption was measured periodically.

Figure 9 illustrates the absorption of CO_2 over time for each of the six sodium hydroxide concentrations.

The absorption of CO_2 at a sodium hydroxide concentration of 0.625 M and 1.25 M is unsatisfactory. A sharp increase of the absorption of CO_2 is observed upon increasing the concentration of the hydroxide. The CO_2 absorption at a sodium hydroxide concentration of 6.25 M {corresponding to a $\text{H}_2\text{O}_2:\text{OH}$ molar ratio of 1.5:1} reaches 100%.

Example 5The effect of hydrogen peroxide concentration on CO₂ absorption

The absorption of CO₂ by an aqueous solution of sodium hydroxide and hydrogen peroxide was measured using the experimental set-up described above. A set of experiments was carried out using as absorption medium consisting of water (30 mL), sodium hydroxide (10 grams; 0.25 mol) and various quantities of hydrogen peroxide. The tested hydrogen peroxide concentrations were 9.25 M, 6.25 M and 5 M. Each experiment was allowed to continue for five minutes, during which the CO₂ absorption was measured periodically.

The results are depicted in Figure 10. The CO₂ absorption value at a hydrogen peroxide concentration of 9.25 M, corresponding to a H₂O₂:OH molar ratio of 1.5:1, reaches 100%. A lower hydrogen peroxide concentration results in reduced CO₂ absorbing capacity.

Example 6Regeneration of sodium hydroxide

The absorption of CO₂ by an aqueous solution of sodium hydroxide and hydrogen peroxide was measured using the experimental set-up described above. The gas trap was loaded with 1.6 mol water (30 mL), 0.25 mol sodium hydroxide (10 grams) and 0.37 mol hydrogen peroxide (11.3 mL 30% H₂O₂ aqueous solution). The experiment was allowed to continue for five minutes, during which the CO₂ absorption was measured periodically .

Four consecutive cycles of CO_2 absorption were carried out, wherein following each cycle, calcium hydroxide (0.25 mol, 10 grams) was added to the gas trap and the reaction mixture was stirred for 3 minutes in order to regenerate sodium hydroxide, following which an additional 0.37 mol of hydrogen peroxide (11.3 mL 30% H_2O_2 aqueous solution) was added to the gas trap.

Figure 11 depicts the absorption of CO_2 (percent relative to the initial CO_2 concentration) as a function of time (seconds) for each of the four absorption cycles, demonstrating that the sodium hydroxide regeneration is fairly effective.

Example 7

Carbon tetrachloride mineralization by an aqueous solution of hydrogen peroxide and sodium hydroxide in the presence of phase transfer catalyst

The experiments described below were conducted in an adiabatic glass reactor (100 ml) equipped with a reflux condenser and magnetic stirrer at ambient conditions.

A mixture of 4ml CCl_4 (50mmol), 8gr sodium hydroxide (200mmol), 1.1gr Aliquat 336 (2.5mmol), 9.3ml 30% hydrogen peroxide (300mmol) and 30ml distilled water were fed into the reactor in one batch. Stirring was continued for 10 minutes at room temperature. The progress of the reaction was monitored by volumetric analysis of the released carbon dioxide, and measuring the reaction temperature. The released carbon dioxide was captured in an aqueous barium hydroxide scrubber, in order to allow the precipitation of barium carbonate. The precipitated barium carbonate was filtered, dried and weighed to confirm the overall mass balance. After the reaction was completed, the aqueous and organic phases were separated and washed by 10 ml of dichloromethane. The

organic phases were combined. The organic solution was tested for the presence of CCl_4 by means of GC with FID detector; no traces of CCl_4 were detected. The aqueous phase was dried at evaporator and the final reaction solid products were determined by means of X-ray diffraction (XRD) analysis, which indicated that the reaction products of CCl_4 mineralization consist of sodium chloride and sodium carbonate.

For the purpose of comparison, CCl_4 mineralization was investigated using three comparative reagents:

(i) sodium hydroxide alone [an alkaline solution consisting of 0.25 mol (10 grams) sodium hydroxide dissolved in 30 ml of water]; the conditions of the experiment were as set out above .

(ii) hydrogen peroxide alone [9.3ml of 30% hydrogen peroxide (300mmol) in 30ml distilled water]; the conditions of the experiment were as set out above.

(iii) solid potassium superoxide (KO_2). The experiment was conducted in an adiabatic glass reactor (100 ml) equipped with a reflux condenser and a magnetic stirrer at ambient conditions. A mixture of 4ml CCl_4 (50mmol) and 10gr potassium superoxide (100mmol) was fed into the reactor in one batch. Stirring was continued for 1 hour. The liquid and organic phases were then separated and washed by 10 ml of dichloromethane . The organic solution was tested for the presence of CCl_4 by means of GC with FID detector.

The results of the experiment according to the invention and the three comparative experiments are presented graphically in Figure 13 which shows the CCl_4 destruction as function of the mineralization agent. As shown, the mineralization of CCl_4 by means of an aqueous solution of sodium hydroxide and hydrogen peroxide ("The Reagent") reached approximately 100% following

a reaction which lasted only ten minutes, in comparison to only negligible efficacy demonstrated by the NaOH, H₂O₂ and K₂O₂ reagents .

Example 8

Methyl iodide mineralization by an aqueous solution of hydrogen peroxide and sodium hydroxide in the presence of phase transfer catalyst

The experiments were conducted in an adiabatic glass reactor (100 ml) equipped with a reflux condenser and magnetic stirrer at ambient conditions.

A mixture of methyl iodide (4 ml, 50mmol), sodium hydroxide (8gr, 200mmol), Aliquat 336 (1.1gr, 2.5mmol), 30% hydrogen peroxide (9.3ml, 300mmol) and 30ml distilled water were fed into reactor in one batch. Stirring was continued for 10 minutes at room temperature. The progress of the reaction was monitored by volumetric analysis of the released carbon dioxide, and measuring the reaction temperature. The released carbon dioxide was captured in an aqueous barium hydroxide scrubber, in order to allow the precipitation of barium carbonate. The precipitated barium carbonate was filtered, dried and weighed to confirm the overall mass balance. After the reaction was completed the aqueous and organic phases were separated and washed by 10 ml of dichloromethane . The organic phases were combined. The organic solution was tested for the presence of CH₃I by means of GC with FID detector; no traces of CH₃I were detected. The aqueous phase was dried at evaporator and the final reaction solid products were determined by means of X-ray diffraction (XRD) analysis, which indicated that the reaction products of CH₃I mineralization consist of sodium iodide and sodium carbonate.

For the purpose of comparison, CH_3I mineralization was investigated using two comparative reagents:

(i) sodium hydroxide alone [an alkaline solution consisting of 0.25 mol (10 grams) sodium hydroxide dissolved in 30 ml of water]; the conditions of the experiment were as set out above.

(ii) hydrogen peroxide alone [9.3ml of 30% hydrogen peroxide (300mmol) in 30ml distilled water]; the conditions of the experiment were as set out above.

The results of the experiment according to the invention and the two comparative experiments are presented graphically in Figure 14 which shows the CH_3I destruction as function of the mineralization agent. As shown, the mineralization of methyl iodide by means of an aqueous solution of sodium hydroxide and hydrogen peroxide ("Our Reagent") reached approximately 100% following a reaction which lasted ten minutes, in comparison to only negligible efficacy demonstrated by the NaOH and H_2O_2 reagents.

Example 9

Carbon tetrachloride mineralization by an aqueous solution of hydrogen peroxide and sodium hydroxide in the presence of various phase transfer catalysts

In the following set of experiment, the effect of the phase transfer catalyst was investigated. The phase transfer catalysts tested were Aliquat 336, CTAB, DDAB, and TOAB. The experiments were conducted in an adiabatic glass reactor (100 ml) equipped with a reflux condenser and magnetic stirrer at ambient conditions.

A mixture of CCl_4 (4ml, 50mmol), sodium hydroxide (8gr, 200mmol), PTC (1.1gr, 2.5mmol), 30% hydrogen peroxide (9.3ml, 300mmol) and 30ml distilled water were fed into reactor in one batch. Stirring was continued for 10 minutes at room temperature. The reaction mixture was treated as set out in previous examples.

For the purpose of comparison, CCl_4 mineralization was measured under the same conditions but without any PTC. The results are graphically depicted in Figure 15. As shown, the mineralization of CCl_4 can be accomplished to a satisfactory extent in the presence of different types of PTC's, with Aliqout 336 demonstrating the best activity.

Example 10-14

Mineralization of halogenated compounds by an aqueous solution of hydrogen peroxide and sodium hydroxide

In the following set of experiments, various halogenated pollutants were treated by means of the method of the invention according to the procedure described in Example 8. The details of the experiments and the results are tabulated in Table 1.

Table 1

Ex.	Halogenated compounds	Reaction Products	Reaction Conversion (%)	Reaction Time (min)	Reaction conditions: ratio of NaOH:H ₂ O ₂
10	CCl_3Br	Na_2CO_3 , NaCl , NaBr , O_2	100	5	1:1.5
11	CHCl_2Br	Na_2CO_3 , NaCl , HBr , O_2	100	5	1:1.5
12	CHI_3	Na_2CO_3 , NaI , HI , O_2	100	5	1:1.5
13	CHBr_3	Na_2CO_3 , NaBr , HBr , O_2	100	5	1:1.5
14	CH_3Cl	Na_2CO_3 , NaCl , O_2	100	5	1:1.5

Example 15-23Mineralization of halogenated organic compounds in soil by an aqueous solution of hydrogen peroxide and sodium hydroxide

The experiments described below were conducted in an adiabatic glass reactor (500 ml) which contained 60gr of soil. The tested halogenated organic compound (0.05-0.3 mol) was sponged in the soil. Two different syringes (50 ml) were prepared, one containing 16.6M sodium hydroxide solution and the other 22 ml of 30% hydrogen peroxide solution (710mmol H₂O₂). The solutions were injected simultaneously into the soil and the treatment was allowed to continue over a period of tern minutes. After the reaction was completed, the treated soil was washed with 100 ml of dichloromethane on a Buchner funnel. The solid and liquid fractions were separated. The liquid (aqueous and organic) phases were separated in a separation funnel and the organic phases were combined. The organic solution was tested for the presence halogenated organic compounds by means of GC with FID detector. The conditions of the experiments and the results are tabulated in Table 2.

Table 2

Ex.	Halogenated compound	Reaction Products	Reaction Conversion (%)	Reaction Time (min)	Reaction conditions: ratio of NaOH:H ₂ O ₂
15	CCl ₄	Na ₂ CO ₃ , NaCl, Cl ₂ , O ₂	100	10	1:1.5
16	CCl ₃ Br	Na ₂ CO ₃ , NaCl, NaBr, O ₂	100	10	1:1.5
17	CHCl ₂ Br	Na ₂ CO ₃ , NaCl, NaBr, O ₂	100	10	1:1.5
18	C ₂ H ₃ Cl ₃	Na ₂ CO ₃ , NaCl, O ₂	100	10	1:1.5
19	C ₂ H ₃ Cl ₂ Br	Na ₂ CO ₃ , NaCl, NaBr, O ₂	100	10	1:1.5
20	C ₂ H ₃ ClBr ₂	Na ₂ CO ₃ , NaCl, NaBr, O ₂	100	10	1:1.5
21	C ₂ H ₂ Cl ₂	Na ₂ CO ₃ , NaCl, O ₂	100	10	1:1.5
22	C ₂ HCl ₃	Na ₂ CO ₃ , NaCl, O ₂	100	10	1:1.5
23	C ₂ Cl ₄	Na ₂ CO ₃ , NaCl, O ₂	100	10	1:1.5

Example 24

Chlorobenzene destruction by an aqueous solution of hydrogen peroxide and sodium hydroxide in the presence of phase transfer catalyst

Into a glass vessel (50 ml) equipped with a reflux condenser and magnetic stirrer were added chlorobenzene (7.35g ml, 50mmol), Aliquat 336 (0.4gr, 1mmol), 30% hydrogen peroxide (6.9ml, 225mmol), sodium hydroxide (6gr, 150mmol) and 34ml distilled water. Stirring was continued for 10 minutes at room temperature.

The graph shown in Figure 16 demonstrates the progress of the reaction, where the abscissa indicates the time of the reaction and the ordinate the degree of chlorobenzene conversion. The Conversion is given by $(1-C_A/C_{A0})$, in which C_A is the reactant (chlorobenzene) concentration and C_{A0} : initial reactant (chlorobenzene) concentration. As shown by the graph, following ten minutes reaction at ambient conditions, chlorobenzene was converted completely (apparently into a more oxidized state).

Claims

- 1) A process for treating a medium by the removal or destruction of one or more undesired substances present in said medium, comprising combining hydrogen peroxide and alkali hydroxide in an aqueous solution to form superoxide, and bringing the resultant superoxide-containing solution into contact with said medium.
- 2) A process according to claim 1, wherein the hydrogen peroxide and the hydroxide source are combined at a molar ratio of not less than 1.2:1 ($H_2O_2:OH^-$).
- 3) A process according to claim 1, wherein the molar ratio is not less than 1.4:1 ($H_2O_2:OH^-$).
- 4) A process according to claim 2 or 3, wherein the hydroxide is added to the aqueous solution at a concentration of not less than 1.5 M.
- 5) A process according to any one of claims 1 to 4, wherein the medium to be treated in a gaseous mixture from which carbon dioxide is removed.
- 6) A process according to claim 5, wherein the carbon dioxide is absorbed by the superoxide-containing aqueous solution in a gas-liquid contactor, whereby said carbon dioxide is converted into an alkali carbonate salt, which is subsequently treated with calcium hydroxide to regenerate the corresponding alkali hydroxide and concurrently form calcium carbonate.

7) The process of claim 6, wherein the calcium carbonate is treated to form calcium hydroxide, which is recycled for regenerating the alkali hydroxide.

8) A process according to any one of claims 1 to 4, wherein the medium to be treated consists solely of one or more halogenated organic pollutant(s) to be destroyed, wherein said medium is brought into contact with the superoxide-containing solution in the presence of a phase transfer catalyst.

9) A process according to any one of claims 1 to 4, wherein the medium to be treated is halogenated organic pollutant-contaminated liquid, which is brought into contact with the superoxide-containing solution in the presence of a phase transfer catalyst.

10) A process according to any one of claims 8 or 9, wherein the halogenated organic pollutant is halogenated aliphatic hydrocarbon.

11) A process according to claim 10, wherein the pollutant is selected from the group consisting of halogenated methane, halogenated ethane and halogenated ethylene compounds.

12) A process according to one of claims 8 to 11, wherein the phase transfer catalyst is composed of a nitrogen-containing cation and an anion which is displaceable by a superoxide anion.

13) A process according to claim 12, wherein the phase transfer catalyst is quaternary ammonium salt of the formula $N^+R_1R_2R_3R_4Hal^-$, wherein each of R_1 , R_2 , R_3 and R_4 is independently C1-C18 alkyl group and Hal^- indicates halide anion.

14) A process according to claim 13, wherein the quaternary ammonium salt is selected from the group consisting of:

$N^+CH_3[(CH_2)_kCH_3]_3Hal^-$,

$N^+(CH_3)_2[(CH_2)_kCH_3]_2Hal^-$,

$N^+(CH_3)_3[(CH_2)_kCH_3]Hal^-$, or

$N^+[(CH_2)_kCH_3]_4Hal^-$,

wherein k is at least 5.



15) A process according to claim 14, wherein the quaternary ammonium salt has the formula $N^+CH_3[(CH_2)_kCH_3]_3Hal^-$, in which k is between 5 and 9.

16) A process according to any one of claim 1 to 4, wherein the medium to be treated is halogenated organic pollutant-contaminated soil.



17) A process according to claim 16, wherein the halogenated pollutant contaminating the soil is chlorinated methane.

18) A process according to claim 17, which is a site remediation process, comprising injecting into halogenated organic pollutant-contaminated soil a first stream of hydrogen peroxide solution and a second stream of aqueous alkali hydroxide, or a combined stream of both, such that the molar ratio between the hydrogen peroxide and the hydroxide ion in the range of 1.2:1 to 2:1.



1/8

Figure 1Figure 2



2/8

Figure 3**Figure 4**



3/8

Figure 5**Figure 6**



4/8

Figure 7**Figure 8**

5/8

Figure 9**Figure 10**


6/8

Figure 11FIGURE 12


7/8

Figure 13



Effectiveness of CTC Destruction as Function of Mimeralization Agent

Figure 14

Effectiveness of CH₃I Destruction as Function of Mineralization Agent



8/8

Figure 15Figure 16

INTERNATIONAL SEARCH REPORT

International application No
PCT/I L2012/00Q394

A. CLASSIFICATION OF SUBJECT MATTER
INV. B09C1/Q8 B01D53/62 C01B15/043
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B09C B01D C01B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal , WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 10 2008 058114 AI (BIOMETHAN N E W GMBH [DE]] 27 May 2010 (2010-05-27)	1-5
Y	paragraphs [0027] , [0056] - [0066] ; claims 25, 26; figure 1	6,7
X	US 6 365 099 B1 (CASTRANTAS HARRY M [US] ET AL) 2 April 2002 (2002-04-02) column 4, line 41 - column 5, line 60; figures 2, 3; examples 1, 2	1-5
Y	US 7 964 170 B2 (SINGH UDAY [US]) 21 June 2011 (2011-06-21) column 14, lines 14-49; figure 6	6
Y	US 2011/226006 AI (LACKNER KLAUS S [US] ET AL) 22 September 2011 (2011-09-22) paragraph [0052] ; figure 1	6,7
		-/-

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

7 March 2013

08/05/2013

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Focante, Francesca

INTERNATIONAL SEARCH REPORT

International application No
PCT/I L2012/00Q394

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	us 2007/269358 A1 (KAMPER FRI EDHELM [DE] ET AL) 22 November 2007 (2007-11-22) cited in the application paragraphs [0015] , [0016] ; claims 1-4; figure 1 -----	1-7
T	us 3 816 604 A (MALAFOSSE J) 11 June 1974 (1974-06-11) column 1, line 16 - column 2, line 13 -----	
T	N. F. GLADYSHEV ET AL: "Choice of a Stabilizer for the Reaction of KOH with Hydrogen Peroxide To Produce Potassium Superoxide" , RUSSIAN JOURNAL OF APPLIED CHEMISTRY, vol. 76, no. 11, 1 November 2003 (2003-11-01) , pages 1858-1859 , XP055055575, column 1, lines 11-19 -----	

INTERNATIONAL SEARCH REPORT

International application No.
PCT/I L2012/00Q394

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:

2. Claims Nos.: because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.

2. As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.

3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

5-7(completely) ; 1-4(partial) ly

Remark on Protest

The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.

The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.

No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 5-7(completely) ; 1-4(partially)

Process for removing carbon dioxide from a gas mixture by treating the gas mixture with a superoxide-containing solution obtained by combining hydrogen peroxide and alkaline hydroxide in an aqueous solution.

2. claims: 8-18 (completely) ; 1-4(partially)

Process for treating a medium containing halogenated organic pollutants with a superoxide-containing solution obtained by combining hydrogen peroxide and alkaline hydroxide in an aqueous solution.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/I L2012/00Q394

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
DE 102008058114 AI	27-05-2010	NONE			
US 6365099 BI	02-04-2002	NONE			
US 7964170 B2	21-06-2011	NONE			
US 2011226006 A1	22-09-2011	US 2008031801 AI	07-02-2008		
		US 2011226006 AI	22-09-2011		
		US 2012302469 AI	29-11-2012		
		Wo 2005108297 A2	17-11-2005		
US 2007269358 A1	22-11-2007	CN 101448560 A	03-06-2009		
		DE 102006023939 AI	22-11-2007		
		EP 2024Q58 AI	18-02-2009		
		JP 2009537294 A	29-10-2009		
		KR 2009Q019789 A	25-02-2009		
		RU 2008150040 A	27-06-2010		
		TW 200815092 A	01-04-2008		
		US 2007269358 AI	22-11-2007		
		Wo 2007134717 AI	29-11-2007		
US 3816604 A	11-06-1974	BE 796888 A1	17-09-1973		
		DE 2313116 A1	20-09-1973		
		ES 412741 A1	16-06-1976		
		ES 439311 A1	16-02-1977		
		FR 2175652 A1	26-10-1973		
		GB 1405063 A	03-09-1975		
		GB 1405064 A	03-09-1975		
		IT 981295 B	10-10-1974		
		JP S495898 A	19-01-1974		
		JP S5617284 B2	21-04-1981		
		NL 7303659 A	19-09-1973		
		US 3816604 A	11-06-1974		