

(12) **United States Patent**
Latta et al.

(10) **Patent No.:** **US 11,508,125 B1**
(45) **Date of Patent:** **Nov. 22, 2022**

(54) **NAVIGATING A VIRTUAL ENVIRONMENT OF A MEDIA CONTENT ITEM**

(71) Applicant: **Lucasfilm Entertainment Company Ltd.**, San Francisco, CA (US)
(72) Inventors: **Lutz Markus Latta**, Mill Valley, CA (US); **Ian Wakelin**, Berkeley, CA (US); **Darby Johnston**, Berkeley, CA (US); **Andrew Grant**, San Francisco, CA (US); **John Gaeta**, Ross, CA (US)

(73) Assignee: **LUCASFILM ENTERTAINMENT COMPANY LTD.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 47 days.

(21) Appl. No.: **16/817,477**

(22) Filed: **Mar. 12, 2020**

Related U.S. Application Data

(63) Continuation of application No. 14/724,584, filed on May 28, 2015, now Pat. No. 10,600,245.

(60) Provisional application No. 62/004,121, filed on May 28, 2014.

(51) **Int. Cl.**
G06T 19/00 (2011.01)
H04L 67/10 (2022.01)
G06F 3/0346 (2013.01)

(52) **U.S. Cl.**
CPC **G06T 19/003** (2013.01); **G06F 3/0346** (2013.01); **G06T 19/006** (2013.01); **H04L 67/10** (2013.01)

(58) **Field of Classification Search**
CPC G06T 19/003; G06T 19/006; G06T 19/00; G06T 7/00; G06F 3/0346; H04L 67/10
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,729,471 A *	3/1998	Jain	H04N 5/2627 348/E13.058
5,729,669 A	3/1998	Appleton	
5,838,906 A	11/1998	Doyle et al.	
5,841,439 A	11/1998	Pose et al.	
5,977,978 A *	11/1999	Carey	G06T 19/00 345/419
6,040,841 A *	3/2000	Cohen	G06T 15/00 345/473

(Continued)

OTHER PUBLICATIONS

Michael Nitsche, "Cinema and Game Spaces," in Video Game Spaces: Image, Play, and Structure in 3D Worlds, MIT Press, 2008, pp. 79-127. (Year: 2008).*

(Continued)


Primary Examiner — Charles L Beard

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57) **ABSTRACT**

Systems and techniques are provided for switching between different modes of a media content item. A media content item may include a movie that has different modes, such as a cinematic mode and an interactive mode. For example, a movie may be presented in a cinematic mode that does not allow certain user interactions with the movie. The movie may be switched to an interactive mode during any point of the movie, allowing a viewer to interact with various aspects of the movie. The movie may be displayed using different formats and resolutions depending on which mode the movie is being presented.

15 Claims, 16 Drawing Sheets



(56)		References Cited						
U.S. PATENT DOCUMENTS				2011/0117922	A1	5/2011	Reitsma et al.	
				2011/0128300	A1*	6/2011	Gay	A63F 13/525 345/633
				2011/0164116	A1*	7/2011	Gay	H04N 13/156 348/E.042
2005/0202868	A1*	9/2005	Sawano	2011/0210962	A1	9/2011	Horan et al.	
				2011/0222757	A1	9/2011	Yeatman, Jr. et al.	
2006/0094503	A1*	5/2006	Ajioka	2011/0225069	A1	9/2011	Cramer et al.	
				2011/0250967	A1	10/2011	Kulas et al.	
2006/0258449	A1*	11/2006	Yasui	2011/0285703	A1	11/2011	Jin et al.	
				2011/0285704	A1	11/2011	Takeda et al.	
2007/0052712	A1	3/2007	Saito et al.	2011/0307919	A1	12/2011	Weerasinghe	
2007/0076585	A1	4/2007	Kim et al.	2011/0320116	A1	12/2011	DeMaio et al.	
2007/0185777	A1	8/2007	Pyle et al.	2012/0001944	A1*	1/2012	Sakurai	G06F 3/04815 345/671
2007/0188501	A1*	8/2007	Yee	2012/0004017	A1*	1/2012	Sakurai	A63F 13/5258 463/2
				2012/0007882	A1*	1/2012	Sakurai	G06F 3/04883 345/619
2007/0236514	A1*	10/2007	Agusanto	2012/0021828	A1	1/2012	Raitt et al.	
				2012/0028706	A1	2/2012	Raitt et al.	
2007/0276590	A1	11/2007	Leonard et al.	2012/0030322	A1	2/2012	Kataoka et al.	
2008/0070684	A1	3/2008	Haigh-hutchinson	2012/0050256	A1*	3/2012	Thiel	H04N 13/156 345/419
2008/0082311	A1	4/2008	Meijer et al.	2012/0054811	A1	3/2012	Spears	
2008/0094358	A1*	4/2008	Sullivan	2012/0075285	A1	3/2012	Oyagi et al.	
				2012/0086631	A1*	4/2012	Osman	A63F 13/525 345/156
2008/0125202	A1*	5/2008	Kamiyama	2012/0087580	A1	4/2012	Woo et al.	
				2012/0105473	A1	5/2012	Bar-Zeev et al.	
2008/0137729	A1	6/2008	Jung	2012/0113261	A1	5/2012	Satoh	
2008/0170133	A1	7/2008	Sun et al.	2012/0122491	A1	5/2012	Kim et al.	
2008/0170749	A1	7/2008	Albertson et al.	2012/0133638	A1*	5/2012	Davison	G06T 19/00 345/419
2008/0172384	A1*	7/2008	Cai	2012/0162228	A1	6/2012	Yamane et al.	
2008/0207323	A1	8/2008	Hiroshige et al.	2012/0176369	A1*	7/2012	Suzuki	H04N 13/302 345/419
2008/0300053	A1*	12/2008	Muller	2012/0188452	A1*	7/2012	Keiser	H04N 5/2224 348/559
				2012/0190442	A1	7/2012	Ito et al.	
2008/0300996	A1	12/2008	Fei et al.	2012/0192115	A1	7/2012	Falchuk et al.	
2009/0058856	A1	3/2009	Kuroda et al.	2012/0200667	A1*	8/2012	Gay	G06T 19/006 348/43
2009/0112457	A1	4/2009	Sanchez et al.	2012/0206560	A1*	8/2012	Setton	H04N 7/147 348/E7.083
2009/0115783	A1	5/2009	Eichenlaub	2012/0210255	A1	8/2012	Ooi et al.	
2009/0119731	A1	5/2009	Perlman et al.	2012/0218259	A1	8/2012	Takahashi et al.	
2009/0187389	A1*	7/2009	Dobbins	2012/0218263	A1*	8/2012	Meier	G06T 19/006 345/419
				2012/0249831	A1*	10/2012	Porter	H04N 5/272 348/222.1
2009/0195650	A1	8/2009	Hanai et al.	2012/0250980	A1*	10/2012	Gillard	H04N 5/272 382/173
2009/0219291	A1	9/2009	Lloyd et al.	2012/0262554	A1*	10/2012	Gotsman	H04N 5/76 348/47
2009/0251460	A1	10/2009	Dunnigan et al.	2012/0268322	A1	10/2012	Takahashi et al.	
2009/0253506	A1	10/2009	Ishii et al.	2012/0278395	A1	11/2012	Garcia et al.	
2009/0253507	A1	10/2009	Ishii et al.	2012/0299920	A1	11/2012	Coombe et al.	
2009/0256837	A1	10/2009	Deb et al.	2012/0307011	A1*	12/2012	Shikata	A63F 13/5258 348/46
2009/0262109	A1	10/2009	Markowitz et al.	2012/0308078	A1	12/2012	Fujibayashi et al.	
2009/0287763	A1	11/2009	Svensden et al.	2012/0309477	A1	12/2012	Mayles et al.	
2009/0309874	A1	12/2009	Salganicoff et al.	2012/0309522	A1*	12/2012	Westlund	H04N 13/122 463/31
2009/0315978	A1*	12/2009	Wurmlin	2012/0309543	A1	12/2012	Shimada	
				2012/0313946	A1	12/2012	Nakamura et al.	
2010/0007665	A1	1/2010	Smith et al.	2012/0316775	A1	12/2012	Hayashi et al.	
2010/0026801	A1*	2/2010	Williams	2012/0320066	A1	12/2012	James et al.	
				2012/0320080	A1	12/2012	Giese et al.	
2010/0041478	A1*	2/2010	Ajioka	2012/0327088	A1	12/2012	Schnitzer et al.	
				2013/0009994	A1	1/2013	Hill et al.	
2010/0045666	A1	2/2010	Kornmann et al.	2013/0073388	A1	3/2013	Heath et al.	
2010/0050221	A1*	2/2010	McCutchen	2013/0117377	A1	5/2013	Miller	
				2013/0132835	A1	5/2013	Goldenberg et al.	
2010/0056183	A1	3/2010	Oh et al.	2013/0135315	A1*	5/2013	Bares	G11B 27/031 345/473
2010/0060575	A1*	3/2010	Ohta					
2010/0085351	A1	4/2010	Deb et al.					
2010/0103075	A1	4/2010	Kalaboukis et al.					
2010/0111417	A1*	5/2010	Ward					
2010/0130236	A1	5/2010	Sivadas et al.					
2010/0156906	A1	6/2010	Montgomery et al.					
2010/0208942	A1*	8/2010	Porter					
2010/0215250	A1	8/2010	Zhu et al.					
2010/0253676	A1	10/2010	Mumbauer et al.					
2010/0257252	A1	10/2010	Dougherty et al.					
2010/0259595	A1	10/2010	Trimeche et al.					
2010/0321377	A1*	12/2010	Gay					
2011/0018868	A1	1/2011	Inoue et al.					
2011/0063138	A1	3/2011	Berkobin et al.					
2011/0076984	A1	3/2011	Flippo et al.					

(56)		References Cited					
U.S. PATENT DOCUMENTS				2015/0062125	A1	3/2015	Aguilera Perez et al.
				2015/0078621	A1	3/2015	Choi et al.
				2015/0082364	A1*	3/2015	Jayaram G11B 27/031 725/109
2013/0135316	A1*	5/2013	Choy G06F 3/04883 345/474	2015/0098615	A1	4/2015	Maggio et al.
2013/0141427	A1	6/2013	Lucas et al.	2015/0106733	A1	4/2015	Matsui
2013/0159939	A1*	6/2013	Krishnamurthi G06F 3/0304 715/863	2015/0109335	A1*	4/2015	Hayakawa G06K 9/6217 345/633
2013/0201188	A1*	8/2013	Choi G06T 19/006 345/419	2015/0138079	A1	5/2015	Lannsjoe
2013/0202265	A1*	8/2013	Arrasvuori H04N 21/23418 386/E5.069	2015/0142875	A1*	5/2015	Gillard H04N 21/47205 709/203
2013/0222385	A1	8/2013	Dorsey et al.	2015/0143421	A1*	5/2015	Williams H04L 67/10 725/38
2013/0249906	A1	9/2013	Gunderson et al.	2015/0145889	A1	5/2015	Hanai
2013/0262565	A1	10/2013	Nakamura et al.	2015/0154753	A1	6/2015	Blanke et al.
2013/0293586	A1	11/2013	Kaino et al.	2015/0156522	A1	6/2015	Shaw et al.
2013/0321395	A1	12/2013	Chen et al.	2015/0163473	A1	6/2015	Yamagishi et al.
2013/0321411	A1	12/2013	Pahwa et al.	2015/0172634	A1*	6/2015	Wheeler H04N 21/21805 348/47
2013/0321472	A1	12/2013	Piemonte et al.	2015/0182855	A1*	7/2015	Tolk A63F 13/428 463/31
2013/0321575	A1*	12/2013	Kirk H04N 13/243 348/E13.064	2015/0187139	A1	7/2015	Ahn
2013/0322634	A1	12/2013	Bennett et al.	2015/0213642	A1	7/2015	Kawai et al.
2013/0325343	A1	12/2013	Blumenberg et al.	2015/0234462	A1	8/2015	Miller et al.
2013/0326407	A1	12/2013	Van Os et al.	2015/0235432	A1	8/2015	Bertolami et al.
2013/0326425	A1	12/2013	Forstall et al.	2015/0254042	A1	9/2015	Seitz
2013/0345980	A1	12/2013	Van Os et al.	2015/0254871	A1*	9/2015	MacMillan H04L 65/612 382/180
2014/0002439	A1	1/2014	Lynch et al.	2015/0262380	A1	9/2015	Schmalstieg et al.
2014/0002457	A1	1/2014	Swindell et al.	2015/0262423	A1*	9/2015	Heinz, II H04N 21/23412 386/241
2014/0019917	A1	1/2014	Piemonte et al.	2015/0279081	A1	10/2015	Monk et al.
2014/0022244	A1	1/2014	Hayashi	2015/0281699	A1	10/2015	Yamasaki et al.
2014/0045482	A1	2/2014	Bisson et al.	2015/0294492	A1	10/2015	Koch et al.
2014/0057717	A1	2/2014	Yoshikawa et al.	2015/0304531	A1*	10/2015	Rodriguez Garcia H04N 5/2224 345/419
2014/0063054	A1	3/2014	Osterhout et al.	2015/0306500	A1*	10/2015	Edsall A63F 13/5255 463/31
2014/0071130	A1	3/2014	Piemonte et al.	2015/0317765	A1	11/2015	Haw
2014/0095122	A1	4/2014	Appleman et al.	2015/0345976	A1	12/2015	Moore et al.
2014/0146046	A1	5/2014	Coombe et al.	2015/0348326	A1*	12/2015	Sanders H04N 5/275 345/633
2014/0160129	A1	6/2014	Sako et al.	2015/0348327	A1	12/2015	Zalewski
2014/0176607	A1	6/2014	Yang et al.	2015/0349972	A1	12/2015	Akasam et al.
2014/0186002	A1*	7/2014	Hanaya G06F 3/011 386/200	2015/0350628	A1	12/2015	Sanders et al.
2014/0192164	A1	7/2014	Tenn et al.	2015/0355711	A1	12/2015	Rihn
2014/0198052	A1	7/2014	Tokutake	2015/0363967	A1	12/2015	Wells et al.
2014/0208365	A1	7/2014	Ellis et al.	2015/0379777	A1	12/2015	Sasaki
2014/0210697	A1	7/2014	Hussain et al.	2016/0025981	A1	1/2016	Sugden et al.
2014/0213361	A1	7/2014	Zhang et al.	2016/0035140	A1	2/2016	Bickerstaff et al.
2014/0243089	A1	8/2014	Tsukioka et al.	2016/0050367	A1*	2/2016	Shimauchi H04N 5/23238 348/36
2014/0244595	A1	8/2014	Cardonha et al.	2016/0054793	A1	2/2016	Kasahara et al.
2014/0258111	A1	9/2014	Yoshikawa et al.	2016/0086379	A1*	3/2016	Sadi G02B 27/0093 345/633
2014/0270706	A1*	9/2014	Pasko H04N 21/854 386/278	2016/0114243	A1	4/2016	Matsuura
2014/0277630	A1	9/2014	Meadows et al.	2016/0129346	A1	5/2016	Mikhailov et al.
2014/0278847	A1	9/2014	Gallo	2016/0132278	A1*	5/2016	Gillard H04N 21/4728 345/682
2014/0280502	A1	9/2014	Cronin et al.	2016/0133052	A1	5/2016	Kang et al.
2014/0283012	A1	9/2014	Eggerton et al.	2016/0134717	A1	5/2016	McNeill et al.
2014/0297575	A1	10/2014	Rapoport et al.	2016/0139786	A1*	5/2016	Kaldma G11B 27/34 715/716
2014/0300775	A1	10/2014	Fan et al.	2016/0140397	A1*	5/2016	Zhang A61B 5/1128 382/103
2014/0301711	A1	10/2014	Suneya et al.	2016/0140733	A1*	5/2016	Gu H04N 13/167 348/43
2014/0302930	A1	10/2014	Iwasaki et al.	2016/0140748	A1	5/2016	Cline et al.
2014/0306995	A1	10/2014	Raheman et al.	2016/0180602	A1	6/2016	Fuchs
2014/0340535	A1	11/2014	Nakamura et al.	2016/0187969	A1*	6/2016	Larsen A63F 13/26 345/156
2014/0354687	A1*	12/2014	Kiuchi A63F 13/525 345/633	2016/0192009	A1*	6/2016	Sugio H04N 21/252 725/32
2014/0357358	A1*	12/2014	Shikata A63F 13/00 463/31	2016/0205341	A1	7/2016	Hollander et al.
2014/0361988	A1	12/2014	Katz et al.	2016/0205379	A1	7/2016	Kurihara
2014/0368426	A1	12/2014	Suzuki et al.	2016/0210834	A1	7/2016	Dayal
2014/0375687	A1*	12/2014	Tanaka G02B 27/0172 345/633				
2014/0378222	A1*	12/2014	Balakrishnan A63F 13/70 463/31				
2015/0004926	A1	1/2015	Alhazme et al.				
2015/0016500	A1	1/2015	Seregin et al.				
2015/0019125	A1	1/2015	Mazanec				
2015/0035822	A1	2/2015	Arsan et al.				
2015/0040073	A1	2/2015	Barcan et al.				
2015/0054823	A1	2/2015	Bezyaeva et al.				
2015/0058709	A1	2/2015	Zaletel				

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0216518	A1	7/2016	Raghoebardajal et al.	2018/0061084	A1*	3/2018	Mitchell	G06F 3/147
2016/0227262	A1*	8/2016	Grant H04N 21/23439	2018/0061108	A1	3/2018	Abramovici et al.	
2016/0239181	A1	8/2016	You et al.	2018/0081178	A1	3/2018	Shpunt	
2016/0239252	A1	8/2016	Nakagawa et al.	2018/0098059	A1	4/2018	Valdivia et al.	
2016/0250554	A1*	9/2016	Haigh-Hutchinson A63F 13/04 463/32	2018/0101960	A1*	4/2018	Boonyasiriwat G06T 7/11	
2016/0253067	A1	9/2016	Webb et al.	2018/0117465	A1	5/2018	Voris et al.	
2016/0258756	A1	9/2016	Ukezono et al.	2018/0143756	A1	5/2018	Mildrew et al.	
2016/0259403	A1	9/2016	Wang et al.	2018/0152660	A1*	5/2018	Tanaka H04N 5/247	
2016/0267942	A1	9/2016	Fisher	2018/0160049	A1*	6/2018	Aizawa H04N 5/2224	
2016/0275717	A1*	9/2016	Mizoguchi A63F 13/577	2018/0174331	A1	6/2018	Pham	
2016/0282619	A1	9/2016	Oto et al.	2018/0174365	A1	6/2018	Cancel Olmo et al.	
2016/0283081	A1*	9/2016	Johnston H04N 5/23216	2018/0176502	A1	6/2018	Bhuruth et al.	
2016/0284136	A1*	9/2016	Johnston H04N 5/23216	2018/0182114	A1*	6/2018	Hanamoto H04N 5/2224	
2016/0291922	A1	10/2016	Montgomerie et al.	2018/0196506	A1	7/2018	Nakashima et al.	
2016/0299661	A1	10/2016	Alpert et al.	2018/0197324	A1	7/2018	Hanamoto	
2016/0300263	A1	10/2016	Priness et al.	2018/0197334	A1*	7/2018	Kitazono A63F 13/40	
2016/0300392	A1	10/2016	Jonczyk et al.	2018/0204343	A1	7/2018	Galvane et al.	
2016/0320951	A1	11/2016	Ernst et al.	2018/0204381	A1*	7/2018	Kanatsu G06T 19/003	
2016/0330408	A1*	11/2016	Costanzo H04N 21/8547	2018/0205940	A1	7/2018	Donovan	
2016/0335796	A1	11/2016	Roimela	2018/0205963	A1*	7/2018	Matei H04N 21/85406	
2016/0337630	A1	11/2016	Raghoebardajal et al.	2018/0225840	A1	8/2018	Ikeda et al.	
2016/0345035	A1*	11/2016	Han H04N 21/21805	2018/0246565	A1	8/2018	Moon et al.	
2016/0357400	A1	12/2016	Penha et al.	2018/0253891	A1*	9/2018	Dohita G06T 15/503	
2016/0360097	A1	12/2016	Penha et al.	2018/0262713	A1*	9/2018	Huang G06T 15/20	
2016/0361649	A1*	12/2016	Hayashi A63F 13/5255	2018/0270412	A1	9/2018	Kanda et al.	
2016/0363767	A1	12/2016	Osborn et al.	2018/0276874	A1	9/2018	Myhill et al.	
2016/0364011	A1	12/2016	Bohn et al.	2018/0288394	A1*	10/2018	Aizawa H04N 5/247	
2016/0364881	A1	12/2016	Mallinson et al.	2018/0308275	A1*	10/2018	Fortmann G05D 1/0094	
2016/0366392	A1	12/2016	Raghoebardajal et al.	2018/0343442	A1*	11/2018	Yoshikawa H04N 13/117	
2016/0379408	A1	12/2016	Gouin et al.	2018/0376122	A1*	12/2018	Park H04N 13/128	
2016/0379682	A1*	12/2016	Williams H04N 5/2224 386/278	2019/0060745	A1*	2/2019	He A63F 13/847	
2016/0381290	A1*	12/2016	Prayle H04N 5/23203 348/207.11	2019/0073831	A1*	3/2019	Kim G03H 1/0005	
2016/0381341	A1*	12/2016	El Choubassi H04N 13/111 348/43	2019/0073832	A1*	3/2019	Kim G06T 19/20	
2017/0018002	A1	1/2017	Champy	2019/0075332	A1*	3/2019	Onuma H04N 21/854	
2017/0021875	A1	1/2017	Hur et al.	2019/0083885	A1*	3/2019	Yee A63F 13/40	
2017/0038941	A1	2/2017	Pylappan et al.	2019/0102949	A1	4/2019	Sheftel et al.	
2017/0041590	A1	2/2017	Silas et al.	2019/0133689	A1	5/2019	Johnson et al.	
2017/0041658	A1	2/2017	Mattingly et al.	2019/0163356	A1*	5/2019	Hanamoto H04N 5/247	
2017/0053217	A1	2/2017	Pardesi	2019/0191146	A1*	6/2019	Koyama H04N 5/222	
2017/0076497	A1*	3/2017	Inomata G06T 19/006	2019/0197779	A1*	6/2019	Avramov G06T 11/60	
2017/0076499	A1*	3/2017	Jiang G06T 7/00	2019/0199992	A1*	6/2019	Shikata H04N 13/243	
2017/0106285	A1*	4/2017	Odagiri A63F 13/30	2019/0199993	A1	6/2019	Babu J D et al.	
2017/0109933	A1	4/2017	Voorhees et al.	2019/0205650	A1*	7/2019	Iwao H04N 5/2357	
2017/0113138	A1*	4/2017	Makino G06T 19/003	2019/0222776	A1*	7/2019	Carter G06V 40/103	
2017/0118458	A1	4/2017	Gronholm et al.	2019/0228230	A1*	7/2019	Onuma H04N 21/21805	
2017/0128833	A1	5/2017	Tsukioka et al.	2019/0228565	A1*	7/2019	Yushiya H04N 21/2187	
2017/0144069	A1	5/2017	Bear et al.	2019/0238789	A1*	8/2019	Tanaka H04N 5/04	
2017/0157512	A1*	6/2017	Long A63F 13/497	2019/0269881	A1*	9/2019	Iida A61M 21/02	
2017/0169612	A1	6/2017	Cashen et al.	2019/0289275	A1*	9/2019	Arai H04N 5/247	
2017/0178687	A1	6/2017	Tamir et al.	2019/0299091	A1*	10/2019	Wu A63F 13/5255	
2017/0182421	A1	6/2017	Hormigo Cebolla et al.	2019/0313021	A1*	10/2019	Hannuksela H04N 21/816	
2017/0206712	A1	7/2017	Petrovskaya et al.	2019/0335154	A1*	10/2019	Tanaka G06T 7/194	
2017/0220225	A1	8/2017	Joly et al.	2019/0335166	A1*	10/2019	Copley G06T 15/08	
2017/0228923	A1	8/2017	Kashihara	2019/0342537	A1*	11/2019	Taya H04N 5/23219	
2017/0232343	A1*	8/2017	Yoshioka H04N 7/185 463/31	2019/0349531	A1*	11/2019	Aizawa G06T 7/73	
2017/0254661	A1	9/2017	Moore et al.	2019/0349560	A1*	11/2019	Yoshimura H04N 5/247	
2017/0257414	A1	9/2017	Zaletel	2020/0012421	A1*	1/2020	Kato G06F 3/0488	
2017/0263058	A1	9/2017	Muta	2020/0035019	A1*	1/2020	Cappello G06T 7/75	
2017/0278228	A1	9/2017	Chui et al.	2020/0035026	A1*	1/2020	Demirchian H04N 21/235	
2017/0278291	A1	9/2017	Young et al.	2020/0051337	A1*	2/2020	Reynolds H04N 13/128	
2017/0280133	A1	9/2017	Niemela et al.	2020/0053336	A1*	2/2020	Kawai H04N 13/111	
2017/0332019	A1	11/2017	Ishihara et al.	2020/0068188	A1*	2/2020	Maeda H04N 13/282	
2017/0357389	A1	12/2017	Fleizach et al.	2020/0073541	A1*	3/2020	Matsubayashi G06T 15/20	
2018/0003979	A1*	1/2018	Nakashima G02B 27/0172	2020/0082603	A1*	3/2020	Arai H04N 5/23216	
2018/0011201	A1	1/2018	Lau et al.	2020/0143592	A1*	5/2020	Cordes H04N 5/247	
2018/0018510	A1*	1/2018	Williams G06K 9/6215	2020/0145635	A1*	5/2020	Yoneda G06F 3/011	
2018/0053337	A1	2/2018	Nakashima et al.	2020/0197807	A1*	6/2020	Tieger G06T 19/00	
2018/0059780	A1*	3/2018	Mitchell A63F 13/21	2020/0234495	A1*	7/2020	Nakao G06T 19/00	
				2020/0236346	A1*	7/2020	Kato G06F 3/017	
				2020/0249765	A1*	8/2020	Johnston G06F 3/0482	
				2020/0265638	A1*	8/2020	Koperwas G02B 27/017	
				2020/0275083	A1*	8/2020	Yoneda H04N 21/4728	
				2020/0275084	A1*	8/2020	Aizawa H04N 5/232	
				2020/0288112	A1*	9/2020	Sheng H04N 13/268	
				2020/0289922	A1*	9/2020	McCoy A63F 13/428	
				2020/0289934	A1*	9/2020	Azmandian G06F 3/0346	
				2020/0298117	A1*	9/2020	Yonezu G06T 19/003	
				2020/0312029	A1*	10/2020	Heinen G06T 19/006	
				2020/0338453	A1*	10/2020	Lee G06F 3/0346	

(56)

References Cited

U.S. PATENT DOCUMENTS

2020/0353349 A1* 11/2020 Palmer A63F 13/22
 2020/0380769 A1* 12/2020 Liu G06F 3/017
 2020/0388073 A1* 12/2020 Mall H04N 5/247
 2020/0409455 A1* 12/2020 Wilson G02B 27/017
 2021/0005023 A1* 1/2021 Yoshimura H04N 13/296
 2021/0037213 A1* 2/2021 Oh H04N 7/181
 2021/0038975 A1* 2/2021 Grillet G06F 3/04815
 2021/0082192 A1* 3/2021 Guo G06T 17/20
 2021/0099734 A1* 4/2021 Kawanishi H04N 21/816
 2021/0105450 A1* 4/2021 Ito H04N 21/21805
 2021/0124475 A1* 4/2021 Inch G06F 3/017
 2021/0125382 A1* 4/2021 Solovykh G06T 11/00
 2021/0144358 A1* 5/2021 Kato H04N 5/2224
 2021/0176450 A1* 6/2021 Yano G06T 15/20
 2021/0205702 A1* 7/2021 Sanders A63F 13/525
 2021/0354036 A1* 11/2021 Swann A63F 13/86
 2021/0385554 A1* 12/2021 Takahashi H04N 21/4316
 2022/0092862 A1* 3/2022 Faulkner G06T 7/20

OTHER PUBLICATIONS

L. Cozic, S. B. Davis and H. Jones, "Intuitive interaction and expressive cinematography in video games," Proceedings Theory and Practice of Computer Graphics, 2004., 2004, pp. 135-142, doi: 10.1109/TPCG.2004.1314463. (Year: 2004).*

Antonov, Michael, "Asynchronous Timewarp Examined," <https://oculus.com/blog/asynchronous-timewarp/>, Mar. 3, 2015.

U.S. Appl. No. 14/483,865, "Final Office Action", dated Jun. 16, 2016, 10 pages.

U.S. Appl. No. 14/483,865, "Non-Final Office Action", dated Dec. 24, 2015, 10 pages.

U.S. Appl. No. 14/483,865, "Notice of Allowance", dated Mar. 16, 2017, 8 pages.

U.S. Appl. No. 14/571,017, "Non-Final Office Action", dated Apr. 22, 2016, 7 pages.

U.S. Appl. No. 14/571,017, "Notice of Allowance", dated Oct. 24, 2016, 6 pages.

U.S. Appl. No. 14/724,578, "Notice of Allowance", dated Jan. 29, 2016, 12 pages.

U.S. Appl. No. 14/724,584, "Advisory Action", dated Feb. 8, 2019, 8 pages.

U.S. Appl. No. 14/724,584, "Final Office Action", dated Nov. 2, 2017, 45 pages.

U.S. Appl. No. 14/724,584, "Final Office Action", dated Nov. 5, 2018, 54 pages.

U.S. Appl. No. 14/724,584, "Non Final Office Action", dated Mar. 24, 2017, 43 pages.

U.S. Appl. No. 14/724,584, "Non Final Office Action", dated May 4, 2018, 49 Pages.

U.S. Appl. No. 14/724,584, "Non-Final Office Action", dated May 13, 2019, 61 pages.

U.S. Appl. No. 14/724,584, "Notice of Allowance", dated Nov. 15, 2019, 41 pages.

U.S. Appl. No. 14/724,584, "Supplemental Notice of Allowability", dated Jan. 7, 2020, 2 pages.

U.S. Appl. No. 15/087,459, "Final Office Action", dated Jun. 26, 2019, 29 pages.

U.S. Appl. No. 15/087,459, "Final Office Action", dated Aug. 16, 2018, 30 pages.

U.S. Appl. No. 15/087,459, "Non-Final Office Action", dated Feb. 8, 2018, 31 pages.

U.S. Appl. No. 15/087,459, "Non-Final Office Action", dated Dec. 31, 2018, 32 pages.

U.S. Appl. No. 15/087,459, "Notice of Allowance", dated Nov. 6, 2019, 8 pages.

U.S. Appl. No. 15/087,459, "Supplemental Notice of Allowability", dated Jan. 30, 2020, 3 pages.

Ni et al., "LANDMARC: Indoor Location Sensing Using Active RFID", Wireless networks, 10(6), 2004, 701-710.

* cited by examiner





FIG. 1

200



202





FIG. 2

300



304




FIG. 3





FIG. 4



500





FIG. 5B

110



608

602

604

606

FIG. 6




FIG. 7




FIG. 9




FIG. 10







FIG. 11A

**FIG. 11B**



**FIG. 12B**




FIG. 13

NAVIGATING A VIRTUAL ENVIRONMENT OF A MEDIA CONTENT ITEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. application No. 14/724,584, filed May 28, 2015, entitled "Navigating A Virtual Environment Of A Media Content Item," which claims the benefit of U.S. Provisional Application No. 62/004,121, filed May 28, 2014, entitled "Providing Immersive and Interactive User Experiences," which are hereby incorporated by reference, in their entirety and for all purposes.

FIELD

The present disclosure generally relates to providing an interactive media content experience to one or more users. For example, techniques and systems may be provided for navigating a virtual environment of a media content item.

BACKGROUND

Media content presentation is an ever-evolving industry that provides viewers with many options to enjoy the media content. For example, an item of media content may include a movie or television programming. In some instances, media content may be presented using a virtual reality system that immerses a viewer in a scene of the media content. To provide high quality media content in such a manner, media files for the media content often include large amounts of data that necessitate intensive storage and processing requirements.

SUMMARY

Techniques and systems are described for presenting media content. In one embodiment, techniques and systems are described for switching between different modes of a media content item. In particular, a media content item may include a movie that has different modes, such as a cinematic mode and an interactive mode. For example, a movie may be presented in a cinematic mode that does not allow certain user interactions with the movie. The movie may be switched to an interactive mode during any point of the movie, allowing a viewer to interact with various aspects of the movie. The movie may be displayed using different formats and resolutions depending on which mode the movie is being presented.

A cinematic mode of a media content item may include the media content item progressing along a predefined timeline over which multiple, simultaneous story threads progress. While the media content is in the cinematic mode, a viewer may passively watch a primary story thread of the media content item from a cinematic perspective. However, interaction with the media content item by the viewer is not enabled while in the cinematic mode. A switch may then be made to the interactive mode, during which the viewer can interact with the media content item. In some examples, the viewer may navigate through a virtual environment of the media content item by moving a virtual camera through the virtual environment. For example, the viewer may use one or more gestures to control a viewing perspective of one or more virtual cameras to change a perspective at which the media content item is viewed. In another example, the viewer may select a virtual object displayed in one or more

images of the media content item, upon which a perspective of a virtual camera may attach to that object. From the point of selection forward, the viewing perspective of the viewer may be from the perspective of the virtual object. In other examples, while navigating through the virtual environment, the viewer may bookmark one or more locations within the environment to create one or more location bookmarks. The viewer may later select a location bookmark to return to a location that corresponds to the selected bookmark. For example, a viewing perspective of a virtual camera may be changed to the location that corresponds to the location bookmark. In some embodiments, the system may present the media content item using different formats and resolutions in the different modes.

Techniques and systems are also described for allowing a viewer to navigate a virtual environment of a media content item using a computing device. The computing device may include a mobile device, such as a mobile phone, a tablet, or other handheld device. A viewer may navigate a scene of a movie using one or more sensors of the computing device. The system may associate or map a position of a virtual camera at which the media content item is viewed to a physical position and/or orientation of the computing device. In some examples, the viewer may view the media content item on the computing device itself. In some examples, the viewer may view the media content item on a viewing device that is separate from the computing device, such as a television, a virtual reality head-mounted device, or other viewing device. Sensors may include an accelerometer, a gyroscope, a magnetometer, a depth sensor, a global positioning system sensor, or other appropriate sensor that can provide signals indicating position and/or orientation.

The systems and techniques described above may utilize a server to render the images of media content items. For example, the images may be rendered remotely by the server, and provided to a viewing device for presentation. Navigation inputs including positioning information (e.g., gesture input, sensor input, head orientation information, or other input) may be sent to the server to control which images are rendered and from which virtual camera viewing perspective the images are rendered. The server may include a cloud server of a cloud network. In some embodiments, a computing device (e.g., a mobile phone, a tablet, a head-mounted device, or other device) may send a signal with initial positioning information and an associated position indicator to the server. The server may use the initial positioning information to render images of the media content item from the perspective at which the user of the computing device is oriented or positioned. The server may send the rendered images back to the computing device with the associated position indicator. The computing device can use the position indicator to determine the initial positioning information at which the images are rendered. The computing device can then check updated positioning information of the computing device, and can use the received associated position indicator, the initial positioning information, and the updated positioning information to modify the rendered image to shift the perspective of the rendered image to that of the updated positioning information.

According to at least one example of switching between different modes of a media content item, a computer-implemented method may be provided that includes receiving, by the computing device while operating in a cinematic mode, a set of images of the media content item, the set of images having been rendered by a cloud server different from the computing device. The set of images include a

predefined cinematic perspective of a virtual camera within a virtual environment of the media content item. The method further includes presenting, by the computing device while operating in the cinematic mode, the media content item in a first format and in a passive manner in which user control of the virtual camera within the virtual environment of the media content item is not enabled. The method further includes receiving, by the computing device, input corresponding to a user command to switch from operation in the cinematic mode to operation in an interactive mode. The method further includes switching, by the computing device, from operation in the cinematic mode to operation in the interactive mode in which user control of the virtual camera within the virtual environment of the media content item is enabled and the media content item is presented in a second format different from the first format. The method further includes receiving, by the computing device while operating in the interactive mode, input corresponding to a navigation command for controlling navigation of the virtual camera within the virtual environment. The input includes initial positioning information for the computing device. The method further includes associating the initial positioning information with a position indicator and storing the initial positioning information in association with the position indicator in a storage device. The method further includes transmitting a signal corresponding to the navigation command to the cloud server. The signal includes the initial positioning information and the position indicator. The method further includes receiving image data from the cloud server. The image data includes the position indicator and an image rendered by the cloud server corresponding to the initial positioning information. The method further includes determining updated positioning information for the computing device, and retrieving the initial positioning information from the storage device based on the position indicator. The method further includes modifying, by the computing device, the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information. The method further includes presenting, by the computing device while operating in the interactive mode, the additional image corresponding to the updated positioning information.

In some embodiments, a computing device may be provided for switching modes associated with a media content item. The computing device includes an input device for receiving, while the computing device is operating in a cinematic mode, a set of images of the media content item, the set of images having been rendered by a cloud server different from the computing device. The set of images include a predefined cinematic perspective of a virtual camera within a virtual environment of the media content item. The computing device further includes one or more processors configurable to present, while the computing device is operating in the cinematic mode, the media content item in a first format and in a passive manner in which user control of the virtual camera within the virtual environment of the media content item is not enabled. The input device is configured to receive input corresponding to a user command to switch from operation in the cinematic mode to operation in an interactive mode, and the one or more processors are configurable to switch from operation in the cinematic mode to operation in the interactive mode in which user control of the virtual camera within the virtual environment of the media content item is enabled and the media content item is presented in a second format different

from the first format. The input device is configured to receive, while the computing device is operating in the interactive mode, input corresponding to a navigation command for controlling navigation of the virtual camera within the virtual environment. The input includes initial positioning information for the computing device. The one or more processors are configurable to associate the initial positioning information with a position indicator and store the initial positioning information in association with the position indicator in a storage device. The computing device further includes an output device for transmitting a signal corresponding to the navigation command to the cloud server. The signal includes the initial positioning information and the position indicator. The input device is configured to receive image data from the cloud server. The image data includes the position indicator and an image rendered by the cloud server corresponding to the initial positioning information. The one or more processors are configurable to determine updated positioning information for the computing device, retrieve the initial positioning information from the storage device based on the position indicator, and modify the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information. The one or more processors are further configurable to present, while the computing device is operating in the interactive mode, the additional image corresponding to the updated positioning information.

In some embodiments, a computer-readable memory storing a plurality of instructions executable by one or more processors may be provided. The plurality of instructions comprise: instructions that cause the one or more processors to receive, while the computing device is operating in a cinematic mode, a set of images of the media content item, the set of images having been rendered by a cloud server different from the computing device and including a predefined cinematic perspective of a virtual camera within a virtual environment of the media content item; instructions that cause the one or more processors to present, while the computing device is operating in the cinematic mode, the media content item in a first format and in a passive manner in which user control of the virtual camera within the virtual environment of the media content item is not enabled; instructions that cause the one or more processors to receive input corresponding to a user command to switch from operation in the cinematic mode to operation in an interactive mode; instructions that cause the one or more processors to switch from operation in the cinematic mode to operation in the interactive mode in which user control of the virtual camera within the virtual environment of the media content item is enabled and the media content item is presented in a second format different from the first format; instructions that cause the one or more processors to receive, while the computing device is operating in the interactive mode, input corresponding to a navigation command for controlling navigation of the virtual camera within the virtual environment, wherein the input includes initial positioning information for the computing device; instructions that cause the one or more processors to associate the initial positioning information with a position indicator; instructions that cause the one or more processors to store the initial positioning information in association with the position indicator in a storage device; instructions that cause the one or more processors to transmit a signal corresponding to the navigation command to the cloud server, the signal including the initial positioning information and the position indicator;

5

instructions that cause the one or more processors to receive image data from the cloud server, the image data including the position indicator and an image rendered by the cloud server corresponding to the initial positioning information; instructions that cause the one or more processors to determine updated positioning information for the computing device; instructions that cause the one or more processors to retrieve the initial positioning information from the storage device based on the position indicator; instructions that cause the one or more processors to modify the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information; and instructions that cause the one or more processors to present, while the computing device is operating in the interactive mode, the additional image corresponding to the updated positioning information.

In some embodiments, the position indicator includes a time stamp, a color, or a shape. In some embodiments, the method, system, and computer-readable memory described above may further include storing, in the storage device, a plurality of sets of positioning information in association with corresponding position indicators, each set of positioning information being associated with a separate position indicator in the storage device. The method, system, and computer-readable memory may further include identifying the position indicator in the received image data. Retrieving the initial positioning information from the storage device based on the position indicator may include identifying a set of positioning information from the plurality of sets that is stored in association with the initial positioning information in the storage device.

In some embodiments, the received image is modified to compensate for a difference in positioning information between the initial positioning information and the updated positioning information.

In some embodiments, the media content item is automatically paused at a first time of a timeline associated with the media content item when the computing device switches from operation in the cinematic mode to operation in the interactive mode.

In some embodiments, the interactive mode allows control of a timeline of the media content item.

In some embodiments, the method, system, and computer-readable memory described above may further include switching operation of the computing device from the interactive mode to the cinematic mode, wherein the virtual camera returns to the predefined cinematic perspective from a user controlled perspective when the computing device is switched from operation in the interactive mode to operation in the cinematic mode.

In some embodiments, the method, system, and computer-readable memory described above may further include receiving input corresponding to selection of a location bookmark, the location bookmark corresponding to a location within the virtual environment, transmitting a signal corresponding to the location bookmark to the cloud server, and receiving at least one image of the media content item from the cloud server, the at least one image including a perspective of the virtual camera at the location within the virtual environment based on the location bookmark. The method, system, and computer-readable memory may further include presenting the at least one image of the media content item.

In some embodiments, the method, system, and computer-readable memory described above may further include

6

pausing the media content item when the computing device is switched from operation in the cinematic mode to operation in the interactive mode, receiving input corresponding to selection of an object within the virtual environment, transmitting a signal corresponding to the selection of the object to the cloud server, and receiving at least one image of the media content item from the cloud server, the at least one image including a perspective of the virtual camera from a point of view of the object. The method, system, and computer-readable memory may further include unpausing the media content item to present the at least one image of the media content item.

In some embodiments, selection of the object includes moving the virtual camera a threshold distance from the object.

According to at least one example of allowing a viewer to navigate a virtual environment of a media content item using a computing device, a computer-implemented method may be provided that includes receiving, by the computing device, a set of images of the virtual environment of the media content item, the set of images having been rendered by a cloud server different from the computing device. The method further includes presenting, by the computing device, the set of images of the virtual environment and receiving, by the computing device, a sensor input in response to movement of the computing device. The sensor input corresponding to a navigation command for controlling navigation of a virtual camera within the virtual environment. The sensor input is received from at least one of an accelerometer, a gyroscope, a depth sensor, or a global positioning system sensor of the computing device. The method further includes determining initial positioning information based on the sensor input, associating the initial positioning information with a position indicator, storing the initial positioning information in association with the position indicator in a storage device, and transmitting a signal corresponding to the navigation command to the cloud server. The signal includes the initial positioning information and the position indicator. The method further includes receiving image data from the cloud server. The image data includes the position indicator and an image rendered by the cloud server corresponding to the initial positioning information. The method further includes determining updated positioning information for the computing device, retrieving the initial positioning information from the storage device based on the position indicator, and modifying, by the computing device, the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information. The method further includes presenting, by the computing device, the additional image corresponding to the updated positioning information.

In some embodiments, a computing device may be provided for navigating a virtual environment of a media content item. The computing device includes an input device for receiving a set of images of the virtual environment of the media content item, the set of images having been rendered by a cloud server different from the computing device. The computing device further includes one or more processors configurable to present the set of images of the virtual environment. The input device is configured to receive a sensor input in response to movement of the computing device. The sensor input corresponds to a navigation command for controlling navigation of a virtual camera within the virtual environment. The sensor input is received from at least one of an accelerometer, a gyroscope,

a depth sensor, or a global positioning system sensor of the computing device. The one or more processors are configurable to determine initial positioning information based on the sensor input, associate the initial positioning information with a position indicator, and store the initial positioning information in association with the position indicator in a storage device. The computing device further includes an output device for transmitting a signal corresponding to the navigation command to the cloud server. The signal includes the initial positioning information and the position indicator. The input device is configured to receive image data from the cloud server. The image data includes the position indicator and an image rendered by the cloud server corresponding to the initial positioning information. The one or more processors are configurable to determine updated positioning information for the computing device, retrieve the initial positioning information from the storage device based on the position indicator, and modify the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information. The one or more processors are further configurable to present the additional image corresponding to the updated positioning information.

In some embodiments, a computer-readable memory storing a plurality of instructions executable by one or more processors may be provided. The plurality of instructions comprise: instructions that cause the one or more processors to receiving a set of images of the virtual environment of the media content item, the set of images having been rendered by a cloud server different from the computing device; instructions that cause the one or more processors to present the set of images of the virtual environment; instructions that cause the one or more processors to receive a sensor input in response to movement of the computing device, the sensor input corresponding to a navigation command for controlling navigation of a virtual camera within the virtual environment, wherein the sensor input is received from at least one of an accelerometer, a gyroscope, a depth sensor, or a global positioning system sensor of the computing device; instructions that cause the one or more processors to determine initial positioning information based on the sensor input; instructions that cause the one or more processors to associate the initial positioning information with a position indicator; instructions that cause the one or more processors to store the initial positioning information in association with the position indicator in a storage device; instructions that cause the one or more processors to transmit a signal corresponding to the navigation command to the cloud server, the signal including the initial positioning information and the position indicator; instructions that cause the one or more processors to receive image data from the cloud server, the image data including the position indicator and an image rendered by the cloud server corresponding to the initial positioning information; instructions that cause the one or more processors to determine updated positioning information for the computing device; instructions that cause the one or more processors to retrieve the initial positioning information from the storage device based on the position indicator; instructions that cause the one or more processors to modify the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information; and

instructions that cause the one or more processors to presenting the additional image corresponding to the updated positioning information.

In some embodiments, the method, system, and computer-readable memory described above for navigating a virtual environment may further include storing, in the storage device, a plurality of sets of positioning information in association with corresponding position indicators.

Each set of positioning information is associated with a separate position indicator in the storage device. The method, system, and computer-readable memory may further include identifying the position indicator in the received image data. Retrieving the initial positioning information from the storage device based on the position indicator may include identifying a set of positioning information from the plurality of sets that is stored in association with the initial positioning information in the storage device.

In some embodiments, the received image is modified to compensate for a difference in positioning information between the initial positioning information and the updated positioning information.

In some embodiments, a position of the virtual camera is mapped to a physical position and orientation of the computing device using the sensor input.

In some embodiments, the position indicator includes a time stamp, a color, or a shape.

This summary is not intended to identify key or essential features of the claimed subject matter, nor is it intended to be used in isolation to determine the scope of the claimed subject matter. The subject matter should be understood by reference to appropriate portions of the entire specification of this patent, any or all drawings, and each claim.

The foregoing, together with other features and embodiments, will be described in more detail below in the following specification, claims, and accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

Illustrative embodiments of the present invention are described in detail below with reference to the following drawing figures:

FIG. 1 is a block diagram illustrating an example of a system for remotely rendering images of a media content item at a server.

FIG. 2 illustrates an example of a system for presenting a media content item.

FIG. 3 illustrates another example of a system for presenting a media content item.

FIG. 4 illustrates another example of a system for presenting a media content item.

FIG. 5A and FIG. 5B illustrate another example of a system for presenting a media content item.

FIG. 6 illustrates an example of a media content item presented in a cinematic mode.

FIG. 7 illustrates an example of a media content item presented in an interactive mode.

FIG. 8 illustrates another example of a media content item presented in an interactive mode.

FIG. 9 is a block diagram illustrating an example of a computing device for use in sending information to a server for remotely rendering images of a media content item.

FIG. 10 is a block diagram illustrating an example of a server for remotely rendering images of a media content item.

FIG. 11A and FIG. 11B illustrate a flow chart of a process for switching modes associated with a media content item displayed on a computing device.

FIG. 12A and FIG. 12B illustrate a flow chart of a process for navigating a virtual environment of a media content item using a computing device.

FIG. 13 shows an example of a computer system that may be used in various embodiments of the present invention.

DETAILED DESCRIPTION

In the following description, for the purposes of explanation, specific details are set forth in order to provide a thorough understanding of embodiments of the invention. However, it will be apparent that various embodiments may be practiced without these specific details. The figures and description are not intended to be restrictive.

The ensuing description provides exemplary embodiments only, and is not intended to limit the scope, applicability, or configuration of the disclosure. Rather, the ensuing description of the exemplary embodiments will provide those skilled in the art with an enabling description for implementing an exemplary embodiment. It should be understood that various changes may be made in the function and arrangement of elements without departing from the spirit and scope of the invention as set forth in the appended claims.

Many devices and systems allow media content to be processed and output for consumption. Media content (e.g., videos, video games, or other media) includes large amounts of data that must be stored and processed to render for display. Furthermore, viewers of media content desire media with the utmost quality and with various interactive options, leading to an even larger amount of data. The amount of storage and processing required to render frames of media content is a heavy burden for consumer devices. Embodiments of the present disclosure include techniques and systems that provide various interactive experience options to viewers while allowing the content to be remotely rendered. A viewer of media content may also be referred to as a user. For example, a user of a computing device (or other device) may view media content on the computing device (or on the other device).

In some embodiments, an interactive content system can provide viewers with media content. For example, FIG. 1 illustrates an example of a system 100 that can remotely render images of a media content item 110. The system 100 may include a server 108 (e.g., one or more server computers) that is configured to and that may communicate with, provide content to, and/or control one or more interactive devices. The one or more interactive devices may include a computing device 102, a head-mounted device 104, a display device 112, or other suitable interactive device. Rendering the media content item 110 in the server 108 compensates for the limited computational power of interactive devices. While embodiments described herein describe the media content item 110 being rendered by the server 108, one of ordinary skill in the art will appreciate that, in some embodiments, the media content item 110 may be rendered in whole or in part by an interactive device. As described in more detail below, the media content item 110 may include interactive serial content (e.g., a movie, a television show, a video game, or the like) that can be presented in one or more modes. Contents of the media content item 110 may include various digital or virtual assets or objects (e.g., movie characters, virtual objects, or any other asset or object) as well as one or more backgrounds, such as a virtual environment depicting a representation of a physical environment.

The server 108 may include a cloud network computer that is part of a cloud network located remotely from the interactive devices. The cloud network may include one or more cloud infrastructure systems that provide cloud services. A cloud infrastructure system may, for example, be operated by a service provider. In some aspects, services provided by the cloud network may include a host of services that are made available to users of the cloud infrastructure system on demand, such as remote rendering of media content. Services provided by the cloud infrastructure system can dynamically scale to meet the needs of its users. The cloud network may comprise one or more computers, servers, and/or systems, including the server 108. In some embodiments, the computers, servers, and/or systems making up the cloud network are different from a customer's on-premises computers, servers, and/or systems. For example, the cloud network may host an application, and a user or customer may order and use the application via a communication network (e.g., network 106).

In some examples, the cloud network may host a Network Address Translation (NAT) Traversal application to establish a secure connection between a service provider of the cloud network and one or more of the interactive devices, such as computing device 102, head-mounted device 104, or display device 112. A separate secure Transmission Control Protocol (TCP) connection may be established by each interactive device for communicating between each interactive device and the server 108 (or other server) of the cloud network. In some embodiments, each secure connection may be kept open for an indefinite period of time so that the cloud network can initiate communications with each respective interactive device at any time. Various protocols may be used to establish a secure connection between each network device and the server 108, including Session Traversal Utilities for NAT (STUN), Traversal Using Relay NAT (TURN), Interactive Connectivity Establishment (ICE), a combination thereof, or any other appropriate NAT traversal protocol.

In some cases, communications between the cloud network and interactive devices may be supported using other types of communication protocols. Such protocols may include a Hypertext Transfer Protocol (HTTP) protocol, a Hypertext Transfer Protocol Secure (HTTPS) protocol, or other suitable communication protocol. In certain embodiments, the cloud network may include a suite of applications, middleware, and database service offerings that are delivered to a customer in a self-service, subscription-based, elastically scalable, reliable, highly available, and secure manner.

In some examples, an interactive device may include a computing device 102. The computing device 102 may include a mobile phone, a tablet device, a laptop computer, a television or other display device, a digital video recording device, a set-top box device, or any other suitable computing device. In some examples, an interactive device may include a head-mounted device 104. For example, the head-mounted device 104 may include a head-mounted virtual reality device, such as virtual reality goggles or glasses. In another example, the head-mounted device 104 may include three-dimensional glasses. In some examples, an interactive device may include a display device 112. For example, the display device 112 may include a television, a desktop or laptop computer, an immersion system or cave, or other suitable display device.

The server 108 may receive a request from an interactive device (e.g., computing device 102, head-mounted device 104, or display device 112) to load a media content item 110

11

onto the requesting interactive device or another interactive device. In some examples, as described in more detail below, the request may be sent by the same interactive device that will display the media content item 110. For example, the computing device 102 may display the media content item and may also allow a viewer or user to interact with the displayed media content item. In other examples, the request may be sent by a different interactive device than that which will display the media content item 110. For example, the computing device 102 may be used to interact with or control a media content item that is displayed on another interactive device, such as the head-mounted device 104 or the display device 112. Accordingly, the head-mounted device 104 and the display device 112 are optional in the system 100, as indicated by the dotted lines of the respective blocks displayed in FIG. 1. Various examples of system configurations with interactive devices are described below with respect to FIGS. 2, 3, 4, 5A, and 5B.

The request for the media content item 110 may be transmitted using a communications link over a network 106. The communications link may include a signal transmitted using the network 106, which may include a wireless network, a wired network, or a combination of a wired and wireless network. A wireless network may include any wireless interface or combination of wireless interfaces and may include any suitable wireless network (e.g., the Internet or other wide area network, a packet-based network, a WiFi™ network, a radio frequency (RF) network, an ultra-wideband (UWB) network, a WiFi-Direct network, a cellular network, a Long-Term Evolution (LTE) network, a WiMax™ network, or the like). A wired network may include any wired interface (e.g., fiber, ethernet, powerline ethernet, ethernet over coaxial cable, digital signal line (DSL), or the like). The wired and/or wireless networks making up the network 106 may be implemented using various equipment, such as one or more base stations, routers, access points, bridges, gateways, switches, or the like.

Upon receiving the request, the server 108 may provide the content to the interactive device (or another interactive device) by rendering the images of the media content item and sending the rendered images to the interactive device. The server 108 may include hardware and software implementing a rendering algorithm for rendering images of the media content item 110. The rendering algorithm may utilize one or more scene files that contain objects in a defined language or data structure. For example, the scene file may include a description of the virtual scene that includes geometries, viewpoints, textures, lighting, and shading information of different virtual environments, virtual backgrounds, and virtual objects in the scene. Any suitable rendering algorithm may be used to process the scene file to render the images of the media content item 110. In some examples, a rendering algorithm may use one or more of rasterization techniques, ray casting techniques, ray tracing techniques, radiosity techniques, or other suitable techniques for rendering an image. In one example, the rendering algorithm used by the server 108 may include rasterization with deferred shading and dynamic global illumination. In some embodiments, the server 108 may include a graphics processing unit (GPU) in addition to a central processing unit (CPU) for rendering the images of the media content item 110.

In some embodiments, the server 108 can stream the images of the media content item 110 as the images are rendered. In some embodiments, the computing device 202 can request certain portions of the media content item 110,

12

in which case the server 108 may send only a portion of the media content item 110. Once the rendered images of the media content item 110 are received, the interactive device may present or display the images to a viewer. In some alternative embodiments, an interactive device may be provided with information usable by the interactive device to render the images of the content itself

FIG. 2 illustrates one example of a system 200 for presenting the media content item 110. The computing device 202 can send a request over the network 106 to the server 108 requesting the media content item 110. Similar to the computing device 102, the computing device 202 may include mobile phone, a tablet device, a laptop computer, a television or other display device, a digital video recording device, a set-top box device, or any other suitable computing device. In some embodiments, the server 108 renders the images of the media content item 110 upon receiving the request. In other embodiments, the images of the media content item 110 may be rendered prior to receiving the request. In response to the request, the server 108 sends the rendered images of the media content item 110 to the computing device 202 over the network 106. The computing device 202 then receives the media content item 110 rendered by the server 108. Once one or more of the images of the media content item 110 are received, the computing device 202 can begin presenting the media content item 110.

In the example of FIG. 2, the computing device 202 also allows the viewer to interact with the displayed media content item 110. Using the system configuration of system 200, a request for a media content item 110 is sent by the same interactive device that displays the media content item 110 and that allows the viewer to interact with the media content item 110.

In other examples, requests for a media content item 110, and control of the media content item 110, may be implemented by a different interactive device than that which displays the media content item 110. For example, FIG. 3 shows another example of a system 300 for presenting the media content item 110. The system 300 includes a computing device 302 and a display device 304. The computing device 302 may include mobile phone, a tablet device, a laptop computer, a digital video recording device, a set-top box device, or any other suitable computing device. The display device 304 may include a television, a desktop or laptop computer, or other suitable display device.

The computing device 302 may be used to control the media content item 110, while the display device 304 may display the media content item 110. For example, the computing device 302 can be used to request the media content item 110 (or portions thereof) from the server 108 over the network 106. The server 108 may send rendered images of the media content item 110 to the display device 304 over the network 106. The computing device 302 can also be used to interact with the media content item 110. The computing device 302 may send commands to the server 108 over the network 106 in order to interact with the media content item 110, as described in more detail below. In some embodiments, both the computing device 302 and the display device 304 may be used to request or to interact with the media content item 110.

In some embodiments, a user of the computing device 302 may view the media content item 110 on the computing device 302. At a later point in time, the user may switch from viewing the media content item 110 on the computing device 302 to viewing the media content item 110 on the display device 304. For example, a player application executed on the computing device 302 may send a control signal to a

13

player application executed on the display device 304. The control signal may instruct the player device of the display device 304 to begin presenting images of the media content item 110 rendered by the server 108. In some examples, the computing device 302 or the display device 304 may send a message to the server 108 instructing the server 108 to begin sending rendered images to the display device 304. In other examples, the computing device 302 may receive rendered images from the server 108. The computing device 302 may then send the rendered images to the display device 304. The computing device 302 can be used to control features of the media content item 110 presented by the display device 304.

FIG. 4 shows yet another example of a system 400 for presenting the media content item 110. The system 400 includes a computing device 402 and a head-mounted device 404. The computing device 402 may include mobile phone, a tablet device, a laptop computer, a digital video recording device, a set-top box device, or any other suitable computing device. The head-mounted device 404 may include a head-mounted virtual reality device (e.g., virtual reality goggles or glasses), three-dimensional glasses, or other head-mounted device.

The computing device 402 may be used to control the media content item 110, and the head-mounted device 404 may display the media content item 110 (as depicted by view 406). For example, head-mounted virtual reality goggles may be used to convey a feeling that the viewer is immersed in a displayed environment. A viewer may operate the computing device 402 to request the media content item 110 (or portions thereof) from the server 108 over the network 106. The server 108 may send rendered images of the media content item 110 to the head-mounted device 404 over the network 106.

The computing device 402 can also be used to interact with the media content item 110 displayed using the head-mounted device 404. The computing device 402 may send commands to the server 108 over the network 106 in order to interact with the media content item 110, as described in more detail below. In some embodiments, both the computing device 402 and the head-mounted device 404 may be used to request or to interact with the media content item 110.

In some embodiments, a user of the computing device 402 may view the media content item 110 on the computing device 402. The user may switch from viewing the media content item 110 on the computing device 402 to viewing the media content item 110 on the head-mounted device 404. For example, a player application executed on the computing device 402 may send a control signal to a player application executed on the head-mounted device 404. The control signal may instruct the player device of the head-mounted device 404 to begin presenting images of the media content item 110 rendered by the server 108. In some examples, the computing device 402 or the head-mounted device 404 may send a message to the server 108 instructing the server 108 to begin sending rendered images to the head-mounted device 404. In other examples, the computing device 402 may receive rendered images from the server 108, and may send the rendered images to the head-mounted device 404. The computing device 402 can be used to control features of the media content item 110 presented by the head-mounted device 404.

FIG. 5A and FIG. 5B illustrate another example of a system 500 for presenting the media content item 110. The system 500 may be referred to as an immersion system. The system 500 includes a computing device 502 and a server 108 that can communicate and/or control one or more

14

display devices 506, 508, 510, 512, 514. The display devices 506, 508, 510, 512, 514 may be configured to and may project one or more images of the media content item 110. In one aspect, the display devices 506, 508, 510, 512, 514 may partially or wholly surround an area 504. While five display devices are shown in FIG. 5A and FIG. 5B, one of ordinary skill in the art will appreciate that the system 500 may include more or fewer display devices. For example, a group of display devices may span each wall of the area 504 to completely surround the area 504 and any persons located within the area 504. As another example, a group of display devices may partially surround the area 504 by creating two walls around the area 504. As still another example, a group of display devices may partially surround the area 504 by creating three walls around the area 504. In some embodiments, a group of display devices may additionally be configured to span a floor of the area 504. In one aspect, the display devices may also generate three-dimensional images (e.g., holograms) of assets, objects, or backgrounds of the media content item 110 such that a viewer is able to perceive depth in the assets, objects, or backgrounds.

In some examples, the system 500 may include a set of projector screens 516, 518, 520, 522, 524 that partially or fully surround the area 504 (e.g., create one or more walls surrounding the area 504). Each of the set of projector screens may be associated with one or more display devices positioned behind the screens to generate images on the screens. For example, display device 506 may project images onto screen 518, display device 508 may project images onto screen 516, display device 510 may project images onto screen 522, display device 512 may project images onto screen 520, and display device 514 may project images onto screen 524. The screen 524 may be placed on the floor of the area 504. The display device 514 may be positioned above or overhead of the area 504 so that images generated by the display device 514 can be projected onto the screen 524 positioned on the floor of the area 504. While FIG. 5A and FIG. 5B illustratively show five screens and their respective display devices surrounding an area 504, one of ordinary skill in the art will appreciate that other configurations may be implemented.

In one aspect, images of the media content item 110 presented by the display devices 506, 508, 510, 512, 514 may be generated in real or substantially real-time by the server 108. The images may be presented in a stereo format such that a user wearing three-dimensional glasses (e.g., three-dimensional (3D) shutter glasses) may perceive three-dimensional assets or holograms from the images.

The system may further include one or more sensors located in the area 504. The sensors may include, for example, cameras, depth sensors, infra-red sensors, light sensors, or other suitable sensors. Such sensors may be used to track the movement and positioning of a user within the area 504 surrounded by the display devices 506, 508, 510, 512, 514 or of others outside of the area 504.

In some examples, the system 500 may establish a communication link with one or more interactive devices, such as the computing device 502, in proximity to the system 500. For example, the system may establish a Bluetooth™ link, a Zigbee™ link, or other communication link with the computing device 502 located within the area 504. Following establishment of the communication link, the system 500 may receive a selection of a particular item of content to present to the user of the computing device 102. The content may be, for example, the media content item 110 or other item of content.

Upon receiving the selection, the server 108 may retrieve information regarding the media content item 110 and may render the images of the media content item 110. The server 108 may send the images of the media content item 110 to the display devices 506, 508, 510, 512, 514. In some embodiments, each display device 506, 508, 510, 512, 514 may be assigned to generate a particular portion of the media content item 110 (e.g., certain assets, objects, and/or environments associated with the content). In some embodiments, the computing device 502 may provide height information for a particular user. Using the height information, the server 108 may adjust the height of assets or objects rendered in images of the media content item 110. For example, if a particular user were 6'5", the server 108 may adjust a particular character in a movie to also be 6'5". In one aspect, assets may be downloaded from the interactive device, from local storage of the system, or from a repository available over the Internet.

The system 500 may be used in several different applications. For example, an actor may use the immersive experience provided by the system 500 to aid in his or her acting performance (e.g., maintain eye level with a digital character). As another example, the immersive experience may be used by a movie viewer to be immersed within a customized movie based on the movie viewer's personal preferences using, for example, one or more of the interactive options described below. Illustratively, the user may prefer that a particular movie occur within a beach environment as opposed to a mountainous environment. As yet another example, a video game user may control a 3D holographic character within an immersive environment and interact with other assets in the immersive environment.

As described in more detail below with respect to FIG. 9 and FIG. 10, a computing device (e.g., computing device 102, 202, 302, 402, or 502), a head-mounted device (e.g., head-mounted device 104 or 404), or the computing device and head-mounted device working in conjunction may detect positioning information corresponding to a position and/or orientation of the viewer at a given point in time while watching the media content item 110. The positioning information may be used to control aspects of the media content item 110.

The media content item 110 can be presented and controlled using any of the configurations shown in FIG. 1-FIG. 5B. As previously described, the media content item 110 may include interactive serial content, such as a movie, a television show, a video game, or the like. The media content item 110 may also be presented using different modes. The different modes may include a cinematic mode and an interactive mode. The cinematic mode includes serially presenting the media content item 110 and does not allow user interaction with the media content item 110. The media content item 110 may be switched to an interactive mode during any point of the media content item 110. While in the interactive mode, a viewer or user can interact with various aspects of the media content item 110.

A computing device (e.g., computing device 102, 202, 302, 402, or 502) can operate in a cinematic and an interactive mode to switch the media content item 110 between the different modes. The media content item 110 contains information for the different modes, and a video player application being executed by the computing device switches between operation in interactive mode and cinematic mode. The media content item 110 may include a computer file containing camera information for the cinematic mode and also scene data necessary to produce the images of the interactive mode. For example, the computer

file comprising the media content item 110 contains scene data (e.g., three-dimensional scene data) that is to be rendered into images viewable by the viewer or user. The images may be two-dimensional images or, in some embodiments, may be three-dimensional images. The computer file further includes a specific track (which may be referred to as a "director track") specifying predefined virtual camera positions that make up the cinematic mode of the media content item 110. A video player application installed on the computing device can load the computer file for playback to the viewer or user. When the video player application is operating in the cinematic mode, the video player application sends one or more signals to a rendering engine (e.g., a cloud-based rendering engine of the server 108, such as the rendering engine 1004 described below) instructing the rendering engine to render the media content item 110 using the director track. When the video player application receives input instructing it to operate in the interactive mode, the video player application allows the user to control the position of an interactive virtual camera. A user may provide input to move the virtual camera to one or more camera positions and/or orientations. When the input is received from the user, the video player application generates control information corresponding to the one or more camera positions and/or orientations. The video player application then sends signals with the control information to the rendering engine. In one example, the video player application may send control information with the physical position and orientation of the computing device to the server. In another example, the video player application may receive gesture input, and may determine a position and orientation based on the gesture input. The computing device may then send control information with the determined position and orientation to the server. The rendering engine can use the control information to render scenes from the camera positions and/or orientations based on the control information rather than the director track. For example, the rendering engine may map the physical position and orientation to the virtual camera position and orientation. The rendered scenes can be sent to the computing device (and/or to a head-mounted device or display device).

In some aspects, the media content item 110 includes a timeline over which multiple, simultaneous story threads progress. A story thread, as used herein, may refer to logical groups of scripted interactions between virtual objects, where each group of scripted interactions is associated with predefined virtual camera orientations or perspectives (which may be referred to as one or more cinematic perspectives). In some embodiments, the media content item 110 may further include two-dimensional (2D) and/or three-dimensional (3D) virtual scenes in which the story threads occur. The 2D and 3D virtual scenes are usable for rendering video in real-time at interactive frame rates for presentation to viewers.

During initial presentation to a viewer, the media content item 110 may be presented in the cinematic mode. FIG. 6 illustrates an example of the media content item 110 presented in cinematic mode. When presented in cinematic mode, a pre-selected primary story thread for the media content item 110 is presented by rendering the 2D and/or 3D virtual scenes from a perspective of a virtual camera at the various predefined virtual camera orientations for the primary story thread. During this initial presentation, the primary story thread is presented in a cinematic, non-interactive mode. Thus, the viewer has no control over the perspectives from which the content is presented or over displayed assets or objects, such as characters 602 and 604.

In some embodiments, the media content item **110** is presented in a default format and resolution while in the cinematic mode. As the primary story thread progresses along the timeline, the server **108** keeps track of and processes multiple non-primary story threads simultaneously over the timeline. The non-primary story threads are non-viewable by the viewer when the media content item **110** is in the cinematic mode.

At any point during the initial presentation, the viewer may specify that he or she wishes to interact with the media content item **110** using, for example, the computing device **102**. In response, the server **108** switches the media content item **110** to an interactive mode for presentation. FIG. 7 illustrates an example of the media content item **110** presented in interactive mode. In some instances, the server **108** may render the images of the media content item **110** using a different format and resolution from the default format and resolution used for the cinematic mode. For example, the media content item **110** may be presented using a different (e.g., higher or lower) frame rate, resolution, aspect ratio, or other format when in the cinematic mode than when in the interactive mode. In one illustrative example, the media content item **110** may be played back in the cinematic mode at 24 frames per second, and can be played back in the interactive mode at 60 frames per second. In some examples of using different formats for the cinematic and interactive modes, the server **108** may render images without the letterbox bars **606** and **608** when the media content item **110** is presented by the computing device **102** in the interactive mode. For example, in cinematic mode, the top and bottom of the image can be masked (e.g., using a crop mask) to give the media content item **110** the appearance of a widescreen movie, but in the interactive mode the masking may not be used.

In some instances, when switching from cinematic to interactive mode, the server **108** may automatically pause or stop the progression of the story threads over the timeline. The viewer may cause the media content item **110** to continue over the timeline by selecting the play icon **710**. In some instances, the media content item **110** may continue to progress along the timeline when switched from cinematic to interactive mode. The viewer may later pause the media content item **110** by selecting a pause icon **708**. The viewer may interact with assets or objects and with the environment while the media content item **110** is paused or while the media content item **110** progresses along the timeline. In some embodiments, images of the media content item **110** (while in interactive mode) may display a timeline bar **702** representing the timeline. The viewer may progress a timing control icon **704** along the timeline to move to certain scenes along the timeline of the media content item **110**.

While the media content item **110** is paused or progressing along the timeline, the viewer may navigate through a virtual environment of the media content item **110** by moving a virtual camera through the virtual environment. The viewer may change the perspective of the virtual camera to modify the perspective at which the media content item is presented. By allowing a viewer to manipulate the virtual camera perspective, the system **100** can simulate the viewer navigating through the virtual environment. In some examples, the viewer may discover other story threads of the media content item **110** other than the primary story thread that progresses along the timeline in the cinematic mode. For example, the viewer may discover one or more of the multiple non-primary story threads that are non-viewable when the media content item **110** is in the cinematic mode. The viewer may discover the previously hidden story

threads by moving the virtual camera so that certain assets or objects associated with the hidden story threads are viewable from the virtual camera. Any discovered story threads may be added to a list of story threads for later access for viewing. Location bookmarks associated with the discovered story threads may also be placed on a scene map with location bookmarks (discussed below).

In some examples, the viewer may perform certain gestures using the computing device **102** to change the perspective of the virtual camera. The gestures may be performed using an interface of the computing device **102**, for example using a touchscreen, a touchpad, a gesture-recognition device (e.g., a camera, depth sensor, or other device), or other interface. A gesture input may be interpreted as a navigation command to modify the virtual camera perspective. The gestures may be sent by computing device **102** to the server **108** over the network **106**. The server **108** can then render new or updated images of the media content item **110** to change the virtual camera perspective based on the navigation commands that correspond to the received gestures. Any number of gestures may be used to change the perspective of the virtual camera. For example, a viewer may move a single finger up and down to cause the virtual camera perspective to angle up (e.g., to view a ceiling in a building) and to cause the virtual camera perspective to angle down (e.g., to view a floor in a building), respectively. As another example of a gesture, the viewer may move two fingers in any direction to cause the virtual camera perspective to crane in the respective direction without angling the virtual camera perspective. As yet another example of a gesture, the viewer may perform a pinching gesture, in which case a pinch of two fingers together may cause the virtual camera perspective to move forward in space and a spreading of two fingers apart may cause the virtual camera perspective to move backwards in space. One of ordinary skill in the art will appreciate that any other gesture or combination of gestures may be used to manipulate a viewing perspective of a virtual camera within the environment of the media content item **110**.

In some examples, the viewer may access a scene map with location bookmarks. For example, while navigating through the virtual environment (e.g., using gestures to change the virtual camera perspective), the viewer may bookmark one or more locations within the environment to create one or more location bookmarks. The viewer may, for example, select a bookmark icon **706** in order to bookmark the location that the viewer is viewing when the bookmark icon **706** is selected. The viewer may later select a location bookmark (e.g., from a displayed list of location bookmarks) to return to a location that corresponds to the selected bookmark. When a location bookmark is selected, a viewing perspective of the virtual camera may be changed to the location that corresponds to the location bookmark.

In some examples, the viewer may move the virtual camera by moving the computing device **102**. In such examples, the computing device **102** may be a handheld device that includes one or more physical sensors. The viewer may view the media content item **110** on the computing device **102** (as shown in FIG. 2), or on a separate device (as shown in any of the examples of FIG. 3-FIG. 5B). Physical sensors of the computing device **102** may include an accelerometer, a gyroscope, a magnetometer, a depth sensor, a global positioning system (GPS) sensor, or other appropriate sensor that can provide signals indicating position and/or orientation. Sensor input from one or more of the sensors may be used to determine a position and/or orientation of the virtual camera. A sensor input may be inter-

10 preped as a navigation command to modify the virtual camera perspective. The sensor input may be sent by computing device 102 to the server 108 over the network 106. The server 108 can then manipulate the images to change the virtual camera perspective based on the navigation commands that correspond to the received sensor input. In one embodiment, as images of the media content item 110 are being presented, the sever 108 may adjust the perspective of the virtual camera in the images based on a navigation command corresponding to the location and movement of the computing device 502. For example, if the computing device 502 (by virtue of the movement of its user) faces or moves towards a certain direction (as indicated by global positioning system (GPS) sensor, accelerometer, gyroscope, a magnetometer, or other sensor information from the computing device 502), a viewpoint of the virtual environment in a scene of the media content item 110 may change accordingly.

20 In some embodiments, the server 108 may associate or map a position of the virtual camera with a physical position and/or orientation of the computing device 102, as determined using the sensor input. For example, when a user causes the computing device 102 and the media content item 110 to switch to the interactive mode, movement of the computing device 102 in the physical world is mapped to movement through the virtual environment of the media content item 110. In some examples, the computing device 102 sends its physical position and orientation to the server 108, and the server 108 maps the physical position and orientation to the virtual camera position and orientation. In one example, a physical position and orientation of the computing device 102 at a first point in time is treated as the origin. As the simulated movement through the virtual environment continues in time, differences in position and/or orientation between the origin position and orientation at the first point in time and later positions and/or orientations are used to translate and rotate the virtual camera. In one embodiment, a physical camera of the computing device 102 may capture an image of a stationary, physical object that is directly ahead of the computing device 102. The computing device 102 may map the image of the physical object with a true north direction of the virtual environment. Thereafter, depending on where the physical object appears in subsequent images, the position of the virtual camera may be moved. For example, if in a subsequent image, the physical object appears on the right side of the image (rather than in the middle of the image when used for mapping), then the virtual camera may be moved accordingly in the westward direction in the virtual environment. In another embodiment, a depth sensor of the computing device 102 may detect the depths of surfaces (e.g., a wall) and/or other objects in the vicinity of the computing device 102. The computing device 102 may map the detected depths of the surfaces and/or objects with particular directions of the virtual environment. Thereafter, depending on how the later detected depths of the surfaces and/or objects change, the position of the virtual camera may be moved in certain directions within the virtual environment. For instance, if a physical wall associated with a north direction in the virtual environment is detected to have a shallower depth than in the past relative to the computing device 102 in subsequent depth sensor readings, then the position of the virtual camera may be moved to the north in the virtual environment. Such a movement may be performed since the shallower depth of the wall indicates that the computing device 102 has moved closer to the wall. The distance that the virtual camera may be moved in the

virtual environment may be based on the physical change in depth of the wall relative to the computing device 102.

5 In some instances, the server 108 may perform a direct association between the virtual camera and the current physical position and/or orientation of the computing device 102. In such instances, even if the computing device 102 is physically facing down and the virtual camera is facing up in the virtual environment or scene of the media content item 110, the mapping would be maintained. In other instances, the server 108 may perform an association between the virtual camera and the current physical position and/or orientation of the computing device 102 based on the virtual scene and the physical environment in which the viewer is located. Thus, if the computing device 102 is facing upwards in the physical world, the virtual camera may also face upwards in the virtual scene. In one example, a scene of the media content item 110 may display a straight ahead virtual camera perspective. The viewer may rotate the computing device 102 to the left, causing one or more of the physical sensors to produce a sensor input that can be sent to the server 108 using one or more signals. As a result, the server 108 may present images of the media content item 110 with the virtual camera rotating to the left and stopping at a perspective showing the left side of an environment of the scene. While the viewer rotates the computing device 102, the media content item 110 may continue to be presented serially or, if paused, may remain paused.

10 In one aspect, based on the movement of the computing device 102, as detected by the physical sensors of the computing device 102, the virtual camera may be moved in the virtual environment. For instance, the server 108 may receive one or more signals corresponding to one or more sensor inputs, and may identify changes in camera images, depth information readings, gyroscope readings, accelerometer readings, magnetometer readings, GPS readings, or other sensor readings, to determine movement of the computing device 102. For example, a depth sensor of the computing device 102 may generate a depth sensor input with depth sensor information indicating a depth of a particular object located in the viewer's physical environment is a certain distance from the computing device 102. The computing device 102 may send a signal corresponding to the depth sensor input to the server 108. The depth information may indicate that the particular object in the physical environment is now closer in distance relative to the computing device 102 relative to a prior depth sensor input reading. Based on the updated depth sensor input reading, the server 108 may determine that the computing device 102 has moved forward three feet. The server 108 may then move the position of the virtual camera in the virtual environment or scene of the media content item 110 an equivalent of three feet in the virtual environment. In this way, a viewer may navigate through the virtual environment by moving and/or orientating his or her handheld device.

15 In some embodiments, as the virtual camera is adjusted to different locations and orientations in the environment of the media content item 110, the sound occurring in the media content item 110 may also be adjusted. For example, an explosion may occur in front of a given camera perspective. As the viewer rotates his or her tablet to the left, the sound of the explosion may be shifted such that the viewer perceives that the explosion is to his or her right side.

20 In embodiments involving the immersive system 500 of FIG. 5A and FIG. 5B, sensors located in or surrounding the area 504 may track the location and movement of a user of the system 500. For example, the sensors may track one or more markers affixed or included on 3D glasses, clothing, or

other items worn by the user to determine location and movement of the user around the area **504**. The markers may be of a particular shape and color, such as circular, spherical, square, white, yellow, green, or other suitable shape or color. Using the tracked markers to determine location and movement of the user, the server **108** may adjust the virtual camera perspective, and also may adjust assets or characters presented in images of the media content item **110**. Adjustment of the virtual camera to track the movement of the user may enable the user to perceive that he or she is moving relative to assets and/or the environment of the media content item **110**. In this way, the content displayed to the user can appear to be occurring in the real world. In one aspect, the system **500** may include one or more speakers presenting audio. In one aspect, the audio presented by the system may be adjusted based on the user's location and movement. In instances in which the immersive system **50** is used to capture actor performances, a green screen or some other matte may be presented by the display devices in a portion of a display behind the user. The green screen may move according to the location and movement of the user and/or the location and movement of a physical camera (which may have a communications link with the server **108**) capturing the performance of the user.

In some embodiments, the viewer may use the computing device **102** to cause the virtual camera to be attached or stuck to certain objects in the virtual environment. For example, the viewer may use the computing device **102** to select a virtual object located in the virtual environment, upon which a perspective of a virtual camera may attach to that object. In one example, the viewer may attach the virtual camera to the virtual object by moving the virtual camera (using the computing device **102**) a certain threshold distance from the object in the virtual environment. The threshold distance may be any suitable distance, such as an inch, two inches, six inches, a foot, or any other suitable distance. The viewer may move the virtual camera by inputting one or more gestures into an interface of the computing device **102**, or by physically moving the computing device **102** (in which case position and/or orientation may be detected using physical sensors), as described in the examples above. In another example, the viewer may select the virtual object (e.g., by inputting a gesture or other input to an interface of the computing device **102**) to attach the virtual camera to the virtual object.

As a result of attaching the virtual camera to the virtual object, the viewing perspective of the virtual camera may be modified to the perspective of the virtual object. In some cases, the virtual camera may follow the virtual object from a particular pre-defined distance and orientation. For example, the virtual camera may appear as if it is hovering above the virtual object at the pre-defined distance and orientation. In some cases, the virtual camera may be from a first person perspective of the virtual object. For example, the virtual camera may appear as if it is looking through the eyes of the virtual object.

FIG. **8** shows an example of a media content item **110** presented in an interactive mode with a modified virtual camera perspective from the perspective of the virtual character **602**. For example, the viewer, while watching the scene shown in FIG. **7**, may attach the virtual camera to the character **602** using any of the techniques described above for attaching the virtual camera to a virtual object. The computing device **102** may send a signal corresponding to selection of the object to the server **108**. The server **108** may then render the image of the media content item **110** shown in FIG. **8** with the virtual camera perspective being from a

first person point of view of the character **602**. The resulting image includes a view of the character **602** looking at the characters **802** and **804**.

In another example, upon reaching a scene of the media content item **110**, the viewer may select an asset (e.g., a virtual character, a virtual object, or other asset of the media content item) currently being displayed. The scene may present a robot from an overhead perspective. The viewer may interact with the computing device **102** to select the robot (e.g., using gestures, physically moving the computing device **102**, or other interaction). Responsive to the selection, the computing device **102** may send the input (e.g., navigation command, gesture input, sensor input, or the like) to the server **108**, and the server **108** may render and present subsequent images of the media content item **110** from a first person viewpoint of the robot.

In embodiments in which the media content item **110** is paused, the viewer may attach the virtual camera to a virtual object when the media content item **110** is paused. When the content is later un-paused, the virtual camera may follow the selected virtual object. The viewer may also attach the virtual camera to a virtual object as the media content item **110** progresses along the timeline in interactive mode. In one example, the media content item **110** may present, in the foreground, a scene where a first protagonist escapes a prison. The media content item **110** may also present, in the background, a starship battle that is occurring as the protagonist escapes the prison. The viewer may pause the media content item **110** using the computing device **102**, and may select a starship from the battle occurring in the background. The server **108** may then present an "in movie" game that enables the viewer to control the selected starship and battle other starships. After completion of the game (or at the viewer's discretion), the game may be exited and the starship battle returned to the background. The viewpoint of the protagonist may be returned to the foreground, and the media content item **110** may continue. In some instances, the outcome of an in movie game may influence the remaining portion of the media content item **110**.

The viewer may detach the virtual camera from a virtual object by either moving the virtual camera a threshold distance away from the virtual object, selecting another virtual object located in the virtual environment, or otherwise indicating that the virtual camera should be detached from the currently selected virtual object. For example, the viewer may input a pinching gesture input into an interface of the computing device **102** to move the virtual camera away from the selected virtual object to a desired location. The server **108** may, in response, render new or updated images of the media content item **110** with the virtual camera perspective being from the desired location.

In some instances, the viewer may be permitted to change certain characteristics of the virtual scene of the media content item **110**, such as environmental attributes or certain clothing attributes of characters. Such changeable characteristics may be limited to a predefined set of attributes. For example, the viewer may be permitted to change cloths of a particular character, but may not be permitted to change other features of the character. In some examples, the media content item **110** may be tailored to provide personalized serial content based on personalization information received from the computing device **102**. For example, a viewer may use the computing device **102** to indicate to the server **108** that the viewer has an affinity for a particular comic book character. In one example, a viewer may provide personalization information using a user interface on the computing device **102**. Such information may then be sent to the server

108. In one aspect, personalized serial content for the user may be distributed to one or more other authorized users selected by the user. The other authorized users may be selected from a user profile associated with the user over a social network.

In some embodiments, the server 108 may load an asset (e.g., a character, an animal, an object, or other asset) into the media content item 108 that is controllable by a user. As an example, a viewer may have a three dimensional hologram of a mouse interact with an environment that includes other generated holographic characters (e.g., a cat). A viewer may control a character in any suitable manner. In examples using the immersive system 500, the sensors located in or surrounding the area 504 may track the movement of the user. Based on the movement identified by the server 108 using the sensor information, the server 108 may cause a hologram of a character controlled by the user to move in a similar manner. In other examples, the viewer may perform gestures on the computing device 102, or may physically move the computing device 102, to cause the hologram of the character to be moved. Such movement of the hologram of the character may be presented to the user in real or substantial real-time on a display device. In one aspect, the server 108 may process the movements to determine whether the hologram of the character has interacted with other assets or objects of the media content item 110. Based on such a determination, the server 108 may cause modifications to the other assets and/or objects. For example, the viewer may cause the hologram of the character to swing a bat at a hologram of a baseball. Responsive to the swing, the server 108 may alter the trajectory of the baseball hologram that is displayed. In some instances using the immersive system 500, the user-controlled character may interact with other users who are within the area 504 surrounded by the display devices 506, 508, 510, 512, 514. In one aspect, a user controlling a character may be outside of the area 504 surrounded by the display devices 506, 508, 510, 512, 514 in a second different area. One or more sensors of the system 500 may be directed at the second different area in order to capture the movement of the user.

In some embodiments, a viewer may use a camera or other sensing device to generate a virtual representative of a real-world object. For example, the viewer may use a camera of the computing device 102 (or an external camera) to capture images of a real-world object from multiple angles. The images may be sent to the server 108, which may generate a virtual representative of the object. The virtual representative may then be inserted into the media content item 110 by the server 108. Thereafter, the viewer may interact with the virtual representative of the real-world object in the images presented by the item of media content.

In the event the media content item 108 is paused (e.g., automatically upon switching to the interactive mode or in response to a pause command issued by the viewer selecting pause icon 708), the viewer may later unpause or continue progression of the media content item over the timeline. For example, the viewer may select a play icon 710, as shown in FIG. 7-FIG. 8. The media content item 110 then proceeds over the timeline from the current position of the virtual camera (or follows an object if attached) with any changes made to characteristics of the virtual scene. The media content item 110 is continued to be presented in the format and resolution for the interactive mode. The viewer may continue to move the virtual camera to view the content from different perspectives while the media content item 110 progresses. The viewer may further access the list of discovered story threads and/or the scene map to switch

between different story threads and their respective predefined virtual camera orientations or locations. In some embodiments, the viewer may perform other functions with respect to the timeline of the media content item 110, including rewinding or fast forwarding to different portions of the media content item 110.

While the media content item 110 is progressing in the interactive mode, the viewer may elect to return to the cinematic mode. For example, the viewer may provide input to the computing device 102 causing the media content item 110 to be returned to the cinematic mode. The computing device 102 may send a signal to the server 108 indicating that the media content item 110 is to be switched from the interactive mode to the cinematic mode. For example, the computing device 102 may send one or more signals to the server 108 (e.g., the rendering engine 1004 of the server 108, described below) instructing the rendering engine to return to rendering the media content item 110 using the director track. As a result, the server 108 may render images of the media content item 110 with the virtual camera returned to the cinematic perspective, including the location or perspective of the virtual camera just prior to entering the interactive mode. As such, the viewer may once again begin viewing the primary story thread from its associated predefined virtual camera orientations. The media content item 110 may further be presented in the default format and resolution for the cinematic mode and may include any of the minor characteristic changes made by the viewer. In some embodiments, the timeline may progress while in interactive mode, in which case the primary story thread may be shown from the current point in the timeline as opposed to the point at which the timeline was paused.

In order to compensate for the limited computational power of the computing device 102 and, if present, the display device 112 and the head-mounted device 104, the system 100 can be used to remotely render the media content item 110 in the different modes, as previously described. However, as a result of latency in the transmission and processing of the image frames of the media content item 110, the rendered images presented to a viewer may not match the current position of the viewer. For example, in virtual reality systems using the head-mounted device 104, the rendered images may not match the head orientation of the viewer. As a consequence, the viewer may have a poor and buggy virtual reality experience.

Accordingly, systems and techniques may be provided that compensate for the discrepancy in position of the viewer. In some examples, navigation inputs including positioning information (e.g., gesture input, sensor input, head orientation information, or other input) may be sent to the server 108 to control which images of the media content item 110 are rendered and from which virtual camera viewing perspective the images are rendered. The navigation inputs and positioning information may be sent by the computing device 102 or by the head-mounted device 104. For example, the computing device 102 may send initial positioning information of the computing device 102 and an associated position indicator to the server. The server 108 may use the initial positioning information to render images of the media content item 110 from the initial position or orientation perspective at which the computing device 102 is oriented. The server 108 may send the rendered images back to the computing device 102 (rendered from the initial position or orientation perspective) with the associated position indicator. The computing device 102 can then check updated positioning information to determine a current position or orientation of the computing device 102, and can

use the received associated position indicator, the initial positioning information, and the updated positioning information to modify the rendered image to shift the perspective of the rendered image to that of the updated positioning information. For example, the computing device **102** can use the position indicator to determine the positioning information that corresponds to the initial position or orientation depicted in the rendered images, and can compare the initial positioning information to the updated positioning information. The computing device **102** can modify the image based on the comparison, as described in more detail below.

FIG. 9 shows an example of the computing device **102** for use in sending information to the server **108** for remotely rendering images of the media content item **110**. In some embodiments, the computing device **102** may be in communication with the head-mounted device **104**. For example, the computing device **102** may include a mobile phone that is insertable in the head-mounted device **104**. The computing device **102** may receive a navigation input including positioning information from the head-mounted device **104**. The positioning information may include a position and/or orientation of the head-mounted device **104** (corresponding to a position and orientation of a user's head). The computing device **102** can process the information and send the processed information to the server **108** for rendering the images of the media content item **110**. In other embodiments, the head-mounted device **104** is not used (as indicated by the dotted box around the head-mounted device **104** in FIG. 9), in which case the computing device **102** performs all of the techniques described herein. For example, the computing device **102** can generate navigation inputs including positioning information corresponding to a position and/or orientation of the computing device **102**. In such an example, the computing device **102** can process the information and send the processed information to the server **108** for rendering the images of the media content item **110**. In yet other embodiments, the components **902**, **904**, **906**, **908**, **910**, and **912** of the computing device **102** may be contained in the head-mounted device **104**, in which case the head-mounted device **104** performs all of the techniques described herein.

The computing device **102** includes a positioning information detection engine **902** that can detect positioning information. In one example, the positioning information can be received from the head-mounted device **104**. The head-mounted device **104** may include a virtual reality system with one or more sensors. In this example, the detected positioning information includes a position and/or orientation of the head-mounted device **104**, which corresponds to the position and/or orientation of the viewer's head at a given point in time while watching the media content item **110**. In some examples, the head-mounted device **104** includes an accelerometer, a magnetometer, and a gyroscope that are used to determine the position and orientation of the head-mounted device **104** in the physical environment. The positioning information may include a set of rotations around three axes (e.g., the x, y, and z axes shown in FIG. 4) in a coordinate system (e.g., a right-handed or left-handed coordinate system), which may indicate an amount of yaw (around the y axis), an amount of pitch (around the x axis), and an amount of roll (around the z axis). For example, the gyroscope may provide a rate of rotation or angular velocity around each of the axes in radians per second. The head-mounted device **104** may periodically or continuously measure angular velocities over time, and may stream the measurements to the position information detection engine **902**. The gyroscope may provide an orientation

relative to a starting point, but may not provide the original orientation of the head-mounted device **104**. Further, the gyroscope may be subject to drift over time, in which case the head-mounted device **104** may be physically aligned in one orientation, but the virtual orientation is aligned in a slightly different orientation. The accelerometer may be used to estimate a gravity vector, and the magnetometer can be used to measure strength and direction of the magnetic field. The sensor information from the accelerometer and the magnetometer can be combined to correct for any drift in one or more of the axes of rotation using known techniques. The resulting positioning information may be provided to the positioning information detection engine **902**.

In another example, the positioning information can be generated by the computing device **102** itself. In such an example, the accelerometer, magnetometer, and gyroscope sensors may be contained on the computing device **102**, in which case the positioning information detection engine **902** may determine the positioning information of the viewer using sensor input information from the sensors similarly as that described above.

The computing device **102** may store a set of position indicators in the storage device **908**. The position indicator may include a color, a time stamp, a shape or other indicator that can be associated with particular positioning information. In one example, the computing device **102** can determine a time at which a particular set of positioning information (e.g., an x, y, z position and/or orientation) is detected. The mapping engine **904** may map or associate the positioning information with a time stamp corresponding to the time. In another example, the mapping engine **904** may select a color, a shape, or other reference object to associate with a given set of positioning information. The mapping engine **904** may then store the positioning information associated with the time stamp, color, shape, or the like in the storage device **908**. For example, the storage device **908** may include a table (e.g., an XML file or other file structure) including numerous sets of positioning information, with each set of positioning information being mapped to an associated position indicator (referred to as positioning information-position indicator pairs). In some embodiments, the computing device **102** may store a last x number of positioning information-position indicator pairs in the storage device **908**, such as the last five, ten, fifteen, or any other appropriate number of positioning information-position indicator pairs.

In one example, a positioning information-position indicator pair may include initial positioning information corresponding to a position and/or orientation of the computing device **102** or head-mounted device **104** at a given point in time, along with an associated position indicator. The output device **906** may transmit to the server **108** a signal including the initial positioning information and the associated position indicator. The output device **906** may include any suitable transmitter or transceiver that is configured to transmit wireless or wired communications signals.

FIG. 10 shows an example of the server **108**. The server **108** receives the signal including the initial positioning information and the associated position indicator using the input device **1002**. The input device **1002** may include any suitable receiver or transceiver that is configured to receive wireless or wired communications signals. The input device **1002** may provide the initial positioning information and the associated position indicator to the rendering engine **1004**. Using the received initial positioning information, the rendering engine **1004** can render one or more images (or image frames) with a perspective of a virtual camera within a

virtual environment of the media content item **110** that corresponds to the initial positioning information. For example, the positioning information may indicate that the computing device **102** or the head-mounted device **104** is physically oriented at a particular amount of yaw (around the y axis), pitch (around the x axis), and roll (around the z axis). The rendering engine **1004** may render the one or more images with the virtual camera adjusted to a corresponding yaw, pitch, and roll in the virtual environment. The server **108** may include hardware and software implementing a rendering algorithm for rendering the one or more images. The rendering algorithm may utilize the positioning information along with one or more scene files that contain objects in a defined language or data structure. Any suitable rendering algorithm may be used to process the positioning information and the scene file to render the images. A rendering algorithm may use one or more of rasterization techniques, ray casting techniques, ray tracing techniques, radiosity techniques, or other suitable techniques for rendering an image. In one example, the rendering algorithm used by the rendering engine **1004** may utilize rasterization with deferred shading and dynamic global illumination. In some embodiments, the rendering engine **1004** may include a graphics processing unit that can be used in addition to a central processing unit for rendering the images.

In some embodiments, the rendering engine **1004** may render the one or more images with the position indicator rendered with the image. For example, in the event the position indicator includes a color or shape, the rendering engine **1004** may insert the shape or color in a corner (or other location) of an image. By inserting the shape or color in the image, the computing device **102** can refer to the color or shape to determine the positioning information that corresponds to the position indicator. In some examples, the one or more images may be rendered with the position indicator by transmitting an $n \times n$ (e.g., 8×8 or other appropriate size) pixel region in a corner of an image. In some cases, the corner may be invisible when the image is viewed through the display screen due to distortion of the display device (e.g., the computing device, head-mounted device, or other display device). The position indicator may be rendered in the invisible corner of the image so that it is not viewable by a viewer of the media content item **110**. In one example, the $n \times n$ region may be an 8×8 pixel region that has one of sixteen shades of gray that can be used by the computing device **102** to determine the position indicator. While there may theoretically be 256 shades of gray possible for an 8×8 region, sixteen shades of gray may be used along with the shrunken 4×4 test region to be more error tolerant in cases in which the video compression or transmission degrades the signal. In other embodiments, the position indicator may include a time stamp. In such embodiments, the server **108** (e.g., the output device **1008** or other component not shown in FIG. **10**) may provide the time stamp along with the rendered images to the computing device **102**.

The rendering engine **1004** may send the rendered images to the compression engine **1006**. The compression engine **1006** applies a compression or coding technique to compress the images to a suitable format for transmission back to the computing device **102**. For example, one or more coding techniques may be implemented by the compression engine, including moving picture experts group (MPEG) encoding, advanced video coding (AVC), high efficiency video coding (HEVC), any extensions thereof, or a combination of the different coding standards. The output device **1008** may then transmit the compressed rendered images to the computing device **102**. The output device **1008** may include any suit-

able transmitter or transceiver that is configured to transmit wireless or wired communications signals. In some embodiments, the rendered images may be sent to the computing device **102** without being compressed. The position indicator is sent with the rendered images to the computing device **102**, either included in the images themselves or in addition to the images (as described above).

Returning to FIG. **9**, the input device **910** receives the one or more rendered images and the position indicator from the server **108**. The input device **910** may include any suitable receiver or transceiver that is configured to receive wireless or wired communications signals. In embodiments in which the rendered images are compressed, the computing device **102** may include any suitable decoding device that can decompress the images (e.g., an MPEG decoder, an AVC decoder, an HEVC decoder, or other suitable decoding device).

The computing device **102** may identify the position indicator in the received rendered images (in embodiments in which the position indicator is rendered in the image), or provided along with the received rendered images (in embodiments in which the position indicator is sent along with the rendered images). For example, as described above, the position indicator may be rendered in an image by transmitting an $n \times n$ pixel region in a corner of an image (e.g., in an invisible corner of the image). In an example in which the $n \times n$ region is an 8×8 pixel region that has one of sixteen shades of gray, the computing device **102** can analyze an inner 4×4 group of pixels of the 8×8 region and can average the pixels. The computing device **102** then rounds to the closest of the sixteen possible gray values to determine which position indicator is in the image.

Once the position indicator is identified, the computing device **102** may access the storage device **908** using the position indicator to retrieve the initial positioning information that corresponds to the position indicator. For example, the computing device **102** (e.g., the image modification engine **912**, the mapping engine **904**, or other component of the computing device **102** not shown in FIG. **9**) may refer to the table of positioning information-position indicator pairs to identify the entry that includes the associated position indicator. The computing device **102** may select the positioning information that corresponds to the associated position indicator. Accordingly, the position indicator allows the computing device **102** to easily determine which position information corresponds to the position or orientation of a virtual camera in a given image.

The computing device **102** may determine updated positioning information that corresponds to a current position or orientation of the computing device **102** or head-mounted device **104**. The computing device **102** (e.g., the image modification engine **912**) may estimate a change in the received image frame based on the updated positioning information and the initial positioning information. In some examples, a difference between the currently measured orientations and/or positions (the updated positioning information) and the previously transmitted orientations and/or positions (the initial positioning information) can be calculated using vector analysis. For example, a difference between two matrices may be determined by multiplying the inverse of one matrix by another matrix. For example, a first matrix may represent the previously transmitted orientation and/or position, and a second matrix may represent the currently measured orientation and/or position. The inverse of the first matrix can be multiplied by the second matrix to determine the difference between the two matrices, and thus the difference between the initial and updated positioning

information. Alternatively, the inverse of the second matrix can be multiplied by the first matrix to determine the difference between the two matrices. A difference matrix can be generated by the computing device **102** representing the difference between the two matrices. In some embodiments when orientation is the only difference, quaternions may be used instead of matrices. In some embodiments, an amount of time that has passed between when the initial positioning information was detected and when the rendered image is received may be taken into account by the image modification engine **912** to determine how much to modify the rendered frame.

The image modification engine **912** can then modify the received rendered images based on the estimated change. The image modification engine **912** may include a graphics processing unit or other processing unit that can modify properties of image frames. In some examples, the image modification engine **912** may construct a modified image frame by shifting or modifying portions of the received image frame to correct for a change or movement in position and/or orientation (e.g., by the computing device **102**, head-mounted device **104**, or other device indicating a position and/or orientation of the user) that occurred after an image was rendered. In one example, the image modification engine **912** may construct a three-dimensional vector through every pixel (from the 2-D pixel coordinate) of the undistorted source image. The image modification engine **912** may multiply the three-dimensional vector by the difference matrix (described above), and may then transform the three-dimensional vector into a new two-dimensional pixel position in the distorted output image. By shifting portions of the image frame, latency perceived by a viewer of the media content item **110** can be reduced or eliminated. In another example, the image modification engine **912** may construct a modified image frame by combining the received image frame with other previously received image frames that include portions of the virtual scene that are viewable based on the current head orientation. The previously received images may be stored in a cache or buffer storage device. The modified image may then be presented to the viewer for viewing on the computing device **102**, the head-mounted device **104**, or other display device.

In some instances, an image frame rendered by the rendering engine **1004** of the server **108** may be larger than what is viewable on computing device **102** or head-mounted device **104**. For example, the rendering engine **1004** may render such larger images to allow for shifting of the image to compensate for head movement. For example, if the viewer moves the computing device **102** or head-mounted device **104** quickly in a certain direction to arrive at a particular position, the frame that is being viewed may not have enough information for the viewer to view image data at the particular position. As a result, the viewer may be presented with a black region. The same black region may occur if a long period of latency occurs between when the computing device **102** or head-mounted device **104** sends the positioning information and when the rendered images are received. The rendering engine **1004** may render an image a certain amount surrounding the viewer's point of view (e.g., 10 degrees to the left, 10 degrees to the right, 10 degrees above, and 10 degrees below the viewer's point of view). The size of the frame that is rendered may be dynamically changed based on a detected amount of latency between the computing device **102** or head-mounted device **104** and the server **108**.

The above-described systems and devices provide content with different modes and interactive options, while compen-

sating for latency issues that arise in certain situations. Various processes will now be described that can utilize the above-described systems and devices.

FIG. **11A** and FIG. **11B** illustrate an example of a process **1100** of switching modes associated with a media content item displayed on a computing device. Process **1100** is illustrated as a logical flow diagram, the operation of which represents a sequence of operations that can be implemented in hardware, computer instructions, or a combination thereof. In the context of computer instructions, the operations represent computer-executable instructions stored on one or more computer-readable storage media that, when executed by one or more processors, perform the recited operations. Generally, computer-executable instructions include routines, programs, objects, components, data structures, and the like that perform particular functions or implement particular data types. The order in which the operations are described is not intended to be construed as a limitation, and any number of the described operations can be combined in any order and/or in parallel to implement the processes.

Additionally, the process **1100** may be performed under the control of one or more computer systems configured with executable instructions and may be implemented as code (e.g., executable instructions, one or more computer programs, or one or more applications) executing collectively on one or more processors, by hardware, or combinations thereof. The code may be stored on a computer-readable storage medium, for example, in the form of a computer program comprising a plurality of instructions executable by one or more processors. The computer-readable storage medium may be non-transitory.

In some aspects, the process **1100** may be performed by a computing device, such as the computing device **102**, the head-mounted device **104**, or the display device **112**.

At **1102**, the process **1100** includes receiving, by the computing device while operating in a cinematic mode, a set of images of the media content item. The received set of images is rendered by a cloud server that is different from the computing device. The media content item is in a cinematic mode when the set of images are received, in which case the received set of images includes a predefined cinematic perspective of a virtual camera within a virtual environment of the media content item.

At **1104**, the process **1100** includes presenting, by the computing device while operating in the cinematic mode, the media content item in a first format and in a passive manner in which user control of the virtual camera within the virtual environment of the media content item is not enabled. The first format may include a particular frame rate, resolution, aspect ratio, or other format. The first format may also include one or more letterbox bars.

At **1106**, the process **1100** includes receiving, by the computing device, input corresponding to a user command to switch from operation in the cinematic mode to operation in an interactive mode. The input may include a touchscreen input, a keypad input, a gesture input, or any other suitable input command. At **1108**, the process **1100** includes switching, by the computing device, from operation in the cinematic mode to operation in the interactive mode in which user control of the virtual camera within the virtual environment of the media content item is enabled and the media content item is presented in a second format different from the first format. The second format may include a different frame rate, resolution, aspect ratio, or other format that is different from the first format. In some embodiments, the first format is the same as the second format, in which case

the media content item is presented in the same format in the cinematic and interactive modes. The second format may also include no letterbox bars.

At **1110**, the process **1100** includes receiving, by the computing device while operating in the interactive mode, input corresponding to a navigation command for controlling navigation of the virtual camera within the virtual environment. The input includes initial positioning information for the computing device. In some embodiments, the input includes a gesture input. In some embodiments, the input includes sensor information indicating a movement of the computing device.

At **1112**, the process **1100** includes associating the initial positioning information with a position indicator. In some embodiments, the position indicator includes a time stamp, a color, a shape, or other indicator that can be associated with particular positioning information. For example, the computing device may store a set of position indicators in a storage device, as described above. At **1114**, the process **1100** includes storing the initial positioning information in association with the position indicator in the storage device. For example, the storage device may include a table (e.g., an XML, file or other file structure) including numerous sets of positioning information, with each set of positioning information being mapped to an associated position indicator (referred to as positioning information-position indicator pairs). In some embodiments, the computing device may store a last x number of positioning information-position indicator pairs in the storage device, including any appropriate number of positioning information-position indicator pairs.

At **1116**, the process **1100** includes transmitting a signal corresponding to the navigation command to the cloud server. The signal includes the initial positioning information and the position indicator. The cloud server may use the initial positioning information to render images with a perspective of a virtual camera within a virtual environment of the media content item that corresponds to the initial positioning information. At **1118**, the process **1100** includes receiving image data from the cloud server, the image data including the position indicator and an image rendered by the cloud server corresponding to the initial positioning information.

At **1120**, the process **1100** includes determining updated positioning information for the computing device. At **1122**, the process **1100** includes retrieving the initial positioning information from the storage device based on the position indicator. In some embodiments, the process **1100** may further include storing, in the storage device, a plurality of sets of positioning information in association with corresponding position indicators. Each set of positioning information is associated with a separate position indicator in the storage device. The process **1100** may further include identifying the position indicator in the received image data. Retrieving the initial positioning information from the storage device based on the position indicator may include identifying a set of positioning information from the plurality of sets that is stored in association with the initial positioning information in the storage device.

At **1124**, the process **1100** includes modifying, by the computing device, the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information. For example, the computing device may estimate a change in the received image frame based on the updated positioning information

and the initial positioning information using the techniques described above. In some embodiments, the received image is modified to compensate for a difference in positioning information between the initial positioning information and the updated positioning information. For example, the computing device may construct a modified image frame by shifting or modifying portions of the received image frame to correct for a change or movement in position and/or orientation by the computing device or other device (e.g., a head-mounted device, or other device indicating a position and/or orientation of the user) that occurred after an image was rendered.

At **1126**, the process **1100** includes presenting, by the computing device while operating in the interactive mode, the additional image corresponding to the updated positioning information.

In some embodiments, the media content item is automatically paused at a first time of a timeline associated with the media content item when the computing device switches from operation in the cinematic mode to operation in the interactive mode. In some embodiments, the interactive mode allows control of a timeline of the media content item.

In some embodiments, the process **1100** includes switching operation of the computing device from the interactive mode to the cinematic mode, wherein the virtual camera returns to the predefined cinematic perspective from a user controlled perspective when the computing device is switched from operation in the interactive mode to operation in the cinematic mode.

In some embodiments, the process **1100** includes receiving input corresponding to selection of a location bookmark. The location bookmark corresponds to a location within the virtual environment. The process **1100** may further include transmitting a signal corresponding to the location bookmark to the cloud server, and receiving at least one image of the media content item from the cloud server. The at least one image includes a perspective of the virtual camera at the location within the virtual environment based on the location bookmark. The process **1100** may further include presenting the at least one image of the media content item.

In some embodiments, the process **1100** includes pausing the media content item when the computing device is switched from operation in the cinematic mode to operation in the interactive mode, receiving input corresponding to selection of an object within the virtual environment, transmitting a signal corresponding to the selection of the object to the cloud server, and receiving at least one image of the media content item from the cloud server. The at least one image includes a perspective of the virtual camera from a point of view of the object. The method **1100** may further include unpausing the media content item to present the at least one image of the media content item. In some embodiments, selection of the object includes moving the virtual camera a threshold distance from the object.

FIG. 12A and FIG. 12B illustrate an example of a process **1200** of navigating a virtual environment of a media content item using a computing device. Process **1200** is illustrated as a logical flow diagram, the operation of which represents a sequence of operations that can be implemented in hardware, computer instructions, or a combination thereof. In the context of computer instructions, the operations represent computer-executable instructions stored on one or more computer-readable storage media that, when executed by one or more processors, perform the recited operations. Generally, computer-executable instructions include routines, programs, objects, components, data structures, and the like that perform particular functions or implement

particular data types. The order in which the operations are described is not intended to be construed as a limitation, and any number of the described operations can be combined in any order and/or in parallel to implement the processes.

Additionally, the process **1200** may be performed under the control of one or more computer systems configured with executable instructions and may be implemented as code (e.g., executable instructions, one or more computer programs, or one or more applications) executing collectively on one or more processors, by hardware, or combinations thereof. The code may be stored on a computer-readable storage medium, for example, in the form of a computer program comprising a plurality of instructions executable by one or more processors. The computer-readable storage medium may be non-transitory.

In some aspects, the process **1200** may be performed by a computing device, such as the computing device **102**, the head-mounted device **104**, or the display device **112**.

At **1202**, the process **1200** includes receiving, by the computing device, a set of images of the virtual environment of the media content item. The received set of images is rendered by a cloud server that is different from the computing device. At **1204**, the process **1200** includes presenting, by the computing device, the set of images of the virtual environment.

At **1206**, the process **1200** includes receiving, by the computing device, a sensor input in response to movement of the computing device. The sensor input corresponds to a navigation command for controlling navigation of a virtual camera within the virtual environment. The sensor input is received from at least one of an accelerometer, a gyroscope, a depth sensor, or a global positioning system sensor of the computing device.

At **1208**, the process **1200** includes determining initial positioning information based on the sensor input. At **1210**, the process **1200** includes associating the initial positioning information with a position indicator. In some embodiments, the position indicator includes a time stamp, a color, a shape, or other indicator that can be associated with particular positioning information. For example, the computing device may store a set of position indicators in a storage device, as described above. At **1212**, the process **1200** includes storing the initial positioning information in association with the position indicator in the storage device. For example, the storage device may include a table (e.g., an XML file or other file structure) including numerous sets of positioning information, with each set of positioning information being mapped to an associated position indicator (referred to as positioning information-position indicator pairs). In some embodiments, the computing device may store a last x number of positioning information-position indicator pairs in the storage device, including any appropriate number of positioning information-position indicator pairs.

At **1214**, the process **1200** includes transmitting a signal corresponding to the navigation command to the cloud server. The signal includes the initial positioning information and the position indicator. The cloud server may use the initial positioning information to render images with a perspective of a virtual camera within a virtual environment of the media content item that corresponds to the initial positioning information. At **1216**, the process **1200** includes receiving image data from the cloud server. The image data includes the position indicator and an image rendered by the cloud server corresponding to the initial positioning information.

At **1218**, the process **1200** includes determining updated positioning information for the computing device. At **1220**, the process **1200** includes retrieving the initial positioning information from the storage device based on the position indicator. In some embodiments, the process **1200** includes storing, in the storage device, a plurality of sets of positioning information in association with corresponding position indicators. Each set of positioning information being associated with a separate position indicator in the storage device. The process **1200** may further include identifying the position indicator in the received image data. Retrieving the initial positioning information from the storage device based on the position indicator may include identifying a set of positioning information from the plurality of sets that is stored in association with the initial positioning information in the storage device.

At **1222**, the process **1200** includes modifying, by the computing device, the received image rendered by the cloud server based on the received position indicator, the retrieved initial positioning information, and the updated positioning information to generate an additional image corresponding to the updated positioning information. For example, the computing device may estimate a change in the received image frame based on the updated positioning information and the initial positioning information using the techniques described above. In some embodiments, the received image is modified to compensate for a difference in positioning information between the initial positioning information and the updated positioning information. For example, the computing device may construct a modified image frame by shifting or modifying portions of the received image frame to correct for a change or movement in position and/or orientation by the computing device or other device (e.g., a head-mounted device, or other device indicating a position and/or orientation of the user) that occurred after an image was rendered.

At **1224**, the process **1200** includes presenting, by the computing device, the additional image corresponding to the updated positioning information.

In some embodiments, a position of the virtual camera is mapped to a physical position and orientation of the computing device using the sensor input. For example, the computing device or server may associate or map movement of the computing device in the physical world to movement through the virtual environment of the media content item. A physical position and orientation of the computing device at a first point in time may be treated as an origin. As the simulated movement through the virtual environment continues in time, differences in position and/or orientation between the origin position and orientation at the first point in time and later positions and/or orientations may be used to translate and rotate the virtual camera. In some instances, the computing device or server may perform a direct association between the virtual camera and the current physical position and/or orientation of the computing device. In other instances, the computing device or server may perform an association between the virtual camera and the current physical position and/or orientation of the computing device based on the virtual scene and the physical environment in which the viewer is located.

Using the above-described systems and techniques, viewers of content may be presented with various interactive options, while allowing the content to be rendered remotely to reduce the burden on computing devices used to display and control the content. Furthermore, techniques are provided to allow the remote rendering to compensate for latency.

Referring to FIG. 13, a schematic diagram is shown of an example of a computer system 1300. This system is exemplary only and one having skill in the art will recognize that variations and modifications are possible. The system 1300 can be used for the operations described above. For example, the computer systems shown in FIG. 13 may be used to implement any or all of the initialization (e.g., face annotation, skull fitting, constraint creation) and stabilization (e.g., skin energy or error determination, nose energy or error determination) techniques and routines described herein.

The system 1300 includes a processor 1310, a memory 1320, a storage device 1330, and an input/output interface 1340. Each of the components 1310, 1320, 1330, and 1340 are interconnected using a system bus 1350. The processor 1310 is capable of processing instructions for execution within the system 1300. In one implementation, the processor 1310 is a single-threaded processor. In another implementation, the processor 1310 is a multi-threaded processor. The processor 1310 is capable of processing instructions stored in the memory 1320 or on the storage device 1330 to provide graphical information via input/output interface 1340 for display on a user interface of one or more input/output device 1360.

The memory 1320 stores information within the system 1300 and may be associated with various characteristics and implementations. For example, the memory 1320 may include various types of computer-readable medium such as volatile memory, a non-volatile memory and other types of memory technology, individually or in combination.

The storage device 1330 is capable of providing mass storage for the system 1300. In one implementation, the storage device 1330 is a computer-readable medium. In various different implementations, the storage device 1330 may be a floppy disk device, a hard disk device, an optical disk device, or a tape device.

The input/output device 1360 provides input/output operations for the system 1300. In one implementation, the input/output device 1360 includes a keyboard and/or pointing device. In another implementation, the input/output device 1360 includes a display unit for displaying graphical user interfaces.

The features described can be implemented in digital electronic circuitry, or in computer hardware, firmware, software, or in combinations of them. The apparatus can be implemented in a computer program product tangibly embodied in an information carrier, e.g., in a machine-readable storage device, for execution by a programmable processor; and method steps can be performed by a programmable processor executing a program of instructions to perform functions of the described implementations by operating on input data and generating output. The described features can be implemented advantageously in one or more computer programs that are executable on a programmable system including at least one programmable processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. A computer program is a set of instructions that can be used, directly or indirectly, in a computer to perform a certain activity or bring about a certain result. A computer program can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment.

Suitable processors for the execution of a program of instructions include, by way of example, both general and special purpose microprocessors, and the sole processor or one of multiple processors of any kind of computer. Generally, a processor will receive instructions and data from a read-only memory or a random access memory or both. The essential elements of a computer are a processor for executing instructions and one or more memories for storing instructions and data. Generally, a computer will also include, or be operatively coupled to communicate with, one or more mass storage devices for storing data files; such devices include magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and optical disks. Storage devices suitable for tangibly embodying computer program instructions and data include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, ASICs (application-specific integrated circuits).

To provide for interaction with a user, the features can be implemented on a computer having a display device such as a CRT (cathode ray tube), LCD (liquid crystal display), LED (light emitting diode) monitor for displaying information to the user and a keyboard and a pointing device such as a mouse or a trackball by which the user can provide input to the computer.

The features can be implemented in a computer system that includes a back-end component, such as a data server, or that includes a middleware component, such as an application server or an Internet server, or that includes a front-end component, such as a client computer having a graphical user interface or an Internet browser, or any combination of them. The components of the system can be connected by any form or medium of digital data communication such as a communication network. Examples of communication networks include, e.g., a LAN, a WAN, and the computers and networks forming the Internet.

The computer system can include clients and servers. A client and server are generally remote from each other and typically interact through a network, such as the described one. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other. Although a few implementations have been described in detail above, other modifications are possible.

In addition, the logic flows depicted in the figures do not require the particular order shown, or sequential order, to achieve desirable results. In addition, other steps may be provided, or steps may be eliminated, from the described flows, and other components may be added to, or removed from, the described systems. Accordingly, other implementations are within the scope of the following claims.

Where components are described as being configured to perform certain operations, such configuration can be accomplished, for example, by designing electronic circuits or other hardware to perform the operation, by programming programmable electronic circuits (e.g., microprocessors, or other suitable electronic circuits) to perform the operation, or any combination thereof.

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the scope of the invention.

What is claimed is:

1. A computer-implemented method of exploring a virtual environment presented in an interactive mode of a media content item using a computing device, the method comprising:

receiving an input to switch from a cinematic mode, in which a primary story thread of the media content item is displayed, to the interactive mode of the media content item, the input causing the media content item to pause a timeline of the media content item;

receiving a selection of an asset in a scene of the virtual environment while a display of the media content item is paused, wherein the asset is a virtual character, wherein the selection of the asset assigns a virtual camera to follow the asset;

receiving, by the computing device, a first set of images of the virtual environment of the media content item, the first set of images having been rendered by a cloud server;

determining initial positioning information based on a position of the asset in the virtual environment;

presenting, by the computing device, the first set of images of the virtual environment, the first set of images representing a first perspective position of the asset in the virtual environment of the media content item;

detaching the virtual camera from the asset by receiving an input from an interface of the computing device, the input causing the virtual camera to move away from the selected asset to a desired location in the virtual environment;

receiving an input to resume playing the timeline of the media content item;

receiving image data from the cloud server, the image data including a position indicator for the selected asset and one or more second images rendered by the cloud server based upon the position indicator, wherein the one or more second images are from an updated position of the asset in the virtual environment, following a movement of the asset as the asset moves during playback of the media content item; and presenting, by the computing device, the one or more second images.

2. The method of claim 1, wherein the asset may be selected by receiving one or more control inputs for the virtual camera moves the virtual camera within a threshold distance from the asset in the virtual environment.

3. The method of claim 1, wherein the virtual camera enables an interactive mode in a game of the media content item, wherein a storyline of a movie of the media content item varies according to an outcome of the game.

4. The method of claim 1, wherein the virtual camera follows the asset from a pre-defined distance at a pre-defined orientation.

5. The method of claim 1, further comprising detaching the virtual camera from the asset by receiving a second selection of a second virtual asset in the virtual environment.

6. A computing device for exploring a virtual environment presented in an interactive mode of a media content item using a computing device, the computing device comprising:

a memory storing one or more instructions; and one or more processors configured to execute the one or more instructions stored in the memory to perform operations comprising:

receiving an input to switch from a cinematic mode, in which a primary story thread of the media content item

is displayed, to the interactive mode of the media content item, the input causing the media content item to pause a timeline of the media content item;

receiving a selection of an asset in a scene of the virtual environment while a display of the media content item is paused, wherein the asset is a virtual character, wherein the selection of the asset assigns a virtual camera to follow the asset;

receiving, by the computing device, a first set of images of the virtual environment of the media content item, the first set of images having been rendered by a cloud server;

determining initial positioning information based on a position of the asset in the virtual environment;

presenting, by the computing device, the first set of images of the virtual environment, the first set of images representing a first perspective position of the asset in the virtual environment of the media content item;

detaching the virtual camera from the asset by receiving an input from an interface of the computing device, the input causing the virtual camera to move away from the selected asset to a desired location in the virtual environment;

receiving an input to resume playing the timeline of the media content item;

receiving image data from the cloud server, the image data including a position indicator for the selected asset and one or more second images rendered by the cloud server based upon the position indicator, wherein the one or more second images are from an updated position of the asset in the virtual environment, following a movement of the asset as the asset moves during playback of the media content item; and presenting, by the computing device, the one or more second images.

7. The computing device of claim 6, wherein the asset may be selected by receiving one or more control inputs for the virtual camera moves the virtual camera within a threshold distance from the asset in the virtual environment.

8. The computing device of claim 6, wherein the virtual camera enables an interactive mode in a game of the media content item, wherein a storyline of a movie of the media content item varies according to an outcome of the game.

9. The computing device of claim 6, wherein the virtual camera follows the asset from a pre-defined distance at a pre-defined orientation.

10. The computing device of claim 6, further comprising additional instructions stored in the memory, the additional instructions when executed by the one or more processors perform operations comprising detaching the virtual camera from the asset by receiving a second selection of a second virtual asset in the virtual environment.

11. A non-transitory computer-readable memory storing a plurality of instructions executable by one or more processors of a computing device, the plurality of instructions comprising:

instructions that cause the one or more processors to receive an input to switch from a cinematic mode, in which a primary story thread of a media content item is displayed, to an interactive mode of a media content item, the input causing the media content item to pause a timeline of the media content item;

instructions that cause the one or more processors to receive a selection of an asset in a scene of a virtual environment of the media content item while a display of the media content item is paused, wherein the asset

is a virtual character, wherein the selection of the asset assigns a virtual camera to follow the asset;

instructions that cause the one or more processors to receive, by the computing device, a first set of images of the virtual environment of the media content item, the first set of images having been rendered by a cloud server;

instructions that cause the one or more processors to determine initial positioning information based on a position of the asset in the virtual environment;

instructions that cause the one or more processors to present, by the computing device, the first set of images of the virtual environment, the first set of images representing a first perspective position of the asset in the virtual environment of the media content item;

instructions that cause the one or more processors to detach the virtual camera from the asset by receiving an input from an interface of the computing device, the input causing the virtual camera to move away from the selected asset to a desired location in the virtual environment;

instructions that cause the one or more processors to receive an input to resume playing the timeline of the media content item;

instructions that cause the one or more processors to receive image data from the cloud server, the image data including a position indicator for the selected asset and one or more second images rendered by the cloud

server based upon the position indicator, wherein the one or more second images are from an updated position of the asset in the virtual environment, following a movement of the asset as the asset moves during playback of the media content item; and

instructions that cause the one or more processors to present, by the computing device, the one or more second images.

12. The non-transitory computer-readable memory of claim 11, wherein the asset may be selected by receiving one or more control inputs for the virtual camera moves the virtual camera within a threshold distance from the asset in the virtual environment.

13. The non-transitory computer-readable memory of claim 11, wherein the virtual camera enables an interactive mode in a game of the media content item, wherein a storyline of a movie of the media content item varies according to an outcome of the game.

14. The non-transitory computer-readable memory of claim 11, wherein the virtual camera follows the asset from a pre-defined distance at a pre-defined orientation.

15. The non-transitory computer-readable memory of claim 11, further comprising instructions that cause the one or more processors to detach the virtual camera from the asset by receiving a second selection of a second virtual asset in the virtual environment.

* * * * *