



(72) BAUMANN, James A., US


(71) MI-JACK PRODUCTS INC., US

(51) Int.Cl.⁶ B66C 1/62, B66C 13/46, B66C 19/00

(30) 1998/03/17 (09/042,934) US

(54) **DISPOSITIF EXTENSIBLE ET REGLABLE D'ELEVATION
D'UNE CHARGE**

(54) **ADJUSTABLE, EXPANSIBLE LOAD LIFTING DEVICE**



(57) An adjustable system for lifting and transferring load containers which comprises a frame, a container lifting device, and a cable attached to the frame and lifting device. A first actuator is provided for raising and lowering the lifting device, which lifting device has a plurality of remotely controllable latches for engaging and disengaging latchable portions of the containers, to permit grasping and lifting of containers by the lifting device. New features of adjustability are provided, to permit the system to lift containers of varying sizes. Also, the lifting device preferably carries an electrically operated location sensing device for sensing and signalling to the operator a proper location of the latches relative to the latchable portions, to permit such latching.

ADJUSTABLE, EXPANSIBLE LOAD LIFTING DEVICE

ABSTRACT OF THE DISCLOSURE

An adjustable system for lifting and transferring load containers which comprises a frame, a container lifting device, and a cable attached to the frame and lifting device. A first actuator is provided for raising and lowering the lifting device, which lifting device has a plurality of remotely controllable latches for engaging and disengaging latchable portions of the containers, to permit grasping and lifting of containers by the lifting device. New features of adjustability are provided, to permit the system to lift containers of varying sizes. Also, the lifting device preferably carries an electrically operated location sensing device for sensing and signalling to the operator a proper location of the latches relative to the latchable portions, to permit such latching.

ADJUSTABLE, EXPANSIBLE LOAD LIFTING DEVICE

Inventor: James A. Baumann

BACKGROUND OF THE INVENTION

Grappler systems for the picking up and transferring of loads are disclosed, for example, in Lanigan et al. U.S. Patent Nos. 4,546,891; 4,667,834; 4,715,762; and 5,415,517, among others.

These devices are particularly adapted to pick up and move containers such as large metal shipping or load containers and even truck trailers (which are included in the term "containers"). Also, the devices of the previous patents include grapplers which are capable of gripping and lifting more than one container in a stack, to transfer several containers at once.

By this invention, systems for lifting and transferring load containers are improved, in that they can vary the dimensions of the distribution of the lifting latches carried by the system, so that containers of differing sizes may be lifted and moved. Also, a system is provided for facilitating alignment of the lifting latches with apertures on the load containers, so that the load containers may be reliably, easily, and safely gripped for lifting without the need for close-up visual adjustment. Rather, the operator in the cab of

the system can quickly and effectively make such latching contact with various sizes of containers.

Also, the system of this invention may be folded up for travel into a relatively compact unit, permitting easier shipping and the like.

DESCRIPTION OF THE INVENTION

By this invention, a system is provided for lifting and transferring load containers. The system comprises a frame, a container lifting device or spreader, a cable or chain attached to the frame and lifting device, and a first actuator, typically an electric motor, for raising and lowering the lifting device. The lifting device has a plurality of remotely controllable latches (typically controllable from the operating cab) for engaging and disengaging latchable portions of the containers, to permit grasping, lifting, and moving of the containers by the lifting device.

Preferably, a second actuator is provided to horizontally move the container lifting device, to provide it with two dimensions of motion. The lifting device may also be on wheels to provide a third horizontal dimension of motion for the moving of loads from one desired location to another.

Also, at least some of the latches may be

carried on vertically extendible and retractable legs, which permits a stack of at least two containers to be carried by the latches and the container lifting device. Preferably, the vertically extendible and retractable legs also have horizontally extendible and retractable portions, so that the container lifting device may be retracted into a compact unit, and it may also be variably extended to lift single containers and stacks of containers of varying sizes.

Other latches may be positioned above the latches carried on the vertically extendible and retractable legs, the other latches being positioned to vertically engage latchable portions positioned on container top walls. Thus the device of this invention can be a "top pick" lifting device, and it can also engage containers from the side to lift them. Thus, the top container in a stack may be engaged by the latches which engage the container top walls, while lower containers in a stack may be engaged by other latches at their sidewalls, so that the entire stack can be lifted. The other, vertically-facing latches may also be carried on horizontally extendible and retractable portions of the assemblies in order to fit containers of varying size.

The lifting system of this invention also defines a transverse telescoping member which is capable

of adjusting the horizontal width of the vertically extendible and retractable legs which carry latches for gripping a load. This enhances the adjustment capability for gripping containers of differing sizes, while also permitting compact stowage. For example, in one embodiment, the vertically extendible and retractable assemblies may be horizontally adjusted to permit engagement of loads having a width of 96 to 102 inches.

Specifically, the vertically extendible and retractable legs may comprise vertically extendable and retractable telescoping rods or tubes which carry latches adjacent their ends for engagement with containers positioned substantially below the bulk of the lifting and load transferring system of this invention. These vertical telescoping members may also be vertically moved as a whole to accommodate differing predetermined container heights, ranging for example from eight feet six inches to nine feet six inches. This can be accomplished by a plurality of lift cylinders to provide desired adjustability to the entire vertically extendible and retractable assembly so that the latches may engage containers of differing heights. Thus, the vertical telescoping rods or tubes may be fully extended, and still they may be vertically adjustable by the lift cylinders to engage the latchable portions of containers of different sizes.

The horizontal width of the lifting system of this invention is at least partially controlled by rotatable arms which are connected to the vertically extendible and retractable legs or assemblies, to move the legs horizontally inwardly and outwardly. The container lifting device may thus be variably extended to lift containers and stacks of containers of varying sizes.

Preferably, each rotatable arm further comprises a pair of laterally spaced, generally parallel arm portions. At least one of the arm portions is pivotally connected to the rest of the rotatable arm at one end, and each of the arm portions is pivotally connected at another end to one of the legs in laterally spaced manner to form a parallelogram-type linkage that holds the leg in vertical position while the arm moves through a variety of rotational positions. Thus, the legs are spontaneously held in a vertical position while the arms rotate to move the legs inwardly and outwardly between a compact travelling position and an extended position.

Thus, a lifting and load transferring system is provided, the system being highly adjustable to accommodate differing types of load containers such as semi-trailers, containerized steel boxes, and the like. The loads may be engaged with the latches of the spreader

or spreaders used for lifting, with the fine adjustment being performed at the control panel of the lifting and load transferring system, without the need for assistance because of the latch location sensing device described herein.

DESCRIPTION OF THE DRAWINGS

In the drawings, Fig. 1 is an elevational view of the load lifting and transferring system of this invention;

Fig. 2 is a detailed perspective view of the spreader of this invention shown in Fig. 1, but with the spreader shown in its compact, closed-up, travelling position;

Fig. 3 is a perspective view of the spreader of Fig. 2, shown in an unfolded position for gripping a pair of stacked rectangular containers;

Fig. 4 is an end elevational view of the spreader of this invention in the configuration of Fig. 2;

Fig. 5 is an end elevational view of the

spreader as shown in Fig. 3;

Fig. 6 is an enlarged, longitudinal sectional view of a location sensing device carried by the lifting and load transferring system of this invention;

Fig. 7 is a sectional view taken along line 7-7 of Fig. 9; and

Fig. 8 is an enlarged, elevational view, taken partly in section, of an alternate design of latch member which may be carried by the lifting and load transferring system of this invention.

DESCRIPTION OF SPECIFIC EMBODIMENTS

Referring to the drawings, Figs. 1-3 show the load transferring and lifting system 10 of this invention which comprises a frame 12 having a platform 14 and legs 16, which are carried on road wheels 18 or rail wheels as desired. Platform 14 carries an operating cabin 20 and a generally conventional winding system for cable 22. Two pairs of cable loops are typically used to suspend the spreader 24 of this invention, which is used to grip containers or any other desired load as they are elevated and shifted.

By the term "cable", it is also intended to include the optional use of chains, rope, or the like in a similar, conventional manner for holding spreader 24. Basically, the lifting and load transferring system shown herein may be conventional except for the design of spreader 24.

Spreader 24 may be horizontally moved by the traversing mechanism 26 carried on elevated platform 14. Capstans 28 are powered to wind and unwind one end of each of cable loops 22 to raise or lower spreader 24 as may be desired. A power system may also be provided to propel the system on its wheels 18, so that the spreader can be moved through three dimensions to pick up and deposit loads in the desired positions.

Referring particularly to Figs. 2 and 4, spreader 24 is shown in a folded-up travel position of minimum volume. Spreader 24 defines a pair of end bars 30 which carry at their respective ends latches 32 which point downwardly, so that the respective four latches at the respective ends of each of end bars 30 can engage latchable recesses 34 positioned in the top of a rectangular container load 36, one latching site being positioned at each corner thereof.

Thus, in the folded configuration of Figs. 2 and 4, spreader 24 comprises a "top pick" spreader. Container 36 may be lifted by spreader 24 of system 10,

horizontally transferred, and then deposited in another desired location. The width between legs 16 of system 10 as shown in Fig. 1 is typically enough to accommodate two or more railroad cars, trucks, or even barges in a manner similar to the disclosures of the last cited patent above, to greatly facilitate the shifting of loads between various vehicles.

Spreader 24 also carries the conventional cable wheels 38 for engagement with cable loops 22 to accomplish its load lifting purpose. Load stabilizers 40 are shown in Figs. 2 and 4 in an upward, folded position out of the way for transport or when otherwise not needed. Their position of use is shown in Figs. 3 and 5, when the load stabilizers 40 are pivoted and locked downwardly to engage and stabilize the corners of container 36, to facilitate centering and lateral support of the container as it is being carried by spreader 24.

Latching devices 32 may incorporate an electrically operated location sensing device as generally described below.

Spreader 24 also defines vertically extensible and retractable telescoping tubes or legs 42 which carry side bars 44, permitting them to be vertically depressed and raised between the respective positions shown in Figs. 2 and 3. A central, vertical telescoping tube 46 of rectangular cross section is shown, positioned between

a pair of cylindrical telescoping tubes or legs 42 for a desired load bearing capability. Also, telescoping tube 46 may comprise part of a hydraulic system for raising and lowering side bars 44.

Side bars 44, carried by legs 42, in turn carry horizontally facing latches 48, which may also incorporate an electrically operated location sensing device as described in detail below. Telescoping tubes 42, 46 and side bars 44 may comprise individual assemblies which may be moved horizontally inwardly and outwardly by means of rotating arms 50, controlled by hydraulic cylinders 51. Transverse scroll member 52 (Fig. 5) provides added transverse telescoping to the legs 42 and arms 50, moving the respective assemblies horizontally outwardly and inwardly as the scroll member 52 rotates so that the system has a maximum width between side bars 44, in this embodiment, of 102 inches and a minimum width of 96 inches.

Scroll member 52 may comprise a horizontal, threaded shaft upon which threaded receptacles are engagingly positioned at each end of the shaft. As the threaded shaft is rotated, the threaded receptacles move inwardly or outwardly, depending on the direction of rotation. The receptacles are attached to lateral portions of spreader 24 including housing sections 49 and rotary arms 50, so that the respective housing sections

49 and the arms 50 can move inwardly and outwardly upon rotation of the scroll member, carrying legs 42, 46 and side bars 44 with them.

Alternatively, horizontal hydraulic cylinders may replace the specific scroll member 52 described above, to perform the same function. This facilitates collapsing the spreader to a minimum size, permitting it to be transported in a container.

Rotary arms 50 rotate about shafts 54 which mount on structure 56. Link 59 is attached to arm 42 at pivot 53 and to structure 56 at pivot 63. Arm 50 and link 59 are each pivotally connected to frame portion 56, and leg 42, to form a parallelogram (four bar) linkage. Link 59 connects at one end to pivot 53 carried on a telescoping tube of vertical leg 42. Link 59 connects at its other end with pivot 63. Arm 50 is pivotally connected to pivot 55. The other end of arm 50 is connected to pivot shaft 54 on structure 56. The vertical spacing between pivots 54 and 63 is equal to the vertical spacing between pivots 55 and 53.

Thus, legs 42 are held in a desired vertical position by this "four bar" linkage as arms 50 are rotated, impelled by pistons and cylinders 51, to move legs 42 inwardly and outwardly between the positions of Figs. 4 and 5. The linkage provided by arm 50 and link 59 is thus pivotally connected in vertically spaced

manner to vertical leg 42, either directly or through a bracket to provide the known, constrained motion of a parallelogram or four bar linkage, which keeps orientation of pivot 55 and pivot 53 constantly vertical as arm 50 rotates through a prescribed arc. Thus, legs 42 are held in the vertical position without adjustment throughout substantially the entire rotation of arms 50.

Each side bar 44 carries added, central latches 48a to permit the sidebars to pick up one or a pair of half-length containers in end-to-end relationship, as an alternative to picking up one full-length container.

Also, arms 50, scroll member 52, and the frame 56 that carries them may be raised and lowered to accommodate container height settings, in this embodiment, of eight feet six inches to nine feet six inches. This is accomplished by four lift cylinders 58, which accordingly can move the respective telescoping rods and tubes 42, 46 upwardly and downwardly relative to end bars 30.

Thus, the respective latches 32, 48 can be moved vertically or horizontally with respect to each other, with the vertical height settings permitting adjustment so that a stack of containers 36, 36a may be simultaneously lifted and transferred to another position. It can be seen that stack 36a may be individually released in a new position by release of

latches 48, followed by retraction of telescoping rods 42, and movement of container 36 to a different location, where latches 32 may release container 36.

Referring to Figs. 6 and 7, in accordance with this invention an electrically operated, ultrasound based, location sensing device 60 is provided in a mounting 61, carried in conjunction with each lower latch 48 carried on extensible rods 42 (Fig. 5).

Latch assemblies 48 have a latching rod or pin 62 capable of hydraulic advancement into engagement with a latchable recess 64 of a container 36a, as shown in dotted lines. Movable latch pin 62 carries a sealed flange 66 which occupies a hydraulic cylinder 68. Conventional hydraulic lines communicate with cylinder 68 so that varying pressures in the cylinder either in front of flange 66 or behind it can cause pin 62 to advance or retract. An advanced position of flange 66 is also shown in phantom lines.

A conventional infrared or ultrasonic sensor/receiver 70 is provided in an aperture 72 of pin 62. Ultrasonic or infrared signals are thus emitted forwardly from pin 62. The operator of the load transferring system, sitting in cab 20, brings spreader 24 into proximity of the desired load 36a to be lifted. The operator may not be able to see the precise position of latch pins 62 relative to apertures 64. However, when

the position is proper so that aperture 64 and pin 62 are aligned, a change in character in the signals is sensed by the sensor portion of signal emitter/sensor 70, which signals may communicate by cable 76 to a microprocessor 77, and then to a readout in the control cabin. If the system is microwave based, an abrupt increase in the signal travel time can be sensed, indicating alignment of recess 64 and latch pin 62. If the signal is infrared, infrared reflective target 74 may cause an abrupt increase in the sensed signal, showing proper alignment of the latch, following which the latch is extended, to lock itself in recess 64 to permit lifting of container 36a when four of such latches 48 have engaged a container.

Engagement sensor 80 is positioned to press against the outer wall of container 36a as a safety check, providing assurance of proper latching. As a final stage of latching, latch pin 62 can be retracted to bring latch system 48 into engagement with the outer wall 82 of container 36a in tightly locked arrangement. As that takes place, spring mounted plunger 84 of engagement sensor 80 is pushed inwardly to its position shown in full lines from its phantom line position. This compression may be sensed by unit 86 in conventional manner, and a confirming signal can be sent through line 88 to microprocessor 77 as a positive indication of

locking between latch 48 and recess 64.

Referring to Fig. 8, the same or a similar latch assembly 48, carried in mounting or housing 61, as shown in the previous drawings can be used to connect to a latchable recess 64a defined in a wall of a container 36b, in which the container recess 64a is of a different design from that of the previous embodiment. Latching rod 62 is shown to be projecting into recess 64a and to hook into an upper aperture 90, defined by an ISO corner fitting 92. Position pin or plunger 84 is also shown engaging the corner of container 36b in a manner similar to that previously described. Location sensing device 60 is not shown in this embodiment, but may be present in a manner similar to that shown with the previous embodiment. Apart from differences shown, latch assembly 48 of Fig. 8 is identical in the way it is carried and utilized, as described with respect to the previous embodiments with respect to latch assemblies 48, 48a shown therein.

Thus an adjustable spreader is provided, being capable of picking up and moving single, rectangular containers, including trailers, truck bodies and similar structures, in which the various containers may be of various sizes. Stacks of containers may be elevated and moved as well as single containers. Also, a system is provided for aligning latches on the spreader with

latchable sites on the various containers, even though the operator cannot directly see the positioning of the latches with the latchable sites, so that the entire operation may be reliably and safely performed by an operator in a cab mounted on the lifting system.

The above has been offered for illustrative purposes only, and is not intended to limit the scope of the invention of this application, which is as defined in the claims below.

THAT WHICH IS CLAIMED:

1. A system for lifting and transferring load containers which comprises a frame; a container lifting device; a cable attached to said frame and lifting device; and a first actuator for raising and lowering said lifting device; said lifting device having a plurality of remotely controllable latches for engaging and disengaging latchable portions of said containers, to permit grasping and lifting of a container by said lifting device, at least some of said latches being carried on vertical legs; rotatable arm members connected to said legs to provide movement of said legs horizontally inwardly and outwardly, whereby the container lifting device may be retracted into a compact unit, and the container lifting device may be variably extended to lift containers and stacks of containers of varying sizes; each rotatable arm member further comprising a pair of spaced, rigid, generally parallel arm portions, said arm portions being each pivotally connected to said frame in spaced manner at one end, and each of said arm portions being pivotally connected at another end to one of said legs in spaced manner forming a parallelogram linkage, to hold said leg in vertical position through a range of rotational positions of said arm portions, whereby said legs are spontaneously held

substantially vertical as said rotatable arm portions move them inwardly and outwardly.

2. The system of Claim 1 in which a second actuator is provided to horizontally move said container lifting device.

3. The system of Claim 1 which further comprises a location sensing device for bringing said latches and recesses on said containers together, which device comprises an ultrasonic emitter, and an ultrasonic sensor positioned to sense reflected ultrasonic signals from the emitter, plus electronics to detect a change in character of the reflected ultrasonic signals indicative of the proper relative positioning of said latches and latchable portions of containers to be lifted by said system.

4. The system of Claim 3 in which said latchable portions comprise recesses, and said change in character of the reflected signals comprises an increase in travel time between signal emission and signal sensing.

5. The system of Claim 1 which further comprises a location sensing device for bringing said

latches and recesses on said containers together, said location sensing device comprising a photoelectric sensing system.

6. The system of Claim 1 in which said legs are vertically extendable and retractable, and said legs carry horizontally extendable and retractable portions which carry at least some of said latches, whereby the container lifting device may be retracted into a compact unit, and the container lifting device may be variably extended to lift single containers and stacks of containers of varying sizes.

7. The system of Claim 6 in which other of said latches are positioned above said latches carried on the vertically extendable and retractable legs, said other latches being positioned to engage latchable portions positioned on container top walls.

8. The system of Claim 7 in which said legs are operatively connected to a second transversely extendable and retractable member which comprises an actuator for horizontally extending and retracting said legs, to provide horizontally movable adjustment to said vertically extendible and retractable legs.

9. The system of Claim 8 in which said second transversely extendable and retractable member moves transversely in a direction substantially perpendicular to said movement horizontally inwardly and outwardly provided by said arm members.

10. The system of Claim 6 in which said vertically extendible and retractable legs comprise a plurality of vertically extendible and retractable telescoping tubes and a fluid pressure system for extending and retracting them.

11. The system of Claim 10 in which said vertically extending and retractable telescoping tubes are raisable and lowerable as a unit by a plurality of hydraulic lift cylinders, to provide adjustability to the vertical position of said telescoping tubes.

12. The system of claim 1 in which said arm portions pivotally connect to said frame and to said leg with substantially equal spacing.

13. A system for lifting and transferring load containers which comprises a frame; a container lifting device; a cable attached to said frame and lifting device; a first actuator for raising and lowering said

lifting device; and a second actuator to horizontally move said container lifting device; said lifting device having a plurality of remotely controllable latches for engaging and disengaging latchable portions of said containers, to permit grasping and lifting of a container by said lifting device, at least some of said latches being carried on vertically extendible and retractable legs; rotatable arm members connected to said legs to provide movement of said legs horizontally inwardly and outwardly, whereby the container lifting device may be retracted into a compact unit, and the container lifting device may be variably extended to lift containers and stacks of containers of varying sizes; each rotatable arm member further comprising a pair of rigid spaced, generally parallel arm portions, said arm portions being each pivotally connected to said frame in spaced manner at one end, and each of said arm portions being pivotally connected at another end to one of said legs in spaced manner, forming a parallelogram linkage to hold said leg in vertical position through a range of rotational positions of said arm portions, whereby said legs are held substantially vertical as said rotatable arm portions move them inwardly and outwardly; said vertically extendible and retractable legs carrying horizontally extendible and retractable portions which carry at least some of said latches, whereby the

container lifting device may be retracted into a compact unit, and the container lifting device may be variably extended to lift single containers and stacks of containers of varying sizes.

14. The system of Claim 13 in which other of said latches are positioned above said latches carried on the vertically extendible and retractable legs, said other latches being positioned to engage latchable portions positioned on container top walls.

15. The system of claim 14 in which said arm portions pivotally connect to said frame and to said leg with substantially equal spacing.

16. The system of Claim 15 in which said legs are operatively connected to a second transversely extendable and retractable member which comprises an actuator for horizontally extending and retracting said legs, to provide horizontally movable adjustment to said vertically extendible and retractable legs.

17. The system of Claim 16 in which said second transversely extendable and retractable member moves transversely in a direction substantially perpendicular to said movement horizontally inwardly and

outwardly provided by said arm members.


18. The system of Claim 17 in which said vertically extendible and retractable legs comprise a plurality of vertically extendible and retractable telescoping tubes and a fluid pressure system for extending and retracting them.

19. The system of Claim 18 in which said vertically extending and retracting telescoping tubes are raisable and lowerable as a unit by a plurality of hydraulic lift cylinders, to provide adjustability to the vertical position of said telescoping tubes.

20. The system of Claim 19 which further comprises a location sensing device for bringing said latches and recesses on containers to be lifted together.

1/5

FIG. 1



Fenlagan & Ingelherst
PATENT AGENTS

2/5

FIG. 2





FIG. 3



Fealson & Seaglehurst
PATENT AGENTS

3/5

FIG. 4







FIG. 5




Fenlagan & Seagleherst
PATENT AGENTS



5/5

FIG. 8



Faulstich & Seigler

PATENT AGENTS