




- (51) International Patent Classification:
A61F 2/16 (2006.01)
- (21) International Application Number:
PCT/US20 14/037646
- (22) International Filing Date:
12 May 2014 (12.05.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/830,491 3 June 2013 (03.06.2013) US
13/969,115 16 August 2013 (16.08.2013) US
- (71) Applicants: CLARVISTA MEDICAL, INC. [US/US];
31 Journey, Suite 110, Aliso Viejo, CA 92656 (US). RE-
GENTS OF THE UNIVERSITY OF COLORADO [US/US];
1800 Grant Street, 8th Floor, Denver, CO 80203
(US).
- (72) Inventors: KAHOOK, Malik, Y.; 9102 E. 34th Avenue,
Denver, CO 80238 (US). MANDAVA, Naresh; 215 Jas-
mine Street, Denver, CO 80220 (US). SUSSMAN, Glenn;
28602 Rancho Grande, Laguna Niguel, CA 92677 (US).
MCLEAN, Paul; 15 Dove Lane, North Oakds, MN 55127
(US). ATKINSON, Robert, E.; 2949 Jonquil Trail, Lake
Elmo, MN 55042 (US).

- (74) Agent: MELWANI, Dinesh, N.; Bookoff McAndrews,
PLLC, 2401 Pennsylvania Avenue, NW, Suite 450, Wash-
ington, DC 20037 (US).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM,
ZW.
- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:
— with international search report (Art. 21(3))

(54) Title: MODULAR INTRAOCULAR LENS DESIGNS AND METHODS

FIG. 29F



(57) Abstract: A modular IOL system including intraocular primary and secondary components, which, when combined, form an intraocular optical correction device, wherein the secondary component is placed on the primary component within the perimeter of the capsulorhexis, thus avoiding the need to touch or otherwise manipulate the capsular bag. The secondary component may be manipulated, removed, and/or exchanged for a different secondary component for correction or modification of the optical result, on an intra-operative or post-operative basis, without the need to remove the primary component and without the need to manipulate the capsular bag. The primary component may have haptics extending therefrom for centration in the capsular bag, and the secondary component may exclude haptics, relying instead on attachment to the primary component for stability. Such attachment may include actuatable interlocking members.

WO 2014/197170 A1

Modular Intraocular Lens Designs and Methods

Cross-Reference to Related Applications

[1] This application claims priority to U.S. Patent Application No. 13/969,115, filed August 16, 2013, entitled "MODULAR INTRAOCULAR LENS DESIGN AND METHODS," which claims priority to U.S. Provisional Patent Application No. 61/830,491, filed June 3, 2013, entitled "MODULAR INTRAOCULAR LENS DESIGNS AND METHODS," the entireties of which are incorporated herein by reference.

Field of the Invention

[2] The present disclosure generally relates to embodiments of intraocular lenses (IOLs). More specifically, the present disclosure relates to embodiments of modular IOL designs and methods.

Background

[3] The human eye functions to provide vision by transmitting light through a clear outer portion called the cornea, and focusing the image by way of a crystalline lens onto a retina. The quality of the focused image depends on many factors including the size and shape of the eye, and the transparency of the cornea and the lens.

[4] When age or disease causes the lens to become less transparent (e.g., cloudy), vision deteriorates because of the diminished light, which can be transmitted to the retina. This deficiency in the lens of the eye is medically known as a cataract. An accepted treatment for this condition is surgical removal of the lens from the capsular bag and placement of an artificial intraocular lens (IOL) in the capsular bag. In the United States, the majority of cataractous lenses are removed by a surgical

technique called phacoemulsification. During this procedure, an opening (capsulorhexis) is made in the anterior side of the capsular bag and a thin phacoemulsification-cutting tip is inserted into the diseased lens and vibrated ultrasonically. The vibrating cutting tip liquefies or emulsifies the lens so that the lens may be aspirated out of the capsular bag. The diseased lens, once removed, is replaced by an IOL.

[5] After cataract surgery to implant an IOL, the optical result may be suboptimal or may need adjustment over time. For example, shortly after the procedure, it may be determined that the refractive correction is erroneous leading to what is sometimes called "refractive surprise." Also for example, long after the procedure, it may be determined that the patient needs or desires a different correction, such as a stronger refractive correction, an astigmatism correction, or a multifocal correction.

[6] In each of these cases, a surgeon may be reluctant to attempt removal of the suboptimal IOL from the capsular bag and replacement with a new IOL. In general, manipulation of the capsular bag to remove an IOL risks damage to the capsular bag including posterior rupture. This risk increases over time as the capsular bag collapses around the IOL and tissue ingrowth surrounds the haptics of the IOL. Thus, it would be desirable to be able to correct or modify the optical result without the need to remove the IOL or manipulate the capsular bag.

[7] A variety of secondary lenses have been proposed to address the aforementioned drawbacks. For example, one possible solution includes a secondary lens that resides anterior to the capsular bag with haptics that engage the ciliary sulcus. While this design may have the advantage of avoiding manipulation of the capsular bag, its primary disadvantage is engaging the ciliary sulcus. The ciliary sulcus is composed of soft vascularized tissue that is susceptible to injury when

engaged by haptics or other materials. Such injury may result in complications such as bleeding, inflammation and hyphema. Thus, in general, it may be desirable to avoid placing a secondary lens in the ciliary sulcus to avoid the potential for complications.

[8] Another potential solution may include a lens system that avoids the potential problems associated with the ciliary sulcus. The lens system may include a primary lens and a secondary lens, where the secondary lens may be attached to the primary lens, both within the capsular bag. The primary lens may have a recess into which an edge of the secondary lens may be inserted for attachment. The recess is preferably located radially outwardly of the opening (capsulorhexis) in the capsular bag to avoid interfering with light transmission. To attach the secondary lens *in-situ*, the capsular bag must be manipulated around the perimeter of the capsulorhexis to gain access to the recess in the primary lens. As stated previously, manipulation of the capsular bag may be undesirable given the risks associated therewith. Therefore, while such lens systems may avoid the potential for injury to the ciliary sulcus by implanting both the primary lens and the secondary lens in the capsular bag, these systems do not avoid manipulation of the capsular bag to attach the secondary lens.

[9] Thus, there remains a need for an IOL system and method that allows for correction or modification of the optical result using a lens that can be attached to a base or primary lens without the need to manipulate the capsular bag.

Summary of the Invention

[10] Embodiments of the present disclosure provide a modular IOL system including intraocular primary and secondary components, which, when combined,

form an intraocular optical correction device. The primary component may comprise an intraocular base, and the secondary component may comprise an intraocular lens, wherein the base is configured to releasably receive the intraocular lens. In some embodiments, the base may be configured as a lens, in which case the modular IOL system may be described as including a primary lens and a secondary lens. The primary component (e.g., base or primary lens) may be placed in the capsular bag using conventional cataract surgery techniques. The primary component may have a diameter greater than the diameter of the capsulorhexis to retain the primary component in the capsular bag. The secondary component (e.g., secondary lens) may have a diameter less than the diameter of the capsulorhexis such that the secondary component may be attached to the primary component without manipulation of the capsular bag. The secondary component may also be manipulated to correct or modify the optical result, intra-operatively or post-operatively, without the need to remove the primary component and without the need to manipulate the capsular bag. For example, the secondary component may be removed, repositioned, and/or exchanged to correct, modify, and/or fine tune the optical result.

[11] Common indications for exchanging the secondary component may be residual refractive error (e.g., for monofocal lenses), decentration error (e.g., for multifocal lenses) due to post-operative healing, astigmatism error (e.g., for toric lenses) induced by surgery, changing optical correction needs due to progressive disease, changing optical correction desires due to lifestyle changes, injury, age, etc.

[12] The primary component may have haptics (e.g., projections) extending therefrom for centration in the capsular bag, and the secondary component may exclude haptics, relying instead on attachment to the primary component for stability.

The secondary component may reside radially inside the perimeter of the capsulorhexis, thereby negating the need to disturb the capsular bag to manipulate or exchange the secondary component. The attachment between the primary component and the secondary component may reside radially inside the perimeter of the capsulorhexis and radially outside the field of view to avoid interference with light transmission. Alternatively or in addition, the attachment may comprise a small fraction of the perimeter (e.g., less than 20%) of the secondary component to minimize the potential for interference in light transmission.

[13] The primary component may have an anterior surface that is in intimate contact with a posterior surface of the secondary component to prevent fluid ingress, tissue ingrowth, and/or optical interference. The secondary component may be removably secured to the primary component by mechanical attachment and/or chemical attraction, for example. Mechanical attachment may be facilitated by mating or interlocking geometries corresponding to each of the primary and the secondary components. Such geometries may be pre-formed by molding or cutting, for example, or formed in-situ by laser etching, for example. Chemical attraction may be facilitated by using similar materials with a smooth surface finish activated by a surface treatment, for example. In some instances, it may be desirable to reduce chemical attraction and rely more on mechanical attachment for stability. In this case, the primary and secondary components may be formed of dissimilar materials or otherwise have adjacent surfaces that do not have a chemical attraction.

[14] The modular IOL systems and methods according to embodiments of the present disclosure may be applied to a variety of IOL types, including fixed monofocal, multifocal, toric, accommodative, and combinations thereof. In addition, the modular IOL systems and methods according to embodiments of the present

disclosure may be used to treat, for example: cataracts, large optical errors in myopic (near-sighted), hyperopic (far-sighted), and astigmatic eyes, ectopia lentis, aphakia, pseudophakia, and nuclear sclerosis.

[15] Various other aspects of embodiments of the present disclosure are described in the following detailed description and drawings.

Brief Description of the Drawings

[16] The drawings illustrate example embodiments of the present disclosure. The drawings are not necessarily to scale, may include similar elements that are numbered the same, and may include dimensions (in millimeters) and angles (in degrees) by way of example, not necessarily limitation. In the drawings:

[17] Figure 1 is a schematic diagram of the human eye shown in cross section;

[18] Figures 2A and 2B are front and side cross-sectional views, respectively, of a modular IOL disposed in a capsular bag according to an embodiment of the present disclosure;

[19] Figures 3A-3D and 4A-4D are front and side cross-sectional views, respectively, schematically illustrating a method for implanting a modular IOL according to an embodiment of the present disclosure;

[20] Figure 5 is a front view of a modular IOL, according to an embodiment of the present disclosure, wherein subsurface attachment mechanisms are provided for connection between the primary and secondary lenses;

[21] Figures 6A and 6B are cross-sectional views taken along line 6-6 in Figure 5, showing two embodiments of subsurface attachment mechanisms;

[22] Figure 7 is a front view of a modular IOL, according to an embodiment of the present disclosure, wherein extension attachment mechanisms are provided to connect the primary and secondary lenses;

[23] Figures 8A-8C are cross-sectional views taken along line 8-8 in Figure 7, showing three embodiments of extension attachment mechanisms;

[24] Figures 9A-9D are front views showing various positions of the attachment mechanisms to adjust the position of the secondary lens relative to the primary lens;

[25] Figure 10 is a front view of a modular IOL, according to an embodiment of the present disclosure, wherein etched subsurface attachment mechanisms are provided for connection between the primary and secondary lenses;

[26] Figures 11A-11F are cross-sectional views of the modular IOL shown in Figure 10, showing various embodiments of etched subsurface attachment mechanisms;

[27] Figures 12A-12C are schematic illustrations of front, sectional and detail views, respectively, of an alternative modular IOL, according to an embodiment of the present disclosure;

[28] Figures 13A and 13B show representative photomicrographs at 4X and 40X magnification, respectively, of a groove (see, arrow) formed by laser etching;

[29] Figures 14-22 are various views of alternative modular IOLs according to embodiments of the present disclosure;

[30] Figures 23A-23D are schematic illustrations of a lens removal system for a modular IOL according to an embodiment of the present disclosure;

[31] Figure 24 is a schematic flow chart of a method for using a modular IOL, according to an embodiment of the present disclosure, wherein an exchange of

the secondary lens is motivated by a sub-optimal optical result detected intra-operative[^];

[32] Figure 25 is a schematic flow chart of a method for using a modular IOL, according to an embodiment of the present disclosure, wherein an exchange of the secondary lens is motivated by a sub-optimal optical result detected post-operatively;

[33] Figure 26 is a schematic flow chart of a method for using a modular IOL, according to an embodiment of the present disclosure, wherein a secondary lens is attached to a primary lens by forming the attachment means *in-situ*;

[34] Figures 27-30B are various views of a further embodiments of modular IOLs, according to the present disclosure; and

[35] Figures 31A-31B are schematic illustrations of an alternative lens removal system for a modular IOL according to an embodiment of the present disclosure.

Detailed Description

[36] With reference to Figure 1, the human eye 10 is shown in cross section. The eye 10 has been described as an organ that reacts to light for several purposes. As a conscious sense organ, the eye allows vision. Rod and cone cells in the retina 24 allow conscious light perception and vision including color differentiation and the perception of depth. In addition, the human eye's non-image-forming photosensitive ganglion cells in the retina 24 receive light signals which affect adjustment of the size of the pupil, regulation and suppression of the hormone melatonin, and entrainment of the body clock.

[37] The eye 10 is not properly a sphere; rather it is a fused two-piece unit. The smaller frontal unit, more curved, called the cornea 12 is linked to the larger unit called the sclera 14. The corneal segment 12 is typically about 8 mm (0.3 in) in radius. The sclera 14 constitutes the remaining five-sixths; its radius is typically about 12 mm. The cornea 12 and sclera 14 are connected by a ring called the limbus. The iris 16, the color of the eye, and its black center, the pupil, are seen instead of the cornea 12 due to the cornea's 12 transparency. To see inside the eye 10, an ophthalmoscope is needed, since light is not reflected out. The fundus (area opposite the pupil), which includes the macula 28, shows the characteristic pale optic disk (papilla), where vessels entering the eye pass across and optic nerve fibers 18 depart the globe.

[38] Thus, the eye 10 is made up of three coats, enclosing three transparent structures. The outermost layer is composed of the cornea 12 and sclera 14. The middle layer consists of the choroid 20, ciliary body 22, and iris 16. The innermost layer is the retina 24, which gets its circulation from the vessels of the choroid 20 as well as the retinal vessels, which can be seen within an ophthalmoscope. Within these coats are the aqueous humor, the vitreous body 26, and the flexible lens 30. The aqueous humor is a clear fluid that is contained in two areas: the anterior chamber between the cornea 12 and the iris 16 and the exposed area of the lens 30; and the posterior chamber, between the iris 16 and the lens 30. The lens 30 is suspended to the ciliary body 22 by the suspensory ciliary ligament 32 (Zonule of Zinn), made up of fine transparent fibers. The vitreous body 26 is a clear jelly that is much larger than the aqueous humor.

[39] The crystalline lens 30 is a transparent, biconvex structure in the eye that, along with the cornea 12, helps to refract light to be focused on the retina 24.

The lens 30, by changing its shape, functions to change the focal distance of the eye so that it can focus on objects at various distances, thus allowing a sharp real image of the object of interest to be formed on the retina 24. This adjustment of the lens 30 is known as accommodation, and is similar to the focusing of a photographic camera via movement of its lenses.

[40] The lens has three main parts: the lens capsule, the lens epithelium, and the lens fibers. The lens capsule forms the outermost layer of the lens and the lens fibers form the bulk of the interior of the lens. The cells of the lens epithelium, located between the lens capsule and the outermost layer of lens fibers, are found predominantly on the anterior side of the lens but extend posteriorly just beyond the equator.

[41] The lens capsule is a smooth, transparent basement membrane that completely surrounds the lens. The capsule is elastic and is composed of collagen. It is synthesized by the lens epithelium and its main components are Type IV collagen and sulfated glycosaminoglycans (GAGs). The capsule is very elastic and so causes the lens to assume a more globular shape when not under the tension of the zonular fibers, which connect the lens capsule to the ciliary body 22. The capsule varies between approximately 2-28 micrometers in thickness, being thickest near the equator and thinnest near the posterior pole. The lens capsule may be involved with the higher anterior curvature than posterior of the lens.

[42] Various diseases and disorders of the lens 30 may be treated with an IOL. By way of example, not necessarily limitation, a modular IOL according to embodiments of the present disclosure may be used to treat cataracts, large optical errors in myopic (near-sighted), hyperopic (far-sighted), and astigmatic eyes, ectopia lentis, aphakia, pseudophakia, and nuclear sclerosis. However, for purposes of

description, the modular IOL embodiments of the present disclosure are described with reference to cataracts.

[43] The following detailed description describes various embodiments of a modular IOL system including primary and secondary intraocular components, namely an intraocular base configured to releasably receive an intraocular lens. In some embodiments, the base may be configured to provide optical correction, in which case the modular IOL system may be described as including a primary lens and a secondary lens. The principles and features described with reference to embodiments where the base is configured for optical correction may be applied to embodiments where the base is not configured for optical correction, and vice versa. Stated more broadly, features described with reference to any one embodiment may be applied to and incorporated into other embodiments.

[44] With reference to Figures 2A and 2B, a modular IOL system 50/60 is shown implanted in the capsular bag 34 of lens 30 having a capsulorhexis 36 formed therein. The modular IOL system may include a primary lens 50 and a secondary lens 60. The primary lens 50 may include a body portion 52, a pair of haptics 54 for anchoring and centering the primary lens 50 in the capsular bag 34, and means for attachment (not shown here, but described later) to the secondary lens 60. The secondary lens 60 may include an optic body portion 62, no haptics, and corresponding means for attachment (not shown here, but described later) to the primary lens 50. The anterior surface of the body portion 52 of the primary lens 50 may be in intimate contact with the posterior surface of the body portion 62 of the secondary lens 60, without any intervening material (e.g., adhesive, aqueous humor, tissue ingrowth, etc.) in between. For example, the anterior surface of the body portion 52 may be in directed contact with the posterior surface of body portion 62.

The secondary lens 60 may be acutely and chronically releasably attached to the primary lens 50 to facilitate exchange of the secondary lens 60 while the primary lens 50 remains in the capsular bag 34 of the lens 30.

[45] The body portion 52 of the primary lens 50 may provide some refractive correction, but less than required for an optimal optical result. The optimal optical result may be provided by the combination of the correction provided by the optical body portion 52 of the primary lens 50 together with the optical body portion 62 of the secondary lens 60. For example, the optical body portion 62 of the secondary lens 60 may change (e.g., add or subtract) refractive power (for monofocal correction), toric features (for astigmatism correction), and/or diffractive features (for multifocal correction).

[46] The secondary lens 60 may have an outside diameter d_1 , the capsulorhexis 36 may have an inside diameter d_2 , and the body 52 of the primary lens 50 may have an outside diameter d_3 , where $d_1 < d_2 \leq d_3$. This arrangement provides a gap between the secondary lens 60 and the perimeter of the capsulorhexis 36 such that the secondary lens 60 may be attached or detached from the primary lens 50 without touching or otherwise disturbing any portion of the capsular bag 34. By way of example, not limitation, assuming the capsulorhexis has a diameter of approximately 5 to 6 mm, the body of the primary lens (i.e., excluding the haptics) may have a diameter of approximately 5 to 8 mm, and the secondary lens may have a diameter of approximately 3 to less than 5 mm, thereby providing a radial gap up to approximately 1.5 mm between the secondary lens and the perimeter of the capsulorhexis. Notwithstanding this example, any suitable dimensions may be selected to provide a gap between the secondary lens and the

perimeter of the capsulorhexis in order to mitigate the need to manipulate the lens capsule to attach the secondary lens to the primary lens.

[47] With reference to Figures 3A-3D (front views) and 4A-4D (side cross-sectional views), a method for implanting a modular IOL system 50/60 is shown schematically. As seen in Figures 3A and 4A, a lens 30 with cataracts includes an opaque or clouded center 38 inside a capsular bag 34. Access to the lens 30 for cataract surgery may be provided by one or more lateral incisions in the cornea. A capsulorhexis (circular hole) 36 may be formed in the anterior capsular bag 34 using manual tools or a femtosecond laser. As seen in Figures 3B and 4B, the opaque center 38 is removed by phacoemulsification and/or aspiration through the capsulorhexis 36. The primary lens 50 is delivered in a rolled configuration using a tube inserted through the capsulorhexis 36 and into the capsular bag 34. The primary lens 50 is ejected from the delivery tube and allowed to unfurl. With gentle manipulation, the haptics 54 of the primary lens engage the inside equator of the lens capsule 34 and center the lens body 52 relative to the capsulorhexis 36 as seen in Figures 3C and 4C. The secondary lens 60 is delivered in a rolled configuration using a tube, positioning the distal tip thereof adjacent the primary lens 50. The secondary lens 60 is ejected from the delivery tube and allowed to unfurl. With gentle manipulation, the secondary lens 60 is centered relative to the capsulorhexis 36. Without manipulating the capsular bag 34 or the primary lens 50, the secondary lens 60 is then attached to the primary lens 50 as seen in Figures 3D and 4D. If necessary, the secondary lens 60 may be removed and/or replaced in a similar manner, reversing the steps where appropriate. As an alternative, the primary 50 and secondary 60 lenses may be implanted as a unit, thus eliminating a delivery step.

[48] Because it may be difficult to ascertain which side of the secondary lens 60 should face the primary lens 50, the secondary lens may include a marking indicative of proper position. For example, a clockwise arrow may be placed along the perimeter of the anterior surface of the secondary lens 60, which appears as a clockwise arrow if positioned right-side-up and a counter-clockwise arrow if positioned wrong-side-up. Alternatively, a two-layered color marking may be placed along the perimeter of the anterior surface of the secondary lens 60, which appears as a first color if positioned right-side-up and a second color if positioned wrong-side-down. Other positionally indicative markings may be employed on the secondary lens 60, and similar marking schemes may be applied to the primary lens 50.

[49] With reference to Figure 5, subsurface attachment mechanisms 70 may be used to releasably secure the secondary lens 60 to the primary lens 50. The attachment mechanisms 70 may be positioned radially inside the perimeter of the capsulorhexis 36 and radially outside the field of view to avoid interference with light transmission. Alternatively or in addition, the attachment mechanism 70 may have radial and lateral extents limited to a small fraction (e.g., less than 10-20%) of the perimeter of the secondary lens 50 to minimize the potential for interference in light transmission. Two diametrically opposed attachment mechanisms 70 are shown, but any suitable number may be used, uniformly or non-uniformly distributed about the circumference of the secondary lens 60.

[50] If the primary lens 50 and the secondary lens 60 are delivered at the same time, it may be desirable to align the attachment mechanisms 70 with the roll axis 80, around which the lenses 50 and 60 may be rolled for insertion via a delivery tool. Because the secondary lens 60 may shift relative to the primary lens 50 when rolled about axis 80, providing the attachment mechanisms 70 along the roll axis 80

minimizes stress to the attachment mechanisms 70. To this end, the attachment mechanisms 70 may be coaxially aligned relative to the roll axis 80 and may be configured to extend a limited distance (e.g., less than 10-20% of the perimeter of the secondary lens 60) from the axis 80.

[51] The attachment mechanisms 70 may be configured to have mating or interlocking geometries as shown in Figures 6A and 6B. Generally, the geometries include a male portion and female portion that are releasably connectable. The female portion is configured to receive the male portion and limit relative motion between the primary lens 50 and the secondary lens 60 in at least two dimensions (e.g., superior-inferior and right-left). The female and male portions may be configured to have an interlocking geometry such that relative motion between the primary lens 50 and the secondary lens 60 is limited in three dimensions (e.g., superior-inferior, right-left, anterior-posterior). The attachment mechanisms 70 may be engaged and disengaged by applying orthogonal force in a posterior (push) and anterior (pull) direction, respectively. The attachment mechanisms 70 may be preformed by molding, cutting, etching, or a combination thereof, for example.

[52] In the examples shown, each attachment mechanism 70 comprises an interlocking cylindrical protrusion 72 and cylindrical recess or groove 74. Other mating or interlocking geometries may be used as well. The cylindrical geometry shown has the advantage of allowing slight rotation of the secondary lens 60 relative to the primary lens 50 when rolled for delivery, thus further reducing stress thereon. As shown in Figure 6A, the cylindrical protrusion 72 may extend anteriorly from the anterior surface of the body 52 of the primary lens 50, and the cylindrical recess 74 may extend anteriorly through the posterior surface of the body 62 of the secondary lens 60 adjacent a radial peripheral zone thereof. Alternatively, as shown in Figure

6B, the cylindrical protrusion 72 may extend posteriorly from the posterior surface of the body 62 of the secondary lens 60 adjacent a radial peripheral zone thereof, and the cylindrical recess 74 may extend posteriorly through the anterior surface of the body 52 of the primary lens 50. The configuration shown in Figure 6B may be particularly suited for the case where the primary lens 50 is a pre-existing implanted IOL into which the recess 74 may be etched *in-situ*, by laser, for example.

[53] With reference to Figure 7, extension attachment mechanisms 90 may be used to releasably connect the primary 50 and secondary 60 lenses. Extension attachment mechanisms 90 may be similar to subsurface attachment mechanisms 70 except as shown and described. Extension attachment mechanisms 90 may extend radially from the perimeter of the secondary lens 60, with each including mating or interlocking geometries, examples of which are shown in Figures 8A-8C. In Figure 8A, a cylindrical portion 92 extends from the outer edge of the secondary lens 60, and a cylindrical recess 94 extends from the outer edge of the primary lens 50. In Figure 8B, the corollary is shown, with the cylindrical portion 92 extending from the outer edge of the primary lens 50, and the cylindrical recess 94 extending from the outer edge of the secondary lens 60. In both embodiments shown in Figures 8A and 8B, the attachment mechanisms 90 may be engaged and disengaged by applying orthogonal force in a posterior (push) and anterior (pull) direction, respectively. Alternatively, in the embodiment shown in Figure 8C, the attachment mechanisms 90 may be engaged and disengaged by applying rotational force in a clockwise or counterclockwise direction, depending on which lens 50/60 is attached to each of the cylindrical portion 92 and the cylindrical recess 94. In addition, although the embodiment of Figure 7 only depicts the use of two

attachment mechanisms 90, any suitable number of attachment mechanisms 90 may be utilized within the principles of the present disclosure.

[54] With reference to Figures 9A-9D, the portion of attachment mechanism 90 associated with the secondary lens 60 may be positioned such that the center of the secondary lens 60 is aligned with the center of the primary lens 50. Alternatively, to adjust for misalignment of the primary lens 50 due to imbalanced post-operative healing, for example, the portion of attachment mechanism 90 associated with the secondary lens 60 may be offset as shown in Figures 9B-9D. In Figure 9B, the portion of attachment mechanism 90 associated with the secondary lens 60 is rotationally offset. In Figure 9C, the portion of attachment mechanism 90 associated with the secondary lens 60 is superiorly offset. In Figure 9D, the portion of attachment mechanism 90 associated with the secondary lens 60 is laterally offset. An anterior-posterior offset may also be employed as described in more detail with reference to Figures 11C and 11F. Each of the embodiments shown in Figures 9B, 9C, 9D, 11C and 11F are provided by way of example, and the offset may be made in any direction (anterior, posterior, superior, inferior, right, left, clockwise, counterclockwise) or combination thereof, to varying magnitudes depending on the misalignment of the primary lens 50. In addition, attachment mechanism 90 is shown by way of example, but the same principles may be applied to other attachment means described herein.

[55] With reference to Figure 10, alternative subsurface attachment mechanisms 100 may be used to releasably connect the secondary lens 50 to the primary lens 60. Subsurface attachment mechanisms 100 may be similar to subsurface attachment mechanisms 70 except as shown and described. Subsurface attachment mechanisms 100 may comprise mating or interlocking geometries

extending along an arcuate path adjacent the peripheral edge of the secondary lens 60. The subsurface attachment mechanism 100 may include a protrusion 102 and a corresponding recess or groove 104 into which the protrusion 102 may be received. The protrusion 102 may extend from the posterior surface of the secondary lens 60 and the corresponding recess or groove 104 may extend into the anterior surface of the primary lens 50 as shown in Figures 11A (separated) and 11D (attached). Alternatively, the protrusion 102 may extend from the anterior surface of the primary lens 50 and the corresponding the recess or groove 104 may extend into the posterior surface of the secondary lens 60 as shown in Figures 11B (separated) and 11E (attached). In either embodiment, the anterior-posterior dimension of the protrusion 102 may match the same dimension of the recess or groove 104 to provide intimate contact between the anterior surface of the primary lens 50 and the posterior surface of the secondary lens 60. Alternatively, the anterior-posterior dimension of the protrusion 102 may exceed the same dimension of the recess or groove 104 to provide an anterior-posterior offset as shown in Figures 11C (separated) and 11F (attached). Further, those of ordinary skill in the art will readily recognize that any suitable number of attachment mechanisms 100 may be utilized within the principles of the present disclosure.

[56] With reference to Figure 12A, alternative subsurface attachment mechanisms 105 may be used to connect the secondary lens 60 to the primary lens 50. Subsurface attachment mechanisms 105 may be similar to subsurface attachment mechanisms 100 except as shown and described. As seen in Figure 12B, which is a cross-sectional view taken along line B-B in Figure 12A, the subsurface attachment mechanism 105 may comprise mating or interlocking geometries including a protrusion 107 and a series of holes 109 into which the

protrusion 107 may be received. The holes 109 may be distributed in a pattern as seen in Figure 12C, which shows several alternative detail views of box C in Figure 12A. In Figure 12C, the protrusion 107 resides in a hole 109 designated as a black circle while the remaining holes 109 designated as white circles remain open. With this arrangement, the protrusions 107 may be placed in a corresponding pair of holes 109 to achieve the desired alignment between the primary 50 and secondary 60 lenses. For example, and with continued reference to Figure 12C, the protrusions 107 may be placed in a corresponding pair of holes 109 to achieve centered (nominal), shift right, shift left, shift up, shift down, rotate clockwise or rotate counterclockwise (labeled C1-C7, respectively) alignment between the primary 50 and secondary 60 lenses. This arrangement provides a range of adjustments as described with reference to Figures 9A-9D. In addition, any suitable number of attachment mechanisms 105 may be disposed uniformly or non-uniformly about a perimeter of lenses 50 and 60.

[57] All or a portion of the various subsurface attachment means described herein may be formed by molding, cutting, milling, etching or a combination thereof. For example, with particular reference to Figure 11A, the groove 104 may be formed by *in-situ* laser etching a pre-existing implanted primary lens 50, and the protrusion may be pre-formed by molding, milling or cutting the secondary lens 60.

[58] Examples of lasers that may be used for *in-situ* etching include femtosecond lasers, ti/saph lasers, diode lasers, YAG lasers, argon lasers and other lasers in the visible, infrared and ultraviolet range. Such lasers may be controlled in terms of energy output, spatial control and temporal control to achieve the desired etch geometry and pattern. *In-situ* etching may be accomplished, for example, by transmitting a laser beam from an external laser source, through the cornea and past

the pupil. Alternatively, *in-situ* etching may be accomplished by transmitting a laser beam from a flexible fiber optic probe inserted into the eye.

[59] With reference to Figures 13A and 13B, photomicrographs at 4X and 40X magnification, respectively, show how a groove (see, arrow) was experimentally etched in a primary lens by laser etching. A femtosecond laser set within the following ranges may be used to etch the groove: power of 1 nJ to 100 μ J; pulse duration of 20 fs up to the picosecond range; and a frequency of 1 to 250 kHz.

[60] The primary and secondary components of the modular IOL systems disclosed herein may be formed of the same, similar or dissimilar materials. Suitable materials may include, for example, acrylate-based materials, silicone materials, hydrophobic polymers or hydrophilic polymers, and such materials may have shape-memory characteristics. For example, materials comprising the optical portions of the modular lens system can be silicone, PMMA, hydrogels, hydrophobic acrylic, hydrophilic acrylic or other transparent materials commonly used for intraocular lenses. Non-optical components of the modular IOL might include nitinol, polyethylene sulfone and/or polyimide.

[61] Materials can be selected to aid performance of certain features of the modular lens system notably the attachment and detachment features necessary for the primary and secondary lenses as previously described. Other features of the modular lens that can be enhanced with specific material selections include manufacturability, intraoperative and post-operative handling, fixation (both intraoperative and at time of post-operative modification), reaching micro-incision sizes (<2.4mm) and exchangeability (minimal trauma on explantation of lenses).

[62] For example, in one embodiment the primary lens and the secondary lens are made from hydrophobic acrylic material having a glass transition

temperature between approximately 5 and 30⁰ C and a refractive index between approximately 1.41-1.60. In another embodiment, the primary and secondary lens can be made from different materials having different glass transition temperatures and mechanical properties to aid fixation and detachment properties of the modular system. In another embodiment, both or either of the modular lens system is made from materials allowing for compression to an outer diameter equal to or smaller than approximately 2.4 mm.

[63] Material properties that are generally desirable in the modular IOL system include minimal to no glistening formation, minimal pitting when exposed to YAG laser application and passing standard MEM elution testing and other biocompatibility testing as per industry standards. The material may contain various chromophores that will enhance UV blocking capabilities of the base material. Generally, wavelengths that are sub 400nm are blocked with standard chromophores at concentrations $\leq 1\%$. Alternatively or in addition, the material may contain blue light blocking chromophores, e.g., yellow dyes which block the desired region of the blue-light spectrum. Suitable materials are generally resistant to damage, e.g., surface abrasion, cracking, or hazing, incurred by mechanical trauma under standard implantation techniques.

[64] The components of the modular IOL may be formed by conventional techniques such as molding, cutting, milling, etching or a combination thereof.

[65] As an alternative to mechanical attachment, chemical attraction between the primary and secondary components may be utilized. Using similar materials with a smooth surface finish may facilitate chemical attraction. Chemical attraction may be enhanced by surface activation techniques such as plasma or chemical activation. In some instances, it may be desirable to reduce chemical

attraction to avoid sticking between the materials and rely more on mechanical attachment for stability. In this case, the primary and secondary components may be formed of dissimilar materials or otherwise have adjacent surfaces that do not have a chemical attraction.

[66] With reference to Figures 14-14C, an alternative modular IOL 140 is shown in front, sectional and detailed views, respectively. Figure 14A shows a cross-sectional view taken along line A-A in Figure 14, Figure 14B shows a cross sectional view taken along line B-B in Figure 14, and Figure 14C shows a detail view of circle C in Figure 14B. Modular IOL 140 may include a primary lens 50 with haptics 54 and a secondary lens 60. The interfacing surfaces of the primary lens 50 (anterior surface) and secondary lens 60 (posterior surface) may be in intimate contact as best seen in Figures 14A and 14B. Maintaining intimate contact (i.e., avoiding a gap) or maintaining a consistent gap between the interfacing surfaces of the primary lens 50 and the secondary lens 60 may reduce the likelihood of induced astigmatism. In some embodiments, however, a substance (e.g., an adhesive agent) may be disposed between the respective surfaces of lenses 50 and 60. A circular extension may be formed in the secondary lens 60, with a correspondingly sized and shaped circular recess formed in the primary lens 50 to form an interference fit therebetween, thus securely connecting the two components. The depth of the recess in the primary lens 50 may be a fraction of the thickness of the secondary lens 60, with a circular extension of the secondary lens 60 extending over a portion of the primary lens 50, thereby forming an overlap joint 142 as best seen in Figure 14C. The overlap joint 142 may extend 360 degrees around the circumference of the secondary lens 60 as shown, or a fraction thereof. The circular extension of the secondary lens 60 rises above the anterior surface of the primary

lens 50 to form a raised portion. In some embodiments, the raised portion may have a radially tapering configuration. The raised portion may be radially compressed with forceps to facilitate connection and disconnection of the primary lens 50 and the secondary lens 60. Using radial compression to insert the secondary lens 60 into the primary lens 50 reduces the anterior-posterior forces applied to the capsular bag during insertion, thereby reducing the risk of capsular rupture.

[67] With reference to Figures 15-15D, an alternative modular IOL 150 is shown in front, sectional and detailed views, respectively. Figure 15A shows a cross-sectional view taken along line A-A in Figure 15, Figure 15B shows a cross sectional view taken along line B-B in Figure 15, Figure 15C shows a detail view of circle C in Figure 15B, and Figure 15D shows an alternative detail view of circle C in Figure 15B. Modular IOL 150 may include a primary lens 50 with haptics 54 and a secondary lens 60. The interfacing surfaces of the primary lens 50 (anterior surface) and secondary lens 60 (posterior surface) may be in intimate contact as best seen in Figures 15A and 15B. The primary lens 50 may include a recess defining a wall into which the correspondingly sized and shaped circular secondary lens 60 may be placed. The wall defined by the recess in the primary lens 50 may extend around the entire perimeter of the primary lens with the exception of two diametrically opposed gaps 152. The gaps 152 thus expose the perimeter edge of the secondary lens 60 as seen in Figure 15A to facilitate insertion and removal by radial compression of the secondary lens 60 using forceps, for example. The remainder of the wall defined by the recess in the primary lens provides for a flush joint as seen in Figures 15B and 15C, where the anterior surface of the secondary lens 60 may be flush with the anterior surface of the primary lens 50. As seen in Figure 15C, the wall defined by the recess in the primary lens 50 and the interfacing edge of the

secondary lens 60 may be canted inwardly to provide a joint 154 with positive mechanical capture and secure connection therebetween. Alternatively, as seen in Figure 15D, the wall defined by the recess in the primary lens 50 and the interfacing edge of the secondary lens 60 may be "S" shaped to provide a joint 156 with positive mechanical capture and secure connection therebetween. Alternative interlocking geometries may be employed.

[68] With reference to Figures 16-16D, an alternative modular IOL 160 is shown in front, sectional and detailed views, respectively. Figure 16A shows a cross-sectional view taken along line A-A in Figure 16, Figure 16B shows a cross sectional view taken along line B-B in Figure 16, Figure 16C shows a detail view of circle C in Figure 16B, and Figure 16D shows a detail view of circle D in Figure 16A. Modular IOL 160 may be configured similar to modular IOL 150 shown in Figures 15-15D with primary lens 50 including a recess defining a wall into which the correspondingly sized and shaped circular secondary lens 60 may be placed. However, in this embodiment, an angular gap 162 (rather than gap 152) is provided along a fraction of the perimeter of the secondary lens 60. The wall defined by a circumferential portion of the perimeter edge of the secondary lens 60 may have the same geometry as the wall defined by the recess in the primary lens 50 to provide a flush joint 154 as best seen in Figure 16C. The wall defined by another (e.g., the remainder) circumferential portion of the perimeter edge of the secondary lens 60 may have a more inwardly angled geometry to provide an angled gap 162 as best seen in Figure 16D. The angled gap 162 thus exposes the perimeter edge of the secondary lens 60 as seen in Figure 16D into which forceps may be placed to facilitate insertion and removal by radial compression of the secondary lens 60. Alternative gap geometries may be employed.

[69] With reference to Figures 17-17C, an alternative modular IOL 170 is shown in front, sectional, detailed and isometric views, respectively. Figure 17A shows a cross-sectional view taken along line A-A in Figure 17, Figure 17B shows a detail view of circle B in Figure 17A, and Figure 17C shows an isometric view of the assembled components. Modular IOL 170 may be configured similar to modular IOL 150 shown in Figures 15-15D with primary lens 50 including a recess defining a wall into which the correspondingly sized and shaped circular secondary lens 60 may be placed. However, in this embodiment, the wall defining the recess in the primary lens 50 includes a portion thereof that is milled down to define two diametrically opposed tabs 172. The inside circumferential walls of the tabs 172 provide for a flush joint 174 as seen in Figure 17B, such that the anterior surface of the secondary lens 60 is flush with the anterior surface of the primary lens 50. The interface of the joint 174 along the tabs 172 may be canted, "S" shaped, or "C" shaped as shown, for example. Elsewhere along the perimeter, away from the tabs 172, in the area where the wall is milled down, the perimeter edge of the secondary lens 60 is exposed as seen in Figure 17C, to facilitate insertion and removal of the secondary lens 60 by radial compression thereof using forceps, for example.

[70] With reference to Figures 18-18C, an alternative modular IOL 180 is shown in front, sectional, detailed and isometric views, respectively. Figure 18A shows a cross-sectional view taken along line A-A in Figure 18, Figure 18B shows a detail view of circle B in Figure 18A, and Figure 18C shows an isometric view of the assembled components. Modular IOL 180 may be configured similar to modular IOL 170 shown in Figures 17-17C with primary lens 50 including a recess defining a partial wall into which the correspondingly sized and shaped circular secondary lens 60 may be placed, interlocking via flush joint 174 in tabs 172. However, in this

embodiment, grasping recesses or holes 182 are provided in each of the tabs 172 and in the adjacent portions of secondary lens 60. In one embodiment, the grasping recesses or holes 182 may not extend through an entire thickness of primary 50 and secondary 60 lenses. The grasping holes 182 in the secondary lens 60 facilitate insertion and removal by radial compression of the secondary lens 60 using forceps, for example. Adjacent grasping holes 182 in the tab portion 172 and the secondary lens 60 may be pulled together or pushed apart in a radial direction to facilitate connection and disconnection, respectively, of the joint 174 using forceps, for example.

[71] Using radial forces applied via the grasping holes 182 to connect and disconnect (or lock and unlock) the joint 174 between the primary lens 50 and the secondary lens 60 reduces the anterior-posterior forces applied to the capsular bag, thereby reducing the risk of capsular rupture. Grasping holes 182 may also be used to facilitate connecting and disconnecting different interlocking geometries while minimizing anterior-posterior forces. For example, a recess in the primary lens 50 may include internal threads that engage corresponding external threads on the perimeter edge of the secondary lens 60. In this embodiment, forceps inserted into the grasping holes 182 may be used to facilitate rotation of the secondary lens 60 relative to the primary lens 50 to screw and unscrew the primary 50 and secondary 60 lenses. In an alternative embodiment, a keyed extension of the secondary lens 60 may be inserted into an keyed opening in the primary lens 50 and rotated using forceps inserted into the grasping holes 182 to lock and unlock the primary 50 and secondary 60 lenses. In another alternative embodiment, forceps or the like may be inserted posteriorly through a hole in the secondary lens 60 to grasp an anterior protrusion on the primary lens 50 like a handle (not shown), followed by applying

posterior pressure to the secondary lens 60 while holding the primary lens 50 stationary. The grasping holes 182 may also be used to rotate the secondary lens 60 relative to the primary lens 50 for purposes of rotational adjustment in toric applications, for example.

[72] With reference to Figures 19-19D, an alternative modular IOL 190 is shown in front, sectional, detailed, isometric exploded and isometric assembled views, respectively. Figure 19A shows a cross-sectional view taken along line A-A in Figure 19, Figure 19B shows a detail view of circle B in Figure 19A, Figure 19C shows an exploded isometric view of the components, and Figure 19D shows an assembled isometric view of the components. Modular IOL 190 differs from some of the previously described embodiments in that the primary component serves as a base 55 but does not necessarily provide for optical correction, whereas the secondary component serves as a lens 65 and provides for optical correction. Base 55 may be configured in the shape of an annulus or ring with a center opening 57 extending therethrough in an anterior-posterior direction. In some embodiments, base 55 may not define a complete ring or annulus. Base 55 may also include haptics 59, which are similar in function to haptics 54 described previously but differ in geometric configuration. Generally, haptics 54/59 function to center the base 55 in the capsular bag. Such haptics may also be configured to apply outward tension against the inside equatorial surface of the capsular bag, similar to capsular tension rings, to aid in symmetric healing and maintain centration of the base. The haptics 59 may include one or more openings therein.

[73] Because the base 55 includes a center opening 57, the posterior optical surface of the lens 65 is not in contact with the base 55. A circular extension may be formed in the lens 65, with a correspondingly sized and shaped circular

recess formed in the base 55 to form a ledge on the base 55 and an overlapping joint 192 with an interference and/or friction fit therebetween, thus securely connecting the two components. Alternatively, the shape of the overlapping joint 192 may form a canted angle or an "S" shape as described previously to form an interlock therebetween. The joint or junction 192 may include a modified surface to reduce light scattering caused by the junction 192. For example, one or both of the interfacing surfaces of the joint 192 may be partially to totally opaque or frosted (i.e., roughened surface) to reduce light scattering caused by the junction 192.

[74] The depth of the recess in the base 55 may be the same thickness of the circular extension of the lens 65 such that the anterior surface of the lens 65 and the anterior surface of the base 55 are flush as best seen in Figure 19B. With this arrangement, the posterior surface of the lens 65 extends more posteriorly than the anterior surface of the base 55. In some embodiments, however, the anterior surface of lens 65 may be disposed relatively higher or lower than the anterior surface of base 55. The dimensions of the recess and the corresponding ledge in the base 55 may be selected relative to the thickness of the lens 65 such that at least a portion of the posterior-most surface of the lens 65 is coplanar with the posterior-most surface of the base 55, or such that at least a portion of the posterior-most surface of the lens 65 is more posterior than the posterior-most surface of the base 55.

[75] As with prior embodiments, the lens may be exchanged for a different lens either intra-operatively or post-operatively. This may be desirable, for example, if the first lens does not provide for the desired refractive correction, in which case the first lens may be exchanged for a second lens with a different refractive correction, without disturbing the lens capsule. In cases where the lens 65 does not

have the desired optical alignment due to movement or misalignment of the base, for example, it may be exchanged for a different lens with an optical portion that is manufactured such that it is offset relative to the base 55. For example, the optical portion of the second lens may be offset in a rotational, lateral and/or axial direction, similar to the embodiments described with reference to Figures 9A-9D. This general concept may be applied to other embodiments herein where the secondary component (e.g., lens) has limited positional adjustability relative to the primary component (e.g., base).

[76] A number of advantages are associated with the general configuration of this embodiment, some of which are mentioned hereinafter. For example, because the posterior optical surface of the lens 65 is not in contact with the base 55, the potential for debris entrapment therebetween is eliminated. Also, by way of example, because the base 55 includes a center opening 57 that is devoid of material, the base 55 may be rolled into a smaller diameter than a primary lens 50 as described previously to facilitate delivery through a smaller incision in the cornea. Alternatively, the base 55 may have a larger outside diameter and be rolled into a similar diameter as primary lens 50. For example, the base lens 55 may have an outside diameter (excluding haptics) of approximately 8mm and be rolled into the same diameter as a primary lens 50 with an outside diameter 6mm. This may allow at least a portion of the junction between the base 55 and lens 65 to be moved radially outward away from the circumferential perimeter of the capsulorhexis, which typically has a diameter of 5-6mm. Moving at least a portion of the junction between the base 55 and the lens 65 radially outward from the perimeter of the capsulorhexis may reduce the amount of the junction that is in the field of view and thus reduce the potential for light scattering or optical aberrations (e.g., dysphotopsias) created

thereby. Of course, notwithstanding this example, any suitable dimensions may be selected to provide a gap between the lens 65 and the perimeter edge of the capsulorhexis in order to mitigate the need to manipulate the lens capsule to connect or disconnect the lens 65 to or from the base 55.

[77] With reference to Figures 20-20D, an alternative modular IOL 200 is shown in front, sectional, detailed, isometric exploded and isometric assembled views, respectively. Figure 20A shows a cross-sectional view taken along line A-A in Figure 20, Figure 20B shows a detail view of circle B in Figure 20A, Figure 20C shows an exploded isometric view of the components, and Figure 20D shows an assembled isometric view of the components. Modular IOL 200 includes a base 55 with associated haptics 59 and a lens 65. The base 55 includes a center hole 57 such that the posterior optical surface of the lens 65 is not in contact with the base 55. The lens 65 includes a circular extension that is sized and shaped to fit in a circular recess formed in the base 55 to form a ledge on the base 55 and an overlapping joint 202. The overlapping joint 202 may be configured with an "S" shaped interface to securely connect the two components. Thus, modular IOL 200 is similar to modular IOL 190, except that the joint 202 between the base 55 and the lens 65 may include a peg-and-hole arrangement. In this arrangement, a pair of diametrically opposed pegs 204 may extend posteriorly from the posterior perimeter of the lens 65 and fit within a selected pair of holes 206 from a series of holes 206 formed in the ledge of the joint 202 in the base 55.

[78] Figures 20E-20I show additional detail of modular IOL 200. Figure 20E shows a side view of the lens 65, Figure 20F shows a rear view of the posterior surface of the lens 65, Figure 20G is a detailed view of circle G in Figure 20E, Figure 20H is a front view of the anterior surface of the base 55, and Figure 20I is a detailed

view of circle I in Figure 20H. As seen in Figures 20E-20F, a pair of diametrically opposed pegs 204 may extend posteriorly from the posterior perimeter of the lens 65. As seen in Figures 20H-20I, the inside diameter of the base 55 along the ledge of the joint 202 includes a series of holes 206, into a selected pair of which the pair of pegs 204 may be inserted. With this arrangement, the lens 65 may be selectively rotated relative to the base 55 for purposes of rotational adjustment in toric applications, for example.

[79] With reference to Figures 21-21 E, an alternative modular IOL 210 is shown in front, sectional, detailed and isometric views, respectively. Figures 21A and 21B show a cross-sectional views taken along line A-A and line B-B, respectively, in Figure 21. Figures 21C and 21D show detail views of circle C in Figure 21A and circle D in Figure 21B, respectively. Figure 21E shows an isometric view of the assembled components of the modular IOL 210. Modular IOL 210 may be configured similar to a combination of modular IOL 190 shown in Figures 19-19D and modular IOL 170 shown in Figures 17-17C. Like modular IOL 190, modular IOL 210 includes a base 55 configured in the shape of an annulus or ring with a center opening and a recess defining a wall into which the correspondingly sized and shaped circular lens 65 may be placed. Like modular IOL 170, the wall defining the recess extends along the inside perimeter of the base 55, with a portion thereof milled down to define two diametrically opposed tabs 212. The inside circumferential walls of the tabs 212 provide for a flush joint 214 as seen in Figure 21C, such that the anterior surface of the lens 65 is flush with the anterior surface of the base 55. The interface of the joint 214 along the tabs 212 may be canted, "S" shaped, or "C" shaped as shown, for example. Elsewhere along the perimeter, away from the tabs 212, in the area where the wall is milled down, the perimeter edge of the lens 65 is

exposed as seen in Figure 21D, to facilitate insertion and removal of the lens 65 by radial compression using forceps, for example.

[80] With reference to Figures 22-22D, an alternative modular IOL 220 is shown in front, sectional, and detailed views, respectively. Figure 22A shows a cross-sectional view taken along line A-A in Figure 22, Figure 22B a cross-sectional view taken along line B-B in Figure 22, Figure 22C shows a detail view of circle C in Figure 22A, and Figure 22D shows a detail view of circle D in Figure 22B. Modular IOL 220 includes a base 55 with associated haptics 59 and a lens 65. The base 55 includes a center hole such that the posterior optical surface of the lens 65 is not in contact with the base 55. The perimeter of the lens 65 is sized and shaped to fit in a circular recess formed in the base 55 to form a ledge on the base 55 and a flush joint 222. The flush joint 222 may be configured with an "S" shaped interface to securely connect the two components. A pair of pegs 224 extend anteriorly from the base 55 adjacent the inside perimeter thereof, and through a pair of arc-shaped slots 226 adjacent the perimeter of the lens 65. The arc-shaped slots may extend along a fraction of the circumference of the lens 65 as shown in Figure 22. With this arrangement, the lens 65 may be selectively rotated relative to the base 55 for purposes of rotational adjustment in toric applications, for example.

[81] The pegs 224 may be sized and configured to rise above the anterior surface of the lens 65 as shown in Figure 22C. Forceps or the like may be inserted posteriorly through the arc-shaped slots 226 in the lens 65 to grasp the pegs 224 like a handle, followed by applying posterior pressure to the lens 65 while holding the pegs 224 stationary. By holding the pegs 224 and thus stabilizing the base 55 during connection of the lens 65 to the base 55, anterior-posterior forces applied to the capsular bag are reduced, thereby reducing the risk of capsular rupture.

[82] With reference Figures 23A-23D, a lens removal system for a modular IOL according to an embodiment of the present disclosure is shown schematically. Figures 23A and 23B are side and top views, respectively, of the lens removal system. Figures 23C and 23D are top views showing how the lens removal system may be used to remove lens 60/65. The lens removal or extractor system may include a cannula 230 and a pair of forceps 235. The cannula 230 may include a lumen sized to slidably receive the forceps 235. The cannula 230 may include a tubular shaft portion 232 and a contoured distal opening 234. The cannula 230 may be formed and configured similar to conventional IOL insertion devices, for example. The forceps 235 include a pair of atraumatic grasping tips 237 and a tubular shaft 239. The tubular shaft 239 may be advanced to compress the tips 237 and grasp the lens 60/65. The forceps 235 may be formed and configured similar to conventional ophthalmology forceps, for example, except that the tips 237 may be formed of or covered by a relatively soft polymeric material to avoid damage to the lens 60/65. Generally, any devices used to manipulate the modular IOL components described herein may be formed of or covered by a relatively soft polymeric material to avoid damage to the components thereof.

[83] With reference to Figures 23C and 23D, the cannula 230 may be inserted through a corneal incision until its distal end is adjacent the capsulorhexis. The forceps 235 may be inserted into and through the cannula 230, until the distal tips 237 extend distally beyond the distal end of the cannula 230. The lens 60/65 to be extracted may be grasped with the forceps 235 as shown in Figure 23C. With the lens 60/65 securely held by the forceps 235, the forceps 235 may be retracted proximally into the cannula 230. As the forceps 235 are retracted into the cannula 230, the lens 60/65 enters the contoured opening 234. The contoured opening 234

encourages the edges of the lens 60/65 to roll and fold as seen in Figure 23D. Complete retraction of the forceps 235 into the cannula 230 thus captures the lens 60/65 safely in the lumen of the cannula 230 after which it may be removed from the eye. A similar approach may also be used to insert the lens 60/65, reversing the relevant steps.

[84] Figures 24-26 describe example methods of using modular IOLs according to embodiments of the present disclosure. Although described with reference to a primary lens and a secondary lens by way of example, not necessarily limitation, the same or similar methods may be applied other modular IOL embodiments, including modular IOL embodiments described herein that comprise a base and a lens.

[85] With reference to Figure 24, a method for using a modular IOL according to an embodiment of the present disclosure is shown in a schematic flow chart. In this example, the secondary lens may be exchanged in the event of a sub-optimal optical result detected intra-operatively. An IOL implant procedure, such as cataract surgery, may be started 110 according to conventional practice. The native lens may then be prepared 112 to receive a modular IOL using conventional steps such as making corneal access incisions, cutting the capsulorhexis in the anterior capsular bag and removing the cataract lens by phacoemulsification. The base lens (i.e., primary lens 50) is then placed 114 in the lens capsule. The secondary lens (i.e., secondary lens 60) is then placed 116 on the base lens within the perimeter of the capsulorhexis without touching or otherwise disturbing the capsular bag. The attachment means is then engaged 118 to releasably connect the secondary lens to the base lens. Alternatively, the secondary lens may be attached to the base lens before placement in the lens capsule, such that the base lens and the secondary

lens are inserted together as a unit. With both the base lens and the secondary lens in place, the optical result may be measured 120, for example by intra-operative aberrometry. The optical result may take into consideration refractive correction, centricity, toric correction, etc. A decision 122 is then made as to whether the optical result is optimal or sub-optimal. If the optical result is optimal or otherwise adequate, the IOL procedure is completed 124. However, if the optical result is sub-optimal, inadequate and/or the patient is otherwise dissatisfied, the attachment means may be disengaged 126 and the secondary lens may be removed 128. A different secondary lens may be then placed 116 on the base lens, following the same subsequent steps as shown. The different secondary lens may have, for example, a different refractive power to correct refractive error, a different offset to correct for decentration, or a different toric power to correct for toric error.

[86] With reference to Figure 25, an alternative method for using a modular IOL according to an embodiment of the present disclosure is shown in a schematic flow chart. In this example, the secondary lens may be exchanged in the event of a sub-optimal optical result detected post-operatively. The same steps 110-118, and 124 may be performed as described previously, except that the patient is allowed to acclimate 130 to the modular IOL for a period of 1-4 weeks or more, for example. Upon a return visit, the optical result is measured 120 and a determination 122 is made as to whether the optical result is optimal or sub-optimal. If the optical result is optimal or otherwise adequate, the procedure is stopped 132. If the optical result is sub-optimal, inadequate and/or the patient is otherwise dissatisfied, a revision procedure may be initiated 134 to replace the secondary lens following steps 126, 128, 116 and 118 as described previously.

[87] This method allows the lens capsule to heal before deciding whether the optical result is sufficient, which may be advantageous to the extent the healing process alters the position of the primary and/or secondary lens. This method may also be applied on a chronic basis, where the optical needs or desires of the patient change over the course of a longer period of time (e.g., > 1 year). In this example, the patient may require or desire a different correction such as a stronger refractive correction, a toric correction, or a multifocal correction, each of which may be addressed with a different secondary lens.

[88] With reference to Figure 26, another alternative method for using a modular IOL according to an embodiment of the present disclosure is shown in a schematic flow chart. In this example, the secondary lens may be implanted in a patient 138 having a pre-existing IOL that is optically sub-optimal or otherwise doesn't meet the needs and desires of the patient. After the procedure starts 110, an attachment mechanism may be formed *in-situ* in the pre-existing (base) IOL (step 140) using laser etching, for example, to form a groove as described previously. Formation of the groove may be performed within the perimeter of the previously cut capsulorhexis to avoid touching or otherwise disturbing the lens capsule. The secondary lens may then be placed 116 on the base lens within the perimeter of the capsulorhexis, and the attachment means may be engaged 118 to connect the secondary lens to the base lens, and the procedure may be completed 124 as described previously.

[89] With reference to Figures 27-27D, an alternative modular IOL 270 is shown in front, sectional and detailed views, respectively. Figures 27A and 27B show cross-sectional views taken along line A-A and line B-B, respectively, in Figure 27. Figures 27C and 27D show detail views of circle C in Figure 27A and circle D

Figure 27B, respectively. Modular IOL 270 may be configured similar to modular IOL 210 shown in Figures 21-21 D. Like modular IOL 210, modular IOL 270 includes a base 55 configured in the shape of an annulus or ring with a center opening and a recess defining a wall into which the correspondingly sized and shaped circular lens 65 may be placed. Also like modular IOL 210, the wall defining the recess extends along the inside perimeter of the base 55, with a portion thereof milled down to define two diametrically opposed tabs 272. The inside circumferential walls of the tabs 272 provide for a flush joint 274 as seen in Figure 27C, such that the anterior surface of the lens 65 is flush with the anterior surface of the base 55. The interface of the joint 274 along the tabs 272 may be canted, "S" shaped, or "C" shaped as shown, for example. Elsewhere along the perimeter, away from the tabs 272, in the area where the wall is milled down, the perimeter edge of the lens 65 is exposed as seen in Figure 27D, to facilitate insertion and removal of the lens 65 by radial compression using forceps, for example.

[90] Because the base 55 includes a center opening that is devoid of material, the base 55 may have a larger outside optic diameter (excluding haptics) of approximately 8mm, for example, and still be rolled into a delivery profile that is sufficiently small to fit through a corneal incision of less than approximately 2.4mm, for example. This may allow at least a portion of the junction between the base 55 and lens 65 to be moved radially outward away from the circumferential perimeter of the capsulorhexis, which typically has a diameter of 5-6mm. Moving at least a portion of the junction between the base 55 and the lens 65 radially outward from the perimeter of the capsulorhexis may reduce the amount of the junction that is in the field of view and thus reduce the potential for light scattering or optical aberrations (e.g., dysphotopsias) created thereby.

[91] To further illustrate this advantage, consider a standard (single component) IOL, which typically has an optic diameter of conventional lenses is 6mm. An IOL with a 6mm diameter optic may be rolled and delivered through a 2.2mm corneal incision. In order to secure the standard IOL in the capsular bag, the capsulorhexis is typically sized to allow the capsular bag to fully capture the standard IOL after the bag collapses and heals down. This drives surgeons to form a capsulorhexis having a diameter of approximately 4.5mm to 5.5mm.

[92] Now consider IOL 270 by comparison. The modular (two piece) nature of IOL 270 and the hole in the base 55 allow both components (base 55 and lens 65) to be rolled and delivered through a small corneal incision (e.g., 2.2mm), but don't require a capsulorhexis of 4.5mm to 5.5mm. Rather, because the base has a diameter of 8mm (excluding haptics), the capsulorhexis diameter may be larger (e.g., 6.0mm to 6.5mm), which allows the lens 65 to comfortably fit inside the perimeter of the capsulorhexis and allows the junction 274 to be more peripheral to further minimize light scatter. Of course, notwithstanding these examples, any suitable dimensions may be selected to provide a gap between the lens 65 and the perimeter edge of the capsulorhexis in order to mitigate the need to manipulate the lens capsule to connect or disconnect the lens 65 to or from the base 55.

[93] With reference to Figures 28A-28G, an alternative modular IOL 280 is shown. Modular IOL 280 may have dimensions as shown in the drawings by way of example, not necessarily limitation. Modular IOL 280 may be the same or similar in terms of functions and advantages as other modular IOL embodiments described herein. Modular IOL 280 provides an alternative interlocking feature used to connect the base and lens as described in more detail hereinafter.

[94] Figures 28A-28D show the base portion 55 of the modular IOL 280, and Figures 28E-28G show the lens portion 65 of the modular IOL 280. Specifically, Figure 28A shows a front view of the base 55, Figure 28B shows a cross-sectional view taken along line B-B in Figure 28A, Figure 28C shows a cross-sectional view taken along line C-C in Figure 28A, and Figure 28D shows a perspective view of the base 55. Figure 28E shows a front view of the lens 65, Figure 28F shows a cross-sectional view taken along line F-F in Figure 28E, and Figure 28G shows a perspective view of the lens 65.

[95] With specific reference to Figures 28A-28D, the base 55 portion of the modular IOL 280 includes a pair of haptics 54 and a center hole 57 such that all or a majority of the posterior optical surface of the lens 65 is not in contact with the base 55 when the lens 65 is attached to the base 55. A recessed ledge 282, which is sized and configured to receive the lens 65, defines the perimeter of the hole 57. The ledge 282 may include one or more keyed portions 284 that are sized and configured to receive tabs 286 on the lens 65.

[96] With specific reference to Figures 28E-28G, the lens 65 includes an optic portion 287 and one or more tabs 286, each with a thru hole 288. Tabs 286 are sized to fit into the keyed portions 284 in the base. More particularly, the tabs 286 may be aligned with the opening (discontinuity of the ledge 282) in the keyed portion 284 and moved posteriorly to rest against a lower portion 283 of the ledge 282 within the keyed portion 284. A probe or similar device may be used to engage the hole 288 in the tab 286, and rotated (e.g., clockwise as shown) to slide the tab 286 in the keyed portion 284 until the tab 286 partially resides under an upper portion 285 of the ledge 282 within the keyed portion 284, thereby connecting the lens 65 to the

base 55. Reverse steps may be followed to disconnect the lens 65 from the base 55.

[97] With reference to Figures 29A-29F, an alternative modular IOL 290 is shown. Modular IOL 290 may have dimensions as shown in the drawings by way of example, not necessarily limitation. Modular IOL 290 may be the same or similar in terms of functions and advantages as other modular IOL embodiments described herein. Modular IOL 290 provides an alternative interlocking feature used to connect the base and lens as described in more detail hereinafter.

[98] Figures 29A-29C show the base portion 55 of the modular IOL 290, and Figures 29D-29F show the lens portion 65 of the modular IOL 290. Specifically, Figure 29A shows a front view of the base 55, Figure 29B shows a cross-sectional view taken along line B-B in Figure 29A, and Figure 29C shows a perspective view of the base 55. Figure 29D shows a front view of the lens 65, Figure 29E shows a cross-sectional view taken along line E-E in Figure 29D, and Figure 29F shows a perspective view of the lens 65.

[99] With specific reference to Figures 29A-29C, the base 55 portion of the modular IOL 290 includes a pair of haptics 54 and a center hole 57 such that, except for the outermost portion, the posterior optical surface of the lens 65 is not in contact with the base 55 when the lens 65 is attached to the base 55. A recessed groove 292, which is sized and configured to receive tab portions 295 and 296 of the lens 65, defines the perimeter of the hole 57.

[100] Recessed groove 292 includes a lower rim 291 and an upper rim 293. The upper rim 293 may have an inside diameter that is greater than the outside diameter of the lens 65 such that the lens 65 can rest inside the hole 57 of the base 55. All or a portion of the lower rim 291 may have an inside diameter that is less

than the outside diameter of the lens 65 such that the lower rim 291 acts as a backstop for the lens 65 when placed in the hole 57 of the base 55. By way of example, not necessarily limitation, the upper rim 293 may have an inside diameter of about 6.0mm, the lower rim 291 may have an inside diameter of about 5.5mm, and the lens 65 may have an outside diameter (including tabs 295 and 296) of about 5.8mm.

[101] The lower 291 and upper 293 rims defining the groove 292 may extend continuously around all or a portion of the perimeter of the hole 57. Alternatively, the lower 291 and upper 293 rims defining the groove 292 may extend discontinuously around all or a portion of the perimeter of the hole 57. An example of a discontinuous arrangement is alternating segments of the lower 291 and upper 293 rims, which may lend itself well to cryo-machining the base 55 in a single part. As shown, the base 55 may be cryo-machined in two parts, including lower or posterior portion 55A and upper or anterior portion 55B, that are subsequently bonded (e.g., adhesive or solvent bond), which may lend itself well to defining a continuous groove 292. To maintain chemical and mechanical property compatibility, the adhesive and the parts 55A/55B of the base 55 may comprise the same monomeric or polymeric formulation. For example, the adhesive may be formulated from the same acrylic monomers used in making the hydrophobic acrylic parts 55A/55B of the base 55. Alternative manufacturing methods well known in the art may also be employed.

[102] Optionally, the base posterior portion 55A may be a solid disc, rather than an annular ring with a hole 57, thereby defining a posterior surface against which the posterior side of the lens 65 would contact. The posterior surface may be flat or curved to conform to the posterior contour of the lens 65. This may have the advantage of providing a backstop for the lens 65 thereby making delivery and

positioning of the lens 65 in the base 55 easier. This may also provide the advantage of reducing the rate of posterior capsular opacification.

[103] With specific reference to Figures 29D-29F, the lens 65 of the modular IOL 290 includes an optic portion 297 and one or more tabs 295 and 296. As shown, tab 295 is fixed, whereas tab 296 may be actuated. As an alternative, fixed tab 295 may be replaced with an actuable tab (e.g., like tab 296). Fixed tab 295 may include a thru hole 298 so that a probe or similar device may be used to engage the hole 288 and manipulate the tab 295. Actuable tab 296 may be actuated between a compressed position for delivery into the hole 57 of the base 55, and an uncompressed extended position (shown) for deployment into the groove 292 of the base 55, thus forming an interlocking connection between the base 55 and the lens 65.

[104] The outside curvature of the fixed tab 295 may have a radius conforming the inside radius of the groove 292. Similarly, the outside curvature of the actuable tab 296 may have a radius that conforms to the inside radius of the groove 292 when the actuable tab 296 is in its uncompressed extended position. This arrangement limits relative movement between the base 55 and the lens 65 once connected.

[105] Optionally, the lens 65 may be oval or ellipsoidal, rather than circular, with the tabs 295 and 296 positioned adjacent the long axis. This arrangement would thus define a gap between the edge of the lens 65 along its short axis and the inside perimeter of the upper rim 293 of the groove 292 in the base 55. The gap may have the advantage of providing access for a probe or similar device to pry apart the lens 65 from the base 55 if separation were needed.

[106] Actuable tab 296 may be attached to and extend from the lens 65 at two ends with the middle portion free of the lens 65 (like a leaf spring) as shown. Alternatively, actuable tab 296 may be attached to and extend from the lens 65 at one end with the other end free (like a cantilever spring). Other spring configurations may be employed as know in the mechanical arts.

[107] The actuable tab 296 may elastically deform (e.g., by application of an inward lateral force) to its compressed position. To facilitate low force compression, a dimple 299 may be provided on the outside (and/or inside) curvature of the tab to form a hinge in the spring.

[108] The modular IOL 290 may be implanted by initially delivering the base 55 into the capsular bag as described previously. Once the base 55 has been delivered and unfurled in the capsular bag, the lens 65 may be connected to the base 55 by first inserting the fixed tab 295 into the groove 292. The actuable tab 296 may then be compressed by application of a lateral force using a probe or similar device, allowing the lens 65 to be advanced into the hole 57 of the base 55 such that the lens 65 and base 55 are coplanar. The compressive force may then be released from the actuable tab 296, allowing it to elastically expand into the groove 292 of the base 55, thus connecting the lens 65 to the base 55. By using a lateral force to compress the interlocking feature rather than an anterior-posterior force, the risk of posterior rupture of the capsular bag is reduced. Reverse steps may be followed to disconnect the lens 65 from the base 55.

[109] The actuable tab 296 and groove 292 may be described as interlocking members that provide an interlocking connection between the base 55 and the lens 65, wherein at least one of the pair of interlocking members is actuable to lock or unlock the connection therebetween. More generally, one or

more interlocking connections may be provided between the base and lens. Each interlocking connection may include a pair of interlocking members, wherein one or both of the interlocking members are actuatable. The actuatable interlocking member may be associated with the lens as described with reference modular IOL 290 in Figures 29A-29F. Alternatively, the actuatable interlocking member may be associated with the base 55 as described with reference to modular IOL 300 shown in Figures 30A-30B.

[110] Figures 30A-30B show an alternative modular IOL 300 including a base 55 and a lens 65. Figure 30A shows a front view of the base 55, and Figure 30B shows a perspective view of the lens 65. The base 55 may include a center hole 57 and a pair of haptics 54 as described previously. Base 55 may also include one or more actuatable tabs 302 sized and configured to fit within a groove 304 in the lens 65. As shown, base 55 includes a pair of actuatable tabs 302, although one of the tabs may be fixed (i.e., not actuatable). Lens 65 includes an optical portion 307 and one or more grooves 304 defined by lower 303 and upper 305 rims. Because the lens 65 may be relatively thin around the perimeter where the groove 304 resides, the groove 304 may be defined by extending the lower 303 and upper 305 rims as shown. As may be appreciated by those skilled in the art, the actuatable tabs 302 and grooves 304 in this embodiment may be the same or similar to the actuatable tab 296 and groove 292 described in the previous embodiment, including the same or similar function, use, variants and advantages.

[111] With reference Figures 31A-31 B, a lens removal or extractor system 310 for a modular IOL according to an embodiment of the present disclosure is shown schematically. Figure 31A shows a perspective view of the extractor system 310 with the lens 60/65 captured, and Figure shows a perspective view of the

extractor system 310 with the lens 60/65 transected. The extractor system 310 is shown in a foreshortened view for purposes of illustration only. The length and diameter of the extractor system 310 may be selected for manual operation through a conventional corneal incision, such as the dimensions of a conventional lens cartridge.

[112] The extractor system includes a handle 314 and a sleeve 312 extending distally therefrom. The sleeve 312 is hollow inside and includes a tongue extension 313 to support the lens 60/65.

[113] A grabber 316 extends distally from the sleeve 312 and is retractable therein by an actuating member (not shown) extending proximally through the handle 314. The grabber 316 may include a distal hook, forceps or other mechanism to engage and pull the lens 60/65. In this example, the grabber 316 engages the distal (opposite) edge of the lens 60/65. Alternatively, micro forceps may be used to grasp the proximal edge of the lens 60/65, or a sharp instrument may be used to penetrate the anterior surface of the lens 60/65 near the proximal edge. This can be done safely as the sharp point is introduced through the sleeve 312 and the extended tongue 313 protects eye anatomy.

[114] A pair of blades 318 may extend slightly beyond the distal end of the sleeve 312 on opposite sides of the proximal end of the tongue extension 313 as shown. Using blade actuator 319, the blades 318 may be advanced for cutting as shown in Figure 31A or retracted into sleeve 312 for no cutting as shown in Figure 31B.

[115] In use, with the lens 60/65 removed from the base in the capsular bag (not shown) and resident in the anterior chamber, the sleeve 312 may be inserted through the corneal incision, and the tongue extension 313 may be positioned under

the lens 60/65 to be extracted. The grabber 316 may then be advanced over the lens 60/65. With the blades 318 extended for cutting, the grabber 316 may be retracted into the sleeve 312 to form cuts in the lens 60/65 that divide the lens into a center section and two lateral sections. The grabber 316 may be retracted until the cuts extend partially (e.g., 80%) across the diameter of the lens, thus retaining a connection between the center section and the two lateral sections. At this point, the blades 318 may be retracted using actuator 319. The grabber 316 may then be retracted further, causing the center section of the lens 60/65 to be pulled into the sleeve 312 and the lateral sections of the lens 60/65 to flip or rotate. Further retraction of the grabber 316 causes the lateral sections of the lens 60/65 to overlap and follow the center section into the sleeve 312. The extractor system 310 may then be removed from the corneal incision, and the lens 60/65 is thus extracted from the eye. The extractor system 310 may also be used to extract other optics, including optics with haptics, where the haptics follow the lateral sections into the sleeve.

[116] The foregoing discussion of the invention has been presented for purposes of illustration and description. The foregoing is not intended to limit the invention to the form or forms disclosed herein. Although the description of the invention has included description of one or more embodiments and certain variations and modifications, other variations and modifications are within the scope of the invention, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights which include alternative embodiments to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures,

functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

CLAIMSWe claim:

1. An intraocular lens system for implantation into a lens capsule of an eye having a capsulorhexis with a perimeter, comprising:
 - a. an intraocular primary component having a body, one or more haptics and a first interlocking member, the primary component configured to fit within the lens capsule, the body having an equatorial perimeter greater than or equal to the perimeter of the capsulorhexis; and
 - b. an intraocular secondary component having a second interlocking member and an optical body with an equatorial perimeter less than the perimeter of the capsulorhexis;
 - c. wherein the first interlocking member of the primary component is configured to releasably receive and connect to the second interlocking member of the secondary component to form an interlocking connection therebetween, and wherein at least one of the first and second interlocking members is actuatable.
2. A system as in claim 1, wherein the primary component includes a center hole extending in an anterior-posterior direction, wherein the hole is sized and configured to receive the secondary component.
3. A system as in claim 1, wherein the primary component is a base and the secondary component is a lens.

4. A system as in claim 1, wherein the primary component is a primary lens and the secondary component is a secondary lens.
5. A system as in claim 1, wherein the first interlocking member is actuatable, and the second interlocking member is fixed.
6. A system as in claim 1, wherein the first interlocking member is fixed, and the second interlocking member is actuatable.
7. A system as in claim 6, wherein the actuatable interlocking member comprises a spring mechanism.
8. A system as in claim 7, wherein the spring mechanism comprises a cantilever spring.
9. A system as in claim 7, wherein the spring mechanism comprises a leaf spring.
10. A system as in claim 7, wherein the actuatable interlocking member comprises an extension and the fixed interlocking member comprises a recess.

11. An intraocular lens (IOL) system for implantation into a lens capsule of an eye having a capsulorhexis with an inside dimension, comprising:
- a. a base having a body with one or more haptics extending therefrom, wherein the body has an outside dimension greater than the inside dimension of the capsulorhexis; and
 - b. a lens having an optical body with a diameter less than the inside dimension of the capsulorhexis;
 - c. wherein the base and the lens are connected by interlocking members associated with each of the base and the lens, and wherein at least one of the interlocking members is actuatable.
12. An IOL system as in claim 11, wherein the base includes an optical portion.
13. An IOL system as in claim 11, wherein the base is annular defining a hole sized and configured to receive the lens therein.
14. An IOL system as in claim 11, wherein the base includes the actuatable interlocking member.
15. An IOL system as in claim 11, wherein the lens includes the actuatable interlocking member.
16. An IOL system as in claim 11, wherein the actuatable interlocking member comprises an extension and the other interlocking member comprises a recess.

17. A method of implanting a modular intraocular lens (IOL) in a lens capsule of an eye, wherein the modular IOL includes a primary component releasably attached to a secondary component by at least one actuatable connector, the method comprising:

- a. preparing the lens capsule for implantation of an IOL including forming a capsulorhexis;
- b. placing the primary component into the lens capsule; and
- c. securing the secondary component to the primary component within a perimeter of the capsulorhexis by actuating the connector.

18. A method as in claim 17, further comprising:

removing the secondary component from the primary component without removing the primary component from the lens capsule.

19. A method as in claim 18, further comprising:

securing a different secondary component having a different optical property to the primary component without removing the primary component from the lens capsule.

20. A method as in claim 17, wherein actuating the connector comprises applying a lateral force to reduce posterior pressure applied to the lens capsule.




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D

4/30




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D





FIG. 11A




FIG. 11D




FIG. 11B




FIG. 11E




FIG. 11C




FIG. 11F

8/30




FIG. 12A




FIG. 12B




FIG. 12C

9/30





FIG. 13A



ETCHED GROOVE

FIG. 13B

FIG. 14




FIG. 14B

FIG. 14C





FIG. 14A






FIG. 16A

FIG. 16




FIG. 16B




FIG. 16C




FIG. 16D




FIG. 17




FIG. 17B








FIG. 17C






FIG. 19




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG. 20




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D

17/30




FIG. 20E




FIG. 20F




FIG. 20G




FIG. 20H




FIG. 20I




FIG. 21




FIG. 21B




FIG. 21A




FIG. 21C




FIG. 21D




FIG. 21E




FIG. 22




FIG. 22B




FIG. 22A




FIG. 22C








FIG. 22D

20/30







FIG. 24







FIG. 26



25/30




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 28D

26/30





FIG. 28F




FIG. 28G

27/30




FIG. 29A




FIG. 29B




FIG. 29C




FIG. 30A






FIG. 30B

30/30



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2014/037646

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/16
 ADD.
 According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
 Minimum documentation searched (classification system followed by classification symbols)
A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal , WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/158560 AI (PORTNEY VALDEMAR [US]) 21 August 2003 (2003-08-21)	1,4, 11, 12
Y	paragraphs [0003] , [0084] , [0085] , [0090] - [0096] , [0112] ; claims 1, 18;	2, 3, 13-16
A	figures 1B, 2, 3, 9A-D, 24A, 24B -----	5, 6, 10
Y	US 2004/148022 AI (EGGLESTON HARRY C [US]) 29 July 2004 (2004-07-29)	2, 3, 13-16
A	paragraphs [0002] , [0014] , [0022] , [0082] ; claims 2, 6, 10, 11; figures 12, 12A, 14 -----	1, 5, 6
A	US 6 113 633 A (PORTNEY VALDEMAR [US]) 5 September 2000 (2000-09-05) column 1, lines 8-12 column 2, line 44 - column 3, line 65; figures 1, 3, 6 -----	1, 2, 4, 6, 7, 11-13
	-/- .	

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 6 August 2014	Date of mailing of the international search report 18/08/2014
---	---

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Merte, Bi rgi t
--	--

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2014/037646

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2004/236422 A1 (ZHANG XIAOXIAO [US] ET AL) 25 November 2004 (2004-11-25) claims 1,6,7; figures 4,5 -----	1,11
X,P	W0 2013/112589 A1 (UNIV COLORADO [US]) 1 August 2013 (2013-08-01) paragraphs [0002], [0010], [0071], [0076], [0077]; claims 1,2,9,10,13,15,16,19-22,24-27; figures -----	1-6, 10-16

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2014/037646

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: 17-20
because they relate to subject matter not required to be searched by this Authority, namely:
Claim 17 and claims 18-20 depending therefrom are directed to a method of implanting a modular IOL in a lens capsule of an eye; comprising the highly invasive step "forming a capsulorhexis" this is a method for treatment of the human or animal body by surgery [Rule 39.1(iv) PCT].
2. Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable items.
2. As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos. :
4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.

The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.

No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/US2014/037646
--

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2003158560	A1	21-08-2003	NONE

US 2004148022	A1	29-07-2004	NONE

US 6113633	A	05-09-2000	EP 0877586 A1 18-11-1998
		JP 2000503867 A	04-04-2000
		US 6113633 A	05-09-2000
		US 6454801 B1	24-09-2002
		US 2002161436 A1	31-10-2002
		WO 9726842 A1	31-07-1997

US 2004236422	A1	25-11-2004	NONE

WO 2013112589	A1	01-08-2013	US 2013190868 A1 25-07-2013
		US 2013310931 A1	21-11-2013
		US 2014052246 A1	20-02-2014
		WO 2013112589 A1	01-08-2013
