Dec. 7, 1971 J. J. ATTAWAY 3,624,973

CONJOINT FACIA AND WATER DAM

Filed Jan. 7, 1970 3 Sheets-Sheet 1

FIG. 1





FIG. 2



INVENTOR

Julian J. Attaway

BY John B. Hammond

ATTORNEY

Dec. 7, 1971 J. J. ATTAWAY 3,624,973

CONJOINT FACIA AND WATER DAM

Filed Jan. 7, 1970 3 Sheets-Sheet 2

FIG. 3




FIG. 4





FIG. 5



INVENTOR
Julian J. Attaway

BY John B. Armstrong

ATTORNEY

Dec. 7, 1971 J. J. ATTAWAY 3,624,973

CONJOINT FACIA AND WATER DAM

Filed Jan. 7, 1970 3 Sheets-Sheet 3

FIG. 6




FIG. 7





FIG. 8



INVENTOR

Julian J. Attaway

BY John B. Armentrout

ATTORNEY

United States Patent Office

3,624,973

Patented Dec. 7, 1971

3,624,973

CONJOINT FACIA AND WATER DAM

Julian J. Attaway, Tucker, Ga., assignor to Miscellaneous Manufacturing Corporation, Tucker, Ga.

Filed Jan. 7, 1970, Ser. No. 1,123
Int. Cl. E04d 13/15
U.S. Cl. 52—60 15 Claims

ABSTRACT OF THE DISCLOSURE

A conjoint facia and water dam for being installed on a roof deck is provided comprising facia and heading and keeper means, a cant, flashing means, and thrust means, the flashing means being characterized by having first and second wall and bearing components and an interconnecting bight portion for engaging the first wall and bearing component with keeper structure of the facia and heading and keeper means in a recess bordered by an upper facia and heading portion of the latter means for the flashing means to extend behind a facia wall of the facia and heading and keeper means having the facia wall upstanding from an end of a roof deck and the second wall and bearing component of the flashing means covering and bearing upon an end of roofing on the cant, the latter supported on the roof deck behind the facia wall, while the thrust means engages the second wall and bearing component of the flashing means with the facia and heading and keeper means in an area of the keeper structure of the latter located exteriorly of the recess for the flashing means to clamp the end of roofing under the second wall and bearing component to an inclined surface of the cant.

The present invention relates more generally to building structures and is more particularly concerned with a conjoint facia and water dam for being associated with a roof deck, and with an end of roofing leading from the roof deck.

In so-called deck roofs, which are characterized by having a low pitch or a substantially horizontal top surface, the introduction of a conjoint facia and water dam is favored in the architectural and construction fields for such reasons as that the installation enables roof water to be suitably controlled without spilling over the end of the deck. A conjoint facia and water dam accordingly used may also serve as a barrier for other material, such as gravel, on the roof deck. Further beneficially, a conjoint facia and water dam as installed contributes facia which leads upwardly outside the end of a roof deck and coextends with the face of the roof deck end to the top surface of the roof deck, thence terminating upwardly of the deck and the cant. Meanwhile, the cant is disposed on the deck top surface and has an inclined surface leading upwardly from the deck as the inclined surface progresses outwardly toward the plane of the roof deck end. Roofing laid on the deck top surface is raised up at an end onto the inclined surface of the cant, and flashing structure of the conjoint facia and water dam is added overlapping the roofing end on the cant and engaging with the upper end of the facia above the cant. In general the flashing is for sealing against water penetration and the resulting barrier represented by the conjoint roof deck facia and water dam, as installed, prevents water from spilling over the barrier, particularly when the deck roof is also equipped with one or more suitable water drains appropriately located entrantly behind the barrier.

An object of the present invention is to provide an improved conjoint facia and water dam which has utility as facia, as a roof water barrier and as a flashing interposed between the facia and a roofing end.

Another object of this invention is that of providing improvements in thrust application in a conjoint facia and water dam.

A further object herein is the provision of interlocking facia heading and keeper means and flashing in association with thrust means engaging the facia heading and keeper means and flashing in a conjoint facia and water dam, having the thrust means capable of exerting thrust upon the flashing with the latter acting upon a roofing end resting upon a cant incline, and reactively to have the thrust means favorably effective for transmitting thrust to the facia and heading and keeper means while the latter and the flashing remain interlocked.

Other objects of this invention in part will be obvious and in part pointed out more fully hereinafter.

A conjoint facia and water dam in accordance with the present invention is characterized by including facia and heading and keeper means having a normally downwardly open recess therein, flashing means, a cant, and thrust means. In the facia and heading and keeper means an upper facia and heading portion is provided bordering the recess. Keeper structure extends from the upper facia and heading portion for being engaged both for downward thrust application to the facia and heading and keeper means to be had in the recess and for upward thrust application to the facia and heading and keeper means to be had exteriorly of the recess. Moreover a lower facia portion of the facia and heading and keeper means extends from the upper facia and heading portion so that with the facia and heading and keeper means in a generally upright position the lower facia portion is suited to lead facially outside a downwardly extending end of a roof deck and upwardly of the roof deck end, having the upper facia and heading portion and the keeper structure above the roof deck and the recess aforementioned downwardly open. The cant is for occupying a position securely on the roof deck adjacent to the roof deck end and has an inclined surface for this surface to lead upwardly from the roof deck in progressing away from the roof deck along with an end of roofing toward the roof deck end. Further, the cant in its secured position on the roof deck relative to the generally upright position of the facia and heading and keeper means is that of being immediately behind the lower facia portion of the facia and heading and keeper means and below the aforementioned keeper structure and recess, for supporting an end of roofing on the inclined surface.

The flashing means in the conjoint facia and water dam comprises laterally opposite first and second wall and bearing components and a bight wall portion interconnecting these components for the flashing means to have the first wall and bearing component thereof engage with the keeper structure in the recess in a downward thrust transmitting relation to the facia and heading and keeper means in the generally upright position of the latter while having the second wall and bearing component coveringly above an end of roofing on the inclined surface of the cant for being pressed downwardly upon the end of roofing clampingly toward the inclined surface of the cant in the aforementioned position of the cant on a roof deck. Also in the foregoing positions of the facia and heading and keeper means and the cant, the thrust means and the keeper structure referred to are interrelated for the thrust means to engage the keeper structure exteriorly of the recess with the second wall and bearing component of the flashing means in an upward thrust transmitting relation to the facia and heading and keeper means and press the second wall and bearing component downwardly upon an end of roofing on the inclined surface of the cant clampingly toward the inclined surface while the facia and heading and keeper

means receives downward thrust from the first wall and bearing component in engagement with the keeper structure in the recess.

In the accompanying drawings wherein several embodiments of this invention are represented:

FIG. 1 is a perspective view with vertical cross section of a conjoint facia and water dam and of a building wall, roof deck and roofing with which the conjoint facia and water dam is associated;

FIG. 2 is a vertical sectional elevation taken along line II—II in FIG. 1;

FIG. 3 is a view in vertical section representing a modified embodiment wherein a conjoint facia and water dam is indicated in association with a wall, a roof deck and roofing of a building;

FIG. 4 is a fragmentary vertical sectional view representing a further embodiment and is more particularly concerned with a seal detail;

FIG. 5 is a vertical sectional localized view representing features of still another embodiment, the cant structure involved being of modified form, with the conjoint facia and water dam otherwise indicated being constructed and having an environment similar to the conjoint facia and water dam in the embodiment represented in FIG. 3; and

FIGS. 6, 7 and 8 are respectively fragmentary vertical sectional views representing several embodiments wherein the conjoint roof deck facia and water dam is characterized by having thrust means thereof include lever structure.

Referring now more especially to FIGS. 1 and 2 of the drawing, and to the embodiment represented therein, a conjoint facia and water dam, designated in general by the reference numeral **10**, is mounted upon a building roof deck D which is supported on a building wall W, the latter having a vertical outside face S that is substantially flush with the outside vertical end face F of the roof deck D. While only a fragment of the conjoint facia and water dam is depicted it will of course be understood that the conjoint facia and water dam actually produces a border, the latter longitudinally coextending with the roof deck end or ends which may be termed as being outside in the building. For simplicity of description for present purposes, it will be assumed that the roof deck D has but one outside end face, the end face F, and that the roof deck is exposed endwise over but one outside wall in the building, namely, the wall W having the outside face S. More generally, however, it will of course be understood that a border longitudinally coextending with two or more outside ends of a roof deck may be formed at those ends over corresponding outside supporting walls through use of the conjoint facia and water dam, and that lapping, splicing, mitering, or joints produced in any other suitable manner, may be included in installing the members of the conjoint facia and water dam to achieve desired longitudinal extent of the border for the prevention of water spill-off from the roof deck end or ends as the case may be.

Considering further the embodiment represented in FIGS. 1 and 2, the conjoint facia and water dam **10** includes a facia and heading and keeper member **11** which is characterized by having a recess **16** therein and by including an upper facia wall and head portion **12**, and keeper structure comprising a first keeper component **14** and a second keeper component **15**. The upper facia and head portion **12** is inclusive of an upper facia portion **17***a* of the facia wall **17** and a head component **18** which longitudinally and laterally border the recess **16** and the head component **18** is connected with the upper facia portion **17***a* and longitudinally and laterally leads behind the upper facia portion. Furthermore the upper facia and head portion **12** coextends longitudinally with the first and second keeper components **14** and **15** which project laterally therefrom, the first keeper component **14** forming a bight **21** with the head component **18** and the upper facia portion **17***a* and the end of the first keeper component interposing a gap **19** leading entrantly into the recess **16** so that the recess thence leading laterally communicates from above with a surface **20** of the first keeper component **14** in the recess. The second keeper component **15** is connected with the bight **21** and is outside the recess **16**. The arrangement is such that with the facia and heading and keeper member **11** situated in a given generally upright normal position of use as shown in FIGS. 1 and 2, a lower portion **17***b* of the facia wall **17** leads facially outside the downwardly extending end face F of the roof deck D and upwardly of the roof deck to the upper portion **17***a* of the facia wall, and the upper facia and head portion **12** and the first and second keeper components **14** and **15** accordingly are above the roof deck, with the recess **16** being upwardly entrant through gap **19** and thence extending laterally over surface **20** of the first keeper component. Also, in the present embodiment the first and second keeper components **14** and **15**, being integral with a bight portion **21**, project in generally opposite directions with reference to each other laterally with the end of the first keeper component **14** leading to the gap **19** as a projection toward the facia wall **17**. Head component **18** in the normal position of use of member **11** leads laterally backwardly and at an acute angle downwardly with reference to upper portion **17***a* of the facia wall, and the second keeper portion **15** leads laterally backwardly from bight portion **21** and forms an obtuse angle with the head component **18**, while the first keeper component **14** projects generally horizontally forwardly toward the facia wall **17** from bight portion **21** and has surface **20** upwardly in the recess **16**. The facia and heading and keeper member **11** may for example be an extrusion or a product of rolling, made of aluminum alloy or from any other suitable material.

A cant member **25** of the conjoint roof deck facia and water dam **10**, as well be seen in FIG. 1, is disposed in a position adjacent to the end face F of the roof deck D and is secured in that position to the roof deck. Cant member **25** is of angular transverse configuration, there being substantially parallel longitudinal arrises **26**, **27** and **28** (FIG. 2) which delineate transverse longitudinal panels **29** and **30** and transverse longitudinal tongues **31** and **32** all of which are angularly related and integral at the corresponding longitudinal arrises **26**, **27** and **28** for tongue **31** in the normal position of use of the cant member to rest upon the top surface of the roof deck while the transversely inclined surface **29***a* of the panel **29** leads upwardly from the roof deck in progressing away from the roof deck toward the vertical plane of the roof deck end surface F, with panel **30** being substantially upright leading outside the building wall surface S from arris **28** and outside the roof deck surface F to arris **27** above the roof deck. From arris **28** the tongue **32** leads downwardly and outwardly away from the building for being engaged. The securement of cant member **25** is effected by any suitable fastening means such as headed nails or screws **33** through the tongue **31** into the roof deck D and headed nails or screws **34** through the lower portion of panel **30** into the roof deck at face F at suitable spacing longitudinally of the cant member. The cant of the conjoint roof deck facia and water dam **10** includes one or more cant members **25** made of sheet material which is bent beforehand to produce the aforementioned arrises, panels and tongues, the sheet material being galvanized steel or of any other suitable type. The cant may of course be made available in longitudinal sections represented by the members **25** which in being installed are for example overlapped, spliced through use of a splice member of like configuration or otherwise suitably jointed at adjacent longitudinal ends to prolong the cant and to preserve continuity. Notably, in the present embodiment, the facia and heading and keeper member **11** is characterized by having a lower lateral hook wall extension **23** including a downwardly and outwardly directed lower facia wall end **22** of lower facia portion **17***b* forming a bight with an upwardly and

inwardly directed hook wall end portion **24** for the lower hook wall extension **23** to be open in a generally upward direction in the normal position of use of the facia and heading and keeper member **11** to engage tongue **32** of the cant **25** and thus for the tongue **32** to restrain member **11** against upward movement while the facia wall **17** is outside the cant panel **30**, with panel **29** and the inclined surface **29***a* thereof being below the upper facia and head portion **12**, recess **16**, and the first and second keeper components **14** and **15**.

An example of structure whereby the conjoint roof deck facia and water dam **10** is prolonged with reference to the facia and heading and keeper member **11** by adding another one of the members **11** is indicated in FIGS. 1 and 2, wherein a liner and splice member **13** is configurated to conform substantially to the lateral inner facial contour of each facia and heading and keeper member **11** starting with having a leg laterally facially abutting surface **20** of the first keeper component **14** in recess **16** and progressing to the bight of the lower hook wall extension **23** and is installed to overlap the adjacent ends of the two members **11** accordingly. In certain embodiments, adjacent longitudinal ends of members **11** are instead simply overlapped one upon the other in prolongation of the conjoint roof deck facia and water dam. The joints may for example be concurrent with longitudinal joints (not shown) in the cant or staggered with reference to the latter joints.

Before completing installation of the conjoint roof deck facia and water dam **10**, roofing R is laid upon the roof deck D and an end E of the roofing is brought up upon the inclined surface **29***a* of the cant member. The conjoint roof deck facia and water dam **10** furthermore includes a flashing member **40** wherein a bight wall portion **45** of wall structure interconnects laterally opposite first and second wall and bearing components **42** and **43** of the flashing member. The second wall and bearing component **43** longitudinally has an outer lateral end flange **44** which in the normal position of use of the flashing projects downwardly.

With the flashing member **40** engaging the first wall and bearing component **42** with the first keeper component **14** at surface **20** of the latter within the recess **16**, the flashing member **40** leads out through gap **19** and the second wall and bearing component **43** covers end E of roofing R on the inclined surface **29***a* of cant panel **29**, having the cant member **25** and the facia and heading and keeper member **11** in their aforementioned positions represented in FIGS. 1 and 2. In this manner, the second wall and bearing component **43** of the flashing member **40** is available for being pressed against the roofing end portion E clampingly toward the inclined surface **29***a* of the cant member **25** and accordingly have flange **44** bite supportingly and sealingly into the roofing end portion.

The combined roof deck facia and water dam **10** further includes thrust means **90** for interengaging the second wall and bearing component **43** with the second keeper component **15** of member **11** in the aforementioned positions of member **11** and cant member **25** represented in FIGS. 1 and 2. In these positions of the latter two members, and with the first wall and bearing component **42** engaging the first keeper component **14** against surface **20** in the recess **16**, thrust is applied by the thrust means **90** and received by the second wall and bearing component **43** with the latter component thus pressing flange **44** into the roofing end E on the cant member **25** clampingly toward the inclined surface **29***a* of panel **29**. Meanwhile the thrust means **90** in the connection thereof with the second keeper component **15** is reactively in a generally upward thrust transmitting relation to the facia and heading and keeper member **11**. Thus, under thrust of the thrust means **90**, the lower hook wall extension **23** of member **11** is forced upwardly against tongue **32** of the cant member **25** which retains member **11** in the installed position represented in FIGS. 1 and 2.

Thrust means **90** more particularly includes a plurality of screw threaded fasteners **91** which directly are threadedly engaged with the second keeper component **15** at spaced apart locations longitudinally along the conjoint roof deck facia and water dam **10**, and are set having their shank ends thrusting upon the second wall and bearing component **43** for pressing the second wall and bearing component clampingly upon the roofing end E resting on the inclined surface of the cant member **25**. If desired, thrust of the thrust means **90** upon the second wall and bearing component **43** of the flashing means may be supplemented by the force of screws **48** or other suitable fastening means which extend through apertures in the second wall and bearing component **43** and engage this component forcefully upon the roofing end E with the cant **25**. Flashing member **40** may illustratively be an extrusion, or a product of rolling or of sheet bending, made of aluminum alloy or of any other suitable material. If desired a plurality of these flashing members **40** may be jointed at longitudinal ends thereof such as by overlapping those ends, or through use of a splice plate of similar cross section. Where the joint is made overlapping beneath one or more of the screw threaded fasteners **91** on the length of the conjoint roof deck facia and water dam **10** the fastener **91** is beneficial for compressionally securing the overlap or splice while exercising thrsut upon the flashing for clamping the flashing to the roofing end. Joints between flashing members **40** may be concurrent with joints between facia and heading and keeper members **11** or may be staggered with reference to the latter joints as occasion may demand.

In the embodiment represented in FIG. 3, a conjoint cornice type roof deck facia and water dam **10′** is provided for a building wherein the roof deck D′ juts outwardly beyond an outside wall W′ of the building and it has become desirable to extend the facia vertically and horizontally over intermediate vertical and return structure I of the building. In this particular embodiment the upper structure of the conjoint cornice type roof deck facia and water dam **10′** may be the same as that of the conjoint roof deck facia and water dam **10** in FIGS. 1 and 2 except that the cant panel **30′** forms a terminal lower end of the cant member **25′** and the lower hook wall extension **23** is engaged with a facia and cornice extension wherein a first facia extension member **50** and a facia and cornice extension member **51** are provided. Member **50** has laterally marginally longitudinally thereof an upper end portion **50***a* secured as by nails or screws to outer end face F′ of the roof deck D′. A downwardly and outwardly longitudinally laterally projecting upper tongue **50***b* of member **50** leads from the marginal upper end portion **50***a* and engages with the lower hook wall extension **23** of a facia and heading and keeper member **11**, of the character hereinbefore described with reference to FIGS. 1 and 2, for restraining the latter member against upward movement. At lower lateral end, the member **50** is characteristized by having a downwardly and outwardly laterally projecting longitudinal facia leg **50***d* joined with the root of tongue **50***b* by the vertical facia wall portion **50***c*. An upwardly and inwardly laterally projecting longitudinal end portion **50***f* and the facia leg **50***d* are interconnected by a bight wall portion **50***e* thus formnig a laterally downwardly and outwardly entrant longitudinal hook wall structure which engages a downwardly and outwardly laterally projecting longitudinal tongue **51***b* of the facia and cornice extension member **51**, the latter having an upper marginal end portion **51***a* which is fastened to the intermediate wall I of the building. A vertical facia wall portion **51***c* of the facia and cornice extension member **51** leads from the root of tongue **51***b* vertically outside the intermediate wall I and forms a corner with a return wall leg portion **51***d* of the facia and cornice extension member **51**, leg portion **51***d* being suitably secured as by nails or screws to a generally horizontal portion of the intermediate wall I. The outward-

ly and downwardly laterally projecting longitudinally facia leg **50***d*, as in the case of the downwardly and outwardly laterally projecting longitudinal facia wall leg portion **22** of the conjoint roof deck facia and water dam **10'**, serve to shed water when water flows on the facia. A downwardly and outwardly laterally directed longitudinal spur wall **51***e* of the facia and cornice wall extension member **51** leads from the corner formed by the vertical facia wall portion **51***c* and the return wall leg portion **51***d* and again serves as a water shed. Members **50** and **51** may for example be extrusions or products of rolling made of aluminum alloy or of any other suitable material. Each of the several members **50** and **51**, and any of the other members of the conjoint cornice type roof deck facia and water dam **10'**, may have longitudinal continuance with a like member suitably joined thereto as already suggested with reference to the embodiment of FIGS. 1 and 2. In FIG. 3 it will be noted that the members **50** and **51** are associated with splice wall elements **55** and **56** which in conforming to the inner faces of these respective members, from lateral end to opposite lateral end of the member, form a splice with the member, and a like member, not shown, on the length of the combined cornice type roof deck facia and water dam **10'**.

In certain embodiments the flashing means in interlocking with the facia and heading and keeper member includes elastomeric sealing means and disposes the sealing means toward the facia and heading and keeper means and sealingly against the latter means while thrust is being applied upon the flashing means by the thrust means. In the particular embodiment represented in FIG. 4, the conjoint facia and roof deck water dam is for example structurally the same as that described hereinbefore with reference to FIGS. 1 and 2, or with reference to FIG. 3, except that the end of the first wall and bearing component **42'** of the flashing member **40'** carries longitudinally continuously an elastomeric sealing member **46** protruding laterally from a longitudinal groove in the first wall and bearing component for pressing sealingly against the facia and heading and keeper member **11** within the recess **16** under the heeling action of bight wall portion **45'** of the flashing member **40'** against the facia wall **17**.

In the embodiment represented in FIG. 5, the cant **25''** comprises a substantially right triangular longitudinal rail of wood or of any other suitable material secured to the roof deck, having the rail support on the inclined surface thereof a marginal end portion of roofing R'' leading up from the roof deck D''. Otherwise, the conjoint facia and water dam in which the cant **25''** is a component is for example similar to that represented in FIG. 3.

In other illustrative embodiments of the present invention, a conjoint roof deck facia and water dam is provided similar to any of the foregoing described herein but differing in the respect that the keeper structure of the facia and heading and keeper means and the structure of the thrust means are of modified form for being engaged to have the thrust means reactively transmit upward thrust to the facia and heading and keeper means. Thus, in the embodiment represented in FIG. 6 a conjoint roof deck facia and water dam is provided including a facia and heading and keeper member **11***a*, a cant member **25***a*, flashing means **40***a* and at least one thrust unit **90***a*. The cant and the flashing means are for example constructed and arranged similarly to those in the embodiment represented in FIGS. 1 and 2 and so is the facia and heading and keeper member **11***a* except that the bight portion **21***a* interconnecting the head component **18***a* with the first keeper component **14***a*, for the latter to present bearing surface **20***a* in the recess **16***a*, is integral with normally upper and lower flanges **60** and **61** which coextend longitudinally with the upper facia and head portion **12***a* and laterally project rearwardly thereof forming a laterally rearwardly open longitudinal groove **62** with the bight portion **21***a* externally of the recess **16***a*. Furthermore, thrust unit **50***a* comprises lever structure **6** 3having a first end portion **64** and an opposite second end portion **65** with the thrust unit also having at least one screw threaded fastener **66** threadedly engaged with the first end portion **64** of the lever structure. In the arrangement as shown and presently preferred it will be understood each screw threaded fastener **66** is a set screw having its shank extending through an aperture wherein the set screw is directly threadedly engaged with the lever structure **63**. If desired, a plurality of the thrust units **90***a* may be used as clips spaced apart from each other longitudinally along the facia and heading and keeper member **11***a* for engaging the flashing means or in certain instances the lever structure **63** may extend substantially continuously longitudinally with the flashing means and the facia and heading and keeper means in the conjoint roof deck facia and water dam thus having a plurality of screw threaded fasteners **66** threadedly engaged with the lever structure at locations longitudinally along the lever structure. The second end portion **65** of the lever structure of the thrust unit comprises a tongue entrantly into the groove **62** afforded in the facia and heading and keeper member **11***a* for the tongue to interlock laterally with the upper and lower flanges **60** and **61** and thus transmit upward thrust to the facia and heading and keeper member **11***a* with the thrust unit **90***a* having the screw threaded fastener or screw threaded fasteners **66**, as the case may be, set pressingly upon the second wall and bearing component **43***a* of the flashing means **40***a* to engage an end of roofing on the inclined surface of the cant member **25***a* clampingly toward that inclined surface while the second wall and bearing component **42***a* of the flashing means **40***a* is engaged against surface **20***a* of the first keeper component **14***a* in the recess **16***a* and is transmitting downward thrust to the facia and heading and keeper member **11***a*. To assure more positive interlock between the upper and lower flanges **60** and **61** with the lever structure **63** under lateral thrust, the lower flange **61** is formed to project upwardly at its outer end in the normal position of use of the facia and heading and keeper member **11***a* and the tongue which the second end portion **65** of the lever structure **63** introduces projects downwardly in the groove **62** in interlock with the lower flange **61** while pressing laterally upwardly against the upper flange **60**. Also, the upper flange **60** at its downward inner face in the groove **62** has ribs **60***a* and the tongue at upper face in this same groove has ribs **65***a* for the ribs on the flange and on the tongue to mesh under thrust of the thrust unit **90***a* thus to achieve more positive interlock.

In the embodiment of FIG. 7, the conjoint roof deck facia and water dam is similar to that of FIG. 6 with the facia and heading and keeper member **11***a'*, however, providing a laterally normally upwardly entrant longitudinal groove **67** introduced by keeper structure **68** and the bight portion **21***a'*, the latter connecting the head component **18***a'* with the first keeper component **14***a'* of the facia and heading and keeper member **11***a'* in a manner already explained with reference to other embodiments herein. A web **68***a* of the keeper structure **68** leads from the juncture of the head component **18***a'* and bight portion **21***a'* of member **11***a'* and supports integrally a tongue **68***b* which laterally projects downwardly from the web portion. Also, in the embodiment of FIG. 7, the conjoint roof deck facia and water dam includes at least one thrust unit **90***a'* which comprises lever structure **63'** having a first end portion **64'** and an opposite second end portion **65'**, and the thrust unit furthermore includes screw threaded fastener means **66'** threadedly engaged with the first end portion **64'** of the lever structure. The second end portion **65'** of the lever structure of the thrust unit forms a normally downwardly entrant groove **70** which is bordered by a laterally upwardly projecting end arm **72** of the second end portion **65'** so that with lever structure **63'** receiving the downwardly projecting tongue **68***b* in

the normally downwardly entrant groove **70** the laterally upwardly projecting end arm **72** is received in the normally upwardly entrant groove **67** for the tongue **68***b* and the second end portion **65'** of the lever structure to interlock laterally of the tongue in an upward thrust transmitting relation having the threaded fastener means **66'** set pressingly upon the second wall and bearing component **43***a'* of the flashing means **40***a'* to engage an end of roofing on the inclined surface of the cant member **25***a'* clampingly toward that inclined surface while the second wall and bearing component **42***a'* of the flashing means **40***a'* is engaged against surface **20***a'* of the first keeper component **14***a'* in the recess **16***a'* and is transmitting downward thrust to the facia and heading and keeper member **11***a*. Bight portion **21***a'* and lever end arm **72** advantageously include stop ledge portions **73** and **74** respectively which engage the lever structure **63'** with the facia and heading and keeper means **11***a'* during installation of the thrust unit **90***a'* before the threaded fastener means **66'** is set to develop thrust against the flashing means **40***a'*. Also, to enhance the interlock had between the thrust unit **90***a'* and tongue **68***b* the tongue preferably is tapered having its laterally opposite sides converging downwardly companion to having the laterally opposite sides of the second end portion **65'** of the lever structure **63'** upwardly divergent and with there being ribs **75** on the lateral face of arm **72** in the groove **70** and ribs **76** on the lateral face of tongue **68***b* which is toward the ribs **75** for the ribs **75** and **76** to mesh under thrust when the thrust unit **90***a'* is applied against the flashing means **40***a'* and rises wedgingly on the tapered tongue **68***b*.

According to certain embodiments of the present invention a conjoint roof deck facia and water dam is provided characterized in that the thrust means includes resilient fastener means comprising first and second arm means, for the resilient fastener means to be resiliently sprung into pressure exercising relation wherein the first arm means of the resilient fastener means and the keeper structure are engaged having the thrust means in an upward thrust transmitting relation to the facia and heading and keeper means, and the second arm means of the resilient fastener means and the second wall and bearing component of the flashing means are engaged having the second arm means press the second wall and bearing component upon an end of roofing on the inclined surface of the cant means clampingly toward the inclined surface, while the keeper structure and the first wall and bearing component of the flashing means are engaged with the facia and heading and keeper means and the cant means in their installed positions. In the embodiment of FIG. 8, the thrust means **80** not only comprises resilient fastener means **82** of the immediately preceding character, but beneficially further includes screw threaded fastener means **81** threadedly engaged rearwardly of ends of the first and second arm means **83** and **84** of the resilient fastener means **82** for the screw threaded fastener means **81** to press downwardly upon the second wall and bearing component **86** of the flashing means rearwardly of where the end **83***a* of the first arm means and the keeper structure **87** are engaged and rearwardly of where the end **84***a* of the second arm means engages the second wall and bearing component **86**, so as to have thrust of the resilient fastener means **82** upon an end of roofing on the inclined surface of the cant clampingly toward that inclined surface enhanced by thrust of the screw threaded fastener means upon the second wall and bearing component **86**. As the facia and heading and keeper means, the cant means, and the flashing means are longitudinally prolonged such as by adding or jointing one or more members of the same, the thrust means **80** may either substantially coextend longitudinally as the conjoint roof deck facia and water dam is prolonged or instead include a plurality of fastener units at different locations longitudinally along the conjoint roof deck facia and water dam. In each such fastener unit the screw threaded fastener means **81** is characterized by including one or more screws with the latter being in number depending upon such factors as the extent of the fastener unit longitudinally of the conjoint roof deck facia and water dam and so as to occur in the fastener unit or units at approriate locations along the length of the conjoint roof deck facia and water dam.

The arrangement according to FIG. 8 will also be understood as having the screw or screws in the fastener unit extending through apertures in the first and second arm means **83** and **84** and threadedly engaged with the resilient fastener means **82** rearwardly of ends **83***a* and **84***a*, having the screw shank ends project from the second arm means **84** for thrust to be exercised. Keeper structure **87** of the facia and heading and keeper means occurs as a projection defining a gap with the facia, with the resulting gap leading into a recess **88** in the upper portion of the facia and heading and keeper means. A first wall and bearing component **85** of the flashing means meanwhile is engaged with the keeper structure **87** inside the recess **88** in a downward thrust exercising relation to the facia and heading and keeper means while end **83***a* of the first arm means **83** of the fastener unit engages the projecting keeper structure **87** exteriorly of the recess **88** for the fastener unit to transmit upward thrust to the facia and heading and keeper means. The second wall and bearing component **86** of the flashing means meanwhile receives thrust from the related screw shank end or ends of the screw threaded fastener means **81** rearwardly of the ends **83***a* and **84***a* of the first and second arm means of the fastener unit and acts clampingly upon an end of roofing on the inclined surface of the cant means.

As the present invention lends itself to many possible embodiments and as many possible changes still in accordance with the invention may be made in the embodiments hereinbefore set forth, it will be distinctly understood that all matter described herein is to be interpreted as illustrative and not as a limitation.

I claim:

1. In a conjoint roof deck facia and water dam, the combination which includes: facia and heading and keeper means having a normally downwardly open recess therein and comprising an upper facia and heading portion bordering said recess, keeper structure extending from said upper facia and heading portion and including an interior keeper portion having a surface in said recess for being engaged for downward thrust application to be had to said facia and heading and keeper means in said recess and an exterior keeper portion exteriorly of said recess to be engaged for upward thrust application to said facia and heading and keeper means to be had exteriorly of said recess, a lower facia portion extending from said upper facia and heading portion so that with said facia and heading and keeper means in a generally upright position said lower facia portion is suited to lead facially outside a downwardly extending end of a roof deck and upwardly of the roof deck end, having said upper facia and heading portion and said keeper structure above the roof deck and said recess downwardly open; cant means having an inclined surface for said cant means securely in a position on a roof deck adjacent to an end of the latter to support an end of roofing on said inclined surface of said cant means downwardly below said recess and said keeper structure and behind said lower facia portion, with said facia and heading and keeper means being in said generally upright position, and with said inclined surface of said cant means leading upwardly with the roofing end from the roof deck in progressing from the roof deck toward the roof deck end; flashing means comprising laterally opposite first and second wall and bearing components and a bight wall portion interconnecting said first and second wall and bearing components, for said flashing means to have said first wall and bearing component engage with said surface of said interior keeper portion in said recess in a downward thrust bearing relation upon said facia and heading and keeper means in said generally

upright position of the latter while having said second wall and bearing component coveringly above an end of roofing on said inclined surface of said cant means for being pressed downwardly upon the end of roofing clampingly toward said inclined surface in said position of said cant means on a roof deck; and thrust means bearing upon said exterior keeper portion exteriorly of said recess and upon said second wall and bearing component of said flashing means and applying thrust upwardly to said facia and heading and keeper means for pressing said second wall and bearing component downwardly upon an end of roofing on said inclined surface of said cant means clampingly toward said inclined surface while said facia and heading and keeper means receives downward thrust from said first wall and bearing component in engagement with said surface of said interior keeper portion in said recess, in said positions of said facia and heading and keeper means and said cant means.

2. In a conjoint roof deck facia and water dam, the combination as set forth in claim 1 wherein said lower facia portion has a generally upwardly open hook wall extension downwardly entrantly to be restrained against upward movement under upward thrust received by said facia and heading and keeper means from said thrust means in engagement with said exterior keeper portion exteriorly of said recess while said first wall and bearing component is engaged with said surface of said interior keeper portion interiorly of said recess and is applying downward thrust to said facia and heading and keeper means and said second wall and bearing component presses upon an end of roofing on said inclined surface of said cant means clampingly toward said inclined surface under thrust upon said second wall and bearing component from said thrust means in said positions of said facia and heading and keeper means and said cant means.

3. In a conjoint roof deck facia and water dam, the combination as as set forth in claim 1 wherein said thrust means includes a plurality of fastener units for engaging said exterior keeper portion exteriorly of said recess in an upward thrust applying relation to said facia and heading and keeper means at spaced apart locations longitudinally along the conjoint roof deck facia and water dam and pressing said second wall and bearing component against an end of roofing on said inclined surface of said cant means clampingly toward said inclined surface while said interior keeper portion supports said first wall and bearing component interiorly of said recess.

4. In a conjoint roof deck facia and water dam, the combination as set forth in claim 3 wherein each of said fastener units includes a screw threaded fastener having an end abutting said second wall and bearing component in said positions of said facia and heading and keeper means and said cant means, for pressing said second wall and bearing component upon an end of roofing on said inclined surface of said cant means clampingly toward said inclined surface while said interior keeper portion supports said first wall and bearing component interiorly of said recess.

5. In a conjoint roof deck facia and water dam, the combination as set forth in claim 4 wherein said screw threaded fastener extends through an aperture in said exterior keeper portion exteriorly of said recess and is engaged with said exterior keeper portion, having an end abutting said second wall and bearing component in said positions of said facia and heading and keeper means and said cant means, for pressing said second wall and bearing component upon an end of roofing on said inclined surface of said cant means clampingly toward said inclined surface while said interior keeper portion supports said first wall and bearing component interiorly of said recess.

6. In a conjoint roof deck facia and water dam, the combination as set forth in claim 1 wherein said thrust means includes at least one fastener unit, said unit comprising lever structure which includes first and second end portions, and screw threaded fastener means engaging said first end portion of said lever structure and for pressing said second wall and bearing component of said flashing means, and said second end portion of said lever structure forming an interlocking connection with said exterior keeper portion exteriorly of said recess for transmitting upward thrust of said screw threaded fastener means to said facia and heading and keeper means while said second wall and bearing component of said flashing means clamps an end of roofing on said inclined surface of said cant means under thrust of said screw threaded fastener means and said interior keeper portion supports said first wall and bearing component interiorly of said recess.

7. In a conjoint roof deck facia and water dam, the combination as set forth in claim 6 wherein said exterior keeper portion and said second end portion of said lever structure in said connection include a tongue and a pair of laterally spaced flanges for said tongue to sustain interlock with said flanges laterally of said flanges under thrust of said screw threaded fastener means.

8. In a conjoint roof deck facia and water dam, the combination as set forth in claim 7 wherein said tongue and at least one of said flanges laterally facially include ribs, and said ribs on said tongue mesh with said ribs on said flange when said tongue interlocks with said flanges laterally of said flanges.

9. In a conjoint roof deck facia and water dam, the combination as set forth in claim 1 wherein said thrust means includes resilient fastener means comprising first and second arm means and bight means interconnecting said first and second arm means, for said resilient fastener means to be resiliently sprung into pressure exercising relation wherein said first arm means and said exterior keeper portion are engaged externally of said recess having said thrust means in an upward thrust transmitting relation to said facia and heading and keeper means, and said second arm means and said second wall and bearing components of said flashing means are engaged having said second arm means press said second wall and bearing component upon an end of roofing on said inclined surface of said cant means clampingly toward said inclined surface, while said interior keeper portion and said first wall and bearing component of said flashing means are engaged interiorly of said recess in said positions of said facia and heading and keeper means and said cant means.

10. In a conjoint roof deck facia and water dam, the combination as set forth in claim 9 wherein said thrust means further includes screw threaded fastener means and said screw threaded fastener means engaging said resilient fastener means rearwardly of ends of said first and second arm means for said screw threaded fastener means to press downwardly upon said second wall and bearing component rearwardly of where said end of said first arm means and said exterior keeper portion are engaged under thrust of said resilient fastener means and rearwardly of where said end of said second arm means and said second wall and bearing component are engaged under thrust of said resilient fastener means.

11. In a conjoint roof deck facia and water dam, the combination which includes: a facia and heading and keeper member having a normally downwardly open recess therein and comprising, an upper facia and head portion bordering said recess and frontally including an upper facia portion of said facia and heading and keeper member and a header component connected with said upper facia portion and leading behind said upper facia portion, keeper structure including a forward projection and interior and exterior keeper portions connected with said header component and said forward projection forming a gap with said upper facia portion with said forward projection and said interior keeper portion having a surface in common interiorly of said recess for downward thrust application on said surface to said facia and heading and keeper member to be had and said exterior keeper

portion extending to be engaged exteriorly of said recess for receiving upward thrust application to said facia and heading and keeper member exteriorly of said recess, and a lower facia portion extending from said upper facia portion so that with said facia and heading and keeper member in a generally upright position said lower facia portion is suited to lead facially outside a downwardly extending end of a roof deck and upwardly of the roof deck end, having said upper facia and heading portion and said keeper structure above the roof deck and said recess downwardly open, a cant having an inclined surface for said cant securely in a position on a roof deck adjacent to an end of the latter to support an end of roofing on said inclined surface downwardly below said upper facia and head portion and said keeper structure and behind said lower facia portion, with said facia and heading and keeper member being in a generally upright position, and with said inclined surface leading upwardly with the roofing end from the roof deck in progressing from the roof deck toward the roof deck end; flashing means comprising laterally opposite first and second wall and bearing components and a bight wall portion interconnecting said first and second wall and bearing components, for said flashing means to lead through said gap having said first wall and bearing component engage with said surface of said forward projection and said interior keeper portion in a downward thrust bearing relation upon said facia and heading and keeper member in said generally upright position of the latter while having said second bearing component coveringly above an end of roofing on said inclined surface of said cant means for being pressed downwardly upon the end of roofing clampingly toward said inclined surface in said position of said cant on a roof deck; and thrust means engaging said exterior keeper portion exteriorly of said recess and bearing upon said second wall and bearing component of said flashing means in an upward thrust transmitting relation to said facia and heading and keeper member for pressing said second wall and bearing component downwardly upon an end of roofing on said inclined surface of said cant clampingly toward said inclined surface while said facia and heading and keeper member receive downward thrust from said first wall and bearing component in engagement with said surface of said interior keeper portion, in said positions of said facia and heading and keeper member and said cant.

12. In a conjoint roof deck facia and water dam, the combination as set forth in claim **11** wherein said lower facia portion has a generally upwardly open hook wall extension downwardly entrantly to be restrained against upward movement under upward thrust received by said facia and heading and keeper member from said thrust means in engagement with said exterior keeper portion exteriorly of said recess while said first wall and bearing component is engaged with said surface of said forward projection and said interior keeper portion and is applying downward thrust to said facia and heading and keeper member at said surface of said projection and interior keeper portion interiorly of said recess and said second wall and bearing component presses upon an end of roofing on said inclined surface of said cant clampingly toward said inclined surface under thrust applied upon said second wall and bearing component by said thrust means in said positions of said facia and heading and keeper member and said cant.

13. In a conjoint roof deck facia and water dam, the combination as set forth in claim **11** wherein said exterior keeper portion includes a flange extending rearwardly of said upper facia and head portion from said head component and there are apertures in said flange at spaced apart locations longitudinally along said conjoint roof deck facia and water dam, and said thrust means includes screw threaded fasteners through said apertures and engaged for thrusting upwardly upon said flange while ends of said screw threaded fasteners press said second wall and bearing component against an end of roofing on said inclined surface of said cant clampingly toward said inclined surface and while said first wall and bearing component of said flashing means is applying downward thrust to said facia and heading and keeper member against said surface of said forward projection and said interior keeper portion in said positions of facia and heading and keeper member and said cant.

14. In a conjoint roof deck facia and water dam, the combination as set forth in claim **11** wherein said thrust means includes at least one fastener unit, said unit comprising lever structure which comprises first and second end portions, and screw threaded fastener means engaging said first end portion of said lever structure and for pressing said second wall and bearing component of said flashing means, and said second end portion of said lever structure forming an interlocking connection with said exterior keeper portion exteriorly of said recess for transmitting upward thrust of said screw threaded fastener means to said facia and heading and keeper member while said second wall and bearing component of said flashing means clamps an end of roofing on said inclined surface of said cant under thrust of said screw threaded fastener means and said interior keeper portion supports said first wall and bearing component interiorly of said recess.

15. In a conjoint roof deck facia and water dam, the combination as set forth in claim **11** wherein said thrust means includes; screw and resilient fastener means comprising first and second arm means and bight means interconnecting said first and second arm means for said resilient fastener means to be resiliently sprung into pressure exercising relation wherein said first arm means and said exterior keeper portion are engaged exteriorly of said recess and said second arm means and said second wall and bearing component of said flashing means are engaged, having said second arm means press said second wall and bearing component upon an end of roofing on said inclined surface of said cant means clampingly toward said inclined surface while said surface of said forward projection and said interior keeper portion is engaged interiorly of said recess in said positions of said facia and heading and keeper member, and screw threaded fastener means engaged with said resilient fastener means rearwardly of ends of said first and second arm means for said screw threaded fastener means to press downwardly upon said second wall and bearing component rearwardly of where said first arm means and said exterior keeper portion are engaged under thrust of said resilient fastener means and rearwardly of where said second arm means and said second wall and bearing component are engaged under thrust of said resilient fastener means.

References Cited

UNITED STATES PATENTS

Re. 26,056	7/1966	Hickman	52—60 X
3,503,162	3/1970	Ward	52—60
3,533,201	10/1970	Tyler	52—60

PRICE C. FAW, JR., Primary Examiner

U.S. Cl. X.R.

52—94