



(12) **DEMANDE DE BREVET CANADIEN**
CANADIAN PATENT APPLICATION

(13) **A1**

(86) Date de dépôt PCT/PCT Filing Date: 2019/08/07
(87) Date publication PCT/PCT Publication Date: 2020/02/13
(85) Entrée phase nationale/National Entry: 2021/02/04
(86) N° demande PCT/PCT Application No.: IB 2019/056735
(87) N° publication PCT/PCT Publication No.: 2020/031117
(30) Priorité/Priority: 2018/08/10 (US16/100,284)

(51) Cl.Int./Int.Cl. *A24F 40/50* (2020.01),
A24F 40/10 (2020.01), *A24F 40/40* (2020.01),
A24F 40/46 (2020.01), *H02J 7/00* (2006.01)
(71) Demandeur/Applicant:
RAI STRATEGIC HOLDINGS, INC., US
(72) Inventeur/Inventor:
SUR, RAJESH, US
(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : DISPOSITIF DE DISTRIBUTION D'AEROSOL COMPRENANT UN ENSEMBLE DE CIRCUITS DE CHARGE
(54) Title: AEROSOL DELIVERY DEVICE COMPRISING CHARGE CIRCUITRY




FIG. 7A

(57) **Abrégé/Abstract:**

An aerosol delivery device is provided that includes a housing structured to retain an aerosol precursor composition, a heating element configured to convert electricity to heat and thereby vaporize components of the aerosol precursor composition, a power source including one or more batteries or battery cells coupled to and configured to power a load including the heating element, and charge circuitry coupled to and configured to controllably charge the power source. The charge circuitry includes an electrical connector configured to connect the charge circuitry to a power supply from which the power source is chargeable, and a buck-boost charge controller coupled to and between the power source and power supply. The buck-boost charge controller is configured to regulate output voltage and output current from the power supply to the power source, selectively in one of a plurality of modes based on a condition of the power supply.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property

Organization

International Bureau

(43) International Publication Date

13 February 2020 (13.02.2020)



(10) International Publication Number

WO 2020/031117 A1

(51) International Patent Classification:

A24F 47/00 (2020.01) H02J 7/00 (2006.01)

(21) International Application Number:

PCT/IB2019/056735

(22) International Filing Date:

07 August 2019 (07.08.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16/100,284 10 August 2018 (10.08.2018) US

(71) Applicant: RAI STRATEGIC HOLDINGS, INC.

[US/US]; 401 North Main Street, Winston-Salem, North Carolina 27101 (US).

(72) Inventor: SUR, Rajesh; 1774 Queen Catherine Lane, Win-

ston-Salem, North Carolina 27106 (US).

(74) Agent: DEADERICK, Elliott J. et al.; Womble Bond Dickinson (US) LLP, Attn: Patent Docketing, P.O. Box 7037, Atlanta, Georgia 30357-0037 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

(54) Title: AEROSOL DELIVERY DEVICE COMPRISING CHARGE CIRCUITRY




FIG. 7A

(57) **Abstract:** An aerosol delivery device is provided that includes a housing structured to retain an aerosol precursor composition, a heating element configured to convert electricity to heat and thereby vaporize components of the aerosol precursor composition, a power source including one or more batteries or battery cells coupled to and configured to power a load including the heating element, and charge circuitry coupled to and configured to controllably charge the power source. The charge circuitry includes an electrical connector configured to connect the charge circuitry to a power supply from which the power source is chargeable, and a buck-boost charge controller coupled to and between the power source and power supply. The buck-boost charge controller is configured to regulate output voltage and output current from the power supply to the power source, selectively in one of a plurality of modes based on a condition of the power supply.

[Continued on next page]



WO 2020/031117 A1

WO 2020/031117 A1

EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to the identity of the inventor (Rule 4.17(i))*
- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*
- *in black and white; the international application as filed contained color or greyscale and is available for download from PATENTSCOPE*

AEROSOL DELIVERY DEVICE COMPRISING CHARGE CIRCUITRY

TECHNOLOGICAL FIELD

[0001] The present disclosure relates to aerosol delivery devices such as electronic cigarettes and heat-not-burn cigarettes. The aerosol delivery device may be configured to heat an aerosol precursor composition, which may be made or derived from tobacco or otherwise incorporate tobacco, to form an inhalable substance for human consumption.

BACKGROUND

[0002] Many smoking articles have been proposed through the years as improvements upon, or alternatives to, smoking products based upon combusting tobacco. Example alternatives have included devices wherein a solid or liquid fuel is combusted to transfer heat to tobacco or wherein a chemical reaction is used to provide such heat source. Examples include the smoking articles described in U.S. Patent No. 9,078,473 to Worm et al., which is incorporated herein by reference.

[0003] The point of the improvements or alternatives to smoking articles typically has been to provide the sensations associated with cigarette, cigar, or pipe smoking, without delivering considerable quantities of incomplete combustion and pyrolysis products. To this end, there have been proposed numerous smoking products, flavor generators, and medicinal inhalers which utilize electrical energy to vaporize or heat a volatile material, or attempt to provide the sensations of cigarette, cigar, or pipe smoking without burning tobacco to a significant degree. See, for example, the various alternative smoking articles, aerosol delivery devices and heat generating sources set forth in the background art described in U.S. Pat. No. 7,726,320 to Robinson et al., U.S. Pat. App. Pub. No. 2013/0255702 to Griffith, Jr. et al., and U.S. Pat. App. Pub. No. 2014/0096781 to Sears et al., which are incorporated herein by reference. See also, for example, the various types of smoking articles, aerosol delivery devices and electrically powered heat generating sources referenced by brand name and commercial source in U.S. Pat. App. Pub. No. 2015/0220232 to Bless et al., which is incorporated herein by reference. Additional types of smoking articles, aerosol delivery devices and electrically powered heat generating sources referenced by brand name and commercial source are listed in U.S. Pat. App. Pub. No. 2015/0245659 to DePiano et al., which is also incorporated herein by reference.

Other representative cigarettes or smoking articles that have been described and, in some instances, been made commercially available include those described in U.S. Pat. No. 4,735,217 to Gerth et al., U.S. Pat. Nos. 4,922,901, 4,947,874, and 4,947,875 to Brooks et al., U.S. Pat. No. 5,060,671 to Counts et al., U.S. Pat. No. 5,249,586 to Morgan et al., U.S. Pat. No. 5,388,594 to Counts et al., U.S. Pat. No. 5,666,977 to Higgins et al., U.S. Pat. No. 6,053,176 to Adams et al., U.S. Pat. No. 6,164,287 to White, U.S. Pat. No. 6,196,218 to Voges, U.S. Pat. No. 6,810,883 to Felter et al., U.S. Pat. No. 6,854,461 to Nichols, U.S. Pat. No. 7,832,410 to Hon, U.S. Pat. No. 7,513,253 to Kobayashi, U.S. Pat. No. 7,726,320 to Robinson et al., U.S. Pat. No. 7,896,006 to Hamano, U.S. Pat. No. 6,772,756 to Shayan, U.S. Pat. Pub. No. 2009/0095311 to Hon, U.S. Pat. Pub. Nos. 2006/0196518, 2009/0126745, and 2009/0188490 to Hon, U.S. Pat. Pub. No. 2009/0272379 to Thorens et al., U.S. Pat. Pub. Nos. 2009/0260641 and 2009/0260642 to Monsees et al., U.S. Pat. Pub. Nos. 2008/0149118 and 2010/0024834 to Oglesby et al., U.S. Pat. Pub. No. 2010/0307518 to Wang, and PCT Pat. App. Pub. No. WO 2010/091593 to Hon, which are incorporated herein by reference.

[0004] Representative products that resemble many of the attributes of traditional types of cigarettes, cigars or pipes have been marketed as ACCORD[®] by Philip Morris Incorporated; ALPHA[™], JOYE 510[™] and M4[™] by InnoVapor LLC; CIRRU[™] and FLING[™] by White Cloud Cigarettes; BLU[™] by Fontem Ventures B.V.; COHITA[™], COLIBRI[™], ELITE CLASSIC[™], MAGNUM[™], PHANTOM[™] and SENSE[™] by EPUFFER[®] International Inc.; DUOPRO[™], STORM[™] and VAPORKING[®] by Electronic Cigarettes, Inc.; EGAR[™] by Egar Australia; eGo-C[™] and eGo-T[™] by Joyetech; ELUSION[™] by Elusion UK Ltd; EONSMOKE[®] by Eonsmoke LLC; FIN[™] by FIN Branding Group, LLC; SMOKE[®] by Green Smoke Inc. USA; GREENARETTE[™] by Greenarette LLC; HALLIGAN[™], HENDU[™], JET[™], MAXXQ[™], PINK[™] and PITBULL[™] by SMOKE STIK[®]; HEATBAR[™] by Philip Morris International, Inc.; HYDRO IMPERIAL[™] and LXET[™] from Crown7; LOGIC[™] and THE CUBAN[™] by LOGIC Technology; LUCI[®] by Luciano Smokes Inc.; METRO[®] by Nicotek, LLC; NJOY[®] and ONEJOY[™] by Sottera, Inc.; NO. 7[™] by SS Choice LLC; PREMIUM ELECTRONIC CIGARETTE[™] by PremiumEstore LLC; RAPP E-MYSTICK[™] by Ruyan America, Inc.; RED DRAGON[™] by Red Dragon Products, LLC; RUYAN[®] by Ruyan Group (Holdings) Ltd.; SF[®] by Smoker Friendly International, LLC; GREEN SMART SMOKER[®] by The Smart Smoking

Electronic Cigarette Company Ltd.; SMOKE ASSIST[®] by Coastline Products LLC; SMOKING EVERYWHERE[®] by Smoking Everywhere, Inc.; V2CIGS[™] by VMR Products LLC; VAPOR NINE[™] by VaporNine LLC; VAPOR4LIFE[®] by Vapor 4 Life, Inc.; VEPPOT[™] by E-CigaretteDirect, LLC; VUSE[®] by R. J. Reynolds Vapor Company; MISTIC MENTHOL product by Mystic Ecigs; the VYPE product by CN Creative Ltd; IQOS[™] by Philip Morris International; GLO[™] by British American Tobacco; MARK TEN products by Nu Mark LLC; and the JUUL product by Juul Labs, Inc. Yet other electrically powered aerosol delivery devices, and in particular those devices that have been characterized as so-called electronic cigarettes, have been marketed under the tradenames COOLER VISIONS[™]; DIRECT E-CIG[™]; DRAGONFLY[™]; EMIST[™]; EVERSMOKE[™]; GAMUCCI[®]; HYBRID FLAME[™]; KNIGHT STICKS[™]; ROYAL BLUES[™]; SMOKETIP[®]; and SOUTH BEACH SMOKE[™]. However, it may be desirable to provide aerosol delivery devices with improved electronics such as may extend usability of the devices.

BRIEF SUMMARY

[0005] The present disclosure relates to aerosol delivery devices configured to produce aerosol and which aerosol delivery devices, in some implementations, may be referred to as electronic cigarettes or heat-not-burn cigarettes. The present disclosure includes, without limitation, the following example implementations.

[0006] Example Implementation 1: An aerosol delivery device comprising: a housing structured to retain an aerosol precursor composition; a heating element configured to convert electricity to heat and thereby vaporize components of the aerosol precursor composition; a power source including one or more batteries or battery cells coupled to and configured to power a load including the heating element; and charge circuitry coupled to and configured to controllably charge the power source, the charge circuitry including: an electrical connector configured to connect the charge circuitry to a power supply from which the power source is chargeable; and a buck-boost charge controller coupled to and between the power source and power supply, and configured to regulate output voltage and output current from the power supply to the power source, selectively in one of a plurality of modes based on a condition of the power supply.

[0007] Example Implementation 2: The aerosol delivery device of any preceding example implementation, or any combination of any preceding example

implementations, wherein the power source includes a plurality of batteries or battery cells.

[0008] **Example Implementation 3:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the plurality of batteries or battery cells are connected to form a plurality of paths for the output current from the power supply to flow through such that the output current is a sum of currents through each path of the plurality of paths.

[0009] **Example Implementation 4:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the one or more batteries or battery cells include one or more lithium-ion, lithium iron phosphate, supercapacitor or solid state batteries or battery cells.

[0010] **Example Implementation 5:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the power supply includes one or more lithium-ion or solid state batteries, or lithium-ion or hybrid lithium-ion capacitors, and the buck-boost charge controller being configured to regulate the output voltage and output current from the power supply includes being configured to regulate the output voltage and output current from the one or more lithium-ion or solid state batteries, or lithium-ion or hybrid lithium-ion capacitors.

[0011] **Example Implementation 6:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the charge circuitry further includes a protection circuit coupled to and between the electrical connector and the power source, and configured to protect the power source from an overcurrent condition in the power supply when the electrical connector is coupled to the power supply.

[0012] **Example Implementation 7:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the protection circuit includes a switch configured to interrupt the output current from the power supply to the power source when the power supply is in the overcurrent condition.

[0013] **Example Implementation 8:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example

implementations, wherein the buck-boost charge controller being configured to regulate the output voltage and output current includes being configured to limit the output current to a maximum current when a terminal voltage of the power source falls below a threshold voltage when the power source is charged from the power supply.

[0014] Example Implementation 9: The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the aerosol precursor composition is a liquid, or a solid or semi-solid.

[0015] Example Implementation 10: The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the aerosol delivery device further comprises a non-inverting unity gain operational amplifier coupled to the heating element and configured to output a constant power to the heating element. The operational amplifier acts as a buffer to amplify the signal which may get attenuated. Usually a unity gain is designed but the gain may be more than 1 depending on the attenuation of the signal.

[0016] Example Implementation 11: The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the plurality of modes includes two or more of a buck mode, a boost mode or a buck-boost mode.

[0017] Example Implementation 12: A control body for an aerosol delivery device, the control body comprising: a heating element or terminals configured to connect the heating element to the control body, the heating element being configured to convert electricity to heat and thereby vaporize components of an aerosol precursor composition; a power source including one or more batteries or battery cells coupled to and configured to power a load including the heating element; and charge circuitry coupled to and configured to controllably charge the power source, the charge circuitry including: an electrical connector configured to connect the charge circuitry to a power supply from which the power source is chargeable; and a buck-boost charge controller coupled to and between the power source and power supply, and configured to regulate output voltage and output current from the power supply to the power source, selectively in one of a plurality of modes based on a condition of the power supply.

[0018] Example Implementation 13: The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the power source includes a plurality of batteries or battery cells.

5 **[0019] Example Implementation 14:** The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the plurality of batteries or battery cells are connected to form a plurality of paths for the output current from the power supply to flow through such that the output current is a sum of currents through each path of the plurality of
10 paths.

[0020] Example Implementation 15: The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the one or more batteries or battery cells include one or more lithium-ion, lithium iron phosphate or solid state batteries or battery cells.

15 **[0021] Example Implementation 16:** The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the power supply includes one or more lithium-ion or solid state batteries, or lithium-ion or hybrid lithium-ion capacitors, and the buck-boost charge controller being configured to regulate the output voltage and output current
20 from the power supply includes being configured to regulate the output voltage and output current from the one or more lithium-ion or solid state batteries, or lithium-ion or hybrid lithium-ion capacitors.

[0022] Example Implementation 17: The control body of any preceding example implementation, or any combination of any preceding example
25 implementations, wherein the charge circuitry further includes a protection circuit coupled to and between the electrical connector and the power source, and configured to protect the power source from an overcurrent condition in the power supply when the electrical connector is coupled to the power supply.

[0023] Example Implementation 18: The control body of any preceding
30 example implementation, or any combination of any preceding example implementations, wherein the protection circuit includes a switch configured to interrupt the output current from the power supply to the power source when the power supply is in the overcurrent condition.

[0024] Example Implementation 19: The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the buck-boost charge controller being configured to regulate the output voltage and output current includes being configured to limit the output current to a maximum current when a terminal voltage of the power source falls below a threshold voltage when the power source is charged from the power supply.

[0025] Example Implementation 20: The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the aerosol precursor composition is a liquid, or a solid or semi-solid.

[0026] Example Implementation 21: The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the control body further comprises a non-inverting unity gain operational amplifier coupled to the heating element and configured to output a constant power to the heating element.

[0027] Example Implementation 22: The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the plurality of modes includes two or more of a buck mode, a boost mode or a buck-boost mode.

[0028] These and other features, aspects, and advantages of the present disclosure will be apparent from a reading of the following detailed description together with the accompanying drawings, which are briefly described below. The present disclosure includes any combination of two, three, four or more features or elements set forth in this disclosure, regardless of whether such features or elements are expressly combined or otherwise recited in a specific example implementation described herein. This disclosure is intended to be read holistically such that any separable features or elements of the disclosure, in any of its aspects and example implementations, should be viewed as combinable, unless the context of the disclosure clearly dictates otherwise.

[0029] It will therefore be appreciated that this Brief Summary is provided merely for purposes of summarizing some example implementations so as to provide a basic understanding of some aspects of the disclosure. Accordingly, it will be appreciated that the above described example implementations are merely examples and should

not be construed to narrow the scope or spirit of the disclosure in any way. Other example implementations, aspects and advantages will become apparent from the following detailed description taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of some described example
5 implementations.

BRIEF DESCRIPTION OF THE FIGURES

[0030] Having thus described aspects of the disclosure in the foregoing general terms, reference will now be made to the accompanying figures, which are not
10 necessarily drawn to scale, and wherein:

[0031] FIG. 1 illustrates a perspective view of an aerosol delivery device including a cartridge and a control body that are coupled to one another, according to an example implementation of the present disclosure;

[0032] FIG. 2 is a partially cut-away view of the aerosol delivery device of FIG. 1
15 in which the cartridge and control body are decoupled from one another, according to an example implementation;

[0033] FIGS. 3 and 4 illustrate a perspective view of an aerosol delivery device comprising a control body and an aerosol source member that are respectively coupled to one another and decoupled from one another, according to another
20 example implementation of the present disclosure;

[0034] FIGS. 5 and 6 illustrate respectively a front view of and a sectional view through the aerosol delivery device of FIGS. 3 and 4, according to an example implementation; and

[0035] FIGS. 7A and 7B are circuit diagrams of an aerosol delivery device
25 according to various example implementations of the present disclosure.

DETAILED DESCRIPTION

[0036] The present disclosure will now be described more fully hereinafter with reference to example implementations thereof. These example implementations are
30 described so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. Indeed, the disclosure may be embodied in many different forms and should not be construed as limited to the implementations set forth herein; rather, these implementations are provided so that this disclosure will satisfy applicable legal requirements. As used in the specification

and the appended claims, the singular forms “a,” “an,” “the” and the like include plural referents unless the context clearly dictates otherwise. Also, while reference may be made herein to quantitative measures, values, geometric relationships or the like, unless otherwise stated, any one or more if not all of these may be absolute or approximate to account for acceptable variations that may occur, such as those due to engineering tolerances or the like.

5 [0037] As described hereinafter, example implementations of the present disclosure relate to aerosol delivery devices. Aerosol delivery devices according to the present disclosure use electrical energy to heat a material (preferably without combusting the material to any significant degree) to form an inhalable substance; and components of such systems have the form of articles most preferably are sufficiently compact to be considered hand-held devices. That is, use of components of preferred aerosol delivery devices does not result in the production of smoke in the sense that aerosol results principally from by-products of combustion or pyrolysis of tobacco, but rather, use of those preferred systems results in the production of vapors resulting from volatilization or vaporization of certain components incorporated therein. In some example implementations, components of aerosol delivery devices may be characterized as electronic cigarettes, and those electronic cigarettes most preferably incorporate tobacco and/or components derived from tobacco, and hence deliver tobacco derived components in aerosol form.

15 [0038] Aerosol generating components of certain preferred aerosol delivery devices may provide many of the sensations (e.g., inhalation and exhalation rituals, types of tastes or flavors, organoleptic effects, physical feel, use rituals, visual cues such as those provided by visible aerosol, and the like) of smoking a cigarette, cigar or pipe that is employed by lighting and burning tobacco (and hence inhaling tobacco smoke), without any substantial degree of combustion of any component thereof. For example, the user of an aerosol delivery device in accordance with some example implementations of the present disclosure can hold and use that component much like a smoker employs a traditional type of smoking article, draw on one end of that component for inhalation of aerosol produced by that component, take or draw puffs at selected intervals of time, and the like.

30 [0039] While the systems are generally described herein in terms of implementations associated with aerosol delivery devices such as so-called “e-cigarettes,” “tobacco heating products” and the like, it should be understood that the

mechanisms, components, features, and methods may be embodied in many different forms and associated with a variety of articles. For example, the description provided herein may be employed in conjunction with implementations of traditional smoking articles (e.g., cigarettes, cigars, pipes, etc.), heat-not-burn cigarettes, and related packaging for any of the products disclosed herein. Accordingly, it should be understood that the description of the mechanisms, components, features, and methods disclosed herein are discussed in terms of implementations relating to aerosol delivery devices by way of example only, and may be embodied and used in various other products and methods.

10 **[0040]** Aerosol delivery devices of the present disclosure also can be characterized as being vapor-producing articles or medicament delivery articles. Thus, such articles or devices can be adapted so as to provide one or more substances (e.g., flavors and/or pharmaceutical active ingredients) in an inhalable form or state. For example, inhalable substances can be substantially in the form of a vapor (i.e., a substance that is in the gas phase at a temperature lower than its critical point). Alternatively, inhalable substances can be in the form of an aerosol (i.e., a suspension of fine solid particles or liquid droplets in a gas). For purposes of simplicity, the term “aerosol” as used herein is meant to include vapors, gases and aerosols of a form or type suitable for human inhalation, whether or not visible, and whether or not of a form that might be considered to be smoke-like.

15 **[0041]** In use, aerosol delivery devices of the present disclosure may be subjected to many of the physical actions employed by an individual in using a traditional type of smoking article (e.g., a cigarette, cigar or pipe that is employed by lighting and inhaling tobacco). For example, the user of an aerosol delivery device of the present disclosure can hold that article much like a traditional type of smoking article, draw on one end of that article for inhalation of aerosol produced by that article, take puffs at selected intervals of time, etc.

20 **[0042]** Aerosol delivery devices of the present disclosure generally include a number of components provided within an outer housing, which may be referred to as a body or shell. The overall design of the housing can vary, and the format or configuration of the housing that can define the overall size and shape of the aerosol delivery device can vary. Typically, an elongated body resembling the shape of a cigarette or cigar can be formed from a single, unitary housing or the elongated housing can be formed of two or more separable bodies. For example, an aerosol

delivery device can comprise an elongated housing that can be substantially tubular in shape and, as such, resemble the shape of a conventional cigarette or cigar. In one example, all of the components of the aerosol delivery device are contained within one housing. Alternatively, an aerosol delivery device can comprise two or more housings that are joined and are separable. For example, an aerosol delivery device can possess at one end a control body comprising a housing containing one or more reusable components (e.g., an accumulator such as a rechargeable battery and/or rechargeable supercapacitor, and various electronics for controlling the operation of that article), and at the other end and removably and coupleable thereto, an outer body or shell containing a disposable portion (e.g., a disposable flavor-containing cartridge). More specific formats, configurations and arrangements of components within the single housing type of unit or within a multi-piece separable housing type of unit will be evident in light of the further disclosure provided herein. Additionally, various aerosol delivery device designs and component arrangements can be appreciated upon consideration of the commercially available electronic aerosol delivery devices. It will be appreciated that alternative non-tubular housing form factors can also be used, including, for example, device housings having a shape and size generally approximating a pack of cigarettes and form factors such as used on the GLO™ by British American Tobacco and IQOS™ by Philip Morris International, Inc.

20 **[0043]** As will be discussed in more detail below, aerosol delivery devices of the present disclosure comprise some combination of a power source (i.e., an electrical power source), at least one control component (e.g., means for actuating, controlling, regulating and ceasing power for heat generation, such as by controlling electrical current flow from the power source to other components of the aerosol delivery device), a heating element (e.g., an electrical resistance heating element or other component and/or an inductive coil or other associated components and/or one or more radiant heating elements), and an aerosol precursor composition (e.g., a solid tobacco material, a semi-solid tobacco material or a liquid aerosol precursor composition) capable of yielding an aerosol upon application of sufficient heat, and a mouth end region or tip to allow drawing upon the aerosol delivery device for aerosol inhalation (e.g., a defined airflow path through the article such that aerosol generated can be withdrawn therefrom upon draw).

30 **[0044]** Alignment of the components within the aerosol delivery device of the present disclosure can vary. In specific implementations, the aerosol precursor

composition can be located near an end of the aerosol delivery device which may be configured to be positioned proximal to the mouth of a user so as to maximize aerosol delivery to the user. Other configurations, however, are not excluded. Generally, the heating element may be positioned sufficiently near the aerosol precursor composition so that heat from the heating element can volatilize the aerosol precursor (as well as one or more flavorants, medicaments, or the like that may likewise be provided for delivery to a user) and form an aerosol for delivery to the user. When the heating element heats the aerosol precursor composition, an aerosol is formed, released, or generated in a physical form suitable for inhalation by a consumer. It should be noted that the foregoing terms are meant to be interchangeable such that reference to release, releasing, releases, or released includes form or generate, forming or generating, forms or generates, and formed or generated. Specifically, an inhalable substance is released in the form of a vapor or aerosol or mixture thereof, wherein such terms are also interchangeably used herein except where otherwise specified.

[0045] As noted above, the aerosol delivery device may incorporate a battery. Supercapacitor, solid state battery or other power source to provide current flow sufficient to provide various functionalities to the aerosol delivery device, such as powering of a heating element, powering of control systems, powering of indicators, and the like. The power source can take on various implementations. Preferably, the power source is able to deliver sufficient power to rapidly activate the heating element to provide for aerosol formation and power the aerosol delivery device through use for a desired duration of time. The power source preferably is sized to fit conveniently within the aerosol delivery device so that the aerosol delivery device can be easily handled. Additionally, a preferred power source is of a sufficiently light weight to not detract from a desirable smoking experience.

[0046] More specific formats, configurations and arrangements of components within the aerosol delivery device of the present disclosure will be evident in light of the further disclosure provided hereinafter. Additionally, the selection of various aerosol delivery device components can be appreciated upon consideration of the commercially available electronic aerosol delivery devices. Further, the arrangement of the components within the aerosol delivery device can also be appreciated upon consideration of the commercially available electronic aerosol delivery devices.

[0047] As described hereinafter, the present disclosure relates to aerosol delivery devices. Aerosol delivery devices may be configured to heat an aerosol precursor

composition (sometimes referred to as an inhalable substance medium) to produce an aerosol (an inhalable substance). The aerosol precursor composition may comprise one or more of a solid tobacco material, a semi-solid tobacco material, and a liquid aerosol precursor composition. In some implementations, the aerosol delivery devices
5 may be configured to heat and produce an aerosol from a fluid aerosol precursor composition (e.g., a liquid aerosol precursor composition). Such aerosol delivery devices may include so-called electronic cigarettes.

[0048] Liquid aerosol precursor composition, also referred to as a vapor precursor composition or “e-liquid,” may comprise a variety of components including, by way
10 of example, a polyhydric alcohol (e.g., glycerin, propylene glycol, or a mixture thereof), nicotine, tobacco, tobacco extract, and/or flavorants. Some liquid aerosol precursor compositions that may be used in conjunction with various implementations may include one or more acids such as levulinic acid, succinic acid, lactic acid, pyruvic acid, benzoic acid, fumaric acid, combinations thereof, and the like.

15 Inclusion of an acid(s) in liquid aerosol precursor compositions including nicotine may provide a protonated liquid aerosol precursor composition, including nicotine in salt form. Representative types of liquid aerosol precursor components and formulations are set forth and characterized in U.S. Pat. No. 7,726,320 to Robinson et al., U.S. Pat. No. 9,254,002 to Chong et al., and U.S. Pat. App. Pub. Nos.
20 2013/0008457 to Zheng et al., 2015/0020823 to Lipowicz et al., and 2015/0020830 to Koller, as well as PCT Pat. App. Pub. No. WO 2014/182736 to Bowen et al., and U.S. Pat. No. 8,881,737 to Collett et al., the disclosures of which are incorporated herein by reference. Other aerosol precursors that may be employed include the aerosol precursors that have been incorporated in any of a number of the representative
25 products identified above. Also desirable are the so-called “smoke juices” for electronic cigarettes that have been available from Johnson Creek Enterprises LLC. Still further example aerosol precursor compositions are sold under the brand names BLACK NOTE, COSMIC FOG, THE MILKMAN E-LIQUID, FIVE PAWNS, THE VAPOR CHEF, VAPE WILD, BOOSTED, THE STEAM FACTORY, MECH
30 SAUCE, CASEY JONES MAINLINE RESERVE, MITTEN VAPORS, DR. CRIMMY’S V-LIQUID, SMILEY E LIQUID, BEANTOWN VAPOR, CUTTWOOD, CYCLOPS VAPOR, SICBOY, GOOD LIFE VAPOR, TELEOS, PINUP VAPORS, SPACE JAM, MT. BAKER VAPOR, and JIMMY THE JUICE MAN. Implementations of effervescent materials can be used with the aerosol

precursor, and are described, by way of example, in U.S. Pat. App. Pub. No. 2012/0055494 to Hunt et al., which is incorporated herein by reference. Further, the use of effervescent materials is described, for example, in U.S. Pat. No. 4,639,368 to Niazi et al., U.S. Pat. No. 5,178,878 to Wehling et al., U.S. Pat. No. 5,223,264 to Wehling et al., U.S. Pat. No. 6,974,590 to Pather et al., U.S. Pat. No. 7,381,667 to Bergquist et al., U.S. Pat. No. 8,424,541 to Crawford et al., U.S. Pat. No. 8,627,828 to Strickland et al., and U.S. Pat. No. 9,307,787 to Sun et al., as well as U.S. Pat. App. Pub. Nos. 2010/0018539 to Brinkley et al., and PCT Pat. App. Pub. No. WO 97/06786 to Johnson et al., all of which are incorporated by reference herein.

10 **[0049]** Representative types of substrates, reservoirs or other components for supporting the aerosol precursor are described in U.S. Pat. No. 8,528,569 to Newton, U.S. Pat. App. Pub. No. 2014/0261487 to Chapman et al., U.S. Pat. App. Pub. No. 2015/0059780 to Davis et al., and U.S. Pat. App. Pub. No. 2015/0216232 to Bless et al., all of which are incorporated herein by reference. Additionally, various wicking
15 materials, and the configuration and operation of those wicking materials within certain types of electronic cigarettes, are set forth in U.S. Pat. No. 8,910,640 to Sears et al., which is incorporated herein by reference.

[0050] In other implementations, the aerosol delivery devices may comprise heat-not-burn devices, configured to heat a solid aerosol precursor composition (e.g., an
20 extruded tobacco rod) or a semi-solid aerosol precursor composition (e.g., a glycerin-loaded tobacco paste). The aerosol precursor composition may comprise tobacco-containing beads, tobacco shreds, tobacco strips, reconstituted tobacco material, or combinations thereof, and/or a mix of finely ground tobacco, tobacco extract, spray dried tobacco extract, or other tobacco form mixed with optional inorganic materials
25 (such as calcium carbonate), optional flavors, and aerosol forming materials to form a substantially solid or moldable (e.g., extrudable) substrate. Representative types of solid and semi-solid aerosol precursor compositions and formulations are disclosed in U.S. Pat. No. 8,424,538 to Thomas et al., U.S. Pat. No. 8,464,726 to Sebastian et al., U.S. Pat. App. Pub. No. 2015/0083150 to Conner et al., U.S. Pat. App. Pub. No.
30 2015/0157052 to Ademe et al., and U.S. Pat. App. Pub. No. 2017/0000188 to Nordskog et al., all of which are incorporated by reference herein. Further representative types of solid and semi-solid aerosol precursor compositions and arrangements include those found in the NEOSTIKS™ consumable aerosol source members for the GLO™ product by British American Tobacco and in the HEETS™

consumable aerosol source members for the IQOS™ product by Philip Morris International, Inc.

[0051] In various implementations, the inhalable substance specifically may be a tobacco component or a tobacco-derived material (i.e., a material that is found naturally in tobacco that may be isolated directly from the tobacco or synthetically prepared). For example, the aerosol precursor composition may comprise tobacco extracts or fractions thereof combined with an inert substrate. The aerosol precursor composition may further comprise unburned tobacco or a composition containing unburned tobacco that, when heated to a temperature below its combustion temperature, releases an inhalable substance. In some implementations, the aerosol precursor composition may comprise tobacco condensates or fractions thereof (i.e., condensed components of the smoke produced by the combustion of tobacco, leaving flavors and, possibly, nicotine).

[0052] Tobacco materials useful in the present disclosure can vary and may include, for example, flue-cured tobacco, burley tobacco, Oriental tobacco or Maryland tobacco, dark tobacco, dark-fired tobacco and *Rustica* tobaccos, as well as other rare or specialty tobaccos, or blends thereof. Tobacco materials also can include so-called “blended” forms and processed forms, such as processed tobacco stems (e.g., cut-rolled or cut-puffed stems), volume expanded tobacco (e.g., puffed tobacco, such as dry ice expanded tobacco (DIET), preferably in cut filler form), reconstituted tobaccos (e.g., reconstituted tobaccos manufactured using paper-making type or cast sheet type processes). Various representative tobacco types, processed types of tobaccos, and types of tobacco blends are set forth in U.S. Pat. Nos. 4,836,224 to Lawson et al., 4,924,888 to Perfetti et al., 5,056,537 to Brown et al., 5,159,942 to Brinkley et al., 5,220,930 to Gentry, 5,360,023 to Blakley et al., 6,701,936 to Shafer et al., 7,011,096 to Li et al., and 7,017,585 to Li et al., 7,025,066 to Lawson et al., U.S. Pat. App. Pub. No. 2004/0255965 to Perfetti et al., PCT Pat. App. Pub. No. WO 02/37990 to Bereman, and Bombick et al., Fund. Appl. Toxicol., 39, p. 11-17 (1997), which are incorporated herein by reference. Further example tobacco compositions that may be useful in a smoking device, including according to the present disclosure, are disclosed in U.S. Pat. No. 7,726,320 to Robinson et al., which is incorporated herein by reference.

[0053] Still further, the aerosol precursor composition may comprise an inert substrate having the inhalable substance, or a precursor thereof, integrated therein or

otherwise deposited thereon. For example, a liquid comprising the inhalable substance may be coated on or absorbed or adsorbed into the inert substrate such that, upon application of heat, the inhalable substance is released in a form that can be withdrawn from the inventive article through application of positive or negative
5 pressure. In some aspects, the aerosol precursor composition may comprise a blend of flavorful and aromatic tobaccos in cut filler form. In another aspect, the aerosol precursor composition may comprise a reconstituted tobacco material, such as described in U.S. Pat. No. 4,807,809 to Pryor et al., U.S. Pat. No. 4,889,143 to Pryor et al. and U.S. Pat. No. 5,025,814 to Raker, the disclosures of which are incorporated
10 herein by reference. For further information regarding suitable aerosol precursor composition, see U.S. Pat. App. Ser. No. 15/916,834 to Sur et al., filed March 9, 2018, which is incorporated herein by reference.

[0054] Regardless of the type of aerosol precursor composition heated, aerosol delivery devices may include a heating element configured to heat the aerosol
15 precursor composition. In some implementations, the heating element is an induction heater. Such heaters often comprise an induction transmitter and an induction receiver. The induction transmitter may include a coil configured to create an oscillating magnetic field (e.g., a magnetic field that varies periodically with time) when alternating current is directed through it. The induction receiver may be at least
20 partially located or received within the induction transmitter and may include a conductive material (ferromagnetic material or an Aluminum coated material). By directing alternating current through the induction transmitter, eddy currents may be generated in the induction receiver via induction. The eddy currents flowing through the resistance of the material defining the induction receiver may heat it by Joule
25 heating (i.e., through the Joule effect). The induction receiver, which may define an atomizer, may be wirelessly heated to form an aerosol from an aerosol precursor composition positioned in proximity to the induction receiver. Various implementations of an aerosol delivery device with an induction heater are described in U.S. Pat. App. Pub. No. 2017/0127722 to Davis et al., U.S. Pat. App. Pub. No.
30 2017/0202266 to Sur et al., U.S. Pat. App. Ser. No. 15/352,153 to Sur et al., filed November 15, 2016, U.S. Pat. App. Ser. No. 15/799,365 to Sebastian et al., filed October 31, 2017, and U.S. Pat. App. Ser. No. 15/836,086 to Sur, all of which are incorporated by reference herein.

[0055] In other implementations including those described more particularly herein, the heating element is a conductive heater such as in the case of electrical resistance heater. These heaters may be configured to produce heat when an electrical current is directed through it. In various implementations, a conductive heater may be provided in a variety forms, such as in the form of a foil, a foam, discs, spirals, fibers, wires, films, yarns, strips, ribbons or cylinders. Such heaters often include a metal material and are configured to produce heat as a result of the electrical resistance associated with passing an electrical current through it. Such resistive heaters may be positioned in proximity to and heat an aerosol precursor composition to produce an aerosol. A variety of conductive substrates that may be usable with the present disclosure are described in the above-cited U.S. Pat. App. Pub. No. 2013/0255702 to Griffith et al.

[0056] In some implementations aerosol delivery devices may include a control body and a cartridge in the case of so-called electronic cigarettes, or a control body and an aerosol source member in the case of heat-not-burn devices. In the case of either electronic cigarettes or heat-not-burn devices, the control body may be reusable, whereas the cartridge / aerosol source member may be configured for a limited number of uses and/or configured to be disposable. The cartridge / aerosol source member may include the aerosol precursor composition. In order to heat the aerosol precursor composition, the heating element may be positioned in contact with or proximate the aerosol precursor composition, such as across the control body and cartridge, or in the control body in which the aerosol source member may be positioned. The control body may include a power source, which may be rechargeable or replaceable, and thereby the control body may be reused with multiple cartridges / aerosol source members.

[0057] The control body may also include means to activate the aerosol delivery device such as a pushbutton, touch-sensitive surface or the like for manual control of the device. Additionally or alternatively, the control body may include a flow sensor to detect when a user draws on the cartridge / aerosol source member to thereby activate the aerosol delivery device.

[0058] In various implementations, the aerosol delivery device according to the present disclosure may have a variety of overall shapes, including, but not limited to an overall shape that may be defined as being substantially rod-like or substantially tubular shaped or substantially cylindrically shaped. In the implementations shown in

and described with reference to the accompanying figures, the aerosol delivery device has a substantially round cross-section; however, other cross-sectional shapes (e.g., oval, square, rectangle, triangle, etc.) also are encompassed by the present disclosure. Such language that is descriptive of the physical shape of the article may also be applied to the individual components thereof, including the control body and the cartridge / aerosol source member. In other implementations, the control body may take another handheld shape, such as a small box shape.

[0059] In more specific implementations, one or both of the control body and the cartridge / aerosol source member may be referred to as being disposable or as being reusable. For example, the control body may have a power source such as a replaceable battery or a rechargeable battery, solid-state battery, thin-film solid-state battery, rechargeable supercapacitor or the like. One example of a power source is a TKI-1550 rechargeable lithium-ion battery produced by Tadiran Batteries GmbH of Germany. In another implementation, a useful power source may be a N50-AAA CADNICA nickel-cadmium cell produced by Sanyo Electric Company, Ltd., of Japan. In other implementations, a plurality of such batteries, for example providing 1.2-volts each, may be connected in series.

[0060] In some examples, then, the power source may be connected to and thereby combined with any type of recharging technology. Examples of suitable chargers include chargers that simply supply constant or pulsed direct current (DC) power to the power source, fast chargers that add control circuitry, three-stage chargers, induction-powered chargers, smart chargers, motion-powered chargers, pulsed chargers, solar chargers, USB-based chargers and the like. In some examples, the charger includes a power adapter and any suitable charge circuitry. In other examples, the charger includes the power adapter and the control body is equipped with charge circuitry. In these other examples, the charger may at times be simply referred to as a power adapter.

[0061] The control body may include any of a number of different terminals, electrical connectors or the like to connect to a suitable charger, and in some examples, to connect to other peripherals for communication. More specific suitable examples include direct current (DC) connectors such as cylindrical connectors, cigarette lighter connectors and USB connectors including those specified by USB 1.x (e.g., Type A, Type B), USB 2.0 and its updates and additions (e.g., Mini A, Mini B, Mini AB, Micro A, Micro B, Micro AB) and USB 3.x (e.g., Type A, Type B, Micro B,

Micro AB, Type C), proprietary connectors such as Apple's Lightning connector, and the like. The control body may directly connect with the charger or other peripheral, or the two may connect via an appropriate cable that also has suitable connectors. In examples in which the two are connected by cable, the control body and charger or
5 other peripheral may have the same or different type of connector with the cable having the one type of connector or both types of connectors.

[0062] In examples involving induction-powered charging, the aerosol delivery device may be equipped with inductive wireless charging technology and include an induction receiver to connect with a wireless charger, charging pad or the like that
10 includes an induction transmitter and uses inductive wireless charging (including for example, wireless charging according to the Qi wireless charging standard from the Wireless Power Consortium (WPC)). Or the power source may be recharged from a wireless radio frequency (RF) based charger. An example of an inductive wireless charging system is described in U.S. Pat. App. Pub. No. 2017/0112196 to Sur et al.,
15 which is incorporated herein by reference in its entirety. Further, in some implementations in the case of an electronic cigarette, the cartridge may comprise a single-use cartridge, as disclosed in U.S. Pat. No. 8,910,639 to Chang et al., which is incorporated herein by reference.

[0063] One or more connections may be employed to connect the power source to
20 a recharging technology, and some may involve a charging case, cradle, dock, sleeve or the like. More specifically, for example, the control body may be configured to engage a cradle that includes a USB connector to connect to a power supply. Or in another example, the control body may be configured to fit within and engage a sleeve that includes a USB connector to connect to a power supply. In these and
25 similar examples, the USB connector may connect directly to the power source, or the USB connector may connect to the power source via a suitable power adapter.

[0064] Examples of power sources are described in U.S. Pat. No. 9,484,155 to Peckerar et al., and U.S. Pat. App. Pub. No. 2017/0112191 to Sur et al., filed October 21, 2015, the disclosures of which are incorporated herein by reference. With respect
30 to the flow sensor, representative current regulating components and other current controlling components including various microcontrollers, sensors, and switches for aerosol delivery devices are described in U.S. Pat. No. 4,735,217 to Gerth et al., U.S. Pat. Nos. 4,922,901, 4,947,874, and 4,947,875, all to Brooks et al., U.S. Pat. No. 5,372,148 to McCafferty et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S.

Pat. No. 7,040,314 to Nguyen et al., U.S. Pat. No. 8,205,622 to Pan, U.S. Pat. App. Pub. No. 8,881,737 to Collet et al., U.S. Pat. No. 9,423,152 to Ampolini et al., U.S. Pat. No. 9,439,454 to Fernando et al., and U.S. Pat. App. Pub. No. 2015/0257445 to Henry et al., all of which are incorporated herein by reference.

5 **[0065]** An input element may be included with the aerosol delivery device (and may replace or supplement a flow sensor). The input may be included to allow a user to control functions of the device and/or for output of information to a user. Any component or combination of components may be utilized as an input for controlling the function of the device. For example, one or more pushbuttons may be used as
10 described in U.S. Pub. No. 2015/0245658 to Worm et al., which is incorporated herein by reference. Likewise, a touchscreen may be used as described in U.S. Pat. App. Ser. No. 14/643,626, filed March 10, 2015, to Sears et al., which is incorporated herein by reference. As a further example, components adapted for gesture recognition based on specified movements of the aerosol delivery device may be used as an input. See
15 U.S. Pub. 2016/0158782 to Henry et al., which is incorporated herein by reference. As still a further example, a capacitive sensor may be implemented on the aerosol delivery device to enable a user to provide input, such as by touching a surface of the device on which the capacitive sensor is implemented. In another example, a sensor capable of detecting a motion associated with the device (e.g., accelerometer,
20 gyroscope, photoelectric proximity sensor, etc.) may be implemented on the aerosol delivery device to enable a user to provide input. Examples of suitable sensors are described in U.S. Pat. App. Pub. No. 2018/0132528 to Sur et al., and U.S. Pat. App. Pub. No. 2016/0158782 to Henry et al., which are incorporated herein by reference.

25 **[0066]** As indicated above, the aerosol delivery device may include at least one control component. A suitable control component may include a number of electronic components, and in some examples may be formed of a printed circuit board (PCB). In some examples, the electronic components include processing circuitry configured to perform data processing, application execution, or other processing, control or management services according to one or more example implementations. The
30 processing circuitry may include a processor embodied in a variety of forms such as at least one processor core, microprocessor, coprocessor, controller, microcontroller or various other computing or processing devices including one or more integrated circuits such as, for example, an ASIC (application specific integrated circuit), an FPGA (field programmable gate array), some combination thereof, or the like. In

some examples, the processing circuitry may include memory coupled to or integrated with the processor, and which may store data, computer program instructions executable by the processor, some combination thereof, or the like.

[0067] In some examples, the control component may include one or more
5 input/output peripherals, which may be coupled to or integrated with the processing circuitry. More particularly, the control component may include a communication interface to enable wireless communication with one or more networks, computing devices or other appropriately-enabled devices. Examples of suitable communication interfaces are disclosed in U.S. Pat. App. Pub. No. 2016/0261020 to Marion et al., the
10 content of which is incorporated herein by reference. Another example of a suitable communication interface is the CC3200 single chip wireless microcontroller unit (MCU) from Texas Instruments. And examples of suitable manners according to which the aerosol delivery device may be configured to wirelessly communicate are disclosed in U.S. Pat. App. Pub. No. 2016/0007651 to Ampolini et al., and U.S. Pat.
15 App. Pub. No. 2016/0219933 to Henry, Jr. et al., each of which is incorporated herein by reference.

[0068] Still further components can be utilized in the aerosol delivery device of the present disclosure. One example of a suitable component is an indicator such as light-emitting diodes (LEDs), quantum dot-based LEDs or the like, which may be
20 illuminated with use of the aerosol delivery device. Examples of suitable LED components, and the configurations and uses thereof, are described in U.S. Pat. No. 5,154,192 to Sprinkel et al., U.S. Pat. No. 8,499,766 to Newton, U.S. Pat. No. 8,539,959 to Scatterday, and U.S. Pat. No. 9,451,791 to Sears et al., all of which are incorporated herein by reference.

[0069] Other indices of operation are also encompassed by the present disclosure. For example, visual indicators of operation also include changes in light color or intensity to show progression of the smoking experience. Tactile (haptic) indicators of operation and sound (audio) indicators of operation similarly are encompassed by the disclosure. Moreover, combinations of such indicators of operation also are
25 suitable to be used in a single smoking article. According to another aspect, the aerosol delivery device may include one or more indicators or indicia, such as, for example, a display configured to provide information corresponding to the operation of the smoking article such as, for example, the amount of power remaining in the
30

power source, progression of the smoking experience, indication corresponding to activating a heat source, and/or the like.

[0070] Yet other components are also contemplated. For example, U.S. Pat. No. 5,154,192 to Sprinkel et al. discloses indicators for smoking articles; U.S. Pat. No. 5,261,424 to Sprinkel, Jr. discloses piezoelectric sensors that can be associated with the mouth-end of a device to detect user lip activity associated with taking a draw and then trigger heating of a heating device; U.S. Pat. No. 5,372,148 to McCafferty et al. discloses a puff sensor for controlling energy flow into a heating load array in response to pressure drop through a mouthpiece; U.S. Pat. No. 5,967,148 to Harris et al. discloses receptacles in a smoking device that include an identifier that detects a non-uniformity in infrared transmissivity of an inserted component and a controller that executes a detection routine as the component is inserted into the receptacle; U.S. Pat. No. 6,040,560 to Fleischhauer et al. describes a defined executable power cycle with multiple differential phases; U.S. Pat. No. 5,934,289 to Watkins et al. discloses photonic-optronic components; U.S. Pat. No. 5,954,979 to Counts et al. discloses means for altering draw resistance through a smoking device; U.S. Pat. No. 6,803,545 to Blake et al. discloses specific battery configurations for use in smoking devices; U.S. Pat. No. 7,293,565 to Griffen et al. discloses various charging systems for use with smoking devices; U.S. Pat. No. 8,402,976 to Fernando et al. discloses computer interfacing means for smoking devices to facilitate charging and allow computer control of the device; U.S. Pat. No. 8,689,804 to Fernando et al. discloses identification systems for smoking devices; and PCT Pat. App. Pub. No. WO 2010/003480 by Flick discloses a fluid flow sensing system indicative of a puff in an aerosol generating system; all of the foregoing disclosures being incorporated herein by reference.

[0071] Further examples of components related to electronic aerosol delivery articles and disclosing materials or components that may be used in the present article include U.S. Pat. No. 4,735,217 to Gerth et al., U.S. Pat. No. 5,249,586 to Morgan et al., U.S. Pat. No. 5,666,977 to Higgins et al., U.S. Pat. No. 6,053,176 to Adams et al., U.S. 6,164,287 to White, U.S. Pat No. 6,196,218 to Voges, U.S. Pat. No. 6,810,883 to Felter et al., U.S. Pat. No. 6,854,461 to Nichols, U.S. Pat. No. 7,832,410 to Hon, U.S. Pat. No. 7,513,253 to Kobayashi, U.S. Pat. No. 7,896,006 to Hamano, U.S. Pat. No. 6,772,756 to Shayan, U.S. Pat. No. 8,156,944 and 8,375,957 to Hon, U.S. Pat. No. 8,794,231 to Thorens et al., U.S. Pat. No. 8,851,083 to Oglesby et al., U.S. Pat. No.

8,915,254 and 8,925,555 to Monsees et al., U.S. Pat. No. 9,220,302 to DePiano et al., U.S. Pat. App. Pub. Nos. 2006/0196518 and 2009/0188490 to Hon, U.S. Pat. App. Pub. No. 2010/0024834 to Oglesby et al., U.S. Pat. App. Pub. No. 2010/0307518 to Wang, PCT Pat. App. Pub. No. WO 2010/091593 to Hon, and PCT Pat. App. Pub. No. WO 2013/089551 to Foo, each of which is incorporated herein by reference. Further, U.S. Pat. App. Pub. No. 2017/0099877 to Worm et al., discloses capsules that may be included in aerosol delivery devices and fob-shape configurations for aerosol delivery devices, and is incorporated herein by reference. A variety of the materials disclosed by the foregoing documents may be incorporated into the present devices in various implementations, and all of the foregoing disclosures are incorporated herein by reference.

[0072] Yet other features, controls or components that can be incorporated into aerosol delivery devices of the present disclosure are described in U.S. Pat. No. 5,967,148 to Harris et al., U.S. Pat. No. 5,934,289 to Watkins et al., U.S. Pat. No. 5,954,979 to Counts et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S. Pat. No. 8,365,742 to Hon, U.S. Pat. No. 8,402,976 to Fernando et al., U.S. Pat. App. Pub. No. 2005/0016550 to Katase, U.S. Pat. No. 8,689,804 to Fernando et al., U.S. Pat. App. Pub. No. 2013/0192623 to Tucker et al., U.S. Pat. No. 9,427,022 to Leven et al., U.S. Pat. App. Pub. No. 2013/0180553 to Kim et al., U.S. Pat. App. Pub. No. 2014/0000638 to Sebastian et al., U.S. Pat. App. Pub. No. 2014/0261495 to Novak et al., and U.S. Pat. No. 9,220,302 to DePiano et al., all of which are incorporated herein by reference.

[0073] FIGS. 1 and 2 illustrate implementations of an aerosol delivery device including a control body and a cartridge in the case of an electronic cigarette. More specifically, FIGS. 1 and 2 illustrate an aerosol delivery device **100** according to an example implementation of the present disclosure. As indicated, the aerosol delivery device may include a control body **102** and a cartridge **104**. The control body and the cartridge can be permanently or detachably aligned in a functioning relationship. In this regard, FIG. 1 illustrates a perspective view of the aerosol delivery device in a coupled configuration, whereas FIG. 2 illustrates a partially cut-away side view of the aerosol delivery device in a decoupled configuration. The aerosol delivery device may, for example, be substantially rod-like, substantially tubular shaped, or substantially cylindrically shaped in some implementations when the control body and the cartridge are in an assembled configuration.

[0074] The control body **102** and the cartridge **104** can be configured to engage one another by a variety of connections, such as a press fit (or interference fit) connection, a threaded connection, a magnetic connection, or the like. As such, the control body may include a first engaging element (e.g., a coupler) that is adapted to engage a second engaging element (e.g., a connector) on the cartridge. The first engaging element and the second engaging element may be reversible. As an example, either of the first engaging element or the second engaging element may be a male thread, and the other may be a female thread. As a further example, either the first engaging element or the second engaging element may be a magnet, and the other may be a metal or a matching magnet. In particular implementations, engaging elements may be defined directly by existing components of the control body and the cartridge. For example, the housing of the control body may define a cavity at an end thereof that is configured to receive at least a portion of the cartridge (e.g., a storage tank or other shell-forming element of the cartridge). In particular, a storage tank of the cartridge may be at least partially received within the cavity of the control body while a mouthpiece of the cartridge remains exposed outside of the cavity of the control body. The cartridge may be retained within the cavity formed by the control body housing, such as by an interference fit (e.g., through use of detents and/or other features creating an interference engagement between an outer surface of the cartridge and an interior surface of a wall forming the control body cavity), by a magnetic engagement (e.g., through use of magnets and/or magnetic metals positioned within the cavity of the control body and positioned on the cartridge), or by other suitable techniques.

[0075] As seen in the cut-away view illustrated in FIG. 2, the control body **102** and cartridge **104** each include a number of respective components. The components illustrated in FIG. 2 are representative of the components that may be present in a control body and cartridge and are not intended to limit the scope of components that are encompassed by the present disclosure. As shown, for example, the control body can be formed of a housing **206** (sometimes referred to as a control body shell) that can include a control component **208** (e.g., processing circuitry, etc.), a flow sensor **210**, a power source **212** (e.g., battery, supercapacitor), and an indicator **214** (e.g., LED, quantum dot-based LED), and such components can be variably aligned. The power source may be rechargeable, and the control body may include charging circuitry **216** coupled to and configured to controllably charge the power source.

[0076] The cartridge **104** can be formed of a housing **218** (sometimes referred to as the cartridge shell) enclosing a reservoir **220** configured to retain the aerosol precursor composition, and including a heating element **222** (sometimes referred to as a heater). In various configurations, this structure may be referred to as a tank; and
5 accordingly, the terms “cartridge,” “tank” and the like may be used interchangeably to refer to a shell or other housing enclosing a reservoir for aerosol precursor composition, and including a heating element.

[0077] As shown, in some examples, the reservoir **220** may be in fluid communication with a liquid transport element **224** adapted to wick or otherwise
10 transport an aerosol precursor composition stored in the reservoir housing to the heating element **222**. In some examples, a valve may be positioned between the reservoir and heating element, and configured to control an amount of aerosol precursor composition passed or delivered from the reservoir to the heating element.

[0078] Various examples of materials configured to produce heat when electrical
15 current is applied therethrough may be employed to form the heating element **222**. The heating element in these examples may be a resistive heating element such as a wire coil, micro heater or the like. Example materials from which the heating element may be formed include Kanthal (FeCrAl), nichrome, nickel,, stainless steel, indium tin oxide, tungsten, molybdenum disilicide (MoSi_2), molybdenum silicide (MoSi),
20 molybdenum disilicide doped with aluminum ($\text{Mo}(\text{Si},\text{Al})_2$), titanium, platinum, silver, palladium, alloys of silver and palladium, graphite and graphite-based materials (e.g., carbon-based foams and yarns), conductive inks, boron doped silica, and ceramics (e.g., positive or negative temperature coefficient ceramics). The heating element may be resistive heating element or a heating element configured to generate heat
25 through induction. The heating element may be coated by heat conductive ceramics such as aluminum nitride, silicon carbide, beryllium oxide, alumina, silicon nitride, or their composites. Example implementations of heating elements useful in aerosol delivery devices according to the present disclosure are further described below, and can be incorporated into devices such as those described herein.

30 [0079] An opening **226** may be present in the housing **218** (e.g., at the mouth end) to allow for egress of formed aerosol from the cartridge **104**.

[0080] The cartridge **104** also may include one or more electronic components **228**, which may include an integrated circuit, a memory component (e.g., EEPROM, flash memory), a sensor, or the like. The electronic components may be adapted to

communicate with the control component **208** and/or with an external device by wired or wireless means. The electronic components may be positioned anywhere within the cartridge or a base **230** thereof.

[0081] Although the control component **208** and the flow sensor **210** are
5 illustrated separately, it is understood that various electronic components including the control component and the flow sensor may be combined on a PCB that supports and electrically connects the electronic components. Further, the PCB may be positioned horizontally relative the illustration of FIG. 1 in that the PCB can be lengthwise parallel to the central axis of the control body. In some examples, the air
10 flow sensor may comprise its own PCB or other base element to which it can be attached. In some examples, a flexible PCB may be utilized. A flexible PCB may be configured into a variety of shapes, include substantially tubular shapes. In some examples, a flexible PCB may be combined with, layered onto, or form part or all of a heater substrate.

[0082] The control body **102** and the cartridge **104** may include components adapted to facilitate a fluid engagement therebetween. As illustrated in FIG. 2, the control body can include a coupler **232** having a cavity **234** therein. The base **230** of the cartridge can be adapted to engage the coupler and can include a projection **236** adapted to fit within the cavity. Such engagement can facilitate a stable connection
20 between the control body and the cartridge as well as establish an electrical connection between the power source **212** and control component **208** in the control body and the heating element **222** in the cartridge. Further, the housing **206** can include an air intake **238**, which may be a notch in the housing where it connects to the coupler that allows for passage of ambient air around the coupler and into the
25 housing where it then passes through the cavity **234** of the coupler and into the cartridge through the projection **236**.

[0083] A coupler and a base useful according to the present disclosure are described in U.S. Pat. App. Pub. No. 2014/0261495 to Novak et al., which is incorporated herein by reference. For example, the coupler **232** as seen in FIG. 2 may
30 define an outer periphery **240** configured to mate with an inner periphery **242** of the base **230**. In one example the inner periphery of the base may define a radius that is substantially equal to, or slightly greater than, a radius of the outer periphery of the coupler. Further, the coupler may define one or more protrusions **244** at the outer periphery configured to engage one or more recesses **246** defined at the inner

periphery of the base. However, various other examples of structures, shapes and components may be employed to couple the base to the coupler. In some examples the connection between the base of the cartridge **104** and the coupler of the control body **102** may be substantially permanent, whereas in other examples the connection therebetween may be releasable such that, for example, the control body may be reused with one or more additional cartridges that may be disposable and/or refillable.

[0084] The reservoir **220** illustrated in FIG. 2 can be a container or can be a fibrous reservoir, as presently described. For example, the reservoir can comprise one or more layers of nonwoven fibers substantially formed into the shape of a tube encircling the interior of the housing **218**, in this example. An aerosol precursor composition can be retained in the reservoir. Liquid components, for example, can be sorptively retained by the reservoir. The reservoir can be in fluid connection with the liquid transport element **224**. The liquid transport element can transport the aerosol precursor composition stored in the reservoir via capillary action to the heating element **222** that is in the form of a metal wire coil in this example. As such, the heating element is in a heating arrangement with the liquid transport element.

[0085] In some examples, a microfluidic chip may be embedded in the reservoir **220**, and the amount and/or mass of aerosol precursor composition delivered from the reservoir may be controlled by a micro pump, such as one based on microelectromechanical systems (MEMS) technology. Other example implementations of reservoirs and transport elements useful in aerosol delivery devices according to the present disclosure are further described herein, and such reservoirs and/or transport elements can be incorporated into devices such as those described herein. In particular, specific combinations of heating members and transport elements as further described herein may be incorporated into devices such as those described herein.

[0086] In use, when a user draws on the aerosol delivery device **100**, airflow is detected by the flow sensor **210**, and the heating element **222** is activated to vaporize components of the aerosol precursor composition. Drawing upon the mouth end of the aerosol delivery device causes ambient air to enter the air intake **238** and pass through the cavity **234** in the coupler **232** and the central opening in the projection **236** of the base **230**. In the cartridge **104**, the drawn air combines with the formed vapor to form an aerosol. The aerosol is whisked, aspirated or otherwise drawn away

from the heating element and out the opening **226** in the mouth end of the aerosol delivery device.

[0087] For further detail regarding implementations of an aerosol delivery device including a control body and a cartridge in the case of an electronic cigarette, see the
5 above-cited U.S. Pat. App. Ser. No. 15/836,086 to Sur, and U.S. Pat. App. Ser. No. 15/916,834 to Sur et al., as well as U.S. Pat. App. Ser. No. 15/916,696 to Sur, filed March 9, 2018, which is also incorporated herein by reference.

[0088] FIGS. 3-6 illustrate implementations of an aerosol delivery device including a control body and an aerosol source member in the case of a heat-not-burn
10 device. More specifically, FIG. 3 illustrates an aerosol delivery device **300** according to an example implementation of the present disclosure. The aerosol delivery device may include a control body **302** and an aerosol source member **304**. In various implementations, the aerosol source member and the control body can be permanently or detachably aligned in a functioning relationship. In this regard, FIG. 3 illustrates
15 the aerosol delivery device in a coupled configuration, whereas FIG. 4 illustrates the aerosol delivery device in a decoupled configuration. Various mechanisms may connect the aerosol source member to the control body to result in a threaded engagement, a press-fit engagement, an interference fit, a sliding fit, a magnetic engagement, or the like.

[0089] As shown in FIG. 4, in various implementations of the present disclosure, the aerosol source member **304** may comprise a heated end **406**, which is configured to be inserted into the control body **302**, and a mouth end **408**, upon which a user draws to create the aerosol. In various implementations, at least a portion of the heated end may include an aerosol precursor composition **410**.

[0090] In various implementations, the aerosol source member **304**, or a portion thereof, may be wrapped in an exterior overwrap material **412**, which may be formed of any material useful for providing additional structure and/or support for the aerosol source member. In various implementations, the exterior overwrap material may comprise a material that resists transfer of heat, which may include a paper or other
25 fibrous material, such as a cellulose material. The exterior overwrap material may also include at least one filler material imbedded or dispersed within the fibrous material. In various implementations, the filler material may have the form of water insoluble particles. Additionally, the filler material may incorporate inorganic components. In various implementations, the exterior overwrap may be formed of
30

multiple layers, such as an underlying, bulk layer and an overlying layer, such as a typical wrapping paper in a cigarette. Such materials may include, for example, lightweight “rag fibers” such as flax, hemp, sisal, rice straw, and/or esparto. The exterior overwrap may also include a material typically used in a filter element of a conventional cigarette, such as cellulose acetate. Further, an excess length of the overwrap at the mouth end **408** of the aerosol source member may function to simply separate the aerosol precursor composition **410** from the mouth of a consumer or to provide space for positioning of a filter material, as described below, or to affect draw on the article or to affect flow characteristics of the vapor or aerosol leaving the device during draw. Further discussion relating to the configurations for overwrap materials that may be used with the present disclosure may be found in the above-cited U.S. Pat. No. 9,078,473 to Worm et al.

[0091] In various implementations other components may exist between the aerosol precursor composition **410** and the mouth end **408** of the aerosol source member **304**, wherein the mouth end may include a filter **414**, which may, for example, be made of a cellulose acetate or polypropylene material. The filter may additionally or alternatively contain strands of tobacco containing material, such as described in U.S. Pat. No. 5,025,814 to Raker et al., which is incorporated herein by reference in its entirety. In various implementations, the filter may increase the structural integrity of the mouth end of the aerosol source member, and/or provide filtering capacity, if desired, and/or provide resistance to draw. In some implementations one or any combination of the following may be positioned between the aerosol precursor composition and the mouth end: an air gap; phase change materials for cooling air; flavor releasing media; ion exchange fibers capable of selective chemical adsorption; aerogel particles as filter medium; and other suitable materials.

[0092] Various implementations of the present disclosure employ one or more conductive heating elements to heat the aerosol precursor composition **410** of the aerosol source member **304**. In various implementations, the heating element may be provided in a variety forms, such as in the form of a foil, a foam, a mesh, a hollow ball, a half ball, discs, spirals, fibers, wires, films, yarns, strips, ribbons, or cylinders. Such heating elements often comprise a metal material and are configured to produce heat as a result of the electrical resistance associated with passing an electrical current therethrough. Such resistive heating elements may be positioned in direct contact

with, or in proximity to, the aerosol source member and particularly, the aerosol precursor composition of the aerosol source member **304**. The heating element may be located in the control body and/or the aerosol source member. In various implementations, the aerosol precursor composition may include components (i.e.,
5 heat conducting constituents) that are imbedded in, or otherwise part of, the substrate portion that may serve as, or facilitate the function of, the heating assembly. Some examples of various heating members and elements are described in U.S. Pat. No. 9,078,473 to Worm et al.

[0093] Some non-limiting examples of various heating element configurations
10 include configurations in which a heating element is placed in proximity with the aerosol source member **304**. For instance, in some examples, at least a portion of a heating element may surround at least a portion of an aerosol source member. In other examples, one or more heating elements may be positioned adjacent an exterior of an aerosol source member when inserted in the control body **302**. In other
15 examples, at least a portion of a heating element may penetrate at least a portion of an aerosol source member (such as, for example, one or more prongs and/or spikes that penetrate an aerosol source member), when the aerosol source member is inserted into the control body. In some instances, the aerosol precursor composition may include a structure in contact with, or a plurality of beads or particles imbedded in, or otherwise
20 part of, the aerosol precursor composition that may serve as, or facilitate the function of the heating element.

[0094] FIG. 5 illustrates a front view of an aerosol delivery device **300** according to an example implementation of the present disclosure, and FIG. 6 illustrates a sectional view through the aerosol delivery device of FIG. 5. In particular, the control
25 body **302** of the depicted implementation may comprise a housing **516** that includes an opening **518** defined in an engaging end thereof, a flow sensor **520** (e.g., a puff sensor or pressure switch), a control component **522** (e.g., processing circuitry, etc.), a power source **524** (e.g., battery, supercapacitor), and an end cap that includes an indicator **526** (e.g., a LED). The power source may be rechargeable, and the control
30 body may include charging circuitry **528** coupled to and configured to controllably charge the power source.

[0095] In one implementation, the indicator **526** may comprise one or more LEDs, quantum dot-based LEDs or the like. The indicator can be in communication with the control component **522** and be illuminated, for example, when a user draws

on the aerosol source member **304**, when coupled to the control body **302**, as detected by the flow sensor **520**.

[0096] The control body **302** of the depicted implementation includes one or more heating assemblies **530** (individually or collectively referred to a heating assembly) configured to heat the aerosol precursor composition **410** of the aerosol source member **304**. Although the heating assembly of various implementations of the present disclosure may take a variety of forms, in the particular implementation depicted in FIGS. 5 and 6, the heating assembly comprises an outer cylinder **532** and a heating element **534**, which in this implementation comprises a plurality of heater prongs that extend from a receiving base **536** (in various configurations, the heating assembly or more specifically the heater prongs may be referred to as a heater). In the depicted implementation, the outer cylinder comprises a double-walled vacuum tube constructed of stainless steel so as to maintain heat generated by the heater prongs within the outer cylinder, and more particularly, maintain heat generated by heater prongs within the aerosol precursor composition. In various implementations, the heater prongs may be constructed of one or more conductive materials, including, but not limited to, copper, aluminum, platinum, gold, silver, iron, steel, brass, bronze, graphite, or any combination thereof.

[0097] As illustrated, the heating assembly **530** may extend proximate an engagement end of the housing **516**, and may be configured to substantially surround a portion of the heated end **406** of the aerosol source member **304** that includes the aerosol precursor composition **410**. In such a manner, the heating assembly may define a generally tubular configuration. As illustrated in FIGS. 5 and 6, the heating element **534** (e.g., plurality of heater prongs) is surrounded by the outer cylinder **532** to create a receiving chamber **538**. In such a manner, in various implementations the outer cylinder may comprise a nonconductive insulating material and/or construction including, but not limited to, an insulating polymer (e.g., plastic or cellulose), glass, rubber, ceramic, porcelain, a double-walled vacuum structure, or any combinations thereof.

[0098] In some implementations, one or more portions or components of the heating assembly **530** may be combined with, packaged with, and/or integral with (e.g., embedded within) the aerosol precursor composition **410**. For example, in some implementations the aerosol precursor composition may be formed of a material as described above and may include one or more conductive materials mixed therein. In

some of these implementations, contacts may be connected directly to the aerosol precursor composition such that, when the aerosol source member is inserted into the receiving chamber of the control body, the contacts make electrical connection with the electrical energy source. Alternatively, the contacts may be integral with the electrical energy source and may extend into the receiving chamber such that, when the aerosol source member is inserted into the receiving chamber of the control body, the contacts make electrical connection with the aerosol precursor composition. Because of the presence of the conductive material in the aerosol precursor composition, the application of power from the electrical energy source to the aerosol precursor composition allows electrical current to flow and thus produce heat from the conductive material. Thus, in some implementations the heating element may be described as being integral with the aerosol precursor composition. As a non-limiting example, graphite or other suitable, conductive material may be mixed with, embedded in, or otherwise present directly on or within the material forming the aerosol precursor composition to make the heating element integral with the medium.

[0099] As noted above, in the illustrated implementation, the outer cylinder 532 may also serve to facilitate proper positioning of the aerosol source member 304 when the aerosol source member is inserted into the housing 516. In various implementations, the outer cylinder of the heating assembly 530 may engage an internal surface of the housing to provide for alignment of the heating assembly with respect to the housing. Thereby, as a result of the fixed coupling between the heating assembly, a longitudinal axis of the heating assembly may extend substantially parallel to a longitudinal axis of the housing. In particular, the support cylinder may extend from the opening 518 of the housing to the receiving base 536 to create the receiving chamber 538.

[0100] The heated end 406 of the aerosol source member 304 is sized and shaped for insertion into the control body 302. In various implementations, the receiving chamber 538 of the control body may be characterized as being defined by a wall with an inner surface and an outer surface, the inner surface defining the interior volume of the receiving chamber. For example, in the depicted implementations, the outer cylinder 532 defines an inner surface defining the interior volume of the receiving chamber. In the illustrated implementation, an inner diameter of the outer cylinder may be slightly larger than or approximately equal to an outer diameter of a corresponding aerosol source member (e.g., to create a sliding fit) such that the outer

cylinder is configured to guide the aerosol source member into the proper position (e.g., lateral position) with respect to the control body. Thus, the largest outer diameter (or other dimension depending upon the specific cross-sectional shape of the implementations) of the aerosol source member may be sized to be less than the inner diameter (or other dimension) at the inner surface of the wall of the open end of the receiving chamber in the control body. In some implementations, the difference in the respective diameters may be sufficiently small so that the aerosol source member fits snugly into the receiving chamber, and frictional forces prevent the aerosol source member from being moved without an applied force. On the other hand, the difference may be sufficient to allow the aerosol source member to slide into or out of the receiving chamber without requiring undue force.

[0101] In the illustrated implementation, the control body **302** is configured such that when the aerosol source member **304** is inserted into the control body, the heating element **534** (e.g., heater prongs) is located in the approximate radial center of at least a portion of the aerosol precursor composition **410** of the heated end **406** of the aerosol source member. In such a manner, when used in conjunction with a solid or semi-solid aerosol precursor composition, the heater prongs may be in direct contact with the aerosol precursor composition. In other implementations, such as when used in conjunction with an extruded aerosol precursor composition that defines a tube structure, the heater prongs may be located inside of a cavity defined by an inner surface of the extruded tube structure, and would not contact the inner surface of the extruded tube structure.

[0102] During use, the consumer initiates heating of the heating assembly **530**, and in particular, the heating element **534** that is adjacent the aerosol precursor composition **410** (or a specific layer thereof). Heating of the aerosol precursor composition releases the inhalable substance within the aerosol source member **304** so as to yield the inhalable substance. When the consumer inhales on the mouth end **408** of the aerosol source member, air is drawn into the aerosol source member through an air intake **540** such as openings or apertures in the control body **302**. The combination of the drawn air and the released inhalable substance is inhaled by the consumer as the drawn materials exit the mouth end of the aerosol source member. In some implementations, to initiate heating, the consumer may manually actuate a pushbutton or similar component that causes the heating element of the heating assembly to receive electrical energy from the battery or other energy source. The

electrical energy may be supplied for a pre-determined length of time or may be manually controlled.

[0103] In some implementations, flow of electrical energy does not substantially proceed in between puffs on the device **300** (although energy flow may proceed to maintain a baseline temperature greater than ambient temperature – e.g., a temperature that facilitates rapid heating to the active heating temperature). In the depicted implementation, however, heating is initiated by the puffing action of the consumer through use of one or more sensors, such as flow sensor **520**. Once the puff is discontinued, heating will stop or be reduced. When the consumer has taken a sufficient number of puffs so as to have released a sufficient amount of the inhalable substance (e.g., an amount sufficient to equate to a typical smoking experience), the aerosol source member **304** may be removed from the control body **302** and discarded. In some implementations, further sensing elements, such as capacitive sensing elements and other sensors, may be used as discussed in U.S. Pat. App. No. 15/707,461 to Phillips et al., which is incorporated herein by reference.

[0104] In various implementations, the aerosol source member **304** may be formed of any material suitable for forming and maintaining an appropriate conformation, such as a tubular shape, and for retaining therein the aerosol precursor composition **410**. In some implementations, the aerosol source member may be formed of a single wall or, in other implementations, multiple walls, and may be formed of a material (natural or synthetic) that is heat resistant so as to retain its structural integrity – e.g., does not degrade – at least at a temperature that is the heating temperature provided by the electrical heating element, as further discussed herein. While in some implementations, a heat resistant polymer may be used, in other implementations, the aerosol source member may be formed from paper, such as a paper that is substantially straw-shaped. As further discussed herein, the aerosol source member may have one or more layers associated therewith that function to substantially prevent movement of vapor therethrough. In one example implementation, an aluminum foil layer may be laminated to one surface of the aerosol source member. Ceramic materials also may be used. In further implementations, an insulating material may be used so as not to unnecessarily move heat away from the aerosol precursor composition. Further example types of components and materials that may be used to provide the functions described above or be used as alternatives to the materials and components noted above can be those

of the types set forth in U.S. Pat. App. Pub. Nos. 2010/00186757 to Crooks et al., 2010/00186757 to Crooks et al., and 2011/0041861 to Sebastian et al., all of which are incorporated herein by reference.

[0105] In the depicted implementation, the control body **302** includes a control component **522** that controls the various functions of the aerosol delivery device **300**, including providing power to the electrical heating element **534**. For example, the control component may include processing circuitry (which may be connected to further components, as further described herein) that is connected by electrically conductive wires (not shown) to the power source **524**. In various implementations, the processing circuitry may control when and how the heating assembly **530**, and particularly the heater prongs, receives electrical energy to heat the aerosol precursor composition **410** for release of the inhalable substance for inhalation by a consumer. In some implementations, such control may be activated by a flow sensor **520** as described in greater detail above.

[0106] As seen in FIGS. 5 and 6, the heating assembly **530** of the depicted implementation comprises an outer cylinder **532** and a heating element **534** (e.g., plurality of heater prongs) that extend from a receiving base **536**. In some implementations, such as those wherein the aerosol precursor composition **410** comprises a tube structure, the heater prongs may be configured to extend into a cavity defined by the inner surface of the aerosol precursor composition. In other implementations, such as the depicted implementation wherein the aerosol precursor composition comprises a solid or semi-solid, the plurality of heater prongs are configured to penetrate into the aerosol precursor composition contained in the heated end **406** of the aerosol source member **304** when the aerosol source member is inserted into the control body **302**. In such implementations, one or more of the components of the heating assembly, including the heater prongs and/or the receiving base, may be constructed of a non-stick or stick-resistant material, for example, certain aluminum, copper, stainless steel, carbon steel, and ceramic materials. In other implementations, one or more of the components of the heating assembly, including the heater prongs and/or the receiving base, may include a non-stick coating, including, for example, a polytetrafluoroethylene (PTFE) coating, such as Teflon[®], or other coatings, such as a stick-resistant enamel coating, or a ceramic coating, such as Greblon[®], or Thermolon[™], or a ceramic coating, such as Greblon[®], or Thermolon[™].

[0107] In addition, although in the depicted implementation there are multiple heater prongs **534** that are substantially equally distributed about the receiving base **536**, it should be noted that in other implementations, any number of heater prongs may be used, including as few as one, with any other suitable spatial configuration.

5 Furthermore, in various implementations the length of the heater prongs may vary. For example, in some implementations the heater prongs may comprise small projections, while in other implementations the heater prongs may extend any portion of the length of the receiving chamber **538**, including up to about 25%, up to about 50%, up to about 75%, and up to about the full length of the receiving chamber. In

10 still other implementations, the heating assembly **530** may take on other configurations. Examples of other heater configurations that may be adapted for use in the present invention per the discussion provided above can be found in U.S. Pat. Nos. 5,060,671 to Counts et al., 5,093,894 to Deevi et al., 5,224,498 to Deevi et al., 5,228,460 to Sprinkel Jr., et al., 5,322,075 to Deevi et al., 5,353,813 to Deevi et al.,

15 5,468,936 to Deevi et al., 5,498,850 to Das, 5,659,656 to Das, 5,498,855 to Deevi et al., 5,530,225 to Hajaligol, 5,665,262 to Hajaligol, 5,573,692 to Das et al.; and 5,591,368 to Fleischhauer et al., which are incorporated herein by reference.

[0108] In various implementations, the control body **302** may include an air intake **538** (e.g., one or more openings or apertures) therein for allowing entrance of ambient

20 air into the interior of the receiving chamber **538**. In such a manner, in some implementations the receiving base **536** may also include an air intake. Thus, in some implementations when a consumer draws on the mouth end of the aerosol source member **304**, air can be drawn through the air intake of the control body and the receiving base into the receiving chamber, pass into the aerosol source member, and

25 be drawn through the aerosol precursor composition **410** of the aerosol source member for inhalation by the consumer. In some implementations, the drawn air carries the inhalable substance through the optional filter **414** and out of an opening at the mouth end **408** of the aerosol source member. With the heating element **534** positioned inside the aerosol precursor composition, the heater prongs may be

30 activated to heat the aerosol precursor composition and cause release of the inhalable substance through the aerosol source member.

[0109] As described above with reference to FIGS. 5 and 6 in particular, various implementations of the present disclosure employ a conductive heater to heat the aerosol precursor composition **410**. As also indicated above, various other

implementations employ an induction heater to heat the aerosol precursor composition. In some of these implementations, the heating assembly **530** may be configured as an induction heater that comprises a transformer with an induction transmitter and an induction receiver. In implementations in which the heating
5 assembly is configured as the induction heater, the outer cylinder **532** may be configured as the induction transmitter, and the heating element **534** (e.g., plurality of heater prongs) that extend from the receiving base **536** may be configured as the induction receiver. In various implementations, one or both of the induction transmitter and induction receiver may be located in the control body **302** and/or the
10 aerosol source member **304**.

[0110] In various implementations, the outer cylinder **532** and heating element **534** as the induction transmitter and induction receiver may be constructed of one or more conductive materials, and in further implementations the induction receiver may be constructed of a ferromagnetic material including, but not limited to, cobalt, iron,
15 nickel, and combinations thereof. In one example implementation, the foil material is constructed of a conductive material and the heater prongs are constructed of a ferromagnetic material. In various implementations, the receiving base may be constructed of a non-conductive and/or insulating material.

[0111] The outer cylinder **532** as the induction transmitter may include a laminate
20 with a foil material that surrounds a support cylinder. In some implementations, the foil material may include an electrical trace printed thereon, such as, for example, one or more electrical traces that may, in some implementations, form a helical coil pattern when the foil material is positioned around the heating element **534** as the induction receiver. The foil material and support cylinder may each define a tubular
25 configuration. The support cylinder may be configured to support the foil material such that the foil material does not move into contact with, and thereby short-circuit with, the heater prongs. In such a manner, the support cylinder may comprise a nonconductive material, which may be substantially transparent to an oscillating magnetic field produced by the foil material. In various implementations, the foil
30 material may be imbedded in, or otherwise coupled to, the support cylinder. In the illustrated implementation, the foil material is engaged with an outer surface of the support cylinder; however, in other implementations, the foil material may be positioned at an inner surface of the support cylinder or be fully imbedded in the support cylinder.

[0112] The foil material of the outer cylinder **532** may be configured to create an oscillating magnetic field (e.g., a magnetic field that varies periodically with time) when alternating current is directed through it. The heater prongs of the heating element **534** may be at least partially located or received within the outer cylinder and include a conductive material. By directing alternating current through the foil material, eddy currents may be generated in the heater prongs via induction. The eddy currents flowing through the resistance of the material defining the heater prongs may heat it by Joule heating (i.e., through the Joule effect). The heater prongs may be wirelessly heated to form an aerosol from the aerosol precursor composition **410** positioned in proximity to the heater prongs.

[0113] Other implementations of the aerosol delivery device, control body and aerosol source member are described in the above-cited U.S. Pat. App. Ser. No. 15/916,834 to Sur et al., U.S. Pat. App. Ser. No. 15/916,696 to Sur, and U.S. Pat. App. Ser. No. 15/836,086 to Sur.

[0114] As described above, the aerosol delivery device of example implementations may include circuitry in the context of either an electronic cigarette or a heat-not-burn device, or even in the case of a device that includes the functionality of both. FIGS. 7A and 7B are circuit diagrams of an aerosol delivery device **700** that may be or incorporate functionality of either or both aerosol delivery devices **100**, **300** according to various example implementations of the present disclosure. As shown, the aerosol delivery device includes a control body **702**, a heating element **704**, power source **706** and charge circuitry **708** that may correspond to or include functionality of respective ones of the control body **102**, **302**, heating element **222**, **534**, power source **212**, **524** and charge circuitry **216**, **528**. And in some examples such as those in which the aerosol delivery device **700** is or incorporates the functionality of aerosol delivery device **100**, the aerosol delivery device **700** (or more specifically its control body **702**) may include terminals **710** configured to connect the heating element to the control body.

[0115] In various implementations, the charge circuitry **708** is coupled to and configured to controllably charge the power source **706**. The power source includes one or more batteries or battery cells coupled to and configured to power a load **712** including the heating element **704** that is configured to convert electricity to heat and thereby vaporize components of the aerosol precursor composition. In some implementations, the one or more batteries or battery cells of the power source

include one or more lithium-ion, lithium iron phosphate or solid state batteries or battery cells.

[0116] As shown in FIG. 7A, in some implementations, the charge circuitry **708** includes an electrical connector **714**, a protection circuit **716** and a buck-boost charge controller **718**. The electrical connector is configured to connect the charge circuitry to a power supply **720** from which the power source **706** is chargeable, directly or indirectly such as via an appropriate power adapter. The electrical connector may be any of a number of suitable types of electrical connectors such as those described above. In some implementations, the electrical connector is a USB connector (e.g., Type A, Type B, Mini A, Mini B, Mini AB, Micro A, Micro B, Micro AB, Type C). In other implementations, the electrical connector is a non-USB connector (e.g. cylindrical connector, cigarette lighter connector, Lightning connector). In these and other implementations, the power adapter may be a USB power adapter or a non-USB power adapter. And in other examples, the charge circuitry may include an induction receiver in lieu of an electrical connector for induction-powered charging.

[0117] In some examples, the charge circuitry **708** can support batteries or battery cells with different electrochemistry such as lithium-ion or lithium iron phosphate. Also, the charge circuitry can provide a low battery quiescent current and have an instant on with no battery or deeply discharged battery. In one example, the charge circuitry may have an over voltage when the power source is removed during the charging process or the user plugs in the wrong battery or battery cell for charging. The electronics in the charge circuitry may have a microcontroller where the profile of the electrochemistry of the Lithium Ion battery can be inserted. If a consumer plugs in a wrong lithium battery, then the profile of the wrong battery may not coincide with the stored profile in the microcontroller. Thus, the battery may take a longer time or shorter time to charge depending on what battery was plugged in. Also the charging current can be fixed on a particular battery. Thus if a different battery is used, the charging time may be increased depending on the size of the battery being used. If the size of the battery is bigger, then the charging time may be longer. Also the charger circuitry can cap the over voltage to a particular value. Thus, irrespective of what battery is plugged in, the over voltage condition will not be violated.

[0118] In some implementations, the protection circuit **716** is coupled to and between the electrical connector **714** and the power source **706**. The protection circuit is configured to protect the power source from an overcurrent condition in the power

supply **720** when the electrical connector is coupled to the power supply. In some implementations, the protection circuit includes a switch (as shown in FIG. 7B) configured to interrupt the output current from the power supply to the power source when the power supply is in the overcurrent condition.

5 **[0119]** In some implementations, the buck-boost charge controller **718** is coupled to and between the power source **706** and the power supply **720**. The buck-boost charge controller is configured to regulate output voltage and output current from the power supply to the power source, selectively in one of a plurality of modes based on a condition of the power supply. In some implementations, the plurality of modes
10 includes two or more of a buck mode, a boost mode or a buck-boost mode. One example of a suitable buck-boost charge controller is the model BQ25703A from Texas Instruments. During the power up of the aerosol delivery device **700**, the buck-boost charge controller may set converter to buck, boost or buck boost mode based on a condition of the power supply. The buck-boost charge controller may automatically
15 transit among buck, boost and buck boost modes without host control.

[0120] In some implementations, a boost circuitry can be used to increase the voltage artificially to a certain value for the circuitry to work. For example, if the voltage goes down to 3.1V, with a boost chip the voltage can be boosted to 3.5 V for the rest of the circuitry to work. For a boost circuitry, the boost regulator can operate
20 from a smaller voltage such as from 2.7V to 3.5V to provide a higher nominal voltage capped at 3.5V. In a boost circuitry, there can be a feedback compensation to ensure that the voltage is always at a constant value. The buck converter may have an integrated step down switching regulator using a hysteretic (or materials showing hysteresis properties) and a step down DC-DC converter. The buck converter can
25 change the voltage of a fully charged battery from 4.1V to a constant voltage of 3.5V, which can provide better efficiency of the battery. The buck-boost circuitry may be a combination of the buck and boost described above and can perform the dual function of both buck and boost.

[0121] In some implementations, the power supply **720** includes one or more
30 lithium-ion or solid state batteries, or lithium-ion or hybrid lithium-ion capacitors, and the buck-boost charge controller **718** is configured to regulate the output voltage and output current from the one or more lithium-ion or solid state batteries, or lithium-ion or hybrid lithium-ion capacitors of the power supply. In some implementations, the buck-boost charge controller is configured to limit the output current to a maximum

current (e.g., 380mA) when a terminal voltage of the power source **706** falls below a threshold voltage when the power source is charged from the power supply.

[0122] FIG. 7B illustrates a circuit diagram of the aerosol delivery device **700** according to various example implementations of the present disclosure. As shown, the aerosol delivery device includes a control body **702**, a heating element **704**, power source **706** and charge circuitry **708**. The charge circuitry is coupled to and configured to controllably charge the power source. Similarly as in FIG. 7A, the charge circuitry includes an electrical connector **714**, a protection circuit **716** and a buck-boost charge controller **718**. The charge circuitry may also include an I/O interface **738** (e.g., an inter-integrated circuit interface) coupled to the buck-boost charge controller. The I/O interface may give the flexibility for the user to change the charging current or limit the charging current to a certain value depending on the battery or capacitor being charged. For example, for a particular lithium ion battery, a supercapacitor or a lithium ion hybrid capacitor being charged, the charging current may be 1C, 2C or 5C charge rate. The I/O interface can limit the charging current to a particular value depending on the maximum rating on the battery, supercapacitor or hybrid lithium ion capacitor. Thus the electronic design may be robust enough to support a variety of lithium ion battery, supercapacitor, hybrid lithium ion capacitor or solid state battery. In one example, a user can set specific values or select type of power source via the I/O interface. In another example, the charge circuitry can select appropriate values from pre-stored correlation between type and value(s), e.g., from a lookup table.

[0123] In some implementations, the protection circuit **716** includes one or more transistors **722**, **724**, **726** and **728** used as one or more switches configured to interrupt the output current from the power supply **720** to the power source **706** when the power supply is in the overcurrent condition. The transistors may be metal-oxide-semiconductor field-effect transistors (MOSFETs). One example of a suitable MOSFET includes the model 2N6659 from Motorola.

[0124] In some implementations, the power source **706** includes a plurality of batteries or battery cells **730**, **732**, **734** and **736**. The plurality of batteries or battery cells are connected to form two or more paths for the output current from the power supply **720** to flow through such that the output current is a sum of currents through each path of the plurality of paths. In one example, the output current from power supply can be 6.35A. In this example, the four batteries as shown in FIG. 7B may be

connected to form two paths for the output current, with a pair of the batteries on each path. The 6.35A may be split between the two paths with each pair of batteries being supplied 3.175A for fast charging. In this way, the four batteries can be charged faster. In another example, the four batteries may be connected to form four paths for the output current, with one of the four batteries on each path.

5 [0125] In some implementations, the aerosol delivery device **700** or the control body **702** further includes a non-inverting unity gain operational amplifier **740** coupled to the heating element **704** and configured to output a constant power to the load **712** or the heating element. The output power to the load or the heating element
10 can be constant irrespective of any parasitics in the circuit board (e.g., printed circuit board) due to traces or other reasons. Also the non-inverting unity gain operational amplifier can nullify the antenna effect of any discrete components in the aerosol delivery device.

[0126] Many modifications and other implementations of the disclosure will come
15 to mind to one skilled in the art to which this disclosure pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the disclosure is not to be limited to the specific implementations disclosed herein and that modifications and other implementations are intended to be included within the scope of the appended claims. Although
20 specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

WHAT IS CLAIMED IS:

1. An aerosol delivery device comprising:
 - a housing structured to retain an aerosol precursor composition;
 - 5 a heating element configured to convert electricity to heat and thereby vaporize components of the aerosol precursor composition;
 - a power source including one or more batteries or battery cells coupled to and configured to power a load including the heating element; and
 - charge circuitry coupled to and configured to controllably charge the power
 - 10 source, the charge circuitry including:
 - an electrical connector configured to connect the charge circuitry to a power supply from which the power source is chargeable; and
 - a buck-boost charge controller coupled to and between the power
 - source and power supply, and configured to regulate output voltage and output
 - 15 current from the power supply to the power source, selectively in one of a plurality of modes based on a condition of the power supply.
2. The aerosol delivery device of claim 1, wherein the power source includes a plurality of batteries or battery cells.
- 20 3. The aerosol delivery device of claim 2, wherein the plurality of batteries or battery cells are connected to form a plurality of paths for the output current from the power supply to flow through such that the output current is a sum of currents through each path of the plurality of paths.
- 25 4. The aerosol delivery device of claim 1, wherein the one or more batteries or battery cells include one or more lithium-ion, lithium iron phosphate or solid-state batteries or battery cells.
- 30 5. The aerosol delivery device of claim 1, wherein the power supply includes one or more lithium-ion or solid-state batteries, or lithium-ion or hybrid lithium-ion capacitors, and the buck-boost charge controller being configured to regulate the output voltage and output current from the power supply includes being

configured to regulate the output voltage and output current from the one or more lithium-ion or solid-state batteries, or lithium-ion or hybrid lithium-ion capacitors.

6. The aerosol delivery device of claim 1, wherein the charge circuitry
5 further includes a protection circuit coupled to and between the electrical connector and the power source, and configured to protect the power source from an overcurrent condition in the power supply when the electrical connector is coupled to the power supply.

10 7. The aerosol delivery device of claim 6, wherein the protection circuit includes a switch configured to interrupt the output current from the power supply to the power source when the power supply is in the overcurrent condition.

8. The aerosol delivery device of claim 1, wherein the buck-boost charge
15 controller being configured to regulate the output voltage and output current includes being configured to limit the output current to a maximum current when a terminal voltage of the power source falls below a threshold voltage when the power source is charged from the power supply.

20 9. The aerosol delivery device of claim 1, wherein the aerosol precursor composition is a liquid, or a solid or semi-solid.

10. The aerosol delivery device of claim 1, further comprising a non-
inverting unity gain operational amplifier coupled to the heating element and
25 configured to output a constant power to the heating element.

11. The aerosol delivery device of claim 1, wherein the plurality of modes includes two or more of a buck mode, a boost mode or a buck-boost mode.

30 12. A control body for an aerosol delivery device, the control body comprising:

a heating element or terminals configured to connect the heating element to the control body, the heating element being configured to convert electricity to heat and thereby vaporize components of an aerosol precursor composition;

a power source including one or more batteries or battery cells coupled to and configured to power a load including the heating element; and

charge circuitry coupled to and configured to controllably charge the power source, the charge circuitry including:

- 5 an electrical connector configured to connect the charge circuitry to a power supply from which the power source is chargeable; and
- a buck-boost charge controller coupled to and between the power source and power supply, and configured to regulate output voltage and output current from the power supply to the power source, selectively in one of a
- 10 plurality of modes based on a condition of the power supply.

13. The control body of claim 12, wherein the power source includes a plurality of batteries or battery cells.

- 15 14. The control body of claim 13, wherein the plurality of batteries or battery cells are connected to form a plurality of paths for the output current from the power supply to flow through such that the output current is a sum of currents through each path of the plurality of paths.

- 20 15. The control body of claim 12, wherein the one or more batteries or battery cells include one or more lithium-ion, lithium iron phosphate or solid-state batteries or battery cells.

16. The control body of claim 12, wherein the power supply includes one
- 25 or more lithium-ion or solid-state batteries, or lithium-ion or hybrid lithium-ion capacitors, and the buck-boost charge controller being configured to regulate the output voltage and output current from the power supply includes being configured to regulate the output voltage and output current from the one or more lithium-ion or solid-state batteries, or lithium-ion or hybrid lithium-ion capacitors.

30

17. The control body of claim 12, wherein the charge circuitry further includes a protection circuit coupled to and between the electrical connector and the power source, and configured to protect the power source from an overcurrent

condition in the power supply when the electrical connector is coupled to the power supply.

18. The control body of claim 17, wherein the protection circuit includes a
5 switch configured to interrupt the output current from the power supply to the power source when the power supply is in the overcurrent condition.

19. The control body of claim 12, wherein the buck-boost charge
controller being configured to regulate the output voltage and output current includes
10 being configured to limit the output current to a maximum current when a terminal voltage of the power source falls below a threshold voltage when the power source is charged from the power supply.

20. The control body of claim 12, wherein the aerosol precursor
15 composition is a liquid, or a solid or semi-solid.

21. The control body of claim 12, further comprising a non-inverting unity
gain operational amplifier coupled to the heating element and configured to output a
constant power to the heating element.

20

22. The control body of claim 12, wherein the plurality of modes includes
two or more of a buck mode, a boost mode or a buck-boost mode.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7A



736*




FIG. 7A