

2-2607 PCT

Australia

Patents Act 1990

NOTICE OF ENTITLEMENT

I, Lorraine J. Francis, Assistant Secretary, of The Mead Corporation, Courthouse Plaza, Northeast, Dayton, Ohio 45463 United States of America being authorised by the Applicant(s)/Nominated Person(s) in respect of an application entitled:

PANEL INTERLOCKING MEANS

state the following:-

1. The Applicant(s)/Nominated Person(s) has/have, for the following reasons, gained entitlement from the actual inventor(s):-

The Applicant(s)/Nominated Person(s) is/are the assignee(s) of the actual inventor(s)

2a.* The Applicant(s)/Nominated Person(s) is/are the applicant(s) of the of the basic application(s) listed* on the Patent Request/ *in the Declaration under Article 8 of the PCT as follows:

2b.* The Applicant(s)/Nominated Person(s) is/are entitled to rely on the basic application(s) listed* on the Patent Request/ *in the Declaration under Article 8 of the PCT as follows:

The Applicant(s)/Nominated Person(s) is/are the assignee(s) of the basic applicant(s)

3.* The basic application(s) listed *on the Patent Request/ *in the Declaration under Article 8 of the PCT is/are the application(s) first made in a Convention Country in respect of the invention.

x4a.* The Applicant(s)/Nominated Person(s) is/are the depositor(s) of the deposit(s) listed in the Schedule hereto

x4b.* The Applicant(s)/Nominated Person(s) has/have the consent of

xxxxxx of the deposit(s) listed in the Schedule hereto, to rely on that/those deposit(s).

DATED this 29th day of June 19 93

Lorraine J. Francis (Signature)

Lorraine J. Francis, Assistant Secretary (Name & Title)

* Delete if not applicable.



AU9227965

(12) PATENT ABRIDGMENT (11) Document No. AU-B-27965/92
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 655851

- (54) Title
PANEL INTERLOCKING MEANS
- International Patent Classification(s)
(51)⁵ **B65D 005/42 B65D 005/02 B65D 065/22 B65D 071/12**
- (21) Application No. : **27965/92** (22) Application Date : **15.10.92**
- (87) PCT Publication Number : **WO93/08085**
- (30) Priority Data
- (31) Number (32) Date (33) Country
775750 15.10.91 US UNITED STATES OF AMERICA
- (43) Publication Date : **21.05.93**
- (44) Publication Date of Accepted Application : **12.01.95**
- (71) Applicant(s)
THE MEAD CORPORATION
- (72) Inventor(s)
JAMES R. OLIFF
- (74) Attorney or Agent
SPRUSON & FERGUSON , GPO Box 3898, SYDNEY NSW 2001
- (56) Prior Art Documents
US 5000313
US 4440340
US 4077095
- (57) Claim

1. An arrangement for interlocking a pair of panels in overlapping face contacting relation, said arrangement comprising:

side by side dual locking tabs each having a base and spaced sides with adjacent shoulders projecting laterally from its sides and disposed in abutting relation to each other and being struck from one of said panels and each being foldably joined at its base to said one panel; and

side by side spaced apart dual retaining tabs struck from the other of said panels and defining locking apertures having side edges of predetermined fixed length and which are formed in said other of said panels, each retaining tab having a base and side and end edges and being foldably joined at its base to said other of said panels and being disposed in abutting relation with one of said locking tabs so as to secure said one locking tab in angular relation to said panels and to aid in holding said panels in face contacting relation following movement of each of said locking tabs through the associated locking aperture.

OPI DATE 21/05/93 APPLN. ID 27965/92
AOJP DATE 22/07/93 PCT NUMBER PCT/US92/08795




AU9227965

PCT

<p>(51) International Patent Classification ⁵ : B65D 5/42</p>	<p>A1</p>	<p>(11) International Publication Number: WO 93/08085 (43) International Publication Date: 29 April 1993 (29.04.93)</p>
<p>(21) International Application Number: PCT/US92/08795 (22) International Filing Date: 15 October 1992 (15.10.92) (30) Priority data: 775,750 15 October 1991 (15.10.91) US (71) Applicant: THE MEAD CORPORATION [US/US]; Courthouse Plaza, Northeast, Dayton, OH 45463 (US). (72) Inventor: OLIFF, James, R. ; 6838 Cherry Log Place, Austell, GA 30001 (US). (74) Agents: DOERR, Erwin; The Mead Corporation, 4850D North Church Lane, Smyrna, GA 30080 (US) et al.</p>		<p>(81) Designated States: AU, BR, CA, CS, HU, JP, KR, PL, RU, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE). Published <i>With international search report.</i> <i>With amended claims.</i></p> <p style="font-size: 2em; text-align: center;">655851</p>

(54) Title: PANEL INTERLOCKING MEANS



(57) Abstract

For interlocking a pair of panels (28, 30) in overlapping face contacting relation, dual side by side locking tabs (37a, b, 38a, 38b) are struck from one panel and are arranged to be driven through side by side dual retaining apertures (33a, b, 34a, b) separated from each other by a reinforcing strut (5) which is integrally connected at its end with the other panel, the reinforcing strut (5) being arranged to occupy the space between the dual retaining apertures.

PANEL INTERLOCKING MEANS

TECHNICAL FIELD

This invention relates to securing the overlapping ends of a tubular wrapper in which a plurality of articles are packaged.

BACKGROUND ART

U. S. patent 4,077,095 issued May 1, 1978 and owned by the assignee of this invention discloses and claims panel interlocking means in which a shouldered locking tab struck from one panel is driven through an aperture in another panel defined by a retaining tab together with a securing aperture formed in the base of the locking tab which receives a securing tab projecting from an edge of the locking aperture.

New Zealand patent 191,646 owned by the assignee of this invention discloses locking tabs and retaining tabs wherein a single locking tab struck from one panel is driven through an aperture defined by a pair of retaining tabs struck from another panel and normally disposed in abutting relationship to each other.

U. S. patent 5,000,313 issued March 19, 1991 and owned by the assignee of this invention discloses a tubular wrapper having overlapping face contacting panels for packaging a plurality of specially shaped cans and in which the wrapper is especially adapted to accommodate cans having inwardly recessed ends.

SUMMARY OF THE INVENTION

There is disclosed herein an arrangement for interlocking a pair of panels in overlapping face contacting relation, said arrangement comprising:

5 side by side dual locking tabs each having a base and spaced sides with adjacent shoulders projecting laterally from its sides and disposed in abutting relation to each other and being struck from one of said panels and each being foldably joined at its base to said one panel; and

10 side by side spaced apart dual retaining tabs struck from the other of said panels and defining locking apertures having side edges of predetermined fixed length and which are formed in said other of said panels, each retaining tab having a base and side and end edges and being foldably joined at its base to said other of said panels and being disposed in abutting relation with one of said locking tabs so as to secure said one locking tab in angular relation to said panels and to aid in holding said panels in face contacting relation following movement of each of said locking tabs through the
15 associated locking aperture.

BRIEF DESCRIPTION OF THE DRAWINGS

A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings, wherein:

FIG. 1 is a plan view of a carton blank as viewed from the inside;

20 FIG. 1a is an enlarged view of one feature shown on FIG. 1;

FIGS. 2, 3, 4 and 5 depict locking and retaining tabs formed according to a preferred embodiment of the invention and which show the structure in progressive stages of the formation of an interlocked relationship between a pair of overlapping panels; and

25 FIG. 6 is a view of a set up carton formed from the blank of FIG. 1 but which shows the carton in an inverted position so as to indicate the disposition of the locking elements formed according to this embodiment.



-3-

BEST MODE OF CARRYING OUT THE INVENTION

With reference primarily to FIG. 1, the numeral 1 designates the carton top wall. A pair of finger receiving apertures 2 and 3 are formed in top wall 1 and are normally closed by tabs 4 and 5 which are foldably joined to top wall 1 along fold lines 6 and 7 respectively. A pair of relief scores 6a and 6b are formed in association with the finger receiving aperture 2 and which diverge generally toward the top wall corner and similar relief scores 7a and 7b are also provided. A pair of continuous uninterrupted bevel strips 8 and 9 are foldably joined to top wall 1 along fold lines 10 and 11 respectively. Fold lines 10 and 11 are provided with divergent extensions which are angularly disposed relative to such fold lines and are identified by the references 10a and 11a. Side walls 12 and 13 are foldably joined to bevel strips 8 and 9 along fold lines 14 and 15 respectively. Anchoring panels 16 and 17 are foldably joined to end edges of side wall 12 along fold lines 18 and 19 respectively while anchoring panels 20 and 21 are foldably joined to the end edges of side wall 13 along fold lines 22 and 23 respectively.

Bevel strip 24 is foldably joined to the bottom edge of side wall 12 along a fold line 25 and bevel strip 26 is foldably joined to the bottom edge of side wall 13 along a fold line 27.

Preferably bevel strips 8 and 9 are slightly wider than bevel strips 24 and 26.

-4-

Bottom lap panel 28 is foldably joined to the bottom edge of bevel strip 24 along fold line 29 and bottom lap panel 30 is foldably joined to the bottom edge of bevel strip 26 along fold line 31.

For securing the packaged cans in a composite package group within the carton, the carton blank is placed above a package group and the anchoring panels 16, 17, 20 and 21 are folded inwardly into flat face contacting relation with the adjacent inner surface of side walls 12 and 13 as is obvious. Web structures generally indicated at 50 and 51, 52 and 53 are disposed astride the upper corners of the carton and prevent dislodgement of cans through the ends of the carton as the known folding applications are performed. In like fashion, web structures 54, 55, 56 and 57 are disposed astride the bottom corners of the carton and aid in securing the cans against dislodgement through the ends of the wrapper.

For securing the lap panels 28 and 30 together in overlapping relation, a plurality of dual retaining tabs 33a, 33b, 34a, 34b and single retaining tabs 32 and 35 are struck from lap panel 28 to define apertures for respectively receiving dual locking tabs 37a, 37b, 38a, 38b and single locking tabs 36 and 39 which are struck from lap panel 30. These locking tabs are driven through the openings defined in the retaining tabs after the blank is securely tightened about a group of packaged cans by means of machine elements which enter tightening apertures 40, 41 and 42 formed in lap panel

SUBSTITUTE SHEET

-5-

28 and by similar machine tightening elements which enter apertures 43, 44 and 45 formed in lap panel 30 and which are drawn inwardly in opposition to each other to tighten the blank about a package group before locking of the lap panels 28 and 30 together in flat face contacting relation to form a composite bottom wall of the carton in a manner well known in the art.

Each web structure comprises a pair of web panels such as 60, 61 and 60a, 61a which are foldably joined together by divergent extensions 10a and 11a respectively which diverge inwardly by an angle which corresponds generally with the angle of taper of the inwardly inclined upper portions of the side wall. One web panel 60 is foldably joined to an end of anchoring panel 16 along fold line 62 and another web panel 60a is foldably joined to anchoring panel 20 along fold line 62a. Web panel 61 is foldably joined to top wall 1 along fold line 63 which is disposed tangentially to the top of the can. Web panel 61a is foldably joined to top wall 1 along fold line 63a. Fold lines 62 and 63 and fold lines 62a and 63a are preferably disposed at an angle of 120 degrees to each other. A cutaway area designated by the numeral 64 serves to isolate the web panel 60 from the bevel strip 8 and cutaway area 64a isolates the web panel 60a from bevel strip 9. Web structure according to that described in conjunction with web structures 50 and 51 also forms web structures 52-57 as is obvious.

Fold lines 29a and 31a correspond to fold lines 10a and 11a respectively and folds 29b and 31b correspond to fold lines 62 and 62a.

When the wrapper of FIG. 1 is disposed about a can group, the web structures such as 50, 51, 54 and 56 are disposed astride the carton corners and securely grip the packaged cans and prevent dislodgement of the cans through the adjacent end of the carton. Similar web structures 52, 53, 55 and 57 secure the opposite end of the carton.

According to this invention, the security of the interlocking arrangement between face contacting overlapping panels is greatly enhanced due to the cooperation of dual locking elements such as 37a, 37b and 38a and 38b which are driven through spaced apart dual retaining apertures defined by dual retaining tabs 33a, 33b and 34a and 34b separated by reinforcing struts S.

FIG. 2 shows panels 28 and 30 and securing tab ST2 prior to the start of a locking operation. The securing tabs ST1 and ST2 allow lock clearing engagement of the locks and are disposed in contact with the adjacent end of the reinforcing strut S. FIG. 3 shows the panels 28 and 30 from the inside of the carton after they are interlocked. FIG. 4 shows the structure enlarged and like FIG. 5 shows retaining tab 34b propped against locking tab 38b. FIG. 4 shows

reinforcing strut S and shows retaining tab 34b folded out of panel 28 along a fold line 34c which is formed by the difference in length of the sides of reinforcing tab 34b. Also the angle A such as is shown in FIG. 1a is an acute angle and causes the retaining tab 34b and other such tabs to reside at an angle to the reinforcing strut S and to panel 28. The shoulders of locking tabs such as 37a and 37b are disposed in abutting relation.

One advantage of this structure is that it improves the tensile strength of the locked panels by some substantial amount as indicated by tests performed in developing this structure. Another advantage of this invention is that the machine for driving the dual locking tabs into the dual spaced apart locking apertures is easy to provide since a single rotary wheel may be provided with two locking plungers P at each locking position by simple procedures utilizing well established known locking machine elements. Another advantage achieved by this invention is the fact that the locking tabs are constructed in such a way that they penetrate the locking apertures more easily due to the angular disposition of the retaining tabs which are adjoined to their associated panel by fold lines which diverge at an acute angle to the reinforcing strut which is disposed between the dual locking apertures.

The claims defining the invention are as follows:

1. An arrangement for interlocking a pair of panels in overlapping face contacting relation, said arrangement comprising:

5 side by side dual locking tabs each having a base and spaced sides with adjacent shoulders projecting laterally from its sides and disposed in abutting relation to each other and being struck from one of said panels and each being foldably joined at its base to said one panel; and

10 side by side spaced apart dual retaining tabs struck from the other of said panels and defining locking apertures having side edges of predetermined fixed length and which are formed in said other of said panels, each retaining tab having a base and side and end edges and being foldably joined at its base to said other of said panels and being disposed in abutting relation with one of said locking tabs so as to secure said one locking tab in angular relation to said panels and to aid in holding said panels in face contacting relation following movement of each of said locking tabs through the
15 associated locking aperture.

2. An arrangement according to claim 1 wherein a reinforcing strut having parallel side edges and having ends which are integral with the other of said panels is interposed between said retaining tabs and integrally connected at its ends with said other of said panels.

20 3. An arrangement according to claim 2 wherein a securing tab is formed integrally with said one panel and interposed between base portions of said dual locking tabs.

4. An arrangement according to claim 3 wherein said securing tab is disposed in overlying relation with said reinforcing strut.

25 5. An arrangement according to any one of claims 2 to 4 wherein adjacent side edges of said dual retaining tabs define opposite side edges of said reinforcing strut.

30 6. An arrangement according to any one of claims 2 to 5 wherein said dual retaining tabs include side edges which are opposite from said parallel side edges of said reinforcing strut and are shorter than said side edges of said reinforcing strut.

7. An arrangement according to any one of claims 2 to 6 wherein each of said dual retaining tabs folds inwardly along a fold line disposed at an acute angle to a side edge of said reinforcing strut when the corresponding dual locking tabs are driven inwardly.

35 8. An arrangement according to any one of claims 2 to 7 wherein the end edge of each of said retaining tabs is disposed in abutting relation with the associated locking tab.

9. An arrangement according to claim 3 wherein said securing tab is struck from adjacent portions of said locking tabs.



10. An arrangement according to claim 9 wherein said reinforcing strut includes an inner surface and wherein adjacent shoulders of said locking tabs overlie the inner surface of said reinforcing strut.

11. An arrangement for interlocking a pair of panels in overlapping face
5 contacting relation, said arrangement being substantially as hereinbefore described with reference to the accompanying drawings.

DATED this Twenty-first Day of October 1994

The Mead Corporation

Patent Attorneys for the Applicant

SPRUSON & FERGUSON

10

SECRET






Fig. 6




Fig. 5




Fig. 4




Fig. 3




Fig. 2

SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/US92/08795

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) : B65D 5/42
US CL : 229/298.12; 206/427

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. :

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 3,410,397 (Cato) 12 November 1968, entire document.	1,2,6
A	US, A, 4,394,903 (Bakx) 26 July 1983.	1,2,6
A	US, A, 4,077,095 (Oliff) 07 March 1978.	1,2,6
A	US, A, 5,000,313 (Oliff) 19 March 1991.	1,2,6
A	US, A, 4,440,340 (Bakx) 03 April 1984.	1,2,6
A	US, A, 3,224,630 (Sperry) 21 December 1965.	1,2,6
A	US, A, 2,872,036 (Forer) 03 February 1959.	1,2,6

Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be part of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z*	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search 24 NOVEMBER 1992	Date of mailing of the international search report 08 JAN 1993
Name and mailing address of the ISA/W Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. NOT APPLICABLE	Authorized officer <i>Joseph Moy</i> JOSEPH MOY INTERNATIONAL DIVISION Telephone No. (703) 308-0608