



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C11D 3/37, 3/00	A1	(11) International Publication Number: WO 99/67352 (43) International Publication Date: 29 December 1999 (29.12.99)
(21) International Application Number: PCT/EP99/04057 (22) International Filing Date: 12 June 1999 (12.06.99) (30) Priority Data: 09/102,556 23 June 1998 (23.06.98) US (71) Applicant (for all designated States except US): BASF AKTIENGESELLSCHAFT [DE/DE]; D-67056 Ludwigshafen (DE). (72) Inventors; and (75) Inventors/Applicants (for US only): BOECKH, Dieter [DE/DE]; Zeppelinstrasse 3, D-67117 Limburgerhof (DE). EHLE, Michael [DE/DE]; Pater-Baroffio-Weg 43, D-67071 Ludwigshafen (DE). ROSER, Angelika [DE/DE]; Richard-Wagner-Strasse 55, D-68165 Mannheim (DE). MOHR, Jürgen [DE/DE]; Hochgewanne 48, D-67269 Grünstadt (DE). CLEARY, James, Albert [US/US]; 3945 Dust Commander Drive, Indian Springs, OH 45011 (US). ZHANG, Shulin [US/US]; 7585 Lakota Springs Drive, West Chester, OH 45069 (US). GOSSELINK, Eugene, Paul [US/US]; 3754 Susanna Drive, Cincinnati, OH 45251 (US). (74) Common Representative: BASF AKTIENGESELLSCHAFT; D-67056 Ludwigshafen (DE).		(81) Designated States: AL, AU, BG, BR, BY, CA, CN, CZ, GE, HU, ID, IL, IN, JP, KR, KZ, LT, LV, MK, MX, NO, NZ, PL, RO, RU, SG, SI, SK, TR, UA, US, ZA, Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: ALKOXYLATED POLYALKYLENEIMINE DISPERSANTS		
$[\text{E}_2\text{N}\cdot\text{R}]_w [\text{N}\cdot\text{R}]_x [\text{N}\cdot\text{R}]_y \text{NE}_2 \quad (I)$		
(57) Abstract The present invention relates to an alkoxyated polyalkyleneimine soil dispersant having formula (I), wherein R is C ₂ -C ₆ linear alkylene, C ₃ -C ₆ branched alkylene, and mixtures thereof; B is a continuation by branching; E is an alkyleneoxy unit having the formula: -(R ¹ O) _m (R ² O) _n R ³ , wherein R ¹ is 1,2-propylene, 1,2-butylene, and mixtures thereof; R ² is ethylene; R ³ is hydrogen, C ₁ -C ₄ alkyl, and mixtures thereof; m is from about 1 to about 10; n is from about 10 to about 40; w, x and y are each independently from about 4 to about 200; provided at least one -(R ¹ O) unit is attached to the backbone prior to attachment of an -(R ² O) unit and further provided m + n is at least 12.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ALKOXYLATED POLYALKYLENEIMINE DISPERSANTS

FIELD OF THE INVENTION

5

The present invention relates to alkoxyated polyalkyleneimine hydrophobic soil dispersants which are suitable for use as soil dispersant in applications.

10 BACKGROUND OF THE INVENTION

Absent a suitable dispersant, hydrophobic (e.g. grime, oil, soot) and hydrophilic (e.g. clay) soil which is removed during the washing step of the laundry process can re-deposit onto the
15 cleaned fabric. Soil dispersants act by sequestering dirt once it is dissolved or dispersed in the laundry liquor and keeps the suspended soil in the laundry liquor where it can be carried away during the normal rinsing process.

20 Typically, if bleaching agents are present, especially peroxygen bleaches which are formulated into both liquid and granular laundry detergent compositions, the formulator must consider the instability of a particular soil dispersant toward bleach. Many successful dispersants have polyalkyleneamine or polyalkyleneimine
25 backbones which are susceptible to oxidation at the amine functionalities and potentially to breakdown or fragmentation by bleaching agents which may be present. From another view, the interaction of bleaching agents with these polyalkyleneimine-based dispersants depletes the amount of bleach present therefore
30 affecting the bleaching performance.


Accordingly, there remains a need in the art for bleach compatible, highly effective hydrophobic soil dispersants. Surprisingly, it has been found that certain higher molecular
35 weight polyalkyleneimines which comprise a mixture of alkyleneoxy units which are appended to a polyalkyleneimine backbone in a particular order provide hydrophobic dispersants having enhanced bleach compatibility as well as enhanced dispersancy.

40 SUMMARY OF THE INVENTION

The present invention meets the aforementioned needs in that it has been surprisingly discovered that polyalkyleneimines having a backbone molecular weight of from about 600 daltons to about
45 25000 daltons wherein the backbone nitrogens have been substituted by an average degree of mixed alkyleneoxylation per N-H unit of from 12 to about 50 alkyleneoxy units provides an

enhanced hydrophobic soil dispersant which is compatible with bleach. The polyamine backbone is first modified by placement of from 1 to 10 propyleneoxy units, butyleneoxy units, and mixtures thereof followed by ethyleneoxy units such that the total degree
 5 of alkyleneoxylation does not exceed about 50 units. The alkoxy-
 lated polyalkyleneimines of the present invention are suitable for use in high and low density granular, heavy duty and light duty liquids, as well as laundry bar detergent compositions.


10 The present invention relates to a soil dispersant having the formula:



15

wherein R is C₂-C₆ linear alkylene, C₃-C₆ branched alkylene, and mixtures thereof; B is a continuation by branching; E is an alkyleneoxy unit having the formula:

20



wherein R¹ is 1,2-propylene, 1,2-butylene, and mixtures thereof; R² is ethylene; R³ is hydrogen, C₁-C₄ alkyl, and mixtures thereof;
 25 m is from about 1 to about 10; n is from about 10 to about 40; w, x and y are each independently from about 4 to about 200; provided at least one -(R¹O) unit is attached to the backbone prior to attachment of an -(R²O) unit and further provided m + n is at least 12.


30

These and other objects, features, and advantages will become apparent to those of ordinary skill in the art from a reading of the following detailed description and the appended claims.

35 All percentages, ratios and proportions herein are by weight, unless otherwise specified. All temperatures are in degrees Celsius (°C) unless otherwise specified. All documents cited are in relevant part, incorporated herein by reference.

40 DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to polyalkyleneimine dispersants which are polyalkyleneoxy substituted wherein propyleneoxy units, butyleneoxy units, and mixtures thereof are attached to the back-
 45 bone nitrogens prior to subsequent attachment of polyethyleneoxy units. The polyamine backbones of the present invention have the general formula:




5 said backbones prior to subsequent modification, comprise primary, secondary and tertiary amine nitrogens connected by R "linking" units. The backbones are comprised of essentially three types of units, which may be randomly distributed along the
10 chain.

The units which make up the polyalkyleneimine backbones are primary units having the formula:



which terminate the main backbone and any branching chains, secondary amine units having the formula:
20




25 and which, after modification, have their hydrogen atom substituted by from 1 to 10 propyleneoxy units, butyleneoxy units, and mixtures thereof followed by from 10 to 40 ethyleneoxy units, and tertiary amine units having the formula:



35 which are the branching points of the main and secondary backbone chains, B representing a continuation of the chain structure by branching. The tertiary units have no replaceable hydrogen atom and are therefore not modified by substitution with an alkyleneoxy unit. During the formation of the polyamine backbones
40 cyclization may occur, therefore, an amount of cyclic polyamine can be present in the parent polyalkyleneimine backbone mixture. Each primary and secondary amine unit of the cyclic alkyleneimines undergoes modification by the addition of alkyleneoxy units
45 in the same manner as linear and branched polyalkyleneimines.

R is C₂-C₆ linear alkylene, C₃-C₆ branched alkylene, and mixtures thereof, preferred branched alkylene is 1,2-propylene, preferred R is ethylene. The preferred polyalkyleneimines of the present invention have backbones which comprise the same R unit, for example, all units are ethylene. Most preferred backbone comprises R groups which are all ethylene units.

The polyalkyleneimines of the present invention are modified by substitution of each N-H unit hydrogen with an alkyleneoxy unit having the formula:



Wherein R¹ is 1,2-propylene, 1,2-butylene, and mixtures thereof, preferably 1,2-propylene. R² is ethylene. R³ is hydrogen, C₁-C₄ alkyl, and mixtures thereof, preferably hydrogen or methyl, more preferably hydrogen. For the purposes of the present invention, at least one propyleneoxy or butyleneoxy unit must be attached to the backbone nitrogen units prior to substitution with any other alkyleneoxy unit. The value of the index m is from about 1, preferably from about 2 to about 10, preferably to about 6, more preferably to about 5. The value of the index n is from about 10, preferably from about 15, more preferably from about 20 to about 40, preferably to about 35, more preferably to about 30. The value of m + n is preferably at least 12, more preferably from about 15, most preferably from about 20 to about 40, more preferably to about 35. An example of a preferred polyalkyleneoxy substituent comprises three 1,2-propyleneoxy units prior to subsequent ethoxylation, especially when the average value of m + n is about 30.


The preferred molecular weight for the polyamine backbones is from about 600 daltons, preferably from about 1200 daltons, more preferably from about 1800 daltons, most preferably from about 2000 daltons to about 25000 daltons, preferably to about 20000 daltons, more preferably to about 15000 daltons, most preferably 5000 daltons. An example of a preferred molecular weight for a polyethyleneimine backbone is 3000 daltons. The indices x and y needed to achieve the preferred molecular weights will vary depending upon the R moiety which comprises the backbone. For example, when R is ethylene a backbone unit averages about 43 gm and when R is hexylene a backbone unit averages about 99 gm.

The polyamines of the present invention can be prepared, for example, by polymerizing ethyleneimine in the presence of a catalyst such as carbon dioxide, sodium bisulfite, sulfuric acid,

hydrogen peroxide, hydrochloric acid, acetic acid, etc. Specific methods for preparing these polyamine backbones are disclosed in U.S. Patent 2,182,306, Ulrich et al., issued December 5, 1939; U.S. Patent 3,033,746, Mayle et al., issued May 8, 1962; U.S. Patent 2,208,095, Esselmann et al., issued July 16, 1940; U.S. Patent 2,806,839, Crowther, issued September 17, 1957; and U.S. Patent 2,553,696, Wilson, issued May 21, 1951; all herein incorporated by reference.

10 The following is an example of a preferred embodiment of the present invention, wherein in formula I R means $-\text{CH}_2-\text{CH}_2-$, the polyethyleneimine thus represented has an average backbone molecular weight of about 3000,

15 E represents $-(\text{R}^1\text{O})_m(\text{R}^2\text{O})_n \text{R}^3$ wherein R^1 is a 1,2-propylene unit having the formula:



R^2 is ethylene, R^3 is hydrogen and $m + n$ is equal to about 30.

25 The modification of the N-H units in the polymer with propylene oxide, butylene oxide and ethylene oxide units is carried out by first reacting the polymer, preferably polyethyleneimine, with propylene oxide, butylene oxide and mixtures thereof and then adding ethylene oxide. In more detail, for instance, polyethyleneimine is first reacted with propylene oxide in the presence of up to about 70 % by weight of water at a temperature of from 25 to 150°C in an autoclave fitted with a stirrer. In the first step of the reaction propylene oxide is added in such an amount that nearly all hydrogen atoms of the N-H-groups of the polyethyleneimine are converted into hydroxy propyl groups. The water is then removed from the autoclave. After the addition of a basic catalyst, for example sodium methylate, potassium tertiary butylate, potassium hydroxide, sodium hydroxide, sodium hydride, potassium hydride or an alkaline ion exchanger in an amount of 0,1 to 15 %, by weight with reference to the addition product obtained in the first step of the propoxylation, further amounts of propylene oxide are added to the reaction product of the first step so that a propoxylated polyethyleneimine is obtained which contains 1-10, preferably 2 to 5, most preferably 3 to 4, propylene oxide units per N-H group of the polymer. The second

step is carried out for instance at temperatures of from 60 to 150°C.

After the addition of propylene oxide to polyethyleneimine in the
5 said amounts the reaction product is further reacted at temperatures in the range from 60 to 150°C with 10 to 40, preferably 20 to 40 most preferred 25 to 35 moles of ethylene oxide forming the soil dispersants of the invention. The second step of the propoxylation and the following oxyethylation of the reaction product
10 obtained in the first step may be carried out in an organic solvent such as xylene.

EXAMPLE 1

15 PEI 3000 (PO)₃.(EO)₂₇


43 g of polyethyleneimine (PEI having an average molecular weight of 3000 and corresponding to 1.0 mol, with reference to ethyleneimine) is added as a 54 % by weight aqueous solution to an
20 autoclave fitted with a stirrer under a nitrogen blanket. The autoclave is sealed and its contents is heated with stirring to 90°C. At this temperature 58 g (1 mol) of propylene oxide are pressurized. The stirring is continued until the pressure remains constant. The contents of the autoclave is then cooled to a
25 temperature of 80°C and 12.5 g of potassium hydroxide are added as a 40 % strength by weight aqueous solution. The water is then removed applying a vacuum of about 20 mbar. 103 g of a viscous oil is obtained.

30 In the second step of alkoxylation 101 g of the hydroxypropylated polyethyleneimine obtained above is placed in a stirred autoclave and is heated under nitrogen to 120°C. The reactor is pressurized several times with nitrogen and its contents is heated to 140 to 145°C. Then 116 g (2 moles) of propylene oxide are introduced
35 under pressure. The reaction mixture is stirred at 140 to 145°C until the pressure is constant. Ethylene oxide is then added in the said temperature range in an amount of 1,180 g (27 moles with reference to ethyleneimine). The reaction mixture is stirred until the pressure is constant and is then cooled to 80°C. About
40 1.4 kg of a viscous brown oil is obtained. The alkoxyated product becomes a brown solid at room temperature and has a melting point of 45 to 50°C.

What is claimed is

1. A soil dispersant having the formula:


5



10

wherein R is C₂-C₆ linear alkylene, C₃-C₆ branched alkylene, and mixtures thereof; B is a continuation by branching; E is an alkyleneoxy unit having the formula:

15



20

wherein R¹ is 1,2-propylene, 1,2-butylene and mixtures thereof; R² is ethylene; R³ is hydrogen, C₁-C₄ alkyl, and mixtures thereof; m is from about 1 to about 10; n is from about 10 to about 40; w, x and y are each independently from about 4 to about 200; provided at least one (R¹O) unit is attached to the backbone prior to attachment of an (R²O) unit and further provided m + n is at least 12.

- 25 2. A soil dispersant according to Claim 1 wherein R is ethylene.

3. A soil dispersant according to Claim 2 wherein R¹ is 1,2-propylene, R³ is hydrogen, m is from about 1 to about 6, n is from about 15 to about 35 and m + n is from about 20 to about 40.

30

4. A soil dispersant according to Claim 3 wherein m is from about 2 to about 5, n is from about 20 to about 30 and m + n is from about 25 to about 35.

35

5. A soil dispersant according to Claim 4 wherein m is 3 and n is 27.

6. A soil dispersant according to Claim 3 wherein the backbone molecular weight prior to modification is from about 600 daltons to about 25000 daltons.

40

45

7. A soil dispersant according to Claim 6 wherein the backbone molecular weight prior to modification is from about 1200 daltons to about 20000 daltons.
- 5 8. A soil dispersant according to Claim 7 wherein the backbone molecular weight prior to modification is from about 2000 daltons to about 5000 daltons.
9. A soil dispersant according to Claim 8 wherein the backbone
10 molecular weight prior to modification is about 3000 daltons.
10. A soil dispersant according to Claim 1 wherein R is ethylene,
R¹ is 1,2-propylene, R² is ethylene, R³ is hydrogen, m is 3, n
is 27, and the indices w, x and y are taken together such
15 that the polyalkyleneimine backbone prior to modification has
a molecular weight of about 3000 daltons.

20

25

30

35

40

45

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/04057

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 C11D3/37 C11D3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, A	WO 99 01530 A (PROCTER & GAMBLE) 14 January 1999 (1999-01-14)	1-10
A	EP 0 112 593 A (PROCTER & GAMBLE) 4 July 1984 (1984-07-04) page 14, line 67 -page 15, line 2; claim 1; example I	1
A	DE 22 27 546 A (BASF AG) 3 January 1974 (1974-01-03) page 10; claim 1	1

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

17 September 1999

Date of mailing of the international search report

04/10/1999

Name and mailing address of the ISA
 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Loiselet-Taisne, S

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No PCT/EP 99/04057

Patent document cited in search report	A	Publication date	Patent family member(s)	Publication date
WO 9901530	A	14-01-1999	AU 7784898 A	25-01-1999
<hr style="border-top: 1px dashed black;"/>				
EP 0112593	A	04-07-1984	US 4597898 A	01-07-1986
			AT 44762 T	15-08-1989
			AU 575034 B	21-07-1988
			AU 2280283 A	28-06-1984
			CA 1220395 A	14-04-1987
			DK 20491 A	06-02-1991
			DK 598283 A, B,	24-06-1984
			EG 17032 A	30-10-1993
			FI 834748 A, B,	24-06-1984
			GB 2133415 A, B	25-07-1984
			GB 2175597 A, B	03-12-1986
			GB 2180249 A, B	25-03-1987
			GR 82407 A	13-12-1984
			HK 58390 A	10-08-1990
			HK 58790 A	10-08-1990
			HK 74590 A	28-09-1990
			IE 56486 B	14-08-1991
			JP 1773204 C	14-07-1993
			JP 4054719 B	01-09-1992
			JP 59166598 A	19-09-1984
			US 4891160 A	02-01-1990
			CA 1213286 A	28-10-1986
<hr style="border-top: 1px dashed black;"/>				
DE 2227546	A	03-01-1974	AR 198839 A	24-07-1974
			FR 2187884 A	18-01-1974
			NL 7307147 A, B,	11-12-1973
			US 3907701 A	23-09-1975
<hr style="border-top: 1px dashed black;"/>				