



(11) EP 2 962 962 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
06.01.2016 Bulletin 2016/01

(51) Int Cl.:
B65G 1/04 (2006.01)

(21) Application number: **15172286.5**

(22) Date of filing: **05.12.2013**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR

(30) Priority: **10.12.2012 NO 20121488**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
13807954.6 / 2 928 794

(71) Applicant: **Jakob Hatteland Logistics AS**
5578 Nedre Vats (NO)

(72) Inventor: **Hognaland, Ingvar**
N-5578 Nedre Vats (NO)

(74) Representative: **Onsagers AS**
P.O. Box 1813 Vika
0123 Oslo (NO)

Remarks:

This application was filed on 16-06-2015 as a divisional application to the application mentioned under INID code 62.

(54) ROBOT FOR TRANSPORTING STORAGE BINS

(57) The present invention relates to a bin storage system (3) comprising a three-dimensional bin storage structure (15) and a plurality of robot vehicles (1) which are movable on top of the bin storage structure to retrieve storage bins (2) from the structure. The structure comprises: pillars which are positioned with internal distances and in a rectangular arrangement accommodating the bins and defining storage columns (8, 8a, 8b) for the bins; supporting rails (13) arranged in a matrix on top of the pillars providing support (14) for the robot vehicles and allowing each robot vehicle to travel across the structure

in a first direction (X) and in a second direction (Y); a storage bin delivery station (60); and a bin lift device (50) which receives bins from the robot vehicles and transport them in a vertical direction from a top level of the structure to the delivery station. Each robot vehicle comprises a vehicle body (4) having: first and second sets of rolling means (10, 11) for moving the robot vehicle along the supporting rails; a cavity (7) for receiving a bin; and a lifting device (9) for retrieving a bin from a storage column and storing the bin in the cavity.




FIG. 8

Description

[0001] The present invention relates to a bin storage system comprising a three-dimensional bin storage structure and a plurality of robot vehicles which are movable on top of the bin storage structure to retrieve storage bins from the bin storage structure, which bin storage structure comprises: a plurality of pillars which are positioned with internal distances and in a rectangular arrangement adapted to accommodate the storage bins, where the rectangular arrangement of the pillars define storage columns for the storage bins; supporting rails which are arranged in a two-dimensional matrix on top of the pillars and provide a vehicle support for the plurality of robot vehicles allowing each robot vehicle to travel across the bin storage structure in a first direction and in a second direction, which is orthogonal to the first direction; a storage bin delivery station; and a bin lift device which is arranged to receive storage bins from the plurality of robot vehicles and transport the storage bins in a vertical direction from a top level of the bin storage structure to the delivery station, which plurality of robot vehicles each comprises a vehicle body which comprises: a first set of rolling means for moving the robot vehicle along the supporting rails in the first direction; a second set of rolling means for moving the robot vehicle along the supporting rails in the second direction; a cavity for receiving a storage bin; and a lifting device for retrieving a storage bin from a storage column and storing the storage bin in the cavity.

[0002] The invention also relates to a method of operating robot vehicles in such a bin storage structure.

[0003] A remotely operated vehicle for picking up storage bins from a storage system is known. A detailed description of a relevant prior art storage system is given in WO 98/49075. Further, details of a prior art vehicle being suitable for such a storage system is disclosed in Norwegian patent NO317366. More specifically the prior art storage system comprises a three dimensional storage grid containing storage bins that are stacked on top of each other to a certain height. The storage grid is normally constructed as aluminium columns interconnected by top rails. A number of remotely operated vehicles, or robots, are arranged on the top rails. Each vehicle is equipped with a lift for picking up, carrying, and placing bins that are stored inside the storage grid.

[0004] Such a prior art storage system art and prior art robot is illustrated in figures 1 and 2, respectively. The storage system 3 comprises a robot 1 which is arranged to move on dedicated supporting rails 13 and to receive a storage bin 2 from a storage column 8 within a bin storing grid 15. The storage system 3 includes a plurality of such robots 1 and a dedicated bin lift device 50, the latter being arranged to receive a storage bin 2 from the robot 1 at the top level of the bin storing grid 15 and to convey the storage bin 2 down in a vertical direction to a delivery station 60. However, the prior art robot 1 shown in both fig. 1 and fig. 2 suffers from several important

disadvantageous during their operation. Firstly, the particular design of the robot prevents access to all off the available storage columns in the storage system. Furthermore, this particular design may cause an undesirable high torque during lifting and transportation of storage bins, thereby creating potential instability problems, as well as a clear limitation of the robots maximum handling weight. An additional disadvantage caused by the prior art robot design is the fact that only one particular bin and one particular bin height may be accepted for each type of robot in order to ensure adequate stability. Finally, the presence of an integrated yoke / overhang in the upper part of the section receiving the storage bin necessitates an undesired speed reduction at the final stage of the lifting process performed by the yoke suspended vehicle lifting device.

[0005] The object of the present invention is to solve, or at least substantially alleviate, the above-described disadvantageous, that is to provide a vehicle / robot with higher stability properties, higher maximum handling weights, a more effective use of available space during operation and a less time consuming lifting and transporting process of storage bins.

[0006] The above-identified objects are achieved by a remotely operated vehicle as defined in claim 1 and storage system as defined in claim 11. Further beneficial features are defined in the dependent claims.

[0007] In particular, the present invention concerns a remotely operated vehicle or robot for picking up storage bins from a storage system. The inventive vehicle or robot comprises a vehicle body, which vehicle body further comprises a first section for storing vehicle driving means and a second section for receiving any storage bin stored in a storage column within the storage system, a vehicle lifting device which is at least indirectly connected to the vehicle body in order to lift the storage bin into the second section, a first set of vehicle rolling means connected to the vehicle body in order to allow movement of the vehicle along a first direction (X) within the storage system during use and a second set of vehicle rolling means connected to the vehicle body in order to allow movement of the vehicle along a second direction (Y) in the storage system during use. The second direction (Y) is oriented perpendicular to the first direction (X).

[0008] The inventive vehicle is characterized in that the second section comprises a cavity arranged centrally within the vehicle body. This cavity has at least one bin receiving opening facing towards the underlying storage columns during use. In addition, at least one of the two sets of vehicle rolling means is arranged fully within the vehicle body.

[0009] In order to allow easy entrance of the storage bin into the central cavity, its volume should be larger than the largest storage bin intended to be picked from the storage system. Likewise, the cross sectional area of at least one of the at least one bin receiving opening should be larger than the cross sectional area of the storage bin walls oriented parallel to the cavity opening(s).

[0010] The vehicle may further comprise means for reversibly and selectively displacing either the first set of vehicle rolling means or the second vehicle rolling means away from an underlying vehicle support within the storage system during a change of vehicle direction between the first direction (X) and the second direction (Y).

[0011] Furthermore, in an embodiment the first section may be arranged relative to the second section in such a way that the cross section of the vehicle parallel to the underlying vehicle support deviates from a quadratic shape.

[0012] In a preferred embodiment the vehicle body covers less or equal to the lateral cross sectional area of one central storage column in the first direction (X) and covers the lateral cross sectional area of more than one central storage column in the second direction (Y) during use. In a more specific example the vehicle body extends beyond the lateral cross sectional area of the central storage column at both sides facing the second direction (Y), i.e. covering also some of the cross sectional areas of the adjacent storage columns extending in the second direction (Y). The degree of extension from the central storage column is preferably equal on both of these sides. Central storage column is defined as the storage column which is immediately below a robot when the latter has reached a position allowing pick-up of a storage bin.

[0013] In order to inter alia allow high vehicle stability both sets of vehicle rolling means is preferably arranged symmetrically around the cavity, for example near the lower corners of the vehicle. At least one, and most preferably both, set(s) of vehicle rolling means may comprise at least four wheels. Other embodiments such as the use two perpendicular oriented caterpillar belts may be envisaged. Furthermore, both sets have an exterior design matching a corresponding exterior design on supporting rails constituting the vehicle support in order to provide increased lateral stability when interconnected. Such supporting rails would be arranged in a two dimensional matrix on top of a bin storing structure or grid, where the principal directions of both the matrix and the grid are congruent with the vehicle's first direction (X) and second direction (Y).

[0014] The vehicle may advantageously also include position sensing means to allow measurements of the vehicle position within the storage system during use. This position sensing means may comprise a plurality of position sensors arranged in at least some of the positions on the vehicle body which would transverse the locations of vehicle support where the supporting rails are crossing, for example underneath the vehicle, close to its lower corners.

[0015] The present invention also concerns a storage system which comprises a remotely operated vehicle in accordance with the above mentioned features, a vehicle support comprising a plurality of supporting rails forming a two dimensional matrix of guiding meshes, wherein the vehicle support is configured to guide the movements of the vehicle in the first direction (X) and the second direc-

tion (Y) during use, a bin storing structure or grid supporting the vehicle support comprising a plurality of storage columns, wherein each of the storage columns is arranged to accommodate a vertical stack of storage bins

5 and wherein the main part of the bin storing structure coincides with positions on the vehicle support where the supporting rails are crossing, and a bin lift device arranged to convey a vehicle delivered storage bin in a direction perpendicular to the lateral plane of the vehicle support between the vehicle support and a delivery station.

[0016] In a preferred embodiment at least some of the supporting rails arranged at the outer lateral border areas of the vehicle support form outer guiding meshes having 15 reduced average cross sectional areas compared to the average cross sectional area of the remaining guiding meshes in the vehicle support. For example, the average reduced cross sectional areas of the outer guiding meshes may be about half of the average cross sectional area

20 of the remaining guiding meshes in the vehicle support. In a particularly preferred embodiment these cross sectional areas of the outer guiding meshes are reduced only along the second direction (Y) of the vehicle support.

[0017] The central arrangement of the cavity in the vehicle body relative to the second direction (Y) effectively remove the undesired torque, thereby improving the stability of the robot or vehicle. This arrangement also results in a lifting and transporting process having a weight distribution with a high degree of symmetry. Furthermore, 25 the novel design allows the same vehicle to be used for lifting and transporting storage bins of heights significantly less than the cavity height (i.e. the height extending from the suspension points of the lifting device and to the lower edge of the vehicle) since the framework / body

30 surrounding at least part of the bin receiving cavity effectively hinders any undesired bin reeling / wobbling. The presence of the cavity surrounding body also allows maintaining full or nearly full lifting speed almost all the way to its end position within the cavity, as well as initiation

35 of stable bin transports towards the delivery station prior to a fully completed bin lifting from a storage column. The protective body around the cavity also gives the possibility of starting a descent of the lifting device event prior to the time the vehicle has come to a final halt 40 above the storage column in question. A significantly higher stability and time efficiency is thus achieved.

[0018] By arranging at least one set of vehicle rolling means fully within the vehicle or robot body additional stability is obtained during the lifting process since the 45 rolling means is situated closer to the storage bin to be lifted. Of the same reason this arrangement reduces the total load on the lifting device. Furthermore, the arrangement is more space efficient relative to the prior art robot illustrated in figure 2 since the roller means does not give any additional extensions in at least one of the two robots moving directions (X and Y). Production of smaller sized robots / vehicles is also rendered possible.

[0019] These and other characteristics of the invention

will be clear from the following description of a preferential form of embodiment, given as a non-restrictive example, with reference to the attached drawings wherein:

Fig. 1 is a perspective view of a prior art storage system;

Fig. 2 is a sectional view of a prior art robot or vehicle forming part of a storage system as illustrated in fig. 1;

Fig. 3 is a perspective base view of a remotely operated vehicle according to the present invention;

Fig. 4 is a perspective top view of a remotely operated vehicle according to the present invention;

Fig. 5 is a perspective top view of a robot assembly comprising a remotely operated vehicle according to the present invention, a storage bin and a fully enclosing cover,

Fig. 6 is a perspective top view of a bin storing grid and a vehicle support in accordance with the present invention;

Fig. 7 is a perspective side view of a bin storing grid and a vehicle support in accordance with the present invention;

Fig. 8 is a perspective side view of part of a storage system in accordance with the present invention including a bin storing grid, a vehicle support and a remotely operated vehicle; and

Fig. 9 is a schematic top view of a remotely operated vehicle moving on a two dimensional matrix of supporting rails.

[0020] Fig. 1 is a schematic, partly cut perspective view of a storage system according to the prior art, and fig. 2 is a sectional view of a corresponding prior art robot. Both figures have already been referred to earlier in the text.

[0021] Fig. 3 and 4 gives a perspective view in two different angles of the inventive robot 1 comprising a rectangular vehicle body or framework 4 with a cavity 7 centrally arranged within the body 4, a top lid 72 covering the top part of the body 4, a first set of four wheels 10 mounted inside the cavity 7 and in parallel to the interior walls of the body 4 and a second set of four wheels 11 mounted in parallel to the exterior walls of the body 4. The first and second set of wheels 10,11 are oriented perpendicular to each other. Further, the vehicle body 4 also includes side parts 5,5a,5b arranged on both sides of the cavity 7 along at least one of the robots 1 direction of movements. For the sake of clarity a Cartesian coordinate system is shown with its X, Y and Z axes aligned along the principal directions of the rectangular vehicle

body 4. The size of the cavity 7 is adapted to contain necessary component for a lifting device 9 and to at least completely contain the largest storage bin 2 intended to be picked up by the robot 1.

5 **[0022]** Fig. 5 gives a perspective view of a robot assembly where the body 4 is completely covered by an enclosing cover 73 comprising handles 74 and transmission means / control panel 75. The design of the enclosing cover 73 is adapted to the particular shape given by the body 4 and the protruding wheels 10. Fig. 5 also shows a small part of a storage bin 2 arranged fully inside the cavity 7 and a small part of the lifting device 9. The latter is preferably composed of *inter alia* four vertically moveable metal bands suspended on the cavity facing side of the top lid 72 in their upper ends and steering rods at the lower ends capable of being steered and fastened into adapted cavities / areas in the storage bin 2 to be picked.

10 **[0023]** The structural principles of a grid assembly comprising a bin storing structure or grid 15, integrated supporting rails 13 constituting the vehicle support 14 and a grid supporting base 76 are illustrated in figs. 6 and 7. The grid 15 comprises a plurality of pillars being arranged with internal distances adapted to accommodate storage bins 2 to be stored in stacks inside the grid 15. The rectangular arrangements of four adjacent pillars therefore constitute a storage column 8. Both the pillars and the rails 13 may be made of Aluminium. As for fig. 3 and 4 a Cartesian coordinate system is shown aligned along the principal directions of the grid assembly to ease the understanding. The supporting rails 13 form a two dimensional matrix of rectangular meshes, and the cross sectional area of most of these meshes coincide with the cross sectional area of each storage columns 8 set up 15 by the underlying grid 15. The meshes at the border area 17,18 of the vehicle support 14 (at both sides in direction Y) is illustrated with cross sectional areas smaller than the remaining meshes. The size of the border meshes 17,18 should preferably be adapted to the degree of extension beyond a central storage column 8a situated immediately below the cavity 7 of the robot 1 when the latter is in a position for initiating pick up of a storage bin 2 contained in the central storage column 8a (see fig. 8 and 9). In this way the robot 1 may reach all the storage 20 columns 8 in the storage system 3, i.e. independently of the robot orientation in the Y direction. For example, if the robot 1 extends exactly over the cross sectional area of one central storage column 8a in the X direction and over $\frac{1}{2}$ of the cross sectional area of the adjacent storage column 8b in the Y direction, the cross sectional area of the meshes 17,18 at the border area in the Y direction should be approximately $\frac{1}{2}$ of the cross sectional area of the remaining meshes. The primary function of these border meshes 17,18 is thus to allow sufficient space for 25 the robot 1 having the novel design.

30 **[0024]** Fig. 8 shows the robot 1 in a lifting position above the central storage column 8a adjacent to the border area 17,18 of the grid assembly. The vehicle lifting

device 9 is in this embodiment lowered a distance into the central storage column 8a in order to hook onto and lift up the underlying storage bin 2. As seen in the exemplary situation in figs. 8 the robot 1, having the body 4 extended in the Y direction compared to the X direction, may be driven all the way to the edge of the grid 15 when the border area is designed with additional border meshes 17,18 with a Y directional width approximately 1/2 of the Y directional widths of the remaining meshes in the grid 15.

[0025] To better illustrate the movement of the robot 1 on the supporting rails 13 constituting the vehicle support 14 some exemplary positions of robots 1 on a grid assembly is illustrated in fig. 9. The thick arrows drawn in the centre of the robots 1 indicate allowed moving directions. When the robot 1 is situated with its cavity 7 exactly above a central storage column 8a, as is the case for the top left and mid centred robot 1, the arrangement of the supporting rails 13 allow movement in both X and Y directions. Any other positions on the grid assembly restrict the robot's 1 movement on the vehicle support 14 either in X direction (lower right robot 1) or in Y direction (top centered and bottom left robot 1). To allow determination of the robot position it is considered advantageous to equip each robot 1 with one or more position sensors 16, for example optical sensors. Such sensors should 16 preferably be mounted in one or more areas of the robot 1 which ensures that the sensors 16 have both non-obstructed view to the underlying supporting rails 13 and that they pass directly above or close to the positions on the vehicle support 14 in which the rails 13 are crossing. The readings from the sensors 16 may inter alia dictate the further movement of the robot 1 and/or the operation of the vehicle lifting device 9.

[0026] All operations of the robot 1 are controlled by wireless communication means 75 and remote control units. This includes control of the robot movement, the vehicle lifting device and the position measurements.

[0027] In the preceding description, various aspects of the apparatus according to the invention have been described with reference to the illustrative embodiment. For purposes of explanation, specific numbers, systems and configurations were set forth in order to provide a thorough understanding of the apparatus and its workings. However, this description is not intended to be construed in a limiting sense. Various modifications and variations of the illustrative embodiment, as well as other embodiments of the apparatus, which are apparent to persons skilled in the art to which the disclosed subject matter pertains, are deemed to lie within the scope of the present invention.

List of reference numerals / letters:

[0028]

- 1 Remotely operated vehicle / robot
- 2 Storage bin

3	Storage system
4	Vehicle body / framework
5	First section (of vehicle body) / component section / side parts
5	5a First section, left
	5b First section, right
6	Vehicle driving means / motor unit
7	Vehicle storage space / second part / cavity / centrally arranged cavity
10	Storage column
	8a Central storage column
	8b Adjacent storage column
9	Vehicle lifting device
10	First set of vehicle rolling means / First set of wheels
15	Second set of vehicle rolling means / Second set of wheels
11	Bin receiving opening
12	Supporting rail
13	Vehicle support
14	Bin storing structure / grid
15	Position sensing means / position sensor
16	Left outer lateral border area of vehicle support / left border mesh
17	Right outer lateral border area of vehicle support / right border mesh
18	Bin lift device
50	Delivery station / port
60	Yoke / overhang
70	Top lid
72	Enclosing cover
73	Handles
74	Transmission means / control panel / wireless communication means
75	Grid supporting base

Claims

- 40 1. A bin storage system (3) comprising a three-dimensional bin storage structure (15) and a plurality of robot vehicles (1) which are movable on top of the bin storage structure (15) to retrieve storage bins (2) from the bin storage structure (15), which bin storage structure (15) comprises:
 - a plurality of pillars which are positioned with internal distances and in a rectangular arrangement adapted to accommodate the storage bins (2), where the rectangular arrangement of the pillars define storage columns (8, 8a, 8b) for the storage bins (2),
 - supporting rails (13) which are arranged in a two-dimensional matrix on top of the pillars and provide a vehicle support (14) for the plurality of robot vehicles (1) allowing each robot vehicle (1) to travel across the bin storage structure (15) in a first direction (X) and in a second direction
- 45
- 50
- 55

(Y), which is orthogonal to the first direction (X),
 - a storage bin delivery station (60), and
 - a bin lift device (50) which is arranged to receive
 storage bins (2) from the plurality of robot vehi-
 cles (1) and transport the storage bins (2) in a
 vertical direction from a top level of the bin stor-
 age structure (15) to the delivery station (60),
 5
 which plurality of robot vehicles (1) each comprises
 a vehicle body (4) which comprises:
 10

- a first set of rolling means (10) for moving the
 robot vehicle (1) along the supporting rails (13)
 in the first direction (X),
- a second set of rolling means (11) for moving
 the robot vehicle (1) along the supporting rails
 (13) in the second direction (Y),
- a cavity (7) for receiving a storage bin (2), and
- a lifting device (9) for retrieving a storage bin
 (2) from a storage column (8, 8a, 8b) and storing
 the storage bin (2) in the cavity (7),
 15
 wherein the cavity (7) is arranged centrally within
 the vehicle body (4).

2. The bin storage system (3) according to claim 1,
characterised in that the vehicle body (4) surrounds
 at least part of the cavity (7).
 25

3. The bin storage system (3) according to claim 2,
characterised in that the vehicle body (4) compris-
 es side parts (5, 5a, 5b) arranged on both sides of
 the cavity (7) along at least one of the robot vehicle's
 30 direction of movements (X, Y).

4. The bin storage system (3) according to any of the
 preceding claims, **characterised in that** the robot
 vehicle (1) comprises a top lid (72) covering the top
 part of the vehicle body (4).
 35

5. The bin storage system (3) according to any one of
 the preceding claims, **characterised in that** the cav-
 ity (7) displays a downwardly facing opening for the
 storage bin (2).
 40

6. The bin storage system (3) according to any one of
 the preceding claims, **characterised in that** both
 sets of vehicle rolling means (10, 11) are arranged
 symmetrically around the cavity (7) near the lower
 45 corners of the robot vehicle (1).
 50

7. The bin storage system (3) according to any one of
 the preceding claims, **characterised in that** said first
 and second sets of rolling means (10, 11) each com-
 prises at least four wheels.
 55

8. A method of operating a bin storage system (3) com-
 prising a three-dimensional bin storage structure
 (15) and a plurality of robot vehicles (1) which are
 movable on top of the bin storage structure (15) to
 retrieve storage bins (2) from the bin storage struc-
 ture (15), which bin storage structure (15) comprises:
 60

- a plurality of pillars which are positioned with
 internal distances and in a rectangular arrange-
 ment adapted to accommodate the storage bins
 (2), where the rectangular arrangement of the
 pillars define storage columns (8, 8a, 8b) for the
 storage bins (2),
- supporting rails (13) which are arranged in a
 two-dimensional matrix on top of the pillars and
 provide a vehicle support (14) for the plurality of
 robot vehicles (1) allowing each robot vehicle
 (1) to travel across the bin storage structure (15)
 in a first direction (X) and a second direction (Y),
 which is orthogonal to the first direction (X),
- a storage bin delivery station (60), and
- a bin lift device (50) which is arranged to trans-
 port the storage bins (2), in a vertical direction,
 from a top level of the bin storage structure (15)
 to the delivery station (60),

 and which plurality of robot vehicles (1) each com-
 prises a vehicle body (4) which comprises:
 65

- a first set of rolling means (10) for moving the
 robot vehicle (1) along the supporting rails (13)
 in the first direction (X),
- a second set of rolling means (11) for moving
 the robot vehicle (1) along the supporting rails
 (13) in the second direction (Y),
- a cavity (7) for receiving a storage bin (2), which
 cavity (7) is arranged centrally within the vehicle
 body (4),
- a lifting device (9) for retrieving a storage bin
 (2) from a storage column (8, 8a, 8b) and storing
 the storage bin (2) in the central cavity (7),

 which method comprises the steps of:
 70

- positioning one of the plurality of robot vehicles
 (1) above one of said storage columns (8a, 8b)
 such that the central cavity (7) of the vehicle
 body (4) is aligned with the storage column (8a,
 8b),
- using the lifting device (9) of the vehicle body
 (4), retrieving a storage bin (2) from the storage
 column (8a, 8b) and storing the storage bin (2)
 inside the central cavity (7),
- using the first and second sets of rolling means
 (10, 11), moving the robot vehicle (1) along the
 supporting rails (13) to the bin lift device (50)
 and transferring the storage bin (2) to the bin lift
 device (50), and
- using the bin lift device (50), conveying the stor-
 age bin (2) down in a vertical direction from the
 top level of the bin storage structure (15) to the

delivery station (60).

9. The method according to claim 8, wherein the vehicle body (4) surrounds at least part of the central cavity (7). 5
10. The method according to claim 9, wherein the vehicle body (4) comprises side parts (5, Sa, 5b) arranged on both sides of the cavity (7) along at least one of the robot vehicle's (1) direction of movements (X, Y). 10
11. The method according to any one of claims 8-10, wherein the robot vehicle (1) comprises a top lid (72) covering the top part of the vehicle body (4). 15
12. The method according to any one of claims 8-11, wherein the central cavity (7) displays a downwardly facing opening for the storage bin (2).
13. The method according to any one of claims 8-12, 20 wherein both sets of vehicle rolling means (10, 11) are arranged symmetrically around the cavity (7) near the lower corners of the robot vehicle (1).
14. The method according to any one of claims 8-13, 25 wherein said first and second sets of rolling means (10, 11) each comprises at least four wheels.

30

35

40

45

50

55




FIG. 1(Prior Art)




FIG. 2 (Prior Art)




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8





EUROPEAN SEARCH REPORT

Application Number
EP 15 17 2286

5

DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (IPC)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
10	A,D WO 98/49075 A1 (JAKOB HATTELAND ELECTRONIC AS [NO]; HOGNALAND INGVAR [NO]) 5 November 1998 (1998-11-05) * pages 5-7; figure 2 *	1-14	INV. B65G1/04
15	A WO 2005/077789 A1 (ICAM S R L [IT]; BIANCO GRAZIANO [IT]; BIANCO ROBERTO [IT]) 25 August 2005 (2005-08-25) * pages 1-14; figures 1-4 *	1-14	
20	A US 2003/229416 A1 (TAI AKITO [JP] ET AL) 11 December 2003 (2003-12-11) * pages 1-11; figures 1-16 *	1-14	
25			
30			TECHNICAL FIELDS SEARCHED (IPC)
35			B65G
40			
45			
1	The present search report has been drawn up for all claims		
50	Place of search The Hague	Date of completion of the search 30 November 2015	Examiner Martin, Benoit
55	CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		
	T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document		

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 15 17 2286

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-11-2015

10

	Patent document cited in search report	Publication date		Patent family member(s)	Publication date
	WO 9849075	A1 05-11-1998	AT	249992 T	15-10-2003
			AU	7086698 A	24-11-1998
			CN	1248954 A	29-03-2000
			DE	69818303 D1	23-10-2003
			DE	69818303 T2	15-07-2004
			DK	1037828 T3	05-01-2004
			EP	1037828 A1	27-09-2000
			ES	2206915 T3	16-05-2004
			HK	1031714 A1	23-04-2004
			JP	4025374 B2	19-12-2007
			JP	2001522342 A	13-11-2001
			PT	1037828 E	27-02-2004
			US	6654662 B1	25-11-2003
			WO	9849075 A1	05-11-1998

	WO 2005077789	A1 25-08-2005		NONE	

	US 2003229416	A1 11-12-2003	CN	1468767 A	21-01-2004
			KR	20030095204 A	18-12-2003
			TW	1233913 B	11-06-2005
			US	2003229416 A1	11-12-2003

	EPO FORM P0469				

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 9849075 A [0003]
- NO 317366 [0003]

摘要

本发明涉及一种箱储藏系统（3），该箱储藏系统包括三维箱储藏结构（15）以及多个机器人车辆（1），该机器人车辆在箱储藏结构的顶部上可移动以检索来自结构的储藏箱（2）。该结构包括：柱子，其定位有内部距离并定位在容纳箱的矩形布置中并限定用于箱的储藏立柱（8、8a、8b）；支撑导轨（13），在柱子的顶部上布置为矩阵以提供用于机器人车辆的支撑（14）并使得每个机器人车辆在第一方向（X）和第二方向（Y）上穿过结构；储藏箱传送站（60）；以及箱提升设备（50），其从机器人车辆接收箱并在垂直方向上从化结构的顶层向传送站运输它们。每个机器人车辆包括车身（4），该车身具有：第一组和第二组滚动装置（10、11），用于沿着支撑导轨移动机器人车辆；腔（7），用于接收箱；以及提升设备（9），用于从储藏立柱检索箱并将其储藏在腔中。