



(10) International Publication Number  
**WO 2016/200722 A1**

(43) International Publication Date  
15 December 2016 (15.12.2016)

(51) International Patent Classification:

A61B 34/30 (2016.01) A61B 17/29 (2006.01)  
A61B 34/00 (2016.01) A61B 17/068 (2006.01)  
A61B 17/34 (2006.01) A61B 17/00 (2006.01)

(21) International Application Number:

PCT/US2016/035980

(22) International Filing Date:

6 June 2016 (06.06.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/172,396 8 June 2015 (08.06.2015) US

(71) Applicant: **COVIDIEN LP** [US/US]; 15 Hampshire Street, Mansfield, Massachusetts 02048 (US).

(72) Inventors: **KAPADIA, Jaimeen**; 45 Fairlawn Avenue, Bridgeport, Connecticut 06605 (US). **ROSMARIN, Josiah**; 1216 Katcalani Avenue, Sebring, Florida 33870 (US).

(74) Agents: **AKYUZ, Ishak** et al; Covidien, 555 Long Wharf Drive, Mail Stop: 8 N-1, New Haven, Connecticut 065 11 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available):

AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available):

ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: MOUNTING DEVICE FOR SURGICAL SYSTEMS AND METHOD OF USE



(57) Abstract: A surgical mounting device may detachably couple to a patient access device to maintain alignment between a surgical instrument and the access device as instruments are interchangeably inserted and removed from the access device. The mounting device may include arms that pivot between a closed configuration in which the arms grip the access device inserted therebetween and an open configuration in which arm are spaced further apart from each other than in the closed configuration. A drive member may transition the arms to the closed configuration when the patient access device is inserted between the arms in the open configuration and pressed against the drive member.

WO 2016/200722 A1

**MOUNTING DEVICE FOR SURGICAL SYSTEMS AND METHOD OF USE****CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] This application claims the benefit of and priority to U.S. Provisional Patent Application No. 82/172,398, filed June 8, 2015, the entire disclosure of which is incorporated by reference herein.

**BACKGROUND**

[0002] Robotic surgical systems used in minimally invasive medical procedures included a console supporting a robot arm which further supported patient access devices, for example, a trocar, surgical port, or the like, through which a surgical instrument having an end effector (e.g., forceps, staplers, grasping tools, etc.) were passed through for use during the medical procedure. The robot arm coupled to the access device and the surgical instrument and moved the access device as the surgical instrument was moved during the procedure. A robot arm included an instrument drive unit that operatively connected to the surgical instrument.

[0003] Prior to or during use of the robotic system, access devices were connected to each robot arm to maintain alignment of the access device with the robot arm after the surgical instruments were removed from the access device and/or robot arm. Certain connecting features of the access devices had to be matingly engaged to corresponding connecting features of the robotic arm to complete the connection. The connection and removal of these access devices required precise alignment and was time consuming.

[0004] There is a need for more efficient connectivity between access devices and robot arms.

SUMMARY

[0005] Surgical mounting devices may include a first arm and a second arm pivotable between a closed configuration in which the first and second arms grip a patient access device inserted therebetween and an open configuration in which a portion of the first and second arms are spaced further apart from each other than in the closed configuration. Surgical mounting devices may also include a drive member coupled between the first and second arms, the drive member driving the arms to the closed configuration when the patient access device is inserted between the arms in the open configuration and pressed against the drive member. These features may enabling access devices to be quickly attached and detached to the surgical mounting device and/or surgical robotic arm when the surgical mounting device is part of the robotic arm.

[0006] The surgical mounting device may also include a surgical robotic arm having an end portion positioned near a surgical access site on the patient. The first and second arms may protrude from the end portion of the surgical robotic arm.

[0007] A release mechanism that may be part of the surgical mounting device may bias the first and the second arms toward the open configuration when actuated. The release mechanism may define an actuation pivot point, such that the release mechanism is pivotable between a non-actuated position and an actuated position. The release mechanism may include a hooked end cooperatively engaging with a surface of the drive member in an actuated position. The release mechanism may include a chamfered profile engaging with a proximal surface of the drive member in an actuated position. The release mechanism may be biased towards a non-actuated position.

[0008] The surgical mounting device may also include two release mechanisms disposed on opposing sides of the housing. In some instances, actuation of both these release mechanisms may bias the first and the second arms toward the open configuration. In some instances, actuation of either of these release mechanisms may bias the first and the second arms toward the open configuration.

[0009] The first and second arms may have an arcuate surface corresponding to an arcuate surface of the patient access device gripped by the arms.

[0010] A surgical mounting device may selectively grip a patient access device therein. The surgical mounting device may include a housing, a clamping assembly supported in the housing and extending therefrom. The clamping assembly may include a plunger assembly supported on the housing and a drive member disposed in the housing coupled to a middle segment disposed distal to the housing. The drive member and middle segment may simultaneously translate between a proximal position and a distal position with respect to the housing.

[0011] A first and a second arm may be supported by the housing and include a proximal portion disposed in the housing and a distal portion extending therefrom. Each arm may be coupled at the proximal end to the drive member and pivotable with respect to the housing between an open position and a closed position. In the open position the first and second arms may be spaced apart relative to one another and in the closed position the first and second arms may be in an approximated position relative to one another.

**[0012]** The clamping assembly may be transitionable between an unlocked configuration and a locked configuration. In the unlocked configuration, the drive member and the middle segment may be in the distal position and the first and second arms may be in the open position. In the locked configuration, the drive member and middle segment may be in the proximal position and the first and second arms may be in the closed position.

**[0013]** The surgical mounting device and/or clamping assembly may include at least one release mechanism. The release mechanism may include a contact surface disposed in the housing and an articulation member in operative communication with the contact surface. A portion of the articulation member may be disposed externally from the housing,

**[0014]** The release mechanism may be transitionable between an initial position and a release position, such that in the initial position the contact surface is spaced away from the drive member, and in the release position the contact surface is in abutment with the drive member. The release position may translate the drive member into the distal position, such that the clamping assembly is transitioned into the unlocked configuration. The release mechanism may include two release mechanisms disposed in opposite sides of the housing.

**[0015]** Each arm may further include an arcuate surface on the distal portion. The middle segment may further include an arcuate surface on a distally facing surface. The first arm, the second arm, and the middle segment may further include a protruding ridge disposed on each of the arcuate surfaces.

**[0016]** The clamping assembly may further include at least one biasing member coupled between the proximal end of each of the first and second arms. The biasing member may bias the

first and second arms into the open position, and bias the drive member and middle segment coupled therewith into the distal position.

[0017] Each arm may further include a pivot point disposed distal to the proximal end, such that pivoting the arms from the open position to the closed position translates the drive member and middle segment coupled therewith from the distal position to the proximal position transitioning the clamping assembly into the locked configuration.

[0018] The middle segment may translate from the proximal position to the distal position, such that the drive member coupled therewith translates distally and the first and second arms pivot from the open position to the closed position transitioning the clamping assembly into the locked configuration.

[0019] The plunger assembly may include a biasing member disposed between the middle segment and the drive member, such that the middle segment is biased distally with respect to the drive member.

[0020] The release mechanism may include a biasing member such that the at least one release mechanism is biased into the initial condition.

[0021] An access device may be mounted to a surgical system via a surgical mounting device. Responsive to positioning the access device into abutment with a middle segment situated between a pair of arms extending distally from a housing of the surgical mounting device on opposing sides of the middle segment, a driving mechanism slidably disposed in the housing and operably coupled to the middle segment may be translated from a distal position to a proximal position.

[0022] Responsive to translating the driving mechanism, the pair of arms coupled at a proximal end to the drive mechanism may be pivoted from a spaced apart position relative to one another to an approximated position relative to one another.

[0023] The drive mechanism may be translated into the proximal position and the pair of arms may be pivoted into the approximated position responsive to depressing the middle segment with the access device.

[0024] The pair of arms may grip the access device responsive to pivoting the pair of arms while the access device is positioned therebetween.

[0025] In response to translating a release mechanism into a release position: a contact surface of the release mechanism may be abutted with the driving mechanism, the driving mechanism may be translated into the distal position, the middle segment may be translated into the distal position, and the pair of arms may be pivoted into the spaced apart configuration.

[0026] Surgical mounting devices may be affixed to a robot arm of a surgical robotic system and include a housing and a clamping assembly enabling access devices to be quickly attached and detached to the robot arm. The clamping assembly may be supported on the housing and includes a first arm, a second arm, and a plunger assembly. The first and second arms may extend distally from the housing and may be coupled at a proximal end to a drive member. Further, the first and second arms may be pivotable between an open configuration and a closed configuration. In the open configuration a distal portion of each of the first and second arms may be spaced apart from one another, and in the closed configuration the distal portions of each first and second arm may be approximated relative to one another.

[0027] The plunger assembly may be supported in the housing and include the drive member coupled to a middle segment. The drive member may be disposed in the housing and the middle segment may be disposed distal to the housing between the first and second arms. The drive member may be translatable between a proximal position and a distal position with respect to the housing. The clamping assembly may be translatable between an open configuration and a closed configuration. In the open configuration the first and second arms may be in the open configuration and the drive member, and middle segment coupled thereto, may be in the distal position. In the closed configuration the first and second arms may be in the closed configuration and the drive member, and middle segment coupled thereto, may be in the proximal position.

[0028] In an embodiment, the surgical mounting device may include at least one release mechanism supported on the housing. The at least one release mechanism may include a contact surface disposed in the housing and coupled to an articulation member. A portion of the articulation member may extend externally of the housing. The at least one release mechanism may be translatable between an initial position and a release position. In the initial position, the contact surface may be spaced apart from the drive member, and in the release position, the contact surface may be in abutment with the drive member. In the release position the clamping assembly may be urged to transition into the open configuration.

[0029] The contact surface and the articulation member of the at least one release mechanism may monolithically formed. The at least one release mechanism may define a pivot point, and may be pivotable between the initial position and the release position. The contact surface of the at least one release mechanism may define a hooked end, and the hooked end may

cooperatively engage with a proximal surface of the drive member in the release position. The contact surface of the at least one release mechanism may define a chamfered profile, and the chamfered profile may cooperatively engage with a proximal surface of the drive member in the release position. The at least one release mechanism may be biased towards the initial position. The at least one release mechanism may include two release mechanisms disposed on opposing sides of the housing. Translation of the at least one release mechanism from the initial position to the release position may translate the drive member, and the middle segment coupled therewith, from the proximal position to the distal position.

**[0030]** The first and second arms may further include an arcuate surface disposed on an inner facing surface of the distal portion relative to one another, and the middle segment may further include an arcuate surface disposed on an outer facing surface with respect to the housing. The first and second arms, and the middle segment, may further include a protruding ridge disposed on the arcuate surface.

**[0031]** Each of the first and second arms may pivot about a point distal to the proximal end. As a result, as first and second arms pivot from the open configuration to the closed configuration, the drive member and the middle segment coupled therewith translate from the distal position to the proximal position. Thus, the clamping assembly transitions from the open configuration to the closed configuration.

**[0032]** The middle segment may be translatable from a distal position to a proximal position. As a result, the drive member coupled therewith translates simultaneously from the distal position to the proximal position, and the first and second arms pivot from the open

configuration to the closed configuration. Thus, the clamping assembly transitions from the open configuration to the closed configuration.

[0033] The plunger assembly may include a spring disposed between the middle segment and the drive member. The spring may bias the middle segment distally with respect to the drive member.

[0034] The clamping assembly may include at least one spring coupled to the proximal ends of each of the first and second arms. The at least one spring may bias the first and second arms into the open configuration and the drive member, and middle segment coupled therewith, may be biased into the distal position.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0035] FIG. 1 is a schematic illustration of a surgical system in accordance with the present disclosure;

[0036] FIG. 2 is a perspective view of a robotic arm of the surgical system of FIG. 1;

[0037] FIG. 3 is a front perspective view of a mounting device of the robotic arm of FIG. 2;

[0038] FIG. 4 is a top plan view of the mounting device of FIG. 3, with a cover removed therefrom;

[0039] FIG. 5 is a plane view, with parts separated, of the mounting device of FIG. 4;

[0040] FIG. 6A is a perspective view of an embodiment of a clamping assembly of the mounting device of FIG. 4;

[0041] FIG. 6B is a perspective view, with parts separated, of the clamping assembly of FIG. 6A;

[0042] FIG. 7A is a rear perspective view of another embodiment of the clamping assembly of FIG. 4;

[0043] FIG. 7B is a perspective view, with parts separated, of the clamping assembly of FIG. 7A;

[0044] FIG. 8A is a perspective view of the mounting device of FIG. 4, with the clamping assembly in an unlocked configuration, for receipt of an access device therein; and

[0045] FIG. 8B is a perspective view of the mounting device of FIG. 4, with the clamping assembly in a locked configuration, and with the access device secured therein.

#### **DETAILED DESCRIPTION**

[0046] Embodiments of the present disclosure are described in detail with reference to the drawings, in which like reference numerals designate identical or corresponding elements in each of the several views. As used herein, the term "distal" refers to that portion of a device that is farther from the user, while the term "proximal" refers to that portion of a device that is closer to the user.

[0047] Referring initially to FIG. 1, a surgical system, such as, for example, a robotic surgical system is shown generally as surgical system 1 and generally includes a plurality of robotic arms 2, 3; a control device 4; and an operating console 5 coupled with control device 4. Operating console 5 includes a display device 6, which is set up in particular to display three-dimensional images; and manual input devices 7, 8, by means of which a person (not shown), for example a surgeon, is able to telemanipulate robotic arms 2, 3 in a first operating mode, as known in principle to a person skilled in the art.

[0048] Each of the robotic arms 2, 3 is composed of a plurality of members, which are connected through joints. System 1 also includes a surgical assembly 10 connected to a distal end of each of robotic arms 2, 3. A surgical instrument 20 supporting an end effector 23 may be attached to surgical assembly 10. As illustrated in FIG. 2, and in accordance with any one of several embodiments disclosed herein, the distal end of each robotic arm 2, 3 may further support a surgical mounting device 100, configured to releasably secure an access device therein, as will be described in greater detail below. Surgical mounting device 100 may be configured to receive any number of access tools or instruments, such as, for example, a trocar, surgical port, cannula or retractor.

[0049] Robotic arms 2, 3 may be driven by electric drives (not shown) that are connected to control device 4. Control device 4 (e.g., a computer) is set up to activate the drives, in particular by means of a computer program, in such a way that robotic arms 2, 3, their surgical assemblies 10 and/or surgical instruments 20 execute a desired movement according to a movement defined by means of manual input devices 7, 8. Control device 4 may also be set up in such a way that it regulates movement of robotic arms 2, 3 and/or of the drives.

[0050] Surgical system 1 is configured for use on a patient 13 lying on a patient table 12 to be treated in a minimally invasive manner by means of an end effector. Surgical system 1 may also include more than two robotic arms 2, 3, the additional robotic arms likewise being connected to control device 4 and being telemanipulatable by means of operating console 5. One or more additional surgical assemblies 10 and/or surgical instruments 20 may also be attached to the additional robotic arm.

[0051] Control device 4 may control a plurality of motors (Motor 1...n) with each motor configured to drive a pushing or a pulling of one or more cables such as cables (not shown) coupled to end effector 23 of surgical instrument 20. In use, as these cables are pushed and/or pulled, the one or more cables effect operation and/or movement of end effector 23 of surgical instrument 20. It is contemplated that control device 4 coordinates the activation of the various motors (Motor 1...n) to coordinate a pushing or a pulling motion of one or more cables in order to coordinate an operation and/or movement of one or more end effectors 23. In embodiments, each motor can be configured to actuate a drive rod or a lever arm to effect operation and/or movement of end effectors 23 in addition to, or instead of one or more cables.

[0052] Control device 4 can include any suitable logic control circuit adapted to perform calculations and/or operate according to a set of instructions. Control device 4 can be configured to communicate with a remote system "RS," either via a wireless (e.g., Wi-Fi, Bluetooth, LTE, etc.) and/or wired connection. Remote system "RS" can include data, instructions and/or information related to the various components, algorithms, and/or operations of work station 1. Remote system "RS" can include any suitable electronic service, database, platform, cloud "C" (see FIG. 1), or the like. Control device 4 may include a central processing unit operably

connected to memory. The memory may include transitory type memory (e.g., RAM) and/or non-transitory type memory (e.g., flash media, disk media, etc.). In some embodiments, the memory is part of, and/or operably coupled to, remote system "RS."

**[0053]** Control device 4 can include a plurality of inputs and outputs for interfacing with the components of work station 1, such as through a driver circuit. Control device 4 can be configured to receive input signals and/or generate output signals to control one or more of the various components (e.g., one or more motors) of work station 1. The output signals can include, and/or can be based upon, algorithmic instructions which may be pre-programmed and/or input by a user. Control device 4 can be configured to accept a plurality of user inputs from a user interface (e.g., switches, buttons, touch screen, etc. of operating console 5) which may be coupled to remote system "RS."

**[0054]** A database 14 can be directly and/or indirectly coupled to control device 4. Database 14 can be configured to store pre-operative data from living being(s) and/or anatomical atlas(es). Database 14 can include memory which can be part of, and/or or operatively coupled to, remote system "RS."

**[0055]** Reference may be made to U.S. Patent Publication No. 2012/01 16416, filed on November 3, 201 1, entitled "Medical Workstation," the entire content of which is incorporated herein by reference, for a detailed discussion of the construction and operation of surgical system 1.

**[0056]** As illustrated in FIGS. 2-4, surgical mounting device 100 is coupled to robotic arm 2 (for example), and includes a housing 200 which supports a clamping assembly 400 and a

release mechanism 600, or release mechanisms 650 (FIGS. 7A and 7B). Surgical mounting device 100 is configured to provide an easy and efficient structure to selectively secure a variety of access tools therein, thereby mounting an access device to the robotic arm. Surgical mounting device 100 further enables an access device docked therein to rotate 360 while maintaining secure fixation therein. While it is envisioned that surgical mounting device 100 may be adapted to receive a variety of access device therein, an access device in the form of a trocar "T" (as seen in FIGS. 8A and 8B) will be discussed in detail herein. Through a transition between an open configuration and a closed configuration of clamping assembly 400, trocar "T" may be releasably secured within surgical mounting device 100 such that trocar "T" is secured to robotic arm 2, as discussed below.

[0057] Housing 200 may be made of any suitable material (e.g., stainless steel) such that the clamping assembly 400 and the release mechanism 600 may be securely supported thereon. It is envisioned that housing 200 may be monolithically formed, or alternatively may have a multi-piece construction. Housing 200 includes a proximal portion 210 adapted to couple to a distal end 25 of the surgical arm 2 (FIG. 2), and a distal portion 220 adapted to support clamping assembly 400 and release mechanism 600. The distal portion 220 of housing 200 defines a cavity 230, such that clamping assembly 400 and release mechanism 600 are partially disposed therein, as discussed below.

[0058] A distal surface 221 of distal portion 220 of housing 200 may further define a receiving recess 222 which is configured to complement an exterior profile of an access device (FIGS 8A and 8B), such that the access device may be positioned in near abutment to, or approximated within the distal surface 221 of housing 200. It is envisioned that the receiving

recess 222 may be adapted to complement a variety of access tools enabling surgical mounting device 100 to secure a variety of access tools to robotic arm 2. As illustrated herein, receiving recess 222 defines an arcuate profile which complements the external profile of trocar "T" (FIG. 8A and 8B), such that trocar "T" may be placed in near abutment to, and/or approximated with distal surface 221 of housing 220.

[0059] Clamping assembly 400 extends distally from cavity 230 of housing 200 and is transitionable between an open configuration and a closed configuration. With trocar "T" in near abutment to, or approximated with clamping assembly 400, clamping assembly 400 can be transitioned into the closed configuration such that trocar "T" is releasably secured therein.

[0060] With additional reference to FIG. 5, clamping assembly 400 includes a first arm 410 positioned opposite a second arm 450, and a plunger assembly 480 positioned therebetween. It should be appreciated that first arm 410 is substantially similar to second arm 450, and thus, in the interest of brevity, the discussion of second arm 450 will be omitted and first and second arms 410, 450 will be described herein with like reference numerals.

[0061] First arm 410 includes a proximal portion 412 disposed in the cavity 230 of housing 200 and a distal portion 414 extending distally therefrom. First arm 410 defines a first through-hole 416 at a proximal end 418 thereof and a second through-hole 420 distal to the proximal end 418 thereof. First arm 410 may further define a receiving surface 422, distal of second through-hole 420, disposed on an inner facing surface with respect to second arm 450. It is envisioned that receiving surface 422 is configured to complement an exterior profile of an access device (FIGS 8A and 8B) in a similar fashion as receiving recess 222 of housing 200 discussed above. In this manner, receiving surface 422 of first arm 410, and thus clamping

assembly 400 of surgical mounting device 100, may accommodate a variety of access tools enabling a variety of access tools to be releasably secured to robotic arm 2. As illustrated herein, receiving surface 422 of first arm 410 provides an arcuate profile which complements the external profile of trocar "T" (FIG. 8A and 8B), such that trocar "T" may be received therein.

[0062] First arm 410 may further include a cover or sleeve 424 configured to slidably engage with the distal portion 414 thereof, such that the distal portion 414 is disposed within a channel 426 (shown in phantom) of cover 424. It is envisioned that channel 426 is configured to accommodate a contour of the distal portion 414 of first arm 410, and further, that an exterior contour 428 of cover 424 is configured to mirror the receiving surface 422 of first arm 410. Cover 424 may be secured to first arm 410 by any means known in the art, such as, for example, glue, screws, pins, frictional engagement, etc. As illustrated herein, cover 424 is secured to first arm 410 via a plurality of screws (not shown) which extend through through-holes 432 of cover 424 and a corresponding number of through-holes 434 of first arm 410.

[0063] Cover 424 may further include a protruding ridge, rib, or shoulder 430 disposed along the exterior contour 428 configured to engage a complementary channel, race, or surface of an access device or trocar "T", as illustrated in FIGS. 8A and 8B. It is envisioned that the protruding ridge 430 provides greater ease when positioning, and better fixation when mounting, an access device within the first and second arms 410, 450 of clamping assembly 400.

[0064] Clamping assembly 400 includes at least one link 550 pivotably interconnecting each of the first and second arms 410, 450, in a similar fashion, to drive member 482. Accordingly, only a detailed description of link 550 will be provided herein with reference to first arm 410. Link 550 defines a first through-hole 552 and a second through-hole 554, such

that a cylindrical body, such as, for example, a pin or screw (not shown), may pass therethrough. A first pin "P1" (FIG. 6A) is disposed within the first through-hole 552 of link 550 and within through-hole 490 of drive member 482, such that link 550 is coupled to drive member 482. A second pin "P2" (FIG. 6A) is disposed within the second through-hole 554 of link 550 and within the first through-hole 416 of first arm 410, thereby coupling first arm 410 to link 450 and thus drive member 482. A third pin "P3" (FIG. 4) is disposed within second through-hole 420 of first arm 410 and may be secured to housing 200 at a position proximal to the distal surface 221 of housing 200. It should be appreciated that the first arm 410 second arms 450 of the clamping assembly 400 pivot about second through-hole 420 and the third pin "P3".

**[0065]** Clamping assembly 400 may further include at least one biasing member 535 coupled between the respective second pin "P2" disposed within the first through-hole 416 of the first arm 410 and within the first through-hole 416 of second arm 450. Biasing member 535 provides a biasing force between first and second arms 410, 450, such that first and second arms 410, 450 are pivotably biased into an open position, as discussed below. In an embodiment, a first biasing member 535 is coupled at a first end of second pin "P2", and a second biasing member 535 is coupled at an opposite second end of second pin "P2", such that two biasing members 535 are coupled between the first and second arms 410, 450.

**[0066]** With continued reference to FIGS. 4 and 5, plunger assembly 480 of clamping assembly 400 includes a drive member 482 slidably supported in cavity 230 of the housing 200, and coupled to a middle segment 500, positioned distal to the housing 200 between first and second arms 410, 450. Drive member 482 includes a proximal portion 484, a distal portion 486, and defines a longitudinal through-hole 488 (shown in phantom) extending therethrough. It is

envisioned that distal portion 486 may narrow at the transition to the proximal portion 484, so as to define a notch or shoulder 487 therebetween. A proximal end 485 of the proximal portion 484 may further define a surface 485a to complement and engage with release mechanism 600. For example, surface 485a may be a chamfered or planar surface disposed on either side of the longitudinal through-hole 488, as discussed below.

[0067] Distal portion 486 of drive member 482 further defines a pair of through-holes 490 extending transverse to, and on opposing sides of, the longitudinal through-hole 488. A distal facing surface 492 of the distal portion 486 further includes a conical recess 494 (shown in phantom), such that a diameter of the longitudinal through-hole 488 increases as it approaches the distal facing surface 492 thereof.

[0068] Middle segment 500 of plunger assembly 480 of clamping assembly 400 includes a proximal surface 502, a distal surface 504, and defines a through-hole 506 (shown in phantom). Middle segment 500 may further include a circular base portion 508 extending proximally from the proximal surface 502, with through-hole 506 extending therein. It is envisioned that conical recess 494 of drive member 482 is complementary to the circular base portion 508, such that the circular base 508 may be received therein. Distal surface 504 of middle segment 500 is configured to complement an exterior profile of an access device (FIGS 8A and 8B) in a similar fashion as receiving surface 422 of first arm 420 and receiving recess 222 of housing 200, discussed above, such that distal surface 504, and thus clamping assembly 400 of surgical mounting device 100 may accommodate a variety of access devices. As illustrated herein, distal surface 504 of middle segment 500 provides an arcuate profile which complements the external profile of trocar "T" (FIG. 8A and 8B), such that trocar "T" may be approximated thereto. Distal

surface 504 of middle segment 500 may further include a protruding ridge, rib, or shoulder 510 disposed transverse to the longitudinal through-hole 506 configured to engage a complementary channel, race, or surface of an access device or trocar "T", as illustrated in FIGS. 8A and 8B. Protruding ridge 510 provides greater ease when positioning, and better fixation when mounting, an access device to clamping assembly 400.

**[0069]** Drive member 482 of plunger assembly 580 of clamping assembly 400 may be coupled to middle segment 500 by any means known in the art, such as, for example, a bar or linkage. With drive member 482 coupled to middle segment 500, any movement by one causes a corresponding movement to the other, as discussed below. In an embodiment, drive member 482 and middle segment 500 are coupled to one another via a coupling bar 520. Coupling bar 520 is slidably supported at a proximal end 522 to a distal wall 224 of housing 200 that partially defines cavity 230 thereof, passes through the longitudinal through-hole 488 of the drive member 482, and supports, at a distal end 524 thereof, the middle segment 500 via through-hole 506. It is envisioned that coupling bar 520 may further include a threaded post or stem 526 extending distally from the distal end 524, such that coupling bar 520 can threadably engage with the through-hole 506 of the middle segment 500.

**[0070]** Plunger assembly 480 may further include another biasing member 530 disposed between the distal surface 504, or circular base portion 508, of the middle segment 500 and the conical recess 594 of drive member 482. Biasing member 530 may be disposed about a distal portion 528 of coupling bar 520 such that coupling bar 520 provides radial support to biasing member 530 when undergoing compressive forces. It is envisioned that biasing member 530

biases the middle segment 500 distally, with respect to drive member 482, such that middle segment 500 is biased towards a spaced apart position with respect to drive member 482.

[0071] With reference to FIGS. 4, 5, 8A and 8B, actuation of clamping assembly 400 will be described. As referenced above, clamping assembly 400 is transitionable between an open, or unlocked, configuration (FIG. 8A) and a closed, locked, configuration (FIG. 8B). It should be appreciated that the pivoting of first and second arms 410, 450 and the translation of drive member 482 and middle segment 500 correspond to the transition of the clamping assembly 400 between the open and closed configurations. First and second arms 410, 450 are pivotable about through-hole 420, which corresponds to axis "Y<sub>1</sub>" and "Y<sub>2</sub>" respectively, between a spaced apart position (FIG. 8A) and an approximated position (FIG. 8B) relative to one another. Drive member 482 and middle segment 500 coupled therewith are translatable between a distal position (FIG. 8A) and a proximal position (FIG. 8B) with respect to housing 200, as indicated by arrows "Z<sub>1</sub>" and "Z<sub>2</sub>". In the open configuration of clamping assembly 400, first and second arms 410, 450 are in the spaced apart position and drive member 482 and middle segment 500 are in the distal position (FIG. 8A). In the closed configuration of clamping assembly 400, first and second arms 410, 450 are in the approximated position and drive member 482 and middle segment 500 are in the proximal position (FIG. 8B).

[0072] It should be appreciated that actuation of first arm 410, second arm 450, drive member 482, and middle segment 500 are interconnected. Thus, clamping assembly 400 can be transitioned from the open configuration to the closed configuration by manually pivoting first and second arms 410, 450, about axis "Y<sub>1</sub>" and "Y<sub>2</sub>" respectively, from the spaced apart position to the approximated position, which in turn translates the drive member 482, and middle segment

500 coupled therewith, in the direction of arrow "Z<sub>i</sub>" from the distal position to the proximal position. Clamping assembly 400 can alternatively be transitioned from the open configuration to the closed configuration by manually translating the middle segment 500, and drive member 482 coupled therewith, in the direction of arrow "Z<sub>1</sub>" from the distal position to the proximal position, which in turn pivots the first and second arms 410, 450, about axis "Y<sub>i</sub>" and "Y<sub>2</sub>" respectively, from the spaced apart position to the approximated position. As discussed above, biasing member 535 acts to bias first and second arms 410, 450 into the open position, which is overcome as the clamping assembly 400 transitions into the closed configuration.

[0073] It is envisioned that drive member 482 may be operably coupled with a motor, servo, electro-controller, or any other means known in the art to achieve automated translation of drive member 482 in the direction of arrow "Z<sub>1</sub>". In such an embodiment, a motor (not shown) is coupled to drive member 482 to effectuate the translation of drive member 482 from the distal position to the proximal position. As drive member 482 is translated into the proximal position, the middle segment 500 coupled therewith is translated into the proximal position and first and second arms 410, 450 are pivoted into the approximated position, thus transitioning the clamping assembly 400 into the closed configuration. A controller (not shown) may be included on an external surface of housing 200, disposed on robotic arm 2, or located at a peripheral location such that the motor can be activated remotely. It should be appreciated that the motor can similarly translate drive member 482 into the distal position in the direction of arrow "Z<sub>2</sub>" (FIG. 8B). As the drive member 482 translates distally middle segment 500 coupled therewith is translated into the distal position and first and second arms 410, 450 are pivoted into the spaced apart position, thus transitioning the clamping assembly 400 into the open configuration.

[0074] With further reference to FIGS. 4 and 5, at least one release mechanism 600 may be partially disposed in the cavity 230 of housing 200. Release mechanism 600 includes a contact or cam member 602 disposed in the cavity 230 and which is coupled to an actuation member or button 604. Cam member 602 includes a contact or cam surface 610 configured to complement a surface of the proximal end 485 of the drive member 482, such as, for example, a complementary chamfered surface. Actuation member 604 extends through housing 200 and may include an ergonomic feature thereon. It is envisioned that actuation member 604 may take the form of a push button (as illustrated in FIGS. 4 and 5) or any other suitable geometry such that a portion is disposed external to housing 200. In an embodiment, a biasing member 608 is disposed between actuation member 604 and cam member 602, and/or housing 200 and release mechanism 600, such that cam member 602 is biased to an initial position, as discussed below. Further, cam member 602 and actuation member 604 may be monolithically formed.

[0075] With reference to FIGS. 8A and 8B, release mechanism 600 is actuatable between an initial position (FIG. 8A) and a release position (FIG. 8B). In the initial position the cam surface 610 of release mechanism 600 is spaced away from the proximal end 485 of the drive member 482. In the release position, release mechanism 600 is actuated in the direction of arrow "R" and the contact surface 610 of release mechanism 600 comes into abutment with the proximal end 485 of the drive member 482, such that the drive member 482 is urged to translate into the distal position in the direction of " $Z_2$ ". As the drive member 482 translates to the distal position the middle segment 500 coupled therewith concurrently translates into the distal position and the first and second arms 410, 450 pivot about axis " $Y_1$ " and " $Y_2$ " respectively into the spaced apart position, thus transitioning clamping assembly 400 into the open configuration.

With clamping assembly 400 in the open configuration, the access device previously secured therein can be removed from surgical mounting device 100.

[0076] With reference to FIGS. 7A and 7B, an alternate embodiment of release mechanism 600 is illustrated and referenced as release mechanism 650. Release mechanism 650 may be inset onto a side wall 226 partially defining cavity 230 of housing 200, and includes a hooked portion 652 extending into cavity 230 adapted to engage a surface of the proximal end 485 of drive member 482 in a release position, as discussed below, and an external surface 654 being flush with housing 200 in an initial position (not shown). Release mechanism 650 further defines a through-hole 656 such that release mechanism 650 is pivotable about through-hole 656 and a fourth pin "P4" (FIG. 7A) disposed therein between an initial position and a release position. It is envisioned that the external surface 654 may include an ergonomic feature 656 disposed thereon. In an embodiment, a biasing member (not shown) is coupled to release mechanism 650 such that release mechanism 650 is biased into the initial position. Further, hooked portion 652 and external surface 654 may be monolithically formed.

[0077] Release mechanism 650 is actuatable between an initial position and a release position (not shown). In the initial position, the external surface 654 of release mechanism 650 may be substantially flush with housing 220, and the hooked portion 652 is spaced away from the proximal end 485 of the drive member 482. In the release position, release mechanism 650 is pivoted about pin "P4", such that the hooked portion 652 comes into abutment with the proximal end 485 of the drive member 482. As release mechanism 650 continues to pivot, hooked portion 650 urges drive member 482 to translate into the distal position in the direction of "Z<sub>2</sub>", concurrently causing the middle segment 500 coupled therewith to translate to the distal position

and the first and second arms 410, 450 to pivot about "Y<sub>1</sub>" and "Y<sub>2</sub>", respectively, into the spaced apart position, thus transitioning clamping assembly 400 into the open configuration.

[0078] As discussed above, biasing member 535 acts to bias first and second arms 410, 450 into the open position, and is overcome as the clamping assembly 400 transitions into the closed configuration. During the transition of clamping assembly 400 from the closed configuration to the open configuration, biasing member 535 facilitates the transition by providing a pivotable threshold. As the drive member 482 begins to translate from the proximal position to the distal position, the first and second arms 410, 450 begin to pivot from the approximated position to the spaced apart position. Once first and second arms 410, 450 pivot past the threshold, biasing member 535 springs or biases first and second arms 410, 450 into the spaced apart position. As a result of first and second arms 410, 450 being biased to the spaced apart position by biasing member 535, drive member 482, and middle segment 500 coupled therewith, are concomitantly sprung into the distal position, thus clamping assembly is sprung into the open configuration.

[0079] It is further envisioned that surgical mounting device 100 may include a sensor (not shown) configured to detect if an access device is properly and completely mounted therein. The sensor may be disposed about surgical mounting device 100, such as, for example, in housing 200, between first and second arms 410, 450, or on middle segment 500. The sensor may take any form known in the art, such as, for example, a hall-effect sensor, contact/contactless sensor, or IR beam. It is envisioned that a sensor and/or receiver may be disposed on an access device, which may or may not, be configured to cooperatively

communicate with a corresponding sensor and/or receiver disposed on surgical mounting device 100, such that proper and complete docking may be detected.

[0080] In operation, with housing 200 of surgical mounting device 100 secured to robotic arm 2 and clamping assembly 400 initially placed in the open configuration, an access device is placed between first and second arms 410, 450 and into abutment with middle segment 500. The clamping device 400 is then transitioned to the closed configuration by pivoting first and second arms 410, 450 to the approximated position, and/or depressing or pressing the access device against the middle segment 500. As a result of pivoting first and second arms 410, 450, or depressing middle segment 500, drive member 482 is concurrently translated to the proximal position. As drive member 482, and middle segment 500 coupled therewith, translate proximally, the at least one link 550 coupling each of the first and second arms 410, 450 thereto causes first and second arms 410, 450 to begin pivoting to the approximated position, such that the pivotable threshold created by biasing member 535 of clamping assembly 400 is overcome. It should be appreciated that with drive member 482 in the proximal most position, drive member 482 and link 550 inhibit and prevent first and second arms 410, 450 from pivoting into the spaced apart position.

[0081] More specifically, in the open configuration of clamping assembly 400, the proximal portion 412 of each first and second arm 410, 450 is disposed in the shoulder 487 defined between the proximal portion 484 and the distal portion 486 of drive member 482. Shoulder 487 thus provides a recess for the proximal portion 412 of each first and second arm 410, 450 to reside when first and second arms 410, 450 are in the spaced apart position, and the clamping assembly 400 is in the open configuration. As drive member 482 translates

proximally, link 550 directs the proximal portion 412 of each first and second arm 410, 450 to pivot out of, and away from, shoulder 487 such that first and second arms 410, 450 pivot to the approximated position. With drive member 482 in the proximal most position, first and second arms 410, 450 are inhibited from pivoting to the open position via the positioning of the proximal portion 412 of each first and second arm 410, 450 with respect to the shoulder 487 of drive member 481. Thus, with drive member 482 translated into the proximal most position, middle segment 500 and first and second arms 410, 450 are locked into the proximal and approximated positions, respectively.

**[0082]** To release the access device from surgical mounting device 100, release mechanism 600, 650 is actuated, such that the drive member 482 is urged to translate to the distal position. As drive member 482 is translated distally, middle segment 500 is caused to translate distally and first and second arms 410, 450 are caused to pivot to the open position, thereby transitioning the clamping assembly into the open configuration, as discussed herein.

**[0083]** Persons skilled in the art will understand that the structures and methods specifically described herein and shown in the accompanying figures are non-limiting exemplary embodiments, and that the description, disclosure, and figures should be construed merely as exemplary of particular embodiments. It is to be understood, therefore, that the present disclosure is not limited to the precise embodiments described, and that various other changes and modifications may be effected by one skilled in the art without departing from the scope or spirit of the disclosure. Additionally, the elements and features shown or described in connection with certain embodiments may be combined with the elements and features of certain other embodiments without departing from the scope of the present disclosure, and that such

modifications and variations are also included within the scope of the present disclosure. Accordingly, the subject matter of the present disclosure is not limited by what has been particularly shown and described.

**WHAT IS CLAIMED IS:**

1. A surgical mounting device comprising:

a first arm and a second arm pivotable between a closed configuration in which the first and second arms grip a patient access device inserted therebetween and an open configuration in which a portion of the first and second arms are spaced further apart from each other than in the closed configuration; and

a drive member coupled between the first and second arms, the drive member driving the arms to the closed configuration when the patient access device is inserted between the arms in the open configuration and pressed against the drive member.

2. The surgical mounting device of claim 1, further comprising:

a surgical robotic arm having an end portion positioned near a surgical access site on the patient, the first and second arms protruding from the end portion of the surgical robotic arm; and

a release mechanism biasing the first and the second arms toward the open configuration when actuated.

3. The surgical mounting device of claim 2, wherein the release mechanism defines an actuation pivot point, such that the release mechanism is pivotable between a non-actuated position and an actuated position.

4. The surgical mounting device of claim 2, wherein the release mechanism includes a hooked end cooperatively engaging with a surface of the drive member in an actuated position.

5. The surgical mounting device of claim 2, wherein the release mechanism includes a chamfered profile engaging with a proximal surface of the drive member in an actuated position.

6. The surgical mounting device of claim 2, wherein the release mechanism is biased towards a non-actuated position.

7. The surgical mounting device of claim 6, wherein the release mechanism includes two release mechanisms disposed on opposing sides of the housing, actuation of both biases of the first and the second arms toward the open configuration.

8. The surgical mounting device of claim 6, wherein release mechanism includes two release mechanisms disposed on opposing sides of the housing, actuation of either biases the first and the second arms toward the open configuration.

9. The surgical mounting device of claim 1, wherein the first and second arms have an arcuate surface corresponding to an arcuate surface of the patient access device gripped by the arms.

10. A surgical mounting device for selectively gripping a patient access device therein, the surgical mounting device comprising:

a housing;

a clamping assembly supported in the housing and extending therefrom, the clamping assembly including:

a plunger assembly supported on the housing and including a drive member disposed in the housing coupled to a middle segment disposed distal to the housing, wherein the drive member and middle segment simultaneously translate between a proximal position and a distal position with respect to the housing; and

a first and second arm supported by the housing and including a proximal portion disposed in the housing and a distal portion extending therefrom, each of the first and second arms coupled at the proximal end to the drive member and pivotable with respect to the housing between an open position and a closed position, wherein in the open position the first and second arms are spaced apart relative to one another and in the closed position the first and second arms are in an approximated position relative to one another,

wherein the clamping assembly is transitionable between an unlocked configuration and a locked configuration, such that in the unlocked configuration the drive member and the middle segment are in the distal position and the first and second arms are in the open position, and in the locked configuration the drive member and middle segment are in the proximal position and the first and second arms are in the closed position, and

at least one release mechanism, the at least one release mechanism including:

a contact surface disposed in the housing; and

an articulation member in operative communication with the contact surface, a portion of the articulation member disposed externally from the housing,

wherein the at least one release mechanism is transitionable between an initial position and a release position, such that in the initial position the contact surface is spaced away from the drive member, and in the release position the contact surface is in abutment with the drive member, the release position translating the drive member into the distal position, such that the clamping assembly is transitioned into the unlocked configuration.

11. The surgical mounting device claim 10, wherein the at least one release mechanism including two release mechanisms disposed in opposite sides of the housing.

12. The surgical mounting device of claim 10, wherein each of the first and second arms further include an arcuate surface on the distal portion, and wherein the middle segment further includes an arcuate surface on a distally facing surface.

13. The surgical mounting device of claim 12, wherein the first arm, the second arm, and the middle segment further includes a protruding ridge disposed on each of the arcuate surfaces.

14. The surgical mounting device of claim 10, wherein the clamping assembly further includes at least one biasing member coupled between the proximal end of each of the first and second arms.

15. The surgical mounting device of claim 14, wherein the at least one biasing member bias the first and second arms into the open position, and bias the drive member and middle segment coupled therewith into the distal position.

16. The surgical mounting device of claim 10, wherein each of the first and second arms further include a pivot point disposed distal to the proximal end, such that pivoting the arms from the open position to the closed position translates the drive member and middle segment coupled therewith from the distal position to the proximal position transitioning the clamping assembly into the locked configuration.

17. The surgical mounting device of claim 10, wherein the middle segment translates from the proximal position to the distal position, such that the drive member coupled therewith translates distally and the first and second arms pivot from the open position to the closed position transitioning the clamping assembly into the locked configuration.

18. The surgical mounting device of claim 10, wherein the plunger assembly further includes a biasing member disposed between the middle segment and the drive member, such that the middle segment is biased distally with respect to the drive member.

19. The surgical mounting device of claim 10, wherein the at least one release mechanism further includes a biasing member such that the at least one release mechanism is biased into the initial condition.

20. A method of mounting an access device to a surgical system via a surgical mounting device, the method comprising:

responsive to positioning the access device into abutment with a middle segment situated between a pair of arms extending distally from a housing of the surgical mounting device on opposing sides of the middle segment, translating a driving mechanism slidably disposed in the

housing and operably coupled to the middle segment from a distal position to a proximal position; and

responsive to translating the driving mechanism, pivoting the pair of arms coupled at a proximal end to the drive mechanism from a spaced apart position relative to one another to an approximated position relative to one another.

21. The method of claim 20, wherein the drive mechanism is translated into the proximal position and the pair of arms are pivoted into the approximated position responsive to depressing the middle segment with the access device.

22. The method of claim 20, further comprising gripping the access device with the pair of arms responsive to pivoting the pair of arms while the access device is positioned therebetween.

23. The method of claim 20, further comprising, responsive to translating a release mechanism into a release position:

abutting a contact surface of the release mechanism with the driving mechanism;

translating the driving mechanism into the distal position;

translating the middle segment into the distal position; and

pivoting the pair of arms into the spaced apart configuration.





FIG. 1



**FIG. 2**




FIG. 3




FIG. 4






FIG. 5






**FIG. 6B**



**FIG. 7A**



**FIG. 7B**




FIG. 8A




FIG. 8B

## INTERNATIONAL SEARCH REPORT

International application No.  
**PCT/US2016/035980****A. CLASSIFICATION OF SUBJECT MATTER****A61B 34/30(2016.01)1, A61B 34/00(2016.01)1, A61B 17/34(2006.01)1, A61B 17/29(2006.01)1, A61B 17/068(2006.01)1, A61B 17/00(2006.01)1**

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

A61B 34/30; B65H 5/18; B25B 5/04; A61B 19/00; A61B 17/00; A61B 19/10; A61B 1/01; A61B 34/00; A61B 17/34; A61B 17/29; A61B 17/068

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) &amp; Keywords: mounting, access device, housing, clamping assembly, first arm, second arm, pivotable, drive member, middle segment, translate, closed configuration, open configuration, release mechanism, contact surface, articulation member

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 8182469 B2 (ANDERSON et al.) 22 May 2012 See column 11, line 58 - column 13, line 49; claims 1, 2, 4, 5, 9-13; and figures 9A-14C.	1-23
A	US 2010-0286669 A1 (GREER et al.) 11 November 2010 See paragraphs [0049]- [0052], [0056]- [0070]; and figures 1-23.	1-23
A	US 2014-0180308 A1 (AVATERAMEDICAL GMBH) 26 June 2014 See paragraphs [0060] - [0068]; and figures 1-5.	1-23
A	US 6451027 B1 (COOPER et al.) 17 September 2002 See column 5, line 40 - column 11, line 4; and figures 1-8.	1-23
A	US 5779623 A (BONNELL, LEONARD J.) 14 July 1998 See column 4, line 14 - column 6, line 45; and figures 1-3.	1-23
A	US 5380338 A (CHRISTIAN, STEVEN C.) 10 January 1995 See column 2, line 26 - column 4, line 65; and figures 1-3.	1-23

**I** Further documents are listed in the continuation of Box C. See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

12 September 2016 (12.09.2016)

Date of mailing of the international search report

**12 September 2016 (12.09.2016)**Name and mailing address of the ISA/KR  
International Application Division  
Korean Intellectual Property Office  
189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea

Facsimile No. +82-42-481-8578

Authorized officer

CHO, KI YUN

Telephone No. +82-42-481-5655



**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

**PCT/US2016/035980**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 8182469 B2	22/05/2012	AT 500793 T	15/03/2011
		CA 2273939 AI	18/06/1998
		CA 2273939 C	11/04/2006
		CN 101242788 A	13/08/2008
		CN 101242788 B	13/04/2011
		CN 101242789 A	13/08/2008
		CN 101242789 B	19/10/2011
		CN 101340848 A	07/01/2009
		CN 101340848 B	21/03/2012
		CN 101340852 A	07/01/2009
		CN 101340852 B	28/12/2011
		CN 101426412 A	06/05/2009
		CN 101426412 B	11/12/2013
		CN 102058437 A	18/05/2011
		CN 102058437 B	25/03/2015
		EP 1015068 AI	05/07/2000
		EP 1015068 BI	07/09/2011
		EP 1146830 AI	24/10/2001
		EP 1146830 BI	21/04/2010
		EP 1197902 A2	17/04/2002
		EP 1197902 A3	07/04/2004
		EP 1897511 A2	12/03/2008
		EP 1897511 A3	23/07/2008
		EP 1897511 BI	12/02/2014
		EP 1928342 AI	11/06/2008
		EP 1931275 AI	18/06/2008
		EP 1931275 BI	09/03/2011
		EP 1962711 AI	03/09/2008
		EP 1962711 BI	29/02/2012
		EP 2135577 A2	23/12/2009
		EP 2135577 A3	25/08/2010
		EP 2135637 A2	23/12/2009
		EP 2135637 A3	15/02/2012
		EP 2135637 BI	21/05/2014
		EP 2263592 A2	22/12/2010
		EP 2263592 A3	20/03/2013
EP 2263592 BI	09/12/2015		
EP 2263593 A2	22/12/2010		
EP 2263593 A3	13/03/2013		
EP 2263593 BI	11/03/2015		
EP 2263594 A2	22/12/2010		
EP 2263594 A3	10/04/2013		
EP 2263595 A2	22/12/2010		
EP 2263595 A3	06/03/2013		
EP 2263595 BI	17/09/2014		
EP 2298216 A2	23/03/2011		
EP 2298216 A3	22/10/2014		
EP 2298216 BI	20/04/2016		
EP 2298217 A2	23/03/2011		

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

**PCT/US2016/035980**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		EP 2298217 A3	22/10/2014
		EP 2298218 A2	23/03/2011
		EP 2298218 B1	15/06/2016
		EP 2298219 A2	23/03/2011
		EP 2298219 A3	30/05/2012
		EP 2298219 B1	20/04/2016
		EP 2335635 A1	22/06/2011
		EP 2338432 A1	29/06/2011
		EP 2338432 B1	11/02/2015
		EP 2338433 A1	29/06/2011
		EP 2338433 B1	11/02/2015
		EP 2356951 A1	17/08/2011
		EP 2359769 A1	24/08/2011
		EP 2359769 B1	14/10/2015
		EP 2359770 A1	24/08/2011
		EP 2359770 B1	06/05/2015
		EP 2360708 A1	24/08/2011
		EP 2363091 A2	07/09/2011
		EP 2363091 A3	28/03/2012
		EP 2363091 B1	27/04/2016
		EP 2559396 A2	20/02/2013
		EP 2559396 A3	11/12/2013
		JP 2002-082977 A	22/03/2002
		JP 2002-500524 A	08/01/2002
		JP 2007-167643 A	05/07/2007
		JP 2007-167644 A	05/07/2007
		JP 2007-325959 A	20/12/2007
		JP 2009-509653 A	12/03/2009
		JP 2009-509654 A	12/03/2009
		JP 2009-520573 A	28/05/2009
		JP 2010-214166 A	30/09/2010
		JP 2011-194247 A	06/10/2011
		JP 2012-120884 A	28/06/2012
		JP 2012-125589 A	05/07/2012
		JP 2012-152583 A	16/08/2012
		JP 2012-254360 A	27/12/2012
		JP 2013-027733 A	07/02/2013
		JP 2013-135862 A	11/07/2013
		JP 2013-138965 A	18/07/2013
		JP 2014-076361 A	01/05/2014
		JP 2014-111080 A	19/06/2014
		JP 2014-111081 A	19/06/2014
		JP 2015-062734 A	09/04/2015
		JP 4058113 B2	05/03/2008
		JP 4552296 B2	29/09/2010
		JP 5043414 B2	10/10/2012
		JP 5101519 B2	19/12/2012
		JP 5193049 B2	08/05/2013
		JP 5283241 B2	04/09/2013
		JP 5288609 B2	11/09/2013

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

**PCT/US2016/035980**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		JP 5301607 B2	25/09/2013
		JP 5318826 B2	16/10/2013
		JP 5386602 B2	15/01/2014
		JP 5403864 B2	29/01/2014
		JP 5610547 B2	22/10/2014
		JP 5709318 B2	30/04/2015
		JP 5787374 B2	30/09/2015
		JP 5807974 B2	10/11/2015
		JP 5866123 B2	17/02/2016
		JP 5898105 B2	06/04/2016
		KR 10-0846252 B1	16/07/2008
		KR 10-1207286 B1	03/12/2012
		KR 10-1299472 B1	29/08/2013
		KR 10-1337270 B1	06/12/2013
		KR 10-1337278 B1	09/12/2013
		KR 10-1337281 B1	06/12/2013
		KR 10-2008-0072625 A	06/08/2008
		US 2002-0032451 A1	14/03/2002
		us 2002-0032452 A1	14/03/2002
		us 2002-0072736 A1	13/06/2002
		us 2002-0091374 A1	11/07/2002
		us 2002-0099763 A1	25/07/2002
		us 2003-0083673 A1	01/05/2003
		us 2005-0021050 A1	27/01/2005
		us 2005-0149003 A1	07/07/2005
		us 2006-0015508 A1	19/01/2006
		us 2006-0161136 A1	20/07/2006
		us 2006-0161137 A1	20/07/2006
		us 2006-0161138 A1	20/07/2006
		us 2006-0235436 A1	19/10/2006
		us 2007-0012135 A1	18/01/2007
		us 2007-0119274 A1	31/05/2007
		us 2007-0137372 A1	21/06/2007
		us 2008-0140088 A1	12/06/2008
		us 2008-0147089 A1	19/06/2008
		us 2008-0147091 A1	19/06/2008
		us 2009-0234371 A1	17/09/2009
		us 2009-0248043 A1	01/10/2009
		us 2010-0163057 A1	01/07/2010
		us 2010-0174293 A1	08/07/2010
		us 2010-0200002 A1	12/08/2010
		us 2011-0028990 A1	03/02/2011
		us 2011-0066161 A1	17/03/2011
		us 2012-209291 A1	16/08/2012
		us 6132368 A	17/10/2000
		us 6331181 B1	18/12/2001
		us 6346072 B1	12/02/2002
		us 6491701 B2	10/12/2002
		us 6866671 B2	15/03/2005
		us 6990489 B2	24/01/2006

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

**PCT/US2016/035980**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		US 7048745 B2	23/05/2006
		US 7357774 B2	15/04/2008
		<b>us</b> 7524320 B2	28/04/2009
		<b>us</b> 7580955 B2	25/08/2009
		<b>us</b> 7666191 B2	23/02/2010
		<b>us</b> 7699855 B2	20/04/2010
		<b>us</b> 7727244 B2	01/06/2010
		<b>us</b> 7819885 B2	26/10/2010
		<b>us</b> 7955322 B2	07/06/2011
		<b>us</b> 7963913 B2	21/06/2011
		<b>us</b> 8105338 B2	31/01/2012
		<b>us</b> 8142447 B2	27/03/2012
		<b>us</b> 8202278 B2	19/06/2012
		<b>us</b> 8206406 B2	26/06/2012
		<b>us</b> 8216250 B2	10/07/2012
		<b>us</b> 8608773 B2	17/12/2013
		<b>us</b> 8672922 B2	18/03/2014
		<b>us</b> 8758352 B2	24/06/2014
		<b>wo</b> 00-33755 AI	15/06/2000
		<b>wo</b> 2007-041093 AI	12/04/2007
		<b>wo</b> 2007-041094 AI	12/04/2007
		<b>wo</b> 2007-075844 AI	05/07/2007
		<b>wo</b> 2007-075864 AI	05/07/2007
		<b>wo</b> 2007-126443 A2	08/11/2007
		<b>wo</b> 2007-126443 A3	30/07/2008
		<b>wo</b> 2007-142698 A2	13/12/2007
		<b>wo</b> 2007-142698 A3	21/02/2008
		<b>wo</b> 2009-061915 A2	14/05/2009
		<b>wo</b> 98-25666 AI	18/06/1998
US 2010-0286669 AI	11/11/2010	CA 2684559 AI	05/03/2009
		EP 2211748 A2	04/08/2010
		EP 2211748 A4	12/03/2014
		JP 2010-531672 A	30/09/2010
		<b>wo</b> 2009-027848 A2	05/03/2009
		<b>wo</b> 2009-027848 A3	28/04/2011
US 2014-0180308 AI	26/06/2014	CN 104869936 A	26/08/2015
		DE 102012025101 AI	26/06/2014
		EP 2934362 AI	28/10/2015
		HK 1211823 AI	03/06/2016
		JP 2016-505316 A	25/02/2016
		<b>wo</b> 2014-094719 AI	26/06/2014
US 6451027 BI	17/09/2002	None	
US 5779623 A	14/07/1998	US 5540649 A	30/07/1996
US 5380338 A	10/01/1995	<b>wo</b> 94-05215 AI	17/03/1994