



US009271206B2

(12) **United States Patent**
Erceg et al.

(10) **Patent No.:** **US 9,271,206 B2**
(45) **Date of Patent:** ***Feb. 23, 2016**

(54) **MULTISERVICE COMMUNICATION DEVICE WITH DEDICATED CONTROL CHANNEL**

(71) Applicant: **BROADCOM CORPORATION**, Irvine, CA (US)

(72) Inventors: **Vinko Erceg**, Cardiff by the Sea, CA (US); **John Walley**, Ladera Ranch, CA (US); **Arya Reza Behzad**, Poway, CA (US); **David Rosmann**, Irvine, CA (US); **Brima B. Ibrahim**, Laguna Hills, CA (US); **Jeyhan Karaoguz**, Irvine, CA (US)

(73) Assignee: **Broadcom Corporation**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 207 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/949,812**

(22) Filed: **Jul. 24, 2013**

(65) **Prior Publication Data**

US 2013/0308603 A1 Nov. 21, 2013

Related U.S. Application Data

(63) Continuation of application No. 12/264,379, filed on Nov. 4, 2008, now Pat. No. 8,521,222.

(51) **Int. Cl.**

H04M 1/00 (2006.01)
H04W 36/14 (2009.01)
H04W 36/00 (2009.01)
H04W 8/24 (2009.01)
H04W 76/02 (2009.01)
H04W 88/06 (2009.01)

(52) **U.S. Cl.**

CPC **H04W 36/14** (2013.01); **H04W 36/0066** (2013.01); **H04W 8/245** (2013.01); **H04W 76/026** (2013.01); **H04W 88/06** (2013.01)

(58) **Field of Classification Search**

CPC H04W 80/04; H04W 80/05; H04W 80/06; H04W 80/07; H04W 80/08; H04W 72/04; H04W 72/05; H04W 72/06

USPC 370/328-332, 338, 241; 455/553.1, 455/436-444, 552.1

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0113128 A1* 5/2005 Bahl et al. 455/522
2006/0015674 A1 1/2006 Murotake
2007/0082632 A1* 4/2007 Liu 455/161.1

* cited by examiner


Primary Examiner — Dady Chery

(74) *Attorney, Agent, or Firm* — Garlick & Markison; Bruce E. Stuckman

(57) **ABSTRACT**

A multiservice communication device includes a plurality of transceivers that wirelessly transceive data with a corresponding plurality of networks in accordance with a corresponding plurality of network protocols. A control channel transceiver transceives control channel data with a remote management unit including local control data sent to the management unit and remote control data received from the management unit. A processing module processes the remote control data and generates a least one control signal in response thereto, the at least one control signal for adapting at least one of the plurality of transceivers based on the remote control data.

20 Claims, 34 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3





FIG. 4



RF transceiver 123

FIG. 5






FIG. 6






FIG. 9




FIG. 11

FIG. 10

FIG. 12




FIG. 13




FIG. 14






FIG. 15






FIG. 18




FIG. 19




FIG. 21




FIG. 20




FIG. 23




FIG. 22




FIG. 25




FIG. 24




FIG. 27




FIG. 26




FIG. 28




FIG. 29

FIG. 30




FIG. 33




FIG. 31




FIG. 32




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 40




FIG. 39




FIG. 42




FIG. 43




FIG. 41




FIG. 45





FIG. 44








FIG. 47









FIG. 50



MULTISERVICE COMMUNICATION DEVICE WITH DEDICATED CONTROL CHANNEL

CROSS-REFERENCE TO RELATED APPLICATIONS

The present U.S. Utility patent application claims priority pursuant to 35 U.S.C. §120, as a continuation, to the U.S. Utility patent application Ser. No. 12/264,379, entitled MULTISERVICE COMMUNICATION DEVICE WITH DEDICATED CONTROL CHANNEL, filed on Nov. 4, 2008, which is hereby incorporated herein by reference in its entirety and made part of the present U.S. Utility patent application for all purposes.

The present application is related to copending applications:

Ser. No. 12/264,372, entitled MULTISERVICE COMMUNICATION DEVICE WITH DEDICATED ENVIRONMENTAL MONITORING, filed on Nov. 4, 2008, issued as U.S. Pat. No. 8,467,305 on Jun. 18, 2013;

Ser. No. 12/264,419, entitled MULTISERVICE COMMUNICATION DEVICE WITH LOGICAL CONTROL CHANNEL, filed on Nov. 4, 2008, issued as U.S. Pat. No. 8,265,690 on Sep. 11, 2012;

Ser. No. 12/264,426, entitled MULTISERVICE COMMUNICATION DEVICE WITH COGNITIVE RADIO TRANSCEIVER, filed on Nov. 4, 2008, issued as U.S. Pat. No. 8,358,978 on Jan. 22, 2013;

Ser. No. 12/264,434, entitled MANAGEMENT UNIT FOR MANAGING A PLURALITY OF MULTISERVICE COMMUNICATION DEVICES, filed on Nov. 4, 2008, issued as U.S. Pat. No. 8,131,220 on Mar. 6, 2012;

Ser. No. 12/264,442, entitled MANAGEMENT UNIT NETWORK FOR MANAGING A PLURALITY OF MULTISERVICE COMMUNICATION DEVICES, filed on Nov. 4, 2008, abandoned;

Ser. No. 12/264,449, entitled SERVICE AGGREGATOR FOR ALLOCATING RESOURCES TO A PLURALITY OF MULTISERVICE COMMUNICATION DEVICES, filed on Nov. 4, 2012, issued as U.S. Pat. No. 8,185,099 on May 22, 2012;

Ser. No. 12/264,454, entitled MANAGEMENT UNIT FOR FACILITATING INTER-NETWORK HAND-OFF FOR A MULTISERVICE COMMUNICATION DEVICE, filed on Nov. 4, 2008, issued as U.S. Pat. No. 8,195,143 on Jun. 5, 2012;

Ser. No. 12/264,459, entitled MANAGEMENT UNIT WITH LOCAL AGENT, filed on Nov. 4, 2008, issued as U.S. Pat. No. 8,923,774 on Dec. 30, 2014;

Ser. No. 12/264,472, entitled MANAGEMENT UNIT NETWORK FOR COLLABORATIVELY MANAGING A PLURALITY OF MULTISERVICE COMMUNICATION DEVICES, filed on Nov. 4, 2008, issued as U.S. Pat. No. 8,855,025 on Oct. 7, 2014;

the contents of which are incorporated herein by reference thereto.

BACKGROUND OF THE INVENTION

1. Technical Field of the Invention

This invention relates generally to communication devices and more particularly to the communication devices that communicate with multiple networks in multiple frequency bands.

2. Description of Related Art

Wireless communication systems are known to support wireless communications between wireless communication

devices affiliated with the system. Such wireless communication systems range from national and/or international cellular telephone systems to point-to-point in-home wireless networks. Each type of wireless communication system is constructed, and hence operates, in accordance with one or more standards. Such wireless communication standards include, but are not limited to IEEE 802.11, 802.15, 802.16, long term evolution (LTE), Bluetooth, advanced mobile phone services (AMPS), digital AMPS, global system for mobile communications (GSM), code division multiple access (CDMA), wireless application protocols (WAP), local multi-point distribution services (LMDS), multi-channel multi-point distribution systems (MMDS), and/or variations thereof.

An IEEE 802.11 compliant wireless communication system includes a plurality of client devices (e.g., laptops, personal computers, personal digital assistants, etc., coupled to a station) that communicate over a wireless link with one or more access points. As is also generally understood in the art, many wireless communications systems employ a carrier-sense multiple access (CSMA) protocol that allows multiple communication devices to share the same radio spectrum. Before a wireless communication device transmits, it "listens" to the wireless link to determine if the spectrum is in use by another station to avoid a potential data collision. In other systems, transmissions can be scheduled using management frames or power save multi-poll (PSMP), for example. In many cases, the transmitting device (e.g., a client device or access point) transmits at a fixed power level regardless of the distance between the transmitting device and a targeted device (e.g., station or access point). Typically, the closer the transmitting device is to the targeted device, the less error there will be in the reception of the transmitted signal.

A cognitive radio is a wireless communication device that can adjust transmission or reception parameters to communicate efficiently to avoiding interference. This alteration of parameters can be based on the active monitoring of several factors in the external and internal radio environment, such as radio frequency spectrum, user behavior and network state.

When one or more of these communication devices is mobile, its transmit and receive characteristics can change with the motion of the device, as it moves closer or farther from a device it is communication with, and as the transmission environment changes due to the devices position with respect to reflecting members, interfering stations, noise sources, etc.

The limitations and disadvantages of conventional and traditional approaches will become apparent to one of ordinary skill in the art through comparison of such systems with the present invention.

BRIEF SUMMARY OF THE INVENTION

The present invention is directed to apparatus and methods of operation that are further described in the following Brief Description of the Drawings, the Detailed Description of the Invention, and the claims. Other features and advantages of the present invention will become apparent from the following detailed description of the invention made with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

FIG. 1 is a schematic block diagram of an embodiment of a communication system in accordance with the present invention;

3

FIG. 2 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 3 presents a pictorial representation of a wireless network 111 in accordance with an embodiment of the present invention.

FIG. 4 is a schematic block diagram of an embodiment of a communication device 125 in accordance with the present invention;

FIG. 5 is a schematic block diagram of an embodiment of an RF transceiver 123 in accordance with the present invention;

FIG. 6 is a schematic block diagram of another embodiment of a communication device 125 in accordance with the present invention;

FIG. 7 is a graphical representation of a spectrum 210 in accordance with an embodiment of the present invention.

FIG. 8 is a graphical representation of a spectrum 220 in accordance with an embodiment of the present invention.

FIG. 9 is a schematic block diagram of an embodiment of an RF receiver 127' in accordance with the present invention;

FIG. 10 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 11 is a schematic block diagram representation of a portion of a protocol stack in accordance with an embodiment of the present invention.

FIG. 12 is a schematic block diagram representation of network protocol packet in accordance with an embodiment of the present invention.

FIG. 13 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 14 is a schematic block diagram of another embodiment of a communication device 125 in accordance with the present invention;

FIG. 15 is a schematic block diagram of another embodiment of an RF transceiver 123' in accordance with the present invention;

FIG. 16 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 17 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 18 is a schematic block diagram of an embodiment of an RF transceiver 123" in accordance with the present invention;

FIG. 19 is a schematic block diagram of an embodiment of an RF transceiver 123'" in accordance with the present invention;

FIG. 20 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 21 is a schematic block diagram of an embodiment of a management unit in accordance with the present invention;

FIG. 22 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 23 is a schematic block diagram of another embodiment of a management unit in accordance with the present invention;

FIG. 24 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

4

FIG. 25 is a schematic block diagram of another embodiment of a management unit in accordance with the present invention;

FIG. 26 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 27 is a schematic block diagram of another embodiment of a management unit in accordance with the present invention;

FIG. 28 is a schematic block diagram of an embodiment of a management network in accordance with the present invention;

FIG. 29 is a schematic block diagram of another embodiment of a management unit in accordance with the present invention;

FIG. 30 is a schematic block diagram of another embodiment of a management unit in accordance with the present invention;

FIG. 31 is a schematic block diagram of an embodiment of a processing module 225 in accordance with the present invention;

FIG. 32 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 33 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 34 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention;

FIG. 35 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 36 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 37 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 38 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 39 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 40 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 41 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 42 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 43 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 44 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 45 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 46 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 47 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 48 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 49 is a flow chart of an embodiment of a method in accordance with the present invention;

FIG. 50 is a flow chart of an embodiment of a method in accordance with the present invention; and

FIG. 51 is a flow chart of an embodiment of a method in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 is a schematic block diagram of an embodiment of a communication system in accordance with the present

5

invention. In particular a communication system is shown that includes a communication device **10** that communicates real-time data **24** and/or non-real-time data **26** wirelessly with one or more other devices such as base station **18**, non-real-time device **20**, real-time device **22**, and non-real-time and/or real-time device **25** of networks **2** and **4**. In addition, communication device **10** can also optionally communicate over a wireline connection with non-real-time device **12**, real-time device **14** and non-real-time and/or real-time device **16**.

In an embodiment of the present invention the wireline connection **28** can be a wired connection that operates in accordance with one or more standard protocols, such as a universal serial bus (USB), Institute of Electrical and Electronics Engineers (IEEE) 488, IEEE 1394 (Firewire), Ethernet, small computer system interface (SCSI), serial or parallel advanced technology attachment (SATA or PATA), or other wired communication protocol, either standard or proprietary. The wireless connections can communicate in accordance with a wireless network protocol such as IEEE 802.11, Bluetooth, Ultra-Wideband (UWB), WIMAX, or other wireless network protocol, a wireless telephony data/voice protocol such as Global System for Mobile Communications (GSM), General Packet Radio Service (GPRS), Enhanced Data Rates for Global Evolution (EDGE), Personal Communication Services (PCS), WCDMA, LTE or other mobile wireless protocol or other wireless communication protocol, either standard or proprietary. Further, the wireless communication paths can include separate transmit and receive paths that use separate carrier frequencies and/or separate frequency channels. Alternatively, a single frequency or frequency channel can be used to bi-directionally communicate data to and from the communication device **10**.

Communication device **10** can be a mobile phone such as a cellular telephone, a personal digital assistant, game console, game device, personal computer, laptop computer, wireless display or other device that performs one or more functions that include communication of voice and/or data via wireline connection **28** and/or the wireless communication paths. In an embodiment of the present invention, the real-time and non-real-time devices **12**, **14**, **16**, **20**, **22** and **25** can be base stations, access points, terminals, personal computers, laptops, PDAs, storage devices, cable replacements, bridge/hub devices, wireless HDMI devices, mobile phones, such as cellular telephones, devices equipped with wireless local area network or Bluetooth transceivers, FM tuners, TV tuners, digital cameras, digital camcorders, or other devices that either produce, process or use audio, video signals or other data or communications.

In operation, the communication device includes one or more applications that include voice communications such as standard telephony applications, voice-over-Internet Protocol (VoIP) applications, local gaming, Internet gaming, email, instant messaging, multimedia messaging, web browsing, audio/video recording, audio/video playback, audio/video downloading, playing of streaming audio/video, office applications such as databases, spreadsheets, word processing, presentation creation and processing and other voice and data applications. In conjunction with these applications, the real-time data **26** includes voice, audio, video and multimedia applications including Internet gaming, etc. The non-real-time data **24** includes text messaging, email, web browsing, file uploading and downloading, etc.

In an embodiment of the present invention, communication device **10** can be a multiservice device that is capable of communicating real time and/or non-real-time data wirelessly with multiple networks such as networks **2** and **4** either contemporaneously or non-contemporaneously. This multi-

6

service functionality can include the ability to engage in communications over multiple networks, to choose the best network or have the best network chosen for it for engaging in a particular communication. For example, communication device **10** wishing to place a telephone call may launch a traditional telephone call with a remote caller over a cellular telephone network via a cellular voice protocol, a voice over IP call over a data network via a wireless local area network protocol, or on a peer-to-peer basis with another communication device via a Bluetooth protocol. In another example, communication device **10** wishing to access a video program might receive a streaming video signal over a cellular telephone network via a cellular data protocol, receive a direct broadcast video signal, download a podcast video signal over a data network via a wireless local area network protocol, etc.

In an embodiment of the present invention, the communication device **10** includes an integrated circuit, such as an RF integrated circuit that includes one or more features or functions of the present invention. Such integrated circuits shall be described in greater detail in association with FIGS. **3-51** that follow.

FIG. **2** is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular, FIG. **2** presents a communication system that includes many common elements of FIG. **1** that are referred to by common reference numerals. Communication device **30** is similar to communication device **10** and is capable of any of the applications, functions and features attributed to communication device **10**, as discussed in conjunction with FIG. **1**. However, communication device **30** includes two or more separate wireless transceivers for communicating, contemporaneously, via two or more wireless communication protocols with data device **32** and/or data base station **34** of network **6** via RF data **40** and voice base station **36** and/or voice device **38** of network **8** via RF voice signals **42**.

FIG. **3** presents a pictorial representation of wireless networks **107** in accordance with an embodiment of the present invention. The wireless network **111**, includes an access point **110** that is coupled to packet switched backbone network **101**. The access point **110** manages communication flow over the wireless network **111** destined for and originating from each of communication devices **91**, **93**, **97** and **125**. Via the access point **110**, each of the communication devices **91**, **93**, **97** and **125** can access service provider network **105** and Internet **103** to, for example, surf web-sites, download audio and/or video programming, send and receive messages such as text messages, voice message and multimedia messages, access broadcast, stored or streaming audio, video or other multimedia content, play games, send and receive telephone calls, and perform any other activities, provided directly by access point **110** or indirectly through packet switched backbone network **101**.

One or more of the communication devices **91**, **93**, **97** and **125**, such as communication device **125** is a mobile device that can include the functionality of communication devices **10** or **30**. In addition, communication device **125** can engage in communications via one or more other networks **2**, **4**, **6** or **8** as discussed in conjunction with FIGS. **1** and **2**.

FIG. **4** is a schematic block diagram of an embodiment of a communication device **125** in accordance with the present invention. In particular, integrated circuit (IC) **50** is shown that implements communication device **125** in conjunction with microphone **60**, keypad/keyboard **58**, memory **54**, speaker/headset interface **62**, display **56**, camera **76**, antenna interfaces **72 . . . 72'**, and wireline port **64**. In operation, RF IC **50** includes a plurality of wireless transceivers such as trans-

ceivers **73** and **73'** having RF and baseband modules for sending and receiving data such as RF real-time data **26** and non-real-time data **24** and transmitting via antenna interfaces **72 . . . 72'** and antennas. Each antenna can be a fixed antenna, a single-input single-output (SISO) antenna, a multi-input multi-output (MIMO) antenna, a diversity antenna system, an antenna array that allows the beam shape, gain, polarization or other antenna parameters to be controlled or other antenna configuration. In addition, IC **50** includes input/output module **71** that includes the appropriate interfaces, drivers, encoders and decoders for communicating via the wireline connection **28** via wireline port **64**, an optional memory interface for communicating with off-chip memory **54**, a codec for encoding voice signals from microphone **60** into digital voice signals, a keypad/keyboard interface for generating data from keypad/keyboard **58** in response to the actions of a user, a display driver for driving display **56**, such as by rendering a color video signal, text, graphics, or other display data, and an audio driver such as an audio amplifier for driving speaker **62** and one or more other interfaces, such as for interfacing with the camera **76** or the other peripheral devices.

Power management circuit (PMU) **95** includes one or more DC-DC converters, voltage regulators, current regulators or other power supplies for supplying the IC **50** and optionally the other components of communication device **10** and/or its peripheral devices with supply voltages and or currents (collectively power supply signals) that may be required to power these devices. Power management circuit **95** can operate from one or more batteries, line power, an inductive power received from a remote device, a piezoelectric source that generates power in response to motion of the integrated circuit and/or from other power sources, not shown. In particular, power management module **95** can selectively supply power supply signals of different voltages, currents or current limits or with adjustable voltages, currents or current limits in response to power mode signals received from the IC **50**. While shown as an off-chip module, PMU **95** can be alternatively implemented as an on-chip circuit.

In addition, IC **50** may include a location generation module **48** that generates location or motion parameters based on the location or motion of the device such as a longitude, latitude, altitude, address, velocity, velocity vector, acceleration (including deceleration), and/or other location or motion parameter. Location generation module **48** can include a global positioning system (GPS) receiver, one or more accelerometers, gyroscopes or positioning sensors, a device that operates via triangulation data received via the network, or other location generation devices that generate or receive such location or motion parameters.

In operation, the RF transceivers **73 . . . 73'** generate outbound RF signals from outbound data and generate inbound data from inbound RF signals to communication with a plurality of networks, such as networks **2, 4, 6, 8**, etc. In an embodiment of the present invention, the IC **50** is a system on a chip integrated circuit that includes at least one processing device. Such a processing device, for instance, processing module **225**, may be a microprocessor, micro-controller, digital signal processor, microcomputer, central processing unit, field programmable gate array, programmable logic device, state machine, logic circuitry, analog circuitry, digital circuitry, and/or any device that manipulates signals (analog and/or digital) based on operational instructions. The associated memory may be a single memory device or a plurality of memory devices that are either on-chip or off-chip such as memory **54**. Such a memory device may be a read-only memory, random access memory, volatile memory, non-volatile memory, static memory, dynamic memory, flash memory,

and/or any device that stores digital information. Note that when the IC **50** implements one or more of its functions via a state machine, analog circuitry, digital circuitry, and/or logic circuitry, the associated memory storing the corresponding operational instructions for this circuitry is embedded with the circuitry comprising the state machine, analog circuitry, digital circuitry, and/or logic circuitry.

Also note that while certain modules of communication device **125** are shown to be included on IC **50** while others are not, IC **50** is shown for illustrative purposes and may include more or less of the modules of communication device **125**, depending on the particular implementation. Further, communication device **125** can include additional modules or fewer modules than those specifically shown. In operation, the IC **50** executes operational instructions that implement one or more of the applications (real-time or non-real-time) attributed to communication devices **125** as discussed above and in conjunction with FIGS. **1-3**.

FIG. **5** is a schematic block diagram of an embodiment of RF transceiver **123**, such as transceiver **73** or **73'**, in accordance with the present invention. The RF transceiver **123** includes an RF transmitter **129**, and an RF receiver **127**. The RF receiver **127** includes a RF front end **140**, a down conversion module **142** and a receiver baseband processing module **144** that operate under the control of control signals **141**. The RF transmitter **129** includes a transmitter baseband processing module **146**, an up conversion module **148**, and a radio transmitter front-end **150** that also operate under control of control signals **141**.

As shown, the receiver and transmitter are each coupled to an antenna through an antenna interface **171** and a diplexer (duplexer) **177**, such as antenna interface **72** or **74**, that couples the transmit signal **155** to the antenna to produce outbound RF signal **170** and couples inbound signal **152** to produce received signal **153**. Alternatively, a transmit/receive switch can be used in place of diplexer **177**. While a single antenna is represented, the receiver and transmitter may share a multiple antenna structure that includes two or more antennas. In another embodiment, the receiver and transmitter may share a multiple input multiple output (MIMO) antenna structure, diversity antenna structure, phased array or other controllable antenna structure that includes a plurality of antennas. Each of these antennas may be fixed, programmable, and antenna array or other antenna configuration.

In operation, the transmitter receives outbound data **162** from other portions of its a host device, such as a communication application executed by processing module **225** or other source via the transmitter processing module **146**. The transmitter processing module **146** processes the outbound data **162** in accordance with a particular wireless communication standard (e.g., IEEE 802.11, Bluetooth, RFID, GSM, CDMA, et cetera) to produce baseband or low intermediate frequency (IF) transmit (TX) signals **164** that contain outbound data **162**. The baseband or low IF TX signals **164** may be digital baseband signals (e.g., have a zero IF) or digital low IF signals, where the low IF typically will be in a frequency range of one hundred kilohertz to a few megahertz. Note that the processing performed by the transmitter processing module **146** can include, but is not limited to, scrambling, encoding, puncturing, mapping, modulation, and/or digital baseband to IF conversion.

The up conversion module **148** includes a digital-to-analog conversion (DAC) module, a filtering and/or gain module, and a mixing section. The DAC module converts the baseband or low IF TX signals **164** from the digital domain to the analog domain. The filtering and/or gain module filters and/or adjusts the gain of the analog signals prior to providing it to

the mixing section. The mixing section converts the analog baseband or low IF signals into up-converted signals **166** based on a transmitter local oscillation.

The radio transmitter front end **150** includes a power amplifier and may also include a transmit filter module. The power amplifier amplifies the up-converted signals **166** to produce outbound RF signals **170**, which may be filtered by the transmitter filter module, if included. The antenna structure transmits the outbound RF signals **170** to a targeted device such as a RF tag, base station, an access point and/or another wireless communication device via an antenna interface **171** coupled to an antenna that provides impedance matching and optional bandpass filtration.

The receiver receives inbound RF signals **152** via the antenna and off-chip antenna interface **171** that operates to process the inbound RF signal **152** into received signal **153** for the receiver front-end **140**. In general, antenna interface **171** provides impedance matching of antenna to the RF front-end **140**, optional bandpass filtration of the inbound RF signal **152** and optionally controls the configuration of the antenna in response to one or more control signals **141** generated by processing module **225**.

The down conversion module **142** includes a mixing section, an analog to digital conversion (ADC) module, and may also include a filtering and/or gain module. The mixing section converts the desired RF signal **154** into a down converted signal **156** that is based on a receiver local oscillation, such as an analog baseband or low IF signal. The ADC module converts the analog baseband or low IF signal into a digital baseband or low IF signal. The filtering and/or gain module high pass and/or low pass filters the digital baseband or low IF signal to produce a baseband or low IF signal **156**. Note that the ordering of the ADC module and filtering and/or gain module may be switched, such that the filtering and/or gain module is an analog module.

The receiver processing module **144** processes the baseband or low IF signal **156** in accordance with a particular wireless communication standard (e.g., IEEE 802.11, Bluetooth, RFID, GSM, CDMA, et cetera) to produce inbound data **160**. The processing performed by the receiver processing module **144** includes, but is not limited to, digital intermediate frequency to baseband conversion, demodulation, demapping, depuncturing, decoding, and/or descrambling.

Further, processing module **225** generates one or more control signals **141** to configure or adapt the RF transceiver **123** to communication with one or more of the networks **2**, **4**, **6** and **8**. In operation, processing module **225** generates control signals **141** to modify the transmit and/or receiver parameters of the RF transceiver **123** such as protocol parameters, data rates, modulation types and other data parameters used by receiver processing module **144** and transmitter processing module **146**, frequency bands, channels and bandwidths, filter settings, gains, power levels, ADC and DAC parameters, and other parameters used by RF front-end **140**, radio transmitter front-end **150**, down conversion module **142** and up conversion module **148**, as well as antenna configurations used by antenna interface **171** to set the beam pattern, gain, polarization or other antenna configuration of the antenna.

The control signals **141** can be analog signals, digital signals, discrete-time signals of other signals that control the modules of RF transceiver **123** to adapt to communication via different networks. For example, in one mode of operation, communication device **125** includes a plurality of different transceivers **73 . . . 73'**, that are each designed and implemented by a particular RF transceiver **123** for communicating with one of the plurality of networks **2**, **4**, **6** and/or **8**. Each of these RF transceivers **123** can be selectively enabled or dis-

abled via control signals **141** to operate under the control of processing module **225** to communicate with its corresponding network **2**, **4**, **6** or **8** when required. In another embodiment of the present invention one or more of the transceivers **73 . . . 73'** is implemented via a cognitive radio transceiver or other flexible RF transceiver **123** that can be configured to communicate with different networks based on a selected mode of operation. For example, such a flexible RF transceiver **123** can be configured to operate as either a Bluetooth transceiver, a GSM transceiver or a 802.11g transceiver based on the generation of the control signals **141** to implement the corresponding transmit and receive characteristics. Further details regarding particular conditions for generating control signals **141** will be discussed in conjunction with FIGS. **6-51** that follow.

FIG. **6** is a schematic block diagram of another embodiment of a communication device **125** in accordance with the present invention. In particular, a communication device is shown that includes many common elements shown in conjunction with FIG. **4**. In this embodiment however, IC **50** includes an optional receiver **77**, such as an environmental monitoring receiver, that can evaluate the RF environment via an analysis of RF signal spectrum **203**.

In particular, communication device **125** includes a plurality of transceivers **73** that wirelessly transceive data with a corresponding plurality of networks, such as networks **2**, **4**, **6**, **8**, etc. in accordance with a corresponding plurality of network protocols. Receiver **77** receives and processes received RF signals, over a broadband spectrum, such as RF signal spectrum **203** and generates environmental data in response thereto. Processing module **225** processes the environmental data and generates one or more control signals **141** in response thereto for adapting the transceivers **73** based on the environmental data.

In operation, receiver **77** analyzed an RF spectrum that encompasses the frequency bands used by each of the transceivers **73** including optional frequency bands that can be used by each of these transceivers. The environmental data can identify unused spectrum, used spectrum, desired channels, undesired channels, noise and interference, that can be used to adapt the transceivers **73** to more favorable conditions.

In one example, when conditions with respect to a particular frequency channel begin to deteriorate or otherwise a better frequency channel is found by receiver **77** for use by one of the plurality of transceivers **73**, processing module **225** can generate control signals **141** and outbound data to coordinate with a remote station via control signaling and to switch the new frequency channel and to change the transceiver **73** to the new frequency channel. In another example, when communications with a particular network begin to deteriorate or otherwise a better network is found by receiver **77** for use by communication device **125**, processing module **225** can generate control signals **141** and outbound data to coordinate a handoff to a new network or a new network device and either adapt a transceiver **73** to the new network or switch the transceiver **73** in use to a transceiver adapted for communication with the new network or network device. In addition, transceiver **73** can take on the function of receiver **77** during idle periods. In a further example, when communication conditions, such as noise and interference change for a particular transceiver, processing module **225** can generate control signals **141** to modify a transmission parameter and/or a receive parameter of the transceiver **73** to adapt to the change in conditions.

FIG. **7** is a graphical representation of a spectrum **210** in accordance with an embodiment of the present invention. In

particular, spectrum **210** represents an example of an RF signal spectrum **203** received by an environmental monitoring receiver, such as receiver **77**. In an embodiment of the present invention, the receiver **77** receives and analyses the RF signal spectrum and can identify unused portions of spectrum, such as available spectrum **212**, based on the lack of signal energy in these spectra. In addition, receiver **77** can identify undesired channels, by identifying regions with unacceptable levels of noise and interference **214** based on signal to noise ratios, signal to noise and interference ratios, packet error rates, data rates, etc.

FIG. **8** is a graphical representation of a spectrum **220** in accordance with an embodiment of the present invention. In particular, spectrum **220** represents another example of an RF signal spectrum **203** received by an environmental monitoring receiver, such as receiver **77**. In addition to the functions and features described in conjunction with FIG. **7**, receiver **77** can identify desired channels, such as desired channel **222**, also based the availability of remote stations with available capacity to service the communication device **125**. In particular, desired channels can be identified based on the presence of strong beacon signals or other communications from remote devices indicating that a network is present and that signals can be received with acceptable levels of noise and/or interference.

FIG. **9** is a schematic block diagram of an embodiment of an RF receiver **127'** in accordance with the present invention. RF receiver **127'**, such as receiver **77**, shares many common elements with RF receiver **127** that are referred to by common reference numerals. Receiver **127'** can be implemented via a dedicated radio receiver, or as a cognitive radio transceiver or other flexible transceiver, such as one of the transceivers **73** configured to operate via control signals **141** as an environmental monitoring transceiver in an environmental monitoring mode of operation. In operation, RF receiver **127'** receives inbound RF signals **152** via the antenna and off-chip antenna interface **171** that operates to process the inbound RF signal **152** into received signal **153** for the receiver front-end **140**. In general, antenna interface **171** provides impedance matching of antenna to the RF front-end **140**, optional bandpass filtration of the inbound RF signal **152** and optionally controls the configuration of the antenna in response to one or more control signals **141** generated by processing module **225**.

The down conversion module **142** includes a mixing section, an analog to digital conversion (ADC) module, and may also include a filtering and/or gain module. The mixing section converts the desired RF signal **154** into a down converted signal **156** that is based on a receiver local oscillation, such as an analog baseband or low IF signal. The ADC module converts the analog baseband or low IF signal into a digital baseband or low IF signal. The filtering and/or gain module, high pass and/or low pass filters the digital baseband or low IF signal to produce a baseband or low IF signal **156**. Note that the ordering of the ADC module and filtering and/or gain module may be switched, such that the filtering and/or gain module is an analog module.

The receiver processing module **144** processes the baseband or low IF signal **156** in accordance with a particular wireless communication standard (e.g., IEEE 802.11, Bluetooth, RFID, GSM, CDMA, et cetera) to produce environmental data **161**. The processing performed by the receiver processing module **144** includes, but is not limited to, digital intermediate frequency to baseband conversion, demodulation, demapping, depuncturing, decoding, and/or descrambling as well as optional further processing to indicate unused spectrum, used spectrum, desired channels, undesired channels, noise and interference, etc.

In an embodiment of the present invention, RF receiver **127'** includes RF front-end **140** and down conversion module **142** that implement a narrowband receiver that is scanned over a broadband spectrum, such as RF signal spectrum **203**. In this fashion, individual portions of the spectrum, the RF receiver **127'** can be tuned to individual frequency bands or individual frequency channels for analysis to generate environmental data **161**. In one mode of operation, the RF receiver **127'** can be adaptively scanned over the broadband spectrum to avoid transmission interference from at least one of the plurality of transceivers **73**. In particular, the RF receiver **127'** can be operated via control signals **141'** generated by processing module **225** to avoid being tuned to frequency bands or channels at the same time the particular a particular frequency band or channel is being used for transmission by one of the other transceivers **73 . . . 73'** of communication device **125**.

In another embodiment of the present invention, the RF receiver **127'** includes RF front-end **140** and down conversion module **142** that implement a broadband receiver that contemporaneously captures the received RF signals over a broadband spectrum and generates environmental data by analyzing the broadband spectrum using frequency domain analysis. For example, the down conversion module **142** can digitize baseband or low IF signals over a broad range of frequencies and perform a fast Fourier transform (FFT) or use other frequency domain methodologies in receiver processing module **144** to generate environmental data **161**. In one mode of operation, the RF receiver **127'** can adaptively capture data from the broadband spectrum to avoid transmission interference from at least one of the plurality of transceivers **73**. In particular, the RF receiver **127'** can be operated via control signals **141'** generated by processing module **225** to avoid capturing or analyzing inbound RF signal **152** at the same time the particular one of the transceivers **73 . . . 73'** of communication device **125** is transmitting.

FIG. **10** is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. Communication device **125** is shown transceiving network data with a plurality of networks **107** and **109**, such as networks **2**, **4**, **6**, **8** in accordance with a plurality of network protocols. In this embodiment of the present invention, control data is communicated between a remote management unit **200** and the communication device **125** via a logical control channel carried via network data communicated via either network **107** or network **109**. The management unit **200** assists the communication device **125** in the configuration of one or more of the transceivers **73 . . . 73'**.

In particular, at least one of the transceivers **73 . . . 73'** further transceives control channel data with the remote management unit **200** contemporaneously with the network data via a logical control channel carried using the corresponding one of the plurality of network protocols. The control channel data includes local control data sent to the management unit **200** and remote control data received from the management unit **200**. In accordance with this embodiment, processing module **225** processes the remote control data and generates a least one control signal **141** in response thereto, the at least one control signal **141** for adapting at least one of the transceivers **73 . . . 73'** based on the remote control data.

The local control data sent to the management unit **200** can include location data or motion data generated by the location generation module **48**; RF environmental data, such as environmental monitoring data **161**, battery remaining generated by power management unit **95**; desired quality of service; a latency preference; a cost preference; a transaction request such as a request for a particular network service or application; a device characteristic; and/or a data rate preference;

13

generated by a communication application executed by processing module 225 or other module of communication device 125.

In an embodiment of the present invention, processing module 225 operates via state machine, algorithm, look-up table or calculation, to generate control signals 141 and/or 141' based on the remote control data received from management unit 200. In this fashion, management unit 200 can evaluate task requests that describe what a user communication device 125 wishes to do, e.g. download an audio file, place a telephone call, send a message, play a game, watch a video, etc., and gather other information from communication device 125 via the local control data regarding the capabilities, preferences and status of the device, and environmental data along with other pertinent data if any, and assist communication device in the configuration of its transceivers to fulfill the requested tasks via networks 107, 109, etc. In addition, management module 200 can evaluate local control data during the provision of a particular network service to assist communication device 125 in adjusting transmit and receive parameters for better performance, switch frequency channels, and/or to handoff to other networks.

FIG. 11 is a schematic block diagram representation of a portion of a protocol stack in accordance with an embodiment of the present invention. As discussed in conjunction with FIG. 10, control data can be communicated between a remote management unit 200 and communication device 125 via a logical control channel. In this embodiment control data is carried via a control channel protocol 230 such as an application specific control channel protocol or universal protocol such as an IP protocol. This control channel protocol 230 is stacked above the particular network protocol 232 in the protocol stack 231 used to communicate between communication device 125 and the wireless network 107 or 109.

In operation, local control data received in network data from communication device 125 via network 107 or 109 is routed to management unit 200. The local control data further includes a device identifier, such as an identification number or address that is specific to communication device 125 that is used to route remote control data from management unit 200 back to communication device 125 via additional network data.

FIG. 12 is a schematic block diagram representation of network protocol packet in accordance with an embodiment of the present invention. In particular, a network protocol packet 234 is shown that includes a packet payload 238 and a packet overhead section 236 such as a packet header or other overhead section. In this embodiment the logical control channel is implemented by tunneling control data, such as control data 235 in a packet payload, such as packet payload 238.

In this embodiment, local control data included in control data 235 and received in network data from communication device 125 via network 107 or 109, can be routed to management unit 200. The local control data further includes a device identifier, such as an identification number or address that is specific to communication device 125 that is used to route remote control data from management unit 200 back to communication device 125 via control data 235.

FIG. 13 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular, an embodiment is shown that includes management unit 201. In this embodiment, management unit 201 operates as management unit 200 described in conjunction with FIG. 10, however management unit 201 communicates with communication device 125 via a separate wireless control channel, such as a direct wireless channel

14

between the management unit 201 and the communication device 125. In an embodiment of the present invention, the control channel is utilizes a control channel protocol, such as a standardized protocol, that differs from the plurality of network protocols used by networks 107, 109, etc. to communicate with communication device 125. In the alternative, a network protocol could be reused for this purpose or a universal protocol such as an IP protocol could further be employed.

In this configuration communication device 125 can include a dedicated control channel transceiver to communicate with management unit 201. In this fashion, the control channel can be present to communicate control data and to assist the communication device 125 in the configuration of one or more of the transceivers 73 . . . 73'. In an alternative embodiment, communication device 125 can configure one of the transceivers 73 . . . 73' to operate as a control channel. For instance, upon start-up of the device, movement to a new area or otherwise in a default mode of operation, the communication device 125 can configure one of the transceivers 73 . . . 73' to operate as a control channel and communicate with management unit 201 to determine what networks and network resources are available. Management unit 201 can exchange control data with communication device 125 to determine particular device parameters to configure one or more of its transceivers 73 . . . 73' to operate with the available network or networks, such as networks 107, 109, etc., based on the particular task or tasks requested by the communication device 125.

Further, after set-up is complete the remote control data received by the management unit 201 can include further reconfigure the particular transceiver 73 or 73', etc., previously used to implement the control channel, to communicate with a network 107, 109, etc. Optionally, the communication device 125 can return the transceiver back to the control channel mode of operation in the event a network is lost, a transceiver 73 . . . 73' becomes available, a start-up is initiated, the communication devices moves to a new area, or otherwise as initiated by a communication application executed by processing module 225 or under user control.

FIG. 14 is a schematic block diagram of another embodiment of communication device in accordance with the present invention. In particular, a communication device is shown that shares many common elements of the communication devices 125 described in conjunction with FIGS. 4 and 9 that are referred to by common reference numerals. In this embodiment however, RFIC 50 includes a control channel transceiver to communicate RF control channel signaling 205 with management unit 201. Transceiver 75 can be a dedicated control channel transceiver. In this fashion, the control channel can be present to communicate control data and to assist the communication device 125 in the configuration of one or more of the transceivers 73 . . . 73'. In an alternative embodiment, communication device 125 can configure one of the transceivers 73 . . . 73' to operate as a control channel transceiver 75 in a control channel mode of operation.

FIG. 15 is a schematic block diagram of another embodiment of an RF transceiver 123' in accordance with the present invention. In particular, an RF transceiver 123' is shown that shares many common elements of the RF transceiver 123 described in conjunction with FIG. 5 that are referred to by common reference numerals and that can be used to implement transceiver 75. RF Transceiver 123' can be a dedicated control channel transceiver that implements a physical control channel via outbound RF signal 170' and inbound RF signal 152'. Inbound RF signals 152' from the management unit 201 are processed by RF receiver 127 to produce remote

15

control data **252**. In addition, local control data **253** is processed by RF transmitter **129** to produce an outbound RF signal **170'** that is sent to the management unit **201**. In this fashion, the control channel can be present to communicate control data and to assist the communication device **125** in the configuration of one or more of the transceivers **73 . . . 73'**. In an alternative embodiment, communication device **125** can configure one of the transceivers **73 . . . 73'** to operate as a RF transceiver **123'** via optional control signals **141** in a control channel mode of operation.

FIG. **16** is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular, a communication system is shown wherein the management unit supplies cognitive transceiver configuration data **260** via a control channel to configure one or more cognitive radio transceivers of communication device **125**. In this fashion, the cognitive radio transceiver can be configured for communication on different frequency channels, different frequency bands, with different networks, via different data rates and different protocols, to adapt to environmental conditions, device conditions and/or to otherwise be adapted with other transmit and receive characteristics.

For example, a logical control channel can be established between the communication device **125** and the management unit **200** via either a dedicated control channel transceiver, a transceiver operated in a control channel mode of operation, or a cognitive radio transceiver configured for operation as a control channel transceiver. Local control channel data is sent to the management unit **200** that can include environmental data collected via a dedicated environmental monitoring transceiver, a transceiver operated in an environmental monitoring mode of operation or a cognitive radio transceiver configured to operate as an environmental monitoring receiver. In addition, the local control data can include a task request, such as to place a telephone call, and further include device conditions such as preferred data rates, battery life remaining, device model and optional operating system or communication application characteristics and other parameters. In response, the management unit selects a particular network, such as network **107** which is, in this example, a 900 MHz GSM mobile telephone network that management unit **200** knows can be received well by communication device **125** based on the environmental data it has received as part of the local control data. Further, management unit **200** generates cognitive transceiver configuration data **260** and sends this data to the communication device **125**. Communication device receives the cognitive transceiver configuration data and configures one of its cognitive radio transceivers to operate as a 900 MHz GSM transceiver, establishes communication with network **107** and begins to fulfill its requested task of placing a telephone call.

Particular cognitive radio transceiver implementations will be discussed in conjunction with FIGS. **18-19** that follow.

FIG. **17** is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. Like the communication system of FIG. **16**, a communication system is shown wherein a management unit supplies cognitive transceiver configuration data **260** via a control channel to configure one or more cognitive radio transceivers of communication device **125**. In this fashion, the cognitive radio transceiver can be configured for communication on different frequency channels, different frequency bands, with different networks, via different data rates and different protocols, to adapt to environmental conditions, device conditions and/or to otherwise be adapted with other transmit and receive characteristics. In this embodiment, a

16

management unit **201** is used in place of management unit to communicates with communication device **125** via a direct or separate physical control channel, as discussed, for instance in conjunction with FIGS. **13-14**.

FIG. **18** is a schematic block diagram of an embodiment of an RF transceiver **123"** in accordance with the present invention. In particular, an RF transceiver **123"** is shown that shares many common elements of the RF transceivers **123** and **123'** described in conjunction with FIGS. **5** and **15** that are referred to by common reference numerals and that can be used to implement transceivers **73**, **73'** and **75**. The RF transceiver **123"** includes an RF transmitter **229**, and an RF receiver **227**. The RF receiver **227** includes a RF front end **140**, a down conversion module **142** and a receiver processing module **144'**. The RF transmitter **229** includes a transmitter processing module **146'**, an up conversion module **148**, and a radio transmitter front-end **150**.

As shown, the receiver and transmitter are each coupled to an antenna through an antenna interface **171** and a diplexer (duplexer) **177**, such as antenna interface **72** or **74**, that couples the transmit signal **155** to the antenna to produce outbound RF signal **170** and couples inbound signal **152** to produce received signal **153**. Alternatively, a transmit/receive switch can be used in place of diplexer **177**. While a single antenna is represented, the receiver and transmitter may share a multiple antenna structure that includes two or more antennas. In another embodiment, the receiver and transmitter may share a multiple input multiple output (MIMO) antenna structure, diversity antenna structure, phased array or other controllable antenna structure that includes a plurality of antennas. Each of these antennas may be fixed, programmable, and antenna array or other antenna configuration.

In operation, the transmitter receives outbound realtime data **162** from other portions of its a host device, such as a communication application executed by processing module **225** or other source via the transmitter processing module **146'**. The transmitter processing module **146'** processes the outbound data **162** in accordance with a particular wireless communication standard (e.g., IEEE 802.11, Bluetooth, RFID, GSM, CDMA, et cetera) to produce baseband or low intermediate frequency (IF) transmit (TX) signals **164** that contain outbound data **162**. The baseband or low IF TX signals **164** may be digital baseband signals (e.g., have a zero IF) or digital low IF signals, where the low IF typically will be in a frequency range of one hundred kilohertz to a few megahertz. Note that the processing performed by the transmitter processing module **146'** can include, but is not limited to, scrambling, encoding, puncturing, mapping, modulation, and/or digital baseband to IF conversion.

The up conversion module **148** includes a digital-to-analog conversion (DAC) module, a filtering and/or gain module, and a mixing section. The DAC module converts the baseband or low IF TX signals **164** from the digital domain to the analog domain. The filtering and/or gain module filters and/or adjusts the gain of the analog signals prior to providing it to the mixing section. The mixing section converts the analog baseband or low IF signals into up-converted signals **166** based on a transmitter local oscillation.

The radio transmitter front end **150** includes a power amplifier and may also include a transmit filter module. The power amplifier amplifies the up-converted signals **166** to produce outbound RF signals **170**, which may be filtered by the transmitter filter module, if included. The antenna structure transmits the outbound RF signals **170** to a targeted device such as a RF tag, base station, an access point and/or another wireless communication device via an antenna inter-

face 171 coupled to an antenna that provides impedance matching and optional bandpass filtration.

The receiver receives inbound RF signals 152 via the antenna and off-chip antenna interface 171 that operates to process the inbound RF signal 152 into received signal 153 for the receiver front-end 140. In general, antenna interface 171 provides impedance matching of antenna to the RF front-end 140, optional bandpass filtration of the inbound RF signal 152 and optionally controls the configuration of the antenna in response to one or more control signals 141 generated by processing module 225.

The down conversion module 142 includes a mixing section, an analog to digital conversion (ADC) module, and may also include a filtering and/or gain module. The mixing section converts the desired RF signal 154 into a down converted signal 156 that is based on a receiver local oscillation, such as an analog baseband or low IF signal. The ADC module converts the analog baseband or low IF signal into a digital baseband or low IF signal. The filtering and/or gain module high pass and/or low pass filters the digital baseband or low IF signal to produce a baseband or low IF signal 156. Note that the ordering of the ADC module and filtering and/or gain module may be switched, such that the filtering and/or gain module is an analog module.

The receiver processing module 144' processes the baseband or low IF signal 156 in accordance with a particular wireless communication standard (e.g., IEEE 802.11, Bluetooth, RFID, GSM, CDMA, et cetera) to produce inbound data 160. The processing performed by the receiver processing module 144' includes, but is not limited to, digital intermediate frequency to baseband conversion, demodulation, demapping, depuncturing, decoding, and/or descrambling.

In an embodiment of the present invention, the RF transceiver 123" can be configured as a control channel transceiver to receive inbound data 160 that includes cognitive transceiver configuration data 260. The RF transceiver 123" can be configured as a control channel transceiver in a default mode of operation and then reconfigure itself based on the cognitive transceiver configuration data 260 received via either a physical or logical control channel established with management unit 200 or 201. Then, for example, when communication device 125 completes the task assigned to it in its reconfigured state, the RF transceiver 123" can reconfigure itself again to revert back to operation as a control channel transceiver.

The processing module 225 receives the cognitive transceiver configuration data 260 and generates one or more control signals 141 to configure or adapt the RF transceiver 123" in response thereto. Like the processing module 225 of RF transceiver 123", processing module 225 generates control signals 141 to modify the transmit and/or receiver parameters of the RF transceiver 123" such as protocol parameters, data rates, modulation types and other data parameters used by receiver processing module 144' and transmitter processing module 146', frequency bands, channels and bandwidths, filter settings, gains, power levels, ADC and DAC parameters, and other parameters used by RF front-end 140, radio transmitter front-end 150, down conversion module 142 and up conversion module 148, as well as antenna configurations used by antenna interface 171 to set the beam pattern, gain, polarization, frequency band or other antenna configuration of the antenna.

For example, the cognitive transceiver configuration data 260 can include receiver frequency band configuration data for configuring the frequency band of the receiver front-end 140 via adjustment of a local oscillator frequency, filter bandwidth, etc, via control signals 141. The cognitive transceiver

configuration data 260 can include transmitter frequency band configuration data for configuring the frequency band of the transmitter front end via adjustment of a local oscillator frequency, filter bandwidth, etc. The cognitive transceiver configuration data 260 can include baseband processing configuration data for configuring at least one baseband processing parameter of the receiver baseband processing module 144' such as a particular modulation scheme, protocol, data rate, etc. The cognitive transceiver configuration data 260 can include baseband processing configuration data for configuring at least one baseband processing parameter of the transmitter baseband processing module 146' such as a particular modulation scheme, protocol, data rate, etc.

The control signals 141 can be analog signals, digital signals, discrete-time signals of other signals that control the modules of RF transceiver 123" to adapt to communication via different networks. In this fashion, such a cognitive RF transceiver 123" can be configured to operate as either a Bluetooth transceiver, a GSM transceiver or a 802.11g transceiver based on the generation of the control signals 141 to implement the corresponding transmit and receive characteristics.

In a further mode of operation, the receiver processing module 144' includes a receiver application memory 240 that stores a receiver application that is executed by the receiver processing module to perform the functionality of this receiver processing module 144'. In a default mode of operation the receiver application memory can store a default receiver application that causes the receiver processing module to operate in a particular configuration—such as a GSM receiver, a Bluetooth receiver, a CDMA receiver, a WIMAX receiver, and UWB receiver, a 802.11 receiver or as a control channel receiver, etc. The cognitive transceiver configuration data 260 can include other baseband processing application data that can be received and stored in receiver application memory 240 and for execution by the receiver baseband processing module 144' in a new configuration. For example, while operating as a control channel receiver, the RF receiver 227 can receive cognitive transceiver configuration data 260 that includes baseband processing application data with a new receiver application, for example a GSM receiver application, that is stored in receiver application memory 240 and executed by the receiver baseband processing module 144' as part of a reconfiguration of the RF receiver 227 by processing module 225 as a GSM receiver.

In a similar fashion, the transmitter processing module 146' includes a transmitter application memory 241 that stores a transmitter application that is executed by the transmitter processing module to perform the functionality of the transmitter processing module 146'. In a default mode of operation, the transmitter application memory can store a default transmitter application that causes the transmitter processing module to operate in a particular configuration—such as a GSM transmitter, a Bluetooth transmitter, a CDMA transmitter, a WIMAX transmitter, and UWB transmitter, a 802.11 transmitter or as a control channel transmitter, etc. The cognitive transceiver configuration data 260 can include other baseband processing application data that can be received and stored in transmitter application memory 241 and for execution by the transmitter baseband processing module 146' in a new configuration. For example, while operating as a control channel transceiver, the RF transceiver 123" can receive cognitive transceiver configuration data 260 that includes baseband processing application data with a new transmitter application, for example a GSM transmitter application, that is stored in transmitter application memory 241 and executed by the transmitter baseband processing module 146' as part of

19

a reconfiguration of the RF transmitter 229 by processing module 225 as a GSM transmitter.

It should be noted that the examples presented above are merely illustrative of the many possible configurations and reconfigurations of such as cognitive RF transceiver 123".

FIG. 19 is a schematic block diagram of an embodiment of an RF transceiver 123" in accordance with the present invention. In particular, an RF transceiver 123" is shown that shares many common elements of the RF transceivers 123, 123' and 123" described in conjunction with FIGS. 5, 15 and 18 that are referred to by common reference numerals and that can be used to implement transceivers 73, 73' and 75. In this embodiment however, the cognitive transceiver configuration data 260 is received via another transceiver, 73, 73' or 75 of communication device 125 that is configured as a physical or logical control channel transceiver. In this fashion, multiple transceivers of communication device 125 can be configured or reconfigured to different applications under the control or collaboration with management unit 200 or 201.

FIG. 20 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular, a network management unit 200 is shown for managing a plurality of multiservice communication devices 125, each capable of communicating via a plurality of networks 107, 109, etc. In particular, management unit 200 communicates with each of the multiservice communication devices 125 via a logical control channel tunneled in and/or otherwise carried in conjunction with network data communicated between the multiservice communication devices 125 and the networks 107, 109, etc. Control data exchanged between the management unit 200 and each of the multiservice communication devices 125 can include remote control data that optionally include cognitive transceiver configuration data, and local control data.

In an embodiment of the present invention, management unit 200 gathers device identification data, such as an IP address, mobile identification number, MAC address or other device identifier corresponding to each of the multiservice communication devices 125 via local control data transmitted from each device to the management unit 200 via the logical control channel. Remote control data transmitted from the management unit 200 to a particular multiservice communication device 125 is addressed via device identifier for the particular device.

Further details regarding a possible implementation of management unit 200 are presented in conjunction with FIG. 21 that follows.

FIG. 21 is a schematic block diagram of an embodiment of a management unit in accordance with the present invention. In particular, a management unit 200 is shown that includes a management processing unit 270 and a network interface 272 that receives network resource data 280 from the plurality of networks, such as network 107, 109, etc. In operation, network interface 272 facilitates a bidirectional data communication with the plurality of multiservice communication devices 125 via a wireless control channel. The bidirectional data communication includes outbound control data 278, such as remote control data sent to at least one of the plurality of multiservice communication devices 125. The bidirectional data communication further includes inbound control data 276, such as local control data, received from at least one of the plurality of multiservice communication devices 125. As discussed in conjunction with FIG. 20, the wireless control channel can be implemented with a logical control channel that is carried by the communication between the plurality of multiservice communication devices 125 and one or more of the plurality of networks 107, 109, etc.

20

Management processing unit 270 can be implemented via at least one dedicated or shared processing device. Such a processing device, may be a microprocessor, micro-controller, digital signal processor, microcomputer, central processing unit, field programmable gate array, programmable logic device, state machine, logic circuitry, analog circuitry, digital circuitry, and/or any device that manipulates signals (analog and/or digital) based on operational instructions. The associated memory may be a single memory device or a plurality of memory devices that are either on-chip or off-chip. Such a memory device may be a read-only memory, random access memory, volatile memory, non-volatile memory, static memory, dynamic memory, flash memory, and/or any device that stores digital information. Note that when the management processing unit 270 implements one or more of its functions via a state machine, analog circuitry, digital circuitry, and/or logic circuitry, the associated memory storing the corresponding operational instructions for this circuitry is embedded with the circuitry comprising the state machine, analog circuitry, digital circuitry, and/or logic circuitry.

In an embodiment of the present invention the network interface can include a modem, switch, router, network interface card, data interface or other interface that is capable of coupling to wireless networks 107, 109, etc. to send and receive inbound control data 276 and outbound control channel 278 via one or more of the networks 107, 109, etc. In addition, network interface 272 includes a control channel interface, a receiver, such as an environmental monitoring receiver, or other input device for receiving or generating network resource data that indicates the availability of network resources, such as frequency channels, time slots or other resources of networks 107, 109, etc.

Management processing unit 270 processes the inbound control data 276 and the network resource data 280 and generates the outbound control data 278 in response. The outbound control data 278 can include network connection data, transmit and receive parameters, protocol parameters, cognitive transceiver configuration data 260 or other control information to adapt or configure the multiservice communication devices 125 to operate with wireless networks 107, 109, etc. As discussed, the cognitive transceiver configuration data 260 can include receiver frequency band configuration data for configuring the frequency band of the receiver front-end; transmitter frequency band configuration data for configuring the frequency band of the transmitter front end; baseband processing configuration data for configuring at least one baseband processing parameter of the receiver baseband processing module; baseband processing application data for execution by the receiver baseband processing module; baseband processing configuration data for configuring at least one baseband processing parameter of the transmitter baseband; and/or processing module baseband processing application data for execution by the transmitter baseband processing module.

For example, the inbound control data 276 can include at least one transaction request, such as a request to download a file, to send a message, to view a video program, to place a telephone call, etc. The management processing unit 270 allocates at least one resource of at least one of the plurality of networks 107, 109, etc. based on the inbound control data and the network resource data. In an embodiment of the present invention, the management processing unit 270 selects one of the plurality of networks 107, 109, etc. to implement a transaction in accordance with the transaction request based on the inbound control data 276, that may further include device characteristics, device status parameters, further preferences, such as RF environmental data, battery remaining, desired

quality of service, a latency preference, a cost preference, a device characteristic, a data rate preference. Management processing unit 270 selects one of the plurality of networks 107, 109, etc. also based on the network resource data 280 that provides information on which network resources are available to potentially service the request. The outbound control data 278 can include a selection of one of the plurality of networks 107, 109, etc along with other remote control data for adapting at least one transceiver of at least one of the plurality of multiservice communication devices.

FIG. 22 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular, a network management unit 201 is shown for managing a plurality of multiservice communication devices 125, each capable of communicating via a plurality of networks 107, 109, etc. In particular, management unit 201 communicates with each of the multiservice communication devices 125 via a separate wireless control channel. Control data exchanged between the management unit 201 and each of the multiservice communication devices 125 can include remote control data that optionally include cognitive transceiver configuration data, and local control data.

In an embodiment of the present invention, management unit 201 gathers device identification data, such as an IP address, mobile identification number, MAC address or other device identifier corresponding to each of the multiservice communication devices 125 via local control data transmitted from each device to the management unit 201 via the physical control channel. Remote control data transmitted from the management unit 201 to a particular multiservice communication device 125 is addressed via device identifier for the particular device.

Further details regarding a possible implementation of management unit 201 are presented in conjunction with FIG. 23 that follows.

FIG. 23 is a schematic block diagram of another embodiment of a management unit in accordance with the present invention. In particular, management unit includes similar elements to management unit 200 that are referred to by common reference numerals. However, network interface 273 operates in a similar fashion to network interface 272 to generate or receive network resource data, however, inbound control data 276 and outbound control channel data 278 are communicated via a communication device interface, such as control channel transceiver 274. In operation, control channel transceiver, such as RF transceiver that is complementary to RF transceiver 123", facilitates a bidirectional data communication with the plurality of multiservice communication devices 125 via the wireless control channel.

FIG. 24 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular a communication system is shown that shares similar elements to the communication system of FIG. 20 that are referred to by common reference numerals. In this embodiment however, management unit 200 includes a local agent 292 that gathers environmental data from remote devices 290 in communication with wireless network 107, and 109 and/or from multiservice communication devices 125. The remote devices 290 can include base stations, access points and other network devices, single service communication devices coupled to networks 107, 109, such as WLAN-enabled computers, wireless telephones or other devices in communication with wireless networks 107, 109, etc.

The environmental data can include RF spectral information and location data from each remote device 290 that is

used by the management unit 200 to map the current RF environment to determine such factors as available channels, unused spectrum, used spectrum, sources and locations of noise and interference, locations of other "trouble zones" where communication via one or more channels of via one or more of the networks 107, 109, etc. can be difficult. Local agent 292 can operate to gather and process this information for use by management unit 200 to determine locations where handoffs will be required because a multiservice communication device is entering a trouble zone, to allocate frequency channels and other network resources and to otherwise generate other outbound control data 278, such as remote control data.

FIG. 25 is a schematic block diagram of another embodiment of a management unit in accordance with the present invention. In particular, a management unit 200 is shown that includes many similar elements described in conjunction with FIG. 21 that are referred to by common reference numerals. In addition, management processing unit 270 includes local agent 292, that can be implemented via hardware, firmware or software to gather environmental data via inbound data 276 from multiservice communication devices 125 and via other remote devices 290 that are part of or in communication with networks 107, 109, etc. As discussed, management processing unit 270 processes the inbound control data including the environmental data, and the network resource data and generate the outbound control data in response thereto.

In particular, local agent 292 can gather the environmental data from a plurality of remote devices, different from the plurality of multiservice communication devices, via the wireless control channel and/or from at least one of the plurality of multiservice communication devices via the wireless control channel.

FIG. 26 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular a communication system is shown that shares similar elements to the communication system of FIG. 22 that are referred to by common reference numerals. In this embodiment however, management unit 201 includes a local agent 292 that gathers environmental data from remote devices 290, from networks 107, 109, etc. and/or from multiservice communication devices 125 via communication over a physical wireless control channel that can be implemented separate from the wireless networks 107, 109, etc. The remote devices 290 can include dedicated sensors configured to gather environmental data, or other devices in communication with management unit 201.

The environmental data can include RF spectral information, power measurements and location data from each remote device 290 that is used by the management unit 201 to map the current RF environment to determine such factors as available channels, unused spectrum, used spectrum, sources and locations of noise and interference, locations of other "trouble zones" where communication via one or more channels of via one or more of the networks 107, 109, etc. can be difficult. In addition, environmental data can optionally be collected by management unit 201 from one or more networks, such as network 107, 109, etc. Local agent 292 can operate to gather and process this information for use by management unit 201 to determine locations where handoffs will be required because a multiservice communication device is entering a trouble zone, to allocate frequency channels and other network resources and to otherwise generate other outbound control data 278, such as remote control data.

FIG. 27 is a schematic block diagram of another embodiment of a management unit in accordance with the present

invention. In particular, a management unit **201** is shown that includes many similar elements described in conjunction with FIG. **23** that are referred to by common reference numerals. In addition, management processing unit **270** includes local agent **292**, that can be implemented via hardware, firm-ware or software to gather environmental data via inbound data **276** from multiservice communication devices **125** and via other remote devices **290** that are part of or in communication with networks **107**, **109**, etc. In particular, local agent **292** can gather the environmental data from a plurality of remote devices, different from the plurality of multiservice communication devices, via the wireless control channel and/or from at least one of the plurality of multiservice communication devices via the wireless control channel. As discussed, management processing unit **270** processes the inbound control data **276**, that includes the environmental data along with the network resource data **280** and generates the outbound control data in response thereto as previously described.

FIG. **28** is a schematic block diagram of an embodiment of a management network in accordance with the present invention. In particular, a hierarchical management unit network is presented for managing a plurality of multiservice communication devices capable of communicating via a plurality of networks. The management unit network includes a plurality of local management units **300**, each of the plurality of local management units engaging in bidirectional data communication with at least one of the plurality of multiservice communication devices, such as communication device **125**, via either a physical or logical wireless control channel. In a similar fashion to management units **200** and **201**, local management units **300** each send outbound control data to, and receive inbound control data, from at least one of the plurality of multiservice communication devices. One or more regional management units are coupled to receive the inbound control data from the at least one of the plurality of local management units, for processing the inbound data to produce the outbound data and for sending the outbound data to the at least one of the plurality of local management units. In one embodiment, the local management units **300** are coupled to receive network resource data **280** from at least one of the plurality of networks, **107**, **109**, etc. and transmit the network resource data **280** to the regional management unit **302**. In response, the regional management units **302** generate the outbound control data **276** further based on the network resource data **280**. In another embodiment, the regional management units **302** are coupled to receive network resource data **280** from the plurality of networks, **107**, **109**, etc. An optional area management unit **304** is coupled to the region management units **302** for optionally participating in the production of the outbound data. The local management units **300** can also be coupled directly to networks **107**, **109**, etc to receive network resource data **280**.

In operation, the functionality of the management units **201** or **200** is split among two or more layers of the hierarchical management network. Local tasks such as the communication of inbound control data **276** and outbound control data **278**, the operation of a local agent for gathering and processing local environmental data is handled at the edge of the network. One or more of the processing functions, such as the allocation of network resources, the storage of cognitive transceiver configuration data, and the generation of other outbound control data **278** can be performed at either the regional management unit level or the optional area management unit level.

FIGS. **29** and **30** are schematic block diagrams of other embodiments of a management unit in accordance with the

present invention. In particular, management units **300** and **300'** operate in a similar fashion to management units **200** and **201**. However, management units **300** and **300'** each include a management layer interface **310** that can be a wired or wireless connection that is either direct or implemented through one or more networks, such as the Internet, to communicate with a complementary management layer interface **312** included in regional management unit **302**. The management units **300** and **300'** are each shown in an optional configuration whereby network resource data is collected by the local management units themselves. However, as discussed in conjunction with FIG. **28**, the regional management units **302**, via their own network interface that operates similarly to network interface **272**, can likewise gather network resource data **280** directly from the corresponding networks **107**, **109**, etc. In addition, in the configuration shown in conjunction with FIG. **28** where the management unit network includes an area management unit **304**, each of the regional management units **302** can further communicate with the area management unit **304** via the management layer interface **312**.

As discussed in conjunction with FIG. **28**, the functionality of the management units **201** or **200** is split among two or more layers of the hierarchical management network. Local tasks such as the communication of inbound control data **276** and outbound control data **278**, the operation of a local agent for gathering and processing local environmental data is handled at the edge of the network in the local management units **300**, via their management processing units **270**. One or more of the processing functions, such as the allocation of network resources, the storage of cognitive transceiver configuration data, and the generation of other outbound control data **278** can be performed at either the regional management unit level or the optional area management unit level via management processing units **270** included in the regional management units **302** and/or via management processing units **270** included in the area management unit **304**. In an embodiment of the present invention, the functionality discussed in conjunction with the management processing unit **270** of management units **200** and **201** can be distributed among the management processing units **270** at the local, regional and optional area layers of the management unit network.

FIG. **31** is a schematic block diagram of an embodiment of a processing module **225** in accordance with the present invention. In particular, processing module **225** of communication device **125** is shown to include a collaboration module **320**, that can be implemented via hardware, software or firmware, depending on the implementation of processing module **225**. In this embodiment, the management unit, such as management processing unit **200**, **201**, or management unit network generates the outbound control data **278** that is received by the collaboration module **320** to collaboratively establish at least one device setting of at least one of the plurality of multiservice communication devices **125**.

In an embodiment of the present invention, the inbound control data **276** includes a transaction request and at least one suggested resource allocation generated by the collaboration module **320** and the management unit **200**, **201** or the management unit network, allocates at least one resource of at least one of the plurality of networks **107**, **109**, etc. based on the inbound control data **276** and the network resource data **280**. In another embodiment of the present invention, the inbound control data **276** includes a transaction request and at least one suggested network and the management unit **200**, **201** or the management unit network, selects one of the plurality of networks **107**, **109**, etc. to implement a transaction in accordance with the transaction request based on the inbound

control data 276 and the network resource data 280. These embodiments, the decision-making resides in the management unit 200, 201 or the management unit network. In this fashion, collaboration module 320, can generate suggested or recommended configurations based on its own analysis of local control data such as location, device characteristics, device preferences, user preferences, and the state of the device.

In other embodiments, the decision-making can reside in the collaboration module 320. For example, the management unit 200, 201 or the management unit network can generate outbound control data 278 that includes a recommended selection of one of the plurality of networks 107, 109, etc. and the collaboration module 320 can select one of the plurality of networks, 107, 109, etc. based on the recommended selection. In another example, the outbound control data 278 is generated to include recommended remote control data for adapting at least one transceiver of at least one of the plurality of multiservice communication devices and the collaboration module chooses whether to adapt the at least one transceiver, based on the recommended remote control data. In addition, the outbound control data 278 can include recommended cognitive transceiver configuration data 260 for configuring at least one cognitive transceiver of a multiservice communication device 125 and the collaboration module 320 chooses whether to configure the at least one cognitive transceiver. In this fashion, management unit 200 or 201, can generate suggested or recommended configurations based on its own analysis of local control data such as location, device characteristics, device preferences, user preferences, and the state of the device. In this fashion, collaboration module 320, can choose from suggested or recommended configurations based on its own analysis of local control data such as location, environment, noise and interference, spectral characteristics, device characteristics, device preferences, user preferences, and the state of the device.

FIG. 32 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular a service aggregator 325 is shown for allocating network resources to a plurality of multiservice communication devices 125 capable of communicating via a plurality of networks 107, 109, etc. In an embodiment of the present invention the service aggregator is implemented in conjunction with a management unit 200 or 201 or a management unit network, such as the management unit network of FIG. 28.

In operation, the service aggregator engages in a bidirectional data communication with the plurality of multiservice communication devices, such as communication device 125, via a wireless control channel. The bidirectional data communication includes outbound control data, such as outbound control data 278 sent to the plurality of multiservice communication devices and inbound control data, such as inbound control data 276 received from the plurality of multiservice communication devices. Network resource data is gathered from the plurality of networks. A management processing unit, such as management processing unit 270, processes the inbound control data and the network resource data and generates the outbound control data in response thereto, wherein the inbound control data includes at least one transaction request and the service aggregator allocates at least one resource of at least one of the plurality of networks based on the inbound control data and the network resource data.

For example, a communication device 125 can, via the wireless control channel, send a request to send a telephone call. The service aggregator 325 locates an available network and sends outbound control data 278 to the communication

device 125 to communication with the network. The outbound control data can include cognitive transceiver configuration data 260 that configures a cognitive transceiver of the communication device 125 to communicate with the chosen network to place the call.

In another example, the communication device 125, while operating as a web browser locates a broadcast video program of interest that is not available via the web. The communication device 125 uses a logical control channel carried via an IP protocol to contact the service aggregator to request access to the broadcast video program. The service aggregator locates a local broadcaster, based on location data provided by communication device 125 via inbound control data 276. Service aggregator downloads baseband processing data to be executed by the receiver processing module and the transmitter processing module of a cognitive transceiver of communication device 125 along with specific channel information that will allow the cognitive receiver to tune to, receive and decode the video broadcast.

These examples merely illustrate the wide range of transactions possible in accordance with the broad scope of the present invention.

FIG. 33 is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In this embodiment, management unit 200 engages in bidirectional data communication with the plurality of multiservice communication devices 125 via a logical control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices. In this example, the wireless control channel is carried by the communication between the plurality of multiservice communication devices 125 and the plurality of networks 107, 109, etc.

The management unit 200 processes the inbound control data along with network resource data received from the networks 107, 109, etc. and generates the outbound control data in response thereto. In operation, the management unit 200, via a corresponding management processing unit, such as management processing unit 270, facilitates the handoff of a real-time service provided by real-time service provider 330 from one network, such as network 107 to a second network such as network 109. While a single service provider 330 is shown, management unit 200 can similarly be implemented to facilitate the handoff for multiple service providers.

For example, the real-time service can be a telephone call, a game, an audio playback, a video playback, a file download, a multimedia application or other real-time service or application. In operation, the management unit 200, via management processing unit 270, detects a potential handoff condition via inbound control data, such a deterioration of performance, possible motion into a trouble zone, a failure of network resources, a change of service is desired such as when a higher data rate service is available or other condition. In response, the management unit 200 via management processing unit 270, selects the second network based on one or more of: RF environmental data, battery remaining, desired quality of service, a latency preference, a cost preference, a device characteristic, a data rate preference and transmits this selection to communication device 125 via the outbound control data 278.

In an embodiment of the present invention, the management unit 200 via management processing unit 270, facilitates the establishment of a connection between the communication device 125, prior to the handoff of the real-time service, based on the outbound control data 278 sent prior to

the handoff of the real-time service. For example, management unit **200** can transmit outbound control data **278** that includes cognitive transceiver configuration data for configuring at least one cognitive transceiver of at least one of the plurality of multiservice communication devices in accordance with the second network. In this fashion, the communication device **125** can configure itself for communication with the second network.

In an embodiment of the present invention, the user of communication device **125** is engaged in a telephone call via wireless network **107** which is a GSM-based mobile telephony network, coupled to a public switched telephone network, and serviced via real-time service provider **330**. When management unit **200** detects, based on location data from the communication device **125**, that the communication device **125** is coming in range of the user's home where wireless network **109**, in this case home wireless network, management unit prepares a handoff to network **109**. In particular, management unit **201** transfers cognitive transceiver configuration data **260** or other outbound control data **276** to the communication device **125** to configure the communication device to communicate with wireless network **109**.

When, based on inbound control data **276**, the management unit **201** detects via inbound control data **276** that the communication device **125** has configured its cognitive radio transceiver and is in range of the wireless network **109**, the management unit **201** negotiates the handoff the call via IP protocol communications with real-time service provider **330** from network **107** to wireless network **109**. In particular, management unit **201** provides the IP address of the communication device **125** along with GSM device identifiers to real-time service provider **330**, who places the call on wireless network **107** on-hold or terminates the mobile call, while transferring the call to a voice-over-IP call accessed via communication device **125** via network **109**.

FIG. **34** is a schematic block diagram of an embodiment of another communication system in accordance with the present invention. In particular a communication system is presented that functions in a similar fashion to the communication system of FIG. **33**. In this embodiment however, control data exchanged between a communication device **125** and the management unit **201** via a separate physical control channel. As described in conjunction with FIG. **33**, management unit **201** communicates control data to facilitate the handoff of a real-time service from real-time service provider **330** from network **107** to **109**. This facilitation can include the establishment of the provision of the real-time service via the network **109**, prior to the handoff. This facilitation can further include the adaption or configuration of one or more transceivers of communication device **125** for communication with the network **109**.

FIG. **35** is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. **1-34**. The method begins by wirelessly transceiving data via a plurality of transceivers with a corresponding plurality of networks in accordance with a plurality of network protocols as shown in step **400**. In step **402**, signals received from an environmental monitoring receiver over a broadband spectrum are processed to generate environmental data. In step **404**, the environmental data is processed to generate at least one control signal for adapting at least one of the plurality of transceivers.

FIG. **36** is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the

functions and features described in conjunction with FIGS. **1-35**. In step **410**, data via a plurality of transceivers are wirelessly transceived with a corresponding plurality of networks in accordance with a plurality of network protocols. In step **412**, signals received from one of the a plurality of transceivers, configured as an environmental monitoring receiver in a environmental monitoring mode of operation, are processed over a broadband spectrum to generate environmental data. In step **414**, the environmental data are processed to generate at least one control signal for adapting at least one of the plurality of transceivers.

FIG. **37** is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. **1-36**. In step **420**, data is wirelessly transceived via a plurality of transceivers with a corresponding plurality of networks in accordance with a plurality of network protocols. In step **422**, signals are transceived via a control channel transceiver with a remote management unit including local control data and remote control data. In step **424**, the remote control data are processed to generate at least one control signal for adapting at least one of the plurality of transceivers.

FIG. **38** is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. **1-37**. In step **430**, data are wirelessly transceived via a plurality of transceivers with a corresponding plurality of networks in accordance with a plurality of network protocols, wherein one of the a plurality of transceivers is configured as a control channel transceiver for transceiving signals via a control channel receiver with a remote management unit in a control channel mode of operation. The signals include both local control data and remote control data. In step **432**, the remote control data are processed to generate at least one control signal for adapting at least one of the plurality of transceivers.

FIG. **39** is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. **1-38**. In step **440**, network data are wirelessly transceived via a plurality of transceivers with a corresponding plurality of networks in accordance with a plurality of network protocols, wherein one of the a plurality of transceivers further transceives control channel data with a remote management unit contemporaneously with the network data via a logical control channel carried using a corresponding one of the plurality of network protocols, the control data including local control data and remote control data. In step **442**, the remote control data are processed to generate at least one control signal for adapting at least one of the plurality of transceivers.

FIG. **40** is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. **1-39**. In step **450**, network data are wirelessly transceived via a plurality of transceivers with a corresponding plurality of networks in accordance with a plurality of network protocols, wherein one of the a plurality of transceivers further transceives control channel data with a remote management unit via a logical control channel embedded in the network data transceived with a corresponding one of the plurality of networks, the control data including local control data and remote control data. In step **452**, the remote control data are

processed to generate at least one control signal for adapting at least one of the plurality of transceivers.

FIG. 41 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-40. In step 460, network data are wirelessly transceived via a plurality of transceivers with a corresponding plurality of networks in accordance with a plurality of network protocols via a multiservice communication device, wherein at least one of the plurality of transceivers includes a cognitive radio transceiver. Step 462 continues by receiving cognitive transceiver configuration data from a management unit in communication with the multiservice communication device, via a control channel. In step 464, at least one cognitive radio transceiver is configured based on the cognitive transceiver configuration data.

FIG. 42 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-41. The method includes processing the cognitive transceiver configuration data to generate at least one control signal in response thereto, as shown in step 470.

FIG. 43 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-42. In step 480, the first cognitive radio transceiver is configured to implement the control channel.

FIG. 44 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-43. In step 490, a bidirectional data communication is facilitated with a plurality of multiservice communication devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices. In step 492, network resource data are received from a plurality of networks. In step 494, the inbound control data and the network resource data are processed to generate the outbound control data in response thereto.

FIG. 45 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-44. Step 500 begins the method by, engaging in a bidirectional data communication between a plurality of local management units and a plurality of multiservice communication devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices. In step 502, the inbound control data are received at a first regional management unit. In step 504, the inbound control data are processed to generate the outbound control data in response thereto.

FIG. 46 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-45. In step 510, a bidirectional data communication is facilitated with a plurality of multiservice communication

devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices, wherein the wireless control channel is separate from the communication between the plurality of multiservice communication devices and the plurality of networks. In step 512, network resource data is received from a plurality of networks. In step 514, the inbound control data and the network resource data are processed to generate the outbound control data in response thereto. The inbound control data includes at least one transaction request and allocating at least one network resources of the plurality of networks based on the inbound control data and the network resource data.

FIG. 47 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-46. In step 520, a bidirectional data communication is facilitated with a plurality of multiservice communication devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices, wherein the wireless control channel is carried by the communication between the plurality of multiservice communication devices and the plurality of networks. In step 522, network resource data is received from a plurality of networks. In step 524, the inbound control data and the network resource data are processed to generate the outbound control data in response thereto, wherein the inbound control data includes at least one transaction request and allocating at least one network resources of the plurality of networks based on the inbound control data and the network resource data.

FIG. 48 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-47. In step 530, a bidirectional data communication is facilitated with a plurality of multiservice communication devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices, wherein the wireless control channel is separate from the communication between the plurality of multiservice communication devices and the plurality of networks. In step 532, network resource data are received from a plurality of networks. In step 534, the inbound control data and the network resource data are processed to generate the outbound control data in response thereto to facilitate the handoff of a real-time service accessed by the at least one of the plurality of multiservice communication devices via a first network of the plurality of networks to a second network of the plurality of networks.

FIG. 49 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-48. In step 540, a bidirectional data communication is facilitated with a plurality of multiservice communication devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of

31

the plurality of multiservice communication devices, wherein the wireless control channel is carried by the communication between the plurality of multiservice communication devices and the plurality of networks. In step 542, network resource data are received from a plurality of networks. In step 544, the inbound control data and the network resource data are processed to generate the outbound control data in response thereto to facilitate the handoff of a real-time service accessed by the at least one of the plurality of multiservice communication devices via a first network of the plurality of networks to a second network of the plurality of networks.

FIG. 50 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-49. In step 550, a bidirectional data communication is facilitated with a plurality of multiservice communication devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices, wherein the wireless control channel is separate from the communication between the plurality of multiservice communication devices and the plurality of networks. In step 552, network resource data are received from a plurality of networks. In step 554, the inbound control data and the network resource data are processed to generate the outbound control data in response thereto to collaboratively establish at least one device setting of at least one of the plurality of multiservice devices via a collaboration module.

FIG. 51 is a flow chart of an embodiment of a method in accordance with the present invention. In particular, a method is presented for use in conjunction with one or more of the functions and features described in conjunction with FIGS. 1-50. In step 560, a bidirectional data communication is facilitated with a plurality of multiservice communication devices via a wireless control channel, the bidirectional data communication including outbound control data sent to at least one of the plurality of multiservice communication devices and inbound control data received from at least one of the plurality of multiservice communication devices, wherein the wireless control channel is carried by the communication between the plurality of multiservice communication devices and the plurality of networks. In step 562, network resource data are received from a plurality of networks. In step 564, the inbound control data and the network resource data are processed to generate the outbound control data in response thereto to collaboratively establish at least one device setting of at least one of the plurality of multiservice devices via a collaboration module.

As may be used herein, the terms “substantially” and “approximately” provides an industry-accepted tolerance for its corresponding term and/or relativity between items. Such an industry-accepted tolerance ranges from less than one percent to fifty percent and corresponds to, but is not limited to, component values, integrated circuit process variations, temperature variations, rise and fall times, and/or thermal noise. Such relativity between items ranges from a difference of a few percent to magnitude differences. As may also be used herein, the term(s) “coupled to” and/or “coupling” and/or includes direct coupling between items and/or indirect coupling between items via an intervening item (e.g., an item includes, but is not limited to, a component, an element, a circuit, and/or a module) where, for indirect coupling, the intervening item does not modify the information of a signal but may adjust its current level, voltage level, and/or power

32

level. As may further be used herein, inferred coupling (i.e., where one element is coupled to another element by inference) includes direct and indirect coupling between two items in the same manner as “coupled to”. As may even further be used herein, the term “operable to” indicates that an item includes one or more of power connections, input(s), output(s), etc., to perform one or more its corresponding functions and may further include inferred coupling to one or more other items. As may still further be used herein, the term “associated with”, includes direct and/or indirect coupling of separate items and/or one item being embedded within another item. As may be used herein, the term “compares favorably”, indicates that a comparison between two or more items, signals, etc., provides a desired relationship. For example, when the desired relationship is that signal 1 has a greater magnitude than signal 2, a favorable comparison may be achieved when the magnitude of signal 1 is greater than that of signal 2 or when the magnitude of signal 2 is less than that of signal 1.

The present invention has also been described above with the aid of method steps illustrating the performance of specified functions and relationships thereof. The boundaries and sequence of these functional building blocks and method steps have been arbitrarily defined herein for convenience of description. Alternate boundaries and sequences can be defined so long as the specified functions and relationships are appropriately performed. Any such alternate boundaries or sequences are thus within the scope and spirit of the claimed invention.

The present invention has been described above with the aid of functional building blocks illustrating the performance of certain significant functions. The boundaries of these functional building blocks have been arbitrarily defined for convenience of description. Alternate boundaries could be defined as long as the certain significant functions are appropriately performed. Similarly, flow diagram blocks may also have been arbitrarily defined herein to illustrate certain significant functionality. To the extent used, the flow diagram block boundaries and sequence could have been defined otherwise and still perform the certain significant functionality. Such alternate definitions of both functional building blocks and flow diagram blocks and sequences are thus within the scope and spirit of the claimed invention. One of average skill in the art will also recognize that the functional building blocks, and other illustrative blocks, modules and components herein, can be implemented as illustrated or by discrete components, application specific integrated circuits, processors executing appropriate software and the like or any combination thereof.

What is claimed is:

1. A multiservice communication device comprising:
 - a plurality of transceivers that wirelessly transceive data with a corresponding plurality of networks in accordance with a corresponding plurality of network protocols, wherein the plurality of transceivers includes:
 - a control channel transceiver that transceives control channel data with a remote management unit including local control data sent to the remote management unit and remote control data received from the remote management unit for adapting at least one of the plurality of transceivers, wherein the remote management unit is coupled to receive network resource data from the plurality of networks and generates the remote control data based on the local control data and the network resource data from the plurality of networks; and

at least one cognitive radio transceiver that is configured based on cognitive transceiver configuration data received via the remote control data.

2. The multiservice communication device of claim 1 wherein the local control data includes at least one of: RF environmental data, battery remaining, desired quality of service, a latency preference, a cost preference, a transaction request, a device characteristic, or a data rate preference.

3. The multiservice communication device of claim 1 wherein the remote control data controls a communication hand off of the multiservice communication device from a first network to a second network.

4. The multiservice communication device of claim 1 wherein the remote control data changes a frequency channel used by at least one of the plurality of transceivers.

5. The multiservice communication device of claim 1 wherein the remote control data modifies a transmission parameter of at least one of the plurality of transceivers.

6. The multiservice communication device of claim 1 wherein the remote control data modifies a receive parameter of at least one of the plurality of transceivers.

7. The multiservice communication device of claim 1 wherein the corresponding plurality of network protocols includes at least one of: a 802.11 protocol, a WIMAX protocol, a Bluetooth protocol, a wireless HDMI protocol, a 60 GHz piconet protocol, a cellular data protocol, or a cellular voice protocol.

8. The multiservice communication device of claim 1 further comprising:

a location generation module, coupled to the control channel transceiver, that generates location data and wherein the local control data includes the location data.

9. The multiservice communication device of claim 8 wherein the location generation module includes a global positioning system receiver.

10. The multiservice communication device of claim 1 further comprising:

a processing module that generates at least a portion of the local control data.

11. The multiservice communication device of claim 10 wherein the processing module processes the remote control data and generates at least one control signal in response thereto, the at least one of the plurality of transceivers is adapted based on the at least one control signal.

12. The multiservice communication device of claim 1 wherein the control channel data is transceived in accordance with a control channel protocol that differs from the corresponding plurality of network protocols.

13. A multiservice communication device comprising:

a plurality of transceivers that wirelessly transceive data with a corresponding plurality of networks in accordance with a corresponding plurality of network protocols, wherein at least one of the plurality of transceivers, in a control channel mode of operation, transceives control channel data with a remote management unit including local control data sent to the remote management unit and remote control data received from the remote management unit, wherein the remote management unit is coupled to receive network resource data from the plurality of networks and generates the remote control

data based on the local control data and the network resource data from the plurality of networks; and a processing module, coupled to the plurality of transceivers, that processes the remote control data and generates at least one control signal in response thereto, the at least one control signal for adapting at least one of the plurality of transceivers based on the remote control data; wherein the plurality of transceivers includes at least one cognitive radio transceiver that is configured based on cognitive transceiver configuration data received via the remote control data.

14. The multiservice communication device of claim 13 wherein the processing module generates at least a portion of the local control data.

15. The multiservice communication device of claim 13 wherein the at least one control signal for adapting at least one of the plurality of transceivers controls a communication hand off of the multiservice communication device from a first network to a second network.

16. The multiservice communication device of claim 13 wherein the at least one control signal for adapting at least one of the plurality of transceivers changes a frequency channel used by at least one of the plurality of transceivers.

17. The multiservice communication device of claim 13 wherein the at least one control signal for adapting at least one of the plurality of transceivers modifies a transmission parameter of at least one of the plurality of transceivers.

18. The multiservice communication device of claim 13 wherein the at least one control signal for adapting at least one of the plurality of transceivers modifies a receive parameter of at least one of the plurality of transceivers.

19. The multiservice communication device of claim 13 further comprising:

a location generation module, coupled to the control channel transceiver, that generates location data and wherein the local control data includes the location data, wherein the location generation module includes a global positioning system receiver.

20. A multiservice communication device comprising:

a plurality of transceivers that wirelessly transceive data with a corresponding plurality of networks in accordance with a corresponding plurality of network protocols, wherein the plurality of transceivers includes:

a control channel transceiver that transceives control channel data with a remote management unit including local control data sent to the remote management unit and remote control data received from the remote management unit for adapting at least one of the plurality of transceivers, wherein the remote management unit is coupled to receive network resource data from the plurality of networks and generates the remote control data based on the local control data and the network resource data from the plurality of networks, wherein the control channel data is transceived in accordance with a control channel protocol that differs from the corresponding plurality of network protocols; and

at least one cognitive radio transceiver that is configured based on cognitive transceiver configuration data received via the remote control data.