



US006489700B1

(12) **United States Patent**
Heiberger et al.

(10) **Patent No.:** **US 6,489,700 B1**
(45) **Date of Patent:** **Dec. 3, 2002**

(54) **HOMOPOLAR MACHINE WITH SHAFT AXIAL THRUST COMPENSATION FOR REDUCED THRUST BEARING WEAR AND NOISE**

(75) Inventors: **Michael Heiberger**, San Diego, CA (US); **Michael Robert Reed**, San Diego, CA (US)

(73) Assignee: **General Atomics**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/559,240**

(22) Filed: **Apr. 26, 2000**

(51) **Int. Cl.**⁷ **H02K 31/00; H02K 7/09**

(52) **U.S. Cl.** **310/178; 310/90.5; 310/90**

(58) **Field of Search** **310/178, 12, 15, 310/90, 90.5, 190, 191**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,890,019 A	6/1975	Boden et al.	308/10
3,944,865 A *	3/1976	Jewitt	310/178
3,976,339 A	8/1976	Sabnis	308/10
4,110,648 A	8/1978	Stillwagon	310/178
4,180,296 A	12/1979	Habermann	308/10
4,185,216 A	1/1980	Mole et al.	310/178
4,208,600 A	6/1980	Hatch	310/178
4,241,271 A	12/1980	Johnson et al.	310/219
4,271,369 A	6/1981	Stillwagon	310/178
4,276,507 A	6/1981	Stillwagon	322/48
4,399,381 A	8/1983	Chabrierie	310/178
4,581,555 A	4/1986	Kuznetsov et al.	310/178
4,602,179 A	7/1986	Kuznetsov et al.	310/178
4,710,656 A	12/1987	Studer	310/51
4,710,666 A	12/1987	Rindal et al.	310/248
4,858,304 A *	8/1989	Weldon et al.	310/178
5,010,563 A	4/1991	Laurent et al.	378/132
5,027,280 A	6/1991	Ando et al.	364/474.16
5,032,748 A	7/1991	Sakuraba et al.	310/52
5,216,308 A	6/1993	Meeks	310/90.5
5,278,470 A	1/1994	Neag	310/178

5,349,256 A *	9/1994	Holliday	310/12
5,385,007 A	1/1995	Hartel et al.	57/76
5,451,825 A	9/1995	Strohm	310/178
5,481,149 A	1/1996	Kambe et al.	310/178
5,514,924 A	5/1996	McMullen et al.	310/90.5
5,517,072 A	5/1996	Hilderbrandt	310/228
5,530,309 A	6/1996	Weldon	310/178
5,572,079 A	11/1996	Pinkerton	310/90.5
5,587,618 A	12/1996	Hathaway	310/178
5,729,066 A	3/1998	Soong et al.	310/90.5
5,731,645 A	3/1998	Clifton et al.	310/74
5,739,606 A	4/1998	Takahata et al.	310/90.5
5,767,597 A	6/1998	Gondhalekar	310/90.5
5,821,659 A	8/1998	Smith	310/178
5,804,899 A	9/1998	Jamain et al.	310/90.5
5,834,867 A	11/1998	Kikuchi et al.	310/51
6,245,440 B1	6/2001	Kuhlmann-Wilsdorf et al.	428/611

FOREIGN PATENT DOCUMENTS

JP 10-136622 * 5/1998 H02K/7/09

* cited by examiner


Primary Examiner—Burton S. Mullins

(74) *Attorney, Agent, or Firm*—Fitch, Even, Tabin, & Flannery

(57) **ABSTRACT**

A homopolar machine produces an axial counterforce on the rotating shaft to compensate for the load on the shaft's thrust bearing to reduce wear and noise and prolong bearing life. The counterforce is produced through magnetic interaction between the shaft and the machine's field coils and is created by changing the current excitation of the field coils, which results in a magnetic flux asymmetry in an inner flux return coupled to the shaft. The homopolar machine may also have a configuration that uses current collectors that maintain substantially constant contact pressure in the presence of high magnetic fields to improve current collector performance. The current collectors are flexible and may be made from either electrically conductive fibers or stacked strips such that they bear up against the armature so that the pressure is maintained by the spring constant of the current collector material.

27 Claims, 10 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

HOMOPOLAR MACHINE WITH SHAFT AXIAL THRUST COMPENSATION FOR REDUCED THRUST BEARING WEAR AND NOISE

BACKGROUND OF THE INVENTION

The present invention relates to direct current machines, and more specifically to homopolar machines.

Homopolar machines are operated by direct current (DC) and are simple in design principle. They have been under development for consideration in ship propulsion applications because of their high efficiency, compact size, low weight, and reduced acoustic signature relative to all other motors.

As is well known in the art, a homopolar machine includes four major components: armature; stator; field coils; and flux return. The armature is connected to the machine's shaft and may also be referred to as the rotor. The armature typically includes a series of concentric, copper cylinders and is free to rotate in a direction at right angles to the magnetic field lines produced by the field coils. When a voltage is applied across the armature in the direction of the shaft, electric current flows parallel to the shaft. The current and magnetic field interaction ($I \times B$) results in torque generation and rotation, thus producing a motor. In contrast, if the armature is driven externally for a generator application, the interaction of the armature rotating at right angles to the magnetic field lines generates a voltage and electric current.

In both the motor and generator scenarios, current flows along the armature and to the stationary stator via sliding electrical contacts referred to herein as current collectors. The current collectors may also be commonly referred to as brushes, and may take the form of many materials. Such materials include but are not limited to flexible fibrous copper, flexible copper strips, or as common to most DC motors, rigid material made from graphite or silver-graphite.

The field coils are typically circumferentially continuous in geometry and aligned on the same central axis with respect to each other. A homopolar machine always cuts (or crosses as it rotates) magnetic flux lines of a magnetic field in the same direction due to the interacting armature and shaft iron being aligned on the same axis. This means that any point on the rotor always sees the same magnetic field as it rotates and no difference in magnetic flux or multiple magnetic poles are encountered by conductive elements of the armature as it rotates. Hence the nomenclature "homopolar machine".

The flux return is typically comprised of a highly magnetically permeable material such as iron or steel. The flux return is designed primarily to limit the undesirable stray magnetic field that radiates from the machine, and therefore, it typically takes the form of a structural housing that surrounds the motor. In addition, the flux return may also be designed to help direct the magnetic field lines produced by the field coils into the armature interaction region to improve the machine's flux utilization.

Although conventional rotating machines are in wide use, most have inherent disadvantages associated with mechanical bearing wear. For example, large machines such as generators connected to turbines, as well as motors used for propulsion, use thrust bearings to react the induced axial mechanical forces on the shaft and to maintain a stable shaft axial position. The mechanical thrust that is induced on the shaft induces an axial thrust on the thrust bearing, which causes thrust bearing wear and noise. The mechanical thrust

induced on the shaft may be from many sources. For example, in a generator application the induced thrust is caused by the axial pressure differential across a connected turbine, and in a propulsion motor application the induced thrust is caused by the thrust exerted by the connected propulsor. If a homopolar machine was used in these applications, it would be prone to this same type of problem. Ships, submarines and airplanes all experience thrust bearing forces within their propulsion systems. The induced axial mechanical forces are also referred to herein as thrust bearing loads.

As thrust bearing loads increase, wear and tear and associated noise increase at a rate on the order of pressure cubed (i.e., p^3 where p is pressure due to the thrust bearing load). This means that a reduction of pressure on the shaft by two fold translates into a reduction of associated wear by eight fold. Such a reduction of pressure on the shaft would result in a thrust bearing lifetime of eight times its original lifetime. Thus, there is a need for a method and/or apparatus that helps to reduce thrust bearing loads in homopolar machines.

A unique disadvantage of homopolar machines is that they tend to have lower reliability in comparison to standard DC motors. Specifically, homopolar machines use current collectors to transfer current between each rotating armature turn and each stationary stator turn. One limitation of the utility of homopolar machines is the heavy dependence on current collectors that are potentially unreliable, a large source of efficiency loss, and maintenance problems.

An important factor in a current collector's performance is its contact pressure with the armature. Performance is measured in terms of current collector wear and current carrying capability. Maintaining an ideal contact pressure is difficult because in a homopolar machine the current collectors must be in the magnetic field zone where the collectors are subject to bending and torque. Homopolar machines have been designed with mechanisms that help to maintain an ideal contact pressure, but these result in size, weight, and cost penalties, and introduce new sources of reliability problems. Thus, there is a need for a method and/or apparatus that helps to reduce the wear and tear of current collectors in homopolar machines.

SUMMARY OF THE INVENTION

The present invention advantageously addresses the needs above as well as other needs by providing an apparatus that includes a homopolar machine. The homopolar machine includes a shaft, an armature assembly coupled to the shaft, an outer flux return that encloses the armature assembly, an inner flux return coupled to the shaft, and means for producing a magnetic field asymmetry within the inner flux return that produces an axial force on the shaft.

Another aspect of the present invention provides a method of operating a homopolar machine. The method includes the steps of energizing a first field coil in the homopolar machine to a first excitation level; and energizing a second field coil in the homopolar machine to a second excitation level that is different than the first excitation level to produce a magnetic field asymmetry within the homopolar machine that produces an axial force on a shaft of the homopolar machine.

And another aspect of the present invention provides a homopolar machine that includes a shaft, an armature assembly, an outer flux return, and a plurality of stator-current collector arrays. The armature assembly is coupled to the shaft and includes a plurality of armature conductor

turns. The outer flux return encloses the armature assembly. The plurality of stator-current collector arrays are coupled to the outer flux return and encircle the armature assembly. Each stator-current collector array includes a plurality of current collectors that maintain substantially constant contact pressure with the armature conductor turns in the presence of high magnetic fields to provide a sliding electrical current interface with the armature conductor turns.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects featured and advantages of the present invention will be more apparent from the following more particular description thereof presented in conjunction with the following drawings herein;

FIG. 1 is a perspective view illustrating the main components of a homopolar machine in accordance with the present invention;

FIG. 2 is a top planar cross-sectional view of the homopolar machine of FIG. 1;

FIG. 3 is a side view illustrating a homopolar machine in accordance with the present invention having an external thrust bearing;

FIG. 4 is a partial top planar cross-sectional view of the homopolar machine of FIG. 1 illustrating the pair of field coils energized to equal but opposite polarity amp-turns and the resulting magnetic fields;

FIG. 5 is a partial top planar cross-sectional view of the homopolar machine of FIG. 1 illustrating the pair of field coils energized to different amp-turns relative to each other causing a magnetic flux asymmetry that produces a compensating axial force in accordance with the present invention;

FIG. 6 is a partial side view taken along line 6—6 in FIG. 2 illustrating one complete stator-current collector assembly and part of an armature assembly that may be employed in the homopolar machine of FIG. 1;

FIG. 7 is an end view as seen from line 7—7 in FIG. 6 of part of the stator-current collector assembly and armature shown in FIG. 6;

FIG. 8 is a perspective view illustrating a ten conductor turn armature assembly that may be used in accordance with the present invention;

FIG. 9 is a close-up perspective view illustrating a portion of the ten conductor turn armature assembly shown in FIG. 8; and

FIG. 10 is a close-up perspective view illustrating the stator-current collector array shown in FIG. 8.

Corresponding reference characters indicate corresponding components throughout several figures.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

The following description of the presently contemplated best mode of practicing the invention is not to be taken in a limiting sense, but is made merely for the purpose of describing the general principle of the invention. The scope of the invention should be determined with reference to the claims.

In accordance with the principles of the present invention, a homopolar machine is described that addresses the problems discussed above with respect to thrust bearing wear and current collector performance.

With respect to thrust bearing wear, a homopolar machine in accordance with the present invention, designed as either

a motor or a generator, produces an axial counterforce on the rotating shaft to compensate for the load on the shaft's thrust bearing to reduce wear and noise and prolong bearing life. The counterforce relieves the thrust bearing load and is produced through magnetic interaction between the shaft and the machine's field coils. As will be discussed below, this is accomplished by positioning part of the machine's iron flux return on the shaft (herein referred to as the inner flux return), which magnetically couples with the magnetic field produced by the field coils. An axial force is produced on the shaft by adjusting the magnetic field produced by the field coils by adjusting the current flow through the field coils to different levels. This can be accomplished without affecting the machine's torque, as long as the ampere-turns change in one coil is maintained equal and opposite of the ampere-turns change in the other coil.

As mentioned above, a bearing's wear rate or "life" reduces exponentially with the load or force on the bearing, so even fractional reductions in bearing load can prolong a bearing's life significantly. An additional benefit of reduced pressure on the thrust bearing is also reduced acoustic noise, an important factor in applications that require quieter running machines, such as submarine propulsion systems.

With respect to current collector performance, a homopolar machine in accordance with another aspect of the present invention has a configuration that uses current collectors that maintain substantially constant contact pressure in the presence of high magnetic fields. This is because the magnetic field lines are oriented in substantially the same direction as the direction of current flow, so the $I \times B$ force that would disturb the contact pressure is minimized. As will be discussed below, the current collectors are flexible and may be made from either electrically conductive fibers or stacked strips such that they bear up against the armature so that the pressure is maintained by the spring constant of the current collector material.

Referring to FIGS. 1 and 2, there is illustrated a homopolar machine 100 in accordance with the present invention. The homopolar machine 100 may be operated as either a direct current (DC) motor or a generator. In general, the homopolar machine 100 includes an outer flux return 102, a shaft 104, an armature assembly 106, several stator-current collector arrays 108, and two field coils 110, 112. The preferred geometry of the homopolar machine 100 is such that the pair of field coils 110, 112 are circumferentially shaped and are mounted in line (along a common z-axis) with the armature assembly 106 located between them. The outer flux return 102 substantially surrounds all the components. By way of example, the homopolar machine 100 may have a radius of approximately 0.5 meters.

The outer flux return 102 is preferably substantially cylindrical in shape and is constructed from a material with high magnetic permeability, such as but not limited to, iron or steel. The outer flux return 102 encloses the machine 100's internal components and substantially reduces the amount of magnetic flux radiating from the machine. The outer flux return 102 may serve as a substantial structure that reacts the machine's torsional and magnetic loads and may be augmented with additional structural reinforcement 114.

The shaft 104 is supported by radial bearings 116 and a thrust bearing 118. As shown in FIG. 2, the thrust bearing 118 is internal to the homopolar machine 100. Alternatively, FIG. 3 illustrates the scenario where a thrust bearing 119 is external to a homopolar machine 101, being part of an interconnecting drive-train. The thrust bearing 119 maintains the axial position of a shaft 105.

The armature assembly **106** and the stator-current collector arrays **108** are preferably comprised of electrically conductive elements made from copper, copper alloy, or other materials with similar electrical properties. The armature assembly **106** preferably includes a plurality of stacked armature electrical conducting turns **120, 122, 124, 126, 128** separated by electrical insulation **130**. The plurality of armature conducting turns **120, 122, 124, 126, 128** are essentially stacked concentric cylinders having a squared-U, radial-axial cross-sectional shape as shown. Each of the conducting turns may be comprised of a single element or a plurality of elements. In the example shown, the armature assembly **106** includes five conducting turns **120, 122, 124, 126, 128**. It should be well understood, however, that the armature assembly **106** may include any number of conducting turns. Furthermore, each armature conductor turn **120, 122, 124, 126, 128** is preferably distributed symmetrically around the circumference, therefore resulting in a substantially uniform electric current distribution around the circumference.

The armature conducting turns **120, 122, 124, 126, 128** conduct current to several current collectors **132** and stator conductor turns **134** that are electrically connected in series between the armature conducting turns **120, 122, 124, 126, 128** to form one of the stator-current collector arrays **108**. A plurality of stator-current collector arrays **108** are preferably distributed circumferentially and symmetrically around the armature assembly **106** to form the stator. This distribution aids in the desired circumferentially uniform distribution of current throughout all the electrically conductive elements of the machine. The uniformity of current distribution circumferentially around the machine is desirable to prevent thermal hot spots and noise harmonics. The electric current carrying elements may be water-cooled via internal cooling channels, cooled by direct spray of a liquid coolant compatible for use with exposed electrical conductors, forced air or internal circulated gas, or any combination of these methods. Such methods would be chosen based on the requirements and heat dissipation characteristics of the machine.

The field coils **110, 112**, which provide the background magnetic field, may be resistive electromagnet coils or superconducting coils. As will be discussed below, the strength of each of the field coils **110, 112** is varied, and therefore, permanent magnets are not used for the field coils **110, 112**. Preferably, the field coils **110, 112** are circumferentially continuous in geometry and are superconducting coils that are formed from circumferentially wrapped electrically superconducting wire. Superconducting coils are the preferred choice due to the higher magnetic fields that may be produced, which results in a smaller and lighter motor. Superconducting wire provides zero or nearly zero electrical resistance when cooled to low temperatures. This property allows more electrical current to flow through the coils as compared with ordinary wire, such as copper wire, which allows higher magnetic fields to be produced to obtain more powerful machines for a given size and weight. Thus, superconducting coils do not contribute significantly to the inefficiency of the machine.

For each of the field coils **110, 112** that is manufactured from superconducting wire, a field coil cryostat **136** is provided that is essentially a vacuum vessel. The vacuum vessel has disposed within it the field coils **110, 112**, which are structurally supported by cryostat cold-to-warm support structures **138**. The field coil cryostat **136** will be discussed in further detail below.

In accordance with the present invention, an inner flux return **140** is positioned around the inner perimeter of the

armature assembly **106**. The inner flux return **140** is preferably cylindrical in shape and is constructed from a material with high magnetic permeability, such as but not limited to iron, steel or other ferromagnetic material. The inner flux return **140** is mechanically coupled to the machine shaft **104** via a shaft structure **142** and is encircled by the armature assembly **106**, i.e., circumferentially surrounded by the armature assembly **106**. The armature assembly **106** and the inner flux return **140** both comprise a rotor assembly, which is rotationally disposed within the stator (i.e., the plurality of stator-current collector arrays **108**). The inner flux return **140** plays an important role in the present invention in that it serves a dual role of producing the axial compensating force and directing the magnetic flux across the armature assembly **106** and stator to maximize flux coupling for higher power utilization.

The field coils **110, 112**, outer flux return **102**, armature assembly **106**, stator current collector arrays **108**, and inner flux return **140** are preferably configured in a cylindrical geometry and assembled so they all share a common central geometric axis **144**. The common central geometric axis **144** is also coincident with the rotational axis of the shaft **104** and the central magnetic axis of the field coils **110, 112**. During operation, the field coils **110, 112** are energized so that their polarities are opposite, causing their magnetic flux lines to repel and deflect into the inner flux return **140** and outer flux return **102**, and across the armature assembly **106** and stator-current collector arrays **108**. Because the magnetic fields are uniformly distributed in the circumferential direction, no difference in magnetic flux or multiple magnetic poles are encountered by conductive elements of the armature assembly **106** as it rotates, thus functioning as a homopolar machine.

The outer flux return **102** and the inner flux return **140**, being constructed from high magnetically permeable material, direct the magnetic field generated by the field coils **110, 112** substantially towards the region disposed by the armature assembly **106**. The field lines generated by the field coils **110, 112** are also directed so that they are substantially parallel to the outward radial direction of current flow through the current collectors **132**. This minimizes any forces generated within the current collectors **132** that arise from current flow that is non-parallel to the field lines, which minimizes current collector deflections in the circumferential direction. These deflections can disturb the contact pressure between the current collector and the armature.

When the homopolar machine **100** is operated as a motor, current is supplied to the rotating armature assembly **106** from the stationary stator via the current collectors **132** located between the armature and the stator. The motor torque is developed as electric current flows at right angles to the flux generated by the stationary field coils **110, 112**. When the homopolar machine **100** is operated as a generator, the mechanically-driven rotating armature assembly **106** generates current as its conductive elements are moved at right angles to the flux, and the current is transported to the stationary stator via the current collectors **132**.

In accordance with the present invention, the homopolar machine **100** is capable of producing an axial force on the shaft **104** to compensate for external axial forces imposed on the shaft **104**. As described above, such external axial forces can be caused, for example, by a connected propulsor in a ship motor scenario. In general, the compensating axial force is created by changing the current excitation of the field coils **110, 112**, which results in an axial magnetic flux asymmetry in the inner flux return **140**.

Referring to FIG. 4, when both identical field coils **110**, **112** are energized to the same level of current but with opposite polarity, they each produce an equal but opposing magnetic field as shown. The inner flux return **140** deflects the magnetic field lines so that they are focused more strongly in the armature assembly **106** interaction region. Furthermore, the field lines are oriented substantially parallel to the direction of the current flow in the stator-current collector arrays **108** region (radially outward). This orientation minimizes the force exerted on the current collectors **132** in the circumferential direction by minimizing the current and field line ($I \times B$) force. By way of example, the illustrated homopolar machine **100** may have an outer diameter of 1 meter and be capable of producing 5000 HP at 1200 rpm, and in this particular example, the field coils **110**, **112** are both energized to produce 1.5×10^6 Amp-turns.

Referring to FIG. 5, by altering the current flow in the field coils **110**, **112** so the current flows (or amp-turns) are different from each other, the homopolar machine **100** produces a compensating axial force **141** on the shaft **104**. When the field coils **110**, **112** are energized to different amp-turns levels relative to each other, an axial flux asymmetry is caused that produces the axial force **141** on the inner flux return **140** mounted to the shaft **104**. External axial forces **143** imposed on the shaft **104** are compensated by the force **141** generated in the inner flux return **140** by the asymmetric magnetic flux. The direction of the compensating axial force **141** is selected to be opposite that of the thrust bearing load. The force **141** is reacted by the thrust bearing **118**, and also by the field coils **110**, **112**, and into the outer flux return **102** through various interconnecting elements. The compensating axial force **141** helps to reduce thrust bearing wear and increases thrust bearing reliability.

FIG. 5 illustrates the intended effect where the current in one field coil **110** is raised by 10% and the current in the other field coil **112** is lowered by 10%. In this particular example, the first field coil **110** is energized to 1.35×10^6 Amp-turns (Peak Field=4.9 Tesla) and the second field coil **112** is energized to 1.65×10^6 Amp-turns (Peak Field=6 Tesla). The peak magnetic field in the stronger coil **112** is about 6 Tesla, and the average coil current density in it is about 10 kA/cm². These are reasonable parameters for a low temperature superconducting coil. In this case, the axial force **141** induced on the shaft **104** by the flux asymmetry is predicted to be 20,000 lbs.

The current in the field coils **110**, **112** can be altered to produce this compensating force **141**, while the total integrated magnetic field-length product through the armature remains constant. This means that the rotational torque, and therefore the rotational speed of the homopolar machine **100**, need not be interrupted.

Thus, the stationary electromagnetic field coils **110**, **112** produce all the magnetic flux necessary for the machine to develop power, and a substantial fraction of this flux is coupled to the inner flux return **140** that is positioned between the field coils **110**, **112** and mounted on the rotating shaft **104**. An axial asymmetry in the flux distribution is created by energizing the field coils **110**, **112** to different levels, which results in an induced axial force **141** on the rotating shaft **104**. The asymmetric axial flux that is created by the field coils **110**, **112** is produced by raising the excitation of one field coil and lowering the excitation of the other field coil approximately by the same amount, so the total flux across the armature and stator interaction region remains constant or substantially constant. This allows the shaft **104**'s induced axial force **141** component to be varied while the shaft's rotational torque is not affected. The

direction of the induced axial force **141** is selected to compensate for mechanical thrust induced on the shaft **104**.

The present invention does not rely on additional auxiliary coils since the main field coil pair **110**, **112** performs the dual function of producing magnetic flux for rotational torque and axial thrust. Furthermore, it is not necessary to vary the mechanical positioning offset of the shaft **104** relative to the field coil alignment. The homopolar machine **100**'s magnetic flux path is also designed to minimize magnetically induced forces that may upset the mechanical pressure exerted by the current collectors **132** on the armature assembly **106**.

Referring to FIG. 6, there is illustrated a top view, looking down on the surface of the rotor, of one complete stator-current collector array **158** and part of the armature assembly **106**. The illustrated example is for an armature assembly **106** with five armature conductor turns **120**, **122**, **124**, **126**, **128**. Again, it should be well understood that the armature assembly **106** may have a different number of armature conductor turns. The stator-current collector array **158** includes stator conductor turns **146**, **148**, **150**, **152**, **154**, **156**, **159**, **160**, **162**, **164**, **165**, **167**. Several stator-current collector arrays **108**, like the array **158**, are arranged circumferentially around the homopolar machine **100** to distribute the current.

FIG. 7 illustrates an end view of a portion of the stator-current collector array **158** and the armature conductor turn **120**. The stator conductor turns **148**, **160** are electrically connected to their corresponding circumferential busbar **166**, while the other illustrated stator conductor turns **146**, **150**, **152**, **154**, **156**, **162** are electrically insulated from the busbar **166** with electrical stator turn-to-turn insulation **168**. The stator conductor turns **146**, **150**, **152**, **154**, **156**, **162** are electrically insulated from the busbar **166** because they correspond to busbars associated with other armature conductor turns. Specifically, the stator conductor turn **150** corresponds to a bus bar (not shown) associated with the armature conductor turn **122**, the stator conductor turn **152** corresponds to a bus bar (not shown) associated with the armature conductor turn **124**, the stator conductor turn **154** corresponds to a bus bar (not shown) associated with the armature conductor turn **126**, and the stator conductor turn **156** corresponds to a bus bar (not shown) associated with the armature conductor turn **128**. In the illustrated embodiment, pairs of stator turns connect to a common busbar. For example, the stator conductor turns **148** and **160** are electrically in parallel and connect to the busbar **166**.

The busbar **166** includes five current collectors **132** that conduct current to or from the armature conductor turn **120**. It should be well understood, however, that any number of current collectors **132** may be attached to the busbar **166**.

Referring to FIGS. 6 and 7 together, DC electric current is routed through the stator terminals **170**, **171**, **172**, **173** such that current flows between the positive (+) terminals **170**, **171** and negative (-) terminals **172**, **173**. Specifically, current that enters the positive (+) terminals **170**, **171** flows through the stator conductor turns **146**, **159**, then through a circumferential busbar (not shown), then through a current collector (not shown), then through the armature conductor turn **120**, then through the current collectors **132**, then through the circumferential bus bar **166**, then through the stator conductor turns **148**, **160**, and continues in a similar manner through the remaining armature conductor turns **122**, **124**, **126**, **128**, and out the negative (-) terminals **172**, **173**.

In accordance with the present invention, the current collectors **132** comprise a flexible electrically conductive

material, such as but not limited to, electrically conductive fibers or foils made from copper or copper alloys or stacked strips. The current collectors **132** are configured to exhibit a spring rate that results in an applied pressure on the armature conductor turn **120** when solidly connected to the circumferential busbar **166**. Furthermore, the current collectors **132** are configured to be free to bear up against the outer edge of the armature turn **120**'s smooth surface. Thus, the current collectors **132** are flexible such that they bear up against the armature so that the pressure is maintained by the spring constant of the current collector material.

As the current collectors **132** wear, the pressure will be relaxed only partially because each current collector is flexible owing to its spring constant. The current collector pressure, however, can be undesirably affected by forces generated on it due to current flowing through it in the presence of a magnetic field. In the present invention, the flux return geometry and field coil configuration are designed so that the magnetic field lines are substantially in the same direction as the direction of the current flow through the current collectors **132**, i.e., radially outward. Since the current flowing through the current collectors passes substantially parallel to the field lines, minimal force ($I \times B$) is induced on the flexible collectors **132**. The force is minimal enough such that the flexible collectors **132** are not deflected enough to change the contact pressure enough to significantly degrade performance.

The wear rate, electrical resistance losses, and friction losses at the current collector **132** and armature conductor turn **120** interface can be mitigated by the presence of a controlled atmospheric chemical composition within the machine enclosure, or by the addition of moisture in the armature region in the form of water humidity or direct wetting with a liquid compatible for use with exposed electrical conductors.

As mentioned above, the armature assembly **106** may have any number of armature conductor turns, and there may be any number of current collectors **132** attached to the busbar **166**. By way of example, FIG. **8** illustrates an armature assembly **200** and a stator-current collector array **202** that may be used in accordance with the present invention. Although the armature assembly **200** would typically be encircled by several stator-current collector arrays, only the one stator-current collector array **202** is illustrated.

The armature assembly **200** includes ten armature conductor turns **206, 208, 210, 212, 214, 216, 218, 220, 222, 224**. The front portion of the stator-current collector array **202** includes stator conductor turns **226, 228, 230, 232, 234, 236, 238, 240, 242, 244, 246**, and the terminals **248, 250**. Referring to FIG. **9**, the stator conductor turns **226, 228, 230, 232, 234, 236, 238, 240, 242, 244, 246** are electrically coupled to the busbars **252, 254, 256, 258, 260, 262, 264, 266, 268, 270, 272**, respectively. The stator conductor turns **228, 230, 232, 234, 236, 238, 240, 242, 244, 246** are also electrically coupled to the busbars **274, 287, 285, 283, 281, 279, 277, 275, 273, 272**, respectively. Furthermore, the stator conductor turns **228, 276** are electrically coupled to the busbars **274** and **254**.

Referring to FIG. **10**, each of the busbars includes ten current collectors attached thereto. For example, the busbar **274** includes the ten current collectors **278, 280, 282, 284, 286, 288, 290, 292, 294, 296**, and the busbar **252** includes the ten current collectors **298, 300, 302, 304, 306, 308, 310, 312, 314, 316**. Thus, any number of current collectors may be attached to the busbars in accordance with the present invention. The current collectors are attached to the busbars

by means of brush mounts (also referred to as brush holders or brush mount interfaces). For example, the current collector **298** is attached to the busbar **252** by means of the brush mount **320**, and the current collector **278** is attached to the busbar **274** by means of the brush mount **322**.

With respect to the field coils **110, 112**, superconducting coils are typically constructed by winding superconducting wire. They may be categorized as low temperature superconductors, which typically must operate in the range of 4 K to 12 K, or high temperature superconductors, which may be capable of operating at temperatures up to 80 K. Typical materials for low temperature superconductors included niobium titanium (NbTi) or niobium and tin (Nb₃Sn), both of which are typically formed in a matrix with copper or copper alloys to form wire. High temperature superconductors use other constituents, such as bismuth or yttrium formed in a metal matrix, typically silver.

Superconducting coils, either high or low temperature, are typically structurally suspended within a cryostat. A cryostat is comprised of a vacuum vessel and a support structure that suspends the coil within it so minimum heat flows into the coil from the structure. The support structure itself is typically strong enough to support the coil against various forces that may be present. The field coils **110, 112** may be cooled within the cryostat **136** by a cryogenic fluid such as liquid helium which typically operates at a temperature of 4.2 K, or other cryogenic fluids can be used such as liquid nitrogen at 77 K, if the superconducting coil is designed to operate at that temperature. The field coils **110, 112** may also be cooled by devices known as cryocoolers, which are closed cycle cryogenic refrigeration devices that can lower the field coil's temperature to the required level.

With respect to the field coil cryostat **136**, the cryostat cold-to-warm support structure **138** is preferably comprised of materials strong enough to physically support the field coil **110, 112** while minimizing the amount of heat that can flow to it from the vacuum vessel, which is at room temperature. Because they are superconducting coils, the field coils **110, 112** are at a much colder temperature, typically in the range of 4 K to 12 K for low temperature superconductors and up to 80 K for high temperature superconductors.

Each of the field coils **110, 112** may be cooled by connecting them to devices called "cryocoolers" via thermally conducting links (not shown). The cryocoolers are generally part of a closed cycle refrigeration system. Another method that can be used to cool the field coils **110, 112** to required temperature makes use of another vessel (not shown) disposed between the coil and the vacuum vessel. The vessel is filled with a liquid cryogen, such as but not limited to liquid helium, liquid hydrogen, or liquid nitrogen, depending on the temperature requirements of the superconductor material used in the field coils **110, 112**. In either method, a cryostat thermal shield **174**, comprising a thermally conductive material such as but not limited to copper or aluminum, is preferably disposed between the cryostat vacuum vessels and the field coils **110, 112**. The cryostat thermal shield **174** is attached to the cryostat cold-to-warm support structure **138** to intercept heat conducted and radiated inward from the cryostat vacuum vessel walls and the field coil current leads **176** that would otherwise leak into the field coils **110, 112**.

The heat is intercepted at thermally conductive mechanical connections **178** between the cryostat cold-to-warm support structure **138** and the cryostat thermal shield **174**, and also at an electrically insulated but thermally conductive

mechanical connection **180** between the field coil current leads **176** and the cryostat thermal shield **174**. The intercepted heat is removed by the cryocooler (not shown) which is connected to the thermal shield **174**, or in the case where a second inner vessel filled with liquid cryogen is used (not shown), the heat may be removed through conduction of the cryogen's boil-off gases that would be routed through a thermally conductive material attached to the cryostat thermal shield **174**. The field coil cryostats **136** are mechanically supported by the outer flux return **102** via the cryostat mounts **182**.

While the invention herein disclosed has been described by the specific embodiments and applications thereof, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope of the invention set forth in the claims.

What is claimed is:

1. An apparatus that includes a homopolar machine, the homopolar machine comprising:
 - a shaft;
 - an armature assembly coupled to the shaft;
 - an outer flux return that encloses the armature assembly;
 - an inner flux return coupled to the shaft; and
 - means for producing a magnetic field asymmetry within the inner flux return for generating an axial force on the shaft to compensate an external axial force imposed on the shaft against a thrust bearing.
2. An apparatus in accordance with claim 1, wherein the homopolar machine further comprises:
 - a thrust bearing configured to bear a thrust bearing load induced on it by mechanical forces induced on the shaft, wherein the axial force on the shaft relieves at least a portion of the thrust bearing load.
3. An apparatus in accordance with claim 1, wherein the apparatus further comprises:
 - a thrust bearing configured to bear a thrust bearing load induced on it by mechanical forces induced on the shaft, wherein the axial force on the shaft relieves at least a portion of the thrust bearing load.
4. An apparatus in accordance with claim 1, wherein the means for producing a magnetic field asymmetry comprises:
 - first and second field coils located within the outer flux return and on opposite sides of the armature assembly, wherein the first field coil is energized to a different level than the second field coil to create the magnetic field asymmetry.
5. An apparatus in accordance with claim 4, wherein an excitation level of the first field coil is raised and an excitation level of the second field coil is lowered by substantially equal amounts so that an integrated magnetic field-length product through the armature assembly remains substantially constant.
6. An apparatus in accordance with claim 4, wherein the first and second field coils are cylindrically shaped and are spaced apart with a common central magnetic axis.
7. An apparatus in accordance with claim 4, wherein the first and second field coils are of opposite polarity when energized with electric current.
8. An apparatus in accordance with claim 4, wherein the first and second field coils comprise superconducting coils.
9. An apparatus in accordance with claim 1, wherein the inner flux return comprises a ferromagnetic material.
10. An apparatus in accordance with claim 1, wherein the inner flux return comprises a cylindrical shape.
11. An apparatus in accordance with claim 1, wherein the inner flux return is encircled by the armature assembly.

12. An apparatus in accordance with claim 1, wherein the inner flux return is mechanically coupled to the shaft via a shaft structure.

13. An apparatus in accordance with claim 1, wherein the means for producing a magnetic flux asymmetry further comprises:

first and second field coils, wherein the inner flux return is disposed between the first and second field coils so that it couples with a magnetic flux produced by the first and second field coils to produce the axial force on the shaft in response to the first and second field coils being energized to different ampere-turns levels relative to each other.

14. An apparatus in accordance with claim 1, wherein the outer flux return acts in opposition to the axial force produced on the shaft via interconnecting structural elements.

15. An apparatus in accordance with claim 1, wherein the homopolar machine further comprises:

a plurality of stator-current collector arrays mounted to the outer flux return that encircle the armature assembly.

16. An apparatus in accordance with claim 15, wherein the armature assembly comprises a plurality of armature conductor turns, and wherein the stator-current collector arrays are configured so that electric current is distributed to each armature conductor turn substantially uniform around a circumference of the armature assembly.

17. An apparatus in accordance with claim 16, wherein each stator-current collector array comprises a plurality of stator conductor turns and a plurality of current collectors, and wherein the current collectors provide a sliding electrical current interface with the armature conductor turns so that electric current flows in series successively from each armature conductor turn to each stator conductor turn.

18. An apparatus in accordance with claim 1, wherein the armature assembly and the outer flux return are configured to direct magnetic field lines in a direction that passes substantially at right angles to current flow in most of a volume occupied by the armature assembly.

19. An apparatus in accordance with claim 1, wherein the armature assembly and the outer flux return are configured in a cylindrical geometry to share a common central geometric axis which is coincident with a rotational axis of the shaft.

20. An apparatus in accordance with claim 1, wherein the homopolar machine is configured to operate as a motor.

21. An apparatus in accordance with claim 1, wherein the homopolar machine is configured to operate as a generator.

22. A method of operating a homopolar machine, comprising:

rotating an armature assembly coupled to a shaft wherein the shaft rotates with the armature assembly;

energizing a first field coil in the homopolar machine to a first excitation level to generate a first magnetic field through the armature assembly and an inner flux return coupled to the shaft; and

energizing a second field coil in the homopolar machine to a second excitation level to generate a second magnetic field through the armature assembly and the inner flux return wherein the second excitation level is different than the first excitation level for producing a magnetic field asymmetry within the inner flux return that generates an axial force on the shaft to compensate an external axial force imposed on the shaft against a thrust bearing.

23. A method in accordance with claim 22, wherein the axial force on the shaft relieves at least a portion of a thrust

13

bearing load that is borne by a thrust bearing associated with the shaft of the homopolar machine.

24. A method in accordance with claim 22, further comprising:

5 establishing an inner flux return coupled to the shaft of the homopolar machine on which at least a portion of the axial force is produced by the magnetic field asymmetry.

25. A method in accordance with claim 22, further comprising:

10 initially energizing both the first and second field coils in the homopolar machine to an initial excitation level.

26. A method in accordance with claim 25, wherein:

14

the homopolar machine to a first excitation level comprises raising the first field coil from the initial excitation level to the first excitation level; and

the step of energizing a second field coil in the homopolar machine to a second excitation level comprises lowering the second field coil from the initial excitation level to the second excitation level.

27. A method in accordance with claim 26, wherein the initial excitation level is substantially centered between the first and second excitation levels so that an integrated magnetic field-length product through an armature assembly of the homopolar machine remains substantially constant.

* * * * *