



US010958974B2

(12) **United States Patent**  
**Glazier et al.**

(10) **Patent No.:** **US 10,958,974 B2**

(45) **Date of Patent:** **\*Mar. 23, 2021**

(54) **METHODS AND SYSTEMS FOR CONTROLLING MEDIA DISPLAY IN A SMART MEDIA DISPLAY ENVIRONMENT**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(71) Applicant: **Google LLC**, Mountain View, CA (US)

(56) **References Cited**

(72) Inventors: **Adam Glazier**, Oakland, CA (US);  
**Tomer Shekel**, San Francisco, CA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Google LLC**, Mountain View, CA (US)

8,880,051 B2 11/2014 Ghosh et al.  
9,106,720 B1\* 8/2015 Hunt ..... H04L 67/30  
(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.  
  
This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

CN 104616675 5/2015  
WO WO 2014145140 9/2014

OTHER PUBLICATIONS

(21) Appl. No.: **16/179,579**

Examination Report dated Oct. 29, 2019 in EP Patent Application No. 17703865.0.

(22) Filed: **Nov. 2, 2018**

(Continued)

(65) **Prior Publication Data**

US 2019/0075358 A1 Mar. 7, 2019

*Primary Examiner* — Cai Y Chen  
(74) *Attorney, Agent, or Firm* — Byrne Poh LLP

**Related U.S. Application Data**

(63) Continuation of application No. 15/002,276, filed on Jan. 20, 2016, now Pat. No. 10,123,077.

(57) **ABSTRACT**


(51) **Int. Cl.**  
**H04N 21/41** (2011.01)  
**H04N 21/45** (2011.01)

(Continued)

A method is implemented on a casting device to enable a follow-me mode in which the casting device controls display of media content on an output device coupled to the casting device. The casting device detects a client device associated with the casting device, and determines a proximity of the client device. In accordance with a determination that the client device is within a proximity threshold of the casting device, the casting device receives content information associated with content recently accessed by the client device, obtains the content from a content source in accordance with the content information, and outputs the obtained content to an output device in accordance with the content information.

(52) **U.S. Cl.**  
CPC ... **H04N 21/4524** (2013.01); **H04N 21/41407** (2013.01); **H04N 21/4333** (2013.01); **H04N 21/43615** (2013.01); **H04N 21/43637** (2013.01); **H04N 21/4432** (2013.01); **H04N 21/4432** (2013.01); **H04N 21/4432** (2013.01); **H04N 21/4436** (2013.01); **H04N 21/44218** (2013.01); **H04N 21/44227** (2013.01); **H04N 21/485** (2013.01)

**19 Claims, 15 Drawing Sheets**



(51)	<b>Int. Cl.</b>			2014/0141714	A1*	5/2014	Ghosh .....	H04W 8/005
	<i>H04N 21/433</i>	(2011.01)						455/39
	<i>H04N 21/442</i>	(2011.01)		2014/0274185	A1	9/2014	Luna et al.	
	<i>H04N 21/414</i>	(2011.01)		2014/0280865	A1	9/2014	Albertson et al.	
	<i>H04N 21/436</i>	(2011.01)		2015/0128194	A1	5/2015	Kuang et al.	
	<i>H04N 21/4363</i>	(2011.01)		2015/0215382	A1	7/2015	Arora et al.	
	<i>H04N 21/443</i>	(2011.01)		2015/0256954	A1	9/2015	Carlsson et al.	
	<i>H04N 21/443</i>	(2011.01)		2015/0314454	A1	11/2015	Breazeal et al.	
	<i>H04N 21/485</i>	(2011.01)		2015/0331666	A1	11/2015	Bucsa et al.	

(56)

**References Cited**

U.S. PATENT DOCUMENTS

9,414,105	B2*	8/2016	Rajapakse .....	H04N 21/41407
9,769,512	B2*	9/2017	Yu .....	H04N 21/44222
2004/0128065	A1	7/2004	Taylor et al.	
2005/0097595	A1	5/2005	Lipsanen et al.	
2005/0246738	A1	11/2005	Lockett et al.	
2008/0141302	A1	6/2008	Ota	
2008/0256590	A1	10/2008	Oosterholt	
2009/0052859	A1	2/2009	Greenberger et al.	
2009/0265729	A1	10/2009	Weinblatt	
2012/0284757	A1	11/2012	Rajapakse	
2013/0165164	A1	6/2013	Rowe	
2013/0332565	A1	12/2013	Wang	

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Mar. 28, 2017 in International Patent Application No. PCT/US2017/014292.  
 Notice of Allowance dated Jun. 26, 2018 in U.S. Appl. No. 15/002,276.  
 Office Action dated Jan. 9, 2017 in U.S. Appl. No. 15/002,276.  
 Office Action dated Mar. 9, 2018 in U.S. Appl. No. 15/002,276.  
 Office Action dated Apr. 13, 2017 in U.S. Appl. No. 15/002,276.  
 Office Action dated Sep. 5, 2017 in U.S. Appl. No. 15/002,276.  
 Office Action dated Jul. 1, 2020 in CN Patent Application No. 201780003582.0.  
 Summons to Attend Oral Proceedings dated Sep. 11, 2020 in EP Patent Application No. 17703865.0.

\* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7

850




FIGURE 8B

800




FIGURE 8A

900




FIGURE 9




FIGURE 10B

FIGURE 10A




FIGURE 11

FIGURE 12




FIGURE 13A




FIGURE 13B

At a casting device having one or more processors and memory storing instructions for execution by the one or more processors, wherein the casting device is coupled to an output device:

1400




FIGURE 14A




FIGURE 14B

1500

At a first casting device having one or more processors and memory storing instructions for execution by the one or more processors, wherein the first casting device is coupled to a display input of an output device:




FIGURE 15

**METHODS AND SYSTEMS FOR  
CONTROLLING MEDIA DISPLAY IN A  
SMART MEDIA DISPLAY ENVIRONMENT**

CROSS-REFERENCE TO RELATED  
APPLICATION

This application is a continuation of U.S. patent application Ser. No. 15/002,276, filed Jan. 20, 2016, which is hereby incorporated by reference herein in its entirety.

TECHNICAL FIELD

This application relates generally to computer technology, including but not limited to methods and systems for controlling display of media content on one or more output display devices within a smart media display environment based on user proximity and/or location detected with respect to one or more casting devices.

BACKGROUND

Media display devices have been widely applied to display media content to audience who gather around the media display devices. As far as they do not interfere with each other, multiple media display devices can be distributed at different locations of a media display environment (e.g., a family household or an office building) to display media content individually or simultaneously. Many existing media display devices are paired with casting devices (e.g., an Apple TV box and a Google TV box) or act as smart television devices to receive television broadcast, satellite broadcast or Internet-based media content. However, these existing media display devices have to be powered on and off individually when a user presses a power button that is located either on a media display device or on a remote control device that is communicatively coupled to its associated media display device.

Under some circumstances, when a user is moving around in a media display environment including multiple media display devices (e.g., from a living room to a bedroom in a family household), he or she has to power off a display device, remember a content source that provides the content displayed thereon, power on another display device, and tune this other display device to continue the display of media content that has been terminated on the previously viewed display device. This could be inconvenient for many users who desire to continue to watch the same media content while moving around in a media environment.

SUMMARY

Accordingly, there is a need for smart media display control, and specifically, a need to create a smart media display environment where display of media content is controlled automatically without user intervention. In various implementations of this application, a smart media display environment includes multiple media display devices each disposed at a distinct location. Each media display device is coupled to a casting device (e.g., a set top box) that is configured to detect a user's proximity to the casting device. The casting device applies detected information of the user proximity to switch the media player device between an active mode and an inactive mode. Furthermore, the casting devices of the smart media environment determine a user location within the smart media display environment based on the user proximity informa-

tion collected at individual casting devices. The casting devices then use the proximity information to support a follow-me mode in which media content that has been watched by a user follows a user to the user location and continues to be displayed at a media display device located at the detected user location. Such methods optionally complement or replace conventional methods of requiring an audience to use a remote control or a client device to control the display of the media content and enabling automatic control of the media display devices without user intervention.

In accordance with one aspect of this application, a method is implemented on a casting device having one or more processors and memory storing one or more programs for execution by the one or more processors. The casting device is coupled to an output device, and the method is implemented to control display of media content on the output device after it is determines that the output device operates at an inactive state. The method includes detecting a client device associated with the casting device, and determining a proximity of the client device, including determining whether the client device is within a proximity threshold from the casting device. The method further includes in accordance with a determination that the client device is within the proximity threshold from the casting device, controlling the output device to change from the inactive state to an active state, and receiving media content from one or more content sources for display on the output device.

In accordance with another aspect of this application, an electronic device is configured to control display of media content on an output device that is coupled to the electronic device. The electronic device includes one or more processors, and memory storing one or more programs to be executed by the one or more processors. The one or more programs further include instructions for implementing the operations of the above method for controlling the display of the media content.

Further, in accordance with one aspect of this application, a method is implemented on a casting device having one or more processors and memory storing one or more programs for execution by the one or more processors. The casting device is coupled to an output device, and the method is implemented to enable a follow-me mode in which the casting device controls display of media content on the output device. The method includes detecting a client device associated with the casting device, and determining a proximity of the client device. The method further includes in accordance with a determination that the client device is within a proximity threshold of the casting device, receiving content information associated with content recently accessed by the client device, obtaining the content from a content source in accordance with the content information, and outputting the obtained content to an output device in accordance with the content information.

In accordance with another aspect of this application, an electronic device is configured to control display of media content on an output device that is coupled to the electronic device according to a follow-me mode. The electronic device includes one or more processors, and memory storing one or more programs to be executed by the one or more processors. The one or more programs further include instructions for implementing the operations of the above method for controlling the display of the media content according to the follow-me mode.

In accordance with some implementations, a casting device includes means for performing the operations of any of the methods described above.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the various described implementations, reference should be made to the Description of Implementations below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

FIG. 1 is an example smart media display environment in accordance with some implementations.

FIG. 2 is an example operating environment in which casting devices interact with a client device or a server system of the smart media display environment in accordance with some implementations.

FIG. 3 is another example operating environment in which casting devices interact with a client device, smart home devices or a server system of the smart media display environment in accordance with some implementations.

FIG. 4 is a block diagram illustrating an example client device that is applied for automatic control of display of media content in a smart media display environment in accordance with some implementations.

FIG. 5 is a block diagram illustrating an example casting device that is applied for automatic control of display of media content in a smart media display environment in accordance with some implementations.

FIG. 6 is a block diagram illustrating an example smart home device in a smart media display environment in accordance with some implementations.

FIG. 7 is a block diagram illustrating an example server system of a smart media display environment in accordance with some implementations.

FIGS. 8A and 8B are two example user interfaces displayed on a display of a client device for controlling media display associated with media applications in accordance with some implementations.

FIG. 9 is an example user interface displayed on a display of a client device for controlling a schedule for an automatic media output mode and a follow-me mode in accordance with some implementations.

FIGS. 10A and 10B are two example user interfaces displayed on a display of a client device for controlling an automatic media output mode and a follow-me mode of a casting device in accordance with some implementations, respectively.

FIG. 11 is another example user interface displayed on a display of a client device for controlling a schedule for an automatic media output mode and a follow-me mode of a media application in accordance with some implementations.

FIG. 12 is an example user interface that displays media content on a display of a client device in accordance with some implementations.

FIGS. 13A and 13B are two example user interfaces displayed on a display of a client device after a casting device detects a proximity of the client device in accordance with some implementations.

FIGS. 14A and 14B are flow diagrams illustrating a method of controlling display of media content for automatic media output based on user proximity or location in accordance with some implementations.

FIG. 15 is a flow diagram illustrating a method of controlling display of media content based on user proximity in accordance with some implementations.

Like reference numerals refer to corresponding parts throughout the several views of the drawings.

#### DETAILED DESCRIPTION

In various implementations of the application, a smart media display environment includes at least one output device that is coupled to a casting device and configured to display media content streamed by the casting device. The smart display environment is created to control the at least one output device and the display of the media content automatically and with no or little user intervention. The casting device detects a user's proximity to the casting device, or the user's location within the smart media display environment. In some implementations, the casting device applies detected information of the user proximity to switch the media player device between an active mode and an inactive mode. For example, the casting device located at a specific location determines that the user is in proximity, and powers on an output device that is coupled to the casting device. It is noted that such automatic control of media display does not need user intervention to power on or control the output device when a user approaches the casting device.

Further, in some implementations, the casting device uses user proximity information to support a follow-me mode in which display of media content that has been watched by a user follows a user to a new user location and continues to be displayed at an output device located at the new user location. Specifically, in an example, a user is moving around in the smart media display environment including multiple output devices for displaying media content (e.g., from a living room to a bedroom in a family household). When the user leaves the living room, she does not need to power off an output device she has watched or remember a content source that provides the content displayed thereon. Rather, the output device could be automatically turned off or muted according to predetermined media control settings. When the user enters the bedroom, another output device located there will be powered on automatically and tuned to continue the display of the media content from where it has been terminated on the previously watched output device. Thus, such methods complement or replace conventional methods of requiring an audience to use a remote control or a client device to control the display of the media content, and enables control of the media display devices automatically and with no or little user intervention.

Reference will now be made in detail to implementations, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described implementations. However, it will be apparent to one of ordinary skill in the art that the various described implementations may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the implementations.

FIG. 1 is an example smart media display environment **100** in accordance with some implementations. The smart media display environment **100** includes a structure **150** (e.g., a house, office building, garage, or mobile home) with various integrated devices. It will be appreciated that devices may also be integrated into a smart media display environment **100** that does not include an entire structure **150**, such as an apartment, condominium, or office space. The depicted structure **150** includes a plurality of rooms **152**, separated at

least partly from each other via walls **154**. The walls **154** may include interior walls or exterior walls. Each room may further include a floor **156** and a ceiling **158**.

One or more media device is disposed in the smart media display environment **100** to provide media content that is stored at a local content source or streamed from a remote content source. The media devices can be classified to two categories: output devices **106** that directly output the media content to audience, and casting devices **108** that streams media content to the output devices **108**. Examples of the output devices **106** include, but are not limited to television (TV) display devices and music players. Examples of the casting devices **108** include, but are not limited to, a set-top boxes (STBs), DVD players and TV boxes. In the example smart media display environment **100**, the output devices **106** are disposed in more than one location, and each output device **106** is coupled to a respective casting device **108** or includes an embedded casting unit. The output device **106-1** includes a TV display that is hard wired to a DVD player or a set top box **108-1**. The output device **106-2** includes a smart TV device that integrates an embedded casting unit to stream media content for display to its audience. The output device **106-3** includes a regular TV display that is coupled to a TV box **108-3** (e.g., Google TV or Apple TV products), and such a TV box **108-3** streams media content received from a media content and provides an access to the Internet for displaying Internet-based content on the output device **106-3**.

In some implementations, an automatic media output mode is implemented at the casting devices **108** located in the smart media display environment **100**. In accordance with the automatic media output mode, an output device **106** automatically switches to an active state based on a proximity of a client device. Specifically, after a casting device **108** determines that an output device **106** coupled thereto operates at an inactive state, the casting device **108** detects a client device **104** associated with the casting device **108**, and determines that a proximity of the client device **104**. The casting device **108** determines whether the client device **104** is within a proximity threshold from the casting device **108**. In accordance with a determination that the client device **104** is within the proximity threshold from the casting device **108**, the casting device **108** controls the output device to change from the inactive state to an active state, and receives media content from one or more content sources for display on the output device. It is noted that when the output device **106** operates at the inactive state, the casting device **108** could power off the output device **106**, cease outputting media content to the output device **106**, cause the output device **106** to pause display of media content received from the casting device **108** and displayed thereon, cease obtaining media content from any content source, cause the output device **106** to reduce an output volume associated with media content displayed thereon, or mute the output device **106**.

In some implementations, a follow-me mode is implemented at casting devices **108** located in the smart media display environment **100**. In accordance with the follow-me mode, display of media content generally follows a user when the user moves among different locations in the smart media display environment **100**. Stated another way, when the user reaches a specific location, an output device located at the specific location is powered on and tuned to display the media content that was previously watched at a different location, allowing the user to continue to watch the media content with no or little interruption. Specifically, a first casting device **108** is located at a first location of the smart

media display environment **100**, and coupled to a display input of a first output device **106** at the first location. The first casting device **108** detects a client device **104** associated with the first casting device **106**. The first casting device **108** determines a proximity of the client device **104**. In accordance with a determination that the client device **104** is within a proximity threshold of the first casting device **108**, the casting device **108** receives content information associated with content recently accessed by the client device **104**, obtains the content from a content source in accordance with the content information, and outputs the obtained content to the first output device **106** in accordance with the content information.

Further, in some implementations, while outputting the obtained content, the first casting device **106** determines that the client device **104** is outside the proximity threshold from the first casting device **106**. The first client device **106** then implements at least one operation of powering off the output device **106**, ceasing outputting the obtained content on the output device **108**, causing the output display **108** to pause the display of the content displayed thereon, ceasing obtaining the content from the content source in accordance with the content information, causing the output device **108** to reduce an output volume associated with the obtained content, and muting the output device. As such, in the follow-me mode, when a user moves from a first location to a second location in the smart media display environment, a casting device **108** located at the first location optionally implements one of the aforementioned operations, while another casting device **108** located at the second location detects a proximity of the user and causes its own output device **106** to display media content that has been displayed to the user at the first location.

In some implementations, smart home devices may be mounted on, integrated with and/or supported by a wall **154**, floor **156** or ceiling **158** of the smart media display environment **100**. The integrated devices include intelligent, multi-sensing, network-connected devices that integrate seamlessly with each other in a smart home network and/or with a central server or a cloud-computing system to provide a variety of useful smart home functions. In various implementations of the application, a smart home device is disposed at the same location of the smart home environment **100** as a casting device **108** and/or an output device **106**, and therefore, is located in proximity to or with a known distance with respect to the casting device **108** and the output device **106**. In some implementations, the smart home device identifies a location or a proximity of a client device **104**, and directly provides to the casting device information related to the location or the proximity of the client device **104**. Alternatively, in some implementations, the smart home device provides to the casting device **108** the information related to the location or the proximity of the client device **104** indirectly via a smart media display server system **140**.

It is also noted that in some implementations, a smart home device identifies a location or a proximity of a user in person, and provides the information related to the location or the proximity of the user either directly to the casting device **108** or indirectly to the casting device **108** via the smart media display server system **140**.

The smart home devices in the smart media display environment **100** may include, but are not limited to, one or more intelligent, multi-sensing, network-connected thermostats **122**, one or more intelligent, network-connected, multi-sensing hazard detectors **124**, one or more intelligent, multi-sensing, network-connected entryway interface devices **126**

and **128** (hereinafter referred to as “smart doorbells **126**” and “smart door locks **128**”), one or more intelligent, multi-sensing, network-connected alarm systems **130**, one or more intelligent, multi-sensing, network-connected camera systems **132**, one or more intelligent, multi-sensing, network-connected microphone devices **134**, and one or more intelligent, multi-sensing, network-connected wall switches **136**. In some implementations, the smart home devices in the smart media display environment **100** of FIG. **1** includes a plurality of intelligent, multi-sensing, network-connected appliances **138** (hereinafter referred to as “smart appliances **138**”), such as refrigerators, stoves, ovens, televisions, washers, dryers, lights, stereos, intercom systems, garage-door openers, floor fans, ceiling fans, wall air conditioners, pool heaters, irrigation systems, security systems, space heaters, window AC units, motorized duct vents, and so forth. Optionally, the smart home devices have a capability of detecting a proximity of a client device or a user.

In some implementations, the smart home devices are configured to detect a presence, proximity and/or location of a user or a client device **104** carried by a user. For example, the smart doorbell **126** and/or the smart door lock **128** may detect a person’s approach to or departure from a location (e.g., a living room). The smart alarm system **130** may detect the presence of an individual within close proximity, e.g., using built-in infrared (IR) sensors. The smart wall plugs **110** may detect occupancy of a room or enclosure. The camera **132** may capture an image or a video clip at a specific location, and the image or the video clip may be processed to identify the presence of a user in the specific location (e.g., a kitchen). Moreover, in some situations, specific individuals may be identified based, for example, on their appearance (e.g., height, face) and/or movement (e.g., their walk/gait) in an image or a video clip. Alternatively, cameras **132** may additionally include one or more embedded sensors (e.g., IR sensors and motion detectors) to detect a presence, proximity or location of a user. In addition, a microphone device **124** can be regarded as a smart home device in this application, and used to determine occupancy of a location in a smart media display environment. Specifically, audio captured by the microphone device **124** may be processed to identify the presence of an occupant in a particular room. Specific individuals may be identified based, for example, on characteristic of their voices.

The smart home devices in the smart media display environment **100** may additionally or alternatively include one or more other occupancy sensors (e.g., touch screens, IR sensors, ambient light sensors and motion detectors). In some implementations, the smart home devices in the smart media display environment **100** include radio-frequency identification (RFID) readers (e.g., in each room **152** or a portion thereof) that determine occupancy based on RFID tags located on or embedded in occupants. For example, RFID readers may be integrated into the smart hazard detectors **104**.

In some implementations, in addition to containing sensing capabilities, devices **122**, **124**, **126**, **128**, **130**, **132**, **134**, **136** and **138** (which are collectively referred to as “the smart home devices” or “the smart home devices **120**”) are capable of data communications and information sharing with other smart home devices, a central server or cloud-computing system, and/or other devices (e.g., the client device **104** and the casting devices **108**) that are network-connected. Similarly, the casting devices **108** are capable of data communications and information sharing with the smart home devices, a central server or cloud-computing system, and/or other devices (e.g., the client device **104** and the other

casting devices **108**) that are network-connected. Data communications may be carried out using any of a variety of custom or standard wireless protocols (e.g., IEEE 802.15.4, Wi-Fi, ZigBee, 6LoWPAN, Thread, Z-Wave, Bluetooth Smart, ISA100.11a, WirelessHART, MiWi, etc.) and/or any of a variety of custom or standard wired protocols (e.g., Ethernet, HomePlug, etc.), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

In some implementations, the casting devices **108** and the smart home devices serve as wireless or wired repeaters. In some implementations, a first one of and the casting devices **108** communicates with a second one of the casting devices **108** and the smart home devices via a wireless router. The casting devices **108** and the smart home devices may further communicate with each other via a connection (e.g., network interface **160**) to a network, such as the Internet **112**. Through the Internet **112**, the casting devices **108** and the smart home devices may communicate with a smart media display server system **140** (also called a central server system and/or a cloud-computing system herein). Optionally, the smart media display server system **140** may be associated with a manufacturer, support entity, or service provider associated with the casting devices **108** and the media content displayed to the user. Accordingly, the smart media display server system **140** may include one or more content hosts **104** that provide the displayed media content, and a casting device host **116** associated with the casting devices **108**.

In some implementations, the network interface **160** includes a conventional network device (e.g., a router). The smart media display environment **100** of FIG. **1** further includes a hub device **180** that is communicatively coupled to the network(s) **112** directly or via the network interface **160**. The hub device **180** is further communicatively coupled to one or more of the above intelligent, multi-sensing, network-connected devices (e.g., smart home devices of the smart media display environment **100**, the casting devices **108** and the client device **104**). Each of these network-connected devices optionally communicates with the hub device **180** using one or more radio communication networks available at least in the smart media display environment **100** (e.g., ZigBee, Z-Wave, Insteon, Bluetooth, Wi-Fi and other radio communication networks). In some implementations, the hub device **180** and devices coupled with/to the hub device can be controlled and/or interacted with via an application running on a smart phone, household controller, laptop, tablet computer, game console or similar electronic device. In some implementations, a user of such controller application can view status of the hub device or coupled network-connected devices, configure the hub device to interoperate with devices newly introduced to the home network, commission new devices, and adjust or view settings of connected devices, etc.

FIG. **2** is an example operating environment in which casting devices **108** interact with a client device **104** or a server system **140** of a smart media display environment **100** in accordance with some implementations. The smart media display environment **100** includes one or more locations, location A and location B. The user **102** is located at location A or B, and could move freely between these two locations. A casting device **108** and an output device **106** are disposed at each of the one or more locations in the display environment **100**, and communicated to each other via wired or wireless communication available therein. At each location, the respective casting device **108** is configured to obtain media content or Internet content for display on the output

device 106 coupled to the casting device 108. In various embodiments of this application, the casting devices 108 are configured to detect a proximity of the user 102 or a client device 104 carried by the user 102, and control display of the media content displayed on the output devices according to the detected proximity of the user 102 or the client device 104.

In some implementations, the user 102 is located at a location (e.g., location A) within the smart media display environment 100, and the output device 106-1 operates at an inactive state. At such an inactive state, the output device 106-1 is optionally powered off, ceases receiving media content from the casting device 108-1, pauses display of any received media content, and/or reduces the volume of its speaker while continuing display of media content. On the other hand, the casting device 108-1 optionally powers off the output device 106-1, ceases outputting media content to the output device 106-1, causes the output device 106-1 to pause the display of any received media content, ceases obtaining media content from any content source, causes the output device 106-1 to reduce an output volume while continuing display of media content, and mutes the speaker of the output device 106-1. Alternatively, in some implementations, when the output device 106-1 is a computer-based display device, the inactive mode is one of a power-off mode, a sleep mode and a hibernate mode.

When the output device 106-1 operates at the inactive device, the casting device 108-1 detects a client device 104 associated with the casting device 108-1. In some implementations, the client device 104 is detected, when the casting device 108-1 identifies existence or identity of the client device 104. The casting device 108-1 determines a proximity of the client device 104 including whether the client device 104 is within a proximity threshold from the casting device 108-1 (e.g., within a range of 5 yards). When it is determined that the client device 104 is within the proximity threshold from the casting device 108-1, the casting device 108-1 controls the output device 106-1 to change from the inactive state to an active state, and receives media content from one or more content sources for display on the output device 106-1. At the active mode, the output device 106-1 may be awake, fully powered on and ready for use. In contrast, in some implementations, when it is determined that the client device 104 is outside the proximity threshold from the casting device 108-1, the casting device 108-1 maintains the inactive state at the output device 106-1.

In some implementations, when it enables the change of the output device 106-1 from the inactive state to the active state, the casting device 104 transmits a prompt to the client device 104. The prompt informs the user 102 of the change to the active state at the output device 106-1, and provides the user 102 with an option to cancel the change to the active state. In some implementations, after it enables the change of the output device 106-1 from the inactive state to the active state, the casting device 104 sends a notification to the client device 104 via the communication networks 112. The notification informs the user 102 of the change to the active state at the output device 106-1, while not providing the user 102 with an option to cancel the change to the active state. More details of the prompt and the notification displayed on the client device 104 are discussed below with reference to FIGS. 13A and 13B.

In some implementations, when the output device operates at the active state, the casting device 108-1 determines that the client device 104 is not within the proximity threshold from the casting device 108-1, and accordingly, controls the output device 106-1 to change from the active

state to the inactive state. However, in some implementations, the casting device 108-1 maintains the status quo of the output device 106-1, and does not control the output device 106-1 to change from the active state to the inactive state, when the output device operates at the active state and the casting device 108-1 determines that the client device 104 is not within the proximity threshold from the casting device 108-1 any longer.

In some implementations, the casting device 108-1 detects the client device 104 and/or determines the proximity of the client device 104 according to a predefined schedule. Proximity determination could be prohibited at one or more predetermined schedules, e.g., when the user is not at home or when the user is asleep at night. More details on how to set forth the schedule for device detection and proximity determination are discussed below with reference to FIG. 9.

The casting device 108-1 could determine the proximity of the client device 104 based on its own detection of the presence of the client device 104. The casting device 108-1 could also determine the proximity of the client device 104 by receiving proximity information from the client device 104 that has detected the proximity of the casting device 108-1. Further, in some implementations, the casting device 108-1 provides its own location information to a server 140. The server 140 is configured to obtain location information of the client device 104 and determine the information of the proximity of the client device based on the location information of both the casting device 108-1 and the client device 104. The casting device 108-1 then obtains from the server 140 information of the proximity of the client device 104. Optionally, the server 140 is a casting device host 116 that has authenticated the client device 104. Optionally, the server 140 is a specific content host 114 that provides the media content for display on the output device 106-1 and recognizes both the casting device 108-1 and the client device 104.

Under some circumstances, an active state is enabled for the output device 106-1 when the user is available. The casting device 108-1 determines availability of the user 102 in addition to the proximity of the user 102 or the client device 104 of the user 102, before the casting device 108-1 controls the output device 106-1 to change from the inactive state to the active state. In some implementations, the casting device 108-1 monitors behavior of the user 102 within a predetermined period of time, and determines the availability of the user 102 according to the monitored behavior. In some implementations, the casting device 108-1 detects that the user 102 is engaged in a telephone conversation, and that the user 102 is present but not available. In accordance with a determination that the user 102 is not available, the casting device 108-1 deactivates the active state, maintains the inactive state and forgoes a change from the inactive state to the active state. Alternatively, in some implementations, the casting device 108-1 identifies the state of the client device, and determines whether to activate the output device according to the state of the client device. For example, the casting device 108-1 identifies that the client device is at a mute mode. Then, the casting device 108-1 determines that the user is present but not available, and maintains the inactive state at the output device 106-1.

In some situations, there is another client device 104' associated with another user is located at the same location (e.g., location A) where the user 102 is currently located. The casting device 108-2 determines whether it is associated with any other client device (e.g., the client device 104'). When it is determined that the other client device 104' is also

11

within the proximity threshold from the casting device **108-1**, the casting device **108-1** further determines that the client device **104** has a priority over the other client device **104'**, before it controls the output device **106-1** to change from the inactive state to the active state and receives media content from the one or more content sources for display on the output device **106-1**.

In accordance with some implementations of this application, the casting devices **108** implement a follow-me mode that allows display of media content to follow the user **102** when the user **102** moves in the smart media display environment **100** (e.g., moves from location A to location B or from location B to location A). For example, the user **102** initially watches "Hoosiers" on the output device **106-2** at a living room (location B). When the user **102** leaves the living room and enters his bedroom (location A), the output device **106-1** is automatically powered on, and tuned to continue to play "Hoosiers" from a scene that was last viewed on the output device **106-2** located at the living room. The output device **106-2** could be powered off, paused or muted.

At the follow-me mode, the casting device **108-1** detects the client device **104** associated with the casting device **108-1**. In some implementations, the client device **104** is detected when the casting device **108-1** identifies existence or identity of the client device **104**. The casting device **108-1** determines a proximity of the client device **104**. When it is determined that the client device is within a proximity threshold of the casting device **108-1** (e.g., within a range of 5 yards), the casting device **108-1** receives content information associated with content recently accessed by the client device **104**, and obtains the content from a content source in accordance with the content information. Then, the casting device **108-1** outputs the obtained content to an output device in accordance with the content information. In an example, the content information includes information of a scene that was last viewed in another location (location B) distinct from location A. The content information is provided to the casting device **108-1** at location A, such that the casting device **108-1** could cause the output device **106-1** to play "Hoosiers" at location A from the scene that was last viewed at location B.

It is noted that the content information is not limited to an output position of the media content that is last accessed or viewed at a distinct location. In some implementations, the content information includes one or more of output position, output quality, output volume and an identifier of the content source. The obtained content is outputted to the output device **106-1** from the media content source in accordance with one or more of the output position, the output quality and the output volume.

When the user **102** leaves location A, the casting device **108-1** determines that the client device **104** is outside the proximity threshold the casting device **108-1**. The casting device **108-1** could update the content information (e.g., output position, output quality, output volume and content source information) to the server **140**. In some implementations, the client device **104** creates at least a token indicating where the content has been stopped at the time of the determination, and updates the content information with the token. Likewise, the content information originally provided to the casting device **108-1** was previously reported by a casting device located at the other location distinct from location A when the user **102** leaves the other location for location A.

Assume that the user **102** moves from location A to location B. At the location (e.g., location B) to which the

12

user **102** is moved, the casting device **108-2** determines that the client device **104** is within a proximity threshold from the casting device **108-2** and that the casting device **108-2** is not associated with any other user or client device in the meantime. The casting device **108-2** receives the content information that has been updated at a previous location (e.g., location A) by the casting device **108-1** or the client device **104**. The casting device **108-2** then obtains the content from the content source in accordance with the content information, and outputs the obtained content to the output device **106-1** in accordance with the content information.

In some implementations, the casting devices **108-1** and **108-2** are associated with a user account of an application (e.g., a casting device application), and the content information is stored in a memory of a remote server **140** associated with the user account of the application. The casting device **108-2** obtains the content information from the remote server **140**, after the casting device **108-1** updates the content information stored at the remote server **140**. Alternatively, the content information is stored in a local memory of the client device **104**, and the casting device **108-2** receives the content information from the client device **104**.

The client device **104** executes an application for controlling the display of the media content on the output devices **106**. Examples of the application include a client device application, a casting device application, a media player application, a TV program application, and a satellite broadcast application. The client device application controls operations of the client device **104**. The casting device application controls operations of the casting devices **108**. The media player application enables display of media content provided by different content sources (e.g., Netflix, Youtube and Hulu). In some implementations, the application executed by the client device **104** displays a user interface including an affordance, and the affordance prompts a user to enter a user input to active the follow-me mode. The displayed affordance could be a toggle button. Alternatively, the application could also display another affordance on the user interface, and the affordance prompts a user input to activate an automatic media output mode in which the output devices **106** automatically changes from an inactive state to an active state upon detection of a proximity of a client device **104**. More details on user interfaces for enabling the automatic media output mode and the follow-me mode are discussed below with reference to FIGS. **8A**, **8B**, **9**, **10A**, **10B**, **11** and **12**.

In some situations, there is another client device **104'** associated with another user and located at the same location as the client device **104**. The casting device **108-1** determines whether it is associated with any other client device (e.g., the client device **104'**). When it is determined that another client device **104'** is also within the proximity threshold from the casting device **108-1**, the casting device **108-1** further determines that the client device **104** has a priority over the other client device **104'**, before it obtains the content from a content source in accordance with the content information and outputs the obtained content to the output device **106-1** in accordance with the content information. Stated another way, the follow-me mode is deactivated if the client device **104** does not have a priority over another client device **104'** that exists at the same location and has been associated with the casting device **108-1**.

Both the automatic media output mode and the follow-me mode require a casting device **108** to determine a proximity of a client device **104** to the casting device **108**.

In some implementations, the proximity of the client device **104** is determined at the casting device **108** at least by receiving an audio signal created by a user **102** of the client device **104** and determining the proximity of the client device **104** according to the audio signal. Optionally, the audio signal is triggered by the user **102** of the client device inadvertently when the user **102** enters the location and creates some noise. Optionally, the audio signal is associated with a predetermined voice command, e.g., "Turn on TV," that has to be spelled out by the user **102** to cause the determination of the proximity of the client device **104**.

In some implementations, the casting device **104** further includes an optical sensor (e.g., an IR sensor). The proximity of the client device **104** is determined at the casting device **108** at least by receiving an optical signal associated with the user of the client device and determining the proximity of the client device according to the optical signal.

In some implementations, the proximity of the client device **104** is determined at the casting device **108** based on a Bluetooth (BT) signal emitted by the client device **104**. For example, the casting device **108** measures the strength of the BT signal, and determines the proximity of the client device **104** based on the strength of the BT signal. In some implementations, the proximity of the client device **104** is determined at the casting device **108** via one or more WiFi signals communicated between the client device **104** and the casting device **108** over a local area network. In some implementations, the proximity of the client device **104** is determined at the casting device **108** based on a global positioning system (GPS) signal associated with the client device. For example, the user of the client device is approaching a household when the casting device determines the proximity of the client device based on the GPS signal. In some implementations, the proximity of the client device **104** is determined at the casting device **108** via two or more of a BT network, a WIFI network and a GPS according to a predetermined operation sequence. In some implementations, the proximity of the client device is determined based on at least two of a group consisting of an audio signal, an optical signal, a BT signal, a WiFi signal, and a GPS signal.

Further, in some implementations, the casting device **108** in the smart media display environment **100** may additionally or alternatively include one or more other occupancy sensors (e.g., touch screens, IR sensors, ambient light sensors and motion detectors). The casting device **108** could include radio-frequency identification (RFID) readers that determine occupancy based on RFID tags located in the client device **104**.

FIG. 3 is another example operating environment in which casting devices **108** interact with a client device **104**, smart home devices **120** or a server system **140** of the smart media display environment **100** in accordance with some implementations. The smart media display environment **100** includes one or more locations, location A and location B, and a user **102** is located at location A or B, and could move freely between these two locations. A casting device **108**, an output device **106** and one or more smart home devices **120** are disposed at each of the one or more locations in the display environment **100**, and communicated to each other via wired or wireless communication available therein. At each location, the respective casting device **108** is configured to obtain media content or Internet content for display on the output device **106** coupled to the casting device **108**. Further, at each of the one or more locations in the display environment **100**, at least one of the one or more smart home devices **120** is disposed at a known spot with respect to the

casting device **108**. The at least one of the smart home devices **120** is configured to detect a proximity of the user **102** or a client device **104** carried by the user **102**, and provide information of the detected proximity to the casting device **108** located at the same location. The casting device **108** is configured to control display of the media content displayed on the output devices **106** according to the information of the detected proximity provided by the at least one of the smart home devices **120**.

As explained above with reference to FIG. 1, the smart home devices **120** in the smart media display environment **100** may include, but are not limited to, smart thermostats **122**, smart hazard detectors **124**, smart doorbells **126**, smart door locks **128**, smart alarm systems **130**, camera systems **132**, microphone devices **134**, smart wall switches **136**, and smart appliances **138**. The smart home devices **120** are configured to detect a presence, proximity and/or location of a user or a client device **104** carried by a user. In some implementations, a network device (e.g., a router) could also function as a smart home device **120** for detecting the proximity of the client device **104**.

The smart home device **120** could determine the proximity of the client device **104** using an audio sensor or an optical sensor (e.g., a built-in IR sensor). For example, a microphone device **124** can be regarded as a smart home device in this application, and used to determine occupancy of a location in a smart media display environment **100**. Specifically, audio captured by the microphone device **124** may be processed to identify the presence and the proximity of the user **102** in a particular room. Moreover, a camera **132** can also be regarded as a smart home device. The camera **132** captures an image or a video clip at a specific location, and the image or the video clip is processed to identify the presence and proximity of a user **102** in the location (e.g., a kitchen). Alternatively, the cameras **132** may additionally include one or more embedded sensors (e.g., IR sensors and motion detectors) to detect a presence, proximity or location of a user **102**.

The smart home device **120** could also determine the proximity of the client device **104** based on one or more of a BT signal, a WiFi signal, and a GPS signal associated with the client device **104**. Further, in some implementations, the smart home device **120** in the smart media display environment **100** may additionally or alternatively include one or more other occupancy sensors (e.g., touch screens, IR sensors, ambient light sensors and motion detectors). The smart home device **120** could include radio-frequency identification (RFID) readers that determine occupancy based on RFID tags located in the client device **104**.

When a smart home device **120** is disposed at a known spot with respect to a casting device **108**, the smart home device **120** or the client device **108** is configured to detect a proximity between the smart home device **120** and the client device **108**, and the casting device **108** obtains from the smart home device **120** or the client device **108** information concerning the proximity between the smart home device **120** and the client device **108**. Such a proximity between the smart home device **120** and the client device **108** is associated with the proximity of the client device **104** to the casting device **108**, because the smart home device **120** is disposed at a known spot with respect to the casting device **108**.

Specifically, the smart home device **120** could determine its proximity of the client device **104** based on its own detection of the presence of the client device **104**, and provide it to the casting device **108** disposed at the same location. Alternatively, the client device **104** could deter-

mine its proximity of the smart home device **120** based on its own detection of the presence of the smart home device **120**, and provide it to the casting device **108** disposed at the same location. Further, in some implementations, the smart home device **102** and the client device **104** provide their respective location information to a server **140**. The server is configured to determine an alternative proximity of the client device with respect to the smart home device **102** based on the location information of both the casting device **108-1** and the client device **104**. The server **140** could then determine the proximity of the client device **104** to the casting device **104** based on the alternative proximity of the client device **104** and the known spot of the smart home device **102**, and notify the casting device **108** of the proximity of the client device **104**. Alternatively, the server could inform the casting device **118** of the alternative proximity of the client device **104**, and the casting device **108** determines the proximity of the client device based on the alternative proximity of the client device **104** and the known spot of the smart home device **102**. Optionally, the server **140** is a casting device host **116** that has authenticated the client device **104**. Optionally, the server **140** is a specific content host **114** that provides the media content for display on the output device **106** and recognizes both the casting device **108** and the client device **104**.

In some implementations, the smart home device **120** is disposed in close proximity to the casting device **108**. The smart home device **120** detect a proximity of the user **102** or a client device **104** carried by the user **102**. Such a proximity to the smart home device **120** could be approximately regarded as the proximity of the client device **104** to the casting device **108** that is located in proximity, and used directly by the casting device **108** to enable the automatic media output mode or the follow-me mode.

FIG. 4 is a block diagram illustrating an example client device **104** that is applied for automatic control of media display in a smart media display environment **100** in accordance with some implementations. Examples of the client device include, but are not limited to, a mobile phone, a tablet computer and a wearable personal device. The client device **104**, typically, includes one or more processing units (CPUs) **402**, one or more network interfaces **404**, memory **406**, and one or more communication buses **408** for interconnecting these components (sometimes called a chipset). The client device **104** includes one or more input devices **410** that facilitate user input, such as a keyboard, a mouse, a voice-command input unit or microphone, a touch screen display, a touch-sensitive input pad, a gesture capturing camera, or other input buttons or controls. Furthermore, some the client devices **104** use a microphone and voice recognition or a camera and gesture recognition to supplement or replace the keyboard. In some implementations, the client device **104** includes one or more cameras, scanners, or photo sensor units for capturing images, for example, of graphic series codes printed on the electronic devices. The client device **104** also includes one or more output devices **412** that enable presentation of user interfaces and display content, including one or more speakers and/or one or more visual displays. Optionally, the client device **104** includes a location detection device **414**, such as a GPS (global positioning satellite) or other geo-location receiver, for determining the location of the client device **104**. The client device **104** could also include a proximity detection device **415**, e.g., an IR sensor, for determining a proximity of a casting device **108** or a smart home device **120**.

Memory **406** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access

solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. Memory **406**, optionally, includes one or more storage devices remotely located from one or more processing units **402**. Memory **406**, or alternatively the non-volatile memory within memory **406**, includes a non-transitory computer readable storage medium. In some implementations, memory **406**, or the non-transitory computer readable storage medium of memory **406**, stores the following programs, modules, and data structures, or a subset or superset thereof:

Operating system **416** including procedures for handling various basic system services and for performing hardware dependent tasks;

Network communication module **418** for connecting the client device **104** to other devices (e.g., the server system **140**, the casting device **108**, the smart home devices **120** and the other client devices **104**) via one or more network interfaces **404** (wired or wireless) and one or more networks **112**, such as the Internet, other wide area networks, local area networks, metropolitan area networks, and so on;

User interface module **420** for enabling presentation of information (e.g., a graphical user interface for presenting application(s) **426-430**, widgets, websites and web pages thereof, and/or games, audio and/or video content, text, etc.) at the client device **104** via one or more output devices **412** (e.g., displays, speakers, etc.) associated with user interface **410**;

Input processing module **422** for detecting one or more user inputs or interactions from one of the one or more input devices **410** and interpreting the detected input or interaction;

Web browser module **424** for navigating, requesting (e.g., via HTTP), and displaying websites and web pages thereof, including a web interface for logging into a user account associated with a casting device **108**, a media application or a smart home device **120**, controlling the casting device **108** or the smart home device **120** if associated with the user account, and editing and reviewing settings and data that are associated with the user account;

One or more applications for execution by the client device (e.g., games, social network applications, smart home applications, and/or other web or non-web based applications for controlling the casting devices **108** and/or the smart home devices **120** and reviewing data captured by such devices), including one or more of: a casting device application **426** that is executed to provide client-side functionalities for device provisioning, device control, and user account management associated with casting device(s) **108**;

one or more media player applications **428** that is executed to provide client-side functionalities for media display and user account management associated with corresponding media sources; and

one or more smart home device applications **430** that is executed to provide client-side functionalities for device provisioning, device control, data processing and data review of corresponding smart home devices **120**; and

client data **432** storing at least data associated with automatic control of media display (e.g., in an automatic media output mode or a follow-up mode), including:

Client device settings **434** for storing information associated with the client device **104** itself, including common device settings (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.), and information for automatic media display control;

Casting device settings **436** for storing information associated with user accounts of the casting device application **426**, including one or more of account access information, information for device settings (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.), and information for automatic media display control;

Media player application settings **438** for storing information associated with user accounts of one or more media player applications **428**, including one or more of account access information, user preferences of media content types, review history data, and information for automatic media display control;

Smart home device settings **440** for storing information associated with user accounts of the smart home applications **430**, including one or more of account access information, information for smart home device settings (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.); and

Location/proximity data **442** including information associated with the presence, proximity or location of any of the client device **104**, the smart home devices **120** and the casting device **108**.

In some implementations, each of the casting device application **426**, the media player applications **428** and the smart home device applications **430** causes display of a respective user interface on the output device **412** of the client device **104**. The user interfaces of the applications **426-430** could display a notification indicating that change of a display mode (e.g., the change from the active mode to the inactive mode) is pending or that display of media content is following a user in the smart media display environment. The user interfaces of the applications **426-430** could also prompt the user to enable automatic control of media display (e.g., in an automatic media output mode or a follow-me mode), create a schedule for such control of media display, set a priority among a plurality of users or their client devices, and confirm or forgo a display mode change. More details on the aforementioned user interfaces are discussed above with reference to FIGS. **8-13**.

In some implementations, information for automatic media display control stored in the client data **432** includes one of more of a first enable setting for an automatic media output mode, a second enable setting for a follow-me mode, a schedule of automatic media display control, and user priority information for automatic media display control. As explained above, information for automatic media display control could be stored in association with one or more of the client device settings **434**, the casting device settings **436** and the media player application settings **438**.

Each of the above identified elements may be stored in one or more of the previously mentioned memory devices, and corresponds to a set of instructions for performing a function described above. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures, modules or data structures, and thus various subsets of these modules may be combined or otherwise re-arranged in various implementations. In some implementations, memory **406**, optionally,

stores a subset of the modules and data structures identified above. Furthermore, memory **406**, optionally, stores additional modules and data structures not described above.

FIG. **5** is a block diagram illustrating an example casting device **108** that is applied for automatic control of display of media content in a smart media display environment **100** in accordance with some implementations. The casting device **108**, typically, includes one or more processing units (CPUs) **502**, one or more network interfaces **504**, memory **506**, and one or more communication buses **508** for interconnecting these components (sometimes called a chipset). Optionally, the casting device **108** includes a proximity/location detection unit **515**, such as an IR sensor, for determining the proximity of a user **102** or a client device **104** of the user **102**.

Memory **506** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. Memory **506**, optionally, includes one or more storage devices remotely located from one or more processing units **502**. Memory **506**, or alternatively the non-volatile memory within memory **506**, includes a non-transitory computer readable storage medium. In some implementations, memory **506**, or the non-transitory computer readable storage medium of memory **506**, stores the following programs, modules, and data structures, or a subset or superset thereof:

Operating system **516** including procedures for handling various basic system services and for performing hardware dependent tasks;

Network communication module **518** for connecting the casting device **108** to other computers or systems (e.g., the server system **140**, the smart home devices **120** and the client device **104**) via one or more network interfaces **504** (wired or wireless) and one or more networks **112**, such as the Internet, other wide area networks, local area networks, metropolitan area networks, cable television systems, satellite television systems, IPTV systems, and so on;

Content Decoding Module **520** for decoding content signals received from one or more content sources **114** and outputting the content in the decoded signals to an output display device **106** coupled to the casting device **108**;

Proximity/location determination module **522** for determining the proximity of the client device **104** based on proximity related information that is detected by the proximity detection unit **515** or provided by the server system **140**;

Automatic media display module **524** for controlling media display, e.g., causing automatic media output to the output device **106** and enabling the display of the output device **106** to follow a user **102** automatically; casting device data **526** storing at least data associated with automatic control of media display (e.g., in an automatic media output mode and a follow-up mode), including:

Casting device settings **528** for storing information associated with user accounts of a casting device application, including one or more of account access information, information for device settings (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.), and information for automatic media display control;

Media player application settings **530** for storing information associated with user accounts of one or more media player applications, including one or more of account access information, user preferences of media content types, review history data, and information for automatic media display control; and  
 Location/proximity data **532** including information associated with the presence, proximity or location of any of the client device **104**, the smart home devices **120** and the casting device **436**.

Information for automatic media display control could be stored in association with either the casting device settings **528** or the media player application settings **530**. Information for automatic media display control includes one of more of a first enable setting for an automatic media output mode, a second enable setting for a follow-me mode, a schedule of automatic media display control, and user priority information for automatic media display control.

Each of the above identified elements may be stored in one or more of the previously mentioned memory devices, and corresponds to a set of instructions for performing a function described above. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures, modules or data structures, and thus various subsets of these modules may be combined or otherwise re-arranged in various implementations. In some implementations, memory **506**, optionally, stores a subset of the modules and data structures identified above. Furthermore, memory **506**, optionally, stores additional modules and data structures not described above.

FIG. 6 is a block diagram illustrating an example smart home device **120** in a smart media display environment **100** in accordance with some implementations. The smart home device **120**, typically, includes one or more processing units (CPUs) **602**, one or more network interfaces **604**, memory **606**, and one or more communication buses **608** for interconnecting these components (sometimes called a chipset). Optionally, the smart home device **120** includes a proximity/location detection unit **615**, such as an IR sensor, for determining a proximity of a user **102** or a client device **104** of the user **102**. In some implementations, the smart home device **120** itself is capable of detecting the presence, location or proximity of a user **102** or a client device **104**, and an example of such a smart home device **120** is a camera.

Memory **606** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. Memory **606**, optionally, includes one or more storage devices remotely located from one or more processing units **602**. Memory **606**, or alternatively the non-volatile memory within memory **606**, includes a non-transitory computer readable storage medium. In some implementations, memory **606**, or the non-transitory computer readable storage medium of memory **606**, stores the following programs, modules, and data structures, or a subset or superset thereof:

Operating system **616** including procedures for handling various basic system services and for performing hardware dependent tasks for the smart home device **120**;  
 Network communication module **618** for connecting the smart home device **120** to other computers or systems (e.g., the server system **140**, the client device **104**, the casting device **108** and other smart home devices **120**)

via one or more network interfaces **604** (wired or wireless) and one or more networks **112**, such as the Internet, other wide area networks, local area networks, metropolitan area networks, and so on;

Proximity/location determination module **620** for determining a location of the smart home device **120** or an alternative proximity of the client device **104** with respect to the smart home device **120** that are detected by the proximity detection unit **615**;

Smart home device module **622** for enabling the smart home device **120** to implement its designated functions (e.g., for capturing and generating multimedia data streams and sending the multimedia data stream to the client device **104** or the server system **140** as a continuous feed or in short bursts, when the smart home device **120** includes a video camera);

Smart home device data **624** storing at least data associated with automatic control of media display (e.g., in an automatic media output mode and a follow-up mode), including location/proximity data **626** associated with the presence, proximity or location of any of the client device **104**, the smart home devices **120** and the casting device **436**.

Each of the above identified elements may be stored in one or more of the previously mentioned memory devices, and corresponds to a set of instructions for performing a function described above. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures, modules or data structures, and thus various subsets of these modules may be combined or otherwise re-arranged in various implementations. In some implementations, memory **606**, optionally, stores a subset of the modules and data structures identified above. Furthermore, memory **606**, optionally, stores additional modules and data structures not described above.

FIG. 7 is a block diagram illustrating an example server in the server system **140** of a smart media display environment **100** in accordance with some implementations. An example server is one of a content source host **114** and a casting device host **116**. The server **140**, typically, includes one or more processing units (CPUs) **702**, one or more network interfaces **704**, memory **706**, and one or more communication buses **708** for interconnecting these components (sometimes called a chipset). The server **140** could include one or more input devices **710** that facilitate user input, such as a keyboard, a mouse, a voice-command input unit or microphone, a touch screen display, a touch-sensitive input pad, a gesture capturing camera, or other input buttons or controls. Furthermore, the server **140** could use a microphone and voice recognition or a camera and gesture recognition to supplement or replace the keyboard. In some implementations, the server **140** includes one or more cameras, scanners, or photo sensor units for capturing images, for example, of graphic series codes printed on the electronic devices. The server **140** could also include one or more output devices **712** that enable presentation of user interfaces and display content, including one or more speakers and/or one or more visual displays.

Memory **706** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and, optionally, includes non-volatile memory, such as one or more magnetic disk storage devices, one or more optical disk storage devices, one or more flash memory devices, or one or more other non-volatile solid state storage devices. Memory **706**, optionally, includes one or more storage devices remotely located from one or more processing units **702**. Memory **706**, or alterna-

tively the non-volatile memory within memory **706**, includes a non-transitory computer readable storage medium. In some implementations, memory **706**, or the non-transitory computer readable storage medium of memory **706**, stores the following programs, modules, and data structures, or a subset or superset thereof:

Operating system **716** including procedures for handling various basic system services and for performing hardware dependent tasks;

Network communication module **718** for connecting the server system **140** to other devices (e.g., various servers in the server system **140**, the client device **104**, the casting device **108**, and the smart home devices **120**) via one or more network interfaces **704** (wired or wireless) and one or more networks **112**, such as the Internet, other wide area networks, local area networks, metropolitan area networks, and so on;

User interface module **720** for enabling presentation of information (e.g., a graphical user interface for presenting application(s) **426-430**, widgets, websites and web pages thereof, and/or games, audio and/or video content, text, etc.) at the client device **104**;

One or more applications for execution on the server side (e.g., games, social network applications, smart home applications, and/or other web or non-web based applications for controlling the client device **104**, the casting devices **108** and the smart home devices **120** and reviewing data captured by such devices), including one or more of:

a casting device application **722** that is executed to provide server-side functionalities for device provisioning, device control, and user account management associated with casting device(s) **108**;

one or more media player applications **724** that is executed to provide server-side functionalities for media display and user account management associated with corresponding media sources; and

one or more smart home device applications **726** that is executed to provide server-side functionalities for device provisioning, device control, data processing and data review of corresponding smart home devices **120**; and

Proximity/location determination module **728** for determining the proximity of the client device **104** to either the casting device **108** or the smart home device **120** based on location information of any of the client device **104**, the smart home device **120** and the casting device **108**;

Server system data **730** storing at least data associated with automatic control of media display (e.g., in an automatic media output mode and a follow-up mode), including:

Client device settings **732** for storing information associated with the client device **104**, including common device settings (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.), and information for automatic media display control;

Casting device settings **734** for storing information associated with user accounts of the casting device application **722**, including one or more of account access information, information for device settings (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.), and information for automatic media display control;

Media player application settings **736** for storing information associated with user accounts of one or more media player applications **724**, including one or more of account access information, user preferences of media content types, review history data, and information for automatic media display control;

Smart home device settings **738** for storing information associated with user accounts of the smart home applications **726**, including one or more of account access information, information for one or more smart home devices **120** (e.g., service tier, device model, storage capacity, processing capabilities, communication capabilities, etc.); and

Location/proximity data **740** including information associated with the presence, proximity or location of any of the client device **104**, the smart home devices **120** and the casting device **108**.

In some implementations, each of the casting device application **722**, the media player applications **724** and the smart home device applications **726** causes display of a respective user interface on the output device **712** of the client device **104**. It is further noted that the server system **140** is optionally a server type selected from a casting device host **116**, a content host **114** and a smart home device host. In some implementations, according to its server type, the server system **140** executes one of the casting device application **722**, the media player applications **724** and the smart home device applications **726** based on corresponding data settings selected from client device settings **732**, casting device settings **734**, and media player application settings **738**.

Further, in some implementations, information for automatic media display control is optionally stored in the server system data **730** in association with one or more of the client device settings **732**, the casting device settings **734** and the media player application settings **736**. The stored information for automatic media display control includes, but is not limited to, one of more of a first enable setting for an automatic media output mode, a second enable setting for a follow-me mode, a schedule of automatic media display control, and user priority information for automatic media display control.

Each of the above identified elements may be stored in one or more of the previously mentioned memory devices, and corresponds to a set of instructions for performing a function described above. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures, modules or data structures, and thus various subsets of these modules may be combined or otherwise re-arranged in various implementations. In some implementations, memory **706**, optionally, stores a subset of the modules and data structures identified above. Furthermore, memory **706**, optionally, stores additional modules and data structures not described above.

FIGS. **8A** and **8B** are two example user interfaces **800** and **850** displayed on a display of a client device **104** for controlling media display associated with media applications in accordance with some implementations. The user interface **800** is displayed on the display of the client device **104**, and allows a user to determine the device settings of the client device **104** that define characteristics related to automatic media output for casting device(s) associated with the client device **104**. The user interface **800** includes a first affordance **802** for enabling and disabling "Automatic Media Output," and a first plurality of media application affordances **804** each representing a media application available on the client device **104** for controlling display of media

content provided by a corresponding media source. Examples of the media applications include, but are not limited to, an Internet-based media application (e.g., Netflix), a radio application, TV applications (e.g., ESPN and Disney), and a satellite TV application. Optionally, the user interface **800** could also be configured to display an instruction (e.g., “select one of the following media applications you want to play via a casting device automatically”) to prompt a user **102** of the client device **104** to select one of the media applications for automatic media output.

In some implementations, the user **102** enables an automatic media output mode by selecting the first affordance **802**. The user **102** could further associate the automatic media output mode with one or more media applications, when the user **102** selects one or more media applications in the list of media applications provided on the user interface **800**. For example, automatic media output could be enabled for and limited to TV applications that display ESPN and Disney TV programs. Thus, in some implementations, when a casting device **108** associated with the client device **104** determines the proximity of the client device **104**, the casting device **108** controls its output device **106** (if operating at an inactive state) to change from the inactive state to an active state, and receives and streams the ESPN or Display TV programs for display on the output device **106**.

The user interface **850** is displayed on the display of the client device **104**, and allows a user to determine the device settings of the client device **104** that define characteristics related to the follow-me mode for casting device(s) associated with the client device **104**. The user interface **850** includes a third affordance **806** for enabling and disabling “Follow-Me Mode,” and a second plurality of media application affordances **808** each representing a media application available on the client device **104** for controlling display of media content provided by a corresponding media source. The media applications associated with the second plurality of media application affordances **808** are optionally identical to or different from those associated with the first plurality of media application affordances **804**. The user interface **800** could also display an instruction (e.g., “select one of the following media applications to follow you”) to prompt a user **102** of the client device **104** to select one of the media applications for display of corresponding media content in the follow-me mode.

In some implementations, the user **102** enables the display of the media content in the follow-me mode by selecting the third affordance **806**. The user **102** could further associate the follow-me mode with one or more media applications, when the user **102** selects one or more media applications in the list of media applications provided on the user interface **850**. For example, the follow-me mode could be enabled for and limited to TV applications that display ESPN and Disney TV programs, i.e., only TV programs from ESPN and Disney follow the user **102** when the user **102** moves in the smart home environment **100** including two or more locations each disposed with a respective casting device **108** and a respective output device **106**.

FIG. 9 is an example user interface **900** displayed on a display of a client device **104** for controlling a schedule for both an automatic media output mode and a follow-me mode in accordance with some implementations. The user interface **900** allows a user **102** to determine device settings of the client device **104** that define the schedule related to the automatic media output mode and the follow-me mode for casting device(s) **108** associated with the client device **104**. Specifically, the user interface **900** includes two affordances **902** and **904** for activating “Automatic Media Output” and

“Follow-Me Mode,” respectively. The user **102** could enable automatic media output to an output device **106** coupled to the client device **104** by selecting the affordance **902**, or enable the display of the media content in the follow-me mode by selecting the affordance **904**.

In addition, the user interface **900** includes a first list of selectable information items **906** and a second list of selectable information items **908** that are associated with the automatic media output mode and the follow-me mode, respectively. The first list of selectable information items **906** includes one or more schedule information items **906A** and an addition information item **906B**. The user **102** could select either the schedule information items **906A** or the addition information item **906B**. In response to a user selection of one of the schedule information items **906A**, the selected schedule information item **906A** becomes editable and allows the user **102** to modify a schedule for automatic media output associated with the selected schedule information item **906A**. Further, in response to a user selection of the addition information item **906B**, a pop-up window is displayed on top of the user interface **900**, or the addition information item **906B** is expanded within the user interface **900**, such that the user **102** could enter a new schedule for automatic media output of casting device(s) associated with the client device **104**.

Similarly, the second list of selectable information items **908** includes one or more schedule information item **908A** and an addition information item **908B**. The user **102** could select either the schedule information items **908A** or the addition information item **908B**. In response to a user selection of one of the schedule information items **908A**, the selected schedule information item **908A** becomes editable and allows the user **102** to modify a schedule for the follow-me mode associated with the selected schedule information item **908A**. Further, in response to a user selection of the addition information item **908B**, a pop-up window is displayed on top of the user interface **900**, or the addition information item **908B** is expanded within the user interface **900**, such that the user **102** could enter a new schedule for enabling the follow-me mode of casting device(s) associated with the client device **104**.

In the example shown in FIG. 9, the automatic media output mode is activated for casting device(s) associated with the client device **104** from 7 PM to 11 PM every evening, and the follow-me mode is activated casting device (s) associated with the client device **104** from 8 PM to 11 PM on the weekdays and from 7 PM to 11:30 PM during the weekend. Stated another way, the automatic media output mode and the follow-me mode are deactivated when the user is not at home or when the user is asleep at night. Thus, a casting device **108** detects the client device **104** and determines the proximity of the client device **104** only when the instant time satisfies the above schedules defined for the automatic media output mode and the follow-me mode. More details on how to set forth the schedule for device detection and proximity determination are discussed above with reference to FIG. 2.

FIGS. 10A and 10B are two example user interfaces **1000** and **1050** displayed on a display of a client device **104** for controlling an automatic media output mode and a follow-me mode of a casting device **108** in accordance with some implementations, respectively. The user interface **1000** allows a user to determine settings of a casting device application for automatic media output associated with one or more casting devices **108** that have been connected to a user account of the casting device application. The user interface **1000** includes a first affordance **1002** for enabling

and disabling “Automatic Media Output.” Optionally, the user interface **1000** further includes a second plurality of user affordances **1004** each representing a user who is allowed to enable automatic media output. Optionally, the user interface **1000** could also be configured to display an instruction or inquiry **1006** (e.g., “Do you want to output media content automatically when someone (you or another person) is close to a media output device?” or “Who is allowed for automatic media output?”) to prompt a user **102** of the client device **104** to enable automatic media output for one or more authorized users **102**.

In some implementations, the user **102** enables an automatic media output mode by selecting the first affordance **1002**. The user **102** could further associate the automatic media output mode with one or more authorized users **102**, when the user **102** selects one or more users in the list of users displayed on the user interface **1000**. For example, automatic media output could be enabled for and limited to a user named “James.” Thus, in some implementations, when a casting device **108** associated with the casting device application determines a proximity of a client device **104** held by James, the casting device **108** controls its output device **106** (if operating at an inactive state) to change from the inactive state to an active state.

Further, the user interface **1050** is displayed on the display of the client device **104**, and allows a user to determine settings of a casting device application for the follow-me mode associated with one or more casting devices **108** that have been connected to a user account of the casting device application. The user interface **1050** includes a third affordance **1012** for enabling and disabling the “Follow-Me Mode.” Optionally, the user interface **1050** further includes a fourth plurality of user affordances **1004** each representing a user and the client device **104** associated with the respective user that will be followed in the follow-me mode. Optionally, the user interface **1050** could also be configured to display an instruction or inquiry **1006** (e.g., “Do you want to the displayed media content to follow someone?” or “Who do you want your casting device(s) to follow?”) to prompt a user **102** of the client device **104** to enable the follow-me mode for one or more authorized users **102**.

In some implementations, the user **102** enables the follow-me mode by selecting the third affordance **1012**. The user **102** could further associate the follow-me mode with one or more authorized users **102**, when the user **102** selects one or more users in the list of users displayed on the user interface **1050**. For example, the follow-me mode could be enabled for and limited to a user named “Jill.” Thus, in some implementations, when a casting device **108** associated with the casting device application determines a proximity of a client device **104** held by Jill, the casting device **108** controls its output device **106** to continue to display media content that was previously displayed for Jill at another output device **106** located at a distinct location of the smart media display environment **100**.

In some implementations not shown in FIGS. **10A** and **10B**, two or more users **102** are selected for the casting device(s) associated with the casting device application on the user interface **1000** or **1050**. The user interface **1000** or **1050** could be configured to rank the selected two or more users (e.g., define that a first user **102** has a priority over a second user **102'**). When the casting device **108** determines the proximity to more than one selected user, the casting device **108** further determines that a first client device **104** of the first user **102** has a priority over the a second client device **104'** of the second user **102'**, before it controls its

output device **106** to display the media content that has been watched by the first user at a distinct location.

FIG. **11** is another example user interface **1100** displayed on a display of a client device **104** for controlling an automatic media output mode and a follow-me mode of a media application in accordance with some implementations. The user interface **1100** allows a user to determine settings of a media application (e.g., Netflix, Amazon Instant, ESPN and Disney) for both an automatic media output mode and a follow-me mode associated with one or more casting devices **108** that have been coupled to the media application. Specifically, the user interface **1100** includes two affordances **1102** and **1104** for activating “Automatic Media Output” and “Follow-Me Mode,” respectively. The user **102** could enable an automatic media output mode for a casting device **108** and its output device **106** by selecting the affordance **1102**, or enable the display of the media content in the follow-me mode by selecting the affordance **1104**. Optionally, the user interface **1100** could also display an instruction or inquiry **1006** (e.g., “Do you want to output media content automatically when you are close to a media output device?” or “Do you want the displayed media content to follow you?”) to prompt a user **102** of the client device **104** to enable the automatic media output mode or the follow-me mode.

In some implementations, the user **102** enables an automatic media output mode by selecting the first affordance **1102**. When a casting device **108** detects the client device **104** held by the user **102** and determines a proximity of the client device **104**, the casting device **108** controls its output device **106** (if operating at an inactive state) to change from the inactive state to an active state, and display media content provided by a media source associated with the media application. Further, in some implementations, the user **102** enables the follow-me mode by selecting the second affordance **1104**. Media content provided by a media source associated with the media application is initially streamed by a first casting device **108-1** for display on a first output device that is coupled to the first casting device **108-1**. When the user **102** leaves the first casting device **108-1** and moves in proximity to a second casting device **108-2**. The second casting device **108-2** detects the client device **104** and determines the proximity of the client device **104**. The second casting device **108-2** operates under the follow-me mode, controlling a second output device **106-2** to continue the display of the media content that was displayed on the first output device **108-1**.

FIG. **12** is an example user interface **1200** that displays media content on a display of a client device **104** in accordance with some implementations. The media content is configured to be provided by a media source associate with a media application. The user interface **1200** includes a display area **1202** and a plurality of control affordances **1204**, e.g., a volume control affordance **1204A**, a media play affordance **1204B**, a pause affordance **1204C**, a status bar affordance **1204D**, an automatic media output affordance **1204E** and a follow-me mode affordance **1204F**. The affordances **1204A-1204D** are applied to control the display of the media content associated with the media application (e.g., adjust the volume, start or pause the display, and select a start frame to review the display).

In some implementations, the media content is displayed on the display area **1202**, and the user **102** enables the automatic media output mode by clicking on the affordance **1204E**. In response to the click on the affordance **1204E**, the client device **104** generates a request for automatic media display on an output device **106** based on a proximity of the

client device **104**. In accordance with the automatic media output mode, a casting device **108** could detect the client device **104** and determine the proximity of the client device **104**. When the casting device **108** determines that the client device **104** is within a proximity threshold from the casting device **108**, the casting device controls the output device **106** coupled to the casting device **108** to change from an inactive state to an active state. The casting device **108** then streams the media content for display on the output device **106** coupled to the casting device, while the display area **1202** is either blank or displays the same media content. In some implementations, a first click on the affordance **1204E** enables the automatic media output mode, and a second click on the affordance **1204E** subsequent to the first click disables the automatic media output mode.

The user **102** could also enable the follow-me mode for the display of the media content associated with the media application by clicking on the affordance **1204F**. In response to the click on the affordance **1204F**, the client device **104** generates a request for displaying the media content in the follow-me mode. Casting devices **108** located at different locations of a smart media display environment **100** could detect the client device **104** and determine the proximity of the client device **104**. Then, when the user **102** move among the different locations in the smart media display environment **100**, the casting devices control the output devices **106** coupled to the casting devices **108**, causing the display of the media content on the output devices **106** to track the location of the client device **104**. In some implementations, a first click on the affordance **1204F** enables the follow-me mode for the display of the media content associated with the media application, and a second click on the affordance **1204F** subsequent to the first click disables the follow-me mode.

FIG. **13A** is an example user interface **1300** displayed on a display of a client device **104** after a casting device **108** detects a proximity of the client device **104** in accordance with some implementations. The casting device **108** has been enabled for an automatic media output mode. After enabling the change of the output device **106** from the inactive state to the active state, the casting device **104** transmits a prompt to the client device **104**. The prompt informs the user **102** of the change to the active state at the output device **106**, and provides the user **102** with an option to cancel the change to the active state. For example, a message **1302** is displayed on the display of the client device **104**, and reads "You are in the proximity range of a TV in your living room. The TV has been powered on and tuned to ESPN. Please disable the media output on the TV if this is not what you desire." The user interface **1300** further includes a first affordance **1304** and a second affordance **1306**. In response to a respective user click on the first or second affordance, the casting device **108** aborts or finalizes the change of the inactive state to the active state, respectively. It is also noted that the prompt could also be enabled on the user interface **1300** before the output device **106** implements the change from the inactive state to the active state. More details of the prompt displayed on the client device **104** are discussed above with reference to FIG. **2**.

FIG. **13B** is another example user interface **1350** displayed on a display of a client device **104** after a casting device **108** detects a proximity of the client device **104** in accordance with some implementations. The casting device **108** has been enabled for an automatic media output mode or a follow-me mode. After enabling the change of the output device **106** from the inactive state to the active state, the casting device **104** transmits a notification to the client

device **104** displayed on a home screen of the client device **104**. For example, a notification **1312** informs the user **102** of the change to the active state at the output device **106** and a TV channel to which the output device **106** is tuned (e.g., ESPN). Another notification **1314** informs the user that the displayed media content is currently following the user. If the user wants to change settings for the automatic media output mode or the follow-me mode, the user needs to unlock the client device **104**, and change the settings in device settings of the client device **104** (FIGS. **8A**, **8B** and **9**), a casting device application associated with the casting device **108** (FIGS. **10A** and **10B**), or a media application associated with the displayed media content (FIGS. **11** and **12**).

FIGS. **14A** and **14B** are flow diagrams illustrating a method **1400** of controlling display of media content for automatic media output based on user proximity or location in accordance with some implementations. The method **1400** is implemented at a casting device (e.g., the casting device **108** shown in FIG. **5**) having one or more processors and memory storing instructions for execution by the one or more processors. The casting device is coupled to a display input of an output device (e.g., the output devices **106-1** and **106-2** shown in FIGS. **2** and **3**). After determining (**1402**) that the output device operates at an inactive state, the casting device detects (**1404**) a client device (e.g., the client device **104** shown in FIG. **4**) associated with the casting device, and determines (**1406**) a proximity of the client device, including determining whether the client device is within a proximity threshold from the casting device. In accordance with a determination that the client device is within the proximity threshold from the casting device, the casting device controls (**1408**) the output device to change from the inactive state to an active state, and receives (**1410**) media content from one or more content sources for display on the output device. Alternatively, in some implementations, in accordance with a determination that the client device is outside the proximity threshold from the casting device, the casting device maintains (**1412**) the inactive state at the output device. In some implementations, in accordance with the active mode, the output device is awake, fully powered on, and ready for use, and in accordance with the inactive mode, the output device operates at one of a power-off mode, a sleep mode and a hibernate mode.

In some implementations, when the output device operates at the inactive state, the casting device implements (**1414**) one of a group of operations consisting of powering off the output device, ceasing outputting media content to the output device, causing the output device to pause display of media content that is received by the output device, ceasing obtaining media content from any content source, causing the output device to reduce an output volume while continuing display of media content received by the output device, and muting a speaker of the output device.

In some implementations, a smart home device is disposed at a known spot with respect to the casting device, and one of the smart home device and the client device is configured to detect a proximity between the smart home device and the client device. The proximity of the client device is determined by the casting device by obtaining (**1416**) from one of a smart home device and the client device information concerning the proximity between the smart home device and the client device. The proximity between the smart home device and the client device is associated with the proximity of the client device to the casting device.

Further, in some implementations, the casting device provides (1418) location information of the casting device to a server (e.g., a server system 140), and obtains (1420) from the server information of the proximity of the client device. The server is configured to obtain location information of the client device and determine the information of the proximity of the client device from the location information of both the casting device and the client device.

In some implementations, the casting device identifies (1422) a state of the client device, and determines (1424) whether to activate the output device according to the state of the client device. For example, the casting device identifies that the client device is at a mute mode, determines that the user is present but not available, and maintains the inactive state at the output device. In some implementations, the casting device detects that the user is engaged in a telephone conversation, and that the user is present but not available. In accordance with a determination that the user is not available, the casting device deactivates the active state, maintains the inactive state and forgoes a change from the inactive state to the active state. Alternatively, the casting device monitors behavior of the user having the client device within a predetermined period of time, and determines the availability of the user according to the monitored behavior.

In some implementations, the casting device transmits (1426) a prompt to the client device. See FIG. 13A. The prompt informs a user of the client device of the change to the active state at the output device and provides the user with an option to cancel the change to the active state. Further, in some implementations, the client device executes an application for controlling the display of the content on the output device, and the application includes an affordance displayed to receive a user input to activate automatic media output. The application executed by the client device is one of a casting device application, a media player application, a TV program application, and a satellite broadcast application. In an example, the displayed affordance includes a toggle button.

In some implementations, while in the active state, the casting device determines (1428) that the client device is outside the proximity threshold from the casting device. In accordance with the determination that the client device is outside of the proximity threshold from the casting device, the casting device controls the output device to change from the active state to the inactive state.

In some implementations, the casting device detects the client device in accordance with a predefined schedule. For example, in accordance with the predefined schedule, proximity determination is prohibited at one or more predetermined times including a first time duration when the user is not at home, and a second time duration when the user is asleep.

The proximity of the client device could be determined based on an audio signal, an optical signal, a BT signal, a WiFi signal, a GPS signal or the like. A proximity/location determination module 522 of the casting device 108 is applied to determine the proximity of the client device. More details on proximity determination concerning the client device are discussed above with reference to at least FIGS. 1 and 2. Alternatively, in some implementations, the proximity of the client device is determined based on user intervention. For example, the first casting device includes a proximity button, and the proximity of a user carrying the client device is determined by the casting device when the user pushes the proximity button the casting device.

FIG. 15 is a flow diagram illustrating a method 1500 of controlling display of media content based on user proximity

in accordance with some implementations. The method 1500 is used to implement a follow-me mode at one or more casting devices including a first casting device (e.g., the casting device 108 shown in FIG. 5) having one or more processors and memory storing instructions for execution by the one or more processors. The first casting device is coupled to a display input of an output device (e.g., the output devices 106-1 and 106-2 shown in FIGS. 2 and 3). The first casting device detects (1502) a client device associated with the first casting device, and determines (1504) a proximity of the client device. In accordance with a determination (1506) that the client device is within a proximity threshold of the first casting device, the first casting device receives (1508) content information associated with content recently accessed by the client device, obtains (1510) the content from a content source (e.g., the content host 114 shown in FIGS. 1-3) in accordance with the content information, and outputs (1512) the obtained content to an output device in accordance with the content information. In some implementations, the proximity of the client device is determined at a proximity/location determination module 522 of the first casting device, and the output of the content is facilitated by an automatic media display module 524.

Further, in some implementations, while outputting the obtained content, in accordance with a determination that the client device is outside the proximity threshold from the first casting device, the casting device 108 implements (1514) one operation of a group of operations consisting of: powering off the output device, ceasing outputting the obtained content on the output device, causing the output device to pause the display of the content displayed thereon, ceasing obtaining the content from the content source in accordance with the content information, causing the output device to reduce an output volume associated with the obtained content, and muting a speaker of the output device.

In some implementations, the content information includes one or more of: output position, output quality, and output volume. The obtained content could be outputted at the output device from the output position, according to the output quality and/or at the output volume. In an example, the content information associated with the content displayed on the output device includes information indicating where the display of the content has been ceased at a last review. In another example, in accordance with a determination that the client device is outside the proximity threshold from the first casting device, the first casting device creates a token indicating at least where the content has been stopped at the time of the determination.

In some implementations, the first casting device is located at a first location of a smart media display environment. After the client device is outside the proximity threshold from the first casting device, a second casting device determines that the client device is within a proximity threshold from the second casting device and that the casting device is not associated with any other casting device. The second casting device receives the content information associated with the content, obtains the content from the content source in accordance with the content information, and outputs the obtained content to the second output device in accordance with the content information. Further, in some situations, the content information includes a token. In accordance with a determination that the client device is outside the proximity threshold from the first casting device, the first casting device updates the token indicating at least where the content has been stopped at the time of the determination. The updated token is received at the second

casting device, and the obtained content is outputted to the second output device according to the token.

In some implementations, the casting device determines whether the first casting device is associated with any other client device. Optionally, the casting device determines that the first casting device is not associated with any other client device when it operates in the follow-me mode. In an example, the client device includes a first client device. The first casting device determines that a second client device is also within the proximity threshold from the casting device and associated with the first casting device, and that the first client device has a priority over the second client device.

In some implementations, the first casting device is associated with a user account of an application. The content information is stored in a memory of a remote server associated with the user account of the application, and the first casting device receives the content information from the remote server. Alternatively, in some implementations, the content information is stored in a local memory of the client device, and the first casting device receives the content information from the client device.

In some implementations, the client device executes an application for controlling the display of the content on the output device, and the application includes an affordance displayed to receive a user input to activate the follow-me mode. The application executed by the client device is one of a casting device application, a media player application, a TV program application, and a satellite broadcast application. In an example, the displayed affordance includes a toggle button.

The proximity of the client device could be determined based on an audio signal, an optical signal, a BT signal, a WiFi signal, a GPS signal or the like. More details on proximity determination concerning the client device are discussed above with reference to at least FIGS. 1 and 2. Alternatively, in some implementations, the proximity of the client device is determined based on user intervention. For example, the first casting device includes a proximity button, and the proximity of a user carrying the client device is determined by the casting device when the user pushes the proximity button the casting device.

Methods 1400 and 1500 are, optionally, governed by instructions that are stored in a non-transitory computer readable storage medium and that are executed by one or more processors of a casting device (e.g., the casting device 108). Each of the operations shown in FIGS. 14A, 14B and 15 may correspond to instructions stored in the computer memory or computer readable storage medium (e.g., memory 506 of the client device 108 in FIG. 5). The computer readable storage medium may include a magnetic or optical disk storage device, solid state storage devices such as Flash memory, or other non-volatile memory device or devices. The computer readable instructions stored on the computer readable storage medium may include one or more of: source code, assembly language code, object code, or other instruction format that is interpreted by one or more processors. Some operations in the method 1400 or 1500 may be combined and/or the order of some operations may be changed.

It should be understood that the particular order in which the operations in FIGS. 14A and 14B or FIG. 15 have been described are merely exemplary and are not intended to indicate that the described order is the only order in which the operations could be performed. One of ordinary skill in the art would recognize various ways to cache and distribute specific data as described herein. Additionally, it should be noted that details of other processes described with respect

to method 1400 (e.g., FIGS. 14A and 14B) are also applicable in an analogous manner to method 1500 described above with respect to FIG. 15, and that details of other processes described with respect to method 1500 (e.g., FIG. 15) are also applicable in an analogous manner to method 1400 described above with respect to FIGS. 14A and 14B. For brevity, these details are not repeated.

It will also be understood that, although the terms first, second, etc. are, in some instances, used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first type of audio feature can be termed a second type of audio feature, and, similarly, a second type of audio feature can be termed a first type of audio feature, without departing from the scope of the various described implementations. The first type of audio feature and the second type of audio feature are both types of audio features, but they are not the same type of audio feature.

The terminology used in the description of the various described implementations herein is for the purpose of describing particular implementations only and is not intended to be limiting. As used in the description of the various described implementations and the appended claims, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

As used herein, the term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting” or “in accordance with a determination that,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event]” or “in accordance with a determination that [a stated condition or event] is detected,” depending on the context.

It is to be appreciated that “smart media display environments” may refer to smart environments for homes such as a single-family house, but the scope of the present teachings is not so limited. The present teachings are also applicable, without limitation, to duplexes, townhomes, multi-unit apartment buildings, hotels, retail stores, office buildings, industrial buildings, and more generally any living space or work space.

It is also to be appreciated that while the terms user, customer, installer, homeowner, occupant, guest, tenant, landlord, repair person, and the like may be used to refer to the person or persons acting in the context of some particularly situations described herein, these references do not limit the scope of the present teachings with respect to the person or persons who are performing such actions. Thus, for example, the terms user, customer, purchaser, installer, subscriber, and homeowner may often refer to the same person in the case of a single-family residential dwelling, because the head of the household is often the person who makes the purchasing decision, buys the unit, and installs

and configures the unit, and is also one of the users of the unit. However, in other scenarios, such as a landlord-tenant environment, the customer may be the landlord with respect to purchasing the unit, the installer may be a local apartment supervisor, a first user may be the tenant, and a second user may again be the landlord with respect to remote control functionality. Importantly, while the identity of the person performing the action may be germane to a particular advantage provided by one or more of the implementations, such identity should not be construed in the descriptions that follow as necessarily limiting the scope of the present teachings to those particular individuals having those particular identities.

Although various drawings illustrate a number of logical stages in a particular order, stages that are not order dependent may be reordered and other stages may be combined or broken out. While some reordering or other groupings are specifically mentioned, others will be obvious to those of ordinary skill in the art, so the ordering and groupings presented herein are not an exhaustive list of alternatives. Moreover, it should be recognized that the stages can be implemented in hardware, firmware, software or any combination thereof.

The foregoing description, for purpose of explanation, has been described with reference to specific implementations. However, the illustrative discussions above are not intended to be exhaustive or to limit the scope of the claims to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The implementations were chosen in order to best explain the principles underlying the claims and their practical applications, to thereby enable others skilled in the art to best use the implementations with various modifications as are suited to the particular uses contemplated.

What is claimed is:

1. A system for implementing a follow-me mode on casting devices, the system comprising:

a first casting device that includes a hardware processor and an imaging device, wherein the hardware processor:

receives, using the imaging device, imaging information corresponding to a smart media display environment that includes the first casting device and a plurality of casting devices;

processes the imaging information to obtain proximity information associated with a user in the smart media display environment;

determines, from the proximity information, that the user is within a proximity threshold of the first casting device;

upon determining that the user is within the proximity threshold of the first casting device:

receives content information associated with a media content item that was accessed by a second casting device from the plurality of casting devices in the smart media display environment;

retrieves the media content item from a content source based on the received content information;

determines that an output device connected to the first casting device is currently in an inactive mode in which the output device is inhibited from presenting media content and switches the output device from the inactive mode to an active mode in which the output device is capable of presenting media content; and

causes the media content item to continue being presented on the output device connected to the

first casting device in accordance with the received content information.

2. The system of claim 1, wherein the first casting device is coupled to a display input of the output device.

3. The system of claim 1, wherein the proximity information corresponds to a client device that is associated with the user in the smart media display environment and wherein the hardware processor further associates both the first casting device and the client device with a user account of an application, wherein the content information is stored in a memory of a remote server associated with the user account of the application, and the first casting device receives the content information from the remote server.

4. The system of claim 1, wherein the content information includes information indicating where display of the media content item has been stopped.

5. The system of claim 1, wherein the hardware processor further:

determines that the user is no longer within the proximity threshold of the first casting device; and

causes the media content item to stop being presented on the output device connected to the first casting device in response to determining that the user is no longer within the proximity threshold of the first casting device.

6. The system of claim 5, wherein the hardware processor further:

generates a token indicating where the media content item stopped being presented on the output device connected to the first casting device based on the determination that the user is no longer within the proximity threshold of the first casting device; and

transmits the token to a server device for updating the content information associated with the media content item.

7. The system of claim 5, wherein the hardware processor further, in response to determining that the user is no longer within the proximity threshold of the first casting device, causes the output device to be powered off.

8. The system of claim 5, wherein the hardware processor further, in response to determining that the user is no longer within the proximity threshold of the first casting device, inhibits the media content item from being retrieved from the content source.

9. The system of claim 5, wherein the hardware processor further, in response to determining that the user is no longer within the proximity threshold of the first casting device, causes the media content item to be paused from being presented on the output device connected to the first casting device.

10. The system of claim 5, wherein the hardware processor further, in response to determining that the user is no longer within the proximity threshold of the first casting device, causes an audio device associated with the output device to be muted.

11. The system of claim 5, wherein the hardware processor further, in response to determining that the user is no longer within the proximity threshold of the first casting device, causes the output device to reduce an output volume associated with the presentation of the media content item.

12. The system of claim 1, wherein the hardware processor further determines that the follow-me mode is associated with a subset of a plurality of users, wherein the subset of the plurality of users includes the user.

13. The system of claim 1, wherein the hardware processor further determines that the follow-me mode is associated with a subset of a plurality of media applications, wherein

the subset of the plurality of media applications includes a first application configured to access the media content item accessed by the second casting device.

14. The system of claim 1, wherein the hardware processor further:

determines a current time associated with the first casting device; and

determines whether the determination that the user is within the proximity threshold of the first casting device should be performed based on the current time and based on a predetermined schedule.

15. The method of claim 1, wherein the proximity information indicates that a first user and a second user are within the proximity threshold of the first casting device and wherein the hardware processor further:

determines that the first user has a priority over the second user; and

retrieves the content information associated with a user account corresponding to the first user.

16. The system of claim 1, wherein the content information includes at least one of output position, output quality, and output volume.

17. The system of claim 1, wherein the smart media display environment includes a plurality of smart home devices and wherein the first casting device receives the proximity information from one of the plurality of smart home devices.

18. A method for implementing a follow-me mode on casting devices, the method comprising:

receiving, using an imaging device of a first casting device, imaging information corresponding to a smart media display environment that includes the first casting device and a plurality of casting devices;

processing, using a hardware processor of the first casting device, proximity information associated with a user in the smart media display environment;

determining, using the hardware processor of the first casting device, from the proximity information, that the user is within a proximity threshold of the first casting device;

upon determining that the user is within the proximity threshold of the first casting device:

receiving, using the hardware processor of the first casting device, content information associated with a media content item that was accessed by a second casting device from the plurality of casting devices in the smart media display environment;

retrieving, using the hardware processor of the first casting device, the media content item from a content source based on the received content information;

determining, using the hardware processor of the first casting device, that an output device connected to the first casting device is currently in an inactive mode in which the output device is inhibited from presenting media content and switches the output device from the inactive mode to an active mode in which the output device is capable of presenting media content; and

causing, using the hardware processor of the first casting device, the media content item to continue being presented on the output device connected to the first casting device in accordance with the received content information.

19. A non-transitory computer-readable medium containing computer executable instructions that, when executed by a processor, cause the processor to execute a method for implementing a follow-me mode on casting devices, the method comprising:

receiving, using an imaging device of a first casting device, imaging information corresponding to a smart media display environment that includes the first casting device and a plurality of casting devices;

processing proximity information associated with a user in the smart media display environment;

determining, from the proximity information, that the user is within a proximity threshold of the first casting device;

upon determining that the user is within the proximity threshold of the first casting device:

receiving content information associated with a media content item that was accessed by a second casting device from the plurality of casting devices in the smart media display environment;

retrieving the media content item from a content source based on the received content information;

determining that an output device connected to the first casting device is currently in an inactive mode in which the output device is inhibited from presenting media content and switches the output device from the inactive mode to an active mode in which the output device is capable of presenting media content; and

causing the media content item to continue being presented on the output device connected to the first casting device in accordance with the received content information.

\* \* \* \* \*