



US00D906956S

(12) **United States Design Patent** (10) **Patent No.:** **US D906,956 S**
Yamamoto et al. (45) **Date of Patent:** **** Jan. 5, 2021**

(54) **BATTERY HOLDER** 4,691,998 A * 9/1987 Sakagaito G02B 26/121
359/216.1
(71) Applicant: **MITSUBISHI CABLE INDUSTRIES,** D316,752 S * 5/1991 Ricketts D24/226
LTD., Tokyo (JP) 5,681,189 A * 10/1997 Dunham F16B 35/042
439/271
(72) Inventors: **Akihiro Yamamoto, Amagasaki (JP);** D582,266 S * 12/2008 Helms, Jr. D9/430
Yutaka Nishimura, Arida (JP) 7,641,508 B2 * 1/2010 Chen H01R 13/2442
439/500
(73) Assignee: **MITSUBISHI CABLE INDUSTRIES,** D651,224 S * 12/2011 Takahashi D15/139
LTD., Tokyo (JP) D760,166 S 6/2016 Cooper
D825,811 S * 8/2018 Clark D26/80
D833,384 S 11/2018 Takayanagi
D854,063 S * 7/2019 Abe D15/139
D863,055 S * 10/2019 Hudson D9/430
D865,823 S * 11/2019 Abe D15/139
(**) Term: **15 Years**
(21) Appl. No.: **29/691,828**
(22) Filed: **May 20, 2019**
(30) **Foreign Application Priority Data**

Feb. 5, 2019 (JP) 2019-002222

(51) **LOC (13) Cl.** **13-02**

(52) **U.S. Cl.**
USPC **D13/103**

(58) **Field of Classification Search**

USPC D13/102-106, 110, 118-119, 154, 156,
D13/184; D8/354, 373, 380, 381, 382,
D8/399; D9/424, 430, 455, 456
CPC Y02E 60/12; Y02E 60/122; Y02E 60/124;
Y02E 60/50; H01M 2/02; H01M 2/022;
H01M 2/0202; H01M 2/0207; H01M
2/0212; H01M 2/1061; H01M 2/1022;
H01M 2/1055; H01M 2/1066; H01M
2/105; H01M 2/204; H01M 10/4257;
H01M 10/0436; H01M 10/48

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,335,613 A * 3/1920 Selle F16B 35/041
411/368
4,487,820 A * 12/1984 Engelstein H05K 3/301
429/100

FOREIGN PATENT DOCUMENTS

JP 1161979 S 12/2002
JP 1407386 S 1/2011
JP 2019110140 A * 7/2019

Primary Examiner — Catherine S Posthauer

Assistant Examiner — Alison M Ofstun

(74) *Attorney, Agent, or Firm* — Maschoff Brennan


(57) **CLAIM**

The ornamental design for a battery holder, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view thereof;
FIG. 2 is a rear elevational view thereof;
FIG. 3 is a left side elevational view thereof;
FIG. 4 is a top plan view thereof; and,
FIG. 5 is a front, top, right side perspective view of a battery holder showing our new design.
The broken lines in the figures represent portions of the article which form no part of the claimed design.

1 Claim, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0148757	A1 *	6/2009	Zhang	H01M 2/1038 429/100
2011/0262790	A1 *	10/2011	Zhu	H01M 2/1044 429/100
2012/0295146	A1 *	11/2012	Song	H01M 2/1044 429/100
2015/0190869	A1 *	7/2015	Roman	B23C 5/06 407/42
2018/0198100	A1 *	7/2018	Blaha	H01M 2/1038

* cited by examiner

FIG.1




FIG.2




FIG.3




FIG.4



FIG.5

