US007610962B2

(12) **United States Patent**
Fowler

(10) **Patent No.: US 7,610,962 B2**
(45) **Date of Patent: Nov. 3, 2009**

(54) **SOUR GAS INJECTION FOR USE WITH IN SITU HEAT TREATMENT**

(75) Inventor: **Thomas David Fowler**, Houston, TX (US)

(73) Assignee: **Shell Oil Company**, Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 196 days.

(21) Appl. No.: **11/788,864**

(22) Filed: **Apr. 20, 2007**

(65) **Prior Publication Data**

US 2008/0173449 A1 Jul. 24, 2008

Related U.S. Application Data

(60) Provisional application No. 60/853,096, filed on Oct. 20, 2006, provisional application No. 60/794,298, filed on Apr. 21, 2006.

(51) **Int. Cl.**
E21B 36/04 (2006.01)
E21B 43/24 (2006.01)
E21B 43/40 (2006.01)

(52) **U.S. Cl.** **166/267**; 166/60; 166/266; 166/272.1; 166/302; 166/902; 405/129.35; 588/250

(58) **Field of Classification Search** ..... None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

48,994	A	7/1865	Parry
94,813	A	9/1869	Dickey
326,439	A	9/1885	McEachen
345,586	A	7/1886	Hall
760,304	A	5/1904	Butler
1,269,747	A	6/1918	Rogers
1,342,741	A	6/1920	Day
1,510,655	A	6/1924	Clark
1,634,236	A	6/1927	Ranney
1,646,599	A	10/1927	Schaefer
1,666,488	A	4/1928	Crawshaw
1,681,523	A	8/1928	Downey et al.
1,913,395	A	6/1933	Karrick
2,244,255	A	6/1941	Looman

(Continued)

FOREIGN PATENT DOCUMENTS

CA 899987 5/1972

(Continued)

OTHER PUBLICATIONS

A303 Reaction Kinetics Between CO2 and Oil Shale Char, A.K. Burnham, Mar. 22, 1978 (18 pages).


(Continued)

Primary Examiner—George Suchfield

(57) **ABSTRACT**

Systems, methods, and heaters for treating a subsurface formation are described herein. At least one method for providing acidic gas to a subsurface formation is described herein. The method may include providing heat from one or more heaters to a portion of a subsurface formation; producing fluids that include one or more acidic gases from the formation using a heat treatment process. At least a portion of one of the acidic gases may be introduced into the formation, or into another formation, through one or more wellbores at a pressure below a lithostatic pressure of the formation in which the acidic gas is introduced.

20 Claims, 176 Drawing Sheets



U.S. PATENT DOCUMENTS

2,244,256	A		6/1941	Looman
2,319,702	A		5/1943	Moon
2,365,591	A		12/1944	Ranney
2,381,256	A		8/1945	Callaway
2,390,770	A		12/1945	Barton et al.
2,423,674	A		7/1947	Agren
2,444,755	A		7/1948	Steffen
2,466,945	A		4/1949	Greene
2,472,445	A		6/1949	Sprong
2,481,051	A		9/1949	Uren
2,484,063	A		10/1949	Ackley
2,497,868	A		2/1950	Dalin
2,548,360	A		4/1951	Germain
2,593,477	A		4/1952	Newman et al.
2,595,979	A		5/1952	Pevere et al.
2,630,306	A		3/1953	Evans
2,630,307	A		3/1953	Martin
2,634,961	A		4/1953	Ljungstrom
2,642,943	A		6/1953	Smith et al.
2,670,802	A		3/1954	Ackley
2,685,930	A		8/1954	Albaugh
2,695,163	A		11/1954	Pearce et al.
2,703,621	A		3/1955	Ford
2,714,930	A		8/1955	Carpenter
2,732,195	A		1/1956	Ljungstrom
2,734,579	A		2/1956	Elkins
2,743,906	A		5/1956	Coyle
2,750,339	A	*	6/1956	Steinhauff 507/244
2,757,739	A		8/1956	Douglas et al.
2,771,954	A		11/1956	Jenks et al.
2,777,679	A		1/1957	Ljungstrom
2,780,449	A		2/1957	Fisher et al.
2,780,450	A		2/1957	Ljungstrom
2,786,660	A		3/1957	Alleman
2,789,805	A		4/1957	Ljungstrom
2,793,696	A		5/1957	Morse
2,794,504	A		6/1957	Carpenter
2,799,341	A		7/1957	Maly
2,801,089	A		7/1957	Scott, Jr.
2,803,305	A		8/1957	Behning et al.
2,804,149	A		8/1957	Kile
2,819,761	A		1/1958	Popham et al.
2,825,408	A		3/1958	Watson
2,841,375	A		7/1958	Salomonsson
2,857,002	A		10/1958	Pevere et al.
2,847,306	A		12/1958	Stewart et al.
2,862,558	A		12/1958	Dixon
2,889,882	A		6/1959	Schleicher
2,890,754	A		6/1959	Hoffstrom et al.
2,890,755	A		6/1959	Eurenius et al.
2,902,270	A		9/1959	Salomonsson et al.
2,906,337	A		9/1959	Henning
2,906,340	A		9/1959	Herzog
2,914,309	A		11/1959	Salomonsson
2,923,535	A		2/1960	Ljungstrom
2,932,352	A		4/1960	Stegemeier
2,939,689	A		6/1960	Ljungstrom
2,942,223	A		6/1960	Lennox et al.
2,954,826	A		10/1960	Sievers
2,958,519	A		11/1960	Hurley
2,969,226	A		1/1961	Huntington
2,970,826	A		2/1961	Woodruff
2,974,937	A		3/1961	Kiel
2,991,046	A		7/1961	Yahn
2,994,376	A		8/1961	Crawford et al.
2,997,105	A		8/1961	Campion et al.
2,998,457	A		8/1961	Paulsen
3,004,601	A		10/1961	Bodine
3,004,603	A		10/1961	Rogers et al.
3,007,521	A		11/1961	Trantham et al.
3,010,513	A		11/1961	Gerner
3,010,516	A		11/1961	Schleicher
3,016,053	A		1/1962	Medovick
3,017,168	A		1/1962	Carr
3,026,940	A		3/1962	Spitz
3,032,102	A		5/1962	Parker
3,036,632	A		5/1962	Koch et al.
3,044,545	A		7/1962	Tooke
3,048,221	A		8/1962	Tek
3,050,123	A		8/1962	Scott
3,051,235	A		8/1962	Banks
3,057,404	A		10/1962	Berstrom
3,061,009	A		10/1962	Shirley
3,062,282	A		11/1962	Schleicher
3,095,031	A		6/1963	Eurenius et al.
3,097,690	A		7/1963	Terwilliger et al.
3,105,545	A		10/1963	Prats et al.
3,106,244	A		10/1963	Parker
3,110,345	A		11/1963	Reed et al.
3,113,619	A		12/1963	Reichle
3,113,620	A		12/1963	Hemminger
3,113,623	A		12/1963	Krueger
3,114,417	A		12/1963	McCarthy
3,116,792	A		1/1964	Purre
3,120,264	A		2/1964	Barron
3,127,935	A		4/1964	Poettmann et al.
3,127,936	A		4/1964	Eurenius
3,131,763	A		5/1964	Kunetka et al.
3,132,692	A		5/1964	Marx et al.
3,137,347	A		6/1964	Parker
3,138,203	A		6/1964	Weiss et al.
3,139,928	A		7/1964	Broussard
3,142,336	A		7/1964	Doscher
3,149,670	A		9/1964	Grant
3,149,672	A		9/1964	Orkiszewski et al.
3,150,715	A		9/1964	Dietz
3,163,745	A		12/1964	Boston
3,164,207	A		1/1965	Thessen et al.
3,165,154	A		1/1965	Santourian
3,170,842	A		2/1965	Kehler
3,181,613	A		5/1965	Krueger
3,182,721	A		5/1965	Hardy
3,183,675	A		5/1965	Schroeder
3,191,679	A		6/1965	Miller
3,205,942	A		9/1965	Sandberg
3,205,944	A		9/1965	Walton
3,205,946	A		9/1965	Prats et al.
3,207,220	A		9/1965	Williams
3,208,531	A		9/1965	Tamplen
3,209,825	A		10/1965	Alexander et al.
3,221,505	A		12/1965	Goodwin et al.
3,221,811	A		12/1965	Prats
3,233,668	A		2/1966	Hamilton et al.
3,237,689	A		3/1966	Justheim
3,241,611	A		3/1966	Dougan
3,246,695	A		4/1966	Robinson
3,250,327	A		5/1966	Crider
3,267,680	A		8/1966	Schlumberger
3,273,640	A		9/1966	Huntington
3,275,076	A		9/1966	Sharp
3,284,281	A		11/1966	Thomas
3,285,335	A		11/1966	Reistle, Jr.
3,288,648	A		11/1966	Jones
3,294,167	A		12/1966	Vogel
3,302,707	A		2/1967	Slusser
3,316,344	A		4/1967	Kidd et al.
3,316,962	A		5/1967	Lange
3,332,480	A		7/1967	Parrish
3,338,306	A		8/1967	Cook
3,342,258	A		9/1967	Prats
3,342,267	A		9/1967	Cotter et al.
3,349,845	A		10/1967	Holbert et al.
3,352,355	A		11/1967	Putman
3,358,756	A		12/1967	Vogel

3,362,751	A		1/1968	Tinlin
3,372,754	A		3/1968	McDonald
3,379,248	A		4/1968	Strange
3,380,913	A		4/1968	Henderson
3,386,508	A		6/1968	Bielstein et al.
3,389,975	A		6/1968	Van Nostrand
3,399,623	A		9/1968	Creed
3,410,977	A		11/1968	Ando
3,412,011	A		11/1968	Lindsay
3,434,541	A		3/1969	Cook et al.
3,455,383	A		7/1969	Prats et al.
3,465,819	A		9/1969	Dixon
3,477,058	A		11/1969	Vedder et al.
3,485,300	A		12/1969	Engle
3,492,463	A		1/1970	Wringer et al.
3,501,201	A		3/1970	Closmann et al.
3,502,372	A		3/1970	Prats
3,513,913	A		5/1970	Bruist
3,515,837	A		6/1970	Ando
3,526,095	A		9/1970	Peck
3,528,501	A		9/1970	Parker
3,529,682	A		9/1970	Coyne et al.
3,537,528	A		11/1970	Herce et al.
3,542,131	A		11/1970	Walton et al.
3,547,192	A		12/1970	Claridge et al.
3,547,193	A		12/1970	Gill
3,554,285	A		1/1971	Meldau
3,562,401	A		2/1971	Long
3,565,171	A		2/1971	Closmann
3,578,080	A		5/1971	Closmann
3,580,987	A		5/1971	Priaroggia
3,593,789	A		7/1971	Prats
3,595,082	A		7/1971	Miller et al.
3,599,714	A		8/1971	Messman et al.
3,605,890	A		9/1971	Holm
3,614,986	A		10/1971	Gill
3,618,663	A		11/1971	Needham
3,623,979	A	*	11/1971	Maddox et al. 507/243
3,629,551	A		12/1971	Ando
3,661,423	A		5/1972	Garrett
3,675,715	A		7/1972	Speller, Jr.
3,679,812	A		7/1972	Owens
3,680,633	A		8/1972	Bennett
3,700,280	A		10/1972	Papadopoulos et al.
3,702,886	A		11/1972	Argauer et al.
3,709,979	A		1/1973	Chu
3,757,860	A		9/1973	Pritchett
3,759,328	A		9/1973	Ueber et al.
3,759,574	A		9/1973	Beard
3,766,982	A		10/1973	Justheim
3,770,398	A		11/1973	Abraham et al.
3,770,614	A		11/1973	Graven
3,779,602	A		12/1973	Beard et al.
3,794,113	A		2/1974	Strange et al.
3,794,116	A		2/1974	Higgins
3,804,169	A		4/1974	Closmann
3,804,172	A		4/1974	Closmann et al.
3,809,159	A		5/1974	Young et al.
3,812,913	A		5/1974	Hardy et al.
3,832,449	A		8/1974	Rosinski et al.
3,853,185	A		12/1974	Dahl et al.
3,881,551	A		5/1975	Terry et al.
3,882,941	A		5/1975	Pelofsky
3,893,918	A		7/1975	Favret, Jr.
3,894,769	A		7/1975	Tham et al
3,907,045	A		9/1975	Dahl et al.
3,922,148	A		11/1975	Child
3,924,680	A		12/1975	Terry
3,933,447	A		1/1976	Pasini, III et al.
3,941,421	A		3/1976	Burton, III et al.
3,943,160	A		3/1976	Farmer, III et al.
3,947,683	A		3/1976	Schultz et al.
3,948,319	A		4/1976	Pritchett
3,948,755	A		4/1976	McCollum et al.
3,948,758	A		4/1976	Bonacci et al.
3,950,029	A		4/1976	Timmins
3,952,802	A		4/1976	Terry
3,954,140	A		5/1976	Hendrick
3,973,628	A		8/1976	Colgate
3,986,349	A		10/1976	Egan
3,986,556	A		10/1976	Haynes
3,986,557	A		10/1976	Striegler et al.
3,987,851	A		10/1976	Tham
3,992,474	A		11/1976	Sobel
3,993,132	A		11/1976	Cram et al.
3,994,340	A		11/1976	Anderson et al.
3,994,341	A		11/1976	Anderson et al.
3,999,607	A		12/1976	Pennington et al.
4,005,752	A		2/1977	Cha
4,006,778	A		2/1977	Redford et al.
4,008,762	A		2/1977	Fisher et al.
4,010,800	A		3/1977	Terry
4,016,239	A		4/1977	Fenton
4,016,245	A		4/1977	Plank et al.
4,018,280	A		4/1977	Daviduk et al.
4,019,575	A		4/1977	Pisio et al.
4,026,357	A		5/1977	Redford
4,029,360	A		6/1977	French
4,031,956	A		6/1977	Terry
4,037,655	A		7/1977	Carpenter
4,042,026	A		8/1977	Pusch et al.
4,043,393	A		8/1977	Fisher et al.
4,048,637	A		9/1977	Jacomini
4,049,053	A		9/1977	Fisher et al.
4,057,293	A		11/1977	Garrett
4,059,308	A		11/1977	Pearson et al.
4,064,943	A		12/1977	Cavin
4,067,390	A		1/1978	Camacho et al.
4,076,761	A		2/1978	Chang et al.
4,076,842	A		2/1978	Plank et al.
4,077,471	A		3/1978	Shupe et al.
4,083,604	A		4/1978	Bohn et al.
4,084,637	A		4/1978	Todd
4,085,803	A		4/1978	Butler
4,087,130	A		5/1978	Garrett
4,089,372	A		5/1978	Terry
4,089,374	A		5/1978	Terry
4,091,869	A		5/1978	Hoyer
4,093,025	A		6/1978	Terry
4,093,026	A		6/1978	Ridley
4,096,163	A		6/1978	Chang et al.
4,099,567	A		7/1978	Terry
4,114,688	A		9/1978	Terry
4,119,349	A		10/1978	Albulescu et al.
4,125,159	A		11/1978	Vann
4,130,575	A		12/1978	Jorn
4,133,825	A		1/1979	Stroud et al.
4,138,442	A		2/1979	Chang et al.
4,140,180	A		2/1979	Bridges et al.
4,140,181	A		2/1979	Ridley et al.
4,144,935	A		3/1979	Bridges et al.
4,148,359	A		4/1979	Laumbach et al.
4,158,467	A		6/1979	Larson et al.
4,169,506	A		10/1979	Berry
4,183,405	A		1/1980	Magnie
4,184,548	A		1/1980	Ginsburgh et al.
4,185,692	A		1/1980	Terry
4,186,801	A		2/1980	Madgavkar et al.
4,193,451	A		3/1980	Dauphine
4,197,911	A		4/1980	Anada
4,199,024	A		4/1980	Rose et al.
4,199,025	A		4/1980	Carpenter
4,216,079	A		8/1980	Newcombe
4,228,853	A		10/1980	Harvey et al.
4,228,854	A		10/1980	Sacuta
4,243,101	A		1/1981	Grupping

4,248,306 A	2/1981	Van Huisen et al.	
4,250,230 A	2/1981	Terry	
4,250,962 A	2/1981	Madgavkar et al.	
4,252,191 A	2/1981	Pusch et al.	
4,254,297 A	3/1981	Frenken et al.	
4,256,945 A	3/1981	Carter et al.	
4,258,955 A	3/1981	Habib, Jr.	
4,265,307 A	5/1981	Elkins	
4,273,188 A	6/1981	Vogel et al.	
4,274,487 A	6/1981	Hollingsworth et al.	
4,277,416 A	7/1981	Grant	
4,282,587 A	8/1981	Silverman	
RE30,738 E	9/1981	Bridges et al.	
4,299,086 A	11/1981	Madgavkar et al.	
4,299,285 A	11/1981	Tsai et al.	
4,303,126 A	12/1981	Blevins	
4,305,463 A	12/1981	Zakiewicz	
4,306,621 A	12/1981	Boyd et al.	
4,310,440 A	1/1982	Wilson et al.	
4,324,292 A	4/1982	Jacobs et al.	
4,344,483 A	8/1982	Fisher et al.	
4,353,418 A	10/1982	Hoekstra et al.	
4,359,687 A	11/1982	Vinegar et al.	
4,363,361 A	12/1982	Madgavkar et al.	
4,366,668 A	1/1983	Madgavkar et al.	
4,368,114 A	1/1983	Chester et al.	
4,378,048 A	3/1983	Madgavkar et al.	
4,380,930 A	4/1983	Podhrasky et al.	
4,381,641 A	5/1983	Madgavkar et al.	
4,382,469 A	5/1983	Bell et al.	
4,384,613 A	5/1983	Owen et al.	
4,384,614 A	5/1983	Justheim	
4,385,661 A	5/1983	Fox	
4,390,067 A	6/1983	Willman	
4,390,973 A	6/1983	Rietsch	
4,396,062 A	8/1983	Iskander	
4,397,732 A	8/1983	Hoover et al.	
4,398,151 A	8/1983	Vinegar et al.	
4,399,866 A	8/1983	Dearth	
4,401,099 A	8/1983	Collier	
4,401,162 A	8/1983	Osborne	
4,401,163 A	8/1983	Elkins	
4,407,973 A	10/1983	van Dijk et al.	
4,409,090 A	10/1983	Hanson et al.	
4,410,042 A	10/1983	Shu	
4,412,124 A	10/1983	Kobayashi	
4,412,585 A	11/1983	Bouck	
4,417,782 A	11/1983	Clarke et al.	
4,418,752 A	12/1983	Boyer et al.	
4,423,311 A	12/1983	Varney, Sr.	
4,425,967 A	1/1984	Hoekstra	
4,428,700 A	1/1984	Lennemann	
4,429,745 A	2/1984	Cook	
4,437,519 A	3/1984	Cha et al.	
4,440,224 A	4/1984	Kreinin et al.	
4,440,871 A	4/1984	Lok et al.	
4,442,896 A	4/1984	Reale et al.	
4,444,255 A	4/1984	Geoffrey et al.	
4,444,258 A	4/1984	Kalmar	
4,445,574 A	5/1984	Vann	
4,446,917 A	5/1984	Todd	
4,452,491 A	6/1984	Seglin et al.	
4,455,215 A	6/1984	Jarrott et al.	
4,456,065 A	6/1984	Heim et al.	
4,457,365 A	7/1984	Kasevich et al.	
4,457,374 A	7/1984	Hoekstra et al.	
4,458,757 A	7/1984	Bock et al.	
4,458,767 A	7/1984	Hoehn, Jr.	
4,460,044 A	7/1984	Porter	
4,474,236 A	10/1984	Kellett	
4,474,238 A	10/1984	Gentry et al.	
4,479,541 A	10/1984	Wang	
4,485,868 A	12/1984	Sresty et al.	
4,485,869 A	12/1984	Sresty et al.	
4,487,257 A	12/1984	Dauphine	
4,489,782 A	12/1984	Perkins	
4,491,179 A	1/1985	Pirson et al.	
4,498,531 A	2/1985	Vrolyk	
4,498,535 A	2/1985	Bridges	
4,499,209 A	2/1985	Hoek et al.	
4,500,651 A	2/1985	Lok et al.	
4,501,326 A	2/1985	Edmunds	
4,501,445 A	2/1985	Gregoli	
4,513,816 A	4/1985	Hubert	
4,518,548 A	5/1985	Yarbrough	
4,524,826 A	6/1985	Savage	
4,524,827 A	6/1985	Bridges et al.	
4,530,401 A	7/1985	Hartman et al.	
4,537,252 A	8/1985	Puri	
4,538,682 A	9/1985	McManus et al.	
4,540,882 A	9/1985	Vinegar et al.	
4,542,648 A	9/1985	Vinegar et al.	
4,545,435 A	10/1985	Bridges et al.	
4,549,396 A	10/1985	Garwood et al.	
4,551,226 A	11/1985	Fern	
4,552,214 A	11/1985	Forgac et al.	
4,570,715 A	2/1986	Van Meurs et al.	
4,571,491 A	2/1986	Vinegar et al.	
4,572,229 A	2/1986	Mueller et al.	
4,572,299 A	2/1986	Van Egmond et al.	
4,573,530 A	3/1986	Audeh et al.	
4,576,231 A	3/1986	Dowling et al.	
4,577,503 A	3/1986	Imaino et al.	
4,577,690 A	3/1986	Medlin	
4,577,691 A	3/1986	Huang et al.	
4,583,046 A	4/1986	Vinegar et al.	
4,583,242 A	4/1986	Vinegar et al.	
4,585,066 A	4/1986	Moore et al.	
4,592,423 A	6/1986	Savage et al.	
4,597,441 A	7/1986	Ware et al.	
4,597,444 A	7/1986	Hutchinson	
4,598,392 A	7/1986	Pann	
4,598,770 A	7/1986	Shu et al.	
4,598,772 A	7/1986	Holmes	
4,605,489 A	8/1986	Madgavkar	
4,605,680 A	8/1986	Beuther et al.	
4,608,818 A	9/1986	Goebel et al.	
4,609,041 A	9/1986	Magda	
4,613,754 A	9/1986	Vinegar et al.	
4,616,705 A	10/1986	Stegemeier et al.	
4,623,401 A	11/1986	Derbyshire et al.	
4,623,444 A	11/1986	Che et al.	
4,626,665 A	12/1986	Fort, III	
4,635,197 A	1/1987	Vinegar et al.	
4,637,464 A	1/1987	Forgac et al.	
4,640,352 A	2/1987	Van Meurs et al.	
4,640,353 A	2/1987	Schuh	
4,644,283 A	2/1987	Vinegar et al.	
4,645,906 A	2/1987	Yagnik et al.	
4,651,825 A	3/1987	Wilson	
4,658,215 A	4/1987	Vinegar et al.	
4,662,437 A	5/1987	Renfro et al.	
4,662,438 A	5/1987	Taflove et al.	
4,662,439 A	5/1987	Puri	
4,662,443 A	5/1987	Puri et al.	
4,663,711 A	5/1987	Vinegar et al.	
4,669,542 A	6/1987	Venkatesan	
4,671,102 A	6/1987	Vinegar et al.	
4,682,652 A	7/1987	Huang et al.	
4,686,029 A	8/1987	Pellet et al.	
4,691,771 A	9/1987	Ware et al.	
4,694,907 A	9/1987	Stahl et al.	
4,695,713 A	9/1987	Krumme	
4,698,149 A	10/1987	Mitchell	
4,698,583 A	10/1987	Sandberg	
4,701,587 A	10/1987	Carter et al.	

4,704,514 A	11/1987	Van Egmond et al.
4,706,751 A	11/1987	Gondouin
4,716,960 A	1/1988	Eastlund et al.
4,717,814 A	1/1988	Krumme
4,719,423 A	1/1988	Vinegar et al.
4,728,892 A	3/1988	Vinegar et al.
4,730,162 A	3/1988	Vinegar et al.
4,733,057 A	3/1988	Stanzel et al.
4,734,115 A	3/1988	Howard et al.
4,743,854 A	5/1988	Vinegar et al.
4,744,245 A	5/1988	White
4,752,673 A	6/1988	Krumme
4,756,367 A	7/1988	Puri et al.
4,762,425 A	8/1988	Shakkottai et al.
4,766,958 A	8/1988	Faecke
4,769,602 A	9/1988	Vinegar et al.
4,769,606 A	9/1988	Vinegar et al.
4,772,634 A	9/1988	Farooque
4,776,638 A	10/1988	Hahn
4,785,163 A	11/1988	Sandberg
4,787,452 A	11/1988	Jennings, Jr.
4,793,409 A	12/1988	Bridges et al.
4,794,226 A	12/1988	Derbyshire
4,808,925 A	2/1989	Baird
4,814,587 A	3/1989	Carter
4,817,711 A	4/1989	Jeambey
4,818,370 A	4/1989	Gregoli et al.
4,821,798 A	4/1989	Bridges et al.
4,823,890 A	4/1989	Lang
4,827,761 A	5/1989	Vinegar et al.
4,828,031 A	5/1989	Davis
4,840,720 A	6/1989	Reid
4,848,460 A	7/1989	Johnson, Jr. et al.
4,848,924 A	7/1989	Nuspl et al.
4,849,611 A	7/1989	Whitney et al.
4,856,341 A	8/1989	Vinegar et al.
4,856,587 A	8/1989	Nielson
4,860,544 A	8/1989	Krieg et al.
4,866,983 A	9/1989	Vinegar et al.
4,884,455 A	12/1989	Vinegar et al.
4,885,080 A	12/1989	Brown et al.
4,886,118 A	12/1989	Van Meurs et al.
4,893,504 A	1/1990	O'Meara, Jr. et al.
4,895,206 A	1/1990	Price
4,912,971 A	4/1990	Jeambey
4,913,065 A	4/1990	Hemsath
4,926,941 A	5/1990	Glandt et al.
4,927,857 A	5/1990	McShea, III et al.
4,928,765 A	5/1990	Nielson
4,940,095 A	7/1990	Newman
4,974,425 A	12/1990	Krieg et al.
4,982,786 A	1/1991	Jennings, Jr.
4,983,319 A	1/1991	Gregoli et al.
4,984,594 A	1/1991	Vinegar et al.
4,985,313 A	1/1991	Penneck et al.
4,987,368 A	1/1991	Vinegar
4,994,093 A	2/1991	Wetzel et al.
5,008,085 A	4/1991	Bain et al.
5,011,329 A	4/1991	Nelson et al.
5,020,596 A	6/1991	Hemsath
5,027,896 A	7/1991	Anderson
5,042,579 A	8/1991	Glandt et al.
5,046,559 A	9/1991	Glandt
5,050,386 A	9/1991	Krieg et al.
5,054,551 A	10/1991	Duerksen
5,059,303 A	10/1991	Taylor et al.
5,060,287 A	10/1991	Van Egmond
5,060,726 A	10/1991	Glandt et al.
5,064,006 A	11/1991	Waters et al.
5,065,501 A	11/1991	Henschen et al.
5,065,818 A	11/1991	Van Egmond
5,066,852 A	11/1991	Willbanks
5,073,625 A	12/1991	Derbyshire
5,082,054 A	1/1992	Kiamanesh
5,082,055 A	1/1992	Hemsath
5,085,276 A	2/1992	Rivas et al.
5,093,002 A	3/1992	Pasternak
5,097,903 A	3/1992	Wilensky
5,099,918 A	3/1992	Bridges et al.
5,102,551 A	4/1992	Pasternak
5,103,909 A	4/1992	Morgenthaler et al.
5,103,920 A	4/1992	Patton
5,126,037 A	6/1992	Showalter
5,133,406 A	7/1992	Puri
5,145,003 A	9/1992	Duerksen
5,150,118 A	9/1992	Finkle et al.
5,152,341 A	10/1992	Kasevich
5,168,927 A	12/1992	Stegemeier et al.
5,173,213 A	12/1992	Miller et al.
5,182,427 A	1/1993	McGaffigan
5,182,792 A	1/1993	Goncalves
5,189,283 A	2/1993	Carl, Jr. et al.
5,190,405 A	3/1993	Vinegar et al.
5,199,490 A	4/1993	Surles et al.
5,201,219 A	4/1993	Bandurski et al.
5,207,273 A	5/1993	Cates et al.
5,209,987 A	5/1993	Penneck et al.
5,211,230 A	5/1993	Ostapovich et al.
5,217,075 A	6/1993	Wittrisch
5,217,076 A	6/1993	Masek
5,226,961 A	7/1993	Nahm et al.
5,229,583 A	7/1993	van Egmond et al.
5,236,039 A	8/1993	Edelstein et al.
5,255,742 A	10/1993	Mikus
5,261,490 A	11/1993	Ebinuma
5,275,726 A	1/1994	Feimer et al.
5,282,957 A	2/1994	Wright et al.
5,284,206 A	2/1994	Surles et al.
5,285,846 A	2/1994	Mohn
5,289,882 A	3/1994	Moore
5,295,763 A	3/1994	Stenborg et al.
5,297,626 A	3/1994	Vinegar et al.
5,305,239 A	4/1994	Kinra
5,305,829 A	4/1994	Kumar
5,306,640 A	4/1994	Vinegar et al.
5,316,664 A	5/1994	Gregoli et al.
5,318,116 A	6/1994	Vinegar et al.
5,318,709 A	6/1994	Wuest et al.
5,332,036 A	7/1994	Shirley et al.
5,339,897 A	8/1994	Leaute
5,339,904 A	8/1994	Jennings, Jr.
5,340,467 A	8/1994	Gregoli et al.
5,349,859 A	9/1994	Kleppe
5,360,067 A	11/1994	Meo, III
5,363,094 A	11/1994	Staron et al.
5,366,012 A	11/1994	Lohbeck
5,377,756 A	1/1995	Northrop et al.
5,388,640 A	2/1995	Puri et al.
5,388,641 A	2/1995	Yee et al.
5,388,642 A	2/1995	Puri et al.
5,388,643 A	2/1995	Yee et al.
5,388,645 A	2/1995	Puri et al.
5,391,291 A	2/1995	Winquist et al.
5,392,854 A	2/1995	Vinegar et al.
5,400,430 A	3/1995	Nenniger
5,404,952 A	4/1995	Vinegar et al.
5,409,071 A	4/1995	Wellington et al.
5,411,086 A	5/1995	Burcham et al.
5,411,089 A	5/1995	Vinegar et al.
5,411,104 A	5/1995	Stanley
5,415,231 A	5/1995	Northrop et al.
5,431,224 A	7/1995	Laali
5,433,271 A	7/1995	Vinegar et al.
5,435,666 A	7/1995	Hassett et al.
5,437,506 A	8/1995	Gray
5,439,054 A	8/1995	Chaback et al.

5,454,666 A	10/1995	Chaback et al.	
5,456,315 A	10/1995	Kisman et al.	
5,458,774 A	10/1995	Mannapperuma	
5,468,372 A	11/1995	Seamans et al.	
5,497,087 A	3/1996	Vinegar et al.	
5,498,960 A	3/1996	Vinegar et al.	
5,512,732 A	4/1996	Yagnik et al.	
5,517,593 A	5/1996	Nenniger et al.	
5,525,322 A	6/1996	Willms	
5,541,517 A	7/1996	Hartmann et al.	
5,545,803 A	8/1996	Heath et al.	
5,553,189 A	9/1996	Stegemeier et al.	
5,554,453 A	9/1996	Steinfeld et al.	
5,566,755 A	10/1996	Seidle et al.	
5,571,403 A	11/1996	Scott et al.	
5,579,575 A	12/1996	Lamome et al.	
5,621,844 A	4/1997	Bridges	
5,621,845 A	4/1997	Bridges et al.	
5,624,188 A	4/1997	West	
5,632,336 A	5/1997	Notz et al.	
5,648,305 A	7/1997	Mansfield et al.	
5,652,389 A	7/1997	Schaps et al.	
5,654,261 A	8/1997	Smith	
5,656,239 A	8/1997	Stegemeier et al.	
5,688,736 A	11/1997	Seamans et al.	
5,713,415 A	2/1998	Bridges	
5,723,423 A	3/1998	Van Slyke	
5,744,025 A	4/1998	Boon et al.	
5,751,895 A	5/1998	Bridges	
5,759,022 A	6/1998	Koppang et al.	
5,760,307 A	6/1998	Latimer et al.	
5,769,569 A	6/1998	Hosseini	
5,777,229 A	7/1998	Geier et al.	
5,782,301 A	7/1998	Neuroth et al.	
5,802,870 A	9/1998	Arnold et al.	
5,826,655 A	10/1998	Snow et al.	
5,828,797 A	10/1998	Minott et al.	
5,861,137 A	1/1999	Edlund	
5,862,858 A	1/1999	Wellington et al.	
5,868,202 A	2/1999	Hsu	
5,879,110 A	3/1999	Carter	
5,899,269 A	5/1999	Wellington et al.	
5,899,958 A	5/1999	Dowell et al.	
5,911,898 A	6/1999	Jacobs et al.	
5,926,437 A	7/1999	Ortiz	
5,935,421 A	8/1999	Brons et al.	
5,968,349 A	10/1999	Duyvesteyn et al.	
5,984,010 A	11/1999	Elias et al.	
5,984,582 A	11/1999	Schwert	
5,985,138 A	11/1999	Humphreys	
5,997,214 A	12/1999	de Rouffignac et al.	
6,015,015 A	1/2000	Luft et al.	
6,016,867 A	1/2000	Gregoli et al.	
6,016,868 A	1/2000	Gregoli et al.	
6,019,172 A	2/2000	Wellington et al.	
6,022,834 A	2/2000	Hsu et al.	
6,023,554 A	2/2000	Vinegar et al.	
6,026,914 A	2/2000	Adams et al.	
6,035,701 A	3/2000	Lowry et al.	
6,039,121 A	3/2000	Kisman	
6,056,057 A	5/2000	Vinegar et al.	
6,078,868 A	6/2000	Dubinsky	
6,079,499 A	6/2000	Mikus et al.	
6,084,826 A	7/2000	Leggett, III	
6,085,512 A	7/2000	Agee et al.	
6,088,294 A	7/2000	Leggett, III et al.	
6,094,048 A	7/2000	Vinegar et al.	
6,099,208 A	8/2000	McAlister	
6,102,122 A	8/2000	de Rouffignac	
6,102,137 A	8/2000	Ward et al.	
6,102,622 A	8/2000	Vinegar et al.	
6,110,358 A	8/2000	Aldous et al.	
6,112,808 A	9/2000	Isted	
6,152,987 A	11/2000	Ma et al.	
6,155,117 A	12/2000	Stevens et al.	
6,172,124 B1	1/2001	Wolflick et al.	
6,173,775 B1	1/2001	Elias et al.	
6,192,748 B1	2/2001	Miller	
6,193,010 B1	2/2001	Minto	
6,196,350 B1	3/2001	Minto	
6,218,333 B1	4/2001	Gabrielov et al.	
6,257,334 B1	7/2001	Cyr et al.	
6,269,310 B1	7/2001	Washbourne	
6,269,881 B1	8/2001	Chou et al.	
6,283,230 B1	9/2001	Peters	
6,288,372 B1	9/2001	Sandberg et al.	
6,290,841 B1	9/2001	Gabrielov et al.	
6,328,104 B1	12/2001	Graue	
6,353,706 B1	3/2002	Bridges	
6,354,373 B1	3/2002	Vercaemer et al.	
6,357,526 B1	3/2002	Abdel-Halim et al.	
6,388,947 B1	5/2002	Washbourne et al.	
6,412,559 B1	7/2002	Gunter et al.	
6,417,268 B1	7/2002	Zhang et al.	
6,422,318 B1	7/2002	Rider	
6,427,124 B1	7/2002	Dubinsky et al.	
6,439,308 B1	8/2002	Wang	
6,467,543 B1	10/2002	Talwani et al.	
6,485,232 B1	11/2002	Vinegar et al.	
6,499,536 B1	12/2002	Ellingsen	
6,516,891 B1	2/2003	Dallas	
6,540,018 B1	4/2003	Vinegar	
6,581,684 B2	6/2003	Wellington et al.	
6,584,406 B1	6/2003	Harmon et al.	
6,585,046 B2	7/2003	Neuroth et al.	
6,588,266 B2	7/2003	Tubel et al.	
6,588,503 B2	7/2003	Karanikas et al.	
6,588,504 B2	7/2003	Wellington et al.	
6,591,906 B2	7/2003	Wellington et al.	
6,591,907 B2	7/2003	Zhang et al.	
6,605,566 B2	8/2003	Le Peltier et al.	
6,607,033 B2	8/2003	Wellington et al.	
6,609,570 B2	8/2003	Wellington et al.	
6,679,332 B2	1/2004	Vinegar et al.	
6,684,948 B1	2/2004	Savage	
6,688,387 B1	2/2004	Wellington et al.	
6,698,515 B2	3/2004	Karanikas et al.	
6,702,016 B2	3/2004	de Rouffignac et al.	
6,708,758 B2	3/2004	de Rouffignac et al.	
6,712,135 B2	3/2004	Wellington et al.	
6,712,136 B2	3/2004	de Rouffignac et al.	
6,712,137 B2	3/2004	Vinegar et al.	
6,715,546 B2	4/2004	Vinegar et al.	
6,715,547 B2	4/2004	Vinegar et al.	
6,715,548 B2	4/2004	Wellington et al.	
6,715,549 B2	4/2004	Wellington et al.	
6,715,550 B2	4/2004	Vinegar et al.	
6,719,047 B2	4/2004	Fowler et al.	
6,722,429 B2	4/2004	de Rouffignac et al.	
6,722,430 B2	4/2004	Vinegar et al.	
6,722,431 B2	4/2004	Karanikas et al.	
6,725,920 B2	4/2004	Zhang et al.	
6,725,921 B2	4/2004	de Rouffignac et al.	
6,725,928 B2	4/2004	Vinegar et al.	
6,729,395 B2	5/2004	Shahin, Jr. et al.	
6,729,396 B2	5/2004	Vinegar et al.	
6,729,397 B2	5/2004	Zhang et al.	
6,729,401 B2	5/2004	Vinegar et al.	
6,732,794 B2	5/2004	Wellington et al.	
6,732,795 B2	5/2004	de Rouffignac et al.	
6,732,796 B2	5/2004	Vinegar et al.	
6,736,215 B2 *	5/2004	Maher et al.	166/402
6,739,393 B2	5/2004	Vinegar et al.	
6,739,394 B2	5/2004	Vinegar et al.	
6,742,587 B2	6/2004	Vinegar et al.	
6,742,588 B2	6/2004	Wellington et al.	

6,742,589	B2	6/2004	Berchenko et al.
6,742,593	B2	6/2004	Vingar et al.
6,745,831	B2	6/2004	de Rouffignac et al.
6,745,832	B2	6/2004	Wellington et al.
6,745,837	B2	6/2004	Wellington et al.
6,749,021	B2	6/2004	Vinegar et al.
6,752,210	B2	6/2004	de Rouffignac et al.
6,755,251	B2	6/2004	Thomas et al.
6,758,268	B2	7/2004	Vinegar et al.
6,759,364	B2	7/2004	Bhan et al.
6,761,216	B2	7/2004	Vinegar et al.
6,763,886	B2	7/2004	Schoeling et al.
6,769,483	B2	8/2004	de Rouffignac et al.
6,769,485	B2	8/2004	Vinegar et al.
6,782,947	B2	8/2004	de Rouffignac et al.
6,789,625	B2	9/2004	de Rouffignac et al.
6,805,194	B2	10/2004	Davidson et al.
6,805,195	B2	10/2004	Vinegar et al.
6,820,688	B2	11/2004	Vinegar et al.
6,821,501	B2	11/2004	Matzakos et al.
6,854,534	B2	2/2005	Livingstone
6,854,929	B2	2/2005	Vinegar et al.
6,866,097	B2	3/2005	Vinegar et al.
6,871,707	B2	3/2005	Karanikas et al.
6,877,554	B2	4/2005	Stegemeier et al.
6,877,555	B2	4/2005	Karanikas et al.
6,880,633	B2	4/2005	Wellington et al.
6,880,635	B2	4/2005	Vinegar et al.
6,889,769	B2	5/2005	Wellington et al.
6,896,053	B2	5/2005	Berchenko et al.
6,902,003	B2	6/2005	Maher et al.
6,902,004	B2	6/2005	de Rouffignac et al.
6,910,536	B2	6/2005	Wellington et al.
6,910,537	B2	6/2005	Brown et al.
6,913,078	B2	7/2005	Shahin, Jr. et al.
6,913,079	B2	7/2005	Tubel
6,915,850	B2	7/2005	Vinegar et al.
6,918,442	B2	7/2005	Wellington et al.
6,918,443	B2	7/2005	Wellington et al.
6,918,444	B2	7/2005	Passey
6,923,257	B2	8/2005	Wellington et al.
6,923,258	B2	8/2005	Wellington et al.
6,929,067	B2	8/2005	Vinegar et al.
6,932,155	B2	8/2005	Vinegar et al.
6,942,037	B1	9/2005	Arnold
6,948,562	B2	9/2005	Wellington et al.
6,948,563	B2	9/2005	Wellington et al.
6,951,247	B2	10/2005	de Rouffignac et al.
6,951,250	B2	10/2005	Reddy et al.
6,953,087	B2	10/2005	de Rouffignac et al.
6,958,704	B2	10/2005	Vinegar et al.
6,959,761	B2	11/2005	Berchenko et al.
6,964,300	B2	11/2005	Vinegar et al.
6,966,372	B2	11/2005	Wellington et al.
6,966,374	B2	11/2005	Vinegar et al.
6,969,123	B2	11/2005	Vinegar et al.
6,973,967	B2	12/2005	Stegemeier et al.
6,981,548	B2	1/2006	Wellington et al.
6,981,553	B2	1/2006	Stegemeier et al.
6,991,032	B2	1/2006	Berchenko et al.
6,991,045	B2	1/2006	Vinegar et al.
6,994,160	B2	2/2006	Wellington et al.
6,994,168	B2	2/2006	Wellington et al.
6,994,169	B2	2/2006	Zhang et al.
6,997,255	B2	2/2006	Wellington et al.
6,997,518	B2	2/2006	Vinegar et al.
7,004,247	B2	2/2006	Cole et al.
7,004,251	B2	2/2006	Ward et al.
7,011,154	B2	3/2006	Maher et al.
RE39,077	E	4/2006	Eaton
7,032,660	B2	4/2006	Vinegar et al.
7,032,809	B1	4/2006	Hopkins
7,036,583	B2	5/2006	de Rouffignac et al.
7,040,397	B2	5/2006	de Rouffignac et al.
7,040,398	B2	5/2006	Wellington et al.
7,040,399	B2	5/2006	Wellington et al.
7,040,400	B2	5/2006	de Rouffignac et al.
7,048,051	B2	5/2006	McQueen
7,055,600	B2	6/2006	Messier et al.
7,055,602	B2	6/2006	Shpakoff et al.
7,063,145	B2	6/2006	Veenstra et al.
7,066,254	B2	6/2006	Vinegar et al.
7,066,257	B2	6/2006	Wellington et al.
7,073,578	B2	7/2006	Vinegar et al.
7,077,198	B2	7/2006	Vinegar et al.
7,077,199	B2	7/2006	Vinegar et al.
RE39,244	E	8/2006	Eaton
7,086,465	B2	8/2006	Wellington et al.
7,086,468	B2	8/2006	de Rouffignac et al.
7,090,013	B2	8/2006	Wellington et al.
7,096,941	B2	8/2006	de Rouffignac et al.
7,096,942	B1	8/2006	de Rouffignac et al.
7,096,953	B2	8/2006	de Rouffignac et al.
7,100,994	B2	9/2006	Vinegar et al.
7,104,319	B2	9/2006	Vinegar et al.
7,114,566	B2	10/2006	Vinegar et al.
7,114,880	B2	10/2006	Carter
7,121,341	B2	10/2006	Vinegar et al.
7,121,342	B2	10/2006	Vinegar et al.
7,124,584	B1	10/2006	Wetzel et al.
7,128,150	B2	10/2006	Thomas et al.
7,128,153	B2	10/2006	Vinegar et al.
7,147,059	B2	12/2006	Hirsch et al.
7,153,373	B2	12/2006	Maziasz et al.
7,156,176	B2	1/2007	Vinegar et al.
7,165,615	B2	1/2007	Vinegar et al.
7,170,424	B2	1/2007	Vinegar et al.
7,204,327	B2	4/2007	Livingstone
7,219,734	B2	5/2007	Bai et al.
7,225,866	B2	6/2007	Berchenko et al.
7,259,688	B2	8/2007	Hirsch et al.
7,320,364	B2	1/2008	Fairbanks
7,331,385	B2	2/2008	Symington et al.
7,353,872	B2	4/2008	Sandberg et al.
7,357,180	B2	4/2008	Vinegar et al.
7,360,588	B2	4/2008	Vinegar et al.
7,370,704	B2	5/2008	Harris
7,383,877	B2	6/2008	Vinegar et al.
7,424,915	B2	9/2008	Vinegar et al.
7,426,959	B2	9/2008	Wang et al.
7,431,076	B2	10/2008	Sandberg et al.
7,435,037	B2	10/2008	McKinzie, II
7,461,691	B2	12/2008	Vinegar et al.
7,481,274	B2	1/2009	Vinegar et al.
7,490,665	B2	2/2009	Sandberg et al.
7,500,528	B2	3/2009	McKinzie et al.
7,510,000	B2	3/2009	Sanz et al.
7,527,094	B2	5/2009	McKinzie et al.
7,533,719	B2	5/2009	Hinson et al.
7,540,324	B2	6/2009	de Rouffignac et al.
7,549,470	B2	6/2009	Vinegar et al.
7,556,095	B2	7/2009	Vinegar
7,556,096	B2	7/2009	Vinegar et al.
2001/0049342	A1	12/2001	Passey et al.
2002/0027001	A1	3/2002	Wellington et al.
2002/0028070	A1	3/2002	Holen
2002/0033253	A1	3/2002	de Rouffignac et al.
2002/0036089	A1	3/2002	Vinegar et al.
2002/0038069	A1	3/2002	Wellington et al.
2002/0040177	A1*	4/2002	Maher et al. 585/943
2002/0040779	A1	4/2002	Wellington et al.
2002/0040780	A1	4/2002	Wellington et al.
2002/0053431	A1	5/2002	Wellington et al.
2002/0076212	A1	6/2002	Zhang et al.
2002/0112890	A1	8/2002	Wentworth et al.
2002/0112987	A1	8/2002	Hou et al.

2002/0153141 A1 10/2002 Hartman et al.
2003/0029617 A1 2/2003 Brown et al.
2003/0038734 A1 2/2003 Hirsch et al.
2003/0066642 A1 4/2003 Wellington et al.
2003/0079877 A1 5/2003 Wellington et al.
2003/0085034 A1 5/2003 Wellington et al.
2003/0098149 A1* 5/2003 Wellington et al. 166/52
2003/0131989 A1 7/2003 Zakiewicz
2003/0146002 A1 8/2003 Vinegar et al.
2003/0157380 A1 8/2003 Assarabowski et al.
2003/0196789 A1 10/2003 Wellington et al.
2003/0201098 A1 10/2003 Karanikas et al.
2004/0035582 A1 2/2004 Zupanick
2004/0140096 A1 7/2004 Sandberg et al.
2004/0144540 A1 7/2004 Sandberg et al.
2004/0144541 A1 7/2004 Picha et al.
2004/0146288 A1 7/2004 Vinegar et al.
2005/0006097 A1 1/2005 Sandberg et al.
2005/0092483 A1* 5/2005 Vinegar et al. 166/60
2005/0133405 A1 6/2005 Wellington et al.
2005/0133414 A1 6/2005 Bhan et al.
2005/0269077 A1 12/2005 Sandberg
2005/0269088 A1 12/2005 Vinegar et al.
2005/0269089 A1 12/2005 Sandberg et al.
2005/0269090 A1 12/2005 Vinegar et al.
2005/0269091 A1 12/2005 Pastor-Sanz et al.
2005/0269092 A1 12/2005 Vinegar
2005/0269093 A1 12/2005 Sandberg et al.
2005/0269094 A1 12/2005 Harris
2005/0269095 A1 12/2005 Fairbanks
2005/0269313 A1 12/2005 Vinegar et al.
2006/0005968 A1 1/2006 Vinegar et al.
2006/0178546 A1 8/2006 Mo et al.
2006/0191820 A1 8/2006 Mo et al.
2006/0213657 A1 9/2006 Berchenko et al.
2006/0231465 A1 10/2006 Bhan et al.
2006/0254769 A1 11/2006 Wang et al.
2006/0289340 A1 12/2006 Brownscombe et al.
2006/0289536 A1 12/2006 Vinegar et al.
2007/0000810 A1 1/2007 Bhan et al.
2007/0045265 A1 3/2007 McKinzie
2007/0045266 A1 3/2007 Sandberg et al.
2007/0045267 A1 3/2007 Vinegar et al.
2007/0045268 A1 3/2007 Vinegar et al.
2007/0095536 A1 5/2007 Vinegar et al.
2007/0095537 A1 5/2007 Vinegar et al.
2007/0108200 A1 5/2007 McKinzie et al.
2007/0108201 A1 5/2007 Vinegar et al.
2007/0119098 A1 5/2007 Diaz et al.
2007/0125533 A1* 6/2007 Minderhoud et al. 166/267
2007/0127897 A1 6/2007 John et al.
2007/0131411 A1 6/2007 Vinegar et al.
2007/0131415 A1 6/2007 Vinegar et al.
2007/0131419 A1 6/2007 Roes et al.
2007/0131420 A1 6/2007 Mo et al.
2007/0131428 A1 6/2007 den Boestert et al.
2007/0133959 A1 6/2007 Vinegar et al.
2007/0133960 A1 6/2007 Vinegar et al.
2007/0137856 A1 6/2007 McKinzie et al.
2007/0137857 A1 6/2007 Vinegar et al.
2007/0144732 A1 6/2007 Kim et al.
2007/0221377 A1 9/2007 Vinegar et al.
2007/0246994 A1 10/2007 Kaminsky et al.
2007/0284108 A1 12/2007 Roes et al.
2007/0289733 A1 12/2007 Hinson et al.
2008/0006410 A1 1/2008 Looney et al.
2008/0017370 A1 1/2008 Vinegar et al.
2008/0017380 A1 1/2008 Vinegar et al.
2008/0035346 A1 2/2008 Nair et al.
2008/0035347 A1 2/2008 Brady et al.
2008/0035348 A1 2/2008 Vitek et al.
2008/0035705 A1 2/2008 Menotti
2008/0038144 A1 2/2008 Maziasz et al.
2008/0107577 A1 5/2008 Vinegar et al.
2008/0128134 A1 6/2008 Mudunuri et al.
2008/0135244 A1 6/2008 Miller
2008/0135253 A1 6/2008 Vinegar et al.
2008/0135254 A1 6/2008 Vinegar et al.
2008/0142216 A1 6/2008 Vinegar et al.
2008/0142217 A1 6/2008 Pietersen et al.
2008/0173442 A1 7/2008 Vinegar et al.
2008/0173444 A1 7/2008 Stone et al.
2008/0174115 A1 7/2008 Lambirth
2008/0185147 A1 8/2008 Vinegar et al.
2008/0216321 A1 9/2008 Guimont et al.
2008/0217003 A1 9/2008 Kuhlman et al.
2008/0217004 A1 9/2008 de Rouffignac et al.
2008/0217015 A1 9/2008 Vinegar et al.
2008/0217016 A1 9/2008 Stegemeier et al.
2008/0217321 A1 9/2008 Vinegar et al.
2008/0236831 A1 10/2008 Hsu
2008/0277113 A1 11/2008 Stegemeier et al.
2008/0283241 A1 11/2008 Kaminsky et al.
2008/0283246 A1 11/2008 Karanikas et al.
2009/0014180 A1 1/2009 Stegemeier et al.
2009/0014181 A1 1/2009 Vinegar et al.
2009/0071652 A1 3/2009 Vinegar et al.
2009/0078461 A1 3/2009 Mansure et al.
2009/0084547 A1 4/2009 Farmayan et al.
2009/0090158 A1 4/2009 Davidson et al.
2009/0090509 A1 4/2009 Vinegar et al.
2009/0095476 A1 4/2009 Nguyen et al.
2009/0095477 A1 4/2009 Nguyen et al.
2009/0095478 A1 4/2009 Karanikas et al.
2009/0095479 A1 4/2009 Karanikas et al.
2009/0095480 A1 4/2009 Vinegar et al.
2009/0101346 A1 4/2009 Vinegar et al.
2009/0120646 A1 5/2009 Kim et al.
2009/0126929 A1 5/2009 Vinegar

FOREIGN PATENT DOCUMENTS

CA	1165361	4/1984
CA	1168283	5/1984
CA	1196594	11/1985
CA	1253555	5/1989
CA	1288043	8/1991
CA	2015460	10/1991
EP	107927	5/1984
EP	130671	9/1985
EP	0940558	9/1999
GB	156396	1/1921
GB	674082	7/1950
GB	697189	9/1953
GB	1010023	11/1965
GB	1204405	9/1970
GB	1454324	11/1976
SE	121737	5/1948
SE	123136	11/1948
SE	123137	11/1948
SE	123138	11/1948
SE	126674	11/1949
SU	1836876	12/1990
WO	9506093	3/1995
WO	97/07321	2/1997
WO	97/23924	7/1997
WO	98/50179	11/1998
WO	9850179	11/1998
WO	9901640	1/1999
WO	00/19061	4/2000
WO	0181505	11/2001
WO	0181723	11/2001
WO	2007098370	8/2007

WO 2008048448 4/2008

OTHER PUBLICATIONS

A304 Reaction Kinetics Between CO2 and Oil Shale Residual Carbon. I. Effect of Heating Rate on Reactivity, Alan K. Burnham, Jul. 11, 1978 (22 pages).
A305 High-Pressure Pyrolysis of Colorado Oil Shale, Alan K. Burnham & Mary F. Singleton, Oct. 1982 (23 pages).
A306 A Possible Mechanism of Alkene/Alkane Production in Oil Shale Retorting, A.K. Burnham, R.L. Ward, Nov. 26, 1980 (20 pages).
A307 Enthalpy Relations For Eastern Oil Shale, David W. Camp, Nov. 1987 (13 pages).
A308 Oil Shale Retorting: Part 3 A Correlation of Shale Oil 1-Alkene/n-Alkane Ratios With Yield, Coburn et al., Aug. 1, 1977 (18 pages).
A309 The Composition of Green River Shale Oil, Glen L. Cook, et al., 1968 (12 pages).
A311 Thermal Degradation of Green River Kerogen at 150° to 350° C Rate of Production Formation, J.J. Cummins & W.E. Robinson, 1972 (18 pages).
A312 Retorting of Green River Oil Shale Under High-Pressure Hydrogen Atmospheres, LaRue et al., Jun. 1977 (38 pages).
A313 Retorting and Combustion Processes In Surface Oil-Shale Retorts, A.E. Lewis & R.L. Braun, May 2, 1980 (12 pages).
A314 Oil Shale Retorting Processes: A Technical Overview, Lewis et al., Mar. 1984 (18 pages).
A315 Study of Gas Evolution During Oil Shale Pyrolysis by TQMS, Oh et al., Feb. 1988 (10 pages).
A316 The Permittivity and Electrical Conductivity of Oil Shale, A.J. Piwinskii & A. Duba, Apr. 28, 1975 (12 pages).
A317 Oil Degradation During Oil Shale Retorting, J.H. Raley & R.L. Braun, May 24, 1976 (14 pages).
A318 Kinetic Analysis of California Oil Shale by Programmed Temperature Microphyrolysis, John G. Reynolds & Alan K. Burnham, Dec. 9, 1991 (14 pages).
A319 Analysis of Oil Shale and Petroleum Source Rock Pyrolysis by Triple Quadrupole Mass Spectrometry: Comparisons of Gas Evolution at the Heating Rate of 10° C/Min., Reynolds et al. Oct. 5, 1990 (57 pages).
A321 Fluidized-Bed Pyrolysis of Oil Shale, J.H. Richardson & E.B. Huss, Oct. 1981 (27 pages).
A322 Retorting Kinetics for Oil Shale From Fluidized-Bed Pyrolysis, Richardson et al., Dec. 1981 (30 pages).
A323 Recent Experimental Developments in Retorting Oil Shale at the Lawrence Livermore Laboratory, Albert J. Rothman, Aug. 1978 (32 pages).
A324 The Lawrence Livermore Laboratory Oil Shale Retorts, Sandholtz et al. Sep. 18, 1978 (30 pages).
A325 Operating Laboratory Oil Shale Retorts In An In-Situ Mode, W. A. Sandholtz et al., Aug. 18, 1977 (16 pages).
A326 Some Relationships of Thermal Effects to Rubble-Bed Structure and Gas-Flow Patterns in Oil Shale Retorts, W. A. Sandholtz, Mar. 1980 (19 pages).
A327 Assay Products from Green River Oil Shale, Singleton et al., Feb. 18, 1986 (213 pages).
A328 Biomarkers in Oil Shale: Occurrence and Applications, Singleton et al., Oct. 1982 (28 pages).
A329 Occurrence of Biomarkers in Green River Shale Oil, Singleton et al., Mar. 1983 (29 pages).
A330 An Instrumentation Proposal for Retorts in the Demonstration Phase of Oil Shale Development, Clyde J. Sisemore, Apr. 19, 1977, (34 pages).
A302 Pyrolysis Kinetics for Green River Oil Shale From the Saline Zone, Burnham et al., Feb. 1982 (33 pages).
A332 SO2 Emissions from the Oxidation of Retorted Oil Shale, Taylor et al., Nov. 1981 (9 pages).
A333 Nitric Oxide (NO) Reduction by Retorted Oil Shale, R.W. Taylor & C.J. Morris, Oct. 1983 (16 pages).
A334 Coproduction of Oil and Electric Power from Colorado Oil Shale, P. Henrik Wallman, Sep. 24, 1991 (20 pages).
A335 13C NMR Studies of Shale Oil, Raymond L. Ward & Alan K. Burnham, Aug. 1982 (22 pages).
A336 Identification by 13C NMR of Carbon Types in Shale Oil and their Relationship to Pyrolysis Conditions, Raymond L Ward & Alan K. Burnham, Sep. 1983 (27 pages).
A337 A Laboratory Study of Green River Oil Shale Retorting Under Pressure In a Nitrogen Atmosphere, Wise et al., Sep. 1976 (24 pages).
A338 Quantitative Analysis and Evolution of Sulfur-Containing Gases from Oil Shale Pyrolysis by Triple Quadrupole Mass Spectrometry, Wong et al., Nov. 1983 (34 pages).
A339 Quantitative Analysis & Kinetics of Trace Sulfur Gas Species from Oil Shale Pyrolysis by Triple Quadrupole Mass Spectrometry (TQMS), Wong et al., Jul. 5-7, 1983 (34 pages).
A340 Application of Self-Adaptive Detector System on a Triple Quadrupole MS/MS to High Expolsives and Sulfur-Containing Pyrolysis Gases from Oil Shale, Carla M. Wong & Richard W. Crawford, Oct. 1983 (17 pages).
A341 An Evaluation of Triple Quadrupole MS/MS for On-Line Gas Analyses of Trace Sulfur Compounds from Oil Shale Processing, Wong et al., Jan. 1985 (30 pages).
A301 General Model of Oil Shale Pyrolysis, Alan K. Burnham & Robert L. Braun, Nov. 1983 (22 pages).
C106 In Situ Measurement of Some Thermoporoelastic Parameters of a Granite, Berchenko et al., Poromechanics, A Tribute to Maurice Biot, 1998, p. 545-550.
D10 Tar and Pitch, G. Collin and H. Hoeke. Ullmann's Encyclopedia of Industrial Chemistry, vol. A 26, 1995, p. 91-127.
E12 Cortez et al., UK Patent Application GB 2,068,014 A, Date of Publication: Aug. 5, 1981.
E13 Wellington et al., U.S. Appl. No. 60/273,354, filed Mar. 5, 2001.
G9 Geology for Petroleum Exploration, Drilling, and Production. Hyne, Norman J. McGraw-Hill Book Company, 1984, p. 264.
T02 Burnham, Alan, K. "Oil Shale Retorting Dependence of timing and composition on temperature and heating rate", Jan. 27, 1995, (23 pages).
T04 Campbell, et al., "Kinetics of oil generation from Colorado Oil Shale" IPC Business Press, Fuel, 1978, (3 pages).
AA19 Bosch et al. "Evaluation of Downhole Electric Impedance Heating Systems for Paraffin Control in Oil Wells," IEEE Transactions on Industrial Applications, 1991, vol. 28; pp. 190-194.
AA20 "McGee et al. ""Electrical Heating with Horizontal Wells, The heat Transfer Problem,"" International Conference on Horizontal Well Tehcnology, Calgary, Alberta Canada, 1996; 14 pages".
T07 Hill et al., "The Characteristics of a Low Temperature in situ Shale Oil" American Institute of Mining, Metallurgical & Petroleum Engineers, 1967 (pp. 75-90).
T13 SSAB report, "A Brief Description of the Ljungstrom Method for Shale Oil Production," 1950, (12 pages).
T14 Salomonsson G., SSAB report, The Lungstrom In Situ-Method for Shale Oil Recovery, 1950 (28 pages).
T15 "Swedish shale oil-Production method in Sweden," Organisation for European Economic Co-operation, 1952, (70 pages).
T16 SSAB report, "Kvarn Torp" 1958, (36 pages).
T17 SSAB report, "Kvarn Torp" 1951 (35 pages).
T19 Vogel et al. "An Analog Computer for Studying Heat Transfrer during a Thermal Recovery Process," AIME Petroleum Transactions, 1955 (pp. 205-212).
T20 "Skiferolja Genom Uppvarmning Av Skifferberget," Faxin Department och Namder, 1941, (3 pages).
T22 Ronnby, E. "Kvarntorp-Sveriges Storsta skifferoljeindustri," 1943, (9 pages).
T23 SAAB report, "The Swedish Shale Oil Industry," 1948 (8 pages).
T24 Gejrot et al., "The Shale Oil Industry in Sweden," Carlo Colombo Publishers-Rome, Proceedings of the Fourth World Petroleum Congress, 1955 (8 pages).
T25 Hedback, T. J., The Swedish Shale as Raw Material for Production of Power, Oil and Gas,' XIth Sectional Meeting World Power Conference, 1957 (9 pages).
T26 SAAB, "Santa Cruz, California, Field Test of the Lins Method for the Recovery of Oil from Sand", 1955 vol. 1, (141 pages) English.
T27 SAAB, "Santa Cruz, California, Field Test of the Lins Method for the Recovery of Oil from Sand-Figures", 1955 vol. 2, (146 pages) English.

T28 "Santa Cruz, California, Field Test of the Lins Method for the Recovery of Oil from Sand-Memorandum re: tests", 1955 vol. 3, (256 pages) English.
T29 Helander, R.E., "Santa Cruz, California, Field Test of Carbon Steel Burner Casings for the Lins Method of Oil Recovery", 1959 (38 pages) English.
T30 Helander et al., Santa Cruz, California, Field Test of Fluidized Bed Burners for the Lins Method of Oil Recovery 1959, (86 pages) English.
T31 SSAB report, "Bradford Residual Oil, Athabasa Ft. McMurray" 1951, (207 pages), partial translation.
T32 "Lins Burner Test Results-English" 1959-1960.
T37 SSAB report, "Assessment of Future Mining Alternatives of Shale and Dolomite," 1962, (59 pages) Swedish.
T38 SSAB report. "Kartong 2 Shale: Ljungstromsanlaggningen" (104 pages) Swedish.
T40 Saab report, "Swedish Geological Survey Report, Plan to Delineate Oil shale Resource in Narkes Area (near Kvarntorp)," 1941 (13 pages). Swedish.
T41 SAAB report, "Recovery Efficiency," 1941, (61 pages). Swedish.
T42 SAAB report, "Geologic Work Conducted to Assess Possibility of Expanding Shale Mining Area in Kvarntorp; Drilling Results, Seismic Results," 1942 (79 pages). Swedish.
T43 SSAB report, "Ojematinigar vid Norrtorp," 1945 (141 pages).
T44 SSAB report, "Inhopplingschema, Norrtorp II 20/3-17/8", 1945 (50 pages). Swedish.
T45 SSAB report, "Secondary Recovery after LINS," 1945 (78 pages).
T46 SSAB report, "Maps and Diagrams, Geology," 1947 (137 pages). Swedish.
T47 SSAB report, Styrehseprotoholl, 1943 (10 pages). Swedish.
T48 SSAB report, "Early Shale Retorting Trials" 1951-1952, (134 pages). Swedish.
T49 SSAB report, "Analysis of Lujunstrom Oil and its Use as Liquid Fuel," Thesis by E. Pals, 1949 (83 pages). Swedish.
T50 SSAB report, "Environmental Sulphur and Effect on Vegetation," 1951 (50 pages). Swedish.
T51 SSAB report, "Tar Sands", vol. 135 1953 (20 pages, pp. 12-15 translated). Swedish.
T52 SSAB report, "Assessment of Skanes Area (Southern Sweden) Shales as Fuel Source," 1954 (54 pages). Swedish.
T53 SSAB report, "From as Utre Dn Text Geology Reserves," 1960 (93 pages). Swedish.
T54 SSAB report, "Kvarntorps-Environmental Area Asessment," 1981 (50 pages). Swedish.
AA21 "IEEE Recommended Practice for Electrical Impedance, Induction, and Skin Effect Heating of Pipelines and Vessels," IEEE Std. 844-200, 2000; 6 pages.
T33 SSAB "Annual Reports, SSAB Laboratory, Address Annually Issues-Shale and Ash, Oil Gas, Waste Water, Analytical," 1953-1954, 166 pages. (Swedish).
T36 SSAB report, "Cost Comparison of Mining and Processing of Shale and Dolomite Using Various Production Alternatives", 1960; 64 pages. (Swedish).
Raad et al., "Converter-Fed Subsea Motor Drives", Industry Applications, IEEE Transactions on vol. 32, Issue 5, Sep.-Oct. 1996 pp. 1069-1079.
Boggs, "The Case for Frequency Domain PD Testing In The Context Of Distribution Cable", Electrical Insulation Magazine, IEEE, vol. 19, Issue 4, Jul.-Aug. 2003, pp. 13-19.
"Refining Processess 2000, Hydrocarbon Processing, Gulf Publishing Co. pp. 87-142de Product" filed Apr. 7, 2006.
Co-pending U.S. Appl. No. 11/585,302 entitled "Temperature Limited Heater With a Conduit substantially electrically isolated from the formation" filed Oct. 20, 2006, available in Pair.
Co-pending U.S. Appl. No. 11/584,804 entitled "Varying Heating in Dawsonite Zones in Hydrocarbon Containing Formations" filed Oct. 20, 2006, available in Pair.
Co-pending U.S. Appl. No. 11/788,863 entitled "Temperature Limited Heaters Using Phase Transformation of Ferromagnetic Material" filed Apr. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/788,826 entitled "Welding Shield for Coupling Heaters" filed Apr. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/788,863 entitled "Temperature Limited Heaters Using Phase Transformation of Ferromagnetic Material" filed Apr. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/788,859 entitled "Time Sequenced Heating of Multiple Layers in a Hydrocarbon Containing Formation" filed Apr. 20, 2007; available in Pair.
BB15. "Frozen Soil Barrier" U.S. Dept. of Energy, Innovative Technology Summary Report, DOE/EM-0483, Oct. 1999, 27 pages.
Co-pending U.S. Appl. No. 11/788,772 entitled "Methods of Producing Transportation Fuel" filed Apr. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/788,822 entitled "Power Systems Utilizing the Heat of Produced Formation Fluid" filed Apr. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/788,861 entitled "Power Systems Utilizing the Heat of Produced Formation Fluid" filed Apr. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/788,858 entitled "High Strength Alloys" filed Apr. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/788,871 entitled "Non-Ferromagnetic Overburden Casing" filed Apr. 20, 2007; available in Pair.
Swatzell et al. "Frozen Soil Barrier Technology" U.S. Dept. Of Energy, Innovative Technology Summary Report, Apr. 1995, 32 pages.
Co-pending U.S. Appl. No. 11/788,868 entitled "Alternate Energy Source Usage for in Situ Heat" filed Apr. 20, 2007 available in Pair.
Co-pending U.S. Appl. No. 11/975,714 entitled "Wax Barrier for Use With In Situ Processes for Treating Formations" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,676 entitled "Heating Tar Sands Formations to Visbreaking Temperatures" filed Oct. 20, 2007 available in Pair.
Co-pending U.S. Appl. No. 11/975,713 entitled "Heating Tar Sands Formations While Controlling Pressure" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,737 entitled "Condensing Vaporized Water In Situ to Treat Tar Sands Formations" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,679 entitled "Moving Hydrocarbons Through Portions of Tar Sands Formations" filed Oct. 20, 20067 available in Pair.
Co-pending U.S. Appl. No. 11/975,700 entitled "Treating Tar Sands Formations With Karsted Zones" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,677 entitled "Treating Tar Sands Formations With Dolomite" to Vinegar et al., filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,689 entitled "Creating and Maintaining a Gas Cap in Tar Sands Formations" to Stegemeier et al.,filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,738 entitled "Creating Fluid Injectivity in Tar Sands Formations" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Patent Application N7. U.S. Appl. No. 11/975,712 entitled "Producing Drive Fluid In Situ in Tar Sands Formations" filed Oct. 20, 2006; available in Pair.
Co-pending U.S. Appl. No. 11/975,712 entitled "Producing Drive Fluid In Situ in Tar Sands Formations" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,688 entitled "Heating Hydrocarbon Containing Formations in a Line Drive Staged" filed Oct. 20, 2006; available in PAI7.
Co-pending U.S. Appl. No. 11/975,691 entitled "Heating Hydrocarbon Containing Formations in a Checkerboard Pattern Staged Process" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,701 entitled "Heating Hydrocarbon Containing Formations in a Spiral Startup Staged Sequence" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,736 entitled "Using Geothermal Energy to Heat a Portion of a Formation for an In Situ Heat Treatment Process" filed Oct. 20, 2007; available in Pair.

Co-pending U.S. Appl. No. 11/975,678 entitled "Gas Injection to Inhibit Migration During an In Situ Heat Treatment Process" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,690 entitled "In Situ Heat Treatment Process Utilizing a Closed Loop Heating System" filed Oct. 20, 2007; available in Pair.
Co-pending U.S. Appl. No. 11/975,724 entitled "In Situ Heat Treatment Process Utilizing Oxidizers to Heat a Subsurface Formation" filed Oct. 20, 2007; available in Pair.
Beal, C. "The Viscosity of Air, Water, Natural Gas, Crude Oil and Its Associated Gases at Oil Field Temperatures and Pressures" TP 2018 in Petroleum Technology, Mar. 1946, pp. 94-115.
Cary, J. W., Mayland, H. F., "Salt and Water Movement in Unsaturated Frozen Soil" Soil Science Society of America, Proceedings, Jul.-Aug. 1972, vol. 36, No. 4, pp. 549-555.
Dash, J. G. "Thermomolecular Pressure in Surface Melting: Motivation for Frost Heave" Science, Dec. 22, 1989, vol. 246, pp. 1591-1593.
Gross et al. "Recent Experimental Work on Solute Redistribution at the Ice/Water Interface. Implications for Electrical Properties and Interface Process" J. de Physique Colloque C1, supplement au No. 3, vol. 48, Mar. 1987, pp. C1-527-C1529.
Hallet, B. "Solute Redistribution in Freezing Ground" Proceeding of the Third International Conference on Permafrost, Edmonton, Alberta, 1978, pp. 86-91.
Harris, J.S. "Ground Freezing in Practice" Telford, 1995, pp. 1-264.
Hofmann et al. "Redistribution of Soil Water and Solutes in Fine and Coarse Textured Soils After Freezing" Proc. Intl. Symp. On Agricultural, Range, and Forest Lands, Mar. 21-22, 1990, Spokane, CCREL Special Report 90-1, K. R. Cooley, Ed., pp. 263-270.
Iskandar, I. K. "Effect of Freezing on the Level of Contaminants in Uncontrolled Hazardous Waste Sites" U.S. Army Corp of Engineers Special Report 86-19, Jul. 1986, pp. 1-33.
Oberlander et al. "Mitigative Techniques for Ground-Water Contamination Associated with Severe Nuclear Accidents", NUREG/CR-4251, PNL-5461. vol. 1, Aug. 1985, pp. 4.103-4.110.
Matthews et al. "Pressure Buildup and Flow Tests in Wells" Society of Petroleum Engineers, 1967, pp. 1-172.
Sanger, F. J. "Ground Freezing in Construction" J. Proceedings of the American Society of Civil Engineers, Jan. 1968, pp. 131-156.
Some Effects of Pressure on Oil-Shale Retorting, Society of Petroleum Engineers Journal, J.H. Bae, Sep. 1969; pp. 287-292.
New in situ shale-oil recovery process uses hot natural gas; The Oil & Gas Journal; May 16, 1966, p. 151.
Evaluation of Downhole Electric Impedance Heating Systems for Paraffin Control in Oil Wells; Industry Applications Society 37th Annual Petroleum and Chemical Industry Conference; The Institute of Electrical and Electronics Engineers Inc., Bosch et al., Sep. 1990, pp. 223-227.
New System Stops Paraffin Build-up; Petroleum Engineer, Eastlund et al., Jan. 1989, (3 pages).
Oil Shale Retorting: Effects of Particle Size and Heating Rate on Oil Evolution and Intraparticle Oil Degradation; Campbell et al. In Situ 2(1), 1978, pp. 1-47.
Molecular Mechanism of Oil Shale Pyrolysis in Nitrogen and Hydrogen Atmospheres, Hershkowitz et al.; Geochemistry and Chemistry of Oil Shales, American Chemical Society, May 1983 pp. 301-316.
The Characteristics of a Low Temperature in Situ Shale Oil; George Richard Hill & Paul Dougan, Quarterly of the Colorado School of Mines, 1967; pp. 75-90.
Direct Production Of A Low Pour Point High Gravity Shale Oil; Hill et al., I & EC Product Research and Development, 6(1), Mar. 1967; pp. 52-59.
The Benefits of In Situ Upgrading Reactions to the Integrated Operations of the Orinoco Heavy-Oil Fields and Downstream Facilities, Myron Kuhlman, Society of Petroleum Engineers, Jun. 2000; pp. 1-14.
Monitoring Oil Shale Retorts by Off-Gas Alkene/Alkane Ratios, John H. Raley, Fuel, vol. 59, Jun. 1980, pp. 419-424.
The Shale Oil Question, Old and New Viewpoints, A Lecture in the Engineering Science Academy, Dr. Fredrik Ljungstrom, Feb. 23, 1950, published in Teknisk Trdskrift, Jan. 1951 p. 33-40.
Underground Shale Oil Pyrolysis According to the Ljungstroem Method; Svenska Skifferolje Aktiebolaget (Swedish Shale Oil Corp.), IVA, vol. 24, 1953, No. 3, pp. 118-123.
Kinetics of Low-Temperature Pyrolysis of Oil Shale by the IITRI RF Process, Sresty et al.; 15th Oil Shale Symposium, Colorado School of Mines, Apr. 1982 pp. 1-13.
Application of a Microretort to Problems in Shale Pyrolysis, A. W. Weitkamp & L.C. Gutberlet, Ind. Eng. Chem. Process Des. Develop. vol. 9, No. 3, 1970, pp. 386-395.
Oil Shale, Yen et al., Developments in Petroleum Science 5, 1976, pp. 187-189, 197-198.
The Composition of Green River Shale Oils, Glenn L. Cook, et al., United Nations Symposium on the Development and Utilization of Oil Shale Resources, 1968, pp. 1-23.
High-Pressure Pyrolysis of Green River Oil Shale, Burnham et al., Geochemistry and Chemistry of Oil Shales, American Chemical Society, 1983, pp. 335-351.
Geochemistry and Pyrolysis of Oil Shales, Tissot et al., Geochemistry and Chemistry of Oil Shales, American Chemical Society, 1983, pp. 1-11.
A Possible Mechanism of Alkene/Alkane Production, Burnham et al., Oil Shale, Tar Sands, and Related Materials, American Chemical Society, 1981, pp. 79-92.
The Ljungstroem In-Situ Method of Shale Oil Recovery, G. Salomonsson, Oil Shale and Cannel Coal, vol. 2, Proceedings of the Second Oil Shale and Cannel Coal Conference, Institute of Petroleum, 1951, London, pp. 260-280.
Developments in Technology for Green River Oil Shale, G.U. Dinneen, United Nations Symposium on the Development and Utilization of Oil Shale Resources, Laramie Petroleum Research Center, Bureau of Mines, 1968, pp. 1-20.
The Thermal and Structural Properties of a Hanna Basin Coal, R.E. Glass, Transactions of the ASME, vol. 106, Jun. 1984, pp. 266-271.
On the Mechanism of Kerogen Pyrolysis, Alan K. Burnham & James A. Happe, Jan. 10, 1984 (17 pages).
Comparison of Methods for Measuring Kerogen Pyrolysis Rates and Fitting Kinetic Parameters, Burnham et al., Mar. 23, 1987, (29 pages).
Further Comparison of Methods for Measuring Kerogen Pyrolysis Rates and Fitting Kinetic Parameters, Burnham et al., Sep. 1987, (16 pages).
Shale Oil Cracking Kinetics and Diagnostics, Bissell et al., Nov. 1983, (27 pages).
Mathematical Modeling of Modified In Situ and Aboveground Oil Shale Retorting, Robert L. Braun, Jan. 1981 (45 pages).
Progress Report on Computer Model for In Situ Oil Shale Retorting, R.L. Braun & R.C.Y. Chin, Jul. 14, 1977 (34 pages).
Chemical Kinetics and Oil Shale Process Design, Alan K. Burnham, Jul. 1993 (16 pages).
Reaction Kinetics and Diagnostics for Oil Shale Retorting, Alan K. Burnham, Oct. 19, 1981 (32 pages).
Reaction Kinetics Between Steam and Oil Shale Char, A.K. Burnham, Oct. 1978 (8 pages).
General Kinetic Model of Oil Shale Pyrolysis, Alan K. Burnham & Robert L. Braun, Dec. 1984 (25 pages).
PCT "International Search Report and Written Opinion" for International Application No. PCT/US07/09741, mailed, Aug. 28, 2008; 12 pages.
PCT "International Search Report and Written Opinion" for International Application No. PCT/US07/81890, mailed, Sep. 2, 2008; 11 pages.
PCT "International Search Report and Written Opinion" for International Application No. PCT/US07/81905, mailed, Aug. 27, 2008; 9 pages.
PCT "International Search Report and Written Opinion" for International Application No. PCT/US07/22376, mailed, Aug. 22, 2008; 10 pages.
PCT "International Search Report and Written Opinion" for International Application No. PCT/US08/60757, mailed, Aug. 22, 2008; 7 pages.
PCT "International Search Report and Written Opinion" for International Application No. PCT/US08/60754, mailed, Aug. 21, 2008; 7 pages.

PCT "International Search Report and Written Opinion" for International Application No. PCT/US08/60748, mailed, Aug. 22, 2008; 7 pages.

PCT "International Search Report and Written Opinion" for International Application No. PCT/US08/60746, mailed, Jul. 18, 2008; 7 pages.

PCT "International Search Report and Written Opinion" for International Application No. PCT/US07/81910, mailed , Aug. 7, 2008; 8 pages.

Moreno, James B., et al., Sandia National Laboratories, "Methods and Energy Sources for Heating Subsurface Geological Formations, Task 1: Heat Delivery Systems," Nov. 20, 2002, pp. 1-166.

PCT "International Search Report and Written Opinion" for International Application No. PCT/US06/40971, mailed , Jul. 23, 2008; 9 pages.

PCT "International Search Report and Written Opinion" for International Application No. PCT/US06/15142, mailed , Jul. 21, 2008; 10 pages.

PCT "International Search Report and Written Opinion" for International Application No. PCT/US08/60750, mailed , Aug. 18, 2008;7 pages.

Carroll, J., et al; "Design Considerations for Acid Gas Injection," Laurance Reid Gas Conditioning Conference, Feb. 1999, pp. 1-26.

Carroll, J., "Phase Equilibria Relevant to Acid Gas Injection, Part 1-Non-Aqueous Phase Behaviour," Journal of Canadian Petroleum Technology, Jun. 2002, vol. 41, No. 6, pp. 1-7.

Carroll, John, "Physical Properties Relevant to Acid Gas Injection," Venezuelan Gas Processors Association XIV International Gas Convention, May 2000, pp. 1-24.

Wong, S., et al"Economics of Acid Gas Reinjection: An Innovative CO2 Storage Opportunity," 2003, pp. 1-4.

* cited by examiner



Y
T (°C)
0
1
2
3
4
0
100
200
300
400
500
1
2
3

FIG. 1



200
202
204
204
206
208
208
210

FIG. 2



224
226
212
230
214
222
228
216
220
218

FIG. 3



226
224
238
218
212
216
236
234
214
232
220

FIG. 4



368
370
374
360'
356
356'
372
366
358
360
362
354
364
246
352
350
344
346
348
342
334
330
340
338
336
332
324
320
240
328
322
326

FIG. 5



354
356a
356b
352
358'
358"
360"
2000
2002
360'
362"
362'
356'
368
370
366
364'
364
374
372
360'

FIG. 5A



368
370
356
355
354
246
352
350
344
346
348
342
334
330
340
338
336
332
324
320
240
328
322
326

FIG. 6



370
368
402
336'
400
412
414
416
398
410
408
394
392
390
396
388
382'
382
404
384
380
406
272'
386
378
376
272

FIG. 7



2004
2014
2006
2012
2010
2008
2012
2006
2008
2008
2010
2012
2014
2006
2008
2012

FIG. 8




FIG. 10




FIG. 9C




FIG. 9B




FIG. 9A




FIG. 11




FIG. 12




FIG. 15




FIG. 14




FIG. 13




FIG. 16




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18




FIG. 21




FIG. 19




FIG. 20




FIG. 24




FIG. 22




FIG. 23




FIG. 25




FIG. 26B




FIG. 27B




FIG. 28B




FIG. 26A




FIG. 27A




FIG. 28A




FIG. 29B




FIG. 30B




FIG. 29A




FIG. 30A




FIG. 35




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 48




FIG. 47




FIG. 49B




FIG. 49A




FIG. 50A




FIG. 50B




FIG. 50C




FIG. 51




FIG. 52




FIG. 53




FIG. 55




FIG. 54




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68




FIG. 69



634
636
530
638
638
638
630
626
624
460
628
638
638
638
644
632
642
640
632

FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82



624
626
628
680
680
680
632
632
632
524
682
670
682
682
524
658
682
524
524
672
674

FIG. 83



626
628
524
624
524
632
632
682
632
682
670
682
682
670
682
682
658
668
668
672
674

FIG. 84



658
706
690
628
632
624
704
632
626
632
688
706
+
-
702

FIG. 86



624
632
670
632B
668
672
674
658
524
632A
628
626
524
632A
670
632B
668

FIG. 85




FIG. 87




FIG. 88




FIG. 89




FIG. 90




FIG. 91




FIG. 92




FIG. 93



714
714
712C
712A
712A
712A
712B
712B
712B
712C
712C
712C
712A
712A
712A
712B
712B
712B
712C
712C
712A
712B

FIG. 94



650
716A
458
460
-V
716B
716C
718
720
724
728
V
534
630
A
A
722
716B
716C
718
720
+V
716A
646

FIG. 95



650
716B
716C
716E
716F
716H
716I
716K
716L
-V
726B
716A
716D
716G
716J
724
728
V
722
+V
726A
646

FIG. 96



458
716L
716J
716K
716I
206
716G
716H
716F
716D
716E
206
716C
716A
460
716B

FIG. 97



458
460
642
726B
716F
716E
716D
716C
716B
716A
726A
722
+V
728
V
-V
724

FIG. 98




FIG. 99




FIG. 100




FIG. 101




FIG. 102




FIG. 103




FIG. 104




FIG. 105




FIG. 106




FIG. 107




FIG. 108




FIG. 109B




FIG. 109A




FIG. 110A



530
458
530
460B
740
460A
742
522
532
744
630B
630A
522B
522A
532
744
530
742
522

FIG. 110B




FIG. 111A




FIG. 111B




FIG. 112




FIG. 113




FIG. 114




FIG. 115A




FIG. 115B



484
484
450
448
2038
2038
2046
2046
2040B
2044B
2040A
2044A
2044A

FIG. 116



484
484
450
2044B
2040B
2046'
2038
2046
2046
2046
448
2038
2044A
2040A

FIG. 117




FIG. 118




FIG. 119




FIG. 120A




FIG. 120B



484
484
2046"
2040B
448
2038
450
2046"'
2044A
2040C
2040A
2046'
2044B

FIG. 121



484
484
2044A
450
2046"
2040B
2046"'
2040C"
2038
2038
2046C
2040C'
2038
2040A
2046'
2044B

FIG. 122



484
484
450
2044A
2040B
2046"
2046"
2038
2050"
2046'
2046'
2040A"
2044B
2038
2050'
2040A'

FIG. 123




FIG. 124




FIG. 125




FIG. 126




FIG. 127




FIG. 128




FIG. 129




FIG. 130





FIG. 131

FIG. 132





746
716
716
716
206A
716
206A
716
716
716
206A
716
206A
716
716
460

FIG. 133



748
206
748
206
748
206
748
206
748
716
748
206
748
206
748
206
748
206
748
716
748
748
748
748
748
716

FIG. 134




FIG. 135




FIG. 136




FIG. 137




FIG. 138




FIG. 139




FIG. 140




FIG. 141




FIG. 142




FIG. 143




FIG. 144




FIG. 145




FIG. 146




FIG. 147




FIG. 148




FIG. 149




FIG. 150




FIG. 151




FIG. 153




FIG. 155




FIG. 152




FIG. 154




FIG. 156




FIG. 157




FIG. 158




FIG. 160




FIG. 159




FIG. 161




FIG. 162




FIG. 163




FIG. 164




FIG. 165




FIG. 166




FIG. 167




FIG. 168




FIG. 169



458
460
2208
2208
2200
2196
2208
2206
2202
2198
534
2200
2194
2206
2192
2206

FIG. 170




FIG. 171




FIG. 172




FIG. 173




FIG. 174




FIG. 175




FIG. 176




FIG. 177




FIG. 178




FIG. 179




FIG. 180





FIG. 181

FIG. 182


922
882
920-21
920-20
920-19
920-18
920-17
920-36
920-22
920-7
920-6
920-5
920-16
920-35
920-23
920-8
920-1
920-4
920-15
920-34
920-24
920-9
920-2
920-3
920-14
920-33
920-25
920-10
920-11
920-12
920-13
920-32
920-26
920-27
920-28
920-29
920-30
920-31




FIG. 183




FIG. 184




FIG. 185




FIG. 186




FIG. 187




FIG. 188




FIG. 189




FIG. 190



956
200
956
922
748/206
202
716
202
716
202
202
882
956
748/206
956

FIG. 191




FIG. 192




FIG. 193




FIG. 194




FIG. 195




FIG. 196



882
748
748
748
748
748
960
960
206
206
748
748
748
206
206
960
960
748
748
206
206
200
922
200

FIG. 197




FIG. 198



2108
2118
206
2116
202
458
2114
2120
460
2110
2122
2120
2112
2124

FIG. 199



0.010
0.009
0.008
0.007
0.006
0.005
0.004
0.003
0.002
0.001
0.000
Ω
0
93
204
315
426
537
648
760
871
°C
964
966
968
970
972
974
976
978

FIG. 200




FIG. 201




FIG. 202




FIG. 203




FIG. 204




FIG. 205




FIG. 206




FIG. 207




FIG. 208




FIG. 209




FIG. 210




FIG. 211




FIG. 212




FIG. 213




FIG. 214




FIG. 215




FIG. 216




FIG. 217




FIG. 218




FIG. 219




FIG. 220




FIG. 221




FIG. 222A




FIG. 222B




FIG. 222C



1224
1222
1220
1218
1216
1214
1212
1210
1208
1206
1204
1202
760
732
704
676
648
621
593
565
537
510
482
454
426
398
371
343
315
112
118
125
131
137
143
149
155
161
167
173
m
°C

FIG. 223



l/kg
0.58
0.50
0.42
0.33
0.25
0.17
0.08
0
1232
1236
1238
1240
1242
1244
1230
1246
1236
1228
1260
1258
1256
1254
1252
1250
1248
1226
820
656
492
328
164
0
W/m
173
167
161
155
149
143
137
131
125
118
112
m

FIG. 224




FIG. 225




FIG. 226




FIG. 227




FIG. 228




FIG. 229




FIG. 230



Power (W/ft)
340
320
300
280
260
240
220
200
Thickness (in.)
.1
0.105
0.11
0.115
0.12
0.125
0.13

FIG. 231



R (ohms) or I (Amps)
80
70
60
50
40
30
20
10
0
1800
1600
1400
1200
1000
800
600
400
200
0
T (°F)
2128
2130
2126
270
265
260
255
250
245
240
235
230
225
Power (W/ft)

FIG. 232



Power (W/ft)
350
300
250
200
150
100
50
0
0
365
730
1095
1460
1825
Time (days)
2134
2136
2132

FIG. 233



T (°F)
1800
1600
1400
1200
1000
800
600
400
200
0
0
365
730
1095
1460
1825
Time (days)
2138
2140
2142
2144
2146
2148
2150

FIG. 234



2.2 x 10^5
1.7 x 10^5
1.1 x 10^5
5.6 x 10^4
0
Cumulative Gas (m^3)
318
238
159
79
0
Cumulative Oil (m^3)
0
1
2
3
4
5
Time (yrs)
1344
1350
1346
1348

FIG. 235




FIG. 236




FIG. 237




FIG. 238




FIG. 239




FIG. 240




FIG. 241




FIG. 242



1396
1394
T
Wt % Phase
Temperature (C)
100
90
80
70
60
50
40
30
20
10
0
600
700
800
900
1000

FIG. 243




FIG. 244




FIG. 245




FIG. 246




FIG. 247




FIG. 248




FIG. 249




FIG. 250




FIG. 251




FIG. 252




FIG. 253




FIG. 254




FIG. 255A




FIG. 255B




FIG. 255C




FIG. 255D




FIG. 255E




FIG. 256




FIG. 257




FIG. 258




FIG. 259




FIG. 260




FIG. 261




FIG. 262




FIG. 263




FIG. 264




FIG. 265




FIG. 266




FIG. 267




FIG. 268




FIG. 269




FIG. 270




FIG. 271




FIG. 272




FIG. 273




FIG. 274




FIG. 275



(ft3/day)
2.00e+5
1.50e+5
1.00e+5
5.00e+4
0.00e+0
300
200
100
0
(bbl/day)
0
1
2
3
4
5
6
7
8
9
10
(Yrs)
1498
1500

FIG. 276



(vol%OBIP)
100
80
60
40
20
0
360
340
320
300
280
260
240
(°C)
2152
2154
2156
2158
2160
2162
(WT%OBIP)

FIG. 277



(wt%OBIP)
50
40
30
20
10
0
360
340
320
300
280
260
240
2164
2166
2168
2170
2172
2174
100
80
60
40
20
0
(WT%OBIP)
(°C)

FIG. 278



(psig)
4500
4000
3500
3000
2500
2000
1500
1000
500
0
360
350
340
330
320
310
300
290
280
270
260
(°C)
2176
2178
2180
2182
45
40
35
30
25
20
15
10
5
0
(°)

FIG. 279




FIG. 280A

FIG. 280B

FIG. 280C

FIG. 280D



Coke Yield
40
35
30
25
20
15
10
5
0
250
260
270
280
290
300
310
320
330
340
350
360
(°C)
2188
2190

FIG. 281




FIG. 282B




FIG. 282A




FIG. 282D




FIG. 282C




FIG. 284




FIG. 283

SOUR GAS INJECTION FOR USE WITH IN SITU HEAT TREATMENT

PRIORITY CLAIM

This patent application claims priority to U.S. Provisional Patent No. 60/794,298 entitled "SYSTEMS AND PROCESSES FOR USE IN TREATING SUBSURFACE FORMATIONS" to Vinegar et al. filed on Apr. 21, 2006, which is incorporated by reference in its entirety; and to U.S. Provisional Patent No. 60/853,096 entitled "SYSTEMS, METHODS, AND PROCESSES FOR USE IN TREATING SUBSURFACE FORMATIONS" to Vinegar et al. filed on Oct. 20, 2006, which is incorporated by reference in its entirety.

GOVERNMENT INTEREST

The Government has certain rights in this invention pursuant to Agreement No. ERD-05-2516 between UT-Battelle, LLC, operating under prime contract No. DE-ACO5-00OR22725 for the US Department of Energy and Shell Exploration and Production Company.

The Government has certain rights in the invention pursuant to Agreement No. SD 10634 between Sandia National Laboratories and Shell Exploration and Production Company.

RELATED PATENTS

This patent application incorporates by reference in its entirety each of U.S. Pat. No. 6,688,387 to Wellington et al.; U.S. Pat. No. 6,991,036 to Sumnu-Dindoruk et al.; U.S. Pat. No. 6,698,515 to Karanikas et al.; U.S. Pat. No. 6,880,633 to Wellington et al.; U.S. Pat. No. 6,782,947 to de Rouffignac et al; U.S. Pat. No. 6,991,045 to Vinegar et al.; U.S. Pat. No. 7,073,578 to Vinegar et al.; and U.S. Pat. No. 7,121,342 to Vinegar et al. This patent application incorporates by reference in its entirety U.S. Patent Application Publication 2005-0269313 to Vinegar et al. This patent application incorporates by reference in its entirety U.S. patent application Ser. No. 11/409,558 to Vinegar et al.; and Ser. No. 11/585,302 to Vinegar et al.

BACKGROUND

1. Field of the Invention

The present invention relates generally to methods and systems for production of hydrocarbons, hydrogen, and/or other products from various subsurface formations such as hydrocarbon containing formations.

2. Description of Related Art

Hydrocarbons obtained from subterranean formations are often used as energy resources, as feedstocks, and as consumer products. Concerns over depletion of available hydrocarbon resources and concerns over declining overall quality of produced hydrocarbons have led to development of processes for more efficient recovery, processing and/or use of available hydrocarbon resources. In situ processes may be used to remove hydrocarbon materials from subterranean formations. Chemical and/or physical properties of hydrocarbon material in a subterranean formation may need to be changed to allow hydrocarbon material to be more easily removed from the subterranean formation. The chemical and physical changes may include in situ reactions that produce removable fluids, composition changes, solubility changes, density changes, phase changes, and/or viscosity changes of the hydrocarbon material in the formation. A fluid may be, but is not limited to, a gas, a liquid, an emulsion, a slurry, and/or a stream of solid particles that has flow characteristics similar to liquid flow.

A wellbore may be formed in a formation. In some embodiments wellbores may be formed using reverse circulation drilling methods. Reverse circulation methods are suggested, for example, in published U.S. Patent Application Publication No. 2004-0079553 to Livingstone, and U.S. Pat. No. 6,854,534 to Livingstone; U.S. Pat. No. 6,892,829 to Livingstone, U.S. Pat. No. 7,090,018 to Livingstone; and U.S. Pat. No. 4,823,890 to Lang, the disclosures of which are incorporated herein by reference. Reverse circulation methods generally involve circulating a drilling fluid to a drilling bit through an annulus between concentric tubulars to the borehole in the vicinity of the drill bit, and then through openings in the drill bit and to the surface through the center of the concentric tubulars, with cuttings from the drilling being carried to the surface with the drilling fluid rising through the center tubular. A wiper or shroud may be provided above the drill bit and above a point where the drilling fluid exits the annulus to prevent the drilling fluid from mixing with formation fluids. The drilling fluids may be, but is not limited to, air, water, brines and/or conventional drilling fluids.

In some embodiments, a casing or other pipe system may be placed or formed in a wellbore. U.S. Pat. No. 4,572,299 issued to Van Egmond et al., which is incorporated by reference as if fully set forth herein, describes spooling an electric heater into a well. In some embodiments, components of a piping system may be welded together. Quality of formed wells may be monitored by various techniques. In some embodiments, quality of welds may be inspected by a hybrid electromagnetic acoustic transmission technique known as EMAT. EMAT is described in U.S. Pat. No. 5,652,389 to Schaps et al.; U.S. Pat. No. 5,760,307 to Latimer et al.; U.S. Pat. No. 5,777,229 to Geier et al.; and U.S. Pat. No. 6,155,117 to Stevens et al., each of which is incorporated by reference as if fully set forth herein.

In some embodiments, an expandable tubular may be used in a wellbore. Expandable tubulars are described in U.S. Pat. No. 5,366,012 to Lohbeck, and U.S. Pat. No. 6,354,373 to Vercaemer et al., each of which is incorporated by reference as if fully set forth herein.

Heaters may be placed in wellbores to heat a formation during an in situ process. Examples of in situ processes utilizing downhole heaters are illustrated in U.S. Pat. No. 2,634,961 to Ljungstrom; U.S. Pat. No. 2,732,195 to Ljungstrom; U.S. Pat. No. 2,780,450 to Ljungstrom; U.S. Pat. No. 2,789,805 to Ljungstrom; U.S. Pat. No. 2,923,535 to Ljungstrom; and U.S. Pat. No. 4,886,118 to Van Meurs et al.; each of which is incorporated by reference as if fully set forth herein.

Application of heat to oil shale formations is described in U.S. Pat. No. 2,923,535 to Ljungstrom and U.S. Pat. No. 4,886,118 to Van Meurs et al. Heat may be applied to the oil shale formation to pyrolyze kerogen in the oil shale formation. The heat may also fracture the formation to increase permeability of the formation. The increased permeability may allow formation fluid to travel to a production well where the fluid is removed from the oil shale formation. In some processes disclosed by Ljungstrom, for example, an oxygen containing gaseous medium is introduced to a permeable stratum, preferably while still hot from a preheating step, to initiate combustion.

A heat source may be used to heat a subterranean formation. Electric heaters may be used to heat the subterranean formation by radiation and/or conduction. An electric heater may resistively heat an element. U.S. Pat. No. 2,548,360 to Germain, which is incorporated by reference as if fully set

forth herein, describes an electric heating element placed in a viscous oil in a wellbore. The heater element heats and thins the oil to allow the oil to be pumped from the wellbore. U.S. Pat. No. 4,716,960 to Eastlund et al., which is incorporated by reference as if fully set forth herein, describes electrically heating tubing of a petroleum well by passing a relatively low voltage current through the tubing to prevent formation of solids. U.S. Pat. No. 5,065,818 to Van Egmond, which is incorporated by reference as if fully set forth herein, describes an electric heating element that is cemented into a well borehole without a casing surrounding the heating element.

U.S. Pat. No. 6,023,554 to Vinegar et al., which is incorporated by reference as if fully set forth herein, describes an electric heating element that is positioned in a casing. The heating element generates radiant energy that heats the casing. A granular solid fill material may be placed between the casing and the formation. The casing may conductively heat the fill material, which in turn conductively heats the formation.

U.S. Pat. No. 4,570,715 to Van Meurs et al., which is incorporated by reference as if fully set forth herein, describes an electric heating element. The heating element has an electrically conductive core, a surrounding layer of insulating material, and a surrounding metallic sheath. The conductive core may have a relatively low resistance at high temperatures. The insulating material may have electrical resistance, compressive strength, and heat conductivity properties that are relatively high at high temperatures. The insulating layer may inhibit arcing from the core to the metallic sheath. The metallic sheath may have tensile strength and creep resistance properties that are relatively high at high temperatures.

U.S. Pat. No. 5,060,287 to Van Egmond, which is incorporated by reference as if fully set forth herein, describes an electrical heating element having a copper-nickel alloy core.

Obtaining permeability in an oil shale formation between injection and production wells tends to be difficult because oil shale is often substantially impermeable. Many methods have attempted to link injection and production wells. These methods include: hydraulic fracturing such as methods investigated by Dow Chemical and Laramie Energy Research Center; electrical fracturing by methods investigated by Laramie Energy Research Center; acid leaching of limestone cavities by methods investigated by Dow Chemical; steam injection into permeable nahcolite zones to dissolve the nahcolite by methods investigated by Shell Oil and Equity Oil; fracturing with chemical explosives by methods investigated by Talley Energy Systems; fracturing with nuclear explosives by methods investigated by Project Bronco; and combinations of these methods. Many of these methods, however, have relatively high operating costs and lack sufficient injection capacity.

Large deposits of heavy hydrocarbons (heavy oil and/or tar) contained in relatively permeable formations (for example in tar sands) are found in North America, South America, Africa, and Asia. Tar can be surface-mined and upgraded to lighter hydrocarbons such as crude oil, naphtha, kerosene, and/or gas oil. Surface milling processes may further separate the bitumen from sand. The separated bitumen may be converted to light hydrocarbons using conventional refinery methods. Mining and upgrading tar sand is usually substantially more expensive than producing lighter hydrocarbons from conventional oil reservoirs.

In situ production of hydrocarbons from tar sand may be accomplished by heating and/or injecting a gas into the formation. U.S. Pat. No. 5,211,230 to Ostapovich et al. and U.S. Pat. No. 5,339,897 to Leaute, which are incorporated by reference as if fully set forth herein, describe a horizontal production well located in an oil-bearing reservoir. A vertical conduit may be used to inject an oxidant gas into the reservoir for in situ combustion.

U.S. Pat. No. 2,780,450 to Ljungstrom describes heating bituminous geological formations in situ to convert or crack a liquid tar-like substance into oils and gases.

U.S. Pat. No. 4,597,441 to Ware et al., which is incorporated by reference as if fully set forth herein, describes contacting oil, heat, and hydrogen simultaneously in a reservoir. Hydrogenation may enhance recovery of oil from the reservoir.

U.S. Pat. No. 5,046,559 to Glandt and U.S. Pat. No. 5,060,726 to Glandt et al., which are incorporated by reference as if fully set forth herein, describe preheating a portion of a tar sand formation between an injector well and a producer well. Steam may be injected from the injector well into the formation to produce hydrocarbons at the producer well.

As outlined above, there has been a significant amount of effort to develop methods and systems to economically produce hydrocarbons, hydrogen, and/or other products from hydrocarbon containing formations. At present, however, there are still many hydrocarbon containing formations from which hydrocarbons, hydrogen, and/or other products cannot be economically produced. Thus, there is still a need for improved methods and systems for production of hydrocarbons, hydrogen, and/or other products from various hydrocarbon containing formations.

SUMMARY

Embodiments described herein generally relate to systems, methods, and heaters for treating a subsurface formation. Embodiments described herein also generally relate to heaters that have novel components therein. Such heaters can be obtained by using the systems and methods described herein.

In certain embodiments, the invention provides one or more systems, methods, and/or heaters. In some embodiments, the systems, methods, and/or heaters are used for treating a subsurface formation.

In certain embodiments, the invention provides a method for providing acidic gas to a subsurface formation, comprising: providing heat from one or more heaters to a portion of a subsurface formation; producing fluids from the formation using a heat treatment process, wherein the produced fluids comprise one or more acidic gases; and introducing at least a portion of one of the acidic gases into the formation, or into another formation, through one or more wellbores at a pressure below a lithostatic pressure of the formation in which the acidic gas is introduced.

In further embodiments, features from specific embodiments may be combined with features from other embodiments. For example, features from one embodiment may be combined with features from any of the other embodiments.

In further embodiments, treating a subsurface formation is performed using any of the methods, systems, or heaters described herein.

In further embodiments, additional features may be added to the specific embodiments described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the present invention may become apparent to those skilled in the art with the benefit of the following detailed description and upon reference to the accompanying drawings in which:

FIG. **1** depicts an illustration of stages of heating a hydrocarbon containing formation.

FIG. **2** shows a schematic view of an embodiment of a portion of an in situ heat treatment system for treating a hydrocarbon containing formation.

FIG. **3** depicts a schematic of an embodiment of a Kalina cycle for producing electricity.

FIG. **4** depicts a schematic of an embodiment of a Kalina cycle for producing electricity.

FIG. **5** depicts a schematic representation of an embodiment of a system for treating the mixture produced from an in situ heat treatment process.

FIG. **5**A depicts a schematic representation of an embodiment of a system for treating a liquid stream produced from an in situ heat treatment process.

FIG. **6** depicts a schematic representation of another embodiment of a system for treating a liquid stream produced from an in situ heat treatment process.

FIG. **7** depicts a schematic representation of an embodiment of a system for treating a liquid stream produced from an in situ heat treatment process.

FIG. **8** depicts a schematic representation of an embodiment of a system for forming and transporting tubing to a treatment area.

FIG. **9**A depicts an embodiment of a drilling string including cutting structures positioned along the drilling string.

FIG. **9**B depicts an embodiment of a drilling string including cutting structures positioned along the drilling string.

FIG. **9**C depicts an embodiment of a drilling string including cutting structures positioned along the drilling string.

FIG. **10** depicts an embodiment of a drill bit including upward cutting structures.

FIG. **11** depicts an embodiment of a tubular including cutting structures positioned in a wellbore.

FIG. **12** depicts a schematic drawing of an embodiment of a drilling system.

FIG. **13** depicts a schematic drawing of an embodiment of a drilling system for drilling into a hot formation.

FIG. **14** depicts a schematic drawing of an embodiment of a drilling system for drilling into a hot formation.

FIG. **15** depicts a schematic drawing of an embodiment of a drilling system for drilling into a hot formation.

FIG. **16** depicts an embodiment of a freeze well for a circulated liquid refrigeration system, wherein a cutaway view of the freeze well is represented below ground surface.

FIG. **17**A depicts an embodiment of a wellbore for introducing wax into a formation to form a wax grout barrier.

FIG. **17**B depicts a representation of a wellbore drilled to an intermediate depth in a formation.

FIG. **17**C depicts a representation of the wellbore drilled to the final depth in the formation.

FIG. **18** depicts an embodiment of a device for longitudinal welding of a tubular using ERW.

FIGS. **19**, **20**, and **21** depict cross-sectional representations of an embodiment of a temperature limited heater with an outer conductor having a ferromagnetic section and a non-ferromagnetic section.

FIGS. **22**, **23**, **24**, and **25** depict cross-sectional representations of an embodiment of a temperature limited heater with an outer conductor having a ferromagnetic section and a non-ferromagnetic section placed inside a sheath.

FIGS. **26**A and **26**B depict cross-sectional representations of an embodiment of a temperature limited heater.

FIGS. **27**A and **27**B depict cross-sectional representations of an embodiment of a temperature limited heater.

FIGS. **28**A and **28**B depict cross-sectional representations of an embodiment of a temperature limited heater.

FIGS. **29**A and **29**B depict cross-sectional representations of an embodiment of a temperature limited heater.

FIGS. **30**A and **30**B depict cross-sectional representations of an embodiment of a temperature limited heater.

FIG. **31** depicts a cross-sectional representation of an embodiment of a composite conductor with a support member.

FIG. **32** depicts a cross-sectional representation of an embodiment of a composite conductor with a support member separating the conductors.

FIG. **33** depicts a cross-sectional representation of an embodiment of a composite conductor surrounding a support member.

FIG. **34** depicts a cross-sectional representation of an embodiment of a composite conductor surrounding a conduit support member.

FIG. **35** depicts a cross-sectional representation of an embodiment of a conductor-in-conduit heat source.

FIG. **36** depicts a cross-sectional representation of an embodiment of a removable conductor-in-conduit heat source.

FIG. **37** depicts an embodiment of a temperature limited heater in which the support member provides a majority of the heat output below the Curie temperature of the ferromagnetic conductor.

FIGS. **38** and **39** depict embodiments of temperature limited heaters in which the jacket provides a majority of the heat output below the Curie temperature of the ferromagnetic conductor.

FIG. **40** depicts a high temperature embodiment of a temperature limited heater.

FIG. **41** depicts hanging stress versus outside diameter for the temperature limited heater shown in FIG. **37** with 347H as the support member.

FIG. **42** depicts hanging stress versus temperature for several materials and varying outside diameters of the temperature limited heater.

FIGS. **43**, **44**, **45**, and **46** depict examples of embodiments for temperature limited heaters that vary the materials and/or dimensions along the length of the heaters to provide desired operating properties.

FIGS. **47** and **48** depict examples of embodiments for temperature limited heaters that vary the diameter and/or materials of the support member along the length of the heaters to provide desired operating properties and sufficient mechanical properties.

FIGS. **49**A and **49**B depict cross-sectional representations of an embodiment of a temperature limited heater component used in an insulated conductor heater.

FIGS. **50**A and **50**B depict an embodiment of a system for installing heaters in a wellbore.

FIG. **50**C depicts an embodiment of an insulated conductor with the sheath shorted to the conductors.

FIG. **51** depicts a top view representation of three insulated conductors in a conduit.

FIG. **52** depicts an embodiment of three-phase wye transformer coupled to a plurality of heaters.

FIG. **53** depicts a side view representation of an end section of three insulated conductors in a conduit.

FIG. **54** depicts one alternative embodiment of a heater with three insulated cores in a conduit.

FIG. **55** depicts another alternative embodiment of a heater with three insulated conductors and an insulated return conductor in a conduit.

FIG. **56** depicts an embodiment of an insulated conductor heater in a conduit with molten metal.

FIG. **57** depicts an embodiment of a substantially horizontal insulated conductor heater in a conduit with molten metal.

FIG. **58** depicts an embodiment for coupling together sections of a long temperature limited heater.

FIG. **59** depicts an embodiment of a shield for orbital welding sections of a long temperature limited heater.

FIG. **60** depicts a schematic representation of an embodiment of a shut off circuit for an orbital welding machine.

FIG. **61** depicts an embodiment of a temperature limited heater with a low temperature ferromagnetic outer conductor.

FIG. **62** depicts an embodiment of a temperature limited conductor-in-conduit heater.

FIG. **63** depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater.

FIG. **64** depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater.

FIG. **65** depicts a cross-sectional view of an embodiment of a conductor-in-conduit temperature limited heater.

FIG. **66** depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater with an insulated conductor.

FIG. **67** depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater with an insulated conductor.

FIG. **68** depicts an embodiment of a three-phase temperature limited heater with a portion shown in cross section.

FIG. **69** depicts an embodiment of temperature limited heaters coupled together in a three-phase configuration.

FIG. **70** depicts an embodiment of three heaters coupled in a three-phase configuration.

FIG. **71** depicts a side view representation of an embodiment of a substantially u-shaped three-phase heater.

FIG. **72** depicts a top view representation of an embodiment of a plurality of triads of three-phase heaters in a formation.

FIG. **73** depicts a top view representation of the embodiment depicted in FIG. **72** with production wells.

FIG. **74** depicts a top view representation of an embodiment of a plurality of triads of three-phase heaters in a hexagonal pattern.

FIG. **75** depicts a top view representation of an embodiment of a hexagon from FIG. **74**.

FIG. **76** depicts an embodiment of triads of heaters coupled to a horizontal bus bar.

FIGS. **77** and **78** depict embodiments for coupling contacting elements of three legs of a heater.

FIG. **79** depicts an embodiment of a container with an initiator for melting the coupling material.

FIG. **80** depicts an embodiment of a container for coupling contacting elements with bulbs on the contacting elements.

FIG. **81** depicts an alternative embodiment of a container.

FIG. **82** depicts an alternative embodiment for coupling contacting elements of three legs of a heater.

FIG. **83** depicts a side-view representation of an embodiment for coupling contacting elements using temperature limited heating elements.

FIG. **84** depicts a side view representation of an alternative embodiment for coupling contacting elements using temperature limited heating elements.

FIG. **85** depicts a side view representation of another alternative embodiment for coupling contacting elements using temperature limited heating elements.

FIG. **86** depicts a side view representation of an alternative embodiment for coupling contacting elements of three legs of a heater.

FIG. **87** depicts a top view representation of the alternative embodiment for coupling contacting elements of three legs of a heater depicted in FIG. **86**.

FIG. **88** depicts an embodiment of a contacting element with a brush contactor.

FIG. **89** depicts an embodiment for coupling contacting elements with brush contactors.

FIG. **90** depicts an embodiment of two temperature limited heaters coupled together in a single contacting section.

FIG. **91** depicts an embodiment of two temperature limited heaters with legs coupled in a contacting section.

FIG. **92** depicts an embodiment of three diads coupled to a three-phase transformer.

FIG. **93** depicts an embodiment of groups of diads in a hexagonal pattern.

FIG. **94** depicts an embodiment of diads in a triangular pattern.

FIG. **95** depicts a side-view representation of an embodiment of substantially u-shaped heaters.

FIG. **96** depicts a representational top view of an embodiment of a surface pattern of heaters depicted in FIG. **95**.

FIG. **97** depicts a cross-sectional representation of substantially u-shaped heaters in a hydrocarbon layer.

FIG. **98** depicts a side view representation of an embodiment of substantially vertical heaters coupled to a substantially horizontal wellbore.

FIG. **99** depicts an embodiment of pluralities of substantially horizontal heaters coupled to bus bars in a hydrocarbon layer.

FIG. **100** depicts an alternative embodiment of pluralities of substantially horizontal heaters coupled to bus bars in a hydrocarbon layer.

FIG. **101** depicts an enlarged view of an embodiment of a bus bar coupled to heater with connectors.

FIG. **102** depicts an enlarged view of an embodiment of a bus bar coupled to a heater with connectors and centralizers.

FIG. **103** depicts a cross-section representation of a connector coupling to a bus bar.

FIG. **104** depicts a three-dimensional representation of a connector coupling to a bus bar.

FIG. **105** depicts an embodiment of a substantially u-shaped heater that electrically isolates itself from the formation.

FIG. **106** depicts an embodiment of a single-ended, substantially horizontal heater that electrically isolates itself from the formation.

FIG. **107** depicts an embodiment of a single-ended, substantially horizontal heater that electrically isolates itself from the formation using an insulated conductor as the center conductor.

FIG. **108** depicts an embodiment of a single-ended, substantially horizontal insulated conductor heater that electrically isolates itself from the formation.

FIGS. **109**A and **109**B depict cross-sectional representations of an embodiment of an insulated conductor that is electrically isolated on the outside of the jacket.

FIGS. **110**A and **110**B depict an embodiment for using substantially u-shaped wellbores to time sequence heat two layers in a hydrocarbon containing formation.

FIGS. **111**A and **111**B depict an embodiment for using horizontal wellbores to time sequence heat two layers in a hydrocarbon containing formation.

FIG. **112** depicts an embodiment of a wellhead.

FIG. **113** depicts an embodiment of a dual continuous tubular suspension mechanism including threads cut on the dual continuous tubular over a built up portion.

FIG. **114** depicts an embodiment of a dual continuous tubular suspension mechanism including a built up portion on a continuous tubular.

FIGS. **115**A-B depict embodiments of dual continuous tubular suspension mechanisms including slip mechanisms.

FIG. **116** depicts an embodiment of a dual continuous tubular suspension mechanism including a slip mechanism and a screw lock system.

FIG. **117** depicts an embodiment of a dual continuous tubular suspension mechanism including a slip mechanism and a screw lock system with counter sunk bolts.

FIG. **118** depicts an embodiment of a pass-through fitting used to suspend tubulars.

FIG. **119** depicts an embodiment of a dual slip mechanism for inhibiting movement of tubulars.

FIG. **120**A-B depict embodiments of split suspension mechanisms and split slip assemblies for hanging dual continuous tubulars.

FIG. **121** depicts an embodiment of a dual slip mechanism for inhibiting movement of tubulars with a reverse configuration.

FIG. **122** depicts an embodiment of a two-part dual slip mechanism for inhibiting movement of tubulars.

FIG. **123** depicts an embodiment of a two-part dual slip mechanism for inhibiting movement of tubulars with separate locks.

FIG. **124** depicts an embodiment of a dual slip mechanism locking plate for inhibiting movement of tubulars.

FIG. **125** depicts an embodiment of a segmented dual slip mechanism with locking screws for inhibiting movement of tubulars.

FIG. **126** depicts a top view representation of the embodiment of a transformer showing the windings and core of the transformer.

FIG. **127** depicts a side view representation of the embodiment of the transformer showing the windings, the core, and the power leads.

FIG. **128** depicts an embodiment of a transformer in a wellbore.

FIG. **129** depicts an embodiment of a transformer in a wellbore with heat pipes.

FIG. **130** depicts a side view representation of an embodiment for producing mobilized fluids from a tar sands formation with a relatively thin hydrocarbon layer.

FIG. **131** depicts a side view representation of an embodiment for producing mobilized fluids from a tar sands formation with a hydrocarbon layer that is thicker than the hydrocarbon layer depicted in FIG. **130**.

FIG. **132** depicts a side view representation of an embodiment for producing mobilized fluids from a tar sands formation with a hydrocarbon layer that is thicker than the hydrocarbon layer depicted in FIG. **131**.

FIG. **133** depicts a side view representation of an embodiment for producing mobilized fluids from a tar sands formation with a hydrocarbon layer that has a shale break.

FIG. **134** depicts a top view representation of an embodiment for preheating using heaters for the drive process.

FIG. **135** depicts a side view representation of an embodiment for preheating using heaters for the drive process.

FIG. **136** depicts a representation of an embodiment for producing hydrocarbons from a tar sands formation.

FIG. **137** depicts a representation of an embodiment for producing hydrocarbons from multiple layers in a tar sands formation.

FIG. **138** depicts an embodiment for heating and producing from a formation with a temperature limited heater in a production wellbore.

FIG. **139** depicts an embodiment for heating and producing from a formation with a temperature limited heater and a production wellbore.

FIG. **140** depicts an embodiment of a heating/production assembly that may be located in a wellbore for gas lifting.

FIG. **141** depicts an embodiment of a heating/production assembly that may be located in a wellbore for gas lifting.

FIG. **142** depicts another embodiment of a heating/production assembly that may be located in a wellbore for gas lifting.

FIG. **143** depicts an embodiment of a production conduit and a heater.

FIG. **144** depicts an embodiment for treating a formation.

FIG. **145** depicts an embodiment of a heater well with selective heating.

FIG. **146** depicts a schematic representation of an embodiment of a downhole oxidizer assembly.

FIG. **147** depicts a cross-sectional representation of an embodiment of a downhole oxidizer including an insulating sleeve.

FIG. **148** depicts a cross-sectional representation of an embodiment of a downhole oxidizer with a gas cooled insulating sleeve.

FIG. **149** depicts a perspective view of an embodiment of a portion of an oxidizer of a downhole oxidizer assembly.

FIG. **150** depicts a cross-sectional representation of an embodiment of an oxidizer shield.

FIG. **151** depicts a cross-sectional representation of an embodiment of an oxidizer shield.

FIG. **152** depicts a cross-sectional representation of an embodiment of an oxidizer shield.

FIG. **153** depicts a cross-sectional representation of an embodiment of an oxidizer shield.

FIG. **154** depicts a cross-sectional representation of an embodiment of an oxidizer shield with multiple flame stabilizers.

FIG. **155** depicts a cross-sectional representation of an embodiment of an oxidizer shield.

FIG. **156** depicts a perspective representation of an embodiment of a sectioned oxidizer.

FIG. **157** depicts a perspective representation of an embodiment of a sectioned oxidizer.

FIG. **158** depicts a perspective representation of an embodiment of a sectioned oxidizer.

FIG. **159** depicts a perspective representation of an embodiment of a portion of an oxidizer of a downhole oxidizer assembly with louvered openings in the shield.

FIG. **160** depicts a cross-sectional representation of a portion of a shield with a louvered opening.

FIG. **161** depicts a cross-sectional of an embodiment of a first oxidizer of an oxidizer assembly.

FIG. **162** depicts a cross-sectional representation of an embodiment of a catalytic burner.

FIG. **163** depicts a cross-sectional representation of an embodiment of a catalytic burner with an igniter.

FIG. **164** depicts a schematic representation of an embodiment of a heater that uses coal as fuel.

FIG. **165** depicts a schematic representation of an embodiment of a heater that uses coal as fuel.

FIG. **166** depicts a schematic representation of a closed loop circulation system for heating a portion of a formation.

FIG. **167** depicts a plan view of wellbore entries and exits from a portion of a formation to be heated using a closed loop circulation system.

FIG. **168** depicts a schematic representation of an embodiment of an in situ heat treatment system that uses a nuclear reactor.

FIG. **169** depicts an elevational view of an in situ heat treatment system using pebble bed reactors.

FIG. **170** depicts a schematic of an embodiment of a U-shaped nuclear heater assembly.

FIG. **171** depicts a schematic of an embodiment of a nuclear heater assembly.

FIG. **172** depicts a schematic an embodiment of a middle portion of a nuclear heater assembly that includes pebble reactors and nuclear moderators.

FIG. **173** depicts a schematic of an embodiment of an end portion of a nuclear heater assembly that includes pebble reactors and nuclear moderators.

FIG. **174** depicts a schematic of an embodiment of a nuclear heater assembly that includes pebble reactors and spacers.

FIG. **175** depicts a schematic an embodiment of a nuclear heater assembly that includes stacked pebble reactors.

FIG. **176** depicts a schematic an embodiment of an embodiment of nuclear heater assembly.

FIG. **177** depicts a side view representation of an embodiment of a system for heating the formation that can use a closed loop circulation system and/or electrical heating.

FIG. **178** depicts a side view representation of an embodiment for an in situ staged heating and producing process for treating a tar sands formation.

FIG. **179** depicts a top view of a rectangular checkerboard pattern embodiment for the in situ staged heating and production process.

FIG. **180** depicts a top view of a ring pattern embodiment for the in situ staged heating and production process.

FIG. **181** depicts a top view of a checkerboard ring pattern embodiment for the in situ staged heating and production process.

FIG. **182** depicts a top view an embodiment of a plurality of rectangular checkerboard patterns in a treatment area for the in situ staged heating and production process.

FIG. **183** depicts a side view representations of embodiments for producing mobilized fluids from a hydrocarbon formation.

FIG. **184** depicts a schematic representation of a system for inhibiting migration of formation fluid from a treatment area.

FIG. **185** depicts an embodiment of a windmill for generating electricity for subsurface heaters.

FIG. **186** depicts an embodiment of a solution mining well.

FIG. **187** depicts a representation of a portion of a solution mining well.

FIG. **188** depicts a representation of a portion of a solution mining well.

FIG. **189** depicts an elevational view of a well pattern for solution mining and/or an in situ heat treatment process.

FIG. **190** depicts a representation of wells of an in situ heating treatment process for solution mining and producing hydrocarbons from a formation.

FIG. **191** depicts an embodiment for solution mining a formation.

FIG. **192** depicts an embodiment of a formation with nahcolite layers in the formation before solution mining nahcolite from the formation.

FIG. **193** depicts the formation of FIG. **192** after the nahcolite has been solution mined.

FIG. **194** depicts an embodiment of two injection wells interconnected by a zone that has been solution mined to remove nahcolite from the zone.

FIG. **195** depicts an embodiment for heating a formation with dawsonite in the formation.

FIG. **196** depicts a representation of an embodiment for solution mining with a steam and electricity cogeneration facility.

FIG. **197** depicts an embodiment of treating a hydrocarbon containing formation with a combustion front.

FIG. **198** depicts an embodiment of cross-sectional view of treating a hydrocarbon containing formation with a combustion front.

FIG. **199** depicts a schematic representation of a system for producing formation fluid and introducing sour gas into a subsurface formation.

FIG. **200** depicts electrical resistance versus temperature at various applied electrical currents for a 446 stainless steel rod.

FIG. **201** shows resistance profiles as a function of temperature at various applied electrical currents for a copper rod contained in a conduit of Sumitomo HCM12A.

FIG. **202** depicts electrical resistance versus temperature at various applied electrical currents for a temperature limited heater.

FIG. **203** depicts raw data for a temperature limited heater.

FIG. **204** depicts electrical resistance versus temperature at various applied electrical currents for a temperature limited heater.

FIG. **205** depicts power versus temperature at various applied electrical currents for a temperature limited heater.

FIG. **206** depicts electrical resistance versus temperature at various applied electrical currents for a temperature limited heater.

FIG. **207** depicts data of electrical resistance versus temperature for a solid 2.54 cm diameter, 1.8 m long 410 stainless steel rod at various applied electrical currents.

FIG. **208** depicts data of electrical resistance versus temperature for a composite 1.9 cm, 1.8 m long alloy 42-6 rod with a copper core (the rod has an outside diameter to copper diameter ratio of 2:1) at various applied electrical currents.

FIG. **209** depicts data of power output versus temperature for a composite 1.9 cm, 1.8 m long alloy 42-6 rod with a copper core (the rod has an outside diameter to copper diameter ratio of 2:1) at various applied electrical currents.

FIG. **210** depicts data for values of skin depth versus temperature for a solid 2.54 cm diameter, 1.8 m long 410 stainless steel rod at various applied AC electrical currents.

FIG. **211** depicts temperature versus time for a temperature limited heater.

FIG. **212** depicts temperature versus log time data for a 2.5 cm solid 410 stainless steel rod and a 2.5 cm solid 304 stainless steel rod.

FIG. **213** depicts experimentally measured resistance versus temperature at several currents for a temperature limited heater with a copper core, a carbon steel ferromagnetic conductor, and a stainless steel 347H stainless steel support member.

FIG. **214** depicts experimentally measured resistance versus temperature at several currents for a temperature limited heater with a copper core, an iron-cobalt ferromagnetic conductor, and a stainless steel 347H stainless steel support member.

FIG. **215** depicts experimentally measured power factor versus temperature at two AC currents for a temperature limited heater with a copper core, a carbon steel ferromagnetic conductor, and a 347H stainless steel support member.

FIG. **216** depicts experimentally measured turndown ratio versus maximum power delivered for a temperature limited heater with a copper core, a carbon steel ferromagnetic conductor, and a 347H stainless steel support member.

FIG. **217** depicts examples of relative magnetic permeability versus magnetic field for both the found correlations and raw data for carbon steel.

FIG. **218** shows the resulting plots of skin depth versus magnetic field for four temperatures and 400 A current.

FIG. **219** shows a comparison between the experimental and numerical (calculated) results for currents of 300 A, 400 A, and 500 A.

FIG. **220** shows the AC resistance per foot of the heater element as a function of skin depth at 1100° F. calculated from the theoretical model.

FIG. **221** depicts the power generated per unit length in each heater component versus skin depth for a temperature limited heater.

FIGS. **222**A-C compare the results of theoretical calculations with experimental data for resistance versus temperature in a temperature limited heater.

FIG. **223** displays temperature of the center conductor of a conductor-in-conduit heater as a function of formation depth for a Curie temperature heater with a turndown ratio of 2:1.

FIG. **224** displays heater heat flux through a formation for a turndown ratio of 2:1 along with the oil shale richness profile.

FIG. **225** displays heater temperature as a function of formation depth for a turndown ratio of 3:1.

FIG. **226** displays heater heat flux through a formation for a turndown ratio of 3:1 along with the oil shale richness profile.

FIG. **227** displays heater temperature as a function of formation depth for a turndown ratio of 4:1.

FIG. **228** depicts heater temperature versus depth for heaters used in a simulation for heating oil shale.

FIG. **229** depicts heater heat flux versus time for heaters used in a simulation for heating oil shale.

FIG. **230** depicts accumulated heat input versus time in a simulation for heating oil shale.

FIG. **231** depicts a plot of heater power versus core diameter.

FIG. **232** depicts power, resistance, and current versus temperature for a heater with core diameters of 0.105".

FIG. **233** depicts actual heater power versus time during the simulation for three different heater designs.

FIG. **234** depicts heater element temperature (core temperature) and average formation temperature versus time for three different heater designs.

FIG. **235** depicts cumulative gas production and cumulative oil production versus time found from a STARS simulation using the heaters and heater pattern depicted in FIGS. **70** and **72**.

FIG. **236** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for iron alloy TC3.

FIG. **237** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for iron alloy FM-4.

FIG. **238** depicts the Curie temperature and phase transformation temperature range for several iron alloys.

FIG. **239** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt and 0.4% by weight manganese.

FIG. **240** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt, 0.4% by weight manganese, and 0.01% carbon.

FIG. **241** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt, 0.4% by weight manganese, and 0.085% carbon.

FIG. **242** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt, 0.4% by weight manganese, 0.085% carbon, and 0.4% titanium.

FIG. **243** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-chromium alloy having 12.25% by weight chromium, 0.1% by weight carbon, 0.5% by weight manganese, and 0.5% by weight silicon.

FIG. **244** depicts experimental calculation of weight percentages of phases versus weight percentages of chromium in an alloy.

FIG. **245** depicts experimental calculation of weight percentages of phases versus weight percentages of silicon in an alloy.

FIG. **246** depicts experimental calculation of weight percentages of phases versus weight percentages of tungsten in an alloy.

FIG. **247** depicts experimental calculation of weight percentages of phases versus weight percentages of niobium in an alloy.

FIG. **248** depicts experimental calculation of weight percentages of phases versus weight percentages of carbon in an alloy.

FIG. **249** depicts experimental calculation of weight percentages of phases versus weight percentages of nitrogen in an alloy.

FIG. **250** depicts experimental calculation of weight percentages of phases versus weight percentages of titanium in an alloy.

FIG. **251** depicts experimental calculation of weight percentages of phases versus weight percentages of copper in an alloy.

FIG. **252** depicts experimental calculation of weight percentages of phases versus weight percentages of manganese in an alloy.

FIG. **253** depicts experimental calculation of weight percentages of phases versus weight percentages of nickel in an alloy.

FIG. **254** depicts experimental calculation of weight percentages of phases versus weight percentages of molybdenum in an alloy.

FIG. **255**A depicts yield strengths and ultimate tensile strengths for different metals.

FIG. **255**B depicts yield strengths for different metals.

FIG. **255**C depicts ultimate tensile strengths for different metals.

FIG. **255**D depicts yield strengths for different metals.

FIG. **255**E depicts ultimate tensile strengths for different metals.

FIG. **256** depicts projected corrosion rates over a one-year period for several metals in a sulfidation atmosphere.

FIG. **257** depicts projected corrosion rates over a one-year period for 410 stainless steel and 410 stainless steel containing various amounts of cobalt in a sulfidation atmosphere.

FIG. **258** depicts an example of richness of an oil shale formation (gal/ton) versus depth (ft).

FIG. **259** depicts resistance per foot (mΩ/ft) versus temperature (° F.) profile of the first heater example.

FIG. **260** depicts average temperature in the formation (° F.) versus time (days) as determined by the simulation for the first example.

FIG. **261** depicts resistance per foot (mΩ/ft) versus temperature (° F.) for the second heater example.

FIG. **262** depicts average temperature in the formation (° F.) versus time (days) as determined by the simulation for the second example.

FIG. **263** depicts net heater energy input (Btu) versus time (days) for the second example.

FIG. **264** depicts power injection per foot (W/ft) versus time (days) for the second example.

FIG. **265** depicts resistance per foot (mΩ/ft) versus temperature (° F.) for the third heater example.

FIG. **266** depicts average temperature in the formation (° F.) versus time (days) as determined by the simulation for the third example.

FIG. **267** depicts cumulative energy injection (Btu) versus time (days) for each of the three heater examples.

FIG. **268** depicts average temperature (° F.) versus time (days) for the third heater example with a 30 foot spacing between heaters in the formation as determined by the simulation.

FIG. **269** depicts average temperature (° F.) versus time (days) for the fourth heater example using the heater configuration and pattern depicted in FIGS. **70** and **72** as determined by the simulation.

FIG. **270** depicts a temperature profile in the formation after 360 days using the STARS simulation.

FIG. **271** depicts an oil saturation profile in the formation after 360 days using the STARS simulation.

FIG. **272** depicts the oil saturation profile in the formation after 1095 days using the STARS simulation.

FIG. **273** depicts the oil saturation profile in the formation after 1470 days using the STARS simulation.

FIG. **274** depicts the oil saturation profile in the formation after 1826 days using the STARS simulation.

FIG. **275** depicts the temperature profile in the formation after 1826 days using the STARS simulation.

FIG. **276** depicts oil production rate and gas production rate versus time.

FIG. **277** depicts weight percentage of original bitumen in place (OBIP) (left axis) and volume percentage of OBIP (right axis) versus temperature (° C.).

FIG. **278** depicts bitumen conversion percentage (weight percentage of (OBIP)) (left axis) and oil, gas, and coke weight percentage (as a weight percentage of OBIP) (right axis) versus temperature (° C.).

FIG. **279** depicts API gravity (°) (left axis) of produced fluids, blow down production, and oil left in place along with pressure (psig) (right axis) versus temperature (° C.).

FIG. **280**A-D depict gas-to-oil ratios (GOR) in thousand cubic feet per barrel ((Mcf/bbl) (y-axis) for versus temperature (° C.) (x-axis) for different types of gas at a low temperature blow down (about 277° C.) and a high temperature blow down (at about 290° C.).

FIG. **281** depicts coke yield (weight percentage) (y-axis) versus temperature (° C.) (x-axis).

FIG. **282**A-D depict assessed hydrocarbon isomer shifts in fluids produced from the experimental cells as a function of temperature and bitumen conversion.

FIG. **283** depicts weight percentage (Wt %) (y-axis) of saturates from SARA analysis of the produced fluids versus temperature (° C.) (x-axis).

FIG. **284** depicts weight percentage (Wt %) (y-axis) of n-C_7 of the produced fluids versus temperature (° C.) (x-axis).

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and may herein be described in detail. The drawings may not be to scale. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

DETAILED DESCRIPTION

The following description generally relates to systems and methods for treating hydrocarbons in the formations. Such formations may be treated to yield hydrocarbon products, hydrogen, and other products.

"Alternating current (AC)" refers to a time-varying current that reverses direction substantially sinusoidally. AC produces skin effect electricity flow in a ferromagnetic conductor.

"API gravity" refers to API gravity at 15.5° C. (60° F.). API gravity is as determined by ASTM Method D6822 or ASTM Method D1298.

"ASTM" refers to American Standard Testing and Materials.

In the context of reduced heat output heating systems, apparatus, and methods, the term "automatically" means such systems, apparatus, and methods function in a certain way without the use of external control (for example, external controllers such as a controller with a temperature sensor and a feedback loop, PID controller, or predictive controller).

"Bare metal" and "exposed metal" refer to metals of elongated members that do not include a layer of electrical insulation, such as mineral insulation, that is designed to provide electrical insulation for the metal throughout an operating temperature range of the elongated member. Bare metal and exposed metal may encompass a metal that includes a corrosion inhibiter such as a naturally occurring oxidation layer, an applied oxidation layer, and/or a film. Bare metal and exposed metal include metals with polymeric or other types of electrical insulation that cannot retain electrical insulating properties at typical operating temperature of the elongated member. Such material may be placed on the metal and may be thermally degraded during use of the heater.

Boiling range distributions for the formation fluid and liquid streams described herein are as determined by ASTM Method D5307 or ASTM Method D2887. Content of hydrocarbon components in weight percent for paraffins, iso-paraffins, olefins, naphthenes and aromatics in the liquid streams is as determined by ASTM Method D6730. Content of aromatics in volume percent is as determined by ASTM Method D1319. Hydrogen Content in hydrocarbons in weight percent is as determined by ASTM Method D3343.

"Carbon number" refers to the number of carbon atoms in a molecule. A hydrocarbon fluid may include various hydrocarbons with different carbon numbers. The hydrocarbon fluid may be described by a carbon number distribution. Carbon numbers and/or carbon number distributions may be determined by true boiling point distribution and/or gas-liquid chromatography.

"Cenospheres" refers to hollow particulate that are formed in thermal processes at high temperatures when molten components are blown up like balloons by the volatilization of organic components.

"Chemically stability" refers to the ability of a formation fluid to be transported without components in the formation fluid reacting to form polymers and/or compositions that plug pipelines, valves, and/or vessels.

"Clogging" refers to impeding and/or inhibiting flow of one or more compositions through a process vessel or a conduit.

"Column X element" or "Column X elements" refer to one or more elements of Column X of the Periodic Table, and/or one or more compounds of one or more elements of Column X of the Periodic Table, in which X corresponds to a column number (for example, 13-18) of the Periodic Table. For example, "Column 15 elements" refer to elements from Column 15 of the Periodic Table and/or compounds of one or more elements from Column 15 of the Periodic Table.

"Column X metal" or "Column X metals" refer to one or more metals of Column X of the Periodic Table and/or one or more compounds of one or more metals of Column X of the Periodic Table, in which X corresponds to a column number (for example, 1-12) of the Periodic Table. For example, "Column 6 metals" refer to metals from Column 6 of the Periodic Table and/or compounds of one or more metals from Column 6 of the Periodic Table.

"Condensable hydrocarbons" are hydrocarbons that condense at 25° C. and one atmosphere absolute pressure. Condensable hydrocarbons may include a mixture of hydrocarbons having carbon numbers greater than 4. "Non-condensable hydrocarbons" are hydrocarbons that do not condense at 25° C. and one atmosphere absolute pressure. Non-condensable hydrocarbons may include hydrocarbons having carbon numbers less than 5.

"Coring" is a process that generally includes drilling a hole into a formation and removing a substantially solid mass of the formation from the hole.

"Cracking" refers to a process involving decomposition and molecular recombination of organic compounds to produce a greater number of molecules than were initially present. In cracking, a series of reactions take place accompanied by a transfer of hydrogen atoms between molecules. For example, naphtha may undergo a thermal cracking reaction to form ethene and H_2.

"Curie temperature" is the temperature above which a ferromagnetic material loses all of its ferromagnetic properties. In addition to losing all of its ferromagnetic properties above the Curie temperature, the ferromagnetic material begins to lose its ferromagnetic properties when an increasing electrical current is passed through the ferromagnetic material.

"Cycle oil" refers to a mixture of light cycle oil and heavy cycle oil. "Light cycle oil" refers to hydrocarbons having a boiling range distribution between 430° F. (221° C.) and 650° F. (343° C.) that are produced from a fluidized catalytic cracking system. Light cycle oil content is determined by ASTM Method D5307. "Heavy cycle oil" refers to hydrocarbons having a boiling range distribution between 650° F. (343° C.) and 800° F. (427° C.) that are produced from a fluidized catalytic cracking system. Heavy cycle oil content is determined by ASTM Method D5307.

"Diad" refers to a group of two items (for example, heaters, wellbores, or other objects) coupled together.

"Diesel" refers to hydrocarbons with a boiling range distribution between 260° C. and 343° C. (500-650° F.) at 0.101 MPa. Diesel content is determined by ASTM Method D2887.

"Enriched air" refers to air having a larger mole fraction of oxygen than air in the atmosphere. Air is typically enriched to increase combustion-supporting ability of the air.

"Fluid pressure" is a pressure generated by a fluid in a formation. "Lithostatic pressure" (sometimes referred to as "lithostatic stress") is a pressure in a formation equal to a weight per unit area of an overlying rock mass. "Hydrostatic pressure" is a pressure in a formation exerted by a column of water.

A "formation" includes one or more hydrocarbon containing layers, one or more non-hydrocarbon layers, an overburden, and/or an underburden. "Hydrocarbon layers" refer to layers in the formation that contain hydrocarbons. The hydrocarbon layers may contain non-hydrocarbon material and hydrocarbon material. The "overburden" and/or the "underburden" include one or more different types of impermeable materials. For example, the overburden and/or underburden may include rock, shale, mudstone, or wet/tight carbonate. In some embodiments of in situ heat treatment processes, the overburden and/or the underburden may include a hydrocarbon containing layer or hydrocarbon containing layers that are relatively impermeable and are not subjected to temperatures during in situ heat treatment processing that result in significant characteristic changes of the hydrocarbon containing layers of the overburden and/or the underburden. For example, the underburden may contain shale or mudstone, but the underburden is not allowed to heat to pyrolysis temperatures during the in situ heat treatment process. In some cases, the overburden and/or the underburden may be somewhat permeable.

"Formation fluids" refer to fluids present in a formation and may include pyrolyzation fluid, synthesis gas, mobilized hydrocarbon, and water (steam). Formation fluids may include hydrocarbon fluids as well as non-hydrocarbon fluids. The term "mobilized fluid" refers to fluids in a hydrocarbon containing formation that are able to flow as a result of thermal treatment of the formation. "Produced fluids" refer to fluids removed from the formation.

"Freezing point" of a hydrocarbon liquid refers to the temperature below which solid hydrocarbon crystals may form in the liquid. Freezing point is as determined by ASTM Method D5901.

"Gasoline hydrocarbons" refer to hydrocarbons having a boiling point range from 32° C. (90° F.) to about 204° C. (400° F.). Gasoline hydrocarbons include, but are not limited to, straight run gasoline, naphtha, fluidized or thermally catalytically cracked gasoline, VB gasoline, and coker gasoline. Gasoline hydrocarbons content is determined by ASTM Method D2887.

"Heat of Combustion" refers to an estimation of the net heat of combustion of a liquid. Heat of combustion is as determined by ASTM Method D3338.

A "heat source" is any system for providing heat to at least a portion of a formation substantially by conductive and/or radiative heat transfer. For example, a heat source may include electric heaters such as an insulated conductor, an elongated member, and/or a conductor disposed in a conduit. A heat source may also include systems that generate heat by burning a fuel external to or in a formation. The systems may be surface burners, downhole gas burners, flameless distributed combustors, and natural distributed combustors. In some embodiments, heat provided to or generated in one or more heat sources may be supplied by other sources of energy. The other sources of energy may directly heat a formation, or the energy may be applied to a transfer medium that directly or indirectly heats the formation. It is to be understood that one or more heat sources that are applying heat to a formation may use different sources of energy. Thus, for example, for a given formation some heat sources may supply heat from electric resistance heaters, some heat sources may provide heat from combustion, and some heat sources may provide heat from one or more other energy sources (for example, chemical reactions, solar energy, wind energy, biomass, or other sources of renewable energy). A chemical reaction may include an exothermic reaction (for example, an oxidation reaction). A heat source may also include a heater that provides heat to a zone proximate and/or surrounding a heating location such as a heater well.

A "heater" is any system or heat source for generating heat in a well or a near wellbore region. Heaters may be, but are not limited to, electric heaters, burners, combustors that react with material in or produced from a formation, and/or combinations thereof.

"Heavy hydrocarbons" are viscous hydrocarbon fluids. Heavy hydrocarbons may include highly viscous hydrocarbon fluids such as heavy oil, tar, and/or asphalt. Heavy hydrocarbons may include carbon and hydrogen, as well as smaller concentrations of sulfur, oxygen, and nitrogen. Additional elements may also be present in heavy hydrocarbons in trace amounts. Heavy hydrocarbons may be classified by API gravity. Heavy hydrocarbons generally have an API gravity below about 20°. Heavy oil, for example, generally has an API gravity of about 10-20°, whereas tar generally has an API gravity below about 10°. The viscosity of heavy hydrocarbons is generally greater than about 100 centipoise at 15° C. Heavy hydrocarbons may include aromatics or other complex ring hydrocarbons.

Heavy hydrocarbons may be found in a relatively permeable formation. The relatively permeable formation may include heavy hydrocarbons entrained in, for example, sand or carbonate. "Relatively permeable" is defined, with respect to formations or portions thereof, as an average permeability of 10 millidarcy or more (for example, 10 or 100 millidarcy). "Relatively low permeability" is defined, with respect to formations or portions thereof, as an average permeability of less than about 10 millidarcy. One darcy is equal to about 0.99 square micrometers. An impermeable layer generally has a permeability of less than about 0.1 millidarcy.

Certain types of formations that include heavy hydrocarbons may also be, but are not limited to, natural mineral waxes, or natural asphaltites. "Natural mineral waxes" typically occur in substantially tubular veins that may be several meters wide, several kilometers long, and hundreds of meters deep. "Natural asphaltites" include solid hydrocarbons of an aromatic composition and typically occur in large veins. In situ recovery of hydrocarbons from formations such as natural mineral waxes and natural asphaltites may include melting to form liquid hydrocarbons and/or solution mining of hydrocarbons from the formations.

"Hydrocarbons" are generally defined as molecules formed primarily by carbon and hydrogen atoms. Hydrocarbons may also include other elements such as, but not limited to, halogens, metallic elements, nitrogen, oxygen, and/or sulfur. Hydrocarbons may be, but are not limited to, kerogen, bitumen, pyrobitumen, oils, natural mineral waxes, and asphaltites. Hydrocarbons may be located in or adjacent to mineral matrices in the earth. Matrices may include, but are not limited to, sedimentary rock, sands, silicilytes, carbonates, diatomites, and other porous media. "Hydrocarbon fluids" are fluids that include hydrocarbons. Hydrocarbon fluids may include, entrain, or be entrained in non-hydrocarbon fluids such as hydrogen, nitrogen, carbon monoxide, carbon dioxide, hydrogen sulfide, water, and ammonia.

An "in situ conversion process" refers to a process of heating a hydrocarbon containing formation from heat sources to raise the temperature of at least a portion of the formation above a pyrolysis temperature so that pyrolyzation fluid is produced in the formation.

An "in situ heat treatment process" refers to a process of heating a hydrocarbon containing formation with heat sources to raise the temperature of at least a portion of the formation above a temperature that results in mobilized fluid, visbreaking, and/or pyrolysis of hydrocarbon containing material so that mobilized fluids, visbroken fluids, and/or pyrolyzation fluids are produced in the formation.

"Insulated conductor" refers to any elongated material that is able to conduct electricity and that is covered, in whole or in part, by an electrically insulating material.

"Karst" is a subsurface shaped by the dissolution of a soluble layer or layers of bedrock, usually carbonate rock such as limestone or dolomite. The dissolution may be caused by meteoric or acidic water. The Grosmont formation in Alberta, Canada is an example of a karst (or "karsted") carbonate formation.

"Kerogen" is a solid, insoluble hydrocarbon that has been converted by natural degradation and that principally contains carbon, hydrogen, nitrogen, oxygen, and sulfur. Coal and oil shale are typical examples of materials that contain kerogen. "Bitumen" is a non-crystalline solid or viscous hydrocarbon material that is substantially soluble in carbon disulfide. "Oil" is a fluid containing a mixture of condensable hydrocarbons.

"Kerosene" refers to hydrocarbons with a boiling range distribution between 204° C. and 260° C. at 0.101 MPa. Kerosene content is determined by ASTM Method D2887.

"Modulated direct current (DC)" refers to any substantially non-sinusoidal time-varying current that produces skin effect electricity flow in a ferromagnetic conductor.

"Naphtha" refers to hydrocarbon components with a boiling range distribution between 38° C. and 200° C. at 0.101 MPa. Naphtha content is determined by American Standard Testing and Materials (ASTM) Method D5307.

"Nitride" refers to a compound of nitrogen and one or more other elements of the Periodic Table. Nitrides include, but are not limited to, silicon nitride, boron nitride, or alumina nitride.

"Nitrogen compound content" refers to an amount of nitrogen in an organic compound. Nitrogen content is as determined by ASTM Method D5762.

"Octane Number" refers to a calculated numerical representation of the antiknock properties of a motor fuel compared to a standard reference fuel. A calculated octane number is determined by ASTM Method D6730.

"Olefins" are molecules that include unsaturated hydrocarbons having one or more non-aromatic carbon-carbon double bonds.

"Orifices" refer to openings, such as openings in conduits, having a wide variety of sizes and cross-sectional shapes including, but not limited to, circles, ovals, squares, rectangles, triangles, slits, or other regular or irregular shapes.

"Pebble" refers to one or more spheres, oval shapes, oblong shapes, irregular or elongated shapes.

"Periodic Table" refers to the Periodic Table as specified by the International Union of Pure and Applied Chemistry (IUPAC), November 2003. In the scope of this application, weight of a metal from the Periodic Table, weight of a compound of a metal from the Periodic Table, weight of an element from the Periodic Table, or weight of a compound of an element from the Periodic Table is calculated as the weight of metal or the weight of element. For example, if 0.1 grams of MoO_3 is used per gram of catalyst, the calculated weight of the molybdenum metal in the catalyst is 0.067 grams per gram of catalyst.

"Physical stability" refers the ability of a formation fluid to not exhibit phase separate or flocculation during transportation of the fluid. Physical stability is determined by ASTM Method D7060.

"Pyrolysis" is the breaking of chemical bonds due to the application of heat. For example, pyrolysis may include transforming a compound into one or more other substances by heat alone. Heat may be transferred to a section of the formation to cause pyrolysis.

"Pyrolyzation fluids" or "pyrolysis products" refers to fluid produced substantially during pyrolysis of hydrocarbons. Fluid produced by pyrolysis reactions may mix with other fluids in a formation. The mixture would be considered pyrolyzation fluid or pyrolyzation product. As used herein, "pyrolysis zone" refers to a volume of a formation (for example, a relatively permeable formation such as a tar sands formation) that is reacted or reacting to form a pyrolyzation fluid.

"Residue" refers to hydrocarbons that have a boiling point above 537° C. (1000° F.).

"Rich layers" in a hydrocarbon containing formation are relatively thin layers (typically about 0.2 m to about 0.5 m thick). Rich layers generally have a richness of about 0.150 L/kg or greater. Some rich layers have a richness of about 0.170 L/kg or greater, of about 0.190 L/kg or greater, or of about 0.210 L/kg or greater. Lean layers of the formation have a richness of about 0.100 L/kg or less and are generally thicker than rich layers. The richness and locations of layers are determined, for example, by coring and subsequent Fischer assay of the core, density or neutron logging, or other logging methods. Rich layers may have a lower initial thermal conductivity than other layers of the formation. Typically, rich layers have a thermal conductivity 1.5 times to 3 times lower than the thermal conductivity of lean layers. In addition, rich layers have a higher thermal expansion coefficient than lean layers of the formation.

"Smart well technology" or "smart wellbore" refers to wells that incorporate downhole measurement and/or control. For injection wells, smart well technology may allow for controlled injection of fluid into the formation in desired zones. For production wells, smart well technology may allow for controlled production of formation fluid from selected zones. Some wells may include smart well technology that allows for formation fluid production from selected zones and simultaneous or staggered solution injection into other zones. Smart well technology may include fiber optic systems and control valves in the wellbore. A smart wellbore used for an in situ heat treatment process may be Westbay Multilevel Well System MP55 available from Westbay Instruments Inc. (Burnaby, British Columbia, Canada).

"Subsidence" is a downward movement of a portion of a formation relative to an initial elevation of the surface.

"Sulfur compound content" refers to an amount of sulfur in an organic compound. Sulfur content is as determined by ASTM Method D4294.

"Superposition of heat" refers to providing heat from two or more heat sources to a selected section of a formation such that the temperature of the formation at least at one location between the heat sources is influenced by the heat sources.

"Synthesis gas" is a mixture including hydrogen and carbon monoxide. Additional components of synthesis gas may include water, carbon dioxide, nitrogen, methane, and other gases. Synthesis gas may be generated by a variety of processes and feedstocks. Synthesis gas may be used for synthesizing a wide range of compounds.

"TAN" refers to a total acid number expressed as milligrams ("mg") of KOH per gram ("g") of sample. TAN is as determined by ASTM Method D3242.

"Tar" is a viscous hydrocarbon that generally has a viscosity greater than about 10,000 centipoise at 15° C. The specific gravity of tar generally is greater than 1.000. Tar may have an API gravity less than 10°.

A "tar sands formation" is a formation in which hydrocarbons are predominantly present in the form of heavy hydrocarbons and/or tar entrained in a mineral grain framework or other host lithology (for example, sand or carbonate). Examples of tar sands formations include formations such as the Athabasca formation, the Grosmont formation, and the Peace River formation, all three in Alberta, Canada; and the Faja formation in the Orinoco belt in Venezuela.

"Temperature limited heater" generally refers to a heater that regulates heat output (for example, reduces heat output) above a specified temperature without the use of external controls such as temperature controllers, power regulators, rectifiers, or other devices. Temperature limited heaters may be AC (alternating current) or modulated (for example, "chopped") DC (direct current) powered electrical resistance heaters.

"Thermally conductive fluid" includes fluid that has a higher thermal conductivity than air at standard temperature and pressure (STP) (0° C. and 101.325 kPa).

"Thermal conductivity" is a property of a material that describes the rate at which heat flows, in steady state, between two surfaces of the material for a given temperature difference between the two surfaces.

"Thermal fracture" refers to fractures created in a formation caused by expansion or contraction of a formation and/or fluids in the formation, which is in turn caused by increasing/decreasing the temperature of the formation and/or fluids in the formation, and/or by increasing/decreasing a pressure of fluids in the formation due to heating.

"Thermal oxidation stability" refers to thermal oxidation stability of a liquid. Thermal Oxidation Stability is as determined by ASTM Method D3241.

"Thickness" of a layer refers to the thickness of a cross section of the layer, wherein the cross section is normal to a face of the layer.

"Time-varying current" refers to electrical current that produces skin effect electricity flow in a ferromagnetic conductor and has a magnitude that varies with time. Time-varying current includes both alternating current (AC) and modulated direct current (DC).

"Triad" refers to a group of three items (for example, heaters, wellbores, or other objects) coupled together.

"Turndown ratio" for the temperature limited heater is the ratio of the highest AC or modulated DC resistance below the Curie temperature to the lowest resistance above the Curie temperature for a given current.

A "u-shaped wellbore" refers to a wellbore that extends from a first opening in the formation, through at least a portion of the formation, and out through a second opening in the formation. In this context, the wellbore may be only roughly in the shape of a "v" or "u", with the understanding that the "legs" of the "u" do not need to be parallel to each other, or perpendicular to the "bottom" of the "u" for the wellbore to be considered "u-shaped".

"Upgrade" refers to increasing the quality of hydrocarbons. For example, upgrading heavy hydrocarbons may result in an increase in the API gravity of the heavy hydrocarbons.

"Visbreaking" refers to the untangling of molecules in fluid during heat treatment and/or to the breaking of large molecules into smaller molecules during heat treatment, which results in a reduction of the viscosity of the fluid.

"Viscosity" refers to kinematic viscosity at 40° C. unless specified. Viscosity is as determined by ASTM Method D445.

"VGO" or "vacuum gas oil" refers to hydrocarbons with a boiling range distribution between 343° C. and 538° C. at 0.101 MPa. VGO content is determined by ASTM Method D5307.

A "vug" is a cavity, void or large pore in a rock that is commonly lined with mineral precipitates.

"Wax" refers to a low melting organic mixture, or a compound of high molecular weight that is a solid at lower tem-

peratures and a liquid at higher temperatures, and when in solid form can form a barrier to water. Examples of waxes include animal waxes, vegetable waxes, mineral waxes, petroleum waxes, and synthetic waxes.

The term "wellbore" refers to a hole in a formation made by drilling or insertion of a conduit into the formation. A wellbore may have a substantially circular cross section, or another cross-sectional shape. As used herein, the terms "well" and "opening," when referring to an opening in the formation may be used interchangeably with the term "wellbore."

Hydrocarbons in formations may be treated in various ways to produce many different products. In certain embodiments, hydrocarbons in formations are treated in stages. FIG. **1** depicts an illustration of stages of heating the hydrocarbon containing formation. FIG. **1** also depicts an example of yield ("Y") in barrels of oil equivalent per ton (y axis) of formation fluids from the formation versus temperature ("T") of the heated formation in degrees Celsius (x axis).

Desorption of methane and vaporization of water occurs during stage 1 heating. Heating of the formation through stage 1 may be performed as quickly as possible. For example, when the hydrocarbon containing formation is initially heated, hydrocarbons in the formation desorb adsorbed methane. The desorbed methane may be produced from the formation. If the hydrocarbon containing formation is heated further, water in the hydrocarbon containing formation is vaporized. Water may occupy, in some hydrocarbon containing formations, between 10% and 50% of the pore volume in the formation. In other formations, water occupies larger or smaller portions of the pore volume. Water typically is vaporized in a formation between 160° C. and 285° C. at pressures of 600 kPa absolute to 7000 kPa absolute. In some embodiments, the vaporized water produces wettability changes in the formation and/or increased formation pressure. The wettability changes and/or increased pressure may affect pyrolysis reactions or other reactions in the formation. In certain embodiments, the vaporized water is produced from the formation. In other embodiments, the vaporized water is used for steam extraction and/or distillation in the formation or outside the formation. Removing the water from and increasing the pore volume in the formation increases the storage space for hydrocarbons in the pore volume.

In certain embodiments, after stage 1 heating, the formation is heated further, such that a temperature in the formation reaches (at least) an initial pyrolyzation temperature (such as a temperature at the lower end of the temperature range shown as stage 2). Hydrocarbons in the formation may be pyrolyzed throughout stage 2. A pyrolysis temperature range varies depending on the types of hydrocarbons in the formation. The pyrolysis temperature range may include temperatures between 250° C. and 900° C. The pyrolysis temperature range for producing desired products may extend through only a portion of the total pyrolysis temperature range. In some embodiments, the pyrolysis temperature range for producing desired products may include temperatures between 250° C. and 400° C. or temperatures between 270° C. and 350° C. If a temperature of hydrocarbons in the formation is slowly raised through the temperature range from 250° C. to 400° C., production of pyrolysis products may be substantially complete when the temperature approaches 400° C. Average temperature of the hydrocarbons may be raised at a rate of less than 5° C. per day, less than 2° C. per day, less than 1° C. per day, or less than 0.5° C. per day through the pyrolysis temperature range for producing desired products. Heating the hydrocarbon containing formation with a plurality of heat sources may establish thermal gradients around the heat sources that slowly raise the temperature of hydrocarbons in the formation through the pyrolysis temperature range.

The rate of temperature increase through the pyrolysis temperature range for desired products may affect the quality and quantity of the formation fluids produced from the hydrocarbon containing formation. Raising the temperature slowly through the pyrolysis temperature range for desired products may inhibit mobilization of large chain molecules in the formation. Raising the temperature slowly through the pyrolysis temperature range for desired products may limit reactions between mobilized hydrocarbons that produce undesired products. Slowly raising the temperature of the formation through the pyrolysis temperature range for desired products may allow for the production of high quality, high API gravity hydrocarbons from the formation. Slowly raising the temperature of the formation through the pyrolysis temperature range for desired products may allow for the removal of a large amount of the hydrocarbons present in the formation as hydrocarbon product.

In some in situ heat treatment embodiments, a portion of the formation is heated to a desired temperature instead of slowly heating the temperature through a temperature range. In some embodiments, the desired temperature is 300° C., 325° C., or 350° C. Other temperatures may be selected as the desired temperature. Superposition of heat from heat sources allows the desired temperature to be relatively quickly and efficiently established in the formation. Energy input into the formation from the heat sources may be adjusted to maintain the temperature in the formation substantially at the desired temperature. The heated portion of the formation is maintained substantially at the desired temperature until pyrolysis declines such that production of desired formation fluids from the formation becomes uneconomical. Parts of the formation that are subjected to pyrolysis may include regions brought into a pyrolysis temperature range by heat transfer from only one heat source.

In certain embodiments, formation fluids including pyrolyzation fluids are produced from the formation. As the temperature of the formation increases, the amount of condensable hydrocarbons in the produced formation fluid may decrease. At high temperatures, the formation may produce mostly methane and/or hydrogen. If the hydrocarbon containing formation is heated throughout an entire pyrolysis range, the formation may produce only small amounts of hydrogen towards an upper limit of the pyrolysis range. After all of the available hydrogen is depleted, a minimal amount of fluid production from the formation will typically occur.

After pyrolysis of hydrocarbons, a large amount of carbon and some hydrogen may still be present in the formation. A significant portion of carbon remaining in the formation can be produced from the formation in the form of synthesis gas. Synthesis gas generation may take place during stage 3 heating depicted in FIG. **1**. Stage 3 may include heating a hydrocarbon containing formation to a temperature sufficient to allow synthesis gas generation. For example, synthesis gas may be produced in a temperature range from about 400° C. to about 1200° C., about 500° C. to about 1100° C., or about 550° C. to about 1000° C. The temperature of the heated portion of the formation when the synthesis gas generating fluid is introduced to the formation determines the composition of synthesis gas produced in the formation. The generated synthesis gas may be removed from the formation through a production well or production wells.

Total energy content of fluids produced from the hydrocarbon containing formation may stay relatively constant throughout pyrolysis and synthesis gas generation. During pyrolysis at relatively low formation temperatures, a signifi-

cant portion of the produced fluid may be condensable hydrocarbons that have a high energy content. At higher pyrolysis temperatures, however, less of the formation fluid may include condensable hydrocarbons. More non-condensable formation fluids may be produced from the formation. Energy content per unit volume of the produced fluid may decline slightly during generation of predominantly non-condensable formation fluids. During synthesis gas generation, energy content per unit volume of produced synthesis gas declines significantly compared to energy content of pyrolyzation fluid. The volume of the produced synthesis gas, however, will in many instances increase substantially, thereby compensating for the decreased energy content.

FIG. **2** depicts a schematic view of an embodiment of a portion of the in situ heat treatment system for treating the hydrocarbon containing formation. The in situ heat treatment system may include barrier wells **200**. Barrier wells are used to form a barrier around a treatment area. The barrier inhibits fluid flow into and/or out of the treatment area. Barrier wells include, but are not limited to, dewatering wells, vacuum wells, capture wells, injection wells, grout wells, freeze wells, or combinations thereof. In some embodiments, barrier wells **200** are dewatering wells. Dewatering wells may remove liquid water and/or inhibit liquid water from entering a portion of the formation to be heated, or to the formation being heated. In the embodiment depicted in FIG. **2**, the barrier wells **200** are shown extending only along one side of heat sources **202**, but the barrier wells typically encircle all heat sources **202** used, or to be used, to heat a treatment area of the formation.

Heat sources **202** are placed in at least a portion of the formation. Heat sources **202** may include heaters such as insulated conductors, conductor-in-conduit heaters, surface burners, flameless distributed combustors, and/or natural distributed combustors. Heat sources **202** may also include other types of heaters. Heat sources **202** provide heat to at least a portion of the formation to heat hydrocarbons in the formation. Energy may be supplied to heat sources **202** through supply lines **204**. Supply lines **204** may be structurally different depending on the type of heat source or heat sources used to heat the formation. Supply lines **204** for heat sources may transmit electricity for electric heaters, may transport fuel for combustors, or may transport heat exchange fluid that is circulated in the formation. In some embodiments, electricity for an in situ heat treatment process may be provided by a nuclear power plant or nuclear power plants. The use of nuclear power may allow for reduction or elimination of carbon dioxide emissions from the in situ heat treatment process.

When the formation is heated, the heat input into the formation may cause expansion of the formation and geomechanical motion. The heat sources turned on before, at the same time, or during a dewatering process. Computer simulations may model formation response to heating. The computer simulations may be used to develop a pattern and time sequence for activating heat sources in the formation so that geomechanical motion of the formation does not adversely affect the functionality of heat sources, production wells, and other equipment in the formation.

Heating the formation may cause an increase in permeability and/or porosity of the formation. Increases in permeability and/or porosity may result from a reduction of mass in the formation due to vaporization and removal of water, removal of hydrocarbons, and/or creation of fractures. Fluid may flow more easily in the heated portion of the formation because of the increased permeability and/or porosity of the formation. Fluid in the heated portion of the formation may move a considerable distance through the formation because of the increased permeability and/or porosity. The considerable distance may be over 1000 m depending on various factors, such as permeability of the formation, properties of the fluid, temperature of the formation, and pressure gradient allowing movement of the fluid. The ability of fluid to travel considerable distance in the formation allows production wells **206** to be spaced relatively far apart in the formation.

Production wells **206** are used to remove formation fluid from the formation. In some embodiments, production well **206** includes a heat source. The heat source in the production well may heat one or more portions of the formation at or near the production well. In some in situ heat treatment process embodiments, the amount of heat supplied to the formation from the production well per meter of the production well is less than the amount of heat applied to the formation from a heat source that heats the formation per meter of the heat source. Heat applied to the formation from the production well may increase formation permeability adjacent to the production well by vaporizing and removing liquid phase fluid adjacent to the production well and/or by increasing the permeability of the formation adjacent to the production well by formation of macro and/or micro fractures.

More than one heat source may be positioned in the production well. A heat source in a lower portion of the production well may be turned off when superposition of heat from adjacent heat sources heats the formation sufficiently to counteract benefits provided by heating the formation with the production well. In some embodiments, the heat source in an upper portion of the production well may remain on after the heat source in the lower portion of the production well is deactivated. The heat source in the upper portion of the well may inhibit condensation and reflux of formation fluid.

In some embodiments, the heat source in production well **206** allows for vapor phase removal of formation fluids from the formation. Providing heating at or through the production well may: (1) inhibit condensation and/or refluxing of production fluid when such production fluid is moving in the production well proximate the overburden, (2) increase heat input into the formation, (3) increase production rate from the production well as compared to a production well without a heat source, (4) inhibit condensation of high carbon number compounds (C6 and above) in the production well, and/or (5) increase formation permeability at or proximate the production well.

Subsurface pressure in the formation may correspond to the fluid pressure generated in the formation. As temperatures in the heated portion of the formation increase, the pressure in the heated portion may increase as a result of increased fluid generation and vaporization of water. Controlling rate of fluid removal from the formation may allow for control of pressure in the formation. Pressure in the formation may be determined at a number of different locations, such as near or at production wells, near or at heat sources, or at monitor wells.

In some hydrocarbon containing formations, production of hydrocarbons from the formation is inhibited until at least some hydrocarbons in the formation have been pyrolyzed. Formation fluid may be produced from the formation when the formation fluid is of a selected quality. In some embodiments, the selected quality includes an API gravity of at least about 20°, 30°, or 40°. Inhibiting production until at least some hydrocarbons are pyrolyzed may increase conversion of heavy hydrocarbons to light hydrocarbons. Inhibiting initial production may minimize the production of heavy hydrocarbons from the formation. Production of substantial amounts of heavy hydrocarbons may require expensive equipment and/or reduce the life of production equipment.

In some hydrocarbon containing formations, hydrocarbons in the formation may be heated to pyrolysis temperatures before substantial permeability has been generated in the heated portion of the formation. An initial lack of permeability may inhibit the transport of generated fluids to production wells **206**. During initial heating, fluid pressure in the formation may increase proximate heat sources **202**. The increased fluid pressure may be released, monitored, altered, and/or controlled through one or more heat sources **202**. For example, selected heat sources **202** or separate pressure relief wells may include pressure relief valves that allow for removal of some fluid from the formation.

In some embodiments, pressure generated by expansion of pyrolysis fluids or other fluids generated in the formation may be allowed to increase although an open path to production wells **206** or any other pressure sink may not yet exist in the formation. The fluid pressure may be allowed to increase towards a lithostatic pressure. Fractures in the hydrocarbon containing formation may form when the fluid approaches the lithostatic pressure. For example, fractures may form from heat sources **202** to production wells **206** in the heated portion of the formation. The generation of fractures in the heated portion may relieve some of the pressure in the portion. Pressure in the formation may have to be maintained below a selected pressure to inhibit unwanted production, fracturing of the overburden or underburden, and/or coking of hydrocarbons in the formation.

After pyrolysis temperatures are reached and production from the formation is allowed, pressure in the formation may be varied to alter and/or control a composition of formation fluid produced, to control a percentage of condensable fluid as compared to non-condensable fluid in the formation fluid, and/or to control an API gravity of formation fluid being produced. For example, decreasing pressure may result in production of a larger condensable fluid component. The condensable fluid component may contain a larger percentage of olefins.

In some in situ heat treatment process embodiments, pressure in the formation may be maintained high enough to promote production of formation fluid with an API gravity of greater than 20°. Maintaining increased pressure in the formation may inhibit formation subsidence during in situ heat treatment. Maintaining increased pressure may facilitate vapor phase production of fluids from the formation. Vapor phase production may allow for a reduction in size of collection conduits used to transport fluids produced from the formation. Maintaining increased pressure may reduce or eliminate the need to compress formation fluids at the surface to transport the fluids in collection conduits to treatment facilities.

Maintaining increased pressure in a heated portion of the formation may surprisingly allow for production of large quantities of hydrocarbons of increased quality and of relatively low molecular weight. Pressure may be maintained so that formation fluid produced has a minimal amount of compounds above a selected carbon number. The selected carbon number may be at most 25, at most 20, at most 12, or at most 8. Some high carbon number compounds may be entrained in vapor in the formation and may be removed from the formation with the vapor. Maintaining increased pressure in the formation may inhibit entrainment of high carbon number compounds and/or multi-ring hydrocarbon compounds in the vapor. High carbon number compounds and/or multi-ring hydrocarbon compounds may remain in a liquid phase in the formation for significant time periods. The significant time periods may provide sufficient time for the compounds to pyrolyze to form lower carbon number compounds.

Generation of relatively low molecular weight hydrocarbons is believed to be due, in part, to autogenous generation and reaction of hydrogen in a portion of the hydrocarbon containing formation. For example, maintaining an increased pressure may force hydrogen generated during pyrolysis into the liquid phase within the formation. Heating the portion to a temperature in a pyrolysis temperature range may pyrolyze hydrocarbons in the formation to generate liquid phase pyrolyzation fluids. The generated liquid phase pyrolyzation fluids components may include double bonds and/or radicals. Hydrogen (H_2) in the liquid phase may reduce double bonds of the generated pyrolyzation fluids, thereby reducing a potential for polymerization or formation of long chain compounds from the generated pyrolyzation fluids. In addition, H_2 may also neutralize radicals in the generated pyrolyzation fluids. Therefore, H_2 in the liquid phase may inhibit the generated pyrolyzation fluids from reacting with each other and/or with other compounds in the formation.

Formation fluid produced from production wells **206** may be transported through collection piping **208** to treatment facilities **210**. Formation fluids may also be produced from heat sources **202**. For example, fluid may be produced from heat sources **202** to control pressure in the formation adjacent to the heat sources. Fluid produced from heat sources **202** may be transported through tubing or piping to collection piping **208** or the produced fluid may be transported through tubing or piping directly to treatment facilities **210**. Treatment facilities **210** may include separation units, reaction units, upgrading units, fuel cells, turbines, storage vessels, and/or other systems and units for processing produced formation fluids. The treatment facilities may form transportation fuel from at least a portion of the hydrocarbons produced from the formation. In some embodiments, the transportation fuel may be jet fuel, such as JP-8.

Formation fluid may be hot when produced from the formation through the production wells. Hot formation fluid may be produced during solution mining processes and/or during in situ heat treatment processes. In some embodiments, electricity may be generated using the heat of the fluid produced from the formation. Also, heat recovered from the formation after the in situ process may be used to generate electricity. The generated electricity may be used to supply power to the in situ heat treatment process. For example, the electricity may be used to power heaters, or to power a refrigeration system for forming or maintaining a low temperature barrier. Electricity may be generated using a Kalina cycle or a modified Kalina cycle.

FIG. **3** depicts a schematic representation of a Kalina cycle that uses relatively high pressure aqua ammonia as the working fluid. In other embodiments, other fluids such as alkanes, hydrochlorofluorocarbons, hydrofluorocarbons, or carbon dioxide may be used as the working fluid. Hot produced fluid from the formation may pass through line **212** to heat exchanger **214**. The produced fluid may have a temperature greater than about 100° C. Line **216** from heat exchanger **214** may direct the produced fluid to a separator or other treatment unit. In some embodiments, the produced fluid is a mineral containing fluid produced during solution mining. In some embodiments, the produced fluid includes hydrocarbons produced using an in situ heat treatment process or using an in situ mobilization process. Heat from the produced fluid is used to evaporate aqua ammonia in heat exchanger **214**.

Aqua ammonia from tank **218** is directed by pump **220** to heat exchanger **214** and heat exchanger **222**. Aqua ammonia from heat exchangers **214**, **222** passes to separator **224**. Sepa-

rator **224** forms a rich ammonia gas stream and a lean ammonia gas stream. The rich ammonia gas stream is sent to turbine **226** to generate electricity.

The lean ammonia gas stream from separator **224** passes through heat exchanger **222**. The lean gas stream leaving heat exchanger **222** is combined with the rich ammonia gas stream leaving turbine **226**. The combination stream is passed through heat exchanger **228** and returned to tank **218**. Heat exchanger **228** may be water cooled. Heater water from heat exchanger **228** may be sent to a surface water reservoir through line **230**.

FIG. **4** depicts a schematic representation of a modified Kalina cycle that uses lower pressure aqua ammonia as the working fluid. In other embodiments, other fluids such as alkanes, hydrochlorofluorcarbons, hydrofluorocarbons, or carbon dioxide may be used as the working fluid. Hot produced fluid from the formation may pass through line **212** to heat exchanger **214**. The produced fluid may have a temperature greater than about 100° C. Second heat exchanger **232** may further reduce the temperature of the produced fluid from the formation before the fluid is sent through line **216** to a separator or other treatment unit. Second heat exchanger may be water cooled.

Aqua ammonia from tank **218** is directed by pump **220** to heat exchanger **234**. The temperature of the aqua ammonia from tank **218** is heated in heat exchanger **234** by transfer with a combined aqua ammonia stream from turbine **226** and separator **224**. The aqua ammonia stream from heat exchanger **234** passes to heat exchanger **236**. The temperature of the stream is raised again by transfer of heat with a lean ammonia stream that exits separator **224**. The stream then passes to heat exchanger **214**. Heat from the produced fluid is used to evaporate aqua ammonia in heat exchanger **214**. The aqua ammonia passes to separator **224**.

Separator **224** forms a rich ammonia gas stream and a lean ammonia gas stream. The rich ammonia gas stream is sent to turbine **226** to generate electricity. The lean ammonia gas stream passes through heat exchanger **236**. After heat exchanger **236**, the lean ammonia gas stream is combined with the rich ammonia gas stream leaving turbine **226**. The combined gas stream is passed through heat exchanger **234** to cooler **238**. After cooler **238**, the stream returns to tank **218**.

Heating a portion of the subsurface formation may cause the mineral structure of the formation to change and form particles. The particles may be dispersed and/or become partially dissolved in the formation fluid. The particles may include metals and/or compounds of metals from Columns 1-2 and Columns 4-13 of the Periodic Table (for example, aluminum, silicon, magnesium, calcium, potassium sodium, beryllium, lithium, chromium, magnesium, copper, zirconium, and so forth). In certain embodiments, the particles include cenospheres. In some embodiments, the particles are coated, for example, with hydrocarbons of the formation fluid. In certain embodiments, the particles include zeolites.

A concentration of particles in formation fluid may range from about 1 ppm to about 3000 ppm, from about 50 ppm to about 2000 ppm, or from about 100 ppm to about 1000 ppm. The size of particles may range from about 0.5 micrometers to about 200 micrometers, from about 5 micrometers to about 150 micrometers, from about 10 micrometers to about 100 micrometers, or about 20 micrometers to about 50 micrometers.

In certain embodiments, formation fluid may include a distribution of particles. The distribution of particles may be, but is not limited to, a trimodal or a bimodal distribution. For example, a trimodal distribution of particles may include from about 1 ppm to about 50 ppm of particles with a size of about 5 micrometers to about 10 micrometers, from about 2 ppm to about 2000 ppm of particles with a size of about 50 micrometers to about 80 micrometers, and from about 1 ppm to about 100 ppm with a size of between about 100 micrometers and about 200 micrometers. A bimodal distribution of particles may include from about 1 ppm to about 60 ppm of particles with a size of between about 50 micrometers and about 60 micrometers and from about 2 ppm to about 2000 ppm of particles with a size between about 100 micrometers and about 200 micrometers.

In some embodiments, the particles may contact the formation fluid and catalyze formation of compounds having a carbon number of at most 25, at most 20, at most 12, or at most 8. In certain embodiments, zeolitic particles may assist in the oxidation and/or reduction of formation fluids to produce compounds not generally found in fluids produced using conventional production methods. Contact of formation fluid with hydrogen in the presence of zeolitic particles may catalyze reduction of double bond compounds in the formation fluid.

In some embodiments, all or a portion of the particles in the produced fluid may be removed from the produced fluid. The particles may be removed by using a centrifuge, by washing, by acid washing, by filtration, by electrostatic precipitation, by froth flotation, and/or by another type of separation process.

Formation fluid produced from the in situ heat treatment process may be sent to the separator to split the stream into the in situ heat treatment process liquid stream and an in situ heat treatment process gas stream. In some embodiments, the formation fluid has a boiling range distribution between about −5° C. and about 350° C., between about 5° C. and about 340° C., between about 10° C. and about 330° C., or between about 15° C. and about 320° C.

The liquid stream and the gas stream may be further treated to yield desired products. When the liquid stream is treated using generally known conditions to produce commercial products, processing equipment may be adversely affected. For example, the processing equipment may clog. Examples of processes to produce commercial products include, but are not limited to, alkylation, distillation, catalytic reforming hydrocracking, hydrotreating, hydrogenation, hydrodesulfurization, catalytic cracking, delayed coking, gasification, or combinations thereof. Processes to produce hydrocarbon streams and/or other products are described in "Refining Processes 2000," Hydrocarbon Processing, Gulf Publishing Co., pp. 87-142, which is incorporated by reference herein. Examples of commercial hydrocarbon products include, but are not limited to, diesel, hydrocarbon gases, kerosene, naphtha, vacuum gas oil ("VGO"), or mixtures thereof.

Process equipment may become clogged or fouled by compositions in the in situ heat treatment process liquid. Clogging compositions may include, but are not limited to, hydrocarbons and/or solids produced from the in situ heat treatment process. Compositions that cause clogging may be formed during heating of the in situ heat treatment process liquid. The compositions may adhere to parts of the equipment and inhibit the flow of the liquid stream through processing units.

Solids that cause clogging may include, but are not limited to, organometallic compounds, inorganic compounds, minerals, mineral compounds, cenospheres, coke, semi-soot, and/or mixtures thereof. The solids may have a particle size such that conventional filtration may not remove the solids from the liquid stream. Hydrocarbons that cause clogging may include, but are not limited to, hydrocarbons that contain heteroatoms, aromatic hydrocarbons, cyclic hydrocarbons, cyclic di-olefins, and/or acyclic di-olefins. In some embodi-

ments, solids and/or hydrocarbons present in the in situ heat treatment process liquid that cause clogging are partially soluble or insoluble in the situ heat treatment process liquid. In some embodiments, conventional filtration of the liquid stream prior to or during heating is insufficient and/or ineffective for removal of all or some of the compositions that clog process equipment.

In some embodiments, clogging compositions are at least partially removed from the liquid stream by washing and/or desalting the liquid stream. In some embodiments, clogging of process equipment is inhibited by filtering at least a portion of the liquid stream through a nanofiltration system. In some embodiments, clogging of process equipment is inhibited by hydrotreating at least a portion of the liquid stream. In some embodiments, at least a portion the liquid stream is nanofiltered and then hydrotreated to remove composition that may clog and/or foul process equipment. The hydrotreated and/or nanofiltered liquid stream may be further processed to produce commercial products. In some embodiments, anti-fouling additives are added to the liquid stream to inhibit clogging of process equipment. Anti-fouling additives are described in U.S. Pat. No. 5,648,305 to Mansfield et al.; U.S. Pat. No. 5,282,957 to Wright et al.; U.S. Pat. No. 5,173,213 to Miller et al.; U.S. Pat. No. 4,840,720 to Reid; U.S. Pat. No. 4,810,397 to Dvoracek; and U.S. Pat. No. 4,551,226 to Fern, all of which are incorporated by reference herein. Examples of commercially available additives include, but are not limited to, Chimec RO 303 Chimec RO 304, Chimec RO 305, Chimec RO 306, Chimec RO 307, Chimec RO 308, (available from Chimec, Rome, Italy), GE-Betz Thermal Flow 7R29 GE-Betz ProChem 3F28, Ge Betz ProChem 3F18 (available from GE Water and Process Technologies, Trevose, Pa., U.S.A.).

FIGS. **5** and **5**A depict schematic representations of an embodiment of a system for producing crude products and/or commercial products from the in situ heat treatment process liquid stream and/or the in situ heat treatment process gas stream. Formation fluid **320** enters fluid separation unit **322** and is separated into in situ heat treatment process liquid stream **324**, in situ heat treatment process gas **240** and aqueous stream **326**. In some embodiments, fluid separation unit **322** includes a quench zone. As produced formation fluid enters the quench zone, quenching fluid such as water, non-potable water and/or other components may be added to the formation fluid to quench and/or cool the formation fluid to a temperature suitable for handling in downstream processing equipment. Quenching the formation fluid may inhibit formation of compounds that contribute to physical and/or chemical instability of the fluid (for example, inhibit formation of compounds that may precipitate from solution, contribute to corrosion, and/or fouling of downstream equipment and/or piping). The quenching fluid may be introduced into the formation fluid as a spray and/or a liquid stream. In some embodiments, the formation fluid is introduced into the quenching fluid. In some embodiments, the formation fluid is cooled by passing the fluid through a heat exchanger to remove some heat from the formation fluid. The quench fluid may be added to the cooled formation fluid when the temperature of the formation fluid is near or at the dew point of the quench fluid. Quenching the formation fluid near or at the dew point of the quench fluid may enhance solubilization of salts that may cause chemical and/or physical instability of the quenched fluid (for example, ammonium salts). In some embodiments, an amount of water used in the quench is minimal so that salts of inorganic compounds and/or other components do not separate from the mixture. In separation unit **322**, at least a portion of the quench fluid may be separated from the quench mixture and recycled to the quench zone with a minimal amount of treatment. Heat produced from the quench may be captured and used in other facilities. In some embodiments, vapor may be produced during the quench. The produced vapor may be sent to gas separation unit **328** and/or sent to other facilities for processing.

In situ heat treatment process gas **240** may enter gas separation unit **328** to separate gas hydrocarbon stream **330** from the in situ heat treatment process gas. The gas separation unit is, in some embodiments, a rectified adsorption and high pressure fractionation unit. Gas hydrocarbon stream **330** includes hydrocarbons having a carbon number of at least 3.

In situ heat treatment process liquid stream **324** enters liquid separation unit **332**. In some embodiments, liquid separation unit **332** is not necessary. In liquid separation unit **332**, separation of in situ heat treatment process liquid stream **324** produces gas hydrocarbon stream **336** and salty process liquid stream **338**. Gas hydrocarbon stream **336** may include hydrocarbons having a carbon number of at most 5. A portion of gas hydrocarbon stream **336** may be combined with gas hydrocarbon stream **330**. Salty process liquid stream **338** may be processed through desalting unit **340** to form liquid stream **334**. Desalting unit **340** removes mineral salts and/or water from salty process liquid stream **338** using known desalting and water removal methods. In certain embodiments, desalting unit **340** is upstream of liquid separation unit **332**.

Liquid stream **334** includes, but is not limited to, hydrocarbons having a carbon number of at least 5 and/or hydrocarbon containing heteroatoms (for example, hydrocarbons containing nitrogen, oxygen, sulfur, and phosphorus). Liquid stream **334** may include at least 0.001 g, at least 0.005 g, or at least 0.01 g of hydrocarbons with a boiling range distribution between about 95° C. and about 200° C. at 0.101 MPa; at least 0.01 g, at least 0.005 g, or at least 0.001 g of hydrocarbons with a boiling range distribution between about 200° C. and about 300° C. at 0.101 MPa; at least 0.001 g, at least 0.005 g, or at least 0.01 g of hydrocarbons with a boiling range distribution between about 300° C. and about 400° C. at 0.101 MPa; and at least 0.001 g, at least 0.005 g, or at least 0.01 g of hydrocarbons with a boiling range distribution between 400° C. and 650° C. at 0.101 MPa. In some embodiments, liquid stream **334** contains at most 10% by weight water, at most 5% by weight water, at most 1% by weight water, or at most 0.1% by weight water.

In some embodiments, the separated liquid stream may have a boiling range distribution between about 50° C. and about 350° C., between about 60° C. and 340° C., between about 70° C. and 330° C. or between about 80° C. and 320° C. In some embodiments, the separated liquid stream has a boiling range distribution between 180° C. and 330° C.

In some embodiments, at least 50%, at least 70%, or at least 90% by weight of the total hydrocarbons in the separated liquid stream have a carbon number from 8 to 13. The separated liquid stream may have from about 50% to about 100%, about 60% to about 95%, about 70% to about 90%, or about 75% to 85% by weight of liquid stream may have a carbon number distribution from 8 to 13. At least 50% by weight to the total hydrocarbon in the separated liquid stream may have a carbon number from about 9 to 12 or from 10 to 11.

In some embodiments the separated liquid stream has at most 15%, at most 10%, at most 5% by weight of naphthenes; at least 70%, at least 80%, or at least 90% by weight total paraffins; at most 5%, at most 3%, or at most 1% by weight olefins; and at most 30%, at most 20%, or at most 10% by weight aromatics.

In some embodiments, the separated liquid stream has a nitrogen compound content of at least 0.01%, at least 0.1% or

at least 0.4% by weight nitrogen compound. The separated liquid stream may have a sulfur compound content of at least 0.01%, at least 0.5% or at least 1% by weight sulfur compound.

After exiting desalting unit **340**, liquid stream **334** enters filtration system **342**. In some embodiments, filtration system **342** is connected to the outlet of the desalting unit. Filtration system **342** separates at least a portion of the clogging compounds from liquid stream **334**. In some embodiments, filtration system **342** is skid mounted. Skid mounting filtration system **342** may allow the filtration system to be moved from one processing unit to another. In some embodiments, filtration system **342** includes one or more membrane separators, for example, one or more nanofiltration membranes or one or more reserve osmosis membranes.

The membrane may be a ceramic membrane and/or a polymeric membrane. The ceramic membrane may be a ceramic membrane having a molecular weight cut off of at most 2000 Daltons (Da), at most 1000 Da, or at most 500 Da. Ceramic membranes do not have to swell in order to work under optimal conditions to remove the desired materials from a substrate (for example, clogging compositions from the liquid stream). In addition, ceramic membranes may be used at elevated temperatures. Examples of ceramic membranes include, but are not limited to, mesoporous titania, mesoporous gamma-alumina, mesoporous zirconia, mesoporous silica, and combinations thereof.

The polymeric membrane includes a top layer made of a dense membrane and a base layer (support) made of a porous membrane. The polymeric membrane may be arranged to allow the liquid stream (permeate) to flow first through the dense membrane top layer and then through the base layer so that the pressure difference over the membrane pushes the top layer onto the base layer. The polymeric membrane is organophilic, or hydrophobic membrane so that water present in the liquid stream is retained or substantially retained in the retentate.

The dense membrane layer may separate at least a portion of or substantially all of the clogging compositions from liquid stream **334**. In some embodiments, the dense polymeric membrane has properties such that liquid stream **334** passes through the membrane by dissolving in and diffusing through its structure. At least a portion of the clogging particles may not dissolve and/or diffuse through the dense membrane, thus they are removed. The clogging particles may not dissolve and/or diffuse through the dense membrane because of the complex structure of the clogging particles and/or their high molecular weight. The dense membrane layer may include a cross-linked structure as described in WO 96/27430 to Schmidt et al., which is incorporated by reference herein. A thickness of the dense membrane layer may range from a 1 micrometer to 15 micrometers, from 2 micrometers to 10 micrometers, or from 3 micrometers to 5 micrometers.

The dense membrane may be made from polysiloxane, poly-di-methyl siloxane, poly-octyl-methyl siloxane, polyimide, polyaramide, poly-tri-methyl silyl propyne, or mixtures thereof. Porous base layers may be made of materials that provide mechanical strength to the membrane and may be any porous membrane used for ultra filtration, nanofiltration, or reverse osmosis. Examples of such materials are polyacrylonitrile, polyamideimide in combination with titanium oxide, polyetherimide, polyvinylidenedifluoroide, polytetrafluoroethylene or combinations thereof.

During separation of clogging compositions from liquid stream **334**, the pressure difference across the membrane may range from about 0.5 MPa to about 6 MPa, from about 1 MPa to about 5 MPa, or from about 2 MPa to about 4 MPa. A temperature of separation may range from the pour point of the liquid stream up to 100° C., from about −20° C. to about 100° C., from about 10° C. to about 90° C., or from about 20° C. to about 85° C. During a continuous operation, the permeate flux rate may be at most 50% of the initial flux, at most 70% of the initial flux, or at most 90% of the initial flux. A weight recovery of the permeate on feed may range from about 50% by weight to 97% by weight, from about 60% by weight to 90% by weight, or from about 70% by weight to 80% by weight.

Filtration system **342** may include one or more membrane separators. The membrane separators may include one or more membrane modules. When two or more membrane separators are used, they may be arranged in a parallel configuration to allow feed (retentate) from a first membrane separator to flow into a second membrane separator. Examples of membrane modules include, but are not limited to, spirally wound modules, plate and frame modules, hollow fibers, and tubular modules. Membrane modules are described in Encyclopedia of Chemical Engineering, 4th Ed., 1995, John Wiley & Sons Inc., Vol. 16, pages 158-164. Examples of spirally wound modules are described in, for example, WO/2006/040307 to Boestert et al., U.S. Pat. No. 5,102,551 to Pasternak; U.S. Pat. No. 5,093,002 to Pasternak; U.S. Pat. No. 5,275,726 to Feimer et al.; U.S. Pat. No. 5,458,774 to Mannapperuma; and U.S. Pat. No. 5,150,118 to Finkle et al, all of which are incorporated by reference herein.

In some embodiments, a spirally wound module is used when a dense membrane is used in filtration system **342**. A spirally wound module may include a membrane assembly of two membrane sheets between which a permeate spacer sheet is sandwiched, and which membrane assembly is sealed at three sides. The fourth side is connected to a permeate outlet conduit such that the area between the membranes in fluid communication with the interior of the conduit. On top of one of the membranes a feed spacer sheet is arranged, and the assembly with feed spacer sheet is rolled up around the permeate outlet conduit, to form a substantially cylindrical spirally wound membrane module. The feed spacer may have a thickness of at least 0.6 mm, at least 1 mm, or at least 3 mm to allow sufficient membrane surface to be packed into a spirally wound module. In some embodiments, the feed spacer is a woven feed spacer. During operation, a feed mixture may be passed from one end of the cylindrical module between the membrane assemblies along the feed spacer sheet sandwiched between feed sides of the membranes. Part of the feed mixture passes through either one of the membrane sheets to the permeate side. The resulting permeate flows along the permeate spacer sheet into the permeate outlet conduit.

In some embodiments, the membrane separation is a continuous process. Liquid stream **334** passes over the membrane due to a pressure difference to obtain a filtered liquid stream **344** (permeate) and/or recycle liquid stream **346** (retentate). In some embodiments, filtered liquid stream **344** may have reduced concentrations of compositions and/or particles that cause clogging in downstream processing systems. Continuous recycling of recycle liquid stream **346** through nanofiltration system can increase the production of filtered liquid stream **344** to as much as 95% of the original volume of liquid stream **334**. Recycle liquid stream **346** may be continuously recycled through a spirally wound membrane module for at least 10 hours, for at least one day, or for at least one week without cleaning the feed side of the membrane. Upon completion of the filtration, waste stream **348** (retentate) may include a high concentration of compositions and/or particles that cause clogging. Waste stream **348** exits filtration system

342 and is transported to other processing units such as, for example, a delayed coking unit and/or a gasification unit.

Filtered liquid stream **344** may exit filtration system **342** and enter one or more process units. Process units as described herein for the production of crude products and/or commercial products may be operated at the following temperatures, pressures, hydrogen source flows, liquid stream flows, or combinations thereof, or operated otherwise as known in the art. Temperatures range from about 200° C. to about 900° C., from about 300° C. to about 800° C., or from about 400° C. to about 700° C. Pressures range from about 0.1 MPa to about 20 MPa, from about 1 MPa to about 12 MPa, from about 4 MPa to about 10 MPa, or from about 6 MPa to about 8 MPa. Liquid hourly space velocities of the liquid stream range from about 0.1 h-1 to about 30 h-1, from about 0.5 h-1 to about 25 h-1, from about 1 h-1 to about 20 h-1, from about 1.5 h-1 to about 15 h-1, or from about 2 h-1 to about 10 h-1.

In FIG. **5**, filtered liquid stream **344** and hydrogen source **246** enter hydrotreating unit **350**. In some embodiments, hydrogen source **246** may be added to filtered liquid stream **344** before entering hydrotreating unit **350**. In some embodiments, sufficient hydrogen is present in liquid stream **334** and hydrogen source **246** is not needed. In hydrotreating unit **350**, contact of filtered liquid stream **344** with hydrogen source **246** in the presence of one or more catalysts produces liquid stream **352**. Hydrotreating unit **350** may be operated such that all or at least a portion of liquid stream **352** is changed sufficiently to remove compositions and/or inhibit formation of compositions that may clog equipment positioned downstream of the hydrotreating unit **350**. The catalyst used in hydrotreating unit **350** may be a commercially available catalyst. In some embodiments, hydrotreating of liquid stream **334** is not necessary.

In some embodiments, liquid stream **334** is contacted with hydrogen in the presence of one or more catalysts to change one or more desired properties of the crude feed to meet transportation and/or refinery specifications using known hydrodemetallation, hydrodesulfurization, hydrodenitrification techniques. Other methods to change one or more desired properties of the crude feed are described in U.S. Published Patent Applications Nos. 2005-0133414; 2006-0231465; and 2007-0000810 to Bhan et al.; 2005-0133405 to Wellington et al.; and 2006-0289340 to Brownscombe et al., all of which are incorporated by reference herein.

In some embodiments, the hydrotreated liquid stream has a nitrogen compound content of at most 200 ppm by weight, at most 150 ppm, at most 110 ppm, at most 50 ppm, or at most 10 ppm of nitrogen compounds. The separated liquid stream may have a sulfur compound content of at most 100 ppm, at most 500 ppm, at most 300 ppm, at most 100 ppm, or at most 10 ppm by weight of sulfur compounds.

In some embodiments, hydrotreating unit **350** is a selective hydrogenation unit. In hydrotreating unit **350**, liquid stream **334** and/or filtered liquid stream **344** are selectively hydrogenated such that di-olefins are reduced to mono-olefins. For example, liquid stream **334** and/or filtered liquid stream **344** is contacted with hydrogen in the presence of a DN-200 (Criterion Catalysts & Technologies, Houston Tex., U.S.A.) at temperatures ranging from 100° C. to 200° C. and total pressures of 0.1 MPa to 40 MPa to produce liquid stream **352**. In some embodiments, filtered liquid stream **344** is hydrotreated at a temperature ranging from about 190° C. and about 200° C. at least 6 MPa. Liquid stream **352** includes a reduced content of di-olefins and an increased content of mono-olefins relative to the di-olefin and mono-olefin content of liquid stream **334**. The conversion of di-olefins to mono-olefins under these conditions is, in some embodiments, at least 50%, at least 60%, at least 80% or at least 90%. Liquid stream **352** exits hydrotreating unit **350** and enters one or more processing units positioned downstream of hydrotreating unit **350**. The units positioned downstream of hydrotreating unit **350** may include distillation units, catalytic reforming units, hydrocracking units, hydrotreating units, hydrogenation units, hydrodesulfurization units, catalytic cracking units, delayed coking units, gasification units, or combinations thereof. In some embodiments, hydrotreating prior to fractionation is not necessary. In some embodiments, liquid stream **352** may be severely hydrotreated to remove undesired compounds from the liquid stream prior to fractionation. In certain embodiments, liquid stream **352** may be fractionated and then produced streams may each be hydrotreated to meet industry standards and/or transportation standards.

Liquid stream **352** may exit hydrotreating unit **350** and enter fractionation unit **354**. In fractionation unit **354**, liquid stream **352** may be distilled to form one or more crude products. Crude products include, but are not limited to, C3-C5 hydrocarbon stream **356**, naphtha stream **358**, kerosene stream **360**, diesel stream **362**, and bottoms stream **364**. Fractionation unit **354** may be operated at atmospheric and/or under vacuum conditions.

As shown in FIG. **5**A, fractionation unit **354** includes two or more zones operated at different temperatures and pressures. Operating the two zones at different temperatures and pressures may inhibit or substantially reduce fouling of fractionation columns, heat exchangers and/or other equipment associated with fractionation unit **354**. Liquid stream **352** may enter first fractionation zone **2000**. Fractionation zone KC200 may be operated at a temperature ranging from about 50° C. to about 350° C., or from about 100° C. to 325° C., or from about 150° C. to 300° C. at 0.101 MPa to separate compounds boiling above 350° from the liquid stream to produce one or more crude products including, but not limited to, C3-C5 hydrocarbon stream **356***a*, naphtha stream **358'**, kerosene stream **360'**, and diesel stream **362'**. Hydrocarbons having a boiling point above 350° C. (for example bottoms stream **364'**) may enter second fractionation zone **2002**. Second fractionation zone **2002** may be operated at temperatures greater than 350° C. at 0.101 MPa to separate form one or more crude products, including but not limited to, C3-C5 hydrocarbon stream **356***b*', naphtha stream **358"**, kerosene stream **360"**, diesel stream **362"**, and bottoms stream **364"**. In some embodiments, second fractionation zone **2002** is operated under vacuum. Bottoms stream **364**, bottoms stream **364'**, and/or bottoms stream **364"** generally includes hydrocarbons having a boiling range distribution of at least 340° C. at 0.101 MPa. In some embodiments, bottoms stream **364** is vacuum gas oil. In other embodiments, bottoms stream **364** bottoms stream **364'**, and/or bottoms stream **364"** includes hydrocarbons with a boiling range distribution of at least 537° C. One or more of the crude products may be sold and/or further processed to gasoline or other commercial products. In certain embodiments, one or more of the crude products may be hydrotreated to meet industry standards and/or transportation standards.

As shown in FIG. **6** hydrotreated liquid stream may be treated in fractionation unit **354** to remove compounds boiling below 180° C. to produce distilled stream **355**. Distilled stream **355** may have a boiling range distribution between about 140° C. and about 350° C., between about 180° C. and about 330° C., or between about 190° C. and about 310° C. In

some embodiments distilled stream **355** may be hydrotreated prior to fractionation to remove undesired compounds (for example, sulfur and/or nitrogen compounds). In certain embodiments, distilled stream **355** is sent to a hydrotreating unit and hydrotreated to meet transportation standards for metals, nitrogen compounds and/or sulfur compounds.

In some embodiments, at least 50%, at least 70%, or at least 90% by weight of the total hydrocarbons in distilled liquid stream **355** have a carbon number from 8 to 13. Distilled liquid stream **355** may have from about 50% to about 100%, about 60% to about 95%, about 70% to about 90%, or about 75% to 85% by weight may have a carbon number from 8 to 13. At least 50% by weight to the total hydrocarbon in distilled liquid stream **355** may have a carbon number from about 9 to 12 or from 10 to 11.

In some embodiments, hydrotreated and distilled liquid stream **355** has at most 15%, at most 10%, at most 5% by weight of naphthenes; at least 70%, at least 80%, or at least 90% by weight total paraffins; at most 5%, at most 3%, or at most 1% by weight olefins; and at most 25%, at most 20%, or at most 15% by weight aromatics.

In some embodiments, hydrotreated and distilled liquid stream **355** has a nitrogen compound content of at most 200 ppm by weight, at most 150 ppm, at most 110 ppm, at most 50 ppm, at most 10 ppm, or at most 5 ppm of nitrogen compounds. The hydrotreated and distilled liquid stream may have a sulfur content of at most 50 ppm, at most 30 ppm or at most 10 ppm by weight sulfur compound.

In some embodiments, hydrotreated and/or distilled liquid stream **355** has a wear scar diameter as measured by ASTM D5001, ranging from about 0.1 mm to about 0.9 mm, from about 0.2 mm to about 0.8 mm, or from 0.3 mm to about 0.7 mm. In some embodiments, hydrotreated and/or distilled liquid stream **355** has a wear scar diameter, as measured by ASTM D5001 of at most 0.85 mm, at most 0.8 mm, at most 0.6 mm, at most 0.5 mm, or at most 0.3 mm. A wear scar diameter, as determined by ASTM D5001, may indicate the hydrotreated and/or distilled stream may have acceptable lubrication properties for transportation fuel (for example, commercial aviation fuel, fuel for military purposes, JP-8 fuel, Jet A-1 fuel).

Hydrotreating to remove undesired compounds (for example, sulfur compounds and nitrogen compounds) from the liquid stream may decrease the liquid stream to be an effective lubricant (for example, lubricity properties when used as a transportation fuel). In some embodiments, hydrotreated and/or distilled liquid stream **355** has a minimal concentration and/or no detectable amounts of sulfur compounds. A low sulfur, nonadditized hydrotreated and/or distilled liquid stream **355** may have acceptable lubricity properties (for example, an acceptable wear scar diameter as measured by ASTM D5001). For example, the hydrotreated and distilled liquid stream may have a boiling range distribution from about 140° C. to about 260° C., a sulfur content of at most 30 ppm by weight, and a wear scar diameter of at most 0.85 mm.

In some embodiments, naphtha stream **358**, kerosene stream **360**, diesel stream **362**, distilled liquid stream **355** are evaluated to determine an amount, if any, of additives and/or hydrocarbons that may be added to prepare a fully formulated transportation fuel and/or lubricant. For example, a distilled stream made by the processes described herein was evaluated for use in military vehicles against Department of Defense standard MIL-DTL-83133E using ASTM test methods. The results of the test are listed in TABLE 1.

TABLE 1

Specification Test	Liquid Stream	MIL-DTL-83133E Standard Min	Max	ASTM Test Method
Total Acid Number, mg KOH/g	0.007		0.015	D3242
Aromatics, % volume	11.4		25.0	D1319
Mercaptan Sulfur, % mass	0.000		0.001	D3227
Total Sulfur, % mass	0.00		0.3	D4294
Distillation:				D2887
IBP, ° C.	180		report	
10% recovered, ° C.	188		186	
20% recovered, ° C.	191		Report	
50% recovered, ° C.	199		Report	
90% recovered, ° C.	215		Report	
EP, ° C.	229		330	
Residue, % volume	0.9		1.5	
Loss, % volume	0.3		1.5	
Flash point, ° C.	60	38		D56
Cetane Index (calculated)	43.7		report	D976
Freeze Point, ° C.	−55		−47	D5901
Viscosity @ −20° C., cSt	4.4		8	D445
Viscosity @ −40° C., cSt	9.0			
Heat of Combustion (calculated), BTU/lb	18644	42.8		D3338
Hydrogen Content, % mass	14.0	13.4		D3343
Smoke Point, mm	26	25.0		D1322
Copper Strip Corrosion	1a			D130
Thermal Stability @ 260° C.:				D3241
Tube Deposit Rating	1			D381
Change in Pressure, mm Hg	0			
Existent Gum, mg/100 mL	1.4			
Water Reaction	1			D1094
Conductivity, pS/m	6*			D2624
Density @ 15° C.	0.801	0.775	0.840	D1298
Lubricity (BOCLE), wear scar mm	<0.85			D5001

To enhance the use of the streams produced from formation fluid, hydrocarbons produced during fractionation of the liquid stream and hydrocarbon gases produced during separating the process gas may be combined to form hydrocarbons having a higher carbon number. The produced hydrocarbon gas stream may include a level of olefins acceptable for alkylation reactions.

In some embodiments, hydrotreated liquid streams and/or streams produced from fractions (for example, distillates and/or naphtha) are blended with the in situ heat treatment process liquid and/or formation fluid to produce a blended fluid. The blended fluid may have enhanced physical stability and chemical stability as compared to the formation fluid. The blended fluid may have a reduced amount of reactive species (for example, di-olefins, other olefins and/or compounds containing oxygen, sulfur and/or nitrogen) relative to the formation fluid. Thus, chemical stability of the blended fluid is enhanced. The blended fluid may decrease an amount of asphaltenes relative to the formation fluid. Thus, physical stability of the blended fluid is enhanced. The blended fluid may be a more a fungible feed than the formation fluid and/or the liquid stream produced from an in situ heat treatment process. The blended feed may be more suitable for transportation, for use in chemical processing units and/or for use in refining units than formation fluid.

In some embodiments, a fluid produced by methods described herein from an oil shale formation may be blended with heavy oil/tar sands in situ heat treatment process (IHTP) fluid. Since the oil shale liquid is substantially paraffinic and the heavy oil/tar sands IHTP fluid is substantially aromatic, the blended fluid exhibits enhanced stability. In certain

embodiments, in situ heat treatment process fluid may be blended with bitumen to obtain a feed suitable for use in refining units. Blending of the IHTP fluid and/or bitumen with the produced fluid may enhance the chemical and/or physical stability of the blended product. Thus, the blend may be transported and/or distributed to processing units.

As shown in FIGS. **5**, **5**A, and **6**, C3-C5 hydrocarbon stream **356** produced from fractionation unit **354** and hydrocarbon gas stream **330** enter alkylation unit **368**. In alkylation unit **368**, reaction of the olefins in hydrocarbon gas stream **330** (for example, propylene, butylenes, amylenes, or combinations thereof) with the iso-paraffins in C3-C5 hydrocarbon stream **356** produces hydrocarbon stream **370**. In some embodiments, the olefin content in hydrocarbon gas stream **330** is acceptable and an additional source of olefins is not needed. Hydrocarbon stream **370** includes hydrocarbons having a carbon number of at least 4. Hydrocarbons having a carbon number of at least 4 include, but are not limited to, butanes, pentanes, hexanes, heptanes, and octanes. In certain embodiments, hydrocarbons produced from alkylation unit **368** have an octane number greater than 70, greater than 80, or greater than 90. In some embodiments, hydrocarbon stream **370** is suitable for use as gasoline without further processing.

In some embodiments, bottoms stream **364** may be hydrocracked to produce naphtha and/or other products. The resulting naphtha may, however, need reformation to alter the octane level so that the product may be sold commercially as gasoline. Alternatively, bottoms stream **364** may be treated in a catalytic cracker to produce naphtha and/or feed for an alkylation unit. In some embodiments, naphtha stream **358**, kerosene stream **360**, and diesel stream **362** have an imbalance of paraffinic hydrocarbons, olefinic hydrocarbons, and/or aromatic hydrocarbons. The streams may not have a suitable quantity of olefins and/or aromatics for use in commercial products. This imbalance may be changed by combining at least a portion of the streams to form combined stream **366** which has a boiling range distribution from about 38° C. to about 343° C. Catalytically cracking combined stream **366** may produce olefins and/or other streams suitable for use in an alkylation unit and/or other processing units. In some embodiments, naphtha stream **358** is hydrocracked to produce olefins.

In FIG. **5** and FIG. **5**A, combined stream **366** and bottoms stream **364** from fractionation unit **354** enters catalytic cracking unit **372**. In FIG. **5**A, combined stream **366** may include all or portions of streams **358'**, **360'**, **362'**, **358"**, **360"**, **362"**. Under controlled cracking conditions (for example, controlled temperatures and pressures), catalytic cracking unit **372** produces additional C3-C5 hydrocarbon stream **356'**, gasoline hydrocarbons stream **374**, and additional kerosene stream **360'**.

Additional C3-C5 hydrocarbon stream **356'** may be sent to alkylation unit **368**, combined with C3-C5 hydrocarbon stream **356**, and/or combined with hydrocarbon gas stream **330** to produce gasoline suitable for commercial sale. In some embodiments, the olefin content in hydrocarbon gas stream **330** is acceptable and an additional source of olefins is not needed.

In some embodiments, an amount of the produced bottoms stream (for example, VGO) is too low to sustain operation of a hydrocracking unit or catalytic cracking unit and the concentration of olefins in the produced gas streams from a fractionation unit and/or a catalytic cracking unit (for example, from fractionation unit **354** and/or from catalytic cracking unit **372** in FIG. **5**) may be too low to sustain operation of an alkylation unit. The naphtha produced from the fractionation unit may be treated to produce olefins for further processing in, for example, an alkylation unit. Reformulated gasoline produced by conventional naphtha reforming processes may not meet commercial specifications such as, for example, California Air Resources Board mandates when liquid stream produced from an in situ heat treatment process liquid is used as a feed stream. An amount of olefins in the naphtha may be saturated during conventional hydrotreating prior to the reforming naphtha process. Thus, reforming of all the hydrotreated naphtha may result in a higher than desired aromatics content in the gasoline pool for reformulated gasoline. The imbalance in the olefin and aromatic content in the reformed naphtha may be changed by producing sufficient alkylate from an alkylation unit to produce reformulated gasoline. Olefins (for example, propylene and butylenes) generated from fractionation and/or cracking of the naphtha may be combined with isobutane to produce gasoline. In addition, it has been found that catalytically cracking the naphtha and/or other fractionated streams produced in a fractionating unit requires additional heat because of a reduced amount of coke production relative to other feedstocks used in catalytic cracking units.

FIG. **7** depicts a schematic for treating liquid streams produced from an in situ heat treatment process stream to produce olefins and/or liquid streams. Similar processes to produce middle distillate and olefins are described in International Publication No. WO 2006/020547 and U.S. Patent Application Publication Nos. 2006-0191820 and 2006-0178546 to Mo et al., all of which are incorporated by referenced herein. Liquid stream **376** enters catalytic cracking system **378**. Liquid stream **376** may include, but is not limited to, liquid stream **334**, hydrotreated liquid stream **352**, filtered liquid stream **344**, naphtha stream **358**, kerosene stream **360**, diesel stream **362**, and bottoms stream **364** from the system depicted in FIG. **5**, any hydrocarbon stream having a boiling range distribution between 65° C. and 800° C., or mixtures thereof. In some embodiments, steam **272** enters catalytic cracking system **378** and may atomize and/or lift liquid stream **376** to enhance contact of the liquid stream with the catalytic cracking catalyst. A ratio of steam to atomize liquid stream **376** to feedstock may range from 0.01 to 2 by weight, or from 0.1 to 1 by weight.

In catalytic cracking system **378**, liquid stream **376** is contacted with a catalytic cracking catalyst to produce one or more crude products. The catalytic cracking catalyst includes a selected catalytic cracking catalyst, at least a portion of used regenerated cracking catalyst stream **380**, at least a portion of a regenerated cracking catalyst stream **382**, or a mixture thereof. Used regenerated cracking catalyst **380** includes a regenerated cracking catalyst that has been used in second catalytic cracking system **384**. Second catalytic cracking system **384** may be used to crack hydrocarbons to produce olefins and/or other crude products. Hydrocarbons provided to second catalytic cracking system **384** may include C3-C5 hydrocarbons produced from the production wells, gasoline hydrocarbons, hydrowax, hydrocarbons produced from Fischer-Tropsch processes, biofuels, or combinations thereof. The use of a mixture of different types of hydrocarbon feed to the second catalytic cracking system may enhance C3-C5 olefin production to meet the alkylate demand. Thus, integration of the products with refinery processes may be enhanced. Second catalytic cracking system **384** may be a dense phase unit, a fixed fluidized bed unit, a riser, a combination of the above mentioned units, or any unit or configuration of units known in the art for cracking hydrocarbons.

Contact of the catalytic cracking catalyst and the liquid stream **376** in catalytic cracking system **378** produces a crude product and spent cracking catalyst. The crude product may

include, but is not limited to, hydrocarbons having a boiling point distribution that is less than the boiling point distribution of liquid stream **376**, a portion of liquid stream **376**, or mixtures thereof. The crude product and spent catalyst enters separation system **386**. Separation system **386** may include, for example, a distillation unit, a stripper, a filtration system, a centrifuge, or any device known in the art capable of separating the crude product from the spent catalyst.

Separated spent cracking catalyst stream **388** exits separation system **386** and enters regeneration unit **390**. In regeneration unit **390**, spent cracking catalyst is contacted with oxygen source **392** (for example, oxygen and/or air) under carbon burning conditions to produce regenerated cracking catalyst stream **382** and combustion gases **394**. Combustion gases may form as a by-product of the removal of carbon and/or other impurities formed on the catalyst during the catalytic cracking process.

The temperature in regeneration unit **390** may range from about 621° C. to about 760° C. or from about 677° C. to about 715° C. The pressure in regeneration unit **390** may range from atmospheric to about 0.345 MPa or from about 0.034 to about 0.345 MPa. The residence time of the separated spent cracking catalyst in regeneration unit **390** ranges from about 1 to about 6 minutes or from or about 2 to about 4 minutes. The coke content on the regenerated cracking catalyst is less than the coke content on the separated spent cracking catalyst. Such coke content is less than 0.5% by weight, with the weight percent being based on the weight of the regenerated cracking catalyst excluding the weight of the coke content. The coke content of the regenerated cracking catalyst may range from 0.01% by weight to 0.5% by weight, 0.05% by weight to 0.3% by weight, or 0.1% by weight to 0.2% by weight.

In some embodiments, regenerated cracking catalyst stream **382** may be divided into two streams with at least a portion of regenerated cracking catalyst stream **382'** exiting regeneration unit **390** and entering second catalytic cracking system **384**. At least another portion of regenerated cracking catalyst stream **382** exits regenerator **390** and enters catalytic cracking system **378**. The relative amount of the used regenerated cracking catalyst to the regenerated cracking catalyst is adjusted to provide for the desired cracking conditions within catalytic cracking system **378**. Adjusting the ratio of used regenerated cracking catalyst to regenerated cracking catalyst may assist in the control of the cracking conditions in catalytic cracking system **378**. A weight ratio of the used regenerated cracking catalyst to the regenerated cracking catalyst may range from 0.1:1 to 100:1, from 0.5:1 to 20:1, or from 1:1 to 10:1. For a system operated at steady state, the weight ratio of used regenerated cracking catalyst-to-regenerated cracking catalyst approximates the weight ratio of the at least a portion of regenerated cracking catalyst passing to the second catalytic cracking system **384** to the remaining portion of regenerated cracking catalyst that is mixed with liquid stream **376** introduced into catalytic cracking system **378**, and, thus, the aforementioned ranges are also applicable to such weight ratio.

Crude product **396** exits separation system **386** and enters liquid separation unit **398**. Liquid separation unit **398** may be any system known to those skilled in the art for recovering and separating the crude product into product streams such as, for example, gas stream **336'**, gasoline hydrocarbons stream **400**, cycle oil stream **402**, and bottom stream **404**. In some embodiments, bottom stream **404** is recycled to catalytic cracking system **378**. Liquid separation unit **398** may include components and/or units such as, for example, absorbers and strippers, fractionators, compressors and separators, or any combination of known systems for providing recovery and separation of products from the crude product. In some embodiments, at least a portion of light cycle oil stream **402** exits liquid separation unit **398** and enters second catalytic cracking system **378**. In some embodiments, none of the light cycle oil stream is sent to the second catalytic cracking system. In some embodiments, at least a portion of gasoline hydrocarbons stream **400** exits liquid separation unit **398** and enters second catalytic cracking system **384**. In some embodiments, none of the gasoline hydrocarbons stream is sent to the second catalytic cracking system. In some embodiments, gasoline hydrocarbons stream **400** is suitable for sale and/or for use in other processes.

At least a portion of gas oil hydrocarbon stream **406** (for example, vacuum gas oil) and/or portions of gasoline hydrocarbons stream **400** and at least a portion of light cycle oil stream **402** are sent to catalytic cracking system **384**. The steams are catalytically cracked in the presence of steam **272'** to produce crude olefin stream **408**. Crude olefin stream **408** may include hydrocarbons having a carbon number of at least 2. In some embodiments, crude olefin stream **408** contains at least 30% by weight C2-C5 olefins, at least 40% by weight C2-C5 olefins, at least 50% by weight C2-C5 olefins, at least 70% by weight C2-C5 olefins, or at least 90% by weight C2-C5 olefins. The recycling of the gasoline hydrocarbons stream **400** into second catalytic cracking system **384** may provide for an additional conversion across the overall process system of gas oil hydrocarbon stream **406** to C2-C5 olefins.

In some embodiments, second catalytic cracking system **384** includes an intermediate reaction zone and a stripping zone that are in fluid communication with each other with the stripping zone located below the intermediate reaction zone. To provide for a high steam velocity within the stripping zone, as compared to its velocity within the intermediate reaction zone, the cross sectional area of the stripping zone is less than the cross sectional area of the intermediate reaction zone. The ratio of the stripping zone cross sectional area to the intermediate reaction zone cross sectional area may range from 0.1:1 to 0.9:1; from 0.2:1 to 0.8:1; or from 0.3:1 to 0.7:1.

In some embodiments, the geometry of the second catalytic cracking system is such that it is generally cylindrical in shape. The length-to-diameter ratio of the stripping zone of the catalytic cracking system is such as to provide for the desired high steam velocity within the stripping zone and to provide enough contact time within the stripping zone for the desired stripping of the used regenerated catalyst that is to be removed from the second catalytic cracking system. Thus, the length-to-diameter dimension of the stripping zone may range of from 1:1 to 25:1; from 2:1 to 15:1; or from 3:1 to 10:1.

In some embodiments, second catalytic cracking system **384** is operated or controlled independently from the operation or control of the catalytic cracking system **378**. This independent operation or control of second catalytic cracking system **384** may improve overall conversion of the gasoline hydrocarbons into the desired products such as ethylene, propylene and butylenes. With the independent operation of second catalytic cracking system **384**, the severity of catalytic cracking unit **378** may be reduced to optimize the yield of C2-C5 olefins. A temperature in second catalytic cracking system **384** may range from about 482° C. (900° F.) to about 871° C. (1600° F.), from about 510° C. (950° F.) to about 871° C. (1600° F.), or from about 538° C. (1000° F.) to about 732° C. (1350° F.). The operating pressure of second catalytic

cracking system **384** may range from atmospheric to about 0.345 MPa (50 psig) or from about 0.034 to 0.345 MPa (5 to 50 psig).

Addition of steam **272'** into second catalytic cracking system **384** may assist in the operational control of the second catalytic cracking unit. In some embodiments, steam is not necessary. In some embodiments, the use of the steam for a given gasoline hydrocarbon conversion across the process system, and in the cracking of the gasoline hydrocarbons, may provide for an improved selectivity toward C2-C5 olefin yield with an increase in propylene and butylenes yield relative to other catalytic cracking processes. A weight ratio of steam to gasoline hydrocarbons introduced into second catalytic cracking system **384** may be in the range of upwardly to or about 15:1; from 0.1:1 to 10:1; from 0.2:1 to 9:1; or from 0.5:1 to 8:1.

Crude olefin stream **408** enters olefin separation system **410**. Olefin separation system **410** can be any system known to those skilled in the art for recovering and separating the crude olefin stream **408** into C2-C5 olefin product streams (for example, ethylene product stream **412**, propylene product stream **414**, and butylenes products stream **416**). Olefin separation system **410** may include such systems as absorbers and strippers, fractionators, compressors and separators, or any combination of known systems or equipment providing for the recovery and separation of C2-C5 olefin products from fluid stream **408**. In some embodiments, olefin streams **412**, **414**, **416** enter alkylation unit **368** to generate hydrocarbon stream **370**. In some embodiments, hydrocarbon stream **370** has an octane number of at least 70, at least 80, or at least 90. In some embodiments, all or portions of one or more of streams **412**, **414**, **416** are transported to other processing units, such as polymerization units, for use as feedstocks.

In some embodiments, the crude product from the catalytic cracking system and the crude olefin stream from second catalytic cracking system may be combined. The combined stream may enter a single separation unit (for example, a combination of liquid separation system **398** and olefin separation system **410**).

In FIG. **7**, used cracking catalyst stream **380** exits second catalytic cracking system **384** and enters catalytic cracking system **378**. Catalyst in used cracking catalyst stream **380** may include a slightly higher concentration of carbon than the concentration of carbon that is on the catalyst in regenerated cracking catalyst **382**. A high concentration of carbon on the catalyst may partially deactivate the catalytic cracking catalysts which provides for an enhanced yield of olefins from the catalytic cracking system **378**. Coke content of the used regenerated catalyst may be at least 0.1% by weight or at least 0.5% by weight. The coke content of the used regenerated catalyst may range from about 0.1% by weight to about 1% by weight or from about 0.1% by weight to about 0.6% by weight.

The catalytic cracking catalyst used in catalytic cracking system **378** and second catalytic cracking system **384** may be any fluidizable cracking catalyst known in the art. The fluidizable cracking catalyst may include a molecular sieve having cracking activity dispersed in a porous, inorganic refractory oxide matrix or binder. "Molecular sieve" refers to any material capable of separating atoms or molecules based on their respective dimensions. Molecular sieves suitable for use as a component of the cracking catalyst include pillared clays, delaminated clays, and crystalline aluminosilicates. In some embodiments, the cracking catalyst contains a crystalline aluminosilicate. Examples of such aluminosilicates include Y zeolites, ultrastable Y zeolites, X zeolites, zeolite beta, zeolite L, offretite, mordenite, faujasite, and zeolite omega. In some embodiments, crystalline aluminosilicates for use in the cracking catalyst are X and/or Y zeolites. U.S. Pat. No. 3,130,007 to Breck describes Y-type zeolites.

The stability and/or acidity of a zeolite used as a component of the cracking catalyst may be increased by exchanging the zeolite with hydrogen ions, ammonium ions, polyvalent metal cations, such as rare earth-containing cations, magnesium cations or calcium cations, or a combination of hydrogen ions, ammonium ions and polyvalent metal cations. The sodium content may be lowered until it is at most 0.8% by weight, at most 0.5% by weight and at most 0.3% by weight, calculated as Na_2O. Methods of carrying out the ion exchange are well known in the art.

The zeolite or other molecular sieve component of the cracking catalyst is combined with a porous, inorganic refractory oxide matrix, or binder to form a finished catalyst prior to use. The refractory oxide component in the finished catalyst may be silica-alumina, silica, alumina, natural or synthetic clays, pillared or delaminated clays, mixtures of one or more of these components, and the like. In some embodiments, the inorganic refractory oxide matrix includes a mixture of silica-alumina and clay such as kaolin, hectorite, sepiolite, and attapulgite. A finished catalyst may contain between about 5% by weight and about 40% by weight zeolite or other molecular sieve and greater than about 20 weight percent inorganic refractory oxide. In some embodiments, the finished catalyst may contain between about 10% and about 35% by weight zeolite or other molecular sieve, between about 10% and about 30% by weight inorganic refractory oxide, and between about 30% and about 70% by weight clay.

The crystalline aluminosilicate or other molecular sieve component of the cracking catalyst may be combined with the porous, inorganic refractory oxide component or a precursor thereof by any suitable technique known in the art including mixing, mulling, blending or homogenization. Examples of precursors that may be used include, but are not limited to, alumina, alumina sols, silica sols, zirconia, alumina hydrogels, polyoxycations of aluminum and zirconium, and peptized alumina. In some embodiments, the zeolite is combined with an alumino-silicate gel or sol or other inorganic, refractory oxide component, and the resultant mixture is spray dried to produce finished catalyst particles normally ranging in diameter between about 40 micrometers and about 80 micrometers. In some embodiments, the zeolite or other molecular sieve may be mulled or otherwise mixed with the refractory oxide component or precursor thereof, extruded and then ground into the desired particle size range. The finished catalyst may have an average bulk density between about 0.30 and about 0.90 gram per cubic centimeter and a pore volume between about 0.10 and about 0.90 cubic centimeter per gram.

In some embodiments, a ZSM-5 additive may be introduced into the intermediate cracking reactor of second catalytic cracking system **384**. When a ZSM-5 additive is used along with the selected cracking catalyst in the intermediate cracking reactor, a yield of the lower olefins such as propylene and butylenes is enhanced. An amount of ZSM-5 ranges from at most 30% by weight, at most 20% by weight, or at most 18% by weight of the regenerated catalyst being introduced into second catalytic cracking system **384**. An amount of ZSM-5 additive is introduced into second catalytic cracking system **384** may range from 1% to 30% by weight, 3% to 20% by weight, or 5% to 18% by weight of the regenerated cracking catalyst being introduced into second catalytic cracking system **384**.

The ZSM-5 additive is a molecular sieve additive selected from the family of medium pore size crystalline aluminosili-

cates or zeolites. Molecular sieves that can be used as the ZSM-5 additive include, but are not limited to, medium pore zeolites as described in "Atlas of Zeolite Structure Types," Eds. W. H. Meier and D. H. Olson, Butterworth-Heineman, Third Edition, 1992. The medium pore size zeolites generally have a pore size from about 0.5 μm, to about 0.7 nm and include, for example, MFI, MFS, MEL, MTW, EUO, MTT, HEU, FER, and TON structure type zeolites (IUPAC Commission of Zeolite Nomenclature). Non-limiting examples of such medium pore size zeolites, include ZSM-5, ZSM-12, ZSM-22, ZSM-23, ZSM-34, ZSM-35, ZSM-38, ZSM-48, ZSM-50, silicalite, and silicalite 2. ZSM-5, are described in U.S. Pat. No. 3,702,886 to Argauer et al. and U.S. Pat. No. 3,770,614 to Graven, both of which are incorporated by reference herein.

ZSM-11 is described in U.S. Pat. No. 3,709,979 to Chu; ZSM-12 in U.S. Pat. No. 3,832,449 to Rosinski et al.; ZSM-21 and ZSM-38 in U.S. Pat. No. 3,948,758 to Bonacci et al.; ZSM-23 in U.S. Pat. No. 4,076,842 to Plank et al.; and ZSM-35 in U.S. Pat. No. 4,016,245 to Plank et al., all of which are incorporated by reference herein. Other suitable molecular sieves include the silicoaluninophosphates (SAPO), such as SAPO-4 and SAPO-11 which is described in U.S. Pat. No. 4,440,871 to Lok et al.; chromosilicates; gallium silicates, iron silicates; aluminum phosphates (ALPO), such as ALPO-11 described in U.S. Pat. No. 4,310,440 to Wilson et al.; titanium aluminosilicates (TASO), such as TASO-45 described in U.S. Pat. No. 4,686,029 to Pellet et al.; boron silicates, described in U.S. Pat. No. 4,254,297 Frenken et al.; titanium aluminophosphates (TAPO), such as TAPO-11 described in U.S. Pat. No. 4,500,651 to Lok et al.; and iron aluminosilicates, all of which are incorporated by reference herein.

U.S. Pat. No. 4,368,114 to Chester et al., which is incorporated by reference herein, describes in detail the class of zeolites that can be suitable ZSM-5 additives. The ZSM-5 additive may be held together with a catalytically inactive inorganic oxide matrix component, in accordance with conventional methods.

In some embodiments, liquid streams produced from a heat treatment conversion process (for example liquid stream **334**, and/or bottoms stream **364**) and/or residue produced from units described in FIGS. **5** and **7** may be used as an energy source. Liquid stream **334** and/or the residue may be gasified to produce gases (for example, hydrogen and/or carbon monoxide) which are burned (for example, burned in a turbine) and/or injected into a subsurface formation (for example, injection of produced carbon dioxide into a subsurface formation). In some embodiments, the liquid streams, formation fluids, and/or residue are heated in the presence of steam and/or a catalyst to produce hydrogen, carbon dioxide and/or carbon monoxide. In certain embodiments, the residue is de-asphalted to produce asphalt. The asphalt may be gasified. U.S. Pat. No. 6,916,562 to Gosselink et al.; and U.S. Pat. No. 4,233,187 to Atwood et al.; and U.S. Patent Application Publication No. 2006-0289340 to Brownscombe et al. described methods to gasify hydrocarbon compounds.

In some embodiments, additives and/or heavier hydrocarbons may be combined with the processed liquid stream to prepare a finished fuel and/or lubricant to meet requirements for use in various industrial, commercial, and/or military applications (for example, fuel and/or lubricants for turbines, diesel trucks, aircraft, military vehicles). Examples of additives include, but are not limited to, corrosion inhibitor, lubricity improver, static dissipate additive, fuel system icing inhibitor, antioxidant, detergents, surfactants, friction modifiers, or mixtures thereof.

In some embodiments, transportation fuel made from hydrocarbons obtained from an in situ heat treatment process and processed as described herein is suitable for use as fuel for aircraft and diesel fuel consuming vehicles and equipment. For example, for example the transportation fuel may be used in commercial utility cargo vehicles, high mobility multipurpose wheeled vehicles, military recovery vehicles, tanks, armored personnel carriers, and multi-ton diesel trucks. The transportation fuel may have a boiling range distribution between about 180° C. and about 330° C. as determined by ASTM D2887, an API gravity between 37 and 51 as determined by ASTM D1298, a freezing point of at most −47° C. as determined by ASTM D5901; a viscosity of at most 8.0 mm^2/s at −20° C. as determined by ASTM D445, a hydrogen content of at least 23.4% by weight as determined by ASTM D3343, an aromatics content of at most 25% by volume as determined by ASTM D1319, sulfur content of at most 0.3% by weight as determined by ASTM D4294, a net heat of combustion of at least 42.8 MJ/kg as determined by ASTM D3338; and thermal oxidation stability properties of: a heat tube deposit of at most 3 and a change in pressure drop of at most 25 mm Hg as determined by ASTM D3241.

During some in situ heat treatment processes, ammonia may be in formation fluid produced from the formation. Produced ammonia may be used for a number of purposes. In some embodiments, the ammonia or a portion of the ammonia may be used to produce hydrogen. In some embodiments, the Haber-Bosch process may be used to produce hydrogen. Ammonia may produce hydrogen and nitrogen according to the following equilibrium reaction:

$$N_2+3H_2 \leftrightarrow 2NH_3 \quad \text{(EQN. 1)}$$

The reaction may be a high temperature, high pressure, catalyzed reaction. The temperature may be from about 300° C. to about 800° C. The pressure may be from about 80 bars to about 220 bars. The catalyst may be composed substantially of iron. The total amount of hydrogen produced may be increased by shifting the equilibrium towards hydrogen and nitrogen production. Equilibrium may be shifted to produce more nitrogen and hydrogen by removing nitrogen and/or hydrogen as they are produced.

Many wells are needed for treating the hydrocarbon formation using the in situ heat treatment process. In some embodiments, vertical or substantially vertical wells are formed in the formation. In some embodiments, horizontal or U-shaped wells are formed in the formation. In some embodiments, combinations of horizontal and vertical wells are formed in the formation.

A manufacturing approach for the formation of wellbores in the formation may be used due to the large number of wells that need to be formed for the in situ heat treatment process. The manufacturing approach may be particularly applicable for forming wells for in situ heat treatment processes that utilize u-shaped wells or other types of wells that have long non-vertically oriented sections. Surface openings for the wells may be positioned in lines running along one or two sides of the treatment area. FIG. **8** depicts a schematic representation of an embodiment of a system for forming wellbores of an in situ heat treatment process.

The manufacturing approach for the formation of wellbores may include: 1) delivering flat rolled steel to near site tube manufacturing plant that forms coiled tubulars and/or pipe for surface pipelines; 2) manufacturing large diameter coiled tubing that is tailored to the required well length using electrical resistance welding (ERW), wherein the coiled tubing has customized ends for the bottom hole assembly (BHA) and hang off at the wellhead; 3) deliver the coiled tubing to a

drilling rig on a large diameter reel; 4) drill to total depth with coil and a retrievable bottom hole assembly; 5) at total depth, disengage the coil and hang the coil on the wellhead; 6) retrieve the BHA; 7) launch an expansion cone to expand the coil against the formation; 8) return empty spool to the tube manufacturing plant to accept a new length of coiled tubing; 9) move the gantry type drilling platform to the next well location; and 10) repeat.

In situ heat treatment process locations may be distant from established cities and transportation networks. Transporting formed pipe or coiled tubing for wellbores to the in situ process location may be untenable due to the lengths and quantity of tubulars needed for the in situ heat treatment process. One or more tube manufacturing facilities **2004** may be formed at or near to the in situ heat treatment process location. The tubular manufacturing facility may form plate steel into coiled tubing. The plate steel may be delivered to tube manufacturing facilities **2004** by truck, train, ship or other transportation system. In some embodiments, different sections of the coiled tubing may be formed of different alloys. The tubular manufacturing facility may use ERW to longitudinally weld the coiled tubing.

Tube manufacturing facilities **2004** may be able to produce tubing having various diameters. Tube manufacturing facilities may initially be used to produce coiled tubing for forming wellbores. The tube manufacturing facilities may also be used to produce heater components, piping for transporting formation fluid to surface facilities, and other piping and tubing needs for the in situ heat treatment process.

Tube manufacturing facilities **2004** may produce coiled tubing used to form wellbores in the formation. The coiled tubing may have a large diameter. The diameter of the coiled tubing may be from about 4 inches to about 8 inches in diameter. In some embodiments, the diameter of the coiled tubing is about 6 inches in diameter. The coiled tubing may be placed on large diameter reels. Large diameter reels may be needed due to the large diameter of the tubing. The diameter of the reel may be from about 10 m to about 50 m. One reel may hold all of the tubing needed for completing a single well to total depth.

In some embodiments, tube manufacturing facilities **2004** has the ability to apply expandable zonal inflow profiler (EZIP) material to one or more sections of the tubing that the facility produces. The EZIP material may be placed on portions of the tubing that are to be positioned near and next to aquifers or high permeability layers in the formation. When activated, the EZIP material forms a seal against the formation may serves to inhibit migration of formation fluid between different layers. The use of EZIP layers may inhibit saline formation fluid from mixing with non-saline formation fluid.

The size of the reels used to hold the coiled tubing may prohibit transport of the reel using standard moving equipment and roads. Because tube manufacturing facility **2004** is at or near the in situ heat treatment location, the equipment used to move the coiled tubing to the well sites does not have to meet existing road transportation regulations and can be designed to move large reels of tubing. In some embodiments the equipment used to move the reels of tubing is similar to cargo gantries used to move shipping containers at ports and other facilities. In some embodiments, the gantries are wheeled units. In some embodiments, the coiled tubing may be moved using a rail system or other transportation system.

The coiled tubing may be moved from the tubing manufacturing facility to the well site using gantries **2006**. Drilling gantry **2008** may be used at the well site. Several drilling gantries **2008** may be used to form wellbores at different locations. Supply systems for drilling fluid or other needs may be coupled to drilling gantries **2008** from central facilities **2010**.

Drilling gantry **2008** or other equipment may be used to set the conductor for the well. Drilling gantry **2008** takes coiled tubing, passes the coiled tubing through a straightener, and a BHA attached to the tubing is used to drill the wellbore to depth. In some embodiments, a composite coil is positioned in the coiled tubing at tube manufacturing facility **2004**. The composite coil allows the wellbore to be formed without having drilling fluid flowing between the formation and the tubing. The composite coil also allows the BHA to be retrieved from the wellbore. The composite coil may be pulled from the tubing after wellbore formation. The composite coil may be returned to the tubing manufacturing facility to be placed in another length of coiled tubing. In some embodiments, the BHAs are not retrieved from the wellbores.

In some embodiments, drilling gantry **2008** takes the reel of coiled tubing from gantry **2006**. In some embodiments, gantry **2006** is coupled to drilling gantry **2008** during the formation of the wellbore. For example, the coiled tubing may be fed from gantry **2006** to drilling gantry **2008**, or the drilling gantry lifts the cargo gantry to a feed position and the tubing is fed from the cargo gantry to the drilling gantry.

The wellbore may be formed using the bottom hole assembly, coiled tubing and the drilling gantry. The BHA may be self-seeking to the destination. The BHA may form the opening at a fast rate. In some embodiments, the BHA forms the opening at a rate of about 100 m per hour.

After the wellbore is drilled to total depth, the tubing may be suspended from the wellhead. An expansion cone may be used to expand the tubular against the formation. In some embodiments, the drilling gantry is used to install a heater and/or other equipment in the wellbore.

When drilling gantry **2008** is finished at well site **2012**, the drilling gantry may release gantry **2006** with the empty reel or return the empty reel to the gantry. Gantry **2006** may take the empty reel back to tube manufacturing facility **2004** to be loaded with another coiled tube. Gantries **2006** may move on looped path **2014** from tube manufacturing facility **2004** to well sites **2012** and back to the tube manufacturing facility.

Drilling gantry **2008** may be moved to the next well site. Global positioning satellite information, lasers and/or other information may be used to position the drilling gantry at desired locations. Additional wellbores may be formed until all of the wellbores for the in situ heat treatment process are formed.

In some embodiments, positioning and/or tracking system may be utilized to track gantries **2006**, drilling gantries **2008**, coiled tubing reels and other equipment and materials used to develop the in situ heat treatment location. Tracking systems may include bar code tracking systems to ensure equipment and materials arrive where and when needed.

Pieces of formation or rock may protrude or fall into the wellbore due to various failures including rock breakage or plastic deformation during and/or after wellbore formation. Protrusions may interfere with drill string movement and/or the flow of drilling fluids. Protrusions may prevent running tubulars into the wellbore after the drill string has been removed from the wellbore. Significant amounts of material entering or protruding into the wellbore may cause wellbore integrity failure and/or lead to the drill string becoming stuck in the wellbore. Some causes of wellbore integrity failure may be in situ stresses and high pore pressures. Mud weight may be increased to hold back the formation and inhibit

wellbore integrity failure during wellbore formation. When increasing the mud weight is not practical, the wellbore may be reamed.

Reaming the wellbore may be accomplished by moving the drill string up and down one joint while rotating and circulating. Picking the drill string up can be difficult because of material protruding into the borehole above the bit or BHA (bottom hole assembly). Picking up the drill string may be facilitated by placing upward facing cutting structures on the drill bit. Without upward facing cutting structures on the drill bit, the rock protruding into the borehole above the drill bit must be broken by grinding or crushing rather than by cutting. Grinding or crushing may induce additional wellbore failure.

Moving the drill string up and down may induce surging or pressure pulses that contribute to wellbore failure. Pressure surging or fluctuations may be aggravated or made worse by blockage of normal drilling fluid flow by protrusions into the wellbore. Thus, attempts to clear the borehole of debris may cause even more debris to enter the wellbore.

When the wellbore fails further up the drill string than one joint from the drill bit, the drill string must be raised more than one joint. Lifting more than one joint in length may require that joints be removed from the drill string during lifting and placed back on the drill string when lowered. Removing and adding joints requires additional time and labor, and increases the risk of surging as circulation is stopped and started for each joint connection.

In some embodiments, cutting structures may be positioned at various points along the drill string. Cutting structures may be positioned on the drill string at selected locations, for example, where the diameter of the drill string or BHA changes. FIG. **9**A and FIG. **9**B depict cutting structures **2020** located at or near diameter changes in drill string **2016** near to drill bit **2022** and/or BHA **2018**. As depicted in FIG. **9**C, cutting structures **2020** may be positioned at selected locations along the length of BHA **2018** and/or drill string **2016** that has a substantially uniform diameter. Cuttings formed by the cutting structures **2020** may be removed from the wellbore by the normal circulation used during the formation of the wellbore.

FIG. **10** depicts an embodiment of drill bit **2022** including cutting structures **2020**. Drill bit **2022** includes downward facing cutting structures **2020***b* for forming the wellbore. Cutting structures **2020***a* are upwardly facing cutting structures for reaming out the wellbore to remove protrusions from the wellbore.

In some embodiments, some cutting structures may be upwardly facing, some cutting structures may be downwardly facing, and/or some cutting structures may be oriented substantially perpendicular to the drill string. FIG. **11** depicts an embodiment of a portion of drilling string **2016** including upward facing cutting structures **2020***a*, downward facing cutting structures **2020***b*, and cutting structures **2020***c* that are substantially perpendicular to the drill string. Cutting structures **2020***a* may remove protrusions extending into wellbore **452** that would inhibit upward movement of drill string **2016**. Cutting structures **2020***a* may facilitate reaming of wellbore **452** and/or removal of drill string **2016** from the wellbore for drill bit change, BHA maintenance and/or when total depth has been reached. Cutting structures **2020***b* may remove protrusions extending into wellbore **452** that would inhibit downward movement of drill string **2016**. Cutting structures **2020***c* may ensure that enlarged diameter portions of drill string **2016** do not become stuck in wellbore **452**.

Positioning downward facing cutting structures **2020***b* at various locations along a length of the drill string may allow for reaming of the wellbore while the drill bit forms additional borehole at the bottom of the wellbore. The ability to ream while drilling may avoid pressure surges in the wellbore caused by the lifting the drill string. Reaming while drilling allows the wellbore to be reamed without interrupting normal drilling operation. Reaming while drilling allows the wellbore to be formed in less time because a separate reaming operation is avoided. Upward facing cutting structures **2020***a* allow for easy removal of the drill string from the wellbore.

In some embodiments, the drill string includes a plurality of cutting structures positioned along the length of the drill string, but not necessarily along the entire length of the drill string. The cutting structures may be positioned at regular or irregular intervals along the length of the drill string. Positioning cutting structures along the length of the drill string allows the entire wellbore to be reamed without the need to remove the entire drill string from the wellbore.

Cutting structures may be coupled or attached to the drill string using techniques known in the are (for example, by welding). In some embodiments, cutting structures are formed as part of a hinged ring or multi-piece ring that may be bolted, welded, or otherwise attached to the drill string. In some embodiments, the distance that the cutting structures extend beyond the drill string may be adjustable. For example, the cutting element of the cutting structure may include threading and a locking ring that allows for positioning and setting of the cutting element.

In some wellbores, a wash over or over-coring operation may be needed to free or recover an object in the wellbore that is stuck in the wellbore due to caving, closing, or squeezing of the formation around the object. The object may be a canister, tool, drill string, or other item. A wash-over pipe with downward facing cutting structures at the bottom of the pipe may be used. The wash over pipe may also include upward facing cutting structures and downward facing cutting structures at locations near the end of the wash-over pipe. The additional upward facing cutting structures and downward facing cutting structures may facilitate freeing and/or recovery of the object stuck in the wellbore. The formation holding the object may be cut away rather than broken by relying on hydraulics and force to break the portion of the formation holding the stuck object.

A problem in some formations is that the formed borehole begins to close soon after the drill string is removed from the borehole. Boreholes which close up soon after being formed make it difficult to insert objects such as tubulars, canisters, tools, or other equipment into the wellbore. In some embodiments, reaming while drilling applied to the core drill string allows for emplacement of the objects in the center of the core drill pipe. The core drill pipe includes one or more upward facing cutting structures in addition to cutting structures located at the end of the core drill pipe. The core drill pipe may be used to form the wellbore for the object to be inserted in the formation. The object may be positioned in the core of the core drill pipe. Then, the core drill pipe may be removed from the formation. Any parts of the formation that may inhibit removal of the core drill pipe are cut by the upward facing cutting structures as the core drill pipe is removed from the formation.

Replacement canisters may be positioned in the formation using over core drill pipe. First, the existing canister to be replaced is over cored. The existing canister is then pulled from within the core drill pipe without removing the core drill pipe from the borehole. The replacement canister is then run inside of the core drill pipe. Then, the core drill pipe is removed from the borehole. Upward facing cutting structures

positioned along the length of the core drill pipe cut portions of the formation that may inhibit removal of the core drill pipe.

FIG. **12** depicts a schematic drawing of a drilling system. Pilot bit **432** may form an opening in the formation. Pilot bit **432** may be followed by final diameter bit **434**. In some embodiments, pilot bit **432** may be about 2.5 cm in diameter. Pilot bit **432** may be one or more meters below final diameter bit **434**. Pilot bit **432** may rotate in a first direction and final diameter bit **434** may rotate in the opposite direction. Counter-rotating bits may allow for the formation of the wellbore along a desired path. Standard mud may be used in both pilot bit **432** and final diameter bit **434**. In some embodiments, air or mist may be used as the drilling fluid in one or both bits.

During some in situ heat treatment processes, wellbores may need to be formed in heated formations. Wellbores drilled into hot formation may be additional or replacement heater wells, additional or replacement production wells and/or monitor wells. In some in situ heat treatment processes, a barrier formed around all or a portion of the in situ heat treatment process is formed by freeze wells that form a low temperature zone around the freeze wells. A portion of the cooling capacity of the freeze well equipment may be utilized to cool the equipment needed to drill into the hot formation. Drilling bits may be advanced slowly in hot sections to ensure that the formed wellbore cools sufficiently to preclude drilling problems.

FIG. **13** depicts a schematic drawing of a system for drilling into a hot formation. Cold mud is introduced to drilling bit **434** through conduit **436**. As the bit penetrates into the formation, the mud cools the bit and the surrounding formation. In an embodiment, a pilot hole is formed first and the wellbore is finished with a larger drill bit later. In an embodiment, the finished wellbore is formed without a pilot hole being formed. Well advancement is very slow to ensure sufficient cooling.

FIG. **14** depicts a schematic drawing of a system for drilling into a hot formation. Mud is introduced through conduit **436**. Closed loop system **438** is used to circulate cooling fluid. The cooling fluid cools the drilling mud and the formation as drilling bit **434** slowly penetrates into the formation.

FIG. **15** depicts a schematic drawing of a system for drilling into a hot formation. Mud is introduced through conduit **436**. Pilot bit **432** is followed by final diameter bit **434**. Closed loop system **438** is used to circulate cooling fluid. The cooling fluid cools the drilling mud supplied to the drill bits. The cooled drilling mud cools the formation.

In some embodiments, one or more portions of a wellbore may need to be isolated from other portions of the wellbore to establish zonal isolation. In some embodiments, an expandable may be positioned in the wellbore adjacent to a section of the wellbore that is to be isolated. A pig or hydraulic pressure may be used to enlarge the expandable to establish zonal isolation.

In some embodiments, pathways may be formed in the formation after the wellbores are formed. Pathways may be formed adjacent to heater wellbores and/or adjacent to production wellbores. The pathways may promote better fluid flow and/or better heat conduction. In some embodiments, pathways are formed by hydraulically fracturing the formation. Other fracturing techniques may also be used. In some embodiments, small diameter bores may be formed in the formation. In some embodiments, heating the formation may expand and close or substantially close the fractures or bores formed in the formation. The fractures or holes may extend when the formation is heated. The presence of fractures of holes may increase heat conduction in the formation.

Some wellbores formed in the formation may be used to facilitate formation of a perimeter barrier around a treatment area. Heat sources in the treatment area may heat hydrocarbons in the formation within the treatment area. The perimeter barrier may be, but is not limited to, a low temperature or frozen barrier formed by freeze wells, dewatering wells, a grout wall formed in the formation, a sulfur cement barrier, a barrier formed by a gel produced in the formation, a barrier formed by precipitation of salts in the formation, a barrier formed by a polymerization reaction in the formation, and/or sheets driven into the formation. Heat sources, production wells, injection wells, dewatering wells, and/or monitoring wells may be installed in the treatment area defined by the barrier prior to, simultaneously with, or after installation of the barrier.

A low temperature zone around at least a portion of a treatment area may be formed by freeze wells. In an embodiment, refrigerant is circulated through freeze wells to form low temperature zones around each freeze well. The freeze wells are placed in the formation so that the low temperature zones overlap and form a low temperature zone around the treatment area. The low temperature zone established by freeze wells is maintained below the freezing temperature of aqueous fluid in the formation. Aqueous fluid entering the low temperature zone freezes and forms the frozen barrier. In other embodiments, the freeze barrier is formed by batch operated freeze wells. A cold fluid, such as liquid nitrogen, is introduced into the freeze wells to form low temperature zones around the freeze wells. The fluid is replenished as needed.

In some embodiments, two or more rows of freeze wells are located about all or a portion of the perimeter of the treatment area to form a thick interconnected low temperature zone. Thick low temperature zones may be formed adjacent to areas in the formation where there is a high flow rate of aqueous fluid in the formation. The thick barrier may ensure that breakthrough of the frozen barrier established by the freeze wells does not occur.

In some embodiments, a double barrier system is used to isolate a treatment area. The double barrier system may be formed with a first barrier and a second barrier. The first barrier may be formed around at least a portion of the treatment area to inhibit fluid from entering or exiting the treatment area. The second barrier may be formed around at least a portion of the first barrier to isolate an inter-barrier zone between the first barrier and the second barrier. The inter-barrier zone may have a thickness from about 1 m to about 300 m. In some embodiments, the thickness of the inter-barrier zone is from about 10 m to about 100 m, or from about 20 m to about 50 m.

The double barrier system may allow greater project depths than a single barrier system. Greater depths are possible with the double barrier system because the stepped differential pressures across the first barrier and the second barrier is less than the differential pressure across a single barrier. The smaller differential pressures across the first barrier and the second barrier make a breach of the double barrier system less likely to occur at depth for the double barrier system as compared to the single barrier system.

The double barrier system reduces the probability that a barrier breach will affect the treatment area or the formation on the outside of the double barrier. That is, the probability that the location and/or time of occurrence of the breach in the first barrier will coincide with the location and/or time of occurrence of the breach in the second barrier is low, especially if the distance between the first barrier and the second barrier is relatively large (for example, greater than about 15

m). Having a double barrier may reduce or eliminate influx of fluid into the treatment area following a breach of the first barrier or the second barrier. The treatment area may not be affected if the second barrier breaches. If the first barrier breaches, only a portion of the fluid in the inter-barrier zone is able to enter the contained zone. Also, fluid from the contained zone will not pass the second barrier. Recovery from a breach of a barrier of the double barrier system may require less time and fewer resources than recovery from a breach of a single barrier system. For example, reheating a treatment area zone following a breach of a double barrier system may require less energy than reheating a similarly sized treatment area zone following a breach of a single barrier system.

The first barrier and the second barrier may be the same type of barrier or different types of barriers. In some embodiments, the first barrier and the second barrier are formed by freeze wells. In some embodiments, the first barrier is formed by freeze wells, and the second barrier is a grout wall. The grout wall may be formed of cement, sulfur, sulfur cement, or combinations thereof. In some embodiments, a portion of the first barrier and/or a portion of the second barrier is a natural barrier, such as an impermeable rock formation.

Vertically positioned freeze wells and/or horizontally positioned freeze wells may be positioned around sides of the treatment area. If the upper layer (the overburden) or the lower layer (the underburden) of the formation is likely to allow fluid flow into the treatment area or out of the treatment area, horizontally positioned freeze wells may be used to form an upper and/or a lower barrier for the treatment area. In some embodiments, an upper barrier and/or a lower barrier may not be necessary if the upper layer and/or the lower layer are at least substantially impermeable. If the upper freeze barrier is formed, portions of heat sources, production wells, injection wells, and/or dewatering wells that pass through the low temperature zone created by the freeze wells forming the upper freeze barrier wells may be insulated and/or heat traced so that the low temperature zone does not adversely affect the functioning of the heat sources, production wells, injection wells and/or dewatering wells passing through the low temperature zone.

Spacing between adjacent freeze wells may be a function of a number of different factors. The factors may include, but are not limited to, physical properties of formation material, type of refrigeration system, coldness and thermal properties of the refrigerant, flow rate of material into or out of the treatment area, time for forming the low temperature zone, and economic considerations. Consolidated or partially consolidated formation material may allow for a large separation distance between freeze wells. A separation distance between freeze wells in consolidated or partially consolidated formation material may be from about 3 m to about 20 m, about 4 m to about 15 m, or about 5 m to about 10 m. In an embodiment, the spacing between adjacent freeze wells is about 5 m. Spacing between freeze wells in unconsolidated or substantially unconsolidated formation material, such as in tar sand, may need to be smaller than spacing in consolidated formation material. A separation distance between freeze wells in unconsolidated material may be from about 1 m to about 5 m.

Freeze wells may be placed in the formation so that there is minimal deviation in orientation of one freeze well relative to an adjacent freeze well. Excessive deviation may create a large separation distance between adjacent freeze wells that may not permit formation of an interconnected low temperature zone between the adjacent freeze wells. Factors that influence the manner in which freeze wells are inserted into the ground include, but are not limited to, freeze well insertion time, depth that the freeze wells are to be inserted, formation properties, desired well orientation, and economics.

Relatively low depth wellbores for freeze wells may be impacted and/or vibrationally inserted into some formations. Wellbores for freeze wells may be impacted and/or vibrationally inserted into formations to depths from about 1 m to about 100 m without excessive deviation in orientation of freeze wells relative to adjacent freeze wells in some types of formations.

Wellbores for freeze wells placed deep in the formation, or wellbores for freeze wells placed in formations with layers that are difficult to impact or vibrate a well through, may be placed in the formation by directional drilling and/or geosteering. Acoustic signals, electrical signals, magnetic signals, and/or other signals produced in a first wellbore may be used to guide directionally drilling of adjacent wellbores so that desired spacing between adjacent wells is maintained. Tight control of the spacing between wellbores for freeze wells is an important factor in minimizing the time for completion of barrier formation.

In some embodiments, one or more portions of freeze wells may be angled in the formation. The freeze wells may be angled in the formation adjacent to aquifers. In some embodiments, the angled portions are angled outwards from the treatment area. In some embodiments, the angled portions may be angled inwards towards the treatment area. The angled portions of the freeze wells allow extra length of freeze well to be positioned in the aquifer zones. Also, the angled portions of the freeze wells may reduce the shear load applied to the frozen barrier by water flowing in the aquifer.

After formation of the wellbore for the freeze well, the wellbore may be backflushed with water adjacent to the part of the formation that is to be reduced in temperature to form a portion of the freeze barrier. The water may displace drilling fluid remaining in the wellbore. The water may displace indigenous gas in cavities adjacent to the formation. In some embodiments, the wellbore is filled with water from a conduit up to the level of the overburden. In some embodiments, the wellbore is backflushed with water in sections. The wellbore may be treated in sections having lengths of about 6 m, 10 m, 14 m, 17 m, or greater. Pressure of the water in the wellbore is maintained below the fracture pressure of the formation. In some embodiments, the water, or a portion of the water is removed from the wellbore, and a freeze well is placed in the formation.

FIG. **16** depicts an embodiment of freeze well **440**. Freeze well **440** may include canister **442**, inlet conduit **444**, spacers **446**, and wellcap **448**. Spacers **446** may position inlet conduit **444** in canister **442** so that an annular space is formed between the canister and the conduit. Spacers **446** may promote turbulent flow of refrigerant in the annular space between inlet conduit **444** and canister **442**, but the spacers may also cause a significant fluid pressure drop. Turbulent fluid flow in the annular space may be promoted by roughening the inner surface of canister **442**, by roughening the outer surface of inlet conduit **444**, and/or by having a small cross-sectional area annular space that allows for high refrigerant velocity in the annular space. In some embodiments, spacers are not used. Wellhead **450** may suspend canister **442** in wellbore **452**.

Formation refrigerant may flow through cold side conduit **454** from a refrigeration unit to inlet conduit **444** of freeze well **440**. The formation refrigerant may flow through an annular space between inlet conduit **444** and canister **442** to warm side conduit **456**. Heat may transfer from the formation to canister **442** and from the canister to the formation refrigerant in the annular space. Inlet conduit **444** may be insulated

to inhibit heat transfer to the formation refrigerant during passage of the formation refrigerant into freeze well **440**. In an embodiment, inlet conduit **444** is a high density polyethylene tube. At cold temperatures, some polymers may exhibit a large amount of thermal contraction. For example, a 260 m initial length of polyethylene conduit subjected to a temperature of about −25° C. may contract by 6 m or more. If a high density polyethylene conduit, or other polymer conduit, is used, the large thermal contraction of the material must be taken into account in determining the final depth of the freeze well. For example, the freeze well may be drilled deeper than needed, and the conduit may be allowed to shrink back during use. In some embodiments, inlet conduit **444** is an insulated metal tube. In some embodiments, the insulation may be a polymer coating, such as, but not limited to, polyvinylchloride, high density polyethylene, and/or polystyrene.

Freeze well **440** may be introduced into the formation using a coiled tubing rig. In an embodiment, canister **442** and inlet conduit **444** are wound on a single reel. The coiled tubing rig introduces the canister and inlet conduit **444** into the formation. In an embodiment, canister **442** is wound on a first reel and inlet conduit **444** is wound on a second reel. The coiled tubing rig introduces canister **442** into the formation. Then, the coiled tubing rig is used to introduce inlet conduit **444** into the canister. In other embodiments, freeze well is assembled in sections at the wellbore site and introduced into the formation.

An insulated section of freeze well **440** may be placed adjacent to overburden **458**. An uninsulated section of freeze well **440** may be placed adjacent to layer or layers **460** where a low temperature zone is to be formed. In some embodiments, uninsulated sections of the freeze wells may be positioned adjacent only to aquifers or other permeable portions of the formation that would allow fluid to flow into or out of the treatment area. Portions of the formation where uninsulated sections of the freeze wells are to be placed may be determined using analysis of cores and/or logging techniques.

Various types of refrigeration systems may be used to form a low temperature zone. Determination of an appropriate refrigeration system may be based on many factors, including, but not limited to: a type of freeze well; a distance between adjacent freeze wells; a refrigerant; a time frame in which to form a low temperature zone; a depth of the low temperature zone; a temperature differential to which the refrigerant will be subjected; one or more chemical and/or physical properties of the refrigerant; one or more environmental concerns related to potential refrigerant releases, leaks or spills; one or more economic factors; water flow rate in the formation; composition and/or properties of formation water including the salinity of the formation water; and one or more properties of the formation such as thermal conductivity, thermal diffusivity, and heat capacity.

A circulated fluid refrigeration system may utilize a liquid refrigerant (formation refrigerant) that is circulated through freeze wells. Some of the desired properties for the formation refrigerant are: low working temperature, low viscosity at and near the working temperature, high density, high specific heat capacity, high thermal conductivity, low cost, low corrosiveness, and low toxicity. A low working temperature of the formation refrigerant allows a large low temperature zone to be established around a freeze well. The low working temperature of formation refrigerant should be about −20° C. or lower. Formation refrigerants having low working temperatures of at least −60° C. may include aqua ammonia, potassium formate solutions such as Dynalene® HC-50 (Dynalene® Heat Transfer Fluids (Whitehall, Pa., U.S.A.)) or FREEZIUM® (Kemira Chemicals (Helsinki, Finland)); silicone heat transfer fluids such as Syltherm XLT® (Dow Corning Corporation (Midland, Mich., U.S.A.); hydrocarbon refrigerants such as propylene; and chlorofluorocarbons such as R-22. Aqua ammonia is a solution of ammonia and water with a weight percent of ammonia between about 20% and about 40%. Aqua ammonia has several properties and characteristics that make use of aqua ammonia as the formation refrigerant desirable. Such properties and characteristics include, but are not limited to, a very low freezing point, a low viscosity, ready availability, and low cost.

Formation refrigerant that is capable of being chilled below a freezing temperature of aqueous formation fluid may be used to form the low temperature zone around the treatment area. The following equation (the Sanger equation) may be used to model the time t1 needed to form a frozen barrier of radius R around a freeze well having a surface temperature of Ts:

$$t_1 = \frac{R^2 L_1}{4k_f v_s}\left(2\ln\frac{R}{r_o} - 1 + \frac{c_{vf} v_s}{L_1}\right) \quad \text{(EQN. 2)}$$

in which:

$$L_1 = L\frac{a_r^2 - 1}{2\ln a_r} c_{vu} v_o.$$

$$a_r = \frac{R_A}{R}.$$

In these equations, k_f is the thermal conductivity of the frozen material; c_{vf} and c_{vu} are the volumetric heat capacity of the frozen and unfrozen material, respectively; r_o is the radius of the freeze well; v_s is the temperature difference between the freeze well surface temperature T_s and the freezing point of water T_o; v_o is the temperature difference between the ambient ground temperature T_g and the freezing point of water T_o; L is the volumetric latent heat of freezing of the formation; R is the radius at the frozen-unfrozen interface; and R_A is a radius at which there is no influence from the refrigeration pipe. The Sanger equation may provide a conservative estimate of the time needed to form a frozen barrier of radius R because the equation does not take into consideration superposition of cooling from other freeze wells. The temperature of the formation refrigerant is an adjustable variable that may significantly affect the spacing between freeze wells.

EQN. 2 implies that a large low temperature zone may be formed by using a refrigerant having an initial temperature that is very low. The use of formation refrigerant having an initial cold temperature of about −30° C. or lower is desirable. Formation refrigerants having initial temperatures warmer than about −30° C. may also be used, but such formation refrigerants require longer times for the low temperature zones produced by individual freeze wells to connect. In addition, such formation refrigerants may require the use of closer freeze well spacings and/or more freeze wells.

The physical properties of the material used to construct the freeze wells may be a factor in the determination of the coldest temperature of the formation refrigerant used to form the low temperature zone around the treatment area. Carbon steel may be used as a construction material of freeze wells. ASTM A333 grade 6 steel alloys and ASTM A333 grade 3 steel alloys may be used for low temperature applications.

ASTM A333 grade 6 steel alloys typically contain little or no nickel and have a low working temperature limit of about −50° C. ASTM A333 grade 3 steel alloys typically contain nickel and have a much colder low working temperature limit. The nickel in the ASTM A333 grade 3 alloy adds ductility at cold temperatures, but also significantly raises the cost of the metal. In some embodiments, the coldest temperature of the refrigerant is from about −35° C. to about −55° C., from about −38° C. to about −47° C., or from about −40° C. to about −45° C. to allow for the use of ASTM A333 grade 6 steel alloys for construction of canisters for freeze wells. Stainless steels, such as 304 stainless steel, may be used to form freeze wells, but the cost of stainless steel is typically much more than the cost of ASTM A333 grade 6 steel alloy.

In some embodiments, the metal used to form the canisters of the freeze wells may be provided as pipe. In some embodiments, the metal used to form the canisters of the freeze wells may be provided in sheet form. The sheet metal may be longitudinally welded to form pipe and/or coiled tubing. Forming the canisters from sheet metal may improve the economics of the system by allowing for coiled tubing insulation and by reducing the equipment and manpower needed to form and install the canisters using pipe.

A refrigeration unit may be used to reduce the temperature of formation refrigerant to the low working temperature. In some embodiments, the refrigeration unit may utilize an ammonia vaporization cycle. Refrigeration units are available from Cool Man Inc. (Milwaukee, Wis., U.S.A.), Gartner Refrigeration & Manufacturing (Minneapolis, Minn., U.S.A.), and other suppliers. In some embodiments, a cascading refrigeration system may be utilized with a first stage of ammonia and a second stage of carbon dioxide. The circulating refrigerant through the freeze wells may be 30% by weight ammonia in water (aqua ammonia). Alternatively, a single stage carbon dioxide refrigeration system may be used.

In some embodiments, refrigeration systems for forming a low temperature barrier for a treatment area may be installed and activated before freeze wells are formed in the formation. As the freeze well wellbores are formed, freeze wells may be installed in the wellbores. Refrigerant may be circulated through the wellbores soon after the freeze well is installed into the wellbore. Limiting the time between wellbore formation and cooling initiation may limit or inhibit cross mixing of formation water between different aquifers.

Grout may be used in combination with freeze wells to provide a barrier for the in situ heat treatment process. The grout fills cavities (vugs) in the formation and reduces the permeability of the formation. Grout may have higher thermal conductivity than gas and/or formation fluid that fills cavities in the formation. Placing grout in the cavities may allow for faster low temperature zone formation. The grout forms a perpetual barrier in the formation that may strengthen the formation. The use of grout in unconsolidated or substantially unconsolidated formation material may allow for larger well spacing than is possible without the use of grout. The combination of grout and the low temperature zone formed by freeze wells may constitute a double barrier for environmental regulation purposes. In some embodiments, the grout is introduced into the formation as a liquid, and the liquid sets in the formation to form a solid. The grout may be any type of grout, including but not limited to, fine cement, micro fine cement, sulfur, sulfur cement, viscous thermoplastics, and/or waxes. The grout may include surfactants, stabilizers or other chemicals that modify the properties of the grout. For example, the presence of surfactant in the grout may promote entry of the grout into small openings in the formation.

Grout may be introduced into the formation through freeze well wellbores. The grout may be allowed to set. The integrity of the grout wall may be checked. The integrity of the grout wall may be checked by logging techniques and/or by hydrostatic testing. If the permeability of a grouted section is too high, additional grout may be introduced into the formation through freeze well wellbores. After the permeability of the grouted section is sufficiently reduced, freeze wells may be installed in the freeze well wellbores.

Grout may be injected into the formation at a pressure that is high, but below the fracture pressure of the formation. In some embodiments, grouting is performed in 16 m increments in the freeze wellbore. Larger or smaller increments may be used if desired. In some embodiments, grout is only applied to certain portions of the formation. For example, grout may be applied to the formation through the freeze wellbore only adjacent to aquifer zones and/or to relatively high permeability zones (for example, zones with a permeability greater than about 0.1 darcy). Applying grout to aquifers may inhibit migration of water from one aquifer to a different aquifer. For grout placed in the formation through freeze well wellbores, the grout may inhibit water migration between aquifers during formation of the low temperature zone. The grout may also inhibit water migration between aquifers when an established low temperature zone is allowed to thaw.

In some embodiments, the grout used to form a barrier may be fine cement and micro fine cement. Cement may provide structural support in the formation. Fine cement may be ASTM type 3 Portland cement. Fine cement may be less expensive than micro fine cement. In an embodiment, a freeze wellbore is formed in the formation. Selected portions of the freeze wellbore are grouted using fine cement. Then, micro fine cement is injected into the formation through the freeze wellbore. The fine cement may reduce the permeability down to about 10 millidarcy. The micro fine cement may further reduce the permeability to about 0.1 millidarcy. After the grout is introduced into the formation, a freeze wellbore canister may be inserted into the formation. The process may be repeated for each freeze well that will be used to form the barrier.

In some embodiments, fine cement is introduced into every other freeze wellbore. Micro fine cement is introduced into the remaining wellbores. For example, grout may be used in a formation with freeze wellbores set at about 5 m spacing. A first wellbore is drilled and fine cement is introduced into the formation through the wellbore. A freeze well canister is positioned in the first wellbore. A second wellbore is drilled 10 m away from the first wellbore. Fine cement is introduced into the formation through the second wellbore. A freeze well canister is positioned in the second wellbore. A third wellbore is drilled between the first wellbore and the second wellbore. In some embodiments, grout from the first and/or second wellbores may be detected in the cuttings of the third wellbore. Micro fine cement is introduced into the formation through the third wellbore. A freeze wellbore canister is positioned in the third wellbore. The same procedure is used to form the remaining freeze wells that will form the barrier around the treatment area.

In some embodiments, wax may be used to form a grout barrier. Wax barriers may be formed in wet, dry or oil wetted formations. Liquid wax introduced into the formation may permeate into adjacent rock and fractures in the formation. Liquid wax may permeate into rock to fill microscopic as well as macroscopic pores and vugs in the rock. The wax solidifies to form a grout barrier that inhibits fluid flow into or out of a treatment area. A wax grout barrier may provide a minimal

amount of structural support in the formation. Molten wax may reduce the strength of poorly consolidated soil by reducing inter-grain friction so that the poorly consolidated soil sloughs or liquefies. Poorly consolidated layers may be consolidated by use of cement or other binding agents before introduction of molten wax.

The wax of a barrier may be a branched paraffin to, for example, inhibit biological degradation of the wax. The wax may include stabilizers, surfactants or other chemicals that modify the physical and/or chemical properties of the wax. The physical properties may be tailored to meet specific needs. The wax may melt at a relative low temperature (for example, the wax may have a typical melting point of about 52° C.). The temperature at which the wax congeals may be at least 5° C., 10° C., 20° C., or 30° C. above the ambient temperature of the formation prior to any heating of the formation. When molten, the wax may have a relatively low viscosity (for example, 4 to 10 cp at about 99° C.). The flash point of the wax may be relatively high (for example, the flash point may be over 204° C.). The wax may have a density less than the density of water and may have a heat capacity that is less than half the heat capacity of water. The solid wax may have a low thermal conductivity (for example, about 0.18 W/m ° C.) so that the solid wax is a thermal insulator. Waxes suitable for forming a barrier are available as WAXFIX™ from Carter Technologies Company (Sugar Land, Tex., U.S.A.).

In some embodiments, a wax barrier or wax barriers may be used as the barriers for the in situ heat treatment process. In some embodiments, a wax barrier may be used in conjunction with freeze wells that form a low temperature barrier around the treatment area. In some embodiments, the wax barrier is formed and freeze wells are installed in the wellbores used for introducing wax into the formation. In some embodiments, the wax barrier is formed in wellbores offset from the freeze well wellbores. The wax barrier may be on the outside or the inside of the freeze wells. In some embodiments, a wax barrier may be formed on both the inside and outside of the freeze wells. The wax barrier may inhibit water flow in the formation that would inhibit the formation of the low temperature zone by the freeze wells. In some embodiments, a wax barrier is formed in the inter-barrier zone between two freeze barriers of a double barrier system.

Wellbores may be formed in the formation around the treatment area at a close spacing. In some embodiments, the spacing is from about 1.5 m to about 4 m. Low temperature heaters may be inserted in the wellbores. The heaters may operate at temperatures from about 260° C. to about 320° C. so that the temperature at the formation face is below the pyrolysis temperature of hydrocarbons in the formation. The heaters may be activated to heat the formation until the overlap between two adjacent heaters raises the temperature of the zone between the two heaters above the melting temperature of the wax. Heating the formation to obtain superposition of heat with a temperature above the melting temperature of the wax may take one month, two months, or longer. After heating, the heaters may be turned off. Wax may be introduced into the wellbores to form the barrier. The wax may flow into the formation and fill any fractures and porosity that has been heated. The wax congeals when the wax flows to cold regions beyond the heated circumference. This wax barrier formation method may form a more complete barrier than some other methods of wax barrier formation, but the time for heating may be longer than for some of the other methods. Also, if a low temperature barrier is to be formed with the freeze wells placed in the wellbores used for wax injection, the freeze wells will have to remove the heat supplied to the formation to allow for introduction of the wax. The low temperature barrier may take longer to form.

In some embodiments, the wax barrier may be formed using a conduit placed in the wellbore. FIG. **17**A depicts an embodiment of a system for forming a wax barrier in a formation. Wellbore **452** may extend into one or more layers **460** below overburden **458**. Wellbore **452** may be an open wellbore below underburden **458**. One or more of the layers **460** may include fracture systems **462**. One or more of the layers may be vuggy so that the layer or a portion of the layer has a high porosity. Conduit **464** may be positioned in wellbore **452**. In some embodiments, low temperature heater **466** may be strapped or attached to conduit **464**. In some embodiments, conduit **464** may be a heater element. Heater **466** may be operated so that the heater does not cause pyrolysis of hydrocarbons adjacent to the heater. At least a portion of wellbore **452** may be filled with fluid. The fluid may be formation fluid or water. Heater **466** may be activated to heat the fluid. A portion of the heated fluid may move outwards from heater **466** into the formation. The heated fluid may be injected into the fractures and permeable vuggy zones. The heated fluid may be injected into the fractures and permeable vuggy zones by introducing heated wax into wellbore **452** in the annular space between conduit **464** and the wellbore. The introduced wax flows to the areas heated by the fluid and congeals when the fluid reaches cold regions not heated by the fluid. The wax fills fracture systems **462** and permeable vuggy pathways heated by the fluid, but the wax may not permeate through a significant portion of the rock matrix as when the hot wax is introduced into a heated formation as described above. The wax flows into fracture systems **462** a sufficient distance to join with wax injected from an adjacent well so that a barrier to fluid flow through the fracture systems forms when the wax congeals. A portion of wax may congeal along the wall of a fracture or a vug without completely blocking the fracture or filling the vug. The congealed wax may act as an insulator and allow additional liquid wax to flow beyond the congealed portion to penetrate deeply into the formation and form blockages to fluid flow when the wax cools below the melting temperature of the wax.

Wax in the annular space of wellbore **452** between conduit **464** and the formation may be removed through conduit by displacing the wax with water or other fluid. Conduit **464** may be removed and a freeze well may be installed in the wellbore. This method may use less wax than the method described above. The heating of the fluid may be accomplished in less than a week or within a day. The small amount of heat input may allow for quicker formation of a low temperature barrier if freeze wells are to be positioned in the wellbores used to introduce wax into the formation.

In some embodiments, a heater may be suspended in the well without a conduit that allows for removal of excess wax from the wellbore. The wax may be introduced into the well. After wax introduction, the heater may be removed from the well. In some embodiments, a conduit may be positioned in the wellbore, but a heater may not be coupled to the conduit. Hot wax may be circulated through the conduit so that the wax enters fractures systems and/or vugs adjacent to the wellbore.

In some embodiments, wax may be used during the formation of a wellbore to improve inter-zonal isolation and protect a low-pressure zone from inflow from a high-pressure zone. During wellbore formation where a high pressure zone and a low pressure zone are penetrated by a common wellbore, it is possible for the high pressure zone to flow into the low pressure zone and cause an underground blowout. To avoid this,

the wellbore may be formed through the first zone. Then, an intermediate casing may be set and cemented through the first zone. Setting casing may be time consuming and expensive. Instead of setting a casing, wax may be used to seal the first zone. The wax may also inhibit or prevent mixing of high salinity brines from lower, high pressure zones with fresher brines in upper, lower pressure zones.

FIG. **17**B depicts wellbore **452** drilled to a first depth in formation **758**. After the surface casing for wellbore **452** is set and cemented in place, the wellbore is drilled to the first depth which passes through a permeable zone, such as an aquifer. The permeable zone may be fracture system **462'**. In some embodiments, a heater is placed in wellbore **452** to heat the vertical interval of fracture system **462'**. In some embodiments, hot fluid is circulated in wellbore **452** to heat the vertical interval of fracture system **462'**. After heating, molten wax is pumped down wellbore **452**. The molten wax flows a selected distance into fracture system **462'** before the wax cools sufficiently to solidify and form a seal. The molten wax is introduced into formation **758** at a pressure below the fracture pressure of the formation. In some embodiments, pressure is maintained on the wellhead until the wax has solidified. In some embodiments, the wax is allowed to cool until the wax in wellbore **452** is almost to the congealing temperature of the wax. The wax in wellbore **452** may then be displaced out of the wellbore. The wax makes the portion of formation **758** near wellbore **452** into a substantially impermeable zone. Wellbore **452** may be drilled to depth through one or more permeable zones that are at higher pressures than the pressure in the first permeable zone, such as fracture system **462"**. Congealed wax in fracture system **462'** may inhibit blowout into the lower pressure zone. FIG. **17**C depicts wellbore **452** drilled to depth with congealed wax **492** in formation **758**.

In some embodiments, wax may be used to contain and inhibit migration in a subsurface formation that has liquid hydrocarbon contaminants (for example, compounds such as benzene, toluene, ethylbenzene and xylene) condensed in fractures in the formation. The location of the contaminants may be surrounded with heated wax injection wells. Wax may be introduced into the wells to form an outer wax barrier. The wax injected into the fractures from the wax injection wells may mix with the contaminants. The contaminants may be solubilized into the wax. When the wax congeals, the contaminants may be permanently contained in the solid wax phase.

In some embodiments, a composition that includes a cross-linkable polymer may be used with or in addition to a wax. Such composition may be provided to the formation as is described above for the wax. The composition may be configured to react and solidify after a selected time in the formation, thereby allowing the composition to be provided as a liquid to the formation. The cross-linkable polymer may include, for example, acrylates, methacrylates, urethanes, and/or epoxies. A cross-linking initiator may be included in the composition. The composition may also include a cross-linking inhibitor. The cross-linking inhibitor may be configured to degrade while in the formation, thereby allowing the composition to solidify.

In situ heat treatment processes and solution mining processes may heat the treatment area, remove mass from the treatment area, and greatly increase the permeability of the treatment area. In certain embodiments, the treatment area after being treated may have a permeability of at least 0.1 darcy. In some embodiments, the treatment area after being treated has a permeability of at least 1 darcy, of at least 10 darcy, or of at least 100 darcy. The increased permeability allows the fluid to spread in the formation into fractures, microfractures, and/or pore spaces in the formation. Outside of the treatment area, the permeability may remain at the initial permeability of the formation. The increased permeability allows fluid introduced to flow easily within the formation.

In certain embodiments, a barrier may be formed in the formation after a solution mining process and/or an in situ heat treatment process by introducing a fluid into the formation. The barrier may inhibit formation fluid from entering the treatment area after the solution mining and/or in situ heat treatment processes have ended. The barrier formed by introducing fluid into the formation may allow for isolation of the treatment area.

The fluid introduced into the formation to form a barrier may include wax, bitumen, heavy oil, sulfur, polymer, gel, saturated saline solution, and/or one or more reactants that react to form a precipitate, solid or high viscosity fluid in the formation. In some embodiments, bitumen, heavy oil, reactants and/or sulfur used to form the barrier are obtained from treatment facilities associated with the in situ heat treatment process. For example, sulfur may be obtained from a Claus process used to treat produced gases to remove hydrogen sulfide and other sulfur compounds.

The fluid may be introduced into the formation as a liquid, vapor, or mixed phase fluid. The fluid may be introduced into a portion of the formation that is at an elevated temperature. In some embodiments, the fluid is introduced into the formation through wells located near a perimeter of the treatment area. The fluid may be directed away from the treatment area. The elevated temperature of the formation maintains or allows the fluid to have a low viscosity so that the fluid moves away from the wells. A portion of the fluid may spread outwards in the formation towards a cooler portion of the formation. The relatively high permeability of the formation allows fluid introduced from one wellbore to spread and mix with fluid introduced from other wellbores. In the cooler portion of the formation, the viscosity of the fluid increases, a portion of the fluid precipitates, and/or the fluid solidifies or thickens so that the fluid forms the barrier to flow of formation fluid into or out of the treatment area.

In some embodiments, a low temperature barrier formed by freeze wells surrounds all or a portion of the treatment area. As the fluid introduced into the formation approaches the low temperature barrier, the temperature of the formation becomes colder. The colder temperature increases the viscosity of the fluid, enhances precipitation, and/or solidifies the fluid to form the barrier to the flow of formation fluid into or out of the formation. The fluid may remain in the formation as a highly viscous fluid or a solid after the low temperature barrier has dissipated.

In certain embodiments, saturated saline solution is introduced into the formation. Components in the saturated saline solution may precipitate out of solution when the solution reaches a colder temperature. The solidified particles may form the barrier to the flow of formation fluid into or out of the formation. The solidified components may be substantially insoluble in formation fluid.

In certain embodiments, brine is introduced into the formation as a reactant. A second reactant, such as carbon dioxide, may be introduced into the formation to react with the brine. The reaction may generate a mineral complex that grows in the formation. The mineral complex may be substantially insoluble to formation fluid. In an embodiment, the brine solution includes a sodium and aluminum solution. The second reactant introduced in the formation is carbon dioxide. The carbon dioxide reacts with the brine solution to produce

dawsonite. The minerals may solidify and form the barrier to the flow of formation fluid into or out of the formation.

In some embodiments, the barrier may be formed around a treatment area using sulfur. Advantageously, elemental sulfur is insoluble in water. Liquid and/or solid sulfur in the formation may form a barrier to formation fluid flow into or out of the treatment area.

A sulfur barrier may be established in the formation during or before initiation of heating to heat the treatment area of the in situ heat treatment process. In some embodiments, sulfur may be introduced into wellbores in the formation that are located between the treatment area and a first barrier (for example, a low temperature barrier established by freeze wells). The formation adjacent to the wellbores that the sulfur is introduced into may be dewatered. In some embodiments, the formation adjacent to the wellbores that the sulfur is introduced into is heated to facilitate removal of water and to prepare the wellbores and adjacent formation for the introduction of sulfur. The formation adjacent to the wellbores may be heated to a temperature below the pyrolysis temperature of hydrocarbons in the formation. The formation may be heated so that the temperature of a portion of the formation between two adjacent heaters is influenced by both heaters. In some embodiments, the heat may increase the permeability of the formation so that a first wellbore is in fluid communication with an adjacent wellbore.

After the formation adjacent to the wellbores is heated, molten sulfur at a temperature below the pyrolysis temperature of hydrocarbons in the formation is introduced into the formation. Over a certain temperature range, the viscosity of molten sulfur increases with increasing temperature. The molten sulfur introduced into the formation may be near the melting temperature of sulfur (about 115° C.) so that the sulfur has a relatively low viscosity (about 4-10 cp). Heaters in the wellbores may be temperature limited heaters with Curie temperatures near the melting temperature of sulfur so that the temperature of the molten sulfur stays relatively constant and below temperatures resulting in the formation of viscous molten sulfur. In some embodiments, the region adjacent to the wellbores may be heated to a temperature above the melting point of sulfur, but below the pyrolysis temperature of hydrocarbons in the formation. The heaters may be turned off and the temperature in the wellbores may be monitored (for example, using a fiber optic temperature monitoring system). When the temperature in the wellbore cools to a temperature near the melting temperature of sulfur, molten sulfur may be introduced into the formation.

The sulfur introduced into the formation is allowed to flow and diffuse into the formation from the wellbores. As the sulfur enters portions of the formation below the melting temperature, the sulfur solidifies and forms a barrier to fluid flow in the formation. Sulfur may be introduced until the formation is not able to accept additional sulfur. Heating may be stopped, and the formation may be allowed to naturally cool so that the sulfur in the formation solidifies. After introduction of the sulfur, the integrity of the formed barrier may be tested using pulse tests and/or tracer tests.

A barrier may be formed around the treatment area after the in situ heat treatment process. The sulfur may form a substantially permanent barrier in the formation. In some embodiments, a low temperature barrier formed by freeze wells surrounds the treatment area. Sulfur may be introduced on one or both sides of the low temperature barrier to form a barrier in the formation. The sulfur may be introduced into the formation as vapor or a liquid. As the sulfur approaches the low temperature barrier, the sulfur may condense and/or solidify in the formation to form the barrier.

In some embodiments, the sulfur may be introduced in the heated portion of the portion. The sulfur may be introduced into the formation through wells located near the perimeter of the treatment area. The temperature of the formation may be hotter than the vaporization temperature of sulfur (about 445° C.). The sulfur may be introduced as a liquid, vapor or mixed phase fluid. If a part of the introduced sulfur is in the liquid phase, the heat of the formation may vaporize the sulfur. The sulfur may flow outwards from the introduction wells towards cooler portions of the formation. The sulfur may condense and/or solidify in the formation to form the barrier.

In some embodiments, the Claus reaction may be used to form sulfur in the formation after the in situ heat treatment process. The Claus reaction is a gas phase equilibrium reaction.

The Claus reaction is:

$$4H_2S+2SO_2 \leftrightarrow 3S_2+4H_2O \quad \text{(EQN. 3)}$$

Hydrogen sulfide may be obtained by separating the hydrogen sulfide from the produced fluid of an ongoing in situ heat treatment process. A portion of the hydrogen sulfide may be burned to form the needed sulfur dioxide. Hydrogen sulfide may be introduced into the formation through a number of wells in the formation. Sulfur dioxide may be introduced into the formation through other wells. The wells used for injecting sulfur dioxide or hydrogen sulfide may have been production wells, heater wells, monitor wells or other type of well during the in situ heat treatment process. The wells used for injecting sulfur dioxide or hydrogen sulfide may be near the perimeter of the treatment area. The number of wells may be enough so that the formation in the vicinity of the injection wells does not cool to a point where the sulfur dioxide and the hydrogen sulfide can form sulfur and condense, rather than remain in the vapor phase. The wells used to introduce the sulfur dioxide into the formation may also be near the perimeter of the treatment area. In some embodiments, the hydrogen sulfide and sulfur dioxide may be introduced into the formation through the same wells (for example, through two conduits positioned in the same wellbore). The hydrogen sulfide and the sulfur dioxide may react in the formation to form sulfur and water. The sulfur may flow outwards in the formation and condense and/or solidify to form the barrier in the formation.

The sulfur barrier may form in the formation beyond the area where hydrocarbons in formation fluid generated by the heat treatment process condense in the formation. Regions near the perimeter of the treated area may be at lower temperatures than the treated area. Sulfur may condense and/or solidify from the vapor phase in these lower temperature regions. Additional hydrogen sulfide, and/or sulfur dioxide may diffuse to these lower temperature regions. Additional sulfur may form by the Claus reaction to maintain an equilibrium concentration of sulfur in the vapor phase. Eventually, a sulfur barrier may form around the treated zone. The vapor phase in the treated region may remain as an equilibrium mixture of sulfur, hydrogen sulfide, sulfur dioxide, water vapor and other vapor products present or evolving from the formation.

The conversion to sulfur is favored at lower temperatures, so the conversion of hydrogen sulfide and sulfur dioxide to sulfur may take place a distance away from the wells that introduce the reactants into the formation. The Claus reaction may result in the formation of sulfur where the temperature of the formation is cooler (for example where the temperature of the formation is at temperatures from about 180° C. to about 240° C.).

A temperature monitoring system may be installed in wellbores of freeze wells and/or in monitor wells adjacent to the freeze wells to monitor the temperature profile of the freeze wells and/or the low temperature zone established by the freeze wells. The monitoring system may be used to monitor progress of low temperature zone formation. The monitoring system may be used to determine the location of high temperature areas, potential breakthrough locations, or breakthrough locations after the low temperature zone has formed. Periodic monitoring of the temperature profile of the freeze wells and/or low temperature zone established by the freeze wells may allow additional cooling to be provided to potential trouble areas before breakthrough occurs. Additional cooling may be provided at or adjacent to breakthroughs and high temperature areas to ensure the integrity of the low temperature zone around the treatment area. Additional cooling may be provided by increasing refrigerant flow through selected freeze wells, installing an additional freeze well or freeze wells, and/or by providing a cryogenic fluid, such as liquid nitrogen, to the high temperature areas. Providing additional cooling to potential problem areas before breakthrough occurs may be more time efficient and cost efficient than sealing a breach, reheating a portion of the treatment area that has been cooled by influx of fluid, and/or remediating an area outside of the breached frozen barrier.

In some embodiments, a traveling thermocouple may be used to monitor the temperature profile of selected freeze wells or monitor wells. In some embodiments, the temperature monitoring system includes thermocouples placed at discrete locations in the wellbores of the freeze wells, in the freeze wells, and/or in the monitoring wells. In some embodiments, the temperature monitoring system comprises a fiber optic temperature monitoring system.

Fiber optic temperature monitoring systems are available from Sensomet (London, United Kingdom), Sensa (Houston, Tex., U.S.A.), Luna Energy (Blacksburg, Va., U.S.A.), Lios Technology GMBH (Cologne, Germany), Oxford Electronics Ltd. (Hampshire, United Kingdom), and Sabeus Sensor Systems (Calabasas, Calif., U.S.A.). The fiber optic temperature monitoring system includes a data system and one or more fiber optic cables. The data system includes one or more lasers for sending light to the fiber optic cable; and one or more computers, software and peripherals for receiving, analyzing, and outputting data. The data system may be coupled to one or more fiber optic cables.

A single fiber optic cable may be several kilometers long. The fiber optic cable may be installed in many freeze wells and/or monitor wells. In some embodiments, two fiber optic cables may be installed in each freeze well and/or monitor well. The two fiber optic cables may be coupled. Using two fiber optic cables per well allows for compensation due to optical losses that occur in the wells and allows for better accuracy of measured temperature profiles.

The fiber optic temperature monitoring system may be used to detect the location of a breach or a potential breach in a frozen barrier. The search for potential breaches may be performed at scheduled intervals, for example, every two or three months. To determine the location of the breach or potential breach, flow of formation refrigerant to the freeze wells of interest is stopped. In some embodiments, the flow of formation refrigerant to all of the freeze wells is stopped. The rise in the temperature profiles, as well as the rate of change of the temperature profiles, provided by the fiber optic temperature monitoring system for each freeze well can be used to determine the location of any breaches or hot spots in the low temperature zone maintained by the freeze wells. The temperature profile monitored by the fiber optic temperature monitoring system for the two freeze wells closest to the hot spot or fluid flow will show the quickest and greatest rise in temperature. A temperature change of a few degrees Centigrade in the temperature profiles of the freeze wells closest to a troubled area may be sufficient to isolate the location of the trouble area. The shut down time of flow of circulation fluid in the freeze wells of interest needed to detect breaches, potential breaches, and hot spots may be on the order of a few hours or days, depending on the well spacing and the amount of fluid flow affecting the low temperature zone.

Fiber optic temperature monitoring systems may also be used to monitor temperatures in heated portions of the formation during in situ heat treatment processes. The fiber of a fiber optic cable used in the heated portion of the formation may be clad with a reflective material to facilitate retention of a signal or signals transmitted down the fiber. In some embodiments, the fiber is clad with gold, copper, nickel, aluminum and/or alloys thereof. The cladding may be formed of a material that is able to withstand chemical and temperature conditions in the heated portion of the formation. For example, gold cladding may allow an optical sensor to be used up to temperatures of 700° C. In some embodiments, the fiber is clad with aluminum. The fiber may be dipped in or run through a bath of liquid aluminum. The clad fiber may then be allowed to cool to secure the aluminum to the fiber. The gold or aluminum cladding may reduce hydrogen darkening of the optical fiber.

A potential source of heat loss from the heated formation is due to reflux in wells. Refluxing occurs when vapors condense in a well and flow into a portion of the well adjacent to the heated portion of the formation. Vapors may condense in the well adjacent to the overburden of the formation to form condensed fluid. Condensed fluid flowing into the well adjacent to the heated formation absorbs heat from the formation. Heat absorbed by condensed fluids cools the formation and necessitates additional energy input into the formation to maintain the formation at a desired temperature. Some fluids that condense in the overburden and flow into the portion of the well adjacent to the heated formation may react to produce undesired compounds and/or coke. Inhibiting fluids from refluxing may significantly improve the thermal efficiency of the in situ heat treatment system and/or the quality of the product produced from the in situ heat treatment system.

For some well embodiments, the portion of the well adjacent to the overburden section of the formation is cemented to the formation. In some well embodiments, the well includes packing material placed near the transition from the heated section of the formation to the overburden. The packing material inhibits formation fluid from passing from the heated section of the formation into the section of the wellbore adjacent to the overburden. Cables, conduits, devices, and/or instruments may pass through the packing material, but the packing material inhibits formation fluid from passing up the wellbore adjacent to the overburden section of the formation.

In some embodiments, one or more baffle systems may be placed in the wellbores to inhibit reflux. The baffle systems may be obstructions to fluid flow into the heated portion of the formation. In some embodiments, refluxing fluid may revaporize on the baffle system before coming into contact with the heated portion of the formation.

In some embodiments, a gas may be introduced into the formation through wellbores to inhibit reflux in the wellbores. In some embodiments, gas may be introduced into wellbores that include baffle systems to inhibit reflux of fluid in the wellbores. The gas may be carbon dioxide, methane, nitrogen or other desired gas. In some embodiments, the introduction of gas may be used in conjunction with one or more baffle

systems in the wellbores. The introduced gas may enhance heat exchange at the baffle systems to help maintain top portions of the baffle systems colder than the lower portions of the baffle systems.

The flow of production fluid up the well to the surface is desired for some types of wells, especially for production wells. Flow of production fluid up the well is also desirable for some heater wells that are used to control pressure in the formation. The overburden, or a conduit in the well used to transport formation fluid from the heated portion of the formation to the surface, may be heated to inhibit condensation on or in the conduit. Providing heat in the overburden, however, may be costly and/or may lead to increased cracking or coking of formation fluid as the formation fluid is being produced from the formation.

To avoid the need to heat the overburden or to heat the conduit passing through the overburden, one or more diverters may be placed in the wellbore to inhibit fluid from refluxing into the wellbore adjacent to the heated portion of the formation. In some embodiments, the diverter retains fluid above the heated portion of the formation. Fluids retained in the diverter may be removed from the diverter using a pump, gas lifting, and/or other fluid removal technique. In certain embodiments, two or more diverters that retain fluid above the heated portion of the formation may be located in the production well. Two or more diverters provide a simple way of separating initial fractions of condensed fluid produced from the in situ heat treatment system. A pump may be placed in each of the diverters to remove condensed fluid from the diverters.

In some embodiments, the diverter directs fluid to a sump below the heated portion of the formation. An inlet for a lift system may be located in the sump. In some embodiments, the intake of the lift system is located in casing in the sump. In some embodiments, the intake of the lift system is located in an open wellbore. The sump is below the heated portion of the formation. The intake of the pump may be located 1 m, 5 m, 10 m, 20 m or more below the deepest heater used to heat the heated portion of the formation. The sump may be at a cooler temperature than the heated portion of the formation. The sump may be more than 10° C., more than 50° C., more than 75° C., or more than 100° C. below the temperature of the heated portion of the formation. A portion of the fluid entering the sump may be liquid. A portion of the fluid entering the sump may condense within the sump. The lift system moves the fluid in the sump to the surface.

Production well lift systems may be used to efficiently transport formation fluid from the bottom of the production wells to the surface. Production well lift systems may provide and maintain the maximum required well drawdown (minimum reservoir producing pressure) and producing rates. The production well lift systems may operate efficiently over a wide range of high temperature/multiphase fluids (gas/vapor/steam/water/hydrocarbon liquids) and production rates expected during the life of a typical project. Production well lift systems may include dual concentric rod pump lift systems, chamber lift systems and other types of lift systems.

Temperature limited heaters may be in configurations and/or may include materials that provide automatic temperature limiting properties for the heater at certain temperatures. In certain embodiments, ferromagnetic materials are used in temperature limited heaters. Ferromagnetic material may self-limit temperature at or near the Curie temperature of the material and/or the phase transformation temperature range to provide a reduced amount of heat when a time-varying current is applied to the material. In certain embodiments, the ferromagnetic material self-limits temperature of the temperature limited heater at a selected temperature that is approximately the Curie temperature and/or in the phase transformation temperature range. In certain embodiments, the selected temperature is within about 35° C., within about 25° C., within about 20° C., or within about 10° C. of the Curie temperature and/or the phase transformation temperature range. In certain embodiments, ferromagnetic materials are coupled with other materials (for example, highly conductive materials, high strength materials, corrosion resistant materials, or combinations thereof) to provide various electrical and/or mechanical properties. Some parts of the temperature limited heater may have a lower resistance (caused by different geometries and/or by using different ferromagnetic and/or non-ferromagnetic materials) than other parts of the temperature limited heater. Having parts of the temperature limited heater with various materials and/or dimensions allows for tailoring the desired heat output from each part of the heater.

Temperature limited heaters may be more reliable than other heaters. Temperature limited heaters may be less apt to break down or fail due to hot spots in the formation. In some embodiments, temperature limited heaters allow for substantially uniform heating of the formation. In some embodiments, temperature limited heaters are able to heat the formation more efficiently by operating at a higher average heat output along the entire length of the heater. The temperature limited heater operates at the higher average heat output along the entire length of the heater because power to the heater does not have to be reduced to the entire heater, as is the case with typical constant wattage heaters, if a temperature along any point of the heater exceeds, or is about to exceed, a maximum operating temperature of the heater. Heat output from portions of a temperature limited heater approaching a Curie temperature and/or the phase transformation temperature range of the heater automatically reduces without controlled adjustment of the time-varying current applied to the heater. The heat output automatically reduces due to changes in electrical properties (for example, electrical resistance) of portions of the temperature limited heater. Thus, more power is supplied by the temperature limited heater during a greater portion of a heating process.

In certain embodiments, the system including temperature limited heaters initially provides a first heat output and then provides a reduced (second heat output) heat output, near, at, or above the Curie temperature and/or the phase transformation temperature range of an electrically resistive portion of the heater when the temperature limited heater is energized by a time-varying current. The first heat output is the heat output at temperatures below which the temperature limited heater begins to self-limit. In some embodiments, the first heat output is the heat output at a temperature about 50° C., about 75° C., about 100° C., or about 125° C. below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic material in the temperature limited heater.

The temperature limited heater may be energized by time-varying current (alternating current or modulated direct current) supplied at the wellhead. The wellhead may include a power source and other components (for example, modulation components, transformers, and/or capacitors) used in supplying power to the temperature limited heater. The temperature limited heater may be one of many heaters used to heat a portion of the formation.

In certain embodiments, the temperature limited heater includes a conductor that operates as a skin effect or proximity effect heater when time-varying current is applied to the conductor. The skin effect limits the depth of current penetration into the interior of the conductor. For ferromagnetic

materials, the skin effect is dominated by the magnetic permeability of the conductor. The relative magnetic permeability of ferromagnetic materials is typically between 10 and 1000 (for example, the relative magnetic permeability of ferromagnetic materials is typically at least 10 and may be at least 50, 100, 500, 1000 or greater). As the temperature of the ferromagnetic material is raised above the Curie temperature, or the phase transformation temperature range, and/or as the applied electrical current is increased, the magnetic permeability of the ferromagnetic material decreases substantially and the skin depth expands rapidly (for example, the skin depth expands as the inverse square root of the magnetic permeability). The reduction in magnetic permeability results in a decrease in the AC or modulated DC resistance of the conductor near, at, or above the Curie temperature, the phase transformation temperature range, and/or as the applied electrical current is increased. When the temperature limited heater is powered by a substantially constant current source, portions of the heater that approach, reach, or are above the Curie temperature and/or the phase transformation temperature range may have reduced heat dissipation. Sections of the temperature limited heater that are not at or near the Curie temperature and/or the phase transformation temperature range may be dominated by skin effect heating that allows the heater to have high heat dissipation due to a higher resistive load.

Curie temperature heaters have been used in soldering equipment, heaters for medical applications, and heating elements for ovens (for example, pizza ovens). Some of these uses are disclosed in U.S. Pat. No. 5,579,575 to Lamome et al.; U.S. Pat. No. 5,065,501 to Henschen et al.; and U.S. Pat. No. 5,512,732 to Yagnik et al., all of which are incorporated by reference as if fully set forth herein. U.S. Pat. No. 4,849,611 to Whitney et al., which is incorporated by reference as if fully set forth herein, describes a plurality of discrete, spaced-apart heating units including a reactive component, a resistive heating component, and a temperature responsive component.

An advantage of using the temperature limited heater to heat hydrocarbons in the formation is that the conductor is chosen to have a Curie temperature and/or a phase transformation temperature range in a desired range of temperature operation. Operation within the desired operating temperature range allows substantial heat injection into the formation while maintaining the temperature of the temperature limited heater, and other equipment, below design limit temperatures. Design limit temperatures are temperatures at which properties such as corrosion, creep, and/or deformation are adversely affected. The temperature limiting properties of the temperature limited heater inhibit overheating or burnout of the heater adjacent to low thermal conductivity "hot spots" in the formation. In some embodiments, the temperature limited heater is able to lower or control heat output and/or withstand heat at temperatures above 25° C., 37° C., 100° C., 250° C., 500° C., 700° C., 800° C., 900° C., or higher up to 1131° C., depending on the materials used in the heater.

The temperature limited heater allows for more heat injection into the formation than constant wattage heaters because the energy input into the temperature limited heater does not have to be limited to accommodate low thermal conductivity regions adjacent to the heater. For example, in Green River oil shale there is a difference of at least a factor of 3 in the thermal conductivity of the lowest richness oil shale layers and the highest richness oil shale layers. When heating such a formation, substantially more heat is transferred to the formation with the temperature limited heater than with the conventional heater that is limited by the temperature at low thermal conductivity layers. The heat output along the entire length of the conventional heater needs to accommodate the low thermal conductivity layers so that the heater does not overheat at the low thermal conductivity layers and burn out. The heat output adjacent to the low thermal conductivity layers that are at high temperature will reduce for the temperature limited heater, but the remaining portions of the temperature limited heater that are not at high temperature will still provide high heat output. Because heaters for heating hydrocarbon formations typically have long lengths (for example, at least 10 m, 100 m, 300 m, 500 m, 1 km or more up to about 10 km), the majority of the length of the temperature limited heater may be operating below the Curie temperature and/or the phase transformation temperature range while only a few portions are at or near the Curie temperature and/or the phase transformation temperature range of the temperature limited heater.

The use of temperature limited heaters allows for efficient transfer of heat to the formation. Efficient transfer of heat allows for reduction in time needed to heat the formation to a desired temperature. For example, in Green River oil shale, pyrolysis typically requires 9.5 years to 10 years of heating when using a 12 m heater well spacing with conventional constant wattage heaters. For the same heater spacing, temperature limited heaters may allow a larger average heat output while maintaining heater equipment temperatures below equipment design limit temperatures. Pyrolysis in the formation may occur at an earlier time with the larger average heat output provided by temperature limited heaters than the lower average heat output provided by constant wattage heaters. For example, in Green River oil shale, pyrolysis may occur in 5 years using temperature limited heaters with a 12 m heater well spacing. Temperature limited heaters counteract hot spots due to inaccurate well spacing or drilling where heater wells come too close together. In certain embodiments, temperature limited heaters allow for increased power output over time for heater wells that have been spaced too far apart, or limit power output for heater wells that are spaced too close together. Temperature limited heaters also supply more power in regions adjacent the overburden and underburden to compensate for temperature losses in these regions.

Temperature limited heaters may be advantageously used in many types of formations. For example, in tar sands formations or relatively permeable formations containing heavy hydrocarbons, temperature limited heaters may be used to provide a controllable low temperature output for reducing the viscosity of fluids, mobilizing fluids, and/or enhancing the radial flow of fluids at or near the wellbore or in the formation. Temperature limited heaters may be used to inhibit excess coke formation due to overheating of the near wellbore region of the formation.

The use of temperature limited heaters, in some embodiments, eliminates or reduces the need for expensive temperature control circuitry. For example, the use of temperature limited heaters eliminates or reduces the need to perform temperature logging and/or the need to use fixed thermocouples on the heaters to monitor potential overheating at hot spots.

In certain embodiments, phase transformation (for example, crystalline phase transformation or a change in the crystal structure) of materials used in a temperature limited heater change the selected temperature at which the heater self-limits. Ferromagnetic material used in the temperature limited heater may have a phase transformation (for example, a transformation from ferrite to austenite) that decreases the magnetic permeability of the ferromagnetic material. This reduction in magnetic permeability is similar to reduction in

magnetic permeability due to the magnetic transition of the ferromagnetic material at the Curie temperature. The Curie temperature is the magnetic transition temperature of the ferrite phase of the ferromagnetic material. The reduction in magnetic permeability results in a decrease in the AC or modulated DC resistance of the temperature limited heater near, at, or above the temperature of the phase transformation and/or the Curie temperature of the ferromagnetic material.

The phase transformation of the ferromagnetic material may occur over a temperature range. The temperature range of the phase transformation depends on the ferromagnetic material and may vary, for example, over a range of about 5° C. to a range of about 200° C. Because the phase transformation takes place over a temperature range, the reduction in the magnetic permeability due to the phase transformation takes place over the temperature range. The reduction in magnetic permeability may also occur hysteretically over the temperature range of the phase transformation. In some embodiments, the phase transformation back to the lower temperature phase of the ferromagnetic material is slower than the phase transformation to the higher temperature phase (for example, the transition from austenite back to ferrite is slower than the transition from ferrite to austenite). The slower phase transformation back to the lower temperature phase may cause hysteretic operation of the heater at or near the phase transformation temperature range that allows the heater to slowly increase to higher resistance after the resistance of the heater reduces due to high temperature.

In some embodiments, the phase transformation temperature range overlaps with the reduction in the magnetic permeability when the temperature approaches the Curie temperature of the ferromagnetic material. The overlap may produce a faster drop in electrical resistance versus temperature than if the reduction in magnetic permeability is solely due to the temperature approaching the Curie temperature. The overlap may also produce hysteretic behavior of the temperature limited heater near the Curie temperature and/or in the phase transformation temperature range.

In certain embodiments, the hysteretic operation due to the phase transformation is a smoother transition than the reduction in magnetic permeability due to magnetic transition at the Curie temperature. The smoother transition may be easier to control (for example, electrical control using a process control device that interacts with the power supply) than the sharper transition at the Curie temperature. In some embodiments, the Curie temperature is located inside the phase transformation range for selected metallurgies used in temperature limited heaters. This phenomenon provides temperature limited heaters with the smooth transition properties of the phase transformation in addition to a sharp and definite transition due to the reduction in magnetic properties at the Curie temperature. Such temperature limited heaters may be easy to control (due to the phase transformation) while providing finite temperature limits (due to the sharp Curie temperature transition). Using the phase transformation temperature range instead of and/or in addition to the Curie temperature in temperature limited heaters increases the number and range of metallurgies that may be used for temperature limited heaters.

In certain embodiments, alloy additions are made to the ferromagnetic material to adjust the temperature range of the phase transformation. For example, adding carbon to the ferromagnetic material may increase the phase transformation temperature range and lower the onset temperature of the phase transformation. Adding titanium to the ferromagnetic material may increase the onset temperature of the phase transformation and decrease the phase transformation temperature range. Alloy compositions may be adjusted to provide desired Curie temperature and phase transformation properties for the ferromagnetic material. The alloy composition of the ferromagnetic material may be chosen based on desired properties for the ferromagnetic material (such as, but not limited to, magnetic permeability transition temperature or temperature range, resistance versus temperature profile, or power output). Addition of titanium may allow higher Curie temperatures to be obtained when adding cobalt to 410 stainless steel by raising the ferrite to austenite phase transformation temperature range to a temperature range that is above, or well above, the Curie temperature of the ferromagnetic material.

In some embodiments, temperature limited heaters are more economical to manufacture or make than standard heaters. Typical ferromagnetic materials include iron, carbon steel, or ferritic stainless steel. Such materials are inexpensive as compared to nickel-based heating alloys (such as nichrome, Kanthal™ (Bulten-Kanthal AB, Sweden), and/or LOHM™ (Driver-Harris Company, Harrison, N.J., U.S.A.)) typically used in insulated conductor (mineral insulated cable) heaters. In one embodiment of the temperature limited heater, the temperature limited heater is manufactured in continuous lengths as an insulated conductor heater to lower costs and improve reliability.

In some embodiments, the temperature limited heater is placed in the heater well using a coiled tubing rig. A heater that can be coiled on a spool may be manufactured by using metal such as ferritic stainless steel (for example, 409 stainless steel) that is welded using electrical resistance welding (ERW). U.S. Pat. No. 7,032,809 to Hopkins, which is incorporated by reference as if fully set forth herein, describes forming seam-welded pipe. To form a heater section, a metal strip from a roll is passed through a former where it is shaped into a tubular and then longitudinally welded using ERW.

FIG. **18** depicts an embodiment of a device for longitudinal welding (seam-welding) of a tubular using ERW. Metal strip **474** is shaped into tubular form as it passes through ERW coil **476**. Metal strip **474** is then welded into a tubular inside shield **478**. As metal strip **474** is joined inside shield **478**, inert gas (for example, argon or another suitable welding gas) is provided inside the forming tubular by gas inlets **480**. Flushing the tubular with inert gas inhibits oxidation of the tubular as it is formed. Shield **478** may have window **482**. Window **482** allows an operator to visually inspect the welding process. Tubular **484** is formed by the welding process.

In some embodiments, a composite tubular may be formed from the seam-welded tubular. The seam-welded tubular is passed through a second former where a conductive strip (for example, a copper strip) is applied, drawn down tightly on the tubular through a die, and longitudinally welded using ERW. A sheath may be formed by longitudinally welding a support material (for example, steel such as 347H or 347HH) over the conductive strip material. The support material may be a strip rolled over the conductive strip material. An overburden section of the heater may be formed in a similar manner.

In certain embodiments, the overburden section uses a non-ferromagnetic material such as 304 stainless steel or 316 stainless steel instead of a ferromagnetic material. The heater section and overburden section may be coupled using standard techniques such as butt welding using an orbital welder. In some embodiments, the overburden section material (the non-ferromagnetic material) may be pre-welded to the ferromagnetic material before rolling. The pre-welding may eliminate the need for a separate coupling step (for example, butt welding). In an embodiment, a flexible cable (for example, a furnace cable such as a MGT 1000 furnace cable) may be

pulled through the center after forming the tubular heater. An end bushing on the flexible cable may be welded to the tubular heater to provide an electrical current return path. The tubular heater, including the flexible cable, may be coiled onto a spool before installation into a heater well. In an embodiment, the temperature limited heater is installed using the coiled tubing rig. The coiled tubing rig may place the temperature limited heater in a deformation resistant container in the formation. The deformation resistant container may be placed in the heater well using conventional methods.

Temperature limited heaters may be used for heating hydrocarbon formations including, but not limited to, oil shale formations, coal formations, tar sands formations, and formations with heavy viscous oils. Temperature limited heaters may also be used in the field of environmental remediation to vaporize or destroy soil contaminants. Embodiments of temperature limited heaters may be used to heat fluids in a wellbore or sub-sea pipeline to inhibit deposition of paraffin or various hydrates. In some embodiments, a temperature limited heater is used for solution mining a subsurface formation (for example, an oil shale or a coal formation). In certain embodiments, a fluid (for example, molten salt) is placed in a wellbore and heated with a temperature limited heater to inhibit deformation and/or collapse of the wellbore. In some embodiments, the temperature limited heater is attached to a sucker rod in the wellbore or is part of the sucker rod itself. In some embodiments, temperature limited heaters are used to heat a near wellbore region to reduce near wellbore oil viscosity during production of high viscosity crude oils and during transport of high viscosity oils to the surface. In some embodiments, a temperature limited heater enables gas lifting of a viscous oil by lowering the viscosity of the oil without coking the oil. Temperature limited heaters may be used in sulfur transfer lines to maintain temperatures between about 110° C. and about 130° C.

The ferromagnetic alloy or ferromagnetic alloys used in the temperature limited heater determine the Curie temperature of the heater. Curie temperature data for various metals is listed in "American Institute of Physics Handbook," Second Edition, McGraw-Hill, pages 5-170 through 5-176. Ferromagnetic conductors may include one or more of the ferromagnetic elements (iron, cobalt, and nickel) and/or alloys of these elements. In some embodiments, ferromagnetic conductors include iron-chromium (Fe—Cr) alloys that contain tungsten (W) (for example, HCM12A and SAVE12 (Sumitomo Metals Co., Japan) and/or iron alloys that contain chromium (for example, Fe—Cr alloys, Fe—Cr—W alloys, Fe—Cr—V (vanadium) alloys, and Fe—Cr—Nb (Niobium) alloys). Of the three main ferromagnetic elements, iron has a Curie temperature of approximately 770° C.; cobalt (Co) has a Curie temperature of approximately 1131° C.; and nickel has a Curie temperature of approximately 358° C. An iron-cobalt alloy has a Curie temperature higher than the Curie temperature of iron. For example, iron-cobalt alloy with 2% by weight cobalt has a Curie temperature of approximately 800° C.; iron-cobalt alloy with 12% by weight cobalt has a Curie temperature of approximately 900° C.; and iron-cobalt alloy with 20% by weight cobalt has a Curie temperature of approximately 950° C. Iron-nickel alloy has a Curie temperature lower than the Curie temperature of iron. For example, iron-nickel alloy with 20% by weight nickel has a Curie temperature of approximately 720° C., and iron-nickel alloy with 60% by weight nickel has a Curie temperature of approximately 560° C.

Some non-ferromagnetic elements used as alloys raise the Curie temperature of iron. For example, an iron-vanadium alloy with 5.9% by weight vanadium has a Curie temperature of approximately 815° C. Other non-ferromagnetic elements (for example, carbon, aluminum, copper, silicon, and/or chromium) may be alloyed with iron or other ferromagnetic materials to lower the Curie temperature. Non-ferromagnetic materials that raise the Curie temperature may be combined with non-ferromagnetic materials that lower the Curie temperature and alloyed with iron or other ferromagnetic materials to produce a material with a desired Curie temperature and other desired physical and/or chemical properties. In some embodiments, the Curie temperature material is a ferrite such as $NiFe_2O_4$. In other embodiments, the Curie temperature material is a binary compound such as $FeNi_3$ or Fe_3Al.

In some embodiments, the improved alloy includes carbon, cobalt, iron, manganese, silicon, or mixtures thereof. In certain embodiments, the improved alloy includes, by weight: about 0.1% to about 10% cobalt; about 0.1% carbon, about 0.5% manganese, about 0.5% silicon, with the balance being iron. In certain embodiments, the improved alloy includes, by weight: about 0.1% to about 10% cobalt; about 0.1% carbon, about 0.5% manganese, about 0.5% silicon, with the balance being iron.

In some embodiments, the improved alloy includes chromium, carbon, cobalt, iron, manganese, silicon, titanium, vanadium, or mixtures thereof. In certain embodiments, the improved alloy includes, by weight: about 5% to about 20% cobalt, about 0.1% carbon, about 0.5% manganese, about 0.5% silicon, about 0.1% to about 2% vanadium with the balance being iron. In some embodiments, the improved alloy includes, by weight: about 12% chromium, about 0.1% carbon, about 0.5% silicon, about 0.1% to about 0.5% manganese, above 0% to about 15% cobalt, above 0% to about 2% vanadium, above 0% to about 1% titanium, with the balance being iron. In some embodiments, the improved alloy includes, by weight: about 12% chromium, about 0.1% carbon, about 0.5% silicon, about 0.1% to about 0.5% manganese, above 0% to about 2% vanadium, above 0% to about 1% titanium, with the balance being iron. In some embodiments, the improved alloy includes, by weight: about 12% chromium, about 0.1% carbon, about 0.5% silicon, about 0.1% to about 0.5% manganese, above 0% to about 2% vanadium, with the balance being iron. In certain embodiments, the improved alloy includes, by weight: about 12% chromium, about 0.1% carbon, about 0.5% silicon, about 0.1% to about 0.5% manganese, above 0% to about 15% cobalt, above 0% to about 1% titanium, with the balance being iron. In certain embodiments, the improved alloy includes, by weight: about 12% chromium, about 0.1% carbon, about 0.5% silicon, about 0.1% to about 0.5% manganese, above 0% to about 15% cobalt, with the balance being iron. The addition of vanadium may allow for use of higher amounts of cobalt in the improved alloy.

Certain embodiments of temperature limited heaters may include more than one ferromagnetic material. Such embodiments are within the scope of embodiments described herein if any conditions described herein apply to at least one of the ferromagnetic materials in the temperature limited heater.

Ferromagnetic properties generally decay as the Curie temperature and/or the phase transformation temperature range is approached. The "Handbook of Electrical Heating for Industry" by C. James Erickson (IEEE Press, 1995) shows a typical curve for 1% carbon steel (steel with 1% carbon by weight). The loss of magnetic permeability starts at temperatures above 650° C. and tends to be complete when temperatures exceed 730° C. Thus, the self-limiting temperature may be somewhat below the actual Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. The skin depth for current flow in 1% carbon steel

is 0.132 cm at room temperature and increases to 0.445 cm at 720° C. From 720° C. to 730° C., the skin depth sharply increases to over 2.5 cm. Thus, a temperature limited heater embodiment using 1% carbon steel begins to self-limit between 650° C. and 730° C.

Skin depth generally defines an effective penetration depth of time-varying current into the conductive material. In general, current density decreases exponentially with distance from an outer surface to the center along the radius of the conductor. The depth at which the current density is approximately 1/e of the surface current density is called the skin depth. For a solid cylindrical rod with a diameter much greater than the penetration depth, or for hollow cylinders with a wall thickness exceeding the penetration depth, the skin depth, δ, is:

$$\delta=1981.5*(\rho/(\mu*f))^{1/2}; \quad \text{(EQN. 4)}$$

in which:

δ=skin depth in inches;

ρ=resistivity at operating temperature (ohm-cm);

μ=relative magnetic permeability; and

f=frequency (Hz).

EQN. 4 is obtained from "Handbook of Electrical Heating for Industry" by C. James Erickson (IEEE Press, 1995). For most metals, resistivity (ρ) increases with temperature. The relative magnetic permeability generally varies with temperature and with current. Additional equations may be used to assess the variance of magnetic permeability and/or skin depth on both temperature and/or current. The dependence of μ on current arises from the dependence of μ on the electromagnetic field.

Materials used in the temperature limited heater may be selected to provide a desired turndown ratio. Turndown ratios of at least 1.1:1, 2:1, 3:1, 4:1, 5:1, 10:1, 30:1, or 50:1 may be selected for temperature limited heaters. Larger turndown ratios may also be used. A selected turndown ratio may depend on a number of factors including, but not limited to, the type of formation in which the temperature limited heater is located (for example, a higher turndown ratio may be used for an oil shale formation with large variations in thermal conductivity between rich and lean oil shale layers) and/or a temperature limit of materials used in the wellbore (for example, temperature limits of heater materials). In some embodiments, the turndown ratio is increased by coupling additional copper or another good electrical conductor to the ferromagnetic material (for example, adding copper to lower the resistance above the Curie temperature and/or the phase transformation temperature range).

The temperature limited heater may provide a maximum heat output (power output) below the Curie temperature and/or the phase transformation temperature range of the heater. In certain embodiments, the maximum heat output is at least 400 W/m (Watts per meter), 600 W/m, 700 W/m, 800 W/m, or higher up to 2000 W/m. The temperature limited heater reduces the amount of heat output by a section of the heater when the temperature of the section of the heater approaches or is above the Curie temperature and/or the phase transformation temperature range. The reduced amount of heat may be substantially less than the heat output below the Curie temperature and/or the phase transformation temperature range. In some embodiments, the reduced amount of heat is at most 400 W/m, 200 W/m, 100 W/m or may approach 0 W/m.

In certain embodiments, the temperature limited heater operates substantially independently of the thermal load on the heater in a certain operating temperature range. "Thermal load" is the rate that heat is transferred from a heating system to its surroundings. It is to be understood that the thermal load may vary with temperature of the surroundings and/or the thermal conductivity of the surroundings. In an embodiment, the temperature limited heater operates at or above the Curie temperature and/or the phase transformation temperature range of the temperature limited heater such that the operating temperature of the heater increases at most by 3° C., 2° C., 1.5° C., 1° C., or 0.5° C. for a decrease in thermal load of 1 W/m proximate to a portion of the heater. In certain embodiments, the temperature limited heater operates in such a manner at a relatively constant current.

The AC or modulated DC resistance and/or the heat output of the temperature limited heater may decrease as the temperature approaches the Curie temperature and/or the phase transformation temperature range and decrease sharply near or above the Curie temperature due to the Curie effect and/or phase transformation effect. In certain embodiments, the value of the electrical resistance or heat output above or near the Curie temperature and/or the phase transformation temperature range is at most one-half of the value of electrical resistance or heat output at a certain point below the Curie temperature and/or the phase transformation temperature range. In some embodiments, the heat output above or near the Curie temperature and/or the phase transformation temperature range is at most 90%, 70%, 50%, 30%, 20%, 10%, or less (down to 1%) of the heat output at a certain point below the Curie temperature and/or the phase transformation temperature range (for example, 30° C. below the Curie temperature, 40° C. below the Curie temperature, 50° C. below the Curie temperature, or 100° C. below the Curie temperature). In certain embodiments, the electrical resistance above or near the Curie temperature and/or the phase transformation temperature range decreases to 80%, 70%, 60%, 50%, or less (down to 1%) of the electrical resistance at a certain point below the Curie temperature and/or the phase transformation temperature range (for example, 30° C. below the Curie temperature, 40° C. below the Curie temperature, 50° C. below the Curie temperature, or 100° C. below the Curie temperature).

In some embodiments, AC frequency is adjusted to change the skin depth of the ferromagnetic material. For example, the skin depth of 1% carbon steel at room temperature is 0.132 cm at 60 Hz, 0.0762 cm at 180 Hz, and 0.046 cm at 440 Hz. Since heater diameter is typically larger than twice the skin depth, using a higher frequency (and thus a heater with a smaller diameter) reduces heater costs. For a fixed geometry, the higher frequency results in a higher turndown ratio. The turndown ratio at a higher frequency is calculated by multiplying the turndown ratio at a lower frequency by the square root of the higher frequency divided by the lower frequency. In some embodiments, a frequency between 100 Hz and 1000 Hz, between 140 Hz and 200 Hz, or between 400 Hz and 600 Hz is used (for example, 180 Hz, 540 Hz, or 720 Hz). In some embodiments, high frequencies may be used. The frequencies may be greater than 1000 Hz.

To maintain a substantially constant skin depth until the Curie temperature and/or the phase transformation temperature range of the temperature limited heater is reached, the heater may be operated at a lower frequency when the heater is cold and operated at a higher frequency when the heater is hot. Line frequency heating is generally favorable, however, because there is less need for expensive components such as power supplies, transformers, or current modulators that alter frequency. Line frequency is the frequency of a general supply of current. Line frequency is typically 60 Hz, but may be 50 Hz or another frequency depending on the source for the supply of the current. Higher frequencies may be produced using commercially available equipment such as solid state

variable frequency power supplies. Transformers that convert three-phase power to single-phase power with three times the frequency are commercially available. For example, high voltage three-phase power at 60 Hz may be transformed to single-phase power at 180 Hz and at a lower voltage. Such transformers are less expensive and more energy efficient than solid state variable frequency power supplies. In certain embodiments, transformers that convert three-phase power to single-phase power are used to increase the frequency of power supplied to the temperature limited heater.

In certain embodiments, modulated DC (for example, chopped DC, waveform modulated DC, or cycled DC) may be used for providing electrical power to the temperature limited heater. A DC modulator or DC chopper may be coupled to a DC power supply to provide an output of modulated direct current. In some embodiments, the DC power supply may include means for modulating DC. One example of a DC modulator is a DC-to-DC converter system. DC-to-DC converter systems are generally known in the art. DC is typically modulated or chopped into a desired waveform. Waveforms for DC modulation include, but are not limited to, square-wave, sinusoidal, deformed sinusoidal, deformed square-wave, triangular, and other regular or irregular waveforms.

The modulated DC waveform generally defines the frequency of the modulated DC. Thus, the modulated DC waveform may be selected to provide a desired modulated DC frequency. The shape and/or the rate of modulation (such as the rate of chopping) of the modulated DC waveform may be varied to vary the modulated DC frequency. DC may be modulated at frequencies that are higher than generally available AC frequencies. For example, modulated DC may be provided at frequencies of at least 1000 Hz. Increasing the frequency of supplied current to higher values advantageously increases the turndown ratio of the temperature limited heater.

In certain embodiments, the modulated DC waveform is adjusted or altered to vary the modulated DC frequency. The DC modulator may be able to adjust or alter the modulated DC waveform at any time during use of the temperature limited heater and at high currents or voltages. Thus, modulated DC provided to the temperature limited heater is not limited to a single frequency or even a small set of frequency values. Waveform selection using the DC modulator typically allows for a wide range of modulated DC frequencies and for discrete control of the modulated DC frequency. Thus, the modulated DC frequency is more easily set at a distinct value whereas AC frequency is generally limited to multiples of the line frequency. Discrete control of the modulated DC frequency allows for more selective control over the turndown ratio of the temperature limited heater. Being able to selectively control the turndown ratio of the temperature limited heater allows for a broader range of materials to be used in designing and constructing the temperature limited heater.

In some embodiments, the modulated DC frequency or the AC frequency is adjusted to compensate for changes in properties (for example, subsurface conditions such as temperature or pressure) of the temperature limited heater during use. The modulated DC frequency or the AC frequency provided to the temperature limited heater is varied based on assessed downhole conditions. For example, as the temperature of the temperature limited heater in the wellbore increases, it may be advantageous to increase the frequency of the current provided to the heater, thus increasing the turndown ratio of the heater. In an embodiment, the downhole temperature of the temperature limited heater in the wellbore is assessed.

In certain embodiments, the modulated DC frequency, or the AC frequency, is varied to adjust the turndown ratio of the temperature limited heater. The turndown ratio may be adjusted to compensate for hot spots occurring along a length of the temperature limited heater. For example, the turndown ratio is increased because the temperature limited heater is getting too hot in certain locations. In some embodiments, the modulated DC frequency, or the AC frequency, are varied to adjust a turndown ratio without assessing a subsurface condition.

At or near the Curie temperature and/or the phase transformation temperature range of the ferromagnetic material, a relatively small change in voltage may cause a relatively large change in current to the load. The relatively small change in voltage may produce problems in the power supplied to the temperature limited heater, especially at or near the Curie temperature and/or the phase transformation temperature range. The problems include, but are not limited to, reducing the power factor, tripping a circuit breaker, and/or blowing a fuse. In some cases, voltage changes may be caused by a change in the load of the temperature limited heater. In certain embodiments, an electrical current supply (for example, a supply of modulated DC or AC) provides a relatively constant amount of current that does not substantially vary with changes in load of the temperature limited heater. In an embodiment, the electrical current supply provides an amount of electrical current that remains within 15%, within 10%, within 5%, or within 2% of a selected constant current value when a load of the temperature limited heater changes.

Temperature limited heaters may generate an inductive load. The inductive load is due to some applied electrical current being used by the ferromagnetic material to generate a magnetic field in addition to generating a resistive heat output. As downhole temperature changes in the temperature limited heater, the inductive load of the heater changes due to changes in the ferromagnetic properties of ferromagnetic materials in the heater with temperature. The inductive load of the temperature limited heater may cause a phase shift between the current and the voltage applied to the heater.

A reduction in actual power applied to the temperature limited heater may be caused by a time lag in the current waveform (for example, the current has a phase shift relative to the voltage due to an inductive load) and/or by distortions in the current waveform (for example, distortions in the current waveform caused by introduced harmonics due to a non-linear load). Thus, it may take more current to apply a selected amount of power due to phase shifting or waveform distortion. The ratio of actual power applied and the apparent power that would have been transmitted if the same current were in phase and undistorted is the power factor. The power factor is always less than or equal to 1. The power factor is 1 when there is no phase shift or distortion in the waveform.

Actual power applied to a heater due to a phase shift may be described by EQN. 5:

$$P = I \times V \times \cos(\theta); \quad \text{(EQN. 5)}$$

in which P is the actual power applied to a heater; I is the applied current; V is the applied voltage; and θ is the phase angle difference between voltage and current. Other phenomena such as waveform distortion may contribute to further lowering of the power factor. If there is no distortion in the waveform, then $\cos(\theta)$ is equal to the power factor.

In certain embodiments, the temperature limited heater includes an inner conductor inside an outer conductor. The inner conductor and the outer conductor are radially disposed about a central axis. The inner and outer conductors may be separated by an insulation layer. In certain embodiments, the

inner and outer conductors are coupled at the bottom of the temperature limited heater. Electrical current may flow into the temperature limited heater through the inner conductor and return through the outer conductor. One or both conductors may include ferromagnetic material.

The insulation layer may comprise an electrically insulating ceramic with high thermal conductivity, such as magnesium oxide, aluminum oxide, silicon dioxide, beryllium oxide, boron nitride, silicon nitride, or combinations thereof. The insulating layer may be a compacted powder (for example, compacted ceramic powder). Compaction may improve thermal conductivity and provide better insulation resistance. For lower temperature applications, polymer insulation made from, for example, fluoropolymers, polyimides, polyamides, and/or polyethylenes, may be used. In some embodiments, the polymer insulation is made of perfluoroalkoxy (PFA) or polyetheretherketone (PEEK™ (Victrex Ltd, England)). The insulating layer may be chosen to be substantially infrared transparent to aid heat transfer from the inner conductor to the outer conductor. In an embodiment, the insulating layer is transparent quartz sand. The insulation layer may be air or a non-reactive gas such as helium, nitrogen, or sulfur hexafluoride. If the insulation layer is air or a non-reactive gas, there may be insulating spacers designed to inhibit electrical contact between the inner conductor and the outer conductor. The insulating spacers may be made of, for example, high purity aluminum oxide or another thermally conducting, electrically insulating material such as silicon nitride. The insulating spacers may be a fibrous ceramic material such as Nextel™ 312 (3M Corporation, St. Paul, Minn., U.S.A.), mica tape, or glass fiber. Ceramic material may be made of alumina, alumina-silicate, alumina-borosilicate, silicon nitride, boron nitride, or other materials.

The insulation layer may be flexible and/or substantially deformation tolerant. For example, if the insulation layer is a solid or compacted material that substantially fills the space between the inner and outer conductors, the temperature limited heater may be flexible and/or substantially deformation tolerant. Forces on the outer conductor can be transmitted through the insulation layer to the solid inner conductor, which may resist crushing. Such a temperature limited heater may be bent, dog-legged, and spiraled without causing the outer conductor and the inner conductor to electrically short to each other. Deformation tolerance may be important if the wellbore is likely to undergo substantial deformation during heating of the formation.

In certain embodiments, an outermost layer of the temperature limited heater (for example, the outer conductor) is chosen for corrosion resistance, yield strength, and/or creep resistance. In one embodiment, austenitic (non-ferromagnetic) stainless steels such as 201, 304H, 347H, 347HH, 316H, 310H, 347HP, NF709 (Nippon Steel Corp., Japan) stainless steels, or combinations thereof may be used in the outer conductor. The outermost layer may also include a clad conductor. For example, a corrosion resistant alloy such as 800H or 347H stainless steel may be clad for corrosion protection over a ferromagnetic carbon steel tubular. If high temperature strength is not required, the outermost layer may be constructed from ferromagnetic metal with good corrosion resistance such as one of the ferritic stainless steels. In one embodiment, a ferritic alloy of 82.3% by weight iron with 17.7% by weight chromium (Curie temperature of 678° C.) provides desired corrosion resistance.

The Metals Handbook, vol. 8, page 291 (American Society of Materials (ASM)) includes a graph of Curie temperature of iron-chromium alloys versus the amount of chromium in the alloys. In some temperature limited heater embodiments, a separate support rod or tubular (made from 347H stainless steel) is coupled to the temperature limited heater made from an iron-chromium alloy to provide yield strength and/or creep resistance. In certain embodiments, the support material and/or the ferromagnetic material is selected to provide a 100,000 hour creep-rupture strength of at least 20.7 MPa at 650° C. In some embodiments, the 100,000 hour creep-rupture strength is at least 13.8 MPa at 650° C. or at least 6.9 MPa at 650° C. For example, 347H steel has a favorable creep-rupture strength at or above 650° C. In some embodiments, the 100,000 hour creep-rupture strength ranges from 6.9 MPa to 41.3 MPa or more for longer heaters and/or higher earth or fluid stresses.

In temperature limited heater embodiments with both an inner ferromagnetic conductor and an outer ferromagnetic conductor, the skin effect current path occurs on the outside of the inner conductor and on the inside of the outer conductor. Thus, the outside of the outer conductor may be clad with the corrosion resistant alloy, such as stainless steel, without affecting the skin effect current path on the inside of the outer conductor.

A ferromagnetic conductor with a thickness of at least the skin depth at the Curie temperature and/or the phase transformation temperature range allows a substantial decrease in resistance of the ferromagnetic material as the skin depth increases sharply near the Curie temperature and/or the phase transformation temperature range. In certain embodiments when the ferromagnetic conductor is not clad with a highly conducting material such as copper, the thickness of the conductor may be 1.5 times the skin depth near the Curie temperature and/or the phase transformation temperature range, 3 times the skin depth near the Curie temperature and/or the phase transformation temperature range, or even 10 or more times the skin depth near the Curie temperature and/or the phase transformation temperature range. If the ferromagnetic conductor is clad with copper, thickness of the ferromagnetic conductor may be substantially the same as the skin depth near the Curie temperature and/or the phase transformation temperature range. In some embodiments, the ferromagnetic conductor clad with copper has a thickness of at least three-fourths of the skin depth near the Curie temperature and/or the phase transformation temperature range.

In certain embodiments, the temperature limited heater includes a composite conductor with a ferromagnetic tubular and a non-ferromagnetic, high electrical conductivity core. The non-ferromagnetic, high electrical conductivity core reduces a required diameter of the conductor. For example, the conductor may be composite 1.19 cm diameter conductor with a core of 0.575 cm diameter copper clad with a 0.298 cm thickness of ferritic stainless steel or carbon steel surrounding the core. The core or non-ferromagnetic conductor may be copper or copper alloy. The core or non-ferromagnetic conductor may also be made of other metals that exhibit low electrical resistivity and relative magnetic permeabilities near 1 (for example, substantially non-ferromagnetic materials such as aluminum and aluminum alloys, phosphor bronze, beryllium copper, and/or brass). A composite conductor allows the electrical resistance of the temperature limited heater to decrease more steeply near the Curie temperature and/or the phase transformation temperature range. As the skin depth increases near the Curie temperature and/or the phase transformation temperature range to include the copper core, the electrical resistance decreases very sharply.

The composite conductor may increase the conductivity of the temperature limited heater and/or allow the heater to operate at lower voltages. In an embodiment, the composite conductor exhibits a relatively flat resistance versus tempera-

ture profile at temperatures below a region near the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor of the composite conductor. In some embodiments, the temperature limited heater exhibits a relatively flat resistance versus temperature profile between 100° C. and 750° C. or between 300° C. and 600° C. The relatively flat resistance versus temperature profile may also be exhibited in other temperature ranges by adjusting, for example, materials and/or the configuration of materials in the temperature limited heater. In certain embodiments, the relative thickness of each material in the composite conductor is selected to produce a desired resistivity versus temperature profile for the temperature limited heater.

In certain embodiments, the relative thickness of each material in a composite conductor is selected to produce a desired resistivity versus temperature profile for a temperature limited heater. In an embodiment, the composite conductor is an inner conductor surrounded by 0.127 cm thick magnesium oxide powder as an insulator. The outer conductor may be 304H stainless steel with a wall thickness of 0.127 cm. The outside diameter of the heater may be about 1.65 cm.

A composite conductor (for example, a composite inner conductor or a composite outer conductor) may be manufactured by methods including, but not limited to, coextrusion, roll forming, tight fit tubing (for example, cooling the inner member and heating the outer member, then inserting the inner member in the outer member, followed by a drawing operation and/or allowing the system to cool), explosive or electromagnetic cladding, arc overlay welding, longitudinal strip welding, plasma powder welding, billet coextrusion, electroplating, drawing, sputtering, plasma deposition, coextrusion casting, magnetic forming, molten cylinder casting (of inner core material inside the outer or vice versa), insertion followed by welding or high temperature braising, shielded active gas welding (SAG), and/or insertion of an inner pipe in an outer pipe followed by mechanical expansion of the inner pipe by hydroforming or use of a pig to expand and swage the inner pipe against the outer pipe. In some embodiments, a ferromagnetic conductor is braided over a non-ferromagnetic conductor. In certain embodiments, composite conductors are formed using methods similar to those used for cladding (for example, cladding copper to steel). A metallurgical bond between copper cladding and base ferromagnetic material may be advantageous. Composite conductors produced by a coextrusion process that forms a good metallurgical bond (for example, a good bond between copper and 446 stainless steel) may be provided by Anomet Products, Inc. (Shrewsbury, Mass., U.S.A.).

FIGS. **19**-**40** depict various embodiments of temperature limited heaters. One or more features of an embodiment of the temperature limited heater depicted in any of these figures may be combined with one or more features of other embodiments of temperature limited heaters depicted in these figures. In certain embodiments described herein, temperature limited heaters are dimensioned to operate at a frequency of 60 Hz AC. It is to be understood that dimensions of the temperature limited heater may be adjusted from those described herein to operate in a similar manner at other AC frequencies or with modulated DC current.

FIG. **19** depicts a cross-sectional representation of an embodiment of the temperature limited heater with an outer conductor having a ferromagnetic section and a non-ferromagnetic section. FIGS. **20** and **21** depict transverse cross-sectional views of the embodiment shown in FIG. **19**. In one embodiment, ferromagnetic section **486** is used to provide heat to hydrocarbon layers in the formation. Non-ferromagnetic section **488** is used in the overburden of the formation. Non-ferromagnetic section **488** provides little or no heat to the overburden, thus inhibiting heat losses in the overburden and improving heater efficiency. Ferromagnetic section **486** includes a ferromagnetic material such as 409 stainless steel or 410 stainless steel. Ferromagnetic section **486** has a thickness of 0.3 cm. Non-ferromagnetic section **488** is copper with a thickness of 0.3 cm. Inner conductor **490** is copper. Inner conductor **490** has a diameter of 0.9 cm. Electrical insulator **500** is silicon nitride, boron nitride, magnesium oxide powder, or another suitable insulator material. Electrical insulator **500** has a thickness of 0.1 cm to 0.3 cm.

FIG. **22** depicts a cross-sectional representation of an embodiment of a temperature limited heater with an outer conductor having a ferromagnetic section and a non-ferromagnetic section placed inside a sheath. FIGS. **23**, **24**, and **25** depict transverse cross-sectional views of the embodiment shown in FIG. **22**. Ferromagnetic section **486** is 410 stainless steel with a thickness of 0.6 cm. Non-ferromagnetic section **488** is copper with a thickness of 0.6 cm. Inner conductor **490** is copper with a diameter of 0.9 cm. Outer conductor **502** includes ferromagnetic material. Outer conductor **502** provides some heat in the overburden section of the heater. Providing some heat in the overburden inhibits condensation or refluxing of fluids in the overburden. Outer conductor **502** is 409, 410, or 446 stainless steel with an outer diameter of 3.0 cm and a thickness of 0.6 cm. Electrical insulator **500** includes compacted magnesium oxide powder with a thickness of 0.3 cm. In some embodiments, electrical insulator **500** includes silicon nitride, boron nitride, or hexagonal type boron nitride. Conductive section **504** may couple inner conductor **490** with ferromagnetic section **486** and/or outer conductor **502**.

FIG. **26**A and FIG. **26**B depict cross-sectional representations of an embodiment of a temperature limited heater with a ferromagnetic inner conductor. Inner conductor **490** is a 1" Schedule XXS 446 stainless steel pipe. In some embodiments, inner conductor **490** includes 409 stainless steel, 410 stainless steel, Invar 36, alloy 42-6, alloy 52, or other ferromagnetic materials. Inner conductor **490** has a diameter of 2.5 cm. Electrical insulator **500** includes compacted silicon nitride, boron nitride, or magnesium oxide powders; or polymers, Nextel ceramic fiber, mica, or glass fibers. Outer conductor **502** is copper or any other non-ferromagnetic material, such as but not limited to copper alloys, aluminum and/or aluminum alloys. Outer conductor **502** is coupled to jacket **506**. Jacket **506** is 304H, 316H, or 347H stainless steel. In this embodiment, a majority of the heat is produced in inner conductor **490**.

FIG. **27**A and FIG. **27**B depict cross-sectional representations of an embodiment of a temperature limited heater with a ferromagnetic inner conductor and a non-ferromagnetic core. Inner conductor **490** may be made of 446 stainless steel, 409 stainless steel, 410 stainless steel, carbon steel, Armco ingot iron, iron-cobalt alloys, or other ferromagnetic materials. Core **508** may be tightly bonded inside inner conductor **490**. Core **508** is copper or other non-ferromagnetic material. In certain embodiments, core **508** is inserted as a tight fit inside inner conductor **490** before a drawing operation. In some embodiments, core **508** and inner conductor **490** are coextrusion bonded. Outer conductor **502** is 347H stainless steel. A drawing or rolling operation to compact electrical insulator **500** (for example, compacted silicon nitride, boron nitride, or magnesium oxide powder) may ensure good electrical contact between inner conductor **490** and core **508**. In this embodiment, heat is produced primarily in inner conductor **490** until the Curie temperature and/or the phase transfor-

mation temperature range is approached. Resistance then decreases sharply as current penetrates core **508**.

FIG. **28**A and FIG. **28**B depict cross-sectional representations of an embodiment of a temperature limited heater with a ferromagnetic outer conductor. Inner conductor **490** is nickel-clad copper. Electrical insulator **500** is silicon nitride, boron nitride, or magnesium oxide. Outer conductor **502** is a 1" Schedule XXS carbon steel pipe. In this embodiment, heat is produced primarily in outer conductor **502**, resulting in a small temperature differential across electrical insulator **500**.

FIG. **29**A and FIG. **29**B depict cross-sectional representations of an embodiment of a temperature limited heater with a ferromagnetic outer conductor that is clad with a corrosion resistant alloy. Inner conductor **490** is copper. Outer conductor **502** is a 1" Schedule XXS carbon steel pipe. Outer conductor **502** is coupled to jacket **506**. Jacket **506** is made of corrosion resistant material (for example, 347H stainless steel). Jacket **506** provides protection from corrosive fluids in the wellbore (for example, sulfidizing and carburizing gases). Heat is produced primarily in outer conductor **502**, resulting in a small temperature differential across electrical insulator **500**.

FIG. **30**A and FIG. **30**B depict cross-sectional representations of an embodiment of a temperature limited heater with a ferromagnetic outer conductor. The outer conductor is clad with a conductive layer and a corrosion resistant alloy. Inner conductor **490** is copper. Electrical insulator **500** is silicon nitride, boron nitride, or magnesium oxide. Outer conductor **502** is a 1" Schedule 80 446 stainless steel pipe. Outer conductor **502** is coupled to jacket **506**. Jacket **506** is made from corrosion resistant material such as 347H stainless steel. In an embodiment, conductive layer **510** is placed between outer conductor **502** and jacket **506**. Conductive layer **510** is a copper layer. Heat is produced primarily in outer conductor **502**, resulting in a small temperature differential across electrical insulator **500**. Conductive layer **510** allows a sharp decrease in the resistance of outer conductor **502** as the outer conductor approaches the Curie temperature and/or the phase transformation temperature range. Jacket **506** provides protection from corrosive fluids in the wellbore.

In some embodiments, the conductor (for example, an inner conductor, an outer conductor, or a ferromagnetic conductor) is the composite conductor that includes two or more different materials. In certain embodiments, the composite conductor includes two or more ferromagnetic materials. In some embodiments, the composite ferromagnetic conductor includes two or more radially disposed materials. In certain embodiments, the composite conductor includes a ferromagnetic conductor and a non-ferromagnetic conductor. In some embodiments, the composite conductor includes the ferromagnetic conductor placed over a non-ferromagnetic core. Two or more materials may be used to obtain a relatively flat electrical resistivity versus temperature profile in a temperature region below the Curie temperature, and/or the phase transformation temperature range, and/or a sharp decrease (a high turndown ratio) in the electrical resistivity at or near the Curie temperature and/or the phase transformation temperature range. In some cases, two or more materials are used to provide more than one Curie temperature and/or phase transformation temperature range for the temperature limited heater.

The composite electrical conductor may be used as the conductor in any electrical heater embodiment described herein. For example, the composite conductor may be used as the conductor in a conductor-in-conduit heater or an insulated conductor heater. In certain embodiments, the composite conductor may be coupled to a support member such as a support conductor. The support member may be used to provide support to the composite conductor so that the composite conductor is not relied upon for strength at or near the Curie temperature and/or the phase transformation temperature range. The support member may be useful for heaters of lengths of at least 100 m. The support member may be a non-ferromagnetic member that has good high temperature creep strength. Examples of materials that are used for a support member include, but are not limited to, Haynes® 625 alloy and Haynes® HR120® alloy (Haynes International, Kokomo, Ind., U.S.A.), NF709, Incoloy® 800H alloy and 347HP alloy (Allegheny Ludlum Corp., Pittsburgh, Pa., U.S.A.). In some embodiments, materials in a composite conductor are directly coupled (for example, brazed, metallurgically bonded, or swaged) to each other and/or the support member. Using a support member may reduce the need for the ferromagnetic member to provide support for the temperature limited heater, especially at or near the Curie temperature and/or the phase transformation temperature range. Thus, the temperature limited heater may be designed with more flexibility in the selection of ferromagnetic materials.

FIG. **31** depicts a cross-sectional representation of an embodiment of the composite conductor with the support member. Core **508** is surrounded by ferromagnetic conductor **512** and support member **514**. In some embodiments, core **508**, ferromagnetic conductor **512**, and support member **514** are directly coupled (for example, brazed together or metallurgically bonded together). In one embodiment, core **508** is copper, ferromagnetic conductor **512** is 446 stainless steel, and support member **514** is 347H alloy. In certain embodiments, support member **514** is a Schedule 80 pipe. Support member **514** surrounds the composite conductor having ferromagnetic conductor **512** and core **508**. Ferromagnetic conductor **512** and core **508** may be joined to form the composite conductor by, for example, a coextrusion process. For example, the composite conductor is a 1.9 cm outside diameter 446 stainless steel ferromagnetic conductor surrounding a 0.95 cm diameter copper core.

In certain embodiments, the diameter of core **508** is adjusted relative to a constant outside diameter of ferromagnetic conductor **512** to adjust the turndown ratio of the temperature limited heater. For example, the diameter of core **508** may be increased to 1.14 cm while maintaining the outside diameter of ferromagnetic conductor **512** at 1.9 cm to increase the turndown ratio of the heater.

In some embodiments, conductors (for example, core **508** and ferromagnetic conductor **512**) in the composite conductor are separated by support member **514**. FIG. **32** depicts a cross-sectional representation of an embodiment of the composite conductor with support member **514** separating the conductors. In one embodiment, core **508** is copper with a diameter of 0.95 cm, support member **514** is 347H alloy with an outside diameter of 1.9 cm, and ferromagnetic conductor **512** is 446 stainless steel with an outside diameter of 2.7 cm. The support member depicted in FIG. **32** has a lower creep strength relative to the support members depicted in FIG. **31**.

In certain embodiments, support member **514** is located inside the composite conductor. FIG. **33** depicts a cross-sectional representation of an embodiment of the composite conductor surrounding support member **514**. Support member **514** is made of 347H alloy. Inner conductor **490** is copper. Ferromagnetic conductor **512** is 446 stainless steel. In one embodiment, support member **514** is 1.25 cm diameter 347H alloy, inner conductor **490** is 1.9 cm outside diameter copper, and ferromagnetic conductor **512** is 2.7 cm outside diameter 446 stainless steel. The turndown ratio is higher than the

turndown ratio for the embodiments depicted in FIGS. **31**, **32**, and **34** for the same outside diameter, but the creep strength is lower.

In some embodiments, the thickness of inner conductor **490**, which is copper, is reduced and the thickness of support member **514** is increased to increase the creep strength at the expense of reduced turndown ratio. For example, the diameter of support member **514** is increased to 1.6 cm while maintaining the outside diameter of inner conductor **490** at 1.9 cm to reduce the thickness of the conduit. This reduction in thickness of inner conductor **490** results in a decreased turndown ratio relative to the thicker inner conductor embodiment but an increased creep strength.

In one embodiment, support member **514** is a conduit (or pipe) inside inner conductor **490** and ferromagnetic conductor **512**. FIG. **34** depicts a cross-sectional representation of an embodiment of the composite conductor surrounding support member **514**. In one embodiment, support member **514** is 347H alloy with a 0.63 cm diameter center hole. In some embodiments, support member **514** is a preformed conduit. In certain embodiments, support member **514** is formed by having a dissolvable material (for example, copper dissolvable by nitric acid) located inside the support member during formation of the composite conductor. The dissolvable material is dissolved to form the hole after the conductor is assembled. In an embodiment, support member **514** is 347H alloy with an inside diameter of 0.63 cm and an outside diameter of 1.6 cm, inner conductor **490** is copper with an outside diameter of 1.8 cm, and ferromagnetic conductor **512** is 446 stainless steel with an outside diameter of 2.7 cm.

In certain embodiments, the composite electrical conductor is used as the conductor in the conductor-in-conduit heater. For example, the composite electrical conductor may be used as conductor **516** in FIG. **35**.

FIG. **35** depicts a cross-sectional representation of an embodiment of the conductor-in-conduit heater. Conductor **516** is disposed in conduit **518**. Conductor **516** is a rod or conduit of electrically conductive material. Low resistance sections **520** are present at both ends of conductor **516** to generate less heating in these sections. Low resistance section **520** is formed by having a greater cross-sectional area of conductor **516** in that section, or the sections are made of material having less resistance. In certain embodiments, low resistance section **520** includes a low resistance conductor coupled to conductor **516**.

Conduit **518** is made of an electrically conductive material. Conduit **518** is disposed in opening **522** in hydrocarbon layer **460**. Opening **522** has a diameter that accommodates conduit **518**.

Conductor **516** may be centered in conduit **518** by centralizers **524**. Centralizers **524** electrically isolate conductor **516** from conduit **518**. Centralizers **524** inhibit movement and properly locate conductor **516** in conduit **518**. Centralizers **524** are made of ceramic material or a combination of ceramic and metallic materials. Centralizers **524** inhibit deformation of conductor **516** in conduit **518**. Centralizers **524** are touching or spaced at intervals between approximately 0.1 m (meters) and approximately 3 m or more along conductor **516**.

A second low resistance section **520** of conductor **516** may couple conductor **516** to wellhead **450**, as depicted in FIG. **35**. Electrical current may be applied to conductor **516** from power cable **526** through low resistance section **520** of conductor **516**. Electrical current passes from conductor **516** through sliding connector **528** to conduit **518**. Conduit **518** may be electrically insulated from overburden casing **530** and from wellhead **450** to return electrical current to power cable **526**. Heat may be generated in conductor **516** and conduit **518**. The generated heat may radiate in conduit **518** and opening **522** to heat at least a portion of hydrocarbon layer **460**.

Overburden casing **530** may be disposed in overburden **458**. Overburden casing **530** is, in some embodiments, surrounded by materials (for example, reinforcing material and/or cement) that inhibit heating of overburden **458**. Low resistance section **520** of conductor **516** may be placed in overburden casing **530**. Low resistance section **520** of conductor **516** is made of, for example, carbon steel. Low resistance section **520** of conductor **516** may be centralized in overburden casing **530** using centralizers **524**. Centralizers **524** are spaced at intervals of approximately 6 m to approximately 12 m or, for example, approximately 9 m along low resistance section **520** of conductor **516**. In a heater embodiment, low resistance section **520** of conductor **516** is coupled to conductor **516** by one or more welds. In other heater embodiments, low resistance sections are threaded, threaded and welded, or otherwise coupled to the conductor. Low resistance section **520** generates little or no heat in overburden casing **530**. Packing **532** may be placed between overburden casing **530** and opening **522**. Packing **532** may be used as a cap at the junction of overburden **458** and hydrocarbon layer **460** to allow filling of materials in the annulus between overburden casing **530** and opening **522**. In some embodiments, packing **532** inhibits fluid from flowing from opening **522** to surface **534**.

FIG. **36** depicts a cross-sectional representation of an embodiment of a removable conductor-in-conduit heat source. Conduit **518** may be placed in opening **522** through overburden **458** such that a gap remains between the conduit and overburden casing **530**. Fluids may be removed from opening **522** through the gap between conduit **518** and overburden casing **530**. Fluids may be removed from the gap through conduit **536**. Conduit **518** and components of the heat source included in the conduit that are coupled to wellhead **450** may be removed from opening **522** as a single unit. The heat source may be removed as a single unit to be repaired, replaced, and/or used in another portion of the formation.

For a temperature limited heater in which the ferromagnetic conductor provides a majority of the resistive heat output below the Curie temperature and/or the phase transformation temperature range, a majority of the current flows through material with highly non-linear functions of magnetic field (H) versus magnetic induction (B). These non-linear functions may cause strong inductive effects and distortion that lead to decreased power factor in the temperature limited heater at temperatures below the Curie temperature and/or the phase transformation temperature range. These effects may render the electrical power supply to the temperature limited heater difficult to control and may result in additional current flow through surface and/or overburden power supply conductors. Expensive and/or difficult to implement control systems such as variable capacitors or modulated power supplies may be used to compensate for these effects and to control temperature limited heaters where the majority of the resistive heat output is provided by current flow through the ferromagnetic material.

In certain temperature limited heater embodiments, the ferromagnetic conductor confines a majority of the flow of electrical current to an electrical conductor coupled to the ferromagnetic conductor when the temperature limited heater is below or near the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. The electrical conductor may be a sheath, jacket, support member, corrosion resistant member, or other electrically

resistive member. In some embodiments, the ferromagnetic conductor confines a majority of the flow of electrical current to the electrical conductor positioned between an outermost layer and the ferromagnetic conductor. The ferromagnetic conductor is located in the cross section of the temperature limited heater such that the magnetic properties of the ferromagnetic conductor at or below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor confine the majority of the flow of electrical current to the electrical conductor. The majority of the flow of electrical current is confined to the electrical conductor due to the skin effect of the ferromagnetic conductor. Thus, the majority of the current is flowing through material with substantially linear resistive properties throughout most of the operating range of the heater.

In certain embodiments, the ferromagnetic conductor and the electrical conductor are located in the cross section of the temperature limited heater so that the skin effect of the ferromagnetic material limits the penetration depth of electrical current in the electrical conductor and the ferromagnetic conductor at temperatures below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. Thus, the electrical conductor provides a majority of the electrically resistive heat output of the temperature limited heater at temperatures up to a temperature at or near the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. In certain embodiments, the dimensions of the electrical conductor may be chosen to provide desired heat output characteristics.

Because the majority of the current flows through the electrical conductor below the Curie temperature and/or the phase transformation temperature range, the temperature limited heater has a resistance versus temperature profile that at least partially reflects the resistance versus temperature profile of the material in the electrical conductor. Thus, the resistance versus temperature profile of the temperature limited heater is substantially linear below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor if the material in the electrical conductor has a substantially linear resistance versus temperature profile. For example, the temperature limited heater in which the majority of the current flows in the electrical conductor below the Curie temperature and/or the phase transformation temperature range may have a resistance versus temperature profile similar to the profile shown in FIG. **214**. The resistance of the temperature limited heater has little or no dependence on the current flowing through the heater until the temperature nears the Curie temperature and/or the phase transformation temperature range. The majority of the current flows in the electrical conductor rather than the ferromagnetic conductor below the Curie temperature and/or the phase transformation temperature range.

Resistance versus temperature profiles for temperature limited heaters in which the majority of the current flows in the electrical conductor also tend to exhibit sharper reductions in resistance near or at the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. For example, the reduction in resistance shown in FIG. **214** is sharper than the reduction in resistance shown in FIG. **200**. The sharper reductions in resistance near or at the Curie temperature and/or the phase transformation temperature range are easier to control than more gradual resistance reductions near the Curie temperature and/or the phase transformation temperature range because little current is flowing through the ferromagnetic material.

In certain embodiments, the material and/or the dimensions of the material in the electrical conductor are selected so that the temperature limited heater has a desired resistance versus temperature profile below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor.

Temperature limited heaters in which the majority of the current flows in the electrical conductor rather than the ferromagnetic conductor below the Curie temperature and/or the phase transformation temperature range are easier to predict and/or control. Behavior of temperature limited heaters in which the majority of the current flows in the electrical conductor rather than the ferromagnetic conductor below the Curie temperature and/or the phase transformation temperature range may be predicted by, for example, its resistance versus temperature profile and/or its power factor versus temperature profile. Resistance versus temperature profiles and/or power factor versus temperature profiles may be assessed or predicted by, for example, experimental measurements that assess the behavior of the temperature limited heater, analytical equations that assess or predict the behavior of the temperature limited heater, and/or simulations that assess or predict the behavior of the temperature limited heater.

In certain embodiments, assessed or predicted behavior of the temperature limited heater is used to control the temperature limited heater. The temperature limited heater may be controlled based on measurements (assessments) of the resistance and/or the power factor during operation of the heater. In some embodiments, the power, or current, supplied to the temperature limited heater is controlled based on assessment of the resistance and/or the power factor of the heater during operation of the heater and the comparison of this assessment versus the predicted behavior of the heater. In certain embodiments, the temperature limited heater is controlled without measurement of the temperature of the heater or a temperature near the heater. Controlling the temperature limited heater without temperature measurement eliminates operating costs associated with downhole temperature measurement. Controlling the temperature limited heater based on assessment of the resistance and/or the power factor of the heater also reduces the time for making adjustments in the power or current supplied to the heater compared to controlling the heater based on measured temperature.

As the temperature of the temperature limited heater approaches or exceeds the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor, reduction in the ferromagnetic properties of the ferromagnetic conductor allows electrical current to flow through a greater portion of the electrically conducting cross section of the temperature limited heater. Thus, the electrical resistance of the temperature limited heater is reduced and the temperature limited heater automatically provides reduced heat output at or near the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. In certain embodiments, a highly electrically conductive member is coupled to the ferromagnetic conductor and the electrical conductor to reduce the electrical resistance of the temperature limited heater at or above the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. The highly electrically conductive member may be an inner conductor, a core, or another conductive member of copper, aluminum, nickel, or alloys thereof.

The ferromagnetic conductor that confines the majority of the flow of electrical current to the electrical conductor at temperatures below the Curie temperature and/or the phase transformation temperature range may have a relatively small cross section compared to the ferromagnetic conductor in temperature limited heaters that use the ferromagnetic con-

ductor to provide the majority of resistive heat output up to or near the Curie temperature and/or the phase transformation temperature range. A temperature limited heater that uses the electrical conductor to provide a majority of the resistive heat output below the Curie temperature and/or the phase transformation temperature range has low magnetic inductance at temperatures below the Curie temperature and/or the phase transformation temperature range because less current is flowing through the ferromagnetic conductor as compared to the temperature limited heater where the majority of the resistive heat output below the Curie temperature and/or the phase transformation temperature range is provided by the ferromagnetic material. Magnetic field (H) at radius (r) of the ferromagnetic conductor is proportional to the current (I) flowing through the ferromagnetic conductor and the core divided by the radius, or:

$$H \propto I/r. \quad \text{(EQN. 6)}$$

Since only a portion of the current flows through the ferromagnetic conductor for a temperature limited heater that uses the outer conductor to provide a majority of the resistive heat output below the Curie temperature and/or the phase transformation temperature range, the magnetic field of the temperature limited heater may be significantly smaller than the magnetic field of the temperature limited heater where the majority of the current flows through the ferromagnetic material. The relative magnetic permeability (μ) may be large for small magnetic fields.

The skin depth (δ) of the ferromagnetic conductor is inversely proportional to the square root of the relative magnetic permeability (μ):

$$\delta \propto (1/\mu)^{1/2}. \quad \text{(EQN. 7)}$$

Increasing the relative magnetic permeability decreases the skin depth of the ferromagnetic conductor. However, because only a portion of the current flows through the ferromagnetic conductor for temperatures below the Curie temperature and/or the phase transformation temperature range, the radius (or thickness) of the ferromagnetic conductor may be decreased for ferromagnetic materials with large relative magnetic permeabilities to compensate for the decreased skin depth while still allowing the skin effect to limit the penetration depth of the electrical current to the electrical conductor at temperatures below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. The radius (thickness) of the ferromagnetic conductor may be between 0.3 mm and 8 mm, between 0.3 mm and 2 mm, or between 2 mm and 4 mm depending on the relative magnetic permeability of the ferromagnetic conductor. Decreasing the thickness of the ferromagnetic conductor decreases costs of manufacturing the temperature limited heater, as the cost of ferromagnetic material tends to be a significant portion of the cost of the temperature limited heater. Increasing the relative magnetic permeability of the ferromagnetic conductor provides a higher turndown ratio and a sharper decrease in electrical resistance for the temperature limited heater at or near the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor.

Ferromagnetic materials (such as purified iron or iron-cobalt alloys) with high relative magnetic permeabilities (for example, at least 200, at least 1000, at least 1×104, or at least 1×105) and/or high Curie temperatures (for example, at least 600° C., at least 700° C., or at least 800° C.) tend to have less corrosion resistance and/or less mechanical strength at high temperatures. The electrical conductor may provide corrosion resistance and/or high mechanical strength at high temperatures for the temperature limited heater. Thus, the ferromagnetic conductor may be chosen primarily for its ferromagnetic properties.

Confining the majority of the flow of electrical current to the electrical conductor below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor reduces variations in the power factor. Because only a portion of the electrical current flows through the ferromagnetic conductor below the Curie temperature and/or the phase transformation temperature range, the nonlinear ferromagnetic properties of the ferromagnetic conductor have little or no effect on the power factor of the temperature limited heater, except at or near the Curie temperature and/or the phase transformation temperature range. Even at or near the Curie temperature and/or the phase transformation temperature range, the effect on the power factor is reduced compared to temperature limited heaters in which the ferromagnetic conductor provides a majority of the resistive heat output below the Curie temperature and/or the phase transformation temperature range. Thus, there is less or no need for external compensation (for example, variable capacitors or waveform modification) to adjust for changes in the inductive load of the temperature limited heater to maintain a relatively high power factor.

In certain embodiments, the temperature limited heater, which confines the majority of the flow of electrical current to the electrical conductor below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor, maintains the power factor above 0.85, above 0.9, or above 0.95 during use of the heater. Any reduction in the power factor occurs only in sections of the temperature limited heater at temperatures near the Curie temperature and/or the phase transformation temperature range. Most sections of the temperature limited heater are typically not at or near the Curie temperature and/or the phase transformation temperature range during use. These sections have a high power factor that approaches 1.0. The power factor for the entire temperature limited heater is maintained above 0.85, above 0.9, or above 0.95 during use of the heater even if some sections of the heater have power factors below 0.85.

Maintaining high power factors allows for less expensive power supplies and/or control devices such as solid state power supplies or SCRs (silicon controlled rectifiers). These devices may fail to operate properly if the power factor varies by too large an amount because of inductive loads. With the power factors maintained at high values; however, these devices may be used to provide power to the temperature limited heater. Solid state power supplies have the advantage of allowing fine tuning and controlled adjustment of the power supplied to the temperature limited heater.

In some embodiments, transformers are used to provide power to the temperature limited heater. Multiple voltage taps may be made into the transformer to provide power to the temperature limited heater. Multiple voltage taps allows the current supplied to switch back and forth between the multiple voltages. This maintains the current within a range bound by the multiple voltage taps.

The highly electrically conductive member, or inner conductor, increases the turndown ratio of the temperature limited heater. In certain embodiments, thickness of the highly electrically conductive member is increased to increase the turndown ratio of the temperature limited heater. In some embodiments, the thickness of the electrical conductor is reduced to increase the turndown ratio of the temperature limited heater. In certain embodiments, the turndown ratio of the temperature limited heater is between 1.1 and 10, between

2 and 8, or between 3 and 6 (for example, the turndown ratio is at least 1.1, at least 2, or at least 3).

FIG. **37** depicts an embodiment of a temperature limited heater in which the support member provides a majority of the heat output below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. Core **508** is an inner conductor of the temperature limited heater. In certain embodiments, core **508** is a highly electrically conductive material such as copper or aluminum. In some embodiments, core **508** is a copper alloy that provides mechanical strength and good electrically conductivity such as a dispersion strengthened copper. In one embodiment, core **508** is Glidcop® (SCM Metal Products, Inc., Research Triangle Park, N.C., U.S.A.). Ferromagnetic conductor **512** is a thin layer of ferromagnetic material between electrical conductor **538** and core **508**. In certain embodiments, electrical conductor **538** is also support member **514**. In certain embodiments, ferromagnetic conductor **512** is iron or an iron alloy. In some embodiments, ferromagnetic conductor **512** includes ferromagnetic material with a high relative magnetic permeability. For example, ferromagnetic conductor **512** may be purified iron such as Armco ingot iron (AK Steel Ltd., United Kingdom). Iron with some impurities typically has a relative magnetic permeability on the order of 400. Purifying the iron by annealing the iron in hydrogen gas (H_2) at 1450° C. increases the relative magnetic permeability of the iron. Increasing the relative magnetic permeability of ferromagnetic conductor **512** allows the thickness of the ferromagnetic conductor to be reduced. For example, the thickness of unpurified iron may be approximately 4.5 mm while the thickness of the purified iron is approximately 0.76 mm.

In certain embodiments, electrical conductor **538** provides support for ferromagnetic conductor **512** and the temperature limited heater. Electrical conductor **538** may be made of a material that provides good mechanical strength at temperatures near or above the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**. In certain embodiments, electrical conductor **538** is a corrosion resistant member. Electrical conductor **538** (support member **514**) may provide support for ferromagnetic conductor **512** and corrosion resistance. Electrical conductor **538** is made from a material that provides desired electrically resistive heat output at temperatures up to and/or above the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**.

In an embodiment, electrical conductor **538** is 347H stainless steel. In some embodiments, electrical conductor **538** is another electrically conductive, good mechanical strength, corrosion resistant material. For example, electrical conductor **538** may be 304H, 316H, 347HH, NF709, Incoloy® 800H alloy (Inco Alloys International, Huntington, West Va., U.S.A.), Haynes® HR120® alloy, or Inconel® 617 alloy.

In some embodiments, electrical conductor **538** (support member **514**) includes different alloys in different portions of the temperature limited heater. For example, a lower portion of electrical conductor **538** (support member **514**) is 347H stainless steel and an upper portion of the electrical conductor (support member) is NF709. In certain embodiments, different alloys are used in different portions of the electrical conductor (support member) to increase the mechanical strength of the electrical conductor (support member) while maintaining desired heating properties for the temperature limited heater.

In some embodiments, ferromagnetic conductor **512** includes different ferromagnetic conductors in different portions of the temperature limited heater. Different ferromagnetic conductors may be used in different portions of the temperature limited heater to vary the Curie temperature and/or the phase transformation temperature range and, thus, the maximum operating temperature in the different portions. In some embodiments, the Curie temperature and/or the phase transformation temperature range in an upper portion of the temperature limited heater is lower than the Curie temperature and/or the phase transformation temperature range in a lower portion of the heater. The lower Curie temperature and/or the phase transformation temperature range in the upper portion increases the creep-rupture strength lifetime in the upper portion of the heater.

In the embodiment depicted in FIG. **37**, ferromagnetic conductor **512**, electrical conductor **538**, and core **508** are dimensioned so that the skin depth of the ferromagnetic conductor limits the penetration depth of the majority of the flow of electrical current to the support member when the temperature is below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. Thus, electrical conductor **538** provides a majority of the electrically resistive heat output of the temperature limited heater at temperatures up to a temperature at or near the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**. In certain embodiments, the temperature limited heater depicted in FIG. **37** is smaller (for example, an outside diameter of 3 cm, 2.9 cm, 2.5 cm, or less) than other temperature limited heaters that do not use electrical conductor **538** to provide the majority of electrically resistive heat output. The temperature limited heater depicted in FIG. **37** may be smaller because ferromagnetic conductor **512** is thin as compared to the size of the ferromagnetic conductor needed for a temperature limited heater in which the majority of the resistive heat output is provided by the ferromagnetic conductor.

In some embodiments, the support member and the corrosion resistant member are different members in the temperature limited heater. FIGS. **38** and **39** depict embodiments of temperature limited heaters in which the jacket provides a majority of the heat output below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. In these embodiments, electrical conductor **538** is jacket **506**. Electrical conductor **538**, ferromagnetic conductor **512**, support member **514**, and core **508** (in FIG. **38**) or inner conductor **490** (in FIG. **39**) are dimensioned so that the skin depth of the ferromagnetic conductor limits the penetration depth of the majority of the flow of electrical current to the thickness of the jacket. In certain embodiments, electrical conductor **538** is a material that is corrosion resistant and provides electrically resistive heat output below the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**. For example, electrical conductor **538** is 825 stainless steel or 347H stainless steel. In some embodiments, electrical conductor **538** has a small thickness (for example, on the order of 0.5 mm).

In FIG. **38**, core **508** is highly electrically conductive material such as copper or aluminum. Support member **514** is 347H stainless steel or another material with good mechanical strength at or near the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**.

In FIG. **39**, support member **514** is the core of the temperature limited heater and is 347H stainless steel or another material with good mechanical strength at or near the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**. Inner conductor **490** is highly electrically conductive material such as copper or aluminum.

In certain embodiments, the materials and design of the temperature limited heater are chosen to allow use of the heater at high temperatures (for example, above 850° C.). FIG. **40** depicts a high temperature embodiment of the temperature limited heater. The heater depicted in FIG. **40** operates as a conductor-in-conduit heater with the majority of heat being generated in conduit **518**. The conductor-in-conduit heater may provide a higher heat output because the majority of heat is generated in conduit **518** rather than conductor **516**. Having the heat generated in conduit **518** reduces heat losses associated with transferring heat between the conduit and conductor **516**.

Core **508** and conductive layer **510** are copper. In some embodiments, core **508** and conductive layer **510** are nickel if the operating temperatures is to be near or above the melting point of copper. Support members **514** are electrically conductive materials with good mechanical strength at high temperatures. Materials for support members **514** that withstand at least a maximum temperature of about 870° C. may be, but are not limited to, MO-RE® alloys (Duraloy Technologies, Inc. (Scottdale, Pa., U.S.A.)), CF8C+(Metaltek Intl. (Waukesha, Wis., U.S.A.)), or Inconel® 617 alloy. Materials for support members **514** that withstand at least a maximum temperature of about 980° C. include, but are not limited to, Incoloy® Alloy MA 956. Support member **514** in conduit **518** provides mechanical support for the conduit. Support member **514** in conductor **516** provides mechanical support for core **508**.

Electrical conductor **538** is a thin corrosion resistant material. In certain embodiments, electrical conductor **538** is 347H, 617, 625, or 800H stainless steel. Ferromagnetic conductor **512** is a high Curie temperature ferromagnetic material such as iron-cobalt alloy (for example, a 15% by weight cobalt, iron-cobalt alloy).

In certain embodiments, electrical conductor **538** provides the majority of heat output of the temperature limited heater at temperatures up to a temperature at or near the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**. Conductive layer **510** increases the turndown ratio of the temperature limited heater.

For long vertical temperature limited heaters (for example, heaters at least 300 m, at least 500 m, or at least 1 km in length), the hanging stress becomes important in the selection of materials for the temperature limited heater. Without the proper selection of material, the support member may not have sufficient mechanical strength (for example, creep-rupture strength) to support the weight of the temperature limited heater at the operating temperatures of the heater. FIG. **41** depicts hanging stress (ksi (kilopounds per square inch)) versus outside diameter (in.) for the temperature limited heater shown in FIG. **37** with 347H as the support member. The hanging stress was assessed with the support member outside a 0.5" copper core and a 0.75" outside diameter carbon steel ferromagnetic conductor. This assessment assumes the support member bears the entire load of the heater and that the heater length is 1000 ft. (about 305 m). As shown in FIG. **41**, increasing the thickness of the support member decreases the hanging stress on the support member. Decreasing the hanging stress on the support member allows the temperature limited heater to operate at higher temperatures.

In certain embodiments, materials for the support member are varied to increase the maximum allowable hanging stress at operating temperatures of the temperature limited heater and, thus, increase the maximum operating temperature of the temperature limited heater. Altering the materials of the support member affects the heat output of the temperature limited heater below the Curie temperature and/or the phase transformation temperature range because changing the materials changes the resistance versus temperature profile of the support member. In certain embodiments, the support member is made of more than one material along the length of the heater so that the temperature limited heater maintains desired operating properties (for example, resistance versus temperature profile below the Curie temperature and/or the phase transformation temperature range) as much as possible while providing sufficient mechanical properties to support the heater.

FIG. **42** depicts hanging stress (ksi) versus temperature (° F.) for several materials and varying outside diameters for the temperature limited heaters. Curve **540** is for 347H stainless steel. Curve **542** is for Incoloy® alloy 800H. Curve **544** is for Haynes® HR120® alloy. Curve **546** is for NF709. Each of the curves includes four points that represent various outside diameters of the support member. The point with the highest stress for each curve corresponds to outside diameter of 1.05". The point with the second highest stress for each curve corresponds to outside diameter of 1.15". The point with the second lowest stress for each curve corresponds to outside diameter of 1.25". The point with the lowest stress for each curve corresponds to outside diameter of 1.315". As shown in FIG. **42**, increasing the strength and/or outside diameter of the material and the support member increases the maximum operating temperature of the temperature limited heater.

FIGS. **43**, **44**, **45**, and **46** depict examples of embodiments for temperature limited heaters able to provide desired heat output and mechanical strength for operating temperatures up to about 770° C. for 30,000 hrs. creep-rupture lifetime. The depicted temperature limited heaters have lengths of 1000 ft, copper cores of 0.5" diameter, and iron ferromagnetic conductors with outside diameters of 0.765". In FIG. **43**, the support member in heater portion **548** is 347H stainless steel. The support member in heater portion **550** is Incoloy® alloy 800H. Portion **548** has a length of 750 ft. and portion **550** has a length of 250 ft. The outside diameter of the support member is 1.315". In FIG. **44**, the support member in heater portion **548** is 347H stainless steel. The support member in heater portion **550** is Incoloy® alloy 800H. The support member in heater portion **552** is Haynes® HR120® alloy. Portion **548** has a length of 650 ft., portion **550** has a length of 300 ft., and portion **552** has a length of 50 ft. The outside diameter of the support member is 1.15". In FIG. **45**, the support member in heater portion **548** is 347H stainless steel. The support member in heater portion **550** is Incoloy® alloy 800H. The support member in heater portion **552** is Haynes® HR120® alloy. Portion **548** has a length of 550 ft., portion **550** has a length of 250 ft., and portion **552** has a length of 200 ft. The outside diameter of the support member is 1.05".

In some embodiments, a transition section is used between sections of the heater. For example, if one or more portions of the heater have varying Curie temperatures and/or phase transformation temperature ranges, a transition section may be used between portions to provide strength that compensates for the differences in temperatures in the portions. FIG. **46** depicts another example of an embodiment of a temperature limited heater able to provide desired heat output and mechanical strength. The support member in heater portion **548** is 347H stainless steel. The support member in heater portion **550** is NF709. The support member in heater portion **552** is 347H. Portion **548** has a length of 550 ft. and a Curie temperature of 843° C., portion **550** has a length of 250 ft. and a Curie temperature of 843° C., and portion **552** has a length of 180 ft. and a Curie temperature of 770° C. Transition section **554** has a length of 20 ft., a Curie temperature of 770° C., and the support member is NF709.

The materials of the support member along the length of the temperature limited heater may be varied to achieve a variety of desired operating properties. The choice of the materials of the temperature limited heater is adjusted depending on a desired use of the temperature limited heater. TABLE 2 lists examples of materials that may be used for the support member. The table provides the hanging stresses (a) of the support members and the maximum operating temperatures of the temperature limited heaters for several different outside diameters (OD) of the support member. The core diameter and the outside diameter of the iron ferromagnetic conductor in each case are 0.5" and 0.765", respectively.

TABLE 2

	OD = 1.05"		OD = 1.15"		OD = 1.25"		OD = 1.315"	
Material	σ (ksi)	T (° F.)	σ (ksi)	T (° F.)	σ (ksi)	T (° F.)	σ (ksi)	T (° F.)
347H stainless steel	7.55	1310	6.33	1340	5.63	1360	5.31	1370
Incoloy ® alloy 800H	7.55	1337	6.33	1378	5.63	1400	5.31	1420
Haynes ® HR120 ® alloy	7.57	1450	6.36	1492	5.65	1520	5.34	1540
HA230	7.91	1475	6.69	1510	5.99	1530	5.67	1540
Haynes ® alloy 556	7.65	1458	6.43	1492	5.72	1512	5.41	1520
NF709	7.57	1440	6.36	1480	5.65	1502	5.34	1512

In certain embodiments, one or more portions of the temperature limited heater have varying outside diameters and/or materials to provide desired properties for the heater. FIGS. **47** and **48** depict examples of embodiments for temperature limited heaters that vary the diameter and/or materials of the support member along the length of the heaters to provide desired operating properties and sufficient mechanical properties (for example, creep-rupture strength properties) for operating temperatures up to about 834° C. for 30,000 hrs., heater lengths of 850 ft, a copper core diameter of 0.5", and an iron-cobalt (6% by weight cobalt) ferromagnetic conductor outside diameter of 0.75". In FIG. **47**, portion **548** is 347H stainless steel with a length of 300 ft and an outside diameter of 1.15". Portion **550** is NF709 with a length of 400 ft and an outside diameter of 1.15". Portion **552** is NF709 with a length of 150 ft and an outside diameter of 1.25". In FIG. **48**, portion **548** is 347H stainless steel with a length of 300 ft and an outside diameter of 1.15". Portion **550** is 347H stainless steel with a length of 100 ft and an outside diameter of 1.20". Portion **552** is NF709 with a length of 350 ft and an outside diameter of 1.20". Portion **556** is NF709 with a length of 100 ft and an outside diameter of 1.25".

In certain embodiments, one or more portions of the temperature limited heater have varying dimensions and/or varying materials to provide different power outputs along the length of the heater. More or less power output may be provided by varying the selected temperature (for example, the Curie temperature and/or the phase transformation temperature range) of the temperature limited heater by using different ferromagnetic materials along its length and/or by varying the electrical resistance of the heater by using different dimensions in the heat generating member along the length of the heater. Different power outputs along the length of the temperature limited heater may be needed to compensate for different thermal properties in the formation adjacent to the heater. For example, an oil shale formation may have different water-filled porosities, dawsonite compositions, and/or nahcolite compositions at different depths in the formation. Portions of the formation with higher water-filled porosities, higher dawsonite compositions, and/or higher nahcolite compositions may need more power input than portions with lower water-filled porosities, lower dawsonite compositions, and/or lower nahcolite compositions to achieve a similar heating rate. Power output may be varied along the length of the heater so that the portions of the formation with different properties (such as water-filled porosities, dawsonite compositions, and/or nahcolite compositions) are heated at approximately the same heating rate.

In certain embodiments, portions of the temperature limited heater have different selected self-limiting temperatures (for example, Curie temperatures and/or phase transformation temperature ranges), materials, and/or dimensions to compensate for varying thermal properties of the formation along the length of the heater. For example, Curie temperatures, phase transformation temperature ranges, support member materials, and/or dimensions of the portions of the heaters depicted in FIGS. **43-48** may be varied to provide varying power outputs and/or operating temperatures along the length of the heater.

As one example, in an embodiment of the temperature limited heater depicted in FIG. **43**, portion **550** may be used to heat portions of the formation that, on average, have higher water-filled porosities, dawsonite compositions, and/or nahcolite compositions than portions of the formation heated by portion **548**. Portion **550** may provide less power output than portion **548** to compensate for the differing thermal properties of the different portions of the formation so that the entire formation is heated at an approximately constant heating rate. Portion **550** may require less power output because, for example, portion **550** is used to heat portions of the formation with low water-filled porosities and/or little or no dawsonite. In one embodiment, portion **550** has a Curie temperature of 770° C. (pure iron) and portion **548** has a Curie temperature of 843° C. (iron with added cobalt). Such an embodiment may provide more power output from portion **548** so that the temperature lag between the two portions is reduced. Adjusting the Curie temperature of portions of the heater adjusts the selected temperature at which the heater self-limits. In some embodiments, the dimensions of portion **550** are adjusted to further reduce the temperature lag so that the formation is heated at an approximately constant heating rate throughout the formation. Dimensions of the heater may be adjusted to adjust the heating rate of one or more portions of the heater. For example, the thickness of an outer conductor in portion **550** may be increased relative to the ferromagnetic member

and/or the core of the heater so that the portion has a higher electrical resistance and the portion provides a higher power output below the Curie temperature of the portion.

Reducing the temperature lag between different portions of the formation may reduce the overall time needed to bring the formation to a desired temperature. Reducing the time needed to bring the formation to the desired temperature reduces heating costs and produces desirable production fluids more quickly.

Temperature limited heaters with varying Curie temperatures and/or phase transformation temperature ranges may also have varying support member materials to provide mechanical strength for the heater (for example, to compensate for hanging stress of the heater and/or provide sufficient creep-rupture strength properties). For example, in the embodiment of the temperature limited heater depicted in FIG. **46**, portions **548** and **550** have a Curie temperature of 843° C. Portion **548** has a support member made of 347H stainless steel. Portion **550** has a support member made of NF709. Portion **552** has a Curie temperature of 770° C. and a support member made of 347H stainless steel. Transition section **554** has a Curie temperature of 770° C. and a support member made of NF709. Transition section **554** may be short in length compared to portions **548**, **550**, and **552**. Transition section **554** may be placed between portions **550** and **552** to compensate for the temperature and material differences between the portions. For example, transition section **554** may be used to compensate for differences in creep properties between portions **550** and **552**.

Such a substantially vertical temperature limited heater may have less expensive, lower strength materials in portion **552** because of the lower Curie temperature in this portion of the heater. For example, 347H stainless steel may be used for the support member because of the lower maximum operating temperature of portion **552** as compared to portion **550**. Portion **550** may require more expensive, higher strength material because of the higher operating temperature of portion **550** due to the higher Curie temperature in this portion.

In some embodiments, a relatively thin conductive layer is used to provide the majority of the electrically resistive heat output of the temperature limited heater at temperatures up to a temperature at or near the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor. Such a temperature limited heater may be used as the heating member in an insulated conductor heater. The heating member of the insulated conductor heater may be located inside a sheath with an insulation layer between the sheath and the heating member.

FIGS. **49**A and **49**B depict cross-sectional representations of an embodiment of the insulated conductor heater with the temperature limited heater as the heating member. Insulated conductor **558** includes core **508**, ferromagnetic conductor **512**, inner conductor **490**, electrical insulator **500**, and jacket **506**. Core **508** is a copper core. Ferromagnetic conductor **512** is, for example, iron or an iron alloy.

Inner conductor **490** is a relatively thin conductive layer of non-ferromagnetic material with a higher electrical conductivity than ferromagnetic conductor **512**. In certain embodiments, inner conductor **490** is copper. Inner conductor **490** may be a copper alloy. Copper alloys typically have a flatter resistance versus temperature profile than pure copper. A flatter resistance versus temperature profile may provide less variation in the heat output as a function of temperature up to the Curie temperature and/or the phase transformation temperature range. In some embodiments, inner conductor **490** is copper with 6% by weight nickel (for example, CuNi6 or LOHM™). In some embodiments, inner conductor **490** is CuNi10Fe1Mn alloy. Below the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**, the magnetic properties of the ferromagnetic conductor confine the majority of the flow of electrical current to inner conductor **490**. Thus, inner conductor **490** provides the majority of the resistive heat output of insulated conductor **558** below the Curie temperature and/or the phase transformation temperature range.

In certain embodiments, inner conductor **490** is dimensioned, along with core **508** and ferromagnetic conductor **512**, so that the inner conductor provides a desired amount of heat output and a desired turndown ratio. For example, inner conductor **490** may have a cross-sectional area that is around 2 or 3 times less than the cross-sectional area of core **508**. Typically, inner conductor **490** has to have a relatively small cross-sectional area to provide a desired heat output if the inner conductor is copper or copper alloy. In an embodiment with copper inner conductor **490**, core **508** has a diameter of 0.66 cm, ferromagnetic conductor **512** has an outside diameter of 0.91 cm, inner conductor **490** has an outside diameter of 1.03 cm, electrical insulator **500** has an outside diameter of 1.53 cm, and jacket **506** has an outside diameter of 1.79 cm. In an embodiment with a CuNi6 inner conductor **490**, core **508** has a diameter of 0.66 cm, ferromagnetic conductor **512** has an outside diameter of 0.91 cm, inner conductor **490** has an outside diameter of 1.12 cm, electrical insulator **500** has an outside diameter of 1.63 cm, and jacket **506** has an outside diameter of 1.88 cm. Such insulated conductors are typically smaller and cheaper to manufacture than insulated conductors that do not use the thin inner conductor to provide the majority of heat output below the Curie temperature and/or the phase transformation temperature range.

Electrical insulator **500** may be magnesium oxide, aluminum oxide, silicon dioxide, beryllium oxide, boron nitride, silicon nitride, or combinations thereof. In certain embodiments, electrical insulator **500** is a compacted powder of magnesium oxide. In some embodiments, electrical insulator **500** includes beads of silicon nitride.

In certain embodiments, a small layer of material is placed between electrical insulator **500** and inner conductor **490** to inhibit copper from migrating into the electrical insulator at higher temperatures. For example, the small layer of nickel (for example, about 0.5 mm of nickel) may be placed between electrical insulator **500** and inner conductor **490**.

Jacket **506** is made of a corrosion resistant material such as, but not limited to, 347 stainless steel, 347H stainless steel, 446 stainless steel, or 825 stainless steel. In some embodiments, jacket **506** provides some mechanical strength for insulated conductor **558** at or above the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor **512**. In certain embodiments, jacket **506** is not used to conduct electrical current.

In certain embodiments of temperature limited heaters, three temperature limited heaters are coupled together in a three-phase wye configuration. Coupling three temperature limited heaters together in the three-phase wye configuration lowers the current in each of the individual temperature limited heaters because the current is split between the three individual heaters. Lowering the current in each individual temperature limited heater allows each heater to have a small diameter. The lower currents allow for higher relative magnetic permeabilities in each of the individual temperature limited heaters and, thus, higher turndown ratios. In addition, there may be no return current needed for each of the individual temperature limited heaters. Thus, the turndown ratio

remains higher for each of the individual temperature limited heaters than if each temperature limited heater had its own return current path.

In the three-phase wye configuration, individual temperature limited heaters may be coupled together by shorting the sheaths, jackets, or canisters of each of the individual temperature limited heaters to the electrically conductive sections (the conductors providing heat) at their terminating ends (for example, the ends of the heaters at the bottom of a heater wellbore). In some embodiments, the sheaths, jackets, canisters, and/or electrically conductive sections are coupled to a support member that supports the temperature limited heaters in the wellbore.

FIG. **50**A depicts an embodiment for installing and coupling heaters in a wellbore. The embodiment in FIG. **50**A depicts insulated conductor heaters being installed into the wellbore. Other types of heaters, such as conductor-in-conduit heaters, may also be installed in the wellbore using the embodiment depicted. Also, in FIG. **50**A, two insulated conductors **558** are shown while a third insulated conductor is not seen from the view depicted. Typically, three insulated conductors **558** would be coupled to support member **560**, as shown in FIG. **50**B. In an embodiment, support member **560** is a thick walled 347H pipe. In some embodiments, thermocouples or other temperature sensors are placed inside support member **560**. The three insulated conductors may be coupled in a three-phase wye configuration.

In FIG. **50**A, insulated conductors **558** are coiled on coiled tubing rigs **562**. As insulated conductors **558** are uncoiled from rigs **562**, the insulated conductors are coupled to support member **560**. In certain embodiments, insulated conductors **558** are simultaneously uncoiled and/or simultaneously coupled to support member **560**. Insulated conductors **558** may be coupled to support member **560** using metal (for example, 304 stainless steel or Inconel® alloys) straps **564**. In some embodiments, insulated conductors **558** are coupled to support member **560** using other types of fasteners such as buckles, wire holders, or snaps. Support member **560** along with insulated conductors **558** are installed into opening **522**. In some embodiments, insulated conductors **558** are coupled together without the use of a support member. For example, one or more straps **564** may be used to couple insulated conductors **558** together.

Insulated conductors **558** may be electrically coupled to each other at a lower end of the insulated conductors. In a three-phase wye configuration, insulated conductors **558** operate without a current return path. In certain embodiments, insulated conductors **558** are electrically coupled to each other in contactor section **566**. In section **566**, sheaths, jackets, canisters, and/or electrically conductive sections are electrically coupled to each other and/or to support member **560** so that insulated conductors **558** are electrically coupled in the section.

In certain embodiments, the sheaths of insulated conductors **558** are shorted to the conductors of the insulated conductors. FIG. **50**C depicts an embodiment of insulated conductor **558** with the sheath shorted to the conductors. Sheath **506** is electrically coupled to core **508**, ferromagnetic conductor **512**, and inner conductor **490** using termination **568**. Termination **568** may be a metal strip or a metal plate at the lower end of insulated conductor **558**. For example, termination **568** may be a copper plate coupled to sheath **506**, core **508**, ferromagnetic conductor **512**, and inner conductor **490** so that they are shorted together. In some embodiments, termination **568** is welded or brazed to sheath **506**, core **508**, ferromagnetic conductor **512**, and inner conductor **490**.

The sheaths of individual insulated conductors **558** may be shorted together to electrically couple the conductors of the insulated conductors, depicted in FIGS. **50**A and **50**B. In some embodiments, the sheaths may be shorted together because the sheaths are in physical contact with each other. For example, the sheaths may in physical contact if the sheaths are strapped together by straps **564**. In some embodiments, the lower ends of the sheaths are physically coupled (for example, welded) at the surface of opening **522** before insulated conductors **558** are installed into the opening.

In certain embodiments, coupling multiple heaters (for example, insulated conductor, or mineral insulated conductor, heaters) to a single power source, such as a transformer, is advantageous. Coupling multiple heaters to a single transformer may result in using fewer transformers to power heaters used for a treatment area as compared to using individual transformers for each heater. Using fewer transformers reduces surface congestion and allows easier access to the heaters and surface components. Using fewer transformers reduces capital costs associated with providing power to the treatment area. In some embodiments, at least 4, at least 5, at least 10, at least 25 heaters, at least 35 heaters, or at least 45 heaters are powered by a single transformer. Additionally, powering multiple heaters (in different heater wells) from the single transformer may reduce overburden losses because of reduced voltage and/or phase differences between each of the heater wells powered by the single transformer. Powering multiple heaters from the single transformer may inhibit current imbalances between the heaters because the heaters are coupled to the single transformer.

In order to provide power to multiple heaters using the single transformer, the transformer may have to provide power at higher voltages to carry the current to each of the heaters effectively. In certain embodiments, the heaters are floating (ungrounded) heaters in the formation. Floating the heaters allows the heaters to operate at higher voltages. In some embodiments, the transformer provides power output of at least about 3 kV, at least about 4 kV, at least about 5 kV, or at least about 6 kV.

FIG. **51** depicts a top view representation of heater **716** with three insulated conductors **558** in conduit **536**. Heater **716** includes three insulated conductors **558** in conduit **536**. Heater **716** may be located in a heater well in the subsurface formation. Conduit **536** may be a sheath, jacket, or other enclosure around insulated conductors **558**. Each insulated conductor **558** includes core **508**, electrical insulator **500**, and jacket **506**. Insulated conductors **558** may be mineral insulated conductors with core **508** being a copper alloy (for example, a copper-nickel alloy such as Alloy 180), electrical insulator **500** being magnesium oxide, and jacket **506** being Incoloy® 825, copper, or stainless steel (for example 347H stainless steel). In some embodiments, jacket **506** includes non-work hardenable metals so that the jacket is annealable.

In some embodiments, core **508** and/or jacket **506** include ferromagnetic materials. In some embodiments, one or more insulated conductors **558** are temperature limited heaters. In certain embodiments, the overburden portion of insulated conductors **558** include high electrical conductivity materials in core **508** (for example, pure copper or copper alloys such as copper with 3% silicon at a weld joint) so that the overburden portions of the insulated conductors provide little or no heat output. In certain embodiments, conduit **536** includes non-corrosive materials and/or high strength materials such as stainless steel. In one embodiment, conduit **536** is 347H stainless steel.

Insulated conductors **558** may be coupled to the single transformer in a three-phase configuration (for example, a

three-phase wye configuration). Each insulated conductor **558** may be coupled to one phase of the single transformer. In certain embodiments, the single transformer is also coupled to a plurality of identical heaters **716** in other heater wells in the formation (for example, the single transformer may couple to 40 heaters or more **716** in the formation). In some embodiments, the single transformer couples to at least 4, at least 5, at least 10, at least 15, or at least 25 additional heaters in the formation.

FIG. **52** depicts an embodiment of three-phase wye transformer **728** coupled to a plurality of heaters **716**. For simplicity in the drawing, only four heaters **716** are shown in FIG. **52**. It is to be understood that several more heaters may be coupled to the transformer **728**. As shown in FIG. **52**, each leg (each insulated conductor) of each heater is coupled to one phase of transformer **728** and current returned to the neutral or ground of the transformer (for example, returned through conductor **2024** depicted in FIGS. **51** and **53**).

Electrical insulator **500'** may be located inside conduit **536** to electrically insulate insulated conductors **558** from the conduit. In certain embodiments, electrical insulator **500'** is magnesium oxide (for example, compacted magnesium oxide). In some embodiments, electrical insulator **500'** is silicon nitride (for example, silicon nitride blocks). Electrical insulator **500'** electrically insulates insulated conductors **558** from conduit **536** so that at high operating voltages (for example, 3 kV or higher), there is no arcing between the conductors and the conduit. In some embodiments, electrical insulator **500'** inside conduit **536** has at least the thickness of electrical insulators **500** in insulated conductors **558**. The increased thickness of insulation in heater **716** (from electrical insulators **500** and/or electrical insulator **500'**) inhibits and may prevent current leakage into the formation from the heater. In some embodiments, electrical insulator **500'** spatially locates insulated conductors **558** inside conduit **536**.

Return conductor **2024** may be electrically coupled to the ends of insulated conductors **558** (as shown in FIG. **53**) and return current from the ends of the insulated conductors to the transformer on the surface of the formation. Return conductor **2024** may include high electrical conductivity materials such as pure copper, nickel, copper alloys, or combinations thereof so that the return conductor provides little or no heat output. In some embodiments, return conductor **2024** is a tubular (for example, a stainless steel tubular) that allows an optical fiber to be placed inside the tubular and used for temperature measurement. In some embodiments, return conductor **2024** is a small insulated conductor (for example, small mineral insulated conductor). Return conductor **2024** may be coupled to the neutral or ground leg of the transformer in a three-phase wye configuration. Thus, insulated conductors **558** are electrically isolated from conduit **536** and the formation. Using return conductor **2024** to return current to the surface may make coupling the heater to a wellhead easier. In some embodiments, current is returned using one or more of jackets **506**, depicted in FIG. **51**. One or more jackets **506** may be coupled to cores **508** at the end of the heaters and return current to the neutral of the three-phase wye transformer.

FIG. **53** depicts a side view representation of the end section of three insulated conductors **558** in conduit **536**. The end section is the section of the heaters the furthest away from (distal from) the surface of the formation. The end section includes contactor section **566** coupled to conduit **536**. In some embodiments, contactor section **566** is welded or brazed to conduit **536**. Termination **568** is located in contactor section **566**. Termination **568** is electrically coupled to insulated conductors **558** and return conductor **2024**. Termination **568** electrically couples the cores of insulated conductors **558** to the return conductor **2024** at the ends of the heaters.

In certain embodiments, heater **716**, depicted in FIGS. **51** and **53**, includes an overburden section using copper as the core of the insulated conductors. The copper in the overburden section may be the same diameter as the cores used in the heating section of the heater. The copper in the overburden section may also have a larger diameter than the cores in the heating section of the heater. Increasing the size of the copper in the overburden section may decrease losses in the overburden section of the heater.

Heaters that include three insulated conductors **558** in conduit **536**, as depicted in FIGS. **51** and **53**, may be made in a multiple step process. In some embodiments, the multiple step process is performed at the site of the formation or treatment area. In some embodiments, the multiple step process is performed at a remote manufacturing site away from the formation. The finished heater is then transported to the treatment area.

Insulated conductors **558** may be pre-assembled prior to the bundling either on site or at a remote location. Insulated conductors **558** and return conductor **2024** may be positioned on spools. A machine may draw insulated conductors **558** and return conductor **2024** from the spools at a selected rate. Preformed blocks of insulation material may be positioned around return conductor **2024** and insulated conductors **558**. In an embodiment, two blocks are positioned around return conductor **2024** and three blocks are positioned around insulated conductors **558** to form electrical insulator **500'**. The insulated conductors and return conductor may be drawn or pushed into a plate of conduit material that has been rolled into a tubular shape. The edges of the plate may be pressed together and welded (for example, by laser welding). After forming conduit **536** around electrical insulator **500'**, the bundle of insulated conductors **558**, and return conductor **2024**, the conduit may be compacted against the electrical insulator **2024** so that all of the components of the heater are pressed together into a compact and tightly fitting form. During the compaction, the electrical insulator may flow and fill any gaps inside the heater.

In some embodiments, heater **716** (which includes conduit **536** around electrical insulator **500'** and the bundle of insulated conductors **558** and return conductor **2024**) is inserted into a coiled tubing tubular that is placed in a wellbore in the formation. The coiled tubing tubular may be left in place in the formation (left in during heating of the formation) or removed from the formation after installation of the heater. The coiled tubing tubular may allow for easier installation of heater **716** into the wellbore.

In some embodiments, one or more components of heater **716** are varied (for example, removed, moved, or replaced) while the operation of the heater remains substantially identical. FIG. **54** depicts one alternative embodiment of heater **716** with three insulated cores **508** in conduit **536**. In this embodiment, electrical insulator **500'** surrounds cores **508** and return conductor **2024** in conduit **536**. Cores **508** are located in conduit **536** without electrical insulator **500** and jacket **506** surrounding the cores. Cores **508** are coupled to the single transformer in a three-phase wye configuration with each core **508** coupled to one phase of the transformer. Return conductor **2024** is electrically coupled to the ends of cores **508** and returns current from the ends of the cores to the transformer on the surface of the formation.

FIG. **55** depicts another alternative embodiment of heater **716** with three insulated conductors **558** and insulated return conductor in conduit **536**. In this embodiment, return conductor **2024** is an insulated conductor with core **508**, electrical

insulator **500**, and jacket **506**. Return conductor **2024** and insulated conductors **558** are located in conduit **536** are surrounded by electrical insulator **500** and conduit **536**. Return conductor **2024** and insulated conductors **558** may be the same size or different sizes. Return conductor **2024** and insulated conductors **558** operate substantially the same as in the embodiment depicted in FIGS. **51** and **53**.

FIG. **56** depicts an embodiment of insulated conductor **558** in conduit **518** with molten metal. Insulated conductor **558** and conduit **518** may be placed in an opening in a subsurface formation. Insulated conductor **558** and conduit **518** may have any orientation in a subsurface formation (for example, the insulated conductor and conduit may be substantially vertical or substantially horizontally oriented in the formation). Insulated conductor **558** includes core **508**, electrical insulator **500**, and jacket **506**. In some embodiments, core **508** is a copper core. In some embodiments, core **508** includes other electrical conductors or alloys (for example, copper alloys). In some embodiments, core **508** includes a ferromagnetic conductor so that insulated conductor **558** operates as a temperature limited heater.

Electrical insulator **500** may be magnesium oxide, aluminum oxide, silicon dioxide, beryllium oxide, boron nitride, silicon nitride, or combinations thereof. In certain embodiments, electrical insulator **500** is a compacted powder of magnesium oxide. In some embodiments, electrical insulator **500** includes beads of silicon nitride. In certain embodiments, a small layer of material is placed between electrical insulator **500** and core **508** to inhibit copper from migrating into the electrical insulator at higher temperatures. For example, the small layer of nickel (for example, about 0.5 mm of nickel) may be placed between electrical insulator **500** and core **508**.

Jacket **506** is made of a corrosion resistant material such as, but not limited to, 347 stainless steel, 347H stainless steel, 446 stainless steel, or 825 stainless steel. In some embodiments, jacket **506** is not used to conduct electrical current.

In an embodiment, core **508** has a diameter of about 1 cm, electrical insulator **500** has an outside diameter of about 1.6 cm, and jacket **506** has an outside diameter of about 1.8 cm.

In certain embodiments, molten metal **2026** is placed inside conduit **518** in the space outside of insulated conductor **558**. In certain embodiments, molten metal **2026** is placed in as balls or pellets of metal. The metal balls or pellets may be made of metal that melts below operating temperatures of insulated conductor **558** but above ambient subsurface formation temperatures. The metal balls or pellets may be placed in conduit **518** after insulated conductor **558** is placed in the conduit. In certain embodiments, molten metal **2026** is placed in as a molten liquid. The molten liquid may be placed in conduit **518** before or after insulated conductor **558** is placed in the conduit (for example, the molten liquid may be poured into the conduit before or after the insulated conductor is placed in the conduit). Additionally, the molten liquid, or the metal balls or pellets, may be placed in conduit **518** before or after insulated conductor **558** is energized (turned on).

Molten metal **2026** may remain a molten liquid at operating temperatures of insulated conductor **558**. In some embodiments, molten metal **2026** melts at temperatures above about 100° C., above about 200° C., or above about 300° C. Molten metal **2026** may remain a molten liquid at temperatures up to about 1400° C., about 1500° C., or about 1600° C. In certain embodiments, molten metal **2026** is a good thermal conductor at or near the operating temperatures of insulated conductor **558**. Molten metal **2026** may include metals such as tin, zinc, an alloy such as a 60% by weight tin, 40% by weight zinc alloy; bismuth; cadmium, aluminum; lead; arsenic; and/or combinations thereof. In one embodiment, molten metal **2026** is tin. Molten metal **2026** may have a high Grashof number. Molten metals with high Grashof numbers will provide good convection currents in conduit **518**.

Molten metal **2026** fills the space between conduit **518** and insulated conductor **558**. Molten metal **2026** may increase heat transfer between conduit **518** and insulated conductor **558** by heat conduction through the molten metal and/or heat convection from movement of the molten metal in the conduit. The temperature differential between conduit **518** and insulated conductor **558** may create convection currents (heat generated movement) in the conduit. Convection of molten metal **2026** may inhibit hot spots along conduit **518** and insulated conductor **558**. Using molten metal **2026** allows insulated conductor **558** to be a smaller diameter insulated conductor, which may be easier and/or cheaper to manufacture.

In some embodiments, molten metal **2026** returns electrical current to the surface from insulated conductor **558** (the molten metal acts as the return or ground conductor for the insulated conductor). Molten metal **2026** may provide a large current path with low resistance so that a long heater (long insulated conductor **558**) is useable in conduit **518**. Molten metal **2026** may also inhibit ferromagnetic effects in conduit **518**, which allows longer heaters with lower voltages. The long heater may operate at low voltages for the length of the heater due to the presence of molten metal **2026**.

In certain embodiments, insulated conductor **558** is buoyant in the molten metal. The buoyancy of insulated conductor **558** reduces creep associated problems in long, substantially vertical heaters. A bottom weight or tie down may be coupled to the bottom of insulated conductor **558** to inhibit the insulated conductor from floating in the molten metal.

Conduit **518** may be a carbon steel or stainless steel canister. In an embodiment, conduit **518** is a canister of 410 stainless steel with an outside diameter of about 6 cm. Conduit **518** may have thin walls as molten metal **2026** may provide internal pressure that inhibits deformation or crushing of the conduit due to external stresses.

FIG. **57** depicts an embodiment of substantially horizontal insulated conductor **558** in conduit **518** with molten metal **2026**. Molten metal **2026** may provide a head in conduit **518** due to the pressure of the molten metal. This pressure head may keep molten metal **2026** in conduit **518**. The pressure head may also provide internal pressure that inhibits deformation or collapse of the conduit due to external stresses.

In some embodiments, a long temperature limited heater (for example, a temperature limited heater in which the support member provides a majority of the heat output below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic conductor) is formed from several sections of heater. The sections of heater may be coupled using a welding process. FIG. **58** depicts an embodiment for coupling together sections of a long temperature limited heater. Ends of ferromagnetic conductors **512** and ends of electrical conductors **538** (support members **514**) are beveled to facilitate coupling the sections of the heater. Core **508** has recesses to allow core coupling material **570** to be placed inside the abutted ends of the heater. Core coupling material **570** may be a pin or dowel that fits tightly in the recesses of cores **508**. Core coupling material **570** may be made out of the same material as cores **508** or a material suitable for coupling the cores together. Core coupling material **570** allows the heaters to be coupled together without welding cores **508** together. Cores **508** are coupled together as a "pin" or "box" joint.

Beveled ends of ferromagnetic conductors **512** and electrical conductors **538** may be coupled together with coupling material **572**. In certain embodiments, ends of ferromagnetic conductors **512** and electrical conductors **538** are welded (for example, orbital welded) together. Coupling material **572** may be 625 stainless steel or any other suitable non-ferromagnetic material for welding together ferromagnetic conductors **512** and/or electrical conductors **538**. Using beveled ends when coupling together sections of the heater may produce a reliable and durable coupling between the sections of the heater.

During heating with the temperature limited heater, core coupling material **570** may expand more radially than ferromagnetic conductors **512**, electrical conductors **538**, and/or coupling material **572**. The greater expansion of core coupling material **570** maintains good electrical contact with the core coupling material. At the coupling junction of the heater, electricity flows through core coupling material **570** rather than coupling material **572**. This flow of electricity inhibits heat generation at the coupling junction so that the junction remains at lower temperatures than other portions of the heater during application of electrical current to the heater. The corrosion resistance and strength of the coupling junction is increased by maintaining the junction at lower temperatures.

In certain embodiments, the junction may be enclosed in a shield during orbital welding to enhance and/or ensure reliability of the weld. If the junction is not enclosed, disturbance of the inert gas caused by wind, humidity or other conditions may cause oxidation and/or porosity of the weld. Without a shield, a first portion of the weld was formed and allowed to cool. A grinder would be used to remove the oxide layer. The process would be repeated until the weld was complete. Enclosing the junction in the shield with an inert gas allows the weld to be formed with no oxidation, thus allowing the weld to be formed in one pass with no need for grinding. Enclosing the junction increases the safety of forming the weld because the arc of the orbital welder is enclosed in the shield during welding. Enclosing the junction in the shield may reduce the time needed to form the weld. Without a shield, producing each weld may take 30 minutes or more. With the shield, each weld may take 10 minutes or less.

FIG. **59** depicts an embodiment of a shield for orbital welding sections of a long temperature limited heater. Orbital welding may also be used to form canisters for freeze wells from sections of pipe. Shield **574** may include upper plate **576**, lower plate **578**, inserts **580**, wall **582**, hinged door **584**, first clamp member **586**, and second clamp member **588**. Wall **582** may include one or more inert gas inlets. Wall **582**, upper plate **576**, and/or lower plate **578** may include one or more openings for monitoring equipment or gas purging. Shield **574** is configured to work with an orbital welder, such as AMI Power Supply (Model 227) and AMI Orbital Weld Head (Model 97-2375) available from Arc Machines, Inc. (Pacoima, Calif., U.S.A.). Inserts **580** may be withdrawn from upper plate **576** and lower plate **578**. The orbital weld head may be positioned in shield **574**. Shield **574** may be placed around a lower conductor of the conductors that are to be welded together. When shield is positioned so that the end of the lower conductor is at a desired position in the middle of the shield, first clamp member may be fastened to second clamp member to secure shield **574** to the lower conductor. The upper conductor may be positioned in shield **574**. Inserts **580** may be placed in upper plate **576** and lower plate **578**.

Hinged door **584** may be closed. When hinged door **584** is closed, shield **574** forms a substantially airtight seal around the portions to be welded together. The orbital welder may be located inside the shield. The orbital welder may weld the lower conductor to the upper conductor. In certain embodiments, an inert gas (such as argon or krypton) is provided through openings (for example, gas feedthroughs) in wall **582**. The inert gas may be provided so that the interior of shield **574** is substantially or completely flushed with the inert gas and any oxidizing fluid (for example, oxygen) is removed from inside the shield. A gas exit (for example, a gas outlet or gas exit feedthrough) may allow gas to be flushed through shield **574**. Having the inert gas inside shield **574** during the welding process and removing oxidizing fluids (such as oxygen) from inside the shield, inhibits oxidization from occurring during the welding process. Inhibiting oxidation during the welding process inhibits the formation of oxide layers on the metals being welded and provides a more reliable welding process, a faster welding process, and a more reliable weld junction.

In certain embodiments, a positive pressure of inert gas is maintained inside shield **574** during the welding process. The positive pressure of inert gas inhibits outside gases (for example, oxygen or other oxidizing gases) from entering the shield, even if the shield has one or more leaks. In some embodiments, a vacuum may be pulled on shield **574** before providing the inert gas into the shield and/or before welding the portions together. Pulling a vacuum on the shield may remove contaminants such as particulates from inside the shield.

Progress of the welding operation may be monitored through viewing windows **590**. When the weld is complete, shield **574** may be supported and first clamp member **586** may be unfastened from second clamp member **588**. One or both inserts **580** may be removed or partially removed from lower plate **578** and upper plate **576** to facilitate lowering of the conductor. The conductor may be lowered in the wellbore until the end of the conductor is located at a desired position in shield **574**. Shield **574** may be secured to the conductor with first clamp member **586** and second clamp member **588**. Another conductor may be positioned in the shield. Inserts **580** may be positioned in upper and lower plates **576**, **578**; hinged door is closed **584**; and the orbital welder is used to weld the conductors together. The process may be repeated until a desired length of conductor is formed.

The shield may be used to weld joints of pipe over an opening in the hydrocarbon containing formation. Hydrocarbon vapors from the formation may create an explosive atmosphere in the shield even though the inert gas supplied to the shield inhibits the formation of dangerous concentrations of hydrocarbons in the shield. A control circuit may be coupled to a power supply for the orbital welder to stop power to the orbital welder to shut off the arc forming the weld if the hydrocarbon level in the shield rises above a selected concentration. FIG. **60** depicts a schematic representation of an embodiment of a shut off circuit for orbital welding machine **600**. An inert gas, such as argon, may enter shield **574** through inlet **602**. Gas may exit shield **574** through purge **604**. Power supply **606** supplies electricity to orbital welding machine **600** through lines **608**, **610**. Switch **612** may be located in line **608** to orbital welding machine **600**. Switch **612** may be electrically coupled to hydrocarbon monitor **614**. Hydrocarbon monitor **614** may detect the hydrocarbon concentration in shield **574**. If the hydrocarbon concentration in shield becomes too high, for example, over 25% of a lower explosion limit concentration, hydrocarbon monitor **614** may open switch **612**. When switch **612** is open, power to orbital welder **600** is interrupted and the arc formed by the orbital welder ends.

In some embodiments, the temperature limited heater is used to achieve lower temperature heating (for example, for heating fluids in a production well, heating a surface pipeline, or reducing the viscosity of fluids in a wellbore or near wellbore region). Varying the ferromagnetic materials of the temperature limited heater allows for lower temperature heating. In some embodiments, the ferromagnetic conductor is made of material with a lower Curie temperature than that of 446 stainless steel. For example, the ferromagnetic conductor may be an alloy of iron and nickel. The alloy may have between 30% by weight and 42% by weight nickel with the rest being iron. In one embodiment, the alloy is Invar 36. Invar 36 is 36% by weight nickel in iron and has a Curie temperature of 277° C. In some embodiments, an alloy is a three component alloy with, for example, chromium, nickel, and iron. For example, an alloy may have 6% by weight chromium, 42% by weight nickel, and 52% by weight iron. A 2.5 cm diameter rod of Invar 36 has a turndown ratio of approximately 2 to 1 at the Curie temperature. Placing the Invar 36 alloy over a copper core may allow for a smaller rod diameter. A copper core may result in a high turndown ratio. The insulator in lower temperature heater embodiments may be made of a high performance polymer insulator (such as PFA or PEEK™) when used with alloys with a Curie temperature that is below the melting point or softening point of the polymer insulator.

In certain embodiments, a conductor-in-conduit temperature limited heater is used in lower temperature applications by using lower Curie temperature and/or the phase transformation temperature range ferromagnetic materials. For example, a lower Curie temperature and/or the phase transformation temperature range ferromagnetic material may be used for heating inside sucker pump rods. Heating sucker pump rods may be useful to lower the viscosity of fluids in the sucker pump or rod and/or to maintain a lower viscosity of fluids in the sucker pump rod. Lowering the viscosity of the oil may inhibit sticking of a pump used to pump the fluids. Fluids in the sucker pump rod may be heated up to temperatures less than about 250° C. or less than about 300° C. Temperatures need to be maintained below these values to inhibit coking of hydrocarbon fluids in the sucker pump system.

FIG. **61** depicts an embodiment of a temperature limited heater with a low temperature ferromagnetic outer conductor. Outer conductor **502** is glass sealing Alloy 42-6. Alloy 42-6 may be obtained from Carpenter Metals (Reading, Pa., U.S.A.) or Anomet Products, Inc. In some embodiments, outer conductor **502** includes other compositions and/or materials to get various Curie temperatures (for example, Carpenter Temperature Compensator "32" (Curie temperature of 199° C.; available from Carpenter Metals) or Invar 36). In an embodiment, conductive layer **510** is coupled (for example, clad, welded, or brazed) to outer conductor **502**. Conductive layer **510** is a copper layer. Conductive layer **510** improves a turndown ratio of outer conductor **502**. Jacket **506** is a ferromagnetic metal such as carbon steel. Jacket **506** protects outer conductor **502** from a corrosive environment. Inner conductor **490** may have electrical insulator **500**. Electrical insulator **500** may be a mica tape winding with overlaid fiberglass braid. In an embodiment, inner conductor **490** and electrical insulator **500** are a 4/0 MGT-1000 furnace cable or 3/0 MGT-1000 furnace cable. 4/0 MGT-1000 furnace cable or 3/0 MGT-1000 furnace cable is available from Allied Wire and Cable (Phoenixville, Pa., U.S.A.). In some embodiments, a protective braid such as a stainless steel braid may be placed over electrical insulator **500**.

Conductive section **504** electrically couples inner conductor **490** to outer conductor **502** and/or jacket **506**. In some embodiments, jacket **506** touches or electrically contacts conductive layer **510** (for example, if the heater is placed in a horizontal configuration). If jacket **506** is a ferromagnetic metal such as carbon steel (with a Curie temperature above the Curie temperature of outer conductor **502**), current will propagate only on the inside of the jacket. Thus, the outside of the jacket remains electrically uncharged during operation. In some embodiments, jacket **506** is drawn down (for example, swaged down in a die) onto conductive layer **510** so that a tight fit is made between the jacket and the conductive layer. The heater may be spooled as coiled tubing for insertion into a wellbore. In other embodiments, an annular space is present between conductive layer **510** and jacket **506**, as depicted in FIG. **61**.

FIG. **62** depicts an embodiment of a temperature limited conductor-in-conduit heater. Conduit **518** is a hollow sucker rod made of a ferromagnetic metal such as Alloy 42-6, Alloy 32, Alloy 52, Invar 36, iron-nickel-chromium alloys, iron-nickel alloys, nickel alloys, or nickel-chromium alloys. Inner conductor **490** has electrical insulator **500**. Electrical insulator **500** is a mica tape winding with overlaid fiberglass braid. In an embodiment, inner conductor **490** and electrical insulator **500** are a 4/0 MGT-1000 furnace cable or 3/0 MGT-1000 furnace cable. In some embodiments, polymer insulations are used for lower temperature, temperature limited heaters. In certain embodiments, a protective braid is placed over electrical insulator **500**. Conduit **518** has a wall thickness that is greater than the skin depth at the Curie temperature (for example, 2 to 3 times the skin depth at the Curie temperature). In some embodiments, a more conductive conductor is coupled to conduit **518** to increase the turndown ratio of the heater.

FIG. **63** depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater. Conductor **516** is coupled (for example, clad, coextruded, press fit, drawn inside) to ferromagnetic conductor **512**. A metallurgical bond between conductor **516** and ferromagnetic conductor **512** is favorable. Ferromagnetic conductor **512** is coupled to the outside of conductor **516** so that current propagates through the skin depth of the ferromagnetic conductor at room temperature. Conductor **516** provides mechanical support for ferromagnetic conductor **512** at elevated temperatures. Ferromagnetic conductor **512** is iron, an iron alloy (for example, iron with 10% to 27% by weight chromium for corrosion resistance), or any other ferromagnetic material. In one embodiment, conductor **516** is 304 stainless steel and ferromagnetic conductor **512** is 446 stainless steel. Conductor **516** and ferromagnetic conductor **512** are electrically coupled to conduit **518** with sliding connector **528**. Conduit **518** may be a non-ferromagnetic material such as austenitic stainless steel.

FIG. **64** depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater. Conduit **518** is coupled to ferromagnetic conductor **512** (for example, clad, press fit, or drawn inside of the ferromagnetic conductor). Ferromagnetic conductor **512** is coupled to the inside of conduit **518** to allow current to propagate through the skin depth of the ferromagnetic conductor at room temperature. Conduit **518** provides mechanical support for ferromagnetic conductor **512** at elevated temperatures. Conduit **518** and ferromagnetic conductor **512** are electrically coupled to conductor **516** with sliding connector **528**.

FIG. **65** depicts a cross-sectional view of an embodiment of a conductor-in-conduit temperature limited heater. Conductor **516** may surround core **508**. In an embodiment, conductor

516 is 347H stainless steel and core 508 is copper. Conductor 516 and core 508 may be formed together as a composite conductor. Conduit 518 may include ferromagnetic conductor 512. In an embodiment, ferromagnetic conductor 512 is Sumitomo HCM12A or 446 stainless steel. Ferromagnetic conductor 512 may have a Schedule XXH thickness so that the conductor is inhibited from deforming. In certain embodiments, conduit 518 also includes jacket 506. Jacket 506 may include corrosion resistant material that inhibits electrons from flowing away from the heater and into a subsurface formation at higher temperatures (for example, temperatures near the Curie temperature and/or the phase transformation temperature range of ferromagnetic conductor 512). For example, jacket 506 may be about a 0.4 cm thick sheath of 410 stainless steel. Inhibiting electrons from flowing to the formation may increase the safety of using the heater in the subsurface formation.

FIG. 66 depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater with an insulated conductor. Insulated conductor 558 may include core 508, electrical insulator 500, and jacket 506. Jacket 506 may be made of a corrosion resistant material (for example, stainless steel). Endcap 616 may be placed at an end of insulated conductor 558 to couple core 508 to sliding connector 528. Endcap 616 may be made of non-corrosive, electrically conducting materials such as nickel or stainless steel. Endcap 616 may be coupled to the end of insulated conductor 558 by any suitable method (for example, welding, soldering, braising). Sliding connector 528 may electrically couple core 508 and endcap 616 to ferromagnetic conductor 512. Conduit 518 may provide support for ferromagnetic conductor 512 at elevated temperatures.

FIG. 67 depicts a cross-sectional representation of an embodiment of a conductor-in-conduit temperature limited heater with an insulated conductor. Insulated conductor 558 includes core 508, electrical insulator 500, and jacket 506. Jacket 506 is made of a highly electrically conductive material such as copper. Core 508 is made of a lower temperature ferromagnetic material such as such as Alloy 42-6, Alloy 32, Invar 36, iron-nickel-chromium alloys, iron-nickel alloys, nickel alloys, or nickel-chromium alloys. In certain embodiments, the materials of jacket 506 and core 508 are reversed so that the jacket is the ferromagnetic conductor and the core is the highly conductive portion of the heater. Ferromagnetic material used in jacket 506 or core 508 may have a thickness greater than the skin depth at the Curie temperature (for example, 2 to 3 times the skin depth at the Curie temperature). Endcap 616 is placed at an end of insulated conductor 558 to couple core 508 to sliding connector 528. Endcap 616 is made of corrosion resistant, electrically conducting materials such as nickel or stainless steel. In certain embodiments, conduit 518 is a hollow sucker rod made from, for example, carbon steel.

In certain embodiments, a temperature limited heater includes a flexible cable (for example, a furnace cable) as the inner conductor. For example, the inner conductor may be a 27% nickel-clad or stainless steel-clad stranded copper wire with four layers of mica tape surrounded by a layer of ceramic and/or mineral fiber (for example, alumina fiber, aluminosilicate fiber, borosilicate fiber, or aluminoborosilicate fiber). A stainless steel-clad stranded copper wire furnace cable may be available from Anomet Products, Inc. The inner conductor may be rated for applications at temperatures of 1000° C. or higher. The inner conductor may be pulled inside a conduit. The conduit may be a ferromagnetic conduit (for example, a ¾" Schedule 80 446 stainless steel pipe). The conduit may be covered with a layer of copper, or other electrical conductor, with a thickness of about 0.3 cm or any other suitable thickness. The assembly may be placed inside a support conduit (for example, a 1¼" Schedule 80 347H or 347HH stainless steel tubular). The support conduit may provide additional creep-rupture strength and protection for the copper and the inner conductor. For uses at temperatures greater than about 1000° C., the inner copper conductor may be plated with a more corrosion resistant alloy (for example, Incoloy® 825) to inhibit oxidation. In some embodiments, the top of the temperature limited heater is sealed to inhibit air from contacting the inner conductor.

The temperature limited heater may be a single-phase heater or a three-phase heater. In a three-phase heater embodiment, the temperature limited heater has a delta or a wye configuration. Each of the three ferromagnetic conductors in the three-phase heater may be inside a separate sheath. A connection between conductors may be made at the bottom of the heater inside a splice section. The three conductors may remain insulated from the sheath inside the splice section.

FIG. 68 depicts an embodiment of a three-phase temperature limited heater with ferromagnetic inner conductors. Each leg 618 has inner conductor 490, core 508, and jacket 506. Inner conductors 490 are ferritic stainless steel or 1% carbon steel. Inner conductors 490 have core 508. Core 508 may be copper. Each inner conductor 490 is coupled to its own jacket 506. Jacket 506 is a sheath made of a corrosion resistant material (such as 304H stainless steel). Electrical insulator 500 is placed between inner conductor 490 and jacket 506. Inner conductor 490 is ferritic stainless steel or carbon steel with an outside diameter of 1.14 cm and a thickness of 0.445 cm. Core 508 is a copper core with a 0.25 cm diameter. Each leg 618 of the heater is coupled to terminal block 620. Terminal block 620 is filled with insulation material 622 and has an outer surface of stainless steel. Insulation material 622 is, in some embodiments, silicon nitride, boron nitride, magnesium oxide or other suitable electrically insulating material. Inner conductors 490 of legs 618 are coupled (welded) in terminal block 620. Jackets 506 of legs 618 are coupled (welded) to an outer surface of terminal block 620. Terminal block 620 may include two halves coupled around the coupled portions of legs 618.

In some embodiments, the three-phase heater includes three legs that are located in separate wellbores. The legs may be coupled in a common contacting section (for example, a central wellbore, a connecting wellbore, or a solution filled contacting section). FIG. 69 depicts an embodiment of temperature limited heaters coupled in a three-phase configuration. Each leg 624, 626, 628 may be located in separate openings 522 in hydrocarbon layer 460. Each leg 624, 626, 628 may include heating element 630. Each leg 624, 626, 628 may be coupled to single contacting element 632 in one opening 522. Contacting element 632 may electrically couple legs 624, 626, 628 together in a three-phase configuration. Contacting element 632 may be located in, for example, a central opening in the formation. Contacting element 632 may be located in a portion of opening 522 below hydrocarbon layer 460 (for example, in the underburden). In certain embodiments, magnetic tracking of a magnetic element located in a central opening (for example, opening 522 of leg 626) is used to guide the formation of the outer openings (for example, openings 522 of legs 624 and 628) so that the outer openings intersect the central opening. The central opening may be formed first using standard wellbore drilling methods. Contacting element 632 may include funnels, guides, or catchers for allowing each leg to be inserted into the contacting element.

FIG. **70** depicts an embodiment of three heaters coupled in a three-phase configuration. Conductor "legs" **624**, **626**, **628** are coupled to three-phase transformer **634**. Transformer **634** may be an isolated three-phase transformer. In certain embodiments, transformer **634** provides three-phase output in a wye configuration, as shown in FIG. **70**. Input to transformer **634** may be made in any input configuration (such as the delta configuration shown in FIG. **70**). Legs **624**, **626**, **628** each include lead-in conductors **636** in the overburden of the formation coupled to heating elements **630** in hydrocarbon layer **460**. Lead-in conductors **636** include copper with an insulation layer. For example, lead-in conductors **636** may be a 4-0 copper cables with TEFLON® insulation, a copper rod with polyurethane insulation, or other metal conductors such as bare copper or aluminum. In certain embodiments, lead-in conductors **636** are located in an overburden portion of the formation. The overburden portion may include overburden casings **530**. Heating elements **630** may be temperature limited heater heating elements. In an embodiment, heating elements **630** are 410 stainless steel rods (for example, 3.1 cm diameter 410 stainless steel rods). In some embodiments, heating elements **630** are composite temperature limited heater heating elements (for example, 347 stainless steel, 410 stainless steel, copper composite heating elements; 347 stainless steel, iron, copper composite heating elements; or 410 stainless steel and copper composite heating elements). In certain embodiments, heating elements **630** have a length of at least about 10 m to about 2000 m, about 20 m to about 400 m, or about 30 m to about 300 m.

In certain embodiments, heating elements **630** are exposed to hydrocarbon layer **460** and fluids from the hydrocarbon layer. Thus, heating elements **630** are "bare metal" or "exposed metal" heating elements. Heating elements **630** may be made from a material that has an acceptable sulfidation rate at high temperatures used for pyrolyzing hydrocarbons. In certain embodiments, heating elements **630** are made from material that has a sulfidation rate that decreases with increasing temperature over at least a certain temperature range (for example, 500° C. to 650° C., 530° C. to 650° C., or 550° C. to 650° C.). For example, 410 stainless steel may have a sulfidation rate that decreases with increasing temperature between 530° C. and 650° C. Using such materials reduces corrosion problems due to sulfur-containing gases (such as H_2S) from the formation. In certain embodiments, heating elements **630** are made from material that has a sulfidation rate below a selected value in a temperature range. In some embodiments, heating elements **630** are made from material that has a sulfidation rate at most about 25 mils per year at a temperature between about 800° C. and about 880° C. In some embodiments, the sulfidation rate is at most about 35 mils per year at a temperature between about 800° C. and about 880° C., at most about 45 mils per year at a temperature between about 800° C. and about 880° C., or at most about 55 mils per year at a temperature between about 800° C. and about 880° C. Heating elements **630** may also be substantially inert to galvanic corrosion.

In some embodiments, heating elements **630** have a thin electrically insulating layer such as aluminum oxide or thermal spray coated aluminum oxide. In some embodiments, the thin electrically insulating layer is a ceramic composition such as an enamel coating. Enamel coatings include, but are not limited to, high temperature porcelain enamels. High temperature porcelain enamels may include silicon dioxide, boron oxide, alumina, and alkaline earth oxides (CaO or MgO), and minor amounts of alkali oxides (Na_2O, K_2O, LiO). The enamel coating may be applied as a finely ground slurry by dipping the heating element into the slurry or spray coating the heating element with the slurry. The coated heating element is then heated in a furnace until the glass transition temperature is reached so that the slurry spreads over the surface of the heating element and makes the porcelain enamel coating. The porcelain enamel coating contracts when cooled below the glass transition temperature so that the coating is in compression. Thus, when the coating is heated during operation of the heater, the coating is able to expand with the heater without cracking.

The thin electrically insulating layer has low thermal impedance allowing heat transfer from the heating element to the formation while inhibiting current leakage between heating elements in adjacent openings and/or current leakage into the formation. In certain embodiments, the thin electrically insulating layer is stable at temperatures above at least 350° C., above 500° C., or above 800° C. In certain embodiments, the thin electrically insulating layer has an emissivity of at least 0.7, at least 0.8, or at least 0.9. Using the thin electrically insulating layer may allow for long heater lengths in the formation with low current leakage.

Heating elements **630** may be coupled to contacting elements **632** at or near the underburden of the formation. Contacting elements **632** are copper or aluminum rods or other highly conductive materials. In certain embodiments, transition sections **638** are located between lead-in conductors **636** and heating elements **630**, and/or between heating elements **630** and contacting elements **632**. Transition sections **638** may be made of a conductive material that is corrosion resistant such as 347 stainless steel over a copper core. In certain embodiments, transition sections **638** are made of materials that electrically couple lead-in conductors **636** and heating elements **630** while providing little or no heat output. Thus, transition sections **638** help to inhibit overheating of conductors and insulation used in lead-in conductors **636** by spacing the lead-in conductors from heating elements **630**. Transition section **638** may have a length of between about 3 m and about 9 m (for example, about 6 m).

Contacting elements **632** are coupled to contactor **640** in contacting section **642** to electrically couple legs **624**, **626**, **628** to each other. In some embodiments, contact solution **644** (for example, conductive cement) is placed in contacting section **642** to electrically couple contacting elements **632** in the contacting section. In certain embodiments, legs **624**, **626**, **628** are substantially parallel in hydrocarbon layer **460** and leg **624** continues substantially vertically into contacting section **642**. The other two legs **626**, **628** are directed (for example, by directionally drilling the wellbores for the legs) to intercept leg **624** in contacting section **642**.

Each leg **624**, **626**, **628** may be one leg of a three-phase heater embodiment so that the legs are substantially electrically isolated from other heaters in the formation and are substantially electrically isolated from the formation. Legs **624**, **626**, **628** may be arranged in a triangular pattern so that the three legs form a triangular shaped three-phase heater. In an embodiment, legs **624**, **626**, **628** are arranged in a triangular pattern with 12 m spacing between the legs (each side of the triangle has a length of 12 m).

In certain embodiments, the thin electrically insulating layer allows for relatively long, substantially horizontal heater leg lengths in the hydrocarbon layer with a substantially u-shaped heater. FIG. **71** depicts a side-view representation of an embodiment of a substantially u-shaped three-phase heater. First ends of legs **624**, **626**, **628** are coupled to transformer **634** at first location **646**. In an embodiment, transformer **634** is a three-phase AC transformer. Ends of legs **624**, **626**, **628** are electrically coupled together with connector **648** at second location **650**. Connector **648** electrically

couples the ends of legs **624**, **626**, **628** so that the legs can be operated in a three-phase configuration. In certain embodiments, legs **624**, **626**, **628** are coupled to operate in a three-phase wye configuration. In certain embodiments, legs **624**, **626**, **628** are substantially parallel in hydrocarbon layer **460**. In certain embodiments, legs **624**, **626**, **628** are arranged in a triangular pattern in hydrocarbon layer **460**. In certain embodiments, heating elements **630** include a thin electrically insulating material (such as a porcelain enamel coating) to inhibit current leakage from the heating elements. In certain embodiments, legs **624**, **626**, **628** are electrically coupled so that the legs are substantially electrically isolated from other heaters in the formation and are substantially electrically isolated from the formation.

In certain embodiments, overburden casings (for example, overburden casings **530**, depicted in FIGS. **70** and **71**) in overburden **458** include materials that inhibit ferromagnetic effects in the casings. Inhibiting ferromagnetic effects in casings **530** reduces heat losses to the overburden. In some embodiments, casings **530** may include non-metallic materials such as fiberglass, polyvinylchloride (PVC), chlorinated polyvinylchloride (CPVC), or high-density polyethylene (HDPE). HDPEs with working temperatures in a range for use in overburden **458** include HDPEs available from Dow Chemical Co., Inc. (Midland, Mich., U.S.A.). A non-metallic casing may also eliminate the need for an insulated overburden conductor. In some embodiments, casings **530** include carbon steel coupled on the inside diameter of a non-ferromagnetic metal (for example, carbon steel clad with copper or aluminum) to inhibit ferromagnetic effects or inductive effects in the carbon steel. Other non-ferromagnetic metals include, but are not limited to, manganese steels with at least 10% by weight manganese, iron aluminum alloys with at least 18% by weight aluminum, and austentitic stainless steels such as 304 stainless steel or 316 stainless steel.

In certain embodiments, one or more non-ferromagnetic materials used in casings **530** are used in a wellhead coupled to the casings and legs **624**, **626**, **628**. Using non-ferromagnetic materials in the wellhead inhibits undesirable heating of components in the wellhead. In some embodiments, a purge gas (for example, carbon dioxide, nitrogen or argon) is introduced into the wellhead and/or inside of casings **530** to inhibit reflux of heated gases into the wellhead and/or the casings.

In certain embodiments, one or more of legs **624**, **626**, **628** are installed in the formation using coiled tubing. In certain embodiments, coiled tubing is installed in the formation, the leg is installed inside the coiled tubing, and the coiled tubing is pulled out of the formation to leave the leg installed in the formation. The leg may be placed concentrically inside the coiled tubing. In some embodiments, coiled tubing with the leg inside the coiled tubing is installed in the formation and the coiled tubing is removed from the formation to leave the leg installed in the formation. The coiled tubing may extend only to a junction of hydrocarbon layer **460** and contacting section **642** or to a point at which the leg begins to bend in the contacting section.

FIG. **72** depicts a top view representation of an embodiment of a plurality of triads of three-phase heaters in the formation. Each triad **652** includes legs A, B, C (which may correspond to legs **624**, **626**, **628** depicted in FIGS. **70** and **71**) that are electrically coupled by linkage **654**. Each triad **652** is coupled to its own electrically isolated three-phase transformer so that the triads are substantially electrically isolated from each other. Electrically isolating the triads inhibits net current flow between triads.

The phases of each triad **652** may be arranged so that legs A, B, C correspond between triads as shown in FIG. **72**. In FIG. **72**, legs A, B, C are arranged such that a phase leg (for example, leg A) in a given triad is about two triad heights from a same phase leg (leg A) in an adjacent triad. The triad height is the distance from a vertex of the triad to a midpoint of the line intersecting the other two vertices of the triad. In certain embodiments, the phases of triads **652** are arranged to inhibit net current flow between individual triads. There may be some leakage of current within an individual triad but little net current flows between two triads due to the substantial electrical isolation of the triads and, in certain embodiments, the arrangement of the triad phases.

In the early stages of heating, an exposed heating element (for example, heating element **630** depicted in FIGS. **70** and **71**) may leak some current to water or other fluids that are electrically conductive in the formation so that the formation itself is heated. After water or other electrically conductive fluids are removed from the wellbore (for example, vaporized or produced), the heating elements become electrically isolated from the formation. Later, when water is removed from the formation, the formation becomes even more electrically resistant and heating of the formation occurs even more predominantly via thermally conductive and/or radiative heating. Typically, the formation (the hydrocarbon layer) has an initial electrical resistance that averages at least 10 ohm·m. In some embodiments, the formation has an initial electrical resistance of at least 100 ohm·m or of at least 300 ohm·m.

Using the temperature limited heaters as the heating elements limits the effect of water saturation on heater efficiency. With water in the formation and in heater wellbores, there is a tendency for electrical current to flow between heater elements at the top of the hydrocarbon layer where the voltage is highest and cause uneven heating in the hydrocarbon layer. This effect is inhibited with temperature limited heaters because the temperature limited heaters reduce localized overheating in the heating elements and in the hydrocarbon layer.

In certain embodiments, production wells are placed at a location at which there is relatively little or zero voltage potential. This location minimizes stray potentials at the production well. Placing production wells at such locations improves the safety of the system and reduces or inhibits undesired heating of the production wells caused by electrical current flow in the production wells. FIG. **73** depicts a top view representation of the embodiment depicted in FIG. **72** with production wells **206**. In certain embodiments, production wells **206** are located at or near center of triad **652**. In certain embodiments, production wells **206** are placed at a location between triads at which there is relatively little or zero voltage potential (at a location at which voltage potentials from vertices of three triads average out to relatively little or zero voltage potential). For example, production well **206** may be at a location equidistant from legs A of one triad, leg B of a second triad, and leg C of a third triad, as shown in FIG. **73**.

FIG. **74** depicts a top view representation of an embodiment of a plurality of triads of three-phase heaters in a hexagonal pattern in the formation. FIG. **75** depicts a top view representation of an embodiment of a hexagon from FIG. **74**. Hexagon **656** includes two triads of heaters. The first triad includes legs A**1**, B**1**, C**1** electrically coupled together by linkages **654** in a three-phase configuration. The second triad includes legs A**2**, B**2**, C**2** electrically coupled together by linkages **654** in a three-phase configuration. The triads are arranged so that corresponding legs of the triads (for example, A**1** and A**2**, B**1** and B**2**, C**1** and C**2**) are at opposite vertices of hexagon **656**. The triads are electrically coupled and arranged

so that there is relatively little or zero voltage potential at or near the center of hexagon **656**.

Production well **206** may be placed at or near the center of hexagon **656**. Placing production well **206** at or near the center of hexagon **656** places the production well at a location that reduces or inhibits undesired heating due to electromagnetic effects caused by electrical current flow in the legs of the triads and increases the safety of the system. Having two triads in hexagon **656** provides for redundant heating around production well **206**. Thus, if one triad fails or has to be turned off, production well **206** still remains at a center of one triad.

As shown in FIG. **74**, hexagons **656** may be arranged in a pattern in the formation such that adjacent hexagons are offset. Using electrically isolated transformers on adjacent hexagons may inhibit electrical potentials in the formation so that little or no net current leaks between hexagons.

Triads of heaters and/or heater legs may be arranged in any shape or desired pattern. For example, as described above, triads may include three heaters and/or heater legs arranged in an equilateral triangular pattern. In some embodiments, triads include three heaters and/or heater legs arranged in other triangular shapes (for example, an isosceles triangle or a right angle triangle). In some embodiments, heater legs in the triad cross each other (for example, criss-cross) in the formation. In certain embodiments, triads includes three heaters and/or heater legs arranged sequentially along a straight line.

FIG. **76** depicts an embodiment with triads coupled to a horizontal connector well. Triad **652**A includes legs **624**A, **626**A, **628**A. Triad **652**B includes legs **624**B, **626**B, **628**B. Legs **624**A, **626**A, **628**A and legs **624**B, **626**B, **628**B may be arranged along a straight line on the surface of the formation. In some embodiments, legs **624**A, **626**A, **628**A are arranged along a straight line and offset from legs **624**B, **626**B, **628**B, which may be arranged along a straight line. Legs **624**A, **626**A, **628**A and legs **624**B, **626**B, **628**B include heating elements **630** located in hydrocarbon layer **460**. Lead-in conductors **636** couple heating elements **630** to the surface of the formation. Heating elements **630** are coupled to contacting elements **632** at or near the underburden of the formation. In certain embodiments, transition sections (for example, transition sections **638** depicted in FIG. **70**) are located between lead-in conductors **636** and heating elements **630**, and/or between heating elements **630** and contacting elements **632**.

Contacting elements **632** are coupled to contactor **640** in contacting section **642** to electrically couple legs **624**A, **626**A, **628**A to each other to form triad **652**A and electrically couple legs **624**B, **626**B, **628**B to each other to form triad **652**B. In certain embodiments, contactor **640** is a ground conductor so that triad **652**A and/or triad **652**B may be coupled in three-phase wye configurations. In certain embodiments, triad **652**A and triad **652**B are electrically isolated from each other. In some embodiments, triad **652**A and triad **652**B are electrically coupled to each other (for example, electrically coupled in series or parallel).

In certain embodiments, contactor **640** is a substantially horizontal contactor located in contacting section **642**. Contactor **640** may be a casing or a solid rod placed in a wellbore drilled substantially horizontally in contacting section **642**. Legs **624**A, **626**A, **628**A and legs **624**B, **626**B, **628**B may be electrically coupled to contactor **640** by any method described herein or any method known in the art. For example, containers with thermite powder are coupled to contactor **640** (for example, by welding or brazing the containers to the contactor); legs **624**A, **626**A, **628**A and legs **624**B, **626**B, **628**B are placed inside the containers; and the thermite powder is activated to electrically couple the legs to the contactor. The containers may be coupled to contactor **640** by, for example, placing the containers in holes or recesses in contactor **640** or coupled to the outside of the contactor and then brazing or welding the containers to the contactor.

As shown in FIG. **70**, contacting elements **632** of legs **624**, **626**, **628** may be coupled using contactor **640** and/or contact solution **644**. In certain embodiments, contacting elements **632** of legs **624**, **626**, **628** are physically coupled, for example, through soldering, welding, or other techniques. FIGS. **77** and **78** depict embodiments for coupling contacting elements **632** of legs **624**, **626**, **628**. Legs **626**, **628** may enter the wellbore of leg **624** from any direction desired. In one embodiment, legs **626**, **628** enter the wellbore of leg **624** from approximately the same side of the wellbore, as shown in FIG. **77**. In an alternative embodiment, legs **626**, **628** enter the wellbore of leg **624** from approximately opposite sides of the wellbore, as shown in FIG. **78**.

Container **658** is coupled to contacting element **632** of leg **624**. Container **658** may be soldered, welded, or otherwise electrically coupled to contacting element **632**. Container **658** is a metal can or other container with at least one opening for receiving one or more contacting elements **632**. In an embodiment, container **658** is a can that has an opening for receiving contacting elements **632** from legs **626**, **628**, as shown in FIG. **77**. In certain embodiments, wellbores for legs **626**, **628** are drilled parallel to the wellbore for leg **624** through the hydrocarbon layer that is to be heated and directionally drilled below the hydrocarbon layer to intercept wellbore for leg **624** at an angle between about 100 and about 200 from vertical. Wellbores may be directionally drilled using known techniques such as techniques used by Vector Magnetics, Inc.

In some embodiments, contacting elements **632** contact the bottom of container **658**. Contacting elements **632** may contact the bottom of container **658** and/or each other to promote electrical connection between the contacting elements and/or the container. In certain embodiments, end portions of contacting elements **632** are annealed to a "dead soft" condition to facilitate entry into container **658**. In some embodiments, rubber or other softening material is attached to end portions of contacting elements **632** to facilitate entry into container **658**. In some embodiments, contacting elements **632** include reticulated sections, such as knuckle-joints or limited rotation knuckle-joints, to facilitate entry into container **658**.

In certain embodiments, an electrical coupling material is placed in container **658**. The electrical coupling material may line the walls of container **658** or fill up a portion of the container. In certain embodiments, the electrical coupling material lines an upper portion, such as the funnel-shaped portion shown in FIG. **79**, of container **658**. The electrical coupling material includes one or more materials that when activated (for example, heated, ignited, exploded, combined, mixed, and/or reacted) form a material that electrically couples one or more elements to each other. In an embodiment, the coupling material electrically couples contacting elements **632** in container **658**. In some embodiments, the coupling material metallically bonds to contacting elements **632** so that the contacting elements are metallically bonded to each other. In some embodiments, container **658** is initially filled with a high viscosity water-based polymer fluid to inhibit drill cuttings or other materials from entering the container prior to using the coupling material to couple the contacting elements. The polymer fluid may be, but is not limited to, a cross-linked XC polymer (available from Baroid Industrial Drilling Products (Houston, Tex., U.S.A.), a frac gel, or a cross-linked polyacrylamide gel.

In certain embodiments, the electrical coupling material is a low-temperature solder that melts at relatively low temperature and when cooled forms an electrical connection to

exposed metal surfaces. In certain embodiments, the electrical coupling material is a solder that melts at a temperature below the boiling point of water at the depth of container **658**. In one embodiment, the electrical coupling material is a 58% by weight bismuth and 42% by weight tin eutectic alloy. Other examples of such solders include, but are not limited to, a 54% by weight bismuth, 16% by weight tin, 30% by weight indium alloy, and a 48% by weight tin, 52% by weight indium alloy. Such low-temperature solders will displace water upon melting so that the water moves to the top of container **658**. Water at the top of container **658** may inhibit heat transfer into the container and thermally insulate the low-temperature solder so that the solder remains at cooler temperatures and does not melt during heating of the formation using the heating elements.

Container **658** may be heated to activate the electrical coupling material to facilitate the connection of contacting elements **632**. In certain embodiments, container **658** is heated to melt the electrical coupling material in the container. The electrical coupling material flows when melted and surrounds contacting elements **632** in container **658**. Any water within container **658** will float to the surface of the metal when the metal is melted. The electrical coupling material is allowed to cool and electrically connects contacting elements **632** to each other. In certain embodiments, contacting elements **632** of legs **626**, **628**, the inside walls of container **658**, and/or the bottom of the container are initially pre-tinned with electrical coupling material.

End portions of contacting elements **632** of legs **624**, **626**, **628** may have shapes and/or features that enhance the electrical connection between the contacting elements and the coupling material. The shapes and/or features of contacting elements **632** may also enhance the physical strength of the connection between the contacting elements and the coupling material (for example, the shape and/or features of the contacting element may anchor the contacting element in the coupling material). Shapes and/or features for end portions of contacting elements **632** include, but are not limited to, grooves, notches, holes, threads, serrated edges, openings, and hollow end portions. In certain embodiments, the shapes and/or features of the end portions of contacting elements **632** are initially pre-tinned with electrical coupling material.

FIG. **79** depicts an embodiment of container **658** with an initiator for melting the coupling material. The initiator is an electrical resistance heating element or any other element for providing heat that activates or melts the coupling material in container **658**. In certain embodiments, heating element **660** is a heating element located in the walls of container **658**. In some embodiments, heating element **660** is located on the outside of container **658**. Heating element **660** may be, for example, a nichrome wire, a mineral-insulated conductor, a polymer-insulated conductor, a cable, or a tape that is inside the walls of container **658** or on the outside of the container. In some embodiments, heating element **660** wraps around the inside walls of the container or around the outside of the container. Lead-in wire **662** may be coupled to a power source at the surface of the formation: Lead-out wire **664** may be coupled to the power source at the surface of the formation. Lead-in wire **662** and/or lead-out wire **664** may be coupled along the length of leg **624** for mechanical support. Lead-in wire **662** and/or lead-out wire **664** may be removed from the wellbore after melting the coupling material. Lead-in wire **662** and/or lead-out wire **664** may be reused in other wellbores.

In some embodiments, container **658** has a funnel-shape, as shown in FIG. **79**, that facilitates the entry of contacting elements **632** into the container. In certain embodiments, container **658** is made of or includes copper for good electrical and thermal conductivity. A copper container **658** makes good electrical contact with contacting elements (such as contacting elements **632** shown in FIGS. **77** and **78**) if the contacting elements touch the walls and/or bottom of the container.

FIG. **80** depicts an embodiment of container **658** with bulbs on contacting elements **632**. Protrusions **666** may be coupled to a lower portion of contacting elements **632**. Protrusions **668** may be coupled to the inner wall of container **658**. Protrusions **666**, **668** may be made of copper or another suitable electrically conductive material. Lower portion of contacting element **632** of leg **628** may have a bulbous shape, as shown in FIG. **80**. In certain embodiments, contacting element **632** of leg **628** is inserted into container **658**. Contacting element **632** of leg **626** is inserted after insertion of contacting element **632** of leg **628**. Both legs may then be pulled upwards simultaneously. Protrusions **666** may lock contacting elements **632** into place against protrusions **668** in container **658**. A friction fit is created between contacting elements **632** and protrusions **666**, **668**.

Lower portions of contacting elements **632** inside container **658** may include 410 stainless steel or any other heat generating electrical conductor. Portions of contacting elements **632** above the heat generating portions of the contacting elements include copper or another highly electrically conductive material. Centralizers **524** may be located on the portions of contacting elements **632** above the heat generating portions of the contacting elements. Centralizers **524** inhibit physical and electrical contact of portions of contacting elements **632** above the heat generating portions of the contacting elements against walls of container **658**.

When contacting elements **632** are locked into place inside container **658** by protrusions **666**, **668**, at least some electrical current may be pass between the contacting elements through the protrusions. As electrical current is passed through the heat generating portions of contacting elements **632**, heat is generated in container **658**. The generated heat may melt coupling material **670** located inside container **658**. Water in container **658** may boil. The boiling water may convect heat to upper portions of container **658** and aid in melting of coupling material **670**. Walls of container **658** may be thermally insulated to reduce heat losses out of the container and allow the inside of the container to heat up faster. Coupling material **670** flows down into the lower portion of container **658** as the coupling material melts. Coupling material **670** fills the lower portion of container **658** until the heat generating portions of contacting elements **632** are below the fill line of the coupling material. Coupling material **670** then electrically couples the portions of contacting elements **632** above the heat generating portions of the contacting elements. The resistance of contacting elements **632** decreases at this point and heat is no longer generated in the contacting elements and the coupling materials is allowed to cool.

In certain embodiments, container **658** includes insulation layer **672** inside the housing of the container. Insulation layer **672** may include thermally insulating materials to inhibit heat losses from the canister. For example, insulation layer **672** may include magnesium oxide, silicon nitride, or other thermally insulating materials that withstand operating temperatures in container **658**. In certain embodiments, container **658** includes liner **674** on an inside surface of the container. Liner **674** may increase electrical conductivity inside container **658**. Liner **674** may include electrically conductive materials such as copper or aluminum.

FIG. **81** depicts an alternative embodiment for container **658**. Coupling material in container **658** includes powder

676. Powder 676 is a chemical mixture that produces a molten metal product from a reaction of the chemical mixture. In an embodiment, powder 676 is thermite powder. Powder 676 lines the walls of container 658 and/or is placed in the container. Igniter 678 is placed in powder 676. Igniter 678 may be, for example, a magnesium ribbon that when activated ignites the reaction of powder 676. When powder 676 reacts, a molten metal produced by the reaction flows and surrounds contacting elements 632 placed in container 658. When the molten metal cools, the cooled metal electrically connects contacting elements 632. In some embodiments, powder 676 is used in combination with another coupling material, such as a low-temperature solder, to couple contacting elements 632. The heat of reaction of powder 676 may be used to melt the low temperature-solder.

In certain embodiments, an explosive element is placed in container 658, depicted in FIG. 77 or FIG. 81. The explosive element may be, for example, a shaped charge explosive or other controlled explosive element. The explosive element may be exploded to crimp contacting elements 632 and/or container 658 together so that the contacting elements and the container are electrically connected. In some embodiments, an explosive element is used in combination with an electrical coupling material such as low-temperature solder or thermite powder to electrically connect contacting elements 632.

FIG. 82 depicts an alternative embodiment for coupling contacting elements 632 of legs 624, 626, 628. Container 658A is coupled to contacting element 632 of leg 626. Container 658B is coupled to contacting element 632 of leg 628. Container 658B is sized and shaped to be placed inside container 658A. Container 658C is coupled to contacting element 632 of leg 624. Container 658C is sized and shaped to be placed inside container 658B. In some embodiments, contacting element 632 of leg 624 is placed in container 658B without a container attached to the contacting element. One or more of containers 658A, 658B, 658C may be filled with a coupling material that is activated to facilitate an electrical connection between contacting elements 632 as described above.

FIG. 83 depicts a side view representation of an embodiment for coupling contacting elements using temperature limited heating elements. Contacting elements 632 of legs 624, 626, 628 may have insulation 680 on portions of the contacting elements above container 658. Container 658 may be shaped and/or have guides at the top to guide the insertion of contacting elements 632 into the container. Coupling material 670 may be located inside container 658 at or near a top of the container. Coupling material 670 may be, for example, a solder material. In some embodiments, inside walls of container 658 are pre-coated with coupling material or another electrically conductive material such as copper or aluminum. Centralizers 524 may be coupled to contacting elements 632 to maintain a spacing of the contacting elements in container 658. Container 658 may be tapered at the bottom to push lower portions of contacting elements 632 together for at least some electrical contact between the lower portions of the contacting elements.

Heating elements 682 may be coupled to portions of contacting elements 632 inside container 658. Heating elements 682 may include ferromagnetic materials such as iron or stainless steel. In an embodiment, heating elements 682 are iron cylinders clad onto contacting elements 632. Heating elements 682 may be designed with dimensions and materials that will produce a desired amount of heat in container 658. In certain embodiments, walls of container 658 are thermally insulated with insulation layer 672, as shown in FIG. 83 to inhibit heat loss from the container. Heating elements 682 may be spaced so that contacting elements 632 have one or more portions of exposed material inside container 658. The exposed portions include exposed copper or another suitable highly electrically conductive material. The exposed portions allow for better electrical contact between contacting elements 632 and coupling material 670 after the coupling material has been melted, fills container 658, and is allowed to cool.

In certain embodiments, heating elements 682 operate as temperature limited heaters when a time-varying current is applied to the heating elements. For example, a 400 Hz, AC current may be applied to heating elements 682. Application of the time-varying current to contacting elements 632 causes heating elements 682 to generate heat and melt coupling material 670. Heating elements 682 may operate as temperature limited heating elements with a self-limiting temperature selected so that coupling material 670 is not overheated. As coupling material 670 fills container 658, the coupling material makes electrical contact between portions of exposed material on contacting elements 632 and electrical current begins to flow through the exposed material portions rather than heating elements 682. Thus, the electrical resistance between the contacting elements decreases. As this occurs, temperatures inside container 658 begin to decrease and coupling material 670 is allowed to cool to create an electrical contacting section between contacting elements 632. In certain embodiments, electrical power to contacting elements 632 and heating elements 682 is turned off when the electrical resistance in the system falls below a selected resistance. The selected resistance may indicate that the coupling material has sufficiently electrically connected the contacting elements. In some embodiments, electrical power is supplied to contacting elements 632 and heating elements 682 for a selected amount of time that is determined to provide enough heat to melt the mass of coupling material 670 provided in container 658.

FIG. 84 depicts a side view representation of an alternative embodiment for coupling contacting elements using temperature limited heating elements. Contacting element 632 of leg 624 may be coupled to container 658 by welding, brazing, or another suitable method. Lower portion of contacting element 632 of leg 628 may have a bulbous shape. Contacting element 632 of leg 628 is inserted into container 658. Contacting element 632 of leg 626 is inserted after insertion of contacting element 632 of leg 628. Both legs may then be pulled upwards simultaneously. Protrusions 668 may lock contacting elements 632 into place and a friction fit may be created between the contacting elements 632. Centralizers 524 may inhibit electrical contact between upper portions of contacting elements 632.

Time-varying electrical current may be applied to contacting elements 632 so that heating elements 682 generate heat. The generated heat may melt coupling material 670 located in container 658 and be allowed to cool, as described for the embodiment depicted in FIG. 83. After cooling of coupling material 670, contacting elements 632 of legs 626, 628, shown in FIG. 84, are electrically coupled in container 658 with the coupling material. In some embodiments, lower portions of contacting elements 632 have protrusions or openings that anchor the contacting elements in cooled coupling material. Exposed portions of the contacting elements provide a low electrical resistance path between the contacting elements and the coupling material.

FIG. 85 depicts a side view representation of another embodiment for coupling contacting elements using temperature limited heating elements. Contacting element 632 of leg 624 may be coupled to container 658 by welding, brazing,

or another suitable method. Lower portion of contacting element **632** of leg **628** may have a bulbous shape. Contacting element **632** of leg **628** is inserted into container **658**. Contacting element **632** of leg **626** is inserted after insertion of contacting element **632** of leg **628**. Both legs may then be pulled upwards simultaneously. Protrusions **668** may lock contacting elements **632** into place and a friction fit may be created between the contacting elements **632**. Centralizers **524** may inhibit electrical contact between upper portions of contacting elements **632**.

End portions **632**B of contacting elements **632** may be made of a ferromagnetic material such as 410 stainless steel. Portions **632**A may include non-ferromagnetic electrically conductive material such as copper or aluminum. Time-varying electrical current may be applied to contacting elements **632** so that end portions **632**B generate heat due to the resistance of the end portions. The generated heat may melt coupling material **670** located in container **658** and be allowed to cool, as described for the embodiment depicted in FIG. **83**. After cooling of coupling material **670**, contacting elements **632** of legs **626**, **628**, shown in FIG. **84**, are electrically coupled in container **658** with the coupling material. Portions **632**A may be below the fill line of coupling material **670** so that these portions of the contacting elements provide a low electrical resistance path between the contacting elements and the coupling material.

FIG. **86** depicts a side view representation of an alternative embodiment for coupling contacting elements of three legs of a heater. FIG. **87** depicts a top view representation of the alternative embodiment for coupling contacting elements of three legs of a heater depicted in FIG. **86**. Container **658** may include inner container **684** and outer container **686**. Inner container **684** may be made of copper or another malleable, electrically conductive metal such as aluminum. Outer container **686** may be made of a rigid material such as stainless steel. Outer container **686** protects inner container **684** and its contents from environmental conditions outside of container **658**.

Inner container **684** may be substantially solid with two openings **688** and **690**. Inner container **684** is coupled to contacting element **632** of leg **624**. For example, inner container **684** may be welded or brazed to contacting element **632** of leg **624**. Openings **688**, **690** are shaped to allow contacting elements **632** of legs **626**, **628** to enter the openings as shown in FIG. **86**. Funnels or other guiding mechanisms may be coupled to the entrances to openings **688**, **690** to guide contacting elements **632** of legs **626**, **628** into the openings. Contacting elements **632** of legs **624**, **626**, **628** may be made of the same material as inner container **684**.

Explosive elements **700** may be coupled to the outer wall of inner container **684**. In certain embodiments, explosive elements **700** are elongated explosive strips that extend along the outer wall of inner container **684**. Explosive elements **700** may be arranged along the outer wall of inner container **684** so that the explosive elements are aligned at or near the centers of contacting elements **632**, as shown in FIG. **87**. Explosive elements **700** are arranged in this configuration so that energy from the explosion of the explosive elements causes contacting elements **632** to be pushed towards the center of inner container **684**.

Explosive elements **700** may be coupled to battery **702** and timer **704**. Battery **702** may provide power to explosive elements **700** to initiate the explosion. Timer **704** may be used to control the time for igniting explosive elements **700**. Battery **702** and timer **704** may be coupled to triggers **706**. Triggers **706** may be located in openings **688**, **690**. Contacting elements **632** may set off triggers **706** as the contacting elements are placed into openings **688**, **690**. When both triggers **706** in openings **688**, **690** are triggered, timer **704** may initiate a countdown before igniting explosive elements **700**. Thus, explosive elements **700** are controlled to explode only after contacting elements **632** are placed sufficiently into openings **688**, **690** so that electrical contact may be made between the contacting elements and inner container **684** after the explosions. Explosion of explosive elements **700** crimps contacting elements **632** and inner container **684** together to make electrical contact between the contacting elements and the inner container. In certain embodiments, explosive elements **700** fire from the bottom towards the top of inner container **684**. Explosive elements **700** may be designed with a length and explosive power (band width) that gives an optimum electrical contact between contacting elements **632** and inner container **684**:

In some embodiments, triggers **706**, battery **702**, and timer **704** may be used to ignite a powder (for example, copper thermite powder) inside a container (for example, container **658** or inner container **684**). Battery **702** may charge a magnesium ribbon or other ignition device in the powder to initiate reaction of the powder to produce a molten metal product. The molten metal product may flow and then cool to electrically contact the contacting elements.

In certain embodiments, electrical connection is made between contacting elements **632** through mechanical means. FIG. **88** depicts an embodiment of contacting element **632** with a brush contactor. Brush contactor **708** is coupled to a lower portion of contacting element **632**. Brush contactor **708** may be made of a malleable, electrically conductive material such as copper or aluminum. Brush contactor **708** may be a webbing of material that is compressible and/or flexible. Centralizer **524** may be located at or near the bottom of contacting element **632**.

FIG. **89** depicts an embodiment for coupling contacting elements **632** with brush contactors **708**. Brush contactors **708** are coupled to each contacting element **632** of legs **624**, **626**, **628**. Brush contactors **708** compress against each other and interlace to electrically couple contacting elements **632** of legs **624**, **626**, **628**. Centralizers **524** maintain spacing between contacting elements **632** of legs **624**, **626**, **628** so that interference and/or clearance issues between the contacting elements are inhibited.

In certain embodiments, contacting elements **632** (depicted in FIGS. **77-89**) are coupled in a zone of the formation that is cooler than the layer of the formation to be heated (for example, in the underburden of the formation). Contacting elements **632** are coupled in a cooler zone to inhibit melting of the coupling material and/or degradation of the electrical connection between the elements during heating of the hydrocarbon layer above the cooler zone. In certain embodiments, contacting elements **632** are coupled in a zone that is at least about 3 m, at least about 6 m, or at least about 9 m below the layer of the formation to be heated. In some embodiments, the zone has a standing water level that is above a depth of containers **658**.

In certain embodiments, two legs in separate wellbores intercept in a single contacting section. FIG. **90** depicts an embodiment of two temperature limited heaters coupled in a single contacting section. Legs **624** and **626** include one or more heating elements **630**. Heating elements **630** may include one or more electrical conductors. In certain embodiments, legs **624** and **626** are electrically coupled in a single-phase configuration with one leg positively biased versus the other leg so that current flows downhole through one leg and returns through the other leg.

Heating elements **630** in legs **624** and **626** may be temperature limited heaters. In certain embodiments, heating elements **630** are solid rod heaters. For example, heating elements **630** may be rods made of a single ferromagnetic conductor element or composite conductors that include ferromagnetic material. During initial heating when water is present in the formation being heated, heating elements **630** may leak current into hydrocarbon layer **460**. The current leaked into hydrocarbon layer **460** may resistively heat the hydrocarbon layer.

In some embodiments (for example, in oil shale formations), heating elements **630** do not need support members. Heating elements **630** may be partially or slightly bent, curved, made into an S-shape, or made into a helical shape to allow for expansion and/or contraction of the heating elements. In certain embodiments, solid rod heating elements **630** are placed in small diameter wellbores (for example, about 3%" (about 9.5 cm) diameter wellbores). Small diameter wellbores may be less expensive to drill or form than larger diameter wellbores, and there will be less cuttings to dispose of.

In certain embodiments, portions of legs **624** and **626** in overburden **458** have insulation (for example, polymer insulation) to inhibit heating the overburden. Heating elements **630** may be substantially vertical and substantially parallel to each other in hydrocarbon layer **460**. At or near the bottom of hydrocarbon layer **460**, leg **624** may be directionally drilled towards leg **626** to intercept leg **626** in contacting section **642**. Drilling two wellbores to intercept each other may be easier and less expensive than drilling three or more wellbores to intercept each other. The depth of contacting section **642** depends on the length of bend in leg **624** needed to intercept leg **626**. For example, for a 40 ft (about 12 m) spacing between vertical portions of legs **624** and **626**, about 200 ft (about 61 m) is needed to allow the bend of leg **624** to intercept leg **626**. Coupling two legs may require a thinner contacting section **642** than coupling three or more legs in the contacting section.

FIG. **91** depicts an embodiment for coupling legs **624** and **626** in contacting section **642**. Heating elements **630** are coupled to contacting elements **632** at or near junction of contacting section **642** and hydrocarbon layer **460**. Contacting elements **632** may be copper or another suitable electrical conductor. In certain embodiments, contacting element **632** in leg **626** is a liner with opening **710**. Contacting element **632** from leg **624** passes through opening **710**. Contactor **640** is coupled to the end of contacting element **632** from leg **624**. Contactor **640** provides electrical coupling between contacting elements in legs **624** and **626**.

In certain embodiments, contacting elements **632** include one or more fins or projections. The fins or projections may increase an electrical contact area of contacting elements **632**. In some embodiments, contacting element **632** of leg **626** has an opening or other orifice that allows the contacting element of **624** to couple to the contacting element of leg **626**.

In certain embodiments, legs **624** and **626** are coupled together to form a diad. Three diads may be coupled to a three-phase transformer to power the legs of the heaters. FIG. **92** depicts an embodiment of three diads coupled to a three-phase transformer. In certain embodiments, transformer **634** is a delta three-phase transformer. Diad **712**A includes legs **624**A and **626**A. Diad **712**B includes legs **624**B and **626**B. Diad **712**C includes legs **624**C and **626**C. Diads **712**A, **712**B, **712**C are coupled to the secondaries of transformer **634**. Diad **712**A is coupled to the "A" secondary. Diad **712**B is coupled to the "B" secondary. Diad **712**C is coupled to the "C" secondary.

Coupling the diads to the secondaries of the delta three-phase transformer isolates the diads from ground. Isolating the diads from ground inhibits leakage to the formation from the diads. Coupling the diads to different phases of the delta three-phase transformer also inhibits leakage between the heating legs of the diads in the formation.

In some embodiments, diads are used for treating formations using triangular or hexagonal heater patterns. FIG. **93** depicts an embodiment of groups of diads in a hexagonal pattern. Heaters may be placed at the vertices of each of the hexagons in the hexagonal pattern. Each group **714** of diads (enclosed by dashed circles) may be coupled to a separate three-phase transformer. "A", "B", and "C" inside groups **714** represent each diad (for example, diads **712**A, **712**B, **712**C depicted in FIG. **92**) that is coupled to each of the three secondary phases of the transformer with each phase coupled to one diad (with the heaters at the vertices of the hexagon). The numbers "1", "2", and "3" inside the hexagons represent the three repeating types of hexagons in the pattern depicted in FIG. **93**.

FIG. **94** depicts an embodiment of diads in a triangular pattern. Three diads **712**A, **712**B, **712**C may be enclosed in each group **714** of diads (enclosed by dashed rectangles). Each group **714** may be coupled to a separate three-phase transformer.

In certain embodiments, exposed metal heating elements are used in substantially horizontal sections of u-shaped wellbores. Substantially u-shaped wellbores may be used in tar sands formations, oil shale formation, or other formations with relatively thin hydrocarbon layers. Tar sands or thin oil shale formations may have thin shallow layers that are more easily and uniformly heated using heaters placed in substantially u-shaped wellbores. Substantially u-shaped wellbores may also be used to process formations with thick hydrocarbon layers in formations. In some embodiments, substantially u-shaped wellbores are used to access rich layers in a thick hydrocarbon formation.

Heaters in substantially u-shaped wellbores may have long lengths compared to heaters in vertical wellbores because horizontal heating sections do not have problems with creep or hanging stress encountered with vertical heating elements. Substantially u-shaped wellbores may make use of natural seals in the formation and/or the limited thickness of the hydrocarbon layer. For example, the wellbores may be placed above or below natural seals in the formation without punching large numbers of holes in the natural seals, as would be needed with vertically oriented wellbores. Using substantially u-shaped wellbores instead of vertical wellbores may also reduce the number of wells needed to treat a surface footprint of the formation. Using less wells reduces capital costs for equipment and reduces the environmental impact of treating the formation by reducing the amount of wellbores on the surface and the amount of equipment on the surface. Substantially u-shaped wellbores may also utilize a lower ratio of overburden section to heated section than vertical wellbores.

Substantially u-shaped wellbores may allow for flexible placement of opening of the wellbores on the surface. Openings to the wellbores may be placed according to the surface topology of the formation. In certain embodiments, the openings of wellbores are placed at geographically accessible locations such as topological highs (for examples, hills). For example, the wellbore may have a first opening on a first topologic high and a second opening on a second topologic high and the wellbore crosses beneath a topologic low (for example, a valley with alluvial fill) between the first and second topologic highs. This placement of the openings may

avoid placing openings or equipment in topologic lows or other inaccessible locations. In addition, the water level may not be artesian in topologically high areas. Wellbores may be drilled so that the openings are not located near environmentally sensitive areas such as, but not limited to, streams, nesting areas, or animal refuges.

FIG. **95** depicts a side-view representation of an embodiment of a heater with an exposed metal heating element placed in a substantially u-shaped wellbore. Heaters **716**A, **716**B, **716**C have first end portions at first location **646** on surface **534** of the formation and second end portions at second location **650** on the surface. Heaters **716**A, **716**B, **716**C have sections **718** in overburden **458**. Sections **718** are configured to provide little or no heat output. In certain embodiments, sections **718** include an insulated electrical conductor such as insulated copper. Sections **718** are coupled to heating elements **630**.

In certain embodiments, portions of heating elements **630** are substantially parallel in hydrocarbon layer **460**. In certain embodiments, heating elements **630** are exposed metal heating elements. In certain embodiments, heating elements **630** are exposed metal temperature limited heating elements. Heating elements **630** may include ferromagnetic materials such as 9% by weight to 13% by weight chromium stainless steel like 410 stainless steel, chromium stainless steels such as T/P91 or T/P92, 409 stainless steel, VM12 (Vallourec and Mannesmann Tubes, France) or iron-cobalt alloys for use as temperature limited heaters. In some embodiments, heating elements **630** are composite temperature limited heating elements such as 410 stainless steel and copper composite heating elements or 347H, iron, copper composite heating elements. Heating elements **630** may have lengths of at least about 100 m, at least about 500 m, or at least about 1000 m, up to lengths of about 6000 m.

Heating elements **630** may be solid rods or tubulars. In certain embodiments, solid rod heating elements have diameters several times the skin depth at the Curie temperature of the ferromagnetic material. Typically, the solid rod heating elements may have diameters of 1.91 cm or larger (for example, 2.5 cm, 3.2 cm, 3.81 cm, or 5.1 cm). In certain embodiments, tubular heating elements have wall thicknesses of at least twice the skin depth at the Curie temperature of the ferromagnetic material. Typically, the tubular heating elements have outside diameters of between about 2.5 cm and about 15.2 cm and wall thickness in range between about 0.13 cm and about 1.01 cm.

In certain embodiments, tubular heating elements **630** allow fluids to be convected through the tubular heating elements. Fluid flowing through the tubular heating elements may be used to preheat the tubular heating elements, to initially heat the formation, and/or to recover heat from the formation after heating is completed for the in situ heat treatment process. Fluids that may be flow through the tubular heating elements include, but are not limited to, air, water, steam, helium, carbon dioxide or other fluids. In some embodiments, a hot fluid, such as carbon dioxide or helium, flows through the tubular heating elements to provide heat to the formation. The hot fluid may be used to provide heat to the formation before electrical heating is used to provide heat to the formation. In some embodiments, the hot fluid is used to provide heat in addition to electrical heating. Using the hot fluid to provide heat to the formation in addition to providing electrical heating may be less expensive than using electrical heating alone to provide heat to the formation. In some embodiments, water and/or steam flows through the tubular heating element to recover heat from the formation. The heated water and/or steam may be used for solution mining and/or other processes.

Transition sections **720** may couple heating elements **630** to sections **718**. In certain embodiments, transition sections **720** include material that has a high electrical conductivity but is corrosion resistant, such as 347 stainless steel over copper. In an embodiment, transition sections include a composite of stainless steel clad over copper. Transition sections **720** inhibit overheating of copper and/or insulation in sections **718**.

FIG. **96** depicts a representational top view of an embodiment of a surface pattern of heaters depicted in FIG. **95**. Heaters **716**A-L may be arranged in a repeating triangular pattern on the surface of the formation, as shown in FIG. **96**. A triangle may be formed by heaters **716**A, **716**B, and **716**C and a triangle formed by heaters **716**C, **716**D, and **716**E. In some embodiments, heaters **716**A-L are arranged in a straight line on the surface of the formation. Heaters **716**A-L have first end portions at first location **646** on the surface and second end portions at second location **650** on the surface. Heaters **716**A-L are arranged such that (a) the patterns at first location **646** and second location **650** correspond to each other, (b) the spacing between heaters is maintained at the two locations on the surface, and/or (c) the heaters all have substantially the same length (substantially the same horizontal distance between the end portions of the heaters on the surface as shown in the top view of FIG. **96**).

As depicted in FIGS. **95** and **96**, cables **722**, **724** may be coupled to transformer **728** and one or more heater units, such as the heater unit including heaters **716**A, **716**B, **716**C. Cables **722**, **724** may carry a large amount of power. In certain embodiments, cables **722**, **724** are capable of carrying high currents with low losses. For example, cables **722**, **724** may be thick copper or aluminum conductors. The cables may also have thick insulation layers. In some embodiments, cable **722** and/or cable **724** may be superconducting cables. The superconducting cables may be cooled by liquid nitrogen. Superconducting cables are available from Superpower, Inc. (Schenectady, N.Y., U.S.A.). Superconducting cables may minimize power loss and reduce the size of the cables needed to couple transformer **728** to the heaters. In some embodiments, cables **722**, **724** may be made of carbon nanotubes. Carbon nanotubes as conductors may have about 1000 times the conductivity of copper for the same diameter. Also, carbon nanotubes may not require refrigeration during use.

In certain embodiments, bus bar **726**A is coupled to first end portions of heaters **716**A-L and bus bar **726**B is coupled to second end portions of heaters **716**A-L. Bus bars **726**A,B electrically couple heaters **716**A-L to cables **722**, **724** and transformer **728**. Bus bars **726**A,B distribute power to heaters **716**A-L. In certain embodiments, bus bars **726**A,B are capable of carrying high currents with low losses. In some embodiments, bus bars **726**A,B are made of superconducting material such as the superconductor material used in cables **722**, **724**. In some embodiments, bus bars **726**A,B may include carbon nanotube conductors.

As shown in FIGS. **95** and **96**, heaters **716**A-L are coupled to a single transformer **728**. In certain embodiments, transformer **728** is a source of time-varying current. In certain embodiments, transformer **728** is an electrically isolated, single-phase transformer. In certain embodiments, transformer **728** provides power to heaters **716**A-L from an isolated secondary phase of the transformer. First end portions of heaters **716**A-L may be coupled to one side of transformer **728** while second end portions of the heaters are coupled to the opposite side of the transformer. Transformer **728** pro-

vides a substantially common voltage to the first end portions of heaters **716**A-L and a substantially common voltage to the second end portions of heaters **716**A-L. In certain embodiments, transformer **728** applies a voltage potential to the first end portions of heaters **716**A-L that is opposite in polarity and substantially equal in magnitude to a voltage potential applied to the second end portions of the heaters. For example, a +660 V potential may be applied to the first end portions of heaters **716**A-L and a −660 V potential applied to the second end portions of the heaters at a selected point on the wave of time-varying current (such as AC or modulated DC). Thus, the voltages at the two end portion of the heaters may be equal in magnitude and opposite in polarity with an average voltage that is substantially at ground potential.

Applying the same voltage potentials to the end portions of all heaters **716**A-L produces voltage potentials along the lengths of the heaters that are substantially the same along the lengths of the heaters. FIG. **97** depicts a cross-section representation, along a vertical plane, such as the plane A-A shown in FIG. **95**, of substantially u-shaped heaters in a hydrocarbon layer. The voltage potential at the cross-sectional point shown in FIG. **97** along the length of heater **716**A is substantially the same as the voltage potential at the corresponding cross-sectional points on heaters **716**A-L shown in FIG. **97**. At lines equidistant between heater wellheads, the voltage potential is approximately zero. Other wells, such as production wells or monitoring wells, may be located along these zero voltage potential lines, if desired. Production wells **206** located close to the overburden may be used to transport formation fluid that is initially in a vapor phase to the surface. Production wells located close to a bottom of the heated portion of the formation may be used to transport formation fluid that is initially in a liquid phase to the surface.

In certain embodiments, the voltage potential at the midpoint of heaters **716**A-L is about zero. Having similar voltage potentials along the lengths of heaters **716**A-L inhibits current leakage between the heaters. Thus, there is little or no current flow in the formation and the heaters may have long lengths as described above. Having the opposite polarity and substantially equal voltage potentials at the end portions of the heaters also halves the voltage applied at either end portion of the heater versus having one end portion of the heater grounded and one end portion at full potential. Reducing (halving) the voltage potential applied to an end portion of the heater generally reduces current leakage, reduces insulator requirements, and/or reduces arcing distances because of the lower voltage potential to ground applied at the end portions of the heaters.

In certain embodiments, substantially vertical heaters are used to provide heat to the formation. Opposite polarity and substantially equal voltage potentials, as described above, may be applied to the end portions of the substantially vertical heaters. FIG. **98** depicts a side-view representation of substantially vertical heaters coupled to a substantially horizontal wellbore. Heaters **716**A, **716**B, **716**C, **716**D, **716**E, **716**F are located substantially vertical in hydrocarbon layer **460**. First end portions of heaters **716**A, **716**B, **716**C, **716**D, **716**E, **716**F are coupled to bus bar **726**A on a surface of the formation. Second end portions of heaters **716**A, **716**B, **716**C, **716**D, **716**E, **716**F are coupled to bus bar **726**B in contacting section **642**.

Bus bar **726**B may be a bus bar located in a substantially horizontal wellbore in contacting section **642**. Second end portions of heaters **716**A, **716**B, **716**C, **716**D, **716**E, **716**F may be coupled to bus bar **726**B by any method described herein or any method known in the art. For example, containers with thermite powder are coupled to bus bar **726**B (for example, by welding or brazing the containers to the bus bar), end portions of heaters **716**A, **716**B, **716**C, **716**D, **716**E, **716**F are placed inside the containers, and the thermite powder is activated to electrically couple the heaters to the bus bar. The containers may be coupled to bus bar **726**B by, for example, placing the containers in holes or recesses in bus bar **726**B or coupled to the outside of the bus bar and then brazing or welding the containers to the bus bar.

Bus bar **726**A and bus bar **726**B may be coupled to transformer **728** with cables **722**, **724**, as described above. Transformer **728** may provide voltages to bar **726**A and bus bar **726**B as described above for the embodiments depicted in FIGS. **95** and **96**. For example, transformer **728** may apply a voltage potential to the first end portions of heaters **716**A-F that is opposite in polarity and substantially equal in magnitude to a voltage potential applied to the second end portions of the heaters. Applying the same voltage potentials to the end portions of all heaters **716**A-F may produce voltage potentials along the lengths of the heaters that are substantially the same along the lengths of the heaters. Applying the same voltage potentials to the end portions of all heaters **716**A-F may inhibit current leakage between the heaters and/or into the formation. In some embodiments, heaters **716**A-F are electrically coupled in pairs to the isolated delta winding on the secondary of a three-phase transformer.

In certain embodiments, it may be advantageous to allow some current leakage into the formation during early stages of heating to heat the formation at a faster rate. Current leakage from the heaters into the formation electrically heats the formation directly. The formation is heated by direct electrical heating in addition to conductive heat provided by the heaters. The formation (the hydrocarbon layer) may have an initial electrical resistance that averages at least 10 ohm·m. In some embodiments, the formation has an initial electrical resistance of at least 100 ohm·m or of at least 300 ohm·m. Direct electrical heating is achieved by having opposite potentials applied to adjacent heaters in the hydrocarbon layer. Current may be allowed to leak into the formation until a selected temperature is reached in the heaters or in the formation. The selected temperature may be below or near the temperature that water proximate one or more heaters boils off. After water boils off, the hydrocarbon layer is substantially electrically isolated from the heaters and direct heating of the formation is inefficient. After the selected temperature is reached, the voltage potential is applied in the opposite polarity and substantially equal magnitude manner described above for FIGS. **95** and **96** so that adjacent heaters will have the same voltage potential along their lengths.

Current is allowed to leak into the formation by reversing the polarity of one or more heaters shown in FIG. **96** so that a first group of heaters has a positive voltage potential at first location **646** and a second group of heaters has a negative voltage potential at the first location. The first end portions, at first location **646**, of a first group of heaters (for example, heaters **716**A, **716**B, **716**D, **716**E, **716**G, **716**H, **716**J, **716**K, depicted in FIG. **96**) are applied with a positive voltage potential that is substantially equal in magnitude to a negative voltage potential applied to the second end portions, at second location **650**, of the first group of heaters. The first end portions, at first location **646**, of the second group of heaters (for example, heaters **716**C, **716**F, **7161**, **716**L) are applied with a negative voltage potential that is substantially equal in magnitude to the positive voltage potential applied to the first end portions of the first group of heaters. Similarly, the second end portions, at second location **650**, of the second group of heaters are applied with a positive voltage potential substantially equal in magnitude to the negative potential applied to

the second end portions of the first group of heaters. After the selected temperature is reached, the first end portions of both groups of heaters are applied with voltage potential that is opposite in polarity and substantially similar in magnitude to the voltage potential applied to the second end portions of both groups of heaters.

In some embodiments, heating elements **630** have a thin electrically insulating layer, described above, to inhibit current leakage from the heating elements. In some embodiments, the thin electrically insulating layer is aluminum oxide or thermal spray coated aluminum oxide. In some embodiments, the thin electrically insulating layer is an enamel coating of a ceramic composition. The thin electrically insulating layer may inhibit heating elements of a three-phase heater from leaking current between the elements, from leaking current into the formation, and from leaking current to other heaters in the formation. Thus, the three-phase heater may have a longer heater length.

In certain embodiments, a plurality of substantially horizontal (or inclined) heaters are coupled to a single substantially horizontal bus bar in the subsurface formation. Having the plurality of substantially horizontal heaters connected to a single bus bar in the subsurface reduces the overall footprint of heaters on the surface of the formation and the number of wells drilled in the formation. The number and spacing of heaters coupled to the single bus bar may be varied depending on factors such as, but not limited to, size of the treatment area, vertical thickness of the formation, heating requirements for the formation, and number of layers in the formation.

FIG. **99** depicts an embodiment of pluralities of substantially horizontal heaters **716**A,B coupled to bus bars **726**A,B in hydrocarbon layer **460**. Heaters **716**A,B have sections **718** in the overburden of hydrocarbon layer **460**. Sections **718** may include high electrical conductivity, low thermal loss electrical conductors such as copper. Heaters **716**A,B enter hydrocarbon layer **460** with substantially vertical sections and then redirect so that the heaters have substantially horizontal sections in the hydrocarbon layer **460**. The substantially horizontal sections of **716**A,B in hydrocarbon layer **460** may provide the majority of the heat to the hydrocarbon layer. Heaters **716**A,B may be coupled to bus bars **726**A,B, which are located distant from each other in the formation while being substantially parallel to each other.

In certain embodiments, heaters **716**A,B include exposed metal heating elements. In certain embodiments, heaters **716**A,B include exposed metal temperature limited heating elements. The heating elements may include ferromagnetic materials such as 9% by weight to 13% by weight chromium stainless steel like 410 stainless steel, chromium stainless steels such as T/P91 or T/P92, 409 stainless steel, VM12 (Vallourec and Mannesmann Tubes, France) or iron-cobalt alloys for use as temperature limited heaters. In some embodiments, the heating elements are composite temperature limited heating elements such as 410 stainless steel and copper composite heating elements or 347H, iron, copper composite heating elements. The substantially horizontal sections of heaters **716**A,B in hydrocarbon layer **460** may have lengths of at least about 100 m, at least about 500 m, or at least about 1000 m, up to lengths of about 6000 m.

In some embodiments, as shown in FIG. **99**, two groups of heaters **716**A,B enter the subsurface near each other and then branch away from each other in hydrocarbon layer **460**. Having the surface portions of more than one group of heaters located near each other creates less of a surface footprint of the heaters and allows a single group of surface facilities to be used for both groups of heaters.

In certain embodiments, the groups of heaters **716**A or **716**B are each coupled to a single transformer. In some embodiments, three heaters in the groups are coupled in a triad configuration (each heater is coupled to one of the phases (A, B, or C) of a three phase transformer and the bus bar is coupled to the neutral, or center point, of the transformer). Each phase of the three-phase transformer may be coupled to more than one heater in each group of heaters (for example, phase A may be coupled to 5 heaters in the group of heaters **716**A). In some embodiments, the heaters are coupled to a single phase transformer (either in series or in parallel configurations).

FIG. **100** depicts an alternative embodiment of pluralities of substantially horizontal heaters **716**A,B coupled to bus bars **726**A,B in hydrocarbon layer **460**. In such an embodiment, two groups of heaters **716**A,B enter the formation at distal locations on the surface of the formation. Heaters **716**A,B branch towards each other in hydrocarbon layer **460** so that the ends of the heaters are directed towards each other. Heaters **716**A,B may be coupled to bus bars **726**A,B, which are located proximate each other and substantially parallel to each other. Bus bars **726**A,B may enter the subsurface in proximity to each other so that the footprint of the bus bars on the surface is small.

In certain embodiments, heaters **716**A,B, depicted in FIG. **100**, are coupled to a single phase transformer in series or parallel. The heaters may be coupled so that the polarity (direction of current flow) alternates in the row of heaters so that each heater has an polarity opposite the heater adjacent to it. Additionally, heaters **716**A,B and bus bars **726**A,B may be electrically coupled such that the bus bars are opposite in polarity from each other (the current flows in opposite directions at any point in time in each bus bar). Coupling the heaters and the bus bars in such manners inhibits current leakage into and/or through the formation.

As shown in FIGS. **99** and **100**, heaters **716**A may be electrically coupled to bus bar **726**A and heaters **716**B may be electrically coupled to bus bar **726**B. Bus bars **726**A,B may electrically couple to the ends of heaters **716**A,B and be a return or neutral connection for the heaters with bus bar **726**A being the neutral connection for heaters **716**A and bus bar **726**B being the neutral connection for heaters **716**B. Bus bars **726**A,B may be located in wellbores that are formed substantially perpendicular to the path of wellbores with heaters **716**A,B, as shown in FIG. **99**. Directional drilling and/or magnetic steering may be used so that the wells for bus bars **726**A,B and the wellbores for heaters **716**A,B intersect.

In certain embodiments, heaters **716**A,B are coupled to bus bars **726**A,B using "mousetrap" type connectors **2028**. In some embodiments, other couplings, such as those described herein or known in the art, are used to couple heaters **716**A,B to bus bars **726**A,B. For example, a molten metal or a liquid conducting fluid may fill up the connection space (in the wellbores) to electrically couple the heaters and the bus bars.

FIG. **101** depicts an enlarged view of an embodiment of bus bar **726** coupled to heater **716** with connectors **2028**. In certain embodiments, bus bar **726** includes carbon steel or other electrically conducting metals. In some embodiments, a high electrical conductivity conductor or metal is coupled to or included in bus bar **726**. For example, bus bar **726** may include carbon steel with copper cladded to the carbon steel.

In some embodiments, a centralizer or other centralizing device is used to locate or guide heaters **716** and/or bus bars **726** so that the heaters and bus bars can be coupled. FIG. **102** depicts an enlarged view of an embodiment of bus bar **726** coupled to heater **716** with connectors **2028** and centralizers **524**. Centralizers **524** may locate heater **716** and/or bus bar

726 so that connectors 2028 easily couple the heater and the bus bar. Centralizers 524 may ensure proper spacing of heater 716 and/or bus bar 726 so that the heater and the bus bar can be coupled with connectors 2028. Centralizers 524 may inhibit heater 716 and/or bus bar 726 from contacting the sides of the wellbores at or near connectors 2028.

FIGS. 103 and 104 depict an embodiment of connector 2028 coupling to bus bar 726. FIG. 103 depicts a cross-section representation of connector 2028 coupling to bus bar 726. FIG. 104 depicts a three-dimensional representation of connector 2028 coupling to bus bar 726. Connector 2028 is shown in proximity to bus bar 726 (before the connector clamps around the bus bar). Connector 2028 is connected or directly attached to the heater so that the connector is rotatable around the end of the heater while maintaining electrical contact with the heater. Connector 2028 includes collets 2030. Collets 2030 are shaped (for example, diagonally cut or helically profiled) so that as the connector is pushed onto bus bar 726, the shape of the collets rotates the head of the connector as the collets slide over the bus bar. Collets 2030 may be spring loaded so that the collets hold down against bus bar 726 after the collets slide over the bus bar. Thus, connector 2028 clamps to bus bar 726 using collets 2030. Connector 2028, including collets 2030, is made of electrically conductive materials so that the connector electrically couples bus bar 726 to the heater attached to the connector.

In certain embodiments, a heater is electrically isolated from the formation because the heater has little or no voltage potential on the outside of the heater. FIG. 105 depicts an embodiment of a substantially u-shaped heater that electrically isolates itself from the formation. Heater 716 has a first end portion at a first opening on surface 534 and a second end portion at a second opening on the surface. In some embodiments, heater 716 has only the first end portion at the surface with the second end of the heater located in hydrocarbon layer 460 (the heater is a single-ended heater). FIGS. 106 and 107 depict embodiments of single-ended heaters that electrically isolate themselves from the formation. In certain embodiments, single-ended heater 716 has an elongated portion that is substantially horizontal in hydrocarbon layer 460, as shown in FIGS. 106 and 107. In some embodiments, single-ended heater 716 has an elongated portion with an orientation other than substantially horizontal in hydrocarbon layer 460. For example, the single-ended heater may have an elongated portion that is oriented 15° off horizontal in the hydrocarbon layer.

As shown in FIGS. 105-107, heater 716 includes heating element 630 located in hydrocarbon layer 460. Heating element 630 may be a ferromagnetic conduit heating element or ferromagnetic tubular heating element. In certain embodiments, heating element 630 is a temperature limited heater tubular heating element. In certain embodiments, heating element 630 is a 9% by weight to 13% by weight chromium stainless steel tubular such as a 410 stainless steel tubular, a T/P91 stainless steel tubular, or a T/P92 stainless steel tubular. In certain embodiments, heating element 630 includes ferromagnetic material with a wall thickness of at least about one skin depth of the ferromagnetic material at 25° C. In some embodiments, heating element 630 includes ferromagnetic material with a wall thickness of at least about two times the skin depth of the ferromagnetic material at 25° C., at least about three times the skin depth of the ferromagnetic material at 25° C., or at least about four times the skin depth of the ferromagnetic material at 25° C.

Heating element 630 is coupled to one or more sections 718. Sections 718 are located in overburden 458. Sections 718 include higher electrical conductivity materials such as copper or aluminum. In certain embodiments, sections 718 are copper clad inside carbon steel.

Center conductor 730 is positioned inside heating element 630. In some embodiments, heating element 630 and center conductor 730 are placed or installed in the formation by unspooling the heating element and the center conductor from one or more spools while they are placed into the formation. In some embodiments, heating element 630 and center conductor 730 are coupled together on a single spool and unspooled as a single system with the center conductor inside the heating element. In some embodiments, heating element 630 and center conductor 730 are located on separate spools and the center conductor is positioned inside the heating element after the heating element is placed in the formation.

In certain embodiments, center conductor 730 is located at or near a center of heating element 630. Center conductor 730 may be substantially electrically isolated from heating element 630 along a length of the center conductor (for example, the length of the center conductor in hydrocarbon layer 460). In certain embodiments, center conductor 730 is separated from heating element 630 by one or more electrically-insulating centralizers. The centralizers may include silicon nitride or another electrically insulating material. The centralizers may inhibit electrical contact between center conductor 730 and heating element 630 so that, for example, arcing or shorting between the center conductor and the heating element is inhibited. In some embodiments, center conductor 730 is a conductor (for example, a solid conductor or a tubular conductor) so that the heater is in a conductor-in-conduit configuration.

In certain embodiments, center conductor 730 is a copper rod or copper tubular. In some embodiments, center conductor 730 and/or heating element 630 has a thin electrically insulating layer to inhibit current leakage from the heating elements. In some embodiments, the thin electrically insulating layer is aluminum oxide or thermal spray coated aluminum oxide. In some embodiments, the thin electrically insulating layer is an enamel coating of a ceramic composition. The thin electrically insulating layer may inhibit heating elements of a three-phase heater from leaking current between the elements, from leaking current into the formation, and from leaking current to other heaters in the formation. Thus, the three-phase heater may have a longer heater length.

In certain embodiments, center conductor 730 is an insulated conductor. The insulated conductor may include an electrically conductive core inside an electrically conductive sheath with electrical insulation between the core and the sheath. In certain embodiments, the insulated conductor includes a copper core inside a non-ferromagnetic stainless steel (for example, 347 stainless steel) sheath with magnesium oxide insulation between the core and the sheath. The core may be used to conduct electrical current through the insulated conductor. In some embodiments, the insulated conductor is placed inside heating element 630 without centralizers or spacers between the insulated conductor and the heating element. The sheath and the electrical insulation of the insulated conductor may electrically insulate the core from heating element 630 if the center conductor and the heating element touch. Thus, the core and heating element 630 are inhibit from electrically shorting to each other. The insulated conductor or another solid center conductor 730 may be inhibited from being crushed or deformed by heating element 630. In certain embodiments, one end portion of center conductor 730 is electrically coupled to one end portion of heating element 630 at surface 534 using electrical coupling 732, as shown in FIG. 105. In some embodiments, the end of center conductor 730 is electrically coupled to the

end of heating element **630** in hydrocarbon layer **460** using electrical coupling **732**, as shown in FIGS. **106** and **107**. Thus, center conductor **730** is electrically coupled to heating element **630** in a series configuration in the embodiments depicted in FIGS. **105-107**. In certain embodiments, center conductor **730** is the insulated conductor and the core of the insulated conductor is electrically coupled to heating element **630** in the series configuration. Center conductor **730** is a return electrical conductor for heating element **630** so that current in the center conductor flows in an opposite direction from current in the heating element (as represented by arrows **734**). The electromagnetic field generated by current flow in center conductor **730** substantially confines the flow of electrons and heat generation to the inside of heating element **630** (for example, the inside wall of the heating element) below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic material in the heating element. Thus, the outside of heating element **630** is at substantially zero potential and the heating element is electrically isolated from the formation and any adjacent heater or heating element at temperatures below the Curie temperature and/or the phase transformation temperature range of the ferromagnetic material (for example, at 25° C.). Having the outside of heating element **630** at substantially zero potential and the heating element electrically isolated from the formation and any adjacent heater or heating element allows for long length heaters to be used in hydrocarbon layer **460** without significant electrical (current) losses to the hydrocarbon layer. For example, heaters with lengths of at least about 100 m, at least about 500 m, or at least about 1000 m may be used in hydrocarbon layer **460**.

During application of electrical current to heating element **630** and center conductor **730**, heat is generated by the heater. In certain embodiments, heating element **630** generates a majority or all of the heat output of the heater. For example, when electrical current flows through ferromagnetic material in heating element **630** and copper or another low resistivity material in center conductor **730**, the heating element generates a majority or all of the heat output of the heater. Generating a majority of the heat in the outer conductor (heating element **630**) instead of center conductor **730** may increase the efficiency of heat transfer to the formation by allowing direct heat transfer from the heat generating element (heating element **630**) to the formation and may reduce heat losses across heater **716** (for example, heat losses between the center conductor and the outer conductor if the center conductor is the heat generating element). Generating heat in heating element **630** instead of center conductor **730** also increases the heat generating surface area of heater **716**. Thus, for the same operating temperature of heater **716**, more heat can be provided to the formation using the outer conductor (heating element **630**) as the heat generating element rather than center conductor **730**.

In some embodiments, a fluid flows through heater **716** (represented by arrows **736** in FIGS. **105** and **106**) to preheat the formation and/or to recover heat from the heating element. In the embodiment depicted in FIG. **105**, fluid flows from one end of heater **716** to the other end of the heater inside and through heating element **630** and outside center conductor **730**, as shown by arrows **736**. In the embodiment depicted in FIG. **106**, fluid flows into heater **716** through center conductor **730**, which is a tubular conductor, as shown by arrows **736**. Center conductor **730** includes openings **738** at the end of the center conductor to allow fluid to exit the center conductor. Openings **738** may be perforations or other orifices that allow fluid to flow into and/or out of center conductor **730**. Fluid then returns to the surface inside heating element **630** and outside center conductor **730**, as shown by arrows **736**.

Fluid flowing inside heater **716** (represented by arrows **736** in FIGS. **105** and **106**) may be used to preheat the heater, to initially heat the formation, and/or to recover heat from the formation after heating is completed for the in situ heat treatment process. Fluids that may flow through the heater include, but are not limited to, air, water, steam, helium, carbon dioxide or other high heat capacity fluids. In some embodiments, a hot fluid, such as carbon dioxide, helium, or DOWTHERM® (The Dow Chemical Company, Midland, Mich., U.S.A.), flows through the tubular heating elements to provide heat to the formation. The hot fluid may be used to provide heat to the formation before electrical heating is used to provide heat to the formation. In some embodiments, the hot fluid is used to provide heat in addition to electrical heating. Using the hot fluid to provide heat to or preheat the formation in addition to providing electrical heating may be less expensive than using electrical heating alone to provide heat to the formation. In some embodiments, water and/or steam flows through the tubular heating element to recover heat from the formation after in situ heat treatment of the formation. The heated water and/or steam may be used for solution mining and/or other processes.

In some embodiments, an insulated conductor heater is placed in the formation by itself and the outside of the insulated conductor heater is electrically isolated from the formation because the heater has little or no voltage potential on the outside of the heater. FIG. **108** depicts an embodiment of a single-ended, substantially horizontal insulated conductor heater that electrically isolates itself from the formation. In such an embodiment, heater **716** is insulated conductor **558**. Insulated conductor **558** may be a mineral insulated conductor heater (for example, insulated conductor **558** depicted in FIGS. **109**A and **109**B). Insulated conductor **558** is located in opening **522** in hydrocarbon layer **460**. In certain embodiments, opening **522** is an uncased or open wellbore. In some embodiments, opening **522** is a cased or lined wellbore. In some embodiments, insulated conductor heater **558** is a substantially u-shaped heater and is located in a substantially u-shaped opening (for example, the opening depicted in FIG. **105**).

As shown in FIG. **108**, insulated conductor **558** has little or no current flowing along the outside surface of the insulated conductor so that the insulated conductor is electrically isolated from the formation and leaks little or no current into the formation. The outside surface (or jacket) of insulated conductor **558** is a metal or thermal radiating body so that heat is radiated from the insulated conductor to the formation.

FIGS. **109**A and **109**B depict cross-sectional representations of an embodiment of insulated conductor **558** that is electrically isolated on the outside of jacket **506**. In certain embodiments, jacket **506** is made of ferromagnetic materials. In one embodiment, jacket **506** is made of 410 stainless steel. In other embodiments, jacket **506** is made of T/P91 or T/P92 stainless steel. Core **508** is made of a highly conductive material such as copper. Electrical insulator **500** is an electrically insulating material such as magnesium oxide. Insulated conductor **558** may be an inexpensive and easy to manufacture heater.

In the embodiment depicted in FIGS. **109**A and **109**B, core **508** brings current into the formation, as shown by the arrow. Core **508** and jacket **506** are electrically coupled at the distal end (bottom) of the heater. Current returns to the surface of the formation through jacket **506**. The ferromagnetic properties of jacket **506** confine the current to the skin depth along

the inside diameter of the jacket, as shown by arrows **736** in FIG. **109**A. Jacket **506** has a thickness at least 2 or 3 times the skin depth of the ferromagnetic material used in the jacket so that most of the current is confined to the inside surface of the jacket and little or no current flows on the outside diameter of the jacket. Thus, there is little or no voltage potential on the outside of jacket **506**. Having little or no voltage potential on the outside surface of insulated conductor **558** does not expose the formation to any high voltages, inhibits current leakage to the formation, and reduces or eliminates the need for isolation transformers, which decrease energy efficiency.

Because core **508** is made of a highly conductive material such as copper and jacket **506** is made of more resistive ferromagnetic material, a majority of the heat generated by insulated conductor **558** is generated in the jacket. Generating the majority of the heat in jacket **506** increases the efficiency of radiative heat transfer from insulated conductor **558** to the formation over an insulated conductor (or other heater) that uses a core or a center conductor to generate the majority of the heat.

In certain embodiments, core **508** is made of copper. Using copper in core **508** allows the heating section of the heater and the overburden section to have identical core materials. Thus, the heater may be made from one long core assembly. The long single core assembly reduces or eliminates the need for welding joints in the core, which can be unreliable and susceptible to failure. Additionally, the long, single core assembly heater may be manufactured remote from the installation site and transported in a final assembly (ready to install assembly) to the installation site. The single core assembly also allows for long heater lengths (for example, about 1000 m or longer) depending on the breakdown voltage of the electrical insulator.

In certain embodiments, jacket **506** is made from two or more layers of the same materials and/or different materials. Jacket **506** may be formed from two or more layers to achieve thicknesses needed for the jacket (for example, to have a thickness at least 3 times the skin depth of the ferromagnetic material used in the jacket). Manufacturing and/or material limitations may limit the thickness of a single layer of jacket material. For example, the amount each layer can be strained during manufacturing (forming) the layer on the heater may limit the thickness of each layer. Thus, to reach jacket thicknesses needed for certain embodiments of insulated conductor **558**, jacket **506** may be formed from several layers of jacket material. For example, three layers of T/P92 stainless steel may be used to form jacket **506** with a thickness of about 3 times the skin depth of the T/P92 stainless steel.

In some embodiments, jacket **506** includes two or more different materials. In some embodiments, jacket **506** includes different materials in different layers of the jacket. For example, jacket **506** may have one or more inner layers of ferromagnetic material chosen for their electrical and/or electromagnetic properties and one or more outer layers chosen for its non-corrosive properties.

In some embodiments, the thickness of jacket **506** and/or the material of the jacket are varied along the heater length. The thickness and/or material of jacket **506** may be varied to vary electrical properties and/or mechanical properties along the length of the heater. For example, the thickness and/or material of jacket **506** may be varied to vary the turndown ratio along the length of the heater. In some embodiments, the inner layer of jacket **506** includes copper or other highly conductive metals in the overburden section of the heater. The inner layer of copper limits heat losses in the overburden section of the heater.

FIGS. **110**A and **110**B depict an embodiment for using substantially unshaped wellbores to time sequence heat two layers in a hydrocarbon containing formation. A single heater is shown in the embodiments depicted in FIGS. **110**A and **110**B, it is to be understood, however, that there are typically several heaters located in a hydrocarbon layer and that only one heater is shown in the drawings for simplicity. In FIG. **110**A, opening **522**A is formed in hydrocarbon layer **460**A extending between openings **522**. In certain embodiments, opening **522**A is a substantially horizontal opening in hydrocarbon layer **460**A. In some embodiments, opening **522**A is an inclined opening in hydrocarbon layer **460**A (for example, the layer may be an angled layer and the opening is angled to be substantially horizontal in the layer). Openings **522** are openings (for example, relatively vertical openings) that extend from the surface into hydrocarbon layer **460**A. Hydrocarbon layer **460**A may be separated from hydrocarbon layer **460**B by impermeable zone **740**. In certain embodiments, hydrocarbon layer **460**B is an upper layer or a layer at a lesser depth than hydrocarbon layer **460**A. In some embodiments, hydrocarbon layer **460**B is a lower layer or a layer at a greater depth than hydrocarbon layer **460**A. In certain embodiments, impermeable zone **740** provides a substantially impermeable seal that inhibits fluid flow between hydrocarbon layer **460**A and hydrocarbon layer **460**B. In certain embodiments (for example, in an oil shale formation), hydrocarbon layer **460**A has a higher richness than hydrocarbon layer **460**B.

As shown in FIG. **110**A, heating element **630**A is located in opening **522**A in hydrocarbon layer **460**A. Overburden casing **530** is placed along the relatively vertical walls of openings **522** in hydrocarbon layer **460**B. Overburden casing **530** inhibits heat transfer to hydrocarbon layer **460**B while heat is provided to hydrocarbon layer **460**A by heating element **630**A. Heating element **630**A is used to provide heat to hydrocarbon layer **460**A. Formation fluids (such as mobilized hydrocarbons, pyrolyzed hydrocarbons, and/or water) may be produced from hydrocarbon layer **460**A during and/or after heating of the layer by heating element **630**A.

Heat may be provided to hydrocarbon layer **460**A by heating element **630**A for a selected amount of time (for example, a first amount of time). The selected amount of time may be based on a variety of factors including, but not limited to, formation characteristics or properties, present or future economic factors, or capital costs. For example, for an oil shale formation, hydrocarbon layer **460**A may have a richness of about 0.12 L/kg (30.5 gals/ton) and the layer is heated for about 25 years. Production of formation fluids from hydrocarbon layer **460**A may continue from the layer until production slows down to an uneconomical rate.

After hydrocarbon layer **460**A is heated for the selected amount of time, heating element **630**A is turned down and/or off. After heating element **630**A is turned off, the heating element may be pulled firmly (for example, yanked) upwards so that the heating element breaks off at links **742**. Both ends of heating element **630**A at the surface may be pulled simultaneously so that links **742** break approximately simultaneously. Links **742** may be weak links designed to pull apart when a selected or sufficient amount of pulling force is applied to the links. For example, links **742** may be breakable mechanical couplings between portions of the heating element. The upper portions of heating element **630**A are then pulled out of the formation and the substantially horizontal portion of heating element **630**A is left in opening **522**A, as shown in FIG. **110**B.

In some embodiments, only one link **742** may be broken so that the upper portion above the one link can be removed and the remaining portions of the heater can be removed by pull-

ing on the opposite end of the heater. Thus, the entire length of heating element **630**A may be removed from the formation.

After upper portions of heating element **630**A are removed from openings **522**, plugs **744** may be placed into openings **522** at a selected location in hydrocarbon layer **460**B, as depicted in FIG. **110**B. In certain embodiments, plugs **744** are placed into openings **522** at or near impermeable zone **740**. Plugs **744** may include isolation materials such as substantially impermeable materials or other materials that inhibit fluid flow between the hydrocarbon layers in the formation in openings **522** (for example, the plugs may isolate hydrocarbon layer **460**A). In some embodiments, packing **532** is placed into openings **522** above plugs **744**. In some embodiments, packing **532** is placed in openings **522** without plugs in the openings. Packing **532** may include substantially impermeable materials or other materials to inhibit fluid flow.

After plugs **744** and/or packing **532** is set into place in openings **522**, substantially horizontal opening **522**B may be formed in hydrocarbon layer **460**B. Opening **522**B may be formed by punching (for example, drilling) through casing **530** on the wall of opening **522**. In certain embodiments, opening **522**B is a substantially horizontal opening in hydrocarbon layer **460**B. In some embodiments, opening **522**B is an inclined opening in hydrocarbon layer **460**B (for example, the layer may be an angled layer and the opening is angled to be substantially horizontal in the layer). Heating element **630**B is then placed into opening **522**B. Heating element **630**B may be used to provide heat to hydrocarbon layer **460**B. Formation fluids, such as pyrolyzed hydrocarbons and/or mobilized hydrocarbons, may be produced from hydrocarbon layer **460**B during and/or after heating of the layer by heating element **630**B.

In certain embodiments, opening **522** is a single-ended horizontal opening in hydrocarbon layer **460**A (for example, the opening has only one end open at the surface of the formation). FIGS. **111**A and **111**B depict an embodiment for using single-ended horizontal wellbores to time sequence heat two layers in a hydrocarbon containing formation. A single heater is shown in the embodiments depicted in FIGS. **111**A and **111**B, it is to be understood, however, that there are typically several heaters located in a hydrocarbon layer and that only one heater is shown in the drawings for simplicity.

In FIG. **111**A, opening **522**A is formed in hydrocarbon layer **460**A extending from opening **522**. In certain embodiments, opening **522**A is a substantially horizontal opening in hydrocarbon layer **460**A that terminates in the layer. In some embodiments, opening **522**A is an inclined opening in hydrocarbon layer **460**A (for example, the layer may be an angled layer and the opening is angled to be substantially horizontal in the layer). Opening **522** is an opening (for example, a relatively vertical opening) that extends from the surface into hydrocarbon layer **460**A. Hydrocarbon layer **460**A may be separated from hydrocarbon layer **460**B by impermeable zone **740**. In certain embodiments, hydrocarbon layer **460**B is an upper layer or a layer at a lesser depth than hydrocarbon layer **460**A. In other embodiments, hydrocarbon layer **460**B is a lower layer or a layer at a greater depth than hydrocarbon layer **460**A. In certain embodiments, impermeable zone **740** provides a substantially impermeable seal that inhibits fluid flow between hydrocarbon layer **460**A and hydrocarbon layer **460**B. In certain embodiments (for example, in an oil shale formation), hydrocarbon layer **460**A has a higher richness than hydrocarbon layer **460**B.

As shown in FIG. **111**A, heating element **630**A is located in opening **522**A in hydrocarbon layer **460**A. Overburden casing **530** is placed along the relatively vertical walls of opening **522** in hydrocarbon layer **460**B. Overburden casing **530** inhibits heat transfer to hydrocarbon layer **460**B while heat is provided to hydrocarbon layer **460**A by heating element **630**A. Heating element **630**A is used to provide heat to hydrocarbon layer **460**A. Formation fluids (such as mobilized hydrocarbons, pyrolyzed hydrocarbons, and/or water) may be produced from hydrocarbon layer **460**A during and/or after heating of the layer by heating element **630**A.

Heat may be provided to hydrocarbon layer **460**A by heating element **630**A for a selected amount of time. The selected amount of time may be based on a variety of factors including, but not limited to, formation characteristics or properties, present or future economic factors, or capital costs. For example, for an oil shale formation, hydrocarbon layer **460**A may have a richness of about 0.12 L/kg (30.5 gals/ton) and the layer is heated for about 25 years. Production of formation fluids from hydrocarbon layer **460**A may continue from the layer until production slows down to an uneconomical rate.

After hydrocarbon layer **460**A is heated for the selected amount of time, heating element **630**A is turned down and/or off. After heating element **630**A is turned down and/or off, the heating element may be removed from opening **522**A. In some embodiments, one or more portions of heating element **630**A are left in opening **522**A. For example, portions of hydrocarbon layer **460**A may clamp or squeeze on heating element **630**A so that the heating element cannot be completely removed from opening **522**A. In such cases, heating element **630**A may be broken at link **742** and the upper portion of heating element **630**A is pulled out of the formation and the substantially horizontal portion of the heating element is left in opening **522**A.

After heating element **630**A is removed from opening **522**, plug **744** may be placed into opening **522** at a selected location in hydrocarbon layer **460**B, as depicted in FIG. **111**B. In certain embodiments, plug **744** is placed into opening **522** at or near impermeable zone **740**. Plug **744** may include isolation materials such as substantially impermeable materials or other materials that inhibit fluid flow between the hydrocarbon layers in the formation in openings **522** (for example, the plug may isolate hydrocarbon layer **460**A). In some embodiments, packing **532** is placed into opening **522** above plug **744**. In some embodiments, packing **532** is placed in opening **522** without a plug in the opening. Packing **532** may include substantially impermeable materials or other materials to inhibit fluid flow.

After plug **744** and/or packing **532** is set into place in opening **522**, substantially horizontal opening **522**B may be formed in hydrocarbon layer **460**B. Opening **522**B may extend horizontally from opening **522**. In certain embodiments, opening **522**B is a substantially horizontal opening in hydrocarbon layer **460**B that terminates in the layer. In some embodiments, opening **522**B is an inclined opening in hydrocarbon layer **460**B (for example, the layer may be an angled layer and the opening is angled to be substantially horizontal in the layer). Opening **522**B may be formed by punching (for example, drilling) through casing **530** on the wall of opening **522**. Heating element **630**B is then placed into opening **522**B. Heating element **630**B may be used to provide heat to hydrocarbon layer **460**B. Formation fluids, such as pyrolyzed hydrocarbons and/or mobilized hydrocarbons, may be produced from hydrocarbon layer **460**B during and/or after heating of the layer by heating element **630**B.

Heating hydrocarbon layers **460**A, **460**B in the time-sequenced manners described above may be more economical than producing from only one layer or using vertical heaters to provide heat to the layers simultaneously. Using relatively vertical openings **522** to access both hydrocarbon layers at

different times may save on capital costs associated with forming openings in the formation and providing surface facilities to power the heating elements. Heating hydrocarbon layer **460**A first before heating hydrocarbon layer **460**B may improve the economics of treating the formation (for example, the net present value of a project to treat the formation). In addition, impermeable zone **740** and packing **532** may provide a seal for hydrocarbon layer **460**A after heating and production from the layer. This seal may be useful for abandonment of the hydrocarbon layer after treating the hydrocarbon layer.

In some embodiments, heat may be scavenged from hydrocarbon layer **460**A and used to provide heat to hydrocarbon layer **460**B. For example, a heat transfer fluid may be circulated through opening **522**A to recover heat from hydrocarbon layer **460**A. The heat transfer fluid may later be used to provide heat directly or indirectly (for example, using a heat exchanger to transfer heat to another heating fluid) to hydrocarbon layer **460**B. In some embodiments, heat recovered from hydrocarbon layer **460**A is used to provide power (for example, electrical power) to other heaters (for example, heating element **630**B used in hydrocarbon layer **460**B).

In some embodiments, synthesis gas generation or other post-treatment processes may be performed in hydrocarbon layer **460**A before heating in hydrocarbon layer **460**B is started. For example, carbon dioxide or other materials may be sequestered in hydrocarbon layer **460**A before plugging or sealing off the layer.

In certain embodiments, portions of the wellbore that extend through the overburden include casings. The casings may include materials that inhibit inductive effects in the casings. Inhibiting inductive effects in the casings may inhibit induced currents in the casing and/or reduce heat losses to the overburden. In some embodiments, the overburden casings may include non-metallic materials such as fiberglass, polyvinylchloride (PVC), chlorinated PVC (CPVC), high-density polyethylene (HDPE), high temperature polymers (such as nitrogen based polymers), or other high temperature plastics. HDPEs with working temperatures in a usable range include HDPEs available from Dow Chemical Co., Inc. (Midland, Mich., U.S.A.). The overburden casings may be made of materials that are spoolable so that the overburden casings can be spooled into the wellbore. In some embodiments, overburden casings may include non-magnetic metals such as aluminum or non-magnetic alloys such as manganese steels having at least 10% manganese, iron aluminum alloys with at least 18% aluminum, or austentitic stainless steels such as 304 stainless steel or 316 stainless steel. In some embodiments, overburden casings may include carbon steel or other ferromagnetic material coupled on the inside diameter to a highly conductive non-ferromagnetic metal (for example, copper or aluminum) to inhibit inductive effects or skin effects. In some embodiments, overburden casings are made of inexpensive materials that may be left in the formation (sacrificial casings).

In certain embodiments, wellheads for the wellbores may be made of one or more non-ferromagnetic materials. FIG. **112** depicts an embodiment of wellhead **2032**. The components in the wellheads may include fiberglass, PVC, CPVC, HDPE, high temperature polymers (such as nitrogen based polymers), and/or non-magnetic alloys or metals. Some materials (such as polymers) may be extruded into a mold or reaction injection molded (RIM) into the shape of the wellhead. Forming the wellhead from a mold may be a less expensive method of making the wellhead and save in capital costs for providing wellheads to a treatment site. Using non-ferromagnetic materials in the wellhead may inhibit undesired heating of components in the wellhead. Ferromagnetic materials used in the wellhead may be electrically and/or thermally insulated from other components of the wellhead. In some embodiments, an inert gas (for example, nitrogen or argon) is purged inside the wellhead and/or inside of casings to inhibit reflux of heated gases into the wellhead and/or the casings.

In some embodiments, ferromagnetic materials in the wellhead are electrically coupled to a non-ferromagnetic material (for example, copper) to inhibit skin effect heat generation in the ferromagnetic materials in the wellhead. The non-ferromagnetic material is in electrical contact with the ferromagnetic material so that current flows through the non-ferromagnetic material. In certain embodiments, as shown in FIG. **112**, non-ferromagnetic material **2034** is coupled (and electrically coupled) to the inside walls of conduit **518** and wellhead walls **2036**. In some embodiments, copper may be plasma sprayed, coated, clad, or lined on the inside and/or outside walls of the wellhead. In some embodiments, a non-ferromagnetic material such as copper is welded, brazed, clad, or otherwise electrically coupled to the inside and/or outside walls of the wellhead. For example, copper may be swaged out to line the inside walls in the wellhead. Copper may be liquid nitrogen cooled and then allowed to expand to contact and swage against the inside walls of the wellhead. In some embodiments, the copper is hydraulically expanded or explosively bonded to contact against the inside walls of the wellhead.

In some embodiments, two or more substantially horizontal wellbores are branched off of a first substantially vertical wellbore drilled downwards from a first location on a surface of the formation. The substantially horizontal wellbores may be substantially parallel through a hydrocarbon layer. The substantially horizontal wellbores may reconnect at a second substantially vertical wellbore drilled downwards at a second location on the surface of the formation. Having multiple wellbores branching off of a single substantially vertical wellbore drilled downwards from the surface reduces the number of openings made at the surface of the formation.

Continuous tubulars, such as coil tubing, have been used for many years. Running continuous tubulars into and/or out of a wellbore may be simpler and faster than running tubing formed of conventional jointed pipe.

Continuous tubulars may be run into and/or out of wellbores using injectors. Injectors may force the continuous tubulars into the wells through a lubricator assembly or stuffing box to overcome any well pressure until the weight of the continuous tubulars exceeds the force applied by the well pressure that acts against the cross-sectional area of the continuous tubulars. Once the weight of the continuous tubular overcomes the pressure, the continuous tubular may need to be supported by the injector. The process may be reversed as the continuous tubular is removed from the well.

A method for running dual jointed tubing strings into and out of wells is described in U.S. Pat. No. 4,474,236 to Kellett, which is incorporated by reference as if fully set forth herein. Kellett describes a method and apparatus for completing a well using jointed production and service strings of different diameters. The method includes steps of running the production string on a main tubing string hanger while maintaining control with a variable bore blowout preventer; and, running the service string into the main tubing string hanger while maintaining control with a dual bore blowout preventer.

Continuous tubulars have been used for various well treatment processes such as fracturing, acidizing, and gravel packing. Typically, several thousand feet of flexible, seamless tubing is coiled onto a large reel that is mounted on a truck or skid. A continuous tubular injector with a chain-track drive,

or equivalent, may be mounted above the wellhead. The continuous tubular may be fed to the injector for injection into the well. The continuous tubular may be straightened as it is removed from the reel by a continuous tubular guide that aligns the continuous tubular with the wellbore and the injector mechanism.

The use of dual continuous tubulars for well servicing and production is known in the art. Recent developments in well completion and well workover have demonstrated the utility of using two continuous tubulars concurrently for many downhole operations. A difficulty with injecting dual continuous tubulars into a wellbore is the proximity of the respective continuous tubulars and the lack of working space to deploy a pair of continuous tubular injector assemblies mounted above the wellhead. This problem was apparently resolved with a coil tubing string injector assembly adapted to simultaneously inject dual string coil tubing into a wellbore, as disclosed in U.S. Pat. No. 6,516,891 to Dallas, which is incorporated herein by reference.

Another problem associated with the injection of dual continuous tubulars into a wellbore is the prevention of fluid leakage during the injection of the dual continuous tubulars, especially when a long downhole tool is connected to one or both of the continuous tubulars. Downhole tools typically have a larger diameter than the continuous tubular and cannot be plastically deformed, which presents certain difficulties. It is known in the art how to overcome these difficulties while injecting a single continuous tubular. For example, U.S. Pat. No. 4,940,095 to Newman, which is incorporated herein by reference, discloses a method of inserting a well service tool connected to a coiled tubing string, which avoids the high and/or remote mounting of a heavy coiled tubing injector drive mechanism. A closed-end lubricator is used to house the tool until it is run down through a blowout preventer connected to a top of the well. The pipe rams of the blowout preventer are closed around the tool to support it while a tubing injector is mounted to the wellhead and the coil tubing string is connected to the tool. The blowout preventer is then opened and the coil tubing string injector is used to run the tool into the well. However, Newman fails to address the use of dual string continuous tubulars.

Many subsurface wells are fitted with permanent sensors, such as pressure and temperature sensors, which require electrical power to transmit signals from the sensors to a remote point at the surface. Subsurface wells may employ subsurface equipment such as pumps or heaters, which may also require electrical power. In order to supply power to these subsurface pieces of equipment, electric current from a source outside of the wellhead must be transferred through the wellhead to the electrically responsive device. Electrical power can be supplied downhole by several methods. These methods include, but are not limited to, electrical umbilical cords, rigid tubular conductors, or coiled tubing. No matter which method of power supply is employed, in order to transfer the power through the wellhead, the power supply is transferred through either the tubing hanger or the casing hanger.

The extreme environmental conditions inside the wellhead coupled with the rough nature of completion operations may cause damage to devices used to supply electrical power. Damaged equipment may potentially lead to electrical short-circuits that can present a hazard to persons working around the wellhead. Since the majority of wellhead equipment is constructed of conductive materials, an electrical short inside of the wellhead may charge the outer surface of the wellhead. Unprotected persons may be exposed to electrical shock if contact is made with the wellhead's outer surface. Continuous tubulars subjected to electrical charge (for example, heaters) may be insulated from the wellhead of the wellbore.

Typically, a continuous tubular is inserted into a wellhead through a lubricator assembly or a stuffing box because there is a pressure differential between the wellbore and atmosphere. The pressure differential may be naturally or artificially created and produce oil or gas, or a mixture thereof, from the pressurized well. Wellhead mechanisms may inhibit movement of continuous tubulars upward and out of the wellbore as well as inhibit downward movement into the wellbore.

In certain embodiments, a suspension mechanism is capable of suspending dual continuous tubulars (for example, dual insulated conductor heaters). In some embodiments, the suspension mechanism includes slips or special fittings. With slips, a radial gripping force keeps dual continuous tubulars suspended and inhibits downward movement. In some embodiments, the slips inhibit upward movement (for example, upward movement of the dual continuous tubulars). Inhibiting upward movement may be accomplished by using a reverse slip arrangement. Conventional wellheads and hangers may not be designed to restrain movement of continuous tubulars in the upward direction. Instead, conventional wellheads and hangers may be only designed to suspend the strings due to the gravitational load of the continuous tubulars.

Deployment and suspension of continuous tubulars in the wellbore may require a mechanism that suspends the dual continuous tubulars in the wellhead by some suitable hanging mechanism or hanger. The hanging/suspension mechanisms may function when the dual legs of the continuous tubulars are deployed simultaneously. Conventionally, dual continuous tubulars are not deployed simultaneously. In some embodiments, a suspension mechanism is able to suspend the vertical downward load of both the tubulars as well as inhibit the upward movement of the tubulars.

FIG. **113** depicts an embodiment of a dual continuous tubular suspension mechanism **2040** for inhibiting movement of at least two continuous tubulars **484**. Suspension mechanism **2040** may be formed or positioned within wellhead **450**. Suspension mechanism **2040** may include threading cut along at least a portion of dual continuous tubulars **484** over expanded portion **484**A of the tubular. In some embodiments, the tubular is a heater. In some embodiments, expanded portion **484**A includes a threaded tubular portion to which a threaded collar is coupled. Suspension mechanism **2040** may include lower portion **2040**A and upper portion **2040**B. Upper portion **2040**B may include at least two openings with diameters large enough to allow passage of the tubulars as well as threaded collar **2042**, but small enough to inhibit passage of expanded portions of the tubulars. Lower portion **2040**A may include lip **2040**A'. Lip **2040**A' may inhibit movement of the threaded collars in a downward direction. Lip **2040**A' restricts movement of the tubulars in a downward direction once the expanded portion of the tubulars are threaded into the collars.

The wellhead and the suspension mechanism may include one or more seals **2038**. Seals **2038** may inhibit wellbore fluids from migrating upwards. Seals **2038** may help maintain a desired pressure in the wellbore. Wellcap **448** keeps the suspension mechanism in place and inhibits upward movement. Wellhead **450** may include an opening in which the suspension mechanism is positioned. The opening may narrow to a diameter less than that of the suspension mechanism to inhibit downward movement of the suspension mechanism.

FIG. **114** depicts an embodiment of dual continuous tubular suspension mechanism **2040** for inhibiting movement of at least two continuous tubulars **484**. Suspension mechanism **2040** may be formed or positioned within wellhead **450**. Continuous tubulars **484** may include expanded portion **484**A and function in a similar fashion as is described in the embodiment depicted in FIG. **113**. Expanded portion **484**A depicted in FIG. **114**, however, may be formed by welding or otherwise attaching two pieces of split cylinder to tubular **484**.

FIGS. **115**A-B depict embodiments of dual continuous tubular suspension mechanisms **2040**. Suspension mechanisms **2040** include slip mechanisms that inhibit upward and downward movement of tubulars **484**. The slip mechanisms may include inhibitors **2044**. Inhibitors **2044** may allow movement in a first direction while inhibiting movement in a second direction. The second direction may be in a direction opposite to the first direction. Inhibitors **2044** may include upper inhibitors **2044**B and lower inhibitors **2044**A. Upper inhibitors **2044**B may allow movement of the tubulars in a downward direction while inhibiting movement of the tubulars in an upward direction. Lower inhibitors **2044**A may allow movement of the tubulars in an upward direction, while inhibiting movement of the tubulars in a downward direction. Inhibitors **2044** may inhibit movement using serrations angled such that the serrations engage a tubular when the tubular moves in a first direction, but not when the tubular moves in a second direction that is substantially opposite to the first direction.

In some embodiments, inhibitors include coatings. The coating may impart specific desirable properties to the inhibitor to which the coating is applied. For example, a coating may include a temperature resistant polymer coating.

Suspension mechanism **2040** may include lower portion **2040**A and upper portion **2040**B. Upper portion **2040**B may include at least two openings with diameters large enough to allow passage of the tubulars at both ends of each opening, but small enough at the proximal ends of the openings to inhibit passage of upper inhibitors **2044**B in an upward direction. The distal ends of the openings may be large enough to allow the upper inhibitors to sit within the openings of the upper portion **2044**B of suspension mechanism **2040**. Lower portion **2040**A may include at least two openings with diameters large enough to allow passage of the tubulars at both ends of the openings, but small enough at the distal end of each opening to inhibit passage of lower inhibitors **2044**A in a downward direction. The proximal ends of the openings may be large enough to allow the lower inhibitors to sit within the openings of lower portion **2040**A of suspension mechanism **2040**.

Suspension mechanism **2040** may include locks **2046**. In some embodiments, locks **2046** are screws, bolts, or other types of fasteners. Locks **2046** inhibit movement of one or more portions of suspension mechanism **2040** within wellhead **450**. Wellhead **450** may include an opening in which suspension mechanism **2040** is positioned. The opening may narrow to a diameter less than that of suspension mechanism **2040** to inhibit downward movement of the suspension mechanism.

FIGS. **116-117** depict embodiments of dual continuous tubular suspension mechanisms **2040** within wellhead **450**. As detailed in FIGS. **115**A-B, suspension mechanisms **2040** employs a slip mechanism using upper and lower inhibitors **2044**. In FIG. **116**, wellcap **448** of wellhead **450** assists in keeping suspension mechanism **2040** in position. Lock **2046** inhibits upward movement of the wellcap and suspension mechanism **2040**. In the embodiment depicted in FIG. **116**, wellcap **448** is a part of a seal assembly using seals **2038**.

FIG. **117** depicts an embodiment of suspension mechanisms **2040** in wellhead **450**. Wellcap **448** may be sandwiched between upper portion **2040**A and lower portion **2040**B of suspension mechanism **2040**. Lock **2046** inhibits upward movement of upper portion **2040**A of the suspension mechanism, and the wellcap and suspension mechanism as a whole. Locks **2046'** inhibit movement of upper portion **2040**A and lower portion **2040**B of suspension mechanism **2040** and wellcap **448** in relation to one another.

FIG. **118** depicts an embodiment of pass-through fitting **2048** used to suspend tubulars **484**. Pass-through fitting **2048** may function to suspend tubulars **484**. Pass-through fitting **2048** may include commercially available products (for example, available from Swagelok Company (Solon, Ohio, USA) or VULKAN LOKRING Rohrverbindung GmbH & Co. KG (Heme, Germany)). Pass-through fitting **2048** may inhibit movement of tubulars **484** in the downward direction. A second mechanism may be utilized to inhibit movement of the tubulars in the upward direction. The second mechanism may be a reverse configuration of the pass-through fittings **2048**.

FIG. **119** depicts an embodiment of dual slip suspension mechanism **2040** for inhibiting movement of tubulars **484** positioned in an opening of wellhead **450**. FIG. **119** depicts a two-way lock arrangement using a slip mechanism. Bottom threading has right-handed threading, and top threading has left-handed threading. Rotation of the center nut in the clockwise direction (when viewed from top) causes the fittings to be drawn together, tightening the slips and causing the slips to grip the tubular/rod/heater. The entire assembly can then be suspended in a wellhead housing as shown. Using the two lock-screws shown in the figure, the entire assembly can be locked into place. The two lock-screws may suspend the tubular/rod/heater and restrict downward and upward movement of the tubular/rod/heater.

FIGS. **120**A-B depict embodiments of lower portion of split suspension mechanisms **2040**A and lower split inhibitor assemblies **2044**A for hanging dual continuous tubulars **484**. Lower inhibitor assemblies **2044**A and lower portion of suspension mechanisms **2040**A may be split such that they fit together around tubulars **484**. When the assembly is positioned in a wellhead the assembly may function as a compression fitting to inhibit downward movement of the tubulars. Lower inhibitor assemblies **2044**A may include special non-marking dies or surfaces (for example, WC particles (tungsten carbide particles) embedded in mild steel) that function to simultaneously hold both the tubulars. Lower inhibitor assemblies **2044**A may include a specific taper angle that sits in lower portion of suspension mechanisms **2040**A. In this configuration, the lower inhibitor assemblies **2044**A are shown to have special grit-faced non-marking surface.

FIG. **121** depicts an embodiment of dual slip suspension mechanisms **2040** for inhibiting movement of tubulars **484** with a reverse configuration relative to the embodiment depicted in FIG. **117**. Upper inhibitor **2044**B, which prevents upward movement, is deployed first and locked into place with bottom locks **2046'** and lower portion of suspension mechanism **2040**A. Lower inhibitor **2044**A, which hangs the weight of the pipe and inhibits downward movement of pipe, is deployed in reverse order and locked in place with bottom locks **2046"** and upper portion of suspension mechanism **2040**B. Wellcap **448** including seals **2038** are introduced next from the top. The suspension mechanism **2040** may be locked in position using locks **2046'"**. A third or middle portion

2040C of the suspension mechanism cradles both the upper and lower inhibitors while the upper portion 2044B and lower portion 2044A of the suspension mechanism inhibit movement of the inhibitors within openings in middle portion 2040C of the suspension mechanism.

FIG. 122 depicts an embodiment of a two-part dual slip mechanism of suspension mechanism 2040 for inhibiting movement of tubulars 484. Middle portion 2040C of the suspension mechanism is divided into two portions, lower portion 2040C' and upper portion 2040C". The two portions of middle portion 2040C may be coupled together using lock 2046C. Lock 2046C may include threaded studs as depicted in FIG. 122. The top half of each stud 2046C may have left-handed threading and the bottom half of each stud may have right-handed threading. Each stud 2046C screws into the bottom and top of upper portion 2040C" and lower portion 2040C' of suspension mechanism 2040. When the stud is rotated in the clockwise direction when viewed from the top, both upper portion 2040C" and lower portion 2040C' approach each other. Each stud is rotated a little each time in sequence going around such that the upper portion 2040C" and lower portion 2040C' move towards each other gradually and substantially uniformly. The movement causes the inhibitors to tighten and grip the tubulars.

In some embodiments, the above operation is done in a 'false wellhead housing' (not shown) just above the wellhead after the inhibitors are tightened together, the tubulars are lifted, until they clear the false-wellhead, which is then removed. The tubulars along with the suspension mechanism are lowered into a wellhead housing and the load is transferred to the shoulder (for example, a protrusion or narrowing of the opening in the wellhead which inhibits movement of the suspension mechanism beyond the protrusion). The locks 2046'" are tightened to inhibit movement of the suspension mechanism relative to the wellhead.

FIG. 123 depicts an embodiment of two-part dual slip suspension mechanism 2040 for inhibiting movement of tubulars 484 with separate locks 2046. FIG. 123 depicts an embodiment with a reverse configuration of inhibitors 2044 from the configuration depicted in FIGS. 121-122. In FIG. 123, the suspension mechanism is depicted in two distinct sections. The two sections may be activated separately. Lower portion 2040A of a suspension mechanism may include lower portion 2040A' and upper portion 2040A". Portions 2040A' and 2040A" function in combination when activated to inhibit movement of inhibitors 2044B and hence inhibit upward movement of tubulars 484. Lower portion 2040A may be activated by assembling portions 2040A', 2040A" and inhibitors 2044B, inserting the assembly until downward movement is inhibited by lip 2050', and upon positioning tubulars 484, activating lock 2046'. Activating lock 2046' may compress lower portion assembly together such that inhibitors 2044B grip tubulars 484. Upper portion 2040B may be activated by assembling portion 2040B and inhibitors 2044A, inserting the assembly until downward movement is inhibited by lip 2050", and activating lock 2046"after positioning tubulars 484. Activating lock 2046" may compress upper portion 2040B against lip 2050". Inhibitors 2044A may be held in position within opening in upper portion 2040B by gravity.

FIG. 124 depicts an embodiment of dual slip suspension mechanism 2040 with locking upper plate 2040B for inhibiting movement of tubulars 484. The embodiment of lower portion 2040A depicted in FIG. 124 may function in a similar manner to upper portion 2040B of the suspension mechanism depicted in FIG. 123. Inhibitors 2044A inhibit downward movement of tubulars 484. However, instead of including a second set of inhibitors to inhibit upward movement as in FIG. 123, upper portion 2040B (for example, a plate) is positioned above lower portion 2040A. Upper portion 2040B locks inhibitors 2044A in place to inhibit upward movement of tubulars 484 upon activation of locks. Activating locks 2046" couples upper portion 2040B to lower portion 2040A.

In some embodiments, lower portion 2040A may include a tapered opening extending through it. The lower portion may include a carrier with a tapered shape complementary to the tapered opening in the lower portion. The carrier may sit within the tapered opening of the lower portion. Inhibitors 2044A fit in complementary tapered openings through the carrier. The load of the tubulars, once positioned, is transferred from the inhibitors to the carrier to the lower portion, and then to the wellhead. Using a lower portion with a carrier for the inhibitors may be advantageous when the distance between tubulars is small.

FIG. 125 depicts an embodiment of segmented dual slip suspension mechanism 2040 with locking screws 2046 for inhibiting movement of tubulars 484. FIG. 125 depicts an arrangement where inhibitors 2044 are shown in six separate segments that are individually controlled by six locks 2046. The profile on inhibitors 2044 are such that when all the inhibitor segments are in-place, the inhibitor segments conform exactly to the contours of the dual tubulars and grip them tight to prevent motion in both the upward and downward directions. The weight of the tubulars is transferred by the inhibitors to a load shoulder (for example, lip 2050) in the wellhead.

Power supplies are used to provide power to downhole power devices (downhole loads) such as, but not limited to, reservoir heaters, electric submersible pumps (ESPs), compressors, electric drills, electrical tools for construction and maintenance, diagnostic systems, sensors, or acoustic wave generators. Surface based power supplies may have long supply cabling (power cables) that contribute to problems such as voltage drops and electrical losses. Thus, it may be necessary to provide power to the downhole loads at high voltages to reduce electrical losses. However, many downhole loads are limited by an acceptable supply voltage level to the load. Therefore, an efficient high-voltage energy supply may not be viable without further conditioning. In such cases, a system for stepping down the voltage from the high voltage supply cable to the low voltage load may be necessary. The system may be a transformer.

The electrical power supply for downhole loads is typically provided using alternating voltage (AC voltage) from supply grids of 50 Hz or 60 Hz frequency. The voltage of the supply grid may correspond to the voltage of the downhole load. High supply voltages may reduce loss and voltage drop in the supply cable and/or allow the use of supply cables with relatively small cross sections. High supply voltages, however, may cause technically difficulties and require cost intensive isolation efforts at the load. Voltage drops, electrical losses, and supply cable cross section limits may limit the length of the supply cable and, thus, the wellbore depth or depth of the downhole load. Locating the transformer downhole may reduce the amount of cabling needed to provide power to the downhole loads and allow deeper wellbore depths and/or downhole load depths while minimizing voltage drops and electrical losses in the power system.

Current technical solutions for offshore-applications make use of sea-bed mounted step-down transformers to reduce cable loss (for example, "Converter-Fed Subsea Motor Drives", Raad, R. O.; Henriksen, T.; Raphael, H. B.; Hadler-Jacobsen, A.; Industry Applications, IEEE Transactions on Volume 32, Issue 5, September-October 1996 Page(s): 1069-1079, which is incorporated by reference as if fully set forth

herein). However, these sea-bed mounted transformers may not be useful to drive downhole loads under solid ground (for example, in a subsurface wellbore).

FIGS. **126** and **127** depict an embodiment of transformer **728** that may be located in a subsurface wellbore. FIG. **126** depicts a top view representation of the embodiment of transformer **728** showing the windings and core of the transformer. FIG. **127** depicts a side view representation of the embodiment of transformer **728** showing the windings, the core, and the power leads. Transformer **728** includes primary windings **2052**A and secondary windings **2052**B. Primary windings **2052**A and secondary windings **2052**B may have different cross-sectional areas.

Core **2054** may include two half-shell core sections **2054**A and **2054**B around primary windings **2052**A and secondary windings **2052**B. In certain embodiments, core sections **2054**A and **2054**B are semicircular, symmetric shells. Core sections **2054**A and **2054**B may be single pieces that extend the full length of transformer **728** or the core sections may be assembled from multiple shell segments put together (for example, multiple pieces strung together to make the core sections). In certain embodiments, a core section is formed by putting together the section from two halves. The two halves of the core section may be put together after the windings, which may be pre-fabricated, are placed in the transformer.

In certain embodiments, core sections **2054**A and **2054**B have about the same cross section on the circumference of transformer **728** so that the core properly guides the magnetic flux in the transformer. Core sections **2054**A and **2054**B may be made of several layers of core material. Certain orientations of these layers may be designed to minimize eddy current losses in transformer **728**. In some embodiments, core sections **2054**A and **2054**B are made of continuous ribbons and windings **2052**A and **2052**B are wound into the core sections.

Transformer **728** may have certain advantages over current transformer configurations (such as a toroid core design with the winding on the outside of the cores). Core sections **2054**A and **2054**B have outer surfaces that offer large surface areas for cooling transformer **728**. Additionally, transformer **728** may be sealed so that a cooling liquid may be continuously run across the outer surfaces of the transformer to cool the transformer. Transformer **728** may be sealed so that cooling liquids do not directly contact the inside of the core and/or the windings. In certain embodiments, transformer is sealed in an epoxy resin or other electrically insulating sealing material. Cooling transformer **728** allows the transformer to operate at higher power densities. In certain embodiments, windings **2052**A and **2052**B are substantially isolated from core sections **2054**A and **2054**B so that the outside surfaces of transformer **728** may touch the walls of a wellbore without causing electrical problems in the wellbore.

In some embodiments, the profile of the core of transformer **728** and/or the winding window profile are made with clearances to allow for additional cooling devices, mechanical supports, and/or electrical contacts on the transformer. In some embodiments, transformer **728** is coupled to one or more additional transformers in the subsurface wellbore to increase power in the wellbore and/or phase options in the wellbore. Transformer **728** and/or the phases of the transformer may be coupled to the additional transformers, and/or the varying phases of the additional transformers, in either series or parallel configurations as needed to provide power to the downhole load.

FIG. **128** depicts an embodiment of transformer **728** in wellbore **756**. Transformer **728** is located in the overburden section of wellbore **756**. The overburden section of wellbore **756** has overburden casing **530** on the walls of the wellbore. Overburden casing **530** electrically and thermally insulates the overburden from the inside of wellbore **756**. Packing material **532** is located at the bottom of the overburden section of wellbore **756**. Packing material **532** inhibits fluid flow between the overburden section of wellbore **756** and the heating section of the wellbore.

Power lead **2058** may be coupled to transformer **728** and pass through packing material **532** to provide power to the downhole load (for example, a downhole heater). In certain embodiments, cooling fluid **2056** is located in wellbore **756**. Transformer **728** may be immersed in cooling fluid **2056**. Cooling fluid **2056** may cool transformer **728** by removing heat from the transformer and moving the heat away from the transformer. Cooling fluid **2056** may be circulated in wellbore **756** to increase heat transfer between transformer **728** and the cooling fluid. In some embodiments, cooling fluid **2056** is circulated to a chiller or other heat exchanger to remove heat from the cooling fluid and maintain a temperature of the cooling fluid at a selected temperature. Maintaining cooling fluid **2056** at a selected temperature may provide efficient heat transfer between the cooling fluid and transformer **728** so that the transformer is maintained at a desired operating temperature.

In certain embodiments, cooling fluid **2056** maintains a temperature of transformer **728** below a selected temperature. The selected temperature may be a maximum operating temperature of the transformer. In some embodiments, the selected temperature is a maximum temperature that allows for a selected operational efficiency of the transformer. In some embodiments, transformer **728** operates at an efficiency of at least 95%, at least 90%, at least 80%, or at least 70% when the transformer operates below the selected temperature.

In certain embodiments, cooling fluid **2056** is water. In some embodiments, cooling fluid **2056** is another heat transfer fluid such as, but not limited to, oil, ammonia, helium, or Freon® (E. I. du Pont de Nemours and Company, Wilmington, Del., U.S.A.). In some embodiments, the wellbore adjacent to the overburden functions as a heat pipe. Transformer **728** boils cooling fluid **2056**. Vaporized cooling fluid **2056** rises in the wellbore, condenses, and flows back to transformer **728**. Vaporization of cooling fluid **2056** transfers heat to the cooling fluid and condensation of the cooling fluid allows heat to transfer to the overburden. Transformer **728** may operate near the vaporization temperature of cooling fluid **2056**.

In some embodiments, cooling fluid is circulated in a pipe that surrounds the transformer. The pipe may be in direct thermal contact with the transformer so that heat is removed from the transformer into the cooling fluid circulating through the pipe. In some embodiments, the transformer includes fans, heat sinks, fins, or other devices that assist in transferring heat away from the transformer. In some embodiments, the transformer is, or includes, a solid state transformer device such as an AC to DC converter.

In certain embodiments, cooling fluid **2056** is circulated using a heat pipe in wellbore **756**. FIG. **129** depicts an embodiment of transformer **728** in wellbore **756** with heat pipes **2060**A,B. Lid 2062 is placed at the top of a reservoir of cooling fluid **2056** that surrounds transformer **728**. Heated cooling fluid expands and flows up heat pipe **2060**A. The heated cooling fluid **2056** cools adjacent to the overburden and flows back to lid **2062**. The cooled cooling fluid **2056** flows back into the reservoir through heat pipe **2060**B. Heat pipes **2060**A,B act to create a flow path for the cooling fluid so

that the cooling fluid circulates around transformer **728** and maintains a temperature of the transformer below the selected temperature.

Computational analysis has shown that a circulated water column was sufficient to cool a 60 Hz transformer that was 125 feet in length and generated 80 W/ft of heat. The transformer and the formation were initially at ambient temperatures. The water column was initially at an elevated temperature. The water column and transformer cooled over a period of about 1 to 2 hours. The transformer initially heated up (but was still at operable temperatures) but then was cooled by the water column to lower operable temperatures. The computations also showed that the transformer would be cooled by the water column when the transformer and the formation were initially at higher than normal temperatures.

In certain embodiments, a temperature limited heater is utilized for heavy oil applications (for example, treatment of relatively permeable formations or tar sands formations). A temperature limited heater may provide a relatively low Curie temperature and/or phase transformation temperature range so that a maximum average operating temperature of the heater is less than 350° C., 300° C., 250° C., 225° C., 200° C., or 150° C. In an embodiment (for example, for a tar sands formation), a maximum temperature of the heater is less than about 250° C. to inhibit olefin generation and production of other cracked products. In some embodiments, a maximum temperature of the heater above about 250° C. is used to produce lighter hydrocarbon products. For example, the maximum temperature of the heater may be at or less than about 500° C.

A heater may heat a volume of formation adjacent to a production wellbore (a near production wellbore region) so that the temperature of fluid in the production wellbore and in the volume adjacent to the production wellbore is less than the temperature that causes degradation of the fluid. The heat source may be located in the production wellbore or near the production wellbore. In some embodiments, the heat source is a temperature limited heater. In some embodiments, two or more heat sources may supply heat to the volume. Heat from the heat source may reduce the viscosity of crude oil in or near the production wellbore. In some embodiments, heat from the heat source mobilizes fluids in or near the production wellbore and/or enhances the radial flow of fluids to the production wellbore. In some embodiments, reducing the viscosity of crude oil allows or enhances gas lifting of heavy oil (approximately at most 100 API gravity oil) or intermediate gravity oil (approximately 12° to 20° API gravity oil) from the production wellbore. In certain embodiments, the initial API gravity of oil in the formation is at most 100, at most 200, at most 25°, or at most 30°. In certain embodiments, the viscosity of oil in the formation is at least 0.05 Pa·s (50 cp). In some embodiments, the viscosity of oil in the formation is at least 0.10 Pa·s (100 cp), at least 0.15 Pa·s (150 cp), or at least at least 0.20 Pa·s (200 cp). Large amounts of natural gas may have to be utilized to provide gas lift of oil with viscosities above 0.05 Pa·s. Reducing the viscosity of oil at or near the production wellbore in the formation to a viscosity of 0.05 Pa·s (50 cp), 0.03 Pa·s (30 cp), 0.02 Pa·s (20 cp), 0.01 Pa·s (10 cp), or less (down to 0.001 Pa·s (1 cp) or lower) lowers the amount of natural gas needed to lift oil from the formation. In some embodiments, reduced viscosity oil is produced by other methods such as pumping.

The rate of production of oil from the formation may be increased by raising the temperature at or near a production wellbore to reduce the viscosity of the oil in the formation in and adjacent to the production wellbore. In certain embodiments, the rate of production of oil from the formation is increased by 2 times, 3 times, 4 times, or greater up to 20 times over standard cold production, which has no external heating of formation during production. Certain formations may be more economically viable for enhanced oil production using the heating of the near production wellbore region. Formations that have a cold production rate approximately between 0.05 m3/(day per meter of wellbore length) and 0.20 m3/(day per meter of wellbore length) may have significant improvements in production rate using heating to reduce the viscosity in the near production wellbore region. In some formations, production wells up to 775 m, up to 1000 m, or up to 1500 m in length are used. For example, production wells between 450 m and 775 m in length are used, between 550 m and 800 m are used, or between 650 m and 900 m are used. Thus, a significant increase in production is achievable in some formations. Heating the near production wellbore region may be used in formations where the cold production rate is not between 0.05 m3/(day per meter of wellbore length) and 0.20 m3/(day per meter of wellbore length), but heating such formations may not be as economically favorable. Higher cold production rates may not be significantly increased by heating the near wellbore region, while lower production rates may not be increased to an economically useful value.

Using the temperature limited heater to reduce the viscosity of oil at or near the production well inhibits problems associated with non-temperature limited heaters and heating the oil in the formation due to hot spots. One possible problem is that non-temperature limited heaters can causing coking of oil at or near the production well if the heater overheats the oil because the heaters are at too high a temperature. Higher temperatures in the production well may also cause brine to boil in the well, which may lead to scale formation in the well. Non-temperature limited heaters that reach higher temperatures may also cause damage to other wellbore components (for example, screens used for sand control, pumps, or valves). Hot spots may be caused by portions of the formation expanding against or collapsing on the heater. In some embodiments, the heater (either the temperature limited heater or another type of non-temperature limited heater) has sections that are lower because of sagging over long heater distances. These lower sections may sit in heavy oil or bitumen that collects in lower portions of the wellbore. At these lower sections, the heater may develop hot spots due to coking of the heavy oil or bitumen. A standard non-temperature limited heater may overheat at these hot spots, thus producing a non-uniform amount of heat along the length of the heater. Using the temperature limited heater may inhibit overheating of the heater at hot spots or lower sections and provide more uniform heating along the length of the wellbore.

In some embodiments, oil or bitumen cokes in a perforated liner or screen in a heater/production wellbore (for example, coke may form between the heater and the liner or between the liner and the formation). Oil or bitumen may also coke in a toe section of a heel and toe heater/production wellbore, as shown in and described below for FIG. **145**. A temperature limited heater may limit a temperature of a heater/production wellbore below a coking temperature to inhibit coking in the well so that the wellbore does not plug up.

In certain embodiments, fluids in the relatively permeable formation containing heavy hydrocarbons are produced with little or no pyrolyzation of hydrocarbons in the formation. In certain embodiments, the relatively permeable formation containing heavy hydrocarbons is a tar sands formation. For example, the formation may be a tar sands formation such as the Athabasca tar sands formation in Alberta, Canada or a carbonate formation such as the Grosmont carbonate forma-

tion in Alberta, Canada. The fluids produced from the formation are mobilized fluids. Producing mobilized fluids may be more economical than producing pyrolyzed fluids from the tar sands formation. Producing mobilized fluids may also increase the total amount of hydrocarbons produced from the tar sands formation.

FIGS. **130-133** depict side view representations of embodiments for producing mobilized fluids from tar sands formations. In FIGS. **130-133**, heaters **716** have substantially horizontal heating sections in hydrocarbon layer **460** (as shown, the heaters have heating sections that go into and out of the page). FIG. **130** depicts a side view representation of an embodiment for producing mobilized fluids from a tar sands formation with a relatively thin hydrocarbon layer. FIG. **131** depicts a side view representation of an embodiment for producing mobilized fluids from a hydrocarbon layer that is thicker than the hydrocarbon layer depicted in FIG. **130**. FIG. **132** depicts a side view representation of an embodiment for producing mobilized fluids from a hydrocarbon layer that is thicker than the hydrocarbon layer depicted in FIG. **131**. FIG. **133** depicts a side view representation of an embodiment for producing mobilized fluids from a tar sands formation with a hydrocarbon layer that has a shale break.

In FIG. **130**, heaters **716** are placed in an alternating triangular pattern in hydrocarbon layer **460**. In FIGS. **131**, **132**, and **133**, heaters **716** are placed in an alternating triangular pattern in hydrocarbon layer **460** that repeats vertically to encompass a majority or all of the hydrocarbon layer. In FIG. **133**, the alternating triangular pattern of heaters **716** in hydrocarbon layer **460** repeats uninterrupted across shale break **746**. In FIGS. **130-133**, heaters **716** may be equidistantly spaced from each other. In the embodiments depicted in FIGS. **130-133**, the number of vertical rows of heaters **716** depends on factors such as, but not limited to, the desired spacing between the heaters, the thickness of hydrocarbon layer **460**, and/or the number and location of shale breaks **746**. In some embodiments, heaters **716** are arranged in other patterns. For example, heaters **716** may be arranged in patterns such as, but not limited to, hexagonal patterns, square patterns, or rectangular patterns.

In the embodiments depicted in FIGS. **130-133**, heaters **716** provide heat that mobilizes hydrocarbons (reduces the viscosity of the hydrocarbons) in hydrocarbon layer **460**. In certain embodiments, heaters **716** provide heat that reduces the viscosity of the hydrocarbons in hydrocarbon layer **460** below about 0.50 Pa·s (500 cp), below about 0.10 Pa·s (100 cp), or below about 0.05 Pa·s (50 cp). The spacing between heaters **716** and/or the heat output of the heaters may be designed and/or controlled to reduce the viscosity of the hydrocarbons in hydrocarbon layer **460** to desirable values. Heat provided by heaters **716** may be controlled so that little or no pyrolyzation occurs in hydrocarbon layer **460**. Superposition of heat between the heaters may create one or more drainage paths (for example, paths for flow of fluids) between the heaters. In certain embodiments, production wells **206**A and/or production wells **206**B are located proximate heaters **716** so that heat from the heaters superimposes over the production wells. The superimposition of heat from heaters **716** over production wells **206**A and/or production wells **206**B creates one or more drainage paths from the heaters to the production wells. In certain embodiments, one or more of the drainage paths converge. For example, the drainage paths may converge at or near a bottommost heater and/or the drainage paths may converge at or near production wells **206**A and/or production wells **206**B. Fluids mobilized in hydrocarbon layer **460** tend to flow towards the bottommost heaters **716**, production wells **206**A and/or production wells **206**B in the hydrocarbon layer because of gravity and the heat and pressure gradients established by the heaters and/or the production wells. The drainage paths and/or the converged drainage paths allow production wells **206**A and/or production wells **206**B to collect mobilized fluids in hydrocarbon layer **460**.

In certain embodiments, hydrocarbon layer **460** has sufficient permeability to allow mobilized fluids to drain to production wells **206**A and/or production wells **206**B. For example, hydrocarbon layer **460** may have a permeability of at least about 0.1 darcy, at least about 1 darcy, at least about 10 darcy, or at least about 100 darcy. In some embodiments, hydrocarbon layer **460** has a relatively large vertical permeability to horizontal permeability ratio (Kv/Kh). For example, hydrocarbon layer **460** may have a Kv/Kh ratio between about 0.01 and about 2, between about 0.1 and about 1, or between about 0.3 and about 0.7.

In certain embodiments, fluids are produced through production wells **206**A located near heaters **716** in the lower portion of hydrocarbon layer **460**. In some embodiments, fluids are produced through production wells **206**B located below and approximately midway between heaters **716** in the lower portion of hydrocarbon layer **460**. At least a portion of production wells **206**A and/or production wells **206**B may be oriented substantially horizontal in hydrocarbon layer **460** (as shown in FIGS. **130-133**, the production wells have horizontal portions that go into and out of the page). Production wells **206**A and/or **206**B may be located proximate lower portion heaters **716** or the bottommost heaters.

In some embodiments, production wells **206**A are positioned substantially vertically below the bottommost heaters in hydrocarbon layer **460**. Production wells **206**A may be located below heaters **716** at the bottom vertex of a pattern of the heaters (for example, at the bottom vertex of the triangular pattern of heaters depicted in FIGS. **130-133**). Locating production wells **206**A substantially vertically below the bottommost heaters may allow for efficient collection of mobilized fluids from hydrocarbon layer **460**.

In certain embodiments, the bottommost heaters are located between about 2 m and about 10 m from the bottom of hydrocarbon layer **460**, between about 4 m and about 8 m from the bottom of the hydrocarbon layer, or between about 5 m and about 7 m from the bottom of the hydrocarbon layer. In certain embodiments, production wells **206**A and/or production wells **206**B are located at a distance from the bottommost heaters **716** that allows heat from the heaters to superimpose over the production wells but at a distance from the heaters that inhibits coking at the production wells. Production wells **206**A and/or production wells **206**B may be located a distance from the nearest heater (for example, the bottommost heater) of at most ¾ of the spacing between heaters in the pattern of heaters (for example, the triangular pattern of heaters depicted in FIGS. **130-133**). In some embodiments, production wells **206**A and/or production wells **206**B are located a distance from the nearest heater of at most ⅔, at most 12, or at most ⅓ of the spacing between heaters in the pattern of heaters. In certain embodiments, production wells **206**A and/or production wells **206**B are located between about 2 m and about 10 m from the bottommost heaters, between about 4 m and about 8 m from the bottommost heaters, or between about 5 m and about 7 m from the bottommost heaters. Production wells **206**A and/or production wells **206**B may be located between about 0.5 m and about 8 m from the bottom of hydrocarbon layer **460**, between about 1 m and about 5 m from the bottom of the hydrocarbon layer, or between about 2 m and about 4 m from the bottom of the hydrocarbon layer.

In some embodiments, at least some production wells **206**A are located substantially vertically below heaters **716** near shale break **746**, as depicted in FIG. **133**. Production wells **206**A may be located between heaters **716** and shale break **746** to produce fluids that flow and collect above the shale break. Shale break **746** may be an impermeable barrier in hydrocarbon layer **460**. In some embodiments, shale break **746** has a thickness between about 1 m and about 6 m, between about 2 m and about 5 m, or between about 3 m and about 4 m. Production wells **206**A between heaters **716** and shale break **746** may produce fluids from the upper portion of hydrocarbon layer **460** (above the shale break) and production wells **206**A below the bottommost heaters in the hydrocarbon layer may produce fluids from the lower portion of the hydrocarbon layer (below the shale break), as depicted in FIG. **133**. In some embodiments, two or more shale breaks may exist in a hydrocarbon layer. In such an embodiment, production wells are placed at or near each of the shale breaks to produce fluids flowing and collecting above the shale breaks.

In some embodiments, shale break **746** breaks down (is desiccated) as the shale break is heated by heaters **716** on either side of the shale break. As shale break **746** breaks down, the permeability of the shale break increases and the shale break allows fluids to flow through the shale break. Once fluids are able to flow through shale break **746**, production wells above the shale break may not be needed for production as fluids can flow to production wells at or near the bottom of hydrocarbon layer **460** and be produced there.

In certain embodiments, the bottommost heaters above shale break **746** are located between about 2 m and about 10 m from the shale break, between about 4 m and about 8 m from the bottom of the shale break, or between about 5 m and about 7 m from the shale break. Production wells **206**A may be located between about 2 m and about 10 m from the bottommost heaters above shale break **746**, between about 4 m and about 8 m from the bottommost heaters above the shale break, or between about 5 m and about 7 m from the bottommost heaters above the shale break. Production wells **206**A may be located between about 0.5 m and about 8 m from shale break **746**, between about 1 m and about 5 m from the shale break, or between about 2 m and about 4 m from the shale break.

In some embodiments, heat is provided in production wells **206**A and/or production wells **206**B, depicted in FIGS. **130**-**133**. Providing heat in production wells **206**A and/or production wells **206**B may maintain and/or enhance the mobility of the fluids in the production wells. Heat provided in production wells **206**A and/or production wells **206**B may superpose with heat from heaters **716** to create the flow path from the heaters to the production wells. In some embodiments, production wells **206**A and/or production wells **206**B include a pump to remove fluids to the surface of the formation. In some embodiments, the viscosity of fluids (oil) in production wells **206**A and/or production wells **206**B is lowered using heaters and/or diluent injection (for example, using a conduit in the production wells for injecting the diluent).

In certain embodiments, in situ heat treatment of the relatively permeable formation containing hydrocarbons (for example, the tar sands formation) includes heating the formation to visbreaking temperatures. For example, the formation may be heated to temperatures between about 100° C. and 260° C., between about 150° C. and about 250° C., or between about 200° C. and about 240° C. At visbreaking temperatures, fluids in the formation have a reduced viscosity (versus their initial viscosity at initial formation temperature) that allows fluids to flow in the formation. The visbroken fluids may have API gravities that are relatively low (for example, at most about 10°, about 12°, or about 15° API gravity), but the API gravities are higher than the API gravity of non-visbroken fluid from the formation. The non-visbroken fluid from the formation may have an API gravity of 7° or less.

In some embodiments, heaters in the formation are operated at full power output to heat the formation to visbreaking temperatures or higher temperatures. Operating at full power may rapidly increase the pressure in the formation. In certain embodiments, fluids are produced from the formation to maintain a pressure in the formation below a selected pressure as the temperature of the formation increases. In some embodiments, the selected pressure is a fracture pressure of the formation. In certain embodiments, the selected pressure is between about 1000 kPa and about 15000 kPa, between about 2000 kPa and about 10000 kPa, or between about 2500 kPa and about 5000 kPa. The fluids produced from the formation may be visbroken, mobilized fluids, and/or pyrolyzed fluids. Maintaining the pressure as close to the fracture pressure as possible may minimize the number of production wells needed for producing fluids from the formation.

In some embodiments, after the formation reaches visbreaking temperatures, the pressure in the formation is reduced. In certain embodiments, the pressure in the formation is reduced at temperatures above visbreaking temperatures. Reducing the pressure at higher temperatures allows more of the hydrocarbons in the formation to be converted to higher quality hydrocarbons by visbreaking and/or pyrolysis. Allowing the formation to reach higher temperatures before pressure reduction, however, may increase the amount of carbon dioxide produced and/or the amount of coking in the formation. For example, in some formations, coking of bitumen (at pressures above 700 kPa) begins at about 280° C. and reaches a maximum rate at about 340° C. At pressures below about 700 kPa, the coking rate in the formation is minimal. Allowing the formation to reach higher temperatures before pressure reduction may decrease the amount of hydrocarbons produced from the formation.

In certain embodiments, the temperature in the formation (for example, an average temperature of the formation) when the pressure in the formation is reduced is selected to balance one or more factors. The factors considered may include: the quality of hydrocarbons produced, the amount of hydrocarbons produced, the amount of carbon dioxide produced, the amount hydrogen sulfide produced, the degree of coking in the formation, and/or the amount of water produced. Experimental assessments using formation samples and/or simulated assessments based on the formation properties may be used to assess results of treating the formation using the in situ heat treatment process. These results may be used to determine a selected temperature, or temperature range, for when the pressure in the formation is to be reduced. The selected temperature, or temperature range, may also be affected by factors such as, but not limited to, hydrocarbon or oil market conditions and other economic factors. In certain embodiments, the selected temperature is in a range between about 275° C. and about 305° C., between about 280° C. and about 300° C., or between about 285° C. and about 295° C.

In certain embodiments, an average temperature in the formation is assessed from an analysis of fluids produced from the formation. For example, the average temperature of the formation may be assessed from an analysis of the fluids that have been produced to maintain the pressure in the formation below the fracture pressure of the formation.

In some embodiments, values of the hydrocarbon isomer shift in fluids (for example, gases) produced from the forma-

tion is used to indicate the average temperature in the formation. Experimental analysis and/or simulation may be used to assess one or more hydrocarbon isomer shifts and relate the values of the hydrocarbon isomer shifts to the average temperature in the formation. The assessed relation between the hydrocarbon isomer shifts and the average temperature may then be used in the field to assess the average temperature in the formation by monitoring one or more of the hydrocarbon isomer shifts in fluids produced from the formation. In some embodiments, the pressure in the formation is reduced when the monitored hydrocarbon isomer shift reaches a selected value. The selected value of the hydrocarbon isomer shift may be chosen based on the selected temperature, or temperature range, in the formation for reducing the pressure in the formation and the assessed relation between the hydrocarbon isomer shift and the average temperature. Examples of hydrocarbon isomer shifts that may be assessed include, but are not limited to, n-butane-$\delta^{13}C_4$ percentage versus propane-$\delta^{13}C_3$ percentage, n-pentane-$\delta^{13}C_5$ percentage versus propane-$\delta^{13}C_3$ percentage, n-pentane-$\delta^{13}C_5$ percentage versus n-butane-$\delta^{13}C_4$ percentage, and i-pentane-$\delta^{13}C_5$ percentage versus i-butane-$\delta^{13}C_4$ percentage. In some embodiments, the hydrocarbon isomer shift in produced fluids is used to indicate the amount of conversion (for example, amount of pyrolysis) that has taken place in the formation.

In some embodiments, weight percentages of saturates in fluids produced from the formation is used to indicate the average temperature in the formation. Experimental analysis and/or simulation may be used to assess the weight percentage of saturates as a function of the average temperature in the formation. For example, SARA (Saturates, Aromatics, Resins, and Asphaltenes) analysis (sometimes referred to as Asphaltene/Wax/Hydrate Deposition analysis) may be used to assess the weight percentage of saturates in a sample of fluids from the formation. In some formations, the weight percentage of saturates has a linear relationship to the average temperature in the formation. The relation between the weight percentage of saturates and the average temperature may then be used in the field to assess the average temperature in the formation by monitoring the weight percentage of saturates in fluids produced from the formation. In some embodiments, the pressure in the formation is reduced when the monitored weight percentage of saturates reaches a selected value. The selected value of the weight percentage of saturates may be chosen based on the selected temperature, or temperature range, in the formation for reducing the pressure in the formation and the relation between the weight percentage of saturates and the average temperature.

In some embodiments, weight percentages of n-C_7 in fluids produced from the formation is used to indicate the average temperature in the formation. Experimental analysis and/or simulation may be used to assess the weight percentages of n-C_7 as a function of the average temperature in the formation. In some formations, the weight percentages of n-C_7 has a linear relationship to the average temperature in the formation. The relation between the weight percentages of n-C_7 and the average temperature may then be used in the field to assess the average temperature in the formation by monitoring the weight percentages of n-C_7 in fluids produced from the formation. In some embodiments, the pressure in the formation is reduced when the monitored weight percentage of n-C_7 reaches a selected value. The selected value of the weight percentage of n-C_7 may be chosen based on the selected temperature, or temperature range, in the formation for reducing the pressure in the formation and the relation between the weight percentage of n-C_7 and the average temperature.

The pressure in the formation may be reduced by producing fluids (for example, visbroken fluids and/or mobilized fluids) from the formation. In some embodiments, the pressure is reduced below a pressure at which fluids coke in the formation to inhibit coking at pyrolysis temperatures. For example, the pressure is reduced to a pressure below about 1000 kPa, below about 800 kPa, or below about 700 kPa (for example, about 690 kPa). In certain embodiments, the selected pressure is at least about 100 kPa, at least about 200 kPa, or at least about 300 kPa. The pressure may be reduced to inhibit coking of asphaltenes or other high molecular weight hydrocarbons in the formation. In some embodiments, the pressure may be maintained below a pressure at which water passes through a liquid phase at downhole (formation) temperatures to inhibit liquid water and dolomite reactions. After reducing the pressure in the formation, the temperature may be increased to pyrolysis temperatures to begin pyrolyzation and/or upgrading of fluids in the formation. The pyrolyzed and/or upgraded fluids may be produced from the formation.

In certain embodiments, the amount of fluids produced at temperatures below visbreaking temperatures, the amount of fluids produced at visbreaking temperatures, the amount of fluids produced before reducing the pressure in the formation, and/or the amount of upgraded or pyrolyzed fluids produced may be varied to control the quality and amount of fluids produced from the formation and the total recovery of hydrocarbons from the formation. For example, producing more fluid during the early stages of treatment (for example, producing fluids before reducing the pressure in the formation) may increase the total recovery of hydrocarbons from the formation while reducing the overall quality (lowering the overall API gravity) of fluid produced from the formation. The overall quality is reduced because more heavy hydrocarbons are produced by producing more fluids at the lower temperatures. Producing less fluids at the lower temperatures may increase the overall quality of the fluids produced from the formation but may lower the total recovery of hydrocarbons from the formation. The total recovery may be lower because more coking occurs in the formation when less fluids are produced at lower temperatures.

In certain embodiments, the formation is heated using isolated cells of heaters (cells or sections of the formation that are not interconnected for fluid flow). The isolated cells may be created by user larger heater spacings in the formation. For example, large heater spacings may be used in the embodiments depicted in FIGS. **130-133**. These isolated cells may be produced during early stages of heating (for example, at temperatures below visbreaking temperatures). Because the cells are isolated from other cells in the formation, the pressures in the isolated cells are high and more liquids are producible from the isolated cells. Thus, more liquids may be produced from the formation and a higher total recovery of hydrocarbons may be reached. During later stages of heating, the heat gradient may interconnect the isolated cells and pressures in the formation will drop.

In certain embodiments, the heat gradient in the formation is modified so that a gas cap is created at or near an upper portion of the hydrocarbon layer. For example, the heat gradient made by heaters **716** depicted in the embodiments depicted in FIGS. **130-133** may be modified to create the gas cap at or near overburden **458** of hydrocarbon layer **460**. The gas cap may push or drive liquids to the bottom of the hydrocarbon layer so that more liquids may be produced from the formation. In situ generation of the gas cap may be more efficient than introducing pressurized fluid into the formation. The in situ generated gas cap applies force evenly through the

formation with little or no channeling or fingering that may reduce the effectiveness of introduced pressurized fluid.

In certain embodiments, the number and/or location of production wells in the formation is varied based on the viscosity of the formation. More or less production wells may be located in zones of the formation with different viscosities. The viscosities of the zones may be assessed before placing the production wells in the formation, before heating the formation, and/or after heating the formation. In some embodiments, more production wells are located in zones in the formation that have lower viscosities. For example, in certain formations, upper portions, or zones, of the formation may have lower viscosities. Thus, more production wells may be located in the upper zones. Locating production wells in the less viscous zones of the formation allows for better pressure control in the formation and/or producing higher quality (more upgraded) oil from the formation.

In some embodiments, zones in the formation with different assessed viscosities are heated at different rates. In certain embodiments, zones in the formation with higher viscosities are heated at higher heating rates than zones with lower viscosities. Heating the zones with higher viscosities at the higher heating rates mobilizes and/or upgrades these zones at a faster rate so that these zones may "catch up" in viscosity and/or quality to the slower heated zones.

In some embodiments, the heater spacing is varied to provide different heating rates to zones in the formation with different assessed viscosities. For example, denser heater spacings (less spaces between heaters) may be used in zones with higher viscosities to heat these zones at higher heating rates. In some embodiments, a production well (for example, a substantially vertical production well) is located in the zones with denser heater spacings and higher viscosities. The production well may be used to remove fluids from the formation and relieve pressure from the higher viscosity zones. In some embodiments, one or more substantially vertical openings, or production wells, are located in the higher viscosity zones to allow fluids to drain in the higher viscosity zones. The draining fluids may be produced from the formation through production wells located near the bottom of the higher viscosity zones.

In certain embodiments, production wells are located in more than one zone in the formation. The zones may have different initial permeabilities. In certain embodiments, a first zone has an initial permeability of at least about 1 darcy and a second zone has an initial permeability of at most about 0.1 darcy. In some embodiments, the first zone has an initial permeability of between about 1 darcy and about 10 darcy. In some embodiments, the second zone has an initial permeability between about 0.01 darcy and 0.1 darcy. The zones may be separated by a substantially impermeable barrier (with an initial permeability of at most about 10 μdarcy or less). Having the production well located in both zones allows for fluid communication (permeability) between the zones and/or pressure equalization between the zones.

In some embodiments, openings (for example, substantially vertical openings) are formed between zones with different initial permeabilities that are separated by a substantially impermeable barrier. Bridging the zones with the openings allows for fluid communication (permeability) between the zones and/or pressure equalization between the zones. In some embodiments, openings in the formation (such as pressure relief openings and/or production wells) allow gases or low viscosity fluids to rise in the openings. As the gases or low viscosity fluids rise, the fluids may condense or increase viscosity in the openings so that the fluids drain back down the openings to be further upgraded in the formation. Thus, the openings may act as heat pipes by transferring heat from the lower portions to the upper portions where the fluids condense. The wellbores may be packed and sealed near or at the overburden to inhibit transport of formation fluid to the surface.

In some embodiments, production of fluids is continued after reducing and/or turning off heating of the formation. The formation may be heated for a selected time. For example, the formation may be heated until it reaches a selected average temperature. Production from the formation may continue after the selected time. Continuing production may produce more fluid from the formation as fluids drain towards the bottom of the formation and/or fluids is upgraded by passing by hot spots in the formation. In some embodiments, a horizontal production well is located at or near the bottom of the formation (or a zone of the formation) to produce fluids after heating is turned down and/or off.

In certain embodiments, initially produced fluids (for example, fluids produced below visbreaking temperatures), fluids produced at visbreaking temperatures, and/or other viscous fluids produced from the formation are blended with diluent to produce fluids with lower viscosities. In some embodiments, the diluent includes upgraded or pyrolyzed fluids produced from the formation. In some embodiments, the diluent includes upgraded or pyrolyzed fluids produced from another portion of the formation or another formation. In certain embodiments, the amount of fluids produced at temperatures below visbreaking temperatures and/or fluids produced at visbreaking temperatures that are blended with upgraded fluids from the formation is adjusted to create a fluid suitable for transportation and/or use in a refinery. The amount of blending may be adjusted so that the fluid has chemical and physical stability. Maintaining the chemical and physical stability of the fluid may allow the fluid to be transported, reduce pre-treatment processes at a refinery and/or reduce or eliminate the need for adjusting the refinery process to compensate for the fluid.

In certain embodiments, formation conditions (for example, pressure and temperature) and/or fluid production are controlled to produce fluids with selected properties. For example, formation conditions and/or fluid production may be controlled to produce fluids with a selected API gravity and/or a selected viscosity. The selected API gravity and/or selected viscosity may be produced by combining fluids produced at different formation conditions (for example, combining fluids produced at different temperatures during the treatment as described above). As an example, formation conditions and/or fluid production may be controlled to produce fluids with an API gravity of about 19° and a viscosity of about 0.35 Pa·s (350 cp) at 19° C.

In some embodiments, formation conditions and/or fluid production is controlled so that water (for example, connate water) is recondensed in the treatment area. Recondensing water in the treatment area keeps the heat of condensation in the formation. In addition, having liquid water in the formation may increase mobility of liquid hydrocarbons (oil) in the formation. Liquid water may wet rock or other strata in the formation by occupying pores or corners in the strata and creating a slick surface that moves liquid hydrocarbons more readily through the formation.

In certain embodiments, a drive process (for example, a steam injection process such as cyclic steam injection, a steam assisted gravity drainage process (SAGD), a solvent injection process, a vapor solvent and SAGD process, or a carbon dioxide injection process) is used to treat the tar sands formation in addition to the in situ heat treatment process. In some embodiments, heaters are used to create high perme-

ability zones (or injection zones) in the formation for the drive process. Heaters may be used to create a mobilization geometry or production network in the formation to allow fluids to flow through the formation during the drive process. For example, heaters may be used to create drainage paths between the heaters and production wells for the drive process. In some embodiments, the heaters are used to provide heat during the drive process. The amount of heat provided by the heaters may be small compared to the heat input from the drive process (for example, the heat input from steam injection).

In some embodiments, the in situ heat treatment process creates or produces the drive fluid in situ. The in situ produced drive fluid may move through the formation and move mobilized hydrocarbons from one portion of the formation to another portion of the formation.

In some embodiments, the in situ heat treatment process may provide less heat to the formation (for example, use a wider heater spacing) if the in situ heat treatment process is followed by the drive process. The drive process may be used to increase the amount of heat provided to the formation to compensate for the loss of heat injection.

In some embodiments, the drive process is used to treat the formation and produce hydrocarbons from the formation. The drive process may recover a low amount of oil in place from the formation (for example, less than 20% recovery of oil in place from the formation). The in situ heat treatment process may be used following the drive process to increase the recovery of oil in place from the formation. In some embodiments, the drive process preheats the formation for the in situ heat treatment process. In some embodiments, the formation is treated using the in situ heat treatment process a significant time after the formation has been treated using the drive process. For example, the in situ heat treatment process is used 1 year, 2 years, 3 years, or longer after a formation has been treated using the drive process. The in situ heat treatment process may be used on formations that have been left dormant after the drive process treatment because further hydrocarbon production using the drive process is not possible and/or not economically feasible. In some embodiments, the formation remains at least somewhat preheated from the drive process even after the significant time.

In some embodiments, heaters are used to preheat the formation for the drive process. For example, heaters may be used to create injectivity in the formation for a drive fluid. The heaters may create high mobility zones (or injection zones) in the formation for the drive process. In certain embodiments, heaters are used to create injectivity in formations with little or no initial injectivity. Heating the formation may create a mobilization geometry or production network in the formation to allow fluids to flow through the formation for the drive process. For example, heaters may be used to create a fluid production network between a horizontal heater and a vertical production well. The heaters used to preheat the formation for the drive process may also be used to provide heat during the drive process.

FIG. **134** depicts a top view representation of an embodiment for preheating using heaters for the drive process. Injection wells **748** and production wells **206** are substantially vertical wells. Heaters **716** are long substantially horizontal heaters positioned so that the heaters pass in the vicinity of injection wells **748**. Heaters **716** intersect the vertical well patterns slightly displaced from the vertical wells.

The vertical location of heaters **716** with respect to injection wells **748** and production wells **206** depends on, for example, the vertical permeability of the formation. In formations with at least some vertical permeability, injected steam will rise to the top of the permeable layer in the formation. In such formations, heaters **716** may be located near the bottom of hydrocarbon layer **460**, as shown in FIG. **135**. In formations with very low vertical permeabilities, more than one horizontal heater may be used with the heaters stacked substantially vertically or with heaters at varying depths in the hydrocarbon layer (for example, heater patterns as shown in FIGS. **130-133**). The vertical spacing between the horizontal heaters in such formations may correspond to the distance between the heaters and the injection wells. Heaters **716** are located in the vicinity of injection wells **748** and/or production wells **206** so that sufficient energy is delivered by the heaters to provide flow rates for the drive process that are economically viable. The spacing between heaters **716** and injection wells **748** or production wells **206** may be varied to provide an economically viable drive process. The amount of preheating may also be varied to provide an economically viable process.

Some formations with little or no initial injectivity (such as karsted formations or karsted layers in formations) may have tight vugs in one or more layers of the formations. The tight vugs may be vugs filled with viscous fluids such as bitumen or heavy oil. In some embodiments, the vugs have a porosity of at least about 20 porosity units, at least about 30 porosity units, or at least about 35 porosity units. The formation may have a porosity of at most about 15 porosity units, at most about 10 porosity units, or at most about 5 porosity units. The tight vugs inhibit steam or other fluids from being injected into the formation or the layers with tight vugs. In certain embodiments, the karsted formation or karsted layers of the formation are treated using the in situ heat treatment process. Heating of these formations or layers may decrease the viscosity of the fluids in the tight vugs and allow the fluids to drain (for example, mobilize the fluids).

In certain embodiments, only the karsted layers of the formation are treated using the in situ heat treatment process. Other non-karsted layers of the formation may be used as seals for the in situ heat treatment process.

In some embodiments, the drive process is used after the in situ heat treatment of the karsted formation or karsted layers. In some embodiments, heaters are used to preheat the karsted formation or karsted layers to create injectivity in the formation.

In certain embodiments, the karsted formation or karsted layers are heated to temperatures below the decomposition temperature of rock (for example, dolomite) in the formation (for example, temperatures at most about 400° C.). In some embodiments, the karsted formation or karsted layers are heated to temperatures above the decomposition temperature of dolomite in the formation. At temperatures above the dolomite decomposition temperature, the dolomite may decompose to produce carbon dioxide. The decomposition of the dolomite and the carbon dioxide production may create permeability in the formation and mobilize viscous fluids in the formation. In some embodiments, the produced carbon dioxide is maintained in the formation to produce a gas cap in the formation. The carbon dioxide may be allowed to rise to the upper portions of the karsted layers to produce the gas cap.

In some embodiments, heaters are used to produce and/or maintain the gas cap in the formation for the in situ heat treatment process and/or the drive process. The gas cap may drive fluids from upper portions to lower portions of the formation and/or from portions of the formation towards portions of the formation at lower pressures (for example, portions with production wells). In some embodiments, little or no heating is provided in the portions of the formation with the gas cap. In some embodiments, heaters in the gas cap are

turned down and/or off after formation of the gas cap. Using less heating in the gas cap may reduce the energy input into the formation and increase the efficiency of the in situ heat treatment process and/or the drive process. In some embodiments, production wells and/or heater wells that are located in the gas cap portion of the formation may be used for injection of fluid (for example, steam) to maintain the gas cap.

In some embodiments, the production front of the drive process follows behind the heat front of the in situ heat treatment process. In some embodiments, areas behind the production front are further heated to produce more fluids from the formation. Further heating behind the production front may also maintain the gas cap behind the production front and/or maintain quality in the production front of the drive process.

In certain embodiments, the drive process is used before the in situ heat treatment of the formation. In some embodiments, the drive process is used to mobilize fluids in a first section of the formation. The mobilized fluids may then be pushed into a second section by heating the first section with heaters. Fluids may be produced from the second section. In some embodiments, the fluids in the second section are pyrolyzed and/or upgraded using the heaters.

In formations with low permeabilities, the drive process may be used to create a "gas cushion" or pressure sink before the in situ heat treatment process. The gas cushion may inhibit pressures from increasing quickly to fracture pressure during the in situ heat treatment process. The gas cushion may provide a path for gases to escape or travel during early stages of heating during the in situ heat treatment process.

In some embodiments, the drive process (for example, the steam injection process) is used to mobilize fluids before the in situ heat treatment process. Steam injection may be used to get hydrocarbons (oil) away from rock or other strata in the formation. The steam injection may mobilize the oil without significantly heating the rock.

In some embodiments, injection of a fluid (for example, steam or carbon dioxide) may consume heat in the formation and cool the formation depending on the pressure in the formation. In some embodiments, the injected fluid is used to recover heat from the formation. The recovered heat may be used in surface processing of fluids and/or to preheat other portions of the formation using the drive process.

FIG. **136** depicts a representation of an embodiment for producing hydrocarbons from a hydrocarbon containing formation (for example, a tar sands formation). Hydrocarbon layer **460** includes one or more portions with heavy hydrocarbons. Hydrocarbons may be produced from hydrocarbon layer **460** using more than one process. In certain embodiments, hydrocarbons are produced from a first portion of hydrocarbon layer **460** using a steam injection process (for example, cyclic steam injection or steam-assisted gravity drainage) and a second portion of the hydrocarbon layer using an in situ heat treatment process. In the steam injection process, steam is injected into the first portion of hydrocarbon layer **460** through injection well **748**. First hydrocarbons are produced from the first portion through production well **206**A. The first hydrocarbons include hydrocarbons mobilized by the injection of steam. In certain embodiments, the first hydrocarbons have an API gravity of at most 15°, at most 10°, at most 8°, or at most 6°.

Heaters **716** are used to heat the second portion of hydrocarbon layer **460** to mobilization, visbreaking, and/or pyrolysis temperatures. Second hydrocarbons are produced from the second portion through production well **206**B. In some embodiments, the second hydrocarbons include at least some pyrolyzed hydrocarbons. In certain embodiments, the second hydrocarbons have an API gravity of at least 15°, at least 20°, or at least 25°.

In some embodiments, the first portion of hydrocarbon layer **460** is treated using heaters after the steam injection process. Heaters may be used to increase the temperature of the first portion and/or treat the first portion using an in situ heat treatment process. Second hydrocarbons (including at least some pyrolyzed hydrocarbons) may be produced from the first portion through production well **206**A.

In some embodiments, the second portion of hydrocarbon layer **460** is treated using the steam injection process before using heaters **716** to treat the second portion. The steam injection process may be used to produce some fluids (for example, first hydrocarbons or hydrocarbons mobilized by the steam injection) through production well **206**B from the second portion and/or preheat the second portion before using heaters **716**. In some embodiments, the steam injection process may be used after using heaters **716** to treat the first portion and/or the second portion.

Producing hydrocarbons through both processes increases the total recovery of hydrocarbons from hydrocarbon layer **460** and may be more economical than using either process alone. In some embodiments, the first portion is treated with the in situ heat treatment process after the steam injection process is completed. For example, after the steam injection process no longer produces viable amounts of hydrocarbon from the first portion, the in situ heat treatment process may be used on the first portion.

Steam is provided to injection well **748** from facility **750**. Facility **750** is a steam and electricity cogeneration facility. Facility **750** may burn hydrocarbons in generators to make electricity. Facility **750** may burn gaseous and/or liquid hydrocarbons to make electricity. The electricity generated is used to provide electrical power for heaters **716**. Waste heat from the generators is used to make steam. In some embodiments, some of the hydrocarbons produced from the formation are used to provide gas for heaters **716**, if the heaters utilize gas to provide heat to the formation. The amount of electricity and steam generated by facility **750** may be controlled to vary the production rate and/or quality of hydrocarbons produced from the first portion and/or the second portion of hydrocarbon layer **460**. The production rate and/or quality of hydrocarbons produced from the first portion and/or the second portion may be varied to produce a selected API gravity in a mixture made by blending the first hydrocarbons with the second hydrocarbons. The first hydrocarbon and the second hydrocarbons may be blended after production to produce the selected API gravity. The production from the first portion and/or the second portion may be varied in response to changes in the marketplace for either first hydrocarbons, second hydrocarbons, and/or a mixture of the first and second hydrocarbons.

First hydrocarbons produced from production well **206**A and/or second hydrocarbons produced from production well **206**B may be used as fuel for facility **750**. In some embodiments, first hydrocarbons and/or second hydrocarbons are treated (for example, removing undesirable products) before being used as fuel for facility **750**. The amount of first hydrocarbons and second hydrocarbons used as fuel for facility **750** may be determined, for example, by economics for the overall process, the marketplace for either first or second hydrocarbons, availability of treatment facilities for either first or second hydrocarbons, and/or transportation facilities available for either first or second hydrocarbons. In some embodiments, most or all the hydrocarbon gas produced from hydrocarbon layer **460** is used as fuel for facility **750**. Burning all

the hydrocarbon gas in facility **750** eliminates the need for treatment and/or transportation of gases produced from hydrocarbon layer **460**.

The produced first hydrocarbons and the second hydrocarbons may be treated and/or blended in facility **752**. In some embodiments, the first and second hydrocarbons are blended to make a mixture that is transportable through a pipeline. In some embodiments, the first and second hydrocarbons are blended to make a mixture that is useable as a feedstock for a refinery. The amount of first and second hydrocarbons produced may be varied based on changes in the requirements for treatment and/or blending of the hydrocarbons. In some embodiments, treated hydrocarbons are used in facility **750**.

In some embodiments, the steam injection process and the in situ heat treatment process (for example, the in situ conversion process) are used synergistically in different layers (for example, vertically displaced layers) in the formation. For example, in a karsted formation, different zones or layers in the formation may have different oil saturations, water saturations, porosities, and/or permeabilities. Some layers may have good steam injectivities while others have near zero steam injectivity. The steam injectivity may depend on the water saturation of the zone and the permeability. Thus, varying the use of the steam injection process and the in situ heat treatment process in these layers may be economically advantageous by, for example, producing more hydrocarbons with less energy input into the formation. The steam injection process may include steam drive, cyclic steam injection, SAGD, or other process of steam injection into the formation.

FIG. **137** depicts a representation of an embodiment for producing hydrocarbons from multiple layers in a tar sands formation. Hydrocarbon layers **460**A,B,C include one or more portions with heavy hydrocarbons. Hydrocarbon layers **460**A,B,C may have different oil saturations, water saturations, porosities, and/or permeabilities. In one embodiment, hydrocarbon layers **460**A,C have lower oil saturations, higher water saturations, and lower porosities than hydrocarbon layer **460**B. The steam injection process may be used in hydrocarbon layers **460**A,C using injection wells **748**A,C and production wells **206**A,C. The in situ heat treatment process may be used in hydrocarbon layer **460**B using heaters **716** and production well **206**B. In some embodiments, the in situ heat treatment process is used in hydrocarbon layer **460**B, which has high oil saturation and low steam injectivity. After the in situ heat treatment of hydrocarbon layer **460**B, the layer may have steam injectivity and be treated using the steam injection process.

Injecting steam into hydrocarbon layers **460**A,C above and below hydrocarbon layer **460**B may increase the efficiency of producing hydrocarbons from the formation. Steam injection in hydrocarbon layers **460**A,C lowers the viscosity and increases the pressures in these layers so that hydrocarbons move into hydrocarbon layer **460**B. Heat from hydrocarbon layer **460**B may conduct and/or convect into hydrocarbon layers **460**A,C and preheat these layers to lower the oil viscosity and/or increase the steam injectivity in hydrocarbon layers **460**A,C. Additionally, some steam may rise from hydrocarbon layer **460**C into hydrocarbon layer **460**B. This steam may provide additional heat and increased mobilization in hydrocarbon layer **460**B. The steam injection process and/or the in situ heat treatment process may be used (for example, varied) as described above for the embodiment depicted in FIG. **136**. Hydrocarbons produced from any of hydrocarbon layers **460**A,B,C may be used and/or processed in facility **750** and/or facility **752**, as described above for the embodiment depicted in FIG. **136**.

In some embodiments, impermeable shale layers exist between hydrocarbon layer **460**B and hydrocarbon layers **460**A,C. Using the in situ heat treatment process on hydrocarbon layer **460**B may desiccate the shale layers and increase the permeability of the shale layers to allow fluid flux through the shale layers. This increased permeability in the shale layers allows mobilized hydrocarbons to flow from hydrocarbon layer **460**A into hydrocarbon layer **460**B. These hydrocarbons may be upgraded and produced in hydrocarbon layer **460**B.

FIG. **138** depicts an embodiment for heating and producing from the formation with the temperature limited heater in a production wellbore. Production conduit **754** is located in wellbore **756**. In certain embodiments, a portion of wellbore **756** is located substantially horizontally in formation **758**. In some embodiments, the wellbore is located substantially vertically in the formation. In an embodiment, wellbore **756** is an open wellbore (an uncased wellbore). In some embodiments, the wellbore has a casing or liner with perforations or openings to allow fluid to flow into the wellbore.

Conduit **754** may be made from carbon steel or more corrosion resistant materials such as stainless steel. Conduit **754** may include apparatus and mechanisms for gas lifting or pumping produced oil to the surface. For example, conduit **754** includes gas lift valves used in a gas lift process. Examples of gas lift control systems and valves are disclosed in U.S. Pat. No. 6,715,550 to Vinegar et al. and U.S. Patent Application Publication Nos. 2002-0036085 to Bass et al. and 2003-0038734 to Hirsch et al., each of which is incorporated by reference as if fully set forth herein. Conduit **754** may include one or more openings (perforations) to allow fluid to flow into the production conduit. In certain embodiments, the openings in conduit **754** are in a portion of the conduit that remains below the liquid level in wellbore **756**. For example, the openings are in a horizontal portion of conduit **754**.

Heater **760** is located in conduit **754**, as shown in FIG. **138**. In some embodiments, heater **760** is located outside conduit **754**, as shown in FIG. **139**. The heater located outside the production conduit may be coupled (strapped) to the production conduit. In some embodiments, more than one heater (for example, two, three, or four heaters) are placed about conduit **754**. The use of more than one heater may reduce bowing or flexing of the production conduit caused by heating on only one side of the production conduit. In an embodiment, heater **760** is a temperature limited heater. Heater **760** provides heat to reduce the viscosity of fluid (such as oil or hydrocarbons) in and near wellbore **756**. In certain embodiments, heater **760** raises the temperature of the fluid in wellbore **756** up to a temperature of 250° C. or less (for example, 225° C., 200° C., or 150° C.). Heater **760** may be at higher temperatures (for example, 275° C., 300° C., or 325° C.) because the heater provides heat to conduit **754** and there is some temperature differential between the heater and the conduit. Thus, heat produced from the heater does not raise the temperature of fluids in the wellbore above 250° C.

In certain embodiments, heater **760** includes ferromagnetic materials such as Carpenter Temperature Compensator "32", Alloy 42-6, Alloy 52, Invar 36, or other iron-nickel or iron-nickel-chromium alloys. In certain embodiments, nickel or nickel-chromium alloys are used in heater **760**. In some embodiments, heater **760** includes a composite conductor with a more highly conductive material such as copper on the inside of the heater to improve the turndown ratio of the heater. Heat from heater **760** heats fluids in or near wellbore **756** to reduce the viscosity of the fluids and increase a production rate through conduit **754**.

In certain embodiments, portions of heater **760** above the liquid level in wellbore **756** (such as the vertical portion of the wellbore depicted in FIGS. **138** and **139**) have a lower maximum temperature than portions of the heater located below the liquid level. For example, portions of heater **760** above the liquid level in wellbore **756** may have a maximum temperature of 100° C. while portions of the heater located below the liquid level have a maximum temperature of 250° C. In certain embodiments, such a heater includes two or more ferromagnetic sections with different Curie temperatures and/or phase transformation temperature ranges to achieve the desired heating pattern. Providing less heat to portions of wellbore **756** above the liquid level and closer to the surface may save energy.

In certain embodiments, heater **760** is electrically isolated on the heater's outside surface and allowed to move freely in conduit **754**. In some embodiments, electrically insulating centralizers are placed on the outside of heater **760** to maintain a gap between conduit **754** and the heater.

In some embodiments, heater **760** is cycled (turned on and off) so that fluids produced through conduit **754** are not overheated. In an embodiment, heater **760** is turned on for a specified amount of time until a temperature of fluids in or near wellbore **756** reaches a desired temperature (for example, the maximum temperature of the heater). During the heating time (for example, 10 days, 20 days, or 30 days), production through conduit **754** may be stopped to allow fluids in the formation to "soak" and obtain a reduced viscosity. After heating is turned off or reduced, production through conduit **754** is started and fluids from the formation are produced without excess heat being provided to the fluids. During production, fluids in or near wellbore **756** will cool down without heat from heater **760** being provided. When the fluids reach a temperature at which production significantly slows down, production is stopped and heater **760** is turned back on to reheat the fluids. This process may be repeated until a desired amount of production is reached. In some embodiments, some heat at a lower temperature is provided to maintain a flow of the produced fluids. For example, low temperature heat (for example, 100° C., 125° C., or 150° C.) may be provided in the upper portions of wellbore **756** to keep fluids from cooling to a lower temperature.

FIG. **140** depicts an embodiment of a heating/production assembly that may be located in a wellbore for gas lifting. Heating/production assembly **762** may be located in a wellbore in the formation (for example, wellbore **756** depicted in FIG. **138** or **139**). Conduit **754** is located inside casing **530**. In an embodiment, conduit **754** is coiled tubing such as 6 cm diameter coiled tubing. Casing **530** has a diameter between 10 cm and 25 cm (for example, a diameter of 14 cm, 16 cm, or 18 cm). Heater **760** is coupled to an end of conduit **754**. In some embodiments, heater **760** is located inside conduit **754**. In some embodiments, heater **760** is a resistive portion of conduit **754**. In some embodiments, heater **760** is coupled to a length of conduit **754**.

Opening **764** is located at or near a junction of heater **760** and conduit **754**. In some embodiments, opening **764** is a slot or a slit in conduit **754**. In some embodiments, opening **764** includes more than one opening in conduit **754**. Opening **764** allows production fluids to flow into conduit **754** from a wellbore. Perforated casing **766** allows fluids to flow into the heating/production assembly **762**. In certain embodiments, perforated casing **766** is a wire wrapped screen. In one embodiment, perforated casing **766** is a 9 cm diameter wire wrapped screen.

Perforated casing **766** may be coupled to casing **530** with packing material **532**. Packing material **532** inhibits fluids from flowing into casing **530** from outside perforated casing **766**. Packing material **532** may also be placed inside casing **530** to inhibit fluids from flowing up the annulus between the casing and conduit **754**. Seal assembly **768** is used to seal conduit **754** to packing material **532**. Seal assembly **768** may fix a position of conduit **754** along a length of a wellbore. In some embodiments, seal assembly **768** allows for unsealing of conduit **754** so that the production conduit and heater **760** may be removed from the wellbore.

Feedthrough **770** is used to pass lead-in cable **636** to supply power to heater **760**. Lead-in cable **636** may be secured to conduit **754** with clamp **772**. In some embodiments, lead-in cable **636** passes through packing material **532** using a separate feedthrough.

A lifting gas (for example, natural gas, methane, carbon dioxide, propane, and/or nitrogen) may be provided to the annulus between conduit **754** and casing **530**. Valves **774** are located along a length of conduit **754** to allow gas to enter the production conduit and provide for gas lifting of fluids in the production conduit. The lifting gas may mix with fluids in conduit **754** to lower the density of the fluids and allow for gas lifting of the fluids out of the formation. In certain embodiments, valves **774** are located in or near the overburden section of the formation so that gas lifting is provided in the overburden section. In some embodiments, fluids are produced through the annulus between conduit **754** and casing **530** and the lifting gas is supplied through valves **774**.

In an embodiment, fluids are produced using a pump coupled to conduit **754**. The pump may be a submersible pump (for example, an electric or gas powered submersible pump). In some embodiments, a heater is coupled to conduit **754** to maintain the reduced viscosity of fluids in the conduit and/or the pump.

In certain embodiments, an additional conduit such as an additional coiled tubing conduit is placed in the formation. Sensors may be placed in the additional conduit. For example, a production logging tool may be placed in the additional conduit to identify locations of producing zones and/or to assess flow rates. In some embodiments, a temperature sensor (for example, a distributed temperature sensor, a fiber optic sensor, and/or an array of thermocouples) is placed in the additional conduit to determine a subsurface temperature profile.

Some embodiments of the heating/production assembly are used in a well that preexists (for example, the heating/production assembly is retrofitted for a preexisting production well, heater well, or monitoring well). An example of the heating/production assembly that may be used in the preexisting well is depicted in FIG. **141**. Some preexisting wells include a pump. The pump in the preexisting well may be left in the heating/production well retrofitted with the heating/production assembly.

FIG. **141** depicts an embodiment of the heating/production assembly that may be located in the wellbore for gas lifting. In FIG. **141**, conduit **754** is located in outside production conduit **776**. In an embodiment, outside production conduit **776** is 11.4 cm diameter production tubing. Casing **530** has a diameter of 24.4 cm. Perforated casing **766** has a diameter of 11.4 cm. Seal assembly **768** seals conduit **754** inside outside production conduit **776**. In an embodiment, pump **778** is a jet pump such as a bottomhole assembly jet pump.

FIG. **142** depicts another embodiment of a heating/production assembly that may be located in a wellbore for gas lifting. Heater **760** is located inside perforated casing **766**. Heater **760** is coupled to lead-in cable **636** through a feedthrough in packing material **532**. Production conduit **754** extends through packing material **532**. Pump **778** is located along

conduit **754**. In certain embodiments, pump **778** is a jet pump or a bean pump. Valves **774** are located along conduit **754** for supplying lift gas to the conduit.

In some embodiments, heat is inhibited from transferring into conduit **754**. FIG. **143** depicts an embodiment of conduit **754** and heaters **760** that inhibit heat transfer into the conduit. Heaters **760** are coupled to conduit **754**. Heaters **760** include ferromagnetic sections **486** and non-ferromagnetic sections **488**. Ferromagnetic sections **486** provide heat at a temperature that reduces the viscosity of fluids in or near a wellbore. Non-ferromagnetic sections **488** provide little or no heat. In certain embodiments, ferromagnetic sections **486** and non-ferromagnetic sections **488** are 6 m in length. In some embodiments, ferromagnetic sections **486** and non-ferromagnetic sections **488** are between 3 m and 12 m in length, between 4 m and 11 m in length, or between 5 m and 10 m in length. In certain embodiments, non-ferromagnetic sections **488** include perforations **780** to allow fluids to flow to conduit **754**. In some embodiments, heater **760** is positioned so that perforations are not needed to allow fluids to flow to conduit **754**.

Conduit **754** may have perforations **780** to allow fluid to enter the conduit. Perforations 780 coincide with non-ferromagnetic sections **488** of heater **760**. Sections of conduit **754** that coincide with ferromagnetic sections **486** include insulation conduit **782**. Conduit **782** may be a vacuum insulated tubular. For example, conduit **782** may be a vacuum insulated production tubular available from Oil Tech Services, Inc. (Houston, Tex., U.S.A.). Conduit **782** inhibits heat transfer into conduit **754** from ferromagnetic sections **486**. Limiting the heat transfer into conduit **754** reduces heat loss and/or inhibits overheating of fluids in the conduit. In an embodiment, heater **760** provides heat along an entire length of the heater and conduit **754** includes conduit **782** along an entire length of the production conduit.

In certain embodiments, more than one wellbore **756** is used to produce heavy oils from a formation using the temperature limited heater. FIG. **144** depicts an end view of an embodiment with wellbores **756** located in hydrocarbon layer **460**. Portions of wellbores **756** are placed substantially horizontally in a triangular pattern in hydrocarbon layer **460**. In certain embodiments, wellbores **756** have a spacing of 30 m to 60 m, 35 m to 55 m, or 40 m to 50 m. Wellbores **756** may include production conduits and heaters previously described. Fluids may be heated and produced through wellbores **756** at an increased production rate above a cold production rate for the formation. Production may continue for a selected time (for example, 5 years to 10 years, 6 years to 9 years, or 7 years to 8 years) until heat produced from each of wellbores **756** begins to overlap (superposition of heat begins). At such a time, heat from lower wellbores (such as wellbores **756** near the bottom of hydrocarbon layer **460**) is continued, reduced, or turned off while production is continued. Production in upper wellbores (such as wellbores **756** near the top of hydrocarbon layer **460**) may be stopped so that fluids in the hydrocarbon layer drain towards the lower wellbores. In some embodiments, power is increased to the upper wellbores and the temperature raised above the Curie temperature and/or the phase transformation temperature range to increase the heat injection rate. Draining fluids in the formation in such a process increases total hydrocarbon recovery from the formation.

In an embodiment, a temperature limited heater is used in a horizontal heater/production well. The temperature limited heater may provide selected amounts of heat to the "toe" and the "heel" of the horizontal portion of the well. More heat may be provided to the formation through the toe than through the heel, creating a "hot portion" at the toe and a "warm portion" at the heel. Formation fluids may be formed in the hot portion and produced through the warm portion, as shown in FIG. **145**.

FIG. **145** depicts an embodiment of a heater well for selectively heating a formation. Heat source **202** is placed in opening **522** in hydrocarbon layer **460**. In certain embodiments, opening **522** is a substantially horizontal opening in hydrocarbon layer **460**. Perforated casing **766** is placed in opening **522**. Perforated casing **766** provides support that inhibits hydrocarbon and/or other material in hydrocarbon layer **460** from collapsing into opening **522**. Perforations in perforated casing **766** allow for fluid flow from hydrocarbon layer **460** into opening **522**. Heat source **202** may include hot portion **784**. Hot portion **784** is a portion of heat source **202** that operates at higher heat output than adjacent portions of the heat source. For example, hot portion **784** may output between 650 W/m and 1650 W/m, 650 W/m and 1500 W/m, or 800 W/m and 1500 W/m. Hot portion **784** may extend from a "heel" of the heat source to the "toe" of the heat source. The heel of the heat source is the portion of the heat source closest to the point at which the heat source enters a hydrocarbon layer. The toe of the heat source is the end of the heat source furthest from the entry of the heat source into the hydrocarbon layer.

In an embodiment, heat source **202** includes warm portion **786**. Warm portion **786** is a portion of heat source **202** that operates at lower heat outputs than hot portion **784**. For example, warm portion **786** may output between 30 W/m and 1000 W/m, 30 W/m and 750 W/m, or 100 W/m and 750 W/m. Warm portion **786** may be located closer to the heel of heat source **202**. In certain embodiments, warm portion **786** is a transition portion (for example, a transition conductor) between hot portion **784** and overburden portion **788**. Overburden portion **788** is located in overburden **458**. Overburden portion **788** provides a lower heat output than warm portion **786**. For example, overburden portion **788** may output between 10 W/m and 90 W/m, 15 W/m and 80 W/m, or 25 W/m and 75 W/m. In some embodiments, overburden portion **788** provides as close to no heat (0 W/m) as possible to overburden **458**. Some heat, however, may be used to maintain fluids produced through opening **522** in a vapor phase or at elevated temperature in overburden **458**.

In certain embodiments, hot portion **784** of heat source **202** heats hydrocarbons to high enough temperatures to result in coke **790** forming in hydrocarbon layer **460**. Coke **790** may occur in an area surrounding opening **522**. Warm portion **786** may be operated at lower heat outputs so that coke does not form at or near the warm portion of heat source **202**. Coke **790** may extend radially from opening **522** as heat from heat source **202** transfers outward from the opening. At a certain distance, however, coke **790** no longer forms because temperatures in hydrocarbon layer **460** at the certain distance will not reach coking temperatures. The distance at which no coke forms is a function of heat output (W/m from heat source **202**), type of formation, hydrocarbon content in the formation, and/or other conditions in the formation.

The formation of coke **790** inhibits fluid flow into opening **522** through the coking. Fluids in the formation may, however, be produced through opening **522** at the heel of heat source **202** (for example, at warm portion **786** of the heat source) where there is little or no coke formation. The lower temperatures at the heel of heat source **202** reduce the possibility of increased cracking of formation fluids produced through the heel. Fluids may flow in a horizontal direction through the formation more easily than in a vertical direction. Typically, horizontal permeability in a relatively permeable

formation is approximately 5 to 10 times greater than vertical permeability. Thus, fluids flow along the length of heat source **202** in a substantially horizontal direction. Producing formation fluids through opening **522** is possible at earlier times than producing fluids through production wells in hydrocarbon layer **460**. The earlier production times through opening **522** is possible because temperatures near the opening increase faster than temperatures further away due to conduction of heat from heat source **202** through hydrocarbon layer **460**. Early production of formation fluids may be used to maintain lower pressures in hydrocarbon layer **460** during start-up heating of the formation. Start-up heating of the formation is the time of heating before production begins at production wells in the formation. Lower pressures in the formation may increase liquid production from the formation. In addition, producing formation fluids through opening **522** may reduce the number of production wells needed in the formation.

In some embodiments, a temperature limited heater positioned in a wellbore heats steam that is provided to the wellbore. The heated steam may be introduced into a portion of the formation. In certain embodiments, the heated steam may be used as a heat transfer fluid to heat a portion of the formation. In some embodiments, the steam is used to solution mine desired minerals from the formation. In some embodiments, the temperature limited heater positioned in the wellbore heats liquid water that is introduced into a portion of the formation.

In an embodiment, the temperature limited heater includes ferromagnetic material with a selected Curie temperature and/or a selected phase transformation temperature range. The use of a temperature limited heater may inhibit a temperature of the heater from increasing beyond a maximum selected temperature (for example, at or about the Curie temperature and/or the phase transformation temperature range). Limiting the temperature of the heater may inhibit potential burnout of the heater. The maximum selected temperature may be a temperature selected to heat the steam to above or near 100% saturation conditions, superheated conditions, or supercritical conditions. Using a temperature limited heater to heat the steam may inhibit overheating of the steam in the wellbore. Steam introduced into a formation may be used for synthesis gas production, to heat the hydrocarbon containing formation, to carry chemicals into the formation, to extract chemicals or minerals from the formation, and/or to control heating of the formation.

A portion of the formation where steam is introduced or that is heated with steam may be at significant depths below the surface (for example, greater than about 1000 m, about 250°, or about 5000 m below the surface). If steam is heated at the surface of the formation and introduced to the formation through a wellbore, a quality of the heated steam provided to the wellbore at the surface may have to be relatively high to accommodate heat losses to the wellbore casing and/or the overburden as the steam travels down the wellbore. Heating the steam in the wellbore may allow the quality of the steam to be significantly improved before the steam is provided to the formation. A temperature limited heater positioned in a lower section of the overburden and/or adjacent to a target zone of the formation may be used to controllably heat steam to improve the quality of the steam injected into the formation and/or inhibit condensation along the length of the heater. In certain embodiments, the temperature limited heater improves the quality of the steam injected and/or inhibits condensation in the wellbore for long steam injection wellbores (especially for long horizontal steam injection wellbores).

A temperature limited heater positioned in a wellbore may be used to heat the steam to above or near 100% saturation conditions or superheated conditions. In some embodiments, a temperature limited heater may heat the steam so that the steam is above or near supercritical conditions. The static head of fluid above the temperature limited heater may facilitate producing 100% saturation, superheated, and/or supercritical conditions in the steam. Supercritical or near supercritical steam may be used to strip hydrocarbon material and/or other materials from the formation. In certain embodiments, steam introduced into the formation may have a high density (for example, a specific gravity of about 0.8 or above). Increasing the density of the steam may improve the ability of the steam to strip hydrocarbon material and/or other materials from the formation.

In some embodiments, the tar sands formation may be treated by the in situ heat treatment process to produce pyrolyzed product from the formation. A significant amount of carbon in the form of coke may remain in tar sands formation when production of pyrolysis product from the formation is complete. In some embodiments, the coke in the formation may be utilized to produce heat and/or additional products from the heated coke containing portions of the formation.

In some embodiments, air, oxygen enriched air, and/or other oxidants may be introduced into the treatment area that has been pyrolyzed to react with the coke in the treatment area. The temperature of the treatment area may be sufficiently hot to support burning of the coke without additional energy input from heaters. The oxidation of the coke may significantly heat the portion of the formation. Some of the heat may transfer to portions of the formation adjacent to the treatment area. The transferred heat may mobilize fluids in portions of the formation adjacent to the treatment area. The mobilized fluids may flow into and be produced from production wells near the perimeter of the treatment area.

Gases produced from the formation heated by combusting coke in the formation may be at high temperature. The hot gases may be utilized in an energy recovery cycle (for example, a Kalina cycle or a Rankine cycle) to produce electricity.

The air, oxygen enriched air and/or other oxidants may be introduced into the formation for a sufficiently long period of time to heat a portion of the treatment area to a desired temperature sufficient to allow for the production of synthesis gas of a desired composition. The temperature may be from 500° C. to about 1000° C. or higher. When the temperature of the portion is at or near the desired temperature, a synthesis gas generating fluid, such as water, may be introduced into the formation to result in the formation of synthesis gas. Synthesis gas produced from the formation may be sent to a treatment facility and/or be sent through a pipeline to a desired location. During introduction of the synthesis gas generating fluid, the introduction of air, oxygen enriched air, and/or other oxidants may be stopped, reduced, or maintained. If the temperature of the formation reduces so that the synthesis gas produced from the formation does not have the desired composition, introduction of the syntheses gas generating fluid may be stopped or reduced, and the introduction of air, enriched air and/or other oxidants may be started or increased so that oxidation of coke in the formation reheats portions of the treatment area. The introduction of oxidant to heat the formation and the introduction of synthesis gas generating fluid to produce synthesis gas may be cycled until all or a significant portion of the treatment area is treated.

In some embodiments, temperature limited heaters are manufactured from austenitic stainless steels. These austenitic steels may include alloys with a face centered cubic (fcc)

austenite phase being the primary phase. The fcc austenite phase may be stabilized by controlling the Fe—Cr—Ni and/or the $Fe_{18}Cr_8$—Ni concentration. Strength of the austenitic phase may be increased by incorporating other alloys in the fcc lattice. For low-temperature applications, the strength may be raised by adding alloying elements that increase the strength of the fcc lattice. This type of strengthening may be referred to as "solid solution strengthening". As the use temperature is increased, however, alloying elements in the austenite phase may react to form new phases such as $M_{23}C_6$, where M includes chromium and other elements that can form carbides. Other phases may form in austenite containing elements from Columns 4-13 of the Periodic Table. Examples of such elements include, but are not limited to, niobium, titanium, vanadium, tungsten, aluminum, or mixtures thereof. The size and distribution of various phases and their stability in the desired use temperature range determines the mechanical properties of the stainless steel. Nano-scale dispersions of precipitates such as carbides may produce the highest strength at high temperatures, but due to the size of the carbides, they may become unstable and coarsen. Alloys containing nano-scale precipitate dispersions may be unstable at temperatures of at least 750° C. Since, heaters may heat a subsurface formation to temperatures at least 700° C., heaters having improved strength alloys capable of withstanding temperatures of at least 700° C. are desired.

In some embodiments, iron, chromium, and nickel alloys containing manganese, copper and tungsten, in combination with niobium, carbon and nitrogen, may maintain a finer grain size despite high temperature solution annealing or processing. Such behavior may be beneficial in reducing a heat-affected-zone in welded material. Higher solution-annealing temperatures are particularly important for achieving the best metal carbide (MC) nanocarbide. For example, niobium carbide nanocarbide strengthens during high-temperature creep service, and such effects are amplified (finer nanocarbide structures that are stable) by compositions of the improved alloys. Tubing and canister applications that include the composition of the improved alloys and are wrought processed result in stainless steels that may be able to age-harden during service at 700° C. to 800° C. Improved alloys may be able to age-harden even more if the alloys are cold-strained prior to high-temperature service, but such cold-prestraining is not necessary for good high temperature properties or age-hardening. Some prior art alloys, such as NF709 require cold-prestraining to achieve good high temperature creep properties, and this is a disadvantage in particular because after such alloys are welded, the advantages of the cold-prestraining in the weld heat effected zone are lost. Other prior art alloys are adversely effected by cold-prestraining with respect to high-temperature strength and long-term durability. Thus, cold prestraining may be limited or not permitted by, for example, construction codes.

In some embodiments of the new alloy compositions, the alloy may be cold worked by, for example, twenty percent, and the yield strength at 800° C. is not changed by more than twenty percent from yield strength at 800° C. of freshly annealed alloy.

The improved alloys described herein are suitable for low temperature applications, for example, cryogenic applications. The improved alloys which have strength and sufficient ductility at temperatures of, for example, −50° C. to −200° C., also retain strength at higher temperatures than many alloys often used in cryogenic applications, such as 201LN and YUS130, thus for services such as liquefied natural gas, where a failure may result in a fire, the improved alloy would retain strength in the vicinity of the fire longer than other materials.

An improved alloy composition may include, by weight: about 18% to about 22% chromium, about 5% to about 13% nickel (and in some embodiments, from about 5% to about 9% by weight nickel), about 1% to about 10% copper (and in some embodiments, above 2% to about 6% copper), about 1% to about 10% manganese, about 0.3% to about 1% silicon, about 0.5% to about 1.5% niobium, about 0.5% to about 2% tungsten, and with the balance being essentially iron (for example, about 47.8% to about 68.12% iron). The composition may, in some embodiments, include other components, for example, about 0.3% to about 1% molybdenum, about 0.08% to about 0.2% carbon, about 0.2% to about 0.5% nitrogen or mixtures thereof. Other impurities or minor components typically present in steels may also be present. Such an improved alloy may be useful when processed by hot deformation, cold deformation, and/or welding into, for example, casings, canisters, or strength members for heaters. In some embodiments, the improved alloy includes, by weight: about 20% chromium, about 3% copper, about 4% manganese, about 0.3% molybdenum, about 0.77% niobium, about 13% nickel, about 0.5% silicon, about 1% tungsten, about 0.09% carbon, and about 0.26% nitrogen, with the balance being essentially iron. In certain embodiments, the improved alloy includes, by weight: about 19% chromium, about 4.2% manganese, about 0.3% molybdenum, about 0.8% niobium, about 12.5% nickel, about 0.5% silicon, about 0.09% carbon, about 0.24% nitrogen by weight with the balance being essentially iron. In certain embodiments, the improved alloy includes, by weight: about 21% chromium, about 3% copper, about 8% manganese, about 0.3% molybdenum, about 0.8% niobium, about 7% nickel, about 0.5% silicon, about 1% tungsten, about 0.13% carbon, and about 0.37% nitrogen, with the balance being essentially iron. In some embodiments, the improved alloy includes, by weight: about 20% chromium, about 4.4% copper, about 4.5% manganese, about 0.3% molybdenum, about 0.8% niobium, about 7% nickel, about 0.5% silicon, about 1% tungsten, about 0.24% carbon, about 0.3% nitrogen by weight with the balance being essentially iron. In some embodiments, improved alloys may vary an amount of manganese, amount of nickel, a W/Cu ratio, a Mo/W ratio, a C/N ratio, a Mn/N ratio, a Mn/Nb ratio, a Mn/Si ratio and/or a Mn/Ni ratio to enhance resistance to high temperature sulfidation, increase high temperature strength, and/or reduce cost. For example, for the improved wrought alloys to have a stable parent austenite phase, high strength from 600° C. to 900° C., and stable nano carbide and nanocarbonitride microstructures, the improved wrought alloys may include combinations of alloying elements present in the improved wrought alloys such that the following ratios (using wt. %) are achieved: a) Mo/W—0.3 to 0.5; b) W/Cu—0.25 to 0.33; c) C/N—0.25 to 0.33; d) Mn/Ni—0.3 to 1.5; e) Mn/N—20 to 25; f) Mn/Nb—5 to 13; and g) Mn/Si—4 to 20; and carbon plus nitrogen is from about 0.3 wt % to about 0.6 wt %.

Improved wrought alloy compositions may include the compositions described in the preceding paragraphs and compositions disclosed in U.S. Pat. No. 7,153,373, which is incorporated herein by reference. The improved wrought alloy composition may include at least 3.25% by weight precipitates at about 800° C. The improved wrought alloy composition may have been processed by aging or hot working and/or by cold working. As a result of such aging or hot working and/or cold working, the improved wrought alloy compositions (for example, NbC, Cr-rich $M_{23}C_6$) may con-

tain nanocarbonitrides precipitates. Such nanocarbonitride precipitates are not known to be present in cast compositions such as those disclosed in U.S. Pat. No. 7,153,373, and are believed to form upon hot working and/or cold working of the compositions. The nanocarbonitride precipitates may include particles having dimensions from about 5 nanometers to about 100 nanometers, from about 10 nanometers to about 90 nanometers, or from about 20 nanometers to about 80 nanometers. These wrought alloys may have microstructures that include, but are not limited to, nanocarbides (for example, NbC, Cr-rich $M_{23}C_6$), which form during aging (stress-free) or creep (stress<0.5 yield stress (YS)). The nanocarbide precipitates may include particles having dimensions from 5 nanometers to 100 nanometers, from about 10 nanometers to about 90 nanometers, or from about 20 nanometers to about 80 nanometers. The microstructures may be a consequence of both the native alloy composition and the details of the wrought processing. In solution annealed material, the concentration of such nanoscale particles may be low. The nanoscale particles may be affected by solution anneal temperature/time (more and finer dispersion with longer anneal above 1150° C.) and by cold- or warm-prestrain (cold work) after the solution anneal treatment. Cold prestrain may create dislocation networks within the grains that may serve as nucleation sites for the nanocarbides. Solution annealed material initially has zero percent cold work. Bending, stretching, coiling, rolling or swaging may create, for example about 5 to about 15% cold work. The effect of the nanocarbides on yield strength or creep strength may be to provide strength based on dislocation-pinning, with more closely-spaced pinning sites (higher concentration, finer dispersion) providing more strength (particles are barriers to climb or glide of dislocations).

The improved wrought alloy may include nanonitrides (for example, niobium chromium nitrides (NbCrN)) in the matrix together with nanocarbides, after, for example, being aged for 1000 hours at about 800° C. The nanonitride precipitates may include particles having dimensions from about 5 nanometers to about 100 nanometers, from about 10 nanometers to about 90 nanometers, or from about 20 nanometers to about 80 nanometers. Niobium chromium nitrides have been identified using analytical electron microscopy as rich in niobium and chromium, and as the tetragonal nitride phase by electron diffraction (both carbides are cubic phases). X-ray energy dispersive quantitative analysis has shown that for the improved alloy compositions, these nanoscale nitride particles may have a composition by weight of: about 63% niobium, about 28% chromium, and about 6% iron, with other components being at most 5% each. Such niobium chromium nitrides were not observed in aged cast stainless steels with similar compositions, and appear to be a direct consequence of the wrought processing.

In some embodiments, the improved wrought alloy may include a mixture of microstructures (for example, a mixture of nanocarbides and nanonitrides). The mixture of microstructures may be responsible for the improved strength of these alloy compositions at elevated temperatures, such as, for example, about 900-1000° C. In some embodiments, the improved alloys may have a yield strength greater than 35 kpsi, or 30 kpsi at about 800° C.

In some embodiments, the improved alloys are processed to produce a wrought material. Processing may include steps such as the following. A centrifugal cast pipe may be cast from the improved alloy. A section may be removed from the casting and heat treated at a temperature of at least 1250° C. for, for example, three hours. The heat treated section may be hot rolled at a temperature of at least 1200° C. to a thickness of about half of the original thickness inches), annealed at a temperature of at least 1200° C. for fifteen minutes, and then sandblasted. The sandblasted section may be cold rolled to a thickness of about one third of the original cast thickness. The cold rolled section may be annealed to a temperature of at least 1250° C. for a period of time, for example, an hour, in, for example, air with an argon cover, and then given a final additional heat treatment for one hour at a temperature of at least 1250° C. in air with an argon blanket. An alternative process may include any of the following: initially homogenizing the cast plate at a temperature of at least 1200° C. for a period of time, for example 1½ hours; hot rolling at a temperature of at least 1200° C. to two thirds of the original cast thickness; and annealing the cold-rolled plate for one hour at a temperature of at least 1200° C. The improved alloys may be extruded at, for example, about 1200° C., with, for example, a mandrel diameter of about 22.9 millimeters (0.9 inches) and a die diameter of about 34.3 millimeters (1.35 inches) to produce good quality tubes.

The wrought material may be welded by, for example, laser welding or tungsten gas arc welding. Thus, tubes may be produced by rolling plates and welding seams.

Annealing the improved alloys at higher temperatures, such as about 1250° C., may improve properties of the alloys. At a higher temperature, more of the phases go into solution and upon cooling precipitate into phases that contribute positively to the properties, such as high temperature creep and tensile strength. Annealing at temperatures higher than 1250° C., such as about 1300° C. may be beneficial. For example, the calculated phase present in the improved alloys may decrease by about 0.08% at about 1300° C. as opposed to the phase present in the improved alloys at about 1200° C. Thus, upon cooling, more useful precipitates may form by about 0.08%. Improved alloys may have high temperature creep strengths and tensile strengths that are superior to conventional alloys. For example, niobium stabilized stainless steel alloys that include manganese, nitrogen, copper and tungsten may have high temperature creep strengths and tensile strengths that are improved, or substantially improved relative to conventional alloys such as 347H.

Improved alloys may have increased strength relative to standard stainless steel alloys such as Super 304H at high temperatures (for example, about 700° C., about 800° C., or above about 1000° C.). Superior high temperature creep-rupture strength (for example, creep-rupture strength at about 800° C., about 900° C., or about 1250° C.) may be improved as a result of (a) composition, (b) stable, fine-grain microstructures induced by high temperature processing, and (c) age-induced precipitation structures in the improved alloys. Precipitation structures include, for example, microcarbides that strengthen grain boundaries and stable nanocarbides that strengthen inside the grains. Presence of phases other than sigma, laves, G, and chi phases contribute to high temperature properties. Stable microstructures may be achieved by proper selection of components. High temperature aging induced or creep-induced microstructures may have minimal or no intermetallic sigma, laves and chi phases. Intermetallic sigma, laves and chi phases may weaken the strength properties of alloys and are therefore generally undesirable.

At about 800° C., the improved alloys may include at least 3% or at least 3.25% by weight of microcarbides, other phases, and/or stable, fine grain microstructure that produce strength. At about 900° C., the improved alloys may include, by weight, at least 1.5%, at least 2%, at least 3%, at least 3.5%, or at least 5% microcarbides, other phases, and/or stable, fine grain microstructure that produce strength. These values may be higher than the corresponding values in 347H or Super

304H stainless steel alloys at about 900° C. At about 1250° C. improved alloys may include at least 0.5% by weight microcarbides, other phases, and/or stable, fine grain microstructure that produce strength. The resulting higher weight percent of microcarbides, other phases, and/or stable, fine grain microstructure, and the exclusion of sigma and laves phases, may account for superior high temperature performance of the improved alloys.

Alloys having similar or superior high temperature performance to the improved alloys may be derived by modeling phase behavior at elevated temperatures and selecting compositions that retain at least 1.5%, at least 2%, or at least 2.5% by weight of phases other than sigma or laves phases at, for example, about 900° C. For example, a stable microstructure may include an amount, by weight, of: niobium that is nearly ten times the amount of carbon, from 1% to 12% manganese, and from 0.15 to 0.5% of nitrogen. Copper and tungsten may be included in the composition to increase the amount of stable microstructures. The choice of elements for the improved alloys allows processing by various methods and results in a stable, fine grain size, even after heat treatments of at least 1250° C. Many prior art alloys tend to grain coarsen significantly when annealed at such high temperatures whereas the improved alloy can be improved by such high temperature treatment. In some embodiments, grain size is controlled to achieve desirable high temperature tensile and creep properties. Stable grain structure in the improved alloys reduces grain boundary sliding, and may be a contributing factor for the better strength relative to commercially available alloys at temperatures above, for example, about 650° C.

A downhole heater assembly may include 5, 10, 20, 40, or more heaters coupled together. For example, a heater assembly may include between 10 and 40 heaters. Heaters in a downhole heater assembly may be coupled in series. In some embodiments, heaters in a heater assembly may be spaced from about 8 meters (about 25 feet) to about 60 meters (about 195 feet) apart. For example, heaters in a heater assembly may be spaced about 15 meters (about 50 feet) apart. Spacing between heaters in a heater assembly may be a function of heat transfer from the heaters to the formation. Spacing between heaters may be chosen to limit temperature variation along a length of a heater assembly to acceptable limits. Heaters in a heater assembly may include, but are not limited to, electrical heaters, flameless distributed combustors, natural distributed combustors, and/or oxidizers. In some embodiments, heaters in a downhole heater assembly may include only oxidizers.

FIG. **146** depicts a schematic of an embodiment of downhole oxidizer assembly **800** including oxidizers **802** connected in series. In some embodiments, oxidizer assembly **800** may include oxidizers **802** and flameless distributed combustors. Oxidizer assembly **800** may be lowered into an opening in a formation and positioned as desired. In some embodiments, a portion of the opening in the formation may be substantially parallel to the surface of the Earth. In some embodiments, the opening of the formation may be otherwise angled with respect to the surface of the Earth. In an embodiment, the opening may include a significant vertical portion and a portion otherwise angled with respect to the surface of the Earth. In certain embodiments, the opening may be a branched opening. Oxidizer assemblies may branch from common fuel and/or oxidant conduits in a central portion of the opening.

Oxidizing fluid **808** may be supplied to oxidizer assembly **800** through oxidant conduit **810**. In some embodiments, fuel conduit **806** and/or oxidizers **802** may be positioned concentrically, or substantially concentrically, in oxidant conduit **810**. In some embodiments, fuel conduit **806** and/or oxidizers **802** may be arranged other than concentrically with respect to oxidant conduit **810**. In certain branched opening embodiments, fuel conduit **806** and/or oxidant conduit **810** may have a weld or coupling to allow placement of oxidizer assemblies **800** in branches of the opening. Exhaust gas **812** may pass through outer conduit **814** and out of the formation.

In some embodiments, the downhole oxidizer assembly includes a water conduit positioned in the oxidant conduit that is configured to deliver water to the fuel conduit prior to the first oxidizer in the oxidizer assembly. A portion of the water conduit may pass through a heated zone generated by the first oxidizer prior to a water entry point into the fuel conduit. In some embodiments, the fuel conduit is positioned adjacent to the oxidizers, and branches from the fuel conduit provide fuel to the other oxidizers. In some embodiments, the fuel conduit may comprise one or more orifices to selectively control the pressure loss along the fuel conduit.

Fuel **804** may be supplied to oxidizers **802** through fuel conduit **806**. In some embodiments, the fuel for the oxidizers may be synthesis gas. In some embodiments, the fuel is synthesis gas (for example, a mixture of hydrogen and carbon monoxide) that was produced using an in situ heat treatment process. In some embodiments, the fuel contains products from a goal or heavy oil gasification process. The coal or heavy oil gasification process may take place above ground or below ground. After initiation of combustion of fuel and oxidant mixture in oxidizers **802**, composition of the fuel may be varied to enhance operational stability of the oxidizers.

In certain embodiments, fuel used to initiate combustion may be enriched to decrease the temperature required for ignition or otherwise facilitate startup of oxidizers **802**. In some embodiments, hydrogen or other hydrogen rich fluids may be used to enrich fuel initially supplied to the oxidizers. After ignition of the oxidizers, enrichment of the fuel may be stopped. In other embodiments, the fuel may comprise natural gas mixed with heavier components such as ethane, propane, butane, or carbon monoxide. In some embodiments, a portion or portions of fuel conduit **806** may include a catalytic surface (for example, a catalytic outer surface) to decrease an ignition temperature of fuel **804**.

Coke formation may occur inside the fuel conduit if the fuel contains hydrocarbons components and the heat flux is sufficiently high. After oxidizer ignition, steps may be taken to reduce coking. For example, steam or water may be added to fuel conduit **806**. In some embodiments, coking is inhibited by decreasing a residence time of fuel in fuel conduit **806**. The residence time of fuel in fuel conduit **806** may decreased by varying the size of the fuel conduit. For example, one portion of fuel conduit **806** may be approximately ¾ inch (approximately 1.9 cm) in diameter while another portion may be approximately ⅜ inch (approximately 0.95 cm) in diameter. Alternatively, the thickness and length of all or portions of fuel conduit **806** may be varied.

In some embodiments, coking is inhibited by insulating portions of fuel conduit **806** that pass through high temperature zones proximate oxidizers **802**. For example, a portion of fuel conduit **806** may be coated with an insulating layer and/or a conductive layer. The insulating layer may be made from thermal insulating materials such as silicon carbide, alumina, mullite, zirconia, and other material known in the art. The conductive layer may be made from commercially available highly conductive materials such as ceramics and/or high temperature metals, including but not limited to Hexyloy (available from Arklay S. Richards Co., Inc.). The insulating layer and/or the conductive layer may be applied to fuel

conduit **806** using a high velocity oxygen fuel or air plasma process. The resulting layer or layers may be heat treated.

In some embodiments, the fuel conduit is treated to remove coke formed in the fuel conduit by decoking. Decoking may be performed through mechanical means and/or chemical means. For example, coke may be removed from the fuel conduit by pumping a metal, studded, foam, or plastic pig through the fuel conduit. In an embodiment, a rod is inserted into fuel conduit **806** to dislodge coke particles and push them towards the last oxidizer in the oxidizer assembly. The rod may be a hydrolance or other high pressure pipe or tube used to direct high pressure water, air, nitrogen, and/or other gas to dislodge the coke.

FIG. **147** and FIG. **148** depict embodiments of oxidizers **802** of oxidizer assemblies positioned in outer conduits **814**. Oxidizer **802** may be coupled to fuel conduit **806** that is positioned in oxidant conduit **810**. Oxidant and fuel enter mix chamber **818** of oxidizer **802**. A combustible mixture of fuel and oxidant passes from mix chamber **818** into the space between fuel conduit **806** and shield **824**. Shield **824** surrounds a portion of fuel conduit **806**. Shield **824** allow development of flame zone **2070** in oxidizer **802**. Shield **824** inhibits gas flowing in oxidant conduit from extinguishing flame zone **2070** formed in oxidizer **802**. Spacers may position oxidizer **802** in oxidant conduit **810**. The spacers may be coupled to shield **824** and/or to oxidizer conduit **810**. An igniter and/or combusting fuel in flame zone **2070** oxidizes the mixture of fuel and oxidant in the flame zone.

Insulating layer **2064** may be placed around fuel conduit **806** to at least partially surround a portion of the fuel conduit. Insulating layer **2064** may be made of a material with low thermal conductivity. Insulating layer **2064** may inhibit coking in fuel conduit **806**. Insulating layer **2064** may only surround portions of fuel conduit **806** that pass through oxidizers **802**. In some embodiments, the insulating layer covers the portion of the fuel conduit passing through the oxidizer and a portion of the fuel conduit before and/or after the oxidizer. In some embodiments, the entire fuel conduit is insulated.

Thermally conductive layer **2066** may surround or partially surround insulating layer **2064**. Thermally conductive layer **2066** may be located adjacent to flame zone **2070**. Thermally conductive layer **2066** may spread the heat of flame zone **2070** over a large area to help reduce the temperature applied to insulating layer **2064** below the flame zone. In some embodiments, the insulating layer does not include a thermally conductive layer.

FIG. **148** depicts a cross-sectional representation of an embodiment of oxidizer **802** with gas cooled sleeve **2068**. A portion of sleeve **2068** may pass through oxidizer **802** to form an annular space. One or more spacers may be located between fuel conduit **806** and sleeve **2068** to position the sleeve relative to the fuel conduit. One or more feedthroughs **2072** may direct fuel from fuel conduit **806** to mix chamber **818** and/or to the area between shield **824** and the fuel conduit of oxidizer **802**. Some gas flowing in oxidant conduit **810** passes between fuel conduit **806** and insulating sleeve **2064**. Insulating sleeve **2064** may include thermally conductive layer **2066** to dissipate some of the heat from flame zone **2070** over a large area. Gas passing between fuel conduit **806** and insulating sleeve **2064** may inhibit excessive heating of the fuel conduit adjacent to flame zone **2070**.

The flow of fuel in fuel conduit **806** is represented by arrow **2074**, and the flow of gas (for example, air and exhaust products and unburned fuel from previous oxidizers) in oxidant conduit **810** is represented by arrow **2076**. Exhaust gases from all of oxidizers in the oxidizer assembly pass through outer conduit **814** in the direction indicated by arrow **2078**. Flow of gas between fuel conduit **806** and insulating sleeve **2064** may reduce the amount of heat transfer from the insulating sleeve to the fuel conduit. Flame zone **2070** may have a temperature of about 1100° C. (about 2000° F.) while the temperature in oxidant conduit adjacent to the shield of oxidizer **802** may be about 700° C. (about 1300° F.).

Oxidant may be supplied through the oxidant conduit to the oxidizers. Oxidizing fluid may include, but is not limited to, air, oxygen enriched air, and/or hydrogen peroxide. Depletion of oxygen in the oxidant may occur toward a terminal end of an oxidizer assembly. In some embodiments, the amount of excess oxidant supplied to the oxidizers is reduced to less than about 50% excess oxidant by weight by controlling the pressure, temperature, and flow rate of the oxidant in the oxidant conduit. For example, after ignition, the amount of oxidant can be reduced when the temperature of the fuel conduit reaches about 650° C. (about 1200° F.). In some embodiments, the amount of excess oxidant is reduced to less than about 25% excess oxidant by weight. In other embodiments, the amount of excess oxidant is reduced to less than about 10% excess oxidant by weight.

In some embodiments, the amount of excess oxidant is reduced when the temperature downstream of the oxidizers becomes sufficiently hot to support reaction of oxidant and fuel outside of the oxidizers. Oxidant and fuel may react in regions between oxidizers. During such operation, the oxidizer assembly functions much like a flameless distributed combustor. Generating heat in the regions between the oxidizers may result in a smoother temperature profile along the length of the oxidizer assembly. The excess oxidant may be reduced such that the last oxidizer in the oxidizer assembly substantially eliminates the remaining oxidant in the oxidant conduit. The last oxidizer may be a catalytic oxidizer to minimize or eliminate oxidant remaining in the oxidant conduit.

When the temperature along the length of the oxidizer assembly increases to a temperature sufficient to support reaction of oxidant with fuel outside of the shields of the oxidizers, the mode of operation of the oxidizer assembly may shift from a series of individual oxidizers with aerodynamically staged flames to a more uniformly distributed or "reactor-stable" mode of operation. During the reactor-stable mode of operation, combustion may take place outside the shield along the entire length of the oxidant conduit. Under this condition stability is achieved by balancing overall heat loss and heat generation over the broad reaction zone. Local recirculation of hot combustion products to incoming reactants enables minimum reaction temperature where fuel-oxidant mixtures will oxidize without aerodynamic stabilization. In this mode of operation, the oxidizers may still serve as a "safety" or means of continuing stabilization, if the temperature falls below the temperature needed to sustain oxidation of the fuel and oxidant in one or more regions of the oxidizer. During reactor-stable mode of operation, the amount of excess oxygen supplied to the oxidizer assembly may be reduced. Having the ability to reduce the amount of excess oxygen supplied to the oxidizer assembly may significantly improve the overall economics of the system used to heat the formation.

A common problem associated with the operation of gas burners employing a flame mechanism is that at high temperatures, particularly above about 1500° C. (about 2730° F.), oxygen and nitrogen present in the air combine by a thermal formation mechanism to form pollutants such as NO and NO_2, commonly referred to as NOx. By controlling the flow of fuel and oxidant and by maintaining a distributed temperature, the formation of NOx may be inhibited. In some embodi-

ments, the flow of fuel and oxidant is controlled to produce less than about 10 parts per million by weight of NOx from the gas burner. The flow of oxidant may be controlled by having openings in shields of the oxidizers sized to bring a sufficient flow rate past to the flame zone to dilute the flame without causing the flame to be extinguished. Additionally, water added to the fuel conduit may inhibit NOx formation.

In some embodiments, initiation of the burner assembly is be accomplished by initializing combustion in a specified sequence beginning with the last oxidizer in the assembly. Referring to FIG. **146**, oxidizer assembly **800** includes first oxidizer **2080**, last oxidizer **2082**, and second-to-last oxidizer **2084**. In some embodiments, fuel is supplied through fuel conduit **806**, and oxidant is supplied through oxidant conduit **810** to provide a first combustible mixture to last oxidizer **2082**. Combustion is initiated in last oxidizer **2082** and the supply of oxidant is adjusted to supply second-to-last oxidizer **2084** with a second combustible mixture. Ignition of last oxidizer **2082** is maintained as second-to-last oxidizer **2084** is ignited. Thereafter this process of adjusting the supply of oxidant to provide a combustible fuel and oxidant mixture to the next unignited oxidizer and initiating combustion in the unignited oxidizer is repeated until first oxidizer **2080** is ignited. In some embodiments, the fuel pressure is greater than the oxidant pressure at an oxidizer before initiating combustion in the oxidizer.

In an embodiment, the start up sequence is optimized by controlling the oxidant and fuel pressure differential along the length of the oxidizer assembly. Because the pressure differential varies over the length of the burner assembly, a planned sequential ignition from oxidizer to oxidizer, starting with last (most remote) oxidizer **2082** may be achieved. In this embodiment, the fuel-oxidant mixture in the ignition region is optimized at last oxidizer **2082**, then at the second to last oxidizer **2084**, and so on, with the fuel-to-oxidant ratio being least optimal at first oxidizer **2080**. The profiles may be controlled to change the sequence of ignition. In an embodiment, the profiles may be reversed so that first oxidizer **2080** is ignited first. Altering the profiles may comprise altering the pressure differential along the oxidizer assembly length by design of the fuel conduit diameter coupled with optimization of opening sizes that provide fuel to the oxidizers, of opening sizes that provide oxidant to the mix chambers of the oxidizers, and of openings in the shields that supply oxidant to the flame zone. In addition, control may be facilitated by flow restrictions positioned in fuel conduit **806**.

FIG. **149** depicts a perspective view of an embodiment of oxidizer **802** of the downhole oxidizer assembly. Oxidizer **802** may include mix chamber **818**, igniter holder **820**, nozzle and flame holder **822**, and shield **824**. Fuel conduit **806** may pass through oxidizer **802**. Fuel conduit **806** may have one or more fuel openings **826** within mix chamber **818** (as shown in FIG. **147**). In some embodiments, additional openings in fuel conduit **806** allow additional fuel to pass into the space between the fuel conduit and shield **824**. Openings **828** allow oxidant to flow into mix chamber **818**. Opening **830** allows a portion of the igniter supported on igniter holder **820** to pass into oxidizer **802**. Shield **824** may include openings **832**. Openings **832** may provide additional oxidant to a flame in shield **824**. Openings **832** may stabilize the flame in oxidizer **802** and moderate the temperature of the flame. Spacers **834** may be positioned on shield **824** to keep oxidizer **802** positioned in oxidant conduit **810**.

In some embodiments, flame stabilizers may be added to the oxidizers. The flame stabilizers may attach the flame to the shield. The high bypass flow around the oxidizer cools the shield and protects the internals of the oxidizer from damage enabling long term operation. FIGS. **150-155** depict various embodiments of shields **824** with flame stabilizers **836**. Flame stabilizer **836** depicted in FIG. **150** is a ring substantially perpendicular to shield **824**. The ring shown in FIG. **151** is angled away from openings **832**. The rings may amount to up to about 25% annular area blockage. The rings may establish a recirculation zone near shield **824** and away from the fuel conduit passing through the center of the shield.

FIG. **152** depicts an embodiment of flame stabilizer **836** in shield **824**. Flame stabilizer **836** is positioned at an angle over the openings. Flame stabilizer **836** may divert incoming fluid flow through openings **832** in an upstream direction. The diverted incoming fluid may set up a flow condition somewhat analogous to high swirl recirculation (reverse flow). One or more stagnation zones may develop where a flame front is stable.

FIG. **153** depicts an embodiment of multiple flame stabilizers **836** in shield **824**. Shield **824** may have two or more sets of openings **832** along an axial length of the shield. Rings may be positioned behind one or more of the sets of openings **832**. In some embodiments, adjacent rings may cause too much gas flow interference. To inhibit gas flow interference, 3 partial rings (each ring being about ⅓ the circumference) may be evenly spaced about the circumference instead of one complete ring. The next set of 3 partial rings along the axial length of heat shield may be staggered (for example, the partial rings may be rotated by 120° relative to the first set of 3 partial rings). FIG. **154** depicts a cross-sectional representation of shield **824** showing the last set of openings **832** and the last set of flame stabilizers **836**. Shield **824** includes spacers **834**. In other embodiments, fewer or more than 3 partial rings may be used (for example, two partial rings may be used for the first set of openings, and four partial rings may be used for the next set of openings). Flame stabilizers **836** may be perpendicular to shield **824**, angled towards openings **832**, angled away from the openings (as depicted in FIG. **153**) or positioned as combinations of perpendicular and angled orientations.

FIG. **155** depicts an embodiment wherein flame stabilizers **836** are deflector plates or baffles extending over all or portions of openings **832**. The portions of flame stabilizers **836** positioned over the openings may be cylindrical sections with the concave portions facing openings **832**. Flame stabilizers **836** may divert incoming fluid flow and allow the flame root area to develop around the deflectors. Some openings in the shield may not include flame stabilizers.

In some embodiments, deflectors may be positioned on the outer surface of the shield near to openings in the shield. The deflectors may direct some of the gas flowing through the oxidant conduit through the openings in the shield.

As depicted in FIGS. **149-155**, shield **824** may include opening **832**. The size and/or number of openings **832** may be varied depending on position of the oxidizer in the oxidizer assembly to moderate the temperature and ensure fuel combustion. In some embodiments, the geometry and size of openings **832** on a single oxidizer may be varied to compensate for changing conditions and needs along the length of the oxidizer.

FIGS. **156-158** depict perspective views of various sectioned oxidizer embodiments. Oxidizers **802** include oxidant openings **828**, mix chambers **818**, nozzle and flame holder **822**, and shield **824**. FIGS. **156-158** depict various positions and sizes for openings **832** in shield **824** oxidant.

In some embodiments, one or more of the openings in the shield may be angled in a non-perpendicular direction relative to the longitudinal axis of the shield. Angled openings act as nozzles to alter the entry path of gas into the shield. Angled openings may promote formation of internal low velocity

recirculation zones where the reaction front can stabilize and improve the stability and reliability of the oxidizer.

The use of flame stabilizers, various sizes of openings in the shield and/or angled openings may establish the flame zone of the oxidizer close to the shield and as far away from the fuel conduit to maximize radial separation of the flame zone from the fuel conduit to minimize direct heating of the fuel conduit by the flame zone. The use of flame stabilizers, various sizes of openings in the shield and/or angled openings may Directional configurations may also achieve lower NOx emissions by effectively aerodynamically staging the combustion zone and creating fuel rich and lean zones. In fuel rich zones N_2 formation (instead of NOx) will be favored and aerodynamic staging will control peak temperatures and thermal NOx formation. Such configurations can also enable control of the peak longitudinal temperature profile and flame radiation, hence suppressing overheating of the fuel conduit.

In one embodiment, the oxidizers may comprise heat shields, which utilize a louvered design to direct flow into the shield. FIG. **159** depicts oxidizer **802** with louvered openings **832** in shield **824**. Louvered openings **832** are in communication with the oxidant conduit and are configured to direct flow into shield **824** in a direction opposite to the direction of flow in the oxidant conduit. FIG. **160** depicts a cross-sectional representation of a portion of shield **824** with louvered opening **832**. Gas with oxidant may be directed from oxidant conduit to the inside of shield **824**. Arrow **2086** indicates the direction of gas flow from the oxidant conduit to the inside of shield. Arrow **2088** indicates the direction of gas flow in the oxidant conduit.

In some embodiments, fuel passes through a heated region before being supplied to the first oxidizer (oxidizer **2080** in FIG. **146**). Passing the fuel through the heated region may preheat the fuel and ensure that the fuel and additives in the fuel (for example, water to inhibit coking) are in the gas phase. Ensuring gas phase fuel may avoid plugging in first oxidizer **2080**. FIG. **161** depicts an embodiment of first oxidizer **2080** and fuel conduit **806**. Fuel conduit **806** may include sleeve **2090**. Fuel may flow through sleeve, and a portion of the fuel may flow in the opposite direction in the annular space between the sleeve and fuel conduit **806**. A portion of the fuel flowing in the annular space between sleeve **2090** and fuel conduit **806** passes through openings **826** into mix chamber **818**.

In some embodiments, a portion of the fuel flowing in the annular space between sleeve **2090** and fuel conduit **806** passes through openings **826** into the annular space between the fuel conduit and shield **824**. Supplying fuel into this annular space may allow flame zone **2070** to extend through a significant portion of first oxidizer **2080** so that the first oxidizer is able to input more heat into the formation. First oxidizer **2080** may be configured to input more heat into the formation to help compensate for heat losses attributable to the oxidizer being the first oxidizer of the oxidizer assembly. Having first oxidizer configured to input more heat into the formation than other oxidizers of the oxidizer assembly may allow for a decrease in the total number of oxidizers needed in the downhole assembly.

One or more of the oxidizers in an oxidizer assembly may be a catalytic burner. The catalytic burners may include a catalytic portion (for example, catalyst chamber) followed by a homogenous portion (for example, mix chamber). Catalytic burners may be started late in an ignition sequence, and may ignite without igniters. Oxidant for the catalytic burners may be sufficiently hot from upstream burners (for example, the oxidant may be at a temperature of about 370° F. (about 700° C.) if the fuel is primarily methane) so that a primary mixture would react over the catalyst in the catalyst portion and produce enough heat so that exiting products ignite a secondary mixture in the homogenous portion of the oxidizer. In some embodiments, the fuel may include enough hydrogen to allow the needed temperature of the oxidant to be lower. Catalysts used for this purpose may include palladium, platinum, platinum/iridium, and platinum/rhodium.

FIG. **162** depicts a cross-sectional representation of catalytic burner **838**. Oxidizer may enter mix chamber **818** through openings **828**. Fuel may enter mix chamber **818** from fuel conduit **806** through fuel openings **826'**. Fuel and oxidizer may flow to catalyst chamber **840**. Catalyst chamber **840** contains catalyst which reacts a mixture from mix chamber **818** to produce reaction products at a temperature that is sufficient to ignite fuel and oxidant. In some embodiments, the catalyst includes palladium on a honeycomb ceramic support. The fuel and oxidant react in catalyst chamber **840** to form hot reaction products. The hot reaction products may be directed to the annular space between shield **824** and fuel conduit **806**. Additional fuel enters the annular space through openings **826"** in fuel conduit **806**. Additional oxidant enters the annular space through openings **832**. The hot reaction products generated by catalyst **840** may ignite fuel and oxidant in autoignition zone **842**. Autoignition zone **842** may allow fuel and oxidant to form flame zone **2070**. In some embodiments, the catalytic burner includes flame stabilizers or other types of gas flow modifiers.

In some embodiments a catalytic burner may include an igniter to simplify startup procedures. FIG. **163** depicts catalytic burner **838** that includes igniter **816**. Igniter **816** is positioned in mix chamber **818**. Catalyst burner **838** includes catalyst chamber **840**. Catalyst chamber contains a catalyst that reacts a mixture from mix chamber **818** to produce reaction products at a temperature that is sufficient to ignite fuel and oxidant. Oxidant enters mix chamber through openings **828**A. Fuel enters the mix chamber from fuel line through fuel openings **826**A. The fuel input into mixture chamber **818** may be only a small fraction of the fuel input for catalytic burner **838**. Igniter **816** raises the temperature of the fuel and oxidant to combustion temperatures in pre-heat zone **846**. Flame stabilizer **836** may be positioned in mixing chamber **818**. Heat from pre-heat zone **846** and/or combustion products may heat additional fuel that enters mixing chamber **818** through fuel openings **826**B and additional oxidant that enters the mixing chamber through openings **828**B. Openings **826**B and openings **828**B may be upstream of flame stabilizer **836**. The additional fuel and oxidant are heated to a temperature sufficient to support reaction on catalyst **840**.

Heated fuel and oxidant from mixing chamber **818** pass to catalyst **840**. The fuel and oxidant react on catalyst **840** to form hot reaction products. The hot reaction products may be directed to heat shield **824**. Additional fuel enters heat shield **824** through openings **826**C in fuel conduit **806**. Additional oxidant enters heat shield **824** through openings **832**. The hot reaction products generated by catalyst **840** may ignite fuel and oxidant in autoignition zone **842**. Autoignition zone **842** may allow fuel and oxidant to form main combustion zone **2070**. In some embodiments, the catalytic burner includes flame stabilizers or other types of gas flow modifiers.

In some embodiments, all of the oxidizers in the oxidizer assembly are catalytic burners. In some embodiments, the first or the first several oxidizers in the oxidizer assembly are catalytic burners. The oxidant supplied to these burners may be at a lower temperature than subsequent burners. Using catalytic burners with igniters may stabilize the first performance of the first several oxidizers in the oxidizer assembly. Catalytic burners may be used in-line with other burners to

reduce emissions by allowing lower flame temperatures while still having substantially complete combustion.

In some embodiments, a catalytic converter may be positioned at the end of the oxidizer assembly or in the exhaust gas return. The catalytic converter may remove unburned hydrocarbons and/or remaining NOx compounds or other pollutants. The catalytic converter may benefit from the relatively high temperature of the exhaust gas. In some embodiments, catalytic burners in series may be integrated with coupled catalytic converters to limit undesired emissions from the oxidizer assembly. In some embodiments, a selectively permeable material may be used to allow carbon dioxide or other fluids to be separated from the exhaust gas.

In one embodiment, initiation of the burner assembly may be accomplished by initializing combustion with hydrogen and later switching to natural gas or another fuel. The use of hydrogen-enriched fuel may suppress flame radiation and reduce heating of the fuel conduit. Oxidizers of the oxidizer assembly may be ignited using hydrogen or fuel that is highly enriched with hydrogen. Once ignited, the composition of fuel may be adjusted to comprise natural gas and/or other fuels. The initial use of hydrogen or hydrogen-enriched fuel widens the flammability envelope enabling much easier startup. An initial fuel composition could then be "chased" with production gas or other more economical gases. Alternatively, the entire system could burn hydrogen. With no carbon in the fuel, there would be no need for additional decoking methods.

In some embodiments, pulverized coal is the fuel used to heat the subsurface formation. The pulverized coal may be carried into the wellbores with a non-oxidizing fluid (for example, carbon dioxide and/or nitrogen). An oxidant may be mixed with the pulverized coal at several locations in the wellbore. The oxidant may be air, oxygen enriched air and/or other types of oxidizing fluids. Igniters located at or near the mixing locations initiate oxidation of the coal and oxidant. The igniters may be catalytic igniters, glow plugs, spark plugs, and/or electrical heaters (for example, an insulated conductor temperature limited heater with heating sections located at mixing locations of pulverized coal and oxidant) that are able to initiate oxidation of the oxidant with the pulverized coal. In FIG. **146**, pulverized coal entrained in a carrier fluid may be fuel **804** supplied to oxidizers **802** through fuel conduit **806**. Initially, oxidizer assembly **800** may be started using hydrogen, natural gas, or other fuel. After temperatures of oxidizers **802** are hot enough to support rapid pulverized coal oxidation (for example, the temperature in and adjacent to the oxidizers is above about 600° C.), the fuel may be changed to pulverized coal and carrier gas.

The particles of the pulverized coal may be small enough to pass through flow orifices and achieve rapid combustion in the oxidant. The pulverized coal may have a particle size distribution from about 1 micron to about 300 microns, from about 5 microns to about 150 microns, or from about 10 microns to about 100 microns. Other pulverized coal particle size distributions may also be used. At 600° C., the time to burn the volatiles in pulverized coal with a particle size distribution from about 10 microns to about 100 microns may be about one second.

When using coal as the fuel for downhole oxidizers, exhaust gases from the heater wells may be treated to remove unreacted coal, ash, fines and/or other particles in the exhaust gas. In some embodiments, the exhaust gas passes through one or more cyclones to remove particles from the exhaust gas. The exhaust gas may be further processed to remove selected compounds (for example, sulfur and/or nitrogen compounds), may be used as a drive fluid for mobilizing hydrocarbons in a formation, may be sequestered in a subsurface formation, and/or may be otherwise handled.

In other embodiments, other types of downhole oxidizers are used for the subsurface oxidation of coal to heat selected portions of the formation. FIG. **164** depicts a schematic representation of heater **2092** that uses pulverized coal as fuel. Heater **2092** may include outer conduit **814**, first conduit **2094**, and second conduit **2096**. First conduit **2094** is positioned in outer conduit **814**, and second conduit **2096** is positioned in the first conduit. The end of second conduit may be closed. Second conduit **2096** may include critical flow orifices **2098**. The flow rate and/or pressures of the fluids flowing through first conduit **2094** and second conduit **2096** may be controlled to allow for mixing of fluid from the first conduit with fluid from the second conduit at desired locations in the first conduit.

In an embodiment, coal and carrier gas is introduced into heater **2092** through first conduit **2094**, and oxidant is introduced through second conduit **2096**. The flow rate and/or pressure in first conduit **2094** and second conduit **2096** are controlled so that the oxidant flows through critical flow orifices **2098** into the coal and carrier gas flowing through first conduit **2094**. Reaction of the coal and oxidant occurs in first conduit **2094**. Exhaust gases pass through outer conduit **814** to the surface. Passing the exhaust gases past the locations where oxidant and coal are oxidized may reduce temperature variations along the length of the heated section of heater **2092**.

In an embodiment, oxidant is introduced into heater **2092** through first conduit **2094**, and coal and carrier gas is introduced through second conduit **2096**. The flow rate and/or pressure of in first conduit **2094** and second conduit **2096** are controlled so that the coal and carrier gas flows through critical flow orifices **2098** into the oxidant flowing through first conduit **2094**. Reaction of the coal and oxidant occurs in first conduit **2094**. Exhaust gases pass through outer conduit **814** to the surface.

FIG. **165** depicts a schematic representation of heater **2092** that uses pulverized coal as fuel. Heater **2092** may include outer conduit **814**, first conduit **2094**, and second conduit **2096**. First conduit **2094** is positioned in outer conduit **814**, and second conduit **2096** is positioned in the first conduit. The end of first conduit **2094** may be sealed closed against second conduit **2096**. Second conduit **2096** may include critical flow orifices **2098**. The flow rate and/or pressures of the fluids flowing through first conduit **2094** and second conduit **2096** may be controlled to allow for mixing of fluid from the first conduit with fluid from the second conduit at desired locations in the second conduit.

In an embodiment, oxidant is introduced into heater **2092** through first conduit **2094**, and coal and carrier gas is introduced through second conduit **2096**. The flow rate and/or pressure of in first conduit **2094** and second conduit **2096** are controlled so that the oxidant flows through critical flow orifices **2098** into the coal and carrier gas flowing through second conduit **2096**. Reaction of the coal and oxidant occurs in second conduit **2096**. Reacting coal and oxidant in second conduit **2096** and passing exhaust gases pass through outer conduit **814** to the surface may reduce the formation of hot zones adjacent to sections of heater **2092** where oxidation occurs.

In an embodiment, coal and carrier gas is introduced into heater **2092** through first conduit **2094**, and oxidant is introduced through second conduit **2096**. The flow rate and/or pressure in first conduit **2094** and second conduit **2096** are controlled so that the coal and carrier gas flows through critical flow orifices **2098** into oxidant flowing through sec-

ond conduit **2096**. Reaction of the coal and oxidant occurs in second conduit **2096**. Exhaust gases pass through outer conduit **814** to the surface.

In some in situ heat treatment process embodiments, a circulation system is used to heat the formation. The circulation system may be a closed loop circulation system. FIG. **166** depicts a schematic representation of a system for heating a formation using a circulation system. The system may be used to heat hydrocarbons that are relatively deep in the ground and that are in formations that are relatively large in extent. In some embodiments, the hydrocarbons may be 100 m, 200 m, 300 m or more below the surface. The circulation system may also be used to heat hydrocarbons that are not as deep in the ground. The hydrocarbons may be in formations that extend lengthwise up to 500 m, 750 m, 1000 m, or more. The circulation system may become economically viable in formations where the length of the hydrocarbon containing formation to be treated is long compared to the thickness of the overburden. The ratio of the hydrocarbon formation extent to be heated by heaters to the overburden thickness may be at least 3, at least 5, or at least 10. The heaters of the circulation system may be positioned relative to adjacent heaters so that superposition of heat between heaters of the circulation system allows the temperature of the formation to be raised at least above the boiling point of aqueous formation fluid in the formation.

In some embodiments, heaters **760** may be formed in the formation by drilling a first wellbore and then drilling a second wellbore that connects with the first wellbore. Piping may be positioned in the U-shaped wellbore to form U-shaped heater **760**. Heaters **760** are connected to heat transfer fluid circulation system **868** by piping. Gas at high pressure may be used as the heat transfer fluid in the closed loop circulation system. In some embodiments, the heat transfer fluid is carbon dioxide. Carbon dioxide is chemically stable at the required temperatures and pressures and has a relatively high molecular weight that results in a high volumetric heat capacity. Other fluids such as steam, air, helium and/or nitrogen may also be used. The pressure of the heat transfer fluid entering the formation may be 3000 kPa or higher. The use of high pressure heat transfer fluid allows the heat transfer fluid to have a greater density, and therefore a greater capacity to transfer heat. Also, the pressure drop across the heaters is less for a system where the heat transfer fluid enters the heaters at a first pressure for a given mass flow rate than when the heat transfer fluid enters the heaters at a second pressure at the same mass flow rate when the first pressure is greater than the second pressure. In some embodiments, a liquid heat transfer fluid may be used. The liquid heat transfer fluid may be a natural or synthetic oil, or other type of high temperature heat transfer fluid.

Heat transfer fluid circulation system **868** may include heat supply **870**, first heat exchanger **872**, second heat exchanger **874**, and compressor **876**. Heat supply **870** heats the heat transfer fluid to a high temperature. Heat supply **870** may be a furnace, solar collector, chemical reactor, nuclear reactor, fuel cell exhaust heat, or other high temperature source able to supply heat to the heat transfer fluid. In the embodiment depicted in FIG. **166**, heat supply **870** is a furnace that heats the heat transfer fluid to a temperature in a range from about 700° C. to about 920° C., from about 770° C. to about 870° C., or from about 800° C. to about 850° C. In an embodiment, heat supply **870** heats the heat transfer fluid to a temperature of about 820° C. The heat transfer fluid flows from heat supply **870** to heaters **760**. Heat transfers from heaters **760** to formation **758** adjacent to the heaters. The temperature of the heat transfer fluid exiting formation **758** may be in a range from about 350° C. to about 580° C., from about 400° C. to about 530° C., or from about 450° C. to about 500° C. In an embodiment, the temperature of the heat transfer fluid exiting formation **758** is about 480° C. The metallurgy of the piping used to form heat transfer fluid circulation system **868** may be varied to significantly reduce costs of the piping. High temperature steel may be used from heat supply **870** to a point where the temperature is sufficiently low so that less expensive steel can be used from that point to first heat exchanger **872**. Several different steel grades may be used to form the piping of heat transfer fluid circulation system **868**.

Heat transfer fluid from heat supply **870** of heat transfer fluid circulation system **868** passes through overburden **458** of formation **758** to hydrocarbon layer **460**. Portions of heaters **760** extending through overburden **458** may be insulated. In some embodiments, the insulation or part of the insulation is a polyimide insulating material. Inlet portions of heaters **760** in hydrocarbon layer **460** may have tapering insulation to reduce overheating of the hydrocarbon layer near the inlet of the heater into the hydrocarbon layer.

In some embodiments, the diameter of the pipe in overburden **458** may be smaller than the diameter of pipe through hydrocarbon layer **460**. The smaller diameter pipe through overburden **458** may allow for less heat transfer to the overburden. Reducing the amount of heat transfer to overburden **458** reduces the amount of cooling of the heat transfer fluid supplied to pipe adjacent to hydrocarbon layer **460**. The increased heat transfer in the smaller diameter pipe due to increased velocity of heat transfer fluid through the small diameter pipe is offset by the smaller surface area of the smaller diameter pipe and the decrease in residence time of the heat transfer fluid in the smaller diameter pipe.

After exiting formation **758**, the heat transfer fluid passes through first heat exchanger **872** and second heat exchanger **874** to compressor **876**. First heat exchanger **872** transfers heat between heat transfer fluid exiting formation **758** and heat transfer fluid exiting compressor **876** to raise the temperature of the heat transfer fluid that enters heat supply **870** and reduce the temperature of the fluid exiting formation **758**. Second heat exchanger **874** further reduces the temperature of the heat transfer fluid before the heat transfer fluid enters compressor **876**.

FIG. **167** depicts a plan view of an embodiment of wellbore openings in the formation that is to be heated using the circulation system. Heat transfer fluid entries **878** into formation **758** alternate with heat transfer fluid exits **880**. Alternating heat transfer fluid entries **878** with heat transfer fluid exits **880** may allow for more uniform heating of the hydrocarbons in formation **758**.

In some embodiments, piping for the circulation system may allow the direction of heat transfer fluid flow through the formation to be changed. Changing the direction of heat transfer fluid flow through the formation allows each end of a unshaped wellbore to initially receive the heat transfer fluid at the heat transfer fluid's hottest temperature for a period of time, which may result in more uniform heating of the formation. The direction of heat transfer fluid may be changed at desired time intervals. The desired time interval may be about a year, about six months, about three months, about two months or any other desired time interval.

In some embodiments, nuclear energy may be used to heat the heat transfer fluid used in the circulation system to heat a portion of the formation. Heat supply **870** in FIG. **166** may be a pebble bed reactor or other type of nuclear reactor, such as a light water reactor. The use of nuclear energy provides a heat source with no carbon dioxide emissions. Also, the use of nuclear energy can be more efficient because energy losses

resulting from the conversion of heat to electricity and electricity to heat are avoided by directly utilizing the heat produced from the nuclear reactions without producing electricity.

In some embodiments, a nuclear reactor may heat helium. For example, helium flows through a pebble bed reactor, and heat transfers to the helium. The helium may be used as the heat transfer fluid to heat the formation. In some embodiments, the nuclear reactor may heat helium, and the helium may be passed through a heat exchanger to provide heat to the heat transfer fluid used to heat the formation. The pebble bed reactor may include a pressure vessel that contains encapsulated enriched uranium dioxide fuel. Helium may be used as a heat transfer fluid to remove heat from the pebble bed reactor. Heat may be transferred in a heat exchanger from the helium to the heat transfer fluid used in the circulation system. The heat transfer fluid used in the circulation system may be carbon dioxide, a molten salt, or other fluid. Pebble bed reactor systems are available from PBMR Ltd (Centurion, South Africa).

FIG. **168** depicts a schematic diagram of a system that uses nuclear energy to heat treatment area **882**. The system may include helium system gas blower **884**, nuclear reactor **886**, heat exchanger units **888**, and heat transfer fluid blower **890**. Helium system gas blower **884** may draw heated helium from nuclear reactor **886** to heat exchanger units **888**. Helium from heat exchanger units **888** may pass through helium system gas blower **884** to nuclear reactor **886**. Helium from nuclear reactor **886** may be at a temperature of about 900° C. to about 1000° C. Helium from helium gas blower **884** may be at a temperature of about 500° C. to about 600° C. Heat transfer fluid blower **890** may draw heat transfer fluid from heat exchanger units **888** through treatment area **882**. Heat transfer fluid may pass through heat transfer fluid blower **890** to heat exchanger units **888**. The heat transfer fluid may be carbon dioxide. The heat transfer fluid may be at a temperature from about 850° C. to about 950° C. after exiting heat exchanger units **888**.

In some embodiments, the system may include auxiliary power unit **900**. In some embodiments, auxiliary power unit **900** generates power by passing the helium from heat exchanger units **888** through a generator to make electricity. The helium may be sent to one or more compressors and/or heat exchangers to adjust the pressure and temperature of the helium before the helium is sent to nuclear reactor **886**. In some embodiments, auxiliary power unit **900** generates power using a heat transfer fluid (for example, ammonia or aqua ammonia). Helium from heat exchanger units **888** is sent to additional heat exchanger units to transfer heat to the heat transfer fluid. The heat transfer fluid is taken through a power cycle (such as a Kalina cycle) to generate electricity. In an embodiment, nuclear reactor **886** is a 400 MW reactor and auxiliary power unit **900** generates about 30 MW of electricity.

FIG. **169** depicts a schematic elevational view of an arrangement for an in situ heat treatment process. U-shaped wellbores may be formed in the formation to define treatment areas **882**A, **882**B, **882**C, **882**D. Additional treatment areas could be formed to the sides of the shown treatment areas. Treatment areas **882**A, **882**B, **882**C, **882**D may have widths of over 300 m, 500 m, 1000 m, or 1500 m. Well exits and entrances for the wellbores may be formed in well openings area **902**. Rail lines **904** may be formed along sides of treatment areas **882**. Warehouses, administration offices and/or spent fuel storage facilities may be located near ends of rail lines **904**. Facilities **906** may be formed at intervals along spurs of rail lines **904**. Each facility **906** may include a nuclear reactor, compressors, heat exchanger units and other equipment needed for circulating hot heat transfer fluid to the wellbores. Facilities **906** may also include surface facilities for treating formation fluid produced from the formation. In some embodiments, heat transfer fluid produced in facility **906'** may be reheated by the reactor in facility **906"** after passing through treatment area **882**A. In some embodiments, each facility **906** is used to provide hot treatment fluid to wells in one half of the treatment area **882** adjacent to the facility. Facilities **906** may be moved by rail to another facility site after production from a treatment area is completed.

In some embodiments, nuclear energy may be used to directly heat a portion of the subsurface formation. The portion of the subsurface formation may be part of the hydrocarbon treatment area. As opposed to using a nuclear reactor facility to heat a heat transfer fluid, which is then provided to the subsurface formation to heat the subsurface formation, one or more self-limiting nuclear heaters may be positioned underground to directly heat the subsurface formation.

In some embodiments, a nuclear heater assembly may include one or more encapsulated nuclear material elements (nuclear pebble heaters) positioned in the subsurface formation. In some embodiments, the encapsulated nuclear material elements are commercially available spheres that include fissionable material encapsulated in carbon. The nuclear pebble heaters are typically used in pebble bed reactors. Nuclear pebble heaters may be positioned in a fuel conduit within the subsurface formation. Nuclear pebble heaters may be positioned in the fuel conduit before and/or after the fuel conduit is positioned in the subsurface formation.

FIG. **170** depicts an embodiment of U-shaped nuclear heater assembly **2192**. FIG. **171** depicts nuclear heater assembly **2192** positioned in a wellbore where only one end of the wellbore extends to the surface. Nuclear heater assembly **2192** may include outer conduit **2194**. Nuclear heater assembly **2192** may include one or more fuel conduits **2196**. In some embodiments, is coiled tubing. Fuel conduit **2196** may be positioned in outer conduit **2194**. Nuclear heater assembly **2192** may include one or more nuclear pebble heaters **2198**. Nuclear pebble heaters **2198**, nuclear modulators **2202**, and/or nuclear reflectors **2200** may be positioned in fuel conduit **2196**. Heat transfer fluid **2206** may be circulated past nuclear pebble heaters **2198**. Heat transfer fluid **2206** may be circulated between the outer surface of fuel conduit **2196** and the inner surface of outer conduit **2194**. Heat transfer fluid may be sealed inside fuel conduit **2196**. Heat transfer fluid **2206** may distribute heat along the length of nuclear heater assembly **2192**. In some embodiments, heat transfer fluid **2206** is helium gas. Nuclear pebble heaters **2198** may be circulated by heat transfer fluid **2206**. Circulation of nuclear pebble heaters **2198** may maintain activation of the nuclear pebble heaters. Heat transfer fluid **2206** may push and/or carry nuclear pebble heaters, nuclear moderators, and/or nuclear reflectors to the surface of the wellbore.

In certain embodiments, fuel conduit **2196** is formed from a material that has high neutron reflectivity. Neutron reflective material may facilitate continuation of the nuclear reactions occurring in nuclear pebble heaters **2198** by reflecting neutrons that escape the nuclear pebble heaters back towards the originating nuclear pebble heaters or other nuclear pebble heaters positioned in fuel conduit **2196**. Neutron reflective material may inhibit neutrons from escaping fuel conduit **2196** into the surrounding subsurface formation. Formation of radioactive isotopes in the subsurface formation adjacent to nuclear heater assembly **2192** may be limited and/or inhibited by surrounding nuclear pebble heaters **2198** with one or

more conduits made out of neutron reflective material (for example, fuel conduit **2196** and outer conduit **2194**).

An example of a neutron reflective material suitable for encasing nuclear pebble materials is iron. In certain embodiments, it may be important to ensure the iron used is relatively pure and avoid some common impurities and/or additives typically combined with iron (such as chromium used in stainless steel). Other elements that may be avoided in a fuel conduit include, but are not limited to, nickel, manganese and cobalt. Additional reflection of thermal neutrons from the carbon and hydrogen atoms in the hydrocarbon containing formation may increase the thermal neutron flux experienced by the nuclear pebble heaters.

In some embodiments, nuclear heater assembly **2192** includes outer conduit **2194**. Fuel conduit **2196** may be positioned in outer conduit **2194** before and/or after the outer conduit has been positioned in the subsurface formation. In some embodiments, the nuclear heater assembly may be positioned in a casing in the sub surface formation. The casing may be cemented in the formation using a graphite based cement (for example 65% by weight graphite based cement). Graphite based cement may assist in maintaining application of a high thermal neutron flux to the nuclear pebble heaters. In certain embodiments, outer conduit **2194** includes material that is complementary to the material in fuel conduit **2196**. For example, fuel conduit **2196** may reflect neutrons but not be resistant to corrosion from fluids in the formation. Thus, outer conduit **2194** may be formed of a corrosion resistant material that may protect the fuel conduit from corrosive elements. In certain embodiments, outer conduit **2194** is formed from a corrosion resistant material such as stainless steel. In some embodiments, outer conduit **2194** is a composite iron or carbide and stainless steel (for example, an inside surface of outer conduit **2194** may be thick iron conduit and the outer surface of the outer conduit is stainless steel).

Commercially available nuclear pebble heater design typically includes low level enriched uranium triple-coated isotropic particles contained in a molded graphite sphere. A coated particle may include a kernel of uranium dioxide surrounded by four coating layers.

During the nuclear pebble heater fabrication process, a solution of uranyl nitrate is sprayed to form microspheres. The microspheres may then be gelled and calcined (baked at high temperature) to produce uranium dioxide fuel "kernels". The kernels are then run through a chemical vapor deposition oven. The chemical vapor deposition oven typically uses an argon environment at a temperature of about 1000° C., and layers of specific chemicals are added with precision.

The first layer deposited on the kernels may be porous carbon, allowing fission products to collect without overpressurizing the coated fuel particles. A second layer may include a thin coating of pyrolytic carbon. Pyrolytic carbon is a very dense form of heat-treated carbon. Following the second layer, a third layer of silicon carbide may be applied. The silicon carbide may function as a refractory material. Following the third layer, a fourth layer of pyrolytic carbon may be applied.

The porous carbon may accommodate any mechanical deformation that the uranium dioxide kernel may undergo during the lifetime of the nuclear pebble heater as well as accommodating gaseous fission products diffusing out of the kernel. The pyrolytic carbon and silicon carbide layers provide a barrier designed to contain the fuel and radioactive fission products resulting from nuclear reactions in the kernel.

In a typical nuclear pebble heater, about 15,000 coated particles are mixed with graphite powder and a phenolic resin and pressed into a spherical shape. The coated particles are about a millimeter in diameter. The resulting sphere is about 50 mm in diameter. A 5 mm thick layer of pure carbon may be added to form a "non-fuel" zone. The resulting spheres may be sintered and annealed to make them hard and durable. The spherical nuclear pebble heater may be machined to a uniform diameter of about 60 mm. Each nuclear pebble heater may include a total of about 9 g of uranium. In other embodiments, the size, number and composition of layers, and/or the amount of fissionable material may be different.

To have a self-sustaining reaction in the nuclear pebble heaters, the uranium in the nuclear pebble heaters may be enriched to include about 9% uranium-235, which is the isotope of uranium that undergoes fission in the nuclear pebble heaters. Uranium-235 occurs in natural uranium at a concentration of about 0.7%.

In some embodiments, nuclear pebble heaters **2198** are acquired new (for example, right after production and before they have been used in a nuclear reactor). Nuclear pebble heaters **2198** are currently produced for use in pebble bed reactors. Nuclear pebble heaters **2198** enriched with 9% uranium-235 may, in some embodiments, be too powerful, produce too much heat, and/or produce heat for too long a time. For example, current commercially produced nuclear pebble heaters have about 9 g of uranium, which equates to a heat production of about 950 watts per pebble. In some embodiments, nuclear heater assembly **2192** requires about 300 watts of energy per foot. Therefore, filling a majority of fuel conduit **2196** with nuclear pebble heaters **2198** capable of producing 950 watts each may produce more heat than necessary to heat the subsurface formation to a desired temperature. In certain embodiments, however, methods or steps may be taken to produce desired energy outputs per foot in nuclear heater assembly **2192**.

In some embodiments, treatment of the subsurface formation requires heating the formation to a desired initial upper range (for example, from about 250° C. to about 350° C.). After heating the subsurface formation to the desired temperature range, the temperature may be maintained in the range for a desired time (for example, until a percentage of hydrocarbons have been pyrolyzed or an average temperature in the formation reaches a selected value). As the formation temperature rises, the heater temperature may be slowly lowered over a period of time. Currently, activated nuclear pebble heaters reach a natural heat output limit that results in a maximum temperature of the nuclear pebble heaters of about 900° C. As the uranium-235 fuel in the nuclear pebble heaters is depleted, the maximum heat output available from the nuclear pebble heaters decreases. The natural energy output curve of nuclear pebble heaters may be used to provide a desired heating versus time profile for certain subsurface formations.

Placing the nuclear pebble heaters in a hydrocarbon-rich zone may be desirable. The nuclear pebble heaters may be designed to provide a maximum heat output equivalent to the heat losses into the formation.

The nuclear pebble heaters have a temperature self-limiting effect due to what is Doppler broadening. Doppler broadening is the broadening of spectral lines due to the Doppler effect. The Doppler effect is described as the thermal movement of atoms or molecules and how that thermal movement shifts the apparent frequency of each emitter. The many different velocities of the thermal neutrons result in many small shifts, the cumulative effect of which is to broaden the line. The resulting line profile is known as a Doppler profile. The broadening may be dependent only on the wavelength of the line, the mass of the emitting particle, and the temperature. As the of the nuclear pebble heater temperature increases, more

thermal neutrons are absorbed by the uranium-238 atoms in the nuclear pebble heater, so less are available for fissioning the remaining uranium-235. In nuclear pebble heaters, the Doppler broadening effect reduces the power generated as the temperature of the nuclear pebble heaters increases.

When the nuclear pebble heater gets hotter, the accelerated motion of the atoms in the fuel increases the probability of neutron capture by uranium-238 atoms present in the nuclear pebble heater. Uranium-238, which typically forms the bulk of the uranium in the reactor, is much more likely to absorb fast neutrons. The neutrons absorbed by the uranium-238 reduces the number of neutrons available to cause remaining uranium-235 fission, thus reducing the power output by the nuclear pebble heater. This natural negative feedback limits the temperature that the individual nuclear pebble heaters can obtain.

As depicted in FIGS. **170-176**, includes one or more neutron reflectors **2200** and/or neutron moderators **2202**. Neutron moderators **2202** slow fast neutrons to thermal velocities that increase the likelihood of the neutrons to cause fission of uranium-235 nuclei. Nuclear heater assembly **2192** may include one or more spacers **2204** that are not involved in the nuclear process. Spacers **2204** may provide spacing between nuclear pebble heaters **2198** to control the amount of heat output per unit length provided by nuclear heater assembly **2192**. Spacers may be made of alumina, silica or other material. Neutron reflectors **2200** and/or moderators **2202** may be positioned in fuel conduit **2196**. Neutron moderators **2202** may be required to maintain sufficient thermal neutron flux of nuclear pebble heaters **2198** to sustain the fission reactions that produce heat.

Neutron reflectors **2200** may be formed from neutron reflective material. In some embodiments, neutron reflectors are formed from a similar material as is used to form fuel conduit **2196**. For example, may be formed from iron, beryllium, tungsten carbide, graphite, or mixtures thereof. Neutron moderators may be formed from graphite. Neutron reflectors and/or neutron moderators may be solid or hollow. Hollow neutron reflectors may be used so that the neutron reflectors are appropriately sized without using excess material, as well as, reducing the weight, transport costs, and/or production costs of the neutron reflectors. The neutron reflectors may reflect neutrons generated by a nuclear reaction in nuclear pebble heaters **2198**. In certain embodiments, neutron reflectors have a similar size and/or shape to nuclear pebble heaters **2198**. Neutron reflectors and/or neutron moderators may be spherical or other easily moved shaped to facilitate placement and/or removal in nuclear heater assembly **2192**.

Positioning one or more neutron reflectors and/or neutron moderators between nuclear pebble heaters **2198** in fuel conduit **2196** allows for the adjustment of the energy per unit length produced by the fuel conduit when the nuclear pebble heaters are positioned and activated. Activated nuclear pebble heaters **2198** have a decaying energy production curve over time. Nuclear pebble heaters are able to produce more energy earlier in their lifetime with their power output decreasing at a predictable rate throughout their lifetime. In some embodiments, as the power of a set of nuclear pebble heaters **2198** positioned in fuel conduit **2196** decreases over time, a number of neutron reflectors positioned between nuclear pebble heaters may be decreased. Decreasing the number of neutron reflectors may increase the density of nuclear pebble heaters (number of nuclear pebble heaters per unit length) in the fuel conduit and, thus, compensate for the natural decay of the nuclear pebble heaters over time. In some embodiments, as neutron reflectors are removed from the fuel conduit, additional nuclear pebble heaters may be positioned in the fuel conduit as required to achieve desired energy output.

As depicted in FIG. **172**, nuclear pebble heaters **2198** may be positioned between nuclear moderators **2202** in a middle portion of fuel conduit **2202** of the heater assembly to regulate heat production at the middle of nuclear heater assembly **2192**. In some embodiments nuclear moderators **2202** may be formed of graphite. The graphite may facilitate heat transfer and reflect neutrons. As depicted in FIG. **173**, nuclear moderators **2202** may be positioned between every two nuclear pebble heaters **2198** at the end of fuel conduit **2202** of the heater assembly. In some embodiments nuclear moderators **2202** may be formed of graphite to facilitate heat transfer and reflect neutrons. In some embodiments, the density of nuclear pebble heaters is increased near the ends of the elements positioned in fuel conduit **2196** to compensate for heat loss and achieve the desired energy output. One or more neutron reflectors **2200** (for example, spheres including tungsten carbide) may be positioned as the end members of the elements positioned in fuel conduit **2196**.

As depicted in FIG. **175**, nuclear pebble heaters **2198**, nuclear moderators **2202** and/or nuclear reflectors **2200** may be sized so to stack in fluid conduit **2202**. Stacking or packing of nuclear pebble heaters **2198**, nuclear moderators **2202** and/or nuclear reflectors **2200** may increase the solid angle thus increase heat production of the nuclear pebble heaters.

As depicted in FIG. **176**, outer conduit **2194** may be positioned in graphite-based cement casing **2208**. Outer conduit **2194** may include iron layer **2210** and stainless steel layer **2212**. Iron layer **2210** may reflect neutrons. Stainless steel layer **2212** may be positioned between iron layer **2210** and casing **2208** to inhibit corrosion of iron layer **2210**. Fuel conduit **2196** may include iron layer **2210'** to reflect neutrons back to the nuclear pebble heaters. Nuclear pebble heaters **2198** may be positioned between nuclear moderators **2202**. Nuclear reflectors **2200** may be positioned at the ends of the series of n nuclear pebble heaters **2198** and nuclear moderators **2202**.

In some embodiments, partially depleted nuclear pebble heaters are used to heat a subsurface formation. Nuclear pebble heaters **2198** may be acquired after they have been used for a time in a pebble bed modular reactor facility. The used nuclear pebble heaters **2198** may have their uranium-235 depleted from an initial value of about 9% to about 3%, from about 8% to about 4%, or from about 7% to about 5%. Partially depleted nuclear pebble heaters may produce less energy per nuclear pebble heater, which may allow the use of few or no nuclear reflectors in fuel conduit **2196**. Typically, depleted or partially depleted nuclear pebble heaters are disposed of by underground storage in a proper facility (for example, encasing the reactors in concrete under the ground). Operators of pebble bed modular reactor facilities usually have to incur significant expenses to properly dispose of the used nuclear pebble heaters. Therefore, partially depleted nuclear pebble heaters may be acquired for little or no cost from pebble bed modular reactor facilities. Acquiring partially depleted nuclear pebble heaters for little or no cost may reduce the costs of developing and treating the hydrocarbon subsurface formation and may utilize material that would otherwise be considered to be useless. In some embodiments, overall costs for developing and treating the subsurface formation may be decreased by as much as 95% using nuclear pebble heaters due to the cost of the energy required to heat the subsurface formation being drastically reduced, even if the nuclear pebble heaters are purchased new. Moreover, less carbon dioxide will be emitted during the in situ heat treat-

ment process when by using nuclear heaters as opposed to using electrical heaters, burners, or in situ combustion to heat the subsurface formation.

In some embodiments, as nuclear pebble heaters **2198** in fuel conduit **2196** are depleted in nuclear heater assembly **2192**, additional fuel conduits may be positioned in the outer conduit as needed. In one embodiment, as nuclear pebble heaters in a first fuel conduit have depleted to such an extent that the first fuel conduit does not produce a desired amount of heat per unit length, the first fuel conduit may be pulled from the formation, and a second fuel conduit containing a second set of nuclear pebble heaters may be inserted into nuclear heater assembly **2192**. The second fuel conduit and second set of nuclear pebble heaters may provide sufficient heat output to heat the formation as desired. In some embodiments, two or more fuel conduits containing nuclear pebble heaters may be positioned in the nuclear heater assembly to increase the heat output from the nuclear heater assembly. Outer conduit **2194** may have an initial size that accommodates two or more fuel conduits.

In some embodiment, nuclear pebble heaters **2198** are specifically designed for nuclear heater assembly **2192**. Special order nuclear pebble heaters may be produced with an appropriate amount of enriched uranium for the desired heat output of nuclear heater assembly **2192**.

In some embodiments, heat transfer fluid **2206** is used in nuclear heater assembly **2192**. Heat transfer fluid **2206** may be supplied to outer conduit **2194** and function to ensure even heating of the subsurface formation from nuclear pebble materials **2198** in fuel conduit **2196**. In some embodiments, one or more nuclear pebble heaters **2198** in fuel conduit **2196** may produce more energy than other nuclear pebble heaters in the fuel conduit leading to potential hot spots in the fuel conduit. Hot spots are areas where one or more nuclear pebble heaters are producing more heat than adjacent nuclear pebble heaters. Heat transfer fluid **2206** circulated through outer conduit **2194** over fuel conduit **2196** may help reduce the effect of hot spots along the fuel conduit. In certain embodiments, heat transfer fluid **2206** includes non-reactive fluids or non-radioactive isotope forming fluids. For example, heat transfer fluid **2206** may include helium gas. Helium gas may inhibit corrosion (for example, oxidation of carbon) of the nuclear pebble heaters at elevated temperatures. Convection and/or conduction of heat by helium gas may smooth temperature profile inside the nuclear heater assembly. In some embodiments, nuclear pebble heater positioning systems are used to periodically reposition activated nuclear pebble heaters **2198** in fuel conduit **2196**, and to move the nuclear pebble heaters to prevent the development of hot spots.

In some embodiments, heat transfer fluid **2206** is sealed within outer conduit **2194** without the assistance of additional systems to help circulate the fluids. In certain embodiments, heat fluid circulation systems are employed to ensure heat transfer fluid **2206** is circulated evenly throughout outer conduit **2194**. The circulation system may be positioned in nuclear heater assembly **2192** (for example, in the outer conduit). In some embodiments, the circulation system is positioned on the surface and exterior to the nuclear heater assembly.

In some embodiments, the circulation system is used to regulate the temperature of nuclear heater assembly **2192**. For example, the circulation system may be used to remove heat produced by the nuclear pebble heaters to limit the heat output available to transfer to the formation. The amount of heat removed may be adjusted by controlling the flow rate of heat transfer fluid through the nuclear heater assembly. The heat removed by the heat transfer fluid may be converted to electricity (for example, using a Kalina and/or Rankine cycle) and/or used to heat other portions of the subsurface formation.

In some embodiments, nuclear pebble heaters **2198** require neutron activation before they will produce heat. Before activation, the nuclear pebble materials may not be thermally hot. In embodiments where unactivated nuclear pebble materials are employed in nuclear heater assembly **2192**, the nuclear heater assembly may include an activation source. The activation source may function as a neutron source capable of initiating the nuclear reaction in the nuclear pebble heaters **2198**. The activation source may be shielded until used.

The activation source may be positioned in nuclear heater assembly **2192**. The activation source may be used to activate nuclear pebble heaters **2198** after they have been positioned in fuel conduit **2196**. In some embodiments, the activation source is used to activate nuclear pebble heaters **2198** as they are positioned in fuel conduit **2196**. The activation source may include a neutron emitting material (for example, californium-252) or a controlled neutron source (for example, a 14 MeV minitron neutron generator). The activation source may be located downhole and then withdrawn from the well (for example, on wireline). The activation source may be located in another coiled tubing that is later withdrawn from the well. The activation source, such as the minitron, may be located at the wellhead. The minitron may activate the nuclear pebble heaters as the nuclear pebble heaters are moved into the formation.

Handling systems for the nuclear pebble heaters may be automated or semi-automated. In some embodiments, upon completion of the treatment of the subsurface formation using nuclear heater assembly **2192**, the assembly may be permanently sealed and capped leaving the activated nuclear pebble in the formation. For example, nuclear heater assembly **2192** may be sealed by filling the outer conduit with concrete.

In some in situ heat treatment embodiments, compressors provide compressed fluid to the treatment area. For example, compressors may be used to provide oxidizing fluid **808** and/or fuel **804** to oxidizers **802** depicted in FIG. **146**. Also, compressors **876** may be used to supply heat transfer fluid to the formation as depicted in FIG. **166**.

A significant cost of the in situ heat treatment process may be operating the compressor over the life of the in situ heat treatment process if conventional electrical energy sources are used to power the compressors of the in situ heat treatment process. In some embodiments, nuclear power may be used to generate electricity that operates the compressors needed for the in situ heat treatment process. The nuclear power may be supplied by one or more nuclear reactors. The nuclear reactors may be light water reactors, pebble bed reactors, and/or other types of nuclear reactors. The nuclear reactors may be located at or near to the in situ heat treatment process site. Locating the nuclear reactors at or near to the in situ heat treatment process site may reduce equipment costs and electrical transmission losses over long distances. The use of nuclear power may reduce or eliminate the amount of carbon dioxide generation associated with operating the compressors over the life of the in situ heat treatment process.

Excess electricity generated by the nuclear reactors may be used for other in situ heat treatment process needs. For example, excess electricity may be used to cool fluid for forming a low temperature barrier (frozen barrier) around treatment areas, and/or for providing electricity to treatment facilities located at or near the in situ heat treatment process site. In some embodiments, the electricity or excess electric-

ity produced by the nuclear reactors may be used to resistively heat the conduits used to circulate heat transfer fluid through the treatment area.

In some embodiments, excess heat available from the nuclear reactors may be used for other in situ processes. For example, excess heat may be used to heat water or make steam that is used in solution mining processes. In some embodiments, excess heat from the nuclear reactors may be used to heat fluids used in the treatment facilities located near or at the in situ heat treatment site.

Circulation systems may be used to heat portions of the formation. Production wells in the formation are used to remove produced fluids. After production from the formation has ended, the circulation system may be used to recover heat from the formation. FIG. **166** depicts an embodiment of a circulation system. Heat transfer fluid may be circulated through heaters **760** after heat supply **870** is disconnected from the circulation system. The heat transfer fluid may be a different heat transfer fluid than the heat transfer fluid used to heat the formation. Heat transfers from the heated formation to the heat transfer fluid. The heat transfer fluid may be used to heat another portion of the formation or the heat transfer fluid may be used for other purposes. In some embodiments, water is introduced into heaters **760** to produce steam. In some embodiments, low temperature steam is introduced into heaters **760** so that the passage of the steam through the heaters increases the temperature of the steam. Other heat transfer fluids including natural or synthetic oils, such as Syltherm oil (Dow Corning Corporation (Midland, Mich., U.S.A.), may be used instead of steam or water.

In some embodiments, the circulation system may be used in conjunction with electrical heating. In some embodiments, at least a portion of the pipe in the U-shaped wellbores adjacent to portions of the formation that are to be heated is made of a ferromagnetic material. For example, the piping adjacent to a layer or layers of the formation to be heated is made of 9% to 13% chromium steel, such as 410 stainless steel. The pipe may be a temperature limited heater when time varying electric current is applied to the piping. The time varying electric current may resistively heat the piping, which heats the formation. In some embodiments, direct electric current may be used to resistively heat the piping, which heats the formation.

In some embodiments, the circulation system is used to heat the formation to a first temperature, and electrical energy is used to maintain the temperature of the formation and/or heat the formation to higher temperatures. The first temperature may be sufficient to vaporize aqueous formation fluid in the formation. The first temperature may be at most about 200° C., at most about 300° C., at most about 350° C., or at most about 400° C. Using the circulation system to heat the formation to the first temperature allows the formation to be dry when electricity is used to heat the formation. Heating the dry formation may minimize electrical current leakage into the formation.

In some embodiments, the circulation system and electrical heating may be used to heat the formation to a first temperature. The formation may be maintained, or the temperature of the formation may be increased from the first temperature, using the circulation system and/or electrical heating. In some embodiments, the formation may be raised to the first temperature using electrical heating, and the temperature may be maintained and/or increased using the circulation system. Economic factors, available electricity, availability of fuel for heating the heat transfer fluid, and other factors may be used to determine when electrical heating and/or circulation system heating are to be used.

In certain embodiments, the portion of heater **760** in hydrocarbon layer **460** is coupled to lead-in conductors. Lead-in conductors may be located in overburden **458**. Lead-in conductors may electrically couple the portion of heater **760** in hydrocarbon layer **460** to one or more wellheads at the surface. Electrical isolators may be located at a junction of the portion of heater **760** in hydrocarbon layer **460** with portions of heater **760** in overburden **458** so that the portions of the heater in the overburden are electrically isolated from the portion of the heater in the hydrocarbon layer. In some embodiments, the lead-in conductors are placed inside of the pipe of the closed loop circulation system. In some embodiments, the lead-in conductors are positioned outside of the pipe of the closed loop circulation system. In some embodiments, the lead-in conductors are insulated conductors with mineral insulation, such as magnesium oxide. The lead-in conductors may include highly electrically conductive materials such as copper or aluminum to reduce heat losses in overburden **458** during electrical heating.

In certain embodiments, the portions of heater **760** in overburden **458** may be used as lead-in conductors. The portions of heater **760** in overburden **458** may be electrically coupled to the portion of heater **760** in hydrocarbon layer **460**. In some embodiments, one or more electrically conducting materials (such as copper or aluminum) are coupled (for example, cladded or welded) to the portions of heater **760** in overburden **458** to reduce the electrical resistance of the portions of the heater in the overburden. Reducing the electrical resistance of the portions of heater **760** in overburden **458** reduces heat losses in the overburden during electrical heating.

In some embodiments, the portion of heater **760** in hydrocarbon layer **460** is a temperature limited heater with a self-limiting temperature between about 600° C. and about 1000° C. The portion of heater **760** in hydrocarbon layer **460** may be a 9% to 13% chromium stainless steel. For example, portion of heater **760** in hydrocarbon layer **460** may be 410 stainless steel. Time-varying current may be applied to the portion of heater **760** in hydrocarbon layer **460** so that the heater operates as a temperature limited heater.

FIG. **177** depicts a side view representation of an embodiment of a system for heating a portion of a formation using a circulated fluid system and/or electrical heating. Wellheads **450** of heaters **760** may be coupled to heat transfer fluid circulation system **868** by piping. Wellheads **450** may also be coupled to electrical power supply system **908**. In some embodiments, heat transfer fluid circulation system **868** is disconnected from the heaters when electrical power is used to heat the formation. In some embodiments, electrical power supply system **908** is disconnected from the heaters when heat transfer fluid circulation system **868** is used to heat the formation.

Electrical power supply system **908** may include transformer **728** and cables **722**, **724**. In certain embodiments, cables **722**, **724** are capable of carrying high currents with low losses. For example, cables **722**, **724** may be thick copper or aluminum conductors. The cables may also have thick insulation layers. In some embodiments, cable **722** and/or cable **724** may be superconducting cables. The superconducting cables may be cooled by liquid nitrogen. Superconducting cables are available from Superpower, Inc. (Schenectady, N.Y., U.S.A.). Superconducting cables may minimize power loss and/or reduce the size of the cables needed to couple transformer **728** to the heaters. In some embodiments, cables **722**, **724** may be made of carbon nanotubes.

In some embodiments, geothermal energy may be used to heat or preheat a treatment area of an in situ heat treatment process or a treatment area to be solution mined. Geothermal

energy may have little or no carbon dioxide emissions. In some embodiments, hot fluid may be produced from a layer or layers located below or near the treatment area. The hot fluid may be steam, water, and/or brine. One or more of the layers may be geothermally pressurized geysers. Hot fluid may be pumped from one or more of the layers. The layer or layers may be 2 km, 4 km, 8 km or more below the surface. The hot fluid may be at a temperature of over 100° C., over 200° C., or over 300° C.

The hot fluid may be produced and circulated through piping in the treatment area to raise the temperature of the treatment area. In some embodiments, the hot fluid is introduced directly into the treatment area. In some embodiments, the hot fluid is circulated through the treatment area or piping in the treatment area without being produced to the surface and re-introduced into the treatment area. In some embodiments, the hot fluid may be produced from a location near the treatment area. The hot fluid may be transported to the treatment area. Once transported to the treatment area, the hot fluid is circulated through piping in the treatment area or the hot fluid is introduced directly into the treatment area.

In some embodiments, hot fluid produced from a layer or layers is used to solution mine minerals from the formation. The hot fluid may be used to raise the temperature of the formation to a temperature below the dissociation temperature of the minerals but to a temperature high enough to increase the amount of mineral going into solution in a first fluid introduced into the formation. The hot fluid may be introduced directly into the formation as all or a portion of the first fluid, or the hot fluid may be circulated through piping in the formation.

In some embodiments, hot fluid produced from a layer or layers may be used to heat the treatment area before using electrical energy or other types of heat sources to heat the treatment area to pyrolysis temperatures. The hot fluid may not be at a temperature sufficient to raise the temperature of the treatment area to pyrolysis temperatures. Using the hot fluid to heat the treatment area before using electrical heaters or other heat sources to heat the treatment area to pyrolysis temperatures may reduce energy costs for the in situ heat treatment process.

In some embodiments, hot dry rock technology may be used to produce steam or other hot heat transfer fluid from a deep portion of the formation. Injection wells may be drilled to a depth where the formation is hot. The injection wells may be over 2 km, over 4 km, or over 8 km deep. Sections of the formation adjacent to the bottom portions of the injection wells may be hydraulically or otherwise fractured to provide large contact area with the formation and/or to provide flow paths to heated fluid production wells. Water, steam and/or other heat transfer fluid may be introduced into the formation through the injection wells. Heat transfers to the introduced fluid from the formation. Steam and/or hot heat transfer fluid may be produced from the heated fluid production wells. In some embodiments, the steam and/or hot heat transfer fluid is directed into the treatment area from the production wells without first producing the steam and/or hot heat transfer fluid to the surface. The steam and/or hot heat transfer fluid may be used to heat a portion of a hydrocarbon containing formation above the deep hot portion of the formation.

In some embodiments, steam produced from heated fluid production wells may be used as the steam for a drive process (for example, a steam flood process or steam assisted gravity drainage process). In some embodiments, steam or other hot heat transfer fluid produced through heated fluid production wells is passed through U-shaped wellbores or other types of wellbores to provide initial heating to the formation. In some embodiments, cooled steam or water, or cooled heat transfer fluid, resulting from the use of the steam and/or heat transfer fluid from the hot portion of the formation may be collected and sent to the hot portion of the formation to be reheated.

In certain embodiments, a controlled or staged in situ heating and production process is used to in situ heat treat a hydrocarbon containing formation (for example, an oil shale formation). The staged in situ heating and production process may use less energy input to produce hydrocarbons from the formation than a continuous or batch in situ heat treatment process. In some embodiments, the staged in situ heating and production process is about 30% more efficient in treating the formation than the continuous or batch in situ heat treatment process. The staged in situ heating and production process may also produce less carbon dioxide emissions than a continuous or batch in situ heat treatment process. In certain embodiments, the staged in situ heating and production process is used to treat rich layers in the oil shale formation. Treating only the rich layers may be more economical than treating both rich layers and lean layers because heat may be wasted heating the lean layers.

FIG. **178** depicts a top view representation of an embodiment for the staged in situ heating and producing process for treating the formation. In certain embodiments, heaters **716** are arranged in triangular patterns. In other embodiments, heaters **716** are arranged in any other regular or irregular patterns. The heater patterns may be divided into one or more sections **910**, **912**, **914**, **916**, and/or **918**. The number of heaters **716** in each section may vary depending on, for example, properties of the formation or a desired heating rate for the formation. One or more production wells **206** may be located in each section **910**, **912**, **914**, **916**, and/or **918**. In certain embodiments, production wells **206** are located at or near the centers of the sections. In some embodiments, production wells **206** are in other portions of sections **910**, **912**, **914**, **916**, and **918**. Production wells **206** may be located at other locations in sections **910**, **912**, **914**, **916**, and/or **918** depending on, for example, a desired quality of products produced from the sections and/or a desired production rate from the formation.

In certain embodiments, heaters **716** in one of the sections are turned on while the heaters in other sections remain turned off. For example, heaters **716** in section **910** may be turned on while the heaters in the other sections are left turned off. Heat from heaters **716** in section **910** may create permeability, mobilize fluids, and/or pyrolysis fluids in section **910**. While heat is being provided by heaters **716** in section **910**, production well **206** in section **912** may be opened to produce fluids from the formation. Some heat from heaters **716** in section **910** may transfer to section **912** and "pre-heat" section **912**. The pre-heating of section **912** may create permeability in section **912**, mobilize fluids in section **912**, and allow fluids to be produced from the section through production well **206**. As fluids are produced from section **912**, the movement of fluids from section **910** to section **912** transfers heat between the sections. The movement of the hot fluids through the formation increases heat transfer within the formation. Allowing hot fluids to flow between the sections uses the energy of the hot fluids for heating of unheated sections rather than removing the heat from the formation by producing the hot fluids directly from section **910**. Thus, the movement of the hot fluids allows for less energy input to get production from the formation than is required if heat is provided from heaters **716** in both sections to get production from the sections.

In some embodiments, section **910** and/or section **912** may be treated prior to turning on heaters **716** to increase the permeability in the sections. For example, the sections may be dewatered to increase the permeability in the sections. In

some embodiments, steam injection or other fluid injection may be used to increase the permeability in the sections.

In certain embodiments, after a selected time, heaters **716** in section **912** are turned on. Turning on heaters **716** in section **912** may provide additional heat to sections **910** and **912** to increase the permeability, mobility, and/or pyrolysis of fluids in these sections. In some embodiments, as heaters **716** in section **912** are turned on, production in section **912** is turned off (shut down) and production well **206** in section **914** is opened to produce fluids from the formation. Thus, fluid flow in the formation towards production well **206** in section **914** and section **914** is heated by the flow of hot fluids as described above for section **912**. In some embodiments, production well **206** in section **912** may be left open after the heaters are turned on in the section, if desired. This process may be repeated for subsequent sections in the formation. For example, after a selected time, heaters in section **914** may be turned on and fluids produced from production well **206** in section **916** and so on through the formation.

In some embodiments, heat is provided by heaters **716** in alternating sections (for example, sections **910**, **914**, and **918**) while fluids are produced from the sections in between the heated sections (for example, sections **912** and **916**). After a selected time, heaters **716** in the unheated sections (sections **912** and **916**) are turned on and fluids are produced from one or more of the sections as desired.

In certain embodiments, a smaller heater spacing is used in the staged in situ heating and producing process than in the continuous or batch in situ heat treatment processes. For example, the continuous or batch in situ heat treatment process may use a heater spacing of about 12 m while the in situ staged heating and producing process uses a heater spacing of about 10 m. The staged in situ heating and producing process may use the smaller heater spacing because the staged process allows for relatively rapid heating of the formation and expansion of the formation.

In some embodiments, the sequence of heated sections begins with the outermost sections and moves inwards. For example, for a selected time, heat may be provided by heaters **716** in sections **910** and **918** as fluids are produced from sections **912** and **916**. After the selected time, heaters **716** in sections **912** and **916** may be turned on and fluids are produced from section **914**. After another selected amount of time, heaters **716** in section **914** may be turned on, if needed.

In certain embodiments, sections **910-918** are substantially equal sized sections. The size and/or location of sections **910-918** may vary based on desired heating and/or production from the formation. For example, simulation of the staged in situ heating and production process treatment of the formation may be used to determine the number of heaters in each section, the optimum pattern of sections and/or the sequence for heater power up and production well startup for the staged in situ heating and production process. The simulation may account for properties such as, but not limited to, formation properties and desired properties and/or quality in the produced fluids. In some embodiments, heaters **716** at the edges of the treated portions of the formation (for example, heaters **716** at the left edge of section **910** or the right edge of section **918**) may have tailored or adjusted heat outputs to produce desired heat treatment of the formation.

In some embodiments, the formation is sectioned into a checkerboard pattern for the staged in situ heating and production process. FIG. **179** depicts a top view of rectangular checkerboard pattern **920** embodiment for the staged in situ heating and production process. In some embodiments, heaters in the "A" sections (sections **910**A, **912**A, **914**A, **916**A, and **918**A) may be turned on and fluids are produced from the "B" sections (sections **910**B, **912**B, **914**B, **916**B, and **918**B). After the selected time, heaters in the "B" sections may be turned on. The size and/or number of "A" and "B" sections in rectangular checkerboard pattern **920** may be varied depending on factors such as, but not limited to, heater spacing, desired heating rate of the formation, desired production rate, size of treatment area, subsurface geomechanical properties, subsurface composition, and/or other formation properties.

In some embodiments, heaters in sections **910**A are turned on and fluids are produced from sections **910**B and/or sections **912**B. After the selected time, heaters in sections **912**A may be turned on and fluids are produced from sections **912**B and/or **914**B. After another selected time, heaters in sections **914**A may be turned on and fluids are produced from sections **914**B and/or **916**B. After another selected time, heaters in sections **916**A may be turned on and fluids are produced from sections **916**B and/or **918**B. In some embodiments, heaters in a "B" section that has been produced from may be turned on when heaters in the subsequent "A" section are turned on. For example, heaters in section **910**B may be turned on when the heaters in section **912**A are turned on. Other alternating heater startup and production sequences may also be contemplated for the in situ staged heating and production process embodiment depicted in FIG. **179**.

In some embodiments, the formation is divided into a circular, ring, or spiral pattern for the staged in situ heating and production process. FIG. **180** depicts a top view of the ring pattern embodiment for the staged in situ heating and production process. Sections **910**, **912**, **914**, **916**, and **918** may be treated with heater startup and production sequences similar to the sequences described above for the embodiments depicted in FIG. **178**. The heater startup and production sequences for the embodiment depicted in FIG. **180** may start with section **910** (going inwards towards the center) or with section **918** (going outwards from the center). Starting with section **910** may allow expansion of the formation as heating moves towards the center of the ring pattern. Shearing of the formation may be minimized or inhibited because the formation is allowed to expand into heated and/or pyrolyzed portions of the formation. In some embodiments, the center section (section **918**) is cooled after treatment.

FIG. **181** depicts a top view of a checkerboard ring pattern embodiment for the staged in situ heating and production process. The embodiment depicted in FIG. **181** divides the ring pattern embodiment depicted in **180** into a checkerboard pattern similar to the checkerboard pattern depicted in FIG. **179**. Sections **910**A, **912**A, **914**A, **916**A, **918**A, **910**B, **912**B, **914**B, **916**B, and **918**B, depicted in **181**, may be treated with heater startup and production sequences similar to the sequences described above for the embodiment depicted in **179**.

In some embodiments, fluids are injected to drive fluids between sections of the formation. Injecting fluids such as steam or carbon dioxide may increase the mobility of hydrocarbons and may increase the efficiency of the staged in situ heating and production process. In some embodiments, fluids are injected into the formation after the in situ heat treatment process to recover heat from the formation. In some embodiments, the fluids injected into the formation for heat recovery include some fluids produced from the formation (for example, carbon dioxide, water, and/or hydrocarbons produced from the formation). In some embodiments, the embodiments depicted in FIGS. **178-181** are used for in situ solution mining of the formation. Hot water or another fluid may be used to get permeability in the formation at low temperatures for solution mining.

In certain embodiments, several rectangular checkerboard patterns (for example, rectangular checkerboard pattern **920** depicted in FIG. **179**) are used to treat a treatment area of the formation. FIG. **182** depicts a top view of a plurality of rectangular checkerboard patterns **920**(**1**-**36**) in treatment area **882** for the staged in situ heating and production process. Treatment area **882** may be enclosed by barrier **922**. Each of rectangular checkerboard patterns **920**(**1**-**36**) may individually be treated according to embodiments described above for the rectangular checkerboard patterns.

In certain embodiments, the startup of treatment of rectangular checkerboard patterns **920**(**1**-**36**) proceeds in a sequential process. The sequential process may include starting the treatment of each of the rectangular checkerboard patterns one by one sequentially. For example, treatment of a second rectangular checkerboard pattern (for example, the onset of heating of the second rectangular checkerboard pattern) may be started after treatment of a first rectangular checkerboard pattern and so on. The startup of treatment of the second rectangular checkerboard pattern may be at any point in time after the treatment of the first rectangular checkerboard pattern has begun. The time selected for startup of treatment of the second rectangular checkerboard pattern may be varied depending on factors such as, but not limited to, desired heating rate of the formation, desired production rate, subsurface geomechanical properties, subsurface composition, and/or other formation properties. In some embodiments, the startup of treatment of the second rectangular checkerboard pattern begins after a selected amount of fluids have been produced from the first rectangular checkerboard pattern area or after the production rate from the first rectangular checkerboard pattern increases above a selected value or falls below a selected value.

In some embodiments, the startup sequence for rectangular checkerboard patterns **920**(**1**-**36**) is arranged to minimize or inhibit expansion stresses in the formation. In an embodiment, the startup sequence of the rectangular checkerboard patterns proceeds in an outward spiral sequence, as shown by the arrows in FIG. **182**. The outward spiral sequence proceeds sequentially beginning with treatment of rectangular checkerboard pattern **920**-**1**, followed by treatment of rectangular checkerboard pattern **920**-**2**, rectangular checkerboard pattern **920**-**3**, rectangular checkerboard pattern **920**-**4**, and continuing the sequence up to rectangular checkerboard pattern **920**-**36**. Sequentially starting the rectangular checkerboard patterns in the outwards spiral sequence may minimize or inhibit expansion stresses in the formation.

Starting treatment in rectangular checkerboard patterns at or near the center of treatment area **882** and moving outwards maximizes the starting distance from barrier **922**. Barrier **922** may be most likely to fail when heat is provided at or near the barrier. Starting treatment/heating at or near the center of treatment area **882** delays heating of rectangular checkerboard patterns near barrier **922** until later times of heating in treatment area **882** or at or near the end of production from the treatment area. Thus, if barrier **922** does fail, the failure of the barrier occurs after a significant portion of treatment area **882** has been treated.

Starting treatment in rectangular checkerboard patterns at or near the center of treatment area **882** and moving outwards also creates open pore space in the inner portions of the outward moving startup pattern. The open pore space allows portions of the formation being started at later times to expand inwards into the open pore space and, for example, minimize shearing in the formation.

In some embodiments, support sections are left between one or more rectangular checkerboard patterns **920**(**1**-**36**). The support sections may be unheated sections that provide support against geomechanical shifting, shearing, and/or expansion stress in the formation. In some embodiments, some heat may be provided in the support sections. The heat provided in the support sections may be less than heat provided inside rectangular checkerboard patterns **920**(**1**-**36**). In some embodiments, each of the support sections may include alternating heated and unheated sections. In some embodiments, fluids are produced from one or more of the unheated support sections.

In some embodiments, one or more of rectangular checkerboard patterns **920**(**1**-**36**) have varying sizes. For example, the outer rectangular checkerboard patterns (such as rectangular checkerboard patterns **920**(**21**-**26**) and rectangular checkerboard patterns **920**(**31**-**36**)) may have smaller areas and/or numbers of checkerboards. Reducing the area and/or the number of checkerboards in the outer rectangular checkerboard patterns may reduce expansion stresses and/or geomechanical shifting in the outer portions of treatment area **882**. Reducing the expansion stresses and/or geomechanical shifting in the outer portions of treatment area **882** may minimize or inhibit expansion stress and/or shifting stress on barrier **922**.

FIG. **183** depicts a side view representation of an embodiments for producing mobilized fluids from the hydrocarbon formation. In FIG. **183**, heaters **716** have substantially horizontal heating sections in hydrocarbon layer **460** (as shown, the heaters have heating sections that go into and out of the page). Heaters **716** provide heat to first section **2100** of hydrocarbon layer **460**. Patterns of heaters, such as triangles, squares, rectangles, hexagons, and/or octagons may be used within first section **2100**. First section **2100** may be heated at least to temperatures sufficient to mobilize some hydrocarbons within the first section. In some embodiments, temperature within first section **2100** may be increased to a pyrolyzation temperature.

In some embodiments, formation fluid is produced from first section **2100**. The formation fluid may be produced through production wells **206**. In some embodiments, the formation fluid is mobilized fluid. The mobilized fluid may include heavy hydrocarbons. An API gravity of the first mixture may be less than about 20°, less than about 15°, or less than about 10°. In some embodiments, the formation fluid includes at least some pyrolyzed hydrocarbons. Some hydrocarbons may be pyrolyzed in portions of first section **2100** that are at higher temperatures than a remainder of the first section. For example, portions of formation adjacent heaters **716** may be at somewhat higher temperatures than the remainder of first section **2100**. The higher temperature of the formation adjacent to heaters **716** may be sufficient to cause pyrolysis of hydrocarbons. Some of the pyrolysis product may be produced through production wells **206**.

One or more sections (for example, second section **2102** and/or third section **2104**) may be above or proximate to first section **2100**. Some heat from first section **2100** may transfer to second section **2102** and third section **2104**. In some embodiments, sufficient heat may transfer from first section **2100** to allow for recovery of some hydrocarbons from second section **2102** and/or third section **2104**.

In some embodiments, heat from first section **2100** may mobilize or substantially mobilize fluid in second section **2102** and/or third section **2104**. In some embodiments, a mobilization fluid is provided to second section **2102** and/or third section **2104** through injection wells **748**A, **748**B to increase mobilization of hydrocarbons within the second section or the third section. Mobilization fluids include, but are not limited to, water, hydrocarbons, surfactants, polymers,

carbon disulfide, or mixtures thereof. The mobilization fluid may increase a flow of mobilized hydrocarbons into first section **2100**. For example, a pressure gradient may be produced between second section **2102** and/or **2104** and first section **2100** such that the flow of fluids from the second section and/or third section to the first section is increased. The mobilization fluid may solubilize a portion of the hydrocarbons in second section **2102** and/or third section **2104** to form a mixture. Solubilization of hydrocarbons in second section **2102** and/or third section **2104** may allow the hydrocarbons to be produced from the second section and/or third section without direct heating of the sections.

Enhanced hydrocarbon recovery methods may be used to produce additional hydrocarbons from portions of the formation adjacent to treatment areas treated using in situ heat treatment processes. Systems and methods for enhanced hydrocarbons recovery are described in U.S. Pat. No. 3,943,160 to Farmer et al.; U.S. Pat. No. 3,946,812 to Gale et al.; U.S. Pat. No. 4,077,471 to Shupe et al.; U.S. Pat. No. 4,216,079 to Newcombe; U.S. Pat. No. 5,318,709 to Wuest et al.; U.S. Pat. No. 5,723,423 to Van Slyke; U.S. Pat. No. 6,022,834 to Hsu et al.; U.S. Pat. No. 6,269,881 to Chou et al.; and U.S. Pat. No. 7,055,0602 to Shpakoff et al., all of which are incorporated by reference herein.

In some embodiments, second section **2102** and/or third section **2104** may be treated with a water flood. The water flood may include injecting water into a portion of second section **2102** and/or third section **2104** through injection wells **748**A, **748**B. Flooding of at least a selected section of second section **2102** and/or third section **2104** may water wet a portion of the sections. The water wet portions of the selected section may be pressurized by known methods and a water/hydrocarbon mixture may be collected using one or more production wells.

In certain embodiments, second section **2102** and/or third section **2104** may be treated with a hydrocarbon flood (for example, naphtha, kerosene, diesel, vacuum gas oil, or a mixture thereof). In some embodiments, the hydrocarbons have an aromatic content of at least 1% by weight, at least 5% by weight, at least 10% by weight, at least 20% by weight or at least 25% by weight. A hydrocarbon flood may include injecting hydrocarbons into a portion of second section **2102** and/or third section **2104** through injection wells **748**A, **748**B. In some embodiments, the hydrocarbons are produced from first section **2100** and/or other portions of the formation. In certain embodiments, the hydrocarbons are produced from the formation, treated to remove heavy fractions of hydrocarbons (for example, asphaltenes, hydrocarbons having a boiling point of at least 300° C., of at least 400° C., at least 500° C., or at least 600° C.) and the hydrocarbons are re-introduced into the formation. In some embodiments, one section may be treated with a hydrocarbon flood while another section is treated with water flood. In some embodiments, water flooding of a section may be alternated with hydrocarbon flooding of the section.

In an embodiment, a blend made from hydrocarbon mixtures produced from first section **2100** may be used as a mobilization fluid. The blend may include about 20 weight % light hydrocarbons (or blending agent) or greater (for example, about 50 weight % or about 80 weight % light hydrocarbons) and about 80 weight % heavy hydrocarbons or less (for example, about 50 weight % or about 20 weight % heavy hydrocarbons). The weight percentage of light hydrocarbons and heavy hydrocarbons may vary depending on, for example, a weight distribution (or API gravity) of light and heavy hydrocarbons, a relative stability of the blend or a desired API gravity of the blend. For example, in some embodiments, the weight percentage of light hydrocarbons in the blend may be less than 50 weight % or less than 20 weight %. In certain embodiments, the weight percentage of light hydrocarbons may be selected to mix the least amount of light hydrocarbons with heavy hydrocarbons that produces a blend with a desired density or viscosity.

Production from second section **2102** and/or third section **2104** may be enhanced by treating the sections with a polymer and/or monomer that mobilizes hydrocarbons towards one or more production wells. The polymer and/or monomer may reduce the mobility of a water phase in pores of the hydrocarbon containing formation. The reduction of water mobility may allow the hydrocarbons to be more easily mobilized through the hydrocarbon containing formation. Polymers that may be used include, but are not limited to, polyacrylamides, partially hydrolyzed polyacrylamide, polyacrylates, ethylenic copolymers, biopolymers, carboxymethylcellulose, polyvinyl alcohol, polystyrene sulfonates, polyvinylpyrrolidone, AMPS (2-acrylamide-2-methyl propane sulfonate) or combinations thereof. Examples of ethylenic copolymers include copolymers of acrylic acid and acrylamide, acrylic acid and lauryl acrylate, lauryl acrylate and acrylamide. Examples of biopolymers include xanthan gum and guar gum. In some embodiments, polymers may be crosslinked in situ in the hydrocarbon containing formation. In other embodiments, polymers may be generated in situ in the hydrocarbon containing formation. Polymers and polymer preparations for use in oil recovery are described in U.S. Pat. No. 6,427,268 to Zhang et al.; U.S. Pat. No. 6,439,308 to Wang; U.S. Pat. No. 5,654,261 to Smith; U.S. Pat. No. 5,284,206 to Surles et al.; U.S. Pat. No. 5,199,490 to Surles et al.; and U.S. Pat. No. 5,103,909 to Morgenthaler et al., all of which are incorporated by reference herein.

In some embodiment, the mobilization fluid may include one or more nonionic additives (for example, alcohols, ethoxylated alcohols, nonionic surfactants and/or sugar based esters). In some embodiments, the mobilization fluid may include one or more anionic surfactants (for example, sulfates, sulfonates, ethoxylated sulfates, and/or phosphates).

In some embodiments, the mobilization fluid may include carbon disulfide. Hydrogen sulfide, in addition to other sulfur compounds produced from the formation, may be converted to carbon disulfide using known methods. Suitable methods may include oxidation reaction of the sulfur compound to sulfur and/or sulfur dioxides, and by reaction of sulfur and/or sulfur dioxides with carbon and/or a carbon containing compound to form the carbon disulfide formulation. The conversion of the sulfur compounds to carbon disulfide and the use of the carbon disulfide for oil recovery are described in U.S. Patent Publication No. 2006/0254769 to Van Dorp et al., which is incorporated by reference as if fully set forth herein. The carbon disulfide may be introduced into second section **2102** and/or third section **2104** as a mobilization fluid.

In certain embodiments, formation fluid is produced from first section **2100**, second section **2102** and/or third section **2104**. The formation fluid may be produced through production wells **206**A, **206**B, **206**C. The formation fluid produced from second section **2102** and/or third section **2104** may include mobilization fluid, hydrocarbons from the second section **2102** and/or third section **2104**, hydrocarbons from first section **2100**, or mixtures thereof.

Producing fluid from production wells in first section **2100** may lower the average pressure in the formation by forming an expansion volume for fluids heated in adjacent sections of the formation. Thus, producing fluid from production wells in the first section **2100** may establish a pressure gradient in the

formation that draws mobilized fluid from second section **2102** and/or third section **2104** into the first section.

In some embodiments, a pressurizing fluid is provided in second section **2102** and/or third section **2104** (for example, through injection wells **748**A, **748**B) to increase mobilization of hydrocarbons within the sections. The pressurizing fluid may enhance the pressure gradient in the formation to flow mobilized hydrocarbons into first section **2100**. In certain embodiments, the production of fluids from first section **2100** allows the pressure in second section **2102** and/or third section **2104** to remain below a selected pressure (for example, a pressure below which fracturing of the overburden and/or underburden may occur).

Hydrocarbons may be produced from first section **2100**, second section **2102** and/or third section **2104** such that at least about 30% by weight, at least about 40%, or at least about 50% by weight of the initial mass of hydrocarbons in the formation are produced. In other embodiments, at least about 60% by weight or at least about 70% by weight of the initial mass of hydrocarbons in the formation are produced.

In certain embodiments, hydrocarbons may be produced from the formation such that at least about 60% by volume of the initial volume in place of hydrocarbons is produced from the formation. In some embodiments, at least about 70% by volume of the initial volume in place of hydrocarbons or at least about 80% by volume of the initial volume in place of hydrocarbons may be produced from the formation.

In some embodiments, a pressurizing fluid is provided to second section **2102** and/or third section **2104** in combination with the mobilization fluid to increase mobility of hydrocarbons within the formation. The pressurizing fluid may include gases such as carbon dioxide, nitrogen, steam, methane, and/or mixtures thereof. In some embodiments, fluids produced from the formation (for example, combustion gases, heater exhaust gases, or produced formation fluids) may be used as pressurizing fluid. Providing a pressurizing fluid may increase a shear rate applied to hydrocarbon fluids in the formation and decrease the viscosity of non-Newtonian hydrocarbon fluids within the formation. In some embodiments, pressurizing fluid is provided to the selected section before significant heating of the formation. Pressurizing fluid injection may increase a portion of the formation available for production. Pressurizing fluid injection may increase a ratio of energy output of the formation (energy content of products produced from the formation) to energy input into the formation (energy costs for treating the formation).

Providing the pressurizing fluid may increase a pressure in a selected section of the formation. The pressure in the selected section may be maintained below a selected pressure. For example, the pressure may be maintained below about 150 bars absolute, about 100 bars absolute, or about 50 bars absolute. In some embodiments, the pressure may be maintained below about 35 bars absolute. Pressure may be varied depending on a number of factors (for example, desired production rate or an initial viscosity of tar in the formation). Injection of a gas into the formation may result in a viscosity reduction of some of the tar in the formation.

In some embodiments, pressure is maintained by controlling flow of the pressurizing fluid into the selected section. In other embodiments, the pressure is controlled by varying a location or locations for injecting the pressurizing fluid. In other embodiments, pressure is maintained by controlling a pressure and/or production rate at production wells **206**. In some embodiments, the pressurized fluid (for example, carbon dioxide) is separated from the produced fluids and reintroduced into the formation. After production has been stopped, the fluid may be sequestered in the formation.

The produced fluids may be transported through conduits (pipelines) between the formation and a treatment facility or refinery. The produced fluids may be transported through a pipeline to another location for further transportation (for example, the fluids can be transported to a facility at a river or a coast through the pipeline where the fluids can be further transported by tanker to a processing plant or refinery).

During an in situ heat treatment process, some formation fluid may migrate outwards from the treatment area. The formation fluid may include benzene and other contaminants. Some portions of the formation that contaminants migrate to will be subsequently treated when a new treatment area is defined and processed using the in situ heat treatment process. Such contaminants may be removed or destroyed by the subsequent in situ heat treatment process. Some areas of the formation to which contaminants migrate may not be become part of a new treatment area subjected to in situ heat treatment. Migration inhibition systems may be implemented to inhibit contaminants from migrating to areas in the formation that are not to be subjected to in situ heat treatment.

In some embodiments, a barrier (for example, a low temperature zone or freeze barrier) surrounds at least a portion of the perimeter of a treatment area. The barrier may be 20 m to 100 m from the closest heaters in the treatment area used in the in situ heat treatment process to heat the formation. Some contaminants may migrate outwards toward the barrier through fractures or highly permeable zones and condense in the formation.

In some in situ heat treatment embodiments, a migration inhibition system may be used to minimize or eliminate migration of formation fluid from the treatment area of the in situ heat treatment process. FIG. **184** depicts a representation of a fluid migration inhibition system. Barrier **922** may surround treatment area **882**. Migration inhibition wells **924** may be placed in the formation between barrier **922** and treatment area **882**. Migration inhibition wells **924** may be offset from wells used to heat the formation and/or from production wells used to produce fluid from the formation. Migration inhibition wells **924** may be placed in formation that is below pyrolysis and/or dissociation temperatures of minerals in the formation.

In some embodiments, one or more of the migration inhibition wells **924** include heaters. The heaters may be used to heat portions of the formation adjacent to the wells to a relatively low temperature. The relatively low temperature may be a temperature below a dissociation temperature of minerals in the formation adjacent to the well or below a pyrolysis temperature of hydrocarbons in the formation. The temperature that the low temperature heater wells raise the formation to may be less than 260° C., less than 230° C., or less than 200° C. In some embodiments, heating elements in low temperature wells **924** may be tailored so that the heating elements only heat portions of the formation that have permeability sufficient to allow for the migration of fluid (for example, fracture systems).

Some or all migration inhibition wells **924** may be injector wells that allow for the introduction of a sweep fluid into the formation. The injector wells may include smart well technology. Sweep fluid may be introduced into the formation through critical orifices, perforations or other types of openings in the injector wells. In some embodiments, the sweep fluid is carbon dioxide. The carbon dioxide may be carbon dioxide produced from an in situ heat treatment process. The sweep fluid may be or include other fluids, such as nitrogen, methane or other non-condensable hydrocarbons, exhaust gases, air, and/or steam. The sweep fluid may provide positive pressure in the formation outside of treatment area **882**. The

positive pressure may inhibit migration of formation fluid from treatment area **882** towards barrier **922**. The sweep fluid may move through fractures in the formation toward or into treatment area **882**. The sweep fluid may carry fluids that have migrated away from treatment area **882** back to the treatment area. The pressure of the fluid introduced through migration inhibition wells **924** may be maintained below the fracture pressure of the formation.

After an in situ process, energy recovery, remediation, and/or sequestration of carbon dioxide or other fluids in the treated area; the treatment area may still be at an elevated temperature. Sulfur may be introduced into the formation to act as a drive fluid to remove remaining formation fluid from the formation. The sulfur may be introduced through outermost wellbores in the formation. The wellbores may be injection wells, production wells, monitor wells, heater wells, barrier wells, or other types of wells that are converted to use as sulfur injection wells. The sulfur may be used to drive fluid inwards towards production wells in the pattern of wells used during the in situ heat treatment process. The wells used as production wells for sulfur may be production wells, heater wells, injection wells, monitor wells, or other types of wells converted for use as sulfur production wells.

In some embodiments, sulfur may be introduced in the treatment area from an outermost set of wells. Formation fluid may be produced from a first inward set of wellbores until substantially only sulfur is produced from the first inward set of wells. The first inward set of wells may be converted to injection wells. Sulfur may be introduced in the first inward set of wells to drive remaining formation fluid towards a second inward set of wells. The pattern may be continued until sulfur has been introduced into all of the treatment area. In some embodiments, a line drive may be used for introducing the sulfur into the treatment area.

In some embodiments, molten sulfur may be injected into the treatment area. The molten sulfur may act as a displacement agent that moves and/or entrains remaining fluid in the treatment area. The molten sulfur may be injected into the formation from selected wells. The sulfur may be at a temperature near a melting point of sulfur so that the sulfur has a relatively low viscosity. In some embodiments, the formation may be at a temperature above the boiling point of sulfur. Sulfur may be introduced into the formation as a gas or as a liquid.

Sulfur may be introduced into the formation until substantially only sulfur is produced from the last sulfur production well or production wells. When substantially only sulfur is produced from the last sulfur production well or production wells, introduction of additional sulfur may be stopped, and the production from the production well or production wells may be stopped. Sulfur in the formation may be allowed to remain in the formation and solidify.

Alternative energy sources may be used to supply electricity for subsurface electric heaters. Alternative energy sources include, but are not limited to, wind, off-peak power, hydroelectric power, geothermal, solar, and tidal wave action. Some of these alternative energy sources provide intermittent, time-variable power, or power-variable power. To provide power for subsurface electric heaters, power provided by these alternative energy sources may be conditioned to produce power with appropriate operating parameters (for example, voltage, frequency, and/or current) for the subsurface heaters.

FIG. **185** depicts an embodiment for generating electricity for subsurface heaters from an intermittent power source. The generated electrical power may be used to power other equipment used to treat a subsurface formation such as, but not limited to, pumps, computers, or other electrical equipment. In certain embodiments, windmill **926** is used to generate electricity to power heaters **760**. Windmill **926** may represent one or more windmills in a wind farm. The windmills convert wind to a usable mechanical form of motion. In some embodiments, the wind farm may include advanced windmills as suggested by the National Renewable Energy Laboratory (Golden, Colo., U.S.A.). In some embodiments, windmill **926** varies its power output during a 24 hour period (for example, the windmill may generate the most power at night). Using windmill **926** as the power source may reduce the carbon dioxide footprint for supplying power to heaters **760**. In some embodiments, windmill **926** includes other intermittent, time-variable, or power-variable power sources.

In some embodiments, gas turbine **928** is used to generate electricity to power heaters **760**. Windmill **926** and/or gas turbine **928** may be coupled to transformer **930**. Transformer **930** may convert power from windmill **926** and/or gas turbine **928** into electrical power with appropriate operating parameters for heaters **760** (for example, AC or DC power with appropriate voltage, current, and/or frequency may be generated by the transformer).

In certain embodiments, tap controller **932** is coupled to transformer **930**, control system **934**, and heaters **760**. Tap controller **932** may monitor and control transformer **930** to maintain a constant voltage to heaters **760**, regardless of the load of the heaters. Tap controller **932** may control power output in a range from 5 MVA (megavolt amps) to 500 MVA, from 10 MVA to 400 MVA, or from 20 MVA to 300 MVA. Tap controller **932** may be designed to meet selected design requirements such as, but not limited to, load limitations of components (such as transformer **930**, control system **934**, and/or heaters **760**) and the expected full load current in the electrical circuit. Tap controller **932** may be an electromechanical, mechanical, electrical, electromagnetic, or solid state tap controller. In one embodiments, tap controller **932** is a 32 step (±16 steps) electromechanical tap controller obtained from ABB Ltd. (Asea Brown Boveri) (Zurich, Switzerland). Tap controller **932** may be a step controller that changes power in steps over a period of time (for example, 1 step per minute). Tap controller **932** may operated over a percentage of the total range (for example, ±15% of the voltage or ±10% of the voltage).

As an example, during operation, an overload of voltage may be sent from transformer **930**. Tap controller **932** may modify the load provided to heaters **760** and distribute the excess load to other heaters and/or other equipment in need of power. In some embodiments, tap controller **932** may store the excess load for future use.

Control system **934** may control tap controller **932**. Control system **934** may be, for example, a computer controller or an analog logic system. Control system **934** may use data supplied from power sensors **936** to generate predictive algorithms and/or control tap controller **932**. For example, data may be an amount of power generated from windmill **926**, gas turbine **928**, and/or transformer **930**. Data may also include an amount of resistive load of heaters **760**. Power sensors **936** may be toroidal current sensors that output voltages that are proportional to the currents in wires passing through the sensors.

Automatic voltage regulation for resistive load of a heater enhances the life of the heaters and/or allows constant heat output from the heaters to a subsurface formation. Adjusting the load demands instead of adjusting the power source allows enhanced control of power supplied to heaters and/or other equipment that requires electricity. Power supplied to heaters **760** may be controlled within selected limits (for example, a power supplied and/or controlled to a heater

within 1%, 5%, 10%, or 20% of power required by the heater). Control of power supplied from alternative energy sources may allow output of prime power at its rating, allow energy produced (for example, from an intermittent source, a subsurface formation, or a hydroelectric source) to be stored and used later, and/or allow use of power generated by intermittent power sources to be used as a constant source of energy.

Some hydrocarbon containing formations, such as oil shale formations, may include nahcolite, trona, dawsonite, and/or other minerals within the formation. In some embodiments, nahcolite is contained in partially unleached or unleached portions of the formation. Unleached portions of the formation are parts of the formation where minerals have not been removed by groundwater in the formation. For example, in the Piceance basin in Colorado, U.S.A., unleached oil shale is found below a depth of about 500 m below grade. Deep unleached oil shale formations in the Piceance basin center tend to be relatively rich in hydrocarbons. For example, about 0.10 liters to about 0.15 liters of oil per kilogram (L/kg) of oil shale may be producible from an unleached oil shale formation.

Nahcolite is a mineral that includes sodium bicarbonate ($NaHCO_3$). Nahcolite may be found in formations in the Green River lakebeds in Colorado, U.S.A. In some embodiments, at least about 5 weight %, at least about 10 weight %, or at least about 20 weight % nahcolite may be present in the formation. Dawsonite is a mineral that includes sodium aluminum carbonate (NaAl(CO3)(OH)2). Dawsonite is typically present in the formation at weight percents greater than about 2 weight % or, in some embodiments, greater than about 5 weight %. Nahcolite and/or dawsonite may dissociate at temperatures used in an in situ heat treatment process. The dissociation is strongly endothermic and may produce large amounts of carbon dioxide.

Nahcolite and/or dawsonite may be solution mined prior to, during, and/or following treatment of the formation in situ to avoid dissociation reactions and/or to obtain desired chemical compounds. In certain embodiments, hot water or steam is used to dissolve nahcolite in situ to form an aqueous sodium bicarbonate solution before the in situ heat treatment process is used to process hydrocarbons in the formation. Nahcolite may form sodium ions (Na+) and bicarbonate ions (HCO3−) in aqueous solution. The solution may be produced from the formation through production wells, thus avoiding dissociation reactions during the in situ heat treatment process. In some embodiments, dawsonite is thermally decomposed to alumina during the in situ heat treatment process for treating hydrocarbons in the formation. The alumina is solution mined after completion of the in situ heat treatment process.

Production wells and/or injection wells used for solution mining and/or for in situ heat treatment processes may include smart well technology. The smart well technology allows the first fluid to be introduced at a desired zone in the formation. The smart well technology allows the second fluid to be removed from a desired zone of the formation.

Formations that include nahcolite and/or dawsonite may be treated using the in situ heat treatment process. A perimeter barrier may be formed around the portion of the formation to be treated. The perimeter barrier may inhibit migration of water into the treatment area. During solution mining and/or the in situ heat treatment process, the perimeter barrier may inhibit migration of dissolved minerals and formation fluid from the treatment area. During initial heating, a portion of the formation to be treated may be raised to a temperature below the dissociation temperature of the nahcolite. The temperature may be at most about 90° C., or in some embodiments, at most about 80° C. The temperature may be any temperature that increases the solvation rate of nahcolite in water, but is also below a temperature at which nahcolite dissociates (above about 95° C. at atmospheric pressure).

A first fluid may be injected into the heated portion. The first fluid may include water, brine, steam, or other fluids that form a solution with nahcolite and/or dawsonite. The first fluid may be at an increased temperature, for example, about 90° C., about 95° C., or about 100° C. The increased temperature may be similar to the temperature of the portion of the formation.

In some embodiments, the first fluid is injected at an increased temperature into a portion of the formation that has not been heated by heat sources. The increased temperature may be a temperature below a boiling point of the first fluid, for example, about 90° C. for water. Providing the first fluid at an increased temperature increases a temperature of a portion of the formation. In certain embodiments, additional heat may be provided from one or more heat sources in the formation during and/or after injection of the first fluid.

In other embodiments, the first fluid is or includes steam. The steam may be produced by forming steam in a previously heated portion of the formation (for example, by passing water through unshaped wellbores that have been used to heat the formation), by heat exchange with fluids produced from the formation, and/or by generating steam in standard steam production facilities. In some embodiments, the first fluid may be fluid introduced directly into a hot portion of the portion and produced from the hot portion of the formation. The first fluid may then be used as the first fluid for solution mining.

In some embodiments, heat from a hot previously treated portion of the formation is used to heat water, brine, and/or steam used for solution mining a new portion of the formation. Heat transfer fluid may be introduced into the hot previously treated portion of the formation. The heat transfer fluid may be water, steam, carbon dioxide, and/or other fluids. Heat may transfer from the hot formation to the heat transfer fluid. The heat transfer fluid is produced from the formation through production wells. The heat transfer fluid is sent to a heat exchanger. The heat exchanger may heat water, brine, and/or steam used as the first fluid to solution mine the new portion of the formation. The heat transfer fluid may be reintroduced into the heated portion of the formation to produce additional hot heat transfer fluid. In some embodiments, heat transfer fluid produced from the formation is treated to remove hydrocarbons or other materials before being reintroduced into the formation as part of a remediation process for the heated portion of the formation.

Steam injected for solution mining may have a temperature below the pyrolysis temperature of hydrocarbons in the formation. Injected steam may be at a temperature below 250° C., below 300° C., or below 400° C. The injected steam may be at a temperature of at least 150° C., at least 135° C., or at least 125° C. Injecting steam at pyrolysis temperatures may cause problems as hydrocarbons pyrolyze and hydrocarbon fines mix with the steam. The mixture of fines and steam may reduce permeability and/or cause plugging of production wells and the formation. Thus, the injected steam temperature is selected to inhibit plugging of the formation and/or wells in the formation.

The temperature of the first fluid may be varied during the solution mining process. As the solution mining progresses and the nahcolite being solution mined is farther away from the injection point, the first fluid temperature may be increased so that steam and/or water that reaches the nahcolite

to be solution mined is at an elevated temperature below the dissociation temperature of the nahcolite. The steam and/or water that reaches the nahcolite is also at a temperature below a temperature that promotes plugging of the formation and/or wells in the formation (for example, the pyrolysis temperature of hydrocarbons in the formation).

A second fluid may be produced from the formation following injection of the first fluid into the formation. The second fluid may include material dissolved in the first fluid. For example, the second fluid may include carbonic acid or other hydrated carbonate compounds formed from the dissolution of nahcolite in the first fluid. The second fluid may also include minerals and/or metals. The minerals and/or metals may include sodium, aluminum, phosphorus, and other elements.

Solution mining the formation before the in situ heat treatment process allows initial heating of the formation to be provided by heat transfer from the first fluid used during solution mining. Solution mining nahcolite or other minerals that decompose or dissociate by means of endothermic reactions before the in situ heat treatment process avoids having energy supplied to heat the formation being used to support these endothermic reactions. Solution mining allows for production of minerals with commercial value. Removing nahcolite or other minerals before the in situ heat treatment process removes mass from the formation. Thus, less mass is present in the formation that needs to be heated to higher temperatures and heating the formation to higher temperatures may be achieved more quickly and/or more efficiently. Removing mass from the formation also may increase the permeability of the formation. Increasing the permeability may reduce the number of production wells needed for the in situ heat treatment process. In certain embodiments, solution mining before the in situ heat treatment process reduces the time delay between startup of heating of the formation and production of hydrocarbons by two years or more.

FIG. **186** depicts an embodiment of solution mining well **938**. Solution mining well **938** may include insulated portion **940**, input **942**, packer **944**, and return **946**. Insulated portion **940** may be adjacent to overburden **458** of the formation. In some embodiments, insulated portion **940** is low conductivity cement. The cement may be low density, low conductivity vermiculite cement or foam cement. Input **942** may direct the first fluid to treatment area **882**. Perforations or other types of openings in input **942** allow the first fluid to contact formation material in treatment area **882**. Packer **944** may be a bottom seal for input **942**. First fluid passes through input **942** into the formation. First fluid dissolves minerals and becomes second fluid. The second fluid may be denser than the first fluid. An entrance into return **946** is typically located below the perforations or openings that allow the first fluid to enter the formation. Second fluid flows to return **946**. The second fluid is removed from the formation through return **946**.

FIG. **187** depicts a representation of an embodiment of solution mining well **938**. Solution mining well **938** may include input **942** and return **946** in casing **948**. Inlet **942** and/or return **946** may be coiled tubing.

FIG. **188** depicts a representation of an embodiment of solution mining well **938**. Insulating portions **940** may surround return **946**. Input **942** may be positioned in return **946**. In some embodiments, input **942** may introduce the first fluid into the treatment area below the entry point into return **946**. In some embodiments, crossovers may be used to direct first fluid flow and second fluid flow so that first fluid is introduced into the formation from input **942** above the entry point of second fluid into return **946**.

FIG. **189** depicts an elevational view of an embodiment of wells used for solution mining and/or for an in situ heat treatment process. Solution mining wells **938** may be placed in the formation in an equilateral triangle pattern. In some embodiments, the spacing between solution mining wells **938** may be about 36 m. Other spacings may be used. Heat sources **202** may also be placed in an equilateral triangle pattern. Solution mining wells **938** substitute for certain heat sources of the pattern. In the shown embodiment, the spacing between heat sources **202** is about 9 m. The ratio of solution mining well spacing to heat source spacing is 4. Other ratios may be used if desired. After solution mining is complete, solution mining wells **938** may be used as production wells for the in situ heat treatment process.

In some formations, a portion of the formation with unleached minerals may be below a leached portion of the formation. The unleached portion may be thick and substantially impermeable. A treatment area may be formed in the unleached portion. Unleached portion of the formation to the sides, above and/or below the treatment area may be used as barriers to fluid flow into and out of the treatment area. A first treatment area may be solution mined to remove minerals, increase permeability in the treatment area, and/or increase the richness of the hydrocarbons in the treatment area. After solution mining the first treatment area, in situ heat treatment may be used to treat a second treatment area. In some embodiments, the second treatment area is the same as the first treatment area. In some embodiments, the second treatment has a smaller volume than the first treatment area so that heat provided by outermost heat sources to the formation do not raise the temperature of unleached portions of the formation to the dissociation temperature of the minerals in the unleached portions.

In some embodiments, a leached or partially leached portion of the formation above an unleached portion of the formation may include significant amounts of hydrocarbon materials. An in situ heating process may be used to produce hydrocarbon fluids from the unleached portions and the leached or partially leached portions of the formation. FIG. **190** depicts a representation of a formation with unleached zone **950** below leached zone **952**. Unleached zone **950** may have an initial permeability before solution mining of less than 0.1 millidarcy. Solution mining wells **938** may be placed in the formation. Solution mining wells **938** may include smart well technology that allows the position of first fluid entrance into the formation and second flow entrance into the solution mining wells to be changed. Solution mining wells **938** may be used to form first treatment area **882'** in unleached zone **950**. Unleached zone **950** may initially be substantially impermeable. Unleached portions of the formation may form a top barrier and side barriers around first treatment area **882'**. After solution mining first treatment area **882'**, the portions of solution mining wells **938** adjacent to the first treatment area may be converted to production wells and/or heater wells.

Heat sources **202** in first treatment area **882'** may be used to heat the first treatment area to pyrolysis temperatures. In some embodiments, one or more heat sources **202** are placed in the formation before first treatment area **882'** is solution mined. The heat sources may be used to provide initial heating to the formation to raise the temperature of the formation and/or to test the functionality of the heat sources. In some embodiments, one or more heat sources are installed during solution mining of the first treatment area, or after solution mining is completed. After solution mining, heat sources **202** may be used to raise the temperature of at least a portion of first treatment area **882'** above the pyrolysis and/or mobiliza-

tion temperature of hydrocarbons in the formation to result in the generation of mobile hydrocarbons in the first treatment area.

Barrier wells **200** may be introduced into the formation. Ends of barrier wells **200** may extend into and terminate in unleached zone **950**. Unleached zone **950** may be impermeable. In some embodiments, barrier wells **200** are freeze wells. Barrier wells **200** may be used to form a barrier to fluid flow into or out of unleached zone **952**. Barrier wells **200**, overburden **458**, and the unleached material above first treatment area **882'** may define second treatment area **882"**. In some embodiments, a first fluid may be introduced into second treatment area **882"** through solution mining wells **938** to raise the initial temperature of the formation in second treatment area **882"** and remove any residual soluble minerals from the second treatment area. In some embodiments, the top barrier above first treatment area **882'** may be solution mined to remove minerals and combine first treatment area **882'** and second treatment area **882"** into one treatment area. After solution mining, heat sources may be activated to heat the treatment area to pyrolysis temperatures.

FIG. **191** depicts an embodiment for solution mining the formation. Barrier **922** (for example, a frozen barrier and/or a grout barrier) may be formed around a perimeter of treatment area **882** of the formation. The footprint defined by the barrier may have any desired shape such as circular, square, rectangular, polygonal, or irregular shape. Barrier **922** may be any barrier formed to inhibit the flow of fluid into or out of treatment area **882**. For example, barrier **922** may include one or more freeze wells that inhibit water flow through the barrier. Barrier **922** may be formed using one or more barrier wells **200**. Formation of barrier **922** may be monitored using monitor wells **956** and/or by monitoring devices placed in barrier wells **200**.

Water inside treatment area **882** may be pumped out of the treatment area through injection wells **748** and/or production wells **206**. In certain embodiments, injection wells **748** are used as production wells **206** and vice versa (the wells are used as both injection wells and production wells). Water may be pumped out until a production rate of water is low or stops.

Heat may be provided to treatment area **882** from heat sources **202**. Heat sources may be operated at temperatures that do not result in the pyrolysis of hydrocarbons in the formation adjacent to the heat sources. In some embodiments, treatment area **882** is heated to a temperature from about 90° C. to about 120° C. (for example, a temperature of about 90° C., 95° C., 100° C., 110° C., or 120° C.). In certain embodiments, heat is provided to treatment area **882** from the first fluid injected into the formation. The first fluid may be injected at a temperature from about 90° C. to about 120° C. (for example, a temperature of about 90° C., 95° C., 100° C., 110° C., or 120° C.). In some embodiments, heat sources **202** are installed in treatment area **882** after the treatment area is solution mined. In some embodiments, some heat is provided from heaters placed in injection wells **748** and/or production wells **206**. A temperature of treatment area **882** may be monitored using temperature measurement devices placed in monitoring wells **956** and/or temperature measurement devices in injection wells **748**, production wells **206**, and/or heat sources **202**.

The first fluid is injected through one or more injection wells **748**. In some embodiments, the first fluid is hot water. The first fluid may mix and/or combine with non-hydrocarbon material that is soluble in the first fluid, such as nahcolite, to produce a second fluid. The second fluid may be removed from the treatment area through injection wells **748**, production wells **206**, and/or heat sources **202**. Injection wells **748**, production wells **206**, and/or heat sources **202** may be heated during removal of the second fluid. Heating one or more wells during removal of the second fluid may maintain the temperature of the fluid during removal of the fluid from the treatment area above a desired value. After producing a desired amount of the soluble non-hydrocarbon material from treatment area **882**, solution remaining within the treatment area may be removed from the treatment area through injection wells **748**, production wells **206**, and/or heat sources **202**. The desired amount of the soluble non-hydrocarbon material may be less than half of the soluble non-hydrocarbon material, a majority of the soluble non-hydrocarbon material, substantially all of the soluble non-hydrocarbon material, or all of the soluble non-hydrocarbon material. Removing soluble non-hydrocarbon material may produce a relatively high permeability treatment area **882**.

Hydrocarbons within treatment area **882** may be pyrolyzed and/or produced using the in situ heat treatment process following removal of soluble non-hydrocarbon materials. The relatively high permeability treatment area allows for easy movement of hydrocarbon fluids in the formation during in situ heat treatment processing. The relatively high permeability treatment area provides an enhanced collection area for pyrolyzed and mobilized fluids in the formation. During the in situ heat treatment process, heat may be provided to treatment area **882** from heat sources **202**. A mixture of hydrocarbons may be produced from the formation through production wells **206** and/or heat sources **202**. In certain embodiments, injection wells **748** are used as either production wells and/or heater wells during the in situ heat treatment process.

In some embodiments, a controlled amount of oxidant (for example, air and/or oxygen) is provided to treatment area **882** at or near heat sources **202** when a temperature in the formation is above a temperature sufficient to support oxidation of hydrocarbons. At such a temperature, the oxidant reacts with the hydrocarbons to provide heat in addition to heat provided by electrical heaters in heat sources **202**. The controlled amount of oxidant may facilitate oxidation of hydrocarbons in the formation to provide additional heat for pyrolyzing hydrocarbons in the formation. The oxidant may more easily flow through treatment area **882** because of the increased permeability of the treatment area after removal of the non-hydrocarbon materials. The oxidant may be provided in a controlled manner to control the heating of the formation. The amount of oxidant provided is controlled so that uncontrolled heating of the formation is avoided. Excess oxidant and combustion products may flow to production wells in treatment area **882**.

Following the in situ heat treatment process, treatment area **882** may be cooled by introducing water to produce steam from the hot portion of the formation. Introduction of water to produce steam may vaporize some hydrocarbons remaining in the formation. Water may be injected through injection wells **748**. The injected water may cool the formation. The remaining hydrocarbons and generated steam may be produced through production wells **206** and/or heat sources **202**. Treatment area **882** may be cooled to a temperature near the boiling point of water. The steam produced from the formation may be used to heat a first fluid used to solution mine another portion of the formation.

Treatment area **882** may be further cooled to a temperature at which water will condense in the formation. Water and/or solvent may be introduced into and be removed from the treatment area. Removing the condensed water and/or solvent from treatment area **882** may remove any additional soluble material remaining in the treatment area. The water and/or

solvent may entrain non-soluble fluid present in the formation. Fluid may be pumped out of treatment area **882** through production well **206** and/or heat sources **202**. The injection and removal of water and/or solvent may be repeated until a desired water quality within treatment area **882** is achieved. Water quality may be measured at injection wells **748**, heat sources **202**, and/or production wells **206**. The water quality may substantially match or exceed the water quality of treatment area **882** prior to treatment.

In some embodiments, treatment area **882** may include a leached zone located above an unleached zone. The leached zone may have been leached naturally and/or by a separate leaching process. In certain embodiments, the unleached zone may be at a depth of at least about 500 m. A thickness of the unleached zone may be between about 100 m and about 500 m. However, the depth and thickness of the unleached zone may vary depending on, for example, a location of treatment area **882** and/or the type of formation. In certain embodiments, the first fluid is injected into the unleached zone below the leached zone. Heat may also be provided into the unleached zone.

In certain embodiments, a section of a formation may be left untreated by solution mining and/or unleached. The unleached section may be proximate a selected section of the formation that has been leached and/or solution mined by providing the first fluid as described above. The unleached section may inhibit the flow of water into the selected section. In some embodiments, more than one unleached section may be proximate a selected section.

Nahcolite may be present in the formation in layers or beds. Prior to solution mining, such layers may have little or no permeability. In certain embodiments, solution mining layered or bedded nahcolite from the formation causes vertical shifting in the formation. FIG. **192** depicts an embodiment of a formation with nahcolite layers in the formation below overburden **458** and before solution mining nahcolite from the formation. Hydrocarbon layers **460**A have substantially no nahcolite and hydrocarbon layers **460**B have nahcolite. FIG. **193** depicts the formation of FIG. **192** after the nahcolite has been solution mined. Layers **460**B have collapsed due to the removal of the nahcolite from the layers. The collapsing of layers **460**B causes compaction of the layers and vertical shifting of the formation. The hydrocarbon richness of layers **460**B is increased after compaction of the layers. In addition, the permeability of layers **460**B may remain relatively high after compaction due to removal of the nahcolite. The permeability may be more than 5 darcy, more than 1 darcy, or more than 0.5 darcy after vertical shifting. The permeability may provide fluid flow paths to production wells when the formation is treated using an in situ heat treatment process. The increased permeability may allow for a large spacing between production wells. Distances between production wells for the in situ heat treatment system after solution mining may be greater than 10 m, greater than 20 m, or greater than 30 meters. Heater wells may be placed in the formation after removal of nahcolite and the subsequent vertical shifting. Forming heater wellbores and/or installing heaters in the formation after the vertical shifting protects the heaters from being damaged due to the vertical shifting.

In certain embodiments, removing nahcolite from the formation interconnects two or more wells in the formation. Removing nahcolite from zones in the formation may increase the permeability in the zones. Some zones may have more nahcolite than others and become more permeable as the nahcolite is removed. At a certain time, zones with the increased permeability may interconnect two or more wells (for example, injection wells or production wells) in the formation.

FIG. **194** depicts an embodiment of two injection wells interconnected by a zone that has been solution mined to remove nahcolite from the zone. Solution mining wells **938** are used to solution mine hydrocarbon layer **460**, which contains nahcolite. During the initial portion of the solution mining process, solution mining wells **938** are used to inject water and/or other fluids, and to produce dissolved nahcolite fluids from the formation. Each solution mining well **938** is used to inject water and produce fluid from a near wellbore region as the permeability of hydrocarbon layer is not sufficient to allow fluid to flow between the injection wells. In certain embodiments, zone **958** has more nahcolite than other portions of hydrocarbon layer **460**. With increased nahcolite removal from zone **958**, the permeability of the zone may increase. The permeability increases from the wellbores outwards as nahcolite is removed from zone **958**. At some point during solution mining of the formation, the permeability of zone **958** increases to allow solution mining wells **938** to become interconnected such that fluid will flow between the wells. At this time, one solution mining well **938'** may be used to inject water while the other solution mining well **938"** is used to produce fluids from the formation in a continuous process. Injecting in one well and producing from a second well may be more economical and more efficient in removing nahcolite, as compared to injecting and producing through the same well. In some embodiments, additional wells may be drilled into zone **958** and/or hydrocarbon layer **460** in addition to injection wells **748**. The additional wells may be used to circulate additional water and/or to produce fluids from the formation. The wells may later be used as heater wells and/or production wells for the in situ heat treatment process treatment of hydrocarbon layer **460**.

In some embodiments, the second fluid produced from the formation during solution mining is used to produce sodium bicarbonate. Sodium bicarbonate may be used in the food and pharmaceutical industries, in leather tanning, in fire retardation, in wastewater treatment, and in flue gas treatment (flue gas desulphurization and hydrogen chloride reduction). The second fluid may be kept pressurized and at an elevated temperature when removed from the formation. The second fluid may be cooled in a crystallizer to precipitate sodium bicarbonate.

In some embodiments, the second fluid produced from the formation during solution mining is used to produce sodium carbonate, which is also referred to as soda ash. Sodium carbonate may be used in the manufacture of glass, in the manufacture of detergents, in water purification, polymer production, tanning, paper manufacturing, effluent neutralization, metal refining, sugar extraction, and/or cement manufacturing. The second fluid removed from the formation may be heated in a treatment facility to form sodium carbonate (soda ash) and/or sodium carbonate brine. Heating sodium bicarbonate will form sodium carbonate according to the equation:

$$2NaHCO_3 \rightarrow Na_2CO_3 + CO_2 + H_2O. \quad \text{(EQN. 8)}$$

In certain embodiments, the heat for heating the sodium bicarbonate is provided using heat from the formation. For example, a heat exchanger that uses steam produced from the water introduced into the hot formation may be used to heat the second fluid to dissociation temperatures of the sodium bicarbonate. In some embodiments, the second fluid is circulated through the formation to utilize heat in the formation for further reaction. Steam and/or hot water may also be added to

facilitate circulation. The second fluid may be circulated through a heated portion of the formation that has been subjected to the in situ heat treatment process to produce hydrocarbons from the formation. At least a portion of the carbon dioxide generated during sodium carbonate dissociation may be adsorbed on carbon that remains in the formation after the in situ heat treatment process. In some embodiments, the second fluid is circulated through conduits previously used to heat the formation.

In some embodiments, higher temperatures are used in the formation (for example, above about 120° C., above about 130° C., above about 150° C., or below about 250° C.) during solution mining of nahcolite. The first fluid is introduced into the formation under pressure sufficient to inhibit sodium bicarbonate from dissociating to produce carbon dioxide. The pressure in the formation may be maintained at sufficiently high pressures to inhibit such nahcolite dissociation but below pressures that would result in fracturing the formation. In addition, the pressure in the formation may be maintained high enough to inhibit steam formation if hot water is being introduced in the formation. In some embodiments, a portion of the nahcolite may begin to decompose in situ. In such cases, nahcolite is removed from the formation as soda ash. If soda ash is produced from solution mining of nahcolite, the soda ash may be transported to a separate facility for treatment. The soda ash may be transported through a pipeline to the separate facility.

As described above, in certain embodiments, following removal of nahcolite from the formation, the formation is treated using the in situ heat treatment process to produce formation fluids from the formation. If dawsonite is present in the formation, dawsonite within the heated portion of the formation decomposes during heating of the formation to pyrolysis temperature. Dawsonite typically decomposes at temperatures above 270° C. according to the reaction:

$$2NaAl(OH)_2CO_3 \rightarrow Na_2CO_3+Al_2O_3+2H_2O+CO_2. \quad \text{(EQN. 9)}$$

Sodium carbonate may be removed from the formation by solution mining the formation with water or other fluid into which sodium carbonate is soluble. In certain embodiments, alumina formed by dawsonite decomposition is solution mined using a chelating agent. The chelating agent may be injected through injection wells, production wells, and/or heater wells used for solution mining nahcolite and/or the in situ heat treatment process (for example, injection wells **748**, production wells **206**, and/or heat sources **202** depicted in FIG. **191**). The chelating agent may be an aqueous acid. In certain embodiments, the chelating agent is EDTA (ethylenediaminetetraacetic acid). Other examples of possible chelating agents include, but are not limited to, ethylenediamine, porphyrins, dimercaprol, nitrilotriacetic acid, diethylenetriaminepentaacetic acid, phosphoric acids, acetic acid, acetoxy benzoic acids, nicotinic acid, pyruvic acid, citric acid, tartaric acid, malonic acid, imidizole, ascorbic acid, phenols, hydroxy ketones, sebacic acid, and boric acid. The mixture of chelating agent and alumina may be produced through production wells or other wells used for solution mining and/or the in situ heat treatment process (for example, injection wells **748**, production wells **206**, and/or heat sources **202**, which are depicted in FIG. **191**). The alumina may be separated from the chelating agent in a treatment facility. The recovered chelating agent may be recirculated back to the formation to solution mine more alumina.

In some embodiments, alumina within the formation may be solution mined using a basic fluid after the in situ heat treatment process. Basic fluids include, but are not limited to, sodium hydroxide, ammonia, magnesium hydroxide, magnesium carbonate, sodium carbonate, potassium carbonate, pyridine, and amines. In an embodiment, sodium carbonate brine, such as 0.5 Normal Na2CO3, is used to solution mine alumina. Sodium carbonate brine may be obtained from solution mining nahcolite from the formation. Obtaining the basic fluid by solution mining the nahcolite may significantly reduce costs associated with obtaining the basic fluid. The basic fluid may be injected into the formation through a heater well and/or an injection well. The basic fluid may combine with alumina to form an alumina solution that is removed from the formation. The alumina solution may be removed through a heater well, injection well, or production well.

Alumina may be extracted from the alumina solution in a treatment facility. In an embodiment, carbon dioxide is bubbled through the alumina solution to precipitate the alumina from the basic fluid. Carbon dioxide may be obtained from dissociation of nahcolite, from the in situ heat treatment process, or from decomposition of the dawsonite during the in situ heat treatment process.

In certain embodiments, a formation may include portions that are significantly rich in either nahcolite or dawsonite only. For example, a formation may contain significant amounts of nahcolite (for example, at least about 20 weight %, at least about 30 weight %, or at least about 40 weight %) in a depocenter of the formation. The depocenter may contain only about 5 weight % or less dawsonite on average. However, in bottom layers of the formation, a weight percent of dawsonite may be about 10 weight % or even as high as about 25 weight %. In such formations, it may be advantageous to solution mine for nahcolite only in nahcolite-rich areas, such as the depocenter, and solution mine for dawsonite only in the dawsonite-rich areas, such as the bottom layers. This selective solution mining may significantly reduce fluid costs, heating costs, and/or equipment costs associated with operating the solution mining process.

In certain formations, dawsonite composition varies between layers in the formation. For example, some layers of the formation may have dawsonite and some layers may not. In certain embodiments, more heat is provided to layers with more dawsonite than to layers with less dawsonite. Tailoring heat input to provide more heat to certain dawsonite layers more uniformly heats the formation as the reaction to decompose dawsonite absorbs some of the heat intended for pyrolyzing hydrocarbons. FIG. **195** depicts an embodiment for heating a formation with dawsonite in the formation. Hydrocarbon layer **460** may be cored to assess the dawsonite composition of the hydrocarbon layer. The mineral composition may be assessed using, for example, FTIR (Fourier transform infrared spectroscopy) or x-ray diffraction. Assessing the core composition may also assess the nahcolite composition of the core. After assessing the dawsonite composition, heater **716** may be placed in wellbore **452**. Heater **716** includes sections to provide more heat to hydrocarbon layers with more dawsonite in the layers (hydrocarbon layers **460**D). Hydrocarbon layers with less dawsonite (hydrocarbon layers **460**C) are provided with less heat by heater **716**. Heat output of heater **716** may be tailored by, for example, adjusting the resistance of the heater along the length of the heater. In one embodiment, heater **716** is a temperature limited heater, described herein, that has a higher temperature limit (for example, higher Curie temperature) in sections proximate layers **460**D as compared to the temperature limit (Curie temperature) of sections proximate layers **460**C. The resistance of heater **716** may also be adjusted by altering the resistive conducting materials along the length of the heater to supply a higher energy input (watts per meter) adjacent to dawsonite rich layers.

Solution mining dawsonite and nahcolite may be relatively simple processes that produce alumina and soda ash from the formation. In some embodiments, hydrocarbons produced from the formation using the in situ heat treatment process may be fuel for a power plant that produces direct current (DC) electricity at or near the site of the in situ heat treatment process. The produced DC electricity may be used on the site to produce aluminum metal from the alumina using the Hall process. Aluminum metal may be produced from the alumina by melting the alumina in a treatment facility on the site. Generating the DC electricity at the site may save on costs associated with using hydrotreaters, pipelines, or other treatment facilities associated with transporting and/or treating hydrocarbons produced from the formation using the in situ heat treatment process.

In some embodiments, acid may be introduced into the formation through selected wells to increase the porosity adjacent to the wells. For example, acid may be injected if the formation comprises limestone or dolomite. The acid used to treat the selected wells may be acid produced during in situ heat treatment of a section of the formation (for example, hydrochloric acid), or acid produced from byproducts of the in situ heat treatment process (for example, sulfuric acid produced from hydrogen sulfide or sulfur).

In some embodiments, a saline rich zone is located at or near an unleached portion of the formation. The saline rich zone may be an aquifer in which water has leached out nahcolite and/or other minerals. A high flow rate may pass through the saline rich zone. Saline water from the saline rich zone may be used to solution mine another portion of the formation. In certain embodiments, a steam and electricity cogeneration facility may be used to heat the saline water prior to use for solution mining.

FIG. **196** depicts a representation of an embodiment for solution mining with a steam and electricity cogeneration facility. Treatment area **882** may be formed in unleached portion **950** of the formation (for example, an oil shale formation). Several treatment areas **882** may be formed in unleached portion **950** leaving top, side, and/or bottom walls of unleached formation as barriers around the individual treatment areas to inhibit inflow and outflow of formation fluid during the in situ heat treatment process. The thickness of the walls surrounding the treatment areas may be 10 m or more. For example, the side wall near closest to saline zone **2106** may be 60 m or more thick, and the top wall may be 30 m or more thick.

Treatment area **882** may have significant amounts of nahcolite. Saline zone **2106** is located at or near treatment area **882**. In certain embodiments, zone **2106** is located up dip from treatment area **882**. Zone **2106** may be leached or partially leached such that the zone is mainly filled with saline water.

In certain embodiments, saline water is removed (pumped) from zone **2106** using production well **206**. Production well **206** may be located at or near the lowest portion of zone **2106** so that saline water flows into the production well. Saline water removed from zone **2106** is heated to hot water and/or steam temperatures in facility **750**. Facility **750** may burn hydrocarbons to run generators that produce electricity. Facility **750** may burn gaseous and/or liquid hydrocarbons to make electricity. In some embodiments, pulverized coal is used to make electricity. The electricity generated may be used to provide electrical power for heaters or other electrical operations (for example, pumping). Waste heat from the generators is used to make hot water and/or steam from the saline water. After the in situ heat treatment process of one or more treatment areas **882** results in the production of hydrocarbons, at least a portion of the produced hydrocarbons may be used as fuel for facility **750**.

The hot water and/or steam made by facility **750** is provided to solution mining well **938**. Solution mining well **938** is used to solution mine treatment area **882**. Nahcolite and/or other minerals are removed from treatment area **882** by solution mining well **938**. The nahcolite may be removed as a nahcolite solution from treatment area **882**. The solution removed from treatment area **882** may be a brine solution with dissolved nahcolite. Heat from the removed nahcolite solution may be used in facility **750** to heat saline water from zone **2106** and/or other fluids. The nahcolite solution may then be injected through injection well **748** into zone **2106**. In some embodiments, injection well **748** injects the nahcolite solution into zone **2106** up dip from production well **206**. Injection may occur a significant distance up dip so that nahcolite solution may be continuously injected as saline water is removed from the zone without the two fluids substantially intermixing. In some embodiments, the nahcolite solution from treatment area **882** is provided to injection well **748** without passing through facility **750** (the nahcolite solution bypasses the facility).

The nahcolite solution injected into zone **2106** may be left in the zone permanently or for an extended period of time (for example, after solution mining, production well **206** may be shut in). In some embodiments, the nahcolite stored in zone **2106** is accessed at later times. The nahcolite may be produced by removing saline water from zone **2106** and processing the saline water to make sodium bicarbonate and/or soda ash.

Solution mining using saline water from zone **2106** and heat from facility **750** to heat the saline water may be a high efficiency process for solution mining treatment area **882**. Facility **750** is efficient at providing heat to the saline water. Using the saline water to solution mine decreases costs associated with pumping and/or transporting water to the treatment site. Additionally, solution mining treatment area **882** preheats the treatment area for any subsequent heat treatment of the treatment area, enriches the hydrocarbon content in the treatment area by removing nahcolite, and/or creates more permeability in the treatment area by removing nahcolite.

In certain embodiments, treatment area **882** is further treated using an in situ heat treatment process following solution mining of the treatment area. A portion of the electricity generated in facility **750** may be used to power heaters for the in situ heat treatment process.

In some embodiments, a perimeter barrier may be formed around the portion of the formation to be treated. The perimeter barrier may inhibit migration of formation fluid into or out of the treatment area. The perimeter barrier may be a frozen barrier and/or a grout barrier. After formation of the perimeter barrier, the treatment area may be processed to produce desired products.

Formations that include non-hydrocarbon materials may be treated to remove and/or dissolve a portion of the non-hydrocarbon materials from a section of the formation before hydrocarbons are produced from the section. In some embodiments, the non-hydrocarbon materials are removed by solution mining. Removing a portion of the non-hydrocarbon materials may reduce the carbon dioxide generation sources present in the formation. Removing a portion of the non-hydrocarbon materials may increase the porosity and/or permeability of the section of the formation. Removing a portion of the non-hydrocarbon materials may result in a raised temperature in the section of the formation.

After solution mining, some of the wells in the treatment may be converted to heater wells, injection wells, and/or production wells. In some embodiments, additional wells are formed in the treatment area. The wells may be heater wells, injection wells, and/or production wells. Logging techniques may be employed to assess the physical characteristics, including any vertical shifting resulting from the solution mining, and/or the composition of material in the formation. Packing, baffles or other techniques may be used to inhibit formation fluid from entering the heater wells. The heater wells may be activated to heat the formation to a temperature sufficient to support combustion.

One or more production wells may be positioned in permeable sections of the treatment area. Production wells may be horizontally and/or vertically oriented. For example, production wells may be positioned in areas of the formation that have a permeability of greater than 5 darcy or 10 darcy. In some embodiments, production wells may be positioned near a perimeter barrier. A production well may allow water and production fluids to be removed from the formation. Positioning the production well near a perimeter barrier enhances the flow of fluids from the warmer zones of the formation to the cooler zones.

FIG. **197** depicts an embodiment of a process for treating a hydrocarbon containing formation with a combustion front. Barrier **922** (for example, a frozen barrier or a grout barrier) may be formed around a perimeter of treatment area **882** of the formation. The footprint defined by the barrier may have any desired shape such as circular, square, rectangular, polygonal, or irregular shape. Barrier **922** may be formed using one or more barrier wells **200**. The barrier may be any barrier formed to inhibit the flow of fluid into or out of treatment area **882**. In some embodiments, barrier **922** may be a double barrier.

Heat may be provided to treatment area **882** through heaters positioned in injection wells **748**. In some embodiments, the heaters in injection wells **748** heat formation adjacent to the injections wells to temperatures sufficient to support combustion. Heaters in injection wells **748** may raise the formation near the injection wells to temperatures from about 90° C. to about 120° C. or higher (for example, a temperature of about 90° C., 95° C., 100° C., 110° C., or 120° C.).

Injection wells **748** may be used to introduce a combustion fuel, an oxidant, steam and/or a heat transfer fluid into treatment area **882**, either before, during, or after heat is provided to the treatment area **882** from heaters. In some embodiments, injection wells **748** are in communication with each other to allow the introduced fluid to flow from one well to another. Injection wells **748** may be located at positions that are relatively far away from perimeter barrier **922**. Introduced fluid may cause combustion of hydrocarbons in treatment area **882**. Heat from the combustion may heat treatment area **882** and mobilize fluids toward production wells **206**.

A temperature of treatment area **882** may be monitored using temperature measurement devices placed in monitoring wells and/or temperature measurement devices in injection wells **748**, production wells **206**, and/or heater wells.

In some embodiments, a controlled amount of oxidant (for example, air and/or oxygen) is provided in injection wells **748** to advance a heat front towards production wells **206**. In some embodiments, the controlled amount of oxidant is introduced into the formation after solution mining has established permeable interconnectivity between at least two injection wells. The amount of oxidant is controlled to limit the advancement rate of the heat front and to limit the temperature of the heat front. The advancing heat front may pyrolyze hydrocarbons. The high permeability in the formation allows the pyrolyzed hydrocarbons to spread in the formation towards production wells without being overtaken by the advancing heat front.

Vaporized formation fluid and/or gas formed during the combustion process may be removed through gas wells **960** and/or injection well **748**. Venting of gases through the gas wells and/or the injection well may force the combustion front in a desired direction.

In some embodiments, the formation may be heated to a temperature sufficient temperature to cause pyrolysis of the formation fluid by the steam and/or heat transfer fluid. The steam and/or heat transfer fluid may be heated to temperatures of about 300° C., about 400° C., about 500° C., or about 600° C. In certain embodiments, the steam and/or heat transfer fluid may be co-injected with the fuel and/or oxidant.

FIG. **198** depicts a representation of a cross-sectional view of an embodiment for treating a hydrocarbon containing formation with a combustion front. As the combustion front is initiated and/or fueled through injection wells **748**, formation fluid near periphery **962** of the combustion front becomes mobile and flow towards production wells **206** located proximate barrier **922**. Injection wells may include smart well technology. Combustion products and noncondensable formation fluid may be removed from the formation through gas wells **960**. In some embodiments, no gas wells are formed in the formation. In such embodiments, formation fluid, combustion products and noncondensable formation fluid are produced through production wells **206**. In embodiments that include gas wells **960**, condensable formation fluid may be produced through production well **206**. In some embodiments, production well **206** is located below injection well **748**. Production well **206** may be about, or above 1 m, 5 m, to 10 m or more below injection well **748**. Production well may be a horizontal well. Periphery **962** of the combustion front may advance from the toe of production well **206** towards the heel of the production well. Production well **206** may include a perforated liner that allows hydrocarbons to flow into the production well. In some embodiments, a catalyst may be placed in production well **206**. The catalyst may upgrade and/or stabilize formation fluid in the production well.

Gases may be produced during in situ heat treatment processes and during many conventional production processes. Some of the produced gases (for example, carbon dioxide and/or hydrogen sulfide) when introduced into water may change the pH of the water to less than 7. Such gases are typically referred to as sour gas or acidic gas. Introducing sour gas from produced fluid into subsurface formations may reduce or eliminate the need for or size of certain surface facilities (for example, a Claus plant or Scot gas treater). Introducing sour gas from produced formation fluid into subsurface formations may make the formation fluid more acceptable for transportation, use, and/or processing. Removal of sour gas having a low heating value (for example, carbon dioxide) from formation fluids may increase the caloric value of the gas stream separated from the formation fluid.

Net release of sour gas to the atmosphere and/or conversion of sour gas to other compounds may be reduced by utilizing the produced sour gas and/or by storing the sour gas within subsurface formations. In some embodiments, the sour gas is stored in deep saline aquifers. Deep saline aquifers may be at depths of about 900 m or more below the surface. The deep saline aquifers may be relatively thick and permeable. A thick and relatively impermeable formation strata may be located over deep saline aquifers. For example, 500 m or more of shale may be located above the deep saline aquifer. The water in the deep saline aquifer may be unusable for agricultural or other common uses because of the high mineral content in the

water. Over time, the minerals in the water may react with introduced sour gas to form precipitates in the deep saline aquifer. The deep saline aquifer used to store sour gas may be below the treatment area, at another location in the same formation, or in another formation. If the deep saline aquifer is located at another location in the same formation or in another formation, the sour gas may be transported to the deep saline aquifer by pipeline.

In some embodiments, injection wells used to inject sour gas may be vertical, slanted, and/or directionally steered wells with a significant horizontal or near horizontal portion. The horizontal or near horizontal portion of the injection well may be located near or at the bottom of the deep saline aquifer. FIG. **199** depicts a representation of an embodiment of a system for injection of sour gases produced from the in situ heat treatment process into the deep saline aquifer. Formation fluids may be produced from hydrocarbon layer **460**. In certain embodiments, formation fluids are produced using an in situ heat treatment process through production well **206**. The sour gas (for example, gas including at least carbon dioxide and hydrogen sulfide) may be separated from the formation fluids in gas/liquid separator **2108** using known gas/liquid separation techniques.

The separated sour gas may be transported to formation **2110** via conduit **2118** (for example, a pipeline). Formation **2110** may include aquifer **2112** (for example, a deep saline aquifer) and barrier portion **2114** (for example, shale). The sour gas may be injected into deep saline aquifer **2112** through injection well **2116**. Injection well **2116** may have vertical portion **2122** and horizontal portion **2124**. Horizontal portion **2124** may be near or at the bottom of deep saline aquifer **2112**. The sour gas may be less dense than formation fluid in the deep saline aquifer. The sour gas may diffuse upwards in the aquifer towards barrier layer **2114**. Horizontal portion **2124** may allow injection of the sour gas in a large portion of deep saline aquifer **2112**. Openings in horizontal portion **2124** may be critical flow orifices so that fluid is introduced substantially equally along the length of the horizontal portion.

Cement **2120** may be used to seal conduit **2118** in formation. Cement **2120** used in injection wellbores to form seals at the surface and/or at an interface of deep saline aquifer with barrier layer **2114** may be selected so that the cement does not degrade due to the temperature, pressure and chemical environment due to exposure to sour gas.

The deep saline aquifer or aquifers used to store sour gas may be at sufficient depth such that the carbon dioxide in the sour gas is introduced in the formation in a supercritical state. Supercritical carbon dioxide injection may maximize the density of the fluid introduced into the formation. The depths of outlets of injection wells used to introduce acidic gases in the formation may be 900 m or more below the surface.

Injection of sour gas into a non-producing formation and/or using sour gas as flooding agents are described in U.S. Pat. No. 7,128,150 to Thomas et al.; U.S. Pat. No. RE39,244 to Eaton; U.S. Pat. No. RE39,077 to Eaton; U.S. Pat. No. 6,755,251 to Thomas et al.; U.S. Pat. No. 6,283,230 to Peters, all of which are incorporated by reference as if fully set forth herein.

During production of formation fluids from a subsurface formation, acidic gases may react with water in the formation and produce acids. For example, carbonic acid may be produced from the reaction of carbon dioxide with water during heating of the formation. Portions of wells made of certain materials, such as carbon steel, may start to deteriorate or corrode in the presence of the produced acids. To inhibit corrosion due to produced acids (for example, carbonic acid), fluids and/or polymers (for example, corrosion inhibitors, foaming agents, surfactants, basic fluids, hydrocarbons, high density polyethylene, or mixtures thereof) may be introduced in the wellbore to neutralize and/or dissolve the acids.

In some embodiments, hydrogen sulfide and/or carbon dioxide are separated from the produced gases and introduced into one or more wellbores in a subsurface formation. Water present in the gas introduced into the formation may interact with hydrogen sulfide to form a sulfide layer on metal surfaces of the injection well. Formation of the sulfide layer may inhibit further corrosion of the metal surfaces of the injection well by carbonic acid and/or other acids. The formation of the sulfide layer may allow for the use of carbon steel or other relatively inexpensive alloys during the introduction of sour gas into subsurface formations.

In certain embodiments, a temperature measurement tool assesses the active impedance of an energized heater. The temperature measurement tool may utilize the frequency domain analysis algorithm associated with Partial Discharge measurement technology (PD) coupled with timed domain reflectometer measurement technology (TDR). A set of frequency domain analysis tools may be applied to a TDR signature. This process may provide unique information in the analysis of the energized heater such as, but not limited to, an impedance log of the entire length of the heater per unit length. The temperature measurement tool may provide certain advantages for assessing the temperature of a downhole heater.

In certain embodiments, the temperature measurement tool assesses the impedance per unit length and gives a profile on the entire length of the heated section of the heater. The impedance profile may be used in association with laboratory data for the heater (such as temperature and resistance profiles for heaters measured at various loads and frequencies) to assess the temperature per unit length of the heated section. The impedance profile may also be used to assess various computer models for heaters that are used in association with the reservoir simulations.

In certain embodiments, the temperature measurement tool assesses an accurate impedance profile of a heater in a specific formation after a number of heater wells have been installed and energized in the specific formation. The accurate impedance profile may assess the actual reactive and real power consumption for each heater that is used similarly. This information may be used to properly size surface electrical distribution equipment and/or eliminate any extra capacity designed to accommodate any anticipated heater impedance turndown ratio or any unknown power factor or reactive power consumption for the heaters.

In certain embodiments, the temperature measurement tool is used to troubleshoot malfunctioning heaters and assess the impedance profile of the length of the heated section. The impedance profile may be able to accurately predict the location of a faulted section and its relative impedance to ground. This information may be used to accurately assess the appropriate reduction in surface voltage to allow the heater to continue to operate in a limited capacity. This method may be more preferable than abandoning the heater in the formation.

In certain embodiments, frequency domain PD testing offers an improved set of PD characterization tools. A basic set of frequency domain PD testing tools are described in "The Case for Frequency Domain PD Testing In The Context Of Distribution Cable", Steven Boggs, Electrical Insulation Magazine, IEEE, Vol. 19, Issue 4, July-August 2003, pages 13-19, which is incorporated by reference as if fully set forth herein. Frequency domain PD detection sensitivity under field conditions may be one to two orders of magnitude

greater than for time domain testing as a result of there not being a need to trigger on the first PD pulse above the broadband noise, and the filtering effect of the cable between the PD detection site and the terminations. As a result of this greatly increased sensitivity and the set of characterization tools, frequency domain PD testing has been developed into a highly sensitive and reliable tool for characterizing the condition of distribution cable during normal operation while the cable is energized, the sensitivity and accuracy of which have been confirmed through independent testing.

EXAMPLES

Non-restrictive examples are set forth below.

Temperature Limited Heater Experimental Data

FIGS. **200-215** depict experimental data for temperature limited heaters. FIG. **200** depicts electrical resistance (Ω) versus temperature (° C.) at various applied electrical currents for a 446 stainless steel rod with a diameter of 2.5 cm and a 410 stainless steel rod with a diameter of 2.5 cm. Both rods had a length of 1.8 m. Curves **964-970** depict resistance profiles as a function of temperature for the 446 stainless steel rod at 440 amps AC (curve **964**), 450 amps AC (curve **966**), 500 amps AC (curve **968**), and 10 amps DC (curve **970**). Curves **972-978** depict resistance profiles as a function of temperature for the 410 stainless steel rod at 400 amps AC (curve **972**), 450 amps AC (curve **974**), 500 amps AC (curve **976**), 10 amps DC (curve **978**). For both rods, the resistance gradually increased with temperature until the Curie temperature was reached. At the Curie temperature, the resistance fell sharply. Above the Curie temperature, the resistance decreased slightly with increasing temperature. Both rods show a trend of decreasing resistance with increasing AC current. Accordingly, the turndown ratio decreased with increasing current. Thus, the rods provide a reduced amount of heat near and above the Curie temperature of the rods. In contrast, the resistance gradually increased with temperature through the Curie temperature with the applied DC current.

FIG. **201** shows electrical resistance (L) profiles as a function of temperature (° C.) at various applied electrical currents for a copper rod contained in a conduit of Sumitomo HCM12A (a high strength 410 stainless steel). The Sumitomo conduit had a diameter of 5.1 cm, a length of 1.8 m, and a wall thickness of about 0.1 cm. Curves **980-990** show that at all applied currents (**980**: 300 amps AC; **982**: 350 amps AC; **984**: 400 amps AC; **986**: 450 amps AC; **988**: 500 amps AC; **990**: 550 amps AC), resistance increased gradually with temperature until the Curie temperature was reached. At the Curie temperature, the resistance fell sharply. As the current increased, the resistance decreased, resulting in a smaller turndown ratio.

FIG. **202** depicts electrical resistance (Ω) versus temperature (° C.) at various applied electrical currents for a temperature limited heater. The temperature limited heater included a 4/0 MGT-1000 furnace cable inside an outer conductor of ¾" Schedule 80 Sandvik (Sweden) 4C54 (446 stainless steel) with a 0.30 cm thick copper sheath welded onto the outside of the Sandvik 4C54 and a length of 1.8 m. Curves **1000** through **1018** show resistance profiles as a function of temperature for AC applied currents ranging from 40 amps to 500 amps (**1000**: 40 amps; **1002**: 80 amps; **1004**: 120 amps; **1006**: 160 amps; **1008**: 250 amps; **1010**: 300 amps; **1012**: 350 amps; **1014**: 400 amps; **1016**: 450 amps; **1018**: 500 amps). FIG. **203** depicts the raw data for curve **1014**. FIG. **204** depicts the data for selected curves **1010**, **1012**, **1014**, **1016**, **1018**, and **1020**. At lower currents (below 250 amps), the resistance increased with increasing temperature up to the Curie temperature. At the Curie temperature, the resistance fell sharply. At higher currents (above 250 amps), the resistance decreased slightly with increasing temperature up to the Curie temperature. At the Curie temperature, the resistance fell sharply. Curve **1020** shows resistance for an applied DC electrical current of 10 amps. Curve **1020** shows a steady increase in resistance with increasing temperature, with little or no deviation at the Curie temperature.

FIG. **205** depicts power (watts per meter (W/m)) versus temperature (° C.) at various applied electrical currents for a temperature limited heater. The temperature limited heater included a 4/0 MGT-1000 furnace cable inside an outer conductor of ¾" Schedule 80 Sandvik (Sweden) 4C54 (446 stainless steel) with a 0.30 cm thick copper sheath welded onto the outside of the Sandvik 4C54 and a length of 1.8 m. Curves **1022-1030** depict power versus temperature for AC applied currents of 300 amps to 500 amps (**1022**: 300 amps; **1024**: 350 amps; **1026**: 400 amps; **1028**: 450 amps; **1030**: 500 amps). Increasing the temperature gradually decreased the power until the Curie temperature was reached. At the Curie temperature, the power decreased rapidly.

FIG. **206** depicts electrical resistance (mΩ) versus temperature (° C.) at various applied electrical currents for a temperature limited heater. The temperature limited heater included a copper rod with a diameter of 1.3 cm inside an outer conductor of 2.5 cm Schedule 80 410 stainless steel pipe with a 0.15 cm thick copper Everdur™ (DuPont Engineering, Wilmington, Del., U.S.A.) welded sheath over the 410 stainless steel pipe and a length of 1.8 m. Curves **1032-1042** show resistance profiles as a function of temperature for AC applied currents ranging from 300 amps to 550 amps (**1032**: 300 amps; **1034**: 350 amps; **1036**: 400 amps; **1038**: 450 amps; **1040**: 500 amps; **1042**: 550 amps). For these AC applied currents, the resistance gradually increases with increasing temperature up to the Curie temperature. At the Curie temperature, the resistance falls sharply. In contrast, curve **1044** shows resistance for an applied DC electrical current of 10 amps. This resistance shows a steady increase with increasing temperature, and little or no deviation at the Curie temperature.

FIG. **207** depicts data of electrical resistance (me) versus temperature (° C.) for a solid 2.54 cm diameter, 1.8 m long 410 stainless steel rod at various applied electrical currents. Curves **1046**, **1048**, **1050**, **1052**, and **1054** depict resistance profiles as a function of temperature for the 410 stainless steel rod at 40 amps AC (curve **1052**), 70 amps AC (curve **1054**), 140 amps AC (curve **1046**), 230 amps AC (curve **1048**), and 10 amps DC (curve **1050**). For the applied AC currents of 140 amps and 230 amps, the resistance increased gradually with increasing temperature until the Curie temperature was reached. At the Curie temperature, the resistance fell sharply. In contrast, the resistance showed a gradual increase with temperature through the Curie temperature for the applied DC current.

FIG. **208** depicts data of electrical resistance (mΩ) versus temperature (° C.) for a composite 1.75 inch (1.9 cm) diameter, 6 foot (1.8 m) long Alloy 42-6 rod with a 0.375 inch diameter copper core (the rod has an outside diameter to copper diameter ratio of 2:1) at various applied electrical currents. Curves **1056**, **1058**, **1060**, **1062**, **1064**, **1066**, **1068**, and **1070** depict resistance profiles as a function of temperature for the copper cored alloy 42-6 rod at 300 A AC (curve **1056**), 350 A AC (curve **1058**), 400 A AC (curve **1060**), 450 A AC (curve **1062**), 500 A AC (curve **1064**), 550 A AC (curve **1066**), 600 A AC (curve **1068**), and 10 A DC (curve **1070**). For the applied AC currents, the resistance decreased gradually

with increasing temperature until the Curie temperature was reached. As the temperature approaches the Curie temperature, the resistance decreased more sharply. In contrast, the resistance showed a gradual increase with temperature for the applied DC current.

FIG. **209** depicts data of power output (watts per foot (W/ft)) versus temperature (° C.) for a composite 1.75 inch (1.9 cm) diameter, 6 foot (1.8 m) long Alloy 42-6 rod with a 0.375 inch diameter copper core (the rod has an outside diameter to copper diameter ratio of 2:1) at various applied electrical currents. Curves **1072**, **1074**, **1076**, **1078**, **1080**, **1082**, **1084**, and **1086** depict power as a function of temperature for the copper cored alloy 42-6 rod at 300 A AC (curve **1072**), 350 A AC (curve **1074**), 400 A AC (curve **1076**), 450 A AC (curve **1078**), 500 A AC (curve **1080**), 550 A AC (curve **1082**), 600 A AC (curve **1084**), and 10 A DC (curve **1086**). For the applied AC currents, the power output decreased gradually with increasing temperature until the Curie temperature was reached. As the temperature approaches the Curie temperature, the power output decreased more sharply. In contrast, the power output showed a relatively flat profile with temperature for the applied DC current.

FIG. **210** depicts data for values of skin depth (cm) versus temperature (° C.) for a solid 2.54 cm diameter, 1.8 m long 410 stainless steel rod at various applied AC electrical currents. The skin depth was calculated using EQN. 10:

$$\delta = R_1 - R_1 \times (1 - (1/R_{AC}/R_{DC}))1/2; \quad \text{(EQN. 10)}$$

where δ is the skin depth, R_1 is the radius of the cylinder, R_{AC} is the AC resistance, and R_{DC} is the DC resistance. In FIG. **210**, curves **1088-1106** show skin depth profiles as a function of temperature for applied AC electrical currents over a range of 50 amps to 500 amps (**1088**: 50 amps; **1090**: 100 amps; **1092**: 150 amps; **1094**: 200 amps; **1096**: 250 amps; **1098**: 300 amps; **1100**: 350 amps; **1102**: 400 amps; **1104**: 450 amps; **1106**: 500 amps). For each applied AC electrical current, the skin depth gradually increased with increasing temperature up to the Curie temperature. At the Curie temperature, the skin depth increased sharply.

FIG. **211** depicts temperature (° C.) versus time (hrs) for a temperature limited heater. The temperature limited heater was a 1.83 m long heater that included a copper rod with a diameter of 1.3 cm inside a 2.5 cm Schedule XXH 410 stainless steel pipe and a 0.325 cm copper sheath. The heater was placed in an oven for heating. Alternating current was applied to the heater when the heater was in the oven. The current was increased over two hours and reached a relatively constant value of 400 amps for the remainder of the time. Temperature of the stainless steel pipe was measured at three points at 0.46 m intervals along the length of the heater. Curve **1108** depicts the temperature of the pipe at a point 0.46 m inside the oven and closest to the lead-in portion of the heater. Curve **1110** depicts the temperature of the pipe at a point 0.46 m from the end of the pipe and furthest from the lead-in portion of the heater. Curve **1112** depicts the temperature of the pipe at about a center point of the heater. The point at the center of the heater was further enclosed in a 0.3 m section of 2.5 cm thick Fiberfrax® (Unifrax Corp., Niagara Falls, N.Y., U.S.A.) insulation. The insulation was used to create a low thermal conductivity section on the heater (a section where heat transfer to the surroundings is slowed or inhibited (a "hot spot")). The temperature of the heater increased with time as shown by curves **1112**, **1110**, and **1108**. Curves **1112**, **1110**, and **1108** show that the temperature of the heater increased to about the same value for all three points along the length of the heater. The resulting temperatures were substantially independent of the added Fiberfrax® insulation. Thus, the operating temperatures of the temperature limited heater were substantially the same despite the differences in thermal load (due to the insulation) at each of the three points along the length of the heater. Thus, the temperature limited heater did not exceed the selected temperature limit in the presence of a low thermal conductivity section.

FIG. **212** depicts temperature (° C.) versus log time (hrs) data for a 2.5 cm solid 410 stainless steel rod and a 2.5 cm solid 304 stainless steel rod. At a constant applied AC electrical current, the temperature of each rod increased with time. Curve **1114** shows data for a thermocouple placed on an outer surface of the 304 stainless steel rod and under a layer of insulation. Curve **1116** shows data for a thermocouple placed on an outer surface of the 304 stainless steel rod without a layer of insulation. Curve **1118** shows data for a thermocouple placed on an outer surface of the 410 stainless steel rod and under a layer of insulation. Curve **1120** shows data for a thermocouple placed on an outer surface of the 410 stainless steel rod without a layer of insulation. A comparison of the curves shows that the temperature of the 304 stainless steel rod (curves **1114** and **1116**) increased more rapidly than the temperature of the 410 stainless steel rod (curves **1118** and **1120**). The temperature of the 304 stainless steel rod (curves **1114** and **1116**) also reached a higher value than the temperature of the 410 stainless steel rod (curves **1118** and **1120**). The temperature difference between the non-insulated section of the 410 stainless steel rod (curve **1120**) and the insulated section of the 410 stainless steel rod (curve **1118**) was less than the temperature difference between the non-insulated section of the 304 stainless steel rod (curve **1116**) and the insulated section of the 304 stainless steel rod (curve **1114**). The temperature of the 304 stainless steel rod was increasing at the termination of the experiment (curves **1114** and **1116**) while the temperature of the 410 stainless steel rod had leveled out (curves **1118** and **1120**). Thus, the 410 stainless steel rod (the temperature limited heater) provided better temperature control than the 304 stainless steel rod (the non-temperature limited heater) in the presence of varying thermal loads (due to the insulation).

A 6 foot temperature limited heater element was placed in a 6 foot 347H stainless steel canister. The heater element was connected to the canister in a series configuration. The heater element and canister were placed in an oven. The oven was used to raise the temperature of the heater element and the canister. At varying temperatures, a series of electrical currents were passed through the heater element and returned through the canister. The resistance of the heater element and the power factor of the heater element were determined from measurements during passing of the electrical currents.

FIG. **213** depicts experimentally measured electrical resistance (mΩ) versus temperature (° C.) at several currents for a temperature limited heater with a copper core, a carbon steel ferromagnetic conductor, and a 347H stainless steel support member. The ferromagnetic conductor was a low-carbon steel with a Curie temperature of 770° C. The ferromagnetic conductor was sandwiched between the copper core and the 347H support member. The copper core had a diameter of 0.5". The ferromagnetic conductor had an outside diameter of 0.765". The support member had an outside diameter of 1.05". The canister was a 3" Schedule 160 347H stainless steel canister.

Data **1122** depicts electrical resistance versus temperature for 300 A at 60 Hz AC applied current. Data **1124** depicts resistance versus temperature for 400 A at 60 Hz AC applied current. Data **1126** depicts resistance versus temperature for 500 A at 60 Hz AC applied current. Curve **1128** depicts resistance versus temperature for 10A DC applied current.

The resistance versus temperature data indicates that the AC resistance of the temperature limited heater linearly increased up to a temperature near the Curie temperature of the ferromagnetic conductor. Near the Curie temperature, the AC resistance decreased rapidly until the AC resistance equaled the DC resistance above the Curie temperature. The linear dependence of the AC resistance below the Curie temperature at least partially reflects the linear dependence of the AC resistance of 347H at these temperatures. Thus, the linear dependence of the AC resistance below the Curie temperature indicates that the majority of the current is flowing through the 347H support member at these temperatures.

FIG. **214** depicts experimentally measured electrical resistance (mΩ) versus temperature (° C.) data at several currents for a temperature limited heater with a copper core, a iron-cobalt ferromagnetic conductor, and a 347H stainless steel support member. The iron-cobalt ferromagnetic conductor was an iron-cobalt conductor with 6% cobalt by weight and a Curie temperature of 834° C. The ferromagnetic conductor was sandwiched between the copper core and the 347H support member. The copper core had a diameter of 0.465". The ferromagnetic conductor had an outside diameter of 0.765". The support member had an outside diameter of 1.05". The canister was a 3" Schedule 160 347H stainless steel canister.

Data **1130** depicts resistance versus temperature for 100 A at 60 Hz. AC applied current. Data **1132** depicts resistance versus temperature for 400 A at 60 Hz AC applied current. Curve **1134** depicts resistance versus temperature for 10A DC. The AC resistance of this temperature limited heater turned down at a higher temperature than the previous temperature limited heater. This was due to the added cobalt increasing the Curie temperature of the ferromagnetic conductor. The AC resistance was substantially the same as the AC resistance of a tube of 347H steel having the dimensions of the support member. This indicates that the majority of the current is flowing through the 347H support member at these temperatures. The resistance curves in FIG. **214** are generally the same shape as the resistance curves in FIG. **213**.

FIG. **215** depicts experimentally measured power factor (y-axis) versus temperature (° C.) at two AC currents for the temperature limited heater with the copper core, the iron-cobalt ferromagnetic conductor, and the 347H stainless steel support member. Curve **1136** depicts power factor versus temperature for 100 A at 60 Hz AC applied current. Curve **1138** depicts power factor versus temperature for 400 A at 60 Hz AC applied current. The power factor was close to unity (1) except for the region around the Curie temperature. In the region around the Curie temperature, the non-linear magnetic properties and a larger portion of the current flowing through the ferromagnetic conductor produce inductive effects and distortion in the heater that lowers the power factor. FIG. **215** shows that the minimum value of the power factor for this heater remained above 0.85 at all temperatures in the experiment. Because only portions of the temperature limited heater used to heat a subsurface formation may be at the Curie temperature at any given point in time and the power factor for these portions does not go below 0.85 during use, the power factor for the entire temperature limited heater would remain above 0.85 (for example, above 0.9 or above 0.95) during use.

From the data in the experiments for the temperature limited heater with the copper core, the iron-cobalt ferromagnetic conductor, and the 347H stainless steel support member, the turndown ratio (y-axis) was calculated as a function of the maximum power (W/m) delivered by the temperature limited heater. The results of these calculations are depicted in FIG. **216**. The curve in FIG. **216** shows that the turndown ratio (y-axis) remains above 2 for heater powers up to approximately 2000 W/m. This curve is used to determine the ability of a heater to effectively provide heat output in a sustainable manner. A temperature limited heater with the curve similar to the curve in FIG. **216** would be able to provide sufficient heat output while maintaining temperature limiting properties that inhibit the heater from overheating or malfunctioning.

A theoretical model has been used to predict the experimental results. The theoretical model is based on an analytical solution for the AC resistance of a composite conductor. The composite conductor has a thin layer of ferromagnetic material, with a relative magnetic permeability $\mu_2/\mu_0>>1$, sandwiched between two non-ferromagnetic materials, whose relative magnetic permeabilities, μ_1/μ_0 and μ_3/μ_0, are close to unity and within which skin effects are negligible. An assumption in the model is that the ferromagnetic material is treated as linear. In addition, the way in which the relative magnetic permeability, μ_2/μ_0, is extracted from magnetic data for use in the model is far from rigorous.

Magnetic data was obtained for carbon steel as a ferromagnetic material. B versus H curves, and hence relative permeabilities, were obtained from the magnetic data at various temperatures up to 1100° F. and magnetic fields up to 200 Oe (oersteds). A correlation was found that fitted the data well through the maximum permeability and beyond. FIG. **217** depicts examples of relative magnetic permeability (y-axis) versus magnetic field (Oe) for both the found correlations and raw data for carbon steel. Data **1140** is raw data for carbon steel at 400° F. Data **1142** is raw data for carbon steel at 1000° F. Curve **1144** is the found correlation for carbon steel at 400° F. Curve **1146** is the found correlation for carbon steel at 1000° F.

For the dimensions and materials of the copper/carbon steel/347H heater element in the experiments above, theoretical calculations were carried out to calculate magnetic field at the outer surface of the carbon steel as a function of skin depth. Results of the theoretical calculations were presented on the same plot as skin depth versus magnetic field from the correlations applied to the magnetic data from FIG. **217**. The theoretical calculations and correlations were made for four temperatures (200° F., 500° F., 800° F., and 1100° F.) and five total root-mean-square (RMS) currents (100 A, 200 A, 300 A, 400 A, and 500 A).

FIG. **218** shows the resulting plots of skin depth (in) versus magnetic field (Oe) for all four temperatures and 400 A current. Curve **1148** is the correlation from magnetic data at 200° F. Curve **1150** is the correlation from magnetic data at 500° F. Curve **1152** is the correlation from magnetic data at 800° F. Curve **1154** is the correlation from magnetic data at 1100° F. Curve **1156** is the theoretical calculation at the outer surface of the carbon steel as a function of skin depth at 200° F. Curve **1158** is the theoretical calculation at the outer surface of the carbon steel as a function of skin depth at 500° F. Curve **1160** is the theoretical calculation at the outer surface of the carbon steel as a function of skin depth at 800° F. Curve **1162** is the theoretical calculation at the outer surface of the carbon steel as a function of skin depth at 1100° F.

The skin depths obtained from the intersections of the same temperature curves in FIG. **218** were input into equations based on theory and the AC resistance per unit length was calculated. The total AC resistance of the entire heater, including that of the canister, was subsequently calculated. A comparison between the experimental and numerical (calculated) results is shown in FIG. **219** for currents of 300 A (experimental data **1164** and numerical curve **1166**), 400 A (experimental data **1168** and numerical curve **1170**), and 500 A (experimental data **1172** and numerical curve **1174**).

Though the numerical results exhibit a steeper trend than the experimental results, the theoretical model captures the close bunching of the experimental data, and the overall values are quite reasonable given the assumptions involved in the theoretical model. For example, one assumption involved the use of a permeability derived from a quasistatic B-H curve to treat a dynamic system.

One feature of the theoretical model describing the flow of alternating current in the three-part temperature limited heater is that the AC resistance does not fall off monotonically with increasing skin depth. FIG. **220** shows the AC resistance (mΩ) per foot of the heater element as a function of skin depth (in.) at 1100° F. calculated from the theoretical model. The AC resistance may be maximized by selecting the skin depth that is at the peak of the non-monotonical portion of the resistance versus skin depth profile (for example, at about 0.23 in. in FIG. **220**).

FIG. **221** shows the power generated per unit length (W/ft) in each heater component (curve **1176** (copper core), curve **1178** (carbon steel), curve **1180** (347H outer layer), and curve **1182** (total)) versus skin depth (in.). As expected, the power dissipation in the 347H falls off while the power dissipation in the copper core increases as the skin depth increases. The maximum power dissipation in the carbon steel occurs at the skin depth of about 0.23 inches and is expected to correspond to the minimum in the power factor, as shown in FIG. **215**. The current density in the carbon steel behaves like a damped wave of wavelength $\lambda=2\pi\delta$ and the effect of this wavelength on the boundary conditions at the copper/carbon steel and carbon steel/347H interface may be behind the structure in FIG. **220**. For example, the local minimum in AC resistance is close to the value at which the thickness of the carbon steel layer corresponds to $\lambda/4$. Formulae may be developed that describe the shapes of the AC resistance versus temperature profiles of temperature limited heaters for use in simulating the performance of the heaters in a particular embodiment. The data in FIGS. **213** and **214** show that the resistances initially rise linearly, then drop off increasingly steeply towards the DC lines.

FIGS. **222** A-C compare the results of the theoretical calculations with experimental data at 300 A (FIG. **222**A), 400 A (FIG. **222**B) and 500 A (FIG. **222**C). FIG. **222**A depicts electrical resistance (mΩ) versus temperature (° F.) at 300 A. Data **1184** is the experimental data at 300 A. Curve **1186** is the theoretical calculation at 300 A. Curve **1188** is a plot of resistance versus temperature at 10 A DC. FIG. **222**B depicts electrical resistance (mΩ) versus temperature (° F.) at 400 A. Data **1190** is the experimental data at 400 A. Curve **1192** is the theoretical calculation at 400 A. Curve **1194** is a plot of resistance versus temperature at 10 A DC. FIG. **222**C depicts electrical resistance (mΩ) versus temperature (° F.) at 500 A. Data **1196** is the experimental data at 500 A. Curve **1198** is the theoretical calculation at 500 A. Curve **1200** is a plot of resistance versus temperature at 10 A DC.

Temperature Limited Heater Simulations

A numerical simulation (FLUENT available from Fluent USA, Lebanon, N.H., U.S.A.) was used to compare operation of temperature limited heaters with three turndown ratios. The simulation was done for heaters in an oil shale formation (Green River oil shale). Simulation conditions were:

- 61 m length conductor-in-conduit temperature limited heaters (center conductor (2.54 cm diameter), conduit outer diameter 7.3 cm)
- downhole heater test field richness profile for an oil shale formation
- 16.5 cm (6.5 inch) diameter wellbores at 9.14 m spacing between wellbores on triangular spacing
- 200 hours power ramp-up time to 820 watts/m initial heat injection rate
- constant current operation after ramp up
- Curie temperature of 720.6° C. for heater
- formation will swell and touch the heater canisters for oil shale richnesses at least 0.14 L/kg (35 gals/ton)

FIG. **223** displays temperature (° C.) of a center conductor of a conductor-in-conduit heater as a function of formation depth (m) for a temperature limited heater with a turndown ratio of 2:1. Curves **1202-1224** depict temperature profiles in the formation at various times ranging from 8 days after the start of heating to 675 days after the start of heating (**1202**: 8 days, **1204**: 50 days, **1206**: 91 days, **1208**: 133 days, **1210**: 216 days, **1212**: 300 days, **1214**: 383 days, **1216**: 466 days, **1218**: 550 days, **1220**: 591 days, **1222**: 633 days, **1224**: 675 days). At a turndown ratio of 2:1, the Curie temperature of 720.6° C. was exceeded after 466 days in the richest oil shale layers. FIG. **224** shows the corresponding heater heat flux (W/m) through the formation for a turndown ratio of 2:1 along with the oil shale richness (l/kg) profile (curve **1226**). Curves **1228-1260** show the heat flux profiles at various times from 8 days after the start of heating to 633 days after the start of heating (**1228**: 8 days; **1230**: 50 days; **1232**: 91 days; **1234**: 133 days; **1238**: 175 days; **1240**: 216 days; **1242**: 258 days; **1244**: 300 days; **1236**: 341 days; **1246**: 383 days; **1248**: 425 days; **1250**: 466 days; **1252**: 508 days; **1254**: 550 days; **1256**: 591 days; **1258**: 633 days; **1260**: 675 days). At a turndown ratio of 2:1, the center conductor temperature exceeded the Curie temperature in the richest oil shale layers.

FIG. **225** displays heater temperature (° C.) as a function of formation depth (m) for a turndown ratio of 3:1. Curves **1262-1284** show temperature profiles through the formation at various times ranging from 12 days after the start of heating to 703 days after the start of heating (**1262**: 12 days; **1264**: 33 days; **1266**: 62 days; **1268**: 102 days; **1270**: 146 days; **1272**: 205 days; **1274**: 271 days; **1276**: 354 days; **1278**: 467 days; **1280**: 605 days; **1282**: 662 days; **1284**: 703 days). At a turndown ratio of 3:1, the Curie temperature was approached after 703 days. FIG. **226** shows the corresponding heater heat flux (W/m) through the formation for a turndown ratio of 3:1 along with the oil shale richness (l/kg) profile (curve **1286**). Curves **1288-1308** show the heat flux profiles at various times from 12 days after the start of heating to 605 days after the start of heating (**1288**: 12 days, **1290**: 32 days, **1292**: 62 days, **1294**: 102 days, **1296**: 146 days, **1298**: 205 days, **1300**: 271 days, **1302**: 354 days, **1304**: 467 days, **1306**: 605 days, **1308**: 749 days). The center conductor temperature never exceeded the Curie temperature for the turndown ratio of 3:1. The center conductor temperature also showed a relatively flat temperature profile for the 3:1 turndown ratio.

FIG. **227** shows heater temperature (° C.) as a function of formation depth (m) for a turndown ratio of 4:1. Curves **1310-1330** show temperature profiles through the formation at various times ranging from 12 days after the start of heating to 467 days after the start of heating (**1310**: 12 days; **1312**: 33 days; **1314**: 62 days; **1316**: 102 days, **1318**: 147 days; **1320**: 205 days; **1322**: 272 days; **1324**: 354 days; **1326**: 467 days; **1328**: 606 days, **1330**: 678 days). At a turndown ratio of 4:1, the Curie temperature was not exceeded even after 678 days. The center conductor temperature never exceeded the Curie temperature for the turndown ratio of 4:1. The center conductor showed a temperature profile for the 4:1 turndown ratio that was somewhat flatter than the temperature profile for the 3:1 turndown ratio. These simulations show that the heater temperature stays at or below the Curie temperature for a

longer time at higher turndown ratios. For this oil shale richness profile, a turndown ratio of at least 3:1 may be desirable.

Simulations have been performed to compare the use of temperature limited heaters and non-temperature limited heaters in an oil shale formation. Simulation data was produced for conductor-in-conduit heaters placed in 16.5 cm (6.5 inch) diameter wellbores with 12.2 m (40 feet) spacing between heaters using a formation simulator (for example, STARS) and a near wellbore simulator (for example, ABAQUS from ABAQUS, Inc., Providence, R.I., U.S.A.). Standard conductor-in-conduit heaters included 304 stainless steel conductors and conduits. Temperature limited conductor-in-conduit heaters included a metal with a Curie temperature of 760° C. for conductors and conduits. Results from the simulations are depicted in FIGS. **228-230**.

FIG. **228** depicts heater temperature (° C.) at the conductor of a conductor-in-conduit heater versus depth (m) of the heater in the formation for a simulation after 20,000 hours of operation. Heater power was set at 820 watts/meter until 760° C. was reached, and the power was reduced to inhibit overheating. Curve **1332** depicts the conductor temperature for standard conductor-in-conduit heaters. Curve **1332** shows that a large variance in conductor temperature and a significant number of hot spots developed along the length of the conductor. The temperature of the conductor had a minimum value of 490° C. Curve **1334** depicts conductor temperature for temperature limited conductor-in-conduit heaters. As shown in FIG. **228**, temperature distribution along the length of the conductor was more controlled for the temperature limited heaters. In addition, the operating temperature of the conductor was 730° C. for the temperature limited heaters. Thus, more heat input would be provided to the formation for a similar heater power using temperature limited heaters.

FIG. **229** depicts heater heat flux (W/m) versus time (yrs) for the heaters used in the simulation for heating oil shale. Curve **1336** depicts heat flux for standard conductor-in-conduit heaters. Curve **1338** depicts heat flux for temperature limited conductor-in-conduit heaters. As shown in FIG. **229**, heat flux for the temperature limited heaters was maintained at a higher value for a longer period of time than heat flux for standard heaters. The higher heat flux may provide more uniform and faster heating of the formation.

FIG. **230** depicts cumulative heat input (kJ/m) (kilojoules per meter) versus time (yrs) for the heaters used in the simulation for heating oil shale. Curve **1340** depicts cumulative heat input for standard conductor-in-conduit heaters. Curve **1342** depicts cumulative heat input for temperature limited conductor-in-conduit heaters. As shown in FIG. **230**, cumulative heat input for the temperature limited heaters increased faster than cumulative heat input for standard heaters. The faster accumulation of heat in the formation using temperature limited heaters may decrease the time needed for retorting the formation. Onset of retorting of the oil shale formation may begin around an average cumulative heat input of 1.1× 108 kJ/meter. This value of cumulative heat input is reached around 5 years for temperature limited heaters and between 9 and 10 years for standard heaters.

High Voltage Insulated Conductors

Simulations (using STARS) were carried out to simulate heating a formation using the heater embodiments shown in FIGS. **51** and **53**. The simulation used insulated conductor heaters with Alloy 180 cores with various diameters inside jackets with a diameter of 0.625" and magnesium oxide insulation between the cores and jackets ((for example, core **508**, electrical insulator **500**, and jacket **506** in FIGS. **51** and **53**). The various core diameters used were 0.125", 0.115", 0.1084", and 0.1016". The various core diameters produced selected amounts of heater power in the heater (using three insulated conductors in the conduit for the heater). FIG. **231** depicts a plot of heater power (W/ft) versus core diameter (in.). As shown in FIG. **231**, core diameters of 0.1016" provides a heater power of about 220 W/ft; core diameters of 0.1084" provides a heater power of about 250 W/ft; core diameters of 0.115" provides a heater power of about 280 W/ft; and core diameters of 0.125" provides a heater power of about 333 W/ft.

For the simulation, the insulated conductor heaters were placed in a conduit (for example, conduit **536** n FIGS. **51** and **53**) with an outside diameter of 1.75". The conduit with the insulated conductors was placed in another outside conduit (an outside tubular) that had an outside diameter of 3.5" and an inside diameter of 3.094". The entire heater assembly was placed in a 6" wellbore in the formation.

The simulation was used to simulate heating of 2000 feet of formation depth (target zone) below an overburden of 1225 feet. The voltage provided to the heaters was a constant voltage of 4160V. The formation properties used were for a typical tar sands formation in the Peace River field in Alberta, Canada. The heater spacing was 40 feet.

FIG. **232** depicts power, resistance, and current versus temperature (° F.) for a heater with core diameters of 0.105". Plot **2126** depicts power (W/ft) (left axis) versus temperature. Plot **2128** depicts current (I) in amps (right axis) versus temperature. Plot **2130** depicts resistance (R) in ohms (right axis) versus temperature. As shown in FIG. **232**, heater power decreased linearly with increasing temperature with resistance and current varying slightly over the temperature range.

FIG. **233** depicts actual heater power (W/ft) versus time (days) during the simulation for three different heater designs (three power outputs based on three core diameters). Plot **2132** depicts power for a heater with a designed heater output of 220 W/ft (0.1016" core diameters). Plot **2134** depicts power for a heater with a designed heater output of 250 W/ft (0.1084" core diameters). Plot **2136** depicts power for a heater with a designed heater output of 280 W/ft (0.115" core diameters). As shown in FIG. **233**, the heater power outputs decrease slightly with time but remain relatively constant over the duration of the simulation.

FIG. **234** depicts heater element temperature (core temperature) (° F.) and average formation temperature (° F.) versus time (days) for three different heater designs (three power outputs based on three core diameters). Plot **2142** depicts heater temperature for the heater with the designed heater output of 220 W/ft (0.1016" core diameters). Plot **2140** depicts heater temperature for the heater with the designed heater output of 250 W/ft (0.1084" core diameters). Plot **2138** depicts heater temperature for the heater with the designed heater output of 280 W/ft (0.115" core diameters). As shown by plots **2138**, **2140**, and **2142**, the heater temperatures increased relatively linearly over time.

Plot **2148** depicts average formation temperature using the heater with the designed heater output of 220 W/ft (0.1016" core diameters). Plot **2146** depicts average formation temperature using the heater with the designed heater output of 250 W/ft (0.1084" core diameters). Plot **2144** depicts average formation temperature using the heater with the designed heater output of 280 W/ft (0.115" core diameters). Plot **2150** depicts the target temperature for the formation of 527° F. As shown by plots **2144**, **2146**, and **2148**, the average formation temperatures increased relatively linearly over time. In addition, time to reach the target formation temperature decreased with the higher powered heaters. For the 220 W/ft heater, the time to reach the target formation temperature was about

1322 days. For the 250 W/ft heater, the time to reach the target formation temperature was about 1145 days. For the 280 W/ft heater, the time to reach the target formation temperature was about 1055 days. The simulation shows that heater embodiments shown in FIGS. **51** and **53** have relatively linear heating properties and may be used to heat subsurface formations to desired temperatures.

Triad Pattern Heater Simulation

FIG. **235** depicts cumulative gas production and cumulative oil production versus time (years) found from a STARS simulation (Computer Modelling Group, LTD., Calgary, Alberta, Canada) using the temperature limited heaters and heater pattern depicted in FIGS. **70** and **72**. Curve **1344** depicts cumulative oil production (m3) for an initial water saturation of 15%. Curve **1346** depicts cumulative gas production (m3) for the initial water saturation of 15%. Curve **1348** depicts cumulative oil production (m3) for an initial water saturation of 85%. Curve **1350** depicts cumulative gas production (m3) for the initial water saturation of 85%. As shown by the small differences between curves **1344** and **1348** for cumulative oil production and curves **1346** and **1350** for cumulative gas production, the initial water saturation does not substantially alter heating of the formation. As a result, the overall production of hydrocarbons from the formation is also not substantially changed by the initial water saturation. Using the temperature limited heaters inhibits variances in heating of the formation that otherwise may be caused by the differences in the initial water saturation.

Phase Transformation and Curie Temperature Experimental Calculations

FIG. **236** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for iron alloy TC3 (0.1% by weight carbon, 5% by weight cobalt, 12% by weight chromium, 0.5% by weight manganese, 0.5% by weight silicon). Curve **1352** depicts weight percentage of the ferrite phase. Curve **1354** depicts weight percentage of the austenite phase. The arrow points to the Curie temperature of the alloy. As shown in FIG. **236**, the phase transformation was close to the Curie temperature but did not overlap with the Curie temperature for this alloy.

FIG. **237** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for iron alloy FM-4 (0.1% by weight carbon, 5% by weight cobalt, 0.5% by weight manganese, 0.5% by weight silicon). Curve **1356** depicts weight percentage of the ferrite phase. Curve **1358** depicts weight percentage of the austenite phase. The arrow points to the Curie temperature of the alloy. As shown in FIG. **237**, the phase transformation broadened without chromium in the alloy and the phase transformation overlapped with the Curie temperature for this alloy.

Calculations for the Curie temperature (T_c) and the phase transformation behavior were done for various mixtures of cobalt, carbon, manganese, silicon, vanadium, and titanium using computational thermodynamic software (ThermoCalc is obtained from Thermo-Calc Software, Inc., (McMurray, Pa., U.S.A) and JMatPro is obtained from Sente Software, Ltd., (Guildford, United Kingdom)) to predict the effect of additional elements on Curie Temperature for selected compositions, the temperature (A_1) at which ferrite transforms to paramagnetic austenite, and the phases present at those temperatures. An equilibrium calculation temperature of 700° C. was used in all calculations to determine the Curie temperature of ferrite. As shown in TABLE 3, as the weight percentage of cobalt in the composition increased, T_c increased and A_1 decreased; however, T_c remained above A_1. An increase in the A_1 temperature may be predicted upon sufficient addition of carbide formers vanadium, titanium, niobium, tantalum, and tungsten. For example, about 0.5% by weight of carbide formers may be used in an alloy that includes about 0.1% by weight of carbon. Addition of carbide formers allows replacement of the Fe_3C carbide phase with a MC carbide phase. From the calculations, excess amounts of vanadium appeared to not have an impact on T_c, while excess amounts of other carbide formers reduced the T_c.

TABLE 3

Composition (% by weight, balance being Fe)						Calculation Results		
Co	C	Mn	Si	V	Ti	T_c (EC)	A_1 (EC)	Phases Present (~700 EC)
0	0.1	0.5	0.5	0	0	758	716	ferrite + Fe_3C (FM2)
2	0.1	0.5	0.5	0	0	776	726	ferrite + Fe_3C (FM4)
5	0.1	0.5	0.5	0	0	803	740	ferrite + Fe_3C (FM6)
8	0.1	0.5	0.5	0	0	829	752	ferrite + Fe_3C (FM8)
5	0.1	0.5	0.5	0.2	0	803	740	ferrite + Fe_3C + VC
5	0.1	0.5	0.5	0.4	0	802	773	ferrite + Fe_3C + VC
5	0.1	0.5	0.5	0.5	0	802	830	ferrite + VC
5	0.1	0.5	0.5	0.6	0	802	855	ferrite + VC
5	0.1	0.5	0.5	0.8	0	803	880	ferrite + VC
5	0.1	0.5	0.5	1.0	0	805	896	ferrite + VC
5	0.1	0.5	0.5	1.5	0	807	928	ferrite + VC
5	0.1	0.5	0.5	2.0	0	810	959	ferrite + VC
6	0.1	0.5	0.5	0.5	0	811	835	ferrite + VC
7	0.1	0.5	0.5	0.5	0	819	839	ferrite + VC
8	0.1	0.5	0.5	0.5	0	828	843	ferrite + VC
9	0.1	0.5	0.5	0.5	0	836	847	ferrite + VC
10	0.1	0.5	0.5	0.5	0	845	852	ferrite + VC
11	0.1	0.5	0.5	0.5	0	853	856	ferrite + VC
12	0.1	0.5	0.5	0.5	0	861	859	ferrite + VC
10	0.1	0.5	0.5	1.0	0	847	907	ferrite + VC
11	0.1	0.5	0.5	1.0	0	855	909	ferrite + VC
12	0.1	0.5	0.5	1.0	0	863	911	ferrite + VC
13	0.1	0.5	0.5	1.0	0	871	913	ferrite + VC
14	0.1	0.5	0.5	1.0	0	879	915	ferrite + VC
15	0.1	0.5	0.5	1.0	0	886	917	ferrite + VC
17	0.1	0.5	0.5	1.0	0	902	920	ferrite + VC
20	0.1	0.5	0.5	1.0	0	924	926	ferrite + VC
5	0.1	0.5	0.5	0	0.2	802	738	ferrite + Fe_3C + TiC
5	0.1	0.5	0.5	0	0.3	802	738	ferrite + Fe_3C + TiC
5	0.1	0.5	0.5	0	0.4	802	867	ferrite + TiC
5	0.1	0.5	0.5	0	0.45	802	896	ferrite + TiC
5	0.1	0.5	0.5	0	0.5	801	902	ferrite + TiC
5	0.1	0.5	0.5	0	1.0	795	934	ferrite + TiC
8	0.1	0.5	0.5	0	0.5	827	905	ferrite + TiC
10	0.1	0.5	0.5	0	0.5	844	908	ferrite + TiC
11	0.1	0.5	0.5	0	0.5	852	909	ferrite + TiC
12	0.1	0.5	0.5	0	0.5	860	911	ferrite + TiC
13	0.1	0.5	0.5	0	0.5	868	912	ferrite + TiC
14	0.1	0.5	0.5	0	0.5	876	914	ferrite + TiC
15	0.1	0.5	0.5	0	0.5	884	915	ferrite + TiC
17	0.1	0.5	0.5	0	0.5	899	918	ferrite + TiC
18	0.1	0.5	0.5	0	0.5	907	920	ferrite + TiC
19	0.1	0.5	0.5	0	0.5	914	921	ferrite + TiC
20	0.1	0.5	0.5	0	0.5	922	923	ferrite + TiC
21	0.1	0.5	0.5	0	0.5	929	924	ferrite + TiC
21	0.1	0.5	0.5	0	0.6	928	926	ferrite + TiC
21	0.1	0.5	0.5	0	0.7	926	928	ferrite + TiC
21	0.1	0.5	0.5	0	0.8	925	930	ferrite + TiC
21	0.1	0.5	0.5	0	1.0	922	934	ferrite + TiC
22	0.1	0.5	0.5	0	1.0	930	935	ferrite + TiC
23	0.1	0.5	0.5	0	1.0	937	936	ferrite + TiC

Several iron-cobalt alloys were prepared and their compositions are given in TABLE 4. These cast alloys were processed into rod and wire, and the measured and calculated T_c for the rods are listed. Averages of cooling and heating T_c measurements were used since no irreversible hysteresis effect was observed during heating and cooling. As shown in TABLE 4, the agreement between calculated T_c and the measured T_c was acceptable.

The measured T_c were performed by a torus technique in which a torus was wound with the sample material. A thermocouple was attached midway along the length.

TABLE 4

Alloy	Nominal Composition (% by weight, balance being Fe)				T_c (EC) (torus	T_c (EC)
Designation	Co	C	Mn	Si	technique)	(calculated)
FM1	0	0	0	0	768	770
FM2	0	0.1	0.5	0.5	—	758
FM3	5	0	0	0	—	818
FM4	5	0.1	0.5	0.5	—	803
FM5	8	0	0	0	—	842
FM6	8	0.1	0.5	0.5	—	826
FM7	10	0	0	0	863	859
FM8	10	0.1	0.5	0.5	—	846

FIG. **238** depicts the Curie temperature (horizontal bars) and phase transformation temperature range (slashed vertical bars) for several iron alloys. Column **1360** is for FM-2 iron-cobalt alloy. Column **1362** is for FM-4 iron-cobalt alloy. Column **1364** is for FM-6 iron-cobalt alloy. Column **1366** is for FM-8 iron-cobalt alloy. Column **1368** is for TC1 410 stainless steel alloy with cobalt. Column **1370** is for TC2 410 stainless steel alloy with cobalt. Column **1372** is for TC3 410 stainless steel alloy with cobalt. Column **1374** is for TC4 410 stainless steel alloy with cobalt. Column **1376** is for TC5 410 stainless steel alloy with cobalt. As shown in FIG. **238**, the iron-cobalt alloys (FM-2, FM-4, FM-6, FM-8) had large phase transformation temperature ranges that overlap with the Curie temperature. The 410 stainless steel alloys with cobalt (TC1, TC2, TC3, TC4, TC5) had small phase transformation temperature ranges. The phase transformation temperature ranges for TC1, TC2, and TC3 were above the Curie temperature. The phase transformation temperature range for TC4 was below the Curie temperature. Thus, a temperature limited heater using TC4 may self-limit at a temperature below the Curie temperature of the TC4.

FIGS. **239-242** depict the effects of alloy addition to iron-cobalt alloys. FIGS. **239** and **240** depict the effects of carbon addition to an iron-cobalt alloy. FIGS. **241** and **242** depict the effects of titanium addition to an iron-cobalt alloy.

FIG. **239** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt and 0.4% by weight manganese. Curve **1378** depicts weight percentage of the ferrite phase. Curve **1380** depicts weight percentage of the austenite phase. The arrow points to the Curie temperature of the alloy. As shown in FIG. **239**, the phase transformation was close to the Curie temperature but did not overlap with the Curie temperature for this alloy.

FIG. **240** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt, 0.4% by weight manganese, and 0.01% carbon. Curve **1382** depicts weight percentage of the ferrite phase. Curve **1384** depicts weight percentage of the austenite phase. The arrow points to the Curie temperature of the alloy. As shown in FIGS. **239** and **240**, the phase transformation broadened with the addition of carbon to the alloy with the onset of the phase transformation shifting to a lower temperature. Thus, carbon may be added to an iron alloy to lower the onset temperature and broaden the temperature range of the phase transformation.

FIG. **241** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt, 0.4% by weight manganese, and 0.085% carbon. Curve **1386** depicts weight percentage of the ferrite phase. Curve **1388** depicts weight percentage of the austenite phase. The arrow points to the Curie temperature of the alloy. As shown in FIG. **241**, the phase transformation overlapped with the Curie temperature.

FIG. **242** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for an iron-cobalt alloy with 5.63% by weight cobalt, 0.4% by weight manganese, 0.085% carbon, and 0.4% titanium. Curve **1390** depicts weight percentage of the ferrite phase. Curve **1392** depicts weight percentage of the austenite phase. The arrow points to the Curie temperature of the alloy. As shown in FIGS. **241** and **242**, the phase transformation narrowed with the addition of titanium to the alloy with the onset of the phase transformation shifting to a higher temperature. Thus, titanium may be added to an iron alloy to raise the onset temperature and narrow the temperature range of the phase transformation.

FIG. **243** depicts experimental calculations of weight percentages of ferrite and austenite phases versus temperature for 410 stainless steel type alloy (12% by weight chromium, 0.1% by weight carbon, 0.5% by weight manganese, 0.5% by weight silicon, with the balance being iron). Curve **1394** depicts weight percentage of the ferrite phase. Curve **1396** depicts weight percentage of the austenite phase. The arrow points to the Curie temperature of the alloy. As shown in FIG. **243**, the Curie temperature is reduced with the addition of chromium.

Calculations for the Curie temperature and the phase transformation behavior were done for various mixtures of cobalt, carbon, manganese, silicon, vanadium, chromium, and titanium using the computational thermodynamic software (ThermoCalc and JMatPro) to predict the effect of additional elements on Curie Temperature (T_c) for selected compositions and the temperature (A_1) at which ferrite transforms to paramagnetic austenite. An equilibrium calculation temperature of 700° C. was used in all calculations. As shown in TABLE 5, as the weight percentage of cobalt in the composition increased, T_c increased and A_1 decreased. As shown in TABLE 5, addition of vanadium and/or titanium increased A_1. The addition of vanadium may allow increased amounts of chromium to be used in Curie heaters.

TABLE 5

Composition (% by weight, balance being Fe)							Calculation Results	
Co	Cr	C	Mn	Si	V	Ti	T_c (EC)	A_1 (EC)
0	12	0.1	0.5	0.5	0	0	723	814
2	12	0.1	0.5	0.5	0	0	739	800
4	12	0.1	0.5	0.5	0	0	754	788
6	12	0.1	0.5	0.5	0	0	769	780
8	12	0.1	0.5	0.5	0	0	783	773
10	12	0.1	0.5	0.5	0	0	797	766
0	12	0.1	0.5	0.5	1	0	726	
2	12	0.1	0.5	0.5	1	0	741	
4	12	0.1	0.5	0.5	1	0	756	
6	12	0.1	0.5	0.5	1	0	770	
8	12	0.1	0.5	0.5	1	0	784	794
10	12	0.1	0.5	0.5	1	0	797	
0	12	0.1	0.5	0.5	2	0	726	
2	12	0.1	0.5	0.5	2	0	742	
6	12	0.1	0.5	0.5	2	0	772	
8	12	0.1	0.5	0.5	2	0	785	817
10	12	0.1	0.5	0.5	2	0	797	
0	12	0.1	0.5	0.5	0	0.5	718	863
2	12	0.1	0.5	0.5	0	0.5	733	825
4	12	0.1	0.5	0.5	0	0.5	747	803

TABLE 5-continued

Composition (% by weight, balance being Fe)							Calculation Results	
Co	Cr	C	Mn	Si	V	Ti	T_c (EC)	A_1 (EC)
6	12	0.1	0.5	0.5	0	0.5	761	787
8	12	0.1	0.5	0.5	0	0.5	775	775
10	12	0.1	0.5	0.5	0	0.5	788	767
0	12	0.1	0.5	0.5	1	0.5	721	
2	12	0.1	0.5	0.5	1	0.5	736	
4	12	0.1	0.5	0.5	1	0.5	750	
6	12	0.1	0.5	0.5	1	0.5	763	
8	12	0.1	0.5	0.5	1	0.5	776	
10	12	0.1	0.5	0.5	1	0.5	788	
0	12	0.1	0.5	0.5	2	0.5	725	
2	12	0.1	0.5	0.5	2	0.5	738	
4	12	0.1	0.5	0.5	2	0.5	752	
6	12	0.1	0.5	0.5	2	0.5	764	
8	12	0.1	0.5	0.5	2	0.5	777	
10	12	0.1	0.5	0.5	2	0.5	788	
0	12	0.1	0.5	0.5	0	1	712	>1000
2	12	0.1	0.5	0.5	0	1	727	877
4	12	0.1	0.5	0.5	0	1	741	836
6	12	0.1	0.5	0.5	0	1	755	810
8	12	0.1	0.5	0.5	0	1	768	794
10	12	0.1	0.5	0.5	0	1	781	780
0	12	0.1	0.5	0.5	1	1	715	
2	12	0.1	0.5	0.5	1	1	730	
4	12	0.1	0.5	0.5	1	1	743	
6	12	0.1	0.5	0.5	1	1	757	
8	12	0.1	0.5	0.5	1	1	770	821
10	12	0.1	0.5	0.5	1	1	782	
0	12	0.1	0.5	0.5	2	1	718	
2	12	0.1	0.5	0.5	2	1	732	
4	12	0.1	0.5	0.5	2	1	745	
6	12	0.1	0.5	0.5	2	1	758	
8	12	0.1	0.5	0.5	2	1	770	873
10	12	0.1	0.5	0.5	2	1	782	
0	12	0.1	0.3	0.5	0	0	727	826
2	12	0.1	0.3	0.5	0	0	742	810
4	12	0.1	0.3	0.5	0	0	758	800
6	12	0.1	0.3	0.5	0	0	772	791
8	12	0.1	0.3	0.5	0	0	786	784
10	12	0.1	0.3	0.5	0	0	800	777
0	12	0.1	0.3	0.5	1	0	730	
2	12	0.1	0.3	0.5	1	0	745	
4	12	0.1	0.3	0.5	1	0	760	
6	12	0.1	0.3	0.5	1	0	774	
8	12	0.1	0.3	0.5	1	0	787	
10	12	0.1	0.3	0.5	1	0	801	
0	12	0.1	0.3	0.5	2	0	730	
2	12	0.1	0.3	0.5	2	0	746	
4	12	0.1	0.3	0.5	2	0	762	
6	12	0.1	0.3	0.5	2	0	775	
8	12	0.1	0.3	0.5	2	0	788	
10	12	0.1	0.3	0.5	2	0	801	
0	12	0.1	0.3	0.5	0	0.5	722	
2	12	0.1	0.3	0.5	0	0.5	737	
4	12	0.1	0.3	0.5	0	0.5	751	
6	12	0.1	0.3	0.5	0	0.5	765	
8	12	0.1	0.3	0.5	0	0.5	779	
10	12	0.1	0.3	0.5	0	0.5	792	
0	12	0.1	0.3	0.5	1	0.5	725	
2	12	0.1	0.3	0.5	1	0.5	740	
4	12	0.1	0.3	0.5	1	0.5	753	
6	12	0.1	0.3	0.5	1	0.5	767	
8	12	0.1	0.3	0.5	1	0.5	780	
10	12	0.1	0.3	0.5	1	0.5	792	
0	12	0.1	0.3	0.5	2	0.5	728	
2	12	0.1	0.3	0.5	2	0.5	742	
4	12	0.1	0.3	0.5	2	0.5	755	
6	12	0.1	0.3	0.5	2	0.5	768	
8	12	0.1	0.3	0.5	2	0.5	780	
10	12	0.1	0.3	0.5	2	0.5	792	
0	12	0.1	0.3	0.5	0	1	715	
2	12	0.1	0.3	0.5	0	1	730	
4	12	0.1	0.3	0.5	0	1	745	
6	12	0.1	0.3	0.5	0	1	759	
8	12	0.1	0.3	0.5	0	1	772	

TABLE 5-continued

Composition (% by weight, balance being Fe)							Calculation Results	
Co	Cr	C	Mn	Si	V	Ti	T_c (EC)	A_1 (EC)
10	12	0.1	0.3	0.5	0	1	785	
0	12	0.1	0.3	0.5	1	1	719	
2	12	0.1	0.3	0.5	1	1	733	
4	12	0.1	0.3	0.5	1	1	747	
6	12	0.1	0.3	0.5	1	1	760	
8	12	0.1	0.3	0.5	1	1	773	834
10	12	0.1	0.3	0.5	1	1	786	
0	12	0.1	0.3	0.5	2	1	722	
2	12	0.1	0.3	0.5	2	1	736	
4	12	0.1	0.3	0.5	2	1	749	
6	12	0.1	0.3	0.5	2	1	762	
8	12	0.1	0.3	0.5	2	1	774	886
10	12	0.1	0.3	0.5	2	1	786	
7.5	12.25	0.1	0.3	0.5	0	0	781	785
8.0	12.25	0.1	0.3	0.5	0	0	785	783
8.5	12.25	0.1	0.3	0.5	0	0	788	781
9.0	12.25	0.1	0.3	0.5	0	0	792	779
9.5	12.25	0.1	0.3	0.5	0	0	795	778
10.0	12.25	0.1	0.3	0.5	0	0	798	776
6.0	12.25	0.1	0.5	0.5	0	0	767	780
6.5	12.25	0.1	0.5	0.5	0	0	771	778
7.0	12.25	0.1	0.5	0.5	0	0	774	776
7.5	12.25	0.1	0.5	0.5	0	0	778	774
7.5	12.25	0.1	0.3	0.5	1	0	782	812
8.0	12.25	0.1	0.3	0.5	1	0	786	809
8.5	12.25	0.1	0.3	0.5	1	0	789	806
9.0	12.25	0.1	0.3	0.5	1	0	792	804
9.5	12.25	0.1	0.3	0.5	1	0	795	801
10.0	12.25	0.1	0.3	0.5	1	0	799	799
7.5	12.25	0.1	0.5	0.5	1	0	779	801
8.0	12.25	0.1	0.5	0.5	1	0	782	799
8.5	12.25	0.1	0.5	0.5	1	0	785	796
9.0	12.25	0.1	0.5	0.5	1	0	788	793
9.5	12.25	0.1	0.5	0.5	1	0	792	791
10.0	12.25	0.1	0.5	0.5	1	0	795	788
7.5	12.25	0.1	0.3	0.5	0	0.5	774	788
8.0	12.25	0.1	0.3	0.5	0	0.5	777	785
8.5	12.25	0.1	0.3	0.5	0	0.5	781	782
9.0	12.25	0.1	0.3	0.5	0	0.5	784	780
7.5	12.25	0.1	0.5	0.5	0	0.5	770	777
8.0	12.25	0.1	0.5	0.5	0	0.5	774	774
8.5	12.25	0.1	0.5	0.5	0	0.5	777	771
7.5	12.25	0.1	0.3	0.5	1	0.5	775	823
8.0	12.25	0.1	0.3	0.5	1	0.5	778	819
8.5	12.25	0.1	0.3	0.5	1	0.5	782	814
9.0	12.25	0.1	0.3	0.5	1	0.5	785	810
9.5	12.25	0.1	0.3	0.5	1	0.5	788	807
10.0	12.25	0.1	0.3	0.5	1	0.5	791	803
10.5	12.25	0.1	0.3	0.5	1	0.5	794	800
11.0	12.25	0.1	0.3	0.5	1	0.5	797	797
7.5	12.25	0.1	0.5	0.5	1	0.5	771	811
8.0	12.25	0.1	0.5	0.5	1	0.5	775	807
8.5	12.25	0.1	0.5	0.5	1	0.5	778	803
9.0	12.25	0.1	0.5	0.5	1	0.5	781	799
9.5	12.25	0.1	0.5	0.5	1	0.5	784	796
10.0	12.25	0.1	0.5	0.5	1	0.5	787	792
10.5	12.25	0.1	0.5	0.5	1	0.5	790	789

Several iron-chromium alloys were prepared and their compositions are given in TABLE 6. These cast alloys were processed into rods and wire, and the calculated and measured T_c using a torus technique is listed, along with calorimetry measurements.

TABLE 6

Alloy	Actual Composition (% by weight, balance Fe)							T_C (EC)	T_C (EC)	T_C (EC)	A_1 (EC)
Designation	Co	Cr	C	Mn	Si	V	Ti	(torus)	(calorimetry)	(calculated)	(calculated)
TC1b	0.02	13.2	0.08	0.45	0.69	0	0.01	692	—	717	819
TC2	2.44	12.3	0.10	0.48	0.47	0	0.01	—	—	742	793
TC3	4.81	12.3	0.10	0.48	0.46	0	0.01	—	—	761	783
TC4	9.75	12.2	0.07	0.49	0.47	0	0.01	759/ 682*	—	793	765
TC5	9.80	12.2	0.10	0.48	0.46	1.02	0.01	—	—	795	790
TC6	7.32	12.3	0.12	0.29	0.46	0.89	0.46	754	752	775	813
TC7	7.46	12.1	0.11	0.27	0.46	0.92	0	747	757	785	811
TC8	7.49	12.1	0.11	0.28	0.45	0	0	761	774	784	786

*Two values represent T_C during heating and T_C during subsequent cooling.

Modeling of Alloy Phase Behavior

Modeling of phase behavior for different improved alloy compositions to determine compositions that contain increased amounts of phases that contribute positively to physical properties was performed. Compositions such as Cu, Z, M(C,N), M_2(C,N), and $M_{23}C_6$, may minimize the amount of phases that are embrittling phases such as G, sigma, laves, and chi. There may be other reasons to include certain components. For example, silicon is typically included in stainless steel alloys to improve processing properties, and nickel and chromium are typically included in the alloys to impart corrosion resistance. When two components may be included to accomplish the same result, then the less expensive component may be beneficially included. For example, to the extent manganese may be substituted for nickel without sacrificing performance, such a substitution may reduce the cost of the alloy at current component prices.

The effect of total phase content of the alloys similar to those described above has been found to be approximated by the equation:

$$\sigma_r = 1.0235(TPC) + 5.5603. \quad \text{(EQN. 11)}$$

Where σ_r is the creep rupture strength for one thousand hours at 800° C. in kilo-pound per square inch (ksi) and TPC is the total phase content calculated for the composition. This estimate was further improved by only including in the TPC term the amount of Cu phase, Z phase, M(C,N) phase, M_2(C,N) phase, and $M_{23}C_6$ phase (the "desirable phases"), and calculating the constants on this basis. Another improvement to this estimate may be to use only the difference between the desirable phases present at the annealing temperature and at 800° C. Thus, the components that do not go into solution in the annealing process were not considered because they do not add significantly to the strength of the alloys at elevated temperatures. For example, the difference between the amount of Cu phase, Z phase, M(C,N) phase, M_2(C,N) phase, and $M_{23}C_6$ phase present based on equilibrium calculations at annealing temperatures less the amount calculated to be present at 800° C. may be 1% by weight of the alloy, or it could be 1.5% by weight of the alloy or 2% by weight of the alloy, to result in an alloy with good high temperature strength. Further, the annealing temperature may be 1200° C., or it may be 1250° C., or it may be 1300° C.

The improved alloys may be further understood by modeling the addition, or reduction, of different metals to determine the effect of changing amounts of that metal on the phase content of the alloy. For example, with a starting composition by weight of: 20% chromium, 3% copper, 4% manganese, 0.3% molybdenum, 0.8% niobium, 12.5% nickel, 0.5% silicon, 1% tungsten, 0.1% carbon and 0.25% elemental nitrogen, modeling with varying amounts of chromium results in included phases of $M_{23}C_6$, M(C,N), M_2(C,N), Z, Cu, chi, laves, G, and sigma at 800° C., according to FIG. **244**. The amount of these phases plotted in each of FIGS. **244-254** is the calculated amount of these phases at 800° C. In FIGS. **244-254**, curve **1398** refers to $M_{23}C_6$, curve **1400** refers to M_2(C,N) phase, curve **1402** refers to Z phase, curve **1404** refers to Cu phase, curve **1406** refers to sigma phase, curve **1408** refers to chi phase, curve **1410** refers to G phase, curve **1412** refers to laves phase, and curve **1414** refers to M(C,N) phase.

FIG. **244** depicts the weight percentages of phases versus weigh percentage of chromium in the alloy. As shown, the weight percentages of phases **1398**, **1400**, **1402**, and **1404** remained relatively constant from 20% by weight to 30% by weight of chromium, while sigma phase **1406** increased linearly above a chromium content of 20.5% by weight. Thus, from the modeling, a chromium content between 20% by weight and 20.5% by weight of the alloy may be favorable.

FIG. **245** depicts weight percentages of phases versus the weight percentage of silicon (Si) in the alloy. As shown in FIG. **245**, varying the silicon content of the alloy resulted in sigma phase **1406** appearing at levels above 1.2% by weight silicon and chi phase **1408** appearing above a content of 1.4% by weight silicon. G phase **1410** appeared above 1.6% by weight silicon and increased as the weight percent of silicon increased. With increasing weight percentages of silicon, phases **1398**, **1400**, and **1402**, remained relatively constant and a slight increase in Cu phase **1404** was predicted. The appearance of sigma phase **1406**, chi phase **1408** and G phase **1410** indicates that a silicon content below 1.2% by weight in this alloy may be favorable.

FIG. **246** depicts weight percentage of phases formed versus weight percentage of tungsten in the alloy. As shown in FIG. **246**, varying the weight percentage of tungsten in the alloy resulted in sigma phase **1406** appearing at 1.4% by weight tungsten. Laves phase **1412** appeared at 1.5% by weight tungsten and increased with increasing weight percentage of tungsten. Thus, the model predicts a tungsten content in this alloy of below 1.3% by weight may be favorable.

FIG. **247** depicts weight percentage of phases formed verse the weight percentage of niobium in the alloy. As shown in FIG. **247**, modeling predicted that weight percentage of Z phase **1402** increased in a linear fashion as the weight percentage of niobium increased in the alloy until the niobium content of the alloy reached 1.55% by weight. As the niobium content increased from 0.1% by weight to 1.4% by weight, M_2(C,N) phase **1400** decreased fairly linearly. The decrease

in $M_2(C,N)$ phase **1400** was compensated for by the increase in Z phase **1402**, Cu phase **1404** and $M_{23}C_6$ phase **1398**. Above 1.5% by weight niobium in the alloy, sigma phase **1406** increased rapidly, Z phase **1402** decreased, $M_{23}C_6$ phase **1398** decreased, and M(C,N) phase **1414** appeared. Thus, the niobium content in the alloy of at most 1.5% by weight may maximize the weight percent of phases **1398**, **1400**, **1402**, and **1404** and avoid minimizing the weight percent of sigma phase **1406** formed in the alloy. In order to make the alloy hot-workable, it was found that at least 0.5% by weight of niobium was desirable. Thus, in some embodiments, the alloy contains from 0.5% by weight to 1.5% by weight or from 0.8% by weight to 1% by weight niobium.

FIG. **248** depicts weight percentages of phases formed versus weight percentage of carbon. As shown in FIG. **248**, weight percentage of sigma phase **1406** was predicted to decrease as the weight percentage of carbon in the alloy increased from 0 to 0.06. The weight percentage of $M_{23}C_6$ phase **1398** was predicted to increase linearly as the weight percentage of carbon in the alloy increased to at most 0.5. $M_2(C,N)$ phase **1400**, Z phase **1402**, and Cu phase **1404** was predicted to remain relatively constant as the weight percentage of carbon increased in the alloy. Since, sigma phase **1406** decreased after 0.06% by weight carbon, a carbon content of 0.06% by weight to 0.2% weight in the alloy may be beneficial.

FIG. **249** depicts weight percentage of phases formed versus weight percentage of nitrogen. As shown in FIG. **249**, the content of nitrogen in the alloy increased from 0% by weight to 0.15% by weight, a content of sigma phase **1406** decreased from 7% by weight to 0% by weight, a content of M(C,N) phase **1414** decreased from 1% by weight to 0% by weight, a content of $M_{23}C6$ phase **1398** increased from 0% by weight to 1.9% by weight, and a content of Z phase **1402** increased from 0% by weight to 1.4% by weight. Above a nitrogen content of 0.15% by weight in the alloy, $M_2(C,N)$ phase **1400** appeared and increased with as the content of nitrogen in the alloy increases. Thus, a nitrogen content in a range of 0.15% to 0.5% by weight in the alloy may be beneficial.

FIG. **250** depicts weight percentage of phases formed versus weight percentage of titanium (Ti). As shown in FIG. **250**, varying the weight percentage of titanium from 0.19 to 1 may contribute to an increase in a weight percentage of sigma phase **1406** from 0 to 7.5 in the alloy. Thus, a titanium content of below 0.2% by weight in the alloy may be desirable. As shown, as the content of titanium increased from 0% by weight to 0.2% by weight, an increase in the weight percentage of M(C,N) phase **1414** occurred, a decrease in the weight percentage of $M_2(C,N)$ phase **1400** occurred, and a decrease in the weight percentage Z phase **1402** occurred. The decreases in the amount of $M_2(C,N)$ phase **1400** and Z phase **1402** appear to offset the increase in the weight percent of M(C,N) phase **1414**. Thus, inclusion of Ti in the alloy may be for purposes other than for increasing the amount of phases that improve properties of the alloy.

FIG. **251** depicts weight percentage of phases formed versus weight percentage of copper. As shown in FIG. **251**, weight percentages of $M_{23}C_6$ phase **1398**, $M_2(C,N)$ phase **1400**, and Z phase **1402** did not vary significantly as the weight percent of copper in the alloy increased. When the content of copper in the alloy increases above 2.5% by weight, Cu phase **1404** increased significantly. Thus, in some embodiments, it is desirable to have more than 3% by weight copper in the alloy. In some embodiments, 10% by weight of copper in the alloy is beneficial.

FIG. **252** depicts weight percentage of phases formed versus weight percentage of manganese. As shown in FIG. **252**, varying the content of manganese in the alloy did not greatly affect the weight percentage of beneficial phases $M_{23}C_6$ phase **1398**, $M_2(C,N)$ phase **1400**, Z phase **1402**, and Cu phase **1404** in the alloy. The amount of manganese may therefore be varied in order to reduce cost, or for other reasons, without significantly effecting the high temperature properties of the alloy, with an acceptable range of manganese content of the alloy being from 2% by weight to 10% by weight.

FIG. **253** depicts weight percentage of phases formed versus weight percentage of nickel. As shown in FIG. **253**, as the nickel content of the alloy increased above 8.4% by weight, a decrease in sigma phase **1406** was observed. As the Ni content of the alloy was increased from 8% by weight to 17% by weight, Cu phase **1404** decreased almost linearly until it disappeared at 17% by weight and a small increase in the weight percentage of $M_2(C,N)$ phase **1400** was predicted. From the model, a content of nickel of 10% by weight to 15% by weight in the alloy, or in other embodiments, a nickel content of 12% by weight to 13% by weight in the alloy may avoid the formation of sigma phase **1406**, while improvements in corrosion properties offset any detrimental effect of less Cu phase **1404**.

FIG. **254** depicts weight percentage of phases formed versus weight percentage of molybdenum. As shown in FIG. **254**, the weight percentage of beneficial phases $M_{23}C_6$ phase **1398**, $M_2(C,N)$ phase **1400**, Z phase **1402**, and Cu phase **1404** remained relatively constant as the weight percentage of molybdenum in the alloy was varied. As Mo content of the alloy exceeded 0.65% by weight, the weight percentages of sigma phase **1406** and chi phase **1408** in the alloy increased significantly with no significant changes in the other phases. The content of molybdenum in the alloy, in some embodiments, may therefore be limited to at most 0.5% by weight.

Alloy Examples

Alloys A through N were prepared according to TABLE 7. Measured compositions are included in the TABLE 7 when such measurements are available. The total phase content of the alloys is calculated for the listed composition.

TABLE 7

		% by weight											
	Alloy	Cr	Cu	Mn	Mo	Nb	Ni	Si	W	C	N	Ti	800° C. Total Phase
A	Target	20	—	4	0.3	0.8	12.5	0.5	—	0.09	0.25	—	
	Actual[b]	19	—	4.2	0.3	0.8	12.5	0.5	—	0.09	0.24	—	3.35[a]
B	Target	20	3	4	0.3	0.8	13	0.5	1	0.09	0.25	—	
	Actual-1[b]	20	3	4	0.3	0.77	13	0.5	1	0.09	0.26	—	4.40[a]
	Actual-2[b]	20.35	2.94	4.09	0.28	0.76	12.52	0.44	1.03	0.09	0.23	—	

TABLE 7-continued

		% by weight										
	Alloy	Cr	Cu	Mn	Mo	Nb	Ni	Si	W	C	N	Ti	800° C. Total Phase
	Actual-3[b,c]	18.78	2.94	2.85	0.29	0.65	12.75	0.39	1.03	0.10	0.23	0.004	
C	Target	20	4.5	4	0.3	0.8	12.5	0.5	1	0.15	0.25	—	7.15
	Actual-1[b]	18.74	4.37	3.68	0.29	0.77	13.00	0.43	1.18	0.11	0.17	0.002	5.45
	Actual-2[c,b]	20.48	4.75	4.13	0.30	0.07	12.81	0.52	1.18	0.17	0.14	0.01	6.23
D	Target	20	4.5	4	0.3	0	12.5	0.5	1	0.2	0.5	0	10
E	Target	20	4	4	0.5	0.8	12.5	0.5	1	0.1	0.3	—	6.2
	Actual	18.84	4.34	3.65	0.29	0.75	12.93	0.43	1.21	0.09	0.2	0.002	5.3
F	Target	20	3	1	0.3	0.77	13	0.5	1	0.09	0.26	—	4.7
	Actual[b]	18.97	2.88	0.92	0.29	0.74	13.25	0.43	1.17	0.05	0.12	<0.001	2.45
G	Target	20	4.5	4	0.3	0.8	7	0.5	1	0.2	0.5	—	
	Actual[e]	20.08	4.36	4	0.3	0.81	7.01	0.5	1.04	0.24	0.31	0.008	9.6[a]
H	Target	21	3	3	0.3	0.80	7	1	2	0.1	0.4	—	
	Actual[e]	21.1	2.95	3.01	0.31	0.82	6.98	0.51	2.06	0.13	0.32	<0.001	13.46[f]
I	Target	21	3	8	0.3	0.80	7	0.5	1	0.1	0.5	—	7.1
	Actual[e]	21.31	2.94	7.95	0.31	0.83	7.02	0.52	1.05	0.13	0.37	0.003	9.45
J	Target	20	4	2	0.5	1.00	12.5	1	1	0.20	0.50	—	9.8
	Actual[e]	19.93	3.85	2.13	0.5	0.99	12.11	1.08	1.01	0.23	0.29	0.022	8.95
K	Target	20	3	4	0.3	0.77	13	0.5	1	0.09	0.26	—	
	Actual[e]	18.94	2.96	4.01	0.31	0.81	13.05	0.52	1.03	0.12	0.35	0.018	5.62
L	Target	20	3	4	0.3	0.10	13	0.5	1	0.09	0.26	—	
	Actual[b]	20.06	2.96	3.95	0.3	0.12	12.93	0.59	1.03	0.11	0.25	0.005	4.28
M	Target	20	3	4	0.3	0.50	13	0.5	1	0.09	0.26	—	
	Actual[b]	20.11	2.93	3.98	0.3	0.51	12.94	0.5	1.03	0.12	0.13	<0.001	2.76
N	Target	20	3.4	4	1	0.80	12.5	0.5	2	0.1	0.3		8.85[g]

[a]Calculated using actual composition;
[b]Nonconsumable-arc melted;
[c]Remelted by element compensation;
[d]Contains 1.7% sigma phase and 1.55% laves phase;
[e]Induction melted;
[f]Contains 3.9% sigma phase and 1.7% chi phase;
[g]Includes 1.7% sigma and 1.55% laves phases.

Hot Working with Niobium Example

To determine the capability for alloys to be hot worked, samples of alloys C, D, E, F, K, L, and M in TABLE 7 were prepared by arc-melting one pound samples into ingots of 25.4 millimeter×25.4 millimeter×101.6 millimeter (1 inch×1 inch×4 inch). After cutting hot-tops and removing some shrinkage underneath, each sample was homogenized at 1200° C. for one hour, and then hot-rolled to a thickness of 12.7 millimeter (0.5 inch) at 1200° C. with intermediate heat. The samples were then cold rolled to a 6.34 millimeter (0.25 inch) thick plate and vacuum annealed at 1200° C. for one hour.

When alloy D (0% by weight niobium) was hot rolled, it cracked and the rolling to 12.7 millimeter (0.5 inch) thickness could not be accomplished. Alloy L (0.12% by weight niobium) could be hot-rolled, but developed cracks from the edge of the samples progressing toward the center of the sample, and would not be a useful material after such hot rolling. Alloy M (0.51% Nb) could be hot-rolled, without developing cracks or any other problems. The other samples were processed using the above described procedure without any problems, resulting in 6.35 millimeter (0.25 inch) plates that were free of cracks. It has been found that even 0.07% by weight niobium in the alloy composition may significantly reduce the tendency of the alloy to develop cracks during hot working. An alloy having at lest 0.5% by weight niobium can be incorporated in wrought alloys to improve properties such as hot workability. Some alloys may have by weight from 0.5% o 1.2% niobium, from 0.6% to 1.0% niobium, or from 0.7% to 0.9% niobium to improve the alloy properties.

High Temperature Heat Treating Example

Samples of alloys A and B from TABLE 7 were processed by two different methods. Process A included a heat treating and an annealing step at a temperature of 1200° C. Process B included a heat treating and an annealing step at a temperature of 1250° C. With the higher heat treating and annealing temperatures, measurable improvements in yield strength and ultimate tensile strength were observed for the two alloys when processed at the higher temperature.

The process at a temperature of 1200° C. was accomplished as follows: sections of 15.24 cm (six inch) ID by 3.81 cm (1.5 inches) thick centrifugally cast pipe were homogenized at a temperature of 1200° C. for one and a half hours; a section was then hot-rolled at 1200° C. to a 25.4 cm (one inch) thickness for alloy A and a 1.91 cm (three-quarter inch) thickness for alloy B; after cooling to room temperature, the plates were annealed at 1200° C. for fifteen minutes; the plates were then cold-rolled to a thickness of 13.97 millimeter (0.55 inches). The cold-rolled plates were annealed for one hour at 1200° C. in air under an argon blanket. The annealed plates were annealed for a final time at 1250° C. for one hour in air under an argon blanket. This process is referred to herein as process A.

The process with higher heat treating and annealing temperatures varied from the above procedure by homogenization of the cast plates at a temperature of 1250° C. for three hours instead of one and a half hours; hot rolling was carried

out at 1200° C. from a 38.1 millimeter (1.5 inch) thickness to a 19.05 millimeter (0.75 inch) thickness; and the resulting plate was annealed for fifteen minute at 1200° C. followed by cold-rolling to 13.97 millimeter (0.55 inch) thickness. This process is referred to herein as process B.

FIGS. **255**A-**255**E depict yield strengths and ultimate tensile strengths for different metals. In FIG. **255**A, data **1416** shows yield strength and data **1418** shows ultimate tensile strength for alloy A treated by process A. Data **1420** shows yield strength and data **1422** shows ultimate tensile strength for alloy B treated by process B. Data **1424** shows yield strength and data **1426** shows ultimate tensile strength for 347H stainless steel.

In FIG. **255**B, data **2214** show yield strength of alloy G treated by process A. Data **2216** and **2218** show yield strength for alloys H and I. Data **2220** shows yield strength of alloy B treated by process A. Data **2222** shows yield strength of alloy B treated by process B. Data **1424** shows yield strength for 347H stainless steel.

In FIG. **255**C, data **2224** show ultimate tensile strength of alloy G treated by process A. Data **2226** and **2228** show ultimate tensile strength for alloys H and I. **2230** shows ultimate tensile strength of alloy B treated by process A. Data **2232** shows ultimate tensile strength of alloy B treated by process B. Data **1426** shows ultimate tensile strength for 347H stainless steel.

In FIG. **255**D, data **2234** and **2236** show yield strength for alloys J and K. Data **2220** shows yield strength of alloy B treated by process A. Data **2222** shows yield strength of alloy B treated by process B. Data **1424** shows yield strength for 347H stainless steel.

In FIG. **255**E data **2238** and **2240** show ultimate tensile strength for alloys J and K. Data **2230** shows ultimate tensile strength of alloy B treated by process A. Data **2232** shows ultimate tensile strength of alloy B treated by process B. Data **1426** shows ultimate tensile strength for 347H stainless steel.

Both ultimate tensile strength and yield strength were greater for the alloys treated at higher temperatures as compared to 347H stainless steel. A considerable improvement over 347H can be seen for alloys A, B, G, H, I, J, and K. For example, alloys A, B, G, H, I, J, and K retained tensile properties to test temperatures of 1000° C. For an application where yield strength of 20 ksi was needed, alloys A, B, G, H, I, J, and K provide the needed yield strength for at least an additional 250° C. For a 5 ksi difference between yield and ultimate tensile strength at test temperatures, alloys A, B, G, H, I, J, and K may be used at temperatures of 950° C. and 1000° C. as opposed to only 870° C. for 347H.

Samples of Alloy B, treated by process A and by process B were subjected to stress-rupture tests and the results are tabulated in TABLE 8. It can be seen from Table 8 that process B, with a higher annealing temperature, resulted in 47% to 474% improvement in time to rupture.

TABLE 8

Temperature (° C.)	Stress (MPa)	Process A life (hours)	Process B life (hours)	Improvement by Process B
800	100	164.2	241.6	47%
850	70	32	151.7	474%
850	55	264.1	500.7	90%
900	42	90.1	140.1	55%

High Temperature Yield After Cold Work and Aging Example

A sample of alloy B, processed by process B, was aged at 750° C. for 1000 hours after being cold worked by 2.5%, 5%, and 10%, and without cold working. After aging, each was tested for tensile strength and yield strength at 750° C. Results are tabulated in TABLE 9. It can be seen from TABLE 9 that the yield strength increased significantly as a result of cold work and high temperature aging. The ultimate tensile strength at 750° C. decreased only slightly as a result of the high temperature aging and cold working. The annealed only sample and the aged only sample were also tested at room temperature for yield strength and ultimate tensile strength. The yield strength at room temperature increased from 307 MPa to 318 MPa as a result of the aging. The ultimate tensile strength decreased from 720 MPa to 710 MPa as a result of the high temperature aging.

TABLE 9

	Annealed	Aged	2.5% Cold Worked and aged	5% Cold Worked and aged	10% Cold Worked and aged
Yield Strength, MPa	170	212	235	290	325
Ultimate Tensile Strength, MPa	372	358	350	360	358

These characteristics may be compared to competing alloys, such as 347H, which significantly lose high temperature properties as a result of only, for example, 10% cold work. Because fabrication of tubulars and heaters useful in an in situ heat treatment process often require cold work for their fabrication, improvement of some high temperature properties, or at least lack of significant loss of high temperature properties may be a significant advantage for alloys having these characteristics. It may be particularly advantageous when these properties are improved, or at least not significantly decreased, by high temperature aging.

Creep Example

Samples of alloys were subjected to 100 MPa stress at 800° C. in a nitrogen with 0.1% oxygen test environment. Each of the samples was first annealed for one hour at 1200° C. TABLE 10 shows the time to rupture, elongation at rupture, and total phase content, where the total phase content is known.

TABLE 10

Alloy	Rupture time (hr)	Elongation (%)	Total Phase Content % at 800° C.	Comments
B	283	7.6	4.4	
B	116	5.6	4.4	
B	127	3.9	4.4	10% cold work
B	228	3.1	4.4	10% cold work
B	185	2.3	4.4	Laser weld
C	60	5.3	5.45	
C	137	3.6	5.45	Repeated test
E	165	5.1	5.3	
F	24	6.6	2.45	
G	178	11.3	9.6	
H	183	9.8	13.46 total 7.86 good phases	

TABLE 10-continued

Alloy	Rupture time (hr)	Elongation (%)	Total Phase Content % at 800° C.	Comments
I	228	12.6	9.45	
J	240	19.7	8.95	
K	123	14.2	5.62	
N	147	7.4	8.85	
347H	1.87	92	0.75	As received
347H	2.1	61	0.75	As received
NF709	56	32		Annealed
NF709	30	29.4		
NF709	36	26		Cold Strain 10%
NF709	82	30.6		Cold Strain 10%
NF709	700	16.2		Cold Strain 15%
NF709	643	11.4		Cold Strain 20%
NF709	1084	6		Cold Strain 20%
NF709	754	37.6		As received

A sample of the improved alloy B was rolled processed and rolled into a tube, and the seam welded, to form a 31.75 millimeter (1.25 inch) OD pipe. The pipe was then cut and welded back together in order to test the strength of the weld. The filler metal was ERNiCrMo-3, and the weld was completed with argon shielding gas and three passes with a preheat minimum temperature of 50° C. and an interpass maximum temperature of 350° C. Creep failure was tested for the segment of welded pipe at 44.8 MPa and 900° C. A rupture time of 41 hours was measured with failure at a strain of 5.5%. This demonstrated that the weld, including the heat affected zone around the weld, was not significantly weaker than the base alloy.

Metal Sulfidation Example

FIG. **256** depicts projected corrosion rates (metal loss per year) over a one-year period for several metals in a sulfidation atmosphere. The metals were exposed to a gaseous mixture containing about 1% by volume carbon monoxide sulfide (COS), about 32% by volume carbon monoxide (CO) and about 67% volume CO_2 at 538° C. (1000° F.), at 649° C. (1200° C.), at 760° C. (1400° F.), and at 871° C. (about 1600° F.) for 384 hours. The resulting data was extrapolated to a one-year time period. The experimental conditions simulates in-situ sub-surface formation sulfidation conditions of 10% H_2 by volume, 10% H_2S by volume and 25% H_2O by volume at 870° C. Curve **1428** depicts 625 stainless steel. Curve **1430** depicts CF8C+ stainless steel. Curve **1432** depicts data for 410 stainless steel. Curve **1434** depicts 20 25 Nb stainless steel. Curve **1436** depicts 253 MA stainless steel. Curve **1438** depicts 347H stainless steel. Curve **1440** depicts 446 stainless steel. 410 stainless steel exhibits a decrease in corrosion at temperatures between about 500° C. and about 650° C.

In some embodiments, cobalt is added to 410 stainless steel to decrease the rate of corrosion at elevated temperatures (for example, temperatures greater than 1200° F.) relative to untreated 410 stainless steel. Addition of cobalt to 410 stainless steel may enhance the strength of the stainless steel at high temperatures (for example, temperatures greater than 1200° F., greater than 1400° F., greater than 1500° F., or greater than 1600° F.) and/or change the magnetic characteristics of the metal. FIG. **257** depicts projected corrosion rates (metal loss per year) for 410 stainless steel and 410 stainless steel containing various amounts of cobalt in a sulfidation atmosphere. The metals were exposed to the same conditions as the metals in FIG. **257**. Bars **1442** depicts data for 410 stainless steel. Bar **1444** depicts data for 410 stainless steel with 2.5% cobalt by weight. Bar **1446** depicts data for 410 stainless steel with 5% cobalt by weight. Bar **1448** depicts data for 410 stainless steel with 10% cobalt by weight. As shown in FIG. **257**, as the amount of cobalt in the 410 stainless steel increases, the corrosion rate in a sulfidation atmosphere decreases relative to non-cobalt containing 410 stainless steel in a temperature range of about 800° C. to about 880° C.

Varying Heater Output Simulation

A STARS simulation determined heating properties using temperature limited heaters with varying power outputs. FIG. **258** depicts an example of richness of an oil shale formation (gal/ton) versus depth (ft). Upper portions of the formation (above about 1210 feet) tend to have a leaner richness, lower water-filled porosity, and/or less dawsonite than deeper portions of the formation. For the simulation, a heater similar to the heater depicted in FIG. **43** was used. Portion **550** had a length of 368 feet above the dashed line shown in FIG. **258** and portion **548** had a length of 587 feet below the dashed line.

In the first example, the temperature limited heater had constant thermal properties along the entire length of the heater. The heater included a 14.34 millimeter (0.565 inch) diameter copper core with a carbon steel conductor (Curie temperature of 1418° F., pure iron with outside diameter of 20.955 millimeter (0.825 inch)) surrounding the copper core. The outer conductor was 347H stainless steel surrounding the carbon steel conductor with an outside diameter of 31.75 millimeter (1.2 inch). The resistance per foot (mΩ/ft) versus temperature (° F.) profile of the heater is shown in FIG. **259**. FIG. **260** depicts average temperature in the formation (° F.) versus time (days) as determined by the simulation for the first example. Curve **1450** depicts average temperature versus time for the top portion of the formation. Curve **1452** depicts average temperature versus time for the entire formation. Curve **1454** depicts average temperature versus time for the bottom portion of the formation. As shown, the average temperature in the bottom portion of the formation lagged behind the average temperature in the top portion of the formation and the entire formation. The top portion of the formation reached an average temperature of 340° C. (644° F.) in 1584 days. The bottom portion of the formation reached an average temperature of 340° C. (644° F.) in 1922 days. Thus, the bottom portion lagged behind the top portion by almost a year to reach an average temperature near a pyrolysis temperature.

In the second example, portion **550** of the temperature limited heater had the same properties used in the first example. Portion **548** of the heater was altered to have a Curie temperature of 843° C. (1550° F.) by the addition of cobalt to the iron conductor. FIG. **261** depicts resistance per foot (mΩ/ft) versus temperature (° F.) for the second heater example. Curve **1456** depicts the resistance profile for the top portion (portion **550**). Curve **1458** depicts the resistance profile for the bottom portion (portion **548**). FIG. **262** depicts average temperature in the formation (° F.) versus time (days) as determined by the simulation for the second example. Curve **1460** depicts average temperature versus time for the top portion of the formation. Curve **1462** depicts average temperature versus time for the entire formation. Curve **1464** depicts average temperature versus time for the bottom portion of the formation. As shown, the average temperature in the bottom portion of the formation lagged behind the average temperature in the top portion of the formation and the entire

formation. The top portion of the formation reached an average temperature of 340° C. (644° F.) in 1574 days. The bottom portion of the formation reached an average temperature of 340° C. (644° F.) in 1701 days. Thus, the bottom portion still lagged behind the top portion to reach an average temperature near a pyrolysis temperature but the time lag was less than the time lag in the first example.

FIG. **263** depicts net heater energy input (Btu) versus time (days) for the second example. Curve **1466** depicts net heater energy input for the bottom portion. Curve **1468** depicts net heater input for the top portion. The net heater energy input to reach a temperature of 340° C. (644° F.) for the bottom portion was 2.35×10^{10} Btu. The net heater energy input to reach a temperature of 340° C. (644° F.) for the top portion was 1.32×10^{10} Btu. Thus, it took 12% more power to reach the desired temperature in the bottom portion.

FIG. **264** depicts power injection per foot (W/ft) versus time (days) for the second example. Curve **1470** depicts power injection rate for the bottom portion. Curve **1472** depicts power injection rate for the top portion. The power injection rate for the bottom portion was about 6% more than the power injection rate for the top portion. Thus, either reducing the power output of the top portion and/or increasing the power output of the bottom portion to a total of about 6% should provide approximately similar heating rates in the top and bottom portions.

In the third example, dimensions of the top portion (portion **550**) were altered to provide less power output. Portion **550** was adjusted to have a copper core with an outside diameter of 13.84 millimeter (0.545 inch), a carbon steel conductor with an outside diameter of 17.78 millimeter (0.700 inch) surrounding the copper core, and an outer conductor of 347H stainless steel with an outside diameter of 30.48 millimeter (1.2 inch) surrounding the carbon steel conductor. The bottom portion (portion **548**) had the same properties as the heater in the second example. FIG. **265** depicts resistance per foot (mΩ/ft) versus temperature (° F.) for the third heater example. Curve **1474** depicts the resistance profile for the top portion (portion **550**). Curve **1476** depicts the resistance profile of the top portion in the second example. Curve **1478** depicts the resistance profile for the bottom portion (portion **548**). FIG. **266** depicts average temperature in the formation (° F.) versus time (days) as determined by the simulation for the third example. Curve **1480** depicts average temperature versus time for the top portion of the formation. Curve **1482** depicts average temperature versus time for the bottom portion of the formation. As shown, the average temperature in the bottom portion of the formation was approximately the same as the average temperature in the top portion of the formation, especially after a time of about 1000 days. The top portion of the formation reached an average temperature of 340° C. (644° F.) in 1642 days. The bottom portion of the formation reached an average temperature of 340° C. (644° F.) in 1649 days. Thus, the bottom portion reached an average temperature near a pyrolysis temperature only 5 days later than the top portion.

FIG. **267** depicts cumulative energy injection (Btu) versus time (days) for each of the three heater examples. Curve **1484** depicts cumulative energy injection for the first heater example. Curve **1486** depicts cumulative energy injection for the second heater example. Curve **1488** depicts cumulative energy injection for the third heater example. The second and third heater examples have nearly identical cumulative energy injections. The first heater example had a cumulative energy injection about 7% higher to reach an average temperature of 340° C. (644° F.) in the bottom portion.

FIGS. **258-267** depict results for heaters with a 40 foot spacing between heaters in a triangular heating pattern. FIG. **268** depicts average temperature (° F.) versus time (days) for the third heater example with a 30 foot spacing between heaters in the formation as determined by the simulation. Curve **1490** depicts average temperature versus time for the top portion of the formation. Curve **1492** depicts average temperature versus time for the bottom portion of the formation. The curves in FIG. **268** still tracked with approximately equal heating rates in the top and bottom portions. The time to reach an average temperature in the portions was reduced. The top portion of the formation reached an average temperature of 340° C. (644° F.) in 903 days. The bottom portion of the formation reached an average temperature of 340° C. (644° F.) in 884 days. Thus, the reduced heater spacing decreases the time needed to reach an average selected temperature in the formation.

As a fourth example, the STARS simulation was used to determine heating properties of temperature limited heaters with varying power outputs when using the temperature limited heaters in the heater configuration and pattern depicted in FIGS. **70** and **72**. The heater pattern had a 30 foot heater spacing. Portion **550** had a length of 368 feet and portion **548** had a length of 587 feet as in the previous examples. Portion **550** included a solid 410 stainless steel conductor with an outside diameter of 31.75 millimeter (1.25 inch). Portion **548** included a solid 410 stainless steel conductor with 9% by weight cobalt added. The Curie temperature of portion **548** is 110° C. (230° F.) higher than the Curie temperature of portion **550**.

FIG. **269** depicts average temperature (° F.) versus time (days) for the fourth heater example using the heater configuration and pattern depicted in FIGS. **70** and **72** as determined by the simulation. Curve **1494** depicts average temperature versus time for the top portion of the formation. Curve **1496** depicts average temperature versus time for the bottom portion of the formation. The curves in FIG. **269** show approximately equal heating rates in the top and bottom portions. The top portion of the formation reached a temperature of 340° C. (644° F.) in 859 days. The bottom portion of the formation reached a temperature of 340° C. (644° F.) in 880 days. In this heater configuration and heater pattern, the top portion of the formation reached a selected temperature at about the same time as a bottom portion of the formation.

Tar Sands Simulation

A STARS simulation was used to simulate heating of a tar sands formation using the heater well pattern depicted in FIG. **130**. The heaters had a horizontal length in the tar sands formation of 600 m. The heating rate of the heaters was about 750 W/m. Production well **206**B, depicted in FIG. **130**, was used at the production well in the simulation. The bottom hole pressure in the horizontal production well was maintained at about 690 kPa. The tar sands formation properties were based on Athabasca tar sands. Input properties for the tar sands formation simulation included: initial porosity equals 0.28; initial oil saturation equals 0.8; initial water saturation equals 0.2; initial fee gas saturation equals 0.0; initial vertical permeability equals 250 millidarcy; initial horizontal permeability equals 500 millidarcy; initial Kv/Kh equals 0.5; hydrocarbon layer thickness equals 28 m; depth of hydrocarbon layer equals 587 m; initial reservoir pressure equals 3771 kPa; distance between production well and lower boundary of hydrocarbon layer equals 2.5 meter; distance of topmost heaters and overburden equals 9 meter; spacing between heaters equals 9.5 meter; initial hydrocarbon layer temperature equals 18.6° C.; viscosity at initial temperature equals 53 Pa·s

(53000 cp); and gas to oil ratio (GOR) in the tar equals 50 standard cubic feet/standard barrel. The heaters were constant wattage heaters with a highest temperature of 538° C. at the sand face and a heater power of 755 W/m. The heater wells had a diameter of 15.2 cm.

FIG. **270** depicts a temperature profile in the formation after 360 days using the STARS simulation. The hottest spots are at or near heaters **716**. The temperature profile shows that portions of the formation between the heaters are warmer than other portions of the formation. These warmer portions create more mobility between the heaters and create a flow path for fluids in the formation to drain downwards towards the production wells.

FIG. **271** depicts an oil saturation profile in the formation after 360 days using the STARS simulation. Oil saturation is shown on a scale of 0.00 to 1.00 with 1.00 being 100% oil saturation. The oil saturation scale is shown in the sidebar. Oil saturation, at 360 days, is somewhat lower at heaters **716** and production well **206**B. FIG. **272** depicts the oil saturation profile in the formation after 1095 days using the STARS simulation. Oil saturation decreased overall in the formation with a greater decrease in oil saturation near the heaters and in between the heaters after 1095 days. FIG. **273** depicts the oil saturation profile in the formation after 1470 days using the STARS simulation. The oil saturation profile in FIG. **273** shows that the oil is mobilized and flowing towards the lower portions of the formation. FIG. **274** depicts the oil saturation profile in the formation after 1826 days using the STARS simulation. The oil saturation is low in a majority of the formation with some higher oil saturation remaining at or near the bottom of the formation in portions below production well **206**B. This oil saturation profile shows that a majority of oil in the formation has been produced from the formation after 1826 days.

FIG. **275** depicts the temperature profile in the formation after 1826 days using the STARS simulation. The temperature profile shows a relatively uniform temperature profile in the formation except at heaters **716** and in the extreme (corner) portions of the formation. The temperature profile shows that a flow path has been created between the heaters and to production well **206**B.

FIG. **276** depicts oil production rate **1498** (bbl/day) (left axis) and gas production rate **1500** (ft^3/day) (right axis) versus time (years). The oil production and gas production plots show that oil is produced at early stages (0-1.5 years) of production with little gas production. The oil produced during this time was most likely heavier mobilized oil that is unpyrolyzed. After about 1.5 years, gas production increased sharply as oil production decreased sharply. The gas production rate quickly decreased at about 2 years. Oil production then slowly increased up to a maximum production around about 3.75 years. Oil production then slowly decreased as oil in the formation was depleted.

From the STARS simulation, the ratio of energy out (produced oil and gas energy content) versus energy in (heater input into the formation) was calculated to be about 12 to 1 after about 5 years. The total recovery percentage of oil in place was calculated to be about 60% after about 5 years. Thus, producing oil from a tar sands formation using an embodiment of the heater and production well pattern depicted in FIG. **130** may produce high oil recoveries and high energy out to energy in ratios.

Tar Sands Example

A STARS simulation was used in combination with experimental analysis to simulate an in situ heat treatment process of a tar sands formation. Heating conditions for the experimental analysis were determined from reservoir simulations. The experimental analysis included heating a cell of tar sands from the formation to a selected temperature and then reducing the pressure of the cell (blow down) to 100 psig. The process was repeated for several different selected temperatures. While heating the cells, formation and fluid properties of the cells were monitored while producing fluids to maintain the pressure below an optimum pressure of 12 MPa before blow down and while producing fluids after blow down (although the pressure may have reached higher pressures in some cases, the pressure was quickly adjusted and does not affect the results of the experiments). FIGS. **277-284** depict results from the simulation and experiments.

FIG. **277** depicts weight percentage of original bitumen in place (OBIP) (left axis) and volume percentage of OBIP (right axis) versus temperature (° C.). The term "OBIP" refers, in these experiments, to the amount of bitumen that was in the laboratory vessel with 100% being the original amount of bitumen in the laboratory vessel. Plot **2152** depicts bitumen conversion (correlated to weight percentage of OBIP). Plot **2152** shows that bitumen conversion began to be significant about 270° C. and ended at about 340° C. and is relatively linear over the temperature range.

Plot **2154** depicts barrels of oil equivalent from producing fluids and production at blow down (correlated to volume percentage of OBIP). Plot **2156** depicts barrels of oil equivalent from producing fluids (correlated to volume percentage of OBIP). Plot **2158** depicts oil production from producing fluids (correlated to volume percentage of OBIP). Plot **2160** depicts barrels of oil equivalent from production at blow down (correlated to volume percentage of OBIP). Plot **2162** depicts oil production at blow down (correlated to volume percentage of OBIP). As shown in FIG. **277**, the production volume began to significantly increase as bitumen conversion began at about 270° C. with a significant portion of the oil and barrels of oil equivalent (the production volume) coming from producing fluids and only some volume coming from the blow down.

FIG. **278** depicts bitumen conversion percentage (weight percentage of (OBIP)) (left axis) and oil, gas, and coke weight percentage (as a weight percentage of OBIP) (right axis) versus temperature (0° C.). Plot **2164** depicts bitumen conversion (correlated to weight percentage of OBIP). Plot **2166** depicts oil production from producing fluids correlated to weight percentage of OBIP (right axis). Plot **2168** depicts coke production correlated to weight percentage of OBIP (right axis). Plot **2170** depicts gas production from producing fluids correlated to weight percentage of OBIP (right axis). Plot **2172** depicts oil production from blow down production correlated to weight percentage of OBIP (right axis). Plot **2174** depicts gas production from blow down production correlated to weight percentage of OBIP (right axis). FIG. **278** shows that coke production begins to increase at about 280° C. and maximizes around 340° C. FIG. **278** also shows that the majority of oil and gas production is from produced fluids with only a small fraction from blow down production.

FIG. **279** depicts API gravity (°) (left axis) of produced fluids, blow down production, and oil left in place along with pressure (psig) (right axis) versus temperature (0° C.). Plot **2176** depicts API gravity of produced fluids versus temperature. Plot **2178** depicts API gravity of fluids produced at blow down versus temperature. Plot **2180** depicts pressure versus temperature. Plot **2182** depicts API gravity of oil (bitumen) in the formation versus temperature. FIG. **279** shows that the API gravity of the oil in the formation remains relatively

constant at about 100 API and that the API gravity of produced fluids and fluids produced at blow down increases slightly at blow down.

FIGS. **280**A-D depict gas-to-oil ratios (GOR) in thousand cubic feet per barrel ((Mcf/bbl) (y-axis) versus temperature (° C.) (x-axis) for different types of gas at a low temperature blow down (about 277° C.) and a high temperature blow down (at about 290° C.). FIG. **280**A depicts the GOR versus temperature for carbon dioxide (CO_2). Plot **2184** depicts the GOR for the low temperature blow down. Plot **2186** depicts the GOR for the high temperature blow down. FIG. **280**B depicts the GOR versus temperature for hydrocarbons. FIG. **280**C depicts the GOR for hydrogen sulfide (H_2S). FIG. **280**D depicts the GOR for hydrogen (H_2). In FIGS. **280**B-D, the GORs were approximately the same for both the low temperature and high temperature blow downs. The GORs for CO_2 (shown in FIG. **280**) was different for the high temperature blow down and the low temperature blow down. The reason for the difference in the GORs for CO_2 may be that CO_2 was produced early (at low temperatures) by the hydrous decomposition of dolomite and other carbonate minerals and clays. At these low temperatures, there was hardly any produced oil so the GOR is very high because the denominator in the ratio is practically zero. The other gases (hydrocarbons, H_2S, and H_2) were produced concurrently with the oil either because they were all generated by the upgrading of bitumen (for example, (hydrocarbons, H_2, and oil) or because they were generated by the decomposition of minerals (such as pyrite) in the same temperature range as that of bitumen upgrading (for example, H_2S). Thus, when the GOR was calculated, the denominator (oil) was non zero for hydrocarbons, H_2S, and H_2.

FIG. **281** depicts coke yield (weight percentage) (y-axis) versus temperature (° C.) (x-axis). Plot **2188** depicts bitumen and kerogen coke as a weight percent of original mass in the formation. Plot **2190** depicts bitumen coke as a weight percent of original bitumen in place (OBIP) in the formation. FIG. **281** shows that kerogen coke is already present at a temperature of about 260° C. (the lowest temperature cell experiment) while bitumen coke begins to form at about 280° C. and maximizes at about 340° C.

FIGS. **282**A-D depict assessed hydrocarbon isomer shifts in fluids produced from the experimental cells as a function of temperature and bitumen conversion. Bitumen conversion and temperature increase from left to right in the plots in FIGS. **282**A-D with the minimum bitumen conversion being 10%, the maximum bitumen conversion being 100%, the minimum temperature being 277° C., and the maximum temperature being 350° C. The arrows in FIGS. **282**A-D show the direction of increasing bitumen conversion and temperature.

FIG. **282**A depicts the hydrocarbon isomer shift of n-butane-$\delta^{13}C_4$ percentage (y-axis) versus propane-$\delta^{13}C_3$ percentage α-axis). FIG. **282**B depicts the hydrocarbon isomer shift of n-pentane-$\delta^{13}C_5$ percentage (y-axis) versus propane-$\delta^{13}C_3$ percentage (x-axis). FIG. **282**C depicts the hydrocarbon isomer shift of n-pentane-$\delta^{13}C_5$ percentage (y-axis) versus n-butane-$\delta^{13}C_4$ percentage (x-axis). FIG. **282**D depicts the hydrocarbon isomer shift of i-pentane-$\delta^{13}C_5$ percentage (y-axis) versus i-butane-$\delta^{13}C_4$ percentage (x-axis). FIGS. **282**A-D show that there is a relatively linear relationship between the hydrocarbon isomer shifts and both temperature and bitumen conversion. The relatively linear relationship may be used to assess formation temperature and/or bitumen conversion by monitoring the hydrocarbon isomer shifts in fluids produced from the formation.

FIG. **283** depicts weight percentage (Wt %) (y-axis) of saturates from SARA analysis of the produced fluids versus temperature (° C.) (x-axis). The logarithmic relationship between the weight percentage of saturates and temperature may be used to assess formation temperature by monitoring the weight percentage of saturates in fluids produced from the formation.

FIG. **284** depicts weight percentage (Wt %) (y-axis) of n-C_7 of the produced fluids versus temperature (° C.) (x-axis). The linear relationship between the weight percentage of n-C_7 and temperature may be used to assess formation temperature by monitoring the weight percentage of n-C_7 in fluids produced from the formation.

Pre-Heating Using Heaters For Injectivity Before Steam Drive Example

An example uses the embodiment depicted in FIGS. **134** and **135** to preheat using heaters for the drive process is described. Injection wells **748** and production wells **206** are substantially vertical wells. Heaters **716** are long substantially horizontal heaters positioned so that the heaters pass in the vicinity of injection wells **748**. Heaters **716** intersect the vertical well patterns slightly displaced from the vertical wells.

The following conditions were assumed for purposes of this example:

(a) heater well spacing; s=330 ft;
(b) formation thickness; h=100 ft;
(c) formation heat capacity; ρc=35 BTU/cu. ft.-° F.
(d) formation thermal conductivity; k=1.2 BTU/ft-hr-° F.;
(e) electric heating rate; q_h=200 watts/ft;
(f) steam injection rate; q_s=500 bbls/day;
(g) enthalpy of steam; h_s=1000 BTU/lb;
(h) time of heating; t=1 year;
(i) total electric heat injection; Q_E=BTU/pattern/year;
(j) radius of electric heat; r=ft; and
(k) total steam heat injected; Q_s=BTU/pattern/year.

Electric heating for one well pattern for one year is given by:

$$Q_E=q_h \cdot t \cdot s \text{ (BTU/pattern/year);} \quad \text{(EQN. 12)}$$

with Q_E=(200 watts/ft)[0.001 kw/watt](1 yr)[365 day/yr][24 hr/day][3413 BTU/kw·hr](330 ft)=1.9733×10^9 BTU/pattern/year.

Steam heating for one well pattern for one year is given by:

$$Q_s=q_s \cdot t \cdot h_s \text{ (BTU/pattern/year);} \quad \text{(EQN. 13)}$$

with Q_s=(500 bbls/day)(1 yr)[365 day/yr][1000 BTU/lb][350 lbs/bbl]=63.875×10^9 BTU/pattern/year.

Thus, electric heat divided by total heat is given by:

$$Q_E/(Q_E+Q_s)\times100=3\% \text{ of the total heat.} \quad \text{(EQN. 14)}$$

Thus, the electrical energy is only a small fraction of the total heat injected into the formation.

The actual temperature of the region around a heater is described by an exponential integral function. The integrated form of the exponential integral function shows that about half the energy injected is nearly equal to about half of the injection well temperature. The temperature required to reduce viscosity of the heavy oil is assumed to be 500° F. The volume heated to 500° F. by an electric heater in one year is give by:

$$V_E=\pi r^2. \quad \text{(EQN. 15)}$$

The heat balance is given by:

$$Q_E=(\pi r_E^2)(s)(\rho c)(\Delta T). \quad \text{(EQN. 16)}$$

Thus, r_E can be solved for and is found to be 10.4 ft. For an electric heater operated at 1000° F., the diameter of a cylinder

heated to half that temperature for one year would be about 23 ft. Depending on the permeability profile in the injection wells, additional horizontal wells may be stacked above the one at the bottom of the formation and/or periods of electric heating may be extended. For a ten year heating period, the diameter of the region heated above 500° F. would be about 60 ft.

If all the steam were injected uniformly into the steam injectors over the 100 ft. interval for a period of one year, the equivalent volume of formation that could be heated to 500° F. would be give by:

$$Q_s=(\pi r_s^2)(s)(\rho c)(\Delta T). \quad \text{(EQN. 17)}$$

Solve for r_s give an r_s of 107 ft. This amount of heat would be sufficient to heat about ¾ of the pattern to 500° F.

Nanofiltration Example

A liquid sample (500 mL, 398.68 grams) was obtained from an in situ heat treatment process. The liquid sample contained 0.0069 grams of sulfur and 0.0118 grams of nitrogen per gram of liquid sample. The final boiling point of the liquid sample was 481° C. and the liquid sample had a density of 0.8474. The membrane separation unit used to filter the sample was a laboratory flat sheet membrane installation type P28 as obtained from CM Celfa Membrantechnik A. G. (Switzerland). A single 2-micron thick poly di-methyl siloxane membrane (GKSS Forschungszentrum GmbH, Geesthact, Germany) was used as the filtration medium. The filtration system was operated at 50° C. and a pressure difference over the membrane was 10 bar. The pressure at the permeate side was nearly atmospheric. The permeate was collected and recycled through the filtration system to simulate a continuous process. The permeate was blanketed with nitrogen to prevent contact with ambient air. The retentate was also collected for analysis. During filtration the average flux of 2 kg/m2/bar/hr did not measurably decline from an initial flux during the filtration. The filtered liquid (298.15 grams, 74.7% recovery) contained 0.007 grams of sulfur and 0.0124 grams of nitrogen per gram of filtered liquid; and the filtered liquid had a density of 0.8459 and a final boiling point of 486° C. The retentate (56.46 grams, 14.16% recovery) contained 0.0076 grams of sulfur and 0.0158 grams of nitrogen per gram of retentate; and the retentate had a density of 0.8714 and a final boiling point of 543° C.

Fouling Testing Example

The unfiltered and filtered liquid samples from previous Example were tested for fouling behavior. Fouling behavior was determined using an Alcor thermal fouling tester. The Alcor thermal fouling tester is a miniature shell and tube heat exchanger made of 1018 steel which was grated with Norton R222 sandpaper before use. During the test the sample outlet temperature, (Tout) was monitored while the heat-exchanger temperature (Tc) was kept at a constant value. If fouling occurs and material is deposited on the tube surface, the heat resistance of the sample increases and consequently the outlet temperature decreases. Hence the decrease in outlet temperature after a given period of time is a measure of fouling severity. The temperature decrease after two hours of operation is used as fouling severity indicator. ΔT=Tout(o)−Tout (2h). Tout(o) is defined as the maximum (stable) outlet temperature obtained at the start of the test, Tout(2h) is recorded 2 hours after the first noted decrease of the outlet temperature or when the outlet temperature has been stable for at least 2 hours.

During each test, the liquid sample was continuously circulated through the heat exchanger at approximately 3 mL/min. The residence time in the heat exchanger was about 10 seconds. The operating conditions were as follows: 40 bar of pressure, T_{sample} was about 50° C., Tc was 350° C., test time was 4.41 hours. The ΔT for the unfiltered liquid stream sample was 15° C. The ΔT for the filtered sample was zero.

This example demonstrates that nanofiltration of a liquid stream produced from an in situ heat treatment process removes at least a portion of clogging compositions.

Olefin Production Example

An experimental pilot system was used to conduct the experiments. The pilot system included a feed supply system, a catalyst loading and transfer system, a fast fluidized riser reactor, a stripper, a product separation and collecting system, and a regenerator. The riser reactor was an adiabatic riser having an inner diameter of from 11 mm to 19 mm and a length of about 3.2 m. The riser reactor outlet was in fluid communication with the stripper that was operated at the same temperature as the riser reactor outlet flow and in a manner to provide essentially 100 percent stripping efficiency. The regenerator was a multi-stage continuous regenerator used for regenerating the spent catalyst. The spent catalyst was fed to the regenerator at a controlled rate and the regenerated catalyst was collected in a vessel. Material balances were obtained during each of the experimental runs at 30-minute intervals. Composite gas samples were analyzed by use of an on-line gas chromatograph and the liquid product samples were collected and analyzed overnight. The coke yield was measured by measuring the catalyst flow and by measuring the delta coke on the catalyst as determined by measuring the coke on the spent and regenerated catalyst samples taken for each run when the unit was operating at steady state.

A liquid stream produced from an in situ heat treatment process was fractioned to obtain a vacuum gas oil (VGO) stream having a boiling range distribution from 310° C. to 640° C. The VGO stream was contacted with a fluidized catalytic cracker E-Cat containing 10% ZSM-5 additive in the catalytic system described above. The riser reactor temperature was maintained at 593° C. (1100° F.). The product produced contained, per gram of product, 0.1402 grams of C3 olefins, 0.137 grams of C4 olefins, 0.0897 grams of C5 olefins, 0.0152 grams of iso-C5 olefins, 0.0505 grams isobutylene, 0.0159 grams of ethane, 0.0249 grams of isobutane, 0.0089 grams of n-butane, 0.0043 grams pentane, 0.0209 grams iso-pentane, 0.2728 grams of a mixture of C6 hydrocarbons and hydrocarbons having a boiling point of at most 232° C. (450° F.), 0.0881 grams of hydrocarbons having a boiling range distribution between 232° C. and 343° C. (between 450° F. and 650° F.), 0.0769 grams of hydrocarbons having a boiling range distribution between 343° C. and 399° C. (650° F. and 750° F.) and 0.0386 grams of hydrocarbons having a boiling range distribution of at least 399° C. (750° F.) and 0.0323 grams of coke.

This example demonstrates a method of producing crude product by fractionating liquid stream produced from separation of the liquid stream from the formation fluid to produce a crude product having a boiling point above 343° C.; and catalytically cracking the crude product having the boiling

point above 343° C. to produce one or more additional crude products, wherein least one of the additional crude products is a second gas stream.

Production of Olefins from a Liquid Stream Example

A thermally cracked naphtha was used to simulate a liquid stream produced from an in situ heat treatment process having a boiling range distribution from 30° C. to 182° C. The naphtha contained, per gram of naphtha, 0.186 grams of naphthenes, 0.238 grams of isoparaffins, 0.328 grams of n-paraffins, 0.029 grams cyclo-olefins, 0.046 grams of iso-olefins, 0.064 grams of n-olefins and 0.109 grams of aromatics. The naphtha stream was contacted with a FCC E-Cat with 10% ZSM-5 additive in the catalytically cracking system described above to produce a crude product. The riser reactor temperature was maintained at 593° C. (1100° F.). The crude product included, per gram of crude product, 0.1308 grams ethylene, 0.0139 grams of ethane, 0.0966 grams C4-olefins, 0.0343 grams C4 iso-olefins, 0.0175 grams butane, 0.0299 grams isobutane, 0.0525 grams C5 olefins, 0.0309 grams C5 iso-olefins, 0.0442 grams pentane, 0.0384 grams iso-pentane, 0.4943 grams of a mixture of C6 hydrocarbons and hydrocarbons having a boiling point of at most 232° C. (450° F.), 0.0201 grams of hydrocarbons having a boiling range distribution between 232° C. and 343° C. (between 450° F. and 650° F.), 0.0029 grams of hydrocarbons having a boiling range distribution between 343° C. and 399° C. (650° F. and 750° F.) and 0.00128 grams of hydrocarbons having a boiling range distribution of at least 399° C. (750° F.) and 0.00128 grams of coke. The total amount of C3-C5 olefins was 0.2799 grams per gram of naphtha.

This example demonstrates a method of producing crude product by fractionating liquid stream produced from separation of the liquid stream from the formation fluid to produce a crude product having a boiling point above 343° C.; and catalytically cracking the crude product having the boiling point above 343° C. to produce one or more additional crude products, wherein least one of the additional crude products is a second gas stream.

In this patent, certain U.S. patents, U.S. patent applications, and other materials (for example, articles) have been incorporated by reference. The text of such U.S. patents, U.S. patent applications, and other materials is, however, only incorporated by reference to the extent that no conflict exists between such text and the other statements and drawings set forth herein. In the event of such conflict, then any such conflicting text in such incorporated by reference U.S. patents, U.S. patent applications, and other materials is specifically not incorporated by reference in this patent.

Further modifications and alternative embodiments of various aspects of the invention may be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the invention. It is to be understood that the forms of the invention shown and described herein are to be taken as the presently preferred embodiments. Elements and materials may be substituted for those illustrated and described herein, parts and processes may be reversed, and certain features of the invention may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of this description of the invention. Changes may be made in the elements described herein without departing from the spirit and scope of the invention as described in the following claims. In addition, it is to be understood that features described herein independently may, in certain embodiments, be combined.

What is claimed is:

1. A method for providing acidic gas to a subsurface formation, comprising:

providing heat from one or more heaters to a portion of a subsurface formation;

producing fluids from the formation using a heat treatment process, wherein the produced fluids comprise one or more acidic gases, wherein at least one of the acidic gases comprises hydrogen sulfide; and

introducing at least a portion of the acidic gas comprising hydrogen sulfide into the formation, or into another formation, through one or more wellbores at a pressure below a lithostatic pressure of the formation in which the acidic gas is introduced.

2. The method of claim **1**, wherein the portion of the introduced acidic gas further comprises carbon dioxide.

3. The method of claim **1**, wherein the hydrogen sulfide forms a sulfide layer on the surface of the walls of the wellbores.

4. The method of claim **3**, wherein at least one of the acidic gases comprises carbon dioxide, and the method further comprises introducing at least a portion of the acidic gas comprising carbon dioxide into the sulfided wellbore.

5. The method of claim **1**, wherein at least some of the acidic gas reacts in the formation.

6. The method of claim **1**, wherein at least some of the acidic gas is sequestered in the formation.

7. The method of claim **1**, wherein at least some of the acidic gas is introduced near the bottom of a saline aquifer.

8. The method of claim **1**, wherein at least one of the heaters is a temperature limited heater.

9. The method of claim **1**, wherein at least one of the heaters is an electrical heater.

10. A method for providing acidic gas to a subsurface formation, comprising:

providing heat from one or more heaters to a portion of a subsurface formation;

producing fluids from the formation using an in situ heat treatment process, wherein the produced fluids comprise one or more acidic gases; and

introducing at least a portion of the acidic gases through a substantially horizontal portion of at least one wellbore positioned near or at the bottom of an aquifer in the formation, or positioned near or at the bottom of an aquifer in another formation.

11. The method of claim **10**, wherein at least one of the acidic gases comprises hydrogen sulfide.

12. The method of claim **10**, wherein at least one of the acidic gases comprises carbon dioxide.

13. The method of claim **10**, wherein at least one of the acidic gases is hydrogen sulfide, carbon dioxide, or a mixture thereof.

14. The method of claim **10**, wherein at least a portion of the acidic gases reacts in the formation.

15. The method of claim **10**, wherein at least a portion of the acidic gases is sequestered in the formation.

16. The method of claim **10**, wherein the formation comprises a barrier portion above the aquifer, and the method further comprises allowing a portion of the acidic gases to diffuse upward towards the barrier portion.

17. The method of claim **16**, wherein the barrier portion is a shale layer.

18. The method of claim **10**, wherein the acidic gases comprise carbon dioxide, and wherein the wellbore is at

sufficient depth such that the carbon dioxide in the acidic gas is introduced in a supercritical state.

19. The method of claim **10**, further comprising sealing at least a portion of the wellbore in the formation at the surface of the formation and/or at an interface of the aquifer.

20. The method of claim **10**, further comprising introducing a fluid to the wellbore used for acidic gas introduction to inhibit corrosion in the wellbore.

* * * * *