



(51) International Patent Classification:

A61M 15/00 (2006.01) A61M 16/00 (2006.01)

(21) International Application Number:

PCT/US2017/030748

(22) International Filing Date:

03 May 2017 (03.05.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/330,970 03 May 2016 (03.05.2016) US

(71) Applicant: INOVA LABS, INC. [US/US]; 3500 COMSOUTH ROAD, SUITE 100, AUSTIN, Texas 78744 (US).

(72) Inventor: NEBRIGIC, Dragan; 226 VAILCO LANE, AUSTIN, Texas 78738 (US).

(74) Agent: MEYERTONS, HOOD, KIVLIN, KOWERT & GOETZEL, P.C.; DELUCA, MARK R., P.O. BOX 398, AUSTIN, Texas 78767-0398 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: METHOD AND SYSTEMS FOR THE DELIVERY OF OXYGEN ENRICHED GAS




FIG. 10

(57) Abstract: Described herein are various embodiments of an oxygen concentrator system and method of delivering oxygen enriched gas to a user. In some embodiments, oxygen concentrator system includes one or more components that improve the efficiency of oxygen enriched gas delivery during operation of the oxygen concentrator system. In some embodiments, time measurements based on the penultimate breath taken by the user are used to alter the oxygen delivery parameters.

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

**TITLE: METHOD AND SYSTEMS FOR THE DELIVERY OF OXYGEN ENRICHED
GAS**

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to methods and system that provide oxygen enriched gas to a subject.

2. Description of the Related Art

There are many patients that require supplemental oxygen as part of Long Term Oxygen Therapy (LTOT). Currently, the vast majority of patients that are receiving LTOT are diagnosed under the general category of Chronic Obstructive Pulmonary Disease, COPD. This general diagnosis includes such common diseases as Chronic Asthma, Emphysema, Congestive Heart Failure and several other cardio-pulmonary conditions. Other people (e.g., obese individuals) may also require supplemental oxygen, for example, to maintain elevated activity levels.

Doctors may prescribe oxygen concentrators or portable tanks of medical oxygen for these patients. Usually a specific oxygen flow rate is prescribed (e.g., 1 liter per minute (LPM), 2 LPM, 3 LPM, etc.). Experts in this field have also recognized that exercise for these patients provide long term benefits that slow the progression of the disease, improve quality of life and extend patient longevity. Most stationary forms of exercise like tread mills and stationary bicycles, however, are too strenuous for these patients. As a result, the need for mobility has long been recognized. Until recently, this mobility has been facilitated by the use of small compressed oxygen tanks. The disadvantage of these tanks is that they have a finite amount of oxygen and they are heavy, weighing about 50 pounds, when mounted on a cart with dolly wheels.

Oxygen concentrators have been in use for about 50 years to supply patients suffering from respiratory insufficiency with supplemental oxygen. Traditional oxygen concentrators used to provide these flow rates have been bulky and heavy making ordinary ambulatory activities with them difficult and impractical. Recently, companies that manufacture large stationary home oxygen concentrators began developing portable oxygen concentrators, POCs. The advantage of POCs concentrators was that they can produce a theoretically endless supply of oxygen. In order to make these devices small for mobility, the various systems necessary for the production of oxygen enriched gas are condensed.

SUMMARY

Systems and methods of providing an oxygen enriched gas to a user of an oxygen concentrator are described herein.

In one embodiment, a method of providing oxygen enriched gas to a user of an oxygen concentrator, includes: measuring the time between at least three successive breaths, wherein a breath is determined to begin when a drop in pressure is measured using a pressure sensor coupled to an outlet of a conduit coupling the user to an oxygen enriched gas source; determining an average breathing rate based on the time between each of the successive breaths, wherein the time between the penultimate breath and the last breath is not used to determine the average breathing rate; and setting an inspiration breath pressure threshold for the pressure sensor based on the determined average breathing rate. In an embodiment, the time is measured between six successive breaths. Adjusting the inspiration breath pressure threshold based on the average breathing rate, in some embodiments, is performed automatically. The oxygen enriched gas source may be an oxygen concentrator system or an oxygen tank.

In some embodiments, the threshold inspiration pressure is lowered when the determined average breathing rate changes from greater than 10 breaths per minute to less than 10 breaths per minute. In some embodiments, the threshold inspiration pressure is increased when the determined average breathing rate changes from less than 15 breaths per minute to greater than 15 breaths per minute. The inspiration breath pressure threshold may be maintained at a current setting when the average breathing rate is between about 10 breaths per minute and about 15 breaths per minute.

In some embodiments, the method further includes switching to an active mode, a sedentary mode, or remaining at the current mode based on the average breathing rate. For example, an active mode may be implemented when the average breathing rate comprises at least 15 breaths per minute. A sedentary mode may be activated when the average breathing rate comprises less than 10 breaths per minute.

In an embodiment, an oxygen concentrator apparatus includes: a pressure sensor, the pressure sensor configured to detect a breath pressure of a user; and a processor operable coupled to the pressure sensor. The processor is capable of executing non-transitory program instructions, wherein the program instructions are operable to: automatically measure the time between at least three successive breaths, wherein a breath is determined to begin when a drop in pressure is measured using the pressure sensor; determine an average breathing rate based on the time between each of the successive breaths, wherein the time between the penultimate breath and the last breath is not used to determine the average breathing rate; and set an inspiration breath pressure threshold for the pressure sensor based on the determined average breathing rate.

In an embodiment, a method of providing oxygen enriched gas to a user of an oxygen concentrator, includes: measuring the time between a plurality of successive breaths, wherein a breath is determined to begin when a drop in pressure is measured using a pressure sensor coupled to an outlet of a conduit coupling the user to an oxygen enriched gas source; determining an average time between each of the successive breaths, wherein the time between the penultimate breath and the last breath is not used to determine the average time; and setting an inspiration breath pressure threshold for the pressure sensor based on the determined average time, wherein the breath pressure threshold is set to an active mode breath pressure threshold if the average time is less than a predefined time, and wherein the breath pressure threshold is set to a sleep mode breath pressure threshold if the average time is greater than a predefined time, wherein the sleep mode breath pressure threshold is lower than the active mode breath pressure threshold; measuring the time since the penultimate breath and the time since the last breath when in sleep mode; and automatically providing oxygen enriched gas to the user if the sum of the time since the penultimate breath plus the time since the last breath is greater than a function of the determined average breathing time. Adjusting the inspiration breath pressure threshold, in an embodiment, is automatically based on the average time.

In some embodiments, the predefined time is between about 8 seconds and about 12 seconds. In some embodiments, the function of the determined average breathing time is a constant times the determined average breathing time, wherein the constant is between 1.5 and 2.5. The method also includes measuring the time since the penultimate breath, wherein if two breaths are not received within a predetermined time, a false breath time is added to the successive breaths and the average calculated. In one embodiment, the method includes measuring the time between at least six successive breaths, wherein the time between the 5th breath and the 6th breath is not used to determine the average time.

In an embodiment, automatically providing oxygen enriched gas comprises delivering oxygen enriched gas to the user every 3 – 4 seconds. In an embodiment, the time between each automatic delivery of oxygen enriched gas is varied randomly between 3-4 seconds. Alternatively, the time between each automatic delivery of oxygen enriched gas is varied by a constant amount, cycling between 3-4 seconds. The automatic delivery of oxygen enriched gas to the user is discontinued if a breath is detected from the user.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the present invention will become apparent to those skilled in the art with the benefit of the following detailed description of embodiments and upon reference to the accompanying drawings in which:

FIG. 1 depicts a schematic diagram of an embodiment of the components of an oxygen concentrator;

FIG. 2 depicts a schematic diagram of an embodiment of the outlet components of an oxygen concentrator;

5 FIG. 3 depicts a schematic diagram of an embodiment of an outlet conduit for an oxygen concentrator;

FIG. 4 depicts a perspective view of an embodiment of a disassembled canister system;

FIG. 5 depicts a perspective view of an embodiment of an end of a canister system;

10 FIG. 6 depicts the assembled end of an embodiment of the canister system end depicted in FIG. 5;

FIG. 7 depicts a perspective view of an embodiment of an opposing end of the canister system depicted in FIG. 4 and 5;

FIG. 8 depicts a perspective view of an embodiment of the assembled opposing end of the canister system end depicted in FIG. 7;

15 FIG. 9 depicts various profiles of embodiments for providing oxygen enriched gas from an oxygen concentrator; and

FIG. 10 depicts a flowchart of a process for adjusting the inspiration breath pressure threshold.

20 While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

25 **DETAILED DESCRIPTION**

It is to be understood the present invention is not limited to particular devices or methods, which may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting. Headings are for organizational purposes only and are not meant to be used to limit or interpret the description or claims. As used in this specification and the appended claims, the singular forms 30 “a”, “an”, and “the” include singular and plural referents unless the content clearly dictates otherwise. Furthermore, the word “may” is used throughout this application in a permissive sense (i.e., having the potential to, being able to), not in a mandatory sense (i.e., must). The term “include,” and derivations thereof, mean “including, but not limited to.”

The term “coupled” as used herein means either a direct connection or an indirect connection (e.g., one or more intervening connections) between one or more objects or components. The phrase “connected” means a direct connection between objects or components such that the objects or components are connected directly to each other. As used herein the phrase “obtaining” a device means that the device is either purchased or constructed.

Oxygen concentrators take advantage of pressure swing adsorption (PSA). Pressure swing adsorption involves using a compressor to increase gas pressure inside a canister that contains particles of a gas separation adsorbent. As the pressure increases, certain molecules in the gas may become adsorbed onto the gas separation adsorbent. Removal of a portion of the gas in the canister under the pressurized conditions allows separation of the non-adsorbed molecules from the adsorbed molecules. The gas separation adsorbent may be regenerated by reducing the pressure, which reverses the adsorption of molecules from the adsorbent. Further details regarding oxygen concentrators may be found, for example, in U.S. Published Patent Application No. 2009-0065007, published March 12, 2009, and entitled “Oxygen Concentrator Apparatus and Method”, which is incorporated herein by reference.

Ambient air usually includes approximately 78% nitrogen and 21% oxygen with the balance comprised of argon, carbon dioxide, water vapor and other trace elements. If a gas mixture such as air, for example, is passed under pressure through a vessel containing a gas separation adsorbent bed that attracts nitrogen more strongly than it does oxygen, part or all of the nitrogen will stay in the bed, and the gas coming out of the vessel will be enriched in oxygen. When the bed reaches the end of its capacity to adsorb nitrogen, it can be regenerated by reducing the pressure, thereby releasing the adsorbed nitrogen. It is then ready for another cycle of producing oxygen enriched air. By alternating canisters in a two-canister system, one canister can be collecting oxygen while the other canister is being purged (resulting in a continuous separation of the oxygen from the nitrogen). In this manner, oxygen can be accumulated out of the air for a variety of uses include providing supplemental oxygen to patients.

FIG. 1 illustrates a schematic diagram of an oxygen concentrator **100**, according to an embodiment. Oxygen concentrator **100** may concentrate oxygen out of an air stream to provide oxygen enriched gas to a user. As used herein, “oxygen enriched gas” is composed of at least about 50% oxygen, at least about 60% oxygen, at least about 70% oxygen, at least about 80% oxygen, at least about 90% oxygen, at least about 95% oxygen, at least about 98% oxygen, or at least about 99% oxygen.

Oxygen concentrator **100** may be a portable oxygen concentrator. For example, oxygen concentrator **100** may have a weight and size that allows the oxygen concentrator to be carried by hand and/or in a carrying case. In one embodiment, oxygen concentrator **100** has a weight of less

than about 20 lbs., less than about 15 lbs., less than about 10 lbs., or less than about 5 lbs. In an embodiment, oxygen concentrator **100** has a volume of less than about 1000 cubic inches, less than about 750 cubic inches; less than about 500 cubic inches, less than about 250 cubic inches, or less than about 200 cubic inches.

5 Oxygen may be collected from ambient air by pressurizing ambient air in canisters **302** and **304**, which include a gas separation adsorbent. Gas separation adsorbents useful in an oxygen concentrator are capable of separating at least nitrogen from an air stream to produce oxygen enriched gas. Examples of gas separation adsorbents include molecular sieves that are capable of separation of nitrogen from an air stream. Examples of adsorbents that may be used in
10 an oxygen concentrator include, but are not limited to, zeolites (natural) or synthetic crystalline aluminosilicates that separate nitrogen from oxygen in an air stream under elevated pressure. Examples of synthetic crystalline aluminosilicates that may be used include, but are not limited to: OXYSIV adsorbents available from UOP LLC, Des Plaines, IW; SYLOBEAD adsorbents available from W. R. Grace & Co, Columbia, MD; SILIPORITE adsorbents available from
15 CECA S.A. of Paris, France; ZEOCHEM adsorbents available from Zeochem AG, Uetikon, Switzerland; and AgLiLSX adsorbent available from Air Products and Chemicals, Inc., Allentown, PA.

As shown in FIG. 1, air may enter the oxygen concentrator through air inlet **106**. Air may be drawn into air inlet **106** by compression system **200**. Compression system **200** may draw in
20 air from the surroundings of the oxygen concentrator and compress the air, forcing the compressed air into one or both canisters **302** and **304**. In an embodiment, an inlet muffler **108** may be coupled to air inlet **106** to reduce sound produced by air being pulled into the oxygen generator by compression system **200**. In an embodiment, inlet muffler **108** may be a moisture and sound absorbing muffler. For example, a water absorbent material (such as a polymer water
25 absorbent material or a zeolite material) may be used to both absorb water from the incoming air and to reduce the sound of the air passing into the air inlet **106**.

Compression system **200** may include one or more compressors capable of compressing air. In some embodiments, compression system may include one, two, three, four, or more compressors. Compression system **200** as depicted that includes compressor **210** and motor **220**.
30 Motor **220** is coupled to compressor **210** and provides an operating force to the compressor to operate the compression mechanism. Pressurized air, produced by compression system **200**, may be forced into one or both of the canisters **302** and **304**. In some embodiments, the ambient air may be pressurized in the canisters to a pressure approximately in a range of 13-20 pounds per square inch (psi). Other pressures may also be used, depending on the type of gas separation
35 adsorbent disposed in the canisters.

In some embodiments, motor **220** is coupled to a pressurizing device (e.g. piston pump or a diaphragm pump). The pressuring device may be a piston pump that has multiple pistons. During operation, the pistons may be selectively turned on or off. In some embodiments, motor **220** may be coupled to multiple pumps. Each pump may be selectively turned on or off. For example, controller **400** may determine which pumps or pistons should be operated based on predetermined operating conditions.

Coupled to each canister **302/304** are inlet valves **122/124** and outlet valves **132/134**. As shown in FIG. 1, inlet valve **122** is coupled to canister **302** and inlet valve **124** is coupled to canister **304**. Outlet valve **132** is coupled to canister **302** and outlet valve **134** is coupled to canister **304**. Inlet valves **122/124** are used to control the passage of air from compression system **200** to the respective canisters. Outlet valves **132/134** are used to release gas from the respective canisters during a venting process. In some embodiments, inlet valves **122/124** and outlet valves **132/134** may be silicon plunger solenoid valves. Other types of valves, however, may be used. Plunger valves offer advantages over other kinds of valves by being quiet and having low slippage.

In some embodiments, a two-step valve actuation voltage may be used to control inlet valves **122/124** and outlet valves **132/134**. For example, a high voltage (e.g., 24 V) may be applied to an inlet valve to open the inlet valve. The voltage may then be reduced (e.g., to 7 V) to keep the inlet valve open. Using less voltage to keep a valve open may use less power (Power = Voltage * Current). This reduction in voltage minimizes heat buildup and power consumption to extend run time from the battery. When the power is cut off to the valve, it closes by spring action. In some embodiments, the voltage may be applied as a function of time that is not necessarily a stepped response (e.g., a curved downward voltage between an initial 24 V and a final 7 V).

In some embodiments, air may be pulled into the oxygen concentrator through compressors **305, 310**. In some embodiments, air may flow from compressors **305, 310** to canisters **302, 304**. In some embodiments, one of valves **122** or **124** may be closed (e.g., as signaled by controller **400**) resulting in the combined output of both compressors **305, 310** flowing through the other respective valve **122** or **124** into a respective canister **302, 304**. For example, if valve **124** is closed, the air from both compressors **305, 310** may flow through valve **122**. If valve **122** is closed, the air from both compressors **305, 310** may flow through valve **124**. In some embodiments, valve **122** and valve **124** may alternate to alternately direct the air from the compressors **305, 310** into respective canisters **302** or **304**.

In an embodiment, pressurized air is sent into one of canisters **302** or **304** while the other canister is being vented. For example, during use, inlet valve **122** is opened while inlet valve **124**

is closed. Pressurized air from compression system **200** is forced into canister **302**, while being inhibited from entering canister **304** by inlet valve **124**. In an embodiment, a controller **400** is electrically coupled to valves **122**, **124**, **132**, and **134**. Controller **400** includes one or more processors **410** operable to execute program instructions stored in memory **420**. The program instructions are operable to perform various predefined methods that are used to operate the oxygen concentrator. Controller **400** may include program instructions for operating inlet valves **122** and **124** out of phase with each other, i.e., when one of inlet valves **122** or **124** is opened, the other valve is closed. During pressurization of canister **302**, outlet valve **132** is closed and outlet valve **134** is opened. Similar to the inlet valves, outlet valves **132** and **134** are operated out of phase with each other. In some embodiments, the voltages and the duration of the voltages used to open the input and output valves may be controlled by controller **400**.

Check valves **142** and **144** are coupled to canisters **302** and **304**, respectively. Check valves **142** and **144** are one way valves that are passively operated by the pressure differentials that occur as the canisters are pressurized and vented. Check valves **142** and **144** are coupled to canisters to allow oxygen produced during pressurization of the canister to flow out of the canister, and to inhibit back flow of oxygen or any other gases into the canister. In this manner, check valves **142** and **144** act as one way valves allowing oxygen enriched gas to exit the respective canister during pressurization.

The term “check valve”, as used herein, refers to a valve that allows flow of a fluid (gas or liquid) in one direction and inhibits back flow of the fluid. Examples of check valves that are suitable for use include, but are not limited to: a ball check valve; a diaphragm check valve; a butterfly check valve; a swing check valve; a duckbill valve; and a lift check valve. Under pressure, nitrogen molecules in the pressurized ambient air are adsorbed by the gas separation adsorbent in the pressurized canister. As the pressure increases, more nitrogen is adsorbed until the gas in the canister is enriched in oxygen. The nonadsorbed gas molecules (mainly oxygen) flow out of the pressurized canister when the pressure reaches a point sufficient to overcome the resistance of the check valve coupled to the canister. In one embodiment, the pressure drop of the check valve in the forward direction is less than 1 psi. The break pressure in the reverse direction is greater than 100 psi. It should be understood, however, that modification of one or more components would alter the operating parameters of these valves. If the forward flow pressure is increased, there is, generally, a reduction in oxygen enriched gas production. If the break pressure for reverse flow is reduced or set too low, there is, generally, a reduction in oxygen enriched gas pressure.

In an exemplary embodiment, canister **302** is pressurized by compressed air produced in compression system **200** and passed into canister **302**. During pressurization of canister **302** inlet

valve **122** is open, outlet valve **132** is closed, inlet valve **124** is closed and outlet valve **134** is open. Outlet valve **134** is opened when outlet valve **132** is closed to allow substantially simultaneous venting of canister **304** while canister **302** is pressurized. Canister **302** is pressurized until the pressure in canister is sufficient to open check valve **142**. Oxygen enriched gas produced in canister **302** exits through check valve and, in one embodiment, is collected in accumulator **106**.

After some time the gas separation adsorbent will become saturated with nitrogen and will be unable to separate significant amounts of nitrogen from incoming air. This point is usually reached after a predetermined time of oxygen enriched gas production. In the embodiment described above, when the gas separation adsorbent in canister **302** reaches this saturation point, the inflow of compressed air is stopped and canister **302** is vented to remove nitrogen. During venting, inlet valve **122** is closed, and outlet valve **132** is opened. While canister **302** is being vented, canister **304** is pressurized to produce oxygen enriched gas in the same manner described above. Pressurization of canister **304** is achieved by closing outlet valve **134** and opening inlet valve **124**. The oxygen enriched gas exits canister **304** through check valve **144**.

During venting of canister **302**, outlet valve **132** is opened allowing pressurized gas (mainly nitrogen) to exit the canister through concentrator outlet **130**. In an embodiment, the vented gases may be directed through muffler **133** to reduce the noise produced by releasing the pressurized gas from the canister. As gas is released from canister **302**, pressure in the canister drops. The drop in pressure may allow the nitrogen to become desorbed from the gas separation adsorbent. The released nitrogen exits the canister through outlet **130**, resetting the canister to a state that allows renewed separation of oxygen from an air stream. Muffler **133** may include open cell foam (or another material) to muffle the sound of the gas leaving the oxygen concentrator. In some embodiments, the combined muffling components/techniques for the input of air and the output of gas may provide for oxygen concentrator operation at a sound level below 50 decibels.

During venting of the canisters, it is advantageous that at least a majority of the nitrogen is removed. In an embodiment, at least about 50%, at least about 60%, at least about 70%, at least about 80%, at least about 90%, at least about 95%, at least about 98%, or substantially all of the nitrogen in a canister is removed before the canister is re-used to separate oxygen from air. In some embodiments, a canister may be further purged of nitrogen using an oxygen enriched stream that is introduced into the canister from the other canister.

In an exemplary embodiment, a portion of the oxygen enriched gas may be transferred from canister **302** to canister **304** when canister **304** is being vented of nitrogen. Transfer of

oxygen enriched gas from canister **302** to **304**, during venting of canister **304**, helps to further purge nitrogen (and other gases) from the canister. In an embodiment, oxygen enriched gas may travel through flow restrictors **151**, **153**, and **155** between the two canisters. Flow restrictor **151** may be a trickle flow restrictor. Flow restrictor **151**, for example, may be a 0.009D flow restrictor (e.g., the flow restrictor has a radius of 0.009 inches which is less than the diameter of the tube it is inside). Flow restrictors **153** and **155** may be 0.013D flow restrictors. Other flow restrictor types and sizes are also contemplated and may be used depending on the specific configuration and tubing used to couple the canisters. In some embodiments, the flow restrictors may be press fit flow restrictors that restrict air flow by introducing a narrower diameter in their respective tube. In some embodiments, the press fit flow restrictors may be made of sapphire, metal or plastic (other materials are also contemplated).

Flow of oxygen enriched gas is also controlled by use of valve **152** and valve **154**. Valves **152** and **154** may be opened for a short duration during the venting process (and may be closed otherwise) to prevent excessive oxygen loss out of the purging canister. Other durations are also contemplated. In an exemplary embodiment, canister **302** is being vented and it is desirable to purge canister **302** by passing a portion of the oxygen enriched gas being produced in canister **304** into canister **302**. A portion of oxygen enriched gas, upon pressurization of canister **304**, will pass through flow restrictor **151** into canister **302** during venting of canister **302**. Additional oxygen enriched air is passed into canister **302**, from canister **304**, through valve **154** and flow restrictor **155**. Valve **152** may remain closed during the transfer process, or may be opened if additional oxygen enriched gas is needed. The selection of appropriate flow restrictors **151** and **155**, coupled with controlled opening of valve **154** allows a controlled amount of oxygen enriched gas to be sent from canister **304** to **302**. In an embodiment, the controlled amount of oxygen enriched gas is an amount sufficient to purge canister **302** and minimize the loss of oxygen enriched gas through venting valve **132** of canister **302**. While this embodiment describes venting of canister **302**, it should be understood that the same process can be used to vent canister **304** using flow restrictor **151**, valve **152** and flow restrictor **153**.

The pair of equalization/vent valves **152/154** work with flow restrictors **153** and **155** to optimize the air flow balance between the two canisters. This may allow for better flow control for venting the canisters with oxygen enriched gas from the other of the canisters. It may also provide better flow direction between the two canisters. It has been found that, while flow valves **152/154** may be operated as bi-directional valves, the flow rate through such valves varies depending on the direction of fluid flowing through the valve. For example, oxygen enriched gas flowing from canister **304** toward canister **302** has a flow rate faster through valve **152** than the flow rate of oxygen enriched gas flowing from canister **302** toward canister **304** through valve

152. If a single valve was to be used, eventually either too much or too little oxygen enriched gas would be sent between the canisters and the canisters would, over time, begin to produce different amounts of oxygen enriched gas. Use of opposing valves and flow restrictors on parallel air pathways may equalize the flow pattern of the oxygen between the two canisters.

- 5 Equalizing the flow may allow for a steady amount of oxygen available to the user over multiple cycles and also may allow a predictable volume of oxygen to purge the other of the canisters. In some embodiments, the air pathway may not have restrictors but may instead have a valve with a built in resistance or the air pathway itself may have a narrow radius to provide resistance.

At times, oxygen concentrator may be shut down for a period of time. When an oxygen
10 concentrator is shut down, the temperature inside the canisters may drop as a result of the loss of adiabatic heat from the compression system. As the temperature drops, the volume occupied by the gases inside the canisters will drop. Cooling of the canisters may lead to a negative pressure in the canisters. Valves (e.g., valves **122**, **124**, **132**, and **134**) leading to and from the canisters are dynamically sealed rather than hermetically sealed. Thus, outside air may enter the canisters
15 after shutdown to accommodate the pressure differential. When outside air enters the canisters, moisture from the outside air may condense inside the canister as the air cools. Condensation of water inside the canisters may lead to gradual degradation of the gas separation adsorbents, steadily reducing ability of the gas separation adsorbents to produce oxygen enriched gas.

In an embodiment, outside air may be inhibited from entering canisters after the oxygen
20 concentrator is shut down by pressurizing both canisters prior to shut down. By storing the canisters under a positive pressure, the valves may be forced into a hermetically closed position by the internal pressure of the air in the canisters. In an embodiment, the pressure in the canisters, at shutdown, should be at least greater than ambient pressure. As used herein the term “ambient pressure” refers to the pressure of the surroundings that the oxygen generator is located
25 (e.g. the pressure inside a room, outside, in a plane, etc.). In an embodiment, the pressure in the canisters, at shutdown, is at least greater than standard atmospheric pressure (i.e., greater than 760 mmHg (Torr), 1 atm, 101,325 Pa). In an embodiment, the pressure in the canisters, at shutdown, is at least about 1.1 times greater than ambient pressure; is at least about 1.5 times greater than ambient pressure; or is at least about 2 times greater than ambient pressure.

30 In an embodiment, pressurization of the canisters may be achieved by directing pressurized air into each canister from the compression system and closing all valves to trap the pressurized air in the canisters. In an exemplary embodiment, when a shutdown sequence is initiated, inlet valves **122** and **124** are opened and outlet valves **132** and **134** are closed. Because inlet valves **122** and **124** are joined together by a common conduit, both canisters **302** and **304**
35 may become pressurized as air and or oxygen enriched gas from one canister may be transferred

to the other canister. This situation may occur when the pathway between the compression system and the two inlet valves allows such transfer. Because the oxygen generator operates in an alternating pressurize/venting mode, at least one of the canisters should be in a pressurized state at any given time. In an alternate embodiment, the pressure may be increased in each canister by operation of compression system **200**. When inlet valves **122** and **124** are opened, pressure between canisters **302** and **304** will equalize, however, the equalized pressure in either canister may not be sufficient to inhibit air from entering the canisters during shutdown. In order to ensure that air is inhibited from entering the canisters, compression system **200** may be operated for a time sufficient to increase the pressure inside both canisters to a level at least greater than ambient pressure. Regardless of the method of pressurization of the canisters, once the canisters are pressurized, inlet valves **122** and **124** are closed, trapping the pressurized air inside the canisters, which inhibits air from entering the canisters during the shutdown period.

An outlet system, coupled to one or more of the canisters, includes one or more conduits for providing oxygen enriched gas to a user. In an embodiment, oxygen enriched gas produced in either of canisters **302** and **304** is collected in accumulator **106** through check valves **142** and **144**, respectively, as depicted schematically in FIG. 1. The oxygen enriched gas leaving the canisters may be collected in oxygen accumulator **106** prior to being provided to a user. In some embodiments, a tube may be coupled to accumulator **106** to provide the oxygen enriched gas to the user. Oxygen enriched gas may be provided to the user through an airway delivery device that transfer the oxygen enriched gas to the user's mouth and/or nose. In an embodiment, an outlet may include a tube that directs the oxygen toward a user's nose and/or mouth that may not be directly coupled to the user's nose.

Turning to FIG. 2, a schematic diagram of an embodiment of an outlet system for an oxygen concentrator is shown. Supply valve **160** may be coupled to outlet tube to control the release of the oxygen enriched gas from accumulator **106** to the user. In an embodiment, supply valve **160** is an electromagnetically actuated plunger valve. Supply valve **160** is actuated by controller **400** to control the delivery of oxygen enriched gas to a user. Actuation of supply valve **160** is not timed or synchronized to the pressure swing adsorption process. Instead, actuation is, in some embodiments, synchronized to the patient's breathing. Additionally, supply valve **160** may have multiple actuations to help establish a clinically effective flow profile for providing oxygen enriched gas.

Oxygen enriched gas in accumulator **106** passes through supply valve **160** into expansion chamber **170** as depicted in FIG. 2. In an embodiment, expansion chamber may include one or more devices capable of being used to determine an oxygen concentration of gas passing through the chamber. Oxygen enriched gas in expansion chamber **170** builds briefly, through release of

gas from accumulator by supply valve **160**, and then is bled through small orifice flow restrictor **175** to flow rate sensor **185** and then to particulate filter **187**. Flow restrictor **175** may be a 0.025 D flow restrictor. Other flow restrictor types and sizes may be used. In some embodiments, the diameter of the air pathway in the housing may be restricted to create restricted air flow. Flow rate sensor **185** may be any sensor capable of assessing the rate of gas flowing through the conduit. Particulate filter **187** may be used to filter bacteria, dust, granule particles, etc. prior to delivery of the oxygen enriched gas to the user. The oxygen enriched gas passes through filter **187** to connector **190** which sends the oxygen enriched gas to the user via conduit **192** and to pressure sensor **194**.

The fluid dynamics of the outlet pathway, coupled with the programmed actuations of supply valve **160**, results in a bolus of oxygen being provided at the correct time and with a flow profile that assures rapid delivery into the patient's lungs without any excessive flow rates that would result in wasted retrograde flow out the nostrils and into the atmosphere. It has been found, in our specific system, that the total volume of the bolus required for prescriptions is equal to 11 mL for each LPM, i.e., 11 mL for a prescription of 1 LPM; 22 mL for a prescription of 2 LPM; 33 mL for a prescription of 3 LPM; 44 mL for a prescription of 4 LPM; 55 mL for a prescription of 5 LPM; etc. This is generally referred to as the LPM equivalent. It should be understood that the LPM equivalent may vary between apparatus due to differences in construction design, tubing size, chamber size, etc.

Expansion chamber **170** may include one or more oxygen sensors capable of being used to determine an oxygen concentration of gas passing through the chamber. In an embodiment, the oxygen concentration of gas passing through expansion chamber **170** is assessed using oxygen sensor **165**. An oxygen sensor is a device capable of detecting oxygen in a gas. Examples of oxygen sensors include, but are not limited to, ultrasonic oxygen sensors, electrical oxygen sensors, and optical oxygen sensors. In one embodiment, oxygen sensor **165** is an ultrasonic oxygen sensor that includes ultrasonic emitter **166** and ultrasonic receiver **168**. In some embodiments, ultrasonic emitter **166** may include multiple ultrasonic emitters and ultrasonic receiver **168** may include multiple ultrasonic receivers. In embodiments having multiple emitters/receivers, the multiple ultrasonic emitters and multiple ultrasonic receivers may be axially aligned (e.g., across the gas mixture flow path which may be perpendicular to the axial alignment).

In use, an ultrasonic sound wave (from emitter **166**) may be directed through oxygen enriched gas disposed in chamber **170** to receiver **168**. Ultrasonic sensor assembly may be based on detecting the speed of sound through the gas mixture to determine the composition of the gas mixture (e.g., the speed of sound is different in nitrogen and oxygen). In a mixture of the two

gases, the speed of sound through the mixture may be an intermediate value proportional to the relative amounts of each gas in the mixture. In use, the sound at the receiver **168** is slightly out of phase with the sound sent from emitter **166**. This phase shift is due to the relatively slow velocity of sound through a gas medium as compared with the relatively fast speed of the electronic pulse through wire. The phase shift, then, is proportional to the distance between the emitter and the receiver and the speed of sound through the expansion chamber. The density of the gas in the chamber affects the speed of sound through the chamber and the density is proportional to the ratio of oxygen to nitrogen in the chamber. Therefore, the phase shift can be used to measure the concentration of oxygen in the expansion chamber. In this manner the relative concentration of oxygen in the accumulation chamber may be assessed as a function of one or more properties of a detected sound wave traveling through the accumulation chamber.

In some embodiments, multiple emitters **166** and receivers **168** may be used. The readings from the emitters **166** and receivers **168** may be averaged to cancel errors that may be inherent in turbulent flow systems. In some embodiments, the presence of other gases may also be detected by measuring the transit time and comparing the measured transit time to predetermined transit times for other gases and/or mixtures of gases.

The sensitivity of the ultrasonic sensor system may be increased by increasing the distance between emitter **166** and receiver **168**, for example to allow several sound wave cycles to occur between emitter **166** and the receiver **168**. In some embodiments, if at least two sound cycles are present, the influence of structural changes of the transducer may be reduced by measuring the phase shift relative to a fixed reference at two points in time. If the earlier phase shift is subtracted from the later phase shift, the shift caused by thermal expansion of expansion chamber **170** may be reduced or cancelled. The shift caused by a change of the distance between emitter **166** and receiver **168** may be the approximately the same at the measuring intervals, whereas a change owing to a change in oxygen concentration may be cumulative. In some embodiments, the shift measured at a later time may be multiplied by the number of intervening cycles and compared to the shift between two adjacent cycles. Further details regarding sensing of oxygen in the expansion chamber may be found, for example, in U.S. Published Patent Application No. 2009-0065007, published March 12, 2009, and entitled "Oxygen Concentrator Apparatus and Method, which is incorporated herein by reference.

Flow rate sensor **185** may be used to determine the flow rate of gas flowing through the outlet system. Flow rate sensors that may be used include, but are not limited to: diaphragm/bellows flow meters; rotary flow meters (e.g. Hall Effect flow meters); turbine flow meters; orifice flow meters; and ultrasonic flow meters. Flow rate sensor **185** may be coupled to controller **400**. The rate of gas flowing through the outlet system may be an indication of the

breathing volume of the user. Changes in the flow rate of gas flowing through the outlet system may also be used to determine a breathing rate of the user. Controller **400** may control actuation of supply valve **160** based on the breathing rate and/or breathing volume of the user, as assessed by flow rate sensor **185**

5 In some embodiments, ultrasonic sensor system **165** and, for example, flow rate sensor **185** may provide a measurement of an actual amount of oxygen being provided. For example, flow rate sensor **185** may measure a volume of gas (based on flow rate) provided and ultrasonic sensor system **165** may provide the concentration of oxygen of the gas provided. These two measurements together may be used by controller **400** to determine an approximation of the
10 actual amount of oxygen provided to the user.

Oxygen enriched gas passes through flow meter **185** to filter **187**. Filter **187** removes bacteria, dust, granule particles, etc. prior to providing the oxygen enriched gas to the user. The filtered oxygen enriched gas passes through filter **187** to connector **190**. Connector **190** may be a “Y” connector coupling the outlet of filter **187** to pressure sensor **194** and outlet conduit **192**.

15 Pressure sensor **194** may be used to monitor the pressure of the gas passing through conduit **192** to the user. Changes in pressure, sensed by pressure sensor **194**, may be used to determine a breathing rate of a user, as well as the onset of inhalation. Controller **400** may control actuation of supply valve **160** based on the breathing rate and/or onset of inhalation of the user, as assessed by pressure sensor **194**. In an embodiment, controller **400** may control actuation of supply valve
20 **160** based on information provided by flow rate sensor **185** and pressure sensor **194**.

Oxygen enriched gas may be provided to a user through conduit **192**. In an embodiment, conduit **192** may be a silicone tube. Conduit **192** may be coupled to a user using an airway coupling member **196**, as depicted in FIG. 3. Airway coupling member **196** may be any device capable of providing the oxygen enriched gas to nasal cavities or oral cavities. Examples of
25 airway coupling members include, but are not limited to: nasal masks, nasal pillows, nasal prongs, nasal cannulas, and mouthpieces. A nasal cannula airway delivery device is depicted in FIG. 3. During use, oxygen enriched gas from oxygen concentrator system **100** is provided to the user through conduit **192** and airway coupling member **196**. Airway coupling member **196** is positioned proximate to a user’s airway (e.g., proximate to the user’s mouth and or nose) to allow
30 delivery of the oxygen enriched gas to the user while allowing the user to breath air from the surroundings.

Canister System

Oxygen concentrator system **100** may include at least two canisters, each canister
35 including a gas separation adsorbent. The canisters of oxygen concentrator system **100** may be

disposed formed from a molded housing. In an embodiment, canister system **300** includes two housing components **310** and **510**, as depicted in FIG. 4. The housing components **310** and **510** may be formed separately and then coupled together. In some embodiments, housing components **310** and **510** may be injection molded or compression molded. Housing components **310** and **510** may be made from a thermoplastic polymer such as polycarbonate, methylene carbide, polystyrene, acrylonitrile butadiene styrene (ABS), polypropylene, polyethylene, or polyvinyl chloride. In another embodiment, housing components **310** and **510** may be made of a thermoset plastic or metal (such as stainless steel or a light-weight aluminum alloy). Lightweight materials may be used to reduce the weight of the oxygen concentrator **100**. In some embodiments, the two housings **310** and **510** may be fastened together using screws or bolts. Alternatively, housing components **310** and **510** may be solvent welded together.

As shown, valve seats **320**, **322**, **324**, and **326** and air pathways **330** and **332** may be integrated into the housing component **310** to reduce the number of sealed connections needed throughout the air flow of the oxygen concentrator **100**. In various embodiments, the housing components **310** and **410** of the oxygen concentrator **100** may form a two-part molded plastic frame that defines two canisters **302** and **304** and accumulation chamber **106**.

Air pathways/tubing between different sections in housing components **310** and **510** may take the form of molded conduits. Conduits in the form of molded channels for air pathways may occupy multiple planes in housing components **310** and **510**. For example, the molded air conduits may be formed at different depths and at different x,y,z positions in housing components **310** and **510**. In some embodiments, a majority or substantially all of the conduits may be integrated into the housing components **310** and **510** to reduce potential leak points.

In some embodiments, prior to coupling housing components **310** and **510** together, O-rings may be placed between various points of housing components **310** and **510** to ensure that the housing components are properly sealed. In some embodiments, components may be integrated and/or coupled separately to housing components **310** and **510**. For example, tubing, flow restrictors (e.g., press fit flow restrictors), oxygen sensors, gas separation adsorbents **139**, check valves, plugs, processors, power supplies, etc. may be coupled to housing components **510** and **410** before and/or after the housing components are coupled together.

In some embodiments, apertures **337** leading to the exterior of housing components **310** and **410** may be used to insert devices such as flow restrictors. Apertures may also be used for increased moldability. One or more of the apertures may be plugged after molding (e.g., with a plastic plug). In some embodiments, flow restrictors may be inserted into passages prior to inserting plug to seal the passage. Press fit flow restrictors may have diameters that may allow a friction fit between the press fit flow restrictors and their respective apertures. In some

embodiments, an adhesive may be added to the exterior of the press fit flow restrictors to hold the press fit flow restrictors in place once inserted. In some embodiments, the plugs may have a friction fit with their respective tubes (or may have an adhesive applied to their outer surface). The press fit flow restrictors and/or other components may be inserted and pressed into their
5 respective apertures using a narrow tip tool or rod (e.g., with a diameter less than the diameter of the respective aperture). In some embodiments, the press fit flow restrictors may be inserted into their respective tubes until they abut a feature in the tube to halt their insertion. For example, the feature may include a reduction in radius. Other features are also contemplated (e.g., a bump in the side of the tubing, threads, etc.). In some embodiments, press fit flow restrictors may be
10 molded into the housing components (e.g., as narrow tube segments).

In some embodiments, spring baffle **129** may be placed into respective canister receiving portions of housing component **310** and **510** with the spring side of the baffle **129** facing the exit of the canister. Spring baffle **129** may apply force to gas separation adsorbent **139** in the canister while also assisting in preventing gas separation adsorbent **139** from entering the exit apertures.
15 Use of a spring baffle **129** may keep the gas separation adsorbent compact while also allowing for expansion (e.g., thermal expansion). Keeping the gas separation adsorbent **139** compact may prevent the gas separation adsorbent from breaking during movement of the oxygen concentrator system **100**).

In some embodiments, pressurized air from the compression system **200** may enter air
20 inlet **306**. Air inlet **306** is coupled to inlet conduit **330**. Air enters housing component **310** through inlet **306** travels through conduit **330**, and then to valve seats **322** and **324**. FIG. 5 and FIG. 6 depict an end view of housing **310**. FIG. 5, depicts an end view of housing **310** prior to fitting valves to housing **310**. FIG. 6 depicts an end view of housing **310** with the valves fitted to the housing **310**. Valve seats **322** and **324** are configured to receive inlet valves **122** and **124**
25 respectively. Inlet valve **122** is coupled to canister **302** and inlet valve **124** is coupled to canister **304**. Housing **310** also includes valve seats **332** and **334** configured to receive outlet valves **132** and **134** respectively. Outlet valve **132** is coupled to canister **302** and outlet valve **134** is coupled to canister **304**. Inlet valves **122/124** are used to control the passage of air from conduit **330** to the respective canisters.

In an embodiment, pressurized air is sent into one of canisters **302** or **304** while the other canister is being vented. For example, during use, inlet valve **122** is opened while inlet valve **124** is closed. Pressurized air from compression system **200** is forced into canister **302**, while being inhibited from entering canister **304** by inlet valve **124**. During pressurization of canister **302**, outlet valve **132** is closed and outlet valve **134** is opened. Similar to the inlet valves, outlet
30 valves **132** and **134** are operated out of phase with each other. Each inlet valve seat **322** includes
35

an opening **375** that passes through housing **310** into canister **302**. Similarly valve seat **324** includes an opening **325** that passes through housing **310** into canister **302**. Air from conduit **330** passes through openings **323**, or **325** if the respective valve (**322** or **324**) is open, and enters a canister.

5 Check valves **142** and **144** (*See*, FIG. 4) are coupled to canisters **302** and **304**, respectively. Check valves **142** and **144** are one way valves that are passively operated by the pressure differentials that occur as the canisters are pressurized and vented. Oxygen enriched gas, produced in canisters **302** and **304** pass from the canister into openings **542** and **544** of housing **410**. A passage (not shown) links openings **542** and **544** to conduits **342** and **344**,
10 respectively. Oxygen enriched gas produced in canister **302** passes from the canister through opening **542** and into conduit **342** when the pressure in the canister is sufficient to open check valve **142**. When check valve **142** is open, oxygen enriched gas flows through conduit **342** toward the end of housing **310**. Similarly, oxygen enriched gas produced in canister **304** passes from the canister through opening **544** and into conduit **344** when the pressure in the canister is
15 sufficient to open check valve **144**. When check valve **144** is open, oxygen enriched gas flows through conduit **344** toward the end of housing **310**.

 Oxygen enriched gas from either canister, travels through conduit **342** or **344** and enters conduit **346** formed in housing **310**. Conduit **346** includes openings that couple the conduit to conduit **342**, conduit **344** and accumulator **106**. Thus oxygen enriched gas, produced in canister
20 **302** or **304**, travels to conduit **346** and passes into accumulator **106**.

 After some time the gas separation adsorbent will become saturated with nitrogen and will be unable to separate significant amounts of nitrogen from incoming air. When the gas separation adsorbent in a canister reaches this saturation point, the inflow of compressed air is stopped and the canister is vented to remove nitrogen. Canister **302** is vented by closing inlet
25 valve **122** and opening outlet valve **132**. Outlet valve **132** releases the vented gas from canister **302** into the volume defined by the end of housing **310**. Foam material may cover the end of housing **310** to reduce the sound made by release of gases from the canisters. Similarly, canister **304** is vented by closing inlet valve **124** and opening outlet valve **134**. Outlet valve **134** releases the vented gas from canister **304** into the volume defined by the end of housing **310**.

30 While canister **302** is being vented, canister **304** is pressurized to produce oxygen enriched gas in the same manner described above. Pressurization of canister **304** is achieved by closing outlet valve **134** and opening inlet valve **124**. The oxygen enriched gas exits canister **304** through check valve **144**.

 In an exemplary embodiment, a portion of the oxygen enriched gas may be transferred
35 from canister **302** to canister **304** when canister **304** is being vented of nitrogen. Transfer of

oxygen enriched gas from canister 302 to canister 304, during venting of canister 304, helps to further purge nitrogen (and other gases) from the canister. Flow of oxygen enriched gas between the canisters is controlled using flow restrictors and valves, as depicted in FIG. 1. Three conduits are formed in housing 510 for use in transferring oxygen enriched gas between canisters. As shown in FIG. 7, conduit 530 couples canister 302 to canister 304. Flow restrictor 151 (not shown) is disposed in conduit 530, between canister 302 and canister 304 to restrict flow of oxygen enriched gas during use. Conduit 532 also couples canister 302 to 304. Conduit 532 is coupled to valve seat 552 which receives valve 152, as shown in FIG. 8. Flow restrictor 153 (not shown) is disposed in conduit 532, between canister 302 and 304. Conduit 534 also couples canister 302 to 304. Conduit 534 is coupled to valve seat 554 which receives valve 154, as shown in FIG. 8. Flow restrictor 155 (not shown) is disposed in conduit 534, between canister 302 and 304. The pair of equalization/vent valves 152/154 work with flow restrictors 153 and 155 to optimize the air flow balance between the two canisters.

Oxygen enriched gas in accumulator 106 passes through supply valve 160 into expansion chamber 170 which is formed in housing 510. An opening (not shown) in housing 510 couples accumulator 106 to supply valve 160. In an embodiment, expansion chamber may include one or more devices capable of being used to determine an oxygen concentration of gas passing through the chamber.

Controller System

Operation of oxygen concentrator system 100 may be performed automatically using an internal controller 400 coupled to various components of the oxygen concentrator system, as described herein. Controller 400 includes one or more processors 410 and internal memory 420, as depicted in FIG. 1. Methods used to operate and monitor oxygen concentrator system 100 may be implemented by program instructions stored in memory 420 or a carrier medium coupled to controller 400, and executed by one or more processors 410. A non-transitory memory medium may include any of various types of memory devices or storage devices. The term “memory medium” is intended to include an installation medium, e.g., a Compact Disc Read Only Memory (CD-ROM), floppy disks, or tape device; a computer system memory or random access memory such as Dynamic Random Access Memory (DRAM), Double Data Rate Random Access Memory (DDR RAM), Static Random Access Memory (SRAM), Extended Data Out Random Access Memory (EDO RAM), Rambus Random Access Memory (RAM), etc.; or a non-volatile memory such as a magnetic media, e.g., a hard drive, or optical storage. The memory medium may comprise other types of memory as well, or combinations thereof. In addition, the memory medium may be located in a first computer in which the programs are executed, or may

be located in a second different computer that connects to the first computer over a network, such as the Internet. In the latter instance, the second computer may provide program instructions to the first computer for execution. The term “memory medium” may include two or more memory mediums that may reside in different locations, e.g., in different computers that are connected
5 over a network.

In some embodiments, controller **400** includes processor **410** that includes, for example, one or more field programmable gate arrays (FPGAs), microcontrollers, etc. included on a circuit board disposed in oxygen concentrator system **100**. Processor **410** is capable of executing programming instructions stored in memory **420**. In some embodiments, programming
10 instructions may be built into processor **410** such that a memory external to the processor may not be separately accessed (i.e., the memory **420** may be internal to the processor **410**).

Processor **410** may be coupled to various components of oxygen concentrator system **100**, including, but not limited to compression system **200**, one or more of the valves used to control fluid flow through the system (e.g., valves **122**, **124**, **132**, **134**, **152**, **154**, **160**, or combinations
15 thereof), oxygen sensor **165**, pressure sensor **194**, flow rate monitor **180**, temperature sensors, fans, and any other component that may be electrically controlled. In some embodiments, a separate processor (and/or memory) may be coupled to one or more of the components.

Controller **400** is programmed to operate oxygen concentrator system **100** and is further programmed to monitor the oxygen concentrator system for malfunction states. For example, in
20 one embodiment, controller **400** is programmed to trigger an alarm if the system is operating and no breathing is detected by the user for a predetermined amount of time. For example, if controller **400** does not detect a breath for a period of 75 seconds, an alarm LED may be lit and/or an audible alarm may be sounded. If the user has truly stopped breathing, for example, during a sleep apnea episode, the alarm may be sufficient to awaken the user, causing the user to
25 resume breathing. The action of breathing may be sufficient for controller **400** to reset this alarm function. Alternatively, if the system is accidentally left on when output conduit **192** is removed from the user, the alarm may serve as a reminder for the user to turn oxygen concentrator system **100** off.

Controller **400** is further coupled to oxygen sensor **165**, and may be programmed for
30 continuous or periodic monitoring of the oxygen concentration of the oxygen enriched gas passing through expansion chamber **170**. A minimum oxygen concentration threshold may be programmed into controller **400**, such that the controller lights an LED visual alarm and/or an audible alarm to warn the patient of the low concentration of oxygen.

Controller **400** is also coupled to internal power supply **180** and is capable of monitoring
35 the level of charge of the internal power supply. A minimum voltage and/or current threshold

may be programmed into controller **400**, such that the controller lights an LED visual alarm and/or an audible alarm to warn the patient of low power condition. The alarms may be activated intermittently and at an increasing frequency as the battery approaches zero usable charge.

Further functions of controller **400** are described in detail in other sections of this disclosure.

A user may have a low breathing rate or depth if relatively inactive (e.g., asleep, sitting, etc.) as assessed by comparing the detected breathing rate or depth to a threshold. The user may have a high breathing rate or depth if relatively active (e.g., walking, exercising, etc.). An active/sleep mode may be assessed automatically and/or the user may manually indicate a respective active or sleep mode by a pressing button for active mode and another button for sleep mode. In some embodiments, a user may toggle a switch from active mode, normal mode, or sedentary mode. The adjustments made by the oxygen concentrator system in response to activating active mode or sleep mode are described in more detail herein.

Methods of Delivery of Oxygen Enriched Gas

The main use of an oxygen concentrator system is to provide supplemental oxygen to a user. Generally, the amount of supplemental oxygen to be provided is assessed by a physician. Typical prescribed amounts of supplemental oxygen may range from about 1 LPM to up to about 10 LPM. The most commonly prescribed amounts are 1 LPM, 2 LPM, 3 LPM, and 4 LPM. Generally, oxygen enriched gas is provided to the use during a breathing cycle to meet the prescription requirement of the user. As used herein the term “breathing cycle” refers to an inhalation followed by an exhalation of a person.

In order to minimize the amount of oxygen enriched gas that is needed to be produced to meet the prescribed amounts, controller **400** may be programmed to time delivery of the oxygen enriched gas with the user’s inhalations. Releasing the oxygen enriched gas to the user as the user inhales may prevent unnecessary oxygen generation (further reducing power requirements) by not releasing oxygen, for example, when the user is exhaling. Reducing the amount of oxygen required may effectively reduce the amount of air compressing needed for oxygen concentrator **100** (and subsequently may reduce the power demand from the compressors).

Oxygen enriched gas, produced by oxygen concentrator system **100** is stored in an oxygen accumulator **106** and released to the user as the user inhales. The amount of oxygen enriched gas provided by the oxygen concentrator system is controlled, in part, by supply valve **160**. In an embodiment, supply valve **160** is opened for a sufficient amount of time to provide the appropriate amount of oxygen enriched gas, as assessed by controller **400**, to the user. In order to minimize the amount of oxygen required to meet the prescription requirements of a user,

the oxygen enriched gas may be provided in a bolus when a user's inhalation is first detected. For example, the bolus of oxygen enriched gas may be provided in the first few milliseconds of a user's inhalation.

In an embodiment, pressure sensor **194** and/or flow rate sensor **185** may be used to determine the onset of inhalation by the user. For example, the user's inhalation may be detected by using pressure sensor **194**. In use, a conduit for providing oxygen enriched gas is coupled to a user's nose and/or mouth (e.g., using a nasal cannula or a face mask). At the onset of an inhalation, the user begins to draw air into their body through the nose and/or mouth. As the air is drawn in, a negative pressure is generated at the end of the conduit, due, in part, to the venturi action of the air being drawn across the end of the delivery conduit. Pressure sensor **194** may be operable to create a signal when a drop in pressure is detected, to signal the onset of inhalation. Upon detection of the onset of inhalation, supply valve **160** is controlled to release a bolus of oxygen enriched gas from the accumulator **106**.

In some embodiments, pressure sensor **194** may provide a signal that is proportional to the amount of positive or negative pressure applied to a sensing surface. The amount of the pressure change detected by pressure sensor **194** may be used to refine the amount of oxygen enriched gas being provided to the user. For example, if a large negative pressure change is detected by pressure sensor **194**, the volume of oxygen enriched gas provided to the user may be increased to take into account the increased volume of gas being inhaled by the user. If a smaller negative pressure is detected, the volume of oxygen enriched gas provided to the user may be decreased to take into account the decreased volume of gas being inhaled by the user. A positive change in the pressure indicates an exhalation by the user and is generally a time that release of oxygen enriched gas is discontinued. Generally while a positive pressure change is sensed, valve **160** remains closed until the next onset of inhalation.

In some embodiments, the sensitivity of the pressure sensor **194** may be affected by the physical distance of the pressure sensor **194** from the user, especially if the pressure sensor is located in oxygen concentrator system **100** and the pressure difference is detected through the tubing coupling the oxygen concentrator system to the user. In some embodiments, the pressure sensor may be placed in the airway delivery device used to provide the oxygen enriched gas to the user. A signal from the pressure sensor may be provided to controller **400** in the oxygen concentrator **100** electronically via a wire or through telemetry such as through BLUETOOTH® (Bluetooth, SIG, Inc. Kirkland, Washington) or other wireless technology.

In an embodiment, the user's inhalation may be detected by using flow rate sensor **185**. In use, a conduit for providing oxygen enriched gas is coupled to a user's nose and/or mouth (e.g., using a nasal cannula or face mask). At the onset of an inhalation, the user begins to draw

air into their body through the nose and/or mouth. As the air is drawn in, an increase in flow of gas passing through conduit is created. Flow rate sensor **185** may be operable to create a signal when an increase in flow rate is detected, to signal the onset of inhalation. Upon detection of the onset of inhalation, supply valve **160** is controlled to release a bolus of oxygen enriched gas from the accumulator **106**.

A user breathing at a rate of 30 breaths per minute (BPM) during an active state (e.g., walking, exercising, etc.) may consume two and one-half times as much oxygen as a user who is breathing at 12 BPM during a sedentary state (e.g., asleep, sitting, etc.). Pressure sensor **194** and/or flow rate sensor **185** may be used to determine the breathing rate of the user. Controller **400** may process information received from pressure sensor **194** and/or flow rate sensor **185** and determine a breathing rate based on the frequency of the onset of inhalation. The detected breathing rate of the user may be used to adjust the bolus of oxygen enriched gas. The volume of the bolus of oxygen enriched gas may be increased as the users breathing rate increase, and may be decreased as the users breathing rate decreases. Controller **400** may automatically adjust the bolus based on the detected activity state of the user. Alternatively, the user may manually indicate a respective active or sedentary mode by selecting the appropriate option on the control panel of the oxygen concentrator. Alternatively, a user may operate controller **400** from a remote electronic device. For example, a user may operate the controller using a smart phone or tablet device.

In some embodiments, if the user's current activity level as assessed using the detected user's breathing rate exceeds a predetermined threshold, controller **400** may implement an alarm (e.g., visual and/or audio) to warn the user that the current breathing rate is exceeding the delivery capacity of the oxygen concentrator system. For example, the threshold may be set at 20 breaths per minute.

Methods of determining the breathing rate of a user typically count the number of breathes taken by the user over a pre-determined time and calculate the breathing rate. When determining the breathing rate of a user, all breaths measured during the pre-determined time period are typically used to calculate the breathing rate. Such a method, however, can lead to significant errors due to sudden changes in the breathing rate of the user. For example, while sleeping it is known that the times between breaths may vary greatly for an individual. Breathing patterns normally change during sleep. During deep sleep, breathing slows and becomes lighter as the body rests. During light sleep and REM, breathing can resemble breathing patterns of the person when awake. Periods of heavy breathing may also occur during dreams. Changes in breathing rate can occur quickly while a user is sleeping and even during awake periods. If the delivery of oxygen enriched gas is not adapted to the breathing patterns of the user properly,

oxygen enriched gas may be wasted, by providing the oxygen enriched gas for too long, or may be insufficient, if the oxygen enriched gas is provided for too short a period.

Attempts have been made to take into account the erratic breathing of a user. For example, U.S. Patent No. 7,841,343 to Deane et al. ("Deane") described the use of a blind time to help compensate for erratic breathing. Specifically, Deane teaches that after a bolus of oxygen enriched gas is delivered to a user, a controller enters a blind time. During this blind time the controller will not accept any triggers to deliver oxygen enriched gas. This time may range from 0.5 to 3 seconds after the bolus is delivered. After this blind time has elapsed the controller sets the inspiration breath pressure threshold to a low level and gradually increases the sensitivity until a breath is detected. According to Deane, this helps to vary the bolus delivery in response to changes in the users breathing.

The method of Deane relies on a blind time in which no breaths are detected. Thus, if the user starts breathing rapidly, shortly after the delivery of a bolus of oxygen enriched gas, the method of Deane may be delayed in reacting to the change in breathing. In the worst case scenario, the user may change to a breathing rate in which every other breath falls within the blind time, leading to the false indication that the user is breathing at a breathing rate that is half the actual breathing rate. Such a situation can lead to oxygen depravity in the individual due to an insufficient amount of oxygen being supplied to the user.

Applicant has devised an improved method of determining a breathing rate, and controlling the inspiration breath pressure threshold based on the determined breathings. In an embodiment, the controller determines the breathing rate based on measuring a predetermined number of breaths (at least three) and discarding information related to the last breath measured. In this method the time between the penultimate breath and the last breath is not used to determine the average breathing rate. The breathing rate, determined using the information collected from the remaining breaths, was found to give a more accurate indication of the current breathing rate of the user. Such a method also provides a way to take into account erratic breathing patterns without having to resort to the extreme measure of creating artificial "blind times," as discussed in Deane.

Over a period of time, controller **400** may collect and store the number of breaths. Based on the number of breaths, or the average time between breaths, over the period of time a breathing rate may be calculated. In some embodiments, the period of time is divided into equal time units. The number of breaths, or the average time between breaths, is determined in each time unit for the set period of time. The number of breaths, or average time between breaths, per time unit is used to determine a breathing rate. In some embodiments, the breathing rate in the last time unit is not used to determine if the delivery parameters should be changed. For

example, if a period of time is broken up into 5 equal time units, the breathing rate determined for the last time unit is not used to determine an average breathing rate (for example, average breaths per minute).

For example, controller **400** may collect the number of breaths over a 5 minute period of time. During the 5 minutes, a user may have a breathing rate of 15 breaths per minute (“BPM”) for the first minute of the 5 minute time period, 10 BPM during the second minute of the 5 minute time period, 25 BPM during the third minute of the 5 minute time period, 30 BPM during the fourth minute of the 5 minute time period, and 40 BPM during the fifth minute of the 5 minute time period. The 40 BPM may be ignored and the remaining breaths averaged (for example, to determine an average breathing rate of 20 BPM. The breathing rate determined during the last minute of the 5 minute time period may be used for averaging of the next 5 minute time period. For example the last minute of the 5 minute time period may be used as the first minute of the next five minute time period. Alternatively, the five minute time period analyzed may be shifted by a minute. In this case, the second minute of the five minute period just analyzed becomes the first minute of the next five minute period. The fifth minute (ignored in the first breathing rate analysis), becomes the fourth minute of the next breathing rate analysis. In either case the last minute is ignored in the breathing rate analysis.

In another embodiment, the breathing rate may be determined by monitoring the time between each breath for at least three breaths. In some embodiments, the times between each of four, five, six, seven, eight, nine, ten, fifteen, sixteen, seventeen, or twenty successive breaths are measured and used to determine an average breathing rate. In this method the time between the penultimate breath and the last breath is ignored, with the breathing rate based on the time between the breaths up to the penultimate breath. For example, if 5 successive breaths are used to determine a breathing rate, the time between the 4th and 5th breath is discarded when determining the breathing rate. For example if the following times between breaths are obtained: 1st-2nd: 4.5 sec., 2nd-3rd: 4.7 sec, 3rd-4th – 4.2 sec, 4th -5th: 5.2 sec, the average time between breaths is determined by averaging the first three times (4.5 sec, 4.7 sec, and 4.2 sec) and ignoring the last breath (5.2 sec). In this manner the average time between breaths is 4.47, giving an average breathing rate of 13.4 breathes per minute.

Using the average breathing rate, the inspiration breath pressure threshold may be adjusted relative to the current inspiration breath pressure threshold. Controller **400** may determine that the average breathing rate has changed from less than 15 breaths per minute to greater than 15 breaths per minute. Controller **400** may send an electronic signal to pressure sensor **194** that raises the threshold breath pressure inspiration relative to the current inspiration breath pressure threshold. When the determined average breathing rate changes from greater

than 10 breaths per minute to less than 10 breaths per minute, controller **400** may send an electronic signal to the pressure sensor **194** that lowers the inspiration breath pressure threshold relative to the current inspiration breath pressure threshold. Controller **400** may determine that the average breathing rate is between 10 breaths per minute and 15 breaths per minute, and
 5 determine that no change in the current inspiration breath pressure threshold is necessary. If the average breathing rate is less than 5 breaths per minute then controller **400** may trigger an alarm. If the inspiration breath pressure threshold has been lowered relative to the current inspiration breath pressure threshold and no inspiration breath pressure is detected after a period of time (for example, 75 seconds), then controller **400** may trigger an alarm.

10 In another embodiment, the change in the inspiration breath pressure threshold may be adjusted by looking at the change in breathing rate over a predetermined period of time. For example, a change in breathing rate can be monitored by creating successive groupings of three or more breaths. For each successive grouping of three or more breaths, the breathing rate is determined (e.g., by calculating the breathing rate based on an average time between each breath
 15 in the grouping). The breathing rate from each grouping is compared to the next grouping to determine how the breathing rate is changing. If the breathing rate is increasing over three or more successive groupings (e.g., the breathing rate increases in at least two of the groupings), the controller may increase the inspiration breath pressure threshold. If the breathing rate is decreasing over three or more successive groupings (e.g., the breathing rate decreases in at least
 20 two of the groupings), the controller may lower the inspiration breath pressure threshold.

In a specific example, the time between each of seventeen successive breaths is measured. The breaths are then divided into four groupings, with each grouping having the inhalation times for four successive breaths. The groupings would then look as shown below, the number in parenthesis refers to the time between the breaths:

1 (5.8s) 2 (5.0s) 3 (4.2s) 4	BPM = 12
(4.0s) 5 (3.5s) 6 (3.5s) 7 (3.0s) 8	BPM = 17
(3.0s) 9 (3.4s) 10 (3.6s) 11 (3.5s) 12	BPM = 18
(2.6s) 13 (2.6s) 14 (2.4s) 15 (2.0s) 16	BPM = 25
(2.7s) 17	

The last time (the time between breath 16 and 17, is not used to determine the breathing rate. In the above example, the first grouping (breaths 1-4) exhibits a breathing rate of 12 BPM. The second grouping exhibits a breathing rate of 17 BPM, which shows that the subjects breathing rate is increasing. Instead of changing the inspiration breath pressure threshold, the controller
 35 goes into a “watch” mode. In the “watch” mode the controller is alerted that a change in the

inspiration breath pressure threshold may be needed. The controller then looks at the third grouping. The third grouping exhibits a breathing rate of 18 BPM. A breathing rate that is within +/- 2 of the previous breathing rate, is not considered to have changed. Since the breathing rate has not changed (as defined above) from the second grouping to the third grouping, the controller remains in watch mode. The controller then looks at the change between the third and fourth groupings. The fourth grouping exhibits a breathing rate of 25 BPM. Since the controller has now seen a second increase among the four groupings measured, the controller increase the inspiration breath pressure threshold. The controller will continue to take additional groupings (in this example, of four successive breaths, excluding the last breath taken) and continue to evaluate whether the inspiration breath pressure threshold should be adjusted.

In some embodiments, rather than ignoring the last breath, the last grouping is ignored. For example, in the above example, the controller bases the decision to change the inspiration breath pressure threshold based on the first three groupings, ignoring the last (4th) grouping. Under these circumstances, the inspiration breath pressure threshold is not changed until additional groupings are taken and it is determined if the increase in breathing rate is continued.

In alternate embodiments, the controller may base decisions on the actual BPM rather than the change in BPM. For example, if the BPM changes to less than 10 breaths per minute in a grouping, the controller may go into a watch mode. If the BPM remains below 10 BPM in one of the next two groupings, the controller may send an electronic signal to the pressure sensor that lowers the inspiration breath pressure threshold relative to the current inspiration breath pressure threshold. If the BPM is between 10 breaths per minute and 15 breaths per minute, then no change is made to the inspiration breath pressure threshold. If the BPM changes to more than 15 breaths per minute in a grouping, the controller may go into a watch mode. If the BPM remains above 15 BPM in one of the next two groupings, the controller may send an electronic signal to the pressure sensor that increase the inspiration breath pressure threshold relative to the current inspiration breath pressure threshold. In this embodiment, as discussed above, the last breath detected or the last grouping measured may be ignored when determining if the inspiration breath pressure threshold should be changed.

In some embodiments, it is not necessary to calculate the breathing rate, but instead the time between breaths may be used in a decision making process. A flow chart of a process of adjusting the inspiration breath pressure threshold is shown in FIG. 10. During use, the times between at least three consecutive breaths is measured. When the time between, for example, the fourth breath and the fifth breath is measured, the controller determines if a change in the inspiration breath pressure threshold is needed. The times between breaths 1 and 2; 2 and 3; and 3 and 4 are used to determine the average time between breaths. The time between breath 4 and

breath 5 is not used to determine the average time between breaths. The average time between breaths 1-4 is then compared to predetermined values. In one embodiment, the subject is considered to be in an active state if the average time between breaths is less than 4 seconds. It should be understood that other times can be used. Thus process therefore includes comparing the average time between breaths of the subject to the predetermined active state time. If the average time between breaths of the subject is less than the active state time, the controller sets the inspiration breath pressure threshold to a high pressure.

If the average time between breaths of the subject is greater than the active state time, the controller compares the time to an inactive state time. In one embodiment, the subject is considered to be in an inactive state if the average time between breaths is greater than 6 seconds. It should be understood that other times can be used. If the average time between breaths of the subject is greater than 6 seconds, the controller sets the inspiration breath pressure threshold to a low pressure. If the average time between breaths of the subject is between 4 and 6 seconds, the controller does not change the inspiration breath pressure threshold.

As shown in FIG. 10, when the breath 6 is taken, the process is repeated, however, the average is now based on the times between breath 2 and breath 5. Once the average time between breaths 2-5 is determined, the same process as discussed above is used to determine whether the inspiration breath pressure threshold should be changed, and, if it should be changed, whether it should be set to a high pressure (active) or a low pressure (inactive). This process may be continued as long as oxygen is being provided to the user.

In some embodiments, controller **400** may send a signal to adjust pressure sensor **194** to adjust the threshold inspiration breath pressure based on the ratio of the change in absolute pressure with respect to time monitored over at least three breaths. In some embodiments, the change in absolute pressure with respect to time between each of four, five, six, seven, eight, nine, ten, fifteen or twenty successive breaths are measured and used to determine a ratio of change in absolute pressure with respect to time. Controller **400** may determine a ratio of the change in absolute pressure with respect to time based during a breathing period and store the information in a non-transitory medium. Based on the determined ratio between the change in absolute pressure with respect to time, controller **400** may send an electronic signal to breath pressure sensor **194** that adjusts the inspiration breath pressure threshold. If ratio is assessed to be negative, and less than, or equal to, -0.5 controller **400** may send an electronic signal to breath pressure sensor **194** that lowers the inspiration breath pressure threshold relative to the current inspiration breath pressure threshold. For example, if the ratio is assessed to be about -1.5 to about -0.5, (i.e., less than or equal to -0.5), controller **400** may send an electronic signal to breath pressure sensor **194** that lowers the inspiration breath pressure threshold relative to the

current inspiration breath pressure threshold. If the ratio is assessed to be slightly positive or slightly negative (e.g., between -0.5 to +0.5), controller **400** may send an electronic signal to breath pressure sensor **194** that keeps the inspiration breath pressure threshold the same as the current inspiration breath pressure threshold. If the ratio is positive, and, for example, greater than or equal to +0.5, for example, controller **400** may send an electronic signal to breath pressure sensor **194** that raises the inspiration breath pressure threshold relative to the current inspiration breath pressure threshold.

In some embodiments, controller **400** may operate the oxygen concentrator based on the change in the inspiration breath pressure threshold. The frequency and/or duration of the provided oxygen enriched gas to the user relative to the current frequency and/or duration may be adjusted based on the change in the inspiration breath pressure threshold. Upon determining that the inspiration breath pressure threshold has been lowered, the controller **400** may switch the oxygen concentrator to a sedentary mode. Controller **400** may switch the oxygen concentrator to an active mode, when the inspiration breath pressure threshold has been raised.

In some embodiments, as seen in FIG. 9, the bolus of provided oxygen enriched gas may include two or more pulses. For example, with a one liter per minute (LPM) delivery rate, the bolus may include two pulses: a first pulse **556** at approximately 7 cubic centimeters and a second pulse **558** at approximately 3 cubic centimeters. Other delivery rates, pulse sizes, and number of pulses are also contemplated. For example, at 2 LPMs, the first pulse may be approximately 14 cubic centimeters and a second pulse may be approximately 6 cubic centimeters and at 3 LPMs, the first pulse may be approximately 21 cubic centimeters and a second pulse may be approximately 9 cubic centimeters. In some embodiments, the larger pulse **556** may be provided when the onset of inhalation is detected (e.g., detected by pressure sensor **194**). In some embodiments, the pulses may be provided when the onset of inhalation is detected and/or may be spread time-wise evenly through the breath. In some embodiments, the pulses may be stair-stepped through the duration of the breath. In some embodiments, the pulses may be distributed in a different pattern. Additional pulses may also be used (e.g., 3, 4, 5, etc. pulses per breath). While the first pulse **556** is shown to be approximately twice the second pulse **558**, in some embodiments, the second pulse **558** may be larger than the first pulse **556**. In some embodiments, pulse size and length may be controlled by, for example, supply valve **160** which may open and close in a timed sequence to provide the pulses. A bolus with multiple pulses may have a smaller impact on a user than a bolus with a single pulse. The multiple pulses may also result in less drying of a user's nasal passages and less blood oxygen desaturation. The multiple pulses may also result in less oxygen waste.

In some embodiments, the sensitivity of the oxygen concentrator **100** may be selectively attenuated to reduce false inhalation detections due to movement of air from a different source (e.g., movement of ambient air). For example, the oxygen concentrator **100** may have two selectable modes – an active mode and an inactive mode. In some embodiments, the user may manually select a mode (e.g., through a switch or user interface). In some embodiments, the mode may be automatically selected by the oxygen concentrator **100** based on a detected breathing rate. For example, the oxygen concentrator **100** may use the pressure sensor **194** to detect a breathing rate of the user. If the breathing rate is above a threshold, the oxygen concentrator **100** may operate in an active mode (otherwise, the oxygen concentrator may operate in an inactive mode). Other modes and thresholds are also contemplated.

In some embodiments, in active mode, the sensitivity of the pressure sensor **194** may be mechanically, electronically, or programmatically attenuated. For example, during active mode, controller **400** may look for a greater pressure difference to indicate the start of a user breath (e.g., an elevated threshold may be compared to the detected pressure difference to determine if the bolus of oxygen should be released). In some embodiments, the pressure sensor **194** may be mechanically altered to be less sensitive to pressure differences. In some embodiments, an electronic signal from the pressure sensor may be electronically altered to ignore small pressure differences. This can be useful when in active mode. In some embodiments, during the inactive mode the sensitivity of the pressure sensor may be increased. For example, the controller **400** may look for a smaller pressure difference to indicate the start of a user breath (e.g., a smaller threshold may be compared to the detected pressure difference to determine if the bolus of oxygen should be released). In some embodiments, with increased sensitivity, the response time for providing the bolus of oxygen during the user's inhalation may be reduced. The increased sensitivity and smaller response time may reduce the size of the bolus necessary for a given flow rate equivalence. The reduced bolus size may also reduce the size and power consumption of the oxygen concentrator **100**.

Providing a Bolus Based on Inhalation Profile

In an embodiment, the bolus profile can be designed to match the profile of a particular user. To do so, an inhalation profile may be generated based on information gathered from pressure sensor **194** and flow rate sensor **185**. An inhalation profile is assessed based on, one or more of the following parameters: the breathing rate of the user; the inhalation volume of the user; the exhalation volume of the user; the inhalation flow rate of the user; and the exhalation flow rate of the user. The breathing rate of the user may be assessed by detecting the onset of inhalation using pressure sensor **194** or flow rate sensor **185** as previously discussed. Inhalation

volume may be assessed by measuring the change in pressure during inhalation and calculating or empirically assessing the inhalation volume based on the change in pressure. Alternatively, inhalation volume may be assessed by measuring the flow rate during inhalation and calculating or empirically assessing the inhalation volume based on the flow rate and the length of the

5 inhalation. Exhalation volume may be assessed in a similar manner using either positive pressure changes during exhalation, or flow rate and exhalation time. Inhalation flow rate of the user is measured from shortly after the onset of inhalation. Detection of the end of inhalation may be from the pressure sensor or the flow rate sensor. When onset of inhalation is detected by the pressure sensor, the onset is characterized by a drop in pressure. When the pressure begins to
10 increase, the inhalation is considered complete. When onset of inhalation is detected by the flow rate sensor, the onset is characterized by an increase in the flow rate. When the flow rate begins to decrease, the inhalation is considered complete.

There is a minimum amount of oxygen necessary for a person to remain conscious. A person who is breathing rapidly is bringing in a lower volume of air in each breath, and thus,
15 requires less oxygen enriched gas per inhalation. While there is some variation from patient to patient, this relationship can be used to establish the mean flow rate for each breath mathematically. By measuring a large population of patients, the profile of the relative flow from onset of inhalation to the onset of exhalation may be established. Using this flow profile as a template, the calculated actual flow based on breathing rate can be adjusted mathematically to a
20 calculated actual flow profile. This profile can be used to adjust the opening and closing of the delivery valve to create an idealized profile for the patient based on their breathing rate. Inhalation profile data gathered from a population of users may be used to create an algorithm that makes the appropriate adjustments based on the detected inhalation profile. Alternatively, a look up table may be used to control valve actuation durations and pulse quantities based on a
25 detected inhalation profile.

Measuring the inhalation profile of the patient provides a more accurate basis for control of the bolus of oxygen enriched gas being provided to the patient. For example, basing the delivery of oxygen enriched gas on the onset of inhalation may not take into account differences between individual users. For example, people having a similar breathing rate can have different
30 inhalation/exhalation volume, inhalation/exhalation flow rates and, thus, different bolus requirements necessary to produce the prescribed amount of oxygen. In one embodiment, an inhalation profile is created based on the flow rate of air during inhalation and the duration of inhalation. The inhalation profile can then be used as a predictor of the volume of air taken in by a specific user during inhalation. Thus, inhalation profile information can be used to modify the
35 amount of oxygen enriched air provided to the user to ensure that the prescribed level of oxygen

is received. The amount of oxygen provided to a user may be adjusted by modifying the frequency and or duration of release of oxygen enriched gas from the accumulator with supply valve **160**. By tracking the inhalation profile of the patient controller adjusts the delivery supply valve actuation to idealize the bolus profile to provide the oxygen at the maximum rate without causing wasteful retrograde flow.

Automatic Delivery of Oxygen Enriched Gas Based on Average Breathing Rate

It is important for patients to continually receive the necessary oxygen treatment. In some cases, however, the detection of breath can become difficult. Some patients, especially when resting or sleeping, may switch from nose breathing to mouth breathing, making it difficult to determine when a breath is being taken if the pressure sensor is in the nasal cannula. It has been found, however, that even if the patient has switched from nose breathing to mouth breathing, it can still be beneficial to deliver oxygen to the nasal region of the patient. Having an increased concentration of oxygen in the nasal region of the patient allows some oxygen to be taken in by the patient through the nose, since mouth breathing typically does not totally exclude some air from entering the nasal passages. It is therefore important to have an algorithm for having the oxygen concentrator deliver oxygen to the patient, even when no breathing is detected. Such an algorithm, however, needs to be designed to conserve the oxygen enriched gas produced by the oxygen concentrator by not delivering oxygen when no necessary.

In an embodiment, the automatic delivery of oxygen enriched gas from an oxygen concentrator is based on an average breathing rate of the patient, measured as either breath per minute ("bpm") or time between breaths. In an embodiment, the time between a plurality of successive breaths is measured. A breath is determined to begin when a drop in pressure is measured using a pressure sensor coupled to an outlet of a conduit coupling the user to an oxygen enriched gas source. The average time between each of the successive breaths is determined or the average bpm is determined. The time between the penultimate breath and the last breath, however, is not used to determine the average time, for the same reasons discussed previously in the application.

An inspiration breath pressure threshold for the pressure sensor is set based on the determined average time. The breath pressure threshold is set to an active mode breath pressure threshold if the average time is less than a predefined time. The breath pressure threshold is set to a sleep mode breath pressure threshold if the average time is greater than a predefined time. In some embodiments, the predefined time is a time between about 6 sec. and about 12 sec., with 8 sec. being the preferred time for most patients. The sleep mode breath pressure threshold is

lower than the active mode breath pressure threshold so that the pressure sensor is more likely to pick up breaths taken by the patient in sleep mode.

Sleep mode can be also be entered be measuring the time since the penultimate breath. In such an embodiment, two timers are used, an even timer and an odd timer. When an odd breath is taken (breath 1st, 3rd, 5th, etc.) then the odd time is reset to a time equal to the maximum time expected for two breaths to be taken. In some embodiments, the maximum time for two breaths to be taken is set in the range from about 25 sec. to about 35 sec., with 30 sec. being preferred. In other embodiments, the maximum time for two breaths is continually determined as two times the average time determined from the patient's breathing pattern. When an even breath is taken (2nd, 4th, 6th, etc.), the even timer is set to a time equal to the maximum time expected for two breaths. If either timer reaches the maximum time, the breath pressure threshold is set to a sleep mode breath pressure threshold. Setting to a sleep mode breath pressure threshold will improve the chances of detecting a breath in the case that the patient has changed from active activity to reduced activity.

Once in sleep mode, the times are continually monitored and compared to the determined average time determined between breaths. In an embodiment, the time elapsed according to the odd timer and the time elapsed according to the even timer are added together and compared to a function of the determined average breathing time. In one embodiment, if the sum of the elapsed times is greater than a constant times the determined average breathing time, then the oxygen concentrator will automatically provide oxygen enriched gas to the user. In some embodiments, the constant is between about 1.5 and 2.5, with a constant of 2.0 being preferred.

During automatic delivery of oxygen enriched gas, the oxygen enriched gas is delivered every 3-4 seconds until breaths are once again detected. During automatic delivery of oxygen enriched gas, the time between each automatic delivery of a bolus of oxygen is varied randomly between 3-4 seconds. Alternately, the time is varied by a constant amount cycling between 3-4 seconds. For example, the time between each delivery of oxygen enriched gas may begin at 3 seconds, then after one or more breaths are delivered the delay time for each breath may be changed to 3.1, then 3.2, etc. until a delay time of 4 seconds is reached. Once the 4 second mark is reached, the time may be reduced in the same manner (4.0, then 3.9, then 3.8, etc.) until the 3 second mark is reached. This pattern may be continued until detectable breathing is resumed by the patient.

The above method may be implemented by a processor operably coupled to the pressure sensor. The processor executes non-transitory program instructions which allow the processor to implement the method. In an embodiment, the method is implemented using three timers. Timer_1 measures the time since an odd numbered breath. Timer_2 measures the time since an

even numbered breath. Timer_3 measures the time between each breath and is reset when a breath is detected or a false breath is registered. The method relies on a sampling routine which continually monitors the timers and adjusts the parameters based on the timers and the average breath times.

- 5 When the oxygen concentrator apparatus is turned on, the system is initialized. The initialization routine is set forth below:

Initialize System

- 10 Timer_1 = MAX_BREATH_TIME
 Timer_2 = TWO_BREATH_TIME
 Breath_Index = 0
 Breath_Register[1...5] = 8 sec
 Average_Breath_Rate = [SUM (Breath_Register [2...5])/4

 15 Timer_1 is the odd timer;

MAX_BREATH_TIME is a constant that is set at the maximum time allowed between breaths (e.g. 15 sec.);

- 20 Timer_2 is the even timer

TWO_BREATH_TIME is a constant that is set at the maximum time allowed for two breaths (e.g. 30 sec.);

- 25 Breath_Index is a variable used to count the number of breaths

- 30 Breath_Register[1...5] is an array of 5 memory locations used to store the time between 6 successive breaths. Breath_Register[5] stores the time elapsed between the 1st breath taken in a series of 6 successive breaths to the 2nd breath taken in the series. Breath_Register[4] stores the time elapsed from the 2nd breath to the 3rd breath. Breath_Register[3] stores the time elapsed from the 3rd breath to the 4th breath. Breath_Register[2] stores the time elapsed from the 4th breath to the 5th breath. Breath_Register[1] stores the time elapsed from the 5th breath (the penultimate breath) to the 6th breath (the last breath detected).

- 35 Average_Breath_Rate is determined by calculating the average of the times in Breath_Registers [2-5]. Breath_Register[1] is not used to calculate the average breath time (or rate).

After initialization, the Sampling Routine continually monitors the pressure sensor for the detection of a breath. The Sampling Routine also continually monitors the Timer_1 and Timer_2

looking for the timer to time out. The current implementation sets each timer to the maximum time allowed and runs the timer backward toward zero. In such an implementation, when a timer reaches zero, the timer is considered to have “timed out.” It should be understood, however that the timers can also be implemented in a forward direction with minimal changes to the programming. The Sampling Routine is set forth below:

Sampling Routine (every 1 msec)

Average Breath Rate > SLEEP_BREATH_TIME; Y- Go to Sleep Mode; N –Go to Active Mode
Breath Detected = Y – Go to Active Breath Detection Routine or Sleep Breath Detection Routine

10 Timer_1 == 0; Y – Go to Active No Breath Detection Routine or Sleep No Breath Detection Routine
Timer_2 == 0; Y – Go to Active No Breath Detection Routine or Sleep No Breath Detection Routine

15 SLEEP_BREATH_TIME is a constant that is set between at a time between about 8 sec. and about 12 sec.

Based on the results of the Sampling Routine, the appropriate action routine is accessed. The action routines include: Active Breath Detection Routine; Sleep Breath Detection Routine; Active No Breath Detection Routine; and Sleep No Breath Detection Routine. Each of these routines are set forth below:

Active Mode Breath Detection Routine

Shift Breath-Registers – Add new time to Breath_Register[1]

Breath_Index = Breath_Index + 1

If Breath_Index is odd; Breath_Register[1] = (MAX_BREATH_TIME - Timer_2)

25 If Breath_Index is even; Breath_Register[1] = (MAX_BREATH_TIME - Timer_1)

Average_Breath_Rate = [SUM (Breath_Register [2...5])/4

If Average_Breath_Rate > SLEEP_BREATH_TIME (10 sec) GOTO SLEEP MODE

If index is odd; Timer_1 = TWO_BREATH_TIME;

If index is even; Timer_2 = TWO_BREATH_TIME;

30

The Active Mode Breath Detection Routine is activated if a new breath is detected while the device is in active mode. This routine starts by shifting the Breath_Registers. This is done by overwriting each register with the value from the adjacent register. Thus, Breath_Register[5] is overwritten with the value from Breath_Register[4]; Breath_Register[4] is then overwritten by the value from Breath_Register[3], etc. The time from the last breath to the newly detected breath is placed in Breath_Register[1]. After the breaths are shifted, a new Average_Breath_Rate is determined. The new Average_Breath_Rate is then compared to the constant, SLEEP_BREATH_TIME. If Average_Breath_Rate (stored as an average time elapsed per breath) is greater than SLEEP_BREATH_TIME, the system will go into Sleep Mode by lowering the inspiration breath pressure threshold for the pressure sensor. Timer_1 or Timer_2 are reset,

40

depending on the value of the Breath_Index and the system goes back to the Sampling Routine until the next event is reached.

Active Mode No Breath Detected Routine

```

5  Shift Breath_Registers
   Index = Index + 1
   Breath_Register[1] = TWO_BREATH_TIME
   Average_Breath_Rate = [SUM (Breath_Register [2...5])]/4
   If Average_Breath_Rate > SLEEP_BREATH_TIME (10 sec) GOTO SLEEP MODE
10  If index is odd; Timer_1 = TWO_BREATH_TIME;
   If index is even; Timer_2 = TWO_BREATH_TIME;

```

If the system is in active mode, and no breath is detected, as indicated by one of the two timers timing out, the Breath_Registers are shifted and a “false breath” is added to Breath_Register[1].

```

15  The false breath added to the register is the constant TWO_BREATH_TIME which is selected
   from between 10 sec to 30 sec. with 15 sec. being typical. After the breaths are shifted, a new
   Average_Breath_Rate is determined. The new Average_Breath_Rate is then compared to the
   constant, SLEEP_BREATH_TIME. If Average_Breath_Rate (stored as an average time elapsed
   per breath) is greater than SLEEP_BREATH_TIME, the system will go into Sleep Mode by
20  lowering the inspiration breath pressure threshold for the pressure sensor. Timer_1 or Timer_2
   are reset, depending on the value of the Breath_Index and the system goes back to the Sampling
   Routine until the next event is reached.

```

```

   If the system is in Sleep Mode, the Sleep Mode routines are accessed. If a breath is detected
25  while in Sleep Mode, the Sleep Mode Breath Detection Routine is accessed.

```

Sleep Mode Breath Detection Routine

```

   Shift Breath-Registers
   Index = Index + 1
30  If Index is odd; Breath_Register[1] = (MAX_BREATH_TIME - Timer_2)
   If Index is even; Breath_Register[1] = (MAX_BREATH_TIME - Timer_1)
   Average_Breath_Rate = [SUM (Breath_Register [2...5])]/4
   If Average_Breath_Rate > SLEEP_BREATH_TIME (10 sec) GOTO ACTIVE MODE
   If index is odd; Timer_1 = TWO_BREATH_TIME;
35  If index is even; Timer_2 = TWO_BREATH_TIME;

```

```

   When a breath is detected in sleep mode, the routine is similar to the routine above for the active
   mode. The primary difference is that the Sleep Mode routine looks to see if the device needs to
   move back to active mode. Specifically, the Average_Breath_Rate is compared to the
40  SLEEP_BREATH_TIME. If the Average_Breath_Rate is greater than the

```

SLEEP_BREATH_TIME, the device will be set to Active Mode, otherwise the device remains in Sleep Mode.

Sleep Mode No Breath Detection Routine

- 5 Shift Breath-Registers
 Index = Index + 1
 Breath_Register[1] = TWO_BREATH_TIME
 Average_Breath_Rate = [SUM (Breath_Register [2...5])]/4
 If Timer_1 + Timer_2 > K_FACTOR * Average_Breath_Rate GOTO Automatic O₂ Delivery
 10 If index is odd; Timer_1 = TWO_BREATH_TIME;
 If index is even; Timer_2 = TWO_BREATH_TIME;

When no breath is detected before the timers time out, in sleep mode, the results are similar to when the timers time out in active mode. The primary difference is that the Sleep Mode routine
 15 looks to see if the device needs to initiate automatic delivery of oxygen enriched gas. Specifically, the elapsed time from Timer_1 and Timer_2 are added and compared to the Average_Breath_Rate * K_FACTOR. K_FACTOR is a constant usually selected from 1.5 to 2.5, with 2.0 being preferred. If the sum of Timer_1 and Timer_2 is greater than the Average_Breath_Rate * K_FACTOR, the device will begin to automatically deliver oxygen
 20 enriched gas to the user, in the manner described earlier. The Automatic O₂ Delivery Mode routine is set forth below:

Automatic O₂ Delivery Mode

- Deliver O₂ enriched gas every 3-4 sec. varying randomly or according to a predetermined pattern
 25 After each O₂ enriched gas deliver:
 If Timer_1 + Timer_2 > K_FACTOR * Average_Breath_Rate
 Yes – Stay in Auto-Dose mode
 No – Go back to Sleep mode; resume Sampling
 30 Automatic O₂ Delivery Mode is used to provide O₂ enriched gas at random or a varying predetermined intervals. After each delivery of O₂ enriched gas, the device monitors for the detection of a breath (signaled by a change in the time of either of Timer_1 or Timer_2) while waiting to deliver the next bolus of oxygen enriched gas.

In this manner, the changing of the operating parameters and the automatic delivery of
 35 oxygen enriched gas is controlled by the average breath rate, determined by ignoring the time between the penultimate and last breath. This method also avoids having to measure the time since the last breath to initiate changes in the system.

In this patent, certain U.S. patents, U.S. patent applications, and other materials (e.g., articles) have been incorporated by reference. The text of such U.S. patents, U.S. patent
 40 applications, and other materials is, however, only incorporated by reference to the extent that no

conflict exists between such text and the other statements and drawings set forth herein. In the event of such conflict, then any such conflicting text in such incorporated by reference U.S. patents, U.S. patent applications, and other materials is specifically not incorporated by reference in this patent.

5 Further modifications and alternative embodiments of various aspects of the invention may be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the invention. It is to be understood that the forms of the invention shown and described herein are to be taken as embodiments. Elements and
10 materials may be substituted for those illustrated and described herein, parts and processes may be reversed, and certain features of the invention may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of this description of the invention. Changes may be made in the elements described herein without departing from the spirit and scope of the invention as described in the following claims.

WHAT IS CLAIMED IS:

1. A method of providing oxygen enriched gas to a user of an oxygen concentrator, comprising:

5 measuring the time between a plurality of successive breaths, wherein a breath is determined to begin when a drop in pressure is measured using a pressure sensor coupled to an outlet of a conduit coupling the user to an oxygen enriched gas source;

10 determining an average time between each of the successive breaths, wherein the time between the penultimate breath and the last breath is not used to determine the average time;

15 setting an inspiration breath pressure threshold for the pressure sensor based on the determined average time, wherein the breath pressure threshold is set to an active mode breath pressure threshold if the average time is less than a predefined time, and wherein the breath pressure threshold is set to a sleep mode breath pressure threshold if the average time is greater than a predefined time, wherein the sleep mode breath pressure threshold is lower than the active mode breath pressure threshold;

20 measuring the time since the penultimate breath and the time since the last breath when in sleep mode; and

25 automatically providing oxygen enriched gas to the user if the sum of the time since the penultimate breath plus the time since the last breath is greater than a function of the determined average breathing time.

2. The method of claim 1, wherein the predefined time is between about 8 seconds and about 12 seconds.

30 3. The method of claim 1, wherein the function of the determined average breathing time is a constant times the determined average breathing time, wherein the constant is between 1.5 and 2.5.

4. The method of claim 1, further comprising measuring the time since the penultimate breath, wherein if two breaths are not received within a predetermined time, a false breath time is added to the successive breaths and the average calculated.
- 5 5. The method of claim 1, wherein the method comprises measuring the time between at least six successive breaths, wherein the time between the 5th breath and the 6th breath is not used to determine the average time.
6. The method of claim 1, wherein adjusting the inspiration breath pressure threshold based on
10 the average time is performed automatically.
7. The method of claim 1, wherein automatically providing oxygen enriched gas comprises delivering oxygen enriched gas to the user every 3 – 4 seconds.
- 15 8. The method of claim 7, wherein the time between each automatic delivery of oxygen enriched gas is varied randomly between 3-4 seconds.
9. The method of claim 7, the time between each automatic delivery of oxygen enriched gas is varied by a constant amount, cycling between 3-4 seconds.
20
10. The method of claim 1, wherein automatically providing oxygen enriched gas to the user is discontinued if a breath is detected from the user.
11. The method of claim 1, wherein the oxygen enriched gas source is an oxygen concentrator
25 system.
12. The method of claim 1, wherein the oxygen enriched gas source is an oxygen tank.
13. An oxygen concentrator apparatus, comprising:
30
a pressure sensor, the pressure sensor configured to detect a breath pressure of a user; and
a processor operable coupled to the pressure sensor, the processor to execute non-transitory program instructions, and wherein the program instructions are operable to
35 provide oxygen according to the method of any one of claims 1-12.

14. The oxygen concentrator apparatus of claim 13, further comprising an oxygen sensor coupled to the processor, wherein the oxygen sensor is capable of detecting oxygen in a gas during use.

5 15. The oxygen concentrator apparatus of claim 13, wherein the oxygen concentrator weighs less than 5 lbs.

16. The oxygen concentrator apparatus of claim 13, further comprising:

10 at least two canisters; and

gas separation adsorbent disposed in at least two canisters, wherein the gas separation adsorbent separates at least some nitrogen from air in the canister to produce oxygen enriched gas.

15

17. A method of providing oxygen enriched gas to a user of an oxygen concentrator, comprising:

measuring the time since a penultimate breath was taken, wherein a breath is determined to begin when a drop in pressure is measured using a pressure sensor coupled to an outlet of a conduit coupling the user to an oxygen enriched gas source; and

20

automatically providing oxygen enriched gas to the user if the time since the penultimate breath was taken is greater than a predetermined time.

25 18. The method of claim 17, wherein the predefined time is between about 10 seconds and about 30 seconds.

19. The method of claim 17, wherein automatically providing oxygen enriched gas comprises delivering oxygen enriched gas to the user every 3 – 4 seconds.

30

20. The method of claim 17, wherein the time between each automatic delivery of oxygen enriched gas is varied randomly between 3-4 seconds.

21. The method of claim 17, the time between each automatic delivery of oxygen enriched gas is varied by a constant amount, cycling between 3-4 seconds.

35

22. The method of claim 17, wherein automatically providing oxygen enriched gas to the user is discontinued if a breath is detected from the user.

23. The method of claim 17, wherein the oxygen enriched gas source is an oxygen concentrator system.

24. The method of claim 17, wherein the oxygen enriched gas source is an oxygen tank.

25. An oxygen concentrator apparatus, comprising:

a pressure sensor, the pressure sensor configured to detect a breath pressure of a user; and

a processor operable coupled to the pressure sensor, the processor to execute non-transitory program instructions, and wherein the program instructions are operable to provide oxygen according to the method of any one of claims 17-24:

measure the time since a penultimate breath was taken, wherein a breath is determined to begin when a drop in pressure is measured using a pressure sensor coupled to an outlet of a conduit coupling the user to an oxygen enriched gas source; and

automatically provide oxygen enriched gas to the user if the time since the penultimate breath was taken is greater than a predetermined time.

26. The oxygen concentrator apparatus of claim 25, wherein the predefined time is between about 10 seconds and about 30 seconds.

27. The oxygen concentrator apparatus of claim 25, wherein automatically providing oxygen enriched gas comprises delivering oxygen enriched gas to the user every 3 – 4 seconds.

28. The oxygen concentrator apparatus of claim 25, wherein the time between each automatic delivery of oxygen enriched gas is varied randomly between 3-4 seconds.

29. The oxygen concentrator apparatus of claim 25, the time between each automatic delivery of oxygen enriched gas is varied by a constant amount, cycling between 3-4 seconds.

30. The oxygen concentrator apparatus of claim 25, wherein automatically providing oxygen enriched gas to the user is discontinued if a breath is detected from the user.

1 / 8





FIG. 1



3 / 8




FIG. 3




FIG. 4

5 / 8




FIG. 5




FIG. 6

6 / 8




FIG. 7




FIG. 8

7 / 8




FIG. 9




FIG. 10

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 17/30748

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - A61M 15/00 (2017.01), A61M 16/00 (2017.01)

CPC - A61M16/107, A61M16/1055, A61M16/0063, A61M16/202, A61M2016/0027, A61M16/0816, A61M2230/42, A61M16/0666

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

See Search History Document

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

See Search History Document

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

See Search History Document

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2014/0137859 A1 (Wilkinson et al.), 22 May 2014 (22.05.2014), entire document, especially Abstract; Para [0019], [0091], [0107], [0110], [0113]-[0115]	1-30
Y	US 2005/0274381 A1 (Deane et al.), 15 December 2005 (12.12.2005), entire document, especially Abstract; Para [0023]-[0024], [0050], [0059]	1-30
Y	US 2009/0199855 A1 (Davenport et al.), 13 August 2009 (13.08.2009), entire document, especially Abstract; Para [0058]-[0060], [0141]-[0144]	7-9, 13-16/(7-9), 19, 21, 25-26/(19,21), 27, 28/(19,21), 29, 30/(19,21)
A	US 2009/0145428 A1 (Sward et al.), 11 June 2009 (11.06.2009), entire document	1-30
A	US 2006/0213519 A1 (Schmidt et al.), 28 September 2006 (28.09.2006), entire document	1-30

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

08 July 2017

Date of mailing of the international search report

04 AUG 2017

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-8300

Authorized officer:

Lee W. Young

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774