

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2017/027595 A1

(43) International Publication Date

16 February 2017 (16.02.2017)

WIPO | PCT

(51) International Patent Classification:

A63B 23/035 (2006.01) A61H 15/00 (2006.01)
A61H 1/00 (2006.01) A61H 7/00 (2006.01)

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:

PCT/US2016/046357

(22) International Filing Date:

10 August 2016 (10.08.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/203,033 10 August 2015 (10.08.2015) US
29/556,042 26 February 2016 (26.02.2016) US
15/231,455 8 August 2016 (08.08.2016) US

(71) Applicant: ROLL RECOVERY, LLC [US/US]; 1668 Valtec Lane, Ste. H, Boulder, CO 80301 (US).

(72) Inventor: NELSON, Jeremy, J.; 4656 Dapple Lane, Boulder, CO 80301 (US).

(74) Agent: MILES, Craig, R.; CR Miles P.C., 405 Mason Court, Suite 119, Fort Collins, CO 80524 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))
- of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: MASSAGE ROLLER

FIG. 2



(57) Abstract: Disclosed herein are embodiments of a massage roller, and methods of making and using such a massage roller, whereby the massage roller includes a massage roller body comprising a generally circular cross section, opposing first and second end portions, a convex medial portion, a first concave lateral portion axially extending between the first end portion and the convex medial portion, and a second concave lateral portion axially extending between the second end portion and the convex medial portion; wherein said massage roller body is asymmetric about a massage roller body vertical centerline.

WO 2017/027595 A1



Published:

— *with international search report (Art. 21(3))*

MASSAGE ROLLER

This International Patent Cooperation Treaty Patent Application is a continuation of United States Non-Provisional Patent Application No. No. 15/231,455, filed August 8, 2016, which is a continuation-in-part of United States Patent Application No. 29/556,042, filed 5 February 26, 2016, and claims the benefit of United States Provisional Patent Application No. 62/203,033, filed August 10, 2015, each hereby incorporated by reference herein.

I. DISCLOSURE OF THE INVENTION

A broad object of a particular embodiment of the invention can be to provide a massage roller, and methods of making and using such a massage roller, whereby the massage roller 10 includes a massage roller body comprising a generally circular cross section, opposing first and second end portions, a convex medial portion, a first concave lateral portion axially extending between the first end portion and the convex medial portion, and a second concave lateral portion axially extending between the second end portion and the convex medial portion; wherein said massage roller body is asymmetric about a massage roller body vertical centerline.

15 Naturally, further objects of the invention are disclosed throughout other areas of the specification, drawings, and claims.

II. BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an illustration of a method of using a particular embodiment of the massage roller to massage a massageable portion of a foot.

20 Figure 2 is a perspective view of a particular embodiment of the massage roller.

Figure 3 is a perspective view of a particular embodiment of the massage roller.

Figure 4 is a front view of the particular embodiment of the massage roller shown in Figure 2 and Figure 3.

25 Figure 5 is a rear view of the particular embodiment of the massage roller shown in Figure 2 and Figure 3.

Figure 6 is a top view of the particular embodiment of the massage roller shown in Figure 2 and Figure 3.

Figure 7 is a bottom view of the particular embodiment of the massage roller shown in Figure 2 and Figure 3.

Figure 8 is a first end view of the particular embodiment of the massage roller shown in Figure 2 and Figure 3.

5 Figure 9 is a second end view of the particular embodiment of the massage roller shown in Figure 2 and Figure 3.

Figure 10 is a cross-sectional view of the particular embodiment of the massage roller shown in Figure 7, whereby the massage roller is sectioned along a massage roller body horizontal axis.

10 Figure 11 is an enlarged view of a substantially linear recess of the particular embodiment of the massage roller shown in Figure 10.

Figure 12 is an enlarged view of a substantially circular recess of the particular embodiment of the massage roller shown in Figure 10.

15 Figure 13 is a cross-sectional view of the particular embodiment of the massage roller shown in Figure 6, whereby the massage roller is sectioned perpendicularly to a massage roller body horizontal axis.

Figure 14 is a perspective view of a particular embodiment of the massage roller formed from first and second pieces.

III. MODE(S) FOR CARRYING OUT THE INVENTION

20 Now referring primarily to Figure 1, which illustrates a method of using a particular embodiment of a massage roller (1) to massage a massageable portion (2) of a body (3), whereby the massage roller (1) includes a massage roller body (4) comprising a generally circular cross section, opposing first and second end portions (5)(6), a convex medial portion (7), a first concave lateral portion (8) axially extending between the first end portion (5) and the convex medial portion (7), and a second concave lateral portion (9) axially extending between the second end portion (6) and the convex medial portion (7), whereby the massage roller body (4) is asymmetric about a massage roller body vertical centerline (10) (as shown in the example of Figure 5). The method includes engaging the massageable portion (2) of the body (3) with an external surface

(11) of the massage roller body (4) and rolling the massage roller (1) to massage the massageable portion (2) of the body (3).

For the purposes of the present invention, the term “generally circular” means a closed shape defined by a line, whereby every point on the line is about the same distance from the center of the shape. As to particular embodiments, every point can be exactly the same distance from the center of the shape, thereby forming a perfectly round circular periphery. As to other particular embodiments, the closed shape can resemble a polygon, such as a pentagon, a hexagon, a heptagon, an octagon, and so forth and so on, which can be used in various permutations of the massage roller (1).

10 For purposes of the present invention, the term “convex” means outwardly extending or curving.

For purposes of the present invention, the term “concave” means inwardly extending or curving.

For the purposes of the present invention, the term “medial” means toward the middle.

15 For the purposes of the present invention, the term “lateral” means toward the side(s) or away from the middle.

20 For the purposes of the present invention, the term “vertical” means positioned up and down rather than from side to side, whereby “vertical” is not intended to be limiting, particularly as to the position, orientation, or use of the invention, but instead, is intended to provide a directional reference for the depiction of the massage roller (1) shown in the Figures to aid the reader’s understanding of the present invention.

25 For the purposes of the present invention, the term “horizontal” means positioned from side to side rather than up and down, whereby “horizontal” is not intended to be limiting, particularly as to the position, orientation, or use of the invention, but instead, is intended to provide a directional reference for the depiction of the massage roller (1) shown in the Figures to aid the reader’s understanding of the present invention.

30 Again referring primarily to Figure 1, as but one illustrative example, the massage roller (1) can be used to massage a massageable portion (2) of a foot (12), whereby the method can include engaging the massageable portion (2) of the foot (12) with the external surface (11) of the massage roller (1) and rolling the massage roller (1) to massage the massageable portion (2)

of the foot (11). As to particular embodiments, the massageable portion (2) of the foot (12) can engage with the external surface (11) of the massage roller (1) to dispose a foot longitudinal axis (13) in angled relation to a massage roller body horizontal axis (14) (such as generally orthogonal relation), whereby massaging can be achieved by rolling the massage roller (1) with the
5 massageable portion (2) of the foot (12) along the foot longitudinal axis (13) to rotate the massage roller (1) about a rotation axis (15) coincident with a massage roller body horizontal centerline (16).

Although the above-illustrated example includes using the massage roller (1) to massage a massageable portion (2) of a foot (12), the massage roller (1) is not limited to use for massaging
10 only a massageable portion (2) of a foot (12), as the massage roller (1) can be used to massage any massageable portion (2) of a body (3), depending upon the application.

Now referring primarily to Figure 2 and Figure 3, the massage roller (1) includes a massage roller body (4) comprising a generally circular cross section when sectioned perpendicularly to the massage roller body horizontal axis (14) (as shown in the example of
15 Figure 13).

As to particular embodiments, the massage roller body (4) can be substantially solid.

As to other particular embodiments, the massage roller body (4) can include a body wall (17) which defines a substantially hollow interior cavity (18) fillable with a gas (such as air), a liquid, or combinations thereof, depending upon the application (as shown in the example of
20 Figure 10). As to these embodiments, the substantially hollow interior cavity (18) can further include one or more supports (19) disposed therein, whereby the supports (19) can be configured to support the massage roller body (4) having the generally circular cross section, thereby maintaining the shape of the massage roller body (4).

As but one illustrative example, a particular embodiment of the massage roller (1) can
25 include a body wall (17) defining a substantially hollow interior cavity (18) having a plurality of supports (19) disposed therein and filled with only gas. Consequently, the substantially hollow interior cavity (18) of this particular embodiment is void of liquid.

The massage roller body (4) can be formed from any of a numerous and wide variety of materials sufficient to permit the massage roller (1) to, upon use, massage a massageable portion
30 (2) of a body (3). As to particular embodiments, the material, whether natural or synthetic, can be substantially rigid and may include, as non-limiting examples: metal, ceramic, plastic, wood,

or the like, or combinations thereof. As to other particular embodiments, the material, whether natural or synthetic, can be a resiliently elastic material which to an extent deforms upon engagement with the massageable portion (2) of the body (3), whereby these materials can include, as non-limiting examples: plasticized resin, rubber, silicone rubber, fluoropolymer, 5 polyurethane, or the like, or combinations thereof.

Now referring primarily to Figure 2 through Figure 9, the massage roller body (4) further includes opposing first and second end portions (5)(6) configured to engage with a support surface (20), whereby each of the first and second end portions (5)(6) can have a generally circular cross section, allowing the massage roller (1) to roll, or rotate about the rotation axis (15) 10 coincident with the massage roller body horizontal centerline (16), along the support surface (20). As to particular embodiments, the first and second end portions (5)(6) can include one or more grippable elements (not shown) which facilitate gripping the support surface (20) to preclude disengagement of the massage roller (1) from the support surface (20) when in use.

Now referring primarily to Figure 4 through Figure 7, each of the first and second end 15 portions (5)(6) can be convexly arcuate along corresponding end portion lengths (21) (as shown in the example of Figure 4).

Now referring primarily to Figure 2 through Figure 7, the massage roller body (4) further includes a convex medial portion (7) disposed between the first and second end portions (5)(6). Akin to the first and second end portions (5)(6), the convex medial portion (7) can be convexly 20 arcuate along a convex medial portion length (22) (as shown in the example of Figure 4).

Again referring primarily to Figure 2 through Figure 7, the convex medial portion (7) can have a convex medial portion maximum diameter (23) which is lesser than first and second end portion maximum diameters (24)(25) of the corresponding first and second end portions (5)(6) 25 (as shown in the example of Figure 5). As such, upon use of the massage roller (1), the convex medial portion (7) does not engage with the support surface (20), as only the first and second end portions (5)(6) engage with the support surface (20).

Again referring primarily to Figure 2 through Figure 7, the convex medial portion (7) provides an arcuate working surface (26), which can engage with corresponding curvature of a massageable portion (2) of the body (3). In relation to a planar working surface, the arcuate 30 working surface (26) can engage the corresponding curvature of the massageable portion (2) of the body (3) with greater uniformity, thereby providing a greater massage to the massageable portion (2) of the body (3). As but one illustrative example, the convex medial portion (7) can

provide a first arcuate working surface (27) configured as a substantially spherical working surface (as shown in the example of Figure 7), which may be useful for massaging a central longitudinal region of the sole of the foot (12), such as the central portion of the plantar fascia.

Again referring primarily to Figure 2 through Figure 7, the massage roller body (4) further 5 includes a first concave lateral portion (8) axially extending between the first end portion (5) and the convex medial portion (7). In contrast to the first and second end portions (5)(6) and the convex medial portion (7), the first concave lateral portion (8) can be concavely arcuate along a first concave lateral portion length (28) (as shown in the example of Figure 4).

As to particular embodiments, the first concave lateral portion (8) can be asymmetric 10 about a first concave lateral portion vertical centerline (29) (as shown in the example of Figure 6).

Now referring primarily to Figure 5, the first concave lateral portion (8) has a first concave lateral portion minimum diameter (30) which is lesser than the convex medial portion maximum diameter (23) and the first and second end portion maximum diameters (24)(25). As such, upon 15 use of the massage roller (1), the first concave lateral portion (8) does not engage with the support surface (20), as only the first and second end portions (5)(6) engage with the support surface (20).

Now referring primarily to Figure 2 through Figure 7, the first concave lateral portion (8) provides an arcuate working surface (26), which can engage with corresponding curvature of a massageable portion (2) of the body (3). In relation to a planar working surface, the arcuate 20 working surface (26) can engage the corresponding curvature of the massageable portion (2) of the body (3) with greater uniformity, thereby providing a greater massage to the massageable portion (2) of the body (3). As but one illustrative example, the first concave lateral portion (8) can provide a second arcuate working surface (31) (as shown in the example of Figure 7), which may be useful for massaging an inner longitudinal region of the sole of the foot (12), such as the 25 medial portion of the plantar fascia or the medial longitudinal arch.

Again referring primarily to Figure 2 through Figure 7, the massage roller body (4) further includes a second concave lateral portion (9) axially extending between the second end portion (6) and the convex medial portion (7). In contrast to the first and second end portions (5)(6) and the convex medial portion (7) and akin to the first concave lateral portion (8), the second concave 30 lateral portion (9) can be concavely arcuate along a second concave lateral portion length (32) (as shown in the example of Figure 4).

As to particular embodiments, the second concave lateral portion (9) can be asymmetric about a second concave lateral portion vertical centerline (33) (as shown in the example of Figure 6).

Now referring primarily to Figure 5, the second concave lateral portion (9) has a second concave lateral portion minimum diameter (34) which is lesser than the convex medial portion maximum diameter (23) and the first and second end portion maximum diameters (24)(25). As such, upon use of the massage roller (1), the second concave lateral portion (9) does not engage with the support surface (20), as only the first and second end portions (5)(6) engage with the support surface (20).

Now referring primarily to Figure 2 through Figure 7, the second concave lateral portion (9) provides an arcuate working surface (26), which can engage with corresponding curvature of a massageable portion (2) of the body (3). In relation to a planar working surface, the arcuate working surface (26) can engage the corresponding curvature of the massageable portion (2) of the body (3) with greater uniformity, thereby providing a greater massage to the massageable portion (2) of the body (3). As but one illustrative example, the second concave lateral portion (9) can provide a third arcuate working surface (35), which may be useful for massaging an outer longitudinal region of the sole of the foot (12), such as the lateral portion of the plantar fascia or the lateral longitudinal arch.

Now referring primarily to Figure 4, as to particular embodiments, the massage roller (1) can have the first concave lateral portion minimum diameter (30) configured to be greater than the second concave lateral portion minimum diameter (34). This particular configuration may be preferable for a massage roller (1) intended to be useful for simultaneously massaging a plurality of massageable portions (2) of a foot (3), whereby a medial plantar portion of the foot (12) downwardly extends a lesser distance from a transverse plane of the foot (12) in relation to a lateral plantar portion of the foot (12), which downwardly extends a greater distance from the transverse plane of the foot (12). Accordingly, when the massage roller (1) engages with a support surface (20), the first concave lateral portion (8), having a greater diameter, can abuttingly engage with the medial plantar portion, which downwardly extends a lesser distance from the transverse plane of the foot (12), while the second concave lateral portion (9), having a lesser diameter, abuttingly engages with the lateral plantar portion, which downwards extends a greater distance from the transverse plane of the foot (12), facilitating simultaneous massaging of both the medial and lateral plantar portions of the foot (12). Additionally, the convex medial portion (7) can

abuttingly engage with a central longitudinal region of the sole of the foot (12) for further simultaneous massaging.

Again referring primarily to Figure 4, as to particular embodiments, the massage roller (1) can have the first concave lateral portion length (28) configured to be lesser than the second 5 concave lateral portion length (32). This particular configuration may be preferable for a massage roller (1) intended to be useful for simultaneously massaging a plurality of massageable portions (2) of a foot (12), whereby a medial plantar portion of the foot (12) has a lesser width (along a foot latitudinal axis in perpendicular relation to the foot longitudinal axis (13)) in relation to a lateral plantar portion of the foot (12), which has a greater width (along the foot latitudinal axis). 10 Accordingly, when the massage roller (1) engages with a support surface (20), the first concave lateral portion (8), having a lesser length, can abuttingly engage with the medial plantar portion, which has a lesser width, while the second concave lateral portion (9), having a greater length, abuttingly engages with the lateral plantar portion, which has a greater width, facilitating simultaneous massaging of both the medial and lateral plantar portions of the foot (12). 15 Additionally, the convex medial portion (7) can abuttingly engage with a central longitudinal region of the sole of the foot (12) for further simultaneous massaging.

Accordingly, the massage roller (1) provides at least three arcuate working surfaces (27)(31)(35) configured to simultaneously massage at least three massageable portions (2) of a foot (12).

20 Now referring primarily to Figure 2 through Figure 12, the convex medial portion (7), the first concave lateral portion (8), the second concave lateral portion (9), or combinations thereof, can, but need not necessarily, include one or more recesses (36) disposed within the corresponding external surface (11), whereby the recesses (36) can facilitate massaging of the massageable portion (2) of the body (3). As but one illustrative example, a plurality of 25 substantially circular recesses (37) can be disposed within the external surface (11) of the convex medial portion (7) in a desired spaced apart relation and a plurality of substantially linear recesses (38) can be disposed within the external surfaces (11) of each of the first and second concave lateral portions (8)(9) to facilitate massaging of corresponding massageable portions (2) of the body (3) (as shown in the examples of Figure 10 through Figure 12).

30 As to other particular embodiments, the convex medial portion (7), the first concave lateral portion (8), the second concave lateral portion (9), or combinations thereof, can, but need not necessarily, include one or more protrusions (not shown) outwardly extending from the

corresponding external surface (11), whereby the protrusions can facilitate massaging of corresponding massageable portions (2) of the body (3).

As to yet other particular embodiments, the convex medial portion (7), the first concave lateral portion (8), the second concave lateral portion (9), or combinations thereof, can, but need 5 not necessarily, include a combination of one or more recesses (36) and one or more protrusions (not shown), as described above.

Now regarding production, a method of making the massage roller (1) includes providing a massage roller body (4) comprising a generally circular cross section, opposing first and second end portions (5)(6), a convex medial portion (7), a first concave lateral portion (8) axially 10 extending between the first end portion (5) and the convex medial portion (7), and a second concave lateral portion (9) axially extending between the second end portion (6) and the convex medial portion (7), whereby the massage roller body (4) is asymmetric about a massage roller body vertical centerline (10) (as shown in the example of Figure 5).

The method of making the massage roller (1) can further include providing additional 15 components of the massage roller (1) as described above.

The massage roller (1) or elements of the massage roller (1) can be made by any of a numerous and wide variety of processes depending upon the application, such as press molding, injection molding, fabrication, machining, printing, additive printing, or the like, or combinations thereof, as a one-piece construct or provided as a plurality of pieces for assembly into an 20 embodiment of the massage roller (1).

Now referring primarily to Figure 14, which illustrates a particular embodiment of the massage roller (1) formed from first and second pieces (39)(40), whereby each piece (39)(40) comprises one of two longitudinal halves of the massage roller (1), the first and second pieces (39)(40) matably engagable for assembly into an embodiment of the massage roller (1).

25 As can be easily understood from the foregoing, the basic concepts of the present invention may be embodied in a variety of ways. The invention involves numerous and varied embodiments of a massage roller and methods for making and using such massage rollers, including the best mode.

As such, the particular embodiments or elements of the invention disclosed by the 30 description or shown in the figures or tables accompanying this application are not intended to

be limiting, but rather exemplary of the numerous and varied embodiments generically encompassed by the invention or equivalents encompassed with respect to any particular element thereof. In addition, the specific description of a single embodiment or element of the invention may not explicitly describe all embodiments or elements possible; many alternatives are 5 implicitly disclosed by the description and figures.

It should be understood that each element of an apparatus or each step of a method may be described by an apparatus term or method term. Such terms can be substituted where desired to make explicit the implicitly broad coverage to which this invention is entitled. As but one example, it should be understood that all steps of a method may be disclosed as an action, a means 10 for taking that action, or as an element which causes that action. Similarly, each element of an apparatus may be disclosed as the physical element or the action which that physical element facilitates. As but one example, the disclosure of a "roller" should be understood to encompass disclosure of the act of "rolling" -- whether explicitly discussed or not -- and, conversely, were there effectively disclosure of the act of "rolling", such a disclosure should be understood to 15 encompass disclosure of a "roller" and even a "means for rolling". Such alternative terms for each element or step are to be understood to be explicitly included in the description.

In addition, as to each term used it should be understood that unless its utilization in this application is inconsistent with such interpretation, common dictionary definitions should be understood to be included in the description for each term as contained in the Random House 20 Webster's Unabridged Dictionary, second edition, each definition hereby incorporated by reference.

All numeric values herein are assumed to be modified by the term "about", whether or not explicitly indicated. For the purposes of the present invention, ranges may be expressed as from "about" one particular value to "about" another particular value. When such a range is 25 expressed, another embodiment includes from the one particular value to the other particular value. The recitation of numerical ranges by endpoints includes all the numeric values subsumed within that range. A numerical range of one to five includes for example the numeric values 1, 1.5, 2, 2.75, 3, 3.80, 4, 5, and so forth. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other 30 endpoint. When a value is expressed as an approximation by use of the antecedent "about," it will be understood that the particular value forms another embodiment. The term "about" generally refers to a range of numeric values that one of skill in the art would consider equivalent to the recited numeric value or having the same function or result. Similarly, the antecedent

“substantially” means largely, but not wholly, the same form, manner or degree and the particular element will have a range of configurations as a person of ordinary skill in the art would consider as having the same function or result. When a particular element is expressed as an approximation by use of the antecedent "substantially," it will be understood that the particular element forms another embodiment.

Moreover, for the purposes of the present invention, the term “a” or “an” entity refers to one or more of that entity unless otherwise limited. As such, the terms “a” or “an”, “one or more” and “at least one” can be used interchangeably herein.

Additionally, all directional references (e.g., proximal, distal, upper, lower, upward, 10 downward, left, right, lateral, front, rear, back, top, bottom, above, below, vertical, horizontal, clockwise, and counterclockwise) are only used for identification purposes to aid the reader's understanding of the present invention, and do not create limitations, particularly as to the position, orientation, or use of the invention.

Thus, the applicant(s) should be understood to claim at least: i) each of the massage rollers 15 herein disclosed and described, ii) the related methods disclosed and described, iii) similar, equivalent, and even implicit variations of each of these devices and methods, iv) those alternative embodiments which accomplish each of the functions shown, disclosed, or described, v) those alternative designs and methods which accomplish each of the functions shown as are implicit to accomplish that which is disclosed and described, vi) each feature, component, and step shown 20 as separate and independent inventions, vii) the applications enhanced by the various systems or components disclosed, viii) the resulting products produced by such systems or components, ix) methods and apparatuses substantially as described hereinbefore and with reference to any of the accompanying examples, x) the various combinations and permutations of each of the previous elements disclosed.

25 The background section of this patent application, if any, provides a statement of the field of endeavor to which the invention pertains. This section may also incorporate or contain paraphrasing of certain United States patents, patent applications, publications, or subject matter of the claimed invention useful in relating information, problems, or concerns about the state of technology to which the invention is drawn toward. It is not intended that any United States 30 patent, patent application, publication, statement or other information cited or incorporated herein be interpreted, construed or deemed to be admitted as prior art with respect to the invention.

The claims set forth in this specification, if any, are hereby incorporated by reference as part of this description of the invention, and the applicant expressly reserves the right to use all of or a portion of such incorporated content of such claims as additional description to support any of or all of the claims or any element or component thereof, and the applicant further 5 expressly reserves the right to move any portion of or all of the incorporated content of such claims or any element or component thereof from the description into the claims or vice-versa as necessary to define the matter for which protection is sought by this application or by any subsequent application or continuation, division, or continuation-in-part application thereof, or to obtain any benefit of, reduction in fees pursuant to, or to comply with the patent laws, rules, or 10 regulations of any country or treaty, and such content incorporated by reference shall survive during the entire pendency of this application including any subsequent continuation, division, or continuation-in-part application thereof or any reissue or extension thereon.

Additionally, the claims set forth in this specification, if any, are further intended to describe the metes and bounds of a limited number of the preferred embodiments of the invention 15 and are not to be construed as the broadest embodiment of the invention or a complete listing of embodiments of the invention that may be claimed. The applicant does not waive any right to develop further claims based upon the description set forth above as a part of any continuation, division, or continuation-in-part, or similar application.

1. A massage roller comprising:
 - a massage roller body comprising:
 - a generally circular cross section;
 - 5 opposing first and second end portions;
 - a convex medial portion;
 - a first concave lateral portion axially extending between said first end portion and said convex medial portion; and
 - a second concave lateral portion axially extending between said second end portion and said convex medial portion;
 - 10 wherein said massage roller body is asymmetric about a massage roller body vertical centerline.
2. The massage roller of claim 1, wherein said massage roller body comprises a body wall which defines a substantially hollow interior cavity.
- 15 3. The massage roller of claim 1, wherein said first and second end portions are configured to engage with a support surface during use of said massage roller.
4. The massage roller of claim 3, wherein said convex medial portion has a convex medial portion maximum diameter which is lesser than first and second end portion maximum diameters of corresponding said first and second end portions.
- 20 5. The massage roller of claim 4, wherein said convex medial portion does not engage with said support surface during use of said massage roller.
6. The massage roller of claim 5, wherein said convex medial portion provides a first arcuate working surface configured as a substantially spherical working surface.
- 25 7. The massage roller of claim 6, wherein said substantially spherical working surface is contoured to abuttingly engage with a central longitudinal region of a sole of a foot during use of said massage roller.
8. The massage roller of claim 7, wherein said first concave lateral portion is asymmetric about a first concave lateral portion vertical centerline.

9. The massage roller of claim 8, wherein said first concave lateral portion has a first concave lateral portion minimum diameter which is lesser than said convex medial portion maximum diameter and said first and second end portion maximum diameters.

10. The massage roller of claim 9, wherein said first concave lateral portion does not engage
5 with said support surface during use of said massage roller.

11. The massage roller of claim 10, wherein said first concave lateral portion provides a second arcuate working surface which is contoured to abuttingly engage with a medial plantar portion of said foot during use of said massage roller.

12. The massage roller of claim 11, wherein said second concave lateral portion is asymmetric
10 about a second concave lateral portion vertical centerline.

13. The massage roller of claim 12, wherein said second concave lateral portion has a second concave lateral portion minimum diameter which is lesser than said convex medial portion maximum diameter and said first and second end portion maximum diameters.

14. The massage roller of claim 13, wherein said second concave lateral portion does not engage
15 with said support surface during use of said massage roller.

15. The massage roller of claim 14, wherein said second concave lateral portion provides a third arcuate working surface which is contoured to abuttingly engage with a lateral plantar portion of said foot during use of said massage roller.

16. The massage roller of claim 15, wherein said first concave lateral portion minimum
20 diameter is greater than said second concave lateral portion minimum diameter.

17. The massage roller of claim 16, wherein said massage roller is configured to simultaneously massage a plurality of massageable portions of said foot.

18. The massage roller of claim 17, wherein said massage roller is configured to simultaneously massage said medial plantar portion of said foot and said lateral plantar portion
25 of said foot.

19. The massage roller of claim 18, wherein said massage roller is configured to simultaneously massage said medial plantar portion of said foot, said lateral plantar portion of said foot, and said central longitudinal region of said sole of said foot.

20. The massage roller of claim 19, wherein a first concave lateral portion length of said first concave lateral portion is lesser than a second concave lateral portion length of said second concave lateral portion.

21. A method of making a massage roller comprising:

5 providing a massage roller body comprising:

a generally circular cross section;

opposing first and second end portions;

a convex medial portion;

a first concave lateral portion axially extending between said first end portion and

10 said convex medial portion; and

a second concave lateral portion axially extending between said second end portion and said convex medial portion;

wherein said massage roller body is asymmetric about a massage roller body vertical centerline.

15 22. The method of claim 21, further comprising configuring said massage roller body to comprise a body wall which defines a substantially hollow interior cavity.

23. The method of claim 21, further comprising configuring said first and second end portions to engage with a support surface during use of said massage roller.

24. The method of claim 23, further comprising configuring said convex medial portion to 20 have a convex medial portion maximum diameter which is lesser than first and second end portion maximum diameters of corresponding said first and second end portions.

25. The method of claim 24, further comprising configuring said convex medial portion to be disengaged from said support surface during use of said massage roller.

26. The method of claim 25, further comprising configuring said convex medial portion to 25 have a first arcuate working surface configured as a substantially spherical working surface.

27. The method of claim 26, further comprising contouring said substantially spherical working surface to abuttingly engage with a central longitudinal region of a sole of a foot during use of said massage roller.

28. The method of claim 27, further comprising configuring said first concave lateral portion 30 as asymmetric about a first concave lateral portion vertical centerline.

29. The method of claim 28, further comprising configuring said first concave lateral portion to have a first concave lateral portion minimum diameter which is lesser than said convex medial portion maximum diameter and said first and second end portion maximum diameters.

30. The method of claim 29, further comprising configuring said first concave lateral portion 5 to be disengaged from said support surface during use of said massage roller.

31. The method of claim 30, further comprising contouring said first concave lateral portion to abuttingly engage with a medial plantar portion of said foot during use of said massage roller.

32. The method of claim 31, further comprising configuring said second concave lateral portion as asymmetric about a second concave lateral portion vertical centerline.

10 33. The method of claim 32, further comprising configuring said second concave lateral portion to have a second concave lateral portion minimum diameter which is lesser than said convex medial portion maximum diameter and said first and second end portion maximum diameters.

15 34. The method of claim 33, further comprising configuring said second concave lateral portion to be disengaged from said support surface during use of said massage roller.

35. The method of claim 34, further comprising contouring said second concave lateral portion to abuttingly engage with a lateral plantar portion of said foot during use of said massage roller.

20 36. The method of claim 35, further comprising configuring said first concave lateral portion to have a minimum diameter which is greater than said second concave lateral portion minimum diameter.

37. The method of claim 36, further comprising configuring said massage roller to simultaneously massage a plurality of massageable portions of said foot.

25 38. The method of claim 37, further comprising configuring said massage roller to simultaneously massage said medial plantar portion of said foot and said lateral plantar portion of said foot.

39. The method of claim 38, further comprising configuring said massage roller to simultaneously massage said medial plantar portion of said foot, said lateral plantar portion of said foot, and said central longitudinal region of said sole of said foot.

40. The method of claim 39, further comprising configuring a first concave lateral portion length of said first concave lateral portion as lesser than a second concave lateral portion length of said second concave lateral portion.

41. A method of using a massage roller to massage a massageable portion of a body, said 5 method comprising:

obtaining said massage roller comprising:

a massage roller body comprising:

a generally circular cross section;

opposing first and second end portions;

10 a convex medial portion;

a first concave lateral portion axially extending between said first end portion and said convex medial portion; and

15 a second concave lateral portion axially extending between said second end portion and said convex medial portion;

wherein said massage roller body is asymmetric about a massage roller body vertical centerline;

engaging said massageable portion of said body with an external surface of said massage roller body; and

rolling said massage roller to massage said massageable portion of said body.

20 42. The method of claim 41, further comprising engaging said first and second end portions with a support surface.

43. The method of claim 42, further comprising:

engaging only said first and second end portions with a support surface;

wherein said convex medial portion, said first concave lateral portion, and said second

25 concave lateral portion do not engage with said support surface.

44. The method of claim 43, wherein said massageable portion of said body comprises one or more massageable portions of a foot, said method further comprising:

engaging said massageable portion of said foot with said external surface of said massage roller body; and

30 rolling said massage roller to massage said massageable portion of said foot.

45. The method of claim 44, further comprising:

disposing a foot longitudinal axis in angled relation to a massage roller body horizontal axis; and

rolling said massage roller along said foot longitudinal axis to rotate said massage roller about a rotation axis coincident with a massage roller body horizontal centerline to massage said 5 massageable portion of said foot.

46. The method of claim 44, further comprising:

abuttingly engaging said convex medial portion with a central longitudinal region of a sole of said foot; and

10 rolling said massage roller to massage said central longitudinal region of said sole of said foot.

47. The method of claim 44, further comprising:

abuttingly engaging said first concave lateral portion with a medial plantar portion of said foot; and

rolling said massage roller to massage said medial plantar portion of said foot.

15 48. The method of claim 44, further comprising:

abuttingly engaging said second concave lateral portion with a lateral plantar portion of said foot; and

rolling said massage roller to massage said lateral plantar portion of said foot.

49. The method of claim 44, further comprising:

20 abuttingly engaging said first concave lateral portion with a medial plantar portion of said foot;

abuttingly engaging said second concave lateral portion with a lateral plantar portion of said foot; and

25 rolling said massage roller to simultaneously massage said medial plantar portion of said foot and said lateral plantar portion of said foot.

50. The method of claim 44, further comprising:

abuttingly engaging said first concave lateral portion with a medial plantar portion of said foot;

30 abuttingly engaging said second concave lateral portion with a lateral plantar portion of said foot;

abuttingly engaging said convex medial portion with a central longitudinal region of a sole of said foot; and

rolling said massage roller to simultaneously massage said medial plantar portion of said foot, said lateral plantar portion of said foot, and said central longitudinal region of said sole of said foot.

1/10








FIG. 2







4/10



5/10



6/10

FIG. 8






FIG. 9



7/10



8/10

FIG. 11




FIG. 12






FIG. 13





INTERNATIONAL SEARCH REPORT

International application No.

PCT/US16/46357

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - A63B 23/035; A61H 1/00, 15/00, 7/00 (2016.01)

CPC - A63B 21/4043, 23/0222, 23/03541; A61H 15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8): A63B 23/035; A61H 1/00, 15/00, 7/00 (2016.01)

CPC: A63B 21/4043, 23/0222, 23/03541; A61H 15/00, 2015/0014, 2201/1261, 2201/1284, 2201/1695, 2203/0443

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PatSeer (US, EP, WO, JP, DE, GB, CN, FR, KR, ES, AU, IN, CA, RU, AT, CH, TH, BR, PH, MX, NL, Other Countries (INPADOC); Google Patents; Questel/Orbit; Google; Google Scholar; EBSCO; PubMed/Medline; massage, kneading, reflexology, shiatsu, roller, asymmetrical, diameter, concave, convex, feet, plantar

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6793636 B1 (PEPERA, JM) September 21, 2004; abstract; figures 1-3, 6; column 2, lines 6-15, 20-23, 26-29, 35-37; column 3, lines 12-23, 31-32, 41-43, 47-54; column 5, lines 5-7, 21-22; column 6, lines 11-12, 19-20	1-3, 21-23, 41-42 ----- 4-20, 24-40, 43-50
Y	US 1722866 A (SNYDER, ES) July 30, 1929; column 2, lines 4-9, 59-67, 93-94	4-20, 24-40, 43-50
Y	US 4378007 A (KACHADOURIAN, G) March 29, 1983; figures 3, 5; column 2, lines 16-51, 66-67	45

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search

07 October 2016 (07.10.2016)

Date of mailing of the international search report

26 OCT 2016

Name and mailing address of the ISA/US

Mail Stop PC1, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450
Facsimile No. 571-273-8300

Authorized officer

Shane Thomas

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774