



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


<p>(51) International Patent Classification ⁵ : A61B 17/34</p>	<p>A1</p>	<p>(11) International Publication Number: WO 91/08712 (43) International Publication Date: 27 June 1991 (27.06.91)</p>
--	------------------	---

(21) International Application Number: PCT/SE90/00810
 (22) International Filing Date: 7 December 1990 (07.12.90)
 (30) Priority data:
 8904141-2 8 December 1989 (08.12.89) SE
 (71) Applicant (for all designated States except US): FREJA INVEST KB [SE/SE]; Box 1123, S-432 15 Varberg (SE).
 (72) Inventor; and
 (75) Inventor/Applicant (for US only) : SUNMO, Leif [SE/SE]; Blomgränd 12, S-432 34 Varberg (SE).
 (74) Agent: CEGUMARK AB; Box 53047, S-400 14 Göteborg (SE).

(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE, DE (Utility model), DE (European patent), DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), GR, GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US.

Published
 With international search report.
 In English translation (filed in Swedish).

(54) Title: AID TO MAKING HOLES



(57) Abstract

An aid to making holes (1) for the purpose of puncturing of parts of the body, comprising a hole-maker (2) capable of being guided by a guide component (3). A hole-maker (2) is connected to an articulated link (6, 7) with a to-and-fro pliable effect the present invention.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	ML	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CI	Côte d'Ivoire	LK	Sri Lanka	TD	Chad
CM	Cameroon	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark	MG	Madagascar		
ES	Spain				

Aid to making holes

The present invention relates to an aid to making holes for the purpose of puncturing of parts of the body, and comprises a hole-maker capable of being guided by a guide component.

5 Previously disclosed aids of the aforementioned kind, for example the arrangement in accordance with SE, B, 8003057-0 (Publ. No. 422 150), do not permit a safe and simple function in line with current requirements.

10 The principal object of the present invention is thus, in the first place, to make available an aid to making holes in parts of the body, which solves said problem by simple means with regard both to the manufacture and use of the aid.

15 Said object is achieved by means of an aid in accordance with the present invention, which is characterized essentially in that the hole-maker is connected to a pliable link capable of to-and-fro movement attached to the guide component.

20 The invention is described below as a preferred illustrative embodiment with reference to the drawings, in which:

Fig. 1 shows a side-view of an aid to making holes in the position of rest;

25 Fig. 2 shows an aid to making holes in the penetration position;

Fig. 3 shows said aid to making holes after making a hole;

Fig. 4 shows a cross-section through an aid to making holes in the position of rest;

30 Fig. 5 shows a front view of the aid to making holes;

Fig. 6 shows a perspective view of the aid in the position of rest;

35 Fig. 7 shows a perspective view of the aid in the position of rest, viewed from below; and

Fig. 8 shows the aid, viewed from below and in the penetration position.

An aid to making holes 1 arranged in accordance with the present invention, comprising a hole-maker 2 which is guided by a guide component 3 so as to permit the puncturing of parts of the body, for example when pricking a finger 4 in conjunction with taking a blood sample, etc., has the hole-maker 2 attached to the guide component 3 via a link 5. Said link, which can be in the form of a number of pivotally arranged arms 6, 7, is plially connected to the guide component 3 in a manner capable of to-and-fro movement in the direction of the arrows 8, 9, against the effect of an influencing force which acts contrary to the directions referred to above.

Said arms 6, 7 are preferably arranged in pairs, or in some other desired number, with each being supported on a corresponding counter-pressure component 10, 11 attached to the guide component 3 of the hole-maker and preferably projecting laterally outwards from said preferably sleeve-shaped guide component 3 of the hole-maker.

For example, said counter-pressure components may be in the form of so-called counter-pressure arms 10, 11, which are appropriately integrated with the sleeve-shaped guide component 3 of the hole-maker at its rear end 3A, viewed in the direction of use 8, i.e. the direction of penetration, or are attached in some other appropriate fashion to said component 3. A hinge 12, 13 is arranged so that it is supported preferably at the outer ends 10A, 11A of each of said counter-pressure arms 10, 11. Connected to each hinge 12, 13 is one of said articulated connecting arms 6, 7, which runs in a lateral sense across the direction of use 8 of the aid inwards towards a compression component 15 situated preferably centrally at the middle 14 of the aid. Said compression component may appropriately be in the form of a thumb-

pressure pad 15, which is integrated with said articulated connecting arm/arms 6,7 and which consists preferably of the rear end of a casing body 16 for the hole-maker 2 situated centrally on the aid 1 in question.

Said hole-maker 2 may, as can be appreciated from the example shown here, consist of different materials, in conjunction with which the body 16 itself may be made of extruded plastic, for example, whereas the actual tip may be in the form of a metal needle 17, which is fixed to the body 16 by its rear end 17A. By casting the needle 17, etc., in situ it is possible to ensure its location in precisely the desired position, so that the correct depth by which the needle projects can be guaranteed in every case. The needle is thus not able to penetrate too deeply into a finger, for example, which has been one of the disadvantages of previously disclosed hole-makers.

Otherwise the hole-making aid 1 also consists of a plastic material, although the use of other materials, such as metallic materials, for example, may be considered.

Thanks to the characteristics of the material, the articulated connecting arms 6, 7 and the counter-pressure arms 10, 11 can be so arranged as to exhibit a spring action in relation to one another, so that the articulated connecting arms 6, 7 are caused to spring back in the direction of the arrow 9, after having been pushed down in the direction of the arrow 8, once the thumb has been pressed against the thumb-pressure pad 15. The hinges 12, 13 can also be arranged with spring action in a similar way to that described above, so as to cause the connecting arms 6, 7 to spring back after these have been pushed down with a certain force F , as shown in Figs. 2 and 3 in the drawings.

The connecting arms 6, 7 and the counter-pressure arms 10, 11 can be attached to one another via

hinges 12, 13 with the pressure pad 15 and the guide component 3 between them, so that an acute angle X is formed at each hinge 12, 13 between the arms 6-7; 10-11, viewed from the side looking at the aid 1, when the aid 1 is held with its hole-maker 2 in the retracted position of rest V ready for making holes, like a rhombus or the arms of a manually operated jack. In the so-called penetration position S, as illustrated in the drawings in Fig. 2, the arms 6, 7 are moved against spring pressure inwards towards the arms 10, 11 until they come close to one another in pairs 6, 10; 7, 11 after the pressure pad 15 has been caused by a thumb to press the hole-maker 2, preferably exhibiting cylindrical cross-section, with a certain force F into the guide sleeve 3 which, at its front end 3B, which is designed to be capable of being turned to face a finger 4 or some other intended part of the body before a hole is made therein, exhibits a flared contact component 18, for example a ring, which provides support for the aid during the hole-making operation.

In order to protect the nail 17, etc., a degradable cover 19 is arranged on said contact component 18, so that the needle 17 cannot be contaminated before use. The effective sharp point 17 of the hole-maker, for example a needle, is so arranged as to be accommodated internally within the accommodating space 20 of said guide component 3 when the hole-maker is being held in the position of rest V, before or after the hole-making operation (Fig. 4 and Fig. 3). The cover 19, which can consist of a membrane of a plastic material or similar, and which is capable of being acted upon by the hole-maker from the inside for the purposes of its degradation, in such a way that the sharp point 17 can be caused to project for hole-making. A piece of plastic film may be welded or bonded, for example, to the outside 18A of the contact component 18.

After the hole-making operation the sharp point 17 is withdrawn, thanks to the spring function of the aid, back into the space 20, when the sharp point 17 is protected against contact. Any disease, such as yellow jaundice or HIV, etc., which may have been transferred from the body 4 to the sharp point 17 during the hole-making operation is prevented by the function and construction of the aid from being spread further via the aid 1, through accidental contact with it, which is of the disposable type, of course.

The function and construction of the aid 1 should have been appreciated clearly from the foregoing and the drawings shown here, although it can be stated briefly that, when the aid 1 is held against a part of the body 4 and pressure is applied against the pressure pad 15, for example with the thumb, at the same time as the index finger and the middle finger, for example, are appropriately placed against the arms 10, 11, the sharp point 17 is pushed out in the direction of the arrow 8, so that the part of the body 4 concerned is punctured, as shown in Fig. 2 in the drawings.

As the aid 1 is removed from the hole 21 which has been produced, the sharp point 17 is automatically retracted into the aid, where it is well protected inside the guide component 3 behind the remains of the degraded protective membrane 19, and within the limits of the guide component 3. The aid 1 is thus both simple to manufacture in hygienic materials and by the use of simple processes, and is easy and safe to use, including by persons who are not familiar with it. The invention is not restricted to the illustrative embodiments described above and shown in the drawings, however, but can be modified within the scope of the Patent Claims without departing from the idea of invention.

The number of arms can be varied, for example, as can their form and that of the aid in question.

P a t e n t C l a i m s

5

1. An aid to making holes (1) for the purpose of puncturing of parts of the body (4), comprising a hole-maker (2) capable of being guided by a guide component (3), **characterized in that** the hole-maker (2) is attached to counter-pressure arms (10, 11) projecting laterally in pairs from a sleeve-shaped guide component (3), at the ends (10A, 11A) of which arms a hinge (12, 13) is supported, from which articulated connecting arms (6, 7) with a pliable to-and-fro (8) action run inwards towards the compression component (15) of the aid, in conjunction with which the articulated connecting arms (6, 7) and counter-pressure arms (10, 11) exhibit a spring action in relation to one another.

2. An aid to making holes in accordance with Patent Claim 1, **characterized in that** the connecting arms (6, 7) are integrated with a pressure plate (15) accommodated in a central location at the rear end (2A) of the hole-maker (2).

3. An aid to making holes in accordance with Patent Claim 2, **characterized in that** the connecting arms (6, 7) and the counter-pressure arms (10, 11) are connected to one another and to the thumb-pressure plate (15) and to the guide component (3) in such a way that the arms (6, 10; 7, 11) form an acute angle (X) between themselves at each hinge (12, 13) when the aid (1) is held with its hole-maker (2) in the retracted position of rest (V) ready for making holes.

4. An aid to making holes in accordance with any of the foregoing Patent Claims, **characterized in that** the effective sharp point (17) of the hole-maker is so arranged as to be accommodated internally (20) within said guide component sleeve (3) when the hole-maker (2) is being held in the position of rest (V).

5. An aid to making holes in accordance with any of the foregoing Patent Claims, in which the point (17) of the hole-maker preferably consists of a metal material whilst the rest of the aid (1) consists of plastic material, **characterized in that** a guide component sleeve (3) designed to accommodate and guide the hole-maker (2) at its end (3B) which is capable of being turned to face an object in which it is intended to make a hole exhibits a flared contact component (18).

6. An aid to making holes in accordance with any of the foregoing Patent Claims, **characterized in that** the aid to making holes (1) exhibits on its front face (18A) a degradable protective cover (19) capable of being acted upon by the hole-maker (2), in conjunction with which the cover preferably consists of a membrane (19), for example made of a plastics material or similar.

1 / 3






FIG. 4





FIG. 5

3/3




FIG. 6




FIG. 7





FIG. 8

INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 90/00810

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC5: A 61 B 17/34		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
IPC5	A 61 B	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched ⁸		
SE,DK,FI,NO classes as above		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category *	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	US, A, 4616649 (J.A. BURNS) 14 October 1986, see figure 1; claim 7 --	1-6
A	GB, A, 2074453 (HANS ENSTRÖM) 4 November 1981, see figure 1 --	1-6
A	EP, A1, 0081665 (BECTON, DICKINSON AND COMPANY) 22 June 1983, see figure 1 --	1-6
A	US, A, 4414975 (F.E. RYDER ET AL) 15 November 1983, see figures 1-10 --	1-6
A	US, A, 3760809 (S.P. CAMPBELL JR) 25 September 1973, see abstract -- -----	6
<p>* Special categories of cited documents:¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
15th March 1991	1991 -03- 29	
International Searching Authority	Signature of Authorized Officer	
SWEDISH PATENT OFFICE	UDO HINZ 	

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 90/00810**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on **91-01-31**. The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 4616649	86-10-14	AU-B- 569988	88-02-25
		AU-D- 4469985	86-03-27
		EP-A- 0178384	86-04-23
		JP-A- 61079450	86-04-23
GB-A- 2074453	81-11-04	AT-B- 383488	87-07-10
		CH-A-B- 652585	85-11-29
		DE-A- 3111737	82-02-11
		FR-A-B- 2481103	81-10-30
		JP-B- 1052018	89-11-07
		JP-C- 1570982	90-07-25
		JP-A- 56151024	81-11-21
		NL-A- 8101537	81-11-16
		SE-B-C- 422150	82-02-22
		SE-A- 8003057	81-10-24
		US-A- 4676244	87-06-30
		US-A- 4712548	87-12-15
		US-A- 4738261	88-04-19
EP-A1- 0081665	83-06-22	AU-B- 551187	86-04-17
		AU-D- 8940382	83-05-26
		JP-B- 1017369	89-03-30
		JP-C- 1535670	89-12-21
		JP-A- 58092347	83-06-01
		US-A- 4449529	84-05-22
US-A- 4414975	83-11-15	DE-A- 3217757	82-12-16
		GB-A- 2098486	82-11-24
		JP-A- 57196963	82-12-03
US-A- 3760809	73-09-25	NONE	